MASTER

ORNL-3206
UC-25 - Metals, Ceramics, and Materials
TID-4500 (17th ed.)

AN EVALUATION OF THE URANIUM
CONTAMINATION ON THE SURFACES OF
ALCLAD URANIUM-ALUMINUM ALLOY RESEARCH
REACTOR FUEL PLATES

R. J. Beaver
J. H. Erwin
R. S. Mateer

OAK RIDGE NATIONAL LABORATORY

operated by

UNION CARBIDE CORPORATION

for the

U.S. ATOMIC ENERGY COMMISSION

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Printed in USA. Price \$0.75 cents. Available from the
Office of Technical Services
U. S. Department of Commerce
Washington 25, D. C.

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

- A. Makes any warranty or representation, express or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or
- B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission to the extent that such employee or contractor prepares, handles or distributes, or provides access to, any information pursuant to his employment or contract with the Commission.

ORNL-3206
UC-25 - Metals, Ceramics, and Materials
TID-4500 (17th ed.)

Contract No. W-7405-eng-26

METALLURGY DIVISION

AN EVALUATION OF THE URANIUM CONTAMINATION ON THE SURFACES
OF ALCLAD URANIUM-ALUMINUM ALLOY RESEARCH REACTOR FUEL PLATES

R. J. Beaver, J. H. Erwin, and R. S. Mateer

DATE ISSUED

MAR 19 1962

OAK RIDGE NATIONAL LABORATORY

Oak Ridge, Tennessee

Operated by

UNION CARBIDE CORPORATION

for the

U. S. ATOMIC ENERGY COMMISSION

AN EVALUATION OF THE URANIUM CONTAMINATION ON THE SURFACES
OF ALCLAD URANIUM-ALUMINUM ALLOY RESEARCH REACTOR FUEL PLATES

R. J. Beaver, J. H. Erwin, and R. S. Mateer¹

ABSTRACT

Reported radioactivity in the Low-Intensity Test Reactor (LITR) water coolant traceable to uranium contamination on the surfaces of the alclad uranium-aluminum plate-type fuel element led to an investigation to determine the sources of uranium contamination on the fuel plate surfaces. Two possible contributors to surface contamination are external sources such as rolling-mill equipment, the most obvious, and diffusion of uranium from the uranium-aluminum alloy fuel into the aluminum cladding. This diffusion is likely because of the 600°C heat treatments used in the conventional fabrication process.²

Uranium determinations based on neutron activation analysis of machined layers from fuel plate surfaces showed that rolling-mill equipment, contaminated with highly enriched uranium, was responsible for transferring as much as 180 ppm U²³⁵ to plate surfaces. By careful practice where cleanliness is emphasized, surface contamination can be reduced to 0.6 ppm U²³⁵.

The residue remaining on the plate surface may be accounted for by diffusion of uranium from the fuel alloy into and through the cladding of the fuel plate. Data obtained from preliminary diffusion studies permitted a good estimate to be made of the diffusion coefficient of uranium into aluminum at 600°C: 2.5×10^{-8} cm²/sec. To minimize diffusion while the plate-type aluminum-base research reactor fuel element is being processed, heat treatments at 600°C should be limited to 2.5 hr. The uranium contamination on the surfaces of the finished fuel plates should then be less than 0.6 ppm U²³⁵.

This investigation also revealed that the solubility limit of uranium in aluminum at 600°C is approx 60 ppm.

¹Summer Research Participant.

²E. J. Boyle and J. E. Cunningham, "MTR-Type Fuel Elements," Proc. Intern. Conf. Peaceful Uses Atomic Energy, Geneva, 1955 9 (1955).

INTRODUCTION

One of the factors, which operators of research reactors, such as the Low-Intensity Test Reactor (LITR) and the Oak Ridge Research Reactor (ORR), must control, is the quantity of radioactive species which contaminate the water coolant. The principal sources of activity are contained either in the water itself or on the surfaces of the aluminum fuel elements. The water can be purified, but activity from sodium-24 at a level ranging from 7.5×10^{-3} to 3.2×10^{-2} $\mu\text{c}/\text{ml}$ will still be noticeable. Reactor operators recognize the possibility of additional activity from fuel plate surfaces contaminated with uranium but feel that it should be limited to less than 10^{-4} $\mu\text{c}/\text{ml}$ (ref 3). In 1957, Moeller and Ledicotte⁴ studied the radioactive nuclides present in the cooling water of the LITR. Prominent nuclides which were identified were neptunium-239 and "certain fission products." They concluded that the source of this nuclide was highly enriched uranium on the surfaces of the fuel plates which was responsible for an iodine-133 activity in the coolant of 6×10^{-5} $\mu\text{c}/\text{ml}$.

There are two possible contributions to surface contamination. The more obvious is the transfer of uranium from rolling-mill equipment to the surfaces of fuel plates. Contamination from this source was examined by scraping or machining 0.001-in.-deep layers from the surfaces of plates which had been heated at 600°C and rolled through highly contaminated rolls as well as through rolls with relatively little uranium contamination. These samples were analyzed for uranium-235 by neutron activation analysis. The other possible source of contamination, although not quite so apparent, is from diffusion of uranium from the uranium-aluminum alloy fuel section into and completely through the cladding of fuel plates during processing. A preliminary examination was made by obtaining samples by machining into the cladding to various depths and then analyzing the machined chips for uranium, again by neutron activation analysis. Because of the preliminary nature of this portion of the investigation, only a limited number of samples were obtained. They were, however,

³Personal communication from F. T. Binford, ORNL Operations Division, ORR Specifications on Radioactivity.

⁴D. W. Moeller and G. W. Ledicotte, Source of Fission Products in LITR Cooling Water, ORNL CF-57-3-120 (March 1957).

sufficient to allow calculations to be made from which the diffusion coefficient and solubility limit of uranium in aluminum at 600°C were estimated.

GENERAL AND THEORETICAL CONSIDERATIONS

Since rolling-mill equipment is obviously a source of contamination in a fabrication facility where uranium or its alloys are rolled, it is necessary to ascertain the quantity of uranium transferred from such equipment to the surfaces of fuel plates during the rolling practices and, subsequently, to determine the percentage of this contaminant which may have been removed during cleaning or brightening treatments of the finished fuel plate. Approach to this problem requires merely a relatively simple sampling of the fuel plate surfaces after the various processing stages and a determination by neutron activation analysis of the uranium concentration in the samples. Then the equipment which transfers contamination on plate surfaces can be isolated.

Since it is possible that at 600°C, given sufficient time, uranium in the aluminum matrix of the uranium-aluminum alloy will diffuse into and completely through the aluminum cladding of the fuel plate, it is desirable to know the amount reaching the surface after a specified time. This, however, requires a knowledge of the diffusion coefficient. The value for this coefficient at 600°C is not known, but from data on other solutes in aluminum⁵ is probably on the order of 10^{-8} cm²/sec. The establishment of the diffusion coefficient requires knowledge of the solid-solubility limit of uranium in aluminum. The uranium-aluminum phase diagram, illustrated in Fig. 1, indicates that no solubility at 600°C exists. Thermodynamically, it cannot be zero. Therefore there will be a driving force for diffusion that will tend to bring the cladding and the matrix of the fuel alloy to the solubility limit of uranium in aluminum.

Support for the diffusion concept of contamination is given by preliminary studies of Kucera⁶ on metallographic changes in the vicinity of the core-clad

⁵Wolfgang Seith, Diffusion in Metals, p. 40, Springer-Verlag, Berlin/Göttingen/Heidelberg, 1955.

⁶Met. Div. Ann. Progr. Rept. Sept. 1, 1959, ORNL-2839, pp. 256-60.

UNCLASSIFIED
Y-20808

Fig. 1. Uranium-Aluminum Phase Diagram.

interface during prolonged heating at 600°C. The drastic nature of these changes is indicated in Fig. 2. It has not been possible to rationalize this phenomenon completely in terms of simple diffusion of uranium from the matrix of the uranium-aluminum alloy. The full explanation also probably involves the redistribution of minor alloy constituents and impurities (iron and silicon) in the cladding alloy and some interactions of solubility limits. However, there can be no question that diffusion processes between the fuel core and the cladding, and within the cladding itself, can be of significant proportions at this temperature.

To estimate the solid-solubility limit and the diffusion coefficient at 600°C from the limited data anticipated, a series of calculations can be made based on the following solution to Fick's equation:

$$\frac{C}{C_0} = 1 - \psi \left(\frac{x}{2 \sqrt{Dt}} \right), \quad (1)$$

where

C = uranium concentration at a distance x from the bonded interface after a time t ,

C_0 = one-half the solid-solubility limit,

ψ = Gauss error function,

D = diffusion coefficient of uranium in the aluminum cladding.

This relationship is expressed graphically in Fig. 3, where C_2 is the solid-solubility limit and $C_2/2$, one-half the solid solubility limit, is C_0 in the above expression.⁵ To determine the diffusion coefficient, it is necessary to know the solid-solubility value, as well as the uranium concentration, at various distances from the alloy interface. If a number of values for C can be determined, it is possible, by assuming various diffusion coefficients, to analytically estimate C_0 and, of course, the solid-solubility limit.

This representation is obviously an ideal condition, and although there is no doubt that the interface does not remain at $x = 0$, the scope of this investigation did not include studies to determine the direction of distortion. The assumption was made that uranium diffuses from the alloy much faster than it can be replenished by dissolution of the UAl_4 intermetallic compound and that the uranium in the aluminum matrix decreases as though it were in simple

(a)

(b)

Fig. 2. Comparison of Bonded Interface in Uranium-Aluminum Alclad Fuel Plate (a) after Cladding by Roll Bonding at 600°C and (b) after 14-Day Heat Treatment at 600°C. Electropolish: 15 parts ethyl alcohol; 1 part perchloric. Etch: 5% NaOH. 250X.

UNCLASSIFIED
ORNL-LR-DWG 53602R

Fig. 3. Ideal Representation of Diffusion from Uranium-Aluminum Alloy into Aluminum Cladding of Alclad Fuel Plates.

solid solution. In fact, analysis of the data is by "curve fitting" on a simple model of a complex diffusion process. However, the parameters obtained represent an over-all measure of the extent of diffusion and should permit analytical extrapolation under conditions of practical interest.

EXPERIMENTAL PROCEDURE

The experimental procedure for evaluating surface contamination was to utilize plates produced with equipment in the Metal Forming and Casting Laboratory of the Metallurgy Division at the Oak Ridge National Laboratory (ORNL). Samples were obtained by scraping surfaces of the plates to a depth of approx 0.0005 in. and the uranium concentration was determined by neutron activation analysis.

Contamination From Rolling Mill

Samples were obtained from plates after the following sequences in the fuel plate processing:

1. hot rolling at 600°C through rolls contaminated with uranium;
2. flux annealing for 40 min at 600°C, cleaning in 2% HF-15% HNO₃ aqueous solution, and rinsing in water;
3. cold rolling through noncontaminated rolls;
4. annealing for 60 min at 600°C, cleaning in 2% HF-15% HNO₃ aqueous solution, and rinsing in water.

A comparative series of samples was prepared in accordance with this procedure with the exception that the hot rolling was conducted through rolls only partially contaminated with uranium. The results of the neutron activation analyses for uranium in the surface layers then permit an evaluation of the contamination as affected by the equipment and fabrication processes.

Contamination From Diffusion

To arrive at an estimate of values for the solid-solubility limit and diffusion coefficient at 600°C, plates were roll-bonded at 600°C and subsequently heat treated for 3, 6, and 9 hr at this temperature. After each heat treatment, the plates were fixed in a vacuum chuck, and a strip, 1/2 in. wide x 10 in. long, was machined from the center portion of the plate surface. The depth of the cut was varied from 0 to 0.003 in., 0.003 to 0.006 in., and 0.006 to 0.009 in. The sample obtained was completely dissolved and then analyzed by neutron activation analysis for uranium.

DISCUSSION OF RESULTS

Contamination From Rolling Mill

Average values of uranium-235 on the surfaces of fuel plates after various sequences in the fabrication process are listed in Table 1. Detailed results are given in Table 1 of Appendix A. As expected, because of uranium contamination on the hot-rolling mill, uranium concentration on the plate surfaces

Table 1. Uranium-235 Concentration in Scrapings from the Surfaces of Alclad Uranium-Aluminum Alloy Fuel Plates after Pertinent Sequences in Plate Processing

Fabrication Sequence	Average U ²³⁵ Concentration (ppm)	
	Hot-Rolling Mill	Hot-Rolling Mill
	Contaminated with U ²³⁵	Partially Contaminated
After hot rolling at 600°C on Mesta 2-High Mill	180.0	8.9
After flux annealing at 600°C for 40 min, etching in 2% HF-15% HNO ₃ aqueous solution, and water rinsing	4.2	1.6
After cold rolling through "clean" rolls on United 2-High Mill	4.2	
After annealing for 60 min at 600°C, cleaning in 2% HF-15% HNO ₃ aqueous solution, and rinsing in water	No data obtained	0.6

after hot rolling was 180 ppm U²³⁵, which is considered extremely high. The contamination was significantly reduced after the flux-annealing treatment, acid cleaning, and water rinsing. Partial cleaning of the rolls by rolling aluminum stock combined with kerosene washing reduced the surface contamination of hot-rolled product to 8.9 ppm U²³⁵. Again, the acid cleaning and water rinsing were observed to reduce the contamination significantly. Additional cleaning after blister annealing, acid pickling, and water rinsing resulted in further reduction to 0.6 ppm U²³⁵. Analyses of the acid cleaning and water rinse solutions verified the presence of uranium, apparently removed from the plate surfaces.

Neutron activation analyses of type 1100 aluminum cladding stock revealed an average uranium concentration of 0.80 ± 0.02 ppm. Detailed results are given in Table A.5. Contribution of the uranium-235 isotope from this material is therefore a negligible 0.008 ppm.

Contamination From Diffusion

Uranium values (based on the data in Table A.4) obtained in the preliminary diffusion studies are plotted in Fig. 4, with the average values from this plot listed in Table 2. The following assumptions were necessary for analytical

Table 2. Average Uranium Concentrations Obtained from Fig. 4 for Various Distances from the Bonded Interfaces after Diffusion from Uranium-Aluminum Alloy into Type 1100 Aluminum Cladding at 600°C

Distance from Bonded Interface (cm)	Uranium Concentration (ppm) after Heat Treatments of		
	3 hr	6 hr	9 hr
0.02	3.5	16.0	33.0
0.03	0.2	7.0	19.0
0.04	0	3.0	10.0
0.05	0	0	4.0

treatment of the data for estimation of diffusion coefficient of uranium in this system and the solubility limit of uranium in aluminum:

1. The diffusion coefficient is independent of concentration.
2. The solubility limit in the aluminum matrix of the uranium-aluminum alloy is the same as in the aluminum cladding.
3. Uranium is the only solute that is diffusing.

The restrictions which these assumptions impose can lead only to first approximations for C_0 and D when applied to data from the complex diffusion process under consideration.

If the data of Table 2 were to conform to the ideal case of Eq. (1), C_0 and D would be true constants. In particular, if D were known, substitution of each C value from Table 2 would lead to the same value of C_0 . If the D value were incorrect, a series of different values would be obtained for the constant C_0 . The constancy of C_0 under trial substitutions of various D

UNCLASSIFIED
ORNL-LR-DWG 53600

Fig. 4. Relationship Between Uranium Concentration and Distance from Bonded Interface of Uranium-Aluminum Alloy Plates Clad with Type 1100 Aluminum and Heat Treated at 600°C for 3, 6, and 9 Hr. Plotted from averages listed in Table A.4.

values for the data of Table 2 is therefore a test for the best-fit value of D. Results of a series of such calculations are given in Table 3 for assumed

Table 3. Calculated C_0 Values Versus Assumed Diffusion Coefficients from 10^{-9} to 10^{-7} cm^2/sec for Diffusion of Uranium from Uranium-Aluminum Alloy into Type 1100 Aluminum Cladding at 600°C after Various Heat-Treatment Periods*

Distance from Bonded Interface (cm)	Uranium Concentration (ppm)				
	For Diffusion Coefficient (cm^2/sec) of				
	1×10^{-9}	5×10^{-8}	2×10^{-8}	1×10^{-8}	1×10^{-7}
<u>Heat Treated for 3 hr</u>					
0.02	116	5	6	7	4
0.03	3	3	50	∞	10
0.04	0	0	0	0	0
0.05	0	0	0	0	0
<u>Heat Treated for 6 hr</u>					
0.02	∞	24	32	46	21
0.03	∞	13	23	41	11
0.04	∞	8	17	54	6
0.05	0	0	0	0	0
<u>Heat Treated for 9 hr</u>					
0.02	1100	46	57	77	42
0.03	∞	32	48	79	27
0.04	∞	21	39	91	16
0.05	∞	10	25	80	8

*Based on results listed in Tables 1 and 2 of Appendix B.

values of D. From these data an estimate of $C_0 = 30$ ppm was made. In no case was C_0 found to be a true constant; however, the most consistent values were found for a diffusion coefficient of 2×10^{-8} cm^2/sec .

Accepting these values as a first approximation, it is possible to predict the extent of diffusion through aluminum cladding of various thicknesses and for heat treatments at 600°C other than these specifically tested. These results are listed in Table 4 and are based on the calculations listed in Table B.2 and the estimated value of 30 ppm U for C_0 .

Table 4. Data Relating Diffusion of Uranium at 600°C
as a Function of Distance and Time from Bonded Uranium-Aluminum Alloy
into Type 1100 Aluminum Cladding*

Distance from Bonded Interface (cm)	Uranium Concentration (ppm)								
	Heat-Treatment Time (hr)								
	0.5	1.0	1.5	2.0	2.5	3.0	4.0	5.0	10.0
0.01	7.05	12.24	14.91	16.59	18.00	18.93	20.16	21.30	23.4
0.02	0.525	2.85	5.22	7.05	8.82	10.08	11.91	13.50	17.79
0.03	0.01	0.54	1.20	2.28	3.39	4.47	6.30	7.74	12.84
0.04		0.03	0.18	0.54	1.02	1.62	2.85	4.02	8.70
0.05			0.02	0.09	0.24	0.48	1.08	1.86	5.55
0.06				0.01	0.06	0.09	0.33	0.72	3.39
0.07							0.09	0.24	1.89

*Diffusion coefficient = 2×10^{-8} cm²/sec.

Since the formula used in these analyses is based on an infinite solid and the case at hand is a finite solid, it is necessary to make corrections. This can be estimated by taking into account a "reflection" curve from the plot generated for the infinite solid.⁷ These curves are compared in Fig. 5 in which the "reflection" curve is shown. Corrected values are tabulated in Table 5. Based on the data listed in Table 5, the uranium concentration at various distances from the bonded interface into the cladding as a function of time at 600°C is graphically illustrated in Fig. 6. The data show that to limit the uranium-235 contamination on the surfaces of finished alclad uranium-aluminum alloy fuel plates to 0.5 ppm, heat treatment of the plates at 600°C should be confined to a period of less than 2.5 hr. After 3 hr, the uranium contamination is 1 ppm; after 5 hr, 4 ppm; and after 10 hr, may reach a value as high as 10 ppm. The importance of limiting the heat treatment is obvious.

⁷Wolfgang Seith, Diffusion in Metals, p. 17, Springer-Verlag, Berlin/Göttingen/Heidelberg, 1955.

Fig. 5. Comparison of Curves Generated for Infinite and Finite Diffusion of Uranium from Uranium-Aluminum Alloy into Aluminum Cladding of Alclad Fuel Plates after 10-Hr Heat Treatment at 600°C.

Table 5. Modification of Data of Table 4 Relating Diffusion of Uranium at 600°C as a Function of Distance and Time from Bonded Uranium-Aluminum Alloy into Type 1100 Aluminum Cladding*

Distance from Bonded Interface (cm)	Uranium Concentration (ppm) Heat-Treatment Time (hr)								
	0.5	1.0	1.5	2.0	2.5	3.0	4.0	5.0	10.0
0.01	7.05	12.24	14.91	16.59	18.00	18.93	20.16	21.30	23.4
0.02	0.53	2.85	5.22	7.05	8.82	10.08	11.91	13.50	17.79
0.03	0.01	0.54	1.20	2.28	3.39	4.47	6.39	7.98	14.73
0.04		0.03	0.18	0.55	1.08	1.69	3.18	4.74	12.60
0.05			0.04	0.18	0.48	0.96	2.16	3.72	11.10
0.06									
0.07									

*Based on 0.058-cm-thick cladding.

CONCLUSIONS

1. Uranium on rolling-mill equipment can be transferred to the surface of rolled-aluminum fuel plates and cause significant increases in activity levels in the water coolant of research reactors.

2. In processing alclad uranium-aluminum alloy fuel plates containing highly enriched uranium, it is conceivable that surface contamination can be limited to a maximum of 0.5 ppm U^{235} if the rolling-mill equipment is free of this contaminant and if heat treatment of fuel plates at 600°C is limited to 2.5 hr.

3. Uranium concentration in type 1100 aluminum cladding stock is 0.80 ± 0.02 ppm.

4. Diffusion of uranium from the uranium-aluminum alloy fuel core into the type 1100 aluminum cladding may contribute significantly to uranium contamination on the surfaces of fuel plates processed at 600°C. The estimated diffusion coefficient of uranium from the uranium-aluminum alloy core into the type 1100 aluminum cladding at 600°C is 2×10^{-8} cm²/sec. (The estimated solid-solubility limit of uranium in aluminum at 600°C is 60 ppm.)

Fig. 6. The Effect of Heat Treatment at 600°C on Diffusion of Uranium from Uranium-Aluminum Alloy into the Aluminum Cladding of Alclad Fuel Plates.

ACKNOWLEDGMENT

The authors wish to acknowledge the assistance of H. J. Wallace of the Metal Forming and Casting Group, who prepared the composite plate specimens used in this investigation. R. J. Gray and his co-workers in the Metallographic Group are also recognized for their efforts in illustrating the effect of diffusion at the bonded interface of alclad uranium-aluminum alloy fuel plates. The assistance of G. W. Ledicotte of the Nuclear Analysis Group in conducting the neutron activation analyses is fully appreciated.

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

APPENDIX A

DATA ON NEUTRON ACTIVATION ANALYSES FOR URANIUM
IN THE CLADDING OF ALCLAD URANIUM-ALUMINUM ALLOY FUEL PLATES

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

Table A.1. Data on Uranium-235 Contamination on Surfaces of Aluminum Fuel Plates Based on Scrapings from the Surfaces after Important Sequences in Fuel Plate Processing

Fabrication Sequence	Specimen Number	Uranium-235 Concentration (ppm)	
		Contaminated Rolls	Partially Contaminated Rolls
After hot rolling at 600°C on Mesta 2-High Mill	HA	138-158	
	HB	91-108	
	HC	291-295	
	D582-1		9.2-11.4
	D582-2		8.9-9.5
	D582-3		7.3-9.6
	D582-4		7.8-7.8
After flux annealing plate for 40 min at 607°C, cleaning in 2% HF-15% HNO ₃ aqueous solution, and rinsing in water	FH	5.3-5.9	
	FI	3.2-3.6	
	FJ	3.7-3.7	
	1X		0.6-1.4
	2X		1.8-5.3
	3X		0.5-1.1
	4X		0.7-1.1
After cold rolling on United 2-High Mill	CK	4.1-4.4	
	CL	5.1-5.4	
After annealing 60 min at 607°C, cleaning in 2% HF-15% HNO ₃ aqueous solution, and rinsing in water	1B		0.4-0.6
	2B		0.4-1.0
	3B		0.4-1.2
	4B		0.5-0.7
	5B		0.3-0.5
2% HF-15% HNO ₃ aqueous solution	ACD		0.12-0.12 (mg/ml)
	ACE		0.12-0.12 (mg/ml)
Water rinse	HOG		0.003-0.003 (mg/ml)
	HOF		0.08-0.08 (mg/ml)

Table A.2. Uranium-235 Contamination on the Surfaces of Finished Alclad Uranium-Aluminum Alloy Fuel Plates Based on the Outer 0.003-in. Thickness of the Aluminum Cladding

Type of Plate	Specimen No.	Uranium-235 Concentration (ppm)
ORR	B-56-0	0.09-0.11
ORR	B-672-12	0.39-0.54
ORR	D-669-A	0.37-0.40
BSR	D-682-0	0.15
TSF	B-61	0.20-0.28
TSF	B-45	0.38-0.46
TSF	B-63	0.18-0.19
Average		0.28

Table A.3. Neutron Activation Analyses of Uranium Content in Machining Shavings of Type 1100 Cladding of Uranium-Aluminum Alloy Fuel Plates after Machining into the Surface of the Composite Plate to Various Depths Subsequent to Designated Heat Treatment at 600°C

Sample No.	Uranium-Aluminum	Cladding Thickness (mils)	Uranium Concentration (ppm)		
	Alloy		at Machining Depth of		
	Concentration (wt %)		0-3 mils	3-6 mils	6-9 mils
<u>Heat-Treated for 3 hr</u>					
D669B	18.5	15	0.37-0.40		
D669C	18.5	15		1.28-1.32	
D669D	18.5	15			5.22-5.34
D669A	14.3	20	0.14-0.17		
D669B	14.3	20		0.19-0.25	
D669C	14.3	20			0.12-0.14
Si-30-11A	48.0	17	0.04-0.10		
Si-30-11B	48.0	17		0.53-0.82	
Si-30-11C	48.0	17			0.85-0.89
<u>Heat-Treated for 6 hr</u>					
D669E	18.5	15	8.0-8.5		
D669F	18.5	15		10.3-10.6	
D669G	18.5	15			17.5-19.6
D682F	14.3	20	2.3-2.3		
D682G	14.3	20		1.4-1.4	
D682H	14.3	20			2.8-3.0
Si-30-11F	48.0	17	5.4-7.8		
Si-30-11H	48.0	17			37.7-50.5
D669I	18.5	15	23.1-23.6		
D669J	18.5	15		20.0-23.0	
D669K	18.5	15			21.0-20.8
D682I	14.3	20	6.0-6.1		
D682J	14.3	20		6.7-6.7	
D682K	14.3	20			16.5-17.4
Si-30-13I	48.0	17	8.3-8.9		
Si-30-13J	48.0	17		15.3-18.0	
Si-30-13K	48.0	17			46.1-53.4

Table A.4. Summary of Average Uranium Concentration*
in Various Layers of Aluminum Cladding
of Uranium-Aluminum Alloy Plates
after Heat Treatment at 600°C

Weight Per Cent of Uranium in Alloy	Cladding Thickness (mils)	Depth Machined into Surface (mils)	Uranium Concentration (ppm) Heat-Treatment Period (hr)		
			3	6	9
14.3	20	0-3	0.2	2.3	6.1
		3-6	0.2	1.4	6.7
		6-9	0.1	2.9	17.0
18.5	15	0-3	0.4	8.3	23.4
		3-6	1.3	10.5	21.2
		6-9	5.3	18.6	20.9
48.0**	17	0-3	0.1	6.6	8.6
		3-6	0.7		16.7
		6-9	0.9	44.0	49.8

*From Table A.3.

**Alloy contained 3% Si.

Table A.5. Uranium Analyses of Type 1100 Aluminum Stock
Utilized as Cladding Material in Fabrication
of Alclad Uranium-Aluminum Alloy Fuel Plates

Sample No.	Uranium Concentration (ppm)
1	0.8-0.9
2	0.6-0.8
3	0.8-0.9
4	0.8-0.8
Average	0.8
Standard deviation	0.02

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

APPENDIX B

DATA RELATING TO ESTIMATE OF DIFFUSION OF URANIUM
FROM URANIUM-ALUMINUM ALLOY FUEL CORE
INTO TYPE 1100 ALUMINUM CLADDING OF COMPOSITE FUEL PLATES

**THIS PAGE
WAS INTENTIONALLY
LEFT BLANK**

Table B.1. Calculation of C/C_0 Values Based on Specific Diffusion Coefficients (D)

Distance from Bonded Interface (cm)	$\frac{X}{2 \sqrt{Dt}}$ for D Values (cm ² /sec) of					C/C_o for D Values (cm ² /sec) of				
	1×10^{-7}	5×10^{-8}	2×10^{-8}	1×10^{-8}	1×10^{-9}	1×10^{-7}	5×10^{-8}	2×10^{-8}	1×10^{-8}	1×10^{-9}
<u>3-hr Heat Treatment</u>										
0.02	0.15	0.21	0.34	0.48	3.04	0.83	0.75	0.630	0.50	0.03
0.03	0.91	1.26	2.04	2.88	9.12	0.20	0.07	0.004	0	0
0.04	0.61	0.856	1.36	1.92	6.08	0.400	0.230	0.054	0	0
0.05	0.76	1.07	1.70	2.41	7.60	0.300	0.140	0.016	0	0
<u>6-hr Heat Treatment</u>										
0.02	0.22	0.30	0.48	0.68	2.16	0.760	0.680	0.497	0.350	0
0.03	0.32	0.46	0.72	1.02	3.24	0.660	0.540	0.309	0.170	0
0.04	0.43	0.61	0.96	1.36	4.32	0.550	0.390	0.175	0.055	0
0.05	0.54	0.75	1.20	1.70	5.38	0.460	0.300	0.090	0.015	0
<u>9-hr Heat Treatment</u>										
0.02	0.18	0.25	0.40	0.55	1.76	0.800	0.720	0.580	0.430	0.013
0.03	0.26	0.37	0.59	0.83	2.64	0.713	0.600	0.400	0.240	0
0.04	0.35	0.50	0.79	1.11	3.51	0.620	0.480	0.260	0.110	0
0.05	0.44	0.62	0.99	1.39	4.40	0.534	0.380	0.160	0.050	0

Table B.2. Calculated Values for C/C_0 Based on Diffusion Coefficient (D) of 2×10^{-8} cm²/sec

Distance from Bonded Interface (cm)	$\frac{X}{2\sqrt{Dt}}$										C/C_0								
	Heat-Treatment Period (hr)										Heat-Treatment Period (hr)								
	0.5	1.0	1.5	2.0	2.5	3.0	4.0	5.0	10.0	0.5	1.0	1.5	2.0	2.5	3.0	4.0	5.0	10.0	
0.01	0.84	0.59	0.48	0.42	0.37	0.34	0.30	0.27	0.19	0.235	0.408	0.497	0.553	0.600	0.631	0.672	0.710	0.780	
0.02	1.68	1.18	0.97	0.84	0.75	0.68	0.59	0.53	0.37	0.175	0.095	0.174	0.235	0.294	0.336	0.397	0.450	0.593	
0.03	2.51	1.67	1.45	1.25	1.12	1.02	0.89	0.80	0.56	0.0004	0.018	0.040	0.076	0.113	0.149	0.210	0.258	0.428	
0.04	3.34	2.36	1.94	1.67	1.49	1.37	1.18	1.06	0.75	0	0.001	0.006	0.018	0.034	0.054	0.095	0.134	0.290	
0.05		2.96	2.41	2.09	1.86	1.71	1.48	1.32	0.93	0	0	0.0006	0.003	0.008	0.016	0.036	0.062	0.185	
0.06				2.50	2.74	2.05	1.77	1.59	1.12	0	0	0	0.0004	0.002	0.003	0.011	0.024	0.113	
0.07				2.92	2.61	2.39	2.07	1.86	1.31	0	0	0	0	0	0	0.003	0.008	0.063	

ORNL-3206
UC-25 - Metals, Ceramics, and Materials
TID-4500 (17th ed.)

INTERNAL DISTRIBUTION

1. Biology Library	59. J. A. Lane
2-3. Central Research Library	60. C. E. Larson
4. Reactor Division Library	61. C. F. Leitten, Jr.
5. ORNL - Y-12 Technical Library	62. R. S. Livingston
Document Reference Section	63. A. L. Lotts
6-25. Laboratory Records Department	64. H. G. MacPherson
26. Laboratory Records, ORNL R.C.	65. W. D. Manly
27. G. M. Adamson, Jr.	66. R. W. McClung
28. R. J. Beaver	67. C. J. McHargue
29. D. S. Billington	68. A. J. Miller
30. A. L. Boch	69. E. C. Miller
31. E. G. Bohlmann	70. K. Z. Morgan
32. B. S. Borie	71. J. P. Murray (K-25)
33. R. B. Briggs	72. M. L. Nelson
34. R. E. Clausing	73. A. R. Olsen
35. J. H. Coobs	74. P. Patriarca
36. J. A. Cox	75. D. Phillips
37. F. L. Culler	76. H. W. Savage
38. J. E. Cunningham	77. L. D. Schaffer
39. J. H. DeVan	78. J. L. Scott
40. D. A. Douglas, Jr.	79. H. E. Seagren
41. J. H. Erwin	80. M. J. Skinner
42. J. H. Frye, Jr.	81. G. M. Slaughter
43. J. H. Gillette	82. C. O. Smith
44. W. R. Grimes	83. J. A. Swartout
45. J. P. Hammond	84. A. Taboada
46. W. O. Harms	85. E. H. Taylor
47. C. S. Harrill	86. W. C. Thurber
48-52. M. R. Hill	87. A. M. Weinberg
53. E. E. Hoffman	88. J. R. Weir, Jr.
54. A. Hollaender	89. J. C. Wilson
55. A. S. Householder	90. A. A. Burr (consultant)
56. H. Inouye	91. J. R. Johnson (consultant)
57. R. G. Jordan (Y-12)	92. C. S. Smith (consultant)
58. M. T. Kelley	93. R. Smoluchowski (consultant)

EXTERNAL DISTRIBUTION

- 94-95. David F. Cope, Oak Ridge Operations Office
96. D. E. Baker, General Electric, Hanford
97. Ersel Evans, General Electric, Hanford
98. J. L. Gregg, Cornell University
99. R. S. Mateer, University of Kentucky
100. J. Simmons, U.S. Atomic Energy Commission, Washington

- 101. E. E. Stansbury, University of Tennessee
- 102. Donald K. Stevens, U.S. Atomic Energy Commission, Washington
- 103-671. Given distribution as shown in TID-4500 (17th ed.) under Metals, Ceramics, and Materials category (75 copies - OTS)