ZONE - A FINITE ELEMENT MESH GENERATOR

Michael J. Burger

MASTER

March 12, 1980

The logo for Lawrence Livermore Laboratory, featuring a stylized 'L' and the text 'Lawrence Livermore Laboratory'.

This is an informal report intended primarily for internal or limited external distribution. The opinions and conclusions stated are those of the author and may or may not be those of the Laboratory.

Work performed under the auspices of the U.S. Department of Energy by the Lawrence Livermore Laboratory under Contract W-7405-Eng-48.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ZONE - A FINITE ELEMENT MESH GENERATOR

Michael J. Burger

Lawrence Livermore Laboratory, University of California
Livermore, California

DISCLAIMER

This book was prepared in an account of work sponsored by an agency of the United States Government, neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, registered trademark, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

I. INTRODUCTION

The ZONE computer program is a finite element mesh generator which produces the nodes and element description of any two dimensional geometry. The geometry is subdivided into a mesh of quadrilateral and triangular zones arranged sequentially in an ordered march through the geometry. The order of march can be chosen so that the minimum bandwidth is obtained.

The node points are defined in terms of the x and y coordinates in a global rectangular coordinate system. The zones generated are quadrilaterals or triangles defined by four node points in a counter clockwise sequence. Node points defining the outside boundary are generated for slide lines and to describe pressure boundary conditions. The mesh that is generated can be used as input to any two dimensional as well as any axisymmetrical structure program.

The output from ZONE is essentially the input file to NAOS, NIKE2D, DYNA2D, TACO, and other two dimensional, finite element programs. Two additional files generated are the input to the PLOT (See Appendix A) program, which is a post processor for ZONE used to generate the graphical display of the geometry for TMDS (TV Monitor Display System) viewing or for hard copy.

II. PROGRAM CONCEPT AND CHARACTERISTICS

The basic concept used in the program is the definition of a two dimensional structure by the intersection of two sets of lines which

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED *24*

describe material and geometric boundaries. The geometry of the structure is established in a global x-y "right handed" rectangular coordinate system and must lie in the positive x quadrants for axisymmetric problems. Non-axisymmetric geometries can lie anywhere in the x-y space. The y axis is the axis of symmetry for axisymmetric geometries. A set of lines called *meridian* are defined, which describe the geometric and material boundaries and run more-or-less in the same direction. Another set of lines called *rays* which intersect the meridians are also defined at material and geometric boundaries. The order in which the meridians are defined is arbitrary. The rays, however, must be defined in sequences as one proceeds from one end of the structure to the other. These rays and meridians are lines which are defined by a sequence of coordinate points in the global system forming a set of linear line segments.

Figure 1. An example illustrating the relationship between rays and meridians. The same structure can be described two different ways. Note that the ray and meridian end points do not have to correspond to the intersection points as in (b)

In general the choice of lines to be designated as rays and those to be designated as meridians is arbitrary. The meridians and rays in Figure 1, for example, can be interchanged if the positive direction of the ray is reversed. Nodes are numbered in sequence along the rays. The zones are similarly numbered, i.e., numbering begins at the meridian first encountered along a ray and continues to the last meridian encountered along the ray.

Associated with every point along the meridian is a local "right handed" x' - y' rectangular coordinate system. The y' axis corresponds to the tangent and the x' axis corresponds to the normal to the meridian at the point. The positive y' direction coincides with the positive direction along the meridian as shown in Figure 2. The sequence of coordinate points defining the meridian establishes the positive direction along the meridian. The positive x' direction is then specified. The rays *must* pass through the *entire* structure in the positive x' direction so that a sequence of ray-meridian intersections is formed. This concept is illustrated in Figure 1, which shows two correct ways to model the same structure. In Figure 1a only two meridians (M1

Figure 2. An example of the relationship of the local x' - y' coordinate system and the x - y global coordinate system in which the meridian is defined.

and M2) and two rays (R1 and R2) are required to completely define the structure. The positive direction and the termination of the rays and meridians are marked by the arrows. In Figure 1b four meridians and four rays are needed to define the same structure. Note that ray R2 as well as R3 and R4 pass through the entire structure. Also ray R1, the first ray, is at the beginning of the structure, i.e., the first ray encountered with a meridian as one proceeds along the meridian in the positive direction from the meridian origin.

III. REGIONS

The section of the structure between successive rays is called a *region* as illustrated in Figure 3, for example, and cannot have material or geometric discontinuities in the meridional direction, i.e., meridians cannot be discontinuous (begin or end) within a region. This means that a meridian must begin or terminate on a ray. Or conversely, a ray must pass through the beginning or end of every meridian. What is

Figure 3. Examples of regions. In (a) the entire structure has only one region between R1 and R2. In (b) region 2 may be a very narrow strip between R2 and R3. Regions 1 and 3 have transition zones automatically generated.

always implied here by the beginning or end point is that an intended ray-meridian intersection be found. The beginning and terminal points of the ray and meridians may, indeed, extend beyond the intersection to insure that the intersection is found as is shown in Figure 1b. A line may also fall short of an intersection to within an ϵ error. Each region is in turn divided into a number of evenly spaced or non-linearly spaced zones in the meridional direction by passing additional intermediate rays through the region. Care must be taken not to extend the meridians to the point that an unintended intersection is found by other rays. In figure 4, for example, meridian M3 can extend into region 2 and will be ignored unless it is within an ϵ distance from R3 or intersects it.

Figure 4. The geometry in (a) is interpreted as shown in (b). Meridian M3 is ignored in region 2 since it is not within an ϵ distance from R3.

A transition zone is automatically generated with triangular zones at the end of each region when the number of zones on the ray at the beginning of the region is not equal to the number of zones on the ray at the end of the region. In region 1 (Figure 3) the transition zone is an expansion from four zones in region 1 to seven zones in region 2.

A nonlinear zoning option in the meridian and ray direction is also available. In the meridian direction this will generate geometric progression of zone spacing between the beginning and end rays in each region. In the ray direction geometric progression of zone spacing can be generated in each layer independently. The three types of zone spacing options available are illustrated in Figure 5.

Figure 5. Nonlinear zoning in the meridian direction.

IV. LAYERS

The ray segment between any two consecutive ray-meridian intersections is called a layer and is described as passing through, or bounding a material or void area in the structure. By definition, a layer is the segment along the ray between two consecutive ray-meridian intersections. Voids are considered layers. The merging point of two meridians is also considered a layer. The number of zones dividing the two sides of a layer (the subdivision of the ray segments) need not be the same.

When they are not the same, a transition zone is generated at the end of the region as explained in Section III. Each layer in the region is treated independently and may have different transition zones. In Figure 3, for example, the two outer layers in region 3 each have different number of zones (in the ray direction) at ray R3 and at ray R4.

V. MERIDIANS

Meridians are defined by a series of up to 200 coordinate points in the global x-y coordinate system and may, therefore, be multivalued functions. Options can be used to generate arcs, straight lines, offset meridians and ellipses. There is no limit to the number of times that any option may be used in defining a meridian, except to satisfy the 200 point limit. The total number of meridians is limited to 40 which can easily be expanded if necessary.

Meridians may be any length and may be discontinuous within the structure, as opposed to rays which must pass through the entire structure. However, a ray must pass through every meridian discontinuity. A discontinuity means the beginning or ending of a line. The meridians cannot cross each other but any number can have a common beginning or end point. The common point may be a coordinate point anywhere along another meridian, as illustrated in Figure 6, in which meridians M3 and M5 have a common beginning point on M4, and M2 has a common point on M1.

Figure 6. An example of meridians with a common point. Meridians M3, M4, and M5 have a common point at ①. Meridians M1 and M2 have a common point at ②.

The sequence in which meridians are defined is *not* important except when meridians meet at a common point. In this case, they must be defined in the sequence that the ray, slightly away from the common point, would intersect them.

1. Offset

A meridian may be defined entirely or in part as an offset from any other meridian which has previously been defined. There is no limit to the number of times the offset option may be used to define a meridian, except to satisfy the 200 point limit.

Two coordinate points define the beginning and end point of any offset as shown in Figure 7, where part of meridian M2 is an offset $(+\delta_1)$ from M1 in the $+x'$ direction between points 1 and 2. The number of intermediate points on M2 are those found on M1 between the normals to points 1 and 2.

● - Input Point
x - Calculated Point

M2

OFFSET $\begin{cases} X_1 & Y_1 \\ X_2 & Y_2 & M1 & +\delta_1 \end{cases}$

ARC - $X_3 \quad Y_3 \quad \theta_3 \quad N$

ARC - $X_4 \quad Y_4 \quad \theta_4 \quad N$

OFFSET - $X_5 \quad Y_5 \quad M1 \quad +\delta_3$

M3

OFFSET $\begin{cases} X_6 & Y_6 \\ X_7 & Y_7 \\ X_8 & Y_8 & M1 & -\delta_2 \\ X_9 & Y_9 \end{cases}$

Figure 7. Example of the offset option.

Part of meridian M3 is also offset $(-\delta_2)$ from M1 in the $-x'$ direction between points 7 and 8.

2. Circular Arc

A meridian may contain a number of circular arc segments which may sweep an arc of up to 360° . There is no limit to the number of times that the arc option may be used to define a meridian except to satisfy the 200 point limit. The arc may be defined three different ways which require two or four cards for definition. The radius and angle options require two cards and the fillet option requires four cards.

a) The angle option - defines an arc which *begins* at a given point and sweeps to an end point at an absolute angle theta (θ) with a radius (R). Theta is measured from the x global axis and is positive

counter clockwise and negative clockwise. The radius is defined from the center of rotation which is also given. The arc is swept in the positive or negative direction depending on the sign of θ . Two examples of angle arc option are shown in Figure 8 in which the beginning point is at point 1, and the center of rotation is at point 2. The radius (R) is the distance between 1 and 2.

Card 1 - $x_1 y_1$
Card 2 - $x_2 y_2 +\theta N$

Card 1 - $x_1 y_1$
Card 2 - $x_2 y_2 -\theta N$

Figure 8. Examples of the angle arc option with the two cards needed for their definition. N is the number of points along the arc.

b) The radius option defines an arc which begins at the first given point and ends with a second given point. An arc with a given radius (R) is swept in the counter clockwise direction for a +1 flag and in the clockwise direction for a -1 flag. If the center of rotation of the arc has a -x' coordinate as measured from the line connecting points 1 and 2, a negative radius ($-R$) is specified. If the center of rotation has a positive coordinate $+x'$, then a positive radius ($+R$) is specified. The examples in Figure 9 illustrate all four radius arc option possibilities.

Card 1 - $x_1 y_1$
 Card 2 - $x_2 y_2 -R N +1$

$x_1 y_1$
 $x_2 y_2 -R N -1$

$x_1 y_1$
 $x_2 y_2 +R N -1$

$x_1 y_1$
 $x_2 y_2 +R N +1$

Figure 9. Example of the radius arc option with the two cards needed for its definition. N is the number of points along the arc.

c) The fillet option defines an arc which has a radius (R) and is tangent to two intersecting line segments. Four cards are used to define the fillet radius of which the second and third card has the same form as the radius option except that the number of points (N) is a negative value. Points 1 and 2 form the first line segment shown in Figure 10 and points 3 and 4 form the second line segment. Point 1 must precede the tangent point on the first line segment and point 4 must succeed the tangent point on the second line segment.

Figure 10. Example of the Fillet Option. An Arc With Radius R is Formed Tangent to Line Segments 1 and 2

3. Ellipse

A meridian may contain a number of elliptical segments which may sweep up to 360 degrees as measured by an absolute positive or negative angle with 0 degrees on the global x axis and the center at the ellipse center. The sweep convention is the same as for the arc. Two points are used to define the ellipse - one per card. The first point (point 1 in the example shown in Figure 11) is the *beginning* of the ellipse. Point 2, the center of the ellipse, is on the second card. Also on the second card are the sweep angle θ , the tilt angle of the major axis ϕ , which is measured just like θ , and half the major and minor ellipse axis (a and b) as shown in Figure 11.

Figure 11. Example of a segment of an ellipse beginning at ① and ending at θ with center at ② and tilt angle ϕ .

VI. RAYS

Rays are lines which must pass through the *entire* geometry intersecting the meridians in the *positive* x' direction as defined in Figure 2.

IMPORTANT -- A ray cannot begin or terminate, like a meridian, arbitrarily within the structure. A ray *must pass through the entire structure.*

This requirement is imposed to insure the minimum bandwidth for every problem. Problems should, therefore, be modeled so that the ray proceeds in the direction of the smallest geometry dimension if bandwidth is critical. Rays are also defined by a series of up to 200 coordinate points in the global x-y coordinate system and may be multivalued functions. There is no limit to the number of rays that may be defined, but they must be defined sequentially beginning at one end of the geometry and *proceeding in the positive direction* along the meridians. Otherwise, the ray geometry is defined in the same way as the meridian using the arc, offset, free form, and ellipse options described in Section V. The offset option for the ray, however, can only be used with an offset from the previously defined ray. In addition to the geometry, however, each ray is preceded by a control card and a set of cards describing the material number and the number of zones in the layer. Each ray, therefore, is comprised of three groups of cards, assembled in the following order:

- 1) one control card,
- 2) one card for each layer in the ray describing the material number and the number of zones in the layer,

3) a set of cards describing the geometry of the ray as for a meridian.

Except for the last one, each ray is followed by a blank card.

VII. COMMON CHARACTERISTICS -- RAYS AND MERIDIANS

a) The beginning point (P2) in Figure 12 need not be specified in the arc, offset or ellipse options if it has already been generated as the termination point of a previously defined arc, offset, ellipse, or free form. The two consecutive arcs in Figure 12, for example, are defined by the three cards shown. The same thing holds for ellipses and offsets or a combination of any two options.

b) Ray and meridian end points need not lie on a geometric or

Figure 12. Example of the definition of consecutive arcs.

material boundary but they must be defined so as to insure ray-meridian intersections. End points may be defined short of a ray-meridian intersection within a distance c .

c) The beginning point of the sequence of points defining a meridian or ray may be at either end but all meridian and ray definitions must be defined in a consistent direction.

d) The positive direction along a ray or meridian coincides with the increasing sequence of x-y coordinate points defining it.

VIII. ZONE INPUT DESCRIPTION

The input file to ZONE is ZIN in which every card except the title and control card is written with a 7F10.5 format.

Any number of parts may make up the ZIN input file. A card with the letter "c" in column one separates the parts. Each part can stand on its own as a ZIN input file. All the parts are merged together to form a ZOUT output file. The node and zone numbering is continued from one part to the next without the need to set NOD or IZ. If NOD and IZ are set, the numbering begins from these values.

NOTE: A blank card delimits the meridians and rays in the ZIN input file; therefore, a blank in columns 1-10 should not be used for a zero. No blank card should follow the last ray. The problem terminates upon encountering the END-OF-FILE mark.

A. IDENTIFICATION (7A10)

Problem identification.

B. PROBLEM CONTROL CARD (4F5.1, 510.40X, 2F5.2)

col 1-5	NLINE	Number of meridians
col 6-10	SCALE	Scale factor for numerals in plot (0.-1.)
col 16-20	SHORT = 1.	Long form - every node and zone is listed.
	SHORT = 0.	Short form - truncated listing of zones.
col 21-30	EPS	ϵ tolerance of ray-meridian mismatch (default $\epsilon = .0001$).
col 71-75	NOD	The zero node number. Every node number, N, is renumbered NOD+N. This is useful when modeling a large complex structure as several smaller substructure problems which are later assembled into one input to an analysis program.
col 76-80	IZ	The zero zone number. Every zone number, I, is renumbered IZ+I.

C. MERIDIAN DEFINITION (7F10.5)

A maximum of 40 meridians and 200 points per meridian are allowed. Any combination of the options below may be used and as often as needed.

1. Line Segment Option (2 Cards)

Card 1

col 1-10	X_1	Coordinate of first point.
col 11-20	Y_1	Coordinate of first point

Card 2

col 1-10	X_2	Coordinate of second point.
col 11-20	Y_2	Coordinate of second point. Any number of point may be used to define a piece-wise linear curve.

2. Arc - Angle Option (2 Cards)

Card 1

col 1-10 X_1 Coordinate of beginning of arc.

col 11-20 Y_1 Coordinate of beginning of arc.

Card 2

col 1-10 X_2 Coordinate of center of rotation of arc.

col 11-20 Y_2 Coordinate of center of rotation of arc.

col 21-30 θ Absolute angle θ , in degrees, as measured from the x axis up to $\pm 360^\circ$. A positive angle indicates a counter clockwise arc sweep starting at the last point defined on the line (card 1 or the last point defined on previous option) and ending at P. A negative angle indicates a clockwise sweep. Since $\theta = -0$, is indistinguishable from $\theta = +0$, a small angle ($\pm 1. \times 10^{-6}$) must be used in place of a value $\theta = \pm 0$.

col 31-40 N The number of points used internally in the program to define the arc. N should be large enough to define the arc properly. The range is $10 < N \leq 200$. If left blank, $N = 20$.

3. Arc - Radius Option (2 Cards)

Card 1

col 1-10 X_1 Coordinate of the beginning of arc.

col 11-20 Y_1 Coordinate of the beginning of arc.

Card 2

col 1-10 X_2 Coordinate of the end of the arc.

col 11-20 Y_2 Coordinate of the end of the arc.

col 21-30 R Radius of arc. A positive radius (+R) indicates a center of rotation on the +x' side of the line connecting the arc end points. A negative radius (-R) indicates a center of rotation on the -x' side (see Figure 9).

col 31-40	N	The number of points used internally in the program to define the arc. N should be large enough to properly define the arc. The range is $10 \leq N \leq 200$. If left blank $N = 20$.
col 41-50	XN1	Flag indicating the direction of arc sweep. A +XN1 indicates a counter clockwise sweep. A -XN1 indicates a clockwise sweep (see Figure 9).

4. Arc - Fillet Option (2 Cards)

Card 1

col 1-10	X_1	Coordinate of first point on first line.
col 11-20	Y_1	Coordinate of first point on first line.

Card 2

col 1-10	X_2	Coordinate of second point on first line.
col 11-20	Y_2	Coordinate of second point on first line.

Card 3

col 1-10	X_3	Coordinate of first point on second line.
col 11-20	Y_3	Coordinate of first point on second line.
col 21-30	R	Radius of arc. Same as in VIII C.3.
col 31-40	N	Number of points. Same as in VIII C.3, except that N is negative. (See Fig. 10.)
col 41-50	XN1	Flag-sweep direction. Same as in VIII C.3.

Card 4

col 1-10	X_4	Coordinate of second point on second line.
col 11-20	Y_4	Coordinate of second point on second line.

5. Ellipse Option (2 Cards)

Card 1

col 1-10	X_1	Coordinate of the beginning of the ellipse.
col 11-20	Y_1	Coordinate of the beginning of the ellipse.

Card 2

col 1-10	X_2	Coordinate of the center of the ellipse.
col 11-20	Y_2	Coordinate of the center of the ellipse.

col 21-30 θ	Absolute angle θ , in degrees, as measured from the x axis up to $\pm 360^\circ$. A positive θ indicates a counter clockwise ellipse is swept starting at the last point defined on the line (card 1 or the last point defined in the previous option) and ending at θ . A negative θ indicates a clockwise sweep. For $\theta = 0$. (see "Arc-Angle Option").
col 31-40 N	The number of points used internally in the program to define the ellipse. N should be large enough to define the ellipse properly. The range is $10 \leq N \leq 200$. If left blank, $N = 20$.
col 41-50 A	The half-length of the major axis of the ellipse.
col 51-60 B	The half-length of the minor axis of the ellipse.
col 61-70 ϕ	The tilt angle ϕ of the major axis measured in degrees the same way as θ (see Figure 11).

6. Offset Option (2 Cards)

Card 1

col 1-10 X_1	Coordinate of the beginning of the offset.
col 11-20 Y_1	Coordinate of the beginning of the offset.

Card 2

col 1-10 X_2	Coordinate of the last point of the offset.
col 11-20 Y_2	Coordinate of the last point of the offset.
col 21-30 M	Meridian number, M, of a previously defined meridian from which the offset distance is measured.
col 31-40 δ	Offset distance $\pm \delta$. A $+\delta$ is measured in the $+x'$ direction from meridian M. A $-\delta$ is measured in the $-x'$ direction. A point

is generated a normal distance $\pm \delta$ from the every point encountered in meridian M between the beginning and end point defined on these two cards (see Figure 7).

NOTE:

1. The beginning and end lie on the new meridian and not on meridian M.
2. The offset distance δ must be smaller than any radius of curvature encountered in meridian M.
3. The maximum offset distance δ is ± 10 .

D. RAY DEFINITION (7F10.5)

The maximum number of points defining a ray is 200. There is no limit to the number of rays that may be used. Any combinations of the options below may be used, and as often as needed.

a. Control Card

col 1-10	NL	Number of layers intersected by this ray. By definition this is the number of ray-meridian intersections minus one.
col 11-20	NR	Number of zones dividing the region between this ray and the next (meridian direction).
col 21-30	NMER	Nonlinear zone spacing option (see Figure 5).
	NMER=1	Fine spacing to course spacing.
	NMER=2	Course spacing to fine spacing.
	NMER=3	Fine-course-fine spacing.

b. Layer Description (NL Cards) (NL < 40)

col 1-10	MN	Material number of succeeding material - the material between this ray and the next. The material number can be any number between 0 and 40.
----------	----	--

NOTE: A zero material number indicates the material that follows is a void space.

col 11-20 NE

Number of zones along the ray segment defined by this layer.

NOTE: The number of zones must be strictly interpreted as the number of divisions that the line itself (ray segment) is subdivided. It must not be interpreted as the number of zones in the previous or succeeding layers because this will lead the user into interpretation difficulties. See, for example, ray R2 in Figure 4.

The number of zones can be one or more. A value for NE = 0 indicates that the meridians bounding this layer converge to a common point on this ray.

col 21-30 SWITCH

An option to change the node point distribution within a layer. ZONE will, at times, produce meshes like the one shown in Figure 13a. Setting SWITCH = 1. will produce the mesh in Figure 13b.

NOTE: ZONE will attempt to make the correct choice between 12a and 12b. Use the switch option only to override the program choice.

col 31-40 NONRAY

Nonlinear zone spacing in the ray direction in the succeeding material in this layer. Each layer may be individually set.

NONRAY=1 Fine spacing to course spacing.

NONRAY=2 Course spacing to fine spacing.

NONRAY=3 Fine-course-fine spacing.

Figure 13. An example of the SWITCH option. ZONE generates the mesh in (a). Setting SWITCH = 1. produces the mesh in (b).

c. Ray Description (Maximum - 200 Points per Ray)

Any combination of the options below may be used to define the geometry of the ray.

1. Line Segment Option
(Same as VIII C.1)
2. Arc - Angle Option
(Same as VIII C.2)
3. Arc - Radius Option
(Same as VIII C.3)
4. Arc - Fillet Option
(Same as VIII C.4)
5. Ellipse Option
(Same as VIII C.5)
6. Offset Option

The offset option for rays is the same as for meridians in VIII C.6 except that the meridian number (M_1) from which the offset is measured is always set to $M_1 = 1$. The offset distance, δ , is input as a positive number and the offset ray will always be generated a positive δ distance from the preceding ray as measured in the positive meridian direction.

7. Vector Option (1 Card)

col 1-10	X	Coordinate of the beginning of a vector.
col 11-20	Y	Coordinate of the beginning of a vector.
col 21-30	θ	Angle, in degrees, of a line (vector) as measured from the global x axis as in the arc option (VIII C.2). A straight line is generated from the X,Y coordinates at an angle θ and with a length of 5000.

IX OUTPUT

OUTPUT FILES

ZONE produces 5 output files as follows:

1. ZOUT - The complete text output file to be used as input to an analysis program. It includes the X-Y coordinates of the nodes, the node connectivities of the zones, the boundary pressure, and all the nodes for slide lines along the entire outer boundary, and the areas, volumes and centroids of each different material in the geometry. The pressure cards and slide line nodes are grouped into an inner surface and an outer surface. The outer surface begins with the first node and moves along the first ray and proceeds counter clockwise around the geometry ending at the last node point. The inner surface also begins at the first node and proceeds clockwise around the geometry ending at the last node point. Caution: Some pressure cards and slide line nodes in complex insets along the boundary may not be generated.

If more than one part is present, then all the pressure card and slide line nodes are assembled in the same sequence as the parts. All the inner nodes are assembled in a list labeled INPRESS and INSLIDE. All the outer nodes are assembled in a list labeled OUTPRESS AND OUTSLIDE.

2. FILE1 - A text file containing the node point coordinates in short form for input to PLOT - a plotting program.
3. FILE2 - A text file containing the node connectivities of the zones in short form for input to PLOT.
4. SAVE - A "cleaned up" copy of the input file, ZIN, which can subsequently be used as the input to ZONE.
5. DUMP - Contains the meridian and ray coordinates as they are interpreted by ZONE from the various input options. It also contains the X-Y coordinates of the ray-meridian intersections found along each ray - very useful when debugging the input.
6. UA80 - A plot file of the geometry that can be viewed with UXTV or hard copy obtained with UXRJ. Each part is plotted on a separate frame and shows only the lines input from ZIN.

X EXAMPLES

A. Example 1

This example illustrates the use of the ellipse option, a/c option, and ray vector option. The dimensions of the geometry are shown in Figure 14a and the resulting mesh is shown in Figure 14b. The listing of the input that follows is the SAVE file generated by ZONE.

Figure 14. (a) geometry for Example 1. (b) The mesh generated by ZONE.

LISTING OF EXAMPLE 1

EXAMPLE 1

5.0000						
3.7000	1.5000					
.0	1.5000					
	MERIDIAN # 2					
3.7000	2.0000					
3.3000	2.0000					
3.2000	2.1000	.2000	.0	-1.0000		
	MERIDIAN # 3					
2.9000	3.0000					
.2500	3.0000					
	MERIDIAN # 4					
2.4000	1.9000					
1.6000	2.2000	-159.4500	30.0000	.0000	.5000	.0
	MERIDIAN # 5					
2.4000	2.5000					
1.6000	2.2000	159.4500	30.0000	1.0000	.5000	.0
	PAY # 1					
1.0000	5.0000					
1.0000	5.0000					
3.7000	1.5000	90.0000	~.0			
	PAY # 2					
2.0000	6.0000					
2.0000	5.0000	1.0000	~.0			
2.0000	9.0000	1.0000	~.0			
3.2000	1.5000					
3.2000	2.1000					
2.9000	3.0000					
	PAY # 3					
3.0000	10.0000					
3.0000	4.0000					
.0	6.0000					
3.0000	4.0000					
2.4000	1.5000					
2.4000	1.9000					
1.6000	2.2000	20.5600	30.0000	1.0000	.5000	.0
2.4000	3.0000					
	PAY # 4					
3.0000	5.0000					
1.0000	4.0000	1.0000	~.0			
1.0000	6.0000	1.0000	~.0			
1.0000	4.0000	1.0000	~.0			
.8000	1.5000					
.9000	1.9000					
1.6000	2.2000	-201.5600	30.0000	1.0000	.5000	.0
.8000	3.0000					
	PAY # 5					
1.0000	~.0					
1.0000	14.0000					
.0	1.5000					
.3000	3.0000	6.0000	40.0000	-1.0000		

Example 2

The mesh for the pressure vessel in Figure 14a is shown in Figure 14b. The input listing for this example is also the SAVE file.

Figure 15. (a) Example 2 pressure vessel geometry. All the rays and meridians are free forms. M4 and M5 are offset from M1. There is a common point on M4 with M2 and M3. (b) Mesh generated by ZONE.

LISTING OF EXAMPLE 2

PRESSURE VESSEL					
			.001	1.967	2.848
					.3
					.01
1.0000	5.2880				
2.4800	1.9760				
3.8800	1.8280				
5.2800	1.6140				
6.6800	1.4900				
8.0800	1.4570				
9.4800	1.4000				
10.8800	1.3200				
12.2800	1.2200				
13.6800	1.0900				
15.0800	1.0200				
16.4800	1.0000				
17.8800	1.0000				
19.2800	1.0000				
20.6800	1.0000				
22.0800	1.0000				
23.4800	1.0000				
24.8800	1.0000				
26.2800	1.0000				
27.6800	1.0000				
29.0800	1.0000				
30.4800	1.0000				
31.8800	1.0000				
33.2800	1.0000				
34.6800	1.0000				
36.0800	1.0000				
37.4800	1.0000				
38.8800	1.0000				
40.2800	1.0000				
41.6800	1.0000				
43.0800	1.0000				
44.4800	1.0000				
45.8800	1.0000				
47.2800	1.0000				
48.6800	1.0000				
50.0800	1.0000				
51.4800	1.0000				
52.8800	1.0000				
54.2800	1.0000				
55.6800	1.0000				
57.0800	1.0000				
58.4800	1.0000				
59.8800	1.0000				
61.2800	1.0000				
62.6800	1.0000				
64.0800	1.0000				
65.4800	1.0000				
66.8800	1.0000				
68.2800	1.0000				
69.6800	1.0000				
71.0800	1.0000				
72.4800	1.0000				
73.8800	1.0000				
75.2800	1.0000				
76.6800	1.0000				
78.0800	1.0000				
79.4800	1.0000				
80.8800	1.0000				
82.2800	1.0000				
83.6800	1.0000				
85.0800	1.0000				
86.4800	1.0000				
87.8800	1.0000				
89.2800	1.0000				
90.6800	1.0000				
92.0800	1.0000				
93.4800	1.0000				
94.8800	1.0000				
96.2800	1.0000				
97.6800	1.0000				
99.0800	1.0000				
100.4800	1.0000				
101.8800	1.0000				
103.2800	1.0000				
104.6800	1.0000				
106.0800	1.0000				
107.4800	1.0000				
108.8800	1.0000				
110.2800	1.0000				
111.6800	1.0000				
113.0800	1.0000				
114.4800	1.0000				
115.8800	1.0000				
117.2800	1.0000				
118.6800	1.0000				
120.0800	1.0000				
121.4800	1.0000				
122.8800	1.0000				
124.2800	1.0000				
125.6800	1.0000				
127.0800	1.0000				
128.4800	1.0000				
129.8800	1.0000				
131.2800	1.0000				
132.6800	1.0000				
134.0800	1.0000				
135.4800	1.0000				
136.8800	1.0000				
138.2800	1.0000				
139.6800	1.0000				
141.0800	1.0000				
142.4800	1.0000				
143.8800	1.0000				
145.2800	1.0000				
146.6800	1.0000				
148.0800	1.0000				
149.4800	1.0000				
150.8800	1.0000				
152.2800	1.0000				
153.6800	1.0000				
155.0800	1.0000				
156.4800	1.0000				
157.8800	1.0000				
159.2800	1.0000				
160.6800	1.0000				
162.0800	1.0000				
163.4800	1.0000				
164.8800	1.0000				
166.2800	1.0000				
167.6800	1.0000				
169.0800	1.0000				
170.4800	1.0000				
171.8800	1.0000				
173.2800	1.0000				
174.6800	1.0000				
176.0800	1.0000				
177.4800	1.0000				
178.8800	1.0000				
180.2800	1.0000				
181.6800	1.0000				
183.0800	1.0000				
184.4800	1.0000				
185.8800	1.0000				
187.2800	1.0000				
188.6800	1.0000				
190.0800	1.0000				
191.4800	1.0000				
192.8800	1.0000				
194.2800	1.0000				
195.6800	1.0000				
197.0800	1.0000				
198.4800	1.0000				
199.8800	1.0000				
201.2800	1.0000				
202.6800	1.0000				
204.0800	1.0000				
205.4800	1.0000				
206.8800	1.0000				
208.2800	1.0000				
209.6800	1.0000				
211.0800	1.0000				
212.4800	1.0000				
213.8800	1.0000				
215.2800	1.0000				
216.6800	1.0000				
218.0800	1.0000				
219.4800	1.0000				
220.8800	1.0000				
222.2800	1.0000				
223.6800	1.0000				
225.0800	1.0000				
226.4800	1.0000				
227.8800	1.0000				
229.2800	1.0000				
230.6800	1.0000				
232.0800	1.0000				
233.4800	1.0000				
234.8800	1.0000				
236.2800	1.0000				
237.6800	1.0000				
239.0800	1.0000				
240.4800	1.0000				
241.8800	1.0000				
243.2800	1.0000				
244.6800	1.0000				
246.0800	1.0000				
247.4800	1.0000				
248.8800	1.0000				
250.2800	1.0000				
251.6800	1.0000				
253.0800	1.0000				
254.4800	1.0000				
255.8800	1.0000				
257.2800	1.0000				
258.6800	1.0000				
260.0800	1.0000				
261.4800	1.0000				
262.8800	1.0000				
264.2800	1.0000				
265.6800	1.0000				
267.0800	1.0000				
268.4800	1.0000				
269.8800	1.0000				
271.2800	1.0000				
272.6800	1.0000				
274.0800	1.0000				
275.4800	1.0000				
276.8800	1.0000				
278.2800	1.0000				
279.6800	1.0000				
281.0800	1.0000				
282.4800	1.0000				
283.8800	1.0000				
285.2800	1.0000				
286.6800	1.0000				
288.0800	1.0000				
289.4800	1.0000				
290.8800	1.0000				
292.2800	1.0000				
293.6800	1.0000				
295.0800	1.0000				
296.4800	1.0000				
297.8800	1.0000				
299.2800	1.0000				
300.6800	1.0000				
302.0800	1.0000				
303.4800	1.0000				
304.8800	1.0000				
306.2800	1.0000				
307.6800	1.0000				
309.0800	1.0000				
310.4800	1.0000				
311.8800	1.0000				
313.2800	1.0000				
314.6800	1.0000				
316.0800	1.0000				
317.4800	1.0000				
318.8800	1.0000				
320.2800	1.0000				
321.6800	1.0000				
323.0800	1.0000				
324.4800	1.0000				
325.8800	1.0000				
327.2800	1.0000				
328.6800	1.0000				
330.0800	1.0000				
331.4800	1.0000				
332.8800	1.0000				
334.2800	1.0000				
335.6800	1.0000				
337.0800	1.0000				
338.4800	1.0000				
339.8800	1.0000				
341.2800	1.0000				
342.6800	1.0000				
344.0800	1.0000				
345.4800	1.0000				
346.8800	1.0000				
348.2800	1.0000				
349.6800	1.0000				
351.0800	1.0000				
352.4800	1.0000				
353.8800	1.0000				
355.2800	1.0000				
356.6800	1.0000				
358.0800	1.0000				
359.4800	1.0000				
360.8800	1.0000				
362.2800	1.0000				
363.6800	1.0000				
365.0800	1.0000				
366.4800	1.0000				
367.8800	1.0000				
369.2800	1.0000				
370.6800	1.0000				
372.0800	1.0000				

		RAY	# 4	
5.0000	15.0000			
1.0000	3.0000			
.0	1.0000			
2.0000	4.0000			
3.0000	2.0000			
.0	10.0000			
2.4180	4.2290			
1.1850	4.2290			
1.1310	4.2510			
1.0500	4.2550			
-.0090	4.2550			
		RAY	# 5	
4.0000	5.0000			
1.0000	3.0000			
2.0000	.0			
2.0000	4.0000			
3.0000	2.0000			
2.3080	2.3180			
1.9570	2.5490			
1.2000	2.5490			
		RAY	# 6	
3.0000	18.0000	1.0000		-.0
.0	.0			
2.0000	4.0000			
3.0000	2.0000			
1.9990	2.0030			
1.2000	2.0030			
		RAY	# 7	
2.0000	-.0			
1.0000	4.0000			
1.0000	2.0000			
.0	.1780			
.0	.8540			

XI PROGRAM AVAILABILITY

The executable object program can be executed from the public library MJBLIB on the CDC 7600's by typing:

X MJBLIB ZONE / T V

The plotting program used with ZONE is PLOT (see Appendix A) and can be obtained from the library by typing:

X MJBLIB PLOT / T V.

APPENDIX A

PLOT Plotting Program

The PLOT program is an interactive plotting program designed to be used with ZONE to generate graphic displays of the geometry, the mesh, and a number of other options listed below. The input files for PLOT, produced by ZONE, are FILE1 and FILE2. FILE1 contains the node point coordinates in a format of (I5, F5.1, 2F10.5) which correspond to the node point number, boundary condition, and x, y coordinates. FILE2 contains the element connectivity in a format of (6I5) which corresponds to the element number, the four nodes, and the material number. The first card is a title card in each file.

The commands listed below are typed on the terminal. Any number of commands, separated by blanks, can be typed on a line, and any number line may be typed.

Valid Plot Commands

<u>Command</u>	<u>Arguments</u>	<u>Explanation</u>
OUTLIN		Draw the geometry outline.
OUTLINM		Draw the geometry outline with a mirror image about the $X = 0$ axis.
ZONE		Draw the geometry including the mesh.
ZONEM		Draw the mesh with a mirror image of the outline on one side.
ZONEN		Draw the mesh with element numbers.
NODE		Draw the mesh with node numbers.
BOTH		Draw the mesh with node and element numbers.
MAT		Draw the mesh with material number in each element.
ELE	N	Specify element N as the center of the zoom window.
X	A	Specify A as the X-coordinate of the center of the zoom window.
Y	B	Specify B as the Y-coordinate of the center of the zoom window.

DX	A	Specify A as the X zoom window width.
DY	B	Specify B as the Y Zoom window height.
SCALN	A	Scale the size of the node and element numbers by a factor of A.
SCALP	A	Scale the size of the geometry by a factor of A. ($0 > A > 1$).
TMIN	N	Begin plotting with element N.
IMAX	N	End plotting with element N.
CHOP	N	Chop geometry into N segments and plot each segment on a different frame.
READ		Read the commands from this table from a TRIX generated file called "PIN".
RETURN		Return control to terminal after reading commands from "PIN". (Last command in "PIN").
END		END plotting.