EGG-NE-9768
MS001.3

APR 27 1992

**Idaho
National
Engineering
Laboratory**

*Managed
by the U.S.
Department
of Energy*

INFORMAL REPORT

**CRITICALITY SAFETY EVALUATION OF ROCKY FLATS
PLANT ONE-GALLON SHIPPING CONTAINERS**

Maria E. Shaw

Published December 1991

INEL
EG&G Idaho, Inc.
Idaho Falls, ID 83415

*Work performed under
DOE Contract
No. DE-AC07-76ID01570*

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

EGG-NE--9768

DE92 012323

CRITICALITY SAFETY EVALUATION OF ROCKY FLATS
PLANT ONE-GALLON SHIPPING CONTAINERS

Maria E. Shaw

Published December 1991

INEL
EG&G Idaho, Inc.
Idaho Falls, ID 83415

J. Blain Briggs
Checked by

[Signature]
Approved By

Prepared for the
U.S. Department of Energy
Idaho Operations Office
Under DOE Contract No. DE-AC07-76ID01570

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

CONTENTS

CRITICALITY SAFETY EVALUATION	1
CRITICALITY SAFETY EVALUATION SIGN-OFF SHEET	2
1. INTRODUCTION	4
2. SUMMARY	5
3. APPROVED EQUIPMENT LIST	7
4. EVALUATION ASSUMPTIONS	8
5. REQUIRED CONTROLS AND ENGINEERED SAFETY FEATURES	10
5.1 Required Controls	10
5.2 Engineered Safety Features	10
6. TECHNICAL BASES	11
6.1 Technical Bases for Controls	11
5.2 Technical Bases for Engineered Safety Features	12
7. CONCLUSIONS	13
8. CHECKLISTS	15
8.1 Double Contingency Analysis	15
8.2 Normal Condition Analysis for Shipping Container Operations	16
8.3 Failure Analysis Checklist for Shipping Container Operations	30
8.4 Evaluation Needs Analysis	55
9. REFERENCES	58
10. DISCUSSION	59
10.1 Codes, Cross Sections and Validations	59
10.2 Dry Uranium and Plutonium Metal	60
10.3 Plutonium Solution	64
10.4 Metal Slurries	67

CONTENTS, cont'd

11. SCALED DRAWING OF THE CONDITIONS MODELED	68
12. SUMMARY OF CALCULATION RESULTS	69
13. DRAFT LIMIT	87
14. CALCULATIONS	88
14.1 Calculated Number Densities for Material	88
14.2 Calculation of Average k_{eff}	89
15. KENO-V.A INPUT LISTINGS	90

FIGURES

1. Unit cell use for representing arrays of cans with offset fuel	61
2. Effects of all degrees of moderation, Pu metal cases	71
3. Volume of Pu solution vs. k_{eff} , double-batched one-gallon cans, stacked 3 high (offset, spherical fuel)	77
4. Effects of stacking arrays of cans with 1/2 inch lead shielding, 100 g U-233 per can	83
5. Density vs. k-effective; 200 g Pu per can, cans stacked 3 high	86

TABLES

1. Summary of Results For Pu Solution (1000 Grams/Liter)	13
2. Summary of KENO-V.a Results For Pu Metal Showing the Effects of all Degrees of Moderation	69
3. Summary of KENO-V.a Results for Pu Metal	72
4. Summary of KENO-V.a Results for Pu Solution Showing the Effects of Variation in the Volume of Fuel	73
5. Summary of KENO-V.a Results for Pu Solution Showing the Effects of All Degrees of Moderation	74
6. Summary of KENO-V.a Results for Plutonium Solution	76
7. Summary of KENO-V.a Results Showing the Effects of Interaction with Slab of Plutonium Solution Having a k_{eff} of 0.90 (Reference 1, Section 5.2.4)	78
8. Summary of KENO-V.a Results for Alternate Geometries	79
9. Summary of KENO-V.a Results for U-233 Metal Showing the Effects of All Degrees of Moderation	80
10. Summary of KENO-V.a Results for U-233 Metal Showing the Effect of Stacking Cans with 1/2 Inch Lead Shielding	82
11. Summary of KENO-V.a Results for Pu Metal Showing the Effect of Increasing Density	84

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 1 of 116

CRITICALITY SAFETY EVALUATION

OPERATION TITLE: Handling, Shipping and Storage of RFP one-gallon containers

BUILDING: A11

AREA: Intracplant

DATE OF EVALUATION: December 1991

EVALUATOR: Maria E. Shaw 12/6/91

SECOND CRITICALITY ENGINEER: Robert R. Jones / Mark Hickey 12/6/91

KENO VALIDATOR: J. Blain Buggs 12/6/91

TECHNICAL REVIEWER: J. Blain Buggs 12/6/91

MANAGER APPROVAL: Paul J. Larson 12/9/91

OPERATIONS CONCURRENCE: H. B. Fleming 12/13/91

OPERATIONS REVIEW COMMITTEE: W. H. Hargrett Jr B-707 12/18/91

Operations concurrence on this form indicates that they have read and understand the CSOBs and indicates that they acknowledge the required controls and ESFs are controlled under CCCP.

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 2 of 116

CRITICALITY SAFETY EVALUATION SIGN-OFF SHEET

Operation: Handling, Shipping and Storage of RFP one-gallon containers

Date: December 1991

1) DOCUMENTATION REQUIREMENTS

The Cover Sheet, Sign off Sheet, and the following items have been adequately documented and verified by J. Blair Briggs (Technical Reviewer).

1. Introduction (Request and Operation Description, etc.)
2. Summary
3. Approved Equipment List
4. Evaluation Assumptions
5. Required Controls and Engineered Safety Features
6. Technical Bases
7. Conclusions (e.g., Request acceptable, limit changed, etc.)
8. Checklists (Evaluation Criteria Checksheets, etc.)
9. References (Previous Evaluations etc.)
10. Discussion
11. Scaled Drawings of the Condition(s) Being Evaluated.
12. Summary of Calculation Results (e.g., k_{eff} , etc.)
13. Draft Limit
14. Calculations
15. KENO Input and Output

2) CONDITIONS TO CALCULATE

The normal and abnormal condition analysis forms were complete
Maria P. Shaw (Evaluator) with appropriate input from engineering, operations, etc.

The normal and abnormal conditions calculated were reviewed by
J. Blair Briggs (Technical Reviewer) with appropriate input from engineering, operations, etc.

3) CALCULATIONAL MODEL

The calculational model was designed by Maria P. Shaw (Evaluator).

The calculational model was reviewed by J. Blair Briggs (Technical Reviewer), and it was found to be neither non conservative, nor too conservative.

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 3 of 116

4) PREPARE INPUT DATA

The computer input data was prepared by Maxie P. Shaw (Evaluator).

The computer input data was reviewed by Robert R. Jones (2nd Engineer), and found to be correct with respect to what was said to be modeled and with the proper selection of computer program options.

5) COMPUTER USE

The use of the computer program and cross sections for this evaluation have been approved by J. Blair Buggs (KENO Validator).

6) INTERPRET RESULTS

The results have been reviewed and checked by Mark Nicky (2nd Engineer), who has determined that the answers were not misread, the calculation converged, there was representative sampling for Monte Carlo calculations.

7) COMMUNICATE CONCLUSIONS

The assumptions, result bias, and conclusions of the calculation study are documented in the evaluation and have been checked for logic and no conclusion is based on only one calculation by J. Blair Buggs (Technical Reviewer).

8) REVIEW

Calculational studies that are not considered routine or that support a change in plant philosophy are to be reviewed by an independent review team as specified by the Criticality Engineering Manager.

Additional Peer Review Required Yes _____ No ☒ _____
If yes, Level I _____ or Level II _____ (CE Manager)

Paul J. Farn 12/9/91

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 4 of 116

1. INTRODUCTION

An initial criticality safety evaluation of Rocky Flats Plant (RFP) One-Gallon Shipping Containers is reported in Reference 1. Due to operational requirements, it is desirable to remove or modify some of the limits and restrictions imposed by the previous evaluation. Specifically, the following changes have been requested:

1. Remove the container limit (20 containers in one location).
2. Apply a mass limit for "dry" plutonium and uranium metal and increase that limit from 20 grams to 50 grams per container. Extend the range of applicability to include plutonium and uranium slurries.
3. Establish a volume limit for plutonium solutions based on a concentration of 1000 grams/liter.
4. Remove the administrative spacing requirement.

This evaluation is being performed to supplement the Reference 1 evaluation and to comply with current requirements. This report documents additional calculations and results that were performed in support of the above modifications.

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 5 of 116

2. SUMMARY

Criticality safety calculations have been performed to provide an analytical basis for handling, storage and transport of RFP one-gallon shipping containers. A mass limit was established for metal (solid uranium or plutonium) and slurries (undissolved U or Pu solids in a "mud", "sludge", or "slurry"). A separate volume limit was developed for plutonium solutions (liquids, either aqueous or organic, containing no visible undissolved solids).

This analysis has been categorized as Quality Level A (according to EG&G Idaho Quality Manual) and is intended to comply with NQA-1.

For convenience, normal case conditions for RFP one-gallon shipping containers were modeled as infinite arrays of containers. Arrays were reflected tightly on top by 30 cm of concrete and on the bottom by 60 cm of concrete. These normal (non-accident) cases were analyzed with mass or volume values at the limits (50 g "dry" plutonium or uranium metal, or 100 ml plutonium solution per container). K_{eff} values of 0.534 ± 0.002 and 0.572 ± 0.004 were calculated for Pu and U-233 metals, respectively. The normal values for Pu and U-233 slurries were 0.629 ± 0.003 and 0.458 ± 0.003 . Metal and slurry cases for this limiting normal condition were stacked 20 high (as discussed in the accident section below and in Section 10.2). The limiting normal case for solution (only Pu solutions were evaluated) was represented as a planar array and produced a k_{eff} of 0.392 ± 0.002 .

To more closely represent typical operating conditions, infinite planar arrays of cans containing the various materials were evaluated with no stacking. Solution concentrations were reduced 10 grams/liter. The resulting k_{eff} for Pu solution was 0.051 ± 0.001 . Calculated k_{eff} values of 0.203 ± 0.002 and 0.219 ± 0.002 resulted for typical condition dry plutonium and U-233 metal systems, respectively. Slurries were slightly less reactive at 0.168 ± 0.002 (Pu) and 0.095 ± 0.001 (U-233).

The following accidents were evaluated:

1. Accidents for "dry" Pu or U metal and metal slurries

- a. Mass violation (double-batching)
- b. Flooding
- c. Sprinkler accident
- d. Vehicle accident, physical damage
- e. Spacing violation

Metal cases, including those flooded at various water volume fractions, were evaluated double-batched and in most cases stacked 20 high (see discussion in Section 10.2).

2. Accidents for Pu solution

- a. Volume violation (double-batching)
- b. Stacking
- c. Flooding
- d. Sprinkler accident
- e. Vehicle accident
- f. Spacing violation

Solution cases were evaluated double batched and stacked 3 high.

Mass and volume violations, stacking, sprinkler accidents, and spacing violations are combinable events. However, it was demonstrated that spacing limits are not required.

The highest k_{eff} calculated for the accidents evaluated was a weighted average of 0.92829 ± 0.00230 . This was for a vehicle accident in which 60 Pu metal spheres (representing the contents of 60 one-gallon cans) were modeled close-packed and fully reflected.

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 7 of 116

3. APPROVED EQUIPMENT LIST

In addition to the fissile materials specified in the limits, the following items may be placed inside one-gallon cans:

Plastic bags

Tape

8801 Vollrath cans

8802 Vollrath cans

Glass or plastic sample vials

Temperature indicating devices

Miscellaneous labels

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 8 of 116

4. EVALUATION ASSUMPTIONS

The following assumptions were made for the evaluation of RFP one-gallon shipping containers:

Assumptions for Container Representation

Outer Diameter 6.5625 in. (16.66875 cm)
Overall Height 7.6875 in. (19.52625 cm)
Wall Thickness 0.010 in. (0.0254 cm)
Material Carbon Steel
Lead Shielding (when used)..... 0.5 in. (1.27 cm)

Assumptions for Container Content Representation

Fissile Material 95 wt.% Pu-239 & 5 wt.% Pu-240
(solid metal, density
19.84 g/cc)
or
100 wt.% U-233 (solid metal,
density 18.70 g/cc), all
isotopes of uranium are
enveloped by U-233
or
95 wt.% Pu-239 and 5 wt.%
Pu-240, 1000 grams/liter
(solution) in 92 vol.% water,
8 vol.% polyethylene
(Reference 2)
or
95 wt.% Pu-239 and 5 wt.%
Pu-240 or 100 wt.% U-233,
> 1000 grams/liter (slurry),
displacing moderator of 92 vol.%
water and 8 vol.% polyethylene
(Reference 2)

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 9 of 116

Moderation (external to fuel) All degrees of moderation (100% polyethylene or 92 vol.% water, 8 vol.% polyethylene at various volume fractions) were evaluated. (See Section 12, Tables 2 and 9.)

Internal Configuration Pu and U metal and slurry spheres offset axially and radially. Pu solution cases in spherical geometry, centered or offset.

Assumptions for Container Configuration

Container Configuration Close-packed triangular-pitch arrays of containers in planar or stacked configurations. (The closed-packed assumption was demonstrated to be the most reactive configuration.)

Reflection Conservative concrete reflection 30 cm on top, 60 cm on bottom.

Moderation All degrees of water moderation between containers.

5. REQUIRED CONTROLS AND ENGINEERED SAFETY FEATURES

5.1 Required Controls

1. The mass of "dry" plutonium or uranium metal or oxide is limited to 50 grams per one-gallon can. A mass limit of 50 grams total, including non-fissile matrix material, applies to metal slurries.
2. The volume of plutonium solutions is limited to 100 ml per one-gallon can regardless of inner containment.
3. The containers must be limited to planar arrays (no stacking).
4. Separation limits between RFP one-gallon containers and other fissile material are not required with the preceding limits on mass, volume, and stacking.
5. A container limit is not required for storage; however, due to the possibility of breaching containers during transport (e.g. in a vehicle accident), the number of containers must be limited to 40 for these operations.
6. Beryllium shall not be placed in one gallon cans containing fissile materials.

5.2 Engineered Safety Features

There are no engineered safety features which pertain to one gallon cans.

6. TECHNICAL BASES

6.1 Technical Bases for Controls

1. The limit for metal and slurries was evaluated and was shown, as requested, to be acceptable at 50 grams/can. It was possible to show that higher mass values for metal were also safe.
2. The 100 ml volume limit for Pu solutions (1000 g/l) was selected as the next lower "round" number which results in a k_{eff} of 0.95 or less with required combined accident scenarios.
3. Without the restriction to planar arrays, stacking to any height becomes a normal condition. Unacceptably high k_{eff} values (> 0.95) can result from:
 - a) Excessive stacking (allowed if this limit is removed) and a single accident (volume, mass or sprinkler violation) - e.g., an infinite array of lead shielded cans combining a mass violation (100 g Pu) and 20 high stacking produced a calculated multiplication factor of $1.041 \pm .005$. (For array sizes $25 \times 24 \times 20$ and $100 \times 100 \times 10$, k_{eff} values were 0.588 ± 0.003 and 0.597 ± 0.003 , respectively.)
 - b) Adding stacking to other required accident combinations - e.g., a volume violation (200 ml Pu solution) and sprinkler combination plus stacking 3 high produced a k_{eff} of $0.964 \pm .003$.
4. Under normal conditions, the effect of having an array of one-gallon cans next to a slab of Pu solution ($k_{eff} \approx 0.90$) is statistically insignificant. In all cases evaluated with unrealistically large (25×50) arrays of cans adjacent the plutonium slab, using the required combinations of two additional events resulted in k_{eff} values ≤ 0.95 . Based on the calculated results, no spacing requirements are needed.
5. The transport limit (40 cans per vehicle) is based on handbook data. Six liters, the contents of 60 cans (100 ml each), is the minimum critical

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 12 of 116

volume for aqueous Pu systems. 80% of 60 gives a limit of 48 cans, which was rounded down to 40. The contents of 40 cans for solutions (Ref.3) and 60 cans for metal (Case 1, Table 8) was demonstrated to be safe. A limit of 40 cans was selected for all contents for consistency.

6. Beryllium was excluded from the analysis since it is never expected to be placed in one gallon cans containing Pu or U.

6.2 Technical Bases for ESFs

There are no engineered safety features which pertain to one gallon cans.

7. CONCLUSIONS

Based on the assumptions in Section 4, the 50 gram per can limit on plutonium and uranium metal (dry and in slurries) is safe for the one-gallon cans.

A summary of accident case (stacking/mass violation combination) results for plutonium solution calculations is given in Table 1.

TABLE 1. SUMMARY OF RESULTS FOR PU SOLUTION (1000 GRAMS/LITER)

<u>k-effective</u>	<u>Volume evaluated</u>
1.0	270 ml
0.95	230 ml
0.90	200 ml

Based on the results shown in the table, a 115 ml/can (one-half of 230 ml) limit is acceptable when double batching is considered. However, because of human factor considerations (100 ml is easier for an operator to remember than 115 ml), the recommended operating limit is 100 ml/can at concentrations no more than 1000 g/l Pu (mass, not volume, limits are applied to slurries). A stacking restriction (planar arrays only) is required for this limit.

The most restrictive limits are imposed on plutonium solutions. Cans containing the plutonium solution require a prohibition on stacking and a transport limit of 40 cans per vehicle. Even though the stacking restriction and the transport limit are less restrictive for metal, to avoid confusion, it is recommended that these limits be applied to all one-gallon containers, regardless of contents.

Spacing restrictions from other fissile material are not required. There is no limit on the number of one-gallon cans in storage arrays.

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 14 of 116

Calculated typical case k_{eff} values were about 0.05 for Pu solution (10 g Pu/l), and around 0.10 to 0.20 for metal and slurry systems (see Section 2). All of these values are so far below code verification benchmark values that their validity is questionable. However, values are included here to comply with requirements and because they provide some indication that there is a considerable margin of safety between typical operating conditions and the accident conditions that were required for the evaluation. Limiting normal case values of about 0.40 to 0.60 (see Section 2) also indicate that criticality safety margins are appreciable.

The vehicle accident model produced the highest k_{eff} , a weighted average of 0.928 ± 0.002 , which is well below the RFP acceptance criteria of 0.95. In this model 60 Pu metal spheres were evaluated close-packed and fully water reflected. A substantial margin of safety still exists in the event of this worst case accident scenario. Additional safety margin is provided because the transport limit is set at 40 cans, optimal reflection is unlikely, and credit was not taken for inner containment.

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 15 of 116

8. CHECKLISTS

8.1 Double Contingency Analysis

Double Contingency Analysis Form

<u>Failure/Accident Scenario</u>	<u>Contingencies (Unlikely Events)</u>	
	<u>No.</u>	<u>Description</u>
Critical assembly of RFP one-gallon containers in storage	1 ^{a,b}	An unrealistically large of array of cans accumulated in storage.
	2 ^c	Mass limit exceeded in most containers by factor of 2 (metal and slurry) or Volume limit exceeded by factor of 2 (solution)
	3 ^c	Violation of stacking restriction
Critical assembly of RFP one-gallon containers as a result of physical damage to cans during handling or transport	1 ^b	Physical damage to containers
	2 ^c	Violation of mass limit (metal or slurry) or violation of volume limit (solution)
	3 ^c	Violation of transport limit (number of containers)

- a. Most cases were evaluated as infinite arrays. Limiting array size to 200,000 cans reduced results by 7.2%; limiting to 12,000 cans reduced results by 43%. The number of cans in an array 25 x 24 x 20 (12,000) is still so large that a can limit is not required.
- b. Needs no combination.
- c. According to RFP requirements this contingency needs to be combined.

Operation Title: Handling, Shipping and Storage of
RFP One-Gallon Containers
Building: All
Area: Intraplant

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 16 of 116

8.2 Normal Condition Analysis for Shipping Container Operations

I. Purpose

The purpose of this analysis is to ensure that all normal conditions which could affect criticality safety of onsite shipping container operations are considered and documented.

NOTE: Special care must be exercised for any onsite shipping container that may have dual utility as an onsite and offsite container. An offsite shipping container should not have onsite limits exceeding offsite shipment limits, except in rare, well justified, and specifically documented circumstances.

II. Standard Considerations

- A. Reflection due to a human body, walls, floors, etc., on the outside of the containers.

Control Needed: Discussion of condition(s) to be considered:

Conservative concrete reflection (30 cm on top, 60 cm on the bottom) was assumed on all infinite planar arrays of cans. Thick concrete reflection envelops other potential reflector conditions due to a human body, etc.

Covered by evaluation case(s): All

NORMAL CONDITION ANALYSIS
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Standard Considerations (cont'd)

- B. Use worst case (most reactive) fissile material quantity, densities, geometry, and matrices. NOTE: 1) Be careful about assuming fissile material is centered in the container, unless physical spacers are used to center the material. 2) The full range of allowed fissile material densities must be considered. 3) Gram estimators and counters may be in error so consider an appropriate amount of fissile material as normal conditions. Be sure and consider the appropriate drum count and estimate errors.

Has the fissile material been placed in the most reactive geometry possible for both single unit and interaction analyses? NOTE: Most reactive geometry for a single unit and for an array may not be the same. Most reactive geometry for arrays may depend strongly on specific units in the array and may vary from case to case.

Control
Needed:
#

Discussion of condition(s) to be considered:

Weapons grade plutonium (95 wt.% Pu-239 and 5 wt.% Pu-240) was assumed for calculations. This adequately approximates actual material present during operations. 100 wt.% U-233 metal envelops all uranium isotopes. Liquid systems were assumed to be 8 Vol.% polyethylene, 92 Vol.% water (Ref. 2). This value was based on experimental results for hand packing polyethylene. Water is conservatively assumed to occupy the 92% of void space. Solutions were modeled as 1000 g/l and slurries (sludges) as 5000 g/l.

Offset spherical geometries were evaluated for dry systems. Solution systems were evaluated with the spherical volume both centered and offset inside the one-gallon cans.

For the arrays of one-gallon containers considered in this evaluation, cylindrical geometries are slightly more reactive than spherical geometries. Combinations of spherical geometries and cylindrical shells would be even more reactive. Spherical geometry

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 18 of 116

conservatively envelops actual possible geometries considering the types of material placed in one-gallon cans and was assumed in most calculations as a modeling simplification. Selected limiting cases were reported with cylindrical geometries to demonstrate that key calculated values remain below 0.95 for accident conditions and 0.90 for normal operating conditions (See Section 12, Table 8 Cases 3-10).

Beryllium was excluded from the analysis. It is not placed in one gallon cans under normal conditions.

Covered by evaluation case(s): A11

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 19 of 116

NORMAL CONDITION ANALYSIS
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Standard Considerations (cont'd)

- C. True container conditions must be considered (e.g., wall thickness, dimensions and tolerances, internal package components such as shielding or celetex, walls, floors, ceilings, etc.). The most conservative dimensions are to be used (thickness, height, radius); these may vary depending on contents. NOTE: A range of package component densities should be evaluated since density of purchased products may vary.

Control
Needed:

#

Discussion of condition(s) to be considered:

True container dimensions are given in the assumptions for container representation in Section 4. Variations of 2% in the container dimensions had no statistically significant impact on calculated results.

Covered by evaluation case(s): All

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 20 of 116

NORMAL CONDITION ANALYSIS
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Standard Considerations (cont'd)

- D. Can long-term storage change the form, density, shape, etc., of the fissile material? Will the density change due to thermal conditions (heating and/or cooling)? Will a sludge form due to a change in pH, or salting/sludge result from long-term loss of moderators due to evaluations, leaking, etc.?

Control
Needed:

Discussion of condition(s) to be considered:

#

The form, density and shape of the fissile material are not expected to change with long-term storage; however, near optimum geometries and theoretical metal densities were evaluated to envelop such changes.

Covered by evaluation case(s): All

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 21 of 116

NORMAL CONDITION ANALYSIS
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Standing Considerations (cont'd)

- E. Has interaction with all other fissile material been considered (adjacent gloveboxes, transfer carts, drums, handcarry materials, etc.)? Most reactive interaction conditions must be considered.

Control
Needed:

Discussion of condition(s) to be considered:

Since all systems at RFP should normally have calculated k_{eff} values of 0.90 or less, interaction with a slab having a $k_{eff} \approx 0.90$ was evaluated.

A separation limit is not required.

Covered by evaluation case(s): Section 12, Table 7

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 22 of 116

NORMAL CONDITION ANALYSIS
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Standard Considerations (cont'd)

- F. Make sure the limits for the containers are consistent with further operations. For example, if you allow 4000 grams to be in one container of one shipping container, you must make sure there are limits for the loading and unloading of 4000 grams in one container. Consider all locations where the limits allow use of the container.

Control
Needed:
#

Discussion of condition(s) to be considered:

The 50 g limit on dry fissile material and slurries, and the 100 ml limit on Pu solutions inside RFP one-gallon containers should not present a criticality problem at any location on plant-site where fissile material is allowed.

If one-gallon containers are to be shipped to areas where stricter limits (e.g. Building 559) are imposed for reasons other than criticality safety (e.g. Safeguards and Security Limits) compliance with the stricter limits is required.

Covered by evaluation case(s): Section 12, Tables 2, 4 and 9

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 23 of 116

NORMAL CONDITION ANALYSIS
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Standard Considerations (cont'd)

- G. The arrangement of containers being evaluated must be combined with the most reactive combination of shipping containers currently approved. This may not be one type of container and contents. Intermixed arrays should be considered. Varied contents and/or varied shipping containers should be considered.

Control
Needed:

Discussion of condition(s) to be considered:

Near optimum configurations were evaluated. Intermixing of one-gallon containers with arrays of other type containers does not increase the reactivity of the array since:

1. The reactivity of a realistic number of one-gallon containers is insignificant (Reference 1, 5.2, Table 2), and
2. Large arrays (25 x 50) of one-gallon containers next to systems that have calculated k_{eff} values of 0.90 (a value that is much greater than the k_{eff} values for realistically sized arrays of other containers) resulted in insignificant changes in calculated k_{eff} values.
3. A stacked infinite array of containers alternating metal and solution as contents resulted in a calculated k_{eff} of 0.716 ± 0.003 .

Covered by evaluation case(s): Section 12, Table 7

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 24 of 116

NORMAL CONDITION ANALYSIS
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Standard Considerations (cont'd)

- H. The arrangement must consider the ability to hexagonally pack the array of containers.

Control
Needed:

Discussion of condition(s) to be considered:

Hexagonally-packed arrays were evaluated.

Covered by evaluation case(s): All _____

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 25 of 116

NORMAL CONDITION ANALYSIS
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Standard Considerations (cont'd)

- I. The array must be evaluated with optimum moderation between the containers. It is possible to have plastics between the containers as a normal condition. If any moderation restrictions must be required, they should be evaluated at varying densities (e.g., all plastic in one corner up to homogeneously distributed). Any restrictions must be specified in the limits. NOTE: The array must be evaluated with and without shielding (lead and plastic) allowed by General Comments and specific building shielding limits considering the full thickness and density ranges of allowed shielding.

Control
Needed:
#

Discussion of condition(s) to be considered:

All degrees of moderation were evaluated. Conservative concrete reflection (30 cm on the top and sides, 60 cm on the bottom) was assumed.

A 92 vol.% water, 8 vol.% polyethylene composition was used as a moderator. This accounts for the maximum amount of polyethylene that can be hand packed between or inside of the one-gallon containers (Reference 2).

Lead shielding was also evaluated (see III, A.).

Covered by evaluation case(s): All

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 26 of 116

NORMAL CONDITION ANALYSIS
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Standard Considerations (cont'd)

- J. Other items to be considered. Attach a draft copy of the nuclear materials safety limit to ensure all normal conditions have been considered.

Control
Needed:
_____ Discussion of condition(s) to be considered:

See Section 13.

Covered by evaluation case(s): All

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 27 of 116

NORMAL CONDITION ANALYSIS
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

III. General Comments

- A. Has the 1/2" lead and 1/8" neutron shielding been added to the containers? (Reference Section II, Item I)

Control
Needed:

Discussion of failure(s) to be considered:

In all plutonium cases evaluated, additional polyethylene moderator inside the container tended to isolate adjacent containers and reduce the k_{eff} of the array. Uranium metal showed slight increases in the multiplication factor with low density moderator between the cans (See Table 9). Limits were based on the most reactive cases.

The addition of 1/2" lead shielding increased k_{eff} 's slightly. The k_{eff} 's of infinite arrays of cans containing metal or slurry, stacked 20 high and double-batched to 100 g per can (limiting accident case), were slightly greater than 1.0. Stacks up to 15 high containing U metal remained below 0.95 k-effective (0.930 ± 0.004) with or without the addition of this shielding (See Table 10). Double-batched cans with lead shielding stacked three high resulted in k_{eff} 's less than 0.95 for all materials of concern. Since the stacking prohibition is applied to one gallon cans regardless of contents, no criticality safety problem is anticipated.

Covered by evaluation case(s): Section 12; Table 2, Cases 17 and 19; Table 5
Case 17; and Table 10

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 28 of 116

NORMAL CONDITION ANALYSIS
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

III. General Comments (cont'd)

- B. All oxide or compound evaluations must have 10 wt.% H₂O added as a normal condition.

Control
Needed:

Liquid systems were evaluated with 8 Vol.% polyethylene - 92 Vol.% water (Ref. 2).

Oxides and compounds are conservatively enveloped by metal.
Calculations indicate that the k_{eff} decreases from 0.767 ± 0.002 for metal to 0.720 ± 0.002 for an equal mass of Pu oxide with 10 wt.% H₂O.

Covered by evaluation case(s): All

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 29 of 116

NORMAL CONDITION ANALYSIS
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

III. General Comments (cont'd)

- C. Other building specific General Comments. NOTE: Appropriate General Comments considered and discussed below.

Control Discussion of failure(s) to be considered:
Needed:

None

Covered by evaluation case(s): N/A

Operation Title: Handling, Shipping and Storage of
RFP One-Gallon Containers
Building: All
Area: Intraplant

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 30 of 116

8.3 Failure Analysis Checksheet for Shipping Container Operations

I. Purpose

The purpose of this analysis is to ensure that all possible failures which could affect criticality safety of shipping container operations are considered and documented.

II. Operator Error

A. Multiple Batching

Can the fissile material be multiple batched? If so, by how much?
CAUTION: If an operator over batches one container, it is likely he or she will over batch more than one, unless there are specific controls to prevent such multiple batching.

Control
Needed:

Discussion of failure(s) to be considered:

A single container could be overbatched by a considerable factor. Large arrays (50 x 25 x 3) of cans with a single heavily loaded can [500 g metal (factor of 10 times the limit) or 4224 ml solution (full can)] were evaluated. The highest k_{eff} determined by the calculations was 0.580 ± 0.003 for the Pu solution.

Uniform double-batching (overbatching by a factor of 2) of all containers was evaluated. Overbatching by more than a factor of 2 is not credible due to stringent safeguards and security measures in the RFP material handling procedures. It is implausible that a sufficient amount of material would be accessible to overbatch a large array of cans by more than a small amount in each can. Additional personnel would become involved in any transfer procedures for filled containers, and accountability requirements make it extremely unlikely that serious overbatching of large numbers of cans would go unnoticed long enough to cause a criticality safety concern.

Covered by evaluation case(s): Section 12, Tables 2.4, and 9

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 31 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Operator Error (cont'd)

B. Spacing Violation of Handcarry Limits

Can one or more containers or items be brought next to other equipment, such as tanks? If so, how many? CAUTION: If an operator violates one spacing, they could violate all spacing restrictions.

Control
Needed:

Discussion of failure(s) to be considered:

It was shown that separation limits are not required. (See Section 10).

Covered by evaluation case(s): Section 12, Table 7

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 32 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Operator Error (cont'd)

- C. What if the operation is left unattended? What effect would long-term neglect have on the operation? For example, leaving containers open under liquid lines and a water leak filling the containers could lead to a criticality safety concern.

Control
Needed:

Discussion of failure(s) to be considered:

Near optimal conditions have been considered. Flooding increased the neutron multiplication factor in some cases and this was considered in establishing the limits.

Covered by evaluation case(s): Section 12; Table 2 Case 10; Table 5, Cases 1, 7, and 14-16

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 33 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Operator Error (cont'd)

- D. Transfer Errors: Can the shipping container be transferred to an area which would be unsafe, or where area limits will be violated (e.g., tank farms, vaults, etc.)?

Control
Needed:

Discussion of failure(s) to be considered:

RFP one-gallon containers could probably be shipped to areas where area limits would be violated; however, interaction with other fissile material has been conservatively evaluated and it was shown that separation limits are not required.

Covered by evaluation case(s): Section 12, Table 7

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 34 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Operator Error (cont'd)

- E. What if an operator adds additional shielding around the containers. For example, poly walls might be stacked around one or more containers to reduce exposure.

Control Needed: Discussion of failure(s) to be considered:

Thick concrete reflection on top (30 cm) and bottom (60 cm) of the array envelops other potential normal and off-normal reflector conditions external to the array of one-gallon containers. Finite arrays of cans were reflected by 30 cm of concrete on the sides also.

All degrees of polyethylene and water moderation between and inside cans were evaluated.

Covered by evaluation case(s): All _____

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 35 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Operator Error (cont'd)

- F. Consider stacking accident where more containers are stacked than allowed (even if no stacking is allowed).

Control
Needed:

Stacking at least 3 high was considered and limits were established based on a violation of stacking restrictions. Stacking 3 high is considered adequate since limits require a restriction to planar arrays only (no stacking). Physical size of the cans and the instability of stacks makes arrays more than 3 high unrealistic.

Metal cases were modeled as an array stacked 20 high. This is considered unrealistic, but eliminates concern over stacking limits and the need to consider stacking accidents for metal.

Covered by evaluation case(s): Section 12, Tables 2, 4, and 9

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 36 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Operator Error (cont'd)

- G. Can this container be mistaken for another and loaded with an unacceptable amount of material approved for the shipping container that the operator thought he/she was filling (e.g., 35 gallon versus 55 gallon)?

Control
Needed:

Discussion of failure(s) to be considered:

#

It is unlikely that RFP one-gallon containers could be mistaken for another type of container. However, the cans were shown to remain safely subcritical in the event that all containers are uniformly double-batched.

Covered by evaluation case(s): Section 12, Table 2, 4, and 9

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 37 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Operator Error (cont'd)

- H. Can mislabeling the shipping container lead to criticality safety concerns (e.g., supercompactor, two-high stacking, etc.)?

Control
Needed:

Discussion of failure(s) to be considered:

The most reactive configuration under accident conditions would be for the contents of all cans to be combined in one location. The minimum critical volume for spherical aqueous systems of Pu-239 is greater than 6 liters. With 100 ml per can, the minimum number of cans that can combine to form a critical volume is 60. Cans being shipped to the supercompactor would be limited to 40 by the transport limit, so there would not be sufficient material present for criticality.

For dry systems, the contents of 60 double-batched cans, modeled as 100 gram spheres (close-packed and water reflected), were shown to be have a k_{eff} below 0.95 (0.928 ± 0.002 for Pu metal. [U-233 metal was less reactive (0.842 ± 0.005) and is not reported in the table.] Therefore, inadvertently directing the cans to the supercompactor does not result in a criticality concern.

Stacking at least three high was evaluated.

Covered by evaluation case(s): Section 12, Table 8, Case 1

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 38 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Operator Error (cont'd)

- I. Truck wreck and pileup must be considered. This should include any possible damage to containers or packing material.

Control
Needed:

The most reactive configuration under accident conditions would be for the contents of all cans to be combined in one location. The minimum critical volume for spherical aqueous systems of Pu-239 is greater than 6 liters (Ref. 3). With 100 ml per can, the minimum number of cans that can combine to form a critical volume is 60.

For dry systems, the contents of 60 double-batched cans (100 g each), in a close-packed array of uncontained, fully water-reflected spheres were shown to have a k_{eff} below 0.95 (0.928 ± 0.002 for Pu metal. [U-233 metal was less reactive (0.842 ± 0.005) and is not reported in the table.]

Conservatism in applying the 80% of critical rule (Reference 4) ($60 \times .8 = 48$ cans, and rounding down to a round number) suggests that the number of cans be limited to 40 during transportation.

Covered by evaluation case(s): Section 12, Table 8, Case 1

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 39 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Operator Error (cont'd)

- J. Has the use of improper inner containers been considered (e.g., loss of spacing, changing in geometry, inner container restrictions, etc.)?

Control
Needed:

Discussion of failure(s) to be considered:

This analysis is not dependent on inner containment. Worst case configurations inside the containers were assumed. These configurations envelop conditions where inner containers are present.

Covered by evaluation case(s): All

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 40 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

II. Operator Error (cont'd)

K. Other operator errors.

Control Discussion of failure(s) to be considered:
Needed:

None

Covered by evaluation case(s): N/A

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 41 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

III. Equipment Failures

- A. Can various thermal conditions affect criticality safety? For example, heating and/or cooling the container contents may change concentration to an unsafe level.

Control
Needed:

Discussion of failure(s) to be considered:

No, optimal or near optimal conditions were assumed.

Covered by evaluation case(s): N/A

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 42 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

III. Equipment Failures (cont'd)

B. Be sure and consider one or more containers rupturing or leaking.

Control
Needed:

Discussion of failure(s) to be considered:

Ruptured containers would result in a less reactive geometry if the contents spreads out over a larger volume. With the mass, volume, and number of containers (40) allowable during transport, accumulation into near optimal geometry is still safely subcritical.

Puncturing large numbers of cans during storage is considered very unlikely. The additional improbability of having a large volume of material (the contents of more than 40 cans) accumulate in an optimally moderated and reflected geometry makes a critical scenario from this type of accident incredible.

Covered by evaluation case(s): Section 12, Table 8 and Handbook data

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 43 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

III. Equipment Failures (cont'd)

C. Standard failure of the counting equipment.

Control
Needed: Discussion of failure(s) to be considered:

Uniform double-batching (overbatching by a factor of 2) of all containers was evaluated. Overbatching by more than a factor of 2 is not credible due to stringent safeguards and security measures in the RFP material handling procedures. It is implausible that a sufficient amount of material would be present to overbatch a large array of cans by more than a small amount per can. (See page 30.)

Covered by evaluation case(s): Section 12, Tables 2 and 4

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 44 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

III. Equipment Failures (cont'd)

- D. Can the dimensions of the container change due to change in pressure (positive or negative) or damage during transport?

Control Needed: Discussion of failure(s) to be considered:
#

The most reactive configuration under accident conditions (damage during transport) would be for the contents of all cans to be combined in one location. The minimum critical volume for spherical aqueous systems of Pu-239 is greater than 6 liters. With 100 ml per can, the minimum number of cans that can combine to form a critical volume is 60. Spreading out the contents would lower the k_{eff} .

For dry systems, the close-packed contents of 60 double-batched cans (100 g each) were shown to have a k_{eff} below 0.95 (0.928 ± 0.002 for Pu metal, 0.842 ± 0.005 for U-233 metal).

Since transport of one-gallon cans is limited to 40, a change in can dimensions will not result in the accumulation of sufficient material (nor would the material be optimally moderated and reflected) to produce excessively high k_{eff} values.

During storage there is no known mechanism that could overpressure and breach a large number of cans. Therefore, storage areas need not be restricted to a limited number of containers.

Covered by evaluation case(s): Section 12, Table 8, Case 1

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 45 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

III. Equipment Failures (cont'd)

E. Other equipment failures.

Control
Needed: Discussion of failure(s) to be considered:

None

Covered by evaluation case(s): N/A _____

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 46 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

IV. Fire Failures

A. Sprinkler activation inside and outside of the containers.

Control Discussion of failure(s) to be considered:

Needed:
#

All degrees of water moderation were evaluated.

Covered by evaluation case(s): Section 12; Table 2, Cases 10-13.
Table 5, Cases 1-16

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 47 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

IV. Fire Failures (cont'd)

- B. Is full flooding possible? CAUTION: Doorways and dams may not be able to handle volumes of water that might be added by a number of firemen using hoses; therefore, pits and basements must be considered flooded.

Control
Needed:

Discussion of failure(s) to be considered:

#

Full flooding is unlikely; however, all degrees of water moderation and full concrete reflection were evaluated.

Covered by evaluation case(s): Section 12: Table 2, Cases 10-13
Table 5, Cases 1-16

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 48 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

IV. Fire Failures (cont'd)

- C. Can a fire result in a loss of moderation, structural, or poison materials? For example, internal packaging materials.

Control
Needed:

Discussion of failure(s) to be considered:

Changes resulting from fire damage are enveloped by the near optimal conditions assumed.

Covered by evaluation case(s): N/A

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 49 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

IV. Fire Failures (cont'd)

- D. Can a fire result in warpage of the container which could result in a criticality safety problem?

Control Needed: Discussion of failure(s) to be considered:

#

Damage to containers may occur, but would not result in a criticality safety problem because optimal configurations were assumed and were shown to be safely subcritical ($k_{eff} < 0.95$).

Covered by evaluation case(s): N/A

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 50 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

IV. Fire Failures (cont'd)

- E. Can the solution be boiled down or the material geometry change to an unsafe concentration or configuration?

Control
Needed:

Discussion of failure(s) to be considered:

Spherical geometry was assumed. More realistic geometries that could result from melting, etc. are less reactive. If liquid evaporates from solution systems, the conditions will approach those evaluated for the metal cases.

Covered by evaluation case(s): All _____

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 51 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

IV. Fire Failures (cont'd)

- F. Can fire change the composition of fissile material approved for the limit (e.g., metal shapes to piled oxide, dissolution into heated firewater, etc.)?

Control
Needed:

#

Discussion of failure(s) to be considered:

Yes, but those changes were enveloped by the evaluation (i.e., oxides were enveloped by metal and slurries).

Covered by evaluation case(s): All

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 52 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

V. Earthquakes

- A. Consider the breakage of all supports or a worst case condition of only a certain number of supports breaking. NOTE: Redesign may be necessary such that supports meet the design basis earthquake (DBE) event.

Control
Needed:
#

Discussion of failure(s) to be considered:

Enveloped by the evaluation (tight-fitting concrete reflector).

Covered by evaluation case(s): N/A

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 53 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

V. Earthquake (cont'd)

B. Pileup of containers or loss of spacing due to DBE.

Control Discussion of failure(s) to be considered:

Needed:

Close-packed hexagonal geometry, stacking at least 3-high, and tight fitting concrete reflection were evaluated.

Covered by evaluation case(s): Section 12, Tables 2 and 4

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 54 of 116

FAILURE ANALYSIS CHECKSHEET
FOR SHIPPING CONTAINER OPERATIONS (cont'd)

VI. Other Accident Conditions to be Considered

None

Covered by evaluation case(s): N/A

Operation Title: Handling, Shipping and Storage of
RFP One-Gallon Containers
Building: All
Area: Intraplant

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 55 of 116

8.4 Evaluation Needs Analysis

I. Purpose

The purpose of this analysis is to prepare for the calculations by defining the normal and accident conditions to be evaluated. Once defined, each of these cases should be ordered from "Expected Most Reactive" to "Expected Least Reactive" and the resulting list of cases examined to eliminate any superfluous calculations.

II. Normal Case Conditions

Normal operating conditions for storage of RFP one-gallon shipping containers were modeled as infinite arrays of containers with 50 g "dry" plutonium or uranium metal, 50 g of plutonium or uranium slurry (sludge), or 100 ml plutonium solution per container. The array is reflected on top by 30 cm of concrete and on bottom by 60 cm of concrete. Calculated k_{eff} values of 0.534 ± 0.002 , 0.629 ± 0.003 , and 0.392 ± 0.002 resulted for normal condition plutonium "dry" metal, Pu slurry, and Pu solution systems, respectively. The U-233 normal case produced a calculated k_{eff} of 0.572 ± 0.004 for metal and 0.458 ± 0.003 for slurry. All of these values are much less than 0.90.

EVALUATIONS NEEDS ANALYSIS

III. Accident Case Conditions

1. Mass or Volume Limit Violation (Factor of 2)
2. Flooding (need not be combined)
3. Sprinkler Violation
4. Stacking Violation
5. Spacing Violation
6. Physical Damage to Containers (breach or compaction due to vehicle accident, earthquakes, etc., need not be combined)

<u>Accident or Event</u>	<u>Case Number(s) or Report Section(s)</u>
1 and 2 ^a	Case 10 of Table 2; Cases 1, 7, 14, 15, and 16 of Table 5, Cases 9 and 10 of Table 9
1 and 3	Cases 10-13 of Table 2, Cases 1-6 of Table 5, Cases 11-15 of Table 9
1 and 4	Cases 1-15 and 17-19 of Table 2, Cases 1-7 of Table 4, Case 17 of Table 5, Cases 1-15, 17 and 18 of Table 9
1 and 5	Case 3, Table 7
1 and 6	N/A, combined events do not apply to damaged container accidents
2 and 3	N/A
2 and 4	N/A
2 and 5	N/A
2 and 6	N/A, potential common mode failure
3 and 4	Cases 10-13 of Table 2, Cases 7-12 of Table 5, Cases 10-15 of Table 9
3 and 5	Case 8, Table 7
3 and 6	Potential common mode failure; enveloped by events 2 and 6

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 57 of 116

Accident Case Conditions, continued.

<u>Accident or Event</u>	<u>Case Number(s) or Report Section (s)</u>
--------------------------	---

4 and 5	Case 4, Table 7
4 and 6	N/A, potential common mode failure
5 and 6	N/A

-
- a. This combination was not required; however, since it was conveniently evaluated and shown safe, results are included in the report.
-

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 58 of 116

9. REFERENCES

1. J. B. Briggs, Criticality Safety Evaluation of Rocky Flats Plant One-Gallon Shipping Containers, EGG-NE-9518, February 1991
2. J. Painter, evaluation for DOT SP-5948/ATMX-600, March 1986.
3. J. T. Thomas, Ed. Nuclear Safety Guide, TID-7016, Rev. 2, June 1978.
4. G. L. Tweed, Nuclear Safety Department Procedure, Criticality Safety Evaluation, 3-NSPPM-5B-01, Rev. 4, E. G. & G, Rocky Flats, October 21, 1991.
5. L. M. Petrie and N. F. Landers, KENO-V.a - An Improved Monte Carlo Criticality Program with Supergrouping, NUREG/CR-0200, Oak Ridge National Laboratory, December 1984.

10. DISCUSSION

10.1 Codes, Cross Sections and Validations

A discussion of benchmark calculations for the KENO-V.a code is included in Section 4 of Reference 1. These calculations were performed on an IBM RISC 6000 workstation, therefore, the benchmark calculations were repeated for system verification. Since all metal systems are included in this report, but were not included in Reference 1, plutonium (JEZEBEL) and U-233 (JEZ-23) metal critical experiments, were also evaluated. The following results were obtained:

<u>Benchmark ID</u>	<u>Description</u>	<u>H/X</u>	<u>KENO Calculated $k \pm \sigma$</u>
PNL-1	Bare sphere	700	1.004 ± 0.003
PNL-2	Bare sphere	131	1.012 ± 0.004
PNL-3	Bare sphere	1204	0.996 ± 0.003
PNL-4	Bare sphere	911	1.007 ± 0.003
PNL-5	Bare sphere	578	1.003 ± 0.003
PNL-7	Reflected sphere	980	1.002 ± 0.003
JEZEBEL	Bare sphere	0	1.002 ± 0.004
JEZ-23	Bare sphere	0	1.002 ± 0.004

Metal, slurry, and solution systems were evaluated separately. The three material types are discussed in the remainder of this section.

10.2 Dry Uranium and Plutonium Metal

Dimensions and materials for the one-gallon cans are identical to those used in the initial evaluation (page 2 of Reference 1) and are given in Section 3 of this report. Densities of 19.84 and 18.70 grams/cc were used to calculate the volume of plutonium and uranium metal, respectively. Atom densities for plutonium metal were calculated for 95 wt.% Pu-239 and 5 wt.% Pu-240. Uranium was evaluated as 100 wt.% U-233.

In order to establish a 50 gram per can limit, arrays of containers were modeled double-batched to 100 grams per can. Various degrees of moderation/reflection inside and between containers were used; however, moderator material was not intermixed with the plutonium or uranium (except for slurries, Section 10.4). KENO-V.a results indicated that arrays of containers containing dry plutonium metal are more reactive without polyethylene or water moderation/reflection inside and between containers. The highest calculated k_{eff} for Pu was 0.767 ± 0.004 . The results are tabulated in Table 2 and shown graphically in Figure 2. For U-233 the highest k_{eff} was 0.827 ± 0.002 (Case 14 of Table 9) with 0.05 water volume fraction between cans.

The spherical fuel was offset axially and radially to the edge of the can. Offsetting the fuel results in the fuel spheres being clustered in groups. Accordingly, they are closer to each other than they would be if centered in the container (Figure 1). Preliminary calculations confirmed that offset fuel configurations were more reactive than those with centered fuel. In the two cases evaluated using an alternative unit cell, it was shown that the change had no impact on the k_{eff} . (Table 3, 1a and 13a). It is recognized that other geometries (i.e., shell type geometries) may be more reactive when represented in arrays of containers; however, the offset spherical geometry used is considered sufficiently conservative for the type of materials that will be placed inside one-gallon containers (See page 17 and Section 12, Table 8).

----- alternate configuration

H048-MES-0891-02

Figure 1. Unit cell used for representing arrays of cans with offset fuel.

Arrays of cans containing uranium and plutonium metal were run with infinite mirror reflection in the x and y planes and stacked 20 high (12.8 ft). Stacking is not the normal operating condition but it was initially expected that this model would eliminate the need to evaluate stacking as an accident case for metal only. However, twenty high stacking was a limiting factor in cases using cans containing lead shielding. Stacking 20 high is considered overly conservative, but because lead shielding increases reactivity, the stacking prohibition must apply to all one-gallon cans regardless of contents even though lower stacks, up to 15 high, were shown to be acceptable (Table 10).

Accident cases for the "dry" metal included overbatching, flooding, sprinkler and physical damage to containers. The first three accidents are reported in Cases 1 through 13 of Tables 2 and 3, and in Table 9. A sprinkler accident case for Pu with a water volume fraction of 0.1 between cans (Case 13, Table 2) produced the highest k_{eff} (0.750 ± 0.004) for "flooded" conditions. The highest value for U-233 was 0.827 ± 0.002 as reported earlier in this section.

The physical damage accident (vehicle accident, earthquake, breach of container, etc.) was modeled using a close packed "pile" of 100 gram spheres of plutonium metal with effectively infinite water reflection. Sixty of the 100 gram spheres resulted in a k_{eff} just below 0.95 (Table 8, Case 1). Modeling 125 50 gram spheres and separating the spheres away from the close packed arrangement lowered the k_{eff} (Cases 2 and 3 of Table 8). U-233 was less reactive than Pu in this model.

The possibility of removing administrative spacing requirements (from other fissile material) was also evaluated. This was accomplished by representing a fully water reflected slab of plutonium solution ($k_{eff}=0.891 \pm 0.004$, Ref. 1, p. 31) next to a planar array of double-batched cans (see Case 1 of Table 7). The resulting k_{eff} (0.890 ± 0.002) indicates that the arrangement has minimal impact on the k_{eff} of the system. An array of single-batched cans, stacked 3 high, next to the slab resulted in a similar value for k_{eff} (0.884 ± 0.002 , Case 2 of Table 7). Double-batched cans

stacked three high next to the slab gave a calculated k_{eff} of 0.880 ± 0.002 (Case 5 of Table 7). The difference between the k_{eff} of the slab itself and a large array of cans next to the slab was statistically insignificant at a 95% confidence level in all but two of the cases evaluated. In these two instances the calculated neutron multiplication factor was lower than for the slab alone. This is due to a portion of the infinite water reflector on the slab being replaced by the array of cans and creating a leakage path. This analysis was performed to determine the safety of removing the requirements for 12 in. spacing between an array of one-gallon cans and other fissile material. Similar effects were seen with U-233 resulting in a k_{eff} of 0.879 ± 0.002 (Case 7 of Table 7). Sprinkler flooding increased k_{eff} values slightly, the worst case was for solutions and is discussed in Section 10.3.

The cans were close-packed in triangular pitch in most arrays. Arrays of cans with both centered and offset spherical Pu fuel were evaluated in a rectangular geometry for comparison with the triangular pitched close-packed arrays. In all cases the k_{eff} decreased by greater than three standard deviations (~6%). This confirms the assumption that triangular pitched arrays provide the most reactive arrangement (Table 8, Cases 4, 5, 6, and 7).

Normal operating and limiting accident cases were each repeated three times using different neutron starting distributions. These results are listed in Table 3 of Section 12 and conform to RFP acceptance criteria.

10.3 Plutonium Solution

For plutonium solutions, a homogeneous mixture composed of 92 vol.% water and 8 vol.% polyethylene with a plutonium (95 wt.% Pu-239, 5 wt.% Pu-240) concentration of 1000 grams/liter was assumed. Most samples are less than 1 grams/liter. Plutonium is only soluble in aqueous solutions up to about 600 grams/liter and solutions above 1000 grams/liter are unrealistic. Most samples are suspensions in oil, in which Pu would be less soluble. If solids are not visible, concentrations are expected to be much less than the assumed 1000 grams/liter. If solids are visible then mass limits will be applied as discussed in Section 10.4. Therefore, the 1000 grams/liter assumption conservatively envelops any credible solution concentrations. The volume limits for the 1000 grams/liter plutonium solution were determined by varying the volume of fuel inside the one-gallon can to generate a range of k_{eff} values from 0.90 to 1.0.

The plutonium solution was modeled in spherical geometry (see page 17 of Section 9.2, Section 10.2, and Table 8 of Section 12) and, in most cases, the spheres were offset in the can as described for the plutonium metal calculations. In some cases the spherical fuel was analyzed centered inside the can for convenience, but limiting cases were compared with results from offset fuel to assure that the more reactive configuration was used. Planar arrays were designed with centered fuel. Conservative concrete reflectors (30 cm on the top and 60 cm on the bottom) were used for the arrays of containers. Tables 4 and 5 in Section 12 list the KENO-V.a results for the solution cases. A volume of 230 ml per can in a stacked (3 high) infinite array produced a k_{eff} of 0.949 ± 0.003 . Limiting and normal operating cases were each repeated three times using different neutron starting distributions. These results are given in Table 6 of Section 12 and conform to RFP acceptance criteria.

Accident cases for plutonium solutions were double-batching, stacking (three high), room flooding, sprinkler flooding, and physical damage. The greater reactivity of solutions as compared to metal, did not allow the 20 high stacking models (discussed in the previous section) to be used. The physical size of cans and the instability of stacks makes arrays more than

three high unrealistic. Since limits restrict the arrays to planar only, three high stacking is sufficient to analyze an accident scenario.

The first two accidents are addressed in Cases 1 through 7 reported in Tables 4 and 6 of Section 12. The average values for these results are also shown graphically in Figure 3. Flooding and sprinkler accident evaluations are reported in Table 5. The highest k_{eff} 's resulted when stacked or double-batched cans were flooded between cans only (0.744 ± 0.003 for stacked cans with a water volume fraction of .75). Flooding increased the k_{eff} of the normal case (100 ml per can, cans not stacked) by about 9.6%; however, the value (0.431 ± 0.003) remained well below 0.90.

An accident or event in which the containers are breached or crushed, such as a vehicle accident, was also evaluated and a safe transport limit on the number of cans in any shipment was established. It was assumed that the contents of all containers involved in the accident were released and allowed to accumulate into an uncontrolled geometry. The data in Figure 2.10 of Reference 3 indicate that a "safe" subcritical volume limit for individual spheres of homogeneous water-reflected and moderated Pu-239 is about 4 liters. With 100 ml of solution per container, 40 containers are required before the "safe" volume limit could be reached. Since vehicle accidents need not be combined with other accidents a limit of 40 containers for transportation will ensure an adequate margin of safety for these operations (also see Section 8.3, page 38).

The effect of bringing other fissile material into contact with an array of cans was evaluated. A fully water reflected slab of plutonium solution ($k_{eff} = 0.891 \pm 0.004$, Ref. 1, p.31) was aligned next to a planar array of double-batched cans (Case 3 of Table 7). The resulting k_{eff} (0.889 ± 0.002) indicates that the arrangement has minimal impact on the k_{eff} of the system. The difference between the k_{eff} of the slab itself and a large array of cans next to the slab is statistically insignificant at the 95% confidence level except when flooded and in one other case (see Section 10.2). This system (the slab plus an array of cans) was also analyzed with single-batched, stacked cans and with double-batched, stacked cans to complete the

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 66 of 116

double-contingency accident scenario. The results, reported in Cases 4 and 6 of Table 7, were similar to Case 3 and indicate that with removal of the spacing requirement the system remains safely subcritical.

The previous conditions were also evaluated combined with sprinkler flooding. The worst case was a stacking/sprinkler (WVF= 0.20) combination for 100 ml Pu solution per can (Table 7, Case 8). Multiplication factors were slightly higher under flooded conditions because the reflection on the slab that was displaced by the cans in the other models was replaced here with water. However, the calculated k_{eff} of 0.927 ± 0.004 demonstrates that even under flooded conditions the array of cans next to the Pu solution slab remains safely subcritical.

10.4 Metal Slurries

The solutions evaluated as discussed in the previous section were limited to a maximum concentration of 1000 g/l. Under operating conditions the actual concentration may not be known; therefore, higher concentrations need to be considered. Since plutonium and uranium are not soluble at these high concentrations the material has been labeled a slurry (solution system containing undissolved solids). This material was modeled as arrays of cans containing a constant mass of 200 grams Pu per can with the solids displacing solution (92 vol.% water, 8 vol.% polyethylene) as the density increased.

Results indicated that the k-effective remains essentially unchanged with increasing density higher than about 5000 g/l (See Table 11 and Figure 5). Slurry accident cases were evaluated using 5000 g/l concentrations for uranium and plutonium. For the normal and typical operating conditions evaluated slurries were less reactive than metals, and for the spacing evaluation the results were statistically identical. However, for some accident cases, the slurries had higher calculated k_{eff} values. This is presumably because the greater volume of slurry (Pu metal density is 19.84 g/cc, slurry is 5 g/cc) is more sensitive to some of the accident conditions. The slurries were shown to be safely subcritical for all required accident scenarios when the same mass limit (50 g) that was established for metals is applied. Mass, not volume limits must be applied if there are undissolved solids in a solution system of unknown concentration.

Neutron multiplication factors greater than 1.0 were calculated when the cans containing 1/2 inch lead shielding were modeled with 100 grams of slurry. As with the metal cases this is considered overly conservative since the cans are stacked 20 high. Slurries were shown safe in lead shielded cans when doubled batched and stacked only 3 high (Case 19 of Table 2, and Case 18 of Table 9). This is adequate to meet double contingency requirements as explained previously.

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 68 of 116

11. SCALED DRAWINGS

See Figure 1, page 61.

12. SUMMARY OF CALCULATION RESULTS

TABLE 2. SUMMARY OF KENO-V.A RESULTS FOR PU METAL SHOWING THE EFFECTS OF ALL DEGREES OF MODERATION

Case ID	Description	$k \pm \sigma$
1	100 grams Pu metal per can, cans stacked 20 high, fuel offset axially and radially in can, 1 ft. concrete reflector above cans, 2 ft. concrete reflector below cans, the remaining volume inside and between cans is void.	0.76716 ± 0.00394
2	Same as Case 1 except moderated/reflected inside and between cans with polyethylene with a volume fraction of 0.01.	0.74639 ± 0.00319
3	Same as Case 1 except moderated/reflected inside and between cans with polyethylene with a volume fraction of 0.05.	0.61082 ± 0.00293
4	Same as Case 1 except moderated/reflected inside and between cans with polyethylene with a volume fraction of 0.07.	0.56717 ± 0.00287
5	Same as Case 1 except moderated/reflected inside and between cans with polyethylene with a volume fraction of 0.10.	0.50825 ± 0.00295
6	Same as Case 1 except moderated/reflected inside and between cans with polyethylene with a volume fraction of 0.25.	0.39061 ± 0.00261
7	Same as Case 1 except moderated/reflected inside and between cans with polyethylene with a volume fraction of 0.50.	0.38303 ± 0.00261
8	Same as Case 1 except moderated/reflected inside and between cans with polyethylene with a volume fraction of 0.75.	0.40956 ± 0.00300
9	Same as Case 1 except moderated/reflected inside and between cans with polyethylene with a volume fraction of 1.00.	0.43939 ± 0.00256

TABLE 2. CONTINUED

Case ID	Description	$k \pm \sigma$
10	Same as Case 1 except moderated/reflected inside and between cans with water with a volume fraction of 1.0 (flooding).	0.41715 ± 0.00272
11	Same as Case 1 except moderated/reflected inside and between cans with water with a volume fraction of 0.5 (sprinkler accident).	0.37717 ± 0.00265
12	Same as Case 1 except moderated/reflected inside and between cans with water with a volume fraction of 0.1 (sprinkler accident).	0.54380 ± 0.00286
13	Same as Case 1 except moderated/reflected between cans with water with a volume fraction of 0.1 (sprinkler accident).	0.74989 ± 0.00398
14	Same as Case 1 except moderator is polyethylene with a volume fraction of 1.0 between cans only.	0.52368 ± 0.00284
15	Same as Case 1 except moderator is polyethylene with a volume fraction of 1.00 inside cans only.	0.42162 ± 0.00247
16	Normal case, 50 grams Pu per can, stacked 20 high, the remaining volume inside and between cans is void.	0.53083 ± 0.00335
17	100 grams Pu per can, stacked 3 high, cans contain 1/2 inch lead shielding	0.36340 ± 0.00235
18	100 grams of Pu slurry (5000 g/l, 20 ml) Pu metal displaces 92% water 8% poly, stacked 20 high	0.88820 ± 0.00302
19	100 grams of Pu slurry (5000 g/l, 20 ml) Pu metal displaces 92% water 8% poly, stacked 3 high, cans contain 1/2 inch lead shielding	0.37881 ± 0.00246

HO49-MES-0491-03

Figure 2. Effects of all degrees of moderation Pu metal cases.

TABLE 3. SUMMARY OF KENO-V.A RESULTS FOR PU METAL

ID ^a	$k_1 \pm \sigma^a$	$k_2 \pm \sigma$	$k_3 \pm \sigma$	$k \pm \sigma$
1	0.76716 ± 0.00394	0.76670 ± 0.00364	0.76574 ± 0.00367	0.76651 ± 0.00216
1a ^b	0.76494 ± 0.00423	0.76697 ± 0.00380	0.76523 ± 0.00383	0.76577 ± 0.00227
10	0.41715 ± 0.00272	0.41573 ± 0.00278	0.41842 ± 0.00334	0.41695 ± 0.00168
13	0.74989 ± 0.00389	0.76110 ± 0.00398	0.75893 ± 0.00364	0.75862 ± 0.00251
13a ^b	0.75597 ± 0.00390	0.76043 ± 0.00432	0.74940 ± 0.00441	0.75539 ± 0.00242
16	0.53083 ± 0.00335	0.53349 ± 0.00332	0.53664 ± 0.00347	0.53358 ± 0.00195
18	0.8820 ± 0.00302	0.88620 ± 0.00278	0.88721 ± 0.00325	0.88714 ± 0.00173

a. From Table 2

b. Cases 1a and 13a were evaluated with the alternate unit cell shown in Figure 1

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 73 of 116

TABLE 4. SUMMARY OF KENO-V.A RESULTS FOR PU SOLUTION SHOWING THE EFFECTS OF VARIATION IN THE VOLUME OF FUEL

Case ID	Description	$k \pm \sigma$
1	200 ml Pu solution (1000 g/l in 92 vol.% water, 8 vol.% polyethylene) per can, cans stacked 3 high, fuel offset axially and radially in can, 30 cm concrete reflector above cans, 60 cm concrete reflector below cans.	0.90225 ± 0.00356
2	Same as Case 1 except fuel volume is 225 ml.	0.93939 ± 0.00359
3	Same as Case 1 except fuel volume is 230 ml.	0.94857 ± 0.00320
4	Same as Case 1 except fuel volume is 250 ml.	0.98180 ± 0.00327
5	Same as Case 1 except fuel volume is 270 ml.	1.00097 ± 0.00329
6	Same as Case 1 except fuel volume is 275 ml.	1.00572 ± 0.00336
7	Same as Case 1 except fuel volume is 300 ml.	1.04231 ± 0.00349
8	Normal case, 100 ml fuel volume infinite planar array, not stacked, fuel centered in can.	0.39345 ± 0.00298

TABLE 5. SUMMARY OF KENO-V.A RESULTS FOR PU SOLUTION SHOWING THE EFFECTS OF ALL DEGREES OF MODERATION

Case ID	Description	$k \pm \sigma$
1	200 ml Pu solution (1000 g/l in 92 vol.% water, 8 vol.% polyethylene) per can, planar, 30 cm concrete above cans, 60 cm concrete below cans. Flooded between cans only with water volume fraction = 1.00.	0.62225 ± 0.00312
2	Same as Case 1 except WVF = 0.75.	0.60386 ± 0.00342
3	Same as Case 1 except WVF = 0.50.	0.59874 ± 0.00293
4	Same as Case 1 except WVF = 0.25.	0.58709 ± 0.00322
5	Same as Case 1 except WVF = 0.10.	0.57580 ± 0.00313
6	Same as Case 1 except WVF = 0.0	0.57341 ± 0.00312
7	100 ml fuel volume, fuel offset in can, cans stacked 3 high, flooded between cans only with a water volume fraction = 1.00.	0.73881 ± 0.00315
8	Same as Case 7 except WVF = 0.75.	0.74358 ± 0.00322
9	Same as Case 7 except WVF = 0.50.	0.73065 ± 0.00306
10	Same as Case 7 except WVF = 0.25.	0.71046 ± 0.00312
11	Same as Case 7 except WVF = 0.10.	0.69074 ± 0.00316
12	Same as Case 7 except WVF = 0.0	0.66872 ± 0.00309
13	Normal case, 100 ml fuel volume, infinite planar array ($k_1=0.39345 \pm 0.00298$, $k_2=0.38931 \pm 0.00289$, $k_3=0.39186 \pm 0.00280$).	0.39151 ± 0.00166^a
14	Same as Case 13 except flooded between cans only, WVF=1.00.	0.43140 ± 0.00265

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 75 of 116

TABLE 5. continued

15	Same as Case 13 except flooded inside cans only, WVF = 1.00.	0.33474 ± 0.00258
16	Same as Case 13 except flooded everywhere, WVF = 1.00	0.32486 ± 0.00260
17	200 ml Pu solution (1000 g/l) per can stacked 3 high, 1/2 inch lead shielding ($k_1=0.92499 \pm 0.00307$, $k_2=0.92654 \pm 0.00306$, $k_3=0.92772 \pm 0.00354$).	0.92630 ± 0.00185^a

a. Weighted average

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 76 of 116

TABLE 6. SUMMARY OF KENO-V.A RESULTS FOR PLUTONIUM SOLUTION

ID ^a	$k_1 \pm \sigma^a$	$k_2 \pm \sigma$	$k_3 \pm \sigma$	$k \pm \sigma$
1	0.90225 ± 0.00356	0.90119 ± 0.00363	0.90423 ± 0.00355	0.90258 ± 0.00207
2	0.93939 ± 0.00359	0.94289 ± 0.00348	0.94216 ± 0.00363	0.94150 ± 0.00206
3	0.94857 ± 0.00320	0.95523 ± 0.00337	0.95814 ± 0.00389	0.95341 ± 0.00199
4	0.98180 ± 0.00327	0.97851 ± 0.00324	0.97584 ± 0.00315	0.97864 ± 0.00186
5	1.00097 ± 0.00329	0.99956 ± 0.00369	1.00738 ± 0.00364	1.00255 ± 0.00204
6	1.00572 ± 0.00336	1.00919 ± 0.00319	1.00817 ± 0.00304	1.00777 ± 0.00184
8	0.39345 ± 0.00298	0.38931 ± 0.00289	0.39186 ± 0.00280	0.39151 ± 0.00167

a. From Table 4

HO49-MES-0891-01

Figure 3. Volume of Pu solution vs. k-effective, double batched 1 gallon cans, stacked 3 high (offset spherical fuel).

TABLE 7. SUMMARY OF KENO-V.A RESULTS SHOWING THE EFFECTS OF INTERACTION WITH SLAB OF PLUTONIUM SOLUTION HAVING A K_{EFF} OF 0.90 (REFERENCE 1, SECTION 5.2.4)

Case ID	Description	$k \pm \sigma$
1	Large array (25 x 50 x 1) of cans against Pu solution slab; 100 grams Pu metal per can ($k_1=0.88934 \pm 0.00393$, $k_2=0.89408 \pm 0.00378$, $k_3=0.88495 \pm 0.00415$).	0.88974 ± 0.00228^a
2	Same as Case 1 except cans contain 50 grams of Pu metal and are stacked 3 high ($k_1=0.88563 \pm 0.00410$, $k_2=0.88720 \pm 0.00382$, $k_3=0.88002 \pm 0.00392$).	0.88430 ± 0.00228^a
3	Same as Case 1 except cans contain 200 ml of Pu Solution (1000 g/l) ($k_1=0.88861 \pm 0.00421$, $k_2=0.88649 \pm 0.00413$, $k_3=0.89351 \pm 0.00423$).	0.88949 ± 0.00242^a
4	Same as Case 1 except cans contain 100 ml of Pu solution (1000 g/L) and cans are stacked 3 high ($k_1=0.88019 \pm 0.00382$, $k_2=0.87909 \pm 0.00383$, $k_3=0.88135 \pm 0.00356$).	0.88027 ± 0.00215^a
5	Same as Case 1 except cans contain 100 g of Pu metal and cans are stacked 3 high ($k_1=0.87947 \pm 0.00387$, $k_2=0.88295 \pm 0.00408$, $k_3=0.87772 \pm 0.00403$).	0.88000 ± 0.00230^a
6	Same as Case 1 except cans contain 200 ml of Pu solution (1000 g/L) and cans are stacked 3 high ($k_1=0.89063 \pm 0.00381$, $k_2=0.88298 \pm 0.00363$, $k_3=0.87957 \pm 0.00386$).	0.88439 ± 0.00217^a
7	Same as Case 5 except cans contain 100 g of U-233 ($k_1=0.88536 \pm 0.00403$, $k_2=0.87722 \pm 0.00337$, $k_3=0.87397 \pm 0.00407$).	0.87867 ± 0.00218^a
8	Same as Case 4 except sprinkler flooded at 0.2 WVF between cans.	0.92651 ± 0.00392

a. Weighted average

TABLE 8. SUMMARY OF KENO-V.A RESULTS FOR ALTERNATE GEOMETRIES

Case ID	Description	$k \pm \sigma$
1	"Pile" of 60 100 g spheres, close-packed fully water reflected (vehicle accident) ($k_1=0.92801 \pm 0.00409$, $k_1=0.92929 \pm 0.00410$, $k_3=0.92768 \pm 0.00378$.)	0.92829 ± 0.00230^a
2	125 50 j spheres, rectangular pitch, close packed ($k_1=0.90321 \pm 0.00439$, $k_2=0.90950 \pm 0.00397$, $k_3=0.90786 \pm 0.00435$).	0.90704 ± 0.00244^a
3	125 50 g sphere, rectangular pitch, separation 1 cm	0.84565 ± 0.00381
4	An infinite rectangular array of one-gallon cans, stacked 20 high, 100 g per can, offset fuel	0.72974 ± 0.00345
5	Same as Case 4 with triangular pitch (see Case 1 of Table 2)	0.76716 ± 0.00394
6	An infinite planar array with rectangular pitch of one-gallon cans, 100 g per can, centered fuel	0.70696 ± 0.00297
7	Same as Case 6 with triangular pitch	0.75232 ± 0.00374
8	Cylindrical fuel, Pu, 100 g/can. Same as Case 1, Table 2 except for cylindrical fuel geometry ($k_1=0.77756 \pm 0.00370$, $k_2=0.77122 \pm 0.00362$, $k_3=0.77038 \pm 0.00409$).	0.77319 ± 0.00370^a
9	Cylindrical fuel, Pu solution, 200 ml/can. Same as Case 1, Table 4 except for cylindrical fuel geometry ($k_1=0.91002 \pm 0.00350$, $k_2=0.90679 \pm 0.00350$, $k_3=0.91477 \pm 0.00368$).	0.91039 ± 0.00205^a
10	Cylindrical fuel, U-233, 100 g/can. Same as Case 14, Table 9 except for cylindrical fuel geometry (flooded between cans with .05 water volume fraction.) ($k_1=0.82619 \pm 0.00364$, $k_2=0.82430 \pm 0.00365$, $k_3=0.83050 \pm 0.00380$).	0.82690 ± 0.00213^a

a. Weighted average

TABLE 9. SUMMARY OF KENO-V.A RESULTS FOR U-233 METAL SHOWING THE EFFECTS OF ALL DEGREES OF MODERATION

Case ID	Description	$k \pm \sigma$
1	100 grams U-233 metal per can, cans stacked 20 high, fuel offset axially and radially in can, 1 ft. concrete reflector above cans, 2 ft. concrete reflector below cans, the remaining volume inside and between cans is void.	0.79622 ± 0.00408
2	Same as Case 1 except moderated/reflected inside and between cans with polyethylene with a volume fraction of 0.01.	0.80980 ± 0.00352
3	Same as Case 1 except moderated/reflected inside and between cans with polyethylene with a volume fraction of 0.05.	0.65447 ± 0.00306
4	Same as Case 1 except moderated/reflected inside and between cans with polyethylene with a volume fraction of 0.10.	0.53258 ± 0.00274
5	Same as Case 1 except moderated/reflected inside and between cans with polyethylene with a volume fraction of 0.25.	0.37072 ± 0.00257
6	Same as Case 1 except moderated/reflected inside and between cans with polyethylene with a volume fraction of 1.00.	0.44877 ± 0.00289
7	Same as Case 1 except moderator is polyethylene with a volume fraction of 1.0 between cans only.	0.55195 ± 0.00291
8	Same as Case 1 except moderator is polyethylene with a volume fraction of 1.00 inside cans only.	0.42662 ± 0.00274
9	Same as Case 1 except moderated/reflected inside and between cans with water with a volume fraction of 1.0 (flooding).	0.42510 ± 0.00282
10	Same as Case 1 except moderated/reflected between cans only with water with a volume fraction of 1.0 (flooding).	0.58126 ± 0.00303

TABLE 9. CONTINUED

Case ID	Description	$k \pm \sigma$
11	Same as Case 1 except moderated/reflected inside and between cans with water with a volume fraction of 0.1 (sprinkler accident).	0.57172 ± 0.00280
12	Same as Case 1 except moderated/reflected between cans only with water with a volume fraction of 0.1 (sprinkler accident).	0.82445 ± 0.00338
13	Same as Case 1 except moderated/reflected between cans only with water with a volume fraction of 0.07 (sprinkler accident).	0.82676 ± 0.00341
14	Same as Case 1 except moderated/reflected between cans only with water with a volume fraction of 0.05 (sprinkler accident). ($k_1=0.82506 \pm 0.00336$ $k_2=0.82256 \pm 0.00409$, $k_3=0.83204 \pm 0.00358$)	0.82681 ± 0.00210^a
15	Same as Case 1 except moderated/reflected between cans only with water with a volume fraction of 0.02 (sprinkler accident).	0.82138 ± 0.00352
16	Normal case, 50 grams U-233 per can, stacked 20 high, the remaining volume inside and between cans is void ($k_1=0.57202 \pm 0.00373$, $k_2=0.57595 \pm 0.00361$, $k_3=0.56682 \pm 0.00367$).	0.57164 ± 0.00212^a
17	100 g U-233 metal slurry (5000 g/l, 20 ml) U metal displaces 92% water 8% polyethylene stacked 20 high	0.70023 ± 0.00336
18	Same as Case 17 except cans contain 1/2 inch lead shielding and are stacked 3 high	0.26011 ± 0.00215

a. Weighted average

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 82 of 116

TABLE 10. SUMMARY OF KENO-V.A RESULTS FOR U-233 METAL SHOWING THE EFFECTS OF STACKING CANS CONTAINING 1/2 INCH LEAD SHIELDING

<u>Case ID</u>	<u>Description</u>	<u>k ± σ</u>
1	100 g U-233 metal per can, stacked 20 high, cans contain 1/2 inch lead shielding	1.14697 ± 0.00476
2	100 g U-233 metal per can, stacked 15 high, cans contain 1/2 inch lead shielding	0.92770 ± 0.00445
3	100 g U-233 metal per can, stacked 10 high, cans contain 1/2 inch lead shielding	0.67499 ± 0.00299
4	100 g U-233 metal per can, stacked 5 high, cans contain 1/2 inch lead shielding	0.45901 ± 0.00266
5	100 g U-233 metal per can, stacked 3 high, cans contain 1/2 inch lead shielding	0.37450 ± 0.00260

Figure 4. Effects of stacking arrays of cans with 1/2 inch lead shielding, 100 grams U-233 per can.

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 84 of 116

TABLE 11. SUMMARY OF KENO-V.A RESULTS FOR PU METAL SHOWING THE EFFECT OF INCREASING DENSITY

Case ID	Description	$k \pm \sigma$
1	200 g Pu slurry (92 vol.% water, 8 vol.% polyethylene) per can, 200 ml, density 1 g/ml stacked 3 high	0.90514 ± 0.00327
2	Same as Case 1, except 150 ml, density 1.3 g/ml	0.82158 ± 0.00342
3	Same as Case 1, except 100 ml, density 2.0 g/ml	0.72848 ± 0.00308
4	Same as Case 1, except 66.7 ml, density 3.0 g/ml	0.65338 ± 0.00324
5	Same as Case 1, except 50 ml, density 4.0 g/ml	0.61673 ± 0.00298
6	Same as Case 1, except 40 ml, density 5.0 g/ml	0.58420 ± 0.00304
7	Same as Case 1, except 33.3 ml, density 6.0 g/ml	0.56429 ± 0.00274
8	Same as Case 1, except 28.6 ml, density 7.0 g/ml	0.54785 ± 0.00283
9	Same as Case 1, except 25 ml, density 8.0 g/ml	0.54413 ± 0.00288
10	Same as Case 1, except 22.2 ml, density 9.0 g/ml	0.54474 ± 0.00290
11	Same as Case 1, except 20 ml, density 10.0 g/ml	0.53389 ± 0.00302

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 85 of 116

TABLE 11. CONTINUED

12	Same as Case 1, except 17.5 ml, density 11.4 g/ml	0.53951 ± 0.00327
13	Same as Case 1, except 15 ml, density 13.3 g/ml	0.53542 ± 0.00308
14	Same as Case 1, except 14.2 ml, density 14.1 g/ml	0.53952 ± 0.00321
15	Same as Case 1, except 12.5 ml, density 16.0 g/ml	0.54476 ± 0.00321
16	Same as Case 1, except 11.1 ml, density 18.0 g/ml	0.54859 ± 0.00301
17	Same as Case 1, except 10.08 ml, density 19.84 g/ml	0.55603 ± 0.00317

Figure 5. Density vs k -effective;
200 grams Pu per can, cans stacked 3 high.

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 87 of 116

13. DRAFT LIMIT

Limits established from this evaluation are based on the requirements for criticality safety. If stricter limits apply due to Safeguards and Security or other reasons, compliance with the most restrictive limits is required.

The following limits apply to RFP one-gallon containers regardless of inner containment. Separation limits from other fissile material are not required. Beryllium shall not be placed in one-gallon cans.

Storage Limits

Solids and slurries (mass limit):

1. The mass of fissile material (uranium or plutonium metal or oxide) shall not exceed 50 g per one-gallon container. Metal slurries (any liquid containing undissolved U or Pu solids) are also subject to this 50 g mass limit. The mass limit applies to the bulk weight of material.
2. Containers shall be limited to planar arrays (i.e., stacking of containers is not allowed).

Plutonium solutions (volume limit):

1. The volume of plutonium solution (organic or aqueous with no visible solids) shall not exceed 100 ml per one-gallon container.
2. Containers shall be limited to planar arrays (i.e., stacking of containers is not allowed).

Transport Limits

Additionally, no more than 40 containers shall be allowed to be transported at one time. Because cans in transport are at risk of being damaged, limiting to 40 the number of containers allowed in one vehicle eliminates concerns over more than that number of cans being breached in a single location so that their collective contents could accumulate in a critical geometry.

NMSL: 90240
 Engineer: MS001.3
 Date: December 1991

Page: 88 of 116

14. CALCULATIONS

14.1 Calculated Number Densities for Materials

<u>Description</u>	<u>Nuclide or Material</u>	<u>KENO-V.a⁵ Library ID</u>	<u>Atom/barn-cm (Volume Fraction)</u>
U-233 metal with density of 18.70 g/cm ³	U-233	92301	4.83300-2
U-233 slurry (5000 g/l U)	U-233	92303	1.29227-3
		92304	1.16304-3
	Water	502	(0.6740)
	Polyethylene	402	(0.0586)
Pu metal with density of 19.84 g/cm ³	Pu-239	94901	4.74882-2
	Pu-240	94003	1.64930-3
		94004	8.39647-4
Pu slurry (5000 g/l Pu)	Pu-239	94904	1.09505-2
		94905	1.01726-3
	Pu-240	94007	6.05333-4
		94008	2.19226-5
	Water	502	(0.6881)
	Polyethylene	402	(0.0598)
Pu solution 1000 g/L in 92 vol.% water, 8 vol.% polyethylene	Pu-239	94907	2.12069-3
		94908	2.72866-4
	Pu-240	94010	9.63766-5
		94011	2.90746-5
	Water	502	(0.92)
	Polyethylene	402	(0.08)
Carbon Steel	C	6100	3.92100-3
	Fe	26100	8.34910-2
Lead	Pb	82100	3.29600-2
Ordinary Concrete		301	(1.00)

14.2 Calculation of Average k_{eff}

As required at RFP,⁴ calculations upon which limits are based were repeated three times with different random number sequences (accomplished by using three different start types [NST=0,1,2]). The three k_{eff} values: k_1 , k_2 , and k_3 , were combined statistically as follows:

$$k = \frac{\sum_{i=1}^3 (k_i / \sigma_i^2)}{\sum_{i=1}^3 (1 / \sigma_i^2)} \quad \text{and}$$

$$\sigma = \left[\sum_{i=1}^3 (1 / \sigma_i^2) \right]^{-1/2}$$

These calculated k_{eff} values were also verified to meet the RFP acceptance criteria⁴ in that each individual k_{eff} value, when rounded to three decimal places, is within the range $\bar{k} \pm 0.010$ where $\bar{k} = (k_1 + k_2 + k_3) / 3$; and that each individual sigma is less than or equal to 0.005.

15. KENO-V.A INPUT LISTINGS

- Listing 1. KENO-V.a Input Listing for Case 1 of Table 2.
- Listing 2. KENO-V.a Input Listing for Case 13 of Table 2.
- Listing 3. KENO-V.a Input Listing for Case 19 of Table 2.
- Listing 4. KENO-V.a Input Listing for Case 1 of Table 4.
- Listing 5. KENO-V.a Input Listing for Case 8 of Table 4.
- Listing 6. KENO-V.a Input Listing for Case 4 of Table 7.
- Listing 7. KENO-V.a Input Listing for Case 5 of Table 7.
- Listing 8. KENO-V.a Input Listing for Case 1 of Table 8.
- Listing 9. KENO-V.a Input Listing for Case 4 of Table 8.
- Listing 10. KENO-V.a Input Listing for Case 9 of Table 8.
- Listing 11. KENO-V.a Input Listing for Case 14 of Table 9.
- Listing 12. KENO-V.a Input Listing for Case 18 of Table 9.
- Listing 13. KENO-V.a Input Listing for Case 2 of Table 11.

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 91 of 116

Listing 1. KENO-V.a Input Listing for Case 1 of Table 2

GAL110 100 G PU METAL; INFINITE ARRAY; SPHERICAL FUEL
READ PARA

TME=120.0 GEN=153 NPG=407 LIB=41
FLX=NO FDN=NO AMX=NO FAR=NO
RUN=YES PLT=YES

END PARA

READ MIXT

MIX-1 94901 4.74882-2
94003 1.64930-3 94004 8.39647-4
MIX-2 6100 3.92100-3 26100 8.34910-2
MIX-3 301 1.0

END MIXT

READ GEOM

UNIT 1

ZHEMICYL+X 0 1 8.308975 2P9.737725
HOLE 4 0.0 7.245345 -8.67409
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 2

ZHEMICYL-X 0 1 8.308975 2P9.737725
HOLE 5 0.0 7.245345 -8.67409
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 3

ZHEMICYL+Y 0 1 8.308975 2P9.737725
HOLE 6 7.245345 0.0 -8.67409
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 4

HEMISPHE+X 1 1 1.06363

UNIT 5

HEMISPHE-X 1 1 1.06363

UNIT 6

HEMISPHE+Y 1 1 1.06363

UNIT 7

HEMISPHE-Y 1 1 1.06363

UNIT 8

ZHEMICYL+X 0 1 8.308975 2P9.737725
HOLE 4 0.0 7.245345 +8.67409
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 9

ZHEMICYL-X 0 1 8.308975 2P9.737725
HOLE 5 0.0 7.245345 +8.67409
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 10

ZHEMICYL+Y 0 1 8.308975 2P9.737725
HOLE 6 7.245345 0.0 +8.67409
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 11

COM=* UNIT CELL, FUEL OFFSET TO BOTTOM OF CAN *

ZHEMICYL-Y 0 1 8.308975 2P9.737725
HOLE 7 7.245345 0.0 -8.67409

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 92 of 116

```
ZHEMICYL-Y 2 1 8.334375 2P9.763125
CUBOID 0 1 2P8.334375 0.0 -28.8712 2P9.763125
HOLE 1 -8.334375 -14.4356 0.0
HOLE 3 0.0 -28.8712 0.0
HOLE 2 +8.334375 -14.4356 0.0
UNIT 12
COM=* UNIT CELL, FUEL OFFSET TO TOP OF CAN *
ZHEMICYL-Y 0 1 8.308975 2P9.737725
HOLE 7 7.245345 0.0 +8.67409
ZHEMICYL-Y 2 1 8.334375 2P9.763125
CUBOID 0 1 2P8.334375 0.0 -28.8712 2P9.763125
HOLE 8 -8.334375 -14.4356 0.0
HOLE 10 0.0 -28.8712 0.0
HOLE 9 +8.334375 -14.4356 0.0
UNIT 13
COM=* ARRAY OF CANS STACKED TWO HIGH *
ARRAY 1 -8.34 -29.0 -19.528
GLOBAL
UNIT 14
COM=* ARRAY OF CANS STACKED TWENTY HIGH *
ARRAY 2 -8.34 -29.0 -195.28
REPLICATE 3 2 4*0.0 2*5.0 6
REPLICATE 3 8 5*0.0 5.0 6
END GEOM
READ START NST=0 END START
READ ARRAY ARA=1 NUX=1 NUY=1 NUZ=2
FILL 12 11 END FILL
ARA=2 NUX=1 NUY=1 NUZ=10
FILL F13 END FILL
END ARRAY
READ BIAS ID=301 2 13 END BIAS
READ BOUNDS XYF=MIRROR END BOUNDS
READ PLOT
PLT=YES PIC=MIX NCH='*0#.'
TTL=* "X-Y SLICE THROUGH ORIGIN" *
XUL=-8.34 YUL=0.0 ZUL=-18.6
XLR=8.34 YLR=-29.0 ZLR=-18.6
UAX=1.0 VDN=-1.0 NAX=130 END
END PLOT
END DATA
```

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 93 of 116

Listing 2. KENO-V.a Input Listing for Case 13 of Table 2

GAL121 100 G PU METAL; INFINITE ARRAY; SPHERICAL FUEL,FLOODED

READ PARA

TME=80.0 GEN=153 NPG=407 LIB=4
FLX=NO FDN=NO AMX=NO FAR=NO
RUN=YES PLT=YES

END PARA

READ MIXT

MIX=1 94901 4.74882-2
94003 1.64930-3 94004 8.39647-4
MIX=2 6100 3.92100-3 26100 8.34910-2
MIX=3 301 1.0
MIX=4 502 0.1

END MIXT

READ GEOM

UNIT 1

ZHEMICYL+X 0 1 8.308975 2P9.737725
HOLE 4 0.0 7.245345 -8.67409
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 2

ZHEMICYL-X 0 1 8.308975 2P9.737725
HOLE 5 0.0 7.245345 -8.67409
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 3

ZHEMICYL+Y 0 1 8.308975 2P9.737725
HOLE 6 7.245345 0.0 -8.67409
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 4

HEMISPHE+X 1 1 1.06363

UNIT 5

HEMISPHE-X 1 1 1.06363

UNIT 6

HEMISPHE+Y 1 1 1.06363

UNIT 7

HEMISPHE-Y 1 1 1.06363

UNIT 8

ZHEMICYL+X 0 1 8.308975 2P9.737725
HOLE 4 0.0 7.245345 +8.67409
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 9

ZHEMICYL-X 0 1 8.308975 2P9.737725
HOLE 5 0.0 7.245345 +8.67409
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 10

ZHEMICYL+Y 0 1 8.308975 2P9.737725
HOLE 6 7.245345 0.0 +8.67409
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 11

COM=* UNIT CELL, FUEL OFFSET TO BOTTOM OF CAN *

ZHEMICYL-Y 0 1 8.308975 2P9.737725

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 9 of 116

```
HOLE          7      7.245345 0.0 -8.67409
ZHEMICYL-Y    2 1    8.334375 2P9.763125
CUBOID         4 1    2P8.334375 0.0 -28.8712 2P9.763125
HOLE          1     -8.334375 -14.4356 0.0
HOLE          3      0.0 -28.8712 0.0
HOLE          2     +8.334375 -14.4356 0.0
UNIT 12
COM=* UNIT CELL, FUEL OFFSET TO TOP OF CAN *
ZHEMICYL-Y    0 1    8.308975 2P9.737725
HOLE          7      7.245345 0.0 +8.67409
ZHEMICYL-Y    2 1    8.334375 2P9.763125
CUBOID         4 1    2P8.334375 0.0 -28.8712 2P9.763125
HOLE          8     -8.334375 -14.4356 0.0
HOLE         10      0.0 -28.8712 0.0
HOLE          9     +8.334375 -14.4356 0.0
UNIT 13
COM=* ARRAY OF CANS STACKED TWO HIGH *
ARRAY          1 -8.34 -29.0 -19.528
GLOBAL
UNIT 14
COM=* ARRAY OF CANS STACKED TWENTY HIGH *
ARRAY          2 -8.34 -29.0 -195.28
REPLICATE      3 2 4*0.0 2*5.0 6
REPLICATE      3 8 5*0.0 5.0 6
END GEOM
READ START NST=0 END START
READ ARRAY ARA=1 NUX=1 NUY=1 NUZ=2
FILL 12 11 END FILL
ARA=2 NUX=1 NUY=1 NUZ=10
FILL F13 END FILL
END ARRAY
READ BIAS ID=301 2 13 END BIAS
READ BOUNDS XYF=MIRROR END BOUNDS
READ PLOT
  PLT=YES PIC=MIX NCH='*0#.'
  TTL=* "X-Y SLICE THROUGH FUEL" *
  XUL=-8.34 YUL=0.0 ZUL=-18.468
  XLR=8.34 YLR=-29.0 ZLR=-18.468
  UAX=1.0 VDN=-1.0 NAX=130 END
END PLOT
END DATA
```

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 95 of 116

Listing 3. KENO-V.a Input Listing for Case 19 of Table 2

SLURP 5000 G/L PU;INFINITE ARRAY STACKED 20 HI; .02 LITER VOL

READ PARA

TME=170.0 GEN=153 NPG=507 LIB=41
FLX=NO FDN=NO AMX=NO FAR=NO
RUN=YES PLT=YES

END PARA

READ MIXT

MIX-1 94904 1.09505-2 94905 1.01726-3
94007 6.05333-4 94008 2.19226-5
502 .6881 402 .0598
MIX-2 6100 3.92100-3 26100 8.34910-2
MIX-3 301 1.0

END MIXT

READ GEOM

UNIT 1

HEMISPHE+X 1 1 1.68389 ORIGIN 0.0 6.625085 -8.053835
ZHEMICYL+X 0 1 8.308975 2P9.737725
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 2

HEMISPHE-X 1 1 1.68389 ORIGIN 0.0 6.625085 -8.053835
ZHEMICYL-X 0 1 8.308975 2P9.737725
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 3

HEMISPHE+Y 1 1 1.68389 ORIGIN 6.625085 0.0 -8.053835
ZHEMICYL+Y 0 1 8.308975 2P9.737725
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 4

HEMISPHE-Y 1 1 1.68389 ORIGIN 6.625085 0.0 -8.053835
ZHEMICYL-Y 0 1 8.308975 2P9.737725
ZHEMICYL-Y 2 1 8.334375 2P9.763125
CUBOID 0 1 2P8.334375 0.0 -28.8712 2P9.763125
HOLE 1 -8.334375 -14.4356 0.0
HOLE 3 0.0 -28.8712 0.0
HOLE 2 +8.334375 -14.4356 0.0

UNIT 5

HEMISPHE+X 1 1 1.68389 ORIGIN 0.0 6.625085 8.053835
ZHEMICYL+X 0 1 8.308975 2P9.737725
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 6

HEMISPHE-X 1 1 1.68389 ORIGIN 0.0 6.625085 8.053835
ZHEMICYL-X 0 1 8.308975 2P9.737725
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 7

HEMISPHE+Y 1 1 1.68389 ORIGIN 6.625085 0.0 8.053835
ZHEMICYL+Y 0 1 8.308975 2P9.737725
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 8

HEMISPHE-Y 1 1 1.68389 ORIGIN 6.625085 0.0 8.053835
ZHEMICYL-Y 0 1 8.308975 2P9.737725

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 96 of 116

```
ZHEMICYL-Y 2 1 8.334375 2P9.763125
CUBOID 0 1 2P8.334375 0.0 -28.8712 2P9.763125
HOLE 5 -8.334375 -14.4356 0.0
HOLE 7 0.0 -28.8712 0.0
HOLE 6 +8.334375 -14.4356 0.0
GLOBAL
UNIT 9
ARRAY 1 -8.34 -29.0 -195.28
REPLICATE 3 2 4*0.0 2*5.0 6
REPLICATE 3 8 5*0.0 5.0 6
END GEOM
READ START NST=1 END START
READ BOUNDS XYF=MIRROR END BOUNDS
READ BIAS ID=301 2 13 END BIAS
READ ARRAY ARA=1 NUX=1 NUY=1 NUZ=20
LOOP 8 1 1 1 1 1 1 1 20 1
      4 1 1 1 1 1 1 2 20 2
END ARRAY
READ PLOT
      PLT=YES PIC=MIX NCH='*@#.'
      TTL='* X-Y SLICE THROUGH ORIGIN *'
      XUL=-8.34 YUL=0.0 ZUL=-9.764
      XLR=8.34 YLR=-29.0 ZLR=-9.764
      UAX=1.0 VDN=-1.0 NAX=130 END
END PLOT
END DATA
```

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 97 of 116

Listing 4. KENO-V.a Input Listing for Case 1 of Table 4

GAL504 1000 G/L PU;INFINITE ARRAY STACKED 3 HI; .20 LITER VOL

READ PARA

TME=70.0 GEN=153 NPG=407 LIB=41
FLX=NO FDN=NO AMX=NO FAR=NO
RUN=YES PLT=YES

END PARA

READ MIXT

MIX-1 94907 2.12069-3 94908 2.72866-4
94010 9.63766-5 94011 2.90746-5
502 .92 402 .08
MIX-2 6100 3.92100-3 26100 8.34910-2
MIX-3 301 1.0

END MIXT

READ GEOM

UNIT 1

HEMISPHE+X 1 1 3.62783 ORIGIN 0.0 4.681145 -6.109895
ZHEMICYL+X 0 1 8.308975 2P9.737725
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 2

HEMISPHE-X 1 1 3.62783 ORIGIN 0.0 4.681145 -6.109895
ZHEMICYL-X 0 1 8.308975 2P9.737725
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 3

HEMISPHE+Y 1 1 3.62783 ORIGIN 4.681145 0.0 -6.109895
ZHEMICYL+Y 0 1 8.308975 2P9.737725
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 4

COM=* UNIT CELL WITH FUEL OFFSET TO BOTTOM OF CANS *

HEMISPHE-Y 1 1 3.62783 ORIGIN 4.681145 0.0 -6.109895
ZHEMICYL-Y 0 1 8.308975 2P9.737725
ZHEMICYL-Y 2 1 8.334375 2P9.763125
CUBOID 0 1 2P8.334375 0.0 -28.8712 2P9.763125
HOLE 1 -8.334375 -14.4356 0.0
HOLE 3 0.0 -28.8712 0.0
HOLE 2 +8.334375 -14.4356 0.0

UNIT 5

HEMISPHE+X 1 1 3.62783 ORIGIN 0.0 4.681145 6.109895
ZHEMICYL+X 0 1 8.308975 2P9.737725
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 6

HEMISPHE-X 1 1 3.62783 ORIGIN 0.0 4.681145 6.109895
ZHEMICYL-X 0 1 8.308975 2P9.737725
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 7

HEMISPHE+Y 1 1 3.62783 ORIGIN 4.681145 0.0 6.109895
ZHEMICYL+Y 0 1 8.308975 2P9.737725
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 8

COM=* UNIT CELL WITH FUEL OFFSET TO TOP OF CANS *

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 98 of 116

HEMISPHE-Y	1 1	3.62783	ORIGIN	4.681145	0.0	6.109895
ZHEMICYL-Y	0 1	8.308975	2P9.737725			
ZHEMICYL-Y	2 1	8.334375	2P9.763125			
CUBOID	0 1	2P8.334375	0.0	-28.8712	2P9.763125	
HOLE	5	-8.334375	-14.4356	0.0		
HOLE	7	0.0	-28.8712	0.0		
HOLE	6	+8.334375	-14.4356	0.0		

GLOBAL

COM=* ARRAY OF CANS STACKED THREE HIGH *

UNIT 9

ARRAY 1 -8.34 -29.0 -19.528

REPLICATE 3 2 4*0.0 2*5.0 6

REPLICATE 3 8 5*0.0 5.0 6

END GEOM

READ START NST=0 END START

READ BOUNDS XYF=MIRROR END BOUNDS

READ BIAS ID=301 2 13 END BIAS

READ ARRAY ARA=1 NUX=1 NUY=1 NUZ=3 FILL 8 4 4 END FILL

END ARRAY

READ PLOT

PLT=YES PIC=MIX NCH='*0#.'

TTL=* "X-Y SLICE THROUGH ORIGIN" *

XUL=-8.34 YUL=0.0 ZUL=-9.764

XLR=8.34 YLR=-29.0 ZLR=-9.764

UAX=1.0 VDN=-1.0 NAX=130 END

END PLOT

END DATA

Listing 5. KENO-V.a Input Listing for Case 8 of Table 4

GAL503 1000 G/L PU;INFINITE PLANAR ARRAY; .10 LITER VOL

READ PARA

TME=60.0 GEN=153 NPG=407 LIB=41
FLX=NO FDN=NO AMX=NO FAR=NO
RUN=YES PLT=YES

END PARA

READ MIXT

MIX-1 94907 2.12069-3 94908 2.72866-4
94010 9.63766-5 94011 2.90746-5
502 .92 402 .08
MIX-2 6100 3.92100-3 26100 8.34910-2
MIX-3 301 1.0

END MIXT

READ GEOM

UNIT 1

HEMISPHE+X 1 1 2.879412
ZHEMICYL+X 0 1 8.308975 2P9.737725
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 2

HEMISPHE-X 1 1 2.879412
ZHEMICYL-X 0 1 8.308975 2P9.737725
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 3

HEMISPHE+Y 1 1 2.879412
ZHEMICYL+Y 0 1 8.308975 2P9.737725
ZHEMICYL+Y 2 1 8.334375 2P9.763125

GLOBAL

UNIT 4

HEMISPHE-Y 1 1 2.879412
ZHEMICYL-Y 0 1 8.308975 2P9.737725
ZHEMICYL-Y 2 1 8.334375 2P9.763125
CUBOID 0 1 2P8.334375 0.0 -28.8712 2P9.763125
HOLF 1 -8.334375 -14.4356 0.0
HOLE 3 0.0 -28.8712 0.0
HOLE 2 +8.334375 -14.4356 0.0

REPLICATE 3 2 4*0.0 2*5.0 6

REPLICATE 3 8 5*0.0 5.0 6

END GEOM

READ START NST=0 END START

READ BOUNDS XYF=MIRROR END BOUNDS

READ BIAS ID=301 2 13 END BIAS

READ PLOT

PLT=YES PIC=MIX NCH='*0#.'

TTL='X-Y SLICE THROUGH ORIGIN' *

XUL=-8.34 YUL=0.0 ZUL=0.0

XLR=8.34 YLR=-29.0 ZLR=0.0

UAX=1.0 VDN=-1.0 NAX=130 END

END PLOT

END DATA

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 100 of 116

Listing 6. KENO-V.a Input Listing for Case 4 of Table 7

GAL550 1000 G/L PU; 25x50x3 PLANAR ARRAY; .20 LITER VOL +SLAB(k=.90)

READ PARA

TME=60.0 GEN=153 NPG=407 LIB=41
FLX=NO FDN=NO AMX=NO FAR=NO
RUN=YES PLT=YES

END PARA

READ MIXT

MIX-1 94907 2.12069-3 94908 2.72866-4
94010 9.63766-5 94011 2.90746-5
502 .92 402 .08
MIX-2 6100 3.92100-3 26100 8.34910-2
MIX-3 301 1.0
MIX-4 502 1.0 94910 3.77930-4
MIX-5 502 1.0

END MIXT

READ GEOM

UNIT 1

HEMISPHE+X 1 1 3.62783
ZHEMICYL+X 0 1 8.308975 2P9.737725
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 2

HEMISPHE-X 1 1 3.62783
ZHEMICYL-X 0 1 8.308975 2P9.737725
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 3

HEMISPHE+Y 1 1 3.62783
ZHEMICYL+Y 0 1 8.308975 2P9.737725
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 4

COM=* "UNIT CELL OF CANS" *

HEMISPHE-Y 1 1 3.62783
ZHEMICYL-Y 0 1 8.308975 2P9.737725
ZHEMICYL-Y 2 1 8.334375 2P9.763125
CUBOID 0 1 2P8.334375 0.0 -28.8712 2P9.763125
HOLE 1 -8.334375 -14.4356 0.0
HOLE 3 0.0 -28.8712 0.0
HOLE 2 +8.334375 -14.4356 0.0

UNIT 5

COM=* PU-WATER SLAB *

CUBOID 4 1 2P2.286 4P100.0
CUBOID 5 1 2P2.286 4P130.0
CUBOID 0 1 2P2.286 2P360.89 2P130.00

UNIT 6

COM=* LARGE ARRAY OF CANS *

ARRAY 1 -208.3594 -360.89 -29.28938
CUBOID 0 1 2P208.3594 2P360.89 2P29.28938

UNIT 7

COM=* "LOWER REFLECTOR FOR ARRAY OF CANS" *

CUBOID 0 1 2P208.3594 2P360.89 2P50.35531

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 101 of 116

```
HOLE 11 193.3594 0.0 0.0
HOLE 12 -15.00 0.0 20.35530
UNIT 8
COM=* "UPPER REFLECTOR FOR ARRAY OF CANS" *
CUBOID 0 1 2P208.3594 2P360.89 2P50.35531
HOLE 11 193.3594 0.0 0.0
HOLE 13 -15.00 0.0 -35.35531
UNIT 9
COM=* "ARRAY OF CANS WITH REFLECTORS" *
ARRAY 2 -208.3594 -360.89 -130.0
CUBOID 0 1 2P208.3594 2P360.89 2P130.00
GLOBAL
UNIT 10
COM=* LARGE ARRAY OF CANS NEXT TO PU SOLUTION SLAB *
ARRAY 3 -225.6455 -360.89 -130.0
REPLICATE 5 2 3.0 5*0.0 10
UNIT 11
CUBOID 5 1 2P15.00 2P100.0 2P50.35531
UNIT 12
CUBOID 3 1 2P193.3594 2P360.89 2P30.00
UNIT 13
CUBOID 3 1 2P193.3594 2P360.89 2P15.00
END GEOM
READ START NST=0 END START
READ BIAS ID=500 2 9 END BIAS
READ ARRAY ARA=1 NUX=25 NUY=25 NUZ=3 FILL F4 END FILL
ARA=2 NUX=1 NUY=1 NUZ=3 FILL 7 6 8 END FILL
ARA=3 NUX=2 NUY=1 NUZ=1 FILL 9 5 END FILL END ARRAY
READ PLOT
PLT=YES PIC=MIX NCH='*0#.'
TTL=* "X-Y SLICE THROUGH FUEL" *
XUL=-226.0 YUL=361.0 ZUL=0.0
XLR=226.0 YLR=-361.0 ZLR=0.0
UAX=1.0 VDN=-1.0 NAX=130 END
END PLOT
END DATA
```

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 102 of 116

Listing 7. KENO-V.a Input Listing for Case 5 of Table 7

GAL555 100 G PU; 25x50x3 ARRAY OF CANS +SLAB(k=.90)

READ PARA

TME=120.0 GEN=153 NPG=407 LIB=41
FLX=NO FDN=NO AMX=NO FAR=NO
RUN=YES PLT=YES

END PARA

READ MIXT

MIX-1 94901 4.74882-2
94003 1.64930-3 94004 8.39647-4
MIX-2 6100 3.92100-3 26100 8.34910-2
MIX-3 301 1.0
MIX-4 502 1.0 94910 3.77930-4
MIX-5 502 1.0

END MIXT

READ GEOM

UNIT 1

ZHEMICYL+X 0 1 8.308975 2P9.737725
HOLE 4 0.0 7.245345 -8.674095
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 2

ZHEMICYL-X 0 1 8.308975 2P9.737725
HOLE 5 0.0 7.245345 -8.674095
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 3

ZHEMICYL+Y 0 1 8.308975 2P9.737725
HOLE 6 7.245345 0.0 -8.674095
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 4

HEMISPHE+X 1 1 1.06363

UNIT 5

HEMISPHE-X 1 1 1.06363

UNIT 6

HEMISPHE+Y 1 1 1.06363

UNIT 7

HEMISPHE-Y 1 1 1.06363

UNIT 8

ZHEMICYL+X 0 1 8.308975 2P9.737725
HOLE 4 0.0 7.245345 +8.674095
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 9

ZHEMICYL-X 0 1 8.308975 2P9.737725
HOLE 5 0.0 7.245345 +8.674095
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 10

ZHEMICYL+Y 0 1 8.308975 2P9.737725
HOLE 6 7.245345 0.0 +8.674095
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 11

ZHEMICYL-Y 0 1 8.308975 2P9.737725

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 103 of 116

```
HOLE      7      7.245345 0.0 -8.674095
ZHEMICYL-Y 2 1      8.334375 2P9.763125
CUBOID     0 1      2P8.334375 0.0 -28.8712 2P9.763125
HOLE      1      -8.334375 -14.4356 0.0
HOLE      3      0.0 -28.8712 0.0
HOLE      2      +8.334375 -14.4356 0.0
UNIT 12
ZHEMICYL-Y 0 1      8.308975 2P9.737725
HOLE      7      7.245345 0.0 +8.674095
ZHEMICYL-Y 2 1      8.334375 2P9.763125
CUBOID     0 1      2P8.334375 0.0 -28.8712 2P9.763125
HOLE      8      -8.334375 -14.4356 0.0
HOLE     10      0.0 -28.8712 0.0
HOLE      9      +8.334375 -14.4356 0.0
UNIT 13
COM=* PU-WATER SLAB *
CUBOID     4 1      2P2.286 4P100.0
CUBOID     5 1      2P2.286 4P130.0
CUBOID     0 1      2P2.286 2P360.89 2P130.00
UNIT 14
COM=* LARGE ARRAY OF CANS *
ARRAY      1      -208.3594 -360.89 -29.28938
CUBOID     0 1      2P208.3594 2P360.89 2P29.28938
UNIT 15
COM=* "LOWER REFLECTOR FOR ARRAY OF CANS" *
CUBOID     0 1      2P208.3594 2P360.89 2P50.35531
HOLE     19      193.3594 0.0 0.0
HOLE     20      -15.00 0.0 20.35530
UNIT 16
COM=* "UPPER REFLECTOR FOR ARRAY OF CANS" *
CUBOID     0 1      2P208.3594 2P360.89 2P50.35531
HOLE     19      193.3594 0.0 0.0
HOLE     21      -15.00 0.0 -35.35531
UNIT 17
COM=* "ARRAY OF CANS WITH REFLECTORS" *
ARRAY      2      -208.3594 -360.89 -130.0
CUBOID     0 1      2P208.3594 2P360.89 2P130.00
GLOBAL
UNIT 18
COM=* LARGE ARRAY OF CANS NEXT TO PU SOLUTION SLAB *
ARRAY      3      -225.6455 -360.89 -130.0
REPLICATE  5 2 3.0 5*0.0 10
UNIT 19
CUBOID     5 1      2P15.00 2P100.0 2P50.35531
UNIT 20
CUBOID     3 1      2P193.3594 2P360.89 2P30.00
UNIT 21
CUBOID     3 1      2P193.3594 2P360.89 2P15.00
END GEOM
READ START NST=0 END START
READ BIAS ID=500 2 9 END BIAS
READ ARRAY ARA=1 NUX=25 NUY=25 NUZ=3 FILL 625R12 1250R11 END FILL
```

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 104 of 116

ARA-2 NUX-1 NUY-1 NUZ-3 FILL 15 14 16 END FILL
ARA-3 NUX-2 NUY-1 NUZ-1 FILL 17 13 END FILL END ARRAY
READ PLOT
PLT=YES PIC=MIX NCH='*0#.'
TTL=* "X-Y SLICE THROUGH FUEL" *
XUL=-226.0 YUL=361.0 ZUL=0.0
XLR=226.0 YLR=-361.0 ZLR=0.0
UAX=1.0 VDN=-1.0 NAX=130 END
END PLOT
END DATA

Listing 8. KENO-V.a Input Listing for Case 1 of Table 8

PILE OF 60 100 G SPHERES OF PU METAL

READ PARA

TME=120.0 GEN=153 NPG=407 LIB=41
 FLX=NO FDN=NO AMX=NO FAR=NO
 RUN=YES PLT=YES

END PARA

READ MIXT

MIX-1 94901 4.74882-2
 94003 1.64930-3 94004 8.39647-4
 MIX-2 502 1.0

END MIXT

READ GEOM

UNIT 1

SPHERE 1 1 1.06362

GLOBAL

UNIT 2

CUBOID	2 1	2P4.748152	2P5.31815	6.590414	-2.910251
HOLE	1	0.0	1.06363	0.0	
HOLE	1	0.0	-1.06363	0.0	
HOLE	1	0.0	3.19089	0.0	
HOLE	1	0.0	-3.19089	0.0	
HOLE	1	1.842261	0.0	0.0	
HOLE	1	-1.842261	0.0	0.0	
HOLE	1	1.842261	-2.12726	0.0	
HOLE	1	-1.842261	-2.12726	0.0	
HOLE	1	1.842261	2.12726	0.0	
HOLE	1	-1.842261	2.12726	0.0	
HOLE	1	0.0	0.0	1.842261	
HOLE	1	0.0	2.12726	1.842261	
HOLE	1	0.0	-2.12726	1.842261	
HOLE	1	0.0	4.25452	1.842261	
HOLE	1	0.0	-4.25452	1.842261	
HOLE	1	1.842261	1.06363	1.842261	
HOLE	1	1.842261	-1.06363	1.842261	
HOLE	1	1.842261	3.19089	1.842261	
HOLE	1	1.842261	-3.19089	1.842261	
HOLE	1	-1.842261	-1.06363	1.842261	
HOLE	1	-1.842261	1.06363	1.842261	
HOLE	1	-1.842261	3.19089	1.842261	
HOLE	1	-1.842261	-3.19089	1.842261	
HOLE	1	3.684522	0.0	1.842261	
HOLE	1	-3.684522	0.0	1.842261	
HOLE	1	3.684522	2.12726	1.842261	
HOLE	1	-3.684522	2.12726	1.842261	
HOLE	1	3.684522	-2.12726	1.842261	
HOLE	1	-3.684522	-2.12726	1.842261	
HOLE	1	0.0	0.0	-1.846621	
HOLE	1	0.0	2.12726	-1.846621	
HOLE	1	0.0	-2.12726	-1.846621	

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 106 of 116

HOLE	1	0.0	4.25452	-1.846621
HOLE	1	0.0	-4.25452	-1.846621
HOLE	1	1.842261	1.06363	-1.846621
HOLE	1	1.842261	-1.06363	-1.846621
HOLE	1	1.842261	3.19089	-1.846621
HOLE	1	1.842261	-3.19089	-1.846621
HOLE	1	-1.842261	-1.06363	-1.846621
HOLE	1	-1.842261	1.06363	-1.846621
HOLE	1	-1.842261	3.19089	-1.846621
HOLE	1	-1.842261	-3.19089	-1.846621
HOLE	1	3.684522	0.0	-1.846621
HOLE	1	-3.684522	0.0	-1.846621
HOLE	1	3.684522	2.12726	-1.846621
HOLE	1	-3.684522	2.12726	-1.846621
HOLE	1	3.684522	-2.12726	-1.846621
HOLE	1	-3.684522	-2.12726	-1.846621
HOLE	1	0.0	1.06363	3.684522
HOLE	1	0.0	-1.06363	3.684522
HOLE	1	0.0	3.19089	3.684522
HOLE	1	0.0	-3.19089	3.684522
HOLE	1	1.842261	0.0	3.684522
HOLE	1	-1.842261	0.0	3.684522
HOLE	1	1.842261	-2.12726	3.684522
HOLE	1	-1.842261	-2.12726	3.684522
HOLE	1	1.842261	2.12726	3.684522
HOLE	1	-1.842261	2.12726	3.684522
HOLE	1	0.0	0.0	5.526784
HOLE	1	0.0	-2.12726	5.526784

REPLICATE 2 2 6*3.0 10
END GEOM
READ START NST=0 END START
READ BIAS ID=500 2 11 END BIAS
READ PLOT
PLT=YES PIC=MIX NCH='*#.'
TTL=* "X-Y SLICE THROUGH ORIGIN" *
XUL=-3.0 YUL=4.3 ZUL=-0.0
XLR=3.0 YLR=-4.3 ZLR=-0.0
UAX=1.0 VDN=-1.0 NAX=130 END
END PLOT
END DATA

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 107 of 116

Listing 9. KENO-V.a Input Listing for Case 4 of Table 8

CYL504 1000 G/L PU;INFINITE ARRAY STACKED 3 HI; .20 LITER VOL

READ PARA

TME=70.0 GEN=153 NPG=407 LIB=41
FLX=NO FDN=NO AMX=NO FAR=NO
RUN=YES PLT=YES

END PARA

READ MIXT

MIX-1 94907 2.12069-3 94908 2.72866-4
94010 9.63766-5 94011 2.90746-5
502 .92 402 .08
MIX-2 6100 3.92100-3 26100 8.34910-2
MIX-3 301 1.0

END MIXT

READ GEOM

UNIT 1

ZHEMICYL+X 1 1 3.1692 -3.3993 -9.737725 ORIGIN 0.0 4.869775
ZHEMICYL+X 0 1 8.308975 2P9.737725
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 2

ZHEMICYL-X 1 1 3.1692 -3.3993 -9.737725 ORIGIN 0.0 4.869775
ZHEMICYL-X 0 1 8.308975 2P9.737725
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 3

ZHEMICYL+Y 1 1 3.1692 -3.3993 -9.737725 ORIGIN 4.869775 0.0
ZHEMICYL+Y 0 1 8.308975 2P9.737725
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 4

COM=* UNIT CELL WITH FUEL OFFSET TO BOTTOM OF CANS *

ZHEMICYL-Y 1 1 3.1692 -3.3993 -9.737725 ORIGIN 4.869775 0.0
ZHEMICYL-Y 0 1 8.308975 2P9.737725
ZHEMICYL-Y 2 1 8.334375 2P9.763125
CUBOID 0 1 2P8.334375 0.0 -28.8712 2P9.763125
HOLE 1 -8.334375 -14.4356 0.0
HOLE 3 0.0 -28.8712 0.0
HOLE 2 +8.334375 -14.4356 0.0

UNIT 5

ZHEMICYL+X 1 1 3.1692 9.737725 3.3993 ORIGIN 0.0 4.869775
ZHEMICYL+X 0 1 8.308975 2P9.737725
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 6

ZHEMICYL-X 1 1 3.1692 9.737725 3.3993 ORIGIN 0.0 4.869775
ZHEMICYL-X 0 1 8.308975 2P9.737725
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 7

ZHEMICYL+Y 1 1 3.1692 9.737725 3.3993 ORIGIN 4.869775 0.0
ZHEMICYL+Y 0 1 8.308975 2P9.737725
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 8

COM=* UNIT CELL WITH FUEL OFFSET TO TOP OF CANS *

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 108 of 116

ZHEMICYL-Y	1 1	3.1692	9.737725	3.3993	ORIGIN	4.869775	0.0
ZHEMICYL-Y	0 1	8.308975	2P9.737725				
ZHEMICYL-Y	2 1	8.334375	2P9.763125				
CUBOID	0 1	2P8.334375	0.0	-28.8712	2P9.763125		
HOLE	5	-8.334375	-14.4356	0.0			
HOLE	7	0.0	-28.8712	0.0			
HOLE	6	+8.334375	-14.4356	0.0			

GLOBAL

COM=* ARRAY OF CANS STACKED THREE HIGH *

UNIT 9

ARRAY 1 -8.34 -29.0 -19.528

REPLICATE 3 2 4*0.0 2*5.0 6

REPLICATE 3 8 5*0.0 5.0 6

END GEOM

READ START NST=0 END START

READ BOUNDS XYF=MIRROR END BOUNDS

READ BIAS ID=301 2 13 END BIAS

READ ARRAY ARA=1 NUX=1 NUY=1 NUZ=3 FILL 8 4 4 END FILL

END ARRAY

READ PLOT

PLT=YES PIC=MIX NCH='*0#.'

TTL=* "X-Y SLICE THROUGH ORIGIN" *

XUL=-8.34 YUL=0.0 ZUL=-9.764

XLR=8.34 YLR=-29.0 ZLR=-9.764

UAX=1.0 VDN=-1.0 NAX=130 END

END PLOT

END DATA

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 109 of 116

Listing 10. KENO-V.a Input Listing for Case 9 of Table 8

GAL161 100 G PU METAL; INFINITE ARRAY; SPHERICAL FUEL; RECTANGULAR PITCH

READ PARA

TME=120.0 GEN=153 NPG=407 LIB=41
FLX=NO FDN=NO AMX=NO FAR=NO
RUN=YES PLT=YES

END PARA

READ MIXT

MIX-1 94901 4.74882-2
94003 1.64930-3 94004 8.39647-4
MIX-2 6100 3.92100-3 26100 8.34910-2
MIX-3 301 1.0

END MIXT

READ GEOM

UNIT 1

COM=* CAN WITH FUEL OFFSET TO RIGHT AND TOP OF CAN *

SPHERE 1 1 1.06363 ORIGIN 7.245345 0.0 8.674095
CYLINDER 0 1 8.308975 2P9.737725
CYLINDER 2 1 8.334375 2P9.763125
CUBOID 0 1 4P8.334375 2P9.763125

UNIT 2

COM=* CAN WITH FUEL OFFSET TO LEFT AND TOP OF CAN *

SPHERE 1 1 1.06363 ORIGIN -7.245345 0.0 8.674095
CYLINDER 0 1 8.308975 2P9.737725
CYLINDER 2 1 8.334375 2P9.763125
CUBOID 0 1 4P8.334375 2P9.763125

UNIT 3

COM=* CAN WITH FUEL OFFSET TO RIGHT AND BOTTOM OF CAN *

SPHERE 1 1 1.06363 ORIGIN 7.245345 0.0 -8.674095
CYLINDER 0 1 8.308975 2P9.737725
CYLINDER 2 1 8.334375 2P9.763125
CUBOID 0 1 4P8.334375 2P9.763125

UNIT 4

COM=* CAN WITH FUEL OFFSET TO LEFT AND BOTTOM OF CAN *

SPHERE 1 1 1.06363 ORIGIN -7.245345 0.0 -8.674095
CYLINDER 0 1 8.308975 2P9.737725
CYLINDER 2 1 8.334375 2P9.763125
CUBOID 0 1 4P8.334375 2P9.763125

UNIT 5

COM=* ARRAY OF CANS STACKED TWO HIGH *

ARRAY 1 -16.66875 -8.334375 -19.52625
CUBOID 0 1 2P16.66875 2P8.334375 2P19.52625

GLOBAL

UNIT 6

COM=* ARRAY OF CANS STACKED TWENTY HIGH *

ARRAY 2 -16.67 -8.34 -195.28
REPLICATE 3 2 4*0.0 2*5.0 6
REPLICATE 3 8 5*0.0 5.0 6

END GEOM

READ START NST=0 END START

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 110 of 116

```
READ ARRAY
ARA-1 NUX-2 NUY-1 NUZ-2
FILL 1 2 3 4 END FILL
ARA-2 NUX-1 NUY-1 NUZ-10
FILL F5 END FILL
END ARRAY
READ BIAS ID=301 2 13 END BIAS
READ BOUNDS XYF=MIRROR END BOUNDS
READ PLOT
  PLT=YES PIC=MIX NCH=' *0#.'
  TTL=* "X-Y SLICE THROUGH FUEL" *
  XUL=-16.67 YUL=8.34 ZUL=-9.764
  XLR=16.67 YLR=-8.34 ZLR=-9.764
  UAX=1.0 VDN=-1.0 NAX=130 END
END PLOT
END DATA
```

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 111 of 116

Listing 11. KENO-V.a Input Listing for Case 14 of Table 9

USPR9 100 G U-233 METAL; INFINITE ARRAY; SPHERICAL FUEL

READ PARA

TME=120.0 GEN=153 NPG=407 LIB=41
FLX=NO FDN=NO AMX=NO FAR=NO
RUN=YES PLT=YES

END PARA

READ MIXT

MIX-1 92301 4.83300-2
MIX-2 6100 3.92100-3 26100 8.34910-2
MIX-3 301 1.0
MIX-4 502 0.05

END MIXT

READ GEOM

UNIT 1

ZHEMICYL+X 0 1 8.308975 2P9.737725
HOLE 4 0.0 7.224155 -8.652905
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 2

ZHEMICYL-X 0 1 8.308975 2P9.737725
HOLE 5 0.0 7.224155 -8.652905
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 3

ZHEMICYL+Y 0 1 8.308975 2P9.737725
HOLE 6 7.224155 0.0 -8.652905
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 4

HEMISPHE+X 1 1 1.084817

UNIT 5

HEMISPHE-X 1 1 1.084817

UNIT 6

HEMISPHE+Y 1 1 1.084817

UNIT 7

HEMISPHE-Y 1 1 1.084817

UNIT 8

ZHEMICYL+X 0 1 8.308975 2P9.737725
HOLE 4 0.0 7.224155 +8.652905
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 9

ZHEMICYL-X 0 1 8.308975 2P9.737725
HOLE 5 0.0 7.224155 +8.652905
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 10

ZHEMICYL+Y 0 1 8.308975 2P9.737725
HOLE 6 7.224155 0.0 +8.652905
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 11

ZHEMICYL-Y 0 1 8.308975 2P9.737725
HOLE 7 7.224155 0.0 -8.652905
ZHEMICYL-Y 2 1 8.334375 2P9.763125

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 112 of 116

```
CUBOID      4 1  2P8.334375  0.0 -28.8712  2P9.763125
HOLE        1  -8.334375  -14.4356  0.0
HOLE        3   0.0    -28.8712  0.0
HOLE        2  +8.334375  -14.4356  0.0
UNIT 12
ZHEMICYL-Y  0 1   8.308975  2P9.737725
HOLE        7   7.224155  0.0 +8.652905
ZHEMICYL-Y  2 1   8.334375  2P9.763125
CUBOID      4 1  2P8.334375  0.0 -28.8712  2P9.763125
HOLE        8  -8.334375  -14.4356  0.0
HOLE       10   0.0    -28.8712  0.0
HOLE        9  +8.334375  -14.4356  0.0
UNIT 13
ARRAY       1 -8.34  -29.0  -19.528
GLOBAL
UNIT 14
ARRAY       2 -8.34  -29.0  -195.28
REPLICATE   3 2  4*0.0  2*5.0  6
REPLICATE   3 8  5*0.0  5.0  6
END GEOM
READ START NST=0 END START
READ ARRAY ARA=1 NUX=1 NUY=1 NUZ=2
FILL 12 11 END FILL
ARA=2 NUX=1 NUY=1 NUZ=10
FILL F13 END FILL
END ARRAY
READ BIAS ID=301 2 13 END BIAS
READ BOUNDS XYF=MIRROR END BOUNDS
READ PLOT
  PLT=YES PIC=MIX NCH='*0#.'
  TTL=* "X-Y SLICE THROUGH ORIGIN" *
  XUL=-8.34 YUL=0.0 ZUL=0.0
  XLR=8.34 YLR=-29.0 ZLR=0.0
  UAX=1.0 VDN=-1.0 NAX=130 END
END PLOT
END DATA
```

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 113 of 116

Listing 12. KENO-V.a Input Listing for Case 18 of Table 9

LEADSLR 5000 G/L U-233;INFINITE ARRAY STACKED 20 HI;.02 LITER VOL, Pb

READ PARA

TME=170.0 GEN=153 NPG=407 LIB=41
FLX=NO FDN=NO AMX=NO FAR=NO
RUN=YES PLT=YES NUB=YES

END PARA

READ MIXT

MIX-1 92303 1.29227-3 92304 1.16304-3
502 0.674 402 0.0586
MIX-2 6100 3.92100-3 26100 8.34910-2
MIX-3 301 1.0
MIX-4 82100 3.296-2

END MIXT

READ GEOM

UNIT 1

HEMISPHE+X 1 1 1.68389 ORIGIN 0.0 5.355085 -6.783835
ZHEMICYL+X 0 1 7.038975 2P8.467725
ZHEMICYL+X 4 1 8.308975 2P9.737725
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 2

HEMISPHE-X 1 1 1.68389 ORIGIN 0.0 5.355085 -6.783835
ZHEMICYL-X 0 1 7.038975 2P8.467725
ZHEMICYL-X 4 1 8.308975 2P9.737725
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 3

HEMISPHE+Y 1 1 1.68389 ORIGIN 5.355085 0.0 -6.783835
ZHEMICYL+Y 0 1 7.038975 2P8.467725
ZHEMICYL+Y 4 1 8.308975 2P9.737725
ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 4

HEMISPHE-Y 1 1 1.68389 ORIGIN 5.355085 0.0 -6.783835
ZHEMICYL-Y 0 1 7.038975 2P8.467725
ZHEMICYL-Y 4 1 8.308975 2P9.737725
ZHEMICYL-Y 2 1 8.334375 2P9.763125
CUBOID 0 1 2P8.334375 0.0 -28.8712 2P9.763125
HOLE 1 -8.334375 -14.4356 0.0
HOLE 3 0.0 -28.8712 0.0
HOLE 2 +8.334375 -14.4356 0.0

UNIT 5

HEMISPHE+X 1 1 1.68389 ORIGIN 0.0 5.355085 6.783835
ZHEMICYL+X 0 1 7.038975 2P8.467725
ZHEMICYL+X 4 1 8.308975 2P9.737725
ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 6

HEMISPHE-X 1 1 1.68389 ORIGIN 0.0 5.355085 6.783835
ZHEMICYL-X 0 1 7.038975 2P8.467725
ZHEMICYL-X 4 1 8.308975 2P9.737725
ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 7

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 114 of 116

```
HEMISPHE+Y 1 1 1.68389 ORIGIN 5.355085 0.0 6.783835
ZHEMICYL+Y 0 1 7.038975 2P8.467725
ZHEMICYL+Y 4 1 8.308975 2P9.737725
ZHEMICYL+Y 2 1 8.334375 2P9.763125
UNIT 8
HEMISPHE-Y 1 1 1.68389 ORIGIN 5.355085 0.0 6.783835
ZHEMICYL-Y 0 1 7.038975 2P8.467725
ZHEMICYL-Y 4 1 8.308975 2P9.737725
ZHEMICYL-Y 2 1 8.334375 2P9.763125
CUBOID 0 1 2P8.334375 0.0 -28.8712 2P9.763125
HOLE 5 -8.334375 -14.4356 0.0
HOLE 7 0.0 -28.8712 0.0
HOLE 6 +8.334375 -14.4356 0.0
GLOBAL
UNIT 9
ARRAY 1 -8.34 -29.0 -195.28
REPLICATE 3 2 4*0.0 2*5.0 6
REPLICATE 3 8 5*0.0 5.0 6
END GEOM
READ START NST=0 END START
READ BOUNDS XYF=MIRROR END BOUNDS
READ BIAS ID=301 2 13 END BIAS
READ ARRAY ARA=1 NUX=1 NUY=1 NUZ=20
LOOP 8 1 1 1 1 1 1 1 20 1
      4 1 1 1 1 1 1 2 20 2
END ARRAY
READ PLOT
PLT=YES PIC=MIX NCH='*0#.'
TTL='*X-Y SLICE THROUGH ORIGIN*'
XUL=-8.34 YUL=0.0 ZUL=-9.764
XLR=8.34 YLR=-29.0 ZLR=-9.764
UAX=1.0 VDN=-1.0 NAX=130 END
END PLOT
END DATA
```

Listing 13. KENO-V.a Input Listing for Case 2 of Table 11

GALMIX1 PU METAL & SOL; INFINITE ARRAY STACKED 3 HI

READ PARA

TME=70.0 GEN=153 NPG=407 LIB=41
 FLX=NO FDN=NO AMX=NO FAR=NO
 RUN=YES PLT=YES

END PARA

READ MIXT

MIX-1 94906 2.29941-3 94907 8.91999-4 94009 5.44499-5
 94010 1.12818-4
 502 .8582 402 .0746
 MIX-2 6100 3.92100-3 26100 8.34910-2
 MIX-3 301 1.0

END MIXT

READ GEOM

UNIT 1

HEMISPHE+X 1 1 3.29610 ORIGIN 0.0 5.012875 -6.441625
 ZHEMICYL+X 0 1 8.308975 2P9.737725
 ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 2

HEMISPHE-X 1 1 3.29610 ORIGIN 0.0 5.012875 -6.441625
 ZHEMICYL-X 0 1 8.308975 2P9.737725
 ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 3

HEMISPHE+Y 1 1 3.29610 ORIGIN 5.012875 0.0 -6.441625
 ZHEMICYL+Y 0 1 8.308975 2P9.737725
 ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 4

HEMISPHE-Y 1 1 3.29610 ORIGIN 5.012875 0.0 -6.441625
 ZHEMICYL-Y 0 1 8.308975 2P9.737725
 ZHEMICYL-Y 2 1 8.334375 2P9.763125
 CUBOID 0 1 2P8.334375 0.0 -28.8712 2P9.763125
 HOLE 1 -8.334375 -14.4356 0.0
 HOLE 3 0.0 -28.8712 0.0
 HOLE 2 +8.334375 -14.4356 0.0

UNIT 5

HEMISPHE+X 1 1 3.29610 ORIGIN 0.0 5.012875 6.441625
 ZHEMICYL+X 0 1 8.308975 2P9.737725
 ZHEMICYL+X 2 1 8.334375 2P9.763125

UNIT 6

HEMISPHE-X 1 1 3.29610 ORIGIN 0.0 5.012875 6.441625
 ZHEMICYL-X 0 1 8.308975 2P9.737725
 ZHEMICYL-X 2 1 8.334375 2P9.763125

UNIT 7

HEMISPHE+Y 1 1 3.29610 ORIGIN 5.012875 0.0 6.441625
 ZHEMICYL+Y 0 1 8.308975 2P9.737725
 ZHEMICYL+Y 2 1 8.334375 2P9.763125

UNIT 8

HEMISPHE-Y 1 1 3.29610 ORIGIN 5.012875 0.0 6.441625
 ZHEMICYL-Y 0 1 8.308975 2P9.737725

NMSL: 90240
Engineer: MS001.3
Date: December 1991

Page: 116 of 116

```
ZHEMICYL-Y 2 1 8.334375 2P9.763125
CUBOID 0 1 2P8.334375 0.0 -28.8712 2P9.763125
HOLE 5 -8.334375 -14.4356 0.0
HOLE 7 0.0 -28.8712 0.0
HOLE 6 +8.334375 -14.4356 0.0
GLOBAL
UNIT 9
ARRAY 1 -8.34 -29.0 -29.2894
REPLICATE 3 2 4*0.0 2*5.0 6
REPLICATE 3 8 5*0.0 5.0 6
END GEOM
READ START NST=0 END START
READ BOUNDS XYF=MIRROR END BOUNDS
READ BIAS ID=301 2 13 END BIAS
READ ARRAY ARA=1 NUX=1 NUY=1 NUZ=3 FILL 8 4 4 END FILL
END ARRAY
READ PLOT
PLT=YES PIC=MIX NCH='*0#.'
TTL=* "X-Y SLICE THROUGH ORIGIN" *
XUL=-8.34 YUL=0.0 ZUL=-9.764
XLR=8.34 YLR=-29.0 ZLR=-9.764
UAX=1.0 VDN=-1.0 MAX=130 END
END PLOT
END DATA
```

END

**DATE
FILMED
6/16/92**