**The Development of Precipitated Iron
Catalysts with Improved Stability**

Contract DE-AC22-87PC79812

DOE/PC/79812--T5

**Hayim Abrevaya
UOP**

DE92 014628

**25 E. Algonquin Road
Des Plaines, Illinois**

**Technical Progress Report No. 8
(6/16/89-9/16/89)**

Contract Objective

The objective of this program is to identify the chemical principles governing the deactivation of precipitated iron catalysts during Fischer-Tropsch synthesis and to use these chemical principles in the design of catalysts suitable for slurry reactors. The performance targets are 88% CO+H₂ conversion with less than 1% deactivation/day for 1 month and a methane and ethane selectivity of no more than 7% (based on hydrocarbons and oxygenates only) at a space velocity of at least 2 normal liters per hr per gram iron (NL/hr/gFe) using a synthesis gas with 0.5-1.0 H₂:CO ratio in a slurry reactor.

Contract Tasks

- Task 1.0: Develop an integrated pilot plant
- Task 2.0: Evaluate a reference iron catalyst
- Task 3.0: Develop a baseline iron catalyst
- Task 4.0: Elucidate the deactivation chemistry for iron catalysts
- Task 5.0: Investigate catalyst chemistry approaches for improved stability
- Task 6.0: Write final report

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

PATENT CLEARED BY CHICAGO

OPC ON February 18, 1992

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MAY 09 1988

Scope of the Work

Previous work under this contract involved the following:

9/16/87-3/16/88

Task 3.0: four catalysts were prepared by precipitation at different pH levels and were characterized.

3/16/88-6/16/88

Task 1.0: the design work necessary for upgrading the existing fixed-bed pilot plant with slurry and Berty reactor testing capabilities was completed.

6/16/88-9/16/88

Task 3.0: a catalyst preparation plant was designed and constructed.

9/16/88-12/16/88

Task 2.0: experiments determined that the fused iron ammonia synthesis catalyst C-73-1-101 cannot be properly activated in situ in the fixed-bed pilot plant at the relatively low temperatures of 200-300°C, that are typical of the Fischer-Tropsch process.

Task 3.0: an experimental iron catalyst tested in the fixed-bed pilot plant was shown to have acceptable stability and higher than desired methane and ethane selectivity.

12/16/88-3/16/89

Task 2.0: the MCSG-4 catalyst from Mobil was shown to have unexpectedly low activity in the fixed-bed reactor test.

3/16/89-6/16/89

Task 3.0: the construction of the slurry autoclave pilot plant was completed, and an experimental iron catalyst was used for plant shakedown.

During this quarter (6/16/89-9/16/89), the filter assembly in the autoclave reactor was modified, and an experimental iron catalyst was tested with the new configuration under Task 3.0.

Experimental

The slurry-bed pilot plant was previously described in the technical progress report covering the period of 3/16/88-6/16/88. Four runs were conducted during this reporting period (Runs 2-5), of which only one, Run 5, was successful. The iron catalyst identification, the nature of the initial wax medium, the catalyst and initial wax weights, and the location and the pore size of the filter are summarized in Table 1. The catalyst and the C_{30} paraffin wax medium were loaded into the 1-liter-autoclave reactor at 120°C. The 4-liter-autoclave was not used for this work. The 1-liter-autoclave was pressure tested with N_2 at 120°C and 18 atm. After a successful pressure test, the pressure was lowered to 11 atm, and the temperature was increased to 280°C under N_2 flow. Synthesis gas was introduced at 280°C. The test conditions were changed several times during this run. Autoclave internal temperatures, pressures, feed compositions, feed rates, space velocities, and stirrer speeds in revolutions/minute (rpm) at different hr on-stream are also summarized in Table 1.

A new filter assembly was used in this work. The new assembly consisted of a ceramic filter at the end of a stainless steel tube. The tube passed through

the autoclave head and formed the gas and liquid exit line for the reactor. The distance between the bottom of the filter and the bottom of the autoclave was 4.625 inches. The filter nominal pore diameter was 0.15 μm , and the absolute diameter was 0.40 μm . The mechanical stirring of the slurry medium was achieved by an impeller at the end of a shaft that was connected to the bottom of the autoclave. The feed gas was introduced through a dip leg that extended to the bottom of the impeller.

Argon was present in the synthesis gas feed at about 6% (by mole) level and was used as an internal standard for determining conversions and light hydrocarbon selectivities according to the following expressions:

$$\text{CO Conversion, \%} = (((\text{CO}/\text{Ar})_{\text{feed}} - (\text{CO}/\text{Ar})_{\text{product}}) / (\text{CO}/\text{Ar})_{\text{feed}}) * 100$$

The CO + H₂ conversion was calculated in a similar manner. The calculation for carbon atom selectivity to CO₂ was:

$$((\text{CO}_2/\text{Ar})_{\text{product}} / ((\text{CO}/\text{Ar})_{\text{feed}} - (\text{CO}/\text{Ar})_{\text{product}})) * 100$$

The carbon atom selectivity to a hydrocarbon with n carbons, C_n, was:

$$((\text{C}_n/\text{Ar})_{\text{product}} * n / ((\text{CO}/\text{Ar})_{\text{feed}} - (\text{CO}/\text{Ar})_{\text{product}})) * (100 / (100 - \text{CO}_2 \text{ Selectivity})) * 100$$

The hydrocarbon and oxygenates carbon atom selectivities were normalized to a total of 100% to back out CO converted to CO₂.

Results and Discussion

The autoclave leaked during the beginning of Run 2. The leak problem could not be solved, and therefore, the test was terminated. Runs 3 and 4 were dedicated to measuring the temperature inside the thermowell, which extended vertically through the slurry medium. These measurements verified that the height at which the temperature showed a rapid drop corresponded, in fact, to

the transition between the liquid phase and the gaseous phase. This temperature drop can then be used to estimate the slurry level in the autoclave.

The results in Run 5 are summarized in Figures 1-6. A new catalyst activation procedure was used in Run 5, which involved 12 hr of 2 NL/hr/g Fe synthesis gas ($0.7 \text{ H}_2 : 1 \text{ CO}$) at 280°C and 11 atm. Temperature surveys taken in the thermowell at 14, 34, and 36 hr on-stream are illustrated in Figure 1, which also shows the autoclave configuration. These results indicate that the slurry height varied between 3.5 and 5 in. during these hours. After 17 hr, the test conditions were established at 1.5 NL/hr/g Fe, 257°C , and 14 atm. Under these conditions, a $\text{CO} + \text{H}_2$ conversion of about 70% was obtained with 2.8% methane selectivity, and 3.1% methane plus ethane selectivity.

In Run 5, a pressure drop developed across the ceramic filter as a result of the build-up of solid particles. The pressure in the exit line and in the high temperature, high pressure separator, therefore, had to be gradually lowered to maintain the autoclave internal pressure at the specified level. The pressure drop gradually increased from 0.2 to 2 atm during the first 30 hr, after which the increase in the pressure drop was much more rapid. At 39 hr on-stream, the pressure drop reached a level of 17 atm, which led to the disintegration of the filter. Significant catalyst loss occurred through the unfiltered exit line during the following hours.

In Run 5, the stirrer rpm was originally set at 3500. The stirrer speed was lowered to 1500 rpm after 33 hr on-stream. Subsequently, conversion dropped from 70% to about 40%. Several other rpm changes were made later in the run.

However, the effect of these changes on the conversion level can not be interpreted because of the loss of catalyst from the autoclave reactor following the disintegration of the filter.

Summary

A ceramic filter with a nominal pore diameter of 0.15 μ was used to drain the excess liquid from the autoclave reactor and to maintain a constant slurry level. The filter rapidly plugged and disintegrated during the test.

Table 1
Run Information

Run	Plant	Catalyst						Diluent			Rpm	Temp In °C	Filter		Press Out, atm	Feed					Hours																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
		Number	% Fe	Wt g	Vol, cc	Mesh	Nature	% Solids	Wt, g (max)	% H ₂			% CO	% Ar		H ₂ CO	Rate sec/min	N/ h/g Fe																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																

FIGURE 1
TEMPERATURE SURVEYS IN THE AUTOCLAVE IN RUN 5

FIGURE 2

EVALUATION OF PRECIPITATED IRON CATALYST 5709-119 IN SLURRY REACTOR - RUN 5

FIGURE 3

EVALUATION OF PRECIPITATED IRON CATALYST 5709-119 IN SLURRY REACTOR - RUN 5

FIGURE 4

EVALUATION OF PRECIPITATED IRON CATALYST 5709-119 IN SLURRY REACTOR - RUN 5

FIGURE 5

EVALUATION OF PRECIPITATED IRON CATALYST 5709-119 IN SLURRY REACTOR - RUN 5

FIGURE 6

EVALUATION OF PRECIPITATED IRON CATALYST 5709-119 IN SLURRY REACTOR - RUN 5

**DATE
FILMED**
7 127 192