**UR
LLE**

**1991 SUMMER RESEARCH PROGRAM FOR HIGH SCHOOL JUNIORS
AT THE
UNIVERSITY OF ROCHESTER'S
LABORATORY FOR LASER ENERGETICS**

STUDENT RESEARCH REPORTS

**PROGRAM DIRECTOR
Prof. David D. Meyerhofer**

APR 15 1992

SEPTEMBER 1991

LABORATORY REPORT NO. 228

Laboratory for Laser Energetics

**College of Engineering and Applied Science
University of Rochester**

1991 SUMMER RESEARCH PROGRAM FOR HIGH SCHOOL JUNIORS

AT THE

**UNIVERSITY OF ROCHESTER'S
LABORATORY FOR LASER ENERGETICS**

DOE/DP/40200--196

DE92 011316

STUDENT RESEARCH REPORTS

PROGRAM DIRECTOR

Prof. David D. Meyerhofer

LABORATORY FOR LASER ENERGETICS

University of Rochester

250 East River Road

Rochester, NY 14623-1299

Ten students participated in the 1991 summer high school student research program at the University of Rochester's Laboratory for Laser Energetics (LLE). The participants spent 8 weeks working and learning at LLE. They spent most of their time working on individual research projects. Each student was assigned a project, upon which he/she worked under the direct supervision of one of the staff members of the laboratory. The students, their high schools, and their projects are listed in Table 1. The program culminated in oral and written reports describing their work. The oral reports were presented at a symposium on 23 August 1991, at which the student's parents and teachers and members of the LLE staff were present. The written reports are collected in this volume. The students participated in a series of seminars designed to teach them some of the concepts underlying the work performed at LLE and went on tours of other facilities.

<p style="text-align: center;">Table 1 High School Students and Their Projects</p>		
Student	High School	Project Title
Roger Clark	Penfield	UV Alignment Table
Ana Cotto	Benjamin-Franklin	Neutron Yields Can be Measured by Using the Relative Gain of a Photomultiplier Tube
Robert Dick	Greece-Arcadia	Scattering in Isotropic and Anisotropic Media
Jeffrey Dvorin	Brighton	A Better Approximation of the Diffusion Equation
Mark D. Forbes	Pittsford/Mendon	Use of the SLAC Code to Produce a Photo-emissive Electrostatic Electron Gun
Elizabeth Randall	East	Spatial Resolution Deteriorates with Increasing Film Exposure
Franklin S. Turner	Rush-Henrietta	Analysis of Refractive Image Distortion
Helen Vayntrub	Brighton	Making of Pinholes for X-Ray Pinhole Cameras
Jeanne Yax	Nazareth	Does Perturbation Theory Accurately Describe Multiphoton Ionization?
Nora Yip	Webster	Wavefront Analysis using Shearing Interferometry

This is the third year that LLE has had a summer program for high school students. The goals of the program are to expose students who are interested in science, mathematics, or technology to real research in these fields, rather than the cookbook labs which they perform in their schools and to excite them about pursuing careers in this fields. Secondly, we hope that the enthusiasm generated by the program will be transferred to some of the student's peers. We have now had 24 students participate in the program.

This year's participants, all of whom had completed their junior years, were selected from 60 outstanding applicants from 23 local high schools. Each student sent a letter of application, an NSF applicant form, and a copy of their transcript. In addition, each student was required to have a letter of recommendation from a science or math teacher.

We plan to hold this program again during the summer of 1992. Requests for applications will be mailed out in March or April, 1992. If you would like more information about the program or an application form please contact the Program Director, Prof. David D. Meyerhofer, at the Laboratory for Laser Energetics.

This program was supported in part by the National Science Foundation under contract No. RCD-9055084 and by the U.S. Department of Energy Office of Inertial Confinement Fusion under agreement No. DE-FC03-85DP40200.

UV ALIGNMENT TABLE

by

ROGER CLARK

Penfield High School

Penfield, NY

UV Alignment Table

R. Clark 8/91

At the University of Rochester's Laboratory for Laser Energetics, laser fusion is taken seriously. The laboratory's job is to study the feasibility for laser fusion as a future energy source. The entire Omega laser system depends on optics to provide the energy to create fusion. The UV Alignment Table is used to provide a constant by which other optics can be measured. Measurements include energy losses of optics from the FCCs to the tank and transmission measurements of single optical elements. Another use is to check alignment drift, or the slow misalignment, of the UV portion of the Omega laser system.

My project began with familiarizing myself to the entire Omega system and learning the role my project fills. After I had a basic knowledge of the system, I began working with the adjustments on the UV Alignment Table to learn the responses and problem areas on the table. Most of the design of the table presented some problem or another from either a quality or reliability standpoint. Difficulties arose from the IR beam quality, the UV beam quality, a large amount of drift in the optics, and the operation of the Ar⁺ ion laser from Spectra-Physics.

The infrared beam on the UVAT is sent across the laser bay from the IR Alignment Table. After traversing the length on the bay and with the number optics, the beam quality is poor, making it difficult to use. To correct the problem some spatial filtering was tried with a 1:1 relay, but the results without a pinhole at the focus were limited. All these optics used up much needed space on the UV AT. The UV beam was also of poor quality (see figure 1). A large majority of the poor beam quality is attributable to the many aluminum optics in the up-collimator. The red dump coaligning the IR beam with the UV beam is also a source of beam degradation. The history of the red dump as a blast window in the tank placed many minute chips in the surface.

The drift of the beam is another large problem when taking sensitive measurements. Even a small movement of the beam, when amplified by the numerous reflections in the beam path, can move

the beam far enough to make all readings disappear. Another major problem of the UVAT is the Argon ion laser. My task of course was to rework the UVAT for ease in use and reliability, but this job is difficult given this laser as a UV source. From the start, this laser has had problems. It failed to work just after installation because the power supply plug inside fused together, shorting two of the three phases of the power supply. After that was fixed, there have been numerous problems tuning and getting a stable output from the laser. During my summer here, there was another problem. All indicators said the laser should work, but because of one 5 volts power supply missing, the laser failed to start. This incident put my project on hold for a week and a half. I began to troubleshoot the problem and found that if the proper signal was given to the tube firing board, the laser started. Even with this information, Spectra-physics could not figure out the problem. In the end, the laser cost over a week delay, \$450 for the service representative's plane fare, and untold aggravation (see diagram one).

The largest problem I wanted to remove is the long focal length up-collimator. To do so, a new lens designed for the blue region of the spectrum was needed. It was decided to use a damaged blue Omega focus lens. To remove the damage, however, required the lens being reground, and no company could be found that would grind and polish the lens. Kodak was suggested, to attempt to remove the damaged unstrippable coating using the new ion figuring process. Initial feelings were apprehensive, spending \$3200 to have the lens ion figured, but it was less than a fifth the replacement cost. The lens was measured for wavefront distortion, found to be about a third of a wave at 351nm, and was sent to Kodak. Two weeks later, the lens returned. The damage spots in the coating transferred to dull spots on the lens, but the rest of it looked very good. The next step will be to measure the lens again to see if the wavefront distortion is acceptable and all the coating was removed. If the lens checks out, it will be used in a new up-collimator in a newer version of the UVAT. Also, if the process was successful, Kodak may be used in the future to repair optics.

Next improvement to be made to the UVAT is the IR beam that was being received from the IR Alignment Table. Not only was the beam quality low, but the transport optics were restricting access to the UVAT and the beam sent across the laser bay was at eye level for some workers, an extreme danger. Fiber optics were studied as a replacement to this system. The array of mirror and lenses would be replaced with a fiber and a single output up-collimating lens, using the divergence of the beam from the fiber as the other lens. Most of

the studies were conducted in ODL next to the fiber patch panel. One day was spent setting up a fiber and learning how to cleave the ends, align the fiber, and maximize energy output. The first experiment began with black sheathed fiber. After the fiber was aligned, observation showed that the beam exit the fiber was elliptical. After question, it was found that the fiber was a polarization preserving fiber, and had an elliptical core to do so. This fiber was removed from the list of choices because polarization was not important, beam shape was important.

The next fiber was a roll of chirping fiber in ODL. This bare 4 micron core fiber was single mode, and because of the length tested, showed that it would not lose much energy over the 100 feet needed for the UVAT. The single mode was TEM₀₀, meaning it only retained the single gaussian mode(the shape of a bell curve), and all other modes were allowed to escape out of the jacket of the fiber. Both of the first two fibers worked on the principle of total internal reflection. The core of the fiber contained two different types of glass, each having a different refractive index. When the two were bonded together into a fiber, the junction of the two fibers, with different refractive indexes, acted a mirror. Any single beam of light striking the junction would be refracted back into the main core of the fiber.

Two more fibers were tested. The first was a gradient index fiber. The opposite of the other fibers, in this fiber the refractive index of glass core slowly varied across the radius of the fiber. This changed two properties of the fiber. One, the fiber did not reflect light back into the center, it slowly bent the light back into the core so the path of the light looked more like a sine wave than a triangle wave. The gradient index fiber also allowed all the modes to pass. The result was undesirable, but very interesting. The output beam looked like a spider web, a mesh of the mode entering the fiber overlapping. As the fiber was bent and repositioned, the pattern of output changed correspondingly. The final fiber tested had a yellow jacket, the fiber running from ODL to the probe lab. This fiber had a nice output beam, but the intensity was quite lower than that of the chirping fiber. At the same time, I tested an idea to use the single new blue Omega focus lens that Kodak was ion-figuring as the output for the up-collimator on both the IR and UV beams. A test in the probe lab with the 25th beam line lens appeared to up-collimate the IR just as well as the Red Omega focus lens.

I decided to go with a length of the chirping fiber for two reasons. First, the output was the best of all of the fibers I tested, and second it was the easiest to use because a sheathing did not have

to be stripped to cleave the fiber. After a day's delay finding if the patch panel will be moved to the driver line, I decided to run the fiber and set up the optic couple in one of the many pickoffs from the Antares. For protection, the fiber was pulled through 3/8" poly-flo tubing before it was run. With the fiber run, I was concerned the energy in the pickoff would be too much for the fiber. After some consultation and checking the energy with the Labmaster, installation was deemed safe for the fiber. With a threshold of 3W, the fiber is now receiving about 1.75W at 1054nm and I approximate its output a little below a watt, accounting for losses in the fiber and the removal of other modes.

With the fiber run and aligned and the argon ion laser working again, I began to work on the table for a new setup. To begin with, the locations of the optics were marked on the table if the new setup proved unusable. The table came clean, every optic was removed from it and transferred to the far-field table. I returned the optics to the UVAT as needed, starting with the first lens. Two more mirrors were brought back, then the 5m meter lens. After the basic UV beam path was set, the lenses were removed and the mirrors were aligned to the center of the beam path. With the mirrors set, the first lens returned, was backreflected, and locked into place. The 5m lens was brought back in and moved to achieve collimation, where the beam is neither converging or diverging. A look at the beam showed the angle on the table caused the beam to clip the mount of the 5m lens badly. Positions of the first mirror, first lens, and output lens were adjusted and finally gave a round beam at collimation. A picture was taken of the UV beam to record quality change. A lineout of the new scanned image was produced (Figure 2).

The IR beam was next constructed on the table. The fiber was mounted and placed on the near side of the argon ion laser pointing in the same direction. The red Omega lens was placed with aspherical side toward the fiber and collimated. Examination with a shear plate showed the result of Diagram 2, and following the beam along its path, the diameters of the beam did strange things. After further consultation, it was suggested to turn around the lens so the aspherical side was away from the fiber. When collimated, it produced the picture in Diagram 3. With both UV and IR beam set up on the table, I injected and coaligned the IR into the UV and the new design was sent off the table.

One problem remains, the mess pickoff, a 4% reflector for calibration, will be difficult to get on the table with the 5m lens so close to the end of the table. It may be possible to place it on the table as it is now, if the lens is skewed and it is not important to get

the total reflection into the integrating sphere. If the missing energy can be calibrated out, the table is fine as it is now. For a better reading, however, I believe that the table can be adjusted slightly to accommodate the mess pickoff. By moving the input lens to the up-collimator forward to the front of the laser table, moving the first mirror up a little more than half the change of the first lens, and adjusting the 5m lens to collimate, the focus lens for the integrating sphere and the sphere may fit behind the first mirror. If not another setup incorporating the blue Omega focus lens from Kodak, a microscope objective as the input to the up-collimator, and a pinhole can be used. A drawing of all three versions are included as Diagrams 4,5,6.

With the new design properly installed, the output quality should be satisfactory to last until the upgrade is installed. I highly recommend the use of fiber optics and something other than the argon ion gas laser. A good replacement for this would be a YLF or Nd:YAG or similar with a frequency tripling cell to produce ultraviolet. The solid state laser not only simplifies the system needed to run it, but allows in house repair as opposed to waiting for a company to show up. I'd would like to thank everyone at the lab, and especially my supervisors for making my experience a good one.

Figure 1: Lineout of original Wbeam cross section

Figure 2: Lineout of current UV beam cross section

Diagram 1:

The current Ar-ion laser is not reliable

Spectra-Physics
LASER PRODUCTS DIVISION
1250 WEST MIDDLEFIELD ROAD
MOUNTAIN VIEW, CA 94035
(415) 961-2550 TLX 348-488

ROCHESTER UNIVERSITY
ACCOUNTS PAYABLE DEPARTMENT
SUITE 260
1325 HOPE AVE.
ROCHESTER, NY 14620

ROCHESTER UNIV
LAB FOR LASER
C. FAHR
250 EAST RIVER
ROCHESTER, NY 14623

Spectra-Physics
SPECTRA-PHYSICS LASERS, INC.
1330 TERRA BELLA AVENUE
MOUNTAIN VIEW, CA 94035-70
(415) 961-2550 TLX 348-488

ROCHESTER UNIVERSITY
ACCOUNTS PAYABLE DEPARTMENT
SUITE 260
1325 HOPE AVE.
ROCHESTER, NY 14620

REPRESENTED BY RALPH SWAINE

ITEM	PRODUCT NUMBER	DESCRIPTION	QTY
1	2045E-20	20W UVS. 3.5W UV ARION LUT 515 S/N	S/N
	2045E-20	ML SYSTEM, ARION, UV, 4W	S/N
	024	PLASMA TUBE	S/N
	2570E	ML POWER SUPPLY MOD 2570E	S/N
	2470	ML REMOTE LINTROL	S/N

REPRESENTED BY RALPH SWAINE

351MM UVM FOR 2025/2045
ARCON OC, UVM, 364MM
MR HIRSH 480-514 5MM, 15.0MM
SALES ORDER SPECIAL INSTRUCTIONS:
CONTACT: DAN LEYER
PHONE: 716-278-0824

Spectra-Physics

Spectra-Physics

Spectra-Physics

ITEM NO	475020
USER	C. FAHR
COMP	UNIVERSITY
ADDRESS	250 EAST RIVER
CITY	ROCHESTER
STATE	NY
ZIP	14623
SP PRODUCT	2045E
PLASMA TUBE	024
POWER SUPPLY	2570E
REMOTE LINTROL	2470
WORK ORDER	1000
DATE	10/15/80
BY	1000
REMARKS	1000

ITEM NO	475020
USER	C. FAHR
COMP	UNIVERSITY
ADDRESS	250 EAST RIVER
CITY	ROCHESTER
STATE	NY
ZIP	14623
SP PRODUCT	2045E
PLASMA TUBE	024
POWER SUPPLY	2570E
REMOTE LINTROL	2470
WORK ORDER	1000
DATE	10/15/80
BY	1000
REMARKS	1000

ITEM NO	475020
USER	C. FAHR
COMP	UNIVERSITY
ADDRESS	250 EAST RIVER
CITY	ROCHESTER
STATE	NY
ZIP	14623
SP PRODUCT	2045E
PLASMA TUBE	024
POWER SUPPLY	2570E
REMOTE LINTROL	2470
WORK ORDER	1000
DATE	10/15/80
BY	1000
REMARKS	1000

RE REQUIRED FOR THIS ORDER
UNITED STATES

SERVICE REPORT

RECEIVED
DATE 10/15/80
BY 1000

SC NO	IR NO	PAGE	OF
2614025	2614025	21	21

Diagram 2: Interference lines of a lens that was put in backwards

Diagram 3: Interference lines of a properly collimated beam

Diagram 4:

ORIGINAL UVAT

96.125 IN

36.000 IN

Diagram 5

CURRENT UVAT

96.125 IN

36.000 IN

Diagram 6:

PLANNED UVAT

**NEUTRON YIELDS CAN BE MEASURED BY USING THE
RELATIVE GAIN OF A PHOTOMULTIPLIER TUBE**

by

ANA COTTO

Benjamin-Franklin High School

Rochester, NY

Neutron yields can be measured by using the relative gain of a Photomultiplier Tube

During this summer I had the opportunity to work at the Experimental Division of the Laboratory for Laser Energetics. The project that I worked at was Photomultiplier Tube Calibrations. With the help of my supervisor, Marie Russotto I began to comprehend what was expected of me. My objective was to be able to know the relative gain of a Photomultiplier Tube at various bias voltages, therefore the lab would be able to: measure neutron yield by comparing the neutron detector's Photomultiplier Tube signal taken at any gain with the detector's neutron calibration, also to be able to calibrate the neutron detector in any place by turning the detector's Photomultiplier Tube (PMT) gain down.

The way that it related to the Omega target is that as the target imploded the fusion reaction produced neutrons, which were detected by the liquid scintillator and converted into light. A liquid scintillator is where the neutrons are converted into light, this happens when a neutron goes into a scintillator it contacts with an atom this atom scatters the neutron and releases protons, then these protons are converted into light. The amount of light that is produced at the scintillator is directly proportional to the number of neutrons which hit the scintillator. The Photomultiplier Tube converts the light from the scintillator into an electrical signal. Which is what we use to make calibration here at the lab (see diagram 1).

The experimental set up that I used was a flashlamp setup which we use to be able to do a controlled experiment which reproduces the effect of light on a PMT (see diagram 2). First there was the flashlamp which substituted the work of the scintillator. What a flashlamp does is instead of converting neutrons into light it has a trigger which fires the flashlamp. The photodiode that's attached to

the flashlamp is the instrument that makes sure that the flashlamp has a constant light output.

Another instrument that I worked with was the filter box, this is where the neutral density filters are placed. The neutral density filters are like square glass plates that enable us to decide how much light goes from the flashlamp to the Photomultiplier Tube, they come in different values such as .3, .7, 1, 2, 3, 4 and 9 from this number we derive different numbers like five and six. Since we are able to accommodate up to three different filters in the filter box we can arrange to have almost any number value. The filter box task is to make sure that no stray light enters the Photomultiplier Tube. Inside the filter box the neutral density filters are almost completely covered, since the less stray light that hits the Photomultiplier Tube the more accurate the results are.

The most important piece of this set up was the Photomultiplier Tube. The Photomultiplier Tube converts light signals that typically consist of no more than a few hundred photons into usable current pulse without adding a large amount of random noise to the signal. The Photomultiplier Tube has it's own procedure, first the light that comes from the flashlamp hits the semitransparent photocathode in which the light is converted into electrons, afterwards the focusing electrodes guide the electrons to the first dynode which releases up to ten electrons for each electron which hits it. Each of these electrons hits the next dynode and produces more electrons. The electrons are multiplied through sometimes up to twelve dynodes depending on the type of the Photomultiplier Tube. Then the electron signal is collected at the anode where the signal is transmitted through a cable to the oscilloscope which is an instrument that measures and displays electrical signal (see diagram 3).

On the oscilloscope we get a pulse from the Photomultiplier Tube. The scintillator/PMT combination can detector the X-rays and gamma-rays as well as neutrons signal (see diagram 4). The shot represented here comes from the LARD scintillator which is one of

the scintillators at the Omega Target Chamber. On this pulse we can see the neutron yield of this specific shot.

The procedure for this Photomultiplier Tube test facility was simple. First the flashlamp would be triggered from either the computer or the nine volt pulser. Then the light from the flashlamp would be filtered by the neutral density filters in the filter box. Afterwards the light would hit the Photomultiplier Tube and convert into electrons then the signal from the anode would go through the cable to the oscilloscope. From the oscilloscope we would get a pulse and then I would sort out the data in the computer and analyze it. After I graph the data that I obtained from the experiment I would give it to Marie and she would analyze it even deeper.

To be able to properly analyze this different data that I took from the PMT, Marie taught me a few equations to help me. First there was the equation of charge depending on filter value (see graph a). This just said that;

$$Q = k * (1/10^f)$$

Where

Q = Charge of PMT pulse

k = charge of previous PMT pulse

**f = filter value that I used
minus filter value that
I was going to use**

For example : If I had used a filter value of .3 and I was going to use a filter value of 1.

$$Q = k * (1/10^{.7}) =$$

Additionally to the preceding equation I also needed to know the slope of the Photomultiplier Tube (see graph b). This equation allows you to convert the PMT charge at one gain into the PMT

change at another gain. To be capable of doing so I followed the following equation:

$$Q_{800}/Q_{1200} = S_{800}/S_{1200}$$

Where

Q = Charge of PMT pulse

S = Slope of PMT pulse

Furthermore I had to find the saturation point of every PMT bias voltage which is the region in which increasing the amount of light on the photocathode cannot increase the current because the dynodes cannot produce anymore secondary electrons. There wasn't a specific equation for this all I had to do was plot the Photomultiplier Tube bias voltage against the filter value where it is saturated (see graph c). In the graph of the saturation point we can see that the Photomultiplier tube at a low bias voltage will saturate with a greater amount of light then if it was at higher voltage. In a more simple what, the PMT at a low bias voltage can detect more light and therefore more neutrons without saturating than a PMT at a higher voltage.

As a result of this experiment I came to the conclusion that now knowing the relative gain of a PMT at various bias voltages allows us to: measure neutron yield by comparing the neutron detector's neutron calibration, also to calibrate the neutron detector in place by running the detector's PMT gain down. Therefore a wide range of neutron yields can be measured from Omega target experiments by taking advantage of the full range of sensitivity of the detector's Photomultiplier Tube.

Relation of PMT with the Omega target

UR
LLE

diagram 1

Experimental setup for PMT relative gain measurement

Photomultiplier Tube¹

diagram 3

¹ Jenhins, Francis A. and White, Harvey E.,
Fundamentals of optics, p.702

The PMT output of a DD target shot

graph a

PMT output at -1600 V bias

graph b

graph c

Example of neutron yield calculation

*Calibrate: $C = 3.006 \times 10^5 \text{ n/V-ns}$ @ -1200V

*Shot # 21534:

PMT @ -1600 V

Charge = 6.208 V-ns

*Use calibration and gain data to find neutron yield:

Convert charge at -1600V to a charge at -1200V

$$Q_{1200} = S_{1200} (1/10^f)$$

$$Q_{1600} = S_{1600} (1/10^f)$$

Divide:

$$Q_{1200} = S_{1200}/S_{1600} (Q_{1600})$$
$$Q_{1200} = 1.89 \times 10^{-5} / 1.36 \times 10^{-4} (6.208 \text{ V-ns})$$

$$Q_{1200} = 0.863 \text{ V-ns}$$

Neutron Yield:

$$Q_{1200} \times C = (.863 \text{ V-ns}) (3.006 \times 10^5 \text{ n/V-ns}) = 2.53 \times 10^5$$

SCATTERING IN ISOTROPIC AND ANISOTROPIC MEDIA

by

ROBERT DICK

Greece Arcadia High School

Rochester, NY

Summary - A data smoothing program using two smoothing techniques was written. The angular intensity distribution of 633 nm HeNe laser light incident on opal glass, ground glass, dentine, and enamel was measured. The intensity distribution of light passing through and being reflected from dentine and enamel was digitized and analyzed.

I. INTRODUCTION

Over the summer I have worked with Wolf Seka to write a data smoothing program and examine the behavior of light in isotropic and anisotropic media. The data smoothing program, although effective, proved unnecessary due to the exceptional quality of the data acquired throughout the experiments.

The information acquired through the following experiments may prove useful in the further study of the behavior of light in organic tissue. The data acquired here has potential to be of use in laser dentistry in the future but there are no present applications in this field.

II. DATA SMOOTHING

The data smoothing program was written in the PV-Wave programming environment. It allows the user to choose between one of two data smoothing methods, triangular or polynomial. The first is recommended for reasons that will become apparent later. There are a few restrictions on what the smoothing program can process. The data to be smoothed must be a two column array and the first term must be the number of rows.

ex:

4.0		
	7.8	1.5
	7.6	1.9
	7.4	2.6
	7.2	3.1

Triangular smoothing is considerably simpler than polynomial smoothing. It averages vectors from the origin to the first three data points to find the approximate midpoint of the triangle that would be formed if the points were connected. It then moves on to the

next adjacent set of three points and repeats this process as shown in figure 1. All the approximate midpoints are stored in an array for future use. One of the advantages of this smoothing method is its strength when working with unevenly spaced data points. This is, however, also a weakness because data processed by this smoothing method is invariably unevenly spaced. Another strength of this program is its flexibility. The user can select a number of recursions of this process through which the data will be put. Thus, data can be heavily or lightly smoothed, depending on the interest of the user. Such flexibility makes this an effective smoothing routine as can be seen in figure 2.

The second smoothing method implemented in the program is polynomial smoothing. This procedure relies heavily on the POLY_FIT function of PV-WAVE. It takes a number of points (x) on either side of a center point (y) and matches their shape (with the least square fit method) to a polynomial with degree (z). In the above description x is a user defined variable, y is a number that starts at x+1 and proceeds to the number of elements in the array to be smoothed - x+1, and z is an arbitrary user defined number. Typically the variable z = 2. This method of smoothing works but has significant restrictions. It produces significantly different results when the user defines different parameters and it is prone to "overshoot" if the user is not careful when defining parameters. This smoothing procedure has one advantage over the triangular smoothing method. It does preserve the original spacing of data.

III. SCATTERING IN DENTAL HARD TISSUE : THEORY

Dental tissue is a translucent material that exhibits anisotropic scattering properties [1], [2]. Studies of dentine and enamel (integrating sphere) show that they absorb very little light. A photon of 633 nm light, on the average, experiences at least one scattering event when traveling through human dentine with a thickness of over 0.011 mm [2]. The samples used in these experiments were on the order of 0.15 mm thick. Direct transmission, therefore, can be considered insignificant. The remaining paths of light are immediate reflection, backscattering and forwardscattering as shown in figure 3. Of these, forwardscattering was found to be the most intense.

Forwardscattering through dental tissue is not as simple as it

would be in a less organized medium. A very intense diffraction pattern is observed in transmitted and backscattered light when a laser is shone upon dentine or enamel. This pattern is aligned perpendicular to the crystalline structure of the tooth. These crystals radiate from the center of the tooth to the edges [2], as can be seen in figure 4. It seems reasonable that this pattern is the Fraunhofer diffraction pattern that is expected when light passes through diffraction grating. The slits between the crystals in the dentine and enamel act as a such a grating [2].

IV. MATERIALS AND METHODS

The materials that were available had varying degrees of quality. The dentine and enamel samples were not particularly uniform. Their thicknesses varied from approximately 0.13 mm to 0.25 mm. The effects of this roughness can be most clearly seen in data taken with a highly focused beam.

Data on absorption was taken with an integrating sphere with an efficient scattering material placed over the majority of its opening. The sample was placed inside the integrating sphere and aligned so that the specular struck the inside of the sphere. A beam of 633 nm laser light was then focused on the sample with a 25 cm convex lens. The actual intensity was read from the photo-diode nested in the integrating sphere with a voltmeter.

Data on angular intensity distribution was taken with a setup involving a photo-diode on a freely rotating arm. A schematic of this setup can be seen in figure 5. The HeNe laser was aimed 110 cm through a line-synchronized chopper and a filter box to a mirror. It was then reflected to a 25 cm focal length convex lens and focused onto the sample. The exact position of the convex lens was changed to study the behavior of tightly and loosely focused light. The actual readings of intensity were taken by a photo-diode located on an arm that rotated freely about the sample. A lock in amplifier was used to increase the signal-to-noise ratio.

It became necessary to establish a more tightly focused beam so this setup was eventually modified. In the alternate setup the HeNe laser was spatially filtered and upcollimated using a convex lens. The beam then traveled approximately 32 cm in its collimated state to arrive at a focussing convex lens with a focal length of 25 cm. The

sample was placed at the point and angular intensity readings were taken with the same photo-diode used in the previous setup. This data was manually entered into a Sun work station for easier manipulation.

Forwardscattered and backscattered intensity distribution were measured with a CCD camera connected to a roving Epson computer running digitizing software. The basic setup for image digitization was basically the same as the spatially filtered setup used above with the addition of a camera and an objective. This setup can be seen in figure 6. For forwardscattered intensity digitization a 5X microscope objective was placed 3 cm from the sample and a CCD camera was placed 16 cm from the objective. For backscattered image collection a cube beam splitter was placed 0.3 cm in front of the sample and the camera and objective were placed perpendicular to the beam incident on the sample at a distance of 0.3 cm from the beam splitter.

Whenever possible the dental sample was oriented with its crystalline structure horizontal so that the diffraction pattern was oriented vertically. By blocking the diffraction pattern and interpolating intensity based on average intensity in some of the experiments, it was concluded that the diffraction pattern is responsible for approximately 60% of the intensity when the photo-diode was located at zero degree. (i.e. directly opposed to the laser beam)

V. RESULTS

Dentine's absorption is shown to be negligible in the integrating sphere experiment. The difference in total intensity of light first passing through dentine and light directly striking the integrating sphere is well within the bounds of experimental error. It was found that dentine is a strongly forwardscattering media. This behavior is evident in figure 7. The intensity of the forwardscattered component of dentine's intensity is approximately 11.8 times the intensity of the backscattered component. The intensity distribution for dentine is by no means lambertian (isotropic) but instead is sharply forward peaked, partially due to the high intensity diffraction pattern. This diffraction pattern is evident in light passing through and being backscattered from dental tissue and causes the forward intensity peak for dentine to be 1.6 times as high as it would otherwise be. Enamel

is found to behave similarly to dentine but has a somewhat higher forward intensity peak as seen in figure 8. The crystalline structure of dentine causes the intensity distribution of transmitted light to be biased if the location of the incident beam is off center. Similar effects are seen if a vertical cross section of dental tissue is rotated.

DISCUSSION

Dental tissue's crystalline structure is partially responsible for its anisotropic behavior. This can be seen in the change in bias of angular intensity distribution accompanying a change in beam position or sample orientation. This asymmetry in transmitted and reflected light is shown in figures 9 and 10. The presence of a high intensity diffraction pattern that has strong bearing on the forward component of the angular intensity distribution also leads one to the belief that this crystalline structure influences dental tissue's scattering properties. The presence or absence of water on dental tissue affect the intensity distribution of light incident on it. Purely qualitative observation shows the intensity of the specular to be almost as high as that of the forwardscattered component when dentine is slightly wet. Enamel does not exhibit this behavior to the degree that dentine does.

REFERENCES

- [1] Brian C. Wilson and Steven L. Jacques, "Optical Reflectance and Transmittance of Tissues: Principles and Applications," *IEEE Journal of Quantum Electronics*, vol. 26, pp. 2186-2199, 1990.
- [2] J.R. Zijp and J.J. Ten Bosch, "Angular Dependence of HeNe-Laser Light Scattering by Bovine and Human Dentine," *Archs. oral Biol.*, vol. 36, pp. 283-289, 1991.

The computer separates the data into triangles and then finds approx. midpoints

Figure 1 - (left) The computer averages vectors from the origin to three adjacent data points to find the approximate midpoints of the triangles thus formed.

(right) Smoother data results.

Figure 2 - (left) Data on angular intensity distribution for light incident on opal glass is intentionally made noisy.

(right) This data is smoothed by the smoothing program and compared to high quality data. They conform closely.

Figure 3 - Light incident on scattering media can behave in a number of different ways.

Figure 4 - Dental tissue exhibits a crystalline structure radiating from the center of the tooth. This structure continues to the edge of the tissue.

Figure 5 - Schematic setup used to examine angular intensity distribution for light incident on opal glass, dentine and enamel.

Figure 6 - Schematic setup used to digitize transmitted intensity distribution for dentine. It is similar to the setup used to digitize back scattered intensity distribution but lacks the cube beam splitter.

Figure 7 - (left and right) Angular intensity distributions for light passing through opal glass and dentine. The differences in behavior between light in opal glass and light in dentine are readily apparent.

Figure 8 - Plot of intensity vs. angle for light incident on dentine and enamel. Although dentine and enamel behave similarly, enamel does have a higher forward scattered intensity.

Figure 9 - (top) The images, from left to right, show the intensity distribution of light passing through dentine for laser beams striking to the left, top, and right of the center of a horizontal cross section of dentine.

Figure 10 - (left) Angular intensity distribution of light incident on dentine for beams striking in different positions on the sample. Dotted is beam right, solid is center, and dashed is left. The asymmetries in this plot and the images in figure 9 are caused by the radial crystalline structure of dental tissue.

**A BETTER APPROXIMATION OF THE DIFFUSION
EQUATION**

by

JEFFREY DVORIN
Brighton High School
Rochester, NY

Introduction:

As every day passes, the world's energy supply diminishes further, and the destruction to the environment continues. The need for a clean, and virtually endless supply of energy grows daily. At the Lab for Laser Energetics at the University of Rochester, a major effort to remedy this impending energy crisis has been undertaken.

The primary work at the Laboratory for Laser Energetics centers around the process of nuclear fusion. Specifically, the laboratory is striving to perfect inertial confinement, direct-drive laser fusion. Fusion is one of the most basic nuclear processes that sustains life on earth. Nuclear fusion is the reaction that keeps the sun burning and emitting solar radiation. Nuclear fusion is a process in which the nuclei of two relatively light atoms are forced to fuse together. The newly formed nucleus has a mass slightly less than the original two nuclei. The mass loss is converted to kinetic energy and gives high velocities to emitted particles. Typically, deuterium and tritium are used as fuel for the fusion reaction, although other particles can be used.

In order for fusion to occur successfully, several extreme conditions must be produced. The deuterium-tritium(DT) fuel must be heated to enormous temperatures, on the order of 100,000,000 degrees Kelvin. The DT fuel must also be compressed under extreme pressure. These two conditions are achieved by the Omega Laser system, a twenty-four beam, twelve terawatt laser. The laser is focused symmetrically around a target filled with the DT fuel. The fusion reactions at the Laboratory for Laser Energetics are categorized as inertial confinement and direct approach reactions. The direct-drive simply means the laser actually strikes the target directly. Inertial confinement refers to the method of confinement. The DT fuel is heated and compressed so rapidly that the inertia of the particles keeps the mixture from exploding outward.

An important aspect of the research performed at the Lab for Laser Energetics is strictly on a theoretical basis. It is very important to have computer programs, or codes, that can accurately simulate different processes of the laser fusion reaction. Computer codes can be both time and money saving. A computer code can be

run to test the possible success of laser fusion under a given set of conditions. Results of the laser fusion can be determined without ever manufacturing a feasible target or even firing any lasers. Possible fuels can be tested for feasibility, and many can be ruled out before experiments with lasers are performed.

The codes are often complex and time consuming on the large supercomputers. Reducing computer time and producing accurate results are among the most important concerns when programming a computer code.

The simulations of laser fusion must address and deal effectively with the movement and behavior of energy. As the Omega laser strikes the target, large amounts of energy move throughout the target. Radiative energy from the photons in the laser deposit energy on the surface of the target. Some of this energy is absorbed, while some of the energy is transmitted into the inner layers. The outer layers heat rapidly and expand outward. By Newton's third law, this expansion pushes the inner core with tremendous pressure. The rapid increase in temperature and pressure causes the beginning of thermonuclear burn, as the DT fuel undergoes nuclear fusion. Once thermonuclear burn is achieved, energy rapidly appears in the core of the target. This energy moves to the outer layers of the target. The complex movement of thermal and radiative energy is very important when designing a code to simulate laser fusion.

The Diffusion Equation:

One method of dealing with the movement of energy, is through the use of the diffusion transport equation. This equation deals effectively with radiation energy transport. The diffusion equation is a second-order, linear, non-homogeneous differential equation. In the typical form of the equation,

$$\left(\frac{1}{c}\right)\left(\frac{\partial \Phi_v}{\partial t}\right) = \epsilon_v - \kappa_v \Phi_v + \frac{1}{3} \nabla \cdot \left(\frac{1}{\kappa_v} \nabla \Phi_v \right) \quad (1)$$

where Φ_v is the energy density, ϵ_v is the emissivity, and κ_v is the opacity, the transport of energy is considered in three dimensions and can be very complex. This equation describes the behavior of the radiative energy near some frequency v . The energy density, Φ , is the amount of energy in a given volume. The units of energy density are ergs per cm^3 . The emissivity, ϵ , is the amount of energy resulting from the emission of photons. For example, as electrons in the heated material return from an excited state to the ground state, photons of energy equal to the electrons' change in energy are spontaneously emitted. The opacity, κ , is proportional to the energy density. The product of the opacity and the energy density is the amount of energy that is absorbed in a given volume. The third part of equation (1) is the diffusion term. This term describes the movement of energy from one spatial zone to neighboring spatial zones. When the diffusion equation is only considered in one dimension the equation simplifies to:

$$\left(\frac{1}{c} \right) \left(\frac{\partial \Phi_v}{\partial t} \right) = \epsilon_v - \kappa_v \Phi_v + \left(\frac{1}{3\kappa} \right) \left(\frac{\partial^2 \Phi_v}{\partial x^2} \right) \quad (2)$$

where κ is assumed to be constant in a zone.

This equation is only an effective and accurate description of the transport of energy if the change in time, or the time step, is arbitrarily low (approaching zero), and number of spatial zones is arbitrarily large (approaching infinity). These two conditions serve to set ∂x and ∂t equal to, or very close to, zero. In order to make the diffusion equation effective in computer codes, a numerical method must be created to deal with a finite difference approximation of equation (2). Methods exist that approximate the diffusion equation with a reasonable time step and number of spatial divisions, or zones. These methods describe the motion of energy from one zone to the next. A new method must be developed with greater accuracy. Figure (1) shows the basic setup for the derivation of the new averaging method. The derivation of the new method uses the transport of energy from zone j to zone $j+1$ and zone $j-1$. Once the

method is examined using this method, it can be applied to more general situations with a reasonable number of spatial zones and a given time step. By differencing equation (2) in one-dimensional space over the volume of zone j , the equation,

$$V_j \left(\frac{1}{c} \frac{\partial \Phi_{v,j}}{\partial t} - \epsilon_{v,j} + \kappa_{v,j} \Phi_{v,j} \right) = D_{v,j-\frac{1}{2}} (\Phi_{v,j} - \Phi_{v,j-1}) - D_{v,j+\frac{1}{2}} (\Phi_{v,j+1} - \Phi_{v,j}) \quad (3)$$

is derived, where V_j is the volume of zone j , where $\epsilon_{v,j}$, $\kappa_{v,j}$, and Φ_v are the average values for the respective zone, and where D the diffusion coefficient. The diffusion coefficient at $j+1/2$ is,

$$D_{v,j+\frac{1}{2}} = \frac{2 \left(R_{j+\frac{1}{2}} \right)}{3(R_j + R_{j+1}) \kappa_o} \quad (4)$$

where A is the area of the interface between zones, R is the radius of the respective zone, and κ_o is the opacity of the interface.

All of the quantities in equation (3) are known, or can be calculated from known physics, the physical conditions in each zone, and other techniques. The question of technique that is the focus of our work exists in the diffusion coefficient. The value of the diffusion coefficient depends on a reasonable value for κ_o , the effective opacity at the interface. This value is often poorly estimated using simple averaging methods. A new method for averaging κ_o from $\kappa_{v,j}$ and $\kappa_{v,j+1}$ must be derived.

The simplest methods for averaging include

$$\frac{1}{\kappa_0} = \frac{1}{2} \left(\frac{1}{\kappa_{J+1}} + \frac{1}{\kappa_J} \right) \quad 5a)$$

or,

$$\frac{1}{\kappa_0} = \left(\frac{2}{\kappa_{J+1} + \kappa_J} \right) \quad 5b)$$

or similar equations where the optical depth, τ ,

$$\tau_{v,J} = \kappa_{v,J} R_J \quad (6)$$

is used instead of the opacity.[1] The optical depth is the product of the opacity and the thickness of each zone. As a unitless measure of opacity, the optical depth is an excellent quality to describe a material's ability to transmit energy. These simple averaging methods work correctly when the energy density has a steady gradient and no large discontinuities in opacity exist. At an interface between an optically thick zone, one that is relatively opaque, and an optically thin zone, one that is relatively transparent, these simple averaging methods can become invalid.

Equation (5a), referred to as the harmonic mean, has major problems at strong discontinuities in opacity. In Equation (5a), the lesser of the two opacities is strongly favored. Since the average of the opacity is the sum of two separate reciprocals, the more transparent, or optically thinner, zone is strongly favored. When the interface of an opaque zone and a transparent zone is considered, the harmonic mean will effectively give the interface the same opacity as the optically thin zone.

On the other extreme, equation (5b), or the arithmetic mean, is also a poor averaging method at strong discontinuities in opacities. The arithmetic mean strongly favors the more opaque of the zones at an interface. At an interface between a relatively opaque zone and a transparent zone, the effective interface opacity, κ_0 , will assume the characteristics of the opaque zone and allow very little

radiation to pass into the transparent zone. A new method that considers more than just the opacities of the neighboring zones must be derived.

The new averaging prescription for κ_0 is derived with the assumptions that the average energy density of each zone is known, that the zone thicknesses are known, and that the opacity is uniform throughout a zone. Graphically displayed, these values will define a step function for the energy density, see figure (2), but at strong discontinuities the step function is often ineffective. The step function approximation for the energy density is only accurate as the number of zones becomes arbitrarily large and the time step becomes arbitrarily small. The number of zones or time steps can often be a limiting factor when running the approximation in a computer code where speed and limited memory space are important. There are different types of zone interfaces, and the cases must be dealt with differently. The first type of zone interface is between two zones that are relatively transparent, or the interface between two optically thin zones.

In order to derive a better expression for the opacity at the interface, the energy current, J , must be considered across the interface. The energy current must be a reasonable number across the interface (it can not be infinite). The energy current must also be a continuous function across the interface. The energy current slightly before the interface in one zone must be approximately equal to the energy current slightly after the interface in the next zone. The energy current, J , across the interface can be defined in terms of the step function of the energy density as

$$J = \frac{2}{3\kappa_0} \left(\frac{\bar{\Phi}_1 - \bar{\Phi}_2}{R_1 + R_2} \right) \quad (7)$$

where Φ_1 and Φ_2 are the average energy densities of the respective zones. The energy current just to the right and left of the interface can also be written in terms of the energy density step function

$$J_1 = \frac{2}{3\kappa_1} \left(\frac{\bar{\Phi}_1 - \Phi_0}{R_1} \right) \quad (8a)$$

and

$$J_2 = \frac{2}{3\kappa_2} \left(\frac{\Phi_0 - \bar{\Phi}_2}{R_2} \right) \quad (8b)$$

where J_1 , J_2 , κ_1 , and κ_2 are the current and opacity of the respective zone, and Φ_0 is the assumed energy density at the interface. Since the energy current must be continuous across the interface, the three equations (7,8a,8b) can be set equal to each other. From the expression $J = J_1 = J_2$, the only two unknowns are Φ_0 and κ_0 . With simple algebra, an expression for κ_0 can be developed. The expression for κ_0 is

$$\kappa_0 = \frac{\tau_1 + \tau_2}{R_1 + R_2} \quad (9)$$

which is the same as eq. (5b). This expression for κ_0 is only valid at the interface between two optically thin zones.

At the interface between two zones with strong differences in opacities, there is a different situation. If zone 1 is assumed to be optically thin, then the energy current is still equal to eq. (8a) throughout the zone. The equation for the energy current across the interface, eq. (7), is also the same. Zone 2 is assumed to be optically thick and now has a different profile. The energy density in opaque zones is typically assumed to have an exponential profile, and from the exponential profile the energy current becomes

$$J_2 = \frac{1}{\sqrt{3}} (\Phi_0 - \bar{\Phi}_2) \quad (10)$$

and this now gives a different value for κ_0 .

$$\kappa_0 = \frac{\tau_1 + \frac{2}{\sqrt{3}}}{R_1 + R_2} \quad (11)$$

In this situation, the optical depth of the opaque zone is given an upper limit. This upper limit serves to allow some energy to penetrate the interface even if the mean free path of the energy is much shorter than the physical thickness of one zone.

The interface between two optically thick zones may present a different situation. The equation for κ_0 may contain an upper limit for both τ_1 and τ_2 . Equation (9), for the interface of two optically thin zones, may also work for two optically thick zones.

As the derivation of κ_0 becomes more complex, a flux limiter must be added to the averaging prescription. Since κ_0 is in the denominator of the diffusion coefficient, it must not be allowed to approach zero. As κ_0 approaches zero or $R_1 + R_2$ approaches zero while the absolute value of $\Phi_1 - \Phi_2$ remains finite, the energy current approaches infinity. An infinite energy current is physically impossible and is only a mathematical quirk of the averaging method.

The concept of a flux limiter, α , changes the effective value of the opacity at the interface. With the new condition,

$$J \leq \alpha \Phi_0 \quad (12)$$

the energy current is limited by the factor, α . This now introduces a third situation, now κ_0 is

$$\kappa_0 = \frac{\tau_1 + \frac{2}{3\alpha}}{R_1 + R_2} \quad (13)$$

and α is the flux limiter. This situation occurs when the optically thin zone is heating the optically thick zone. When the situation is reversed, an optically thick zone heating an optically thin zone, a

Fleck and Cummings.[2] Figures 3-6 show the results of the radiation simulation code.

Figure (3) shows the first of the test problems. This example is relatively simple with no strong discontinuities in opacity. The 4 cm slab is divided into ten evenly spaced zones of .4 cm each. The slab is uniformly heated from the left side from a 1 KeV source. This test problem is frequency dependant. The opacity depends on the frequency,

$$\kappa_{\nu} = \frac{27}{(h\nu)^3} \left(1 - e^{\frac{-h\nu}{kT}} \right) \quad (16)$$

where h is Planck's constant, k is Boltzmann's constant, T is the temperature, and ν is the frequency. The asterisks are the results published in Fleck and Cumming's Implicit Monte Carlo method of discussing energy transport. The solid line results are the output from the computer code. The code handles this test problem well with no major problems.

The test problem shown in figure (4) is a more difficult problem. The slab is divided into 10 uniform zones. In this problem all of the zones are not optically thin. Some zones are optically thick to photons above a certain energy. A new averaging method must be used. The expression for κ_0 from equation (15) is used. The results are again very good with no major problems.

The temperature-dependant problem shown in figure (5) is an even more difficult test of the new averaging prescription. In this test problem the opacity of the material changes as the material heats up. The opacity

$$\kappa_{\nu} = \frac{27}{(h\nu)^3} \frac{1}{(kT)^{\frac{3}{2}}} \left(1 - e^{\frac{-h\nu}{kT}} \right) \quad (17)$$

changes with the temperature of the material. The simple averaging methods have problems when tried with this test problem. The left plot in figure (5) shows the arithmetic mean which allows too little energy to penetrate the slab. The new method, however, functioned well as an averaging method. The results, shown in the right plot, are very close to the Fleck and Cummings results.

The final test problem was a very difficult example. The material consists of 9 relatively thin zones, and one optically thick zone. The sixth zone of the material is very opaque. The first plot shows the results of the averaging prescription. The results are fairly good but still are not exact. The other two plots show the results of using the simple averaging techniques. The second plot used the harmonic mean to derive κ_0 . This type of averaging effectively ignored the opaque zone, and energy freely moved through the entire material. On the other hand, the third plot shows the results of the arithmetic mean. This type of averaging strongly favors the opaque zone, and energy is completely stopped by the opaque zone. Both simple averaging methods could not deal with this test problem.

The new method for averaging the effective value for κ_0 fosters a better approximation of the diffusion equation. The approximation will also become more accurate as the zoning of a material is refined. With more spatial zones and shorter time steps, the more accurate the approximation becomes. If the number of spatial zones cannot be increased, the new averaging method gives better results than simple averaging techniques.

References

1. Bowers, Richard L. and Wilson, James R., Numerical Modeling In Applied Physics and Astrophysics, (Jones and Bartlett Publishers, Boston, 1991), pgs. 420-422.
2. Fleck, J. A. and Cummings, J. D., Journal of Computational Physics, " An Implicit Monte Carlo Scheme for Calculating Time and Frequency Dependant Nonlinear Radiation Transport, **8**, 313 (1971).

Figure 1

Figure 2

Figure 3

Figure 4

AVERAGING TYPE = 4
 PRESCRIPTION # = 4
 IMPLICITY = 2

Figure 5

AVERAGING TYPE = 4
PRESCRIPTION # = 4
IMPLICITY = 2

Figure 6

Heating of a Slab with Single Opaque Zone

**USE OF THE SLAC CODE TO PRODUCE A PHOTOEMISSIVE
ELECTROSTATIC ELECTRON GUN**

by

MARK D. FORBES

Pittsford/Mendon High School

Rochester, NY

Use of the SLAC code to produce a photo-emissive electrostatic electron gun

Mark D. Forbes

August 31, 1991

Pittsford Mendon High School

Laboratory for Laser Energetics student intern

Electron optics is one of the many sciences put to use at the University of Rochester's Laboratory for Laser Energetics. Its use is spread over a large range of projects. Examples of such projects are beam analysis of the Omega laser system by a streak camera and crystal structure investigation. The project I worked on also dealt with electron optics. The task was to design a photo-emissive electrostatic electron gun which would produce the smallest diameter beam possible and provide a beam that would diverge very little over a distance of about one to two feet. To accomplish my task I was introduced to the SLAC electrostatic electron optics code. This program allows the user to see a simulation of an electron optics system before it is built, allowing the user to design a perfect, working system to his specifications without the cost of testing different designs by building them. I was also required to produce an easy to use manual on how to operate the SLAC code so others in the future may benefit from my experience on this particular program. The utilization of this program has led to the production of a design that meets the specifications required for this project.

Electron optics is the science of how electron paths may be changed or directed by the use of electrical or magnetic fields, similar in the way light is refracted by the use of lenses of materials such as glass. The electron gun that was designed only uses electric fields since magnetic fields would only interfere in the operation of the system the gun was intended for. The use of electrical fields in electron optics is called electrostatics.

The main tool in electron optics is the electron gun. An electron gun is composed of four vital main parts: the cathode, electrodes to produce the lenses, anode, and the vacuum chamber in which it is housed. The cathode is the surface at which the electrons are emitted. There are many types of cathodes such as filament cathodes which utilize electricity for power and photo cathodes which use light to release electrons. A filament cathode releases electrons of energies in a range between zero and one electron volts. On the other hand a photo-emissive cathode releases electrons in a range between zero and one fifth of an electron volt. This is due to the fact that a photo-emissive cathode only requires light for electrons to be released from its surface -light has much lower energy than that of the electricity of the filament. The electrodes of the streak camera are very important in focusing of the electrons. In electrostatic streak cameras series of electrodes at different voltages are used to vary the electrical field throughout the streak camera. These changes in the electrical field cause electrons traveling through the system to diverge or converge depending on the change in voltage whether positive or negative. When a specific voltage is used on an electrode in the system, instead of acting like a lens the electrode can behave like a mirror, reflecting electrons. The other part of an electrostatic lens that affects how electron optics focus is the shape and size of the electrode. The shape and size affect the shape of the equal potential lines thereby affecting voltage distribution throughout the system causing converging and diverging actions just like the reactions when the voltage is changed. The anode of the system is simply the last electrode. The vacuum casing is very important otherwise the charges would arc through the air causing permanent damage to the electron gun itself and possibly damaging other items as well. All of these components are necessary to form an electrostatic electron gun.

The SLAC electron optics program originated at Stanford University in California at the Stanford Linear Accelerator Center. The program's primary purpose was to help produce a well designed linear accelerator. It was created by William B. Herrmannsfeldt. The

original code was used for all different applications-electrostatic and magnetic. A few errors did exist in the programming which questioned its worth. Later Paul Jaanimagi, currently working at the Laboratory for Laser Energetics in Rochester, New York, took the program and altered it for electrostatic electron optics use only thereby eliminating many of the errors that existed in the program.

Fortunately this program was available for this project as it would have been very difficult to reproduce the results of the computer simulation. The program derives the voltages of up to 161,000 points in the simulated electron gun. With this information the computer then calculates the positions of electrons, after they are emitted from a cathode, at different points in time forming trajectories. All this information leads to a summary and graph file which shows the results of the program.

The user supplies all the information needed in the form of an input and boundary file. This information is all inclusive beginning with the electron's starting conditions to the exact size and shape of the boundaries of the electrodes and their voltages.

The program is very accurate in most instances because the amount of error usually gets smaller with each run of the program due to the equations that make it up. The SLAC code operates on Laplace's equation which is a nine point difference equation.

$$\frac{\partial^2 U}{\partial r^2} + \frac{1}{r} \frac{\partial U}{\partial r} + \frac{\partial^2 U}{\partial z^2} \equiv 0$$

It determines the voltage at V0 from the change in voltage at the the other eight points. From this information it can go down columns of

the graph of the electron gun and determine the voltage of every point quickly. Through this process the basis for the rest of the simulation is centered on using the voltage to determine such things as the speed and the placement of the paths of the electrons.

Two electrostatic electron gun designs were taken into consideration for this project: the telefocus gun and the Riddle-Einzel lens system. There were papers written on each system defining the capabilities. The systems met the requirements of a small diameter beam and long focusing distance. Each system was studied more in depth through the SLAC program.

To begin the simulation correctly proper starting conditions had to be maintained. A photo-emissive cathode was used in each electron gun with proper starting conditions for each electron trajectory. At each point source along the cathode one electron came off perpendicular to the cathode at one thousandth of an electron volt and two electrons were set at two tenths of an electron volt coming off the cathode nearly parallel to it, each in opposite directions, north and south along the r axis. This electron point source gives a basic outline of the entire spectrum of possible electron trajectories from any point source on a flat cathode such as this. About seven to ten of these point sources were used in each model to help define the beam that each gun would produce.

After the guns' boundaries were entered into the program each electron gun design was run through the program twenty iterations. This significantly reduced the amount of error due to the fact that the program corrects for its errors every run. The results of the two runs were totally unacceptable. This was expected because the cathode was changed from a filament cathode to a photo-emissive cathode. This was the time at which I had to begin my task of modifying the guns until they worked to the proper specifications.

One of the electron guns tested was the Telefocus electron gun. It appeared to be very promising since it was rather simple to

change. The telefocus electron gun could be dramatically altered by adjusting the position of the anode. The change took only a few minutes to conduct. Changing the anode location was the primary technique used to alter this particular gun because changes in voltage either had no effect or produced a negative effect to the gun. After the proper placement of the anode was found the simulation of the electron gun produced a thin beam of about 75 microns in radius in the gun itself, but after leaving the gun it rapidly diverged. After further simulations of this gun it proved necessary to drop this design since improvements that were created through further modification were only nominal.

The second electrostatic lens system achieved greater success than the telefocus lens system. It used a combination of a Riddle and an Einzel lens system. This combination was created at the University of Arizona. The most effective part of the Einzel lens system is the 500 micron pinhole at which the electrons being emitted from the cathode must pass through. This serves to give a colimated beam with trajectories at small angles to the z axis, making it fairly flexible to alter the beam focal length and diameter with the lenses that follow it. The second lens in the Riddle system was altered to serve as a beam converger to counter the already diverging beam's action. This was done by altering the voltage. The third lens of the Riddle system was combined with the first lens of the Einzel system to make the third lens. This lens was used to also slow down the rate of convergence in the beam. The fifth lens served as the main converging lens. This lens converges the trajectories until they cross each other. The voltage remained fixed on this lens as it did not need to be changed once a voltage was found that caused a convergence that resulted in a crossover of the trajectories. The fourth lens of the entire system controls the angles at which the trajectories hit the fifth converging lens. This ability is controlled by changing the voltage of the fourth lens. Controlling the angle results in the ability to change the convergence of the beam. This allows a beam to converge over a length of a couple feet with a small beam diameter.

The Riddle-Einzel lens system proved successful with the photo-cathode. It produced a beam that had a focal length of approximately 33 inches with a spot size of approximately 600 microns. Furthermore this system of lenses has just been built in the University of Rochester's chemistry labs and similar results have been shown proving the accuracy of the SLAC electron optics code. In addition to the other requirements of the summer internship program a manual on how to use the SLAC program will be available through Hani Elsayed-Ali. This manual is basically a supplement to the information already available on the program. Its purpose is to help speed the learning of the program by a new user. This program has proved very successful in my project since it led to the solution of the problem and came up with an effective design.

500 UM PINHOLE E_GUN V={0.0, 6000.0}

UR
ULE

Acknowledgements

The author wishes to express his gratitude to his supervisors Paul Jaanimagi and Hani Elsayed-Ali for their support and help in this project, also to David Meyerhofer for coordinating and carrying out this summer internship program.

References

J. Orloff and L.W. Swanson, J. Appl. Phys. 4, 2494(1979)

G.H.N. Riddle, J. Vac. Sci. Technol. 3, 857(1978)

**SPATIAL RESOLUTION DETERIORATES WITH
INCREASING FILM EXPOSURE**

by

ELIZABETH RANDALL

East High School

Rochester, NY

During the summer of 1991, I was one of ten high school students who had the opportunity to work at the Laboratory for Laser Energetics in Rochester, NY. Each of us was assigned our own research project and supervisor. The projects were designed to educate us as well as to contribute valuable information to the laser fusion work at the laboratory. The laboratory's ultimate goal is to accomplish laser fusion. Almost all of the work done at the lab is to help in reaching this goal. A laser system called Omega is used to produce fusion reactions at the lab. The system is composed of 24 laser beams that uniformly hit a minute target, composed of a deuterium-tritium mixture. The target area temperature is raised to around 100,000,000 degrees Celcius and the deuterium and tritium atoms fuse. This fusion produces alpha particles and neutrons. The neutrons are then used as an energy source. Each of our projects was supposed to relate to the laser fusion work at the lab and somehow to each other. Some of the projects involved data collection and analysis for things that seemed to have no relation to laser fusion or any other project in the beginning, while others involved alot of reading and note-taking that lead to alot of thinking. Eventually, each of us uncovered what our project was about and most discovered that it did, in fact, have something to do with either the Omega system or another aspect of laser fusion. And that was how each of our projects related to each other. Besides the direct relationships between common data analysis proceses or overlaping physics theories, each of us was working at the Laboratory for Laser Energetics to further an important application of lasers.

A system was designed and built to measure the MTF of film as a function of incident exposure level from a pulsed high power laser source. The MTF, as a measure of frequency response, is used in film analysis. The preliminary data showed that the MTF deteriorates as the incident exposure level increases.

The object of my research was to quantitatively describe how the spatial resolution of film deteriorates with film density (which can be defined as blackness of the film or mathematically as $\text{Log}(1/\text{transmittance})$) for typical laser pulses at the Laboratory for Laser Energetics. This research was set up so that the results could aid progress in the lab. Although this project does not relate directly to the laser fusion work at LLE, the results of the research will be useful in diagnostic experiments intrinsic in reaching laser fusion. The results will be useful in selecting photographic materials for specific optical systems when photographic data is required. Film is used for things like monitoring intensity distribution of laser beams and spectroscopic diagnostics.

To find how the spatial resolution of film deteriorates with density, the use of the modulation transfer function (MTF) was used. This function is defined as: $\text{MTF} = \frac{E(\text{max}) - E(\text{min})}{E(\text{max}) + E(\text{min})}$. MTF describes the accuracy of reproduction by photographic materials of sinusoidal inputs as a function of spatial (or fringe) frequency. It measures the effects of light scatter in the film's emulsion during exposure (and the chemical dynamics that occur during the development process, although this was not studied in this project). Scattering within the emulsion results in a net reduction in the maximum exposure (or energy) and a corresponding increase in minimum exposure, and is increasingly obvious at high spatial frequencies. Therefore, MTF typically gets worse as spatial frequency increases. This research was set up to describe MTF breakdown with higher incident exposures. A photographic image showing a fringe sequence is shown in Figure 1a. Variations in density of the photographic image are shown in Fig. 1b. The conversion from density variations to their corresponding exposures is done using the D-LogE curve (density versus $\text{Log}(\text{exposure})$). A typical D-LogE curve is shown in Fig. 2.

Fig. 1a Image of a test object

Fig. 1b Variations in density shown after digitization

D-LogE curve (density versus $\text{Log}(\text{exposure})$). A characteristic D-LogE curve is shown in Fig. 2.

Fig. 2 The D-Log E curve

For this experiment, MTF can be described as the visibility of an image on film. If a piece of film were fully exposed to light, there would be no difference between maximum

and minimum exposure, so MTF would equal zero and there would be basically no visibility. When the minimum exposure is zero (what is desired for the MTF of an optical system), MTF equals one. When MTF of a system equals one, the MTF of the film can be more easily calculated. An MTF curve is a graph of MTF versus spatial frequency. A typical MTF curve is shown in Fig.3.

Fig. 3 A typical MTF curve

This project was set up in the GDL (Glass Development Laser) bay using the 1.054 um wavelength laser as a light source. The setup is shown in Fig.4.

Fig. 4

When the light enters the system in the form of a beam, it is intercepted by a cylindrical lens which reflects about 8% of the beam into a diagnostic. The primary diagnostic used for data collection was a camera, but sometimes it was replaced by light sensors (a sliding slit diode and a CCD array were used) for use in quantifying the system intensity modulation. This intensity modulation was used for calculating the MTF of the optical system. The MTF for the optical system we used was equal to approximately 0.8, so the value for the film MTF was off by a factor of around 2.

The light that was not reflected by the cylindrical lens was focused down into a point of such high energy that it caused air breakdown. The remaining beam diverged again and hit a series of absorbing glass plates which absorbed all of the light. This part of the setup (the lens and light absorbers) is called the light dump. When early pictures were taken, there seemed to be a source of light creating background light on the film. To combat this, a black felt tent was put up around the setup from over the cylindrical lens to the camera, and two light blocks were put up behind the lens so as not to interfere with the beam.

The purpose for the cylindrical lens was to establish the fringe pattern in the beam which entered the camera and was recorded on film. A picture of this film is shown in Fig.5. A fringe pattern was needed for the MTF because it established a maximum and minimum exposure along with fringe frequency.

Fig.5 A picture of the film

The way the fringe pattern was set up was through interference of the reflected waves from the two uncoated 4% reflective surfaces of the cylindrical lens. Interference is the combination of separate waves to produce a resultant wave. Destructive interference (dark bands or no light) occurs when the path difference between the two lenses is an odd number of $1/2$ wavelengths. Constructive interference (bright bands) occurs when the path difference is zero or a whole number of wavelengths. A more familiar fringe pattern produced through interference, Newton's rings, is created through interference from a spherical lens. In this project, straight fringes were necessary for digitization.

Digitization is the conversion of a photograph into a digital image. This is done by scanning a piece of film with a microdensitometer to convert the varying density levels in the image into numbers. The straight fringes were necessary because in the process of digitization, the density levels were vertically averaged and the individual values had to be consistent.

Two RG-1000 filters were put in the camera before the film to let only infra-red light (the wavelength of the laser light) pass through the camera to the film. A step wedge was also placed in the camera before the film (but close to it). The step wedge contained OD 1.4 and OD 0.77 filters. The filters were configured so that the top of the beam passed through the OD 1.4 filter, the middle of the beam passed through a slit between the two filters, and the bottom of the beam passed through the OD 0.77 filter (Fig. 5).

Transmission of an OD 1.4 filter is 4% and transmission of an OD 0.77 filter is 17%. The reason for using different filters is to get different densities on the same piece of film.

These values were important for the MTF calculations. They gave three different regions to calculate and compare MTF values for.

Four pieces of data (pictures) were collected. Two types of film were used: Kodak high speed infra-red 4143, and Kodak TMAX 400. Two pictures were taken with each film, one with energy at around 14 joules and the other at around 40 joules. The film was then digitized and line outs from each density level were taken. The digitization process simply converts the density values of the film into numbers. By using the characteristic D-LogE curves for each film (calculated especially for this experiment using this setup), the density values could be converted to their corresponding exposure levels. Exposure-converted line out graphs were then made. The line-out graphs for a piece of TMAX 400 film at middle, and high spatial frequency regions are shown in Figs. 6a-b. Using these line out graphs, spatial frequency was found because it is indirectly proportional to the wavelength. The maximum and minimum exposure values were also found. With spatial frequency and exposure levels, the MTF curves were calculated for the different films, exposure levels, and frequency regions. The resulting MTF curves are shown in Fig. 7.

The results from this experiment were fairly limited because of the time constraints, the incompleteness in the D-Log E curves, and the need for flatter intensity profiles. However, this project is going to continue and the results from my experiment will be the core information that this research is based on. Eventually, this research will aid laser fusion work at the Laboratory for Laser Energetics (and other laser labs) indirectly by providing a basis for analyzing film data that has been used in diagnostic experiments. It will tell how well the film used in the experiments reproduced an image, and will give a basis for what to expect in terms of visibility from photographs taken under certain conditions.

Figs. 6a-b The line-out graphs

Fig. 7 The MTF curves

ANALYSIS OF REFRACTIVE IMAGE DISTORTION

by

FRANKLIN S. TURNER

Rush-Henrietta High School

Henrietta, NY

Analysis of Refractive Image Distortion

Franklin S. Turner

Introduction:

The purpose of this project was to analyze a technique for plasma characterization known as "refractive image distortion" (RID)¹. An experiment using this technique was carried out in 1989, resulting in fourteen photographs. These photographs were processed in the course of this project, allowing a quantitative analysis of this experiment to be made for the first time.

When a laser is focused onto a target it produces a plasma. This plasma is a hot ionized gas that expands from the surface of the target back towards the laser. This expansion is similar to the expulsion of hot gases from a rocket. Further, just as the rocket is forced up by the movement of the fuel, so the plasma expands outward and causes the target to move in the opposite direction. When this effect is applied to a spherical target, implosion occurs. This spherical implosion is essential to laser fusion. In order to better comprehend the laser fusion process, it is important to characterize the plasma that is produced from a target struck by a laser.

One method to characterize a plasma is shown schematically in Figure 1. The plasma is formed by the laser striking the target from the right. A second (probe) laser passes through the plasma and the refraction of this laser light is measured. The refraction of the probe rays is much like the refraction light rays experience at the interface between two dissimilar materials. An excellent example of this is the appearance of an object submerged in water. The object appears to be closer to the surface than it really is. However, refraction at an interface is not exactly the same as the bending of the probe rays that pass through the plasma, for the probe rays are continuously refracted, while the image of the object in water is refracted only once. The probe rays experience the largest refraction in the regions of the plasma with greatest density. If a large number of these probe rays are passed through the plasma, then information about the entire plasma can be obtained. By measuring the deflection angles of the probe rays, information about the size and density of the plasma can be obtained. As Figure 2 demonstrates, two deflection angles need to be measured for each

ray. These results can be compared with a simulation code's representation of the plasma.

An experiment using this technique was carried out at KMS Fusion Inc., in which an incident laser (0.5 μm wavelength) struck a solid plastic target producing a plasma. At the same time, a probe laser (0.25 μm wavelength) passed through a 50.8 μm grid and into the plasma. Distortions of the probe rays occurred due to refraction, and the new ray trajectories were collected onto film. The experiment resulted in fourteen photographs of the grid at various locations within the plasma (object planes 1-14 as shown in Figure 2a). No useful information has previously been obtained from the experiment, as, before this project, no attempt had been made to analyze the photographs and extract quantitative data from them. The present analysis found for each ray on the grid in the probe laser beam, two deflection angles. These allow for a comparison of the experimental results with a computer simulation of the experiment to observe how well the laser-target interaction can be modeled.

In the experiment illustrated in Figure 1, the lens forms an image on the film of an "object" located in the plasma, in the object plane. The formula³ $1/u + 1/v = 1/f$, where f is the focal length of the lens, u is the distance of the object plane to the lens and v is the distance from the lens to the image plane, demonstrates that, by changing the location of the film (image plane), the object plane changes. This allows for the point P to appear to come from points such as P_1 or P_{14} (See Figure 2). However, the film, as shown in Figure 1a, only provides one object plane. In order to determine the slope of the dashed lines in Figure 2, two or more object planes are necessary. Therefore, holography was used. By placing a holographic plate after the $f/2$ lens (but not at the focal point) in Figure 1a, and simultaneously exposing the holographic plate to another (reference) laser, the wavefront was recorded. After the holographic plate was developed, the wavefront of this third laser was then subtracted from the hologram. The end result was 14 reconstructions that were equivalent to performing identical experiments 14 times, with the film at different positions. These positions correspond to the object plane at positions 1 through 14.

Data Reduction:

The result of the holographic reconstructions was a set of fourteen photographs, three of which are shown in Figure 3. The

region of grid on the left is the undistorted portion of the grid, to the left of the target. (The target was sufficiently thick that it did not move appreciably during the experiment). In the middle is seen a gap, or a dark region. This region is where the target resides and where the probe rays were distorted beyond the collection optics' ability to capture them. The grid on the right is the distorted part, where the rays passed through the plasma.

In order to extract meaningful data, the images had to be entered into a computer. The ideal process for this was hand digitization. This was accomplished by using PV-Wave, a programming language on the UNIX operating system. However, the resulting data was not on the same coordinate system for every image. The images increase in magnification as they progress in the series. For example, the image in Figure 3a is smaller than that in Figure 3c, yet the figures represent the same grid. Further, the nature of the hand digitization process causes unknown rotations and translations to occur. Therefore, a means to place the images on a common system was required. The solution to this problem lies in understanding that the combined effect of the magnification, rotation, and translation is given by the following transformation between the digitized coordinates (x,y) and the true coordinates (X,Y, in microns):

$$X = ax + by + c$$

$$Y = dx + ey + f$$

where a-f are unknown constants, to be calculated separately for each image.

By selecting three points common to each image that appear not to have undergone any refractive distortions, the following six equations allow the values of a-f to be solved for:

$$X_1 = ax_1 + by_1 + c$$

$$X_2 = ax_2 + by_2 + c$$

$$X_3 = ax_3 + by_3 + c$$

$$Y_1 = dx_1 + ey_1 + f$$

$$Y_2 = dx_2 + ey_2 + f$$

$$Y_3 = dx_3 + ey_3 + f$$

The values of a-f are solved for as follows:

$$\Omega_1 = X_1 - X_2$$

$$\Omega_2 = X_2 - X_3$$

$$\omega_1 = x_1 - x_2$$

$$\omega_2 = x_2 - x_3$$

$$\Phi_1 = Y_1 - Y_2$$

$$\Phi_2 = Y_2 - Y_3$$

$$\phi_1 = y_1 - y_2$$

$$\phi_2 = y_2 - y_3$$

$$\begin{aligned}
a &= \frac{\phi_2 \Omega_1 - \phi_1 \Omega_2}{\phi_2 \omega_1 - \phi_1 \omega_2} \\
b &= \frac{\Omega_1 \omega_2 - \Omega_2 \omega_1}{\phi_1 \omega_2 - \phi_2 \omega_1} \\
c &= X_1 - ax_1 - by_1 \\
d &= \frac{\phi_2 \Phi_1 - \phi_1 \Phi_2}{\phi_2 \omega_1 - \phi_1 \omega_2} \\
e &= \frac{\Phi_1 \omega_2 - \Phi_2 \omega_1}{\phi_1 \omega_2 - \phi_2 \omega_1} \\
f &= Y_1 - dx_1 - ey_1
\end{aligned}$$

Once a-f have been calculated, the coordinates of each grid point can be transformed to the common system. The last step in transforming the coordinate system is to rescale to microns. This is accomplished by averaging the distances between the undistorted grid in the x and y directions. This distance is then proportional to 50.8 microns, the known size of the grid spacing in the experiment.

In order to see that the hand digitization process is one which is accurate, observe Figure 4, an overlay of digitized images six and seven. The close match demonstrates the accuracy, because images six and seven are identical. This fact was not known at the time the images were digitized.

The next step was to label the data that was hand digitized. The easiest method to accomplish this was manual labeling. This process was accomplished by assigning a unique (i,j) to each grid element of each image. This then allows for each grid element to be traced through the 14 images, and its apparent path through the plasma found. A routine was written in PV-Wave that allows the user to manually select points with a mouse and assign the values (i,j) to each element. The axes on Figure 4 demonstrate the relative coordinate system that was assigned to the fourteen images.

After the data was labeled, it needed straight lines to be fit to it. Figure 2 demonstrates why this must be so. The light rays enter the plasma and their trajectories are altered. The new trajectories are caught by the holographic film and recorded. Once the wavefront is reconstructed, the optics of the system trace back the apparent trajectories of the rays. The dotted lines in Figure 2, which are straight lines, show how the optics perform this trace back.

The procedure used to fit lines to the data is known as least squares fitting². The data consists of coordinate pairs, the independent variable being the image position (z), and the dependent variable being the vertical or horizontal positions (y and x). The line is of the form:

$$y=a+bz$$

Given n data points of the form (z_i,y_i), the function F(a,b) may be defined by taking the sum of the squares of the differences between the experimental y value of the point and its linear value as follows:

$$F(a,b)=\sum_{i=1}^n [y_i-(a+bz_i)]^2$$

The next step is to find values of a and b for which the function of (a,b) is a minimum. This is accomplished through the use of calculus, leading to two equations in a,b,y_i,z_i, as follows:

$$\sum y_i - na - b\sum z_i = 0$$

$$\sum y_i z_i - a\sum z_i - b\sum z_i^2 = 0$$

Solving these equations for a and b yields the following equations:

$$a = \frac{1}{\Delta} \left(\sum z_i^2 \sum y_i - \sum z_i \sum z_i y_i \right)$$

$$b = \frac{1}{\Delta} (n \sum z_i y_i - \sum z_i \sum y_i)$$

$$\Delta = n \sum z_i^2 - (\sum z_i)^2$$

The process of the least squares fit was performed for every point on the grid. Most of the images provided data for each of the grid elements, but a few elements were not extractable. As many points as possible were digitized, but the image quality fell off near the edges of the photographs. Those grid points that did not occur in 4 or more images were not fitted with lines. The results of a typical linear fit are shown in Figure 5. The graphs show that the grid element is one whose trajectory can be fitted well, for the deflections in both the (x,z) plane (Figure 5a) and the (y,z) plane (Figure 5b). Typically, the standard deviation in the slopes was less than one degree, but there were a few exceptions. The points with more than a one-degree standard deviation were either on the edge of the image where the image quality deteriorates or points near the right hand edge of the dark region of Figure 3 whose angles were above 4 degrees.

At this point the refraction angles (in the x and y directions) have been found for each (i,j) point on the grid.

Results:

Now that the data reduction is complete, the results can be displayed. One useful form for display is the refraction angle (Θ) as a function of position, as demonstrated in Figure 6. Figure 6a shows that the general trend in x deflection is an increasing Θ_x with decreasing position. In other words the refraction of the ray trajectories increases as the grid elements get closer to the solid

plastic target. This conforms to the anticipated result, since the plasma is expected to have its highest density closest to the target. This results in the gap just to the right of the target, where the rays are refracted beyond the collection optic. Figure 6a confirms this. However, once x is less than $450\text{ }\mu\text{m}$, the target is passed and the undistorted grid is reached. The Θ_x for these grid elements in all cases should be zero. The vertical lines that pass through each 'x' symbol on the graph represent plus or minus one standard deviation of the linear fit. As this graph shows, the standard deviations are quite small.

Similarly, Figure 6b relates the general trends for Θ_y passing through a horizontal position (x) close to the target on the plasma side. Figure 6b illustrates the refraction angle as a function of position. The deflection in y occurs because the light strikes a curved edge of the plasma. This effect is illustrated in Figure 2b. The greatest angles occur near the extremes of the data because this is where the plasma shows its greatest curvature in the (y,z) plane. The figure also suggests that the refraction angle will eventually become zero at the farthest extremes. Unfortunately, the experimental data did not extend quite far enough in y for this to be seen in the results. However, this must be true, for once the distance of the light ray from the plasma is great enough, the plasma's density is too small to provide any noticeable refraction. In general, Figure 6 demonstrates that the experimental results are qualitatively as expected.

A more complete representation of the data is a contour plot. The shape of the contours has a relationship to the density contours. This relationship exists because the magnitude of Θ_x and Θ_y depend upon the density of the plasma. Figure 7a demonstrates the general shape of the plasma. Further, it provides information about the plasma that would be hard to detect from the photographs or the Θ graphs of Figure 6. Notice the fine-scale structures of the contours: at several values of y the contours bend in or out in the x direction. From top to bottom several deviations from the average curve were detected. These deviations were systematic, suggesting

that perhaps the plasma itself contained fine-scale structures. Additionally, the contours of Figure 7a seem to be symmetric about the line $y=350-400\text{ }\mu\text{m}$, the probable axis of the irradiating laser.

Further, the contour plot of Figure 7a clearly shows that the data itself possesses quite a large range of accuracy. The minimum value shown in the figure is 0.25 degrees. This number is quite small in comparison to the highest contour value of 8 degrees.

Besides Figure 7a, Figure 7b provides interesting insights into the nature of the plasma. First, it shows the general pattern of the y distortion. The pattern is much the same for the positive refraction and the negative refraction. Both show apparent ray trajectories curving away from the target. This suggests that the less dense plasma is at the outer edges, which is as expected. Further, the deflection in y approaches zero in the middle of the plot, for reasons of symmetry (See Figure 2b). These two graphs demonstrate that the experimental results are qualitatively as expected.

The contour plots of Figure 7 enable a comparison to be made with the simulation code. Figure 8 shows the contour plots produced by SAGE (SAGE is a FORTRAN code that simulates the plasma production and motion and allows for the prediction of various properties of the plasma). The first noticeable point of similarity is that the contours have the same general shape, as is clear by comparing Figure 7 with its counterpart in Figure 8. In addition the ranges of the contours are quite close. SAGE results in Θ_x contours that range from 1 to 8. Its maximum contour value is 8 degrees, which indicates that the predicted properties of the plasma are quite close to the experimental. There is one obvious discrepancy between the Θ_x contour plots, that being the bulge in SAGE's 1 and 2 degree contours. This is simply noise in the SAGE calculations. While the simulation otherwise agrees with the contour plot of Θ_x , the Θ_y contour plots show some differences. The calculated and experimental contour shapes are similar, but not as

close as the Θ_x 's. However, the experiment has shown that it can provide contour data good enough to test the code modeling.

The final step was to evaluate the potential of the technique of RID. Judging from the close relationship of predicted to experimental deflection angles, the process shows promise. However, the complex holography that was involved in reconstructing the wavefront would certainly make RID a slow process. Further, processing data from 14 photographs takes a considerable amount of time. The solution to this may lie in reducing the number of photographs, to the minimum of two if possible. The feasibility of this solution can be tested from the experiment that was processed above. By using two photographs at the object planes on either side of the plasma (e.g. Figure 1a, object planes 1 and 14), the results can be compared with the original ones. Figure 9 shows contour plots of the Θ_x and Θ_y resulting from linear fits to images 2 and 13. The results were rather close to Figure 7. The general shapes and locations of the contours match those of the original processed data. More noise can be detected in Figure 9 than in Figure 7. For example, along the outer extremes of the contour lines (e.g. the one degree contour) in Figure 9a and Figure 7a this fact is clearly illustrated. The noise is to be understood for the quality of the photographs deteriorates at the edges, and there is less data to "smooth" the fits. Aside from the noise, only a few minor differences can be observed. This demonstrates the feasibility of the RID process as one to diagnose plasmas induced by lasers, provided that an optical design can be arrived at for a system to simultaneously give two images focused at different object planes.

One final method to display the data is a three dimensional plot, illustrated by Figure 10. The plot shows selected ray trajectories as they appear to pass through the plasma. These rays have not had lines fit to them. The rays propagate in an increasing z direction. The set of rays on the left of the graph at $i=5$ are rays from the undistorted grid. The rays at $i=9$ illustrate the greatest bending. This figure may help visualization the ray trajectories in the experiment.

Conclusion:

The project started with 14 images that had been produced from an experiment to investigate refractive image distortion, and processed them into quantitative data. The images were first digitized. Then they were labeled to allow for the apparent ray paths to be traced from image to image. The last step in data reduction was fitting two lines to each labeled ray. The slopes of these lines gave the deflection angles for the apparent path of each probe ray. These angles were then displayed as contour plots to allow for a comparison with predicted deflection angles.

The results of this experiment are of particular interest to plasma physicists, for it allows them to better understand plasmas and how to model them with codes. This RID technique may lead to a better understanding of the plasmas that are essential to laser fusion. While the target in the experiment at KMS Fusion Inc. was a flat one, RID could very easily be performed on spherical targets, such as OMEGA targets. In the future, it would be desirable to perform these experiments with only two images, since holography is a time-consuming process that should be avoided. Overall, the technique of RID is an easy, productive technique to study plasmas. It shows promise as a plasma diagnostic, and may eventually allow for a better modeling of laser fusion targets.

References:

1. C. Darrow, D.S. Montgomery, K. Estabrook, R.P. Drake, G.E. Busch and, E.F. Gabl, "An experimental investigation of refraction-induced distortions in harmonic-light images of laser produced plasmas," J. Appl. Phys. 67, 3630 (1990)
2. P.R. Bevington, Data Reduction and Error Analysis for the Physical Sciences, McGraw-Hill, Inc., USA (1969)
3. F.W. Sears, M.W. Zemansky and, H.D. Young, College Physics, Addison Wesley Publishing Company, MA (1980)

4. R.S. Craxton, C. Darrow, G.E. Busch and, E.F. Gabl, "Image Distortion as a Diagnostic of Refraction in Long-Scale-Length Plasmas," Bull. Am. Phys. Soc. 34, 2140 (1989)

Figure 1: (a) Schematic of experiment performed at KMS Fusion Inc. The solid target is irradiated by the incident laser from the right, producing a plasma. The probe laser passes at a right angle to the incident laser through the plasma and onto the film. (The f/2 collection optic actually used in the experiment was a concave mirror, but it is shown here as a lens for simplicity.) (b) Target and grid as used in the experiment before plasma formation

Figure 2 Illustration of the ray bending in the plasma. The actual paths of typical rays are shown by the solid lines. The apparent paths are illustrated by the dashed lines. (a) Ray paths in the xz plane. The point P_1 is the apparent location of the grid element at point P when the

Figure 3. Photographs before processing. (a) Image 2, the second photograph in the series, before hand digitization. On the left is the undistorted portion of the grid. In the middle of the image, the dark region is due partly to the target shadow and partly to probe rays bent outside the optics. On the right of the image is the plasma and the distorted grid. (b) Image 7, an image in the middle of the series. (c) Image 9, an image towards the end. These figures also illustrate the differences that occur in magnification between images. Notice that the vertical lines in (a) are bent towards the target, the vertical lines in (b) are relatively undistorted, and the vertical lines in (c) are bent away from the target.

(9)

(c)

Figure 4: Overlay of digitized images 7 (teusrael) and 6 (olive cinnel). Since these images are duplicates of the same photograph, the figure

Figure 5. Example of least squares fit to the data from the digitized photographs. Each triangle represents grid element (10,3) as it appears at various image positions. The line represents the apparent path of the light ray as it passes through the plasma (the actual path is curved). (a) Least squares fit to the horizontal position (x) of the ray. (b) Least squares fit to the vertical position (y) of the ray. The slopes of these lines give the refraction angles θ_x and θ_y for the grid element (10,3).

Figure 6 Refraction angle as a function of position. The 'x' symbol represents the resulting slope after a least squares fit to the data (See Figure 5). The vertical line in the middle of each 'x' represents plus or minus one standard deviation of the fit. (a) The horizontal refraction angle (θ_x) versus the horizontal position (x), at $j=9$. (b) The vertical refraction angle (θ_y) as a function of vertical position (y), at $i=10$.

Figure 7: Contours of the refraction angles. (a) Contour plot of the horizontal refraction angle (θ_x). The contours include 1/4, 1/2, and 1 to 8 in one degree increments. The few lines on the left, at 0.25 degrees, demonstrate that the limit of the data's accuracy has been obtained, since that portion of the graph is the undistorted grid, for which the refraction angle should be zero. (b) Contour plot of the vertical refraction angle (θ_y). The contours range from -3 to 3 in one degree increments, excluding zero. The contours on the bottom of the graph are negative, and the ones on the top are positive.

Figure 8: Predicted refraction angle contours for the plasma, as calculated by SAGE. (a) Horizontal refraction angle (Θ_x) . The contours range from 1 to 8 in degrees. (b) Vertical refraction angle (Θ_y) . The contours range from -4 to 4 in one degree increments, excluding zero. This figure is on the same scale as Figure 7. Note that the figures agree in many respects.

Figure 9: As Figure 7, except that it shows the refraction angles obtained from only two images (2 and 13). (a) Horizontal refraction angles. The contours range from 1 to 8 in one degree increments. (b) Vertical refraction angles. The contours range from -3 to 3 degrees, excluding zero.

Three Dimensional Representation of Grid Refraction

Figure 10: Three dimensional representation of selected ray trajectories, $i=5, 9, 13, 17$ and $j=3, 4, 5, \dots, 11$.

MAKING OF PINHOLES FOR X-RAY PINHOLE CAMERAS

by

HELEN VAYNTRUB

Brighton High School

Rochester, NY

Introduction

During the summer of 1991, ten high school students had the opportunity to work at the Laboratory for Laser Energetics. The laboratory's primary research is in the area of laser fusion. Each of us was assigned our own research project and supervisor. The projects were designed to educate us as well as to contribute valuable information to the laser fusion research.

Nuclear fusion occurs when two atoms combine and give off energy in the process. A 24 laser beam system, the third largest in the world, called Omega is used to produce fusion reactions¹. As the 24 laser beams hit a target smaller than a pinhead (.2 to .3 millimeters), the outer shell of the target reaches temperatures of 100,000,000 degrees Celsius, several times hotter than the sun. Because of these extreme temperatures, the outer shell is ablated. The expansion of the outer shell compresses the central region, composed of a deuterium - tritium mixture, to densities 1,000 times its primary density of .2 grams/cm³, approximately the density at the center of the sun. The isotopes of hydrogen fuse together and give off high energy neutrons which can then be used to produce electricity. Nuclear fusion produces less toxic waste than nuclear fission, and can be easily controlled, so it is safer than nuclear fission. Another benefit of nuclear fusion is the large supply of hydrogen fuel which can be found in common sea water. The fuels used now, such as coal, oil, and uranium, will eventually run out, and nuclear fusion is the energy source that may be used in the future.

In conclusion, many of our projects can be related to the laser fusion research at the lab and to each other. Besides the direct relationships between common data analysis processing or overlapping physics theories, each of us was working at the Laboratory for Laser Energetics to further an important application of lasers, which has great significance on our future hopes and dreams.

¹Craxton, Stephen R., et al. "Progress in Laser Fusion" Scientific American, August 1986, pp. 68 - 79

Making of Pinholes for X-Ray Pinhole Cameras

Helen Vayntrub

Abstract

In this paper the methods and problems faced when making pinholes for x-ray pinhole cameras is discussed.

I. Introduction

This summer I had an opportunity to work at the University of Rochester Laboratory for Laser Energetics in laser produced pinhole production. My task was to contribute to the making of small pinholes for x-ray pinhole cameras which are widely employed in fusion experiments on LLE's Omega laser system. The pinholes are two to ten microns (μm) in diameter, drilled in metal foils of 25 to 50 μm in thickness.

II. Pinhole Cameras

The phenomena of imaging was first realized in Italy. When shutters were closed in the daytime, sometimes an image of the outside would appear on the wall (Figure 1). The pinhole camera acts much as a shutter and a wall. It consists of a screen with a pinhole and film. Today cameras with lenses have replaced the simple pinhole.

However, no lenses for x-rays exist, so we are forced to go back to pinhole cameras for x-ray imagery. Since laser fusion targets are very hot they must be photographed in the x-ray range of the spectrum. To obtain a spatial resolution of a few microns, the pinholes also need to be a few microns in diameter. Since conventional drills cannot drill such small diameters, we use laser for this purpose. A schematic of the actual laser system used in pinhole production is shown in Figure 2. It consists of a pulsed infrared laser ($\lambda = 1,053 \text{ nm}$), a spatial filter, a Helium - Neon alignment laser ($\lambda = 543 \text{ nm}$) and a microscope.

III. Laser and focal spot diameters

The laser, an acronym for Light Amplification by Stimulated Emission of Radiation, has many special properties that allow it to drill very small pinholes. Figure 3 compares white light from an ordinary house light bulb with laser light. Unlike white light, laser light is coherent, which means that the laser light has one wavelength and all of its constituent waves are in phase. In phase means that the peak of one wave is in the same position as the peak of the wave next to it. Ordinary white light is composed of many different wavelengths and has random phase.

The interaction between a laser and lens can be expressed using one simple formula:

$$d=f\lambda/D$$

The beam diameter at focus, d , is inversely proportional to the diameter of the laser at the lens as shown in (Figure 4). As the diameter of the laser increases, the focal spot decreases. The focal spot size is also directly proportional to the wavelength and focal length, i.e. the smaller the wavelength or the focal length, the smaller the focal spot.

The microscope objective (Figure 5) has a very short focal length and is therefore very effective in focusing the laser beam.

One of the problems faced when drilling small pinholes are lens aberrations. Since the infra-red laser is sent along the axis of the lens, off axis lens aberrations are kept to a minimum. However, aberrations associated with the wavelength dependent design of the conventional objective are still present.

IV. Results

Figure 6 shows three different pinholes. The largest pinhole with the most scattered metal around it was drilled at the peak intensity of the laser, with no spatial filter and was measured to be 29 μm in front and 26 μm in back. The pinhole next to it was also drilled at peak intensity but with the spatial filter in the beam. The pinhole diameter was measured as 26 μm in front and 18 μm in back. The smallest pinhole was drilled with

minimum intensity with a spatial filter in the beam and was measured as $11\text{ }\mu\text{m}$ in front and $9\text{ }\mu\text{m}$ in back. The smaller diameter of the pinhole in back, shows the conical shape of the pinhole.

As evident from Figure 6 the lower intensity beams drilled smaller pinholes. This is plausible if we consider the Gaussian intensity profile of the laser beam (Figure 7). This figure shows a cross section of the intensity of the laser versus the radius from the center of the laser beam. The laser is thought of as a cylinder with highest intensity at the center and lower intensity with increasing distance from the center. The radius at which the higher intensity laser will ablate the metal is much larger than that of the low intensity. The tacit assumption made here is that ablation occurs, as indicated by the arrows in the figure, that at intensities above the threshold limits.

V. Conclusion

In conclusion, x-rays can be imaged by a pinhole camera with a pinhole of about two to five micrometers in diameter. Lasers are the most practical way to make such small pinholes. As we have shown the diameter and purity of the pinholes drilled by lasers depends on a number of parameters such as laser beam quality, focusing, arrangement, beam energy and number of pulses used to drill the holes. In the light of these complexities, I was happy that I could drill holes as small as $10\text{ }\mu\text{m}$ in diameter.

Figure 1

Figure 2

Figure 3

Figure 4

Figure 5

Figure 6

Figure 7

**DOES PERTURBATION THEORY ACCURATELY DESCRIBE
MULTIPHOTON IONIZATION?**

by

**JEANNE YAX
Nazareth High School
Rochester, NY**

Over the course of this summer, I analyzed data from several multiphoton ionization experiments done at the University of Rochester's Laboratory for Laser Energetics and elsewhere. The laboratory's main objective is to research and develop nuclear fusion as a reliable source of fuel for the future.

The 24-beam laser system at the laboratory, Omega, uses a DT (deuterium-tritium) fuel target. All 24 beams of the system are focused on the target, which is smaller than a pinhead. When the system is fired and the beams hit the target simultaneously, the target is compressed to extremely high densities. This causes an implosion, during which deuterium and tritium atoms may combine and give off energy.

Multiphoton ionization experiments are performed at the lab because they, like nuclear fusion, are an example of high energy density physics, and allow the study of how individual atoms react in situations with high energy densities.

Multiphoton ionization occurs when an atom interacts with a high intensity laser. When some of the laser's photons are absorbed by the atom, the photons' energy is transferred to one of the electrons in orbit around the atom. This energy allows the electron to break the force which binds it to the atom (Fig.1)

Multiphoton ionization experiments require a certain experimental set-up in order to be performed (Fig.2). A laser is focused down to a small spot inside a vacuum chamber filled with one of the noble gases. There is a small electric field at the focal point, which causes any ions formed to travel through the TOF (time

Fig.1: Basic Process of Multiphoton Ionization

of flight) drift tube to the MCP (Micro Channel Plate). The MCP is an electron multiplier which produces a signal which can be read and converted back into the number of ions produced.

Fig.2: Set-Up of Experiment

In order for an atom to be ionized, it must absorb several photons at one time. The photons' combined energy must be greater than the binding energy, of the electron to the atom (Fig. 3 (example: 1st charge state of xenon)). Any photon energy not used to overcome the binding energy is given to the newly freed electron in the form of kinetic energy. This is shown by the formula:

$$\Delta E = |E_B| + E_K = N\hbar\omega$$

where E_B is the binding energy, or ionization potential, E_K is the kinetic energy, N is the number of photons, and $\hbar\omega$ is the energy of each individual photon.

Fig. 3: Energy conservation during multiphoton ionization

However, the energy of the individual photons differs with differing wavelengths of laser light:

$$\text{Photon Energy (eV)} = \frac{1.2399}{\lambda(\mu\text{m})}$$

and the number of photons required for ionization changes with different photon energies, so the number of needed photons relies on the wavelength of the laser (Fig. 4).

Fig. 4: Varying photon energies ionize Xe+

An atom can be ionized more than once (Fig. 5). If more photons are absorbed by the atom after it loses an electron, it may lose more electrons, although the probability of losing additional electrons is less, because the ionization potential of higher charge states is much greater. Increasingly more photons are needed to ionize an atom a second time, and the probability of the right amount of photons being absorbed at the same time becomes increasingly smaller.

Fig. 5: First 3 charge states of krypton at 1.064 μm

Lowest Order Perturbation Theory states that:

$$\Gamma = \sigma I^N$$

where Γ is the rate of ionization, σ is a constant, I is the intensity of the laser, and

$$N = \frac{E}{\hbar\omega}$$

where E is the ionization potential. This is true because (1) intensity is proportional to the number of photons per second per unit area:

$$I \propto \frac{k}{As}$$

(2) The rate of absorption of one photon is proportional to the intensity times the area of the atom:

$$\Gamma_1 \propto Ia$$

(3) Therefore, the rate of absorption of N photons is equal to the rate of absorption of one photon to the N th power and since the rate of absorption of N photons is directly proportional to the rate of ionization:

$$\Gamma = \Gamma_1^N \propto (a^N)(I^N)$$

(4) Since the constant σ accounts for the value of a^N , it must be true that:

$$\Gamma = \sigma I^N$$

While studying perturbation theory, it can be observed that if the change in the number of ions ΔM_i is much smaller than the original number of ions M_0 , then the number of ions produced is proportional to I^N . This is shown by:

$$\frac{\Delta M_i}{\tau} = \Gamma M_0 \quad \text{and} \quad \Delta M_i = \Gamma \tau M_0 \propto I^N$$

where τ is the pulse width and Γ is the rate of ionization. For example, in figure 6, it is seen that the number of ions does scale like I^N until saturation, or when the graph starts to curve. In this figure, the slope divided by the number of photons required for ionization should be equivalent to one, according to perturbation theory. In figure 4, it is shown that with wavelengths of approximately one

Fig. 6: Xenon+ at 1.064 microns

micron, the number of photons needed is eleven to ionize the first charge state of xenon. In figure 6, the slope is equal to 11.1, so this example is described well by perturbation theory. To determine if most of the analyzed data could be described in the same manner, I plotted the slope divided by the number of photons needed by the number of cycles. I used this because it took both the frequency of the laser and the pulse width into consideration, because the number

of cycles is equivalent to the frequency times the pulse width. Figure 7 shows that most of the data I analyzed follows perturbation theory, with the exception of the data taken with a very short pulsed laser or with a laser with a long wavelength.

Fig. 7: Support for Perturbation Theory

In conclusion, multiphoton ionization depends upon the number of photons absorbed, the energy of the photons, and the intensity of the laser. Also, Perturbation Theory states that the rate of ionization scales like I^N . Perhaps most important of all, Lowest Order Perturbation Theory accurately describes multiphoton ionization unless the wavelength of the laser is too long or the pulse is extremely short.

**WAVEFRONT ANALYSIS USING SHEARING
INTERFEROMETRY**

by

NORA YIP

Webster High School

Webster, NY

WAVEFRONT ANALYSIS USING SHEARING INTERFEROMETRY

Nora Loey Yip

The University of Rochester / Laboratory for Laser Energetics

250 East River Road

Rochester, New York 14623-1299

I. Abstract

Examining an optic of using a laser beam is most commonly done with the two-beam interferometry technique. A novel method of testing optics utilizing shearing interferometry has been investigated. With this procedure of just capturing a visual image, calculating and plugging values into an equation, calibrating shearplates and inspecting optics for aberrations will be a much more efficient task.

II. Introduction

Experimental wavefront analysis using shearing interferometry has proven to be beneficial. The goals of my experiment were to 1) compare two-beam interferometry to shearing interferometry; 2) validate the mathematical expression relating decollimation to fringe rotation and 3) determine practical sensitivity of a Murty shearplate.

A shearplate is an optic which interferes the defocused wavefront with a laterally shifted copy of itself--the shift can be either along the x or y axis. The Murty shearplate interferometer compares two laterally shifted wavefronts. In Figure 1, two circles depicting laser beams are shown, one intersecting the other. The shear distance is defined as the distance between the centers of the two beams. ΔW represents the difference in wavelength between the two beams. The shift in this

Figure 2 LATERAL SHEARING INTERFEROMETER

example is along the y axis. Also, a shearplate tests the phase of the beam primarily to find the amount of defocus (either collimated, converging or diverging), as shown in Figure 2. The collimated lateral shearing interferometer means that the laser beam is in phase and that it is at a plane or flat wave. The convergent LSI shows that there is a focal point in the center and the laser beam has a curved surface. This signifies that defocus is inside the system.

III. Principles of Operation

The purpose of the shearing interferometry experiment was to verify the existing equation for defocus and compare the shearing results to two-beam interferometry results. Theoretically, the shearing and two-beam statistics should be the same. The main goal was to know if they were the same and if not, how close or far apart the values were.

IV. Experimental setup

In Figure 3, the setup of the experiment is shown. A Helium-Neon gas laser with a wavelength of 632.8 nm transmits a laser beam through a collimator which increases the diameter of the beam. The laser beam then travels through a beamsplitter which divides the beam into two separate paths--50 percent of the beam passes through two lenses (L1 and L2) and reflects off a mirror (M1) and the other 50 percent reflects off a mirror only (M2). The purpose of the two lenses is to produce aberrations such as tilt, defocus, coma, astigmatism or spherical. The wavefronts recombine at the beamsplitter, producing an interference pattern which contains information about any aberrations which may be present. Then 100 percent of the laser beam reflects off a mirror (M3) which directs it into a camera lens, CCD camera

Figure 3

onto a personal computer. This setup is used to detect the phase of the beam using the SSPD (Spatial Synchronous Phase Detection) computer program. This program uses the Fourier transform technique for measuring differential phase of fringe images.

In shearing interferometry, a shearplate is substituted instead of the mirror (M3). When the laser beam hits the shearplate, the shearplate laterally displaces the laser beam phase with its two surfaces which reflect (S1 and S2). The displacement of the two laser beams form an interference fringe pattern which is captured in a CCD camera and stored on a personal computer. Shearing Interferometry Images, shown in Figure 4, are printed with a video copy processor.

In Figure 4, two laser beams interfere to produce fringes. These fringes are rotated from the horizontal axis by an amount θ and laterally displaced by an amount S . Slight longitudinal adjustments along the optical axis of the two lenses in one of the arms of the Twyman-Green interferometer creates defocus. Fringe rotations on the order of $\lambda/10$ can be monitored using the electronic imaging process.

Two beams overlap each other causing an interference pattern in Figure 5. One fringe equals one wavelength. S is equal to the shear distance, the distance between the centers of the two beams. Fringe rotation, θ , is the angle between the fringe and the horizontal axis. T equals to fringe distance, the distance between two fringes. Wavelength denotes λ , and Y is equal to the beam semi-diameter, the distance between the edge of the circle to the center of the beam. These values contribute to equations of defocus:

$$\# \text{ waves of defocus} = \frac{Y^2 \sin \theta}{2 S T}$$

$$\text{OPD} = \frac{Y^2 \lambda \sin (\theta)}{2 S T}$$

Figure 4

Figure 5

Defocus or decollimation, is the physical curvature between two wavefronts. Converging or diverging beams characterize a defocused wavefront. The optical path difference is related to the defocus by the optical wavelength λ .

V. Experimental procedures

The experiment involved varying different positions of fringes and calculating the values into the equation. The first step involved recording images with the video copy processor. The angle of each image was found by extending the lines of any one of the fringes and the horizontal line. A ruler was used to measure the horizontal line and the perpendicular drawn from the fringe to horizontal. The tangent theta was calculated with these measurements. By assessing the distance between any two fringes and dividing it by the number of fringes in between, the value for fringe distance was acquired. The value for shear was found by measuring the distance of the two edges of a beam minus the distance of the two edges of the interference intersection. Since the shear and tilt have to be in unit radius, it is necessary to divide by the radius. In order to minimize the affect of human error, values of S/Y and T/Y were averaged.

VI. Experimental Images

Figure 6 is a picture of the shearing fringes rotated to position 4 at a large angle. This shows that large fringe rotation indicates large defocus. The larger θ is, the larger the defocus that is introduced.

Shearing fringes rotate in opposite directions for positive and negative defocus. Positive defocus rotates clockwise and negative defocus rotates counterclockwise. Position 2 shearing is illustrated in Figure 7.

Figure 6

Figure 7

In Figure 8, two-beam interference patterns and shearing interference patterns are portrayed. The horizontal axis and fringes are parallel to each other, therefore indicating that the laser beam is collimated. Shearing fringes are coarse compared to two-beam SSPD fringes.

High frequency carrier fringes are used in two-beam interferometry to detect the wavefront of the laser beam with the SSPD technique developed in the Wavefront Analysis Laboratory. As shown in Figure 9, a pink circle that surrounds the fringes represent the area of interest. This AOI will be shrunk to test the phase of the beam.

Figure 10 demonstrates that there is an initial error on the two-beam phase map. These bright colors are responsible for deviation in the graph. The two-beam SSPD analysis reinstates the residual phase error on the collimated beam.

Two-beam interferometry confirms the small decollimation sensed with shearing technique. In Figure 11, the phase map for position 3 is pictured. Each central color equals to approximately $\lambda/100$.

As illustrated in Figure 12, the position 4 phase map shows that each color is approximately $\lambda/20$. This means that two-beam interferometry easily measures large amounts of decollimation.

Figure 13 shows a phase map of position 2. Higher order aberrations cause disagreement between two-beam and shearing interferometry. The colors change inwardly from the strong edge to center from Figure 12 to Figure 13.

VII. Results

Figure 14 illustrates the shearing angles referenced to the horizontal axis at various positions. After substituting the values in the equation, the final results were compared to the two-beam interferometry done on the computer. Position 1 was clockwise at a small angle, position 2 clockwise at a big angle, position 3

Figure 8

Figure 9

Figure 10

Figure 11

Figure 12

Figure 13

Figure 14

Shearing angles referenced to horizontal

Position 1

$$13.3/250 = \sin \theta = 0.053$$

$$T = 7.83$$

$$T/Y = 0.253$$

0.203 waves

Position 2

$$42.3/250 = \sin \theta = 0.167$$

$$T = 7.67$$

$$T/Y = 0.247$$

0.655 waves

Position 3

$$4.7/250 = \sin \theta = 0.019$$

$$T = 7.83$$

$$T/Y = 0.253$$

0.073 waves

Position 4

$$47.7/250 = \sin \theta = 0.187$$

$$T = 7.75$$

$$T/Y = 0.25$$

0.725 waves

$$Y = 31$$

$$S = 16$$

$$\text{average } S/Y = 0.516$$

$$\text{average } T/Y = 0.250$$

counterclockwise at a small angle and position 4 counterclockwise at a big angle. The compiled phase data are shown in a table in Figure 15. All of the values obtained are in waves. SA3 is the third order spherical aberrations. The final results, demonstrated in Figure 16, can be shown by a graph, two-beam defocus versus shearing defocus. The dashed line represents a perfect measurement. The red squares represent the values obtained through shearing interferometry. This graph shows that shearing interferometry is quite close to the two-beam interferometry. Therefore, shearing interferometry could be an advantageous way to test wavefronts.

The usefulness and practicality of shearplate has both advantages and disadvantages. The advantages of a shearplate are: 1) does not require a separate reference, unlike two-beam interferometry; 2) can determine the phase information quickly with low to medium qualitative precision; 3) can check the alignment of lenses (to see if it is in backwards, etc.) and 4) can check collimation for the alignment table and pinhole production research projects. However, one disadvantage is that special software is required to analyze the interferograms. Presently, no computer code programs can study them correctly.

A shearplate is relevant to laser fusion in that a shearplate can be employed for quality assurance of optics in high powered laser systems such as OMEGA. In addition, the shearing process can analyze the wavefront of optics in the laser system. Measuring amplified laser beams and the associated optical system separately utilizing a CW laser source will allow the shearplate to determine if the optics meet the standard quality. Also, it will help to understand how solid state lasers irradiate fusion targets and drive fuel in thermal nuclear reactions. Shearplates can easily be used to determine the collimation state of a laser beam, and small laser sources, both pulsed and CW (continuous wave).

Figure 15

Compiled phase data

Position number	Shearing defocus (waves)	2-beam defocus (waves)	PV (waves)	RMS (waves)
0	0.000	0.029	0.112	0.022
1	0.203	0.206	0.236	0.065
2	0.655	0.603	0.547 spherical SA3=-0.311	0.180
3	-0.073	-0.010	0.080	0.018
4	-0.725	-0.534	0.503 spherical SA3=0.49	0.163
SA3 causes error in defocus comparison between 2- beam and shearing				

Figure 16

VIII. Conclusion

Results of this experiment show that shearing interferometry is more effective than two-beam interferometry. A shearplate is easier and faster to set up, does not need perfect reference wavefront to operate and is portable and vibrationally stable. Also, shearing interferometry verifies the mathematical equation for defocus. And, demonstrates $\lambda/7$ to $\lambda/10$ collimation sensitivity.

In conclusion, shearing interferometry is a simple and accurate method to collimate laser beams. Wavefront analysis using shearing interferometry will play an important role in the University of Rochester Laboratory for Laser Energetics OMEGA Laser System. This accomplishment of establishing a basis for shearing will help the Wavefront Analysis Laboratory in calibrating all their shearplates. Hopefully, the technique of shearing interferometry will be implemented in the near future.

END

**DATE
FILMED**

6 / 1 / 92