QUARTERLY PROGRESS REPORT #6

TITLE: Combustion of Dense Streams of Coal Particles

GRANT NO: De-FG-22-90PC90310

REPORT PERIOD: Nov. 29, 1991 to Feb. 28, 1992

PRINCIPAL INVESTIGATOR: Kalyan Annamalai
Mechanical Engineering
Texas A&M University
College Station, TX 77843-3123
409-845-2562

GRADUATE STUDENTS: K. Esam
C. Gopalakrishnan
X.Y.Du

SUBMITTED TO: Pittsburgh Energy Tech. Center
US Department of Energy
P.O. Box 10940
Pittsburgh, PA 15236

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER
ds

Objectives for November 29, 1992 to February 28, 1992

1. Submit the manuscript on Part II of review article.
2. Complete the experimental set up with the video-imaging system.
3. Obtain preliminary data on combustion of coal streams.

Activities During Nov. 29, 1991 to Feb. 28, 1992

1. The proof of Part I of review article dealing with drop arrays and cloud is about 75 pages long and is scheduled to be published in the next issue of Prog. in Energy and Comb. Sc. The final version of Part II of Review is planned for submission sometime in April 1992. Interesting observations are: 1) the similarity between drop array and char array combustion, ii) zones of combustion of porous char and group combustion, and iii) effectiveness factors for cloud combustion in addition to effectiveness factor for porous char in the cloud. Further analytical results on char array combustion and internal ignition of porous char are presented. ignition etc.
2. The flat flame burner set up is complete (Fig.F.F.1). Water cooled isokinetic sampling system is complete (Fig.F.F.2). Preliminary runs have been made and a blue flat flame has been obtained. See progress report on Flat Flame Burner.

A CID camera, EPIX frame grabber and software, Sony monitor and a 486 Computer to handle image processing frame by frame have been acquired. Difficulties were encountered in assembling the system components acquired from various sources due to compatibilities of cables, etc. They are being resolved. See progress report on Video-imaging.

3. A new coal feeder has been constructed for feeding through the flat flame burner. Coal experiments have not yet been conducted. Coal samples from Penn State Coal Bank were also acquired for use in the experiments. They include bituminous and sub-bituminous coals of differing VM. With funds from other sources, a coal crusher (for wet to dry grinding) and a SO_x analyzer are being acquired.

Objectives for Feb. 29, 1992 to May 28, 1992

1. Conduct experiments with coal streams and determine the burnt fraction as a function of coal denseness. Since the burner is mounted on a platform which is vertically adjustable, the burnt fraction could also be obtained as a function of residence time.
2. Compare the experimental data on burnt fraction with predictions.
3. Since the video-imaging system is also complete now, video imaging will be carried out in order for the following: a) cigarette flame (stationary source), b) Two cigarette-lighter flames adjacent to each other (stationary), c) two match stick flames in various configurations (one behind other, adjacent to each other, etc.) and d) double flame in the coal stream injected into the flat flame burner.

FLAT FLAME BURNER SET UP

Combustion of coal particles has been experimentally studied earlier using various techniques including laminar flow reactor and flat flame burners. Flat flame burners provide better optical accessibility of flames and feasibility for adjusting the residence time compared to laminar flow reactor. This section briefly presents the flat flame burner arrangement and the experimental set up used.

Flat flame burner:

The burner has been described in the previous report #5.

The burner is of cylindrical construction with a 6 cm diameter flame area. The flame produced is stabilized above this 6 cm diameter sintered stainless steel plug with cooling coil embedded in it. Water is used as cooling medium. The flame produced is shielded from entrainment effects by a inert gas (nitrogen) shroud. The burner has vertical coal feeding tube at the center. The fuel air mixture entering through the sintered steel plug provides the flat flame (and hence the necessary heat source) for ignition and combustion of coal particles. The burner is mounted on a movable platform which enables adjustment of residence time.

Experimental set up:

Figure F.F1 shows the overall schematic of the burner facility. Methane gas is used as fuel while F.F2 shows the details of the water cooled coal collection system. Methane from the gas cylinder is passing through a flow meter(0 to 5 scfh) before mixing with air. The compressed air from the line is also similarly flowing through flow meter(0 to 200 scfh). These two flow meters controls the fuel and air proportions in the mixture. This mixture flow can also be controlled. The mixture is ignited at the burner after passing through sintered plug and a flash back arrester. Nitrogen gas from a cylinder is passed through an annular sintered ring. It serves as shroud gas in minimizing air entrainment and change in O₂ concentration. This nitrogen flow is also metered (0 to 200 scfh) at the flow control panel. The sintered plug of the burner is constantly cooled by circulating water.

Experiment:

i) calculation:

Superficial flow velocity of Methane fuel air mixture is assumed as 1.5 m/s. The flow rate for the fuel mixture for this velocity with the 6.6cm dia injectors calculated to be $(3.14 \times 0.066^2 / 4) \times 1.4 = 0.00513 \text{ m}^3/\text{s}$ ie 650 scfh(hot). The cold flow can be estimated as 160scfh assuming $T_{\text{hot}} = 1200\text{K}$ and T_{cold} as 300 K.

For 10% oxygen concentration in the products,

The air fuel ratio is 19.297 for this condition. Hence for every scfh of methane, 19.3 scfh will be supplied. Thus for 160 scfh flow of the mixture, methane flow is estimated as 8 scfh and air flow is found to be 152 scfh. The air flow will be set around this value to maintain 10% oxygen concentration. ZrO₂ analyzer will be used to maintain oxygen level.

Proceeding similarly, Nitrogen flow is calculated to be $(1.5 \times 1160 \times 10^{-6} \times 300 / 1200) 4.4 \times 10^{-4} \text{ m}^3/\text{s}$ ie 55 scfh

ii) experiment

First, the burner cooling water is allowed to flow. Methane flow is first started at 2 scfh and air flow is increased in steps. The flame is yellowish in color to start with and changes its color to blue as the air flow rate is increased. Initially carbon of methane cracks due to oxygen starvation and results in soot burning giving rise to characteristic yellow color. Then the air flow is adjusted until a flat blue flame is anchored to the burner. The cooling water flow is also adjusted to anchor flame at the burner and later on the flow is allowed to be normal.

The first step, before combusting coal particles, is to get stabilized temperature range above the burner. Hence the sheathed 'K' chrome alumel thermo couples are used to find the maximum temperature that could be attained with this flame. Since these thermocouples are slow in response and not suitable for high temperatures it is decided to use Pt-Rh 5 or 10 nil thermocouples. The same experimental procedure will be followed once the thermocouples are acquired.

Further Work:

The flow control panel will be installed with additional flow meters required for carrier, pressurizing, fluidizing and exhaust air for feeding coal particles. The hose connections from the air line to control panel, then to coal feeder are to be made. The coal feeding tube from the feeder to the burner is to be fixed. Once the particle collector system is made operational, the actual experiment with coal particles can be started.

WATER COOLED ISOKINETIC SAMPLING SYSTEM

1- Design of a Coal Collection System (see attached sketch).

A coal Collection system has been designed to withdraw a cylindrical stream of burning coal particles fed to the Flat Flame Burner. The system provides a constant or variable suction pressure for isokinetic sampling. System components include:

A) Vacuum Pump

The vacuum pump is the main component in this system. It creates suction pressure capable of withdrawing stream of burning coal particles. Specifications of the pump are as follows: 115 Volts, 1725 RPM, 1/2 Hp, Suction Pressure and manufactured by GAST Corporation.

B) Pyrex Beaker

The used Pyrex beaker can stand high temperatures as well as high pressures. It collects the sample particles withdrawn from the flat flame burner after being cooled, thus enabling a later analysis of the burned coal.

C) Manometer

A manometer is used here to measure the pressure in the suction line.

D) Water Cooled Collector

A water cooled collector has been designed to withdraw the burning coal samples. The cooling system is designed in such a way to cool the collector effectively.

F.F.1: schematic for flat flame burner experimental set up

F. F. 2 : Coal Collection System

Image Processing System Setup

The image processing system consists of the following components:

A) CID 2250D2 camera

Features include: 1- Square contiguous pixels.

2- A synchronous full-frame capture.

3- High-Speed variable frame output.

4- Superior anti-blooming.

5- Multiple-frame integration.

6- Wide spectral response.

7- On-chip windowing.

Source: CIDTEC

101 Commerce Blvd.

Liverpool, NY. 13088

B) 4MEG Video Imaging Board

This frame grabber offers unparalleled flexibility in video acquisition and display. Analog video signals can be digitized at up to 10 million samples per second, a reconfigurable image memory can be organized as one or many images of arbitrary dimension and the pixel clock can be generated internally or derived from an external source.

C) 4MIP Supporting Software

4MIP Software allows immediate access to the frame grabber functionality. Functions and image processing routines can be invoked via a mouse interface.

Source: EPIX

310 Anthony Trail.

Northbrook, Illinois 60062

D) 486 personal computer

Features include: 1- Intel 80486 C.P.U rated and operating at 33 Mhz.

2- 8 Mb system R.A.M.

3- 3.5" 1.44 Mb and 5.25" Mb floppy drives.

4- 200 Mb Hard drive capacity.

5- 14" monitor with VGA board.

6- 101-key enhanced keyboard.

Source: ADOSEA Tech.

College Station, Tx. 77840

E) High resolution color monitor

Features include: 1- PAL, SECAM, and NTSC color systems.

2- Horizontal Resolution-600 lines, 900H x 200V pixels.

3- Character Display-2000 characters.

4- RGB inputs and digital input, and video input.

Source: MicroDISC Inc.

4615 South West Freeway

Suite 420E

Houston, Tx. 77027

All the components have been acquired and the system is in the process of integration. Difficulties were encountered in integrating the components due to misaligned cables. They are being fixed. Imaging applications will be tried on different flame structures such as cigarette, candles etc. before applying to coal flame.

**DATE
FILMED**

7/22/92