DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

DISCLAIMER
This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

LALP--81-45

January 1982

DE82 013755

Los Alamos MINI-REVIEW

Fenton Hill during drilling of well EE-3. This 20-acre site in the Jemez Mountains of northern New Mexico contains both the pioneering Hot Dry Rock Research (Phase I) System and the follow-on Engineering (Phase II) System. The Research System, behind the red drilling rig, has operated successfully for more than a

year at heat-extraction rates up to 5 million watts with no detectable environmental effect. The Engineering System, under construction, will investigate the economic feasibility of generating electricity for commercial use.

NOTICE

PORTIONS OF THIS REPORT ARE UNCLASSIFIED
It has been reproduced from the best available copy to permit the broadest possible availability.

The hot dry rock geothermal energy project

MASTER
Don C. Smith

Geothermal energy, the natural heat in the Earth's interior, is the largest supply of usable energy that is accessible to man. Most of this heat originates in the slow decay within the Earth of elements of the types that are mined to make fuels for nuclear reactors—chiefly forms of uranium, thorium, and potassium. Because the soils, gravels, and rocks that make up

the Earth's outer crust are poor conductors of heat, much of the heat produced in this way has been retained within the Earth. As a result, most of the Earth's interior is very hot—at or near the melting temperatures of the rocks and metals that exist there.

When a hole is drilled down from the Earth's surface, it usually passes first through layers of sediments and frac-

tured rock that are kept cool by the circulation of groundwater. In some places, the hole may then encounter a trapped body of natural hot water or steam: a hydrothermal reservoir. Unfortunately (because these are excellent sources of energy) such occurrences are quite rare. Usually as the hole is deepened it penetrates rock of progressively decreasing porosity and permeability,

MBW

MINI REVIEW

THERMAL GRADIENT MAP OF THE CONTERMINOUS U.S.

Fig. 1. Preliminary regional map of conductive geothermal gradients in the United States.

with less and less water contained in it or moving through it. Typically, as the hole goes deeper, it becomes hotter and drier, hence "hot dry rock" (HDR).

The rate at which temperature increases with depth is called the geothermal gradient. On the average it is about 30°C per kilometer of depth (17°F per thousand feet); however, where the crust is thin or it has been disturbed by volcanic activity or large-scale earth movements, the gradient may be much higher. Figure 1 is a preliminary map of the 48 adjacent United States, showing known hot spots in regions where the measurements do not appear to be affected by groundwater circulation, the presence of hydrothermal reservoirs, or nearby volcanism. The map is still very incomplete, but it indicates that areas of this type, with above-normal geothermal gradients, cover not less than 20% of the land area of the United States. At usefully high temperatures and at depths that can be reached with present drilling technolo-

gy, this represents a supply of energy much larger than that in all of the nation's fossil fuels and uranium combined.

Extracting heat from the rock

In natural hydrothermal systems, surface waters have penetrated the Earth

Fig. 2. Pressurized "penny shaped" hydraulic fracture.

deeply enough to reach hot rock. They have been heated by extracting heat from the rock, but were trapped in some porous formation or large fracture system before they could return to the surface.

When there is little or no natural fluid in the rock, the obvious—and probably cheapest—way to recover heat is to imitate nature by creating a system that will permit water to circulate through the rock. There are a number of ways in which this might be done. What now seems to be the safest and least expensive method is to drill two holes a few hundred meters apart and then connect them through the hot rock by means of a set of cracks produced by pressurizing one of the holes. This operation, hydraulic fracturing, is performed hundreds of times a week in oil and gas wells, to increase the flow of oil or gas toward the wells. Most simply, it is accomplished by pumping water down the well until the downhole pressure is sufficient to split the wall of the hole, much as the expansion that accompanies freezing will split a water pipe. By continuing to pump water into the crack, we can extend it radially from the borehole to distances of hundreds of meters (Fig. 2). The fracture is a very narrow "penny shaped" opening. If it intersects or is intersected by a second well, a connected underground circulation loop is completed, with a very large surface area for heat extraction.

Fortunately, at depths where usefully hot rock is likely to be found, hydraulic fractures tend to grow vertically and are generally oriented in a specific compass direction (controlled by the stress condition in the rock). Once this direction has been determined in any given locality, the behavior of a hydraulic fracture can be predicted with reasonable confidence.

The hot dry rock geothermal energy program

Fig. 3. Original Phase I Fenton Hill heat-extraction system.

The HDR program

In 1970, a group of Los Alamos scientists conceived the idea of using hydraulic fracturing to create a heat-extraction loop in low-permeability hot rock in the Earth's crust. After several years of background studies, preliminary experiments, and development of necessary downhole technology, equipment, and instruments, they completed the loop shown in Fig. 3. The connection between the two wells (EE-1 and GT-2) was made in hot granitic rock underlying the Jemez Plateau at Fenton Hill, New Mexico (Fig. 4), at a depth of about 2600 m (8500 ft) and a rock temperature of about 185°C (365°F). The system operated successfully for several months

in 1977 and 1978. It was then enlarged by additional hydraulic fracturing and operated again for periods up to 9 months.

Cool water pumped into EE-1 was heated as it circulated through the fracture system, was brought to the surface through GT-2 under sufficient pressure to prevent boiling, and then was cooled and reinjected in EE-1 to recirculate and bring up more heat. During the 9-month run, water leaving the fracture system cooled from about 158°C to 149°C (316°F to 300°F). Heat was extracted at rates up to 5 million watts (17 million Btu/h), water-loss rates were low, water quality remained good, and there were no detectable environmental effects from system operation. Probably because the rock shrank as heat was extracted from

it, both the volume and the effective heat-transfer area of the fracture system increased with operating time.

When it would not interfere with other experiments, part of the heat brought to the surface was used in an experimental electrical generating unit. Heat from the water was used to boil Freon 114, whose heavy vapor drove a small turbine. The turbine rotated an alternator, producing 60 kVA of electrical power that was used at the site.

Results from this system demonstrate the technical feasibility of creating and operating a hydraulically fractured HDR energy system. However, the system is too small to be commercially useful or to give an accurate estimate of the economics to be expected of a commercial-size system. Therefore, a larger,

Fig. 4. The Fenton Hill location.

Fig 5. Phase II Fenton Hill system, under construction.

deeper, hotter heat-extraction loop is now being constructed at Fenton Hill; it is designed to produce heat at a rate of about 35 million watts (thermal), at a temperature above 200°C (390°F) for a period of at least 10 years. As illustrated in Fig. 5, two very deep, inclined holes have been drilled into granitic rock at a temperature of about 300°C (570°F). To provide the heat-transfer area needed to extract heat at a high rate for a long time, they will be connected by a number of parallel, vertical, hydraulic fractures. If the system operates as planned, it may eventually be used as the energy supply for a small commercial electrical power plant.

In the meantime, geological, geophysical, geochemical, and heat-flow studies are being conducted throughout

the United States to improve the resource map of Fig. 1 and to identify promising HDR areas for future experiments or eventual commercial development.

Program participation

The HDR Geothermal Energy Program is sponsored by the Division of Geothermal Energy of the US Department of Energy and is managed by Los Alamos National Laboratory. Its goal is to establish the commercial usefulness of an extremely large, broadly distributed, new energy source that is environmentally benign and secure against interruption.

Because the energy resources of most other countries are even more limited than those of the United States, foreign interest in HDR energy systems is increasing. Following a NATO study, the United States and Italy are cooperating in HDR systems development. Both the European Community and the International Energy Agency now have HDR programs. The governments of West Germany and Japan contribute financially to the Fenton Hill Project, are represented on its International Steering Committee, and assign scientists to work at Los Alamos. An agreement between the University of California and the Camborne (England) School of Mines provides for cooperation between the United States and United Kingdom pro-

grams. Both short- and long-term foreign visitors to Los Alamos are common, and their presence points to the international appeal of the HDR program.

The future of HDR

Many variations of the HDR system can be developed, making it possible to recover useful heat in almost any location or geological environment. Preliminary economic studies indicate that where geothermal gradients are high and the subsurface geology is favorable, the cost of heat from HDR should be comparable, for example, to that from coal. However, where the gradient is low, drilling is difficult, water loss is excessive, or rock/water interactions lead to scaling or corrosion problems, economics may not be favorable. Additional large-scale experiments are needed in a variety of locations and geologies before the widespread usefulness of HDR energy systems will have been convincingly demonstrated.

However, if these experiments are successful, they will make available to the world an essentially inexhaustible, secure, decentralized energy supply that is environmentally benign and capable of contributing significantly to solution of the world's energy problems.

For more information write to Morton C. Smith, Los Alamos National Laboratory, Los Alamos, NM 87545. Permission to reproduce this article is granted.

Los Alamos National Laboratory is operated by the University of California for the United States Department of Energy under contract W-7405-ENG-36. The Laboratory is an affirmative action/equal opportunity employer.