PROGRESS REPORT AND FUTURE PLANS

DOE DE-FG02-91ER25099

Numerical Methods for Molecular Dynamics
Robert D. Skeel, University of Illinois

DOE/ER/25099--1

DE92 010934

Amount: 30,822 first year

Period: August 1, 1991 to July 31, 1993.

1. Introduction. This grant supports the research of a Ph.D graduate student Michael Holst, who is working with his thesis adviser Faisal Saied and the PI. This report was prepared by M. Holst under the supervision of the PI.

This report summarizes our research progress to date on the use of multigrid methods for three-dimensional elliptic partial differential equations, with particular emphasis on application to the Poisson-Boltzmann equation of molecular biophysics. This research is motivated by the need for fast and accurate numerical solution techniques for three-dimensional problems arising in physics and engineering. In many applications these problems must be solved repeatedly, and the extremely large number of discrete unknowns required to accurately approximate solutions to partial differential equations in three-dimensional regions necessitates the use of efficient solution methods.

This situation makes clear the importance of developing methods which are of *optimal order* (or nearly so), meaning that the number of operations required to solve the discrete problem is on the order of the number of discrete unknowns. Multigrid methods are generally regarded as being in this class of methods, and are in fact provably optimal order for an increasingly large class of problems. The fundamental goal of this research is to develop a fast and accurate numerical technique, based on multi-level principles, for the solution of the Poisson-Boltzmann equation of molecular biophysics and similar equations occurring in other applications.

An outline of the report is as follows. We first present some background material, followed by a survey of the literature on the use of multigrid methods for solving problems similar to the Poisson-Boltzmann equation. A short description of the software we have developed so far is then given, and numerical results are discussed. Finally, our research plans for the coming year are presented.

2. Background. We begin with a brief summary of some basic ideas about the Poisson-Boltzmann equation and the numerical solution of elliptic equations, including discretization techniques and multigrid methods.

Molecular Biophysics and the Poisson-Boltzmann Equation. In the molecular dynamics simulation of a macromolecule in an ionic solution, Newton's equations of motion describing the dynamics of the macromolecule are integrated numerically. However, before Newton's equations can be integrated, the electrostatic forces must be evaluated, and this is often the most time-consuming part of the entire simulation. Direct calculation of the forces can be accomplished for only a small number of solution molecules due to its complexity.

In 1923, Debye and Hückel proposed a continuum method for the calculation of electrostatic free energy of small spherical ions in an ionic solution as an alternative method to treating the solution molecules individually [39]. This idea has been extended to more complicated macromolecules (cf. [42]), and is based on the model shown in Figure 1. In the model, the ionic solution is treated as a continuum, with the molecule surrounded by an exclusion layer in which no ions are present. The electrostatics of this model are described by Gauss' law and the Boltzmann distribution law. After some analysis, a three-dimensional second order nonlinear partial differential equation governing the

FIG. 1. Two-dimensional view of the three-dimensional Debye-Hückel model.

electrostatic potential $\Phi(\mathbf{r})$ at position $\mathbf{r}$ results:

$$(1) \quad -\nabla \cdot (\epsilon(\mathbf{r}) \nabla \Phi(\mathbf{r})) + \bar{\kappa}^2 \left(\frac{k_B T}{e_c} \right) \sinh \left(\frac{e_c \Phi(\mathbf{r})}{k_B T} \right) = 4\pi \sum_{i=1}^{N_m} q_i \delta(\mathbf{r} - \mathbf{r}_i) \quad \text{in } \Omega \subset \mathbb{R}^3.$$

The piecewise constant dielectric $\epsilon(\mathbf{r})$ takes different values in the three regions in the model, and the Debye-Hückel parameter $\bar{\kappa}$ depends on properties of the solution such as ionic strength. The macromolecule is represented by N_m point charges q_i at positions $\mathbf{r}_i$; hence the form of the right hand side of (1). The constants e_c , k_B , and T represent the charge of an electron, Boltzmann's constant, and the absolute temperature, respectively. We refer to equation (1) as the *nonlinear Poisson-Boltzmann equation* (NPBE). See either of [39, 42] for more thorough discussions of Debye-Hückel theory and the Poisson-Boltzmann equation.

Using the first term in the series expansion for $\sinh x$, we can approximate the solution of the NPBE by solving the following linearized equation

$$(2) \quad -\nabla \cdot (\epsilon(\mathbf{r}) \nabla \Phi(\mathbf{r})) + \bar{\kappa}^2 \Phi(\mathbf{r}) = 4\pi \sum_{i=1}^{N_m} q_i \delta(\mathbf{r} - \mathbf{r}_i) \quad \text{in } \Omega \subset \mathbb{R}^3.$$

We refer to (2) as the *linearized Poisson-Boltzmann equation* (LPBE).

Note that analytic solutions exist only in the case of the LPBE, and these are valid only in the simplest of situations; therefore, the use of highly efficient numerical methods for approximation of these solutions may lead to substantial progress in molecular dynamics simulation.

Elliptic Partial Differential Equations. The LPBE is an example of a second order linear elliptic equation, written more generally as:

$$(3) \quad -\nabla \cdot (a \nabla u) + b \cdot \nabla u + cu = f \quad \text{in } \Omega \subset \mathbb{R}^3, \quad u = g \quad \text{on } \Gamma.$$

In the nonlinear (or more correctly, *semi-linear*) case, the general form is:

$$(4) \quad -\nabla \cdot (a \nabla u) + b(\mathbf{x}, u, \nabla u) = 0 \quad \text{in } \Omega \subset \mathbb{R}^3, \quad u = g \quad \text{on } \Gamma.$$

Material discontinuities or *interfaces* in physical problems in general lead to discontinuities in the coefficients a , b , and c , and possibly f , in the governing equations. It is well-known that numerical methods have difficulties with these types of problems.

Discretization Techniques. The regularity of the solution must be considered in the discretization process. Note that a Taylor series approach to discretization is not reliable since the truncation error depends on various derivatives of the solution. An alternative is the *box method*, which has been one of the standard approaches for discretizing two and three-dimensional interface problems occurring in reactor physics and reservoir simulation [22, 38, 45]. If discontinuities lie along box boundaries, then rigorous error estimates may be obtained, and the resulting linear algebraic systems have several other important properties [10, 44].

A second alternative is the *finite element method*, which utilizes the weak forms of (3) and (4). A simple application of the finite element method ignoring the interfaces may lead to large error near interfaces, as the standard error estimates involve terms depending on the solution regularity *within* individual elements in the domain [3, 41]. However, if coefficient discontinuities lie along element boundaries, then good approximation with rigorous error estimates can be obtained.

Multigrid Methods. Multigrid methods are highly efficient numerical techniques for solving the algebraic equations resulting from the discretization of a partial differential equation on a fine mesh by using auxiliary problems on coarser meshes. They are provably optimal order for certain classes of problems [8, 14], and are also extremely effective for a much wider class of problems. Detailed descriptions of the multigrid method, for both linear and nonlinear elliptic problems, can be found in [17, 27].

For interface problems, it has been demonstrated numerically [1, 20, 21] that it is often desirable to form the coarse grid equations using the *Galerkin procedure*:

$$L_H = \tau L_h p,$$

where L_h and L_H are the fine and coarse grid discrete operators, respectively. In addition, the linear *prolongation* operator p (with $\tau = p^*$) is often constructed using elements of the discrete operator L_h , referred to as *operator interpolation* [1].

3. Summary of Overall Progress. We now discuss some of the work completed so far, including a brief survey of the multigrid literature, and a discussion of the software we have developed.

3.1. Survey of the Multigrid Literature. The formulation of a multigrid method appeared first in the Russian literature in [23], although block relaxation methods which are similar in some respects are described earlier in the west [40, 45]. Multigrid methods were applied to problems with discontinuous coefficients shortly after 1980, although convergence theory applied only to the case of regular solutions.

Interface Problems. One of the earliest of these applications was by Alcouffe et al. in [1]. It was found that the usual formulations of multigrid performed poorly when applied to the two-dimensional neutron diffusion equation having the form of (3), where the coefficients had jump discontinuities along interfaces in the domain. To improve the performance of multigrid, the concept of *operator interpolation* was developed, based on the idea of approximating the continuity of $a\nabla u$ across internal interfaces. When the box scheme was used to discretize (3), it was found that the resulting combination of point and line relaxation, operator interpolation, and Galerkin formulation of the restriction operator and coarse grid equations produced the typical good convergence properties of the multigrid method.

Other numerical studies of the techniques in [1] for both neutron diffusion and reservoir simulation include the three studies by Behie and Forsyth in 1983 [11, 12, 13], the 1985 paper by Scott [38], the 1987 study of Dendy [21], the application to the pressure equation of reservoir simulation in [22], and the recent paper by de Zeeuw [20]. In particular, in [21] it was found that operator interpolation, Galerkin formulation of the coarse grid equations, and plane relaxation based on two-dimensional multigrid (suggested in [43]) combine to produce multigrid methods which perform quite well.

Liu, Liu, and McCormick [31] recently developed an alternative to the Galerkin formulation of the coarse grid equations for the two-dimensional case. Their method produces coarse grid operators which do not require extensive computation to form and which remain five-point operators on all coarse grids. Additionally, they develop an operator-based interpolation scheme similar to that of [1]. Numerical results indicated that their method achieved good convergence rates, comparable to that achieved by the normal multigrid formulation for smooth problems.

Convergence Theory. The first multigrid convergence proofs [4, 24, 25] using Fourier analysis were restricted to model problems. Results can be shown for more general problems if a variational formulation is used. The earliest approaches [2, 8, 26, 36] were for the W-cycle only, and convergence was shown only for "sufficiently many" smoothings per iteration. In addition, these proofs hinge on duality arguments which require a certain elliptic regularity of the solution, as well as assumptions about the approximation properties of the finite element subspaces involved.

More recent V-cycle proofs for any positive number of smoothings per iteration include [7, 14, 32, 34]. These proofs also require the regularity and approximation assumptions, and typically hold only for the symmetric positive definite case. The convergence rate bounds are of the form:

$$(5) \quad \|u - u_l^1\| \leq \delta \|u - u_l^0\|, \quad \delta = \frac{C(\alpha)}{C(\alpha) + \nu} < 1,$$

where $\|\cdot\|$ denotes the energy norm, ν is the total number of smoothings, and $C(\alpha)$ is a constant depending on the regularity parameter α of the underlying elliptic problem.

For the duality arguments used in most of the above approaches, a full elliptic regularity assumption ($\alpha = 1$) of the following form is required: there exists a constant C satisfying

$$\|u\|_{1+\alpha} \leq C \|f\|_{\alpha-1},$$

where $\|\cdot\|_s$ denotes the usual Sobolev norm of order $s \in \mathbf{R}$. Other proofs [8] require only the weaker assumption $\alpha > 0$. More recent results include [16, 33], which apply to nonsymmetric problems. In [15], the V-cycle is analyzed specifically in terms of the regularity parameter α , which must be positive.

There are no convergence proofs in the case of discontinuous coefficients, although it has been suggested that the convergence theory for hierarchical basis multigrid methods, which requires only the verification of a strengthened Cauchy-Schwarz inequality within each element in the domain and no regularity assumptions, may be applicable [6]. There is also a lack of convergence theory for the techniques developed for discontinuous coefficients, such as methods employing operator interpolation.

3.2. Software Development. Work during the period of August 1991 through January 1992 has involved the development of several software tools for the solution of the Poisson-Boltzmann equation, including an initial multigrid code. A description of some related work on multigrid methods for parabolic equations that led to the current project can be found in [29, 30].

MultiGrid Code. The multigrid code which has been developed is also applicable to more general second order linear elliptic equations of the form (3). It is robust, easy to use, and runs with high parallel efficiency on a number of shared memory architectures such as the Cray Y-MP. Features of this code include:

- solution of three-dimensional linear elliptic problems in real, double, or complex arithmetic
- automatic compiler directive insertion for several different machines
- correction scheme or full approximation scheme, V-cycle or full multigrid
- library of smoothing operator choices (including point red/black Gauss-Seidel)
- library of test problems (including the Poisson-Boltzmann equation with uniform dielectric)

- solution output in ASCII or NCSA HDF (color) format
- automatic post-run performance analysis (timings and megaflop rates)
- near gigaflop performance on an eight processor Cray Y-MP

An additional feature is automatic installation on UNIX-based machines.

The interface to the multigrid code is through a single FORTRAN subroutine call of the form

```
call mgdriv (iparam,rparam,x,iwork,rwork,a,c,f,g)
```

where *iparam* and *rparam* contain integer and real controlling parameters, *iwork* and *rwork* are user-supplied integer and real work arrays, *a*, *c*, *f*, *g* are arrays containing the coefficients of problem (3), and *x* is the returned computed solution. This interface is similar to a standard interface used for iterative linear system solvers [28].

X Window Interface. While being extremely efficient, multigrid methods are notorious for being difficult to program and use. As an attempt to overcome these problems, we have made the single FORTRAN subroutine interface to the multigrid code extremely simple and easy to understand. In addition, we have developed an *XWindow* interface to the multigrid code, called XMG, which is written in C. XMG provides a simple interface for setting up the problem, produces interactive information during the solution process, and provides immediate access to output such as performance information and solution values, through the use of various windows, displays, and visualization tools. XMG was designed to work with NCSA's color visualization tools based on the HDF data format, *XImage* and *XDataSlice*, which allows XMG to produce color images almost immediately for display on an *XWindow*-based workstation. A sample of the type of displays provided by the interface is given in Figure 2.

Both the FORTRAN multigrid code and the *XWindow* interface run without modification on any of the machines we have tested (all had standard FORTRAN compilers and the standard *X11R4* distribution), including the following: Cray Y-MP, Convex C240, Alliant FX/2800, Sun 3 and 4, and the IBM RS6000. In addition, the FORTRAN multigrid code runs with high parallel efficiency, including over six hundred megaflops on four processors of the Cray Y-MP, as shown in Figure 3.

4. Future Work. While we have developed some extremely efficient and useful codes for the linear case, our initial multigrid code is restricted to smooth coefficients, which means that we are currently restricted to uniform dielectric values in the Poisson-Boltzmann equation (2). The dielectric discontinuities occurring in the Poisson-Boltzmann equation are typically only of one or two orders of magnitude, and also divide the region into only two distinct regions with differing dielectric values. Therefore, based on the experience of others [1], there is hope that our current method coupled with a Galerkin coarsening procedure to form the coarse grid equations may be sufficient for the LPBE.

If this is not the case, then operator interpolation techniques along the lines of [21] may have to be employed. An interesting question is whether techniques such as polynomial acceleration can improve multigrid convergence properties without resorting to special multigrid techniques.

In any event, these preliminary results indicate it is likely that a fast, useful, and easy to use software package for the solution of the linearized Poisson-Boltzmann equation, based on the multigrid method, will be one of the results of our work.

Although we have concentrated on the LPBE in this preliminary work, the final goal is a fast and accurate numerical solution technique for the full NPBE. In the nonlinear case, we are faced with all of the problems created by the discontinuous dielectric, complicated by the nonlinear nature of the problem. While there is a notion of Galerkin coarsening in the nonlinear case, the question of which coarse grid formulation will be most successful is still open one. Operator interpolation may be useful, but the definition of the interpolation operator in this case is unclear. The choice of the proper nonlinear smoothing operator, as well as the role of Newton-like methods, are other unresolved

FIG. 2. A sample display produced by the XMG software.

questions. For example, Newton-multigrid iteration has been used successfully for semi-conductor device simulation and other applications [5, 9], while others claim that the nonlinear multigrid method is more advantageous [18].

Another open question is the convergence theory of the methods for discontinuous coefficients described in this report. While numerous studies indicate that the multigrid method can be made to work with its characteristic high efficiency for these types of problems, the usual convergence theory is no longer applicable. We have begun to look at some of the fundamental convergence theorems [8, 14, 32, 34] to gain an understanding of the role of regularity in the arguments employed, and to obtain insight into how alternate arguments without regularity assumptions might be used.

Finally, regarding the Poisson-Boltzmann equation in particular, it is clear that sophisticated numerical methods have only recently begun to appear in the field of molecular biophysics. In [37], results of a Gauss-Seidel method are given, while in [19] a detailed numerical comparison of Gauss-Seidel, SOR, and conjugate gradient iteration is presented. A third paper [35] details a very sophisticated use of SOR in which a near optimal relaxation parameter is determined adaptively. In the course of this work we have been in contact with the Molecular Biophysics Group at Columbia University, authors of the *DelPhi* program described in [35]. Our correspondence has led to a collaboration in which we have been provided with maps of the dielectric and molecular charges of a protein for use in our codes, as well as potential maps will be provided for testing. This allows for the comparison of solution accuracy and sequential performance to existing techniques for the LPBE, as described in [35].

FIG. 3. Performance of the FORTRAN multigrid code on several architectures.

REFERENCES

- [1] R. E. ALCOUFFE, A. BRANDT, J. E. DENDY, JR., AND J. W. PAINTER, *The multi-grid method for the diffusion equation with strongly discontinuous coefficients*, SIAM J. Sci. Stat. Comput., 2 (1981), pp. 430-454.
- [2] G. P. ASTRAKHANTSEV, *An iterative method of solving elliptic net problems*, USSR Comput. Math. and Math. Phys., 11 (1971), pp. 439-448.
- [3] O. AXELSSON AND V. BARKER, *Finite Element Solution of Boundary Value Problems*, Academic Press, Orlando, FL, 1984.
- [4] N. S. BAKHVALOV, *On the convergence of a relaxation method with natural constraints on the elliptic operator*, USSR Comput. Math. and Math. Phys., 6 (1966), pp. 861-885.
- [5] R. E. BANK, *A multi-level iterative method for nonlinear elliptic equation*, in Proceedings of the Conference on Elliptic Problem Solvers, G. Birkhoff and A. Schoenstadt, eds., New York, NY, 1984, Academic Press.
- [6] ———, *Private communication*, 1991.
- [7] R. E. BANK AND C. C. DOUGLAS, *Sharp estimates for multigrid rates of convergence with general smoothing and acceleration*, SIAM J. Numer. Anal., 22 (1985), pp. 617-633.
- [8] R. E. BANK AND T. F. DUPONT, *An optimal order process for solving finite element equations*, Math. Comp., 36 (1981), pp. 35-51.
- [9] R. E. BANK AND D. J. ROSE, *Analysis of a multilevel iterative method for nonlinear finite element equations*, Math. Comp., 39 (1982), pp. 453-465.
- [10] ———, *Some error estimates for the box method*, SIAM J. Numer. Anal., 24 (1987), pp. 777-787.
- [11] A. BEHIE AND P. FORSYTH, JR., *Comparison of fast iterative methods for symmetric systems*, IMA Journal of Numerical Analysis, 3 (1983), pp. 41-63.
- [12] ———, *Multigrid solution of the pressure equation in reservoir simulation*, Soc. Petr. Engr. J., 23 (1983), pp. 623-632.
- [13] ———, *Multigrid solution of three-dimensional problems with discontinuous coefficients*, Appl. Math. Comp., 13 (1983), pp. 229-240.
- [14] D. BRAESS AND W. HACKBUSCH, *A new convergence proof for the multigrid method including the V-cycle*, SIAM J. Numer. Anal., 20 (1983), pp. 967-975.
- [15] J. H. BRAMBLE AND J. E. PASCIAK, *New convergence estimates for multigrid algorithms*, Math. Comp., 49 (1987), pp. 311-329.
- [16] J. H. BRAMBLE, J. E. PASCIAK, AND J. XU, *An analysis of multigrid algorithms for nonsymmetric and indefinite elliptic problems*, Math. Comp., 51 (1988), pp. 389-414.
- [17] A. BRANDT, *Multi-level adaptive solutions to boundary-value problems*, Math. Comp., 31 (1977), pp. 333-390.
- [18] ———, *Multigrid techniques: 1984 guide with applications to fluid dynamics*, Tech. Rep. GMD-Studien Nr. 85, GMD, Bonn, 1984.
- [19] M. E. DAVIS AND J. A. MCCAMMON, *Solving the finite difference linearized Poisson-Boltzmann equation: A comparison of relaxation and conjugate gradient methods*, J. Comp. Chem., 10 (1989), pp. 386-391.
- [20] P. M. DE ZEEUW, *Matrix-dependent prolongations and restrictions in a blackbox multigrid solver*, J. of Comp. and

- Appl. Math., 33 (1990), pp. 1-27.
- [21] J. E. DENDY, JR., *Two multigrid methods for three-dimensional problems with discontinuous and anisotropic coefficients*, SIAM J. Sci. Stat. Comput., 8 (1987), pp. 673-685.
 - [22] J. E. DENDY, JR., S. F. McCORMICK, J. W. RUGE, T. F. RUSSELL, AND S. SCHAFER, *Multigrid methods for three-dimensional petroleum reservoir simulation*, Tech. Rep. SPE 18409, Society of Petroleum Engineers, 1986.
 - [23] R. P. FEDORENKO, *A relaxation method for solving elliptic difference equations*, USSR Comput. Math. and Math. Phys., 1 (1961), pp. 1092-1096.
 - [24] ———, *The speed of convergence of one iterative process*, USSR Comput. Math. and Math. Phys., 4 (1964), pp. 227-235.
 - [25] W. HACKBUSCH, *Ein iteratives verfahren zur schnellen auflösung elliptischer randwert-problem*, Tech. Rep. 76-12, Universität zu Köln, 1976.
 - [26] ———, *Multi-grid convergence theory*, in Multigrid Methods: Proceedings of Köln-Porz Conference on Multigrid Methods, Lecture notes in Mathematics 960, W. Hackbusch and U. Trottenberg, eds., Berlin, Germany, 1982, Springer-Verlag.
 - [27] ———, *Multi-grid Methods and Applications*, Springer-Verlag, Berlin, Germany, 1985.
 - [28] M. HOLST, *CgCode: Software for solving linear systems with conjugate gradient methods*, Master's thesis, Dept. of Computer Science, University of Illinois, Urbana, May 1990.
 - [29] M. HOLST AND F. SAIED, *Multigrid methods for computational ocean acoustics on vector and parallel computers*, in Proceedings of the Third IMACS Symposium on Computational Acoustics, New York, NY, 1991, North Holland. (In preparation).
 - [30] ———, *Parallel performance of some multigrid solvers for three-dimensional parabolic equations*, Tech. Rep. UIUCDCS-R-91-1697, University of Illinois at Urbana-Champaign, 1991.
 - [31] C. LIU, Z. LIU, AND S. McCORMICK, *An efficient multigrid scheme for elliptic equations with discontinuous coefficients*, tech. rep., Computational Mathematics Group, University of Colorado at Denver, 1991.
 - [32] J.-F. MAITRE AND F. MUSY, *Multigrid methods for symmetric variational problems: A general theory and convergence estimates for usual smoothers*, Appl. Math. Comp., 21 (1987), pp. 21-43.
 - [33] J. MANDEL, *Multigrid convergence for nonsymmetric, indefinite variational problems and one smoothing step*, in Proceedings of the Second Copper Mountain Conference on Multigrid Methods, S. McCormick, ed., Marcel Dekker, 1986, pp. 201-216.
 - [34] S. F. McCORMICK, *Multigrid methods for variational problems: General theory for the v-cycle*, SIAM J. Numer. Anal., 22 (1985), pp. 634-643.
 - [35] A. NICHOLLS AND B. HONIG, *A rapid finite difference algorithm, utilizing successive over-relaxation to solve the Poisson-Boltzmann equation*, J. Comp. Chem., 12 (1991), pp. 435-445.
 - [36] R. A. NICOLAIDES, *On the l^2 convergence of an algorithm for solving finite element equations*, Math. Comp., 31 (1977), pp. 892-906.
 - [37] C. NIEDERMEIER AND K. SCHULTEN, *Molecular dynamics simulations in heterogeneous dielectrics and Debye-Hückel media - application to the protein bovine pancreatic trypsin inhibitor*, tech. rep., Department of Physics and Beckman Institute, University of Illinois at Urbana-Champaign, 1990.
 - [38] T. SCOTT, *Multigrid methods for oil reservoir simulation in two and three dimensions*, J. Comp. Phys., 59 (1985), pp. 290-307.
 - [39] R. B. SETLOW AND E. C. POLLARD, *Molecular Biophysics*, Addison-Wesley Publishing Company, Reading, MA, 1962.
 - [40] R. V. SOUTHWELL, *Relaxation Methods in Theoretical Physics*, Clarendon Press, Oxford, 1946.
 - [41] G. STRANG AND G. FIX, *An Analysis of the Finite Element Method*, Prentice-Hall, Englewood Cliffs, NJ, 1973.
 - [42] C. TANFORD, *Physical Chemistry of Macromolecules*, John Wiley & Sons, New York, NY, 1961.
 - [43] C.-A. THOLE AND U. TROTTEBERG, *Basic smoothing procedures for the multigrid treatment of elliptic 3d-operators*, Tech. Rep. GMD-Studien Nr. 141, GMD, Bonn, 1985.
 - [44] R. S. VARGA, *Matrix Iterative Analysis*, Prentice-Hall, Englewood Cliffs, NJ, 1962.
 - [45] E. L. WACHSPRESS, *Iterative Solution of Elliptic Systems and Applications to the Neutron Diffusion Equations of Reactor Physics*, Prentice-Hall, Englewood Cliffs, NJ, 1966.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

END

**DATE
FILMED
6 104192**