USGS-OFR--80-313

DE82 904219

MASIER

UNITED STATES DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

Lassen Known Geothermal Resource Area, California: ~~Audio-magnetotelluric,~~
~~Telluric Profiling, and Self-Potential Studies~~

by

K. R. Christopherson, D. B. Hoover, V. Lewis,
B. Radtke, and R. M. Senterfit

Open-file Report 80-313

1980

This report is preliminary and has not been edited
or reviewed for conformity with U.S. Geological
standards and nomenclature.

NOTICE

PORTIONS OF THIS REPORT ARE ILLEGIBLE. It
has been reproduced from the best available
copy to permit the broadest possible avail-
ability. MN ONLY

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

JS

PURCHASE ORDER NO. 03X-44450
RECEIVED 6-3-82

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Lassen Known Geothermal Resource Area, California:

Audio-magnetotelluric, telluric profiling and self-potential studies

by

K. Christopherson, D. Hoover, V. Lewis, B. Radtke, and R. Senterfit

During the summer of 1979, geophysical work was done in the Lassen KGRA in northeastern California to assess the geothermal potential of the area. As part of the study, 68 audio-magnetotelluric (AMT) soundings were made and 2 telluric and self-potential (SP) profiles were done. For descriptions of these techniques and the equipment used see Hoover et al (1978), Corwin and Hoover (1979), and Beyer (1977).

The AMT station locations are shown in figure 1. The scalar resistivities (table 1) were contoured for 7.5 and 27 hertz data at north-south and east-west E-line orientations (figures 2 through 5). The contour maps are complex, reflecting both lateral changes in geology and geothermal activity.

The locations of the telluric and self-potential traverses are given in figure 6. The profiles for traverse 1 (figure 7) show varied SP and telluric responses. The variations are probably geologically related with the drop in SP voltage and telluric resistivity on the east end of the traverse caused by a lateral lithology change.

The profiles for traverse 2 (figure 8) show a sharp drop in SP voltage combined with a sharp increase in telluric resistivity near station 6. This could be associated with large-scale intrusive features (a ring dike?) which trend to the northwest.

FIG. 2: AUDIO-MAGNETOTELLURIC APPARENT RESISTIVITY MAP
7.5 HERTZ - E-LINE N-S
LASSEN KNOWN GEOTHERMAL RESOURCE AREA CA

LOGARITHMIC CONTOURS IN OHM-METERS

SCALE: 0 1 MILE

FIG. 3: AUDIO-MAGNETOTELLURIC APPARENT RESISTIVITY MAP
7.5 HERTZ : E-LINE E-W
LASSEN KNOWN GEOTHERMAL RESOURCE AREA, CA

LOGARITHMIC CONTOURS IN OHM-METERS
SCALE: 1 MILE

FIG. 5: AUDIO-MAGNETOTELLURIC APPARENT RESISTIVITY MAP
27 HERTZ : E-LINE E-W
LASSEN KNOWN GEOTHERMAL RESOURCE AREA, CA

LOGARITHMIC CONTOURS IN OHM-METERS
SCALE: 1 MILE
1 KILOMETER

FIG. 6: TELLURIC TRAVERSES LOCATION MAP - LASSEN KGRA, CA

FIG. 7: PROFILES - TRAVERSE 1
LASSEN KGRA, CA

FIG. 8: PROFILES - TRAVERSE 2
LASSEN KGRA, CA

TABLE 1: U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LASSEN KGRA, CA

JUNE 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

— = no data

"NOTE" - Telluric line orientation indicated with station numbers.

FREQUENCY													
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	13.6K
1NS	pa	22.6	30.4	15.0	25.2	33.6	52.5	—	—	—	43.0	39.9	103.
	N	4	7	9	8	6	7				5	5	1
	Er	1.23	2.46	2.40	1.26	1.95	5.51				5.13	1.05	—
1EW	pa	18.9	11.9	12.6	7.80	15.2	19.9	—	—	—	17.9	76.0	636.
	N	10	7	11	6	9	7				7	1	1
	Er	0.70	2.04	0.51	0.66	0.81	2.42				2.02	—	—
2NS	pa	40.0	45.8	43.7	33.3	50.9	70.6	—	—	—	71.1	48.1	181.
	N	8	8	8	8	7	9				7	5	1
	Er	3.38	4.51	3.45	4.71	4.85	6.43				5.31	2.04	—
2EW	pa	51.4	76.2	45.1	30.1	33.4	51.6	—	—	—	47.2	52.3	74.5
	N	8	6	10	10	10	9				8	1	1
	Er	6.79	12.8	2.72	1.07	0.81	6.63				0.68	—	—
3NS	pa	32.3	32.2	21.8	25.2	28.3	38.4	—	—	—	34.0	29.6	51.3
	N	9	9	9	7	7	8				8	4	1
	Er	3.57	4.25	1.09	1.72	1.30	2.02				2.09	3.31	—
3EW	pa	52.8	38.0	40.9	27.7	37.5	30.9	—	—	—	45.3	39.3	189.
	N	9	9	9	10	7	5				6	1	1
	Er	3.80	3.48	2.41	1.79	1.80	4.02				1.13	—	—
4NS	pa	10.6	14.0	22.7	47.5	101.	46.2	—	—	—	6.84	21.0	84.6
	N	11	7	11	7	8	4				8	1	1
	Er	1.23	3.31	2.79	6.83	21.6	14.3				0.42	—	—
4EW	pa	19.5	21.3	30.7	40.3	106.	86.7	—	—	—	7.70	73.9	185.
	N	11	8	8	7	8	8				7	1	1
	Er	1.35	1.72	2.70	3.12	7.48	9.19				0.99	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

Lassen KGRA, CA

June 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

— = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
5NS	pa	100.	66.6	77.9	113.	161.	435.	—	—	—	111.	87.1	327
	N	8	9	8	10	8	8				7	1	1
	Er	13.1	5.82	4.02	10.6	27.2	106				8.35	—	—
5EW	pa	4.95	5.14	7.42	9.34	25.1	49.0	—	—	—	62.1	147.	107.
	N	12	9	10	10	10	7				7	1	1
	Er	0.28	0.49	0.26	0.72	1.35	4.64				6.44	—	—
6NS	pa	283.	119.	63.2	86.7	133.	206.	—	—	—	79.4	92.3	154.
	N	8	6	11	9	9	8				8	7	1
	Er	24.4	20.0	4.78	10.5	7.38	12.0				4.52	5.78	—
6EW	pa	129.	80.2	48.7	51.0	118.	168.	—	—	—	27.1	125.	261.
	N	7	6	9	10	9	8				7	1	1
	Er	24.8	22.7	3.96	4.79	9.48	19.8				2.34	—	—
7NS	pa	23.5	30.7	27.5	53.5	121.	159.	—	—	—	90.9	189.	486.
	N	10	7	8	8	10	7				9	1	1
	Er	1.87	3.12	2.93	6.51	12.4	9.94				4.23	—	—
7EW	pa	16.9	19.1	21.7	26.3	63.1	97.1	—	—	—	25.3	560.	343
	N	8	10	9	9	7	6				9	1	1
	Er	1.42	1.72	1.26	1.62	3.15	13.2				1.51	—	—
8NS	pa	132.	87.4	113.	119.	103.	27.6	—	—	—	0.55	10.2	10.6
	N	10	7	8	10	11	7				8	1	1
	Er	8.23	11.2	13.1	6.79	4.52	5.22				0.04	—	—
8EW	pa	116.	76.5	82.2	44.0	39.8	14.2	—	—	—	7.13	59.5	32.3
	N	14	12	12	11	13	11				6	1	6
	Er	5.94	3.59	4.00	1.74	2.95	0.82				0.75	—	0.69

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LASSEN KGRA, CA

JUNE 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
9NS	pa	20.3	32.1	81.9 [?]	39.1	59.5	87.7	—	—	—	85.2	111.	200.
	N	5	5	4	6	8	5				6	1	1
	Er	1.94	6.50	19.8	8.12	2.36	4.69				6.60	—	—
9EW	pa	22.9	20.3	44.2 [?]	20.8	60.0	213.?	—	—	—	227.	274.	502.
	N	6	8	6	6	8	4				7.	1	1
	Er	1.80	3.01	2.07	2.73	4.30	17.6				7.87	—	—
10NS	pa	67.9	39.8	45.1	54.7	32.4	20.7	—	—	—	52.3	279.	369.
	N	6	5	6	9	7	7				5	1	1
	Er	10.6	9.83	3.25	5.53	1.80	3.70				1.41	—	—
10EW	pa	32.3	19.5	28.8	29.0	44.8	27.9	—	—	—	59.3	342.	1061.
	N	9	11	9	12	10	6				4	1	1
	Er	2.38	1.60	2.52	2.57	2.75	3.10				9.61	—	—
11NS	pa	34.3	54.4	49.4	72.5	67.9	44.8	—	—	—	30.3	40.4	141.
	N	9	7	8	8	8	7				10	1	1
	Er	4.35	8.02	12.9	5.04	4.33	3.42				0.96	—	—
11EW	pa	24.3	20.0	33.0	20.8	7.62 [?]	17.8	—	—	—	13.0	137.	1.00 [?]
	N	12	7	8	10	12	6				6	1	1
	Er	1.18	1.99	2.50	1.25	0.49	2.36				0.51	—	—
12NS	pa	20.2	25.5	31.4	71.9	53.3	178	—	—	—	150.	591.	480.
	N	5	7	7	8	8	5				7	1	1
	Er	2.73	1.55	2.25	13.4	4.82	37.2				5.10	—	—
12EW	pa	64.5	46.5	48.5	32.5	32.8	56.6	—	—	—	187.	474.	956.
	N	9	10	11	12	9	6				9	1	1
	Er	5.36	3.75	2.30	1.43	1.39	3.14				147	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LASSEN KGRA, CA

JUNE 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
13NS	pa	45.7	70.5	56.8	68.9	45.6	115.	—	—	—	192.	764.	1297.
	N	10	8	9	10	8	8				7	1	1
	Er	5.98	6.72	4.22	4.92	2.68	40.7				5.59	—	—
13EW	pa	36.2	35.8	47.4	39.5	58.2	74.2	—	—	—	344.	696.	1038.
	N	8	7	8	8	12	10				8	1	1
	Er	2.13	2.55	1.45	6.13	2.59	2.60				18.4	—	—
14NS	pa	59.7	54.4	49.8	83.7	188.	192.	—	—	—	36.9	154.	198.
	N	10	9	9	10	8	9				7	1	1
	Er	4.75	6.08	3.74	8.51	7.32	8.40				1.17	—	—
14EW	pa	23.4	33.3	45.2	47.2	125.	146.	—	—	—	85.2	136.	345.
	N	9	11	10	7	10	7				9	1	1
	Er	1.94	1.72	2.45	3.48	4.52	6.91				2.94	—	—
15NS	pa	52.8	36.8	38.6	30.4	39.5	36.3	—	—	—	9.35	104.	35.5
	N	10	9	9	10	10	10				9	1	8
	Er	3.34	4.30	2.67	3.45	3.27	1.69				0.62	—	0.89
15EW	pa	16.3	23.1	23.8	19.1	24.6	30.8	—	—	—	23.5	149.	65.0
	N	10	10	11	10	13	10				8	1	10
	Er	1.05	2.14	1.69	1.23	1.12	1.58				1.61	—	1.14
16NS	pa	39.8	26.4	41.6	32.7	14.4	4.07	—	—	—	5.86	20.6	32.1
	N	9	9	12	9	10	8				12	1	1
	Er	4.54	2.65	3.10	3.02	0.80	0.14				0.34	—	—
16EW	pa	7.86	4.94	1.40	2.13	3.33	3.69	—	—	—	3.58	8.18	28.2
	N	5	5	7	11	12	10				9	1	1
	Er	1.47	0.64	0.24	0.15	0.19	0.10				0.17	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LASSEN KGRA, CA

June 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

FREQUENCY													
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
17ns	pa	37.5	42.2	32.9	48.2	88.0	79.9	—	—	—	124.	388.	258.
	N	12	8	11	11	10	8	—	—	—	8	1	1
	Er	4.92	3.85	2.05	2.67	4.70	1.19	—	—	—	13.5	—	—
17ew	pa	14.3	13.9	16.8	20.4	53.1	97.7	—	—	—	140.	306.	139.
	N	10	7	9	11	10	12	—	—	—	9	1	1
	Er	0.88	1.45	0.97	1.61	2.24	8.48	—	—	—	9.33	—	—
18ns	pa	15.4	15.5	8.98	10.8	14.9	13.9	—	—	—	16.9	53.2	107
	N	7	8	10	10	11	11	—	—	—	8	1	1
	Er	2.10	2.69	0.85	0.78	0.82	1.25	—	—	—	1.62	—	—
18ew	pa	8.59	9.31	10.2	10.6	16.6	15.8	—	—	—	16.5	59.5	37.3
	N	7	7	9	9	12	9	—	—	—	9	1	1
	Er	0.72	1.75	0.89	1.13	0.95	1.61	—	—	—	1.10	—	—
19ns	pa	371.	472.	569.	411.	373.	246.	—	—	—	53.8	57.6	247.
	N	9	9	9	10	8	7	—	—	—	10	1	1
	Er	27.6	50.1	143.	29.3	31.9	27.1	—	—	—	3.97	—	—
19ew	pa	138.	118.	138.	80.6	88.9	13.4	—	—	—	27.6	81.7	150
	N	10	11	8	11	10	6	—	—	—	7	1	1
	Er	12.2	10.9	16.8	3.08	2.52	1.07	—	—	—	1.65	—	—
20ns	pa	33.1	39.8	22.0	17.7	9.15	11.5	—	—	—	34.1	179.	312.
	N	7	8	10	10	6	9	—	—	—	8	1	1
	Er	3.95	4.72	2.54	1.68	1.80	1.52	—	—	—	1.80	—	—
20ew	pa	30.9	24.0	25.2	17.3	23.3	38.4	—	—	—	99.2	169.	156.
	N	10	11	12	11	13	11	—	—	—	9	1	1
	Er	1.92	1.81	1.92	0.58	0.65	1.22	—	—	—	2.97	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LASSEN KGRA, CA
JUNE 1979

pa = observed apparent resistivity in ohm-meters
N = number of observations

Er = standard error in ohm meters

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
2/NS	pa	161.	168.	115.	128.	123.	96.7	—	—	—	28.7	134.	170.
	N	8	5	13	10	9	8				9	1	1
	Er	21.7	16.4	9.61	8.53	5.70	10.1				1.54	—	—
21EW	pa	142.	8.18?	5.10	21.6	17.1	64.1	—	—	—	84.7	156.	96.9
	N	5	7	4	6	5	8				7	1	4
	Er	18.0	0.85	1.11	4.49	2.97	15.0				5.50	—	4.89
22NS	pa	61.2	107.	70.2	105.	65.3	37.8	—	—	—	56.0	275.	383.
	N	8	8	12	8	6	10				9	1	1
	Er	5.27	18.5	6.14	8.98	3.79	1.14				2.55	—	—
22EW	pa	50.8	49.8	61.0	69.7	96.8	99.5	—	—	—	256.	237.	28.7
	N	10	12	11	10	12	12				9	1	1
	Er	4.58	3.44	2.21	8.75	7.06	5.37				14.4	—	—
23NS	pa	26.6	39.6	47.8	87.8	111.	184.	—	—	—	52.5	103.	1.19
	N	9	7	10	11	11	11				7	1	1
	Er	2.96	6.59	2.91	7.77	11.1	14.8				3.97	—	—
23EW	pa	15.0	7.49	9.54	7.42	17.2	30.6	—	—	—	24.4	111.	
	N	6	6	7	8	11	9				6	1	
	Er	2.54	0.35	1.11	0.87	1.70	4.03				1.98	—	—
24NS	pa	240.	129.	91.4	134.	203.	155.	—	—	—	135.	788.	395.
	N	5	9	7	9	7	7				6	1	1
	Er	17.7	24.2	22.1	12.3	8.85	20.7				8.33	—	—
24EW	pa	37.0	35.9	53.7	69.4	208.	269.	—	—	—	87.7	1008.	1643.
	N	12	9	13	12	11	9				7	1	1
	Er	2.22	3.63	2.67	3.51	7.24	16.4				1.18	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LASSEN KGRA, CA

JUNE 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

— = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
25ns	pa	52.0	57.9	105.	157.	341.	277.	—	—	—	11.3	36.9	46.5
	N	8	7	7	5	11	10				9	1	1
	Er	7.95	6.02	11.3	12.0	27.1	17.9				0.42	—	—
25sw	pa	29.2	30.3	41.2	55.9	131.	123.	—	—	—	12.2	52.9	51.4
	N	18	13	13	11	13	12				8	1	6
	Er	2.04	2.07	2.65	2.84	7.81	4.53				1.34	—	3.84
26ns	pa	48.8	76.5	74.1	124.	260.	242.	—	—	—	104.	229.	446.
	N	9	10	12	11	9	10				6	1	1
	Er	5.09	10.9	4.46	5.42	19.2	23.5				13.8	—	—
26sw	pa	56.2	43.5	65.1	77.5	164.	252.	—	—	—	74.6	279.	154.
	N	9	12	12	13	13	8				7	1	3
	Er	6.34	3.85	4.11	3.96	5.04	22.5				6.05	—	2.33
27ns	pa	168.	245.	283.	238.	1176. [?]	684.	—	—	—	202.	737.	804.
	N	8	11	12	6	6	7				7	1	1
	Er	20.3	28.9	19.1	27.3	78.8	95.9				5.09	—	—
27sw	pa	33.8	59.6	95.1	102.	368.	587.	—	—	—	167.	575.	185.
	N	7	12	11	12	13	10				10	1	1
	Er	5.11	4.81	5.37	5.07	16.5	42.0				11.3	—	—
28ns	pa	81.3	136.	98.7	295.	303.	230.	—	—	—	169.	809.	852.
	N	10	6	8	12	6	12				8	—	1
	Er	7.02	4.78	6.70	19.8	29.3	17.2				9.54	—	—
28sw	pa	71.1	74.5	91.9	119.	281.	262.	—	—	—	159.	355.	213.
	N	13	9	11	12	9	10				8	1	1
	Er	6.82	7.54	3.72	3.95	6.02	11.6				9.35	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LASSEN KGRA, CA

JUNE 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

— = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
29ns	pa	18.6	25.6	20.3	21.5	21.7	3.74	—	—	—	14.4	123.	147.
	N	14	12	11	9	8	7	—	—	—	8	1	1
	Er	1.13	1.71	2.20	1.93	1.09	0.80	—	—	—	0.77	—	—
29ew	pa	29.3	27.9	26.9	27.7	44.9	8.77	—	—	—	11.3	237.	43.0
	N	12	10	12	12	12	7	—	—	—	6	1	1
	Er	1.63	1.64	1.51	1.00	2.61	0.86	—	—	—	1.23	—	—
30ns	pa	16.6	15.8	10.2	19.9	23.2	24.9	—	—	—	21.7	57.6	148.
	N	9	9	8	11	13	6	—	—	—	10	1	1
	Er	1.10	1.73	0.44	2.07	0.64	4.22	—	—	—	1.33	—	—
30ew	pa	9.36	12.8	8.28	5.93	—	7.16	—	—	—	2.82	51.3	149.
	N	8	8	11	13	—	5	—	—	—	8	1	1
	Er	0.92	1.99	0.52	0.57	—	1.00	—	—	—	0.35	—	—
31ns	pa	97.0	73.0	70.8	89.7	148.	352.	—	—	—	13.8	892.	17.2
	N	10	8	8	10	9	6	—	—	—	7	1	1
	Er	5.16	9.20	3.60	8.94	10.9	139.	—	—	—	1.7	—	—
31ew	pa	265.	254.	115.	47.3	50.3	30.8	—	—	—	716.	254.	—
	N	2	6	7	11	9	7	—	—	—	6	1	—
	Er	265	53.3	16.5	3.71	2.79	2.10	—	—	—	49.1	1	—
32ns	pa	59.4	49.8	51.9	69.3	88.8	135.	—	—	—	400.	827.	1850.
	N	14	13	11	10	15	7	—	—	—	7.	1	1
	Er	6.67	5.23	2.69	5.09	10.1	21.3	—	—	—	19.0	—	—
32ew	pa	58.2	36.9	43.3	39.3	100.	196.	—	—	—	108.	1193.	716.
	N	13	9	9	11	15	8	—	—	—	9	1	1
	Er	4.60	5.49	2.85	2.32	3.30	26.3	—	—	—	5.87	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

WASSEN KGRA, CA

JUNE 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

— = no data

"NOTE" - Telluric line orientation indicated with station numbers.

FREQUENCY													
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
33NS	pa	116.	54.9	70.6	108.	69.6	31.3	—	—	—	344.	793.	4040.
	N	5	7	5	11	6	8				13	1	1
	Er	25.8	6.27	12.6	6.20	4.74	4.35				9.71	—	—
33EW	pa	49.1	51.4	38.7	32.8	45.9	79.9	—	—	—	183.	3180.	660.
	N	14	15	14	8	15	11				8	1	1
	Er	5.01	6.08	1.84	2.63	2.87	6.6?				13.7	—	—
34NS	pa	595.?	512.?	162.	196.	131.	348.	—	—	—	627.	2240.	2115.
	N	3	5	5	8	7	11				9	1	1
	Er	131.	47.6	24.3	20.7	27.5	48.8				32.1	—	—
34EW	pa	191.	72.9	70.0	57.4	118.	76.1	—	—	—	270.	1011.	8195.
	N	8	12	14	12	10	6				9	1	1
	Er	23.6	7.25	5.83	5.54	16.0	14.4				15.1	—	—
35NS	pa	38.1	50.0	30.7	47.7	52.0	67.8	—	—	—	89.9	1074.	378.
	N	8	9	7	11	9	9				8	1	1
	Er	4.52	4.90	4.16	3.64	2.52	8.31				4.80	—	—
35EW	pa	56.3	36.5	29.8	23.9	27.7	52.9	—	—	—	86.7		
	N	12	9	11	10	9	9				8		
	Er	2.88	3.54	2.34	1.51	1.68	5.92				8.91		
36NS	pa	53.9	79.8	21.6	32.1	109.?	248.?	—	—	—	39.9	36.6	288.
	N	12	2	12	10	5	5				7	1	1
	Er	5.40	5.84	1.71	3.93	8.73	25.4				1.40	—	—
36EW	pa	25.8	55.5	26.7	21.4	95.7	65.6	—	—	—	34.8	162.	4730.
	N	11	6	8	6	8	5				7	1	1
	Er	3.64	7.26	2.25	2.46	16.1	6.36				4.21	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LASSEN KGRA, CA

JUNE 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

— = no data

"NOTE" - Telluric line orientation indicated with station numbers.

FREQUENCY													
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
37ns	pa	59.4	27.0	27.9	47.4	23.0	14.4	—	—	—	152.	452.	645.
	N	7	6	6	9	5	7				10	1	1
	Er	6.67	4.33	3.47	6.75	1.90	2.65				4.07	—	—
37nw	pa	13.3	6.79	14.1	13.2	18.5	16.5	—	—	—	50.0	810.	1195.
	N	11	9	11	12	10	6				8	1	1
	Er	1.17	0.48	0.73	0.96	1.22	1.92				3.63	—	—
39ns	pa	119.	129.	73.9	73.0	97.6	107.	—	—	—	32.1	122.	116.
	N	8	5	11	10	9	8				10	1	1
	Er	6.73	11.9	6.08	14.6	6.86	14.7				1.60	—	—
39nw	pa	125.	126.	64.6	46.7	53.8	58.5	—	—	—	41.2	130.	335.
	N	7	9	7	13	15	11	—			10	1	1
	Er	10.2	12.3	4.23	4.31	3.80	3.60				2.90	—	—
40ns	pa	82.2	80.6	74.9	108.	193.	109.	—	—	—	71.3	108.	313.
	N	10	8	10	11	12	9				8	1	1
	Er	7.71	6.23	2.36	5.24	10.7	13.9				5.27	—	—
40nw	pa	65.1	37.7	55.3	49.9	139.	183.	—	—	—	149.	237.	419.
	N	6	7	11	14	12	12				7	1	1
	Er	13.2	2.67	5.83	3.06	4.35	13.4				13.5	—	—
41ns	pa	90.2	103.	88.7	174.	434.	657.	—	—	—	50.6	161.	171.
	N	5	6	9	8	8	8				8	1	1
	Er	19.0	8.68	3.93	12.1	18.5	57.8				1.28	—	—
41nw	pa	24.8	27.3	56.1	56.9	149.	177.	—	—	—	71.9	313.	167.
	N	6	8	11	9	11	7				8	1	1
	Er	3.07	4.38	5.09	3.71	8.90	17.5				8.24	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LASSEN KGRA, CA

June 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

— = no data

"NOTE" - Telluric line orientation indicated with station numbers.

FREQUENCY													
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
42 _{us}	pa	100.	79.2	50.0	69.1	97.4	27.5	—	—	—	37.0	40.8	206.
	N	8	7	11	12	11	7				6	1	1
	Er	12.8	6.07	3.78	4.88	6.54	4.78				3.60	—	—
42 _{ew}	pa	56.1	50.0	57.4	47.4	70.4	46.1	—	—	—	22.2	255.	431.
	N	10	8	13	10	10	6				7	1	1
	Er	3.01	3.59	3.33	3.79	4.63	5.97				2.98	—	—
43 _{us}	pa	40.4	92.6	34.8	70.7	112.	151.	—	—	—	178.	520.	1195.
	N	8	10	11	11	9	5				8	1	1
	Er	3.88	16.7	1.32	5.62	10.2	44.6				9.70	—	—
43 _{ew}	pa	91.0	104.	51.1	40.1	98.9	205.	—	—	—	108.	1780.	2410.
	N	7	7	11	11	9	9				9	1	1
	Er	8.00	10.6	4.39	2.45	3.75	18.0				19.8	—	—
44 _{us}	pa	66.7	102.	78.0	97.9	91.9	160.	—	—	—	286.	865.	1330.
	N	8	6	7	10	12	4				10	1	1
	Er	7.17	10.2	5.61	4.81	6.20	29.4				13.9	—	—
44 _{ew}	pa	51.3	35.6	43.6	37.8	65.9	23.2	—	—	—	111.	2680.	549.
	N	10	5	8	13	10	9				8	1	1
	Er	1.91	12.3	3.00	2.89	8.14	3.27				7.18	—	—
45 _{us}	pa	23.5	45.3	27.3	42.1	62.5	58.7	—	—	—	62.4	70.7	366.
	N	7	8	9	10	11	10				7	1	1
	Er	2.46	3.61	2.13	3.53	3.48	7.18				3.10	—	—
45 _{ew}	pa	18.8	18.2	31.0	31.9	67.3	218.	—	—	—	96.5	488.	252.
	N	12	12	11	8	12	8				11	1	1
	Er	1.60	1.91	2.64	5.12	2.04	16.0				5.58	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LASSEN KGRA, CA

JUNE 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

— = no data

"NOTE" - Telluric line orientation indicated with station numbers.

FREQUENCY													
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
46ns	pa	36.9	29.2	23.7	23.6	9.23	11.9	—	—	—	39.2	115.	239.
	N	7	8	10	11	9	9				8	1	1
	Er	3.49	3.46	1.66	1.58	1.24	1.37				1.18	—	—
46ew	pa	40.7	30.1	17.2	9.61	22.0	21.5	—	—	—	33.8	54.5	3720.
	N	9	7	7	12	10	12				9	1	1
	Er	4.51	2.23	0.99	0.55	3.09	1.01				1.49	—	—
47ns	pa	164.	178.	208.	199.	149.	107.	—	—	—	61.4	87.1	198.
	N	7	4	11	5	12	12				10	1	1
	Er	20.7	43.4	21.0	26.6	10.9	10.3				2.16	—	—
47ew	pa	81.8	207?	74.3	76.5	57.4	78.4	—	—	—	55.8	82.3	182.
	N	4	6	10	13	14	15				11	1	5
	Er	14.8	28.3	6.39	4.47	2.03	4.72				1.54	—	3.43
48ns	pa	93.3	91.3	114.	157.	231.	121.	—	—	—	152.	588.	719.
	N	11	11	11	11	11	10				7	1	1
	Er	6.45	12.1	6.24	13.7	18.8	10.3				12.3	—	—
48ew	pa	71.7	80.2	93.2	99.5	197.	166.	—	—	—	195.	303.	1820.
	N	9	7	9	12	12	9				9	1	1
	Er	8.62	5.66	8.75	7.23	7.34	14.28				12.4	—	—
49ns	pa	42.5	45.9	34.1	89.6	148.	54.6	—	—	—	72.9	45.3	408.
	N	9	11	10	11	9	9				10	1	1
	Er	4.87	5.21	2.27	8.22	16.9	4.62				6.33	—	—
49ew	pa	82.2	58.3	80.8	112.	300.	248.	—	—	—	233.	848.	1020.
	N	8	11	9	10	12	10				7	1	1
	Er	10.1	6.90	7.40	7.12	14.4	20.5				12.9	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LASSEN AREA, CA

JUNE 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

— = no data

"NOTE" - Telluric line orientation indicated with station numbers.

FREQUENCY													
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
50ns	pa	63.7	80.4	97.1	172.	284.	112.	—	—	—	95.2	313.	176.
	N	11	9	11	10	9	10				8	1	1
	Er	2.95	10.0	4.50	12.9	33.8	10.8				8.76	—	—
50ew	pa	56.2	65.7	82.1	96.1	235.	406.	—	—	—	190.	618.	470.
	N	9	8	11	12	11	10				8	1	1
	Er	5.51	8.45	4.21	4.70	5.71	23.4				16.9	—	—
51ps	pa	45.7	75.1	59.6	83.6	116.	64.7	—	—	—	56.1	87.1	96.1
	N	9	10	12	12	12	9				10	1	1
	Er	4.23	5.39	4.63	4.23	5.12	8.94				1.50	—	—
51ew	pa	48.5	52.8	52.5	60.1	146.	117.	—	—	—	79.0	253.	215.
	N	6	10	11	11	11	8				10	1	1
	Er	7.03	2.76	3.55	2.06	8.94	15.5				6.63	—	—
52ns	pa	132.	163.	131.	111.	143.	116.	—	—	—	55.1	134.	94.5
	N	3	4	6	9	12	7				10	1	1
	Er	37.8	38.0	13.7	7.99	6.71	9.2				2.68	—	—
52ew	pa	57.5	49.2	128.	97.0	212.	132.	—	—	—	27.9	59.5	59.5
	N	12	10	7	8	10	10				9	1	1
	Er	5.68	3.26	16.8	7.79	17.2	14.0				2.76	—	—
53ns	pa	24.6	24.7	22.1	21.4	17.8	12.4	—	—	—	22.0	32.3	44.2
	N	12	14	15	10	13	9				10	1	1
	Er	2.25	1.62	1.10	1.06	0.96	1.00				1.53	—	—
53ew	pa	37.6	31.4	33.8	20.7	19.5	14.0	—	—	—	18.0	42.6	253
	N	11	11	10	13	11	11				10	1	1
	Er	3.65	1.55	2.37	0.73	0.74	1.11				1.22	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LASSON KGRA, CA

JUNE 1979

pa = observed apparent resistivity in ohm-meters
 N = number of observations
 Er = standard error in ohm meters   - = no data

"NOTE" - Telluric line orientation indicated with station numbers.

FREQUENCY													
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
54ns	pa	10.4	8.98	11.9	14.8	21.1	16.5	—	—	—	21.2	15.1	196.
	N	11	9	13	13	13	8				10	1	1
	Er	0.61	0.48	0.63	1.15	1.23	0.96				0.88	—	—
54w	pa	7.91	5.46	7.63	9.07	16.6	16.2	—	—	—	26.9	34.1	38.4
	N	10	8	10	11	10	10				9	1	1
	Er	1.00	0.22	0.36	0.37	1.03	1.29				1.07	—	—
55ns	pa	54.6	89.8	61.1	96.6	215.	261.	—	—	—	279.	348.	552.
	N	9	8	10	10	9	7				8	1	1
	Er	6.88	8.05	3.35	5.73	11.9	26.3				23.6	—	—
55w	pa	31.9	22.0	41.5	54.2	129.	229.	—	—	—	180.	367	87.5
	N	6	7	9	11	11	10				8	1	1
	Er	6.78	1.33	2.01	2.65	5.78	9.35				5.31	—	—
56ns	pa	59.7	79.4	95.4	152.	216.	199.	—	—	—	125.	130.	711.
	N	13	10	8	13	9	9				7	6	1
	Er	3.98	4.60	1.98	12.3	8.68	30.4				5.96	5.98	—
56w	pa	115.	118.	132.	144.	298.	313.	—	—	—	370.	786.	871.
	N	5	8	12	9	11	10				8	1	1
	Er	13.1	10.9	6.93	6.07	12.8	23.9				29.5	—	—
57ns	pa	154.	194.	143.	245.	270.	166.	—	—	—	320.	1364.	968.
	N	10	9	13	12	10	8				10	1	1
	Er	14.7	13.1	4.77	14.4	20.3	16.2				14.7	—	—
57w	pa	95.1	75.3	92.8	93.1	223.	352.	—	—	—	289.	643.	836.
	N	5	8	10	11	12	10				9	7	1
	Er	9.37	8.93	7.80	3.48	12.4	21.6				19.8	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LASSEN, KGRA, CA.

JUNE 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

— = no data

"NOTE" - Telluric line orientation indicated with station numbers.

FREQUENCY													
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
58ns	pa	39.1	34.0	33.1	66.6	124.	435.	—	—	—	173.	191.	382.
	N	6	7	6	9	9	9				8	1	1
	Er	4.83	2.94	4.37	6.87	10.6	34.7				8.32	—	—
58ew	pa	29.8	64.7	45.7	44.1	139.	298.	—	—	—	414.	582.	310.
	N	6	8	11	7	11	11				7	1	4
	Er	3.71	11.3	3.69	3.58	6.97	13.9				17.3	—	16.8
59ns	pa	97.4	141.	75.3	111.	205.	377.	—	—	—	123.	64.2	162.
	N	7	6	9	11	9	10				11	9	1
	Er	12.8	14.6	4.66	4.50	17.5	19.6				4.97	1.76	—
59ew	pa	58.8	75.1	50.1	71.1	175.	326.	—	—	—	350.	243.	387.
	N	10	11	11	7	11	9				11	11	1
	Er	6.15	14.0	3.20	6.40	10.6	9.82				15.0	11.2	—
60ns	pa	10.4	11.8	9.03	14.7	23.4	49.6	—	—	—	132.	146.	126.
	N	6	7	11	9	8	7				8	6	1
	Er	1.86	0.72	1.71	1.07	1.79	5.53				6.98	5.16	—
60ew	pa	11.7	7.39	8.62	7.52	13.4	24.1	—	—	—	163.	136.	137.
	N	11	9	10	10	11	8				8	6	5
	Er	1.08	0.44	0.55	0.44	0.52	1.34				5.75	7.82	6.09
61ns	pa	137.	389.?	116.	40.6	47.4	30.4	—	—	—	21.1	13.7	69.9
	N	5	4	5	5	9	7				6	7	1
	Er	18.1	54.6	12.3	3.24	1.33	5.31				1.07	1.34	—
61ew	pa	50.8	40.9	39.9	22.4	34.6	36.3	—	—	—	47.8	45.0	199.
	N	9	12	8	9	11	8				7	1	1
	Er	4.60	2.37	3.05	1.04	1.67	1.57				2.63	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LAUSEN KGRA, CA

June 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

NOTE - REFERENCE THE OPERATING INSTRUCTIONS													
		FREQUENCY											
Sta. No.		7.5	10	14	27	76	235	685	1.2K	3.3K	6.7K	10.2K	18.6K
62ws	pa	11.6	15.1	12.3	19.2	31.8	11.5	—	—	—	10.0	15.9	83.7
	N	9	9	10	11	5	8	—	—	—	6	1	1
	Er	0.95	1.01	0.46	1.09	0.84	0.78	—	—	—	0.21	—	—
62ew	pa	14.4	10.8	16.7	14.5	36.5	43.2	—	—	—	21.3	59.5	133.
	N	7	8	9	10	12	9	—	—	—	8	1	1
	Er	1.10	0.66	0.91	0.67	1.22	1.88	—	—	—	2.24	—	—
63ws	pa	7.93	8.31	7.48	8.82	11.9	5.71	—	—	—	2.78	3.70	44.2
	N	9	10	11	9	10	11	—	—	—	8	7	1
	Er	0.66	1.06	0.36	0.49	0.79	0.55	—	—	—	0.16	0.22	—
63ew	pa	12.3	9.99	11.0	7.94	11.2	7.57	—	—	—	4.71	20.2	63.9
	N	7	11	10	12	9	10	—	—	—	11	1	1
	Er	1.37	0.84	0.42	0.41	0.55	0.37	—	—	—	0.27	—	—
64ws	pa	72.1	61.9	72.7	141.	471.?	243.	—	—	—	29.6	—	—
	N	10	12	5	5	6	8	—	—	—	8	43.4	110.
	Er	3.55	5.32	9.07	16.3	25.0	20.4	—	—	—	2.44	6	1
64ew	pa	78.6	104.	102.	← power line → 265. 1144. 122.			—	—	—	27.3	5.18	—
	N	3	4	6	6	4	8	—	—	—	9	45.0	85.0
	Er	12.7	24.5	23.6	28.4	36.1	8.36	—	—	—	1.22	1	1
65ws	pa	70.7	118.	88.8	174.	172.	267.	—	—	—	53.9	—	—
	N	9	9	9	10	9	8	—	—	—	8	—	—
	Er	6.15	23.2	13.8	12.7	19.9	35.1	—	—	—	5.56	—	—
65ew	pa	55.9	49.8	77.1	19.7	133.	11.6.	—	—	—	93.0	—	—
	N	7	9	11	11	9	10	—	—	—	9	—	—
	Er	5.52	4.81	4.65	1.70	6.94	6.52	—	—	—	3.82	—	—

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

LASSEN KGRA, CA

JUNE 1979

pa = observed apparent resistivity in ohm-meters

N = number of observations

Er = standard error in ohm meters

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

FREQUENCY													
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
66ns	pa	15.0	60.6	31.0	32.6	35.3	68.0	—	—	—	90.7	115.	246.0
	N	9	7	6	9	8	6				6	1	1
	Er	1.64	7.94	4.11	3.23	2.18	7.16				14.4	—	—
66ew	pa	35.3	55.2	26.4	17.7	30.8	55.1	—	—	—	145.	145.	859.
	N	8	10	10	10	10	10				7	1	1
	Er	3.89	6.53	1.23	0.90	1.76	2.70				5.94	—	—
67ns	pa	29.8	40.3	30.5	56.5	92.0	39.3	—	—	—	36.3	125.	59.7
	N	9	6	10	8	10	6				6	1	4
	Er	4.72	3.30	1.64	3.67	6.56	3.46				1.67	—	0.86
67ew	pa	39.8	26.9	28.8	34.8	41.2	17.8	—	—	—	31.6	169.	64.5
	N	8	6	10	9	8	9				8	1	5
	Er	2.23	3.99	2.38	2.58	3.81	1.17				3.30	—	1.93
68ns	pa	96.1	160.	164.	207.	393.	283.	—	—	—	67.9	189.	72.3
	N	7	7	8	12	8	8				6	1	5
	Er	5.48	16.3	8.36	16.7	20.5	16.6				6.40	—	2.93
68ew	pa	67.7	126.	87.0	116.	209.	311.	—	—	—	174.	40.6	217
	N	6	7	9	6	9	6				6	1	5
	Er	7.02	18.3	7.51	9.33	14.6	79.8				11.0	—	8.59
69ns	pa	200.	355.	195.	263.	302.	201.	—	—	—	84.2	72.2	39.8
	N	7	11	10	11	12	12				9	1	6
	Er	16.9	30.0	11.6	23.3	31.8	11.3				4.26	—	1.68
69ew	pa	48.3	69.5	61.5	64.7	117.	158.	—	—	—	200.	291.	219.
	N	12	6	12	10	10	10				9	1	6
	Er	3.15	8.80	2.25	3.57	3.75	6.38				15.0	—	0.94

References

- Beyer, J. H., 1977, "Telluric and D.C. Resistivity Techniques Applied to the Geophysical Investigation of Basin and Range Geothermal Systems, Part I: The E-field Ratio Telluric Method," PhD Thesis, Lawrence Berkeley Laboratories, Univ. of California, Berkeley, Report LBL-6325, 1/3.
- Corwin, R. F. and D. B. Hoover, 1979, "The Self-Potential Method in Geothermal Exploration," *Geophysics*, vol. 44, no. 2, 226-245.
- Hoover, D. B., C. L. Long, and R. M. Senterfit, 1978, "Some Results from Audio-Magnetotelluric Investigations in Geothermal Area," *Geophysics*, vol. 43, no. 7, 1501-1514.