Cover

The front cover image portrays the concentration and spatial distribution of a hypothetical chemical contaminant sometime after it has been released into the subsurface soil beneath a water table. The front portion of the plume has been cut away to reveal concentration variations within a red shell that defines the outermost extent of the contamination. This image was constructed from a computer simulation of chemical migration through a "pseudo-realistic" soil. The chemical plume moves with the flow of the groundwater, spreads out, and becomes diluted in much the same way a plume of smoke moves through the wind, although at a much slower rate. The images on the back cover are

three snapshots of such an evolution. The contorted shape of the chemical plume is caused by irregularities in the soil character that give rise to preferential channels of groundwater flow.

These simulations are based on an idealized model of soil heterogeneity. The soil properties used in the model retain a few of the characteristics of variability measured in real field soils. These simulations are used to study the way in which contaminants move in variable soils, and they provide certain physical insights and perspective into actual contamination problems that engineers, who are unable to see such details, can use when working in the field.

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial products, processes, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California and shall not be used for advertising or product endorsement purposes.

Work performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract No. W-7405-Eng-48.

Lawrence Livermore National Laboratory

UCRL-LR--106135

DE91 017132

Earth Sciences

Report 1989/90

Scientific Editor:	Leland W. Younker
General Editors:	Steven J. Peterson M. Elaine Price
Art Coordinator:	Frank Uhlig
Manuscript Date:	March 1991

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

28

Contents

Overview	1
<i>Leland W. Younker</i>	
Prototype Engineered Barrier System Field Test	5
<i>Abelardo L. Ramirez</i>	
Geochemical Modeling: An Integrated Approach to Nuclear Waste Disposal Issues	19
<i>Carol J. Bruton, Brian E. Viani, William L. Bourcier, Kenneth J. Jackson, and Roger D. Aines</i>	
Modeling Petroleum Generation and Expulsion	37
<i>Jerry J. Sweeney, Robert L. Braun, and Alan K. Burnham</i>	
Hydrodynamic Interactions and Transport Coefficients in a Suspension of Spherical Particles	47
<i>Anthony J. C. Ladd</i>	
New Method to Analyze Fluid-Driven Fracturing in Jointed Rocks	61
<i>François E. Heuzé, Ronald J. Shaffer, and Stephen C. Blair</i>	
Discriminating between Nuclear Explosions and Earthquakes	73
<i>Steven R. Taylor</i>	
Developing Codes to Analyze Underground Nuclear Explosions and Shock Propagation	83
<i>Lewis A. Glenn, Bill Moran, William C. Moss, and John T. Rambo</i>	
Large-Scale Simulation of Solute Transport in Heterogeneous and Reactive Porous Media	89
<i>Andrew F. B. Tompson and Richard B. Knapp</i>	
Oxygen Diffusion in Olivine: The Effect of Oxygen Fugacity and Implications for Creep	103
<i>Frederick J. Ryerson and William B. Durham</i>	
Rupture Process of the 1965 Rat Islands Earthquake	113
<i>Susan L. Beck</i>	
Testing Newton's Inverse-Square Law of Gravity Using the BREN Tower	123
<i>Paul W. Kasameyer</i>	
Tectonic Stress and Lithospheric Structure in the Basin and Range	135
<i>Howard J. Patton and George Zandt</i>	
Earth Sciences Publications List	147
Earth Sciences Professional Staff—1989/90	181

Overview

Leland W. Younker

Earth Sciences Department

The Earth Sciences Department at Lawrence Livermore National Laboratory (LLNL) conducts work in support of the Laboratory's energy, defense, environmental, and basic research programs. The Department comprises more than 100 professional scientific personnel spanning a variety of subdisciplines: geology, seismology, physics, geophysics, geochemistry, hydrology, chemical engineering, and mechanical engineering. Resident technical support groups add significant additional technical expertise, including Containment Engineering, Computations, Electronic Engineering, Mechanical Engineering, Chemistry and Materials Science, and Technical Information. In total, approximately 180 professional scientists and engineers are housed in the Earth Sciences Department, making it one of the largest geoscience research groups in the nation.

Previous Earth Sciences reports have presented an outline of the technical capabilities and accomplishments of the groups within the Department. In this FY 89/90 Report, we have chosen instead to present twelve of our projects in full-length technical articles. This *Overview* introduces those articles and highlights other significant research performed during this period.

Energy

Yucca Mountain Project

The Yucca Mountain Project is the largest single activity within the Earth Sciences Department. Yucca Mountain is a potential site for the permanent geologic disposal of nuclear waste. Our work is primarily focused on characterizing the operating environment and predicting the performance of high-level nuclear waste packages and the engineered components associated with them.

Recently, we completed the Prototype Engineered Barrier System Field Test (PEBSFT). This test was conducted at the Nevada Test Site (NTS);

in the G-Tunnel Underground Facility in the Grouse Canyon tuff. The PEBSFT is a precursor to the Engineered Barrier System Field Tests (EBSFT) that will be conducted west of NTS in the Exploratory Shaft Facility of the Yucca Mountain Project in the Topopah Springs tuff.

The PEBSFT was conducted to evaluate the performance of candidate hardware, measurement techniques, numerical models, and procedures under conditions similar to those expected in the EBSFT. Information obtained from this test will be used to characterize the ambient environmental conditions to which waste packages could be exposed, as well as possible perturbations to those conditions caused by the emplacement of nuclear waste. For a detailed discussion of this topic, see the article: *Prototype Engineered Barrier System Field Test*.

Geochemical Modeling

Geochemical modeling plays an integral role in predicting the long term performance of potential nuclear waste package repositories. We must be able to predict the

response of repository components and of the enclosing host rocks and fluids to temperature fluctuations, fluid flow, and radionuclide releases over periods of up to 100,000 years. To meet this challenge, we are using the computer codes EQ3NR and EQ6 and their thermodynamic data base to simulate the complex interplay among the processes that control rates of waste form degradation and changes in the geochemical environment throughout the post-closure period of a repository. We are using the code EQ3/6 for reproducing and evaluating experimental results to determine the controls of observed phenomena and to guide future experimentation. These codes are also being applied to some diverse geochemical problems to demonstrate their general utility and flexibility. For a detailed discussion of this topic, see the article: *Geochemical Modeling: An Integrated Approach to Nuclear Waste Disposal Issues*.

Fossil Energy

Our major effort in the Fossil Energy Program has been in developing

a model of the generation and expulsion of petroleum from source rocks in the geological environment. We have used our detailed chemical kinetic model of oil and gas generation and destruction and also a simple mechanical model of source rock compaction to make the first rigorous, nonproprietary calculation of oil expulsion from a generating source rock. For a detailed discussion of this topic, see the article: *Modeling Petroleum Generation and Expulsion*.

We are continuing our work in modeling particulate flow behavior because understanding the flow properties of granular solids has broad scientific and industrial applications that range from soil mechanics to process control. The development of commercial-scale synthetic-fuel processing plants will, for example, involve the handling and processing of large quantities of solids. We have recently extended two-dimensional polygonal particle models to three dimensions for inelastic, frictional spheres in rapid shearing flows and in gravity-driven flows. We are currently comparing the results of these simulations with laboratory data, and we have used the simulations to help design LLNL's pilot-scale oil-shale retort. We are now using well-known numerical statistical mechanics techniques to extend this work to include particulate suspensions of solids in liquids, which can be understood in terms of the microstructure of the solid phase.

In another Fossil Energy project, we developed a general computational method for calculating the forces and torques exerted by slowly moving spheres suspended in an incompressible fluid. This method can be used to determine bulk constitutive properties of solid-fluid suspensions or particulate porous media. For a detailed discussion of this topic, see the

article: *Hydrodynamic Interactions and Transport Coefficients in a Suspension of Spherical Particles*.

We are also creating a new method for analyzing the propagation of induced fluid-driven fractures in rock masses that contain pre-existing discontinuities such as joints, faults, bed interfaces, and lens boundaries. This technique is based on a two-dimensional time-dependent model, with coupled solid mechanics, fracture mechanics, and fluid dynamics. The solid and fracture mechanics are solved by an implicit finite element approach that provides for mixed-mode fracture propagation in arbitrary stress fields. The pressure profile inside the crack and the crack velocity are provided by a one-dimensional analytical formulation, corresponding to a constant-height fracture. For a detailed discussion of this topic, see the article: *New Method to Analyze Fluid-Driven Fracturing in Jointed Rocks*.

Defense

Three of our programs primarily support defense research; they are Nuclear Test Containment, Treaty Verification, and Shock Physics.

The primary objective of the Containment Program is to ensure the containment of radioactive debris from the Laboratory's underground nuclear tests at the Nevada Test Site. The Verification Program supports a variety of tasks largely focused on developing better methods for verifying compliance with nuclear test ban treaties and on supporting the U.S. Department of Energy (DOE) personnel who help formulate arms control agreements, negotiate treaties, and evaluate treaty compliance. The Shock Physics effort provides calculational support to the Containment, Verification, and Weapons programs at the Laboratory.

Verification Program personnel are providing ongoing support to the U.S. delegations negotiating with the Soviets on the Threshold Test Ban Treaty (TTBT) protocol. We are using our expertise in nuclear testing and in seismic and hydrodynamic monitoring techniques to analyze monitoring options and to examine both the U.S. and the Soviet positions. The results of our technical efforts are being used by DOE policymakers and other U.S. agencies involved in these negotiations.

We are continuing our longer range research program aimed at assessing technical capabilities that could be used to monitor possible future nuclear test limitation treaties. One such capability is the use of regional seismic signals to discriminate between nuclear explosions and earthquakes. We employed a multivariate analysis technique to make a detailed discrimination study of a large number of NTS nuclear explosions and western United States earthquakes. We are currently analyzing events that were misclassified so that we can assess opportunities for evasion and also obtain a better physical understanding of how the discriminants work. For a detailed discussion of this topic, see the article: *Discriminating between Nuclear Explosions and Earthquakes*. We are also investigating the application of artificial neural networks to the discrimination problem.

All of our defense-related work relies to some extent on our ability to simulate the interaction of nuclear explosions and geological materials. Until 1988, these numerical simulations were performed using TENSOR, which is a two-dimensional, Lagrangian finite-difference hydrocode. TENSOR was operational only on our CDC 7600 computers, which were taken out of service in October 1988. We have successfully adapted DYNA2D to do all of our containment and

verification calculations. We selected DYNA2D because it is a state-of-the-art hydrocode that is used worldwide. The capabilities of DYNA2D and DYNA3D will ultimately allow us to address emplacement conditions involving very complex geological characteristics. For a discussion of this topic, see the article: *Developing Codes to Analyze Underground Nuclear Explosions and Shock Propagation*.

Environment

There is a growing interest within DOE to address the issue of environmental restoration at DOE sites. The LLNL Earth Sciences Department has provided geological, geophysical, hydrological, and project management support to ongoing Livermore and Site 300 environmental restoration programs.

The Environmental Technology Program was organized in FY 90 to research, develop, demonstrate, test, and evaluate innovative technologies for reducing the costs and increasing the effectiveness of environmental restoration and waste management. The Earth Sciences Department supports this Program by conducting research in subsurface (groundwater and soil) remediation.

Expanded computational capabilities will be the core element of our increased role in hazardous waste/environmental restoration research. Toward this goal, we enhanced our modeling codes that simulate the transport of contaminants in complex geological environments. We also developed a theory describing infiltration in partially saturated, fractured, porous media.

In another code development effort, we implemented several reactive-transport codes and began developing a particle-based simulator for reactive transport problems in porous media. The ability to model the movement and transformation

of dissolved aqueous or gaseous chemicals in porous flow systems is important in a number of scientific disciplines. With these improved codes, we examined the effects of material heterogeneities on groundwater flow and transport processes and expanded our understanding of the nature of the chemical interactions that take place in such systems. For a detailed discussion of this topic, see the article: *Large-Scale Simulation of Solute Transport in Heterogeneous and Reactive Porous Media*.

Basic Research

The Earth Sciences Department has for some time been actively involved in a vigorous basic research program. Funded initially by the Office of Basic Energy Sciences (OBES) Geoscience Program, the effort has recently been augmented by the Laboratory's Institutional Research and Development Program.

Last summer, as part of the National Continental Scientific Drilling Program, we undertook field investigations at Katmai, Alaska. Katmai, the site of the largest rhyolitic eruption in 20 centuries, has been proposed as the site of the next major scientific drilling project in the U.S.

In the laboratory, we have recently constructed a large-volume split-cone apparatus capable of reaching pressures as high as 250 kbar and temperatures up to 2000°C. When completed, this facility will provide a capability unique in the western U.S. by extending the experimentally accessible "depth" to pressures believed to exist in the earth's lower mantle (depths greater than 600 km).

In a joint project with the LLNL Physics Department, we are using a 465-m tower in the desert at NTS to test Newton's inverse-square law of gravity. The first-phase results of

our search for distance-dependent deviations from Newtonian gravity show no evidence for a fifth force. These high-sensitivity results provide an important benchmark for grand unification theories. For a detailed discussion of this topic, see the article: *Testing Newton's Inverse-Square Law of Gravity Using the BREN Tower*.

During this reporting period, we also applied a method based on surface-wave excitation and seismic moment-tensor theories to obtain the source mechanisms of moderate-size earthquakes. This method is particularly suited to studying remote earthquakes with limited seismic station coverage. The object of our research was an improved characterization of the regional stress field in the western U.S. to gain a better understanding of the geophysical processes that modify tectonic evolution. For a detailed discussion of this topic, see the article: *Tectonic Stress and Lithospheric Structure in the Basin and Range*.

In another basic research project, we performed oxygen self-diffusion experiments on single crystals of San Carlos olivine and found that oxygen is not the slowest diffusing species in olivine. We compared the activation energy for oxygen diffusion to that obtained in a majority of measurements of creep in single crystal olivine. We found that for oxygen diffusion to contribute to the control of creep in olivine, it must be coupled to another process having a non-zero activation energy. For a detailed discussion of this topic, see the article: *Oxygen Diffusion in Olivine: The Effect of Oxygen Fugacity and Implications for Creep*.

Our basic research program has been significantly enhanced by the rapid development of the Center for Geosciences in the Institute of Geophysics and Planetary Physics (IGPP). The primary purpose of the

Center is to promote collaborative Earth Science research between scientists at LLNL and students and researchers at University of California campuses. Between 10 and 15 projects have been supported in recent years with the research emphasis on the physics and chemistry of the solid earth.

One project sponsored by IGPP was a study of the great Rat Islands underthrusting earthquake ($M_w = 8.7$) of February 4, 1965, which represented a subduction of the Pacific plate beneath the North American plate along a 600-km segment of the western end of the Aleutian Islands. We used body-wave inversion

techniques to determine the spatial and temporal heterogeneities associated with this earthquake. For a detailed discussion of this topic, see the article: *Rupture Process of the 1965 Rat Islands Earthquake*.

Prototype Engineered Barrier System Field Test

Abelardo L. Ramirez

Major Contributors

Jane A. Beatty, Thomas A. Buscheck, Richard C. Carlson,
William D. Daily, V. Robert LaTorre, Kenrick Lee, Wunan Lin,
John J. Nitao, Donald F. Towse, Tzou-Shin Ueng,
Donald Watwood, Dale G. Wilder, and Jesse T. Yow

Yucca Mountain Project

The Prototype Engineered Barrier System Field Test (PEBSFT) was conducted at the Nevada Test Site (NTS) in the G-Tunnel Underground Facility in the Grouse Canyon tuff. This test is a precursor to the Engineered Barrier System Field Tests (EBSFT) that will be conducted west of NTS in the Exploratory Shaft Facility of the Yucca Mountain Project in the Topopah Springs tuff. The EBSFT will consist of in situ tests of the geohydrologic and geochemical environment in the near field (within a few meters) of heaters emplaced in welded tuff to simulate the thermal effects of nuclear waste containers. The PEBSFT was conducted to evaluate the performance of candidate hardware, measurement techniques, numerical models, and procedures under conditions similar to those expected in the EBSFT.

The EBSFT results will be used in waste package design and in waste package performance assessments that are needed to meet licensing requirements. Information obtained from the EBSFT will define the initial environmental conditions to which waste packages will be exposed as well as the perturbations to those conditions resulting from the heat generated by nuclear waste containers emplaced in welded tuff. The results from the prototype testing will not be used to make conclusions about Yucca Mountain; however, this test was conducted in a similar rock mass so that the physical phenomena can be investigated with techniques and models that might be useful in the Yucca Mountain tests.

During this prototype test, we studied the evolution of hydrothermal behavior, including rock temperatures, changes in rock moisture content, air permeability of fractures, and gas-phase humidity in the heater borehole.

We conducted the PEBSFT experiment in the G-Tunnel Underground Facility, which is located at NTS (Ramirez et al., 1989). The G-Tunnel is physically removed from Yucca Mountain, Nevada and is in the Grouse Canyon tuff rather than in the Topopah Springs tuff; however, welded tuffs with properties believed to be similar to tuffs in Yucca

Mountain are located in a portion of G-Tunnel (Zimmerman and Finley, 1986).

Results from the PEBSFT will be used to evaluate whether hardware, measurement techniques, numerical models, and procedures developed for this field test can provide the information needed to characterize the waste package environment and

whether they can be applied to future EBSFT experiments that will be conducted in the Exploratory Shaft Facility at Yucca Mountain. The Engineered Barrier System must be appropriately designed (and its performance assessed) to meet the objectives for nuclear waste packages as stated in the 1988 U.S. Department of Energy Site Characterization Plan.

Engineered Barrier Systems Field Tests

The EBSFT will consist of in situ tests of the geohydrologic environment near heaters emplaced in welded tuff. As part of the Yucca Mountain Project testing program in the Exploratory Shaft Facility, a series of field tests have been designed that simulate the emplacement of nuclear waste packages containing high-level radioactive material.

Information obtained from the EBSFT will be used to characterize ambient environmental conditions to which waste packages will be exposed as well as perturbations to those conditions caused by the emplacement of nuclear waste.

The environmental conditions of concern for the waste package include those that exist during the heating phase when rock temperatures increase after the waste is emplaced, and those that exist in the subsequent cooldown phase that result from the gradual decay of radioactivity and heat output. Studies of the environmental conditions need to consider:

- The heating of the rock mass adjacent to the waste packages and the resulting drying of this rock mass.
- The cooling of that same rock mass, the subsequent rewetting of the dried-out rock mass, and the readjustment of the rock mass deformations.

Meeting the technical challenge of being able to predict long-term hydrothermal properties of welded tuff is critical because of the long time frame (10,000 years) of interest in performance assessment.

The performance strategy for the waste package is based on limited liquid-water contact with the waste package during the first one thousand years of the package's life. It is important to be able to

characterize the chemical composition (preferably benign) of any water that might come in contact with the waste package. This water chemistry should be compatible with the waste-form release-rate investigations performed by other researchers.

The results from EBSFT tests will be used in conjunction with laboratory studies and numerical modeling simulations to evaluate the evolution of the post-closure repository environment with which the waste packages must interact. The information on the post-closure environment will be used as boundary conditions in designing the waste packages and in assessing their performance.

Prototype Test

This discussion includes the key results and supporting data from the PEBSFT in which we studied the hydrothermal perturbation of welded tuff near a horizontally oriented heater.

As part of the PEBSFT, we measured several parameters as a function of location and time so that we could examine the effects of heating and cooling during a thermal pulse that lasted ~195 days.

A schematic of the hydrologic environment expected to develop around a heater during thermal loading is shown in Fig. 1 (see Yow, 1985, for additional details on the expected environmental conditions). This figure depicts the primary mechanisms of heat and fluid flow for an idealized example of a horizontal heater that is intersected by a near vertical fracture. The actual heater borehole was intersected by more than a dozen fractures. The rock mass consisted of matrix blocks that were bounded by fractures and the borehole wall (for blocks immediately adjacent to the heater). Under ambient conditions,

the matrix blocks are partially saturated, and the fractures and borehole are essentially dry. The heater heats the borehole surface primarily via thermal radiation. As heat is conducted through the fractured rock mass, vaporization begins on the outer surfaces of the matrix blocks closest to the borehole and then proceeds in toward the center of each block. Where temperatures are in excess of saturation conditions, vigorous boiling occurs. For water vapor to flow out of the matrix blocks, gas-phase pressures must increase from the surface of the matrix block to its interior, resulting in the elevation of the boiling temperature with distance into the matrix block. Water vapor that enters the fractures is subsequently driven by gas pressure gradients (including buoyancy effects) within the fracture network. In general, vapor flow in the fractures is directed away from the center of the boiling, either radially outward or inward toward the heater hole. Vapor flow in the fractures persists until condensation conditions are encountered. Condensed water in the fractures, which is not immediately imbibed by the matrix, flows under gravity and capillary forces in the fractures either (1) back toward the boiling zone where it reboils, or (2) out into the condensation zone where it is eventually completely imbibed by the matrix.

Parameters Measured

The following parameters were measured to characterize the behavior of the rock mass within a few meters of the heater before, during, and after the thermal cycle. This discussion includes the results for a subset of the measured parameters and present interpretations pertaining to the evolution of the near-field environment around a simulated waste package.

Figure 1. Schematic of a vertical cross section of a probable hydrologic scenario in partially saturated welded tuff subjected to a thermal load.

Rock Mass Temperatures

Rock mass temperatures were used in reconstructing the thermal response of the rock and in evaluating the performance of the test equipment.

Rock Mass Gas Pressure and Atmospheric Pressure

Rock mass gas pressure and atmospheric pressure were used in reconstructing the flow regime of the air and water vapor in the rock mass.

Borehole Measurements of the Relative Dielectric Constant and Thermal Neutron Counts

Cross borehole measurements of the relative dielectric constant of

the rock and single borehole measurements of thermal neutron counts were used to infer the spatial and temporal changes in the moisture content of the rock mass.

Air Humidity

Air humidity measurements in the rock mass were used to calculate the pore pressure gradients that drive the movement of liquid water within the rock mass. Changes in the moisture content and pore pressure information were used to reconstruct the flow regime of liquid water in the rock mass. The spatial variations in moisture content were used to infer the flow paths of the liquid water and to define regions that are losing or gaining water as a function of time.

Air Permeability

The air permeability measurements were used to detect changes in the permeability of the rock surrounding the heater emplacement borehole. These measurements were made along the heater borehole after all of the boreholes were drilled and sealed. The measurements were repeated after the heating sequence was completed and after the heater was removed from the borehole.

Fracture Locations and Orientations

Fracture locations and orientations were measured in all boreholes by means of a borescope and/or by borehole television surveys performed before the heater was energized. The measurements were repeated along the heater emplacement borehole after heating was completed, and these data were used:

- To determine the effects of heating on the stability of the emplacement borehole walls.
- To interpret the changes in fracture permeability caused by the heating and cooling cycle.
- To analyze the flow regime of vapor and liquid water in the rock mass as inferred from other measurements.

Condensed Volume of Steam

The measurements of the condensed volume of steam invading the heater borehole were used to estimate the amount of gas phase humidity that flows toward the heater borehole.

Test Description

Sandia National Laboratories constructed the G-Tunnel Underground Facility for the Yucca Mountain Project (Fig. 2). This facility consists of drifts driven in welded tuff under Rainier Mesa, NTS. The PFBSFT was conducted

Figure 2. G-Tunnel Underground Facility.

in the rock mass between the small diameter heater alcove and the rock mechanics drift.

The test included an accelerated thermal cycle to examine the effects of the heating and cooling sides of a thermal pulse. Figure 3 shows the test's power schedule. The initial thermal loading for the 3-m heater was ~ 3.3 kW (1.1 kW/m of heater length). To increase the disturbed volume of rock within the relatively short time available for prototype testing and to create sufficiently high rock temperatures to drive two-phase fluid flow, we set the initial thermal load per unit length of emplacement borehole higher than the loading expected for a typical spent fuel container (0.4 – 0.7 kW/m).

The duration of the heating was based on the test criteria of heating the rock mass until the boiling point isotherm moved ~ 0.6 – 0.7 m radially from the heater borehole wall. Another test criteria involved achieving emplacement heater borehole temperatures similar to those expected for the repository (235°C). The spatial extent of the heating affected a volume of rock large enough to include several fractures.

Figures 4 and 5 show the borehole layout and the measurement stations for the various instruments used. The test location within G-Tunnel is bounded by the small diameter heater alcove and the rock mechanics drift, as shown in Fig. 4. The heater borehole is inclined slightly upward (elevation

increases from the collar to the end of the borehole) from the rock mechanics incline. The diameter of the heater borehole is 30.5 cm.

Twelve of the boreholes were used to monitor the rock response; all of these were nearly horizontal and were inclined slightly downward. The majority of the boreholes were orthogonal to the emplacement hole axis, which provided better coverage of the spatial variations in rock responses that occur parallel to the radius of the emplacement borehole. This arrangement allowed measurements in the direction of expected maximum thermal and hydrologic gradients.

Three boreholes were drilled parallel to the heater borehole axis to monitor rock response beyond the ends of the heater.

Figure 3. Heater power schedule used for the PEBSTT.

Changes in Rock Mass Moisture Content

A thorough understanding of local hydrology over the package lifetime is central to understanding waste package performance. Geophysical techniques were used to monitor changes in rock moisture content during the test. The techniques chosen included neutron logging in single boreholes and high-frequency electromagnetic measurements performed between boreholes. In this article, we interpret only the neutron log results; for the electromagnetic measurement results, see Daily et al. (1989).

The neutron logging probe contains a source of high-energy neutrons and a detector for slow (thermal) neutrons. When water is present in the rock, the hydrogen in the water slows the neutrons for detection. Seven boreholes

(NE-1 through NE-7) were sampled before the heater was turned on; the measurements were repeated frequently after the heater was energized to monitor temporal and spatial changes in moisture content. A paraffin shield included with the probe was sampled at the beginning and end of each logging day to verify that the tool was functioning properly.

For each borehole, we calculated the differences between the "before" and "after" measurements ("after" heating minus "before" heating) to produce a difference log. We have chosen to use differences rather than absolute values of moisture content because the effects of the borehole liners and the grout with in the survey boreholes are still unknown.

A spatial filter was applied to each difference log to smooth the spikes in the trace caused by the random fluctuations in the number of neutrons generated by the

Figure 4. Plan view of the as-built borehole layout. The various line patterns identify the type of measurement made in each borehole. The locations of the rock mechanics incline and the small diameter heater alcove in G-Tunnel are shown for reference.

Figure 5. Side view of the as-built borehole layout as viewed from the rock mechanics incline. The various line patterns identify the type of measurement made in each borehole.

radioactive source in the probe. The precision for the filtered data is estimated to be $\pm 0.003 \text{ g/cm}^3$. This precision estimate means that for any one point on a difference trace that equals or exceeds $\pm 0.003 \text{ g/cm}^3$, there is a 95% probability that the difference is caused by true changes in the measurement and a 5% probability that it is caused by random fluctuations in the neutron output of the radioactive source.

Boreholes NE-2A, NE-6, and NE-7 are three coplanar boreholes located above and below the center of the heater as shown in Fig. 5. The data collected along these boreholes were combined and plotted as a function of radial distance to the center point of the heater assembly. The changes shown were calculated relative to preheating moisture measurements. Figures 6–8 consist of two plots each that show the same data at two different scales so that the smaller changes

occurring at the more distant locations can be examined.

Figures 6 and 7 show radial profiles of changes in moisture content during the drying and rewetting phases of the test. These figures also

show the difference traces calculated from day 70 data (the heater was energized on day 0) and for day 301 (the last data set was collected 106 days after the heater was de-energized). The data in Fig. 6 were collected midway through the maximum power phase of the test. As expected, the rock closest to the heater (the shortest distance) lost substantial amounts of moisture. However, the rock near borehole NE-2A dried at a faster rate than the rock near NE-6. Fracture maps of the test region suggest that a higher concentration of fractures mapped along NE-2A may be one cause for this faster rate of drying. Also note that rock located between 1.75- and 2.25-m radii showed a small increase in moisture content as a result of the condensation of steam generated in hotter regions closer to the heater.

Between days 70 and 127 (data are not shown), the NE-2A profile showed very little additional drying when compared to Fig. 6, whereas the NE-6 profile showed significant additional drying. Both profiles are closely matched with the caveat that the width of the

Figure 6. Changes in moisture content plotted against radial distance after 70 days of heating (approximately midway through the maximum power phase). A subset of the curves in (a) are shown enlarged in (b). Changes are calculated relative to the preheating moisture conditions.

Figure 7. Changes in moisture content plotted against radial distance for the next to last day of maximum power heating. A subset of the curves in (a) are shown enlarged in (b). Changes are calculated relative to the preheating moisture conditions.

drying region appeared to be slightly wider near NE-2A. The closely matched profiles suggest that the rock near NE-2A and NE-6 was almost completely dry because very little additional drying occurred near NE-2A during the 57 days of continued heater operation at maximum power. The radius of

the dry zone achieved was ~ 0.7 m; this is consistent with the test objective of achieving boiling conditions within a 0.6–0.7-m radius.

The radial profile of changes in moisture content for day 301 is shown in Fig. 8. These data were collected during the postheating phase of the test, 106 days after the heater

was de-energized. The data show relatively little change in the rock near the heater during the power rampdown and postheating phase of the test. The data also show that the rock above the heater (borehole NE-6) rewet more quickly than the rock below the heater (borehole NE-2A) for distances less than or equal to 0.5 m. This suggests that the gravity-driven flow plays a role in the rewetting process.

We gained further insights into the rewetting process by calculating changes in moisture content relative to the last day of full power heating. Figure 9 presents changes in moisture in borehole NE-2A, where "after" minus "before" changes are calculated relative to day 127 (i.e., the "before" data correspond to day 127, which was the day before the last day of maximum power heating). The data were obtained during the power rampdown and postheating phases of the test when the rock was cooling and rewetting. Also shown are fractures mapped along the boreholes. Note the rock regions that show the greatest rewetting are clustered around the fractures in NE-2A. The high correlation between fracture locations and high rewetting suggests that fractures play a dominant role in the rewetting process. One mechanism for rewetting along fractures may be capillary condensation of air humidity in the fractures because humid air (found in the wetter portions of the rock mass) can travel with relative ease along the fractures. Another mechanism that may be playing a role in the rewetting process is water dripping along fractures; Fig. 8 shows evidence consistent with this argument in that the rewetting front has penetrated more quickly above the heater (borehole NE-6) than below the heater (NE-2A).

Figure 8. Changes in moisture content plotted against radial distance 301 days after the start of heating (106 days after the heater was de-energized). A subset of the curves in (a) are shown enlarged in (b). Changes are calculated relative to preheating moisture conditions.

Figure 9. Changes in moisture content mapped along borehole NE-2A. Changes are calculated relative to the last day of full power heating. Fractures mapped are shown for comparison.

Temperature Measurements

Temperature measurements were made to characterize the thermal response of the medium around the heater. There were a total of 112 thermocouples used in this test. All of these thermocouples were chromel-alumel (Type K) with an accuracy of $\pm 1^\circ\text{C}$ (1.8°F). Ten thermocouples were installed within the heated portion of the heater borehole to monitor container and borehole wall temperatures. The other 102 thermocouples were located in boreholes TC-1, TC-2, P-1, P-2, and P-3.

Figure 10 shows the temperatures measured in all boreholes during the last day of the maximum power phase (day 128). The temperatures are plotted as a function of the natural log of radial distance to observe the linearity or nonlinearity of the temperature profiles. Note that with the exception of the P-3 profile, all profiles are fairly linear. This indicates that thermal conduction is the predominant heat transfer mechanism for the regions sampled. There are a few temperature values (in both P-2 and P-3) that deviate from a straight line for values of the radial distance < 1 m (natural log < 0). At these locations,

fractures were mapped in close proximity (within a few centimeters) of the thermocouple locations. This close proximity suggests that the depressed temperature values within the boiling region are caused by fractures. At least two explanations can be postulated:

1. The fractures create more permeable flow paths for vapor to escape the system. As water is converted to vapor and allowed to escape, energy is removed from these locations. This energy is therefore not available to elevate the rock temperatures.
2. The fractures also create flow paths along which drilling water

Figure 10. Temperatures in various boreholes measured during the last day of full-power heating.

moves downward. Borehole P-3 is lower in elevation than P-2. The matrix adjacent to these fractures might have imbibed some of the drill water, thereby increasing the initial saturation near the fractures. This elevated saturation would also tend to depress the local temperature for the same reason as stated above in explanation 1.

The temperatures along borehole TC-2 are generally cooler than those in other boreholes at the same radial distance. The temperatures in P-2 are the highest among the five boreholes. Boreholes TC-1, P-1, and P-3 registered about the same temperatures. These differences in temperature are probably due to the heterogeneous thermal properties of the rock mass. The almost linear portion of these curves at larger radial distances indicate that conduction is probably the main heat transfer mechanism. Also, the TC-2 profile shows a more shallow slope, which implies that the

thermal conductivity of the rock around TC-2 is higher than at other locations.

A comparison of the P-2 and P-3 temperature profiles in Fig. 10 shows that the temperatures in P-3 are consistently lower than those in P-2. This is probably due to the higher temperatures measured at the top of the container. Air circulation within the heater container (i.e., hotter air rising to the top of the container) may have caused the asymmetry in temperatures.

Figure 11 shows the temperatures for thermocouples 86 through 89 as a function of time. These thermocouples are located below and to the side of the heater (Fig. 12). Thermocouples 86 and 87 show typical profiles of temperatures within the boiling region. The temperature increased quickly at the beginning of heating, then became almost linear with time. At these later times, the temperature-time plot

Figure 11. Evolution of selected temperatures in the P-3 borehole as a function of time. Thermocouples 88 and 89 show a flattening of the profiles between days 50 and 150 that may be due to the movement of condensed water in this region.

Figure 12. Cross section near the heater midplane, showing thermocouple locations relative to the heater. Data for thermocouples 86 to 89 are shown in Fig. 11.

has no obvious change of slope. A change in slope would indicate a change in the thermal conductivity and heat capacity of the rock. At later heating times, changes in slope may be attributed to the latent heat capacity of the water as the water boils or condenses in the rock mass.

Thermocouples 88 and 89 in Fig. 11 show very atypical temperature profiles. Note that the maximum temperature for both profiles is $\sim 97^{\circ}\text{C}$. Also the profiles remained near the maximum temperature for 70 or more days even though the rest of the rock mass continued to increase in temperature during this period (maximum power phase). In addition, the slope on the left side of the flattened portions of these two profiles rapidly increased before the flattening occurred. This indicates that additional energy was

being deposited at these locations. We postulate that condensed water with near-boiling temperature moved into this region from regions above the heater as illustrated by the conceptual model shown in Fig. 13. We recognize the possibility that this type of temperature signature is due to a heat pipe effect, but we consider this unlikely because of the rapid increase in slope observed prior to the flattening.

Changes in Air Permeability

Air permeability testing was conducted along sections of the heater emplacement borehole before heating and at the end of the power rampdown phase of the test. The objectives of this test were to characterize the in situ permeability of the fractured tuff around the heater

borehole and to determine the effect of a heating and cooling cycle on rock mass permeability. A number of permeability measurements were made along packed-off sections of the borehole before the rock mass was heated and again after all heating was completed.

We used steady-state air-injection to measure the permeability. Inflatable packers were placed in preselected sections of the borehole to isolate these sections for testing. Preheating and postheating permeability values are compared in Fig. 14. Equivalent porous medium permeabilities along the heater borehole are also compared with mapped fracture locations. The permeabilities shown here were measured at a nominal pressure of 34 kPa (5 psi). The permeability of a 36-cm-long test zone varies from a minimum of 0.04 darcy (D) to a maximum

Figure 13. Proposed flow phenomena for a fracture perpendicular to the heater axis. The view is along the fracture plane. This conceptual model was proposed as an explanation for the atypical temperatures shown by thermocouples 88 and 89 (shown in Fig. 11). Also shown are the increased regions of the drying and wetting fronts along the fracture.

of 150 D. The higher permeability value corresponds to a highly fractured zone, a few inches thick, at a depth of about 7.7 m from the collar.

A comparison of the preheating and postheating profiles in Fig. 14 shows that portions of the measured region had increases in gas permeability as a result of the heating cycle. Note that the greatest percentage change occurred near the center of the heater element location. This is also the portion of the borehole with the fewest fractures mapped. We postulate that the increase in permeability is due to an increase in the number of

small fractures (microcracks) intercepting the heater borehole. Television surveys of the borehole showed no change in the visible fractures relative to the preheating survey. This implies that any new fractures were small enough to escape detection. Given that the lowest permeabilities were measured in the region of greatest change, increases in microfractures would have a relatively greater effect here than in regions with a higher preheating permeability. Note that the increased permeability is low when compared with the natural heterogeneity in air permeability along the borehole.

Steam Invading the Heater Emplacement Borehole

The thermal loading exerted by the heater dries the partially saturated rock surrounding the emplacement borehole. Vapor pressure gradients drive steam into pressure sinks such as the emplacement borehole and fractures (see Fig. 1). Steam may also move along the fractures toward the emplacement hole or move outward and condense where the temperatures are sufficiently cool. The moisture entering the heater emplacement borehole was collected to provide a measure of the resistance to vapor transport toward the heater relative to the resistance to transport away from the heater as a function of time.

The moisture migrating into the heater emplacement borehole was collected using a high-temperature inflatable packer fitted to a 51-mm-i.d. aluminum pipe. The packer sealed the borehole 50 cm outward (i.e., toward the collar) from the heater and allowed the steam to flow through the aluminum center pipe, condense, and flow to the borehole collar and into a collection device (the isolated section remained unpressurized at all times). The heater emplacement borehole had a slope of 5° downward to the collar to facilitate the collection of the condensed moisture.

Figure 15 presents the results from an analysis of the water collection rates during the test. Also shown for comparison is the partial pressure of water within 15 cm of the intake for the steam collection system; the partial pressure values are calculated based on relative humidity and air temperature measurements. These data show

Figure 14. Gas permeability measurements made along the heater borehole before and after the heating of the borehole.

that an insignificant volume of water was collected within the first two weeks of the experiment. Thereafter, the rate of water collection reached a maximum of ~ 0.05 liters/day, which is less than the value of ~ 0.5 liters/day predicted by the scoping calculation. The reasons for this discrepancy are unclear at present. One possible explanation is that the packer temperature at the intake point for the system is below the dew point. This might have caused some vapor to condense, pond, and possibly drain into fractures, instead of entering the center pipe at the packer. Temperatures at some points on the packer suggest that packer surfaces could have acted as condensation points. Another possible reason for the discrepancy is that the scoping calculations assume an infinitely long heater. This assumption would result in a substantial overestimate of the steam produced. Additional work is in progress to evaluate the impact of this assumption.

The water collection rate (Fig. 15) peaked at about day 50 and then

decreased between days 50 and 90. We did not expect this decrease and have not yet explained it. Note that the partial pressure of the water in the air remained approximately constant between days 50 and 128. All other conditions being equal, we expected the moisture collection rate to remain constant if the partial pressure of the air in the heater borehole remained constant. The partial pressure of the water started to decrease as expected on day 128 when the power rampdown phase began.

Another unexplained aspect of the moisture collection rate is the abrupt water collection rate decrease at about day 90. This signature may be an indication of problems with the sensor; however, post-test calibration of the sensor did not indicate that the sensor was flawed.

Figure 15. Moisture collection rate and partial pressure of water in the heater borehole air as function of time.

Summary

The PEBST provided valuable experience that will improve our ability to conduct the Engineered Barrier System Field Tests planned for the Exploratory Shaft Facility in Yucca Mountain. The results from the PEBST indicate that many environmental conditions expected to develop around a heater in welded tuff are as described in Fig. 1. The test also showed us which of the applied measurement techniques performed adequately under realistic environmental conditions and which ones may need to be modified or replaced.

The PEBST confirmed elements of the conceptual model of predicted environmental conditions. Test results confirm that a dry zone develops around the heater borehole (refer to the conceptual model in Fig. 13) and that the degree of drying increases with proximity to the heater. A "halo" of increased saturation develops adjacent to the dry region and migrates away from the heater as rock temperatures increase. Some of the fractures intercepting the heater borehole increase the penetration of hot-dry conditions into the rock mass. A build-up of pore gas pressure develops in rock regions where vigorous evaporation is occurring.

During the portions of the test, when the heater power was gradually reduced and eventually turned off, the dry region around the heater cooled off and slowly regained water (refer to the conceptual model in Fig. 16). Rewetting of the dry region occurred first in the rock above the heater and in the rock adjacent to fractures.

To explain the differences in the drying and rewetting behavior above and below the heater, we developed conceptual models that are based on the results described here and on our numerical modeling study. In general, we found that

water vapor generated in a matrix block moves toward the closest fracture face (or toward the surface of the heater borehole if the block is adjacent to the borehole). Upon entering the fracture, water vapor tends to move radially outward through the fracture system until encountering condensation conditions. The heater borehole moisture collection system and the condensation on the heater packer cause some of the vapor in the fractures to move radially inward toward the heater hole. Water that condenses above the heater drains downward through the fractures. Much of this

downward flow intersects the boiling zone and is reboiled, thereby slowing the upward progress of the boiling front. We observed that some of the downward flowing condensate reboiled at the lower flank of the heater, thereby stabilizing the boiling front at that location. Water that condenses below the heater drains away from the boiling zone.

Since the matrix imbibition rate is slow relative to the condensate generation and drainage rates, most of the downward draining condensate located below the heater left the system before it

Figure 16. Proposed conceptual model of mechanisms that affect the rock rewetting process around a heater. Proposed conceptual model of the mechanisms that dominate the dry region rewetting process during cooldown of the rock mass. A transect along a matrix block intersected by a fracture is shown.

could be subsequently reboiled. We also observed that the boiling zone effectively acted as an "umbrella" shielding the rock below the heater from the downward drainage of condensate generated above the heater. Rewetting of the rock above the heater and to one side of the heater was partially the result of condensate drainage in fractures. Throughout the fractured rock mass, rewetting also occurred via binary diffusion of water vapor (driven by relative humidity gradients) and via Darcy flow (driven by pressure gradients). As this water vapor reached drier rock, it condensed along the fracture faces (by capillary condensation) and was imbibed by the matrix.

Measurements of air permeability made along the heater borehole

prior to heating show that the fracture system exhibits a strong heterogeneity in fracture permeability. Measurements made after the heater was turned off show that there was an increase in air permeability as large as an order of magnitude for the rock that reached the highest temperatures.

The test also yielded some surprises in terms of environmental conditions. The temperature above the heater container was $\sim 30^{\circ}\text{C}$ (54°F) higher than below the container. This condition might be a consequence of hotter air accumulating at the top of the container; it might also be related to the higher moisture content below the heater borehole. The amount of steam that invaded the heater borehole is much less than that predicted by

the scoping calculations. The reasons for this discrepancy are not clearly understood, but they might be a result of an inadequate system used to collect and condense the steam or might be an indication of invalid assumptions used in the scoping calculations.

Acknowledgments

This article was prepared by Yucca Mountain Project (YMP) participants as part of the Civilian Radioactive Waste Management Program. The YMP project is managed by the Yucca Mountain Project Office of the U.S. Department of Energy, Nevada Operations Office; YMP work is sponsored by the DOE Office of Civilian Radioactive Waste Management.

References

- Daily, W., A. Ramirez, T. Leng, and V. LaTorre (1989), *High Frequency Electromagnetic Tomography to Study Near Field Hydrology*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-101865; also submitted to the *Proc. of the ANS Topical Meeting, Focus '89 Nuclear Waste isolation in an Unsaturated Zone*, Las Vegas, NV, September 18-21, 1989.
- Ramirez, A. L., J. Beatty, T. A. Buscheck, R. Carlson, W. Daily, V. R. LaTorre, K. Lee, W. Lin, N. Mao, J. J. Nitao, D. Towse, T. Leng, D. Watwood, and D. Wilder (1989), *Prototype Engineered Barrier System Field Test Progress Report*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-101615.
- Yow, J., Jr. (1985), "Test Concept for Waste Package Environment Tests at Yucca Mountain," in the *Proc. of the 28th U.S. Symposium on Rock Mechanics*, Tucson, AZ, pp. 1035-1042; also in Lawrence Livermore National Laboratory, Livermore, CA, UCRL-95568.
- Zimmerman, R. M., and R. E. Finley (1986), *Summary of Geomechanical Measurements Taken in and around the G-Tunnel Underground Facility*, NTS, Sandia National Laboratories, Albuquerque, NM, SAND86-1015.

Geochemical Modeling: An Integrated Approach to Nuclear Waste Disposal Issues

Carol J. Bruton, Brian E. Viani, William L. Bourcier,
Kenneth J. Jackson, and Roger D. Aines

Geochemical Modeling Project

The application of geochemical models will play an integral role in predicting the long-term performance of proposed nuclear waste disposal repositories. To meet waste repository licensing requirements, we must be able to predict the response of repository components and of the enclosing host rocks and fluids to temperature fluctuations, fluid flow, and radionuclide releases over time periods of up to 100,000 years. Results from experimental programs cannot be used alone to accurately predict the effect of extended time periods on waste packages and on the environment, nor can they be used to evaluate all possible variables that might affect the repository system. Experimental results must be translated into quantitative models capable of predicting system response. Confidence in these models will be increased if the basic chemical mechanisms controlling system response are understood, and if process-oriented and mechanistic, rather than empirical, models are developed. We are using the computer codes EQ3NR and EQ6 and their thermodynamic data base to simulate the complex interplay among processes that control rates of waste form degradation and changes in the geochemical environment throughout the post-closure period. Experimental results are being reproduced and evaluated with EQ3/6 to determine the controls of observed phenomena and to guide future experimentation. These codes are also being applied to some diverse geochemical problems to demonstrate their general utility and flexibility.

For many years, geologists have studied the changes that occur in rocks as their physical and chemical environments vary in response to geologic events. The storage of nuclear waste in underground repositories will perturb the physical and chemical environment of the host rocks and pore fluids in a manner that is analogous to naturally occurring geologic events. Quantitative, process-oriented models can be used to analyze changes described in the field and studied further in the laboratory. Ongoing work at LLNL indicates that geochemical modeling techniques in conjunction with experimentation can be

an invaluable tool for predicting the long-term performance of nuclear waste repositories.

Before a license permitting nuclear waste disposal can be issued, the performance of a repository must satisfy specific safety standards set by government regulations. To meet these requirements, the responses of the repository components and of the enclosing host rocks and fluids to temperature fluctuations, fluid flow, radionuclide release, and other factors must be predicted over time periods of up to 100,000 years. We must develop quantitative geochemical models capable of predicting

system response over these extended time periods.

Confidence in the models will be increased if the basic mechanisms controlling system response are understood, and if process-oriented and mechanistic, rather than empirical, models are developed.

In this article, we illustrate various ways in which geochemical modeling can be used to address some of the key issues in nuclear waste disposal.

- We discuss the necessity of integrating geochemical modeling with experimentation.
- We describe the computer codes EQ3NR and EQ6, which are

representative examples of geochemical modeling codes widely used today, and their thermodynamic data base.

- We briefly review the proposed Yucca Mountain, Nevada, nuclear waste repository.
- We outline some of the areas in nuclear waste management to which geochemical modeling can be applied.
- We discuss how government regulations focus nuclear waste disposal research.
- We present five examples of ongoing research projects at LLNL that involve the application of EQ3/6 to a diverse set of geochemical problems.

Integration between Geochemical Modeling and Experimentation

Geochemical modeling is being used to examine the types of processes affecting the repository and host rocks and to predict repository system performance over tens of thousands of years. Experimental programs form the basis for many of the conclusions made thus far about system performance. However, geochemical modeling is required to supplement experimental programs because laboratory experiments:

- Cannot determine the effect of extended time periods on waste form degradation rates and on geochemical changes in the repository and host rock.
- Can reproduce only a limited number of potential variations and combinations of variables that may impact the repository system.

Models based solely on site-specific experimental results tend to be empirical in nature, and they cannot be extrapolated with confidence to predict results under different sets of conditions. In addition,

laboratory experiments last a few years at most, and their results cannot be used to accurately predict the changes that will occur in the repository over thousands of years. Geochemical modeling codes can, however, be used to simulate the complex interplay among processes that control rates of waste form degradation and changes in the geochemical environment throughout the post-closure period, provided appropriate process-oriented models are available.

Geochemical simulations can be used to reproduce and evaluate experimental results to determine the controls of observed phenomena and to guide future experimentation. The efficiency and speed of computer simulations allow sensitivity analyses to be made of the impact of various scenarios on repository performance. Our confidence in predictions of system performance will be improved if we can develop a basic understanding of the controlling processes. Laboratory and field experiments, as well as natural analogue studies, are required to test and validate the geochemical modeling codes and their thermodynamic data bases prior to making long-term predictions of repository performance.

Geochemical Modeling with the EQ3/6 Computer Codes

Basic Concepts

The geochemical modeling code package EQ3/6 is used at LLNL to simulate chemical reactions between solids and an aqueous phase as a function of changes in the physical and chemical environment (Wolery, 1979). The package consists of two codes: EQ3NR (Wolery, 1983) and EQ6 (Wolery and Daveler, 1989), and their requisite thermodynamic data base (Delany and Lundeen, 1989). EQ3NR carries out

species distribution calculations in which species complexation within the aqueous phase is calculated for a given bulk fluid composition at a specified temperature and pressure.

EQ6 is a dynamic, reaction-path modeling code that simulates the reaction between a fluid and a specified set of solid phases or another aqueous phase. The code solves equations of charge and mass balance, mass action, and rates of solid precipitation and dissolution. Basic input to EQ6 consists of the following:

- Mineralogic or chemical composition of the reactant solid, rock, or fluid.
- Starting fluid composition, pH, and redox potential.
- Temperature and temperature changes during reaction.
- Relative or absolute rates of solid precipitation and dissolution.
- Specification of a closed or open system.

The simulation of the reaction between fluids and solids yields:

- The sequence of solid precipitation/dissolution events and the amounts and compositions of solids produced and/or destroyed during the reaction.
- The changing composition of the aqueous phase during the reaction, including pH and redox potential.
- The derived physical and chemical parameters such as volumes of solid phases, compositions of solid solution precipitates, and dissolution affinities for reactants.

For more detailed descriptions of the EQ3/6 codes, including detailed descriptions of the governing equations and numerical methods, see Wolery (1983) and Wolery and Daveler (1989). For references to published literature on applications of EQ3/6 and other geochemical modeling codes, see Wolery et al. (1989, 1984), and Jackson and Bourcier (1989).

The basic operation of EQ6 involves the stepwise, irreversible reaction of specified reactants with a fluid phase. Rates of reaction can be arbitrarily chosen or can be specified by a kinetic rate law (see "Kinetics in Glass Dissolution," later in this article). Temperature can be held constant at values from 0 to 300°C, or varied as a function of time. The driving forces for reaction are thus the initial disequilibrium between reactants and the fluid, and/or changes in temperature. As the reactants are added to the fluid, the fluid composition is changed, and the code recomputes the species distribution in the fluid. The rates of equilibration within the aqueous phase are considered to be instantaneous and reversible. The affinities for precipitation of all possible solid phases in the thermodynamic data base for the chemical system under consideration are checked. If any phases are supersaturated, the most supersaturated phase is precipitated until the solution comes to equilibrium with respect to that phase. All affinities are checked again, and additional solids are precipitated until the solution is in overall equilibrium with the solid precipitates. The code then adds more reactant to the fluid and repeats the entire cycle. The reaction continues until overall system equilibrium is attained, or until the user stops the reaction.

The application of a geochemical modeling code to the study of a particular system or subsystem depends on whether appropriate submodels exist in the code to account for the significant processes involved. Submodels in EQ6 that can be invoked as needed to describe specific scenarios of repository performance include:

- Solid dissolution and precipitation kinetics.
- Solid solution (see "Solid Solution Models for Clinoptilolite and Smectites," later in this article).

- Cation exchange.
 - Thermodynamic properties of high ionic strength solutions.
 - Fixed fugacity of gases.
- Wolery et al. (1989) describes EQ3/6 capabilities and recent code improvements. The incorporation of these options into EQ3/6 greatly increases the realism of applying geochemical modeling to the study of reactions in the repository and in the surrounding environment.

System Conceptualization Required to Formulate Code Input

Effective application of geochemical simulations in waste disposal and in other areas requires that the user first conceptualize the physical situation to be modeled, and then define the starting physical and chemical conditions of the system. The conceptual model thus derived is used as the basis for setting up simulation calculations, and it controls the usefulness and applicability of simulation results.

Natural and even man-made systems tend to be extraordinarily complex. The initial input to a simulation is usually designed to simplify the system to its most integral features and to guide system evolution through its simplest and most direct path. Thus, simulations often begin by assuming a closed system with fixed rates of reactant dissolution and with equilibrium precipitation and dissolution of all other phases. The initial equilibrium simulation serves as a baseline calculation from which further work proceeds.

Sometimes the initial baseline calculations can be useful in understanding system evolution (see, "Diagenesis in Sedimentary Basins," later in this article). The degree of match between simulation and field and/or laboratory data often reveals the adequacy of the initial simplifying assumptions. The initial conceptualized system can be

"customized" by including additional chemical processes in further simulations so that a more reasonable match to observed or anticipated data can be obtained. For example, a diagenetic system may be modeled as an open system, subject to externally imposed variations in component concentrations, rather than as a closed system (Harrison, 1989). Later in "Kinetics of Glass Dissolution," we describe the formulation of a rate equation for nuclear waste glass dissolution, which exemplifies this approach.

Thermodynamic Data Base

Our ability to produce relevant and informative simulations of chemical processes depends on the adequacy of the thermodynamic data base as well as the adequacy of the models in the geochemical simulator. The thermodynamic data base for EQ3/6 currently contains data for 78 elements, 619 aqueous species, and 886 solids and gases. It is much more complete, however, for common aqueous species and rock-forming minerals than it is for aqueous species and solids containing radionuclides.

The thermodynamic properties of radionuclides have been relatively recently added to the data base and, therefore, are not as thoroughly tested through years of applications as the remainder of the data base. Much effort is required to amass a complete and internally consistent data base for radionuclides and to test this data base by comparing simulation results with laboratory and field data.

With the addition of improved solid solution models and cation exchange models in EQ3/6, it is crucial to fully test these models and their input parameters with experimental and field data. Later in this article, we present an example of an EQ3/6 application that focuses on predicting clinoptilolite composition as a function of

groundwater composition (see "Solid Solution Models for Clinoptilolite and Smectites") to demonstrate this point.

Geochemical Modeling Applications in Nuclear Waste Disposal

Potential Repository Site

The feasibility of burying high-level nuclear waste in the unsaturated zone at Yucca Mountain, Nevada is currently under study. We can use a description of a proposed high-level nuclear waste repository at Yucca Mountain to illustrate some of the potential applications of EQ3/6 to nuclear waste disposal problems.

The potential repository horizon at Yucca Mountain lies at depths of 200 to 400 m in the Topopah Spring Member of the Paintbrush Tuff. The tuff is densely welded and devitrified at the proposed repository horizon, and it contains secondary phases such as clays and zeolites. The proposed repository horizon is located in the unsaturated zone above the water table in order to limit water access to the repository. The waste will consist of spent nuclear fuel and, in lesser quantities, borosilicate glass. Waste will be enclosed in a package that, together with any overpacking materials, borehole liners, and repository seals, will form an engineered barrier system designed to isolate the waste as effectively as possible from the environment (U.S. DOE, 1988).

Scenario of Radionuclide Release

When the waste package is emplaced in the repository, the temperatures surrounding the waste package will rise to a maximum of about 250°C within 50 years or less, and then will gradually decrease (Glassley, 1986; O'Neal et al., 1984). Pore fluids in the host rock will be

heated and, possibly, vaporized and will migrate in some fashion. Fluids will eventually return to the waste package as it cools.

If the engineered barrier system surrounding the waste is breached at any time, pore fluids may come in contact with the waste. The radioactive waste form may then begin to dissolve into the fluid. If this fluid exits the waste package, it will carry radionuclides into the host rock.

Heating of the host rock may cause mineralogical changes and may alter pore fluid chemistry. The mineralogical transformations may change the transport properties of the rock (e.g., permeability), which would affect radionuclide transport away from the waste package. The ability of zeolites and clays in the host rock to sequester released radionuclides may also be compromised or enhanced (U.S. DOE, 1988). If the fluid chemistry changes significantly, it will effect the waste package system's susceptibility to corrosion. Geochemical models are especially applicable to these types of studies because they were designed to study similar problems in mineral dissolution/precipitation as a function of changes in the physical and chemical environment. The modeling codes calculate the changes in the composition of the fluid phase and the changes in mineralogy.

The rates of radionuclide release from the glass and spent fuel waste forms over time periods of tens of thousands of years must be known in order to predict the magnitude of radionuclide release. Radionuclide release rate models will also serve as the source term for other calculations involving the fate of radionuclides in solution. Kinetic models for both glass and spent fuel waste form dissolution must be developed. To be accurate, these models must take into account the entire range of physical and chemical

conditions that might be expected in the repository.

The physical and chemical characteristics of the fluid phase will determine its capacity to hold radionuclides in solution. Radionuclides may be carried in the fluid phase as dissolved species, colloids, and even particulate matter. Characteristics such as the composition, pH, and redox potential of the fluid phase can greatly affect radionuclide solubility as well as colloid and particulate formation. Geochemical modeling can help to predict radionuclide solubilities as a function of the chemical characteristics of the fluid phase.

Once the radionuclides have been released from the waste form and incorporated into a fluid phase, their transport away from the waste package must be considered. The physical aspects of fluid flow away from the waste package must be coupled to models that characterize the sequestering of radionuclides by various components of the engineered barrier system and host rock.

Knapp (1989) recently coupled EQ6 to a one-dimensional fluid flow model to calculate the spatial and temporal distribution of solid precipitation/dissolution events. This code calculates the location and movement of reaction fronts during fluid flow at a fixed velocity through a permeable medium. Dissolution of host rock mineralogy and precipitation of secondary phases must be considered, as well as the exchange of radionuclides and cations in surface exchange reactions with pre-existing clays and zeolites in the host rock tuffs. Geochemical models must be extended to include provisions for surface processes such as cation exchange reactions and sorption, especially with regard to radionuclides. Radionuclides could also be sequestered as trace components of solid solutions; solid solution

models (Bourcier, 1985) must be extended to account for these trace components.

There are many other potential applications of geochemical codes to nuclear waste disposal research topics that we do not discuss here. However, our examples illustrate the different ways in which geochemical modeling can be used, and the variety of study areas to which it can be applied. Limits of geochemical modeling capabilities are set by the availability of computer codes to model the processes and mechanisms of interest, and by the adequacy of the thermodynamic data base.

Impact of Government Regulations on Research

Much of the geochemical research in nuclear waste disposal done by national laboratories such as LLNL is primarily devoted to demonstrating whether or not a specific repository meets the performance requirements set by the U.S. Nuclear Regulatory Commission (NRC) and the U.S. Environmental Protection Agency (EPA). Licensing of the waste repository for operation requires that the repository performance meets limits on quantities and rates of radionuclide release over extended time periods. For example, the Code of Federal Regulation 10 CFR 60 (NRC, 1983) requires a satisfactory demonstration that the release rate for a number of specific radionuclides will not exceed one part in 10^5 of the waste inventory per year in the period following 1000 years after closure of the repository. The Code of Federal Regulation, 40 CFR 191 (EPA, 1985), sets limits on the total release of radionuclides to the accessible environment (Aines, 1986; Oversby, 1986). Our initial modeling efforts at LLNL have, therefore, focused on

developing kinetic models for waste form dissolution and on determining the controls of radionuclide concentrations in solution.

It is significant that the federal regulations require the prediction of system performance over time periods of thousands to 100,000 years. Because laboratory experiments are limited in their ability to provide us with meaningful extrapolations of data over such long time periods, the experiments must be supplemented and extended by process-oriented geochemical models.

Applications of Geochemical Modeling at LLNL

The following examples illustrate various facets of EQ3/6 applications relevant to nuclear waste disposal issues and other areas of research in fluid-rock interactions. Note how different aspects of a problem are examined. Although the entire repository system may not be amenable to simulation, geochemical modeling can often be usefully applied to a given subsystem to elucidate underlying reaction controls and to develop process-oriented models. For example, process-oriented models are being developed to describe the kinetics of glass dissolution by integrating experimental programs with geochemical simulations. Although the kinetics of spent fuel dissolution are not yet known, the potential compositions of solutions contacting the spent fuel waste form are still important. Currently, simulations of spent fuel dissolution are made by tracking the extent of reaction in terms of the amount of waste form dissolution per mass of water, rather than tracking the reaction explicitly in time.

Modeling the changing composition of solid solutions and their stability is required to tackle issues such as the magnitude of clinoptilolite-smectite-radionuclide exchange at the waste site. Diagenesis in sedimentary basins can be considered a natural analogue of the "accelerated" diagenesis that is expected to occur in the host rock around the waste packages. The thermodynamic data underlying the models are continuously updated (e.g., including data for organic species) to allow more realistic simulations of geologic processes to be made.

Kinetics of Glass Dissolution

Experimental investigations of borosilicate glass dissolution indicate that the mechanism for glass dissolution at near-neutral pH involves the formation of two surface layers that reach constant thicknesses at steady state (Fig. 1; Abrajano et al., 1988). The inner, diffusion layer is a partially hydrated surface layer through which ions diffuse to an outer gel layer. The gel layer releases soluble elements into solution and concentrates relatively insoluble elements. The insoluble elements later age and crystallize into secondary phases. Secondary phases also precipitate directly on the glass surface when the addition of glass components to the fluid phase causes supersaturation (Bourcier et al., 1989). Release of elements into solution is nonstoichiometric (i.e., element concentrations in solution tend to change at different rates).

Recent experiments by Bourcier et al. (1989) document the changing composition of the fluid phase and the gel layer that accompany nuclear waste borosilicate-glass dissolution at temperatures from 100 to 250°C. The goal of the geochemical modeling aspect of their study was to

develop a process-oriented kinetic model of glass dissolution that is consistent with the experimental data and the progressive alteration of the glass surface. They conceptualized the gel layer as a reactant that releases components into solution at a rate given by

$$\frac{dc_i}{dt} = \frac{A}{V} v_i k_i (1 - e^{-A \cdot RT}), \quad (1)$$

where c_i and v_i represent the concentration of element i in solution and the stoichiometric factor of element i in the solid, respectively, and t refers to time. A/V is the ratio of the surface area of the solid to the volume of the solution, k_i represents the rate constant for solid dissolution, and A denotes the dissolution affinity of the solid (Lasaga, 1984).

The necessary rate constant for glass dissolution was derived by

fitting simulation results to analytical compositional trends in the fluid with time. Experiments are now being carried out to obtain rate constants independently as a function of pH and temperature. When the pH dependency of the rate constant is determined, there should be no need to use the rate constant as a fitting parameter in the model. The free energy of the gel layer was calculated by assuming an ideal solid solution among amorphous oxides and hydroxides that are proxies for the compositional components of the gel layer.

Bourcier et al. (1989) carried out geochemical simulations of glass dissolution with EQ6: alternately allowing no secondary precipitates to form and then allowing a secondary nontronitic clay to precipitate. Nontronite was the most abundant secondary phase observed in

the experiments. A comparison of the two sets of simulation results with the experimental results for pH and boron concentrations are shown in Fig. 2a and b. If secondary phases are not allowed to precipitate, the curves for the concentrations of B and for pH level off at values consistent with saturation with respect to the amorphous surface layer (curves labeled "no precipitate" in Fig. 2). The formation of a crystalline secondary phase forces the solution to remain undersaturated with respect to the amorphous surface layer, and dissolution continues at a nearly linear rate (curves labeled "precipitate" in Fig. 2).

Comparison of the simulation results with the experimental data (Fig. 2) suggests that the dissolution affinity term in Eq. (1) may control the release rate of elements from waste glass. The characteristic parabolic shape of the release rate curves may, therefore, result from surface reaction control of dissolution, rather than diffusion control (Doremus, 1975).

If dissolution affinity controls rates of glass dissolution, these rates would be expected to increase over time as secondary precipitates form and cause the elemental concentrations in solution to decrease. As a result, the dissolution affinity of the glass may actually increase and cause the rate of glass dissolution to increase [Eq. (1)]. This effect is illustrated in Fig. 2a by the existence of greater concentrations of B in solution at a given time when precipitates are allowed to form. Further work is required to better determine the thermodynamic properties of the gel layer and potential secondary precipitates. Independent evaluations of the rate constant as a function of temperature and pH are also necessary to confirm the proposed model of glass dissolution (Bourcier et al., 1989).

Figure 1. Schematic diagram showing surface layers that develop on glass during dissolution and the concentration profiles of calcium, sodium, and hydrogen in these layers (from Bourcier et al., 1989). Surface precipitates are also shown. Adapted from Abrajano et al. (1988).

Figure 2. (a) pH and (b) boron concentration as a function of time (days) from closed-system SRL-165 glass-dissolution experiments (triangles). The curves represent the results of EQ6 simulations of the glass dissolution process. The "no precipitate" curve represents EQ6 predictions when no solid precipitates were allowed to form. The "precipitate" curve was generated with EQ6 when it was assumed that a nontronitic clay phase precipitates, as observed in the experiments.

Dissolution of Spent Fuel Waste Form in Groundwater

Wilson (1987a, 1987b) has carried out a sequence of laboratory tests involving dissolution of spent fuel waste form in J-13 groundwater at 25 and 85°C. J-13 well water is considered to be representative of Yucca Mountain vadose water (Harrar et al., 1988). Wilson immersed spent

fuel, with attendant assembly hardware and cladding, in J-13 water for periods of up to ~2 years. In general, the concentrations of actinides in Wilson's tests tended to increase rapidly and then dropped to steady state values. The concentrations of fission product elements (e.g., Tc, Cs, I, and Sr) increased continuously (Wilson and Bruton, 1989). Geochemical modeling of spent fuel waste form

dissolution in J-13 water with EQ3/6 was carried out to determine the controls of observed nuclide concentrations in solution.

In the initial simulations of spent fuel dissolution, we assumed that the waste undergoes stoichiometric dissolution, without consideration of enhanced grain boundary dissolution. Because no kinetic model for spent fuel dissolution was available,

we tracked the extent of reaction, a proxy for time, in terms of the mass of spent fuel waste form that dissolved in 1 kg of J-13 water. Experimental results can be compared to simulation predictions by determining the masses of the spent fuel waste form that dissolve in a given volume of water during the course of the experiment. Simulation predictions can be directly related to time when kinetic models for spent fuel dissolution become available.

Simulation of spent fuel waste form dissolution at 25°C predicts the formation of a sequence of secondary precipitates (Fig. 3) as nuclides are released into solution. Figure 4 shows the correlation between predicted uranium concentrations in solution and solid precipitates containing uranium. The measured

steady state concentrations of U in solution in Wilson's HBR-3-25 test at 25°C are shown for comparison. The test results are shown as a bar positioned relative to the y axis only; the amount of spent fuel dissolution during the tests is unknown (Bruton and Shaw, 1987).

Precipitates of:
uranophane

$(\text{Ca}(\text{UO}_2)_2(\text{SiO}_3\text{OH})_2 \cdot 5\text{H}_2\text{O})$,
soddyite

$((\text{UO}_2)_2\text{SiO}_4 \cdot 2\text{H}_2\text{O})$,

and possibly haiweeite,

$(\text{Ca}(\text{UO}_2)_2\text{Si}_6\text{O}_{13} \cdot 5\text{H}_2\text{O})$

were identified in Wilson's tests at 85°C, but no precipitates were found at 25°C. In the simulations, haiweeite was considered as a proxy for uranophane because they are similar in composition and because no reliable thermodynamic data for

uranophane are available. The steady state concentrations of U in Wilson's test are consistent with the precipitation of soddyite at 25°C.

Simulation results suggest that U concentrations in solution are dependent on the identity of the U precipitate and the extent of reaction. Uranium concentrations might thus be expected to vary with time even in a closed system. The transition from U-silicates such as haiweeite and soddyite to schoepite, a hydrous uranium oxide, is caused by the depletion of silicon in solution owing to the continued precipitation of silicates and the absence of Si in spent fuel. The relative rates of the Si supply from groundwater and the Si loss from precipitation of silicates greatly affect the release of U from fuel dissolution and the concentration of U in solution. If water containing U eventually escapes the engineered barrier system at Yucca Mountain, it will invade the surrounding silica-rich tuffaceous rocks. It might be anticipated that the abundant supply of Si from the host rock would maintain U concentrations at relatively low values owing to the precipitation of relatively insoluble uranium silicates.

The neptunium concentrations in solution during the simulations increased steadily until the NpO_2 precipitated (Fig. 5). The Np concentrations in equilibrium with NpO_2 proved to be highly dependent on the fugacity of $\text{O}_2(\text{g})$, as shown by Lemire (1984). Simulations made assuming an atmospheric $\text{O}_2(\text{g})$ fugacity over-estimated Np concentrations in solution relative to measured values (Fig. 5). A simulation made assuming a $\text{O}_2(\text{g})$ fugacity of 10^{-12} bars more closely matched test results. The redox state of the test was neither known nor controlled; computed Np concentrations will depend on the expected redox state in the waste package.

Figure 3. Predicted paragenetic sequence of secondary solid phases formed during the dissolution of spent fuel in J-13 water at 25°C and atmospheric $\text{O}_2(\text{g})$ and $\text{CO}_2(\text{g})$ fugacities.

Figure 4. (a) Predicted sequence of uranium precipitates and (b) concentration of uranium in solution as a function of the amount of spent fuel dissolution per kilogram of J-13 water at 25°C (see Fig. 3). Steady state concentration of uranium in Wilson's test HBR-3-25 (Wilson and Bruton, 1989) is shown for reference.

The identities of the nuclide precipitates and the solution composition have significant impacts on nuclide concentrations in solution. Figure 6 shows the results of four simulations. At a given oxygen fugacity, one simulation allowed crystalline PuO_2 to precipitate and sequester plutonium, whereas the other simulation allowed precipitation of amorphous $\text{Pu}(\text{OH})_4$. The Pu concentrations in solution in equilibrium with $\text{Pu}(\text{OH})_4$ are about 8 orders of magnitude greater than concentrations controlled by PuO_2 . The measured steady-state Pu

concentration falls between the values for PuO_2 and $\text{Pu}(\text{OH})_4$. The experiments of Rai and Ryan (1982) show that initial Pu precipitates tend to be amorphous, but they age to increasingly crystalline forms.

Comparisons of simulation results with test results are being used to better understand the controls of nuclide concentrations in solution. For example, the above simulations emphasize the need to characterize parameters such as the redox state of the system through time. Comparisons also help to identify precipitates that may

control nuclide concentrations under various chemical conditions, even though the precipitates may occur in such small masses that they escape analytical detection.

Solid Solution Models for Clinoptilolite and Smectites

Clinoptilolite is a common alteration mineral in the silicic volcanic rocks at Yucca Mountain. Because of its tendency to equilibrate with coexisting fluids through cation exchange, clinoptilolite may play an important role in sequestering radionuclides that may escape from degrading nuclear waste forms. Regional variations in fluid chemistry should, therefore, be reflected in the cation occupancy of clinoptilolite exchange sites if clinoptilolite exchanges rapidly. We used published experimental data that describes cation exchange reactions to derive a solid solution model for clinoptilolite. This model will be used to test for equilibrium between Yucca Mountain waters and co-existing clinoptilolite. Solid solution models for dioctahedral and trioctahedral smectites were also tested and refined using experimental and field data in a similar manner. Exchange data for radionuclides will ultimately be added to these models in order to evaluate the ability of zeolites and clays to sequester radionuclides.

Viani et al. (1989) derived thermodynamic data for component end-members of a clinoptilolite solid solution by using the calorimetric data for a single clinoptilolite (Johnson et al., 1989) as a starting point. Free energies of cation exchange, estimation algorithms, and an ideal site-mixing model modified to account for coupled substitutions of multivalent cations and vacancies were combined to derive the end-member data. The modified ideal site-mixing model and end-member data were

Figure 5. (a) Predicted Np precipitate and (b) predicted concentrations of neptunium in solution as a function of the amount of spent fuel dissolution per kilogram of J-13 water at 25°C. Results are superimposed for two different simulations: assuming that NpO_2 controls Np concentrations at $\text{O}_2(\text{g})$ fugacities of $10^{-0.7}$ (atmospheric) and 10^{-12} bars. NpO_2 precipitates at different stages in reaction progress depending on the $\text{O}_2(\text{g})$ fugacity. Steady state concentration of neptunium in Wilson's test HBR-3-25 (Wilson and Bruton, 1989) is shown for reference.

then incorporated in the EQ3/6 computer modeling code. A simple molecular mixing model for clinoptilolite was also incorporated into EQ3/6 for comparison.

The solid solution model for clinoptilolite was tested and refined by comparing cation occupancies predicted to be in equilibrium with Yucca Mountain waters with analytically determined clinoptilolite compositions from adjacent areas. The simple molecular mixing model did not adequately describe the full range of analytically determined

clinoptilolite compositions because it was constrained to end-members containing one mole of exchangeable cation per formula unit. The modified ideal site-mixing model, in contrast, takes explicit account of the stoichiometric number of cations in the exchange site.

Figure 7 illustrates the match between predictions of Na-Ca exchange in clinoptilolite using the modified ideal site-mixing model and binary exchange data determined experimentally by Ames (1964). Individual simulations were

made assuming the existence of one site and two sites. A comparison between predicted clinoptilolite cation occupancy and analytically determined fluid compositions at Yucca Mountain is shown in Fig. 8. Results for Na-Ca and K-Ca exchange suggest that a two-site model better reproduces experimental exchange data and observed compositional trends in natural clinoptilolites. In future work, we plan to better constrain the proportioning of sites and to regress experimental data to obtain better estimates of the energies at the two sites.

Smectite compositions in EQ3/6 from Wolery (1978) are insufficient to describe the full compositional variation of Yucca Mountain smectites. Use of an ideal site-mixing model (Aagaard and Helgeson, 1983) to describe compositional variations in dioctahedral smectites revealed that the mole fractions of exchangeable cations were dependent on the degree of substitution in the octahedral and tetrahedral sites in a manner that was contrary to published experimental data. The modified ideal site-mixing model of Viani et al. (1989), which is incorporated in EQ3/6, has the effect of decoupling equilibrium on the exchange site from that on the structural sites. Viani et al. derived end-member stabilities for dioctahedral smectites by combining published smectite solubility data, cation exchange data, and the modified ideal site-mixing model to regress best estimates for thermodynamic data of the component end-members.

Work is continuing to further refine the solid solution models for clinoptilolite and smectite. The effects of Al/Si exchange in clinoptilolite, among other phenomena, may need to be explicitly taken into account in our models.

Improvements in the solid solution modeling capabilities of

Figure 6. (a) Predicted plutonium precipitate and (b) predicted concentrations of Pu in solution as a function of the amount of spent fuel dissolution per kilogram of J-13 water at 25°C. Results are superimposed for four different simulations; assuming that $\text{PuO}_2(\text{c})$ and $\text{Pu}(\text{OH})_4$ alternately, control Pu concentration at $\text{O}_2(\text{g})$ fugacities of $10^{-0.7}$ (atmospheric) and 10^{-12} bars. $\text{PuO}_2(\text{c})$ precipitates immediately in both simulations; $\text{Pu}(\text{OH})_4$ precipitates at different stages in reaction progress depending on the $\text{O}_2(\text{g})$ fugacity. Steady state concentration of plutonium in Wilson's test HBR-3-25 (Wilson and Bruton, 1989) is shown for reference.

EQ3/6, such as those described above, allow more accurate thermodynamic characterization of solid solution phases (e.g., clays, micas, feldspars, and zeolites). We can also model cation exchange with EQ3/6 when the exchanger is not in overall equilibrium with the solution. Exchange reactions between an exchanger of fixed mass and a fluid can be specified using either

the Vanselow or Gapon conventions (Sposito, 1981) in an isothermal system. This option is required to model the cation exchange properties of clay-rich backfill materials and to calculate the extent of the sequestering of cations during fluid flow through host rocks composed of minerals with relatively constant cation exchange capacities.

Diagenesis in Sedimentary Basins

Diagenetic reactions can significantly change rock porosity and permeability, which are major factors controlling the quality of petroleum reservoirs. If we can understand the forces that interact to produce observed diagenetic changes in petroleum reservoirs, we will be better prepared to predict reservoir quality as a function of geologic setting and burial history. Diagenesis in natural systems can also be considered a natural analogue for the fluid-rock interactions that will occur when temperatures increase in the host rock surrounding an emplaced waste package. The man-made "accelerated" diagenetic reactions may be similar to reactions observed in natural systems.

Diagenetic reactions recorded in rocks result from complex fluid-rock interactions during burial. Observations of reactions preserved in rocks, however, form incomplete records of a rock's diagenetic evolution. Computer models of fluid-rock interactions allow the effects of competing reactions and processes to be quantitatively evaluated in the context of the continuous diagenetic evolution of the sediment and pore fluids.

Fluid-rock interactions during burial diagenesis can be simulated by reacting typical mineralogical components of sedimentary rocks with basinal fluids (Bruton, 1989). In the following example, a quartzose sandstone is reacted with river water from 10°C at the Earth's surface to 200°C to simulate burial diagenesis in a closed system. Given a linear geothermal gradient of 30°C/km, a temperature of 200°C would be attained roughly at a depth of 6 km. Solid solutions are treated according to the modified ideal site-mixing model described above.

The representative orthoquartzite sedimentary rock used in the simulation is dominated by quartz,

Figure 7. Comparison of binary exchange data from Ames (1964) for Na-Ca exchange in clinoptilolite under ambient conditions with adsorption isotherms predicted using one- and two-site modified ideal site-mixing models.

Figure 8. Comparison of compositions of coexisting clinoptilolites and formation waters at Yucca Mountain with adsorption isotherms predicted using one- and two-site modified ideal site-mixing models. Formation water chemistry at Yucca Mountain was obtained from Benson et al. (1983), Benson and McKinley (1985), and Ogard and Kerrisk (1984). Clinoptilolite compositions were determined through microprobe analysis by Broxton et al. (1986) and Levy (1984). Produced formation waters were matched as closely as possible with clinoptilolites from associated stratigraphic horizons.

with minor amounts of microcline, albite, anorthite, calcite, and magnetite (which represents an Fe-rich phase) and 14Å-clinocllore (which represents a Mg-chlorite). Equal amounts of albite and anorthite are proxies for the end member components of an ideal plagioclase solid solution with the composition An_{50} . The presence of calcite suggests that the quartzose sandstone has been subjected to surface weathering. The quartzose sandstone was reacted with a typical river water (Bruton, 1989).

A generalized synthetic diagenetic sequence illustrating typical diagenetic events predicted to occur during burial of quartzose sandstone and river water is shown in Fig. 9a. A chronological sequence of diagenetic events in sandstones deposited in non-marine

environments deduced through petrographic studies by McBride (1983) is shown in Fig. 9b for comparison. The early precipitation of clays such as kaolinite and dioctahedral smectites are both predicted and observed during early diagenesis. Precipitation of Mg-rich saponitic clays, calcite solid solution, and the two zeolites, mesolite and scolecite, dominate the middle portion of the predicted sequence of events. As temperatures increase, a garnet solid solution, tremolite, and prehnite precipitate, representing the transition to low-grade metamorphism. The closed-system simulation did not reproduce the dissolution/hydrocarbon migration events observed in some sandstones that are open to fluid flow. With further simulations, we can customize the computer simulations

to provide for known fluid flow regimes or other particular characteristics of an area under study (Harrison, 1989).

The change of pH during reaction is superimposed on Fig. 9a for comparison to the changes in mineralogy. By the end of the simulation, the temperature increases to 200°C and the pH drops to 6.7. The neutral pH at 200°C is 5.64. The initial rise in pH results from the early dissolution of the nonfeldspathic minor minerals in the quartzose sandstone. The pH steadily decreases when minerals that are increasingly poor in Al precipitate, starting with trioctahedral smectite. The pH is controlled by the relative quantities and stoichiometries of minerals that precipitate and dissolve at each point in time. The controls on the pH trends can be

Figure 9. (a) Generalized synthetic diagenetic sequence for reaction between quartzose sandstone and river water from 10 to 200°C, calculated using the EQ3/6 computer code package. The pH value, during reaction are overlaid on the diagenetic sequence. (b) Chronological sequence of diagenetic events in sandstones, deposited in non-marine environments and deduced through petrographic study (after McBride, 1983).

deduced by writing the hydrolysis reactions for the minerals of interest in terms of the dominant aqueous species in solution [i.e., $\text{Al}(\text{OH})_4^-$, rather than Al^{+++}]. The impact on pH during a mineral precipitation/dissolution event is related to the ratio of the sum of the cation equivalents in the mineral formula, exclusive of Al and Si, to the number of Al ions in the mineral formula. The pH effects in dilute solutions are greatest when the minerals contain no Al.

Simulation results indicate the need to rigorously evaluate newly acquired calorimetric data for zeolites such as mesolite and scolecite (Johnson et al., 1983), relative to the stability of phases such as laumontite. Laumontite is commonly observed in nature but is never predicted to form. Observed versus predicted stabilities of zeolites relative to clays and other phases must also be evaluated further. The performance of new solid solution models for smectites, saponites, calcite, garnet, and other minerals in EQ3/6 must be evaluated by comparing predictions with observed mineral occurrences and associations, both in terms of overall phase stability and composition.

Significant discrepancies between predicted and observed zeolite stabilities are introduced when the thermodynamic properties of zeolites, obtained using silicate calorimetry, are referenced to silicalite (Johnson et al., 1987) rather than to α -quartz. Figure 10 illustrates the predicted diagenetic sequence when thermodynamic data for clinoptilolite is referenced to silicalite rather than to α -quartz (Fig. 9a). Clinoptilolite is stable from 25 to 200°C, and its formation precludes the precipitation of kaolinite, muscovite, and other zeolites. A series of simulations with different rock types and the silicalite-referenced clinoptilolite data would suggest

that clinoptilolite precipitation is favored in almost all environments at temperatures as high as 300°C, which is not consistent with observation. Care must be taken to ensure internal consistency between calorimetric data and data derived from phase equilibrium studies.

The synthetic diagenetic sequences constructed in the above manner are designed as a general guide to the controls of diagenetic reactions that generate commonly observed patterns in diagenetic sequences (McBride, 1983; Hurst and Irwin, 1982). We hope to be able to use synthetic diagenetic sequences to predict the effects of changes in rock composition, fluid chemistry, and burial history on the diagenetic evolution of sediments and their reservoir quality. Geochemical simulations of this type may be used to evaluate the relative impact

of geologic events on diagenesis. Simulations often reveal potential controls of reactions that may not have been previously anticipated, yet must be considered (Bruton, 1989).

Interactions between Organic and Inorganic Systems

Even though organic compounds, inorganic minerals, and aqueous solutions coexist in many geologic environments, the chemical interactions between them are infrequently studied. The study of such interactions is made difficult by the lack of thermodynamic data for many aqueous organic species and because a wide variety of aqueous species are preserved in metastable equilibrium in natural systems (Shock, 1988). Among other potential interactions between the

Figure 10. Generalized synthetic diagenetic sequence for reaction between quartzose sandstone and river water from 10 to 200°C, calculated using the EQ3/6 computer code package and using calorimetric data for clinoptilolite referenced to silicalite.

inorganic and aqueous organic fractions of geochemical systems, researchers believe that aqueous organic compounds enhance mineral solubilities and rates of dissolution (Hem and Lind, 1974; Surdam et al., 1984; Stumm et al., 1985; Crossey et al., 1986) participate in the redox and complexation reactions that govern transport and deposition of some metals (Radtke and Scheiner, 1970; Giordano, 1985; Sverjensky, 1986; Drummond and Palmer, 1986; Johnson et al., 1987), and alter the ion exchange capacity of clay minerals through sorption (Rausell-Colom and Serratos, 1987). Geochemical modeling calculations can provide insight into the nature of chemical interactions affecting these processes (Rose and Jackson, 1989), but it is prerequisite that the data base used in conjunction with the modeling codes adequately describes both the inorganic compounds and the aqueous organic components comprising the system.

Shock and Helgeson (1989) used equations of state and correlation algorithms developed for inorganic

aqueous species to generate a thermodynamic data base for a wide variety of aqueous organic species. Their data are being incorporated into the thermodynamic data base for the EQ3/6 geochemical modeling codes. We are specifically taking into account the metastable persistence of suites of organic compounds that are out of redox equilibrium with other carbon-containing species. The user specifies explicit reactions between each aqueous organic species and "basis species" to which the thermodynamic properties of each organic species are referenced. The abundance of each organic species is then computed from its designated basis species, independent of other organic suites in the system, to represent metastability. Using EQ3/6 with the organic/inorganic data base, we will be able to calculate various stable and metastable equilibria that can be used to assess quantitatively the chemical interactions that may take place between aqueous organic and inorganic components in natural systems.

We added a representative suite of 18 aqueous organic species from the Shock and Helgeson (1989) data base to the EQ3/6 data base to represent a small subset of aqueous organic species in natural waters (Rose and Jackson, 1989). Figure 11 shows the computed distribution of the most abundant aqueous organic species as a function of pH when all organic species, except for CO_2 and CH_4 , are assumed to be in equilibrium with acetic acid in a dilute groundwater containing ~ 0.001 molal concentration of organic material at 25°C (see Fig. 11 caption). The assumption of equilibrium with acetic acid may not be appropriate in the study of natural systems. These calculations can, however, be used as an equilibrium "baseline" with which to compare natural distributions of organic species with future calculations of metastable equilibria. We include Fig. 11 as a reminder that organic speciation, as well as inorganic speciation, varies with pH and other solution characteristics. The impact of changes in both the organic and inorganic

Figure 11. Calculated abundances of predominant aqueous organic components present in metastable equilibrium with acetic acid. It is assumed that the organic species are out of equilibrium with respect to the more thermodynamically stable forms of carbon in solution, such as CO_2 and CH_4 . The overall composition of the solution is held constant at each pH, and the oxygen fugacity is set at an atmospheric value. Activity coefficients for the neutral aqueous species are assumed to equal one. Activity coefficients of charged species are computed using the B-dot extended Debye-Huckel equations (Helgeson, 1969).

subsystems, and their interactions, on fluid-fluid and fluid-rock interactions must be considered in order to understand natural processes.

Conclusions

Geochemical modeling will play an important role in predicting the long-term performance of proposed nuclear waste repositories.

Geochemical modeling applications also serve as an integrator between experimentation and theory, and they are a driving force behind code and data base developments. Geochemical models such as EQ3/6 are sufficiently general that a wide variety of natural processes and man-made phenomena, such as waste disposal and toxic waste issues, can be studied. Common

ground exists in many of these seemingly independent studies, and what is learned in one area can invariably be applied with good effect to research in other areas. We are carrying out a variety of studies at LLNL. Advances in each application and in code and data base development will enable us to gain confidence in the validity of our models and predictions.

References

- Aagaard, P., and H. C. Helgeson (1983), "Activity/Composition Relations among Silicates and Aqueous Solutions: II. Chemical and Thermodynamic Consequences of Ideal Mixing of Atoms on Homologous Sites in Montmorillonites, Illites, and Mixed-Layer Clays," *Clays and Clay Miner.* **31**, 207-217.
- Abrajano, T. A., J. K. Bates, T. J. Gerding, and W. L. Ebert (1988), *The Reaction of Glass during Gamma Irradiation in a Saturated Tuff Environment. Part 3: Long-Term Experiments at 1×10^4 rad/hour*, Argonne National Laboratory, Argonne, IL, ANL-88-14.
- Aines, R. D. (1986), *Estimates of Radionuclide Release from Glass Waste Forms in a Tuff Repository and the Effects on Regulatory Compliance*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-93735.
- Ames, Jr., L. L. (1964), "Some Zeolite Equilibria with Alkali Metal Cations," *Am. Miner.* **49**, 127-145.
- Benson, L. V., and P. W. McKinley (1985), *Chemical Composition of Ground Water in the Yucca Mountain Area, Nevada, 1971-84*, U.S. Geological Survey Open-File Report 85-484.
- Benson, L. V., J. H. Robison, R. K. Blankennagel, and A. E. Ogard (1983), *Chemical Composition of Ground Water and the Locations of Permeable Zones in the Yucca Mountain Area, Nevada*, U.S. Geological Survey Open-File Report 83-854.
- Bourcier, W. L. (1985), *Improvements in the Solid Solution Modeling Capabilities of the EQ3/6 Geochemical Code*, Lawrence Livermore National Laboratory, Livermore, CA, UCID-20387.
- Bourcier, W. L., K. G. Knauss, and C. I. Merzbacher (1989), "A Kinetic Model for the Dissolution of Borosilicate Glass," *Proc. Sixth International Symposium on Water-Rock Interaction*, August 3-12, 1989, Malvern, England.
- Broxton, D. E., R. G. Warren, R. C. Hagan, and G. Luedemann (1986), *Chemistry of Diagenetically-Altered Tuffs at a Potential Nuclear Waste Repository, Yucca Mountain, Nye County, Nevada*, Los Alamos National Laboratory, Los Alamos, NM, LA-10802.
- Bruton, C. J. (1989), "Predicting Mineral Dissolution and Precipitation during Burial: Synthetic Diagenetic Sequences," *Proc. Workshop on Geochemical Modeling*, Sept. 14-17, 1986, Fallen Leaf Lake, CA, K. J. Jackson and W. L. Bourcier, Eds., Lawrence Livermore National Laboratory, Livermore, CA, CONF-8609134.
- Bruton, C. J., and H. F. Shaw (1987), *Geochemical Simulation of Reaction between Spent Fuel Waste Form and J-13 Water at 25°C and 90°C*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-96702.
- Crossey, L. J., R. C. Surdam, and R. Lahann (1986), "Application of Organic/Inorganic Diagenesis to Porosity Prediction," *Roles of Organic Matter in Sediment Diagenesis*, D. L. Gautier, Ed. (Soc. Economic Paleontologists and Mineralogists, Tulsa, OK), SEPM Special Publication No. 38, pp. 147-155.
- Delany, J. M., and S. R. Lundeen (1989), *The LLNL Thermochemical Data Base: Revised Data and File Format for the EQ3/6 Package*, Lawrence Livermore National Laboratory, Livermore, CA, UCID-21658 (in prep).
- Doremus, R. H. (1975), "Interdiffusion of Hydrogen and Alkali Ions in a Glass Surface," *J. Noncryst. Solids* **19**, 137-144.
- Drummond, S. E., and D. A. Palmer (1986), "Thermal Decarboxylation of Acetate. Part II. Boundary Conditions for the Role of Acetate in the Primary Migration of Natural Gas and the Transportation of Metals in Hydrothermal Systems," *Geochim. Cosmochim. Acta* **50**, 825-833.
- Environmental Protection Agency (1985), "Environmental Standards for the Management and Disposal of Spent Nuclear Fuel, High-Level and Transuranic Wastes: Final Rule," Title 40, Part 191, *Code of Federal Regulations*, Federal Register Vol. 50, No. 182 (Sept. 19) (U.S. Government Printing Office, Washington, DC).
- Giordano, T. H. (1985), "A Preliminary Evaluation of Organic Ligands and Metal-Organic Complexing in Mississippi Valley-Type Ore Solutions," *Econ. Geol.* **80**, 96-106.

- Glassley, W. E. (1986), *Reference Waste Package Environment Report*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-53726.
- Harrar, J. E., J. F. Carley, W. F. Isherwood, and E. Raber (1988), *Report of the Committee to Review the Use of I-13 Well Water in Nevada Nuclear Waste Storage Investigations*, Lawrence Livermore National Laboratory, Livermore, CA (Sept.).
- Harrison, W. J. (1989), "Modeling Fluid/Rock Interactions in Sedimentary Basins," *Quantitative Dynamic Stratigraphy*, T. A. Cross, Ed. (Elsevier, New York, NY, in press).
- Helgeson, H. C. (1969), "Thermodynamics of Hydrothermal Systems at Elevated Temperatures and Pressures," *Am. J. Sci.* **267**, 729-804.
- Hem, J. D., and C. J. Lind (1974), "Mineral Synthesis at 25°C," *Science* **184**, 1171-1173.
- Hurst, A., and H. Irwin (1982), "Geological Modelling of Clay Diagenesis in Sandstones," *Clay Minerals* **17**, 5-22.
- Jackson, K. J., and W. L. Bourcier, Eds. (1989), *Proc. Workshop on Geochemical Modeling*, Sept. 14-17, 1986, Fallen Leaf Lake, CA. Lawrence Livermore National Laboratory, Livermore, CA. CONF-8609134.
- Johnson, G. K., H. E. Flotow, and P. A. G. O'Hare (1983), "Thermodynamic Studies of Zeolites: Natrolite, Mesolite and Scolecite," *Am. Miner.* **68**, 1134-1145.
- Johnson, G. K., I. R. Tasker, and D. A. Howell (1987), "Thermodynamic Properties of Silicalite SiO_2 ," *J. Chem. Therm.* **19**, 617-632.
- Johnson, G. K., I. R. Tasker, R. Jurgens, and P. A. G. O'Hare (1989), "Thermodynamic Studies of Zeolites: Clinoptilolite," to be submitted to *J. Chem. Therm.*
- Johnson, S. Y., K. Otton, and D. L. Macke (1987), "Geology of the Holocene Surficial Uranium Deposit of the North Fork of Flodelle Creek, Northeast Washington," *Geol. Soc. Am. Bull.* **98**, 77-85.
- Knapp, R. B. (1989), "Spatial and Temporal Scales of Local Equilibrium in Dynamic Fluid-Rock Systems," *Geochim. Cosmochim. Acta* **53**, 1955-1964.
- Lasaga, A. C. (1984), "Chemical Kinetics of Water-Rock Interactions," *J. Geophys. Res.* **89**, 4009-4025.
- Lemire, R. J. (1984), *An Assessment of the Thermodynamic Behavior of Neptunium in Water and Model Groundwater from 25°C to 150°C*, Atomic Energy of Canada Limited, Whiteshell Nucl. Res. Estbl., AECL-7817.
- Levy, S. S. (1984), *Petrology of Samples from Drill Holes USWH-3, H-4, and H-5, Yucca Mountain, Nevada*, Los Alamos National Laboratory, Los Alamos, NM, LA-9706.
- McBride, F. F. (1983), *Sandstone Diagenesis: Principles Useful in Exploration*, New Orleans Geological Society Short Course (Nov. 17).
- Ogard, A. E., and J. F. Kerrick (1984), *Groundwater Chemistry along Flow Paths between a Proposed Repository Site and the Accessible Environment*, Los Alamos National Laboratory, Los Alamos, NM, LA-10188.
- O'Neal, W. C., D. W. Greg, J. N. Hockman, E. W. Russell, and W. Stein (1984), *Preclosure Analysis of Conceptual Waste Package Designs for a Nuclear Waste Repository in Tuff*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-53595.
- Oversby, V. M. (1986), *Important Radionuclides in High Level Nuclear Waste Disposal: Determination Using a Comparison of the EPA and NRC Regulations*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-94222.
- Radtke, A. S., and B. J. Scheiner (1970), "Studies of Hydrothermal Gold Deposition (I). Carlin Gold Deposits, Nevada," *Econ. Geol.* **65**, 87-102.
- Rai, D., and J. L. Ryan (1982), "Crystallinity and Solubility of Pu(IV) Oxide and Hydrated Oxide in Aged Aqueous Suspensions," *Radiochimica Acta* **30**, 213-216.
- Rausell-Colom, J. A., and J. M. Serratosa (1987), "Reactions of Clays with Organic Substances," *Chemistry of Clays and Clay Minerals*, A. C. D. Newton, Ed. (John Wiley and Sons, New York, NY), pp. 371-422.
- Rose, N. M., and K. J. Jackson (1989), "Computation of Coupled Aqueous Organic-Inorganic Equilibria in Hydrothermal Systems," *Abstracts, 1989 Geol. Soc. Am. Annual Meeting*, St. Louis, MO, p. A-49.
- Shock, E. L. (1988), "Organic Acid Metastability in Sedimentary Basins," *Geology* **16**, 886-890.
- Shock, E. L., and H. C. Helgeson (1989), "Calculation of the Thermodynamic and Transport Properties of Aqueous Species at High Pressures and Temperatures. Standard and Partial Molal Properties of Organic Species," *Geochim. Cosmochim. Acta* **53** (in press).
- Shock, E. L., and H. C. Helgeson (1988), "Calculation of the Thermodynamic and Transport Properties of Aqueous Species at High Pressures and Temperatures. Correlation Algorithms for Ionic Species and Equation of State Predictions to 1 kb and 1000°C," *Geochim. Cosmochim. Acta* **52**, 2009-2036.
- Sposito, G. (1981), *The Thermodynamics of Soil Solutions* (Oxford University Press, New York, NY).

- Stumm, W., G. Furrer, E. Wieland, and B. Zinder (1985), "The Effects of Complex-Forming Ligands on the Dissolution of Oxides and Aluminosilicates," *The Chemistry of Weathering*, J. I. Drever, Ed. (D. Reidel Publishing Co., Dordrecht, Netherlands), pp. 55-74.
- Surdam, R. C., S. W. Boeses, and L. J. Crossley (1984), "The Chemistry of Secondary Porosity," *Clastic Diagenesis*, D. A. McDonald and R. C. Surdam, Eds. (American Assoc. Petroleum Geol., Tulsa, OK), pp. 127-149.
- Sverjensky, D. A. (1986), "Genesis of Mississippi Valley-Type Lead-Zinc Deposits," *Ann. Rev. Earth Plan. Sci.* **14**, 177-199.
- U.S. Department of Energy, OCRWM (1988), *Site Characterization Plan Consultation Draft, Yucca Mountain Site, Nevada Research and Development Area, Nevada*, U.S. Department of Energy, Washington, DC, DOE/RW-0160 (Jan.).
- U.S. Nuclear Regulatory Commission (1983), "Disposal of High-Level Radioactive Wastes in Geologic Repositories," Title 10, Part 60, *Code of Federal Regulations* (U.S. Government Printing Office, Washington, DC).
- Viani, B. E., C. J. Bruton, and W. L. Bourcier (1989), "Comparison of Ideal Mixing Models Used to Describe Smectite Solid Solutions for Geochemical Modeling," *Abstracts, 9th International Clay Conference, Strasbourg, France, August, 1989* (Association Internationale pour L'Étude des Argiles, France).
- Wilson, C. N. (1987a), *Results from Cycles 1 and 2 of NNWSI Series 2 Spent Fuel Dissolution Tests*, Hanford Engineering Development Laboratory, Hanford, WA, HEDL-TME 85-22.
- Wilson, C. N. (1987b), "Summary Results from the Series 2 and Series 3 NNWSI Bare Fuel Dissolution Tests," *Scientific Basis for Nuclear Waste Management XI*, M. J. Apted and R. E. Westerman, Eds. (Materials Research Soc., Pittsburgh, PA), vol. 112, pp. 473-483.
- Wilson, C. N., and C. J. Bruton (1989), *Studies on Spent Fuel Dissolution Behavior under Yucca Mountain Repository Conditions*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-100223.
- Wolery, T. J. (1978), *Some Chemical Aspects of Hydrothermal Processes at Mid-Oceanic Ridges—A Theoretical Study*, Ph.D. dissertation, Northwestern University, Evanston, IL.
- Wolery, T. J. (1979), *Calculation of Chemical Equilibrium between Aqueous Solution and Minerals: The EQ3/6 Software Package*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-52658.
- Wolery, T. J. (1983), *EQ3NR: A Computer Program for Geochemical Aqueous Speciation-Solubility Calculations, User's Guide and Documentation*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-53414.
- Wolery, T. J., D. J. Isherwood, K. J. Jackson, J. M. Delany, and I. Puigdomenech (1984), *EQ3/6: Status and Applications*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-91884.
- Wolery, T. J., K. J. Jackson, W. L. Bourcier, C. J. Bruton, B. E. Viani, K. G. Knauss, and J. M. Delany (1989), "The EQ3/6 Software Package for Geochemical Modeling: Current Status," *Chemical Modeling in Aqueous Systems II*, D. C. Melchior and R. L. Bassett, Eds. (American Chemical Society Symposium Series, in press).
- Wolery, T. J., and S. A. Daveler (1989), *EQ6, A Computer Program for Reaction Path Modeling of Aqueous Geochemical Systems: User's Guide and Documentation*, Lawrence Livermore National Laboratory, Livermore, CA (in prep).

Modeling Petroleum Generation and Expulsion

Jerry J. Sweeney, Robert L. Braun,
and Alan K. Burnham

Petroleum Geochemistry Project

We have developed a new kinetic model of vitrinite reflectance that will help test sediment thermal history models, and we have improved a detailed chemical kinetic model of petroleum generation and degradation so that it can calculate expulsion timing and efficiency. We are using the vitrinite reflectance model and a simple model of petroleum generation without degradation to predict the characteristics of oil generation in the Maracaibo Basin, Venezuela. Once we have gained confidence in our model, we hope to predict the location of undiscovered petroleum deposits.

Traditional petroleum exploration has used geophysical techniques to locate traps where petroleum (oil and gas) may have accumulated. Our general objective is to raise the odds of finding oil by improving modeling techniques that predict whether a given trap is likely to contain oil.

Oil is generated from organic matter (principally phytoplankton) that is deposited in an oxygen-poor environment and subsequently heated to 80–160°C by burial to 3–6 km over tens of millions of years. Once formed, oil may either be expelled from the source rock to accumulate in a trap (reservoir) or may be converted to gas as it undergoes further burial.

Integrated Basin Analysis Technique

Our efforts are specifically directed toward improving the reliability of a technique called *integrated basin analysis*, which is being developed and applied by the oil industry. This technique incorporates many aspects of geology, geophysics, geochemistry, and hydrology in an attempt to

model in a deterministic fashion when and where oil is generated, migrates, and accumulates. The model calculates the thermal history of the basin, combines that thermal history with chemical kinetic expressions to predict when and where oil and gas are generated, and then estimates from various physical parameters when and where the oil moves. Not only must the model predict whether oil and gas were formed, but it must also predict whether expulsion from the source rock occurred at the right time and geometry to fill a trap. A trap may be formed before, after, or during expulsion by crustal folding, faulting, or erosion and redeposition. This modeling must be accurate, or the results will be counterproductive.

Recently, we have made significant advances in two aspects of integrated basin analysis:

- We developed an improved chemical kinetic model of vitrinite maturation and reflectance that will better constrain thermal history models of sedimentary basins.
- We incorporated fluid equations of state, a simple mechanical

model of source rock compaction, and a *pseudo*-one-dimensional calculation of mass transport into our detailed chemical kinetic model of oil and gas generation and destruction. We then made the first rigorous, nonproprietary calculation of oil expulsion from a generating source rock.

A crucial aspect in integrated basin analysis is deriving a thermal history for all sedimentary layers at locations throughout the basin. This involves calculating the steady-state heat flow at all historical times using inferred sedimentary thicknesses. There are many approximations required and many possible sources of error, so it is necessary to have some means to verify the calculated thermal history. The reflectance of light from vitrinite, a major constituent of coal and a minor constituent in many other sediments, is the most common indicator used to constrain geothermal histories. However, there is a long-standing disagreement in the literature (Barker, 1989; Larter, 1978; Lopatin, 1971; Price, 1983; Burnham and Sweeney, 1989) on how vitrinite reflectance depends on time and temperature.

We have developed an improved method for calculating vitrinite reflectance from thermal histories. Our model builds on the well-known historical correlation between vitrinite reflectance and its composition, particularly its hydrogen-to-carbon ratio. As vitrinite becomes more graphitic, its reflectance increases. We derived a simple chemical kinetic model that reproduces changes in vitrinite composition (and hence its reflectance) for both geological and laboratory maturation. The model assumes that maturation proceeds by four independent reactions eliminating water, carbon dioxide, oil, and methane from the vitrinite structure. Each reaction is described by a distribution of activation energies. We then use data from the literature (McCartney and Ergun, 1958; Davis, 1978) to derive improved correlations between composition and reflectance. Combining these two aspects allows us to calculate

reflectance for maturation at time scales ranging from hours to millions of years. Measured and calculated reflectance values at three different time scales are compared in Fig. 1.

Once a thermal history for each sedimentary layer has been calculated and checked, it can be used to calculate the timing of oil generation in various parts of a basin. Our calculations for the Uinta Basin in Utah have been described previously (Sweeney and Burnham, 1987). However, the most crucial question is not when oil is generated, but when it is expelled from the source rock so that it can migrate to a trap. While in the source rock, oil is continually cracked to lower-molecular-weight oil and gas, so the delay between generation and expulsion has a large impact on the oil/gas ratio expected in a given trap.

To model this process, we must understand the chemical kinetics of

oil cracking: how oil and gas volumes depend on temperature and pressure, how the decrease in rock porosity (compaction) depends on overburden (lithostatic) pressure, how expulsion depends on porosity and pore-fluid pressure, and how compaction is inhibited by pore pressure. To calculate the volumes and compositions of the oil and gas phases, we added corrected Redlich-Kwong-Soave equations of state to our chemical kinetic model. We allowed the source rock to be an open, closed, or leaky system. For the leaky system, we adopted the mechanical model shown in Fig. 2. We assumed that the equilibrium porosity decreases exponentially with the difference between the lithostatic pressure and the excess pore pressure (pore pressure in excess of hydrostatic pressure). We also assumed that the rate of expulsion was proportional to the effective hydraulic conductivity estimated from the Kozeny-Carmen

Figure 1. Comparison of measured and calculated vitrinite reflectance values for three drastically different time-temperature regimes: (a) sealed-bomb pyrolysis experiments for samples heated at 1°C/week, (b) temperatures of 200–450°C experienced over 50,000 to 500,000 years as heat dissipates from a volcanic intrusion (assuming 1143°C magma), and (c) normal sedimentary heating to 180°C over 80 million years caused by deposition and subsidence (geothermal gradient of 24°C/km).

Figure 2. Simple mechanical model for source rock compaction and petroleum expulsion.

equation. Finally, we added a pressure relief valve so that the pore pressure could not exceed lithostatic pressure; activation of this valve simulates the process of natural hydrofracturing.

Figure 3 shows a calculation of generation and expulsion for an idealized segment of source rock buried at $3^\circ\text{C}/\text{million yr}$ in a geothermal gradient of $25^\circ\text{C}/\text{km}$. We chose the proportionality constant for leakage so that the excess pore pressures were similar to those observed in the oil window of the Uinta Basin. We see that oil expulsion is delayed from generation by $\sim 10^6$ yr (three million years) during which time about 30% of the oil is cracked to gas. Other parameter studies show that the relative amount of oil cracking prior to expulsion is much larger for a source rock with less organic matter. These

predictions are qualitatively consistent with general observations, but quantitative testing will take further work.

Application to the Maracaibo Basin

Our support from the U.S. Department of Energy, Office of Fossil Energy, involves cooperative work with INTEVEP, the research arm of the Venezuelan National Oil Company. We have been working with INTEVEP scientists to apply our integrated basin analysis methods to predicting the characteristics of oil and gas generation in the extensively explored Maracaibo Basin of Venezuela. We plan to test the method in Venezuela and, once we have gained confidence in it, apply the same techniques to little explored basins, where we hope to be

able to predict the location of undiscovered petroleum deposits.

Geologists at INTEVEP have provided us with estimates of the thermal history for lithologies in 80 wells in the Maracaibo Basin, where the main hydrocarbon-producing unit is the La Luna shale formation. The La Luna shale is a very rich marine source rock overlain by the Colon Formation, an organically lean shale with low permeability. The Colon Formation acts as a seal for migrating hydrocarbons, and the La Luna source rock can thus be its own reservoir (Talukdar et al., 1986). Other reservoirs are contained in the overlying Eocene and Miocene formations and in the Cretaceous limestones below the La Luna. It is this diversity of reservoir types that we hope to use in comparing predicted generation characteristics

Figure 3. Simulation of oil generation and degradation and of oil expulsion for Green River Shale. The shale initially contained 3% total organic carbon (TOC), was heated at 3°C/million yr, and had an effective geothermal gradient of 25°C/km.

with the characteristics of the recovered hydrocarbons and the organic residue left behind in the source rock.

The characteristics of the organic matter in the La Luna source rock are quite uniform throughout the Maracaibo Basin, so we are confident that chemical kinetic parameters describing hydrocarbon generation determined from a few immature samples can be applied throughout the basin. In the initial part of our study, we determined kinetic parameters for oil generation by means of laboratory pyrolysis experiments, but we have not completed the characterization of the kinetic parameters needed to model coking and cracking. We estimate gas generation characteristics in the basin by using kinetic parameters derived from coal pyrolysis (Braun et al., 1988).

The first step in the modeling process is to verify the accuracy of the thermal history estimates; this is done using the vitrinite reflectance modeling described

above. Figure 4 shows the thermal histories of the bottom of the La Luna Formation for two wells located in the Maracaibo Basin. The corresponding vitrinite-depth data set, with calculated values of vitrinite reflectance from our model, is shown in Fig. 5. Because the wells are close together and have similar thermal histories, we combined these two vitrinite data sets in Fig. 5. Values of vitrinite reflectance at depths other than those of the bottom of the La Luna Formation are calculated with thermal histories that follow the same general trend as those in Fig. 4. Originally, INTEVEP geologists used a surface temperature of 53°C in the models to account for a high geothermal gradient at shallow depths, but vitrinite reflectance calculated with those values was too high. With a surface temperature of 33°C, the calculated and measured values of vitrinite are in good agreement as shown in Fig. 5. The sudden increase in vitrinite values at depths of ~3600 m is due to a higher

geothermal gradient that exists below the top of the Colon Formation. The thick, low porosity Colon and La Luna shales have lower thermal conductivities and, thus, greater thermal gradients across them. In the thermal history model, we accounted for this by making the geothermal gradient ~50% higher for formations below the top of the Colon shale once they reached a depth of ~2000 m.

With the thermal histories adjusted according to the above procedure, our next step was to use our simple pyrolysis kinetics model to calculate oil and gas generation in the La Luna Formation. We found that the oil and gas generation characteristics can be grouped into four general categories mainly based on differences in the thermal histories in various parts of the basin. We used four different sets of oil generation kinetic parameters (determined by rapid pyrolysis at several heating rates) to calculate the oil generation throughout the burial history of the

Figure 4. Time-temperature history of the bottom of the La Luna Formation in the Ambrosio and Icotea wells, Maracaibo Basin.

Figure 5. Vitrinite reflectance at depth for the Ambrosio and Icotea wells. (Circles are measured values from well cuttings; line shows calculated values using time and temperature histories for selected depths and our vitrinite reflectance model.

bottom of the La Luna Formation (Fig. 6). Differences between the four sets of kinetic parameters (QL7A, BEICIP, Pyromat, and Pyromat shifted) represent uncertainties in the laboratory-determined values; Pyromat shifted is the preferred value at our present stage of analysis.

Group A consists of wells (Fig. 6a) in which all organic matter was converted to oil between about 55 and 45 Ma (million years before present). Because the La Luna Formation at these locations was heated past the point at which all organic matter was converted to oil, all of the oil at these locations has probably been converted to gas.

Group B consists of wells at which temperatures in the La Luna were high enough starting at about 45 Ma to begin oil generation, but burial had ceased by 35 Ma, which arrested continued oil generation (Fig. 6b). Later burial beginning about 15 Ma restarted the oil generation, which continues to the present day. The La Luna Formation at these well locations is generally overpressured (i.e., fluid pressures are greater than hydrostatic pressures) because of ongoing oil and gas generation.

Group C wells are those at which burial sufficient to cause oil generation began later, typically about 10 Ma (Fig. 6c). However, burial heating was very rapid, and oil generation from the La Luna was completed in most of these wells, and they are now primarily gas producers.

As with Group C, the La Luna Formation in the Group D wells (Fig. 6d) also began to generate oil only within the past 10–15 Ma, but in this group burial rates were not as dramatic; consequently, oil generation is still active today, and gas generation is just beginning.

The relative timing of oil and gas generation throughout the basin is best examined with contour maps (see Fig. 7a–d). Data for these contour maps are generated by our pyrolysis kinetics oil and gas generation models. The contour maps in Fig. 7a and b show the relative extent of oil generation by the La Luna Formation at 38 and 12 Ma. Early generation occurred in the northeast as the basin subsided, with deeper water to the northeast, during the late Eocene and early Oligocene epochs. Later generation started in the southwest as the Andean foreland developed and as that part of the basin subsided during the late Miocene.

If we assume, as indicated by the equation-of-state modeling discussed above, that expulsion of oil begins when ~30% of the kerogen has been converted to oil, we can produce a map showing the beginning of oil expulsion from the La Luna Formation (see Fig. 7c). Expulsion occurred early in the history of the basin on its northeastern side but has only recently begun in the central part. This has an impact on the nature of the migrated oil, since early-generated oil tends to be heavier than late-generated oil. We are currently trying to determine when non-Cretaceous structural traps in the basin developed so that we can correlate their

development with the time of expulsion and the consequent characteristics of the oil that may have migrated away from the source rock. If we assume, as indicated by detailed modeling, that secondary gas generation begins when ~80% of the kerogen has been converted to oil, then we can generate a map (Fig. 7d) that shows when the secondary gas generation from the La Luna Formation began. Here again, secondary gas generation began early in the northeastern

part of the basin and has only recently begun elsewhere. We are studying oil/gas ratio data from recovered hydrocarbons in the wells in order to compare our predictions with field data.

Comparison of the predicted and observed characteristics of the hydrocarbon generation in the basin is difficult and is partially based on inferences because the geochemical data set is not complete and because the oil may have migrated, which means that the

recovered oil is not necessarily located where it was generated. Some of our initial results are shown in Figs. 8 and 9. Because of the chemistry of the hydrocarbon generation process, the hydrogen-to-carbon atomic ratio of the residual-source-rock kerogen tends to steadily decrease as kerogen is transformed. Measured values of hydrogen-to-carbon ratios in the La Luna Formation plotted as a function of kerogen conversion (Fig. 8) agree fairly well with

Figure 6. Oil evolution curves for wells representative of the four major thermal history types (see text) in the Maracaibo Basin. Oil evolution is represented as the fraction of kerogen converted to oil, which is calculated using a distributed activation energy model. The three curves in each example represent calculations using three different sets of kinetic parameters, which are determined by separate rapid pyrolysis experiments on the same sample.

Figure 7. Contour maps of the Maracaibo Basin. The extent of oil generation [kerogen converted to oil (%)]:(a) at 38 Ma and (b) at 12 Ma. Contours for (a) and (b) are for 20% conversion. (c) The timing (Ma) of the beginning of oil expulsion (30% of kerogen converted to oil). Contours are 10 Ma. (d) The timing (Ma) of the beginning of gas generation (80% of kerogen converted to oil). The circles are the locations of the wells that were the source of the data used in these calculations.

this observation and with a separate calculation of the ratio. API gravity (a measure of the density of the oil and, more importantly, its market value) tends to increase as kerogen is converted to oil because the oil's molecular weight and viscosity decrease. This general observation is confirmed in Fig. 9, which compares the API gravity of oil, recovered from Cretaceous reservoirs near the La Luna Formation, with our calculated values of the extent of kerogen conversion. This data set is still preliminary, and many of the

maturity calculations are based on uncertain thermal histories, which we are in the process of verifying.

Our study of the Maracaibo Basin is in an intermediate phase. We have made initial calculations of oil and gas generation characteristics in the basin, and we are beginning to compare our predictions with geochemical data from the basin. We hope to refine the comparison in the near future after we obtain more complete pyrolysis data that will allow us to carry out calculations with our improved chemical kinetics model.

Acknowledgments

This work is sponsored by the U.S. Department of Energy (DOE):

- Office of Fossil Energy (Oil, Gas, and Shale Division),
 - Office of Energy Research (Basic Energy Research Division),
- and by a consortium of seven international oil companies and research organizations under the auspices of the LLNL Technology Transfer Program: Exxon, ARCO, Norsk Hydro, I.K.U. (Norwegian), Chevron, Statoil, and J.N.O.C. (Japan National Oil Co.).

Figure 8. Plot of the calculated fraction of kerogen converted to oil and measured hydrogen-to-carbon atomic ratio in the residual kerogen for wells in the Maracaibo Basin.

Figure 9. Plot of the measured API gravity (a measure of oil density) from oil recovered from Cretaceous reservoirs and the calculated fraction of kerogen converted to oil for wells in the Maracaibo Basin.

References

- Barker, C. E. (1989), "Temperature and Time in the Thermal Maturation of Sedimentary Organic Matter," *Thermal History of Sedimentary Basins—Methods and Case Histories*, N. D. Naeser and T. H. McCulloh, Eds. (Springer-Verlag, New York), pp. 75–98.
- Braun, R. L., A. K. Burnham, and J. J. Sweeney (1988), *Petroleum Geochemistry Project Annual Report, October 1987–September 1988*, Lawrence Livermore National Laboratory, Livermore, CA, UCID-21393-88-4.
- Burnham, A. K., and J. J. Sweeney (1989), "A Chemical Kinetic Model of Vitrinite Maturation and Reflectance," (to be published in *Geochim. Cosmochim. Acta*).
- Davis, A. (1978), "A Discussion of Methods of Physical Characterization Used for Coal," *Scientific Problems of Coal Utilization*, B. R. Cooper, Ed., (Technical Information Center, U.S. Department of Energy), pp. 13–45.
- Larter, S. R. (1978), "Some Pragmatic Perspectives in Source Rock Geochemistry," *Marine and Petroleum Geol.* **5**, 194–204.
- Lopatin, N.V. (1971), "Temperature and Geologic Time as a Factor in Coalification," *Izvest. Akad. Nauk. SSSR, Ser. Geol.* **3** 95–106.
- McCartney, J. T., and S. Ergun (1958), "Optical Properties of Graphite and Coal," *Fuel* **37**, 272–281.
- Price, L. C. (1983), "Geologic Time as a Parameter in Organic Metamorphism and Vitrinite Reflectance as an Absolute Paleogeothermometer," *J. Petroleum Geol.* **6**, 5–38.
- Sweeney, J. J., and R. L. Burnham (1987), "Modeling the Generation of Oil and Gas," *Energy and Technology Review*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-52000-87-5.
- Talukdar, S., O. Gallango, and M. Chin-A-Lien (1986), "Generation and Migration of Hydrocarbons in the Maracaibo Basin, Venezuela: An Integrated Basin Study," *Org. Geochem.* **10**, 261–279.

Hydrodynamic Interactions and Transport Coefficients in a Suspension of Spherical Particles

Anthony J. C. Ladd

Fossil Energy Group

Particulate suspensions of solids in liquids can be understood in terms of the microstructure of the solid phase by using the well-known techniques of numerical statistical mechanics. This permits a unified approach to solid-fluid flow problems in which different macroscopic behavior arises solely from variations in the structure of the solid phase, which is specified explicitly. A long-standing problem in such an approach has been the incorporation of the long-range, many-body hydrodynamic forces between the suspended particles. We describe a general computational method for calculating the forces and torques exerted by slowly moving spheres suspended in an incompressible fluid. This method can be used to determine bulk constitutive properties of solid-fluid suspensions or particulate porous media. Numerical results for high frequency transport properties of monodisperse suspensions (viscosity, diffusion constant, and permeability) have been obtained, and the results compare very well with experimental measurements.

Transport processes in simple liquids can be described by linear constitutive laws, characterized by transport coefficients that depend only on the thermodynamic state of the system. This is because there are large separations of length scale and time scale between the macroscopic fluxes and the underlying microscopic processes. For particulate suspensions, these scale separations are not as large and the macroscopic constitutive laws can be nonlocal in time and nonlinear in the applied fields. These complicated constitutive relations can be obtained directly from a statistical analysis of the microscopic interactions (Happel and Brenner, 1986), including all of the important length scales and time scales explicitly. In the present context, for instance, this means that the complete boundary surface of the solid phase must be specified rather than

just the macroscopic parameters such as packing fraction; however, the molecular structure of the solid and fluid phases can be ignored. A complete calculation involves first determining what the microscopic interactions are for a particular configuration of solid particles and then averaging over an appropriate ensemble of configurations to obtain macroscopic transport coefficients such as viscosity, sedimentation velocity (mobility), and permeability. This well-defined procedure requires as input only the distribution of solid-particle sizes, the viscosity of the suspending fluid (assuming it is a simple Newtonian fluid), and a boundary condition at the solid-fluid surface, usually the hydrodynamic "no-slip" condition.

Microscopic modeling has two basic advantages over a macroscopic description. First, apparently

diverse phenomena can be understood on a unified basis; second, a fundamental description of the phenomena in terms of well-understood physical laws is possible. The first application of a statistical theory of particulate suspensions was contained in Einstein's thesis work around 1905 and led to the well-known expression relating to the viscosity η of a dilute suspension of spheres to the viscosity η_0 of the pure fluid (Einstein, 1956),

$$\eta/\eta_0 = 1 + \frac{5}{2}\phi, \quad (1)$$

where ϕ is the volume fraction occupied by the solid spheres. In the dilute limit, it is sufficient to treat the suspension as an assembly of noninteracting spheres, but at higher solid densities the particles interact by means of viscous forces transmitted through the fluid. These hydrodynamic interactions

cannot be written down in closed form except for isolated pairs of particles. However, in this paper, we indicate how the hydrodynamic interactions between arbitrary assemblies of spheres can be calculated numerically to any desired accuracy. Once the hydrodynamic interactions are known, the method of molecular dynamics can be used to determine ensemble-averaged thermodynamic and transport properties. Molecular dynamics is a brute-force solution of Newton's equations of motion for interacting particles (Ciccotti et al., 1987). Its use as a statistical-mechanical tool to investigate molecular liquids was pioneered by Berni Alder at Lawrence Livermore National Laboratory in the 1950s. One surprising, but very important, result of this early work was the realization that, by using periodic boundary conditions, only about 100 particles were necessary to obtain bulk macroscopic properties, with errors less than a few percent. This is true even for systems of particles interacting via long-range forces, such as charged ions or dipolar molecules. However, in such cases, one must be careful to take the periodic boundary conditions into account when calculating certain bulk properties such as the dielectric constant (Pollack and Alder, 1980). Similar considerations apply to the long-range hydrodynamic interactions in particulate suspensions; we will indicate how the boundary effects are incorporated into a calculation of the suspension viscosity.

Hydrodynamic Interactions

The motion of solid particles suspended in a fluid is a complex problem, primarily because of the difficulties involved in calculating the long-range, many-body hydrodynamic interactions. If the relative velocities of the solid and fluid phases are small, the inertial terms

in the Navier-Stokes equation describing the motion of the fluid can be ignored. The fluid flow is then stationary in time and incompressible, leading to the so-called "creeping-flow" equations, for the velocity field $\mathbf{v}$ and the pressure p (Happel and Brenner, 1986),

$$\nabla \cdot \mathbf{v} = 0, \quad (2)$$

$$\nabla p = \eta_0 \nabla^2 \mathbf{v}, \quad (3)$$

where η_0 is the shear viscosity of the pure fluid. Finite Reynolds number corrections are generally negligible for particle sizes up to 1 mm. However, even with this important simplification from the full nonlinear Navier-Stokes equation, the calculation of the resulting forces on an assembly of moving particles is still difficult.

Since the creeping-flow equations are linear in the velocity and pressure fields, the forces $\mathbf{F}$ and torques $\mathbf{T}$ exerted on the particles by the fluid can be related to the particle velocities $\mathbf{U}$ and angular velocities $\boldsymbol{\Omega}$ via the configuration-dependent friction-coefficient matrices $\boldsymbol{\zeta}$,

$$\mathbf{F}_i = - \sum_{j=1}^N \{ \boldsymbol{\zeta}_{ij}^{TT} \cdot \mathbf{U}_j + \boldsymbol{\zeta}_{ij}^{TR} \cdot \boldsymbol{\Omega}_j \}, \quad (4)$$

$$\mathbf{T}_i = - \sum_{j=1}^N \{ \boldsymbol{\zeta}_{ij}^{KT} \cdot \mathbf{U}_j + \boldsymbol{\zeta}_{ij}^{KK} \cdot \boldsymbol{\Omega}_j \}, \quad (5)$$

where the superscripts T and R refer to the translational and rotational components of $\boldsymbol{\zeta}$, and the sums extend over all N particles in the suspension. Equations (4) and (5) can be inverted to find the corresponding mobility matrices $\boldsymbol{\mu}$

$$\mathbf{U}_i = - \sum_{j=1}^N \{ \boldsymbol{\mu}_{ij}^{TT} \cdot \mathbf{F}_j + \boldsymbol{\mu}_{ij}^{TR} \cdot \mathbf{T}_j \}, \quad (6)$$

$$\boldsymbol{\Omega}_i = - \sum_{j=1}^N \{ \boldsymbol{\mu}_{ij}^{KT} \cdot \mathbf{F}_j + \boldsymbol{\mu}_{ij}^{KR} \cdot \mathbf{T}_j \}. \quad (7)$$

The friction and mobility coefficients are complicated functions of all of the particle coordinates; calculating them for arbitrary assemblies of spherical particles is the main objective of the method described in this work. Specifically, it is assumed that the spheres are of uniform size and that hydrodynamic stick boundary conditions apply between the solid-fluid surfaces. Then the fluid velocity field on the surface of a particle is given by

$$\mathbf{v}(\mathbf{r}) = \mathbf{U} - \boldsymbol{\Omega} \times (\mathbf{r} - \mathbf{R}) \quad (8)$$

for $|\mathbf{r} - \mathbf{R}| = a$.

where $\mathbf{U}$, $\boldsymbol{\Omega}$, and $\mathbf{R}$ are the velocity, angular velocity, and location of the particle, and a is the particle radius. Equations (2), (3), and (8), together with periodic boundary conditions applied to a set of N spheres in a cubic unit cell of volume V , completely specify the problem, which can be solved by the method of induced forces (Mazur and Van Saarloos, 1982).

The stick boundary conditions are satisfied by introducing an induced-force density on the surface of each particle, which is to be chosen so that the fluid velocity field matches the surface velocity of each particle [Eq. (8)] at all points on the particle surface. The fluid velocity field anywhere in the system can be written in terms of this induced-force density $\mathbf{F}_{\text{ind}}$,

$$\mathbf{v}(\mathbf{r}) = \int_V \mathbf{T}(\mathbf{r} - \mathbf{r}') \cdot \mathbf{F}_{\text{ind}}(\mathbf{r}') d\mathbf{r}', \quad (9)$$

where $\mathbf{T}$ is the Oseen tensor describing the velocity field arising from a point force

$$\mathbf{T}(\mathbf{r}) = \frac{1}{8\pi\eta_0 r} [\mathbf{I} - \hat{\mathbf{r}}\hat{\mathbf{r}}]; \quad (10)$$

the vector $\hat{\mathbf{r}}$ denotes the unit vector $\mathbf{r}/r$, and $\mathbf{I}$ represents the second-rank unit tensor. The integral in Eq. (9) extends over the macroscopic sample volume V_{sp} , and includes all the

periodic images of the unit cell. Because the Oseen tensor is long-range, this integral can diverge, and therefore it is necessary to take careful account of the macroscopic boundary conditions. In general, there can be no net force on the fluid; otherwise, it will accelerate without bound. A gravitational force, for instance, must always be balanced by a compensating pressure gradient. With this constraint, we can rewrite Eq. (9) in a form consistent with periodic boundary conditions (Ladd, 1988),

$$\mathbf{v}(\mathbf{r}) = \frac{1}{V} \sum_{\mathbf{k} \neq 0} \frac{e^{i\mathbf{k} \cdot \mathbf{r}}}{\eta_0 k^2} \mathbf{I} - \mathbf{k} \mathbf{k}^T \cdot \mathbf{F}_{\text{ind}}(\mathbf{k}), \quad (11)$$

where $\mathbf{F}_{\text{ind}}(\mathbf{k})$ is a finite Fourier transform over the volume V of the unit cell containing the N spheres,

$$\mathbf{F}_{\text{ind}}(\mathbf{k}) = \int_V e^{i\mathbf{k} \cdot \mathbf{r}} \mathbf{F}_{\text{ind}}(\mathbf{r}) d\mathbf{r}. \quad (12)$$

The sum in Eq. (11) includes all $\mathbf{k}$ vectors commensurate with the unit cell. The $\mathbf{k} = 0$ term is omitted from the summation, as it is assumed that there is no net ($\mathbf{k} = 0$) force on the system. Results for periodic boundary conditions can be directly related to an experimental geometry in which a macroscopic sphere, consisting of replicas of the basic unit cell, is immersed in a fluid of infinite viscosity (Ladd and Smith, 1989).

Since the induced-force density is localized on the surface of each sphere, force multipoles can be defined as surface integrals involving the induced traction $\mathbf{t}$ (i.e., the induced force per unit area on the particle surface) and irreducible tensor products of the unit vector $\hat{\mathbf{r}}_i$ denoting a point on the surface of sphere i , relative to its center. Thus, the p th order force multipole of particle i is a tensor of rank $p+1$,

$$\mathbf{F}_i^{p+1} = \frac{1}{p!} \int_{\text{surface}} \hat{\mathbf{r}}_i^p \mathbf{t}_i(\mathbf{r}_i) d\mathbf{r}_i, \quad (13)$$

where S_i indicates an integral over the (spherical) surface of particle i . The notation $\hat{\mathbf{r}}^p$ is used to indicate an irreducible tensor of rank p . The forces and torques exerted by the fluid on a particular particle, denoted by $\mathbf{F}_i$ and $\mathbf{T}_i$, respectively, are related to the first two force moments

$$\mathbf{F}_i = -\mathbf{F}_i^1; \quad \mathbf{T}_i = \epsilon \mathbf{F}_i^2, \quad (14)$$

where ϵ is the Levi-Civita tensor and $\mathbf{F}_i^{2a}$ indicates the part of $\mathbf{F}_i^2$ that is antisymmetric with respect to permutation of the Cartesian indices. Throughout this work, tensor products are carried out by contracting the last index of the first tensor with the first index of the second, and so on, e.g.,

$$\epsilon : \mathbf{F}^2 \equiv \epsilon_{\alpha\beta\gamma} F_{\alpha\beta\gamma}.$$

The traceless symmetric part of $\mathbf{F}^2$ is the contribution to the pressure tensor arising from the induced-force density on particle i ; it is related to the shear viscosity, as will be seen in the next section. The trace of $\mathbf{F}_i^2$ is related to the induced pressure and has no effect on the fluid motion because of the incompressibility condition. The total moment $\mathbf{F}^2$ is the sum of these three contributions: antisymmetric, traceless symmetric, and trace; i.e.,

$$\mathbf{F}^2 = \mathbf{F}^{2a} + \mathbf{F}^{2s} + \frac{1}{3} (\text{tr } \mathbf{F}^2) \mathbf{I}.$$

All the properties of the suspension that are of physical interest can be derived from the first two force moments, but the higher moments are necessary to give an accurate description of the fluid flow in densely packed suspensions.

Irreducible moments of the fluid velocity on the surface of each sphere can be defined in an analogous manner to the force moments

$$\mathbf{V}_i^{p+1} = \frac{(2p+1)!!}{4\pi a^{2p}} \int_{\text{surface}} \hat{\mathbf{r}}_i^p \mathbf{v}(\mathbf{r}_i) d\mathbf{r}_i, \quad (15)$$

These moments are similarly related to the particle velocities and angular velocities

$$\mathbf{U}_i = \mathbf{V}_i^1; \quad \Omega_i = -(2a)^{-1} \epsilon : \mathbf{V}_i^2, \quad (16)$$

Because the stick boundary conditions allow no relative solid-fluid motion on the surface of the particles, all higher velocity moments, including $\mathbf{V}_i^{2a}$, are zero.

It follows from Eqs. (11), (13), and (15) that the force moments and velocity moments are linearly related,

$$\mathbf{V}_i^{p+1} = \sum_{j=1}^N \sum_{p'=0}^{\infty} \mathbf{G}_{ij}^{p+1, p'+1} \odot \mathbf{F}_j^{p'+1}, \quad (17)$$

where $\odot$ indicates a $p'+1$ -fold contraction between the tensors

$$\mathbf{G}_{ij}^{p+1, p'+1}$$

and

$$\mathbf{F}_j^{p'+1},$$

contracting the last index of

$$\mathbf{G}_{ij}^{p+1, p'+1}$$

with the first index of $\mathbf{F}_j^{p'+1}$, etc. By substituting the spherical-harmonic expansion of the plane wave $e^{i\mathbf{k} \cdot \mathbf{r}}$ in the expression for the velocity field (Eq. (11)), together with the definitions of force and velocity moments [Eqs. (13) and (15)], it is straightforward to show that (Ladd, 1988)

$$\begin{aligned} \mathbf{G}_{ij}^{p+1, p'+1} &= (i)^p (-i)^{p'} (2p+1)!! (2p'+1)!! \\ &\quad \sum_{\mathbf{k} \neq 0} e^{i\mathbf{k} \cdot \mathbf{R}_{ij}} \frac{R_{ij}^p (i\mathbf{k})^p (i\mathbf{k})^{p'}}{\eta_0 k^2 V} \\ &\quad \hat{\mathbf{k}}^p (1 - \hat{\mathbf{k}} \hat{\mathbf{k}}^T) \hat{\mathbf{k}}^{p'}. \end{aligned} \quad (18)$$

The computation of these matrix elements $\mathbf{G}_{ij}^{p+1, p'+1}$ is the most difficult and one of the most time consuming parts of the calculation. We now have an algorithmically

efficient and highly vector/parallel code running on the Alliant FX/8 and FX/80 computers (Ladd, 1988; Ladd, 1989). The terms in Eq. (18) are summed explicitly within a sphere of radius $k_{\max}$ and then the remaining contributions are approximated, with sufficient accuracy for large enough $k_{\max}$, by integrals. A typical calculation with $N = 16$ particles, including force moments up to $p_{\max} = 4$ takes about two minutes per configuration on the FX/8. The computational effort scales as N^2 and as $p_{\max}^3$ for $p_{\max} \leq 3$. For higher moments, the computational effort in calculating the $\mathbf{G}$ tensors does not depend strongly on the number of force moments because the matrix elements linking the higher force and velocity moments are short-range in real space and can be computed without the lengthy k -space sums.

The set of linear simultaneous equations represented by Eq. (17) can be solved by triangular decomposition, followed by the appropriate back solves to obtain the friction coefficients $\zeta = \mathbf{G}^{-1}$,

$$\begin{aligned}\zeta_{ij}^{TT} &= \zeta_{ij}^{1,1}; \\ \zeta_{ij}^{TR} &= \mu \zeta_{ij}^{1,2}, \zeta_{ij}^{2,1}; \\ \zeta_{ij}^{KT} &= -\alpha \zeta_{ij}^{2,1}, \zeta_{ij}^{1,2}; \\ \zeta_{ij}^{KR} &= -\alpha^2 \zeta_{ij}^{2,2}, \zeta_{ij}^{2,2}; \quad (19)\end{aligned}$$

The $6N \times 6N$ friction-coefficient matrix, constructed from the 3×3 submatrices defined in Eq. (19), can be also inverted to determine the mobility matrix μ . The computational effort required to solve the simultaneous equations [Eq. (18)] scales as $(Np_{\max}^3)$ and thus dominates the computation for large systems. For the same sample problem mentioned earlier ($N = 16$; $p_{\max} = 4$), the solution and construction of the friction coefficient matrix takes about one minute, so that a single configuration takes about three minutes of central processing unit time. This particular problem

runs at about 15 Mflops on the FX/8, which is typical for our current computer program, although in some instances it runs at over 20 Mflops. By comparison, the peak speed of the FX/8 is around 50 Mflops. Further enhancements in performance will have to come largely from algorithmic improvements; for instance, for large numbers of particles, an iterative scheme for solving dense linear systems would be much faster than triangular decomposition.

When a pair of particles is close to contact, the hydrodynamic forces diverge as s^{-1} and $\ln s^{-1}$, where $s = (R_{12} - 2a)/a$ is the gap between the particles, relative to the radius (Jeffrey and Onishi, 1984). Under these circumstances, the multipole moment expansion described above converges very poorly, or not at all (Ladd, 1989). To overcome this difficulty, we use the fact that these short-range, lubrication forces are pairwise additive, since they are basically interactions between points rather than surfaces. Thus, we can replace the approximate pairwise-additive friction coefficients [Eq. (19)] by the exact ones, which are already known from other work (Kim and Mifflin, 1985). This is quite straightforward since, for two particles, the friction coefficients can be written as scalar functions of the separation multiplied by appropriate spherical harmonics to describe the angular variation (Kim and Mifflin, 1985). The scalar functions, computed from the approximate and exact two-particle friction coefficients, are stored in tabular form. The interpolation procedure used ensures that the s^{-1} and $\ln s^{-1}$ singularities are handled exactly.

Shear Viscosity

In the previous section, we showed how to calculate the dissipative hydrodynamic forces acting on suspended particles that are moving under the influence of external forces or fluctuating Brownian

force. We are also interested in the response of the suspension to an imposed external shear rate. We ignored the effects of the imposed flow on the suspension microstructure and assumed that it is an equilibrium distribution of hard spheres, freely moving without hydrodynamic forces and torques. Such a situation can be realized experimentally by using an oscillating strain rate, with a sufficiently high frequency that the solid particles cannot follow it. The following theory (Ladd, 1988) and calculations apply to that situation. Low frequency transport coefficients will be considered in future work.

In the absence of solid particles, homogeneous fluid flow can be described by the equation

$$\nabla_0(\tau) = \dot{\epsilon}_0 \cdot \tau, \quad (20)$$

where the traceless tensor $\dot{\epsilon}_0 = (\nabla \cdot v_0)^T$ is independent of location. Because the hydrodynamic equations are linear, the velocity fields arising from the induced forces and the externally imposed flow can be superposed, leading to a generalization of Eq. (17),

$$\begin{aligned}\mathbf{V}_i^{p+1} &= \mathbf{V}_{i,0}^{p+1} \\ &+ \sum_{i'=1}^N \sum_{p'=0}^m \mathbf{G}_{ii'}^{p+1, p'-1} \odot \mathbf{F}_{i'}^{p'-1},\end{aligned} \quad (21)$$

where the moments of the imposed flow $\mathbf{V}_{i,0}^{p+1}$ are calculated from the equivalent of Eq. (15), with the results

$$\mathbf{V}_{i,0}^1 = \dot{\epsilon}_0 \cdot \mathbf{R}_i; \quad \mathbf{V}_{i,0}^2 = \alpha \dot{\epsilon}_0^2, \quad (22)$$

all higher moments being zero. The assumption that the spheres are freely moving implies that

$$\mathbf{V}_i^1 = \mathbf{V}_{i,0}^1, \quad \mathbf{V}_i^2 = \mathbf{V}_{i,0}^2,$$

and

$$\mathbf{F}_i^1 = \mathbf{F}_i^2 = 0.$$

Thus, the first non-vanishing force moments, $\mathbf{F}_i^{2s}$, are given by

$$\mathbf{F}_i^{2s} = - \sum_{j=1}^N \zeta_{ij}^{2s, 2s} : \mathbf{V}_{j,0}^{2s} \\ = -n \sum_{i=1}^N \zeta_{ii}^{2s, 2s} : \mathbf{e}_0^s, \quad (23)$$

where $\zeta_{ij}^{2s, 2s}$ is given by

$$\zeta_{ij}^{2s, 2s} = \zeta^{2s, 2s} \\ = \begin{bmatrix} \zeta^{2s, T} & \zeta^{2s, R} \end{bmatrix} \cdot \begin{bmatrix} \zeta^{TT} & \zeta^{TR} \\ \zeta^{RT} & \zeta^{RR} \end{bmatrix} \cdot \begin{bmatrix} \zeta^{T, 2s} \\ \zeta^{R, 2s} \end{bmatrix}; \quad (24)$$

$\zeta^{2s, T}$ and $\zeta^{2s, R}$ are defined by analogy with Eq. (19). The imposed strain rate tensor $\dot{\epsilon}_0$ has been split into traceless-symmetric and anti-symmetric parts. The antisymmetric part drives the particle rotation, but does not affect the stress.

The induced stress arising from a fixed configuration of solid particles in the externally driven flow can be calculated by integrating $[-r \mathbf{F}_{\text{ind}}(\mathbf{r})]$ over a spherical volume, radius $a + \delta$, enclosing a sphere i . The resulting contribution from particle i to the stress tensor of that particular configuration is

$$-V^{-1} a \mathbf{F}_i^{2s}.$$

Since the ensemble-averaged stress tensor is homogeneous, it can be related to the imposed shear rate via the ensemble-averaged dipole-dipole friction tensor $\langle \zeta_{ij}^{2s, 2s} \rangle$,

$$\langle \sigma_{\text{ind}} \rangle = -V^{-1} a \sum_{i=1}^N \langle \mathbf{F}_i^{2s} \rangle \\ = na^2 \langle \zeta_{ii}^{2s, 2s} \rangle : \mathbf{e}_0^s, \quad (25)$$

where $n = N/V$ is the number density,

$$\langle \zeta_{ij}^{2s, 2s} \rangle = \langle N^{-1} \sum_{i,j=1}^N \zeta_{ij}^{2s, 2s} \rangle,$$

and $\langle \dots \rangle$ denotes an ensemble average over the N -particle hard

sphere distribution function. The total stress in the suspension is given by the sum of the induced stress and the fluid stress,

$$\langle \sigma \rangle = 2\eta_0 \langle \dot{\epsilon}^s \rangle + na^2 \langle \zeta_{ii}^{2s, 2s} \rangle : \mathbf{e}_0^s. \quad (26)$$

The fluid stress is proportional to the ensemble-averaged shear rate in the presence of the suspended particles $\langle \dot{\epsilon}^s \rangle$. The relation between $\langle \dot{\epsilon}^s \rangle$ and the imposed shear rate $\dot{\epsilon}_0$ is dependent on the macroscopic boundary conditions and will be discussed below.

Since the components of the dipole-dipole friction tensor are long-ranged, varying as R_{ij}^{-3} (Beenakker, 1984), its ensemble average $\langle \zeta_{ij}^{2s, 2s} \rangle$ is also dependent on the boundary conditions. This in turn affects the average stress in the suspension, but the viscosity is independent of the boundary conditions because of compensating variations in the average shear rate (Felderhof, 1976). Assuming that the induced-force density is slowly varying over the surface of each sphere, then the perturbation in the velocity field arising from a fixed configuration of spheres [Eq. (9)] can be expressed in terms of the force moments, beginning with $\mathbf{F}_i^{2s}$. The Oseen tensor is expanded in a multipole series

$$\mathbf{T}(\mathbf{r} - \delta\mathbf{r}) = \mathbf{T}(\mathbf{r}) - \delta\mathbf{r} \cdot \nabla \mathbf{T}(\mathbf{r}) + \dots,$$

and, to lowest order, the strain-rate field is given by

$$[\nabla \cdot \mathbf{v}(\mathbf{r})]^s = [\nabla \cdot \mathbf{v}_0(\mathbf{r})]^s \\ - n \sum_j \mathbf{T}^{2s, 2s}(\mathbf{r} - \mathbf{R}_j) : \mathbf{F}_j^{2s}. \quad (27)$$

The sum extends over all particles in the macroscopic system, including, if appropriate, all periodic images.

The propagator $\mathbf{T}^{2s, 2s}$ is simply $\nabla \nabla \cdot \mathbf{T}$, suitably symmetrized,

$$\mathbf{T}_{\alpha\beta\gamma\delta}^{2s, 2s} = \frac{1}{4} (\nabla_\alpha \nabla_\gamma \mathbf{T}_{\beta\delta} + \nabla_\beta \nabla_\delta \mathbf{T}_{\alpha\gamma} \\ + \nabla_\alpha \nabla_\delta \mathbf{T}_{\beta\gamma} + \nabla_\beta \nabla_\gamma \mathbf{T}_{\alpha\delta}). \quad (28)$$

After ensemble averaging, and using Eq. (23) to express the induced force moments in terms of the imposed shear rate and the dipole-dipole friction tensor, then for the particular case of an xy shear, the average shear rate is

$$\langle \dot{\epsilon}_{xy}^s \rangle = \langle V_M^{-1} \int_V |\nabla_x \nabla_y(\mathbf{r})| d\mathbf{r} \rangle \\ = \dot{\epsilon}_0^s \{ 1 + 4na^2 \langle \zeta_{ii}^{2s, 2s} \rangle \int_{V_M} \mathbf{T}_{xyxy}^{2s, 2s}(\mathbf{r}) d\mathbf{r} \}, \quad (29)$$

where the integrals are again over the whole macroscopic volume. The factor of 4 arises from the contractions of the

$$\langle \zeta_{ii}^{2s, 2s} \rangle$$

tensor with $\mathbf{T}^{2s, 2s}$ and $\dot{\epsilon}_0^s$. At low densities,

$$\zeta_{ii}^{2s, 2s} \rightarrow (10/3) \pi \eta_0 a,$$

and defining γ to be the ratio of

$$\langle \zeta_{ii}^{2s, 2s} \rangle$$

to its low-density limit, i.e.,

$$\gamma = 3 \langle \zeta_{ii}^{2s, 2s} \rangle / 10 \pi \eta_0 a,$$

the shear stress and shear rate are given by

$$\langle \sigma_{xy} \rangle = 2\eta_0 \left(\langle \dot{\epsilon}_{xy}^s \rangle + \frac{5}{2} \phi \gamma \dot{\epsilon}_0 \right); \\ \langle \dot{\epsilon}_{xy}^s \rangle = \dot{\epsilon}_0 (1 + 10 \phi \gamma \chi), \quad (30)$$

where χ is the sample shape dependent factor

$$\chi = \int_{V_M} \eta_0 \mathbf{T}_{xyxy}^{2s, 2s}(\mathbf{r}) d\mathbf{r}. \quad (31)$$

Consequently, the expression for the shear viscosity, including the sample-shape dependence of the shear rate explicitly, is

$$\frac{\eta}{\eta_0} = 1 + \frac{5 \phi \gamma}{(1 + 10 \phi \gamma \chi)}. \quad (32)$$

It now only remains to evaluate χ for the various sample geometries.

The volume integral in Eq. (31) can be transformed into a surface integral and, for a spherical sample independent of the sample size, $\chi = -1/10$. For periodic boundary conditions, we find that $\chi = 0$, which implies that the shear rate is unaffected by the presence of the solid particles. This is because the absence of a boundary surface prevents the development of a back flow, in opposition to the imposed shear flow. Instead, a larger stress develops in the system, as was verified analytically in Ladd (1988). Thus, for periodic boundaries, the viscosity is given by

$$\frac{\eta}{\eta_0} = 1 + \frac{5}{2}\phi \quad (33)$$

Transport Coefficients

The transport properties of a random dispersion of hard spheres has been a subject of theoretical interest for a long time (Happel and Brenner, 1986). Properties of particular interest are:

- The permeability of a fixed array of spheres (Brinkman, 1947; Tam, 1969; Itoh, 1983; Kim and Russel, 1985).
- The single-particle and collective mobility coefficients (sedimentation velocity) (Beenakker and Mazur, 1983; Beenakker and Mazur, 1984).
- The viscosity (Beenakker, 1984).

In all cases, the underlying assumption is that the distribution of configuration of spheres is the equilibrium one, unaffected by the hydrodynamic interactions. This assumption is valid only at short times or high frequencies. Experimentally all the transport coefficients, except the collective mobility coefficient, can be measured under these conditions.

Systematic theoretical studies of the behavior of the transport coefficients away from the dilute limit began with Batchelor (1972) who

included the interaction between pairs of particles, leading to expansions in packing fraction for the self-diffusion coefficient (Batchelor, 1976):

$$D_s/D_0 = 1 - A_1\phi + \dots \quad (34)$$

the collective mobility (Batchelor, 1972; Batchelor, 1976):

$$\mu/\mu_0 = 1 - A_2\phi + \dots \quad (35)$$

and the shear viscosity (Batchelor and Green, 1972):

$$\eta/\eta_0 = 1 + \frac{5}{2}\phi + B_2\phi^2 + \dots \quad (36)$$

In these expressions,

$$D_0/(k_B T) = \mu_0 = 6\pi\eta_0 a$$

is the mobility of an isolated sphere of radius a , and η_0 is the viscosity of the pure solvent. Batchelor's calculation of $A_2 = 1.83$ and $A_3 = 6.55$ are in good agreement with recent results (Cichocki and Felderhof, 1988) ($A_2 = 1.831$; $A_3 = 6.546$), but his calculation of $B_2 = 5.2 \pm 0.3$ was too large, as shown by more accurate calculations (Cichocki and Felderhof, 1988; Ladd, 1989), which give $B_2 = 5.00$. Batchelor's work has been extended to higher densities, keeping the assumption of pairwise additivity of the hydrodynamic interactions but using a density-dependent pair distribution function (Russel and Gast, 1986; Wagner and Russel, 1989). However, it is now known that the many-body hydrodynamic interactions must be included for quantitative results beyond about a 10% solids fraction (Beenakker and Mazur, 1983). In a recent paper (Ladd, 1989), I used the method outlined earlier in this article, under "Hydrodynamic Interactions" to calculate the shear viscosity of a random dispersion of spheres. Although the method is exact if a sufficient number of force moments are included, the full effects of the short-range lubrication forces were not included and, consequently, the convergence of the

viscosity with increasing numbers of force moments was quite poor at a high-packing fraction. The resulting estimates for the viscosity are too small by about 5% at $\phi = 0.35$ and about 10% at $\phi = 0.45$. Phillips et al. (1988) included the effects of lubrication but only used a low-order moment approximation to the many-body hydrodynamic interactions, corresponding to the $\mu_{\max} = 1$ approximation in this work. This turns out to give quite accurate results for the viscosity and self-diffusion coefficients, because lubrication is important in these transport processes, but it gives only qualitatively correct collective mobility (sedimentation velocity) and permeability coefficients at a high-packing fraction. In this work, an exact treatment of lubrication forces is coupled with an accurate description of the many-body hydrodynamic interactions. The convergence of the transport properties with the number of force moments and the number of solid particles is examined and the extrapolated results ($\mu_{\max} \rightarrow \infty$, $N \rightarrow \infty$) are compared with theory and experiment.

The transport coefficients that we are interested in are related to ensemble averages of the appropriate elements of the friction and mobility tensors. The inverse permeability K^{-1} is defined via Darcy's law, relating the macroscopic pressure gradient $\nabla\langle p \rangle$ to the average velocity $\langle \mathbf{u} \rangle$,

$$\nabla\langle p \rangle = -\eta_0 K^{-1} \langle \mathbf{u} \rangle \quad (37)$$

The pressure gradient is balanced by the average force per unit volume exerted by the particles on the fluid

$$\begin{aligned} \nabla\langle p \rangle &= -V^{-1} \left\langle \sum_i \mathbf{F}_i \right\rangle \\ &= -V^{-1} \left\langle \sum_{i,j=1}^N \mathbf{f}_{ij}^T \right\rangle \cdot \langle \mathbf{u} \rangle \quad (38) \end{aligned}$$

where $\mathbf{F}_i$ is the total force exerted on the fluid by particle i [Eq. (14)].

For an isotropic system, K^{-1} is a scalar quantity, related to ζ^{TT} via Eqs. (37) and (38)

$$K^{-1} = (\eta_0 V) \frac{1}{3} \text{tr} \left\langle \sum_{i,j=1}^N \zeta_{ij}^{TT} \right\rangle. \quad (39)$$

Our results for the inverse permeability are expressed in terms of the dimensionless quantity K_0/K , where

$$K_0^{-1} = \frac{9}{2} \eta_0^{-1} \tau$$

is the low density limit of K^{-1} .

The single-particle and collective mobilities describe the velocity response of one particle or all N particles to an applied force; thus from Eq. (6)

$$D_s(k_B T) = N^{-1} \frac{1}{3} \text{tr} \left\langle \sum_{i,j=1}^N \mu_{ij}^{TT} \right\rangle \quad (40)$$

and

$$\mu = N^{-1} \frac{1}{3} \text{tr} \left\langle \sum_{i,j=1}^N \mu_{ij}^{TT} \right\rangle, \quad (41)$$

where

$$\begin{bmatrix} \mu^{TT} & \mu^{TR} \\ \mu^{RT} & \mu^{RR} \end{bmatrix} = \begin{bmatrix} \zeta^{TT} & \zeta^{TR} \\ \zeta^{RT} & \zeta^{RR} \end{bmatrix}^{-1}. \quad (42)$$

Finally, the shear viscosity is calculated from the dipole-dipole friction tensor $\zeta^{2,2}$ as described earlier in "Shear Viscosity."

Numerical results were obtained by averaging over 100 statistically independent configurations of hard spheres. For most densities ($\phi > 0.002$), the configurations were obtained from snapshots, equally spaced in time, along a molecular dynamics trajectory. The time spacing was large, of the order of the time taken for a particle to diffuse over a distance $2a$. At very low densities, random configurations of spheres were generated, rejecting any configurations with overlapping spheres. Our results have small statistical errors, the 95% confidence

limits are within 1% of the mean in all cases and in general are smaller. Simulations were run for 16, 32, 54, and 108 particles using moment approximations for $p_{\max} = 1$ to $p_{\max} = 7$, corresponding to between 12 and 192 equations per particle. The packing fractions range from $\phi = 0.001$ to $\phi = 0.45$, near the solid-liquid freezing transition of hard spheres at $\phi = 0.49$.

Results at the highest packing fractions, $\phi = 0.45$, are shown in Table 1. For the smallest system ($N = 16$), we have used a sufficient number of force moments to ensure that all transport coefficients have converged to within 1% of the exact ($p_{\max} \rightarrow \infty$) results at all packing fractions. It is not computationally feasible at present to run the larger systems with the same number of force moments as the 16-particle systems; we used force moments up to $p_{\max} = 5$, $p_{\max} = 3$, and $p_{\max} = 2$ for the $N = 32$, $N = 54$, and $N = 108$ particle systems, respectively. Fortunately, the higher force moments are only important for clusters of particles that are relatively close together, and therefore their effects are more or less independent of system size. This can be verified from Table 1 by noting that the difference between transport coefficients derived from successive moment approximations is essentially independent of N . Thus, we can estimate the large $p_{\max}$ results for all the system sizes considered, assuming that the effects of the higher force moments are the same as for $N = 16$. This leads to consistent results for the $p_{\max} \rightarrow \infty$ transport coefficients even at $\phi = 0.45$, where the high-moment effects are most important. The fully-converged transport coefficients for the different size systems, over a range of packing fractions, are shown in Table 2.

The inverse permeability and viscosity are insensitive to system size,

and the difference between $N = 32$, $N = 54$, and $N = 108$ is not statistically significant (Table 2). However, both the single-particle and collective mobility coefficients show a strong size dependence, deviating from the thermodynamic limit by terms of order $N^{-1/3}$ (Table 2). We can understand and quantitatively predict these deviations by first considering the sedimentation of a single particle in a periodic system with a large but finite unit cell. This problem was solved by Hasimoto (1959), who derived the low-density expansion for the diffusion coefficient of a simple-cubic lattice

$$D_{sc}/D_0 = 1 - 1.7601 \phi^{1/3} + o(\phi) \quad (43)$$

We can superpose the effects of the neighboring particles and the periodic-image particles to relate the N -particle periodic diffusion coefficient to its thermodynamic limit (Phillips et al., 1988),

$$D_s(N)/k_B T = D_s - D_0 [1.7601 (\phi/N)^{1/3} - \phi/N]. \quad (44)$$

Equivalently we can derive a correction to the N -particle diffusion coefficient so that

$$D_s = D_s(N) + D_{\text{corr}}(N), \quad (45)$$

with

$$D_{\text{corr}}(N) k_B T = (6\pi\eta_0)^{-1} [1.7601 (\phi/N)^{1/3} - \phi/N]. \quad (46)$$

This correction works well at low solids packing, but at higher packing fractions the neighboring particles partially screen the effects of the periodic images, reducing the magnitude of the correction. Since the distance between the sedimenting particle and its periodic images are generally large compared with the particle size, we can account for this screening by simply replacing the pure-fluid viscosity with the suspension viscosity.

Table 1. Dependence of the transport coefficients (permeability K , mobility μ , self-diffusion D_s , and viscosity η) on the number of force moments at $\phi = 0.45$. In each case, the transport coefficients are scaled by the appropriate low-density limit (see text). The statistical errors in the least significant figure (one standard deviation in the mean) are given in parentheses.

ϕ	N	$p_{\max}$	K_0/K	μ/μ_0	D_s/D_0	η/η_0
0.45	16	1	10.63(5)	0.0982(5)	0.173(1)	5.41(4)
		2	23.39(8)	0.0480(3)	0.157(1)	5.29(4)
		3	26.19(8)	0.0439(2)	0.151(1)	5.48(4)
		4	27.68(8)	0.0418(2)	0.152(1)	5.41(4)
		5	28.25(9)	0.0415(2)	0.149(1)	5.54(5)
		6	28.53(9)	0.0412(2)	0.148(1)	5.55(5)
		7	28.59(9)	0.0410(2)	0.149(1)	5.50(4)
	32	1	10.37(2)	0.1012(2)	0.1827(6)	5.70(2)
		2	22.99(4)	0.0499(2)	0.1733(5)	5.53(2)
		3	25.85(5)	0.0453(1)	0.1697(5)	5.58(2)
		4	27.35(5)	0.0433(2)	0.1678(5)	5.63(2)
		5	28.04(5)	0.0427(1)	0.1672(5)	5.65(2)
	54	1	10.40(1)	0.1014(2)	0.1949(5)	5.69(2)
		2	22.91(3)	0.0505(1)	0.1867(5)	5.55(2)
		3	25.75(4)	0.0460(1)	0.1831(5)	5.61(2)
	108	1	10.36(1)	0.1018(2)	0.2041(4)	5.73(1)
		2	22.93(4)	0.0507(2)	0.1996(7)	5.52(2)

Table 2. Variation of the transport coefficients (defined in Table 1) with system size. At high densities, the transport coefficients for $N = 32, 54$, and 108 have been corrected for neglected force moments. Finite-size corrections for the mobility and self-diffusion coefficients have been calculated independently (see text) and are shown in parentheses, followed by the resulting estimate of the $N \rightarrow \infty$ transport coefficient.

ϕ	N	K_0/K	μ/μ_0	D_s/D_0	η/η_0
0.001	16	1.096	0.927 (+0.069 = 0.996)	0.9288 (+0.0696 = 0.9984)	1.00250
	32	1.088	0.938 (+0.055 = 0.993)	0.9432 (+0.0553 = 0.9985)	1.00250
	54	1.081	0.947 (+0.046 = 0.993)	0.9520 (+0.0464 = 0.9984)	1.00250
	108	1.073	0.960 (+0.037 = 0.997)	0.9615 (+0.0369 = 0.9984)	1.00251
0.05	16	1.96	0.570 (+0.164 = 0.734)	0.688 (+0.223 = 0.911)	1.1383
	32	1.92	0.600 (+0.130 = 0.730)	0.731 (+0.178 = 0.909)	1.1387
	54	1.90	0.621 (+0.109 = 0.730)	0.759 (+0.150 = 0.909)	1.1389
	108	1.89	0.640 (+0.087 = 0.727)	0.789 (+0.119 = 0.908)	1.1391
0.25	16	7.47	0.162 (+0.039 = 0.201)	0.348 (+0.196 = 0.544)	2.17
	32	7.38	0.167 (+0.031 = 0.198)	0.389 (+0.157 = 0.546)	2.17
	54	7.33	0.174 (+0.027 = 0.201)	0.411 (+0.133 = 0.544)	2.17
	108	7.31	0.178 (+0.021 = 0.199)	0.437 (+0.106 = 0.543)	2.17
0.45	16	28.6	0.0410 (+0.0041 = 0.0451)	0.149 (+0.091 = 0.240)	5.5
	32	28.3	0.0423 (+0.0034 = 0.0457)	0.166 (+0.073 = 0.239)	5.6
	54	28.2	0.0431 (+0.0029 = 0.0460)	0.180 (+0.062 = 0.242)	5.6
	108	28.2	0.0437 (+0.0023 = 0.0460)	0.192 (+0.050 = 0.242)	5.6

Thus, the N -dependent corrections to the self-diffusion constant can be calculated at all densities in a simple way,

$$D_c = D_c(N) + (\eta/\eta_0) D_{\text{corr}}(N), \quad (47)$$

where $D_{\text{corr}}(N)$ is as given in Eq. (46). The corrections to D_c , calculated in this way, are shown in parentheses in Table 2. It can be seen that a consistent estimate of the thermodynamic limit of D_c is obtained for all system sizes and all packing fractions, verifying our assumptions *a posteriori*.

The number dependence of the collective mobility μ is similar to the single-particle mobility at low packing fractions, but is much smaller at high packing fractions. In fact, it was undetected in earlier, less accurate simulations (Phillips et al., 1988). The number dependence of μ can be quantitatively described in a similar fashion to the single-particle mobility by considering the sedimenting N -particle unit cell as a single particle of effective radius R_{eff} , where

$$R_{\text{eff}}/a = \mu_1/\mu. \quad (48)$$

Thus, our expression relating the infinite system mobility to the N -particle mobility is simply

$$\mu = \mu(N) + (\eta_0/\eta) (\mu/\mu_0) D_{\text{corr}} N/k_B T. \quad (49)$$

These corrections are also shown in parentheses in Table 2, and once again the estimates of the thermodynamic limit of the mobility are consistent. We believe the results quoted in Table 2 are within 1–2% of the exact results of the creeping-flow-fluid model. A more complete set of transport coefficients is shown in Figs. 1–4.

Results for the inverse permeability K^{-1} of a random assembly of spheres are shown in Fig. 1. Our results agree quite well with the Carman equation (Carman, 1937), which is an empirical fit to experimental data on fluid flow over

packed beds of spheres. There is an almost constant discrepancy of about 1.4 between the simulation results for K_0/K and the Carman equation, which would be undetectable at the higher packing fractions ($\phi > 0.6$) of the experiments. Our simulation results at low packing fraction ($\phi \leq 0.01$) agree, within numerical error, with the known asymptotic expansion (Kim and Russel, 1985)

$$K_0/K = 1 + \frac{3}{\sqrt{2}} \phi^{1/2} + \frac{135}{64} \phi \ln \phi + 16.456\phi, \quad (50)$$

but deviate significantly for packing fractions greater than about 0.1. The permeability derived from the Brinkman theory (Brinkman, 1947) is also shown in Fig. 1. It is consistently smaller than both the simulation results and the Carman equation, except at low packing fractions

($\phi \leq 0.1$). Attempts to improve the Brinkman theory at higher packing fractions (Tam, 1969; Itoh, 1983; Kim and Russel, 1985) do not lead to a significantly better agreement with the simulation results reported here.

Results for the collective mobility μ are shown in Fig. 2. Experimentally μ can be measured from the sedimentation velocity of the solid phase (Buscall et al., 1982; Bacri et al., 1986) or from long-wavelength light scattering (Cebula et al., 1981). In both cases, the experiments measure only the long time transport coefficients; the sedimentation experiments are steady state and the relaxation times probed by the light scattering experiments, proportional to $(Dk^2)^{-1}$, are long compared with the relaxation time for Brownian motion. There has been some question as to the difference between the long- and short-time mobilities (Beenakker and Mazur, 1984), but our results

Figure 1. Inverse permeability of suspended hard spheres. The solid circles are the simulation results; the solid line is the Carman correlation function (Carman, 1937), which is an empirical fit to experimental data at high packing fractions, and the dashed line is Brinkman's theoretical analysis (Brinkman, 1947).

show that the differences are in fact small, unlike the single-particle diffusion coefficient (Pusey and van Megen, 1983; Ottewill and Williams, 1987; van Megen and Underwood, 1989) and the shear viscosity (van der Werff et al., 1989). At low packing fractions, it is known that there is no difference between long- and short-time mobilities (Batchelor, 1972), and our simulation results are consistent with the theoretical value $A_H = 6.55$ (Batchelor, 1972; Cichocki and Felderhof, 1988). Experimentally, A_H tends to be smaller than the theoretical value (Bacri et al., 1986), which is thought to be due to van der Waals forces between

the spheres (Batchelor, 1972), which cause additional clustering at separations around $2a$. Our results indicate that there is little structural rearrangement during the sedimentation of a high-density microsphere suspension.

The dashed lines in Figs. 2-4 are theoretical results of Beenakker and Mazur (Beenakker, 1984; Beenakker and Mazur, 1984), based on calculating the hydrodynamic interactions between pairs of particles in an effective medium, which represents in an average way the many-body hydrodynamic interactions. The theoretical results are in good agreement overall with the simulations, particularly for the viscosity

(Beenakker, 1984) and self-diffusion coefficients (Beenakker and Mazur, 1984). The collective mobility (Beenakker and Mazur, 1984) is in less good agreement with the simulation results, but the worst discrepancy, around $\alpha = 0.25$, is still only about 20%.

The single-particle diffusion coefficient D_s is shown in Fig. 3. The experimental results are derived by light scattering from optically tagged particles (Pusey and van Megen, 1983; Ottewill and Williams, 1987; van Megen and Underwood, 1989). In these experiments, it is possible to measure the short-time transport coefficient so that the comparison between experiment and simulation should be precise. Our simulation results are in excellent agreement with the experiments of Pusey and van Megen (1983) and Ottewill and Williams (1987), but in less good agreement with the most recent experiments of van Megen and Underwood (1989). These diffusion constants are consistently smaller than those obtained in previous experiments but are within the range of uncertainty of the experimental results (van Megen and Underwood, 1989). Our simulation results lie within the range of the experimental data.

Finally, the high frequency viscosity is shown in Fig. 4. The experimental results of van der Werff et al. (1989) were derived from oscillating Couette viscometry. The results shown here correspond to a sufficiently high frequency that the solid particles are unaffected by the imposed shear flow, so that the distribution of configurations is just the equilibrium distribution assumed in the simulations. At the lower packing fractions ($\alpha < 0.35$), the experimental and simulation results are indistinguishable but, at high packing fractions, there is some spread in the experimental data depending on the particle size. The larger size particles tend to have the larger

Figure 2. Short-time sedimentation velocity (mobility) of suspended hard spheres. The solid circles are the simulation results; the open symbols are experimental results from Buscall et al. (1982), and Bacri et al. (1986). The dashed line is the theoretical analysis of Beenakker and Mazur (1984).

Figure 3. Short-time self-diffusion coefficient of suspended hard spheres. The solid circles are the simulation results; the open symbols are experimental results from Pusey and van Megen (1983), Ottewill and Williams (1987), and van Megen and Underwood (1989). The dashed line is the theoretical analysis of Beenakker and Mazur (1984).

viscosities that are in better agreement with our simulations than the results for smaller spheres.

An expression for the viscosity has been proposed by Bedeaux (1987)

$$\frac{\eta/\eta_0 - 1}{\eta/\eta_0 - \frac{1}{2}} = 0.1 + S(\phi), \quad (51)$$

which incorporates a mean-field description of the hydrodynamic interactions when $S(\phi) = 0$. Thus, a virial expansion of $S(\phi)$ should lead to a more rapidly converging viscosity than the usual expansion

of η/η_0 [Eq. (36)]. Van der Werff et al. used their experimental data to deduce an expansion for S ,

$$S(\phi) = (1.41 \pm 0.14)\phi - (1.19 \pm 0.34)\phi^2, \quad (52)$$

but this is inconsistent with the known second virial coefficient for hard-sphere dispersions (Cichocki and Felderhof, 1988; Ladd, 1989), which implies that, at low packing fractions, $S(\phi) \rightarrow 1.00\phi$. Our simulation data are fitted quite well over almost the whole density range by this simple expression for S . However, a best fit to the simulation data

includes small quadratic and cubic contributions,

$$S(\phi) = \phi + \phi^2 - 2.3\phi^3. \quad (53)$$

Since the viscosity is a rather insensitive function of S at low packing fractions, the difference in viscosity resulting from Eqs. (52) and (53) is negligible for $\phi \leq 0.35$. At higher packing fractions, Eq. (53) fits the simulation data and the 76 mm-sphere experimental data better than Eq. (52).

The excellent agreement between the transport coefficients derived from simulation and experiment is a confirmation of the accuracy with which it is now possible to calculate hydrodynamic interactions, using an *ab initio* method that does not include any adjustable parameters. Current computations require large amounts of computer time but improvements in algorithmic and numerical techniques, together with parallel-processing computers, should make these calculations more routine in the future.

Conclusion

We developed a method to calculate the many-body hydrodynamic forces between spherical particles suspended in an incompressible fluid. The perturbations in the fluid flow resulting from the presence of the solid particles can be approximated systematically, to any desired accuracy, in terms of moments of the induced-force density on the surface of each particle, combined with the pairwise-additive lubrication forces. We derived an expression for the suspension viscosity applicable to samples with periodic boundaries, and applied the resulting formula to calculations of the viscosity of random dispersions of spheres.

Our numerical results demonstrate that it is feasible, with current computer technology, to precisely

Figure 4. High frequency viscosity of suspensions of hard spheres. The solid circles are the simulation results; the open symbols are experimental results with different size spheres from van der Werff et al. (1989). The dashed line is Beenakker's theoretical analysis (1984).

calculate the hydrodynamic interactions between small numbers of spherical particles. At low-packing fractions, this means approximately 100 particles can be studied, but at high-packing fractions, when a large number of force moments are necessary, the number is reduced to less than 20. Nevertheless, we obtained accurate estimates for the transport properties of random dispersions of spheres, which are in excellent agreement with experimental results.

Future work may involve attempting to improve the convergence of the moment expansion by resuming

some of the neglected hydrodynamic interactions. This leads to a wavelength dependent viscosity that incorporates some of the short-range interactions (Beenakker and Mazur, 1983). However, our initial attempts have not been very encouraging. Alternatively, we may try to move away from integral equation formulations, which require excessive computational resources for large systems. Direct Navier-Stokes is not attractive because of the complex and constant problem of rezoning the system as the solid particles move; such simulations are usually

restricted to point-particle approximations (Fogelson and Peskin, 1988).

An interesting alternative is the use of lattice-gas cellular automata to model the fluid phase. Lattice-gas models are simplified molecular models, in which particles with a discrete set of velocities move from one node to another of a space-filling lattice, undergoing collisions with other particles occupying the same nodes. For a sufficiently large number of particles, these models are equivalent to the continuum Navier-Stokes equations, with the added advantage that thermal fluctuations, which give rise to Brownian motion, are also included (Ladd et al., 1988). The essential point of cellular automata is that they can be updated by local, logical rules and are, therefore, very well-suited for implementation on massively parallel computers consisting of logical microprocessors. The combination of particle models of the solid-phase and lattice-gas models of the fluid phase can handle the whole range of solid-fluid suspensions, from sub-micron particle sizes where Brownian motion is important to macroscopic size particles. Moreover, there is the possibility of studying gas-solid suspensions, where the fluid flow is often turbulent. Lattice-gas models can also be used to study fluid flow in porous media, both in packed-bed or pore geometries.

In the future, both the creeping-flow and lattice-gas computer-simulation models of the fluid phase will be used to study the rheological properties of suspensions. These simulations will incorporate the dynamical effects of the hydrodynamic forces on the structure of the suspension (Ermak and McCammon, 1978); these effects are crucial to quantitative predictions of suspension rheology.

References

- Bacri, J.-C., C. Frénois, M. Hoyos, R. Perzynski, N. Rakotomalala, and D. Salin (1986), "Acoustic Study of Suspension Sedimentation," *Europhys. Lett.* **2**(2), 123-128.
- Batchelor, G. K. (1972), "Sedimentation in a Dilute Dispersion of Spheres," *J. Fluid Mech.* **52**(2), 245-268.
- Batchelor, G. K. (1976), "Brownian Diffusion of Particles with Hydrodynamic Interaction," *J. Fluid Mech.* **74**(1), 1-29.
- Batchelor, G. K., and J. T. Green (1972), "The Determination of the Bulk Stress in a Suspension of Spherical Particles to Order C^2 ," *J. Fluid Mech.* **56**(3), 401-427.
- Bedeaux, D. (1987), "The Effective Viscosity for a Suspension of Spheres," *J. Colloid and Interface Sci.*, **118**(1), 80.
- Beenakker, C. W. J. (1984), "The Effective Viscosity of a Concentrated Suspension of Spheres (and its Relation to Diffusion)," *Physica* **128A**, 48-81.
- Beenakker, C. W. J., and P. Mazur (1983), "Self-Diffusion of Spheres in a Concentrated Suspension," *Physica* **120A**, 388-410.
- Beenakker, C. W. J., and P. Mazur (1984), "Diffusion of Spheres in a Concentrated Suspension II," *Physica* **126A**, 349-370.
- Brinkman, H. C. (1947), "A Calculation of the Viscous Force Exerted by a Flowing Fluid on a Dense Swarm of Particles," *Appl. Sci. Res.* **A1**, 27.
- Buscall, R., J. W. Goodwin, R. H. Ottewill, and T. F. Tadros (1982), "The Settling of Particles through Newtonian and Non-Newtonian Media," *J. Colloid Interface Sci.* **85**, 78.
- Carman, P. C. (1937), "Fluid Flow through Granular Beds," *Trans. Inst. Chem. Engrs.* **15**, 150.
- Cebula, D. J., R. H. Ottewill, J. Ralston, and P. N. Pusey (1981), "Investigations of Microemulsions by Light Scattering and Neutron Scattering," *J. Chem. Soc. Faraday Trans. 1* **77**, 2585-2612.
- Ciccotti, G., D. Frenkel, and I. R. McDonald (1987), *Simulation of Liquids and Solids*, (North-Holland, Amsterdam).
- Cichocki, B., and B. U. Felderhof (1988), "Short-Time Diffusion Coefficients and High Frequency Viscosity of Dilute Suspensions of Spherical Brownian Particles," *J. Chem. Phys.* **89**(2), 1049.
- Einstein, A. (1956), *Investigations on the Theory of the Brownian Movement*, (Dover Publications, New York).
- Ermak, D. L., and J. A. McCammon (1978), "Brownian Dynamics with Hydrodynamic Interactions," *J. Chem. Phys.* **69**(4), 1352.
- Felderhof, B. U. (1976), "Rheology of Polymer Suspensions: II. Translation, Rotation, and Viscosity," *Physica* **82A**, 611-622.
- Fogelson, A. L., and C. S. Peskin (1988), "A Fast Numerical Method for Solving the Three-Dimensional Stokes' Equations in the Presence of Suspended Particles," *J. Comp. Phys.* **79**, 50-69.
- Happel, J., and H. Brenner (1986), *Low-Reynolds Number Hydrodynamics* (Martinus Nijhoff, Dordrecht).
- Iasimato, H. (1959), "On the Periodic Fundamental Solutions of the Stokes Equations and their Application to Viscous Flow Past a Cubic Array of Spheres," *J. Fluid Mech.* **5**, 317.
- Itoh, S. (1983), "The Permeability of a Random Array of Identical Rigid-Spheres," *J. Phys. Soc. Japan* (Physical Society of Japan) **52**, 2379.
- Jeffrey, D. J., and Y. Onishi (1984), "Calculation of the Resistance and Mobility Functions for Two Unequal Rigid Spheres in Low-Reynolds-Number Flow," *J. Fluid Mech.* **139**, 261.
- Kim, S., and R. T. Mifflin (1985), "The Resistance and Mobility Functions of Two Equal Spheres in Low-Reynolds-Number Flow," *Phys. Fluids* **28**, 2033.
- Kim, S., and W. B. Russel (1985), "Modelling of Porous Media by Renormalization of the Stokes Equations," *J. Fluid Mech.* **154**, 269.
- Ladd, A. J. C. (1988), "Hydrodynamic Interactions in a Suspension of Spherical Particles," *J. Chem. Phys.* **88**(8), 5051.
- Ladd, A. J. C. (1989), "Hydrodynamic Interactions and the Viscosity of Suspensions of Freely Moving Spheres," *J. Chem. Phys.* **90**(2), 1149.
- Ladd, A. J. C., M. E. Colvin, and D. Frenkel (1988), "Application of Lattice-Gas Cellular Automata to the Brownian Motion of Solids in Suspension," *Phys. Rev. Lett.* **60**(11), 975.
- Ladd, A. J. C., and E. R. Smith (1989), unpublished work, Lawrence Livermore National Laboratory, Livermore, CA.
- Mazur, P., and W. Van Saarloos (1982), "Many-Sphere Hydrodynamic Interactions and Mobilities in a Suspension," *Physica* **115A**, 21-57.
- Ottewill, R. H., and N. St. J. Williams (1987), "Study of Particle Motion in Concentrated Dispersions by Tracer Diffusion," *Nature* **325**, 232.
- Phillips, R. J., J. F. Brady, and G. Bossis (1988), "Hydrodynamic Transport Properties of Hard-Sphere Dispersions. I. Suspensions of Freely Mobile Particles," *Phys. Fluids* **31**(12), 3462.

- Pollock E. L., and B. J. Alder (1980), "Static Dielectric Properties of Stockmayer Fluids," *Physica* **102A**, 1–21.
- Pusey, P. N., and W. van Meegen (1983), "Measurement of the Short-Time Self-Mobility of Particles in Concentrated Suspension. Evidence for Many-Particle Hydrodynamic Interactions," *J. Physique (Paris)* **44**, 285–291.
- Russel, W. B., and A. P. Gast (1986), "Nonequilibrium Statistical Mechanics of Concentrated Colloidal Dispersions: Hard Spheres in Weak Flows," *J. Chem. Phys.* **84**(3), 1815.
- Tam, C. K. W. (1969), "The Drag on a Cloud of Spherical Particles in Low Reynolds Number Flow," *J. Fluid Mech.* **38**(3), 537–546.
- van Meegen, W., and S. M. Underwood (1989), "Tracer Diffusion in Concentrated Colloidal Dispersions. III. Mean Squared Displacements and Self-Diffusion Coefficients," *J. Chem. Phys.* **91**(1), 552.
- van der Werff, J. C., C. G. de Kruif, C. Blom, and J. Mellema (1989), "Linear Viscoelastic Behavior of Dense Hard-Sphere Dispersions," *Phys. Rev. A* **39**(2), 795.
- Wagner, N. J., and W. B. Russel (1989), "Nonequilibrium Statistical Mechanics of Concentrated Colloidal Dispersions: Hard Spheres in Weak Flows with Many-Body Thermodynamic Interactions," *Physica* **155A**, 475–518.

New Method to Analyze Fluid-Driven Fracturing in Jointed Rocks

François E. Heuzé, Ronald J. Shaffer,
and Stephen C. Blair

Unconventional Gas Program

We have developed a new method of analysis to describe the propagation of induced fluid-driven fractures in rock masses that contain pre-existing discontinuities such as joints, faults, bed interfaces, and lens boundaries. The analysis is based on a two-dimensional time-dependent model, with coupled solid mechanics, fracture mechanics, and fluid dynamics. The solid and fracture mechanics are solved by an implicit finite element approach that provides for mixed-mode (I and II) fracture propagation in arbitrary stress fields. The pressure profile inside the crack and the crack velocity are provided by a one-dimensional analytical formulation, corresponding to a constant-height fracture. Both arbitrary flow-rate and constant borehole pressure conditions can be simulated; these may correspond, respectively, to conventional two-wing hydrofracturing and to gas-driven tailored-pulse loading for multiple fractures. We have verified the model against analytical time-dependent solutions for fracturing in permeable and impermeable media. This new coupled model has also been validated against controlled physical tests in which we hydrofractured blocks containing sandstone lenses. These blocks were loaded independently in three orthogonal directions, and the fracture in each was tracked in space and time. These new analysis tools can be used in a wide variety of applications that include obtaining a better understanding of the stimulation of unconventional gas reservoirs (i.e., lenticular sandstones, coal beds, and Devonian shale), or making improvements in the design of underground waste disposal by hydrofracturing, or enhancing the fracturing of geothermal reservoirs.

Fracturing rocks underground, using pressurized fluids, is a common procedure for attempting to enhance the productivity of certain gas and oil reservoirs (Veatch, 1983a,b; Mendelsohn, 1984a,b; Cleary, 1988; Boone et al., 1989) and for estimating in situ stresses in rock masses (National Research Council, 1983). This procedure has also been used to dispose of unwanted liquid wastes (Weeren et al., 1982). A significant number of mathematical simulations have been developed to assist in designing

such fracturing injections; excellent overviews of these models have been published by Veatch (1983a,b), Mendelsohn (1984a,b), and Cleary (1988).

The remarkable common thread throughout these models is that they assume the rock medium to be continuous. This is significant because it is well-known that rock masses in place are seldom, even approximately, continuous; typically, they are transected by all manner of discontinuities (e.g., joints, shear zones, faults, bedding contacts,

and lens boundaries). More importantly, it is also known that these interfaces can have a strong detrimental effect on our ability to control and extend fluid-driven fractures. Recent innovative field tests involving a "mine-back" of fracture paths have provided vivid documentation of fractures stopping at interfaces, branching out sideways, or reinitiating in a stepped fashion after stopping at a contact (Warpinski, 1985).

With the above considerations in mind, we have pursued a course

of development and validation of new analysis methods to describe the propagation of fluid-driven fractures in discontinuous media (Heuzé, 1986; Heuzé, 1987). These methods are embodied in FEFFLAP (Finite Element Fracture and Flow Analysis Program), which is a two-dimensional implicit numerical model with capabilities to simulate steady state flow in fractures and joints, as well as time-dependent fluid-driven fracturing.

Steady State Analysis

The steady state model, FEFFLAP Version 1.0, was constructed from several building blocks to achieve a capability for simulating coupled solid mechanics, fracture mechanics, and flow analysis. The components assembled into this new model were as follows:

- The FEAP two-dimensional implicit finite element program for solid and fracture mechanics (Ingraffea et al., 1984), which modeled only continuous media.
- The joint finite elements with sophisticated constitutive laws as developed in the JPLAXD code (Heuzé, 1981), which were incorporated in FEAP.
- The flow-in-fracture algorithms contained in the JFLOW finite element model (Noorshad et al., 1971).

The fracture mechanics algorithms, the joint models, the flow equations, and the logic to couple the analysis are reported in detail by Ingraffea et al. (1985) and Shaffer et al. (1985). The verification against analytical results (Sih, 1973; Ouchterlony, 1982), and the validation against physical model tests are also extensively documented (Thorpe et al., 1984; Shaffer et al., 1984). This information is not repeated here because this earlier work was considered to be a prelude to developing the time-dependent analysis.

Time-Dependent Model

Rationale for the New Developments

The value of developing the steady state model was two-fold:

- To establish the procedure for coupling solid/fracture mechanics and fluid flow analyses.
- To provide some interesting insights into the interplay between induced fractures and natural fractures.

However, this model could not provide the crucial diagnostics that are needed in the field during the execution of underground fracturing. That is, it would be valuable to be able to use time-pressure records in the field to determine the type of interaction a fluid-driven fracture is experiencing with a rock mass and to answer questions such as:

- Is the fracture stopped for a time?
- Is it branching-out laterally?
- Is it restarting after an offset at an interface?

These questions are particularly relevant when stimulating sandstone lenses away from wells or when containing a hydrofracture within a given horizon.

We pursued the time-dependent developments of our analyses with the expectation of providing a measure of this forward modeling capability that would show features of time-pressure records corresponding to induced/natural fracture interactions. The new flow model is represented by the FAST (Fracturing and Simultaneous Transport) program (Nilson and Peterka, 1986), which is now part of our FEFFLAP Version 2.0 model.

The FAST formulation that we adopted was developed for wedge-shaped fractures of constant height, i.e., the Geertsma-DeKlerk type (Geertsma and DeKlerk, 1969) in which the fluid flow along the fracture can be described by a

one-dimensional analysis where the fluid pressure, temperature, and velocity depend on a single independent variable, which is the position along the crack length. The mathematics of this flow model are described by Nilson and Peterka (1986).

The Coupling of FAST to FEFFLAP

We begin a time step with the crack tip located at a fixed point on the grid, as determined from FEFFLAP's solid/fracture analysis. FAST then generates a provisional solution, including the pressure profile along the crack and the propagation speed. FEFFLAP, in turn, calculates new values of crack width w and stress intensity factor K_I , corresponding to the new pressure profile. Next, FAST uses the new values of w , K_I , and pressure to generate a better candidate for the pressure profile, and so on. We determine the progress of iterations by monitoring the convergence of the pressure profile and stress intensity.

FAST only uses the Mode I stress intensity factor to adjust the pressure profile, because FAST is modeling a crack propagating in-plane. However, FEFFLAP does not have this restriction; therefore, it can propagate cracks in mixed-mode. At the end of a FAST cycle, a new crack direction can be determined by FEFFLAP, if warranted. Thus, the effect of the FAST limitation is only to restrict crack propagation to linear increments. The overall fracture can still curve, as guided by the stress field and material properties.

To model the interaction among multiple fractures, we developed a procedure that allows FAST to process one crack at a time, thereby, obtaining a new pressure profile for each crack. Once pressure boundary

conditions have been determined for all the cracks, FEFFLAP simultaneously calculates the displacements along all the cracks so that any one crack can influence all the others. The algorithms are written in a fashion that allows the user to monitor the progress of the calculations and interactively tailor the iteration sequence to obtain better convergence.

When the FAST/FEFFLAP iterations have reached the desired degree of convergence, the problem is advanced by a time increment Δt . At this point, tip speeds L are available for all of the cracks, and FEFFLAP has determined the direction of propagation for each. Thus, if necessary, each of the cracks can be shifted forward by $\Delta L = L\Delta t$, in the direction appropriate for mixed-mode fracture.

Verification and Validation of FEFFLAP 2.0/FAST

Analytical Solution for Gas-Driven Fractures with Constant Borehole Pressure

Figure 1 shows a geometry of interest for gas-driven fracturing from a borehole in which two fractures have begun to dominate. We performed a FEFFLAP analysis of that geometry with the following conditions:

- Borehole radius, 0.1 m
- Borehole pressure, 40 MPa
- Borehole temperature, 300 K
- Confining stress, 10 MPa
- Fracture toughness, 0
- Shear modulus, 3 GPa
- Poisson's ratio, 0.3
- Surface roughness, 400 μm
- Rock porosity, 0.3
- Gas viscosity, 10^{-5} Pa-s
- Molecular weight, 28
- Ambient pore pressure, 0.1 MPa.

We assumed that the rock permeability was negligible so that it

could be compared with an analytical, self-similar solution for the extension of the major cracks (Nilson, 1981). Figure 2 shows good agreement between the FEFFLAP computation of the crack speed gradient

and the analytical solution at a crack length exceeding five borehole diameters (note that the similarity solution requires the cracks to be long with respect to borehole diameter).

Figure 1. Geometry for FEFFLAP/FAST analysis of multiple gas-driven fractures.

Figure 2. Comparison of FEFFLAP results with those of a similarity solution (Nilson, 1981).

Analytical Solutions for Laminar Incompressible Fluid Flow with Constant Flow Rate

Geertsma and DeKlerk analytically obtained approximate solutions for a two-wing wedge-shaped fracture driven by the laminar flow of an incompressible fluid injected at constant flow rate (Geertsma and DeKlerk, 1969). At early times, seepage losses are negligible, and the fracture growth can be expressed as a fraction of crack speed L :

$$L = \frac{2}{3} \left\{ 0.48 \left[\frac{GQ^3}{(1-\nu)\mu} \right]^{1/3} \right\}^{3/2} \times \left(\frac{1}{L} \right)^{1/2} \quad (\text{early}) \quad (1)$$

where G is the elastic shear modulus of the medium, Q is the flow rate, ν is the rock's Poisson ratio, and μ is the fluid's viscosity.

At late times, seepage losses change the growth to:

$$L = \frac{1}{2} \left(\frac{Q}{2\pi C} \right)^{2/3} \frac{1}{L} \quad (\text{late}) \quad (2)$$

where C is the Carter seepage loss coefficient (Howard and Fast, 1970).

In Fig. 4, we compare results of FAST calculations in stand-alone, and FEFFLAP 2.0/FAST with the mesh of Fig. 3, to the above analytical results. The agreement is excellent over a wide range of fracture speeds and lengths. This is true even though the FEFFLAP code does not include the inertial effects of the solids; however, the maximum calculated crack speeds were no more than about 100 m/s, which is a small fraction of the shear wave speed. Other models could be used to estimate the importance of these effects at much higher crack speeds (Svenson and Ingraffea, 1987).

Validation against Physical Block Tests

Recently, we performed sophisticated block tests at LLNL to provide physical benchmarks against which

Figure 3. Close-up view of mesh for a FEFFLAP 2.0 calculation near the borehole with a constant flow rate.

Figure 4. FEFFLAP 2.0 results compared with FAST and with analytical flow rate results from Geertsma and DeKlerk (1969).

to validate our numerical developments (see Blair et al., 1989 and Heuzé et al., 1989 for details).

We tested three gypsum cement blocks (A, B, and C) in which we had embedded sandstone tablets (lenses) (Fig. 5). These experiments revealed the progression of fluid-driven fractures through the sandstone lenses.

These fractures were forced to initiate and propagate from a high-pressure steel tube that was slotted on one side.

A wrap-around tape, extending out about 2 cm, kept the gypsum cement from entering the slot while the block was being cast, and also directed the crack into a

sympathetic stress field. The fractures were constrained to travel unilaterally, and the fracture front was determined by resistance changes denoted by the rupture of thin tungsten wires embedded perpendicular to the fracture plane.

To maintain constant height, the fracture was contained in the vertical direction by wire mesh screens embedded near the top and bottom of the block and perpendicular to the injection tube. The screens and sandstone lenses were anchored using piano wire stretched across each mold.

The gypsum cement was prepared carefully, according to pre-planned sifting, wetting, mixing, and pouring procedures. A light oil was used to propagate the fracture, and it was pumped at a steady rate with a ball-screw piston. The blocks were triaxially loaded for the duration of crack propagation.

The injection pressure was closely monitored during the fracturing process.

Figure 6, corresponding to test B, is given as an example to provide data for comparison with calculations. Crack velocity was estimated from the breakage times of the embedded wires (points A and B on Fig. 6). After fracturing, the blocks were dissected to show the exact fracture outline, as well as the extent of leakoff. Dissection of the blocks showed them to be very homogeneous.

A cross section representing the gypsum block geometry was meshed for analysis with FEFFLAP and is shown in Fig. 7. First, two calculations were performed without modeling the steel injection tube. The cracks were advanced to the times when they just reached the sandstone lens. Crack length at this point was 12.7 cm. Propagation was

not continued through the lens in the calculation because the sandstone is more permeable. We believe that the crack essentially stopped in the experiment while fluid filled the lens, and then it restarted. The current version of FEFFLAP does not have a flow storage capability to model such a phenomenon.

A pressure-time curve was generated from the successive crack tip locations during propagation. For comparison, we superimposed the curve over the experiment record (Fig. 6). Early pressures are not expected to compare well because of the steel tube and tape used to start and initially direct the fracture. In fact, the tip location next to the borehole where the crack initiated is not included in the curve because the pressure was not calculated owing to the coarseness of the finite element mesh at that location. Later pressures compare well with the experimental results.

The pressure profile down the crack and the crack shape from the numerical results at 11.5 cm (largest crack length before the interface is intersected) are shown in Figs. 8 and 9, respectively; results are given for both permeabilities, $k = 3.3$ and 15 millidarcy (mD). When the crack reached 11.5 cm, the fluid front had just reached the tip of the propagating crack at the highest leakoff rate, but it had already arrived at the tip at the lower leakoff rate. However, at early times (not shown) the fluid did not reach the crack tip for either permeability. The pressure profile is slightly higher near the borehole for greater leakoff. For either value of k , pressure falls off rather quickly because of leakoff. Notice the ballooning of the crack, a feature of a single-wing crack in which the borehole constrains one end of the crack. This ballooning is not significantly influenced by the value of k .

Figure 5. Schematic of block-fracturing experiments. The blocks are under three independent compressive stresses (σ_1 , σ_2 , and σ_3).

Figure 6. Pressure-time record for test B compared with FEFFLAP pressure-time history.

Figure 7. Finite element mesh for FEFFLAP 2.0 analysis of a crack propagating from a borehole to a sandstone lens in a gypsum block.

Figure 8. Pressure profiles as a crack nears a lens for two values of permeability.

Figure 9. Crack shape as it nears a lens for two values of permeability.

Figure 10. Decay of the crack tip velocity as the crack extends ($k = 3.3$ mD). The experimental value corresponds to an average value computed between points A and B in Fig. 6.

Figure 10 shows the calculated crack tip velocity as a function of crack length for $k = 3.3$ mD. Crack velocity decreases quickly as the crack extends, and then decreases slowly. At later times, the crack velocity agrees very well with the experimental value determined from points A and B on Fig. 6 (where the wires broke). We noted that, for $k = 15$ mD, the late-time crack tip velocity was slowed by a factor of 44, but fluid velocity at the inlet was slowed by only 3%. Another calculation with $k = 3.3$ mD was performed that included the elastic effects of the steel tube in the borehole. In this case, the early crack extension required a higher pressure, as shown

by Point P₁ on Fig. 6, owing to the higher stiffness of the tube. The pressure is in reasonable agreement with the experimental value. At late times, the effects of the tube should be minimal.

Examples of Application

To illustrate the capabilities of the time-dependent model, FEFFLAP 2.0 was set up to simulate the gas-driven development of multiple fractures around boreholes, as can be performed to stimulate gas-well production with solid propellants.

First, we ran a symmetric problem in which six cracks were made to emanate from a borehole at 60°

intervals (Fig. 11). We chose this geometry because all cracks are identical. Cracks can be extended in the model by either specifying a length or a time of propagation (the model then returns the corresponding time or length). In this test case, the cracks were extended by specifying an equal length for each. Once the crack length is specified, all the other values are calculated in the FEFFLAP model. If the FEFFLAP model is working correctly, it will return the same parametric values for all the cracks. These parametric values are given in Table 1 for the upper three cracks shown in Fig. 11. From symmetry, the values for the lower three cracks are identical to those for the upper three cracks. The aperture represents the crack opening at the borehole. All parameters agree well. Since the cracks have the same speed, they will extend together and remain equal in length.

After this first check had been performed on the model, less symmetric problems were addressed. We made a small change in the previous configuration, by making one of the cracks shorter. For this problem, the cracks were propagated again in their own plane. The FEFFLAP solution is shown in Fig. 12. The smaller aperture of the shorter crack is clearly seen. Parametric values for this case are given in Table 2. It is interesting to note that although the short cracks are 60% of the length of the longer cracks, their speed is about one-third of that of the longer cracks. This means that the shorter cracks will die out quickly in favor of the longer cracks.

Figure 13 illustrates what happens when even less symmetric cracking takes place. The cracks that are close to each other tend to repel each other. To our knowledge, this result has not been obtained before. In this example, crack tip speed was ~10% of shear-wave speed.

Table 1. Parametric values for a six-fold symmetric crack problem.

Crack No.	Time (s)	Length (m)	Speed (m/s)	Aperture (cm)
1	0.003324	0.403	177.5	0.189
2	0.003300	0.400	176.4	0.188
3	0.003316	0.402	178.9	0.190

< Figure 11. Six-fold symmetric cracking from a borehole. All cracks propagate radially outward at the same speed.

Table 2. Parametric values for a two-fold symmetric crack problem.

Crack No.	Time (s)	Length (m)	Speed (m/s)	Aperture (cm)
1	0.003422	0.407	232.4	0.222
2	0.002005	0.243	84.6	0.085
3	0.003408	0.405	232.9	0.221

< Figure 12. Two-fold symmetric cracking from a borehole. The long cracks are extending nearly three times faster than the short cracks.

< Figure 13. Cracking from a borehole in which propagating cracks repel each other.

Summary

We have pursued a joint numerical and experimental program designed to gain insight into the interactions between induced fluid-driven fractures and natural discontinuities in rock masses.

The numerical developments resulted from the coupling of several building blocks:

- A solid and fracture mechanics model capable of representing mixed-mode fracture propagation in arbitrary stress fields.
- Models of rock discontinuities that account for nonlinear joint behavior.
- Models of fluid flow for both liquids and gases, covering the steady state as well as the transient time-domain.

These models have been verified against analytical solutions for fluid-driven cracks. In addition, a measure of validation of these numerical models was achieved by comparing them with the results of physical experiments, which consisted of blocks of different rock simulants, with interfaces and/or inclusions that were hydraulically fractured. The calculated fracture paths and pressure-time histories compared well with results obtained using the physical model.

Although a plethora of hydrofracture simulation models exist that are based on continuum assumptions, we believe that the above developments are thus far unique in tackling fluid-driven

fracturing in discontinuous media. On the other hand, we are well aware of the limitations of these methods, which do not account for the following:

- The three-dimensional effects.
- The potential effects of solid inertia at very high crack speeds.
- The storage of fluid in the medium.

In addition, the models have not been validated for the apportioning of the flow between several cracks evolving dynamically from an intersection.

Clearly, the field of simulation of fluid-fracturing in real rock masses continues to be rich in opportunities for significant future developments.

References

- Boone, T. J., A. R. Ingraffea, and J. C. Roegiers (1989), "Visualization of Hydraulically-Driven Fracture Propagation in Poroelastic Media Using a Superworkstation," *J. Petroleum Technol.*, 574-580 (June).
- Blair, S. C., R. K. Thorpe, F. E. Heuzé, and R. J. Shaffer (1989), "Laboratory Observations of the Effect of Geologic Discontinuities on Hydrofracture Propagation," in the *Proc. of the 30th U.S. Symposium on Rock Mechanics, Morgantown, WV* (A. A. Balkema, Brookfield, VT), pp. 443-450.
- Cleary, M. P. (1988), "The Engineering of Hydraulic Fractures. State of the Art, and Technology of the Future," *J. Petroleum Technol.*, 13-21 (Jan.).
- Geertsma, J., and F. DeKlerk (1969), "A Rapid Method for Predicting the Width and Extent of Hydraulically Induced Fractures," *J. Petroleum Technol.*, 21, 1571-1581.
- Heuzé, F. E. (1981), *JPLAXD: A Finite Element Program for Static, Plane and Axisymmetric Analysis of Structures in Jointed Rock*, Lawrence Livermore National Laboratory, Livermore, CA, UCID-19047.
- Heuzé, F. E. (1986), *The Unconventional Gas Program at the Lawrence Livermore National Laboratory*, Lawrence Livermore National Laboratory, Livermore, CA, UCID-20610.
- Heuzé, F. E. (1987), *Status of the Western Gas Sands Project at Lawrence Livermore National Laboratory*, Lawrence Livermore National Laboratory, Livermore, CA, UCID-21108.
- Heuzé, F. E., R. J. Shaffer, S. C. Blair, and R. K. Thorpe (1989), *Understanding the Effect of Natural Fractures on the Hydrofracture Stimulation of Natural Gas Reservoirs*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-100229. Also available as SPE 18956, *SPE Joint Rocky Mountain Regional Meeting and Low Permeability Reservoir Symposium*, Denver, CO (March).
- Howard, G. C., and C. R. Fast (1970), "Hydraulic Fracturing," *Monograph Vol. 2* (Soc. Petroleum Eng., Richardson, TX).
- Ingraffea, A. R., W. Gerstle, P. Gergely, and V. Saouma (1984), "Fracture Mechanics of Bond in Reinforced Concrete," *ASCE J. Struct. Div.* 110(4), 871-890.
- Ingraffea, A. R., R. J. Shaffer, and F. E. Heuzé (1985), *FEFFLAP: A Finite Element Program for Analysis of Fluid-Driven Fracture Propagation in Jointed Rock. Vol. 1: Theory and Programmer's Manual*, Lawrence Livermore National Laboratory, Livermore, CA, UCID-20368.
- Mendelsohn, D. A. (1984a), "A Review of Hydraulic Fracture Modeling—Part 1: General Concepts, 2D Models, Motivation for 3D Modeling," *ASME J. Energy Resources Technol.* 106, 369-376.
- Mendelsohn, D. A. (1984b), "A Review of Hydraulic Fracture Modeling—Part 2: 3D Modeling and Vertical Growth in Layered Rock," *ASME J. Energy Resources Technol.* 106, 543-553.

- National Research Council (1983), "Hydraulic Fracturing Stress Measurements," *Proceedings of a Workshop* (National Academy Press, Washington, DC).
- Nilson, R. H. (1981), "Gas-Driven Fracture Propagation," *ASME J. Applied Mechanics* **45**, 757-762.
- Nilson, R. H., and D. L. Peterka (1986), *User's Manual for the FAST Hydrofracture Code*, Lawrence Livermore National Laboratory, Livermore, CA, prepared by S-Cubed, La Jolla, CA, UCRL-15852.
- Noorishad, J., P. A. Witherspoon, and T. L. Brekke (1971), "A Method for Coupled Stress and Flow Analysis of Fractured Rock Masses," *Geotechnical Eng. Publ. No. 71-6*, University of California, Berkeley, CA.
- Ouchterlony, F. (1982), "Analysis of Cracks Related to Rock Fragmentation," *Part I of Lectures at the International Center for Mechanical Sciences (CISM), Udine, Italy*, DS 1982-4.
- Shaffer, R. J., R. K. Thorpe, A. R. Ingraffea, and F. E. Heuzé (1984), "Numerical and Physical Studies of Fluid-Driven Fracture Propagation in Jointed Rock," in *Proc. of the 25th U.S. Symposium on Rock Mechanics*, Evanston, IL (Soc. Mining Eng., Littleton, CO), pp. 117-126.
- Shaffer, R. J., A. R. Ingraffea, and F. E. Heuzé (1985), "FEFLAP" *A Finite Element Program for Analysis of Fluid-Driven Fracture Propagation in Jointed Rock, Vol. 2: User's Manual and Model Verification*, Lawrence Livermore National Laboratory, Livermore, CA, UCID-20369.
- Sih, G. C. (1973), *Handbook of Stress Intensity Factors*, Institute of Fracture and Solid Mechanics, Lehigh University, Bethlehem, PA.
- Swenson, D. V., and A. R. Ingraffea (1987), "A Finite Element Model of Dynamic Crack Propagation with an Application to Intersecting Cracks," in *Proc. of the 4th Int. Conf. Numerical Meth. in Fract. Mech.*, San Antonio, TX, March 2-27 (Pineridge Press, Swansea, U.K.), pp. 191-204.
- Thorpe, R. K., F. E. Heuzé, and R. J. Shaffer (1984), *An Experimental Study of Hydraulic Fracture-Interface Interaction*, Lawrence Livermore National Laboratory, Livermore, CA, UCID-20114.
- Veatch, R. W. (1983a), "Overview of Current Hydraulic Fracturing Design and Treatment Technology—Part 1," *J. Petroleum Technol.*, 677-687 (April).
- Veatch, R. W. (1983b), "Overview of Current Hydraulic Fracturing Design and Treatment Technology—Part 2," *J. Petroleum Technol.*, 853-864 (May).
- Warpinski, N. R. (1985), *In-Situ Measurements of Hydraulic Fracture Behavior: PTE-3 Final Report*, Sandia National Laboratory, Albuquerque, NM, SAND 83-1826.
- Weeren, H. O., J. H. Coobs, C. S. Haase, R. J. Sun, and T. Tamura (1982), *Disposal of Radioactive Wastes by Hydraulic Fracturing*, Oak Ridge National Laboratory, Oak Ridge, TN, ORNL/CF-81/245.

Discriminating between Nuclear Explosions and Earthquakes

Steven R. Taylor

Seismic Research Group

Verification of a Low Yield Threshold Test Ban Treaty or a Comprehensive Test Ban Treaty will require the use of in-country seismic stations. One aspect of in-country monitoring involves using regional seismic signals to discriminate between nuclear explosions and earthquakes. To evaluate our discrimination capabilities, we employed a multivariate analysis technique to comprehensively study a large number of Nevada Test Site nuclear explosions and western United States earthquakes. We are currently analyzing events that were misclassified so that we can assess opportunities for evasion and also obtain a better physical understanding of how the discriminants work. We are also investigating the application of artificial neural networks to the discrimination problem.

The primary mission of the seismic verification program at LLNL is to improve this nation's ability to monitor and verify treaties limiting or banning nuclear tests. The two treaties currently in effect are:

- The Threshold Test Ban Treaty (TTBT).
- The Peaceful Nuclear Explosion Treaty (PNET).

Two possible future treaties are:

- A Low-Yield Threshold Test Ban Treaty (LYTTBT).
- A Comprehensive Threshold Test Ban Treaty (CTBT).

Our work is carried out primarily for the Office of Arms Control of the U.S. Department of Energy (DOE).

Our seismic research program mainly addresses the following verification issues:

- Detection and location of events.
- Discrimination between earthquakes and explosions.
- Yield estimation of nuclear explosions.

The emphasis of our program is on developing seismic techniques for monitoring a LYTTBT and possibly a CTBT; both will require the use

of in-country seismic monitoring stations to collect data. Thus, it is necessary to develop the capability to detect and identify seismic events having small magnitudes ($m_b > 2.5$) and occurring at regional distances (< 2000 km) from the station. Effective discrimination for events with Richter magnitudes of $\sim 4.0 - 4.5$ at teleseismic distances (> 2000 km) appears to be feasible with today's instruments and analytical methods (Dahlman and Israelson, 1977). This magnitude range corresponds to yields of 1–5 kt for explosions detonated in hard rock. However, discrimination of small-magnitude events that are not recorded at teleseismic distances is more complicated, and more research is needed to devise techniques for analyzing and interpreting the data recorded by seismic stations at regional distances.

Although "effective discrimination" involves both technical determinations and policy judgments, the emphasis of this discussion is on the technical aspects of using seismic signals to discriminate between earthquakes and nuclear explosions.

In monitoring a CTBT, it will be necessary to extend the discrimination to smaller magnitude events recorded at regional distances from an in-country seismic network. Pomeroy et al. (1982) summarized the use of regional seismic discriminants and concluded:

"most have been tested only on limited data, usually from one geographic region and only one or two recording stations. No systematic analyses have been done to determine the best individual discriminant or combination of them."

Their major conclusion stated:

"a systematic and comparative evaluation of all the proposed regional discriminants is now required, utilizing a common data base derived from all present-day test sites. This evaluation would suggest the optimal discrimination procedure using regional waves and would also define areas of needed research."

To explore the issue of regional discrimination, we analyzed seismic signals from a large number of western United States earthquakes and explosions (Taylor et al., 1989). These signals were recorded by four broadband seismic stations operated by LLNL. Using these data, we systematically evaluated 12 of the most promising of the regional discriminants outlined in Pomeroy et al. (1982). In this study, we closely followed the descriptions given in previous studies (i.e., filtering the broadband data to simulate the different instruments used in the original studies, and taking measurements in the same velocity windows and frequency bands).

We use a multivariate analysis technique to analyze (1) the performance of individual discriminants and (2) the performance of combinations of discriminants from individual stations and from the four-station network.

Our studies include determining the impact of source, path, and receiver effects on different discriminants. This research is currently being extended to include new and modified discriminants using our broadband capabilities with improved propagation corrections and measurement parameters. We are also closely examining misclassified events to discover why they were misclassified. This information will help us assess opportunities for evasion and possibilities for issuing false alarms. Our seismic discrimination studies include an evaluation of the utility of new recognition algorithms such as artificial neural networks (ANN).

The data set for this study consists of 233 Nevada Test Site (NTS) explosions and 130 western U. S. earthquakes in the magnitude range of ~2.5 to 6.5 recorded at four broadband seismic stations operated by LLNL (Fig. 1). These

stations surround NTS at distances of ~200 to 400 km, and they are routinely used to obtain rapid estimates of explosion yields. The propagation paths for the earthquakes range from ~175 to 1300 km and are confined mainly to the Basin and Range.

The earthquakes in our data set occurred between 1979 and 1985. Generally they lie in the magnitude range of ~2.5 to 6.5 and are at regional distances to the LLNL stations (~175 to 1300 km). The explosions occurred between 1969 and 1984 and span approximately the same magnitude range as the earthquakes.

Physical Basis of Discrimination

Most of the discriminants that we evaluated are based on the expected physical differences between earthquakes and explosions. For example, earthquakes result from the sudden release of stored elastic energy along a fault surface. The shearing along the rupture surface releases a large amount of shear energy relative to compressional energy. Thus, the shear phases (S , L_v , Rayleigh, and Love) are expected to be large relative to the compressional phases (P and P_g). In contrast, a pure explosion

Figure 1. Map of the western U.S. showing the location of the earthquakes and explosions used in this study. The distances from NTS to the four LLNL stations are approximately: ELK: 400 km, KNB: 292 km, LAC: 313 km, and MNV: 226 km.

source is a center of compression and, in theory, releases only P waves and vertical-component surface waves (surface waves are generated from the complex interaction of the curved wavefront with the free surface). A typical explosion seismogram is therefore expected to have much more compressional energy relative to the late-arriving shear energy.

Earthquakes and explosions are also expected to have different time histories associated with their energy releases; as a result, they will radiate different spectral shapes. These spectral shapes are also critically dependent on the physical properties of the near-source material and on secondary effects such as spallation of the surface layers above an explosion.

Transportability of U.S. Developed Discriminants

In the western U.S., we have observed that the earthquakes are generally richer in high frequencies relative to explosions of the same size; this observation forms the basis for a promising discriminant. However, because much of the Soviet Union's crust has significantly different geophysical properties than those found in the western U.S., we may actually see the opposite pattern in the Soviet Union.

This raises another important issue: the transportability of discriminants developed in our work to studies in the Soviet Union. We already know that the seismic-signal propagation characteristics in much of the Soviet Union are

significantly different than those in the western U.S. We also suspect that source and near-source effects may also differ. Thus, a discriminant that works well in the western U.S. may prove to be disappointing in the Soviet Union. It is necessary to have a good physical understanding of how these discriminants work in order to evaluate their performance in other geophysical regions and to assess possible opportunities for evasion.

Figure 2 shows examples of seismograms and associated spectra for an earthquake and explosion of similar sizes ($m_b \sim 4.2$) occurring at NTS and recorded at the station ELK. The earthquake is characterized by strong, late-arriving surface waves that are poorly developed for the explosions. This is the basis

Figure 2. (a) Examples of seismograms and spectra from an earthquake and a nuclear explosion of similar sizes ($m_b \sim 4.2$) both occurring on NTS and recorded at the station ELK. Note that the large, late-arriving surface waves from the earthquake are poorly developed for the explosion (although the relative amplitudes for the other phases are similar); this is the basis of the $m_b - M_s$ discriminant. (b) L_x spectra from the (a) seismograms. Note the existence of more high frequency energy for the earthquake relative to the explosion; this is the basis of the spectral-ratio discriminant.

of the $m_p - M_s$ discriminant: for an earthquake and an explosion of similar m_p , the earthquake will generally have a greater M_s .

Spectral differences are also observed between the two sources. Although the low frequency spectral levels are similar, the earthquake is characterized by more high frequency energy than the explosion.

Assessment of Individual Discriminants

We selected 12 regional discriminants from Pomeroy et al. (1982) that appeared to have promising discrimination potential. These

can be divided into three broad categories:

- Long-period time-domain amplitudes.
- Short-period time-domain amplitudes.
- Spectral ratios.

The long-period amplitudes use the ratios of the surface-wave to body-wave amplitudes and include both measurements of Love and Rayleigh waves and of higher mode surface waves. The short-period discriminants consist of amplitude ratios of the prominent regional phases (such as L_g to P_g). The spectral ratios were generally formed by comparing the frequency content in

different frequency bands for a given phase.

The onset times of P_w , P_g , and L_g were measured by an analyst and were used to define measurement windows for certain discriminants. Thus, a total of 144 measurements (based on 36 variables per station $\times$ 4 stations) was possible for each event. However, because of problems such as weak signals, recording or processing errors, and station unavailability, none of the events has a complete set of reliable measurements.

Examples of discriminants averaged for the four-station network are illustrated in Fig. 3. Two of the

Figure 3. Network-averaged discriminants plotted vs body-wave magnitude (m_b). (a) Rayleigh-wave amplitude, (b) Love-wave energy, (c) L_g/P_g amplitude ratio, and (d) L_g spectral ratio.

plots in Fig. 3 (a and b) illustrate the performance of long-period discriminants, comparing the relative energy of Love and Rayleigh waves to body waves. As discussed above, an earthquake source is expected to generate more shear energy than an explosion source. In theory, a pure compressional source does not generate Love waves. However, explosions can cause the release of stored elastic energy in the Earth's crust, and measurable Love waves are often observed.

In general, the performance of the long-period discriminants was quite good. However, small magnitude events do not efficiently generate long-period surface waves, and signal-to-noise ratios are often quite poor. For the $m_b - M_s$ discriminant, it was often not possible to obtain Rayleigh wave measurements for frequencies <0.1 Hz for $m_b < 3.5$ to 4.0. In contrast, earthquake M_s values were obtained for m_b values down to about 2.5. This difference in lower M_s thresholds for earthquakes than for explosions could conceivably be used to discriminate between the two populations at low magnitudes (using negative evidence). Research is currently underway at LLNL to find frequency bands that have the optimal signal-to-noise ratios for the surface-wave measurements.

An example of a short-period time-domain discriminant (L_x/P_x amplitude ratio) is illustrated in Fig. 3c. This discriminant basically compares the short-period ratio of shear and compressional energy; earthquake sources are expected to produce a higher ratio than explosions. The data show that there is a tendency for the ratio to be higher for earthquakes than for explosions, but the scatter in the measurements is high, particularly for the earthquakes, and the results are inconsistent. The results from this discriminant are typical of many of the short-period discriminants.

The short-period regional phases propagate efficiently, and the signal-to-noise ratios are generally good resulting in many measurements. However, the nature of the generation and propagation of many of these regional phases is quite complex. It has been clearly documented from both observational and theoretical studies that complex crustal structure has a dramatic effect on regional phases. The long-period surface waves have longer wavelengths (~ 30 – 80 km) than L_x and P_x and tend to smooth out the effects of velocity heterogeneity. In contrast, L_x and P_x waves have shorter wavelengths (~ 4 – 6 km) and can be dominated by scattering effects resulting in very complicated signatures.

An example of an L_x spectral ratio discriminant is shown in Fig. 3d. This discriminant was computed as part of a follow-on pilot study and was applied to 72 earthquakes and 64 explosions. The 1–2 to 6–8 Hz spectral ratio was computed for each of the three phases (P_x , P_{xy} and L_x). The spectral ratio discriminant appears to be as good as any of the discriminants tested on narrow band recording systems, particularly at low magnitudes. The apparent success of this discriminant is based on the observation that earthquakes produce more high frequency energy than the explosions for magnitudes less than -4.5 to 5.5 . As discussed above, the long-period discriminants show good separation between earthquake and explosion populations, but the measurements are difficult to make at low magnitudes. In contrast, the spectral ratio discriminant is easy to measure and involves only a simple distance correction.

Our studies showed that a few of the explosions were characterized by low spectral ratios and were consistently misclassified. These explosions were found to be "overburied" (i.e., they were detonated at

depths greater than necessary for containment).

Subsequent studies have shown that the spectral ratio may be affected by spallation of the surface layers above the explosion. Spall is defined as the parting of near-surface layers above a buried explosion. It is thought to be caused by the tensile failure that is the result of the interaction of an ongoing compressional wave with a downgoing tensile wave reflected from the free surface.

The spalled surface layers are sent into ballistic free fall and eventually impact with the earth. The result is an energy increase in the 0.2–2 Hz frequency band. Thus, the signals from explosions detonated at normal containment depths are contaminated by spall and have a higher spectral ratio. In contrast, overburied explosions do not generate enough energy near the free surface to cause significant spall, resulting in relatively less low frequency energy and a lower spectral ratio. This is of concern because, although the spectral ratio discriminant appears to perform well, it may be possible to evade the spectral ratio discriminant by overburied an explosion to mask surface effects.

Multivariate Analysis

The misclassification performance of individual discriminants generally ranges from a few percent to a maximum of 40% at individual stations and to 25% when network averages are used. These misclassification percentages only apply to those events for which measurements could be obtained and generally represent 50–75% of the total available data.)

To reduce misclassification probabilities, we combined certain discriminants. For example, the $m_b - M_s$ discriminant works well for $m_b > 4$, and the spectral ratio

discriminant is effective at low magnitudes. Standard multivariate classification techniques can be used to define a discrimination function that combines the discriminants in an optimum fashion, thereby reducing misclassification probabilities.

We investigated the utility of the multivariate discrimination technique at each of the individual stations and for the four-station network. For each event, the measured discrimination parameters can be thought of as forming a vector pointing to a location in multi-dimensional hyperspace. The dimension of the hyperspace is defined by the number of parameters measured for a particular event.

The multivariate analysis is used to compute a discriminant function that defines a surface providing the maximum separation between the earthquake and explosion populations (Fig. 4). For example, the four discriminants in Fig. 3 form a four-element vector that identifies a point in a four-dimensional hyperspace.

It is necessary to transform the measurements into variables that are insensitive to magnitude, path, or features of the nuclear test program. For example, m_b is not acceptable as a discrimination parameter, but $m_b - M_s$ is. If we had chosen only earthquakes with $m_b < 4$ and explosions with $m_b > 4$, then it would appear that any new, low magnitude

event would be an earthquake. In reality, this apparent separation is an artifact of our data selection process, and it would be possible to detonate an explosion with $m_b < 4$ that would be misclassified on the basis of magnitude alone. However, $m_b - M_s$ provides a measure of the body-wave to surface-wave amplitude ratio (with appropriate distance corrections) and has a fundamental physical basis for separating earthquakes and explosions.

The multivariate discrimination function takes into account (1) the *a priori* probability that a recorded event is an earthquake or an explosion and (2) the costs associated with misclassification. In monitoring a CTBT, most events recorded by an in-country network are expected to be earthquakes or industrial explosions; therefore, the *a priori* probability of observing an explosion would be set at some small number. The misclassification costs depend wholly on political judgments. This is illustrated in Fig. 5 for the $m_b - M_s$ discriminant. The decision lines PX are controlled by the product $C(Q|X)P(X)$, where $P(X)$ is the *a priori* probability that a recorded event is an explosion, and $C(Q|X)$ is the cost associated with misclassifying an explosion as an earthquake. In a CTBT context, $P(X)$ would be expected to be a low value. Thus, $PX 0.998$ indicates a high cost associated with misclassifying an explosion [$C(Q|X)$ large]. This results in numerous false alarms. $PX 0.002$ indicates a high cost associated with misclassifying an earthquake [$C(X|Q)$ large]. This results in many misidentified explosions (missed violations). $PX 0.5$ is the line that best separates both populations, e.g., $C(Q|X) = C(X|Q)$ and $P(X) = P(Q)$. In our technical analysis, we assume equal prior probabilities and equal misclassification costs ($PX 0.5$), which result

Figure 4. Example of multivariate analysis in two dimensions used to compute a discriminant function that defines a surface that provides the maximum separation between two populations (e.g., earthquakes and explosions).

Figure 5. Examples of different decision lines based on different choices of prior probabilities of occurrence and misclassification costs applied to the $m_b - M_s$ discriminant.

in minimizing the average estimated misclassification probabilities.

Applying the multivariate technique to individual stations for the entire data set shows misclassification rates ranging from 3–10% for explosions and 4–26% for earthquakes.

Multistation discrimination shows misclassification probabilities of 0–2% for explosions and of 3–4% for earthquakes.

A breakdown of the misclassification probabilities as a function of m_b is shown in Fig. 6 for the

individual stations and the network. These plots show that:

- Misclassification rates are generally higher for $m_b < 4$.
- Higher misclassification rates are observed for earthquakes than for explosions.
- Significant differences in discrimination capability are observed between the four stations.

The higher misclassification rates for the low magnitude events may be due to poorer signal-to-noise ratios, particularly for the long-period measurements, which appeared to perform so well (Fig. 3a and b). Part of this problem may be that, in general, low magnitude events had fewer usable measurements on which to base a classification.

The higher misclassification rates for earthquakes are probably due to their having a wider variety of propagation paths, distances, depths, and source mechanisms. Because all of the explosions were from the same region, it is difficult to separate out complications that can be attributed to the source or to propagation. If these explosions had been more widely distributed over the western U.S., more variability in the explosion data set might have been observed and discrimination performance might have been degraded.

Figure 6. Probabilities for misclassifying (a) an explosion as an earthquake—a missed violation; (b) an earthquake as an explosion—a false alarm.

Misclassified Events

Our discrimination studies include the examination of misclassified events (outliers). Understanding why anomalous events are anomalous is important because we can use this information to identify opportunities for evasion. The most important question is:

Was an event misclassified because of some factor that can be controlled by the country conducting the test?

If the answer is yes, this factor provides an opportunity for evasion. A classic example of such a factor is cavity decoupling during which the amplitudes of seismic waves from an explosion detonated in a large cavity (such as a salt dome) can be reduced by a factor of ~70. Detailed analysis of anomalous events identified in our study has led to an improved understanding of explosion source physics and the generation of seismic waves. We have focused our analysis on low magnitude events ($m_b < 4$), which pose the most difficulties.

As discussed above, the long-period discriminants provide good separation between earthquakes and explosions. However, for $m_b < 4$, these measurements are difficult to obtain because of poor signal-to-noise ratios. The short-period time-domain discriminants are obtainable to small magnitudes but show relatively poor separation between the two populations (Fig. 3c). Our pilot study (Taylor et al., 1988) of spectral discriminants showed good separation down to at least $m_b = 3.5$. However, a few explosions conspicuously plotted lower in the earthquake population (Fig. 3d). Two of these three explosions were overburied (i.e., they were detonated at depths greater than necessary for containment) and were characterized by a higher frequency content than

normally buried explosions. In a theoretical study using synthetic seismograms, we showed how the spallation of the surface layers above the explosion could cause differences in the spectral content between normally buried and overburied explosions (Taylor and Randall, 1989).

One explosion, Queso, was not significantly overburied but showed a low spectral ratio. We noticed that a large (~564 m³) funnel-shaped region filled with unconsolidated sand existed directly above the Queso detonation point (Fig. 7). To determine if this region could have affected the seismic signals, we compared the

Queso signals with those from a nearby explosion, Pera, of similar size and burial depth (Taylor and Rambo, 1989). Comparison of the spectra from accelerometer records taken 90 m from the explosions show remarkable similarities to those at 400 km (Fig. 8). This indicates that the spectral characteristics from explosion sources are established at very close ranges.

Our modeling suggests that the anomalous region above Queso may have partially decoupled the upgoing energy resulting in a reduction of low frequency spectral levels. Additionally, the unconsolidated sand and voids above Queso strongly attenuated the outgoing

Figure 7. Queso emplacement configuration.

Figure 8. Comparison of surface ground zero and far-field spectrum for Queso.

shock wave, therefore reducing the energy available for pore collapse and the fracturing of surrounding rock. This, in turn, resulted in the radiation of more impulsive, shorter-duration waveforms that produced a less-rapid high frequency spectral decay. These two effects resulted in a lower spectral ratio for Queso.

Application of Artificial Neural Networks to Seismic Discrimination

In addition to evaluating multivariate-analysis seismic-discrimination techniques, we are also evaluating the application of artificial neural networks (ANNs) to the discrimination problem (Dowla et al., 1989). Artificial neural networks are designed to mimic the pattern recognition processes of the human brain and are well-suited to classification problems.

An example of an ANN is shown in Fig. 9; it consists of many nonlinear elements operating in parallel and arranged in patterns that mimic those of biological neural nets. The ANN nodes sum the output from the nodes of the input layer and obtain a value

(or weight) that is subsequently input to each of the nodes in the next layer. These nodes are conceptually similar to the neurons of the human brain. The interconnections between each of the nodes represent the biological synapses. To represent the firing of the synapses, the output from each node is weighted by a nonlinear transfer function.

A number of techniques are available for training a neural network. We use a backpropagation algorithm that allows for learning in multilayered feedforward networks with nonlinear transfer functions. The learning phase basically consists

of feeding data from a training set of known events to the input layers (e.g., parameter data, spectral data, and waveforms) and setting the proper weight to the output nodes (e.g., 0 for earthquake or 1 for explosion). The backpropagation algorithm then iterates until the difference between the observed output from the ANN and the desired output is minimized. Once the weights are established, unknown events can be input and classified.

We tested the ANN on a set of distance-corrected P_n , P_g , and L_g spectra from a set of 83 western U.S. earthquakes and 87 NTS explosions

Figure 9. Architecture of an ANN. Seismic spectra are input to a 3-layer network of interconnected nodes. Each node weights and sums the input from each node in the underlying layer. Output passes through a nonlinear transfer function that simulates firing of biological synapses and is input into each node in the next layer. The final output is a number between 0 and 1 (0 is an explosion, 1 is an earthquake, and 0.5 is undecided).

recorded at the four broadband LLNL seismic stations. The spectra were sampled logarithmically at 41 points between 0.1 and 10 Hz for each phase and checked for adequate signal-to-noise ratios ($S/N > 2$). We found that by using even simple ANN architectures [82 input units (for the P_x and L_x spectra), 1 hidden unit and 2 output units], powerful discrimination systems can be designed. For this data set, the rate of correct recognition for untrained data was >93% for both earthquakes and explosions at any signal station. Using a majority voting scheme with the

four-station network, the rate of correct classification was >97%. Examination of the network weights suggests that in addition to discrimination on the basis of spectral shapes, the ANN utilized the L_x/P_x amplitude ratio.

We compared the performance of the ANN with the traditional linear (Fisher) discrimination method similar to that described earlier in the "Multivariate Analysis" section of this article. The two techniques performed about the same, but three advantages of the ANN were identified. First, for large data sets, the traditional techniques may suffer from

computational problems. Because of this, the ANN may have advantages in an operational setting. Second, as new events are recorded and independently identified, they can be input to the ANN and the weights can be updated. In contrast, a number of difficult calculations would have to be performed to update a linear discrimination function. For this particular data set, a simple network architecture performed well. Third, for more difficult problems, it is well known that the ANN can be adapted to fit more complex decision surfaces than the traditional techniques.

References

- Dahlman, O., and H. Israelson (1977), *Monitoring Underground Nuclear Explosions* (Elsevier Scientific Publishing Co., Amsterdam).
- Dowla, F. U., S. R. Taylor, and R. W. Anderson (1989), *Seismic Discrimination with Artificial Neural Networks: Preliminary Results with Regional Seismic Data*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-102310, submitted to *Bull. Seism. Soc. Am.*
- Pomeroy, P. W., W. J. Best, and T. V. McEvilly (1982), "Test Ban Treaty Verification with Regional Data—A Review," *Bull. Seism. Soc. Amer.* **72**, S89–S129.
- Taylor, S. R., M. D. Denny, E. S. Vergino, and R. E. Glaser (1989), "Regional Discrimination between NTS Explosions and Western U.S. Earthquakes," *Bull. Seism. Soc. Am.* **79**, 1142–1176.
- Taylor, S. R., and J. T. Rambo (1989), *Near-Source Effects on Regional Seismograms: An Analysis of the NTS Explosions PERA and QUESO*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-101704, submitted to *J. Geophys. Res.*
- Taylor, S. R., and G. E. Randall (1989), "The Effects of Spall on Regional Seismograms," *Geophys. Res. Lett.* **16**, 211–214.
- Taylor, S. R., N. W. Sherman, and M. D. Denny (1988), "Spectral Discrimination between NTS Explosions and Western United States Earthquakes at Regional Distances," *Bull. Seism. Soc. Am.* **78**, 1563–1579.

Developing Codes to Analyze Underground Nuclear Explosions and Shock Propagation

Lewis A. Glenn, Bill Moran,
William C. Moss, and John T. Rambo

Shock Physics Group

The Shock Physics Group has the responsibility of performing analyses and simulations in support of the Nuclear Test Containment Program, the Treaty Verification Program, and the Weapon Effects Program. We duplicated the hydrocode TENSOR's capabilities to simulate underground nuclear explosions by modifying DYNA2D to run on the Cray computers. We also accurately modeled the aspherical shock propagation of a underground nuclear explosion to assist in hydrodynamic yield estimation for verification purposes.

In the United States, nuclear tests are conducted underground to prevent the release of radiation and radioactive debris. The geologies in which these tests are conducted can be complicated—they often consist of many layers of material with different tensile strengths, bulk and shear responses, water saturation and porosity, as well as faults and cracks. Failure to recognize the effects of different material properties and geologic features on the shock wave generated by the explosion could lead to a containment failure, as exemplified by the Baneberry Event in 1970, which released radioactive debris to the atmosphere through shock-generated cracks that extended from the working point to the surface. Following the Baneberry Event, numerical simulations of underground nuclear explosions (including Baneberry) were performed to identify potential containment weaknesses.

Until October 1988, the numerical simulations were done using TENSOR (a two-dimensional, Lagrangian, finite-difference hydrocode). TENSOR was operational only on the CDC 7600 computers,

which were shut down in October 1988. In anticipation of the shutdown of the CDC 7600s, efforts were initiated by others to make a version of TENSOR that could be run on the Cray computers, but these efforts were unsuccessful. Consequently, we chose to use DYNA2D (Hallquist, 1987), which is a two-dimensional, Lagrangian, finite-element hydrocode. We selected DYNA2D because it is a state-of-the-art hydrocode that is used worldwide. It is approximately six times faster than TENSOR, has slide-lines, color graphics, and portability (it is easily transferred to other machines). There is also a three-dimensional version that will allow analyses of very complex geologies.

Our immediate goals were to duplicate TENSOR's capabilities. The reasons for this were practical, not technical. The Containment Evaluation Panel, which approves events for detonation based on the probability of successful containment, had developed confidence in TENSOR's calculations over the past 15 years. We did not want to weaken this confidence, so we added those features of TENSOR to DYNA2D that are

necessary to do geologic problems: geologic material models, dezoning, and overburden. We also modified the DYNA2D post-processor to produce graphical output of quantities relevant to containment so that TENSOR and DYNA2D output could be compared. We will first describe containment calculations, then show how this calculational capability has been recently used by the Treaty Verification Program.

What is a Containment Calculation?

A typical numerical simulation of an underground nuclear explosion consists of constructing a two-dimensional representation of the test geology. The results of well loggings, analyses of cuttings, and geologic surveys are used to construct the numerical representation of the test geology. Colors are used to represent different materials. Although the geology is three-dimensional, two-dimensional (axisymmetric about the z axis) representations have been found to be adequate.

The geology is divided into small, discrete elements in which the equations of motion (conservation of mass, momentum, and energy) are difference, and solved. The parameters for the material model are obtained from experimental data when possible or from theoretical models when data are not available. The cavity (centered at $r = 0$, $z = 0$) contains the device, which is modeled as a gas with an appropriate pressure-volume relation. Typically, the calculation begins at ~ 3 ms (0.1 Mbar cavity pressure) so that radiation can be neglected. The calculation is terminated at ~ 1 s, which is usually long enough for the dynamic solution to approach static equilibrium.

In order for there to be "good numerical containment," we examine the stress field around the cavity and the spatial extent of material that has failed in tension during the calculation. We look for a spatially thick region around the cavity in which the in-plane and out-of-plane hoop stresses are compressive and exceed the cavity pressure. We also require a thick region of uncracked material between the cavity and the surface. We do not want to see a pattern of cracks (even if they are currently closed) that extend from the cavity to the surface.

In general, interpreting the results of numerical calculations and making conclusions about containment is subjective and difficult. The numerical calculations are useful because they allow us to do controlled sensitivity studies to address particular containment issues that arise. These sensitivity studies can be done quickly and easily with DYNA2D.

Comparisons of DYNA2D and TENSOR

Figure 1 shows contours of the out-of-plane hoop stress at 800 ms

for an event planned for hole U8n, as calculated by DYNA2D and TENSOR. Identical meshes, boundary conditions, and material properties were used in these calculations.

The contour levels (colors) are identical in both calculations, increasing from dark blue to red. Compressive stresses are positive. The calculations are very similar. The complicated material geometry and large number of materials (14) with different material properties assures us that the agreement is not fortuitous and that we have incorporated the relevant features of TENSOR's geologic model in DYNA2D.

We have compared DYNA2D and TENSOR simulations of events that showed good, marginal, and poor compressive stress fields around the cavity at late times. These simulations also were in agreement. Consequently, DYNA2D is a reliable tool for doing containment calculations and can be used for all future LLNL containment calculations.

Calculating Shock Propagation for Treaty Verification

The Threshold Test Ban Treaty (TTBT) was signed by Presidents Bush and Gorbachev in June 1990. It was subsequently ratified by the United States and the Soviet Union and is now in effect. The TTBT limits nuclear testing to yields below 150 kt, a practice that has been observed by the United States for the last 15 years but was not mandated by treaty obligation. Verification of compliance is an important element of any treaty, including the TTBT. Seismic monitoring, satellite observations, and hydrodynamic methods can all be combined to verify compliance with the TTBT. Of the three, the latter is generally considered to be the most accurate.

Hydrodynamic Yield Estimation

Hydrodynamic methods of determining the yield refer to using the measured strength and/or position of the shock front to estimate the yield. The position of the shock generated by the explosion is obtained by measuring the length of a coaxial cable as it is crushed by the shock wave from the explosion (Fig. 2).

An instrumentation system called CORRTEX (Continuous Reflectometry for Radius versus Time Experiment) is commonly used to obtain the shock position. The hydrodynamic yield of a nuclear explosion can then be determined by scaling the measured shock radius vs time (R/t) curve to a standard R/t curve in similar media. The standard (R/t) curve can be obtained from a hydrocode calculation or can be measured experimentally from a previous test in a geologic site similar to the explosion in question.

Figure 3 is a graphical representation of the hydrodynamic yield scaling method. The estimated yield, $W(t)$, is obtained by scaling the experimental $R(t)$ to the standard $R_s(t)$, for which the yield is W_s , using the formula,

$$[W(t)/W_s] = (R(t)/R_s)^3 = (t/t_s)^3$$

and different values of R/t . In the strong-shock region, where the pressure is large compared with the rock strength, $W(t)$ will be approximately constant and equal to the explosion yield.

The yield determination method that uses the hydrocode-generated calibration curve is called simulated explosion scaling. The yield method that uses data from a previous nuclear test is called similar explosion scaling. Simulated explosion scaling

Figure 1. Out-of-plane hoop stress at 800 ms for an event in hole U8n, as calculated by (a) TENSOR and (b) DYNA2D.

Figure 2. Schematic showing the crushing of a coaxial cable.

Figure 3. Schematic showing hydrodynamic yield scaling.

is considered more accurate because it can account for emplacement irregularities and highly localized geology, but it requires accurate descriptions of the nuclear source (Moran and Goldwire, 1989) and the equation-of-state (EOS) of the rock surrounding the device. The EOS is constructed from analyses of shock-wave experiments with emplacement region samples (cores) and borehole logs of the rock near the device.

Shock Propagation near a Nuclear Explosion

In a typical underground nuclear test, the device is placed in a cylindrical canister. The shock emerges with an aspherical front that converges toward sphericity as it propagates. Our ability to accurately simulate the shock front is crucial to the hydrodynamic yield estimates that we obtain because, for typical rocks, the yield is roughly proportional to the sixth power of the shock-front radius. We have therefore implemented a zone-size-independent technique that locates the shock front from our computer simulations. Figure 4 shows the qualitative progression toward sphericity from an initially aspherical source. The data obtained from our calculations are then analyzed for yield estimates and can be used to determine any bias due to the size and shape of the device canister. Furthermore, our calculations provide estimates of the pressure and mass velocity at the shock front that can be used to evaluate other methods for yield estimation.

Figure 4. Evolution of an aspherical shock front.

References

- Hallquist, J. O. (1987), *User's Manual for DYNA2D—An Explicit Two-Dimensional Hydrodynamic Finite Element Code with Interactive Rezoning and Graphical Display*, Lawrence Livermore National Laboratory, Livermore, CA, UCID-18756, Rev. 3.
- Moran, B., and H. C. Goldwire, Jr. (1989). *Effect of Source Modeling on the Inferred Yield from an Underground Nuclear Explosion*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-100914; submitted to the *Proceedings of the American Physical Society Topical Conference* held in Albuquerque, NM, August 14–17, 1989.

Large-Scale Simulation of Solute Transport in Heterogeneous and Reactive Porous Media

Andrew F. B. Tompson and Richard B. Knapp
Flow and Transport Group

The ability to model the movement and transformation of dissolved aqueous or gaseous chemicals in porous flow systems is important in a number of different scientific disciplines. We report here on our efforts to improve and apply several computational tools that may allow us to better understand a number of complex chemical and physical phenomena that occur in natural subsurface flow systems. In particular, our studies have focused on examining the effects of material heterogeneities on groundwater flow and transport processes as well as on understanding the nature of the chemical interactions that take place in such systems. Advances in these areas will be critically important in seeking solutions to the variety of hazardous and nuclear waste disposal problems now being faced in the United States and other industrialized countries.

The physics of fluid flow and chemical transport in porous media has long been of interest to scientists in a number of disciplines, including agricultural, chemical, and petroleum engineering, as well as hydrology and geology. The study of these phenomena has traditionally been pursued, for example, in the course of producing domestic water supplies from groundwater aquifers, developing economic irrigation practices, designing chemical processes in fluidized reaction beds, optimizing petroleum recovery, or gaining a better understanding of long-term diagenetic and other mineral production processes. More recently, a significant amount of effort has been devoted to the study of transport and reactive processes associated with aqueous toxic or radioactive materials that have been (or could be) released into subsurface flow systems.

Because groundwater supplies in many parts of the U.S. have been contaminated with hazardous materials leached from landfills or other disposal operations, there is an interest both in characterizing the extent and evolution of these contamination problems and also in designing ways to clean up the affected groundwater. There is an analogous interest in characterizing potential contamination events that may result from failures of engineered nuclear or other hazardous waste disposal systems. Many of these research activities will rely on predictive mathematical models of the natural flow and transport systems, which, in turn, must rely on an accurate understanding of the relevant physical, chemical, and biological processes. Much of our current research has been aimed in these directions, with particular emphasis on modeling reactive solute transport and physical processes within heterogeneous media.

Solute Transport in Heterogeneous Formations

Subsurface porous materials typically exhibit a large degree of natural variability in terms of their type and spatial distribution. Geologic formations that act as flow conduits are often characterized by variable, three-dimensional structures consisting of layers, lenses, and, perhaps, fractures, in various materials ranging from sands and gravels to clays or rocks. Our ability to fully characterize or simulate the detailed local hydraulic behavior (Fig. 1) in actual formations over large spatial regions is extremely limited. Because of this, a substantial amount of research in recent years has been devoted to developing more systematic and predictive modeling techniques aimed at the quantitative description of bulk hydraulic behavior (Fig. 1) over large temporal and

Figure 1. Local and large scales of observation. In (a), (c), and (d), local variations in the conductivity K , head h , flux q , or concentration c may be easily observed from point measurements in the field. Accurate prediction of the flux or concentration fields at this scale will require an extremely resolved computational mesh and data set (b). Since this is impossible in most field problems, we seek to operate on a larger scale in which a coarser computational and measurement grid can be used (b). In this case, we seek to solve mean equations based on effective coefficients (a) to predict mean hydraulic fields (c) and (d). We also predict approximate bounds around the mean predictions in which local measurements should lie.

spatial scales while accounting for the influence of small-scale material variabilities (e.g., Gelhar and Axness, 1983; Dagan, 1984, 1986; Gelhar, 1984, 1987; Mantoglou and Gelhar, 1987a-c; Neuman et al., 1987; Graham and McLaughlin, 1988). Many of the new techniques involve the adoption of a statistical model of the local material structure and the subsequent development of large-scale balance equations written in terms of a set of mean or effective coefficients. Quantitative measures of the error, or variance, between predicted bulk hydraulic quantities and their local field counterparts are also predicted (Fig. 1). The effective coefficients and variance estimates are functions of the statistical characteristics of local material variabilities.

We have developed and applied a detailed transport model for studying conservative contaminant movements through large heterogeneous flow systems in porous media under constant temperature conditions. This model is applicable to large, three-dimensional problems that include the transport of one or more aqueous chemical constituents through saturated or unsaturated flow systems characterized by spatially variable hydraulic parameters. The interest in carrying out these simulations stems from a desire to validate large-scale theories by examining the detailed spatial and temporal effects of variable flow systems on developing solute plumes. In particular, the bulk dispersive behavior induced by such fields on the solute mass distribution can be quantitatively measured and compared with the theoretical behavior predicted by a number of the larger scale stochastic models referenced above.

The modeling approach reviewed here envisions the development of detailed synthetic flow fields that correspond to hypothetical, spatially variable hydraulic

conductivity distributions, the subsequent simulation of solute transport within these fields, and the analysis of the ensuing hydraulic and dispersive behavior. The flow problem involves solving

$$\nabla \cdot (K \nabla h) = 0 \quad (1)$$

on a cubic region Ω_c (Fig. 2) for the hydraulic head $h(x)$, along with suitable conditions for h on the domain boundary $\partial\Omega_c$. In typical problems, constant values of h will be maintained on two opposite

faces of the domain, while no-flux conditions will be enforced on the remaining faces. The local medium fluid velocity is determined from

$$q = \epsilon v = -K \nabla h, \quad (2)$$

where ϵ is the fluid phase void fraction, or porosity. We adopted a seven-point finite difference scheme using an iterative solution method to solve the flow problem [Eq. (1)], from which approximate, constant cell velocities can be developed from Eq. (2). Specific details

Figure 2. Computational flow domain Ω_c used in the flow and transport calculations. The head gradient applied between faces 1 and 3 is shown. The initial pulse location for the three transport problems discussed in text is also indicated. The length of the domain in each direction i is $50 \Delta x_i = 25 \lambda$, where λ is the heterogeneity correlation scale and $\Delta x_i = 0.5$ (dimensionless).

regarding the flow model and its solution can be found in the work of Ababou et al. (1988).

The hydraulic conductivity field $K(x)$ is represented by

$$K(x) = K_G e^{f(x)}, \quad (3)$$

where $f(x)$ is a second-order stationary, spatially correlated random field (Vanmarcke, 1983; Gelhar, 1984, 1986) of mean zero and constant variance σ_f^2 , and K_G is the geometric mean of K , assumed also to be constant. The degree of variability in K can be described by the magnitude of σ_f , while the spatial "persistence" of K values along some direction i can be described by the correlation structure of $f(x)$, or, in an abbreviated sense, by a set of characteristic correlation lengths, λ_i . This is a simple and commonly used model of spatial variability and is well supported by field data (e.g., Hoeksema and Kitanidis, 1985). Specific realizations of this field have been generated for use in the flow calculations from a turning-bands random field generator (Tompson et al., 1989).

The general transport problem for a single liquid-phase chemical constituent i at constant temperature involves solving the mass balance equation

$$\frac{\partial(\epsilon c_i)}{\partial t} + \nabla \cdot (\epsilon c_i \mathbf{v}) - \nabla \cdot (\mathbf{D} \nabla c_i) - \tau R_i = 0 \quad (4)$$

for the concentration c_i in Ω , over a period of time, subject to a set of initial and boundary conditions for c_i . In this equation, $\mathbf{D}$ represents the local hydrodynamic dispersion tensor, and R_i is the rate of production of constituent i via homogeneous or heterogeneous reaction, decay, or phase change. The local dispersion tensor is written as

$$\mathbf{D} = (\alpha_L V + \alpha_T |\mathbf{v}|) \frac{\mathbf{v} \mathbf{v}^T}{V}, \quad (5)$$

where α_L and α_T are dispersivity coefficients, V is the molecular

diffusivity in the porous medium, and V is the velocity magnitude, $|\mathbf{v}|$. The simulations discussed here consider a single nonreactive solute ($R_i = 0$) in one or more saturated systems where ϵ , α_L , α_T , and $\mathbf{D}$ are constant. Typical simulations involve injecting a pulse of solute within the flow field and monitoring its motion as it moves within the domain Ω .

Particle Transport Model

The transport simulations have been carried out using a particle-tracking method. These algorithms are based on representing the spatial distribution of some extensive quantity, such as the mass of a particular chemical constituent, by a large collection of particles. The "state" of the system at some particular time is defined by a set of attributes associated with each particle, which may include position, mass, charge, or constituent type. A "simulation" involves changing the various particle attributes or the number of particles with time according to a set of "forces" or other conditions determined by some interparticle relationship, space-dependent field property, or boundary condition. Our simulations will proceed by moving particles through space by individual advective and diffusive steps computed from a random walk model. This method is based on analogies between mass transport equations and certain stochastic differential equations. A particle is displaced according to the simple relationship

$$\mathbf{x}^{n+1} = \mathbf{x}^n + \mathbf{A}(\mathbf{x}^n) \Delta t_{n+1} + \mathbf{B}(\mathbf{x}^n) \Delta \mathbf{W}(t_n), \quad (6)$$

where $\mathbf{x}^n$ is its position at time level t_n , $\mathbf{A}$ is a deterministic forcing vector, $\Delta \mathbf{W}$ is a random forcing vector, and $\mathbf{B}$ is a deterministic, square scaling tensor. The vector $\Delta \mathbf{W}$ may

be written as $\mathbf{Z} \sqrt{\Delta t}$, where $\mathbf{Z}$ contains three independent random numbers with mean zero and unit variance, and $\Delta t = t_n - t_{n-1}$. If a large, yet finite number of identical particles associated with constituent i are moved simultaneously, then their density $f_i(\mathbf{x}, t)$ will approximately satisfy (Haken, 1983; Kinzelbach, 1987)

$$\frac{\partial f_i}{\partial t} + \nabla \cdot (\mathbf{A} f_i) - \nabla \cdot \left(\frac{1}{2} \mathbf{B} \cdot \mathbf{B}^T f_i \right) = 0. \quad (7)$$

The balance of mass for a conservative aqueous constituent is given by Eq. (4) with $R_i = 0$. As the particle density f_i is analogous to ϵc_i , the particle method succeeds if $\mathbf{A}$ and $\mathbf{B}$ are chosen from

$$\mathbf{A} \equiv \mathbf{v} + \nabla \cdot \mathbf{D} + \frac{1}{\epsilon} \mathbf{D} \cdot \nabla \epsilon \quad (8)$$

and

$$\mathbf{B} \cdot \mathbf{B}^T \equiv 2\mathbf{D}. \quad (9)$$

It is useful to mention that the particle approach is evolutionary in nature, and that "steady state" solutions can only be achieved in an asymptotic manner by fixing steady boundary conditions (Tompson and Dougherty, 1988) and letting transients resulting from initial conditions decay.

The computational effort per time step used in this kind of approach will be proportional to the number of particles used (N_p). More conventional finite element or finite difference methods will involve the solution of N_g algebraic equations (where N_g is the number of grid points) and a computational expense that is bounded by N_g^2 . The selection of a method based on work estimates will thus depend on the values of N_p and N_g .

Below, we summarize a set of problems conducted on a cubic computational domain Ω composed of roughly 10^3 nodes or cells. Given that 10^3 to 10^4 particles may be sufficient for a one-constituent model

(Ahlstrom et al., 1977), it is clear that the particle-tracking method is a logical choice for these simulations. Note that, because the motion of one particle is statistically independent from that of another, the algorithm Eq. (6) is aptly suited for (an even faster) implementation on parallel architecture computers.

Examples

Three different flow fields corresponding to three different conductivity distributions were developed on the computational region pictured in Fig. 2. The flow domain was discretized into a set of $50 \times 50 \times 50$ cells of (dimensionless) length $\Delta x_i = 0.5$ in each coordinate direction. The conductivity distributions were developed from Eq. (3) with $K_G = 1$ and an exponential correlation function in which $\lambda_i = 1.0$ and $\sigma_i = 1.0, 1.7$, and 2.3 . Each field resulted from solving the system of Eqs. (1) and (2) subject to the imposition of constant values of $h(x) = \pm 0.05$ on the two faces (1 and 3) of Ω_2 , intersecting the x axis and no-flow conditions on all other faces. Within each flow field, a pulse of 8000 particles was introduced in a $4 \times 4 \times 4$ cluster of cells centered at $x = 1.5, 12.5, 12.5$, near the upstream x_1 face. The particles were displaced in time according to the algorithm [Eq. (6)] until a relatively complete breakthrough curve was obtained at the downstream x_1 face. In all simulations, the dispersion parameters α_L, α_T , and $\mathcal{D}$ appearing in Eq. (5) were set to values of $0.05, 0.005$, and 0 , respectively, and approximate cell-constant velocities were used. The time step used in each simulation was adjusted so that no particle ever traversed a distance greater than a fraction of a cell's length.

Log-contours of a portion of the conductivity distribution associated with the third flow problem ($\sigma = 2.3$)

are shown in Fig. 3. Notice that the initial location of the plume associated with this field straddles a dipping zone (green) of high conductivity near the upstream face. A set of five three-dimensional contour images of the plume associated with this field at times 0, 33, 66, 99, and 132 are shown in Fig. 4a-e. They serve to illustrate the expansion of the plume with time and the highly variable mass distribution associated with the plume's internal structure and external boundaries. They also indicate that a portion of the plume quickly moved downward though the high conductivity zone, while another part remained much closer to its initial location. Each figure was created by using the raw particle count in each cell at a given time as an approximate concentration. The smoothed contours were developed from a three-dimensional volumetric imaging

package (courtesy of Dynamic Graphics, Inc., Berkeley, Calif.).

It is clear from the figures that the solute mass distribution initially moves in response to local velocities and dispersion processes, but at later times shows a bulk motion consistent with some "average" velocity and a spreading pattern strongly affected by the fluctuations in the velocity field.

The only way for these bulk characteristics to be produced in a modeling exercise is to either use all the computational detail shown here (with appropriate resolution of the data), or to solve a modified set of balance equations [similar to Eqs. (1) and (2)] for smoothed or averaged quantities, $\bar{v}$ or $\bar{c}$ on a much coarser grid. These are, in fact, one of the main products of most stochastic models (e.g., Gelhar and Axness, 1983; Dagan, 1984; Gelhar, 1984, 1987; Neuman et al., 1987). In

Figure 3. Schematic illustration of a portion of the $\ln K(x)$ structure used for the third flow problem from the same perspective as Fig. 2. Green indicates regions of higher conductivity; red indicates regions of lower conductivity.

Figure 4. Schematic images of the evolution of the plume associated with the third flow problem at dimensionless times 0, 33, 66, 99, and 132. Red-yellow indicate low concentrations; green-blue indicate intermediate concentrations; and purple-pink indicate high concentrations.

actual field investigations, the average behavior is meant to be determined from a set of mean equations written in terms of bulk coefficients that are functions of (measurable) structural statistics of the medium; local measurements are only expected to lie in a band around the mean behavior (Fig. 1). Furthermore, the computational expense is expected to be much more tractable.

We would like to compare the bulk characteristics of the simulated plumes to the analogous characteristics predicted by the larger scale theories. More specifically, we would like to answer the following two questions:

- Will the bulk plume velocity be similar to the average theoretical field velocity?
- Will the bulk rate of its spreading be quantitatively consistent with predicted larger scale dispersion processes?

The "velocity" of a plume can be determined by examining the rate of change of the plume's center of mass, $\bar{\mathbf{X}}(t)$, defined by

$$\bar{\mathbf{X}}(t) = \frac{1}{N_p} \sum_{p \in N_p} \mathbf{X}_p(t), \quad (10a)$$

where N_p is the total number of particles and $\mathbf{X}_p(t)$ is the position of the p th particle at time t . Plots of the $\bar{\mathbf{X}}_x(t)$ and $\bar{\mathbf{X}}_y(t)$ vs $\bar{\mathbf{X}}_x(t)$ are shown in Fig. 5a and indicate that the plumes generally tend to move in the positive x_1 direction after an initial developmental period. A plot of the path displacement

$$s_p(t) = \int_0^t |d\bar{\mathbf{X}}(t)| \quad (10b)$$

is shown in Fig. 5b. These curves indicate that the plumes gradually come to move with constant (albeit different) speeds. The mean field velocity based on the stochastic analysis of Gelhar and Axness (1983) can be determined from

$$\epsilon \bar{\mathbf{v}} = -K_e \nabla \bar{h}, \quad (11)$$

where K_e is an effective conductivity, equal, in this case, to

$$K_e = \sigma_e^2 / \epsilon,$$

$\bar{h}$ is a mean head gradient, equal, in this case, to $-0.004i$, and ϵ is the porosity. Note that the asymptotic direction of motion of each plume is parallel with $\bar{\mathbf{v}}$. The (theoretical) velocity magnitudes are compared in Fig. 6 with the plume speeds and the averaged x_1 component of the computed field velocities. The approximate agreement of all these values validates, in some sense, the mean behavior predicted in Eq. (11).

One way in which the three-dimensional "spreading" of a plume can be described is through the second-order moment tensor, corrected for the center of mass,

$$\Sigma^2(t) = \frac{1}{N_p} \sum_{p \in N_p} \mathbf{X}_p(t) \mathbf{X}_p(t)^T - \bar{\mathbf{X}}(t) \bar{\mathbf{X}}(t)^T. \quad (12)$$

The mean concentration $\bar{c}$ will satisfy the balance equation

$$\begin{aligned} \frac{\partial(\epsilon \bar{c})}{\partial t} + \nabla \cdot (\epsilon \bar{c} \bar{\mathbf{v}}) - \nabla \cdot \{ \epsilon [\bar{\mathbf{V}} \mathbf{A}(t) + \mathbf{E}_{local}] \cdot \nabla \bar{c} \} &= 0, \end{aligned} \quad (13)$$

where $\bar{\mathbf{V}} \mathbf{A}(t)$ is a time-dependent "macroscopic" dispersion tensor and $\mathbf{E}_{local}$ is $\mathbf{D}$ of Eq. (5) evaluated in terms of $\bar{\mathbf{v}}$. If $\bar{\mathbf{v}} = \text{constant}$, then it is possible to show that

$$\begin{aligned} \frac{d \Sigma_{ii}^2}{ds_p} &\rightarrow 2 \{ \mathbf{A}(\infty) + \mathbf{E}_{local} / |d\bar{\mathbf{X}}/dt| \} \\ &= \text{constant as } t \rightarrow \infty, \end{aligned} \quad (14)$$

where $\mathbf{A}(\infty)$ is a constant, asymptotic value. The primary component of the diagonalized form of $\mathbf{A}(\infty)$ has been evaluated analytically by Gelhar and Axness (1983) to be

$$A_{11}(\infty) = \frac{\sigma_y^2 \gamma}{\gamma^2}, \quad (15)$$

where $\gamma = e^{\sigma_y^2/6}$. This result is meant to be applicable in systems with small variances and local dispersivities (i.e., $\sigma_y^2 < 1$ and $\alpha_L, \alpha_T \ll \lambda$). Based on the plume simulations, we have computed the primary component of the diagonalized form of $\Sigma^2(t)$ and plotted it versus s_p for each of the three transport simulations (Fig. 7). The asymptotic slopes of these curves were used to compute experimental values of $A_{11}(\infty)$, which are compared in Fig. 8 with the theoretical prediction Eq. (15) and a competing theory of Neuman et al. (1987) in which $\gamma = 1$. We generally see a closer agreement with Gelhar's work, even though the theory is somewhat questionable for larger values of σ_y and the full development of asymptotic conditions (Fig. 7) may not have been achieved over the time frame of the simulations.

We close this subsection by summarizing our conclusions from these results. We found that simulations of flow and transport in heterogeneous media can be credibly performed if they are carried out in one of the following ways:

- With a high resolution (as done here) in which a large amount of parametric data and computational power are required,
- On a larger scale in which only the bulk hydraulic characteristics are revealed.

The nature and scale of most field investigations precludes any detailed simulations of the type considered here from being done. Realistic and tractable approaches must rely on simulating the larger scale behavior as pictured in Fig. 1 and described in Eqs. (11) and (13). These equations express the conservation of bulk fluid momentum and solute mass in terms of a set of large-scale, effective medium coefficients, such as K_e and $\mathbf{A}(t)$. For many types of heterogeneous formations, these coefficients have been related theoretically to specific

Figure 5. (a) Plots of the $\bar{X}_2$ and $\bar{X}_3$ components of the center of mass $\bar{X}(t)$ vs the $\bar{X}_1$ component for each flow/transport problem. Note: 1.3 refers to the first flow problem, where $\sigma_f = 1$; 2.3 refers to the second flow problem, where $\sigma_f = 1.7$; and 3.3 refers to the third flow problem, where $\sigma_f = 2.3$. (b) Plots of the path displacement s_p vs dimensionless time for each problem considered.

Figure 6. Plot of the normalized x_1 velocity component as determined from the motion of the plume, the average of all calculated field velocities, and the theoretical derivations of Gelhar and Axness (1963) and Neuman et al. (1987). (Runs 1.3U, 1.3D, and 1.3I are not discussed in text.)

Figure 7. Plots of the primary spreading variance component Σ_{11}^{*2} vs path displacement s_p for each transport problem.

Figure 8. Plots of the normalized asymptotic macrodispersivity component vs σ_f as determined from the examination of the sloped Σ_{11}^{*2} vs s_p curves and from the theoretical derivations of Gelhar and Axness (1983) and Neuman et al. (1987). (Runs 1.3U, 1.3D, and 1.3I are not discussed in text.)

measurable characteristics of the medium heterogeneity (such as K_C , σ_i , and λ_i). The results in Figs. 6 and 8 suggest that the predictions of these coefficients are approximately consistent with the behavior observed in the numerical experiments. For realistic field applications, this means that such coefficients (as estimated from measured heterogeneity characteristics) may be used with a larger degree of reliability to predict gross displacement and spreading rates of groundwater contamination plumes. Future work will continue along these lines with added emphasis on field applications, nonstationary media (in which K_C , σ_i , and λ_i are functions of space), and the effects of chemical (e.g., sorption) phenomena and unsaturated flows.

Simulation of Reactive Transport

More often than not the chemical contaminants introduced into a groundwater environment may chemically interact with indigenous dissolved chemicals, other liquid contaminants, or the solid phase minerals in the soil matrix. In many cases, these types of interactions may act to inhibit or hasten the overall transport of the contaminants. Attempts to predict the transport or fate of such chemicals must therefore take these effects into account. The kinds of interactions that may occur will depend on the chemical characteristics of the contaminants, the groundwater, and the soil matrix, and may be generally large in number. Heterogeneities in the chemical phenomena may exist in addition to heterogeneities in the physical flow patterns. Simulation of the transport of one or more reactive chemicals through a groundwater regime can be much more complex than the nonreactive simulations discussed above. Hence,

some of our current research efforts are now being directed toward developing improved computer models of reactive transport in porous media. Ultimately, such models may be used to look at the same kinds of problems discussed above in which both chemical and physical heterogeneities are present.

Generally speaking, a reactive transport problem involves the solution of one or more equations of the form of Eq. (4) in which the source term R_i does not vanish. These problems can be quite complex in nature, primarily because of the number of chemical constituents that must be considered, the range of specific types of interactions that may occur, and the computational intricacies they may introduce (e.g., Oran and Boris, 1987; Yeh and Tripathi, 1989). One may often consider systems comprising $I = 1, 2, \dots, N_c$ chemical constituents that may exist in liquid, solid, or gaseous states. A "precise" description of the physical and chemical effects that may occur in an (isothermal) system would involve the simultaneous solution of Eq. (2) and a series of equations like Eq. (4) for each constituent, where $R_i = R_i(c_j)$ and $K = K(c_j, t)$, $j = 1, 2, \dots, N_c$. In addition, these equations may have to be solved in conjunction with a set of algebraic constraints that represent $Q_i(c_j) = 0$, the effects of equilibrium behavior. Furthermore, a similar set of equations may have to be solved for solid or gas phase behavior, along with appropriate momentum balances analogous to Eq. (2).

Chemical reactions are typically classified as homogeneous in which all participant constituents are of the same phase, or heterogeneous, in which they are of different phases. Homogeneous reactions in natural systems can include complexing reactions or radioactive decay that occur in liquid, solid, and gaseous phases. Heterogeneous reactions

may include solid phase sorption or ion exchange phenomena, mineral precipitation and dissolution processes, or even mass exchange resulting from phase change. The interactions will be highly dependent on the chemical composition of the medium and host liquids, on the nature of the flow field, and on the thermodynamic state (pressure and temperature). The way in which they are treated in mathematical models will depend on the following: the number of constituents present; the time and length scales associated with the flow, reactions, and simulation goals; and the computational or data limitations.

Extension of the Particle Approach

The direct solution of a nonconservative multicomponent transport problem such as Eq. (4) using traditional finite element or finite difference techniques has been discussed widely in the hydrological literature (e.g., Nguyen et al., 1982; Huyakorn and Pinder, 1983; Cederberg et al., 1985; Lewis et al., 1986) and in the literature of other disciplines (e.g., Oran and Boris, 1987).

We are currently involved in extending the capabilities of the particle transport model introduced above to include the treatment of some classes of nonconservative problems, with the hope that some computational advantages will be gained. Within the particle approach, the easiest way to treat the gain or loss of constituent mass at a point is to periodically apply an explicit "correction" algorithm in which particles of a specific type are added or removed according to models of the relevant chemical mechanism. Alternatively, the masses of particles may be modified to reflect the same behavior. Simple reaction models, such as linear adsorption and binary ion exchange, have been accommodated

by a modification similar to this (Ahlstrom et al., 1977; Washburn et al., 1980). The inclusion of more complicated processes can pose some computational difficulties (Garven and Freeze, 1984) and warrants careful development of specific, efficient chemistry modules.

If different types of chemical exchanges are to be examined simultaneously, then the individual rates of their progress may differ and should be used to plan the order in which the correction algorithms are applied (Nguyen et al., 1982). The fastest type of reactions are those that are considered to reach equilibrium over the characteristic time step of a simulation. They have no "memory" of the travel path. These modifications must be made first because the slower phenomena may depend on their products.

Slower reactions will attain equilibrium after many time steps of a simulation; however, their progress may be modified by different conditions encountered while moving through the medium. It is possible that the time step of the simulation may be large enough to prevent accurate advancement of the reaction products, in which case, a smaller time step must be chosen, or an implicit correction method must be adopted.

In most cases, these source/sink mechanisms are modeled in terms of mass concentrations and not in terms of mass itself. Thus, the effective application of particle methods to nonconservative problems requires interpolation methods from the discrete particle system to a continuum concentration field and vice versa (Hockney and Eastwood, 1981). The simplest of these schemes usually leads to concentration estimates that exhibit a "noisy" behavior in space. Noisy concentration estimates may affect reaction mass corrections, could cause oscillatory heterogeneous equilibria, and may propagate certain errors forward in

time. The noise is an artifact of the particle method and can be reduced by increasing the number of particles N_p used for a given constituent. Because the reduction is proportional to $1/\sqrt{N_p}$, less expensive approaches may involve the use of modified weighting functions or the application of filtering techniques (e.g., image processing) to smooth the solution (Ahlstrom et al., 1977; Thompson and Dougherty, 1988).

The computational effort per time step involved in a coupled multicomponent particle model composed of s components will be roughly proportional to $sN_p + G$, where N_p is the number of particles used for one constituent (assuming a similar number is used for all others), and G is the cost of evaluating the geochemical interactions. This may be compared with a bounding cost of $(sN_p)^2 + G$ for an explicit finite element or finite difference approach.

Because the particle method [Eq. (6)] is inherently explicit, the treatment of any coupling terms must, at first glance, proceed similarly. However, implicit approaches may be preferred for stability or accuracy reasons in conventional approaches, and their necessity may be dictated by the relative magnitudes of the computational time step and the characteristic times of the reaction rates. Implicit approaches are possible in particle models and will necessarily add an iterative loop to the cost estimate, regardless of whether reactions are present. In general, then, the particle computational effort will (minimally) increase linearly with the number of components considered, as compared with (at least) a quadratic increase with conventional methods. Particle models, then, may be most competitive in multidimensional or densely gridded problems, especially if the constituent mass is, in some sense, localized in some small region of the flow domain.

Alternative Purely Advective, Lagrangian Approach

We have implemented a simplified approach to the solution of Eq. (4) for multicomponent systems. In this approach, we assume that transport by advection is much greater than transport via dispersion and diffusion. In addition, we transform Eq. (4) into a Lagrangian reference frame by employing the substantial derivative to represent the time derivative and accumulation term:

$$\frac{D(\epsilon c_i)}{Dt} - \epsilon R_i = 0. \quad (16)$$

The governing equation now describes the chemical evolution of a hypothetical, constant-density fluid packet as it flows along a predetermined path line.

A software package solving this system of equations [Eq. (16)] for polymineralic, multiple-component aqueous systems was previously developed by Wolery (1979) in the EQ3/6 geochemical modeling package. EQ3/6 describes the chemical evolution of a single fluid packet that flows through a rock, dissolves minerals initially present, and eventually precipitates new product phases. However, in real systems, there are multiple fluid packets and each succeeding fluid packet reacts with the previously altered rock as opposed to the initial rock encountered by the first fluid packet.

We have successfully modified EQ3/6 to model the chemical evolution of multiple fluid packets (Knapp, 1989). In addition, we have incorporated a quasi-stationary state scheme suggested by Lichtner (1988), which permits large time steps to be taken. The quasi-stationary state concept is based on the fact that precipitation fronts in natural systems move exceedingly slow ($\mu\text{m}/\text{yr}$). The kinetics of heterogeneous reactions and the aqueous

transport of components occur at much faster rates, resulting in the development of steady-state profiles upstream of each precipitation front. The rates of dissolution and precipitation in these steady-state areas can be linearly extrapolated through time until the dissolution rate changes significantly, a reactant mineral completely dissolves, fluid velocity changes, or inlet fluid composition changes. Typically these times are on the order of hundreds or thousands of years. Times define the duration of the stationary-state and the magnitude of the time step; a fluid packet every hundred or thousand of years needs to be modeled instead of every single fluid packet.

The modified version of EQ3/6 has been applied to a test case with quartz and potassium feldspar as reactants and with a dilute acid solution as the initial fluid. Chemical evolution after the first fluid packet

is as expected, with first gibbsite, then kaolinite, then quartz, and finally muscovite coming into equilibrium with the fluid and being deposited (Fig. 9). The initial dissolution of quartz and the dissolution of K-feldspar throughout the system results in a decrease in their total mass, a decrease in their total surface areas and, consequently, a decrease in their dissolution rates. The rate of decrease in dissolution rates is low so that the mineralogic sequence in Fig. 9 persists for about 200 years. A fluid packet traversing the system at this time will experience a slower chemical evolution resulting from the slower dissolution rates. In general, subsequent fluid packets will not be in equilibrium with product phases deposited by earlier fluid packets at their precipitation fronts. At these points, previously deposited minerals become reactants causing a migration of the precipitation front

(Fig. 10). After 1000 years, a small zone of dissolving gibbsite, kaolinite, and muscovite exists before their respective current precipitation front locations. Precipitation front migration rates are indeed low ($\mu\text{m}/\text{yr}$) (Fig. 11), confirming our use of the stationary-state concept. These results are generally consistent with those presented in Lichtner (1988).

Our future activities will focus on coupling some of the logic within this simulator with the particle simulator.

Acknowledgments

This work was funded by the Institutional Research and Development Program of Lawrence Livermore National Laboratory, the Repository Technology Program of the U. S. Department of Energy, and the Subsurface Science Program of the Office of Energy Research, U. S. Department of Energy.

Figure 9. Paragenesis with quartz and K-feldspar as initial reactants at 1 yr. Gibbsite, kaolinite, and muscovite are products at this time; quartz is a reactant upstream but becomes a product as quartz and feldspar dissolution rates increase the dissolved silica concentration. There is a small zone where gibbsite and kaolinite coexist, and there is also a small zone where kaolinite and muscovite coexist. The precipitation fronts move downstream with subsequent fluid packets (arrows) because of a decrease in the upstream dissolution rates.

Figure 10. Paragenesis with quartz and K-feldspar as initial reactants predicted at 1000 yr. In contrast to the conditions at 1 yr (Fig. 9), the secondary minerals gibbsite, kaolinite, and muscovite are both products and reactants at this time. Upstream decreases in quartz and K-feldspar dissolution rates retard the approach to equilibrium for each of these minerals; this causes precipitation fronts to propagate downstream (arrows) and causes minerals previously deposited at the upstream margin to dissolve.

Figure 11. Migration rates of the precipitation fronts as a function of time.

References

- Ababou, R., D. B. McLaughlin, L. W. Gelhar (1988), *Three-Dimensional Flow in Random Porous Media*, R. M. Parsons Laboratory, Department of Civil Engineering, Massachusetts Institute of Technology, Cambridge, MA, Tech. Report No. 318.
- Ahlstrom, S., H. Foote, R. Arnett, C. Cole, and R. Serne (1977), *Multicomponent Mass Transport Model: Theory and Numerical Implementation*, Battelle Pacific Northwest Laboratories, Richland, WA, BNWL-2127.
- Cederberg, G. A., R. L. Street, and J. O. Leikie (1985), "A Groundwater Mass Transport and Equilibrium Chemistry Model for Multicomponent Systems," *Water Resources Res.* 21(8), 1095.
- Dagan, G. (1984), "Solute Transport in Heterogeneous Porous Formations," *J. Fluid. Mech.* 145, 151.
- Dagan, G. (1986), "Statistical Theory of Groundwater Flow and Transport: Pore to Laboratory, Laboratory to Formation, and Formation to Regional Scale," *Water Resources Res.* 22(9), 120s.
- Garven, G., and R. A. Freeze (1984), "Theoretical Analysis of the Role of Groundwater Flow in the Genesis of Stratabound Ore Deposits. I. Mathematical and Numerical Model," *Am. J. Sci.* 284, 1085.

- Gelhar, L. W. (1984), "Stochastic Analysis of Flow in Heterogeneous Porous Media," *Fundamentals of Transport Phenomena in Porous Media*, J. Bear and M. Corapcioglu, Eds. (Martinus Nijhof, Dordrecht, Netherlands), p. 673.
- Gelhar, L. W. (1986), "Stochastic Subsurface Hydrology: From Theory to Applications," *Water Resources Res.* 22(9), 135s.
- Gelhar, L. W. (1987), "Stochastic Analysis of Transport in Saturated and Unsaturated Porous Media," *Advances in Transport Phenomena in Porous Media*, J. Bear and M. Corapcioglu, Eds. (Martinus Nijhof, Dordrecht, Netherlands), p. 657.
- Gelhar, L. W., and C. W. Axness (1983), "Three-Dimensional Analysis of Macrodispersion in Aquifers," *Water Resources Res.* 19(1), 161.
- Graham, W., and D. McLaughlin (1988), "Stochastic Analysis of Nonstationary Subsurface Solute Transport, 1. Unconditional Moments," *Water Resources Res.* (to be published).
- Haken, H. (1983), *Advanced Synergetic* (Springer Verlag, New York, NY).
- Hockney, R. W., and J. W. Eastwood (1981), *Computer Simulation Using Particles* (McGraw-Hill, New York, NY).
- Hoecksema, R. J., and P. K. Kitanidis (1985), "Analysis of the Spatial Structure of Properties of Selected Aquifers," *Water Resources Res.* 21(4), 563.
- Huyakorn, P. S., and G. F. Pinder (1983), *Computational Methods in Subsurface Flow* (Academic Press, New York, NY).
- Kinzelbach, W. (1987), "The Random Walk Method in Pollutant Transport Simulation," *Groundwater Flow and Quality Modelling*, E. Custodio, A. Gurgui, and J. P. Lobo Ferreira, Eds. (D. Riedel, Dordrecht, Netherlands).
- Knapp, R. B. (1989), "A Lagrangian Transport Simulator with Multiple Paths and Stationary-States: Concepts, Implementation and Verification," Lawrence Livermore National Laboratory, Livermore, CA, UCRL-100952.
- Lewis, F. M., C. I. Voss, and J. Rubin (1986), "Numerical Simulation of Advective-Dispersive Multisolute Transport with Sorption, Ion Exchange, and Equilibrium Chemistry," *Water Resources Investigations*, U.S. Geological Survey, Reston, VA, Report 86-4022.
- Lichtner, P. C. (1988), "The Quasi-Stationary State Approximation to Coupled Mass Transport in Hydrothermal Systems," *Geochim. Cosmochim. Acta* 52, 143-165.
- Mantoglou, A., and L. W. Gelhar (1987a), "Stochastic Modeling of Large Scale, Transient Unsaturated Flow Systems," *Water Resources Res.* 23(1), 37.
- Mantoglou, A., and L. W. Gelhar (1987b), "Capillary Tension Head Variance, Mean Soil Moisture Content, and Effective Specific Soil Moisture Capacity of Transient, Unsaturated Flow in Stratified Soils," *Water Resources Res.* 23(1), 47.
- Mantoglou, A., and L. W. Gelhar (1987c), "Effective Hydraulic Conductivities of Transient Unsaturated Flow in Stratified Soils," *Water Resources Res.* 23(1), 57.
- Neuman, S. P., C. L. Winter, and C. M. Newman (1987), "Stochastic Theory of Field Scale Dispersion in Anisotropic Porous Media," *Water Resources Res.* 23(3), 453.
- Nguyen, V. V., W. G. Gray, G. F. Pinder, J. F. Botha, and D. A. Crerar (1982), "A Theoretical Investigation on the Transport of Chemicals in Reactive Porous Media," *Water Resources Res.* 18(4), 1149.
- Oran, E. S., and J. P. Boris (1987), *Numerical Simulation of Reactive Flow* (Elsevier, London).
- Tompson, A. F. B., and D. E. Dougherty (1988), "On the Use of Particle Tracking Methods in Modeling Solute Transport in Porous Media," *Computational Methods in Water Resources, vol. 2, Numerical Methods for Transport and Hydrologic Processes*, M. Celia, L. Ferrand, C. Brebbia, W. Gray, and G. Pinder, Eds. (Elsevier, London).
- Tompson, A. F. B., R. Ababou, and L. W. Gelhar (1989), "Implementation of the Three-Dimensional Turning Bands Random Field Generator," *Water Resources Res.* 25(10), 2227-2243.
- Vanmarcke, E. (1983), *Random Fields, Analysis and Synthesis* (MIT Press, Cambridge, MA).
- Washburn, J. F., F. E. Haszeta, C. S. Simmons, and C. R. Cole (1980), *Multicomponent Mass Transport Model: A Model for Simulating Migration of Radionuclides in Ground Water*, Pacific Northwest Laboratory, Richland, WA, PNL-3179.
- Wolery, T. J. (1979), *Calculation of Chemical Equilibrium between Aqueous Solution and Minerals: The EQ3/6 Software Package*, Lawrence Livermore National Laboratory, Livermore, CA, UCRL-52658.
- Yeh, G. T., and V. S. Tripathi (1989), "A Critical Evaluation of Recent Developments in Hydrogeochemical Transport Models of Reactive Multichemical Components," *Water Resources Res.* 25(1), 93.

Oxygen Diffusion in Olivine: The Effect of Oxygen Fugacity and Implications for Creep

Frederick J. Ryerson and William B. Durham

Experimental Geophysics Group

Our oxygen self-diffusion experiments on single crystals of San Carlos olivine ($\sim F_{O_{\text{ex}}}$) at $1200^{\circ}\text{C} \leq T \leq 1400^{\circ}\text{C}$, oxygen fugacities (f_{O_2}) along the Ni-NiO and Fe-FeO buffers, and on silica activity at the olivine-orthopyroxene buffer indicate that oxygen is not the slowest diffusing species in olivine. The activation energy for oxygen diffusion is also low compared with that obtained in a majority of measurements of creep in single crystal olivine. Hence, if oxygen diffusion contributes to the control of creep in olivine, it must be coupled to another process having a nonzero activation energy. A subinvestigation of the rate of sublimation from polished olivine surfaces, using a high-resolution thermal balance, showed surface erosion rates at 1300°C of 0.13 ± 0.10 nm/h. Such values are far too slow to noticeably affect our diffusion measurements at $\leq 1400^{\circ}\text{C}$.

Ionic diffusion in minerals plays a central role in controlling the rates of processes such as isotopic exchange, mineral growth and dissolution, solid-state reactions, homogenization of zoned crystals, formation of exsolution lamellae, and solid-state creep. In recent years, much attention has been focused on diffusion in olivine, $(\text{Fe,Mg})_2\text{SiO}_4$, because of its direct relevance to solid-state creep or rheology of the Earth's upper mantle (Weertman, 1970; Weertman and Weertman, 1975). Upper mantle rheology plays an important role in determining the rate of melt segregation, diapirism, and ultimately the balance of forces controlling plate motion and mantle convection.

Most steady-state creep mechanisms require diffusion. Depending on the material and temperature, diffusion rates may directly control the creep rate. The dependence of diffusion on chemical environment arises from the presence of crystalline imperfections (i.e., point defects) within the lattice. Without such defects, diffusion would be exceedingly

difficult. In terms of the Gibbs Phase Rule, each type of defect effectively represents a new component. The chemical activity of these components must be defined to completely describe the thermodynamic state of the material (Smyth and Stocker, 1975; Nakamura and Schmalzried, 1983). The diffusion coefficient depends on the concentration and mobility of crystalline defects, which in turn are a function of the energetics of defect formation and migration (Shewmon, 1963). Because defect concentrations are controlled by the thermodynamic conditions imposed on the material, it follows that the rates of diffusion are similarly controlled. In minerals containing cations with multiple oxidation states, the fugacity of oxygen f_{O_2} may be especially important.

The central interest in olivine concerns its modal dominance in the Earth's upper mantle, its probable role in controlling solid-state creep in this region, and the possibility that solid-state creep in olivine may be lattice diffusion-limited.

Before laboratory measurements of lattice diffusion-limited creep can be extrapolated to mantle strain rates, it must be established that creep in the upper mantle is similarly lattice diffusion-limited. Once established, it may be possible to predict the dependence of creep rate on external conditions from the dependence of the diffusion rate on external conditions. The strongest case for lattice diffusion-limited creep can be made by demonstrating that the creep rate and the lattice self-diffusion rate have the same dependence on external conditions.

The primary goal of our study is to determine the effect of variations in oxygen fugacity on the rate of oxygen self-diffusion in San Carlos olivine ($\sim F_{O_{\text{ex}}}$). The f_{O_2} dependence of oxygen diffusion is compared to that for creep to improve our physical understanding of the constitutive law for creep in olivine, a necessary step toward improving confidence in large extrapolations in strain rate.

Experimental Procedures

Surface Preparation and Orientation

The starting materials for the experiments were two single crystals of San Carlos olivine, both about 2 cm in diameter, chosen on the basis of clarity and the absence of inclusions and fractures. We oriented the crystals using optical and Laue back-reflection techniques. We cut slabs ~1 mm thick from the oriented crystals using a rotary diamond saw. We selected two orientations, parallel to the [010] and [100] crystallographic planes. We then polished the slabs to 0.3-mm Al_2O_3 . At this point, we set aside some of the material and gave it no further surface preparation. The remaining material was chemically etched in a dilute HF solution ($\text{HF}:\text{H}_2\text{O} = 1:10$ by volume) for 10–15 s. Again, we set aside a portion of this material and gave it no further surface preparation. We ion-milled the remaining material for 4 hr using Ar ions under an accelerating voltage of 4 kV, a milling angle of 15° from the horizontal, and a beam current of 150 mA over a target area ~20 mm in diameter. The surface preparation protocol resulted in three groups of oriented olivine samples: polished only (P), polished and etched (PE), and polished, etched, and milled (PEM). As a final step, we cemented the slabs to petrographic slides and cut them into prisms with dimensions of approximately $5 \times 5 \times 1$ mm.

Pretreatment of Olivine Samples

The diffusion of any atom in a crystalline material depends on the concentration of the appropriate point defects within the crystal, which in turn are determined by the chemical parameters of the components within the system (e.g., Kroger, 1974; Schmalzried, 1981).

Thus, in an investigation of diffusion in crystalline materials, one must control as many of the intensive chemical variables as possible.

The time necessary for the point-defect equilibration in olivine depends on the mobility of the point-defect and the dimensions of the sample (e.g., Yurek and Schmalzried, 1974). Mobilities can be obtained from the relaxation times observed in measurements of various point-defect-related phenomena. Following a change in f_{O_2} , relaxation times in creep tests in the range 1200–1400°C are also typically 1 hr or less (Mackwell et al., 1988). Those authors concluded that if creep is limited by dislocation climb, re-equilibration of minority as well as majority defects must occur within the observed relaxation time. Electrical conductivity is also controlled by the concentration of majority defects; conductivity measurements in olivine attain new equilibrium values in times typically less than 1 hr for temperatures above 1200°C following a change in f_{O_2} (Schock et al., 1989).

The relaxation data on natural olivines indicates that the times for equilibration of point defects in samples on the order of 1-mm thick are relatively rapid, ~1 hr at temperatures above 1000°C. To ensure that the olivine samples attained point defect equilibria prior to the introduction of ^{18}O , we preannealed the samples in flowing CO/CO_2 for times greater than or equal to those to be used in the diffusion anneals. In all cases, the preanneals were longer than 24 hr and the f_{O_2} and T were always identical to those used in the diffusion experiments. We performed the preanneals in a standard Deltech furnace equipped with an Al_2O_3 muffle tube and gas-mixing apparatus, and monitored the f_{O_2} with a zirconia sensor cell. The sample assembly consisted of the prepared olivine crystal, which sat in a sample boat

fabricated from powdered San Carlos peridotite sintered at 1100°C on the Ni-NiO buffer. We suspended the sample assembly from an Al_2O_3 rod with Pt-Pt 30% Rh wire; the sample boat prevented the Pt-Pt 30% Rh wire from coming in contact with the olivine crystal, thereby preventing loss of iron to the wire under reducing conditions.

Surface Sublimation Experiments

An early concern in our study was that surface sublimation might displace the effective position of the sample surface with respect to the diffusion profile during a high-temperature diffusion anneal. We performed an experiment to study the sublimation rate of San Carlos olivine under conditions duplicating those of our diffusion anneals. In addition, we attempted to reproduce the sublimation in pure forsterite observed by T. Shankland (unpublished) and by Durham et al. (1979). For both studies, we used a high-resolution thermal balance built to measure changes in nonstoichiometry in oxides (Dieckmann, 1982). We cut the samples into round discs with a diameter of ~7.5 mm and a thickness of ~0.9 mm. We oriented the forsterite discs normal to [100]; we did not cut the olivine discs to a preselected crystallographic orientation. From the orientation of characteristic [010]-plane microfractures often observed in San Carlos olivine [e.g., Wanamaker and Evans (1985)] and from the shape of the starting crystal, we estimate that the normal to the olivine discs was about 70° to [010]. We polished all discs on both sides, but did not acid etch or ion-mill them.

Samples in the thermal balance sit in an Al_2O_3 basket that is suspended at the end of a platinum wire or, for H_2 -rich atmospheres, a thin Al_2O_3 tube fastened with W wire. The activity of oxygen is established by flowing CO/CO_2

gas through the sample chamber, as is done in the preanneal of the diffusion samples. Volatilization of platinum or the reaction of platinum with olivine (alloying of iron with platinum depletes the olivine in iron causing the formation of orthopyroxene and the liberation of O_2) (Kohlstedt and Mackwell, 1987; Jaoul et al., 1987). This would lead to higher weight losses than that caused solely by olivine sublimation. Aside from weight losses caused solely by the loss of O_2 , uptake of Fe by the Pt would not be detected by the thermal balance because the weight monitored is that of the entire sample assembly and not that of the sample alone.

Oxygen-Diffusion Experiments

The most difficult aspect of the oxygen-diffusion experiment is the simultaneous control of both oxygen fugacity and the isotopic composition of the gas. The f_{O_2} must remain constant during the course of an experiment. It is desirable that the isotopic composition of the gas reservoir remain constant. This ensures that the experiment does measure diffusion in a semi-infinite medium from a well-stirred reservoir of constant composition. In these experiments, we used mixtures of CO and CO_2 that are 99% enriched in ^{18}O . We constructed a closed-system vacuum furnace in which a small sample (~160 mL) of isotopically enriched gas can be recirculated through the furnace hot zone and then recaptured at the end of the experiment (Fig. 1).

The system is based on a standard Deltech furnace with a small-bore (12.7-mm) Al_2O_3 muffle tube. The muffle tube is connected to a sorption pump and gas-supply system by water-cooled vacuum fittings at both ends of the tube. Other than the muffle tube, all of the valves, tubing, and gas-storage bottles in the system are standard stainless-steel, high-vacuum pressure fittings. The upper

Figure 1. Schematic of the vacuum furnace, pump, and gas storage assembly used for the oxygen-diffusion experiments.

fitting on the muffle tube has a vacuum feed-through to allow positioning of the sample assembly in the furnace.

We conditioned the muffle tube itself in ^{18}O at $1200^\circ C$ for as long as a week prior to any diffusion experiments to minimize the exchange of ^{18}O with the tube during the diffusion experiments. As in the preanneals, the sample assembly was made of boats of sintered San Carlos peridotite connected by Pt-Pt 30% Rh wire. These boats minimized line-of-sight contact between the noble metal wire and the olivine crystal and eliminated contact between the diffusion sample and the wire. This assembly allowed two olivine crystals (different orientations) to be placed in the hot zone of the furnace, along with solid buffer material (Fig. 2).

To control f_{O_2} during the diffusion experiments, we used solid Ni-NiO (NNO) and Fe-FeO (IW) buffers as an integral part of the sample assembly (Fig. 2). For runs conducted at NNO conditions, we placed a

Figure 2. Schematic of the sample assembly used in diffusion anneals containing pretreated olivine crystals and buffers.

Ni-metal cup filled with Ni^{18}O and Ni-metal powders in the sample assembly, which we then filled with a CO/CO_2 gas that was 99% CO_2 by volume. We prepared the Ni^{18}O by oxidizing Ni-metal powder in ^{18}O at 1200°C for 1 hr.

At the beginning of each experiment, we heated the furnace to run conditions. We attached the sample assembly to the feed-through sample rod assembly, which we connected to the muffle tube with the sample rod retracted to keep the sample assembly in the cold region of the furnace ($\sim 30^\circ\text{C}$). We used a sorption pump to evacuate the furnace to a pressure of ~ 1 Pa. After evacuation, we isolated the pump and added the ^{18}O enriched gas to the furnace until the pressure in the system was ~ 0.1 MPa. We then moved the sample from the cold end of the furnace to the hot zone. The sample reached the experimental temperature in 5–10 m. Because most of the diffusion experiments lasted longer than 8 hr, the duration of sample heating is expected to have a negligible effect on the observed diffusivities. At the end of the run, we retracted the sample rod and assembly to the cold end of the furnace. The sample assembly cooled quickly after retraction. For instance, a run at 1205°C cooled to 170°C within 6 min after being removed from the hot zone. Diffusion taking place during sample cooling is negligible. When the sample assembly reached room temperature, we pumped the ^{18}O -enriched gas from the furnace with a liquid-nitrogen-cooled, stainless-steel, gas-storage cylinder.

Analytical Procedures

We measured the oxygen diffusion profiles by the nuclear reaction $^{18}\text{O}(p, \alpha)^{15}\text{N}$. This technique has been used to obtain depth profiles in a number of oxygen-diffusion studies (Choudhury et al., 1965; Robin et al., 1973; Jaoul et al., 1980;

Figure 3. Typical α spectra obtained from an oxygen-diffused olivine sample during nuclear reaction analysis.

1981; Reddy and Cooper, 1982). When a sample containing ^{18}O is irradiated with monoenergetic protons, the reaction $^{18}\text{O}(p, \alpha)^{15}\text{N}$ is induced, producing α particles. The energy of the α particles as they leave the sample depends on the depth in the sample from which they were generated, whereas the intensity of the α -particle signal at a given energy depends on the concentration of ^{18}O at a particular depth. A typical energy spectrum from an olivine sample subsequent to an ^{18}O -diffusion anneal is shown in Fig. 3. The relationship between the energy of α -particles and their depth of emission is illustrated in Fig. 4. The protons strike the sample surface with an initial energy E_p . As the protons pass through the sample, they lose energy because of coulombic interaction with the sample. The energy at any depth is given by $E_p(X)$, and the rate of energy loss is a function of the sample composition. At depth X_R , the reaction occurs, and an α particle is produced. The reaction is exothermic ($Q = 3.97$ MeV), and the energy of the α particle at depth X_R is given by $E_\alpha(X_R)$. As for the protons, α particles leaving the sample lose energy; the energy at any depth X is a function of X and the depth of emission X_R and is given as $E_\alpha(X_R, X)$. The rate of energy loss is largely

a function of sample composition. As it leaves the surface of the sample, the α -particle energy is solely a function of its depth of origin $E_\alpha(X_R, 0)$. The α -particle energy spectrum observed will be a convolution of the ^{18}O depth profile and spreading factors due to beam energy spread, the straggling of protons and α particles. The depth

Figure 4. Energy-depth relations for incident protons and product α -particles during nuclear reaction analysis.

profile is obtained by deconvolution of these effects.

Data Reduction

We deconvoluted the energy spectra to obtain depth profiles, ^{18}O vs depth. We obtained diffusivities from the depth profiles by fitting the data to a solution to Fick's second law for one-dimensional diffusion into a semi-infinite medium from a surface held at constant composition (Crank, 1975). As in many diffusion experiments, it is difficult to obtain the surface concentration directly from the depth profile because of the finite depth or spatial resolution of the analytical technique. Following the procedure of Watson et al. (1985), we (1) estimated the value of C_0 from the depth profile, (2) fit a straight line to the inverted data using this value, and (3) assessed the quality of the estimated surface concentration.

Results and Analysis

Sublimation Experiments

We annealed two discs of polished San Carlos olivine and two discs of synthetic forsterite in the thermal balance. We ran all samples at $T = 1300^\circ\text{C}$. The olivine samples were run at $f_{\text{O}_2} = 3.3 \times 10^{-2}$ (NNO buffer); we ran the forsterite samples in a gas mixture of 5% H_2 and 95% Ar at a total pressure of 50 kPa.

We heated the first olivine run for 770 hr. The olivine showed a decelerating mass loss amounting to 20 mg over the first 10 hr of the anneal, 11 mg over the next 90 hr, and 2 mg over the remaining 57 hr. Blind runs before and after this anneal showed the balance to be very steady. On the basis of a mass loss of 2 mg/57 hr, the surface erosion rate from the sample averaged 0.13 nm/hr, or ~ 1 unit cell spacing

every 5 hr. The resolution of the measurement is about 0.1 nm/hr. These rates of sublimation are too small to affect the measured diffusion coefficients.

Diffusion Experiments

We conducted diffusion experiments between 1200°C and 1400°C at both IW and NNO conditions for the [100] and [010] directions (Table 1). In all cases, orthopyroxene was in excess (as a component of the peridotite sample boat). The profiles obtained in all of our experiments are in good agreement with the solution to Fick's law for the idealized one-dimensional geometry. Potential artifacts caused by differences in surface preparation have been eliminated or at least reduced to a constant level in this study.

An additional criterion that must be satisfied by all diffusion

Table 1. Experimental conditions and results. (IW is the Fe-FeO buffer; NNO is the Ni-NiO buffer; P is polished; E is etched; M is Ar-ion milled.)

Run	Surface preparation	Direction	Temperature ($^\circ\text{C}$)	Buffer	Time (s)	D (m^2s^{-1})
OA-1	P	[100]	1198	NNO	1.73×10^5	2.78×10^{-20}
OA-2	PE	[100]	1198	NNO	1.73×10^5	3.10×10^{-20}
OA-3	PEM	[100]	1198	NNO	1.73×10^5	2.75×10^{-20}
OA-4	P	[100]	1302	NNO	1.75×10^5	2.10×10^{-19}
OA-5	PE	[100]	1302	NNO	1.75×10^5	1.95×10^{-19}
OA-6	PEM	[100]	1302	NNO	1.75×10^5	1.76×10^{-19}
OA-7	PEM	[010]	1206	NNO	6.78×10^5	2.78×10^{-20}
OA-8	PEM	[100]	1206	NNO	6.78×10^5	2.06×10^{-20}
OA-9	PEM	[010]	1203	NNO	1.72×10^5	2.58×10^{-20}
OA-10	PEM	[100]	1203	NNO	1.72×10^5	3.43×10^{-20}
OA-11	PEM	[100]	1300	NNO	7.45×10^5	1.56×10^{-19}
OA-12	PEM	[010]	1300	NNO	7.45×10^5	4.03×10^{-19}
OA-13	PEM	[100]	1398	NNO	2.14×10^5	1.04×10^{-18}
OA-14	PEM	[010]	1398	NNO	2.14×10^5	1.94×10^{-18}
OA-15	PEM	[100]	1100	NNO	4.31×10^5	5.12×10^{-21}
OA-16	PEM	[010]	1100	NNO	4.31×10^5	2.66×10^{-21}
OA-17	PEM	[100]	1401	IW	2.10×10^4	1.35×10^{-19}
OA-18	PEM	[010]	1401	IW	2.10×10^4	2.04×10^{-19}
OA-19	PEM	[010]	1301	IW	2.56×10^5	2.26×10^{-20}
OA-20	PEM	[100]	1301	IW	2.56×10^5	1.56×10^{-20}

studies is the constancy of the measured diffusion coefficient as a function of time. Failure to meet this criterion may indicate the presence of a transport path other than lattice diffusion or chemical changes in the sample itself. Given the demonstrated reproducibility of the measurements, the constant value of the diffusion coefficient with time, and diffusion profiles consistent with the idealized initial and boundary conditions, we are confident that lattice diffusion is the only significant transport process being measured in these experiments.

The effect of temperature is much more pronounced than that of orientation. Most surprising, however, is the magnitude of the effect caused by changing f_{O_2} (Fig. 5). For instance, runs OA-13 and OA-17 were both performed at 1400°C in the [100] direction for comparable durations. OA-13 was conducted at NNO conditions, while OA-17 was conducted at IW conditions, a difference of four orders of magnitude in f_{O_2} . The resulting profiles indicate that diffusion is more rapid at NNO conditions, i.e., oxygen diffusion in olivine has a positive f_{O_2} dependence. The effect of changing the f_{O_2} from IW to the NNO buffer is comparable to that produced by a 100°C change in temperature at fixed f_{O_2} and orientation.

The results of all experiments are summarized in Fig. 6 as an Arrhenius plot of $\log D$ vs $1/T$. The lines on Fig. 6 are least-squares fits to the data obtained for a particular buffer and along a particular direction. For a typical Arrhenius-type treatment of the data (T as the only independent variable), the slopes of these lines yield the activation energy. It is important to recognize that, because the present experiments were conducted with solid buffers, T and f_{O_2} cannot be varied independently. Hence, the

slopes obtained from fitting the data in Fig. 6 yield only "apparent" activation energies. The oxygen-diffusion coefficient varies as a function of both T and f_{O_2} , so the variation in diffusion coefficients obtained along a given buffer reflect the effects of varying both T and f_{O_2} .

There is a clear separation between the results obtained under NNO and IW conditions at all temperatures. Diffusion at NNO conditions is always significantly faster at any temperature and for any orientation. Results for the IW runs indicate that diffusion in the [010] direction may be slightly faster than that in the [100]. The apparent activation energies for the IW experiments are 481 kJ·mol⁻¹ and 472 kJ·mol⁻¹ for [010] and [100], respectively. At NNO, the diffusivities for the two orientations are again very similar. However, at temperatures greater than 1200°C, the [010] direction is faster than the [100], and at temperatures

below 1200°C the [100] direction is faster than the [010]. This results in apparent activation energies that are different for the two directions.

The true activation energy for oxygen diffusion in olivine, 266 kJ·mol⁻¹, is significantly less than the apparent activation energies determined from the NNO and IW-buffered experiments.

In the context of understanding the point-defect chemistry of olivine, the most important result of this study is the positive dependence of oxygen diffusion on f_{O_2} . Both oxygen and silicon diffusion in forsterite are insensitive to variations in f_{O_2} . Our results yield a dependence of oxygen diffusion on f_{O_2} to the power $m \sim 0.2$. The value of $m \sim 1/6$ has also been observed for Mg-Fe interdiffusion (Buening and Buseck, 1973), and a value of 0.2 has been observed for tracer diffusion of Fe in olivine (Hermeling and Schmalzried, 1981). Because both oxygen and silicon diffusion in forsterite (Fe-free) are insensitive

Figure 5. Comparison of depth profiles obtained at NNO and IW conditions in the [100] direction at 1400°C.

Figure 6. Arrhenius plot of "apparent diffusivities" for the NNO and IW buffers in the [100] and [010] directions.

to variations in f_{O_2} , the positive dependence of diffusivities in olivine on f_{O_2} appears to be associated with the presence of Fe in the lattice.

Discussion

Point-Defect Chemistry vs Diffusion

The point-defect chemistry of a crystalline solid is a function of its composition and externally imposed physical and thermodynamic constraints. The point-defect chemistry of olivine has been the subject of a number of theoretical treatments

over the last two decades (Smyth and Stocker, 1975; Stocker, 1978a, b; Stocker and Smyth, 1978; Nakamura and Schmalzried, 1983, and others). Although diffusion is not necessarily impossible in a perfect crystal, steric complications argue that, energetically, it should be extremely unfavorable. The variation in diffusion coefficients with changing external conditions can be related to variations in point-defect chemistry.

Oxygen-vacancy-controlled diffusion is a mechanism commonly proposed for oxygen diffusion in olivine (e.g., Ricoult and Kohlstedt,

1985). Given the size of the oxygen anion relative to that of the interstices in such crystals, it is reasonable to expect that oxygen diffusion will always take place by a vacancy mechanism. Oxygen vacancies should disappear with increasing f_{O_2} , causing a decrease in oxygen diffusivity. Hence, an inverse correlation between f_{O_2} and oxygen diffusion is a logical expectation. The concentration of oxygen vacancies in orthopyroxene-buffered olivine varies as the $-1/6$ th power of f_{O_2} (Stocker and Smyth, 1978). The vacancy concentration and D_O should both decrease with increasing f_{O_2} . D_O measured in our experiments increases with increasing f_{O_2} ; hence we must conclude that oxygen diffusion in olivine is not controlled by an oxygen-vacancy mechanism. However, the concentration of doubly charged oxygen interstitials O_i^{2-} would control diffusion by either an interstitial or interstitialcy mechanism (Shewmon, 1963). The concentration of O_i^{2-} is expected to increase as the $+1/6$ power of f_{O_2} (e.g., Stocker and Smyth, 1978).

This exponent is close to the value of 0.2 measured here. Based on this similarity, it is enticing to conclude that oxygen diffuses by an interstitial mechanism. Indeed, Hobbs (1983) and Ricoult and Kohlstedt (1985) suggested that the diffusion of oxygen by an interstitial mechanism is the diffusive step controlling olivine deformation. The difficulty recognized by both groups was the steric complication introduced in the close-packed olivine structure by a large interstitial oxygen anion. The size of the oxygen anion (with charges of either -2 or -1) is simply too large to occupy any of the available interstitial sites in olivine.

In summary, the precise diffusion mechanism for oxygen in olivine cannot be determined from the currently available data. It can, however, be stated that oxygen

diffusion in olivine does not take place by a vacancy mechanism. The simplest explanation for the data is one of oxygen diffusion by an oxygen interstitial mechanism, as the f_{O_2} dependencies in both buffered olivine and forsterite correlate with the concentration of O_i expected from point-defect chemistry. The over-riding argument against this mechanism is the large size of the oxygen anion relative to that of the interstices in the olivine structure. The concentration of O_i in olivine is expected to vary with the activity of enstatite. The exponent for this dependence is $-2/3$ (Stocker and Smyth, 1978). Hence, at fixed f_{O_2} and T , D_O should decrease with increasing activity of enstatite.

Implications for Creep

"Creep" is a process whose precise description (e.g., activation energy, f_{O_2}) depends on external conditions. Different creep mechanisms abound for polycrystalline olivine [see deformation maps,

e.g., those of Stocker and Ashby (1973)]. Within the realm of intracrystalline dislocation creep, different slip systems have different constitutive descriptions, and, as revealed by a recent study by Bai et al. (1991), even these descriptions have a multiplicity depending on whether one buffers the SiO_2 activity with enstatite or magnesio-wüstite. If creep of olivine is limited by the oxygen diffusion or diffusion of some other component, then there should be some similarity in the way in which creep and diffusion depend on external conditions. Table 2 compares the temperature, f_{O_2} , and pressure dependence of creep, oxygen diffusion, and static recovery.

Considered in light of the data of Bai et al. (1991), it is easy to find agreement with our values of $m = 0.2$ and $Q = 266 \text{ kJ mol}^{-1}$. In most cases, however, the activation energy for creep is well in excess of that measured for oxygen diffusion. This result implies that, if oxygen diffusion

does play a part in the creep mechanism, it may be only part of a rate-limiting sequence. The entire creep process may be composed of a number of processes in such a way that the activation energy and m value (i.e., f_{O_2} dependence) for creep are equal to the sum of the activation energies and m values, respectively, of its parts. Note that the m value of processes coupled to diffusion in the rate-limiting sequence must be close to zero if the m values for creep and oxygen diffusion are approximately the same (Ricoult and Kohlstedt, 1985).

A plausible rate-limiting sequence involving self-diffusion is jog formation plus diffusion (Gueguen, 1979; Hobbs, 1983; Ricoult and Kohlstedt, 1985). Ricoult and Kohlstedt (1985) argue on the basis of point-defect models that the concentration of negatively charged jogs should show $m = -1/6$ and that the concentration of positively charged jogs should show $m = +1/6$. Adding these values to our result, $m = 0.2$

Table 2. Creep, recovery, and oxygen self-diffusion in olivine. Measurements made under enstatite buffer except as noted. $\tau \propto \tau_0^m \exp \{-(Q + PV^*)/RT\}$

Process	m		$Q \text{ kJ mol}^{-1}$		$V^* \text{ cm}^3 \text{ mol}^{-1}$	
	Value	References ^b	Value	References ^b	Value	References ^b
Creep	$1/6^a$	1, 2, 8	523	1		
	0	1	448	2	18^a	6
	$0-0.34$	3	240-1000	3		
			564^a	4	19^a	5
Recovery	-0.05 ± 0.04^a	9	323^a	5	14^a	7
			389^a	7		
Oxygen diffusion	0.2	This study	265	This study		

^aUnbuffered test.

^bReferences:

1. Ricoult and Kohlstedt (1985)

2. Kohlstedt and Hornack (1981)

3. Bai et al. (1991)

4. Goetze and Kohlstedt (1973)

5. Kohlstedt et al. (1980) as corrected by Karato (1981)

6. Ross et al. (1970) as corrected by Kohlstedt et al. (1980)

7. Karato and Ogawa (1982)

8. Jaoul et al. (1980)

9. Karato and Sato (1982)

covers the extremes in m for creep that Bai et al. (1991) found. Both types of jogs may limit creep in single crystal olivine under different crystallographic and thermodynamic conditions.

For situations where creep is self-diffusion limited, there is a possibility that oxygen is not the slowest diffusing species and, therefore, rate-limiting species. Direct measurements by Houlier et al. (1988) show that at 1300°C D_{Si} in olivine is two orders of magnitude lower than D_O . These results are counter-intuitive if one thinks in terms of the ionic radii of Si^{4+} and O^{2-} ions as they attempt to push themselves through the lattice. On the other hand, we have already stated that steric considerations also make O_i an unlikely player in oxygen self-diffusion.

The main question for upper-mantle rheology may be the relevance of the various creep mechanisms in Table 2 to flow in polycrystalline olivine. Activation energies for the polycrystal are consistent with the higher numbers in Table 2, being somewhat in excess of 500 kJ·mol⁻¹ (Karato et al., 1982; Chopra and Paterson, 1984), but as stated above, this value can be consistent with a diffusion-controlled creep mechanism. Creep in polycrystalline olivine has recently been measured as a function of f_{O_2} , yielding

values of $m > 0$ (Beeman, 1989). This strongly suggests that deformation in polycrystalline olivine is a complex, inhomogeneous blend of many individual systems that also show $m > 0$.

The one experiment done to measure the effect of oxygen fugacity on dislocation recovery in the static (unstressed) situation indicated that recovery was faster at lower f_{O_2} (Karato and Sato, 1982). This is the opposite of what one would expect from the creep results. Recovery counteracts the growth of dislocation density during creep; where recovery rate limits creep, faster recovery will result in a higher rate of deformation. Possible explanations are that the static recovery process is fundamentally different from what occurs during creep, or that recovery did not limit creep for any of the measurements in Table 2 (Karato and Sato, 1982).

Conclusions

The data presented here indicate that self-consistent diffusion coefficients and Fickian diffusion profiles can be obtained for oxygen diffusion in San Carlos olivine by employing methods to (1) prevent mass transport between Pt-bearing parts of the sample assembly and the olivine crystals, (2) remove the

cold-worked surface of the sample, and equilibrate the sample at the appropriate f_{O_2} prior to exposure to the tracer gas, and (3) impose appropriate thermodynamic controls on other oxide components. For CO/CO₂ mixtures producing f_{O_2} values between those at the NNO and IW buffers, surface sublimation is sufficiently slow as to have no significant effect on measured oxygen diffusion coefficients below 1400°C.

The positive f_{O_2} dependence displayed by these data preclude diffusion of oxygen by a vacancy mechanism within the f_{O_2} range studied. Hence, we must appeal to either diffusion by an interstitial/interstitially mechanism, or a coupled mechanism such as counter-vacancy diffusion. For countervacancy diffusion, the migration of anions is related to the concentration of vacancies on cation sites.

The activation energy for oxygen diffusion in olivine is similar to that of oxygen in forsterite, but is lower than that measured for a majority of creep processes in olivine. Hence, if oxygen diffusion plays a part in any of these processes, it must be coupled with an additional process, e.g., formation of kinks or jogs (see Ricoult and Kohlstedt, 1985), to account for the difference in activation energy between creep and diffusion.

References

- Bai, Q., S. Mackwell and D. Kohlstedt (1991), "High-Temperature Creep of Olivine Crystals: I. Mechanical Results for Buffered Samples," *J. Geophys. Res.* (in press).
- Beeman, M. L. (1989), *Deformation of Olivine-Glass Aggregates at High-Temperatures and Confining Pressures*, Ph.D. thesis, Cornell Univ., Ithaca, NY.
- Buening, D. K., and P. R. Buseck (1973), "Fe-Mg Lattice Diffusion in Olivine," *J. Geophys. Res.* **78**, 6852-6862.
- Chopra, P. N., and M. S. Paterson (1984), "The Role of Water in the Deformation of Dunite," *J. Geophys. Res.* **89**, 7861-7876.
- Choudhury, A., D. W. Palmer, G. Amsel, H. Curien, and P. Baruch (1965), "Study of Oxygen Diffusion in Quartz Using the Nuclear Reaction ¹⁸O(p, α)¹⁵N," *Solid State Comm.* **3**, 119-122.
- Crank, J. (1975), *The Mathematics of Diffusion*, (New York, Oxford University Press), p. 414.
- Dieckmann, R. (1982), "Defects and Cation Diffusion in Magnetite (IV): Nonstoichiometry and Point Defect Structure of Magnetite (Fe_{1-x}O₄)," *Ber. Bunsenges. Phys. Chem.* **86**, 112-118.
- Durham, W. B., C. Froidevaux, and O. Jaoul (1979), "Transient and Steady-State Creep of Pure Forsterite at Low Stress," *Phys. Earth Planet. Int.* **19**, 263-274.

- Gueguen, Y. (1979), "High-Temperature Olivine Creep: Evidence for Control by Edge Dislocations," *Geophys. Res. Lett.* **6**, 357-360.
- Hermeling, J., and H. Schmalzried (1984), "Tracer Diffusion of Fe-Cations in Olivine ($\text{Fe}_x\text{Mg}_{1-x}\text{SiO}_4$ (III)," *Phys. Chem. Miner.* **11**, 161-166.
- Hobbs, B. E. (1983), "Constraints on the Mechanism of Deformation of Olivine Imposed by Defect Chemistry," *Tectonophysics*, **92**, 35-69.
- Houlier, B., O. Jaoul, F. Abel, and R. C. Liebermann (1988), "Oxygen and Silicon Self-Diffusion in Natural Olivine at $T = 1300^\circ\text{C}$," *Phys. Earth Planet. Inter.* **50**, 240-250.
- Jaoul, O., C. Froidevaux, W. B. Durham, and M. Michet (1980), "Oxygen Self-Diffusion in Forsterite: Implications for the High-Temperature Creep Mechanism," *Earth Planet. Sci. Lett.* **47**, 391-397.
- Jaoul, O., M. Poumellec, C. Froidevaux, and A. Havette (1981), "Silicon Diffusion in Forsterite: A New Constraint for Understanding Mantle Deformation," F. D. Stacey, M. S. Paterson, and A. Nicolas, Eds., *Anelasticity in the Earth, Geodyn. Ser.* **4**, 95-100 (AGU, Washington, DC).
- Jaoul, O., B. Houlier, M. Cheraghmakani, R. Pichon, and R. C. Lieberman (1987), "Surface Destabilization and Laboratory-Induced Non-Stoichiometry in San Carlos Olivine," *Phys. Chem. Miner.* **15**, 41-53.
- Karato, S., and H. Sato (1982), "Effect of Oxygen Partial Pressure on the Dislocation Recovery in Olivine: A New Constraint on Creep Mechanisms," *Phys. Earth Planet. Inter.* **28**, 312-319.
- Karato, S., M. Toriumi, and T. Fujii (1982), "Dynamic Recrystallization and High-Temperature Rheology of Olivine, High-Pressure Research in Geophysics," S. Akimoto and M. H. Manghni, Eds., *Adv. Earth Planet. Sci.* **12**, 171-189.
- Kohlstedt, D. L., and P. Hornack (1981), "Effect of Oxygen Partial Pressure on the Creep of Olivine," F. D. Stacey, M. S. Paterson, and A. Nicolas, Eds., *Anelasticity in the Earth, Geodyn. Ser.* **4**, 101-107, (AGU, Washington, DC).
- Kohlstedt, D. L., and S. J. Mackwell (1987), "High-Temperature Stability of San Carlos Olivine," *Contrib. Mineral. Petrol.* **95**, 226-230.
- Kroger, F. A. (1974), *Chemistry of Imperfect Crystals*, (North-Holland, Amsterdam).
- Mackwell, S. J., D. Emsos, and D. L. Kohlstedt (1988), "Transient Creep of Olivine: Point-Defect Relaxation Times," *Philos. Mag.*, **57**, 779-789.
- Nakamura, A., and H. Schmalzried (1983), "On the Nonstoichiometry and Point Defects of Olivine," *Phys. Chem. Miner.* **10**, 27-37.
- Reddy, K. P. R., and Cooper, A. R. (1982), "Oxygen Diffusion in Sapphire," *J. Am. Ceram. Soc.* **65**, 634-638.
- Ricoult, D., and D. Kohlstedt (1985), "Experimental Evidence for the Effect of Chemical Environment upon the Creep Rate of Olivine," R. N. Schock, Ed., *Point Defects in Minerals. Geophys. Monograph Ser.* **31**, 171-184 (AGU, Washington, DC).
- Robin, R., A. R. Cooper, and A. H. Heuer (1973), "Application of a Non-Destructive Single-Spectrum Proton Activation Energy to Study Oxygen Diffusion in Zinc Oxide," *J. Appl. Phys.* **44**, 3770-3777.
- Schmalzried, H. (1981), *Solid State Reactions* (Verlag-Chemie, Weinheim, Germany).
- Schock, R. N., A. G. Duba, and T. J. Shankland (1989), "Electrical Conduction in Olivine," *J. Geophys. Res.* **94**, 5829-5839.
- T. Shankland, Los Alamos National Laboratory, Los Alamos, NM (unpublished).
- Shewmon, P. G. (1963), *Diffusion in Solids* (McGraw-Hill, New York).
- Smyth, D. M., and R. L. Stocker (1975), "Point Defects and Non-Stoichiometry in Forsterite," *Phys. Earth Planet. Inter.* **10**, 183-192.
- Stocker, R. L., and M. F. Ashby (1973), "On the Rheology of the Upper Mantle," *Rev. Geophys.* **11**, 391-426.
- Stocker, R. L. (1978a), "Point-Defect Formation Parameters in Olivine," *Phys. Earth Planet. Inter.* **17**, 108-117.
- Stocker, R. L. (1978b), "Influence of Oxygen Partial Pressure on Defect Concentrations in Olivine with a Fixed Cationic Ratio," *Phys. Earth Planet. Inter.* **17**, 118-129.
- Stocker, R. L., and D. M. Smyth (1978), "Effect of Enstatite Activity and Oxygen Partial Pressure on the Point-Defect Chemistry of Olivine," *Phys. Earth Planet. Inter.* **16**, 145-156.
- Wanamaker, B. J., and B. Evans (1985), "Experimental Diffusional Crack Healing in Quartz," R. N. Schock, Ed., *Point Defects in Minerals. Geophys. Monograph Ser.* **31**, 194-210 (AGU, Washington, DC).
- Watson, E. B., T. M. Harrison, and F. J. Ryerson (1985), "Diffusion of Sm, Sr, and Pb in Fluorapatite," *Geochim. Cosmochim. Acta* **49**, 1813-1823.
- Weertman, J. (1970), "The Creep Strength of the Earth's Mantle," *Rev. Geophys.* **8**, 145-168.
- Weertman, J., and J. R. Weertman (1975), "High-Temperature Creep of Rock and Mantle Viscosity," *Annu. Rev. Geophys.* **5**, 293-315.
- Yurek, C. J., and H. Schmalzried (1974), "Interdiffusion in (ABO)-Type Solid Solutions and the Validity of Darken's Equation," *Ber. Bunsenges. Phys. Chem.* **78**, 1379-1386.

Rupture Process of the 1965 Rat Islands Earthquake

Susan L. Beck

Seismology and Applied Geophysics Group
Institute of Geophysics and Planetary Physics

The great Rat Islands underthrusting earthquake ($M_W = 8.7$) of February 4, 1965, represents subduction of the Pacific plate beneath the North American plate along a 600-km segment of the western end of the Aleutian Islands. Body-wave inversion techniques are used to determine the spatial and temporal heterogeneities associated with the Rat Islands earthquake. Source time functions deconvolved from long-period teleseismic P-waves show three main pulses of moment release. Three asperities along the fault are identified and located. The first and largest asperity extends from the epicenter to 100 km in the direction of 300° . The second and third asperities are centered ~ 240 and ~ 380 km WNW of the epicenter. The overriding plate along the western Aleutian subduction zone is laterally segmented into a series of rigid tectonic blocks separated by fault-controlled canyons and extensional basins (Geist et al., 1988). We suggest that the central undeformed parts of the blocks have the strongest coupling with the down-going plate and are the sites of the largest moment release during an underthrusting earthquake. The three asperities determined from the P-waves correspond to the Rat, Buldir, and Near tectonic blocks. Hence, the P-wave seismic moment release of the Rat Islands earthquake is controlled by the lateral segmentation of the overriding plate

Although plate boundary segments fail repeatedly in large earthquakes, the seismic moment release and the recurrence intervals for underthrusting earthquakes vary dramatically in successive earthquake cycles. This variation indicates spatial heterogeneity in the stress level and material properties along the plate boundary. We do not yet understand the temporal and spatial heterogeneities associated with the faulting nor the interaction of plate boundary segments. This lack of understanding is due in part to a lack of knowledge about the rupture process of individual earthquakes and of more than one earthquake cycle along the same segment of the plate boundary. The asperity model provides a framework in which to view many aspects

of fault heterogeneities (Kanamori, 1981; Lay et al., 1982). In the asperity model, a fault consists of patches having different failure strengths. The strongest regions are often termed asperities, and they rupture in the largest earthquakes. The distribution and size of the dominant asperities, along a plate boundary, control the rupture of the largest earthquakes. Many studies have identified asperities associated with an individual earthquake rupture (e.g., Beck and Ruff, 1984; Schwartz and Ruff, 1987). However, the physical properties of asperities, the interaction of adjacent asperities along a plate boundary segment, and the variations between successive earthquake cycles are not well understood. The February 4, 1965, Rat Islands earthquake

($M_W = 8.7$) yields information about the details of the rupture of a truly great earthquake and provides some insight into asperity interaction and correlation with the lateral segmentation along the plate boundary.

The 1965 Rat Islands earthquake is one of the largest underthrusting earthquakes to occur since the deployment of the World Wide Standard Seismograph Network (WWSSN). This earthquake represents subduction of the Pacific plate beneath the North American plate along a 600-km segment of the western end of the Aleutian Islands (Fig. 1). We have studied the temporal and spatial heterogeneities associated with the rupture of the 1965 Rat Islands earthquake. The large surface-wave seismic moment

Figure 1. Western Aleutian arc showing the epicenter (large black diamond) of the February 4, 1965, Rat Islands main shock. The diamonds are the aftershocks with $M > 5$ relocated by Spence (1977), occurring between the February 4, 1965, main shock and March 30, 1965. The focal mechanism for the main shock determined from surface waves (Wu and Kanamori, 1973) is shown.

of 140×10^{27} dyne-cm (Wu and Kanamori, 1973) and the long aftershock area (~ 600 km along the strike) allow us to study the fault-plane heterogeneities associated with a great subduction zone earthquake. We have compared the spatial heterogeneities of the main shock with the aftershocks and the lateral segmentation along the subduction zone. There is a good correlation between the spatial moment release as determined from the P -waves for the main shock and the lateral segmentation of the overriding plate.

P-Wave Analysis

For an earthquake this large all the WWSSN nondiffracted long-period vertical P -waves are off scale. Hence, very few studies have been done on the body waves of such large earthquakes. We have used both long-period nondiffracted

horizontal and diffracted vertical P -wave seismograms. Horizontal receiver factors were determined by comparing horizontal- and vertical-component amplitudes for the first few P -wave cycles or by using a theoretical correction (Bullen, 1963) if the vertical component went off-scale immediately. We used diffracted P -waves to increase the azimuthal coverage and to determine the total source duration.

The long-period P -waves for the February 4, 1965, earthquake are complex with a long duration and an emergent start (Fig. 2). The start times for the P -waves were picked from short-period vertical components when possible. Single-station source-time functions are deconvolved with a Green's function distributed over a depth range of 10–40 km (Fig. 2). The Green's functions included the direct P , pP , and sP surface reflections and ocean-layer multiple reflections (Ruff and

Kanamori, 1983). Figure 2 shows some examples of source-time functions for single stations with a P -wave duration of at least 3 min. The source-time functions are complex but consistently show at least three main pulses of seismic moment release (Fig. 2). The three pulses of moment release have variable character and different durations.

The first pulse of moment release has a duration of 50–55 s with a long ramp at the beginning. The initial ramp rises for ~ 40 s. This pulse of moment release is fairly smooth. There is observable directivity associated with the truncation of the pulse (labeled A1 in Fig. 2). The second pulse of moment release is less coherent from station to station and consists of two to three subpulses. Stations to the NW and N show two subpulses. Stations to the NE and E show a more complex series of three subpulses. It is hard to pick consistent features associated with this pulse of moment release for directivity analysis. The third pulse of moment release has a duration of 25–30 s and is consistent from station to station. The truncation (C1) of the third pulse of moment release shows consistent directivity. The observable directivity allows us to locate spatially the temporal moment release along the fault for the consistent features in the source-time functions.

The directivity analysis consists of identifying consistent features in the source-time functions from different stations and of using the variation in timing relative to the initial onset of the P -wave to spatially locate the feature. The observed delay time of any feature at the i th station relative to the epicentral arrival time T_i is linearly related to X and t by $T_i = \Gamma_i X + t$, where Γ_i is the directivity parameter for the i th station (product of the ray parameter and the cosine of the angle between the rupture azimuth and station azimuth). The distance

Figure 2. Deconvolved single-station source-time functions for the February 4, 1965, Rat Island earthquake. The solid trace is the observed seismogram, and the dotted trace is the synthetic seismogram for the source-time function shown for each station. The station azimuth (AZ), epicentral distance (Dist), and horizontal component (N, E) if used are shown for each station. The source-time functions show three main pulses of moment release (A, B, C). A1, A2, B1, B2, C1, and C2 indicate the consistent features that can be observed at many stations within each pulse of moment release.

X and the actual delay time t of the feature are given by the slope and y intercept, respectively, of the best-fit line through the data (Fig. 3). To determine the best rupture direction, we step through all possible rupture azimuths and find the azimuth that produces the overall best-fit straight line (Fig. 3).

Although the first pulse of moment release is smooth, we were able to pick the time at which the pulse began to go down (labeled A1)

for 21 stations. The truncation of the first pulse (A1) occurs at 41.4 ± 0.3 s and is located 103 ± 11 km WNW of the epicenter. This gives an apparent rupture velocity of 2.49 km/s. This location gives a correlation coefficient of 0.90 for the best-fit straight line (Fig. 3).

The second pulse of moment release is variable in character, and it is much harder to pick coherent features. We looked at the directivity associated with the largest

subpulse (B1) at 15 stations and found a delay time of 100.8 ± 0.5 s and a location 223 ± 18 km WNW of the epicenter. However, this is not very reliable due to the variable character of the pulse. To determine how coherent this second pulse of moment release is, we used an inversion technique discussed in the next section.

The third pulse is a sharp feature on the source-time functions. Directivity analysis indicates a

Figure 3. Best-fit (least-squares) straight lines for the delay time T_i vs directivity parameter ($p \cos \theta$), for each station for the three main features identified on the source-time functions. The slope of the line X gives the horizontal distance to the feature and the zero-intercept t gives the actual delay time. The best rupture direction is 300° for each feature. The plot in the lower right shows the correlation coefficients of the best-fit straight lines as a function of the assumed rupture azimuth for each feature.

delay of 156.5 ± 0.2 s and a location 386 ± 18 km WNW of the epicenter for the truncation of the third pulse. The correlation coefficient for the best-fit straight line is 0.99 for a rupture direction of 300° (Fig. 3). This gives an overall average rupture velocity of 2.47 km/s. After the third pulse of moment release, we see no coherent moment release in the source-time functions. However, there could be low-level moment release that is not resolvable in the body waves.

It is hard to determine the seismic moment from P -waves for this earthquake, because we do not have any vertical nondiffracted P -waves. Stations such as COP (72.8°) and PTO (87.7°) give seismic moments of 40 and 34×10^{27} dyne-cm, respectively. This is much less than the surface-wave moment of 140×10^{27} dyne-cm (Wu and Kanamori, 1973). Seismic-moment determinations of great earthquakes from body waves tend to underestimate the total seismic-moment

release because of the limited pass band of the instrument.

However, the body waves are sensitive to the rupture complexities. The discrepancy in moment release indicates that a long-period component of moment release is not accounted for in our body-wave modeling. This missing moment release cannot be confined to the individual asperities but must be spread over a large part of, if not the entire, fault area. This implies that there is substantial moment release

in the areas around the asperities. If we add the long-period seismic moment release to the source time function as a long-period half-sine wave over 240 s so that the total moment is 140×10^{27} dyne-cm, the synthetic seismograms still fit the observed seismogram extremely well.

Tomographic Inversion

To quantitatively determine the moment release along the fault, we have used the inversion method devised by Ruff (1987). We have inverted the previously determined single-station source-time functions for a space-time image of the rupture. This method uses *a priori* estimates of the rupture azimuth and velocity, and iteratively determines the moment-release distribution that best fits the observed time functions in a least-squares sense. Many rupture azimuths and velocities can be tested easily and quickly, and the best overall fit to the time functions gives the best choice of rupture parameters. This method assumes the following about the earthquake rupture. First, the fault length (~600 km) is much longer than the width (~50 to 70 km), therefore, we solve only for one spatial dimension. Second, this method assumes that the rupture front spreads out from the epicenter and that most of the displacement or moment release occurs as the rupture front passes by. In other words, a portion of the fault does not rerupture after the rupture front has gone by. If we accept this view of earthquake rupture, then we can invert for coherent features along the one dimension of the fault.

We first tested a fault with a unilateral rupture from 0 to 600 km, discretized with a 20-km spatial interval and 240-s source-time function duration. We used 12 source-time functions with a duration of 240 s.

The source-time functions were baseline normalized to have zero moment in order to determine the best rupture azimuth. Synthetic source-time functions are produced for each model image. The match between the synthetic and observed source function is measured by the parameter c , the ratio of the error vector length to the data vector length. After ten iterations there was very little decrease in the error parameter. To determine the best rupture azimuth, the inversion is performed systematically for a large range of azimuths. A rupture azimuth of 300° yields the smallest value of c for all rupture velocities. We tested for rupture velocity but found very little resolution between 2.0 and 3.5 km/s. We also tested for a bilateral rupture to determine if there was any resolvable moment release ESE of the epicenter. In this case, the initial model estimate has moment release symmetric about the epicenter, but, with each successive iteration, the moment release is concentrated in the WNW direction.

Hence, the rupture appears to be unilateral to the WNW direction. For our final model we use a rupture azimuth of 300° , a rupture velocity of 2.5 km/s, and a fault length of 500 km (Fig. 4). We normalized the source-time functions to have a seismic moment of 30×10^{27} dyne-cm, the average seismic moment determined from the *P*-waves. Figure 4 shows the first and tenth iteration of the rupture image and data. There are three main pulses of moment release. We find no coherent moment release after 160 s, which corresponds spatially to beyond ~400 km WNW of the epicenter. This method also computes the time-integrated moment density along the fault (Fig. 5).

From the *P*-waves we can identify three regions of concentrated moment release. We interpret these

as asperities for the 1965 Rat Island earthquake. The first asperity corresponds to a smooth rupture occurring between the epicenter and 100 km to the WNW. The second region of moment release is less coherent and is probably a series of small asperities close together in time and space. The third asperity is coherent from station to station, but much shorter in duration and spatial extent than the first asperity, and occurs between 360–420 km WNW of the epicenter. Although the aftershocks extend for ~600 km WNW of the epicenter, we cannot resolve any moment release beyond ~400 km WNW of the epicenter.

The moment release determined from the *P*-waves is less than one-third the surface-wave moment. We have also used the tomographic inversion including the entire surface-wave moment (140×10^{27} dyne-cm). Of course, there is no spatial resolution on the additional moment that is added into the source-time functions as a smooth half-sine wave. We can estimate the peak seismic displacement from this moment-rate density function, assuming a fault width and a rigidity.

For a fault width of 60 km and a rigidity of 5×10^{11} dyne/cm², the peak resolvable seismic displacement is 12 m. For a fault width of 100 km, the peak displacement is 7.5 m. A larger fault width would decrease the displacement.

Aftershocks

The U.S. Coast and Geodetic Survey recorded 870 aftershocks that were large enough to routinely locate. These aftershocks occurred in the 45 days following the February 4, 1965, main shock. These events covered an area ~650 km long and ~200 km wide. Stauder (1968) determined focal mechanisms from *P*-wave first-motion and *S*-wave polarization data for the largest aftershocks. Stauder (1968) found

Figure 4. Final space-time image of the rupture process of the 1965 Rat Islands earthquake from the tomographic imaging technique devised by Ruff (1987). The data on the right are the previously determined source-time functions shown as the solid traces. The screened traces are the synthetic source-time functions for the rupture model shown on the left. The rupture image has spatial extent from 0 (corresponding to the epicenter) to 500 km in the direction of 300° and an *a priori* rupture velocity of 2.5 km/s. The rupture image shows three pulses of moment release.

two types of focal mechanisms: (1) underthrusting mechanisms similar to the main shock from events located arcward of the trench, and (2) normal-fault focal mechanisms from events occurring near the trench. The largest aftershock was a normal fault event on March 30, 1965 ($M_s = 7.5$), and was located trenchward of the epicenter and largest asperity (Fig. 5).

Spence (1977) relocated the aftershocks for the 1965 Rat Islands earthquake for events having 70 or more teleseismic *P*-wave observations ($M > 5.3$) by the first-order arrival time difference (ATD) model. *P*-wave arrival times from the nuclear explosion Long Shot and from an event on September 27, 1965, were the reference data for the relocation. Figure 5 shows the aftershocks between the main shock and the large normal fault aftershock ($M_s = 7.5$) on March 30, 1965.

The relocated aftershocks define an area of ~600 km along the strike and ~50–60-km wide. We have used these relocated aftershocks to define the width of faulting. There is a noticeable lack of large underthrusting type aftershocks between the epicenter and 130 km WNW along the strike (Fig. 5). This region corresponds to the location of the largest asperity determined from *P*-waves for the 1965 main shock. The lack of $M > 5$ aftershocks suggests that the asperity region failed completely during the main shock.

Lateral Segmentation of the Aleutian Subduction Zone

Many studies have identified temporal and spatial heterogeneity associated with the rupture of underthrusting subduction-zone earthquakes using body waves and have interpreted the heterogeneity

Figure 5. Map view of the first-order asperity distribution for the February 4, 1965, Rat Islands earthquake. The insert shows the moment rate-density function along the fault strike based on the tomographic imaging. The asperities in the map view are constrained to 50 km wide. There is a lack of aftershocks occurring in the first and third asperity regions. The three regions of moment release or asperities are labeled A, B, and C.

in the framework of asperities. However, it is not clear what asperities represent physically. Efforts to identify bathymetric features (such as fracture zones and a seismic ridges) on the down-going plate that correlate with the asperities have generally been unsuccessful. We find a correlation between the lateral segmentation of the overriding plate and asperities determined from the *P*-waves for the 1965 Rat Islands earthquake.

Between 180°W and 170°E along the Aleutian trench the overriding plate consists of a series of transverse tectonic canyons that cut through the Aleutian Trench and trend nearly at right angles to the regional slip vector of the oceanic lithosphere (Spence, 1977). Gates and Gibson (1956) suggested that these canyons are of tectonic origin rather than of

an erosional origin based on geomorphic evidence. Geist et al. (1988) have defined three rigid tectonic blocks: from east to west, the Rat block, Buldir block, and Near block (Fig. 6). They suggest these blocks formed as a result of clockwise rotation due to oblique subduction. The transverse canyons in the overriding plate are formed by differential rotation and along arc translation of the blocks (Geist et al., 1988). The blocks are internally undeformed but separated by fault-controlled canyons and extensional basins (Fig. 6). We suggest the central undeformed parts of the blocks have the strongest coupling with the down-going plate and, hence, are the sites of the largest moment release during an underthrusting earthquake.

The first pulse of seismic moment release occurs between the

epicenter ~100 km WNW of the epicenter. This pulse of moment release is very smooth with a long duration. This region corresponds to smooth subducting seafloor and the eastern two-thirds of the Rat tectonic block. It also corresponds to a lack of $M > 5$ aftershocks (Spence, 1977). This suggests that this region was probably strongly coupled over a large area and failed completely during the main shock rupture. The second pulse of moment release in the source time functions is variable in character and consists of several small pulses. The locations of these pulses of moment release correspond to the Buldir block. We interpret this as an indication of several smaller regions breaking in a less strongly coupled area of the fault. This region also corresponds to $M < 5$ aftershocks. This would suggest that the Buldir block is not as strongly coupled as the Rat block. The third pulse of moment release occurs ~400 km WNW of the epicenter and within the eastern half of the Near Block. This pulse of moment release has a spatial dimension of ~50 km, about one-half of the first pulse. The moment release associated with the February 4, 1965, earthquake corresponds with the lateral segmentation of the overriding plate along the subduction zone.

Previous Earthquakes

This same segment of the subduction zone had several earthquakes between 1898 and 1929. From east to west they are:

- October 11, 1898 ($M_S = 6.9$),
- August 17, 1906 ($M_S = 7.8$),
- September 9, 1910 ($M_S = 7.0$),
- March 22, 1905, ($M_S = 7.0$),
- June 29, 1898 ($M_S = 7.6$),
- September 15, 1905 ($M_S = 7.4$),
- March 7, 1929 ($M_S = 7.7$),
- September 2, 1907 ($M_S = 7.4$),

(Boyd and Learner-Lam, 1988; Abe and Noguchi 1983; Geller and

Figure 6. Western end of the Aleutian arc showing the tectonic blocks from Geist et al. (1988), and the locations of the asperities identified in this study.

Kanamori, 1977) (Fig. 7). The relocations from Boyd and Learner-Lam (1988) indicate that the events at the turn-of-the-century cluster at the ends of the 1965 aftershock area. It is hard to evaluate the reliability of the locations for earthquakes at the turn-of-the-century. The revised magnitudes by Abe and Noguchi (1983) are smaller than previous magnitude estimates. There are two possible interpretations for the earthquakes at the turn-of-the-century:

- These events are not equivalent to the 1965 main shock. The entire plate segment did not fail. The location of the events at the edges of the 1965 zone and the revised magnitudes indicate that these events did not fail the entire 1965 zone. The sum of the turn-of-the-century events is $<10\%$ of the 1965 event. This suggests that we have not seen a

previous earthquake cycle and the recurrence interval is longer than ~ 65 yr.

- The events at the turn-of-the-century represent failure of the entire segment that failed in 1965. This implies a recurrence interval of 65 yr as well as a variation on the rupture mode between successive earthquake cycles.

Sykes et al. (1981) suggested that the turn-of-the-century earthquakes began with smaller initial events than the 1965 earthquake and, thus, failed to trigger a rupture over the entire area as one event.

Assuming the turn-of-the-century earthquakes represent an earthquake cycle, the accumulated tectonic displacement with a convergence rate of 8 cm/yr is 5 m . As discussed previously, the peak seismic displacement is 12 m (assuming a 60-km fault width). This value

is larger than the accumulated tectonic displacement between 1900 and 1965. If we assume the asperities stay locked between subsequent earthquakes, then the recurrence interval should be ~ 160 yr or more.

We should consider the possibility that the turn-of-the-century events are not the previous earthquake cycle. These events occurred at the edges of the 1965 rupture zone, outside the locations of the dominant asperities.

The February 4, 1965, Rat Islands earthquake failed as a multiple asperity event with three identifiable regions of concentrated moment release. The asperities for the Rat Islands earthquake correspond to the segmentation of the overriding plate along the western Aleutian arc. For this earthquake, the tectonic blocks in the overriding plate controlled the rupture of this

- Lay, T., H. Kanamori, and L. Ruff (1982), "The Asperity Model and the Nature of Large Subduction Zone Earthquakes," *Earthquake Predict. Res.* **1**, 3–71.
- Minster, J., and T. Jordan (1978), "Present-Day Plate Motions," *J. Geophys. Res.* **83**, 5331–5354.
- Ruff, L. (1987), "Tomographic Imaging of Seismic Sources," *Seismic Tomography*, G. Nolet, Ed., (D. Reidel Publishing Company), pp. 339–366.
- Ruff, L., and H. Kanamori (1983), "The Rupture Process and Asperity Distribution of Three Great Earthquakes from Long-Period Diffracted P-Waves," *Phys. Earth Planet. Inter.* **31**, 202–230.
- Schwartz, S., and L. Ruff (1987), "Asperity Distribution and Earthquake Occurrence in the Southern Kurile Arc," *Phys. Earth Planet. Inter.* **49**, 54–77.
- Spence, W. (1977), "The Aleutian Arc: Tectonic Blocks, Episodic Subduction, Strain Diffusion and Magma Generation," *J. Geophys. Res.* **82**, 213–230.
- Stauder, W. (1968), "Mechanism of the Rat Island Earthquake Sequence of February 4, 1965, with Relation to Island Arcs and Sea Floor Spreading," *J. Geophys. Res.* **73**, 3847–3858.
- Sykes, L., J. B. Kisslinger, L. S. House, J. N. Davies, and K. H. Jacob (1981), "Rupture Zones and Repeat Times of Great Earthquakes along the Alaska-Aleutian Arc," *Earthquake Prediction, an International Review*, Maurice Ewing Series, vol. 4, D. W. Simpson and P. G. Richards, Eds., (AGU, Washington D.C.), pp. 73–80.
- Wu, F. T., and H. Kanamori (1973), "Source Mechanism of February 4, 1965, Rat Island Earthquake," *J. Geophys. Res.* **78**, 6082–6092.

Testing Newton's Inverse-Square Law of Gravity Using the BREN Tower

Paul W. Kasameyer

Major Contributors

Orrin D. Fackler, Donald J. Felske, Robert L. Harris,
Judith E. Kammeraad, Melvyn R. Millett,
Marshall J. Mugge, and James Thomas

Seismology and Applied Geophysics Group

We performed a test of Newton's universal theory of gravitation at the Nevada Test Site (NTS) using the BREN (Bare Reactor Experiment Nevada) tower. We measured gravity at 12 heights on this 465-m tower and at 281 locations on the ground. The surface points fell within 91 optimally chosen sectors that extended out to 2.6 km from the tower. These data were combined with 60,000 additional surface gravity measurements within 300 km of the tower. We used a surface integral derived from Laplace's equation to continue the surface gravity field upward. The first-phase results from our search for distance-dependent deviations from Newtonian gravity show no evidence for a fifth force. These high-sensitivity results provide an important benchmark for grand unification theories.

Three centuries ago, Sir Isaac Newton proposed the law of gravitation. This law states that any two particles of matter in the universe attract each other with a force that acts along the line joining them, and that the magnitude of this force is proportional to the product of the particle masses and is inversely proportional to the square of the distance between them. This last aspect, called the inverse-square law of gravity, is discussed here.

Newton's law of gravity has withstood exhaustive testing in the laboratory with small masses and on the planetary scale with natural and man-made satellites. Until recently, however, it had not been tested in the intermediate range (from 10 m to 10 km). Such tests are of particular interest because grand unification theories, which seek to unify the force of gravity with the three other fundamental forces (strong

interactions, electromagnetism, and weak interactions), have suggested that Newton's law may break down in this range (Gibbons and Whiting, 1981). The effects of such a breakdown would be small but could be observed using modern equipment.

Experimental Tests for Non-Newtonian Gravity

The experiments conducted in the past century to search for instances of non-Newtonian gravity (i.e., gravitational behavior that departs from that predicted by Newton's law) have been mostly of two types: composition-dependent tests and distance-dependent tests.

Composition-Dependent Tests

In the first type of experiment (composition-dependent), one searches for a dependence of the gravitational force on the type of

material, not just its mass. The most famous experiment in this category was reported in 1922 by Eötvös, who placed masses of different materials on a torsion balance. The motion of the balance showed whether the ratio of gravitational to Coriolis force was the same for each material. Eötvös claimed to observe identical forces for many materials. However, Fischbach et al., reanalyzed this experiment in 1986; they claimed that they found evidence suggesting the possible existence of non-Newtonian gravity or another fundamental force—a "fifth force." This claim generated a flurry of experiments, of which the most precise were conducted by Stubbs et al. (1987) and Adelberger et al. (1987). They found no evidence for a composition-dependent fifth force within the sensitivity limits of their instruments. The conflicting results of these experiments have not yet been fully explained.

Distance-Dependent Tests

In the second type of experiment (distance-dependent), one searches for a deviation from the inverse-square law in the distance-dependence of the gravitational force. One approach is to measure gravity at a number of different locations down a borehole and to compare these measurements with predictions obtained using Newton's law. The reliability of these predictions depends on having reliable information on the density variations in the Earth.

In another distance-dependent experimental approach, the gravity is measured on the surface of the Earth around a tower. Laplace's equation is used to predict the gravity on the tower, and then these predictions are compared with the actual measurements. Knowing the Earth's density distribution is not necessary in this approach. Although this procedure seems straightforward, it is complicated by the following:

- The Earth does not have a simple shape, which is a particularly important fact in the design of a gravity survey.
- Gravity measurements cannot be obtained everywhere on the Earth's surface, so sampling uncertainties must be carefully determined.
- Each experimenter uses a different method to predict gravity on the tower from the surface gravity measurements and to determine the corresponding uncertainties, making it difficult to compare results from different experiments.

Nevertheless, this method, when carefully applied, can provide an important benchmark for grand unification theories.

Borehole vs Tower Experiments

Several borehole experiments have been conducted by Stacey and

his collaborators in the past 10 years (Stacey et al., 1981; Holding and Tuck, 1984; Holding et al., 1986). Their most famous experiment, conducted in a deep Australian mine, led them to conclude that there is a *repulsive* intermediate-range interaction that has a strength of about 1% of Newtonian gravity and that decreases exponentially over a range of about 200 m. However, other more recent experiments do not agree with the magnitude of the interaction or even with whether it is *attractive* or *repulsive*. For example, in a tower experiment in 1988, Eckhardt et al. (1988) and Romaldes et al. (1989) claimed to observe a breakdown of Newtonian gravity that indicated an additional *attractive* force.

Because of the conflicting results obtained in borehole and tower experiments, it is important to consider the possible sources of error in these experiments. In a borehole experiment, the prediction of the gravitational force between a known mass and the Earth involves a summation of the contributions from all directions. This prediction would be simple if the Earth were spherically symmetric, that is, if it were a perfect sphere and if density depended only on distance from the center of the Earth. Then, by employing the Gauss theorem, the contribution from the shell of earth that is above the measurement location at Earth radius r would be identically zero, and only the mass within r would contribute to the force. For example, suppose that the Earth's density were a constant ρ . The mass within radius r would be $(4/3)\pi r^3 \rho$, and the gravitational force F on a reference mass m_{ref} at distance r would be

$$F = G [(4/3)\pi r^3 \rho] (m_{ref}/r^2) \propto \rho r,$$

where G is the universal gravitational constant. However, because we know that the Earth is more dense in the center than at the

surface, we must know with great accuracy how the density changes with depth in order to predict F . Furthermore, any lateral density variation inside or outside the measuring radius could cause an apparent discrepancy between the borehole gravity measurement and the prediction. This could be misinterpreted as evidence for a new force. Geophysicists have known for many years that there are density anomalies in the Earth; in fact, areal surveys detecting and measuring such anomalies are used to prospect for mineral deposits. It is extremely difficult, at best, to make all the required corrections accurately enough to reliably detect a small variation from the inverse-square law of gravity in a borehole experiment.

We performed an experiment similar to Stacey's in boreholes at the Nevada Test Site and also found a discrepancy between the measured and calculated variation of gravity with depth (Thomas et al., 1988); in fact, our discrepancy was five times greater than Stacey's. The difference between the measurements obtained in Australia and in Nevada is caused by the different density structures beneath the experimental sites and clearly demonstrates the inherent unreliability of borehole experiments.

In a tower experiment, however, the difficulty described above can be avoided. The predictions of gravity on the tower depend not on estimates of the Earth's density variations but rather on measurements of gravity at many locations on the ground around the tower out to a large distance. Thus, this technique accounts for density anomalies at all depths. In mathematical terms, the important difference between a tower and borehole experiment is that in a tower experiment one must solve Laplace's equation for the gravitational field in a source-free region, whereas in a

borehole experiment one must solve Poisson's equation for the gravitational field in the midst of sources that must be well understood. Therefore, a tower experiment can provide unambiguous results. Of course, the quality of the tower gravity predictions depends on the quality of the ground gravity measurements, which must be numerous, properly spaced around the tower, and sufficiently accurate.

LLNL's Search for Non-Newtonian Gravity

The LLNL experiments to test Newton's law are a coordinated effort involving not only the Seismology and Applied Geophysics Group but also the Nuclear Test Experimental Science Program, E Division in the Physics Department, the Affirmative Action/Equal Employment Opportunity Program, and the Nuclear Test Operations Department Nevada.

We are conducting these experiments at the BREN tower because attributes of the tower and the site make it possible for us to conduct the most sensitive search to date for distance-dependent deviations from Newtonian gravity. This tower is 465 m tall (Fig. 1). It was built in 1962 to support a reactor that has been removed, leaving a stable structure for making gravity measurements. The tower has 12 work platforms, spaced ~42 m apart, at which gravity measurements can be made.

The tower is free from electrical interference because it is not used for broadcasting; this interference can affect gravity measurements. Also, the area around BREN is very accessible and clear of obstructions, which makes it easy to take surface measurements.

BREN rises above Jackass Flats, Nevada, on gently sloping alluvial deposits from a ring of hills that cover about 50% of the horizon. The

slope of 1.5° is nearly constant out to 2 km from the tower; the summits of the nearest hills are 5 km away from the tower; these hills rise to about the same elevation as the tower. Thus, near the tower, the topography is more gentle than in the previous tower experiment (Eckhardt et al., 1988; Romaides et al., 1989). At a distance of eight to ten tower heights, where the terrain is less important but not negligible, the BREN site includes more terrain variations than the sites used in previous experiments.

Another important advantage of using this site is the fact that an extensive, high-quality gravity data base already exists for the area; it was accumulated as part of the NTS nuclear test and nuclear waste isolation programs.

We are conducting this experiment in two phases. In Phase 1, which is described here, the experiment was sensitive enough to detect a deviation of 1 part in 10^7 between the measured gravity and the Newtonian prediction. In Phase 2, in progress, the experiment sensitivity is three times better (3 parts in 10^8).

Tower Survey

We used LaCoste-Romberg gravity meters to measure gravity on the tower (Figs. 2 and 3). A gravity meter is essentially a very accurate balance that measures relative changes in the Earth's gravity. We first measured the gravity (actually, the acceleration of gravity on a reference mass) on the tower relative to the gravity at the base of the tower. We then measured the gravity at the base of the tower relative to two nearby gravity stations established by the U.S. Geological Survey (USGS). Each measurement is accurate to about 1 part in 10^8 of the Earth's gravitational field. At this level of accuracy, one must make certain that systematic errors are not introduced. For example,

Figure 1. The BREN tower at the Nevada Test Site is the location of our gravity test. It is nearly 465 m high, 84 m taller than the 381-m tall Empire State Building. The BREN tower is far from operating machinery or other buildings that could cause vibrations or produce electrical interference, and the long lines of sight over the flat, treeless desert allow us to locate and measure a dense grid of gravity stations on the ground surface.

the effect of the tidal forces must be removed. The instrument must be carefully calibrated, and the instrumental drift must be measured and removed. Also, because tower vibrations can affect the gravity meter, we took tower data only when the wind speed was <5 km/hr.

Figure 2. An LLNL researcher uses a gravity meter to measure the force of gravity at the base of the BREN tower. The LaCoste-Romberg gravity meters used in this experiment are small and lightweight ($20 \times 18 \times 25$ cm, 10 kg), highly accurate, and rugged, making them well-suited to such field studies.

We measured elevations with a Leitz REDmini 2 EDM system, which we bolted to the railing at each level on the tower. We measured the distance from the railing to five corner reflectors set on the concrete base of the tower and also measured the distance from the base of the gravimeter to the railing to determine the height of the gravimeter. We repeated the height measurements for each gravity

measurement; all repeats at each height fell within 15 mm of the mean.

The predictions of gravity on the tower were based on our measurements of gravity on the Earth's surface around the tower out to a 300-km radius. For the region within 2.5 km from the tower, we measured gravity at 760 locations on a grid (Fig. 4). Ninety of these locations, shown as triangles in the figure, were included in the first

phase of the experiment; the results of which we report here. In the region between 3 and 10 km, we are measuring gravity (in Phase 2 of this experiment) at about 150 additional locations chosen to complement the gravity data base provided by the USGS and the National Oceanographic and Atmospheric Administration (NOAA) (Saltus, 1988; Ponce, 1984). From 10 to 300 km, we rely

Figure 3. Diagram of the zero-length spring gravimeter, as used in the LaCoste-Romberg gravity meters. A zero-length spring is prestressed so that a force is required to separate the coils. The spring supports a mass at the end of a beam. Thus, known relations of the spring force (product of the spring constant and the length of the spring), the length of the beam, the weight of the mass, and the angular displacement of the beam can be combined to determine the gravitational force.

entirely on the USGS and NOAA data base, which contains measurements taken about every 700 m across NTS.

In principle, if gravity were known for the entire surface of the Earth, we could make an exact prediction of the gravity on the tower. Of course, practical considerations limit us to measuring gravity at a finite number of locations. The number of locations and their spacing were chosen to minimize our uncertainties in the gravity predictions on the tower. (The details of our error analysis as well as of our method for predicting gravity on the tower from ground gravity data have been presented elsewhere by Thomas, 1989.)

In addition to measuring the gravity at numerous locations on

the surface and on the tower, we also had to determine the elevation at each of the measurement locations. For this, we used an electronic distance-measuring device that emits an infrared pulse that is returned along a parallel path by a corner cube reflector at a reference location. The round-trip time of the pulse, when corrected for atmospheric effects and Earth curvature, allows us to calculate the elevation to sufficient accuracy. The elevation measurements on the tower were obtained at the same time as the gravity measurements so that expansion or contraction of the tower with changes in temperature would not affect the data. We measured the elevations of the many surface gravity locations relative to the base of the

tower, which was in turn measured relative to 10 surveyors' benchmarks located within 3 km of the tower.

Theoretical Basis for Non-Newtonian Experiments

The basis of the various experimental approaches taken in testing Newton's law can be understood by writing the Newtonian formula for the magnitude of the gravitational acceleration g (defined as positive downward) at a point R on a nonrotating Earth as a volume integral over the density distribution ρ in the Earth:

$$g(r) = |\nabla U(r)| = G \int \frac{\rho(r') dV'}{|r - r'|^2}, \quad (1)$$

where G is the universal gravitational constant postulated by Newton, and U is the gravitational potential.

We assume a spherical Earth, and describe its density distribution with two terms: $\bar{\rho}(r)$, which is a model representing our best guess of the average density in each spherical shell of the Earth, and $\Delta\rho(r, \theta, \phi)$, which represents all the deviations from that model, including the lateral variations of density within the Earth. The radial component of the Newtonian gravity field is given by integrating over these density distributions:

$$g_r(r) = \frac{G\bar{m}(r)}{r^2} + G \int \frac{\Delta\rho(r', \theta', \phi') \cdot (r - r') \cdot \hat{r} dV'}{r - r')^3} = \frac{G\bar{m}(r)}{r^2} + f(r), \quad (2)$$

where the Gauss theorem has been used to simplify the integral over $\bar{\rho}(r)$. $\bar{m}(r)$ is the mass of the model lying beneath the shell of radius r , and the $\hat{r}$ indicates a unit

Figure 4. Contour map of the BREN tower area showing the locations of the surface gravity measurements. (In the central region, there are 256 additional locations, which are not shown.) The triangles are the locations used in the first phase of the experiment; the locations marked with a plus are being used in the second phase. The squares denote locations at which data were taken by the USGS or NOAA.

vector. The details of the average density model below the experiment are not important.

All experiments use this Newtonian model to predict the difference between the gravity values measured at two radii. Defining the observed gravity anomaly to be

$$\Delta g_r(r) = g_r(r) - \frac{Gm(r)}{r^2} \quad (3a)$$

gives the following simple equation to use in an empirical test of Newton's law,

$$\Delta g_r(r_1) - \Delta g_r(r_2) = I(r_1) - I(r_2), \quad (3b)$$

where the differences in the observed gravity anomalies at different radii are compared to a volume integral over the density anomalies in the Earth.

The integrals on the right hand side contain all of the complexities associated with the lateral variations of density within the Earth. If these are ignored, Eq. (3b) describes an apparently straightforward test of Newton's law, first proposed by G. B. Airy in 1854 (cited in Hammer, 1950). In this test, the difference in the average-Earth model at two radii is usually expressed as the sum of two terms: the free-air gradient term and an integral over the vertical variations in density.

Derivation of our Method

If Eq. (1) is correct and if the density of air is neglected, then the gravitational potential is a solution to Laplace's equation $\nabla^2 U = 0$ outside the Earth, and so is $r\nabla(rU) = r g_r$. Because the solution to Laplace's equation is uniquely determined by values on a closed boundary, we know there is a functional relationship F that operates on the values of $r g_r$ on the entire surface to produce

the value at some height above the surface,

$$r g_r(\text{air}) = F[r g_r(\text{surface})]. \quad (4)$$

Furthermore, this relationship holds for the Newtonian gravitational field of any proposed mass lying beneath the Earth's surface. Using Eq. (3a) to subtract the effect of the average Earth model $\bar{p}(r)$ from both sides, and dividing through by r gives

$$\Delta g_r(\text{air}) = \Delta g_r(\text{air}) - \frac{Gm_{\text{Earth}}(\text{air})}{r^2} = \frac{1}{r} F[r \Delta g_r(\text{surface})]. \quad (5)$$

Equation (5) describes a test of Newton's law that involves a direct comparison of observable data, with no assumptions about the density within the Earth. This experiment has two limitations:

- Our inability to completely sample the gravity anomalies on the Earth's surface.
- Our inability to evaluate the function F with sufficient accuracy.

Previous experimenters (Eckhardt et al., 1988; Romaides et al., 1989) used three different approaches to evaluate F and argued that they produced similar results. We have chosen the simplest approximation so that we can treat our gravity measurements as if they were collected at the same elevation; this approach turns the functional relationship into a surface integral. The error in this approximation is estimated from numerical studies described later. The advantage of this approximation is that when the surface integral is "discretized" for numerical evaluation, it reduces the surface sampling problem to the estimation of the mean values of the gravity anomalies within areas on the Earth's surface, and it allows us to use a rather straightforward analysis to estimate the

errors caused by sampling and truncation of the integral (Thomas, 1989).

If the surface data were collected on a sphere of radius a , then Eq. (4) becomes Poisson's equation:

$$r g_r(r, 0, 0) = \frac{a^2(r^2 - a^2)}{4\pi} \int_{\Omega} \frac{d\Omega}{(r^2 + a^2 - 2ar\cos\theta)^{3/2}}, \quad (6)$$

where $d\Omega$ is an element of solid angle and r is the distance of the point of observation from the center of the sphere. If z is the elevation of the point on the tower above the surface ($z = r - a$) and r' is the distance along the surface of the sphere to a measurement point ($r' = a\theta$), then we can expand Eq. (6) in powers of z/a , keep leading terms, and find

$$\Delta g(z, 0, 0) = \frac{z(1 - z/a)^2}{2\pi} \int_0^{2\pi} \int_0^\pi \Delta g(0, r', 0) \frac{r' dr' d\theta}{[r^2 + z^2(1 - z/a)]^{3/2}}, \quad (7)$$

where the average-Earth model has been eliminated as in Eq. (5). Here and in the following, the subscript r is implied. The perturbations, caused by ignoring the terms of $(2/a)^2$, are small, about 1 part in 70 million, as is the effect of the ellipsoidal shape of the Earth. Equation (7) describes a relationship between values measured with a gravity meter on the Earth's surface and on a tower; we use this spherical approximation to test the validity of Newton's law.

Gravity meters measure the magnitude of the gravity force vector, described here in units of gal (after Galileo), where 1 Gal = 1 cm/s². The force vector is dominated by the 980 Gal attraction of $\bar{p}(r)$, but also includes the effects

of mass anomalies and topography (<50 mGal), the centrifugal effect caused by the Earth's rotation (<4 Gal), and the tidal forces (<0.3 mGal). The magnitude of the force vector is always nearly the sum of the radial components of these effects. Centrifugal effects are not harmonic, and tidal forces change with time; therefore, these effects do not obey Eq. (7) and are removed from all gravity data.

Gravity cannot be measured continuously over the surface of the Earth. Thomas (1989) described the steps involved in approximating the integral in Eq. (7) based on a finite set of samples over a limited portion of the Earth and has quantified the sizes of the resulting errors. The samples are collected in sectors lying in rings around the tower. Several steps are involved in choosing the ring radii and sector sizes. We define the experimental observable to be the difference in Δg at two heights on the tower. This modifies the integral in Eq. (7) by making the integrand the difference of two terms. Next, we reduce the integral to a sum over sectors where the average gravity value must be measured. We derive the expression for the error in the sum based on the uncertainty in estimating the mean gravity of each sector, using a preliminary data set to estimate how well a single measurement of gravity represents the average value as a function of sector size.

Based on that preliminary sampling information, we chose sector sizes to minimize the expected sampling error, subject to two conditions: a fixed number of nearly square sectors and a decreasing error with distance so that the sum converges. In addition, we estimated the truncation error that resulted from limiting the integral to a finite distance. Thus, we reduced the test of Newton's law to a problem of estimating the average gravity value in rings around the tower, using a

weighted sum of those averages to predict the differences in gravity anomaly values at different heights on the tower.

Results

We calculated the gravity anomaly Δg at each point on the tower and ground surface, using a slightly more complicated earth model than is indicated in Eq. (3). We removed the effect of a standard "whole-Earth" World Geodetic System model, 1984 (WGS84), which places the entire mass of the Earth (excluding the average atmosphere above the measurement point) below the geoid. The latitude dependence of that model includes the radial component of the centrifugal effect. This step included the $1/r^2$ factor, as described in Eq. (5).

Tower Measurements

Our results are shown as a solid line in Fig. 5. In this plot, Δg at the base of the tower has been removed from all measurements. The line through the data is a straight line fit to the individual points, whose scatter is not visible on this plot. We can make two observations:

- The data set on the tower is linear and shows no obvious curvature caused by non-Newtonian effects.
- The data do not agree with the predictions of the globally symmetric model of the Earth, differing by 2.8 mGal at the highest station.

The gravity gradient on the BREN tower, 0.3030 mg/m, is about 1.8% lower than the model predicts. Very little can be concluded from these observations alone because topographic effects or geologic variations could conspire to produce an anomalous gradient or to mask an exponential gravitational field. In fact, about 50% of the anomalous gradient is predicted by calculating the effect of topography, with an assumed density of 2.2 g/cm³, out

to 300 km. These results illustrate that other measurements are needed to determine the effects of lateral variations before one can study the reliability of the $1/r^2$ force law from a measurement of the vertical variation of gravity.

Integration of Surface Data to Predict Values on the Tower

We used the surface gravity measurements and Eq. (6) to obtain predictions for gravity at each of the 12 tower platforms (at elevation z relative to the tower base).

The prediction, $\Delta g_{\text{pred}}(z)$, was obtained from the surface gravity measurements, using Eq. (7), and is shown in Fig. 5. Next, we calculated the difference in residual gravity values between each tower height z and the tower base. As shown in Fig. 5, we then plotted $\Delta g(H) - \Delta g(\text{base})$ for each of the 12 locations on the tower as a function of z . In this figure, triangles denote tower gravity measurements and circles denote predictions calculated from the surface gravity measurements.

The good agreement seen in Fig. 5 between the measured tower gravity values and those predicted from the surface measurements shows that within the sensitivity of our experiment, gravity does indeed obey a Newtonian inverse-square law. Our predictions are within 93 μ Gal of the observations at all heights on the tower, and the uncertainties at each height are as large as 95 μ Gal. The error bars in Fig. 5 indicate the single standard deviation uncertainty from sampling errors, which are the largest source of error in this experiment. At all heights, these errors overlap the observed gravity, providing no evidence for a breakdown of Newtonian gravity. In addition, the nonzero values of measured residual gravity values can now be related to the inaccuracy of the WGS84 Earth-model for the BREN tower locality. Thus, other

Figure 5. Results for two tests of Newton's law. Observed values of Δg change as a function of height for experiments on the BREN tower. The solid lines indicate linear fits to the observations (triangles). The dashed lines are linear fits to the predictions (circles) based on Newton's law (Eq. 7). The measurement errors are negligible on this scale. The stated errors in the predictions are represented by vertical bars. The anomalous gradient we observe on the BREN tower is predicted from the surface survey within our sampling uncertainty.

experiments that rely solely on this symmetric-Earth model in their test for non-Newtonian gravity could encounter similar problems in predicting gravity at other localities.

Possible Sources of Systematic and Random Error

Spherical Approximation for Upward Continuation

The surface field can be uniquely translated into a continuous surface-density distribution from which the values above the Earth can be readily

calculated. For an irregular surface, this transformation requires solving a Fredholm integral equation that is cumbersome to solve over the distance scales needed for this problem (Bhattacharyya and Chan, 1977). However, in the approximation that the Earth's surface is a smooth sphere, this integral equation reduces to an integral [Eq. (7)] that can be evaluated easily. This approximation is potentially our most significant source of systematic error. Because we cannot correctly predict what we would have measured on the smooth surface, some errors result from our estimates of

gravity on that surface. Analysis of the Fredholm integral equation solution for irregular terrain does not provide insights into the size of this effect.

We are using a digital model of the terrain in a 54-km square centered on the tower to estimate the magnitude of the errors from the spherical approximation. We digitized elevation contours (6.1-m intervals) within a rectangle extending 6.1 km north, 5.2 km east, 8.3 km south, and 12.0 km west of the tower (U. S. Geological Survey, 1983). For the rest of the square, we used digital terrain sampled on a 15-s grid (Plouff, 1977). The mass of terrain was approximated by a 300×300 grid of density 1.8 gm/cm^3 , right-rectangular prisms of an identical square cross section, with all bases at an arbitrary depth ($\sim 3318 \text{ m}$ below sea level) and tops at the height of the smoothed terrain at their centers. At greater distances, we assumed the Earth's surface to be constant to long distances at values determined from the averages of the nearest side of the 54-km square. We calculated the vertical component of gravity caused by this mass at all observation points on the tower and at the model elevation in each sector (Plouff, 1976). Using Eq. (7) to integrate the artificial surface numbers, we found that the spherical approximation underestimates the calculated magnitude of $\Delta g(r_1) - \Delta g(r_2)$ by $\sim 100 \mu\text{Gal}$ for a number of different gridding options. We are expanding this study to include the effects of mass anomalies and to evaluate the effectiveness of including terrain corrections in the definition of Δg .

Random Errors and Bias Caused by Sampling

Because gravity is strongly correlated with elevation, the observations must adequately sample both the topography and the effects of density variations. Variations in topography and density (on a scale

that is large compared to the sectors) do not contribute to errors in estimating the sector means. We bound the uncertainty in estimating a sector mean by calculating the sample variance of all gravity values in a ring of n sectors about the mean gravity for the ring, m_{ring} . The sample variance is a useful bound on the ring variance of the ring mean.

$$\exp \left[\frac{1}{n-1} \sum (\Delta g_i - m_{ring})^2 \right] \\ = \frac{1}{n-1} \sum (m_{i,j} - m_{ring})^2 + \sigma_{ring}^2 \quad (8)$$

In practice, we improve this estimate by removing long-wavelength effects on the scale of the ring radius. This is done by fitting one or two intersecting planes through $\Delta g(\theta)$ around a ring and by removing that "regional" from the data before the ring uncertainty is estimated.

To estimate the uncertainties in the ring means, we assumed that the effects of sampling were uncorrelated from sector to sector. This assumption is valid for data taken within 2.6 km of the tower because we chose locations independent of topography. However, because it may be easier to take measurements in either the valleys or the highlands, a sampling bias may exist in the elevations of measured points beyond 2.6 km. It is, therefore, important to estimate the magnitude of elevation bias.

We reduce the effect of the sampling by taking averages of many sectors per ring, but the average in each sector can be biased if the

sectors are larger than the topographic features influencing the sampling distribution. We used our largest sectors (the ring from about 270 to 300 km from the tower) to study the magnitude of this bias. Here, the sectors are large compared with the data density and comparable in size to many topographic features in the western United States. In many of these sectors, there is a preponderance of data in valleys, but the mountains are sampled on a 4–5 km spacing. We estimated the elevation bias in our outermost ring by subdividing each sector into nearly square subsectors, determining the sector means from the sum of the means in the subsectors, and calculating the ring average as a function of the size of the subsectors. The maximum or minimum value as a function of subsector size represents the best averaging we can do with our data set.

We found that the best subsector size was about 7 km and that the ring-averaged total gravity and elevation differed from our original values by -7 mGal and 31 m. These numbers indicate that, for this ring, Δg is biased by ~ 2.5 mGal. We believe that this represents a reasonable estimate of the elevation sampling bias beyond 80 km and that, if it were applied to the data beyond 80 km, it would change the prediction at the top of the tower by only 25 μ Gal. Inside 80 km, the sector size is below 7 km, and more than 85% of the sectors in each ring are filled, except for

the ring at 6.3 km, which has only 63% of its sectors filled. Based on the studies of the outermost ring, data density appears to eliminate much of the bias in sampling topography.

We have estimated the effects of other sources of error on gravity at the top of the tower. These sources include ignoring the ellipsoidal shape of the Earth, uncertainties in gravity-meter calibration and measurement error, surveying errors near the tower, changes in geoid height over the range of our surface survey, and the effect of our trucks on the measurements in the tower. Only those sources discussed in detail above appear to be important.

Conclusion

The results from Phase 1 of our experiment (Thomas et al., 1989) support Newton's theory of gravitational force. We observed no evidence for a fifth force to a sensitivity level of 1 part in 10^7 , although previous experiments had been interpreted to indicate an effect of 5 parts in 10^7 . This is the first tower experiment to observe a null result at this high level of sensitivity. (In Phase 2 of this experiment, our sensitivity will be three times greater.) The results reported to date set very strong limits on the strength and radial dependence of any possible fifth force and thus provide an important benchmark for grand unification theories.

References

- Adelberger, E. G., C. W. Stubbs, W. F. Rogers, F. J. Raab, B. R. Heckel, J. H. Gundlach, H. E. Swanton, and R. Watanabe (1987), "New Constraints on Composition-Dependent Interactions Weaker than Gravity," *Phys. Rev. Lett.* **59**, 849.
- Bhattacharyya, B. K., and K. C. Chan (1977), "Reduction of Magnetic and Gravity Data on an Arbitrary Surface Acquired in a Region of High Topographic Relief," *Geophys.* **42**, 1411.
- Eckhardt, D. H., C. J. Jekeli, A. R. Lazarewicz, A. J. Romaides, and R. W. Sands (1988), "A Tower Gravity Experiment: Evidence for Non-Newtonian Gravity," *Phys. Rev. Lett.* **60**, 2567.

- Eötvös, R. V., D. Pekár, and E. Fekete (1922), "Contributions to the Law of Proportionality of Inertia and Gravity," *Ann. Phys. (Leipzig)* **68**, 11; also translation by J. Achtzehnter, M. Bickeböller, K. Bräuer, P. Buck, E. Fischbach, G. Lübeck, and C. Talmadge, Institute for Nuclear Theory, Department of Physics, FM-15, University of Washington, Seattle, WA, Report 40048-13-N6.
- Fischbach, E., D. Sudarsky, A. Szaffar, C. Talmadge, and S. H. Rosen (1986), "Reanalysis of the Eötvös Experiment," *Phys. Rev. Lett.* **56**, 3.
- Gibbons, G. W., and B. F. Whiting (1981), "Newtonian Gravity Measurements Impose Constraints on Unification Theories," *Nature* **291**, 636.
- Hammer, S. (1950), "Density Determinations by Underground Gravity Measurements," *Geophys.* **15**, 637.
- Holding, S. C., and G. J. Tuck (1984), "A New Determination of the Newtonian Gravitational Constant," *Nature* **307**, 714.
- Holding, S. C., F. D. Stacey, and G. J. Tuck (1986), "Gravity in Mines—An Investigation of Newton's Law," *Phys. Rev. D* **33**, 3487.
- Plouff, D. (1977), *Preliminary Documentation for a FORTRAN Program to Compute Gravity Terrain Corrections Based on Topography Digitized on a Geographic Grid*, U. S. Geological Survey, Open-File Report 77-534.
- Plouff, D. (1976), "Gravity and Magnetism of Polygonal Prisms and Application to Magnetic Terrain Corrections," *Geophys.* **41**, 727.
- Ponce, D. A. (1984), "Preliminary Gravity Investigations of the Wahmonie Site, Nevada Test Site, Nye County, Nevada," *J. Geophys. Res.* **89**, 9401; also U.S. Geological Survey, Open-File Report 81-522.
- Romaides, A. J., C. Jekeli, A. R. Lazarewicz, D. H. Eckhardt, and R. W. Sands (1989), "A Detection of Non-Newtonian Gravity," *J. Geophys. Res.* **94**, 1563.
- Saltus, R. W. (1988), "Gravity Data for the State of Nevada on Magnetic Tape," U. S. Geological Survey, Open-File Report 88-433.
- Stubbs, C. W., E. G. Adelberger, F. J. Raab, J. H. Gundlach, B. R. Heckel, K. D. McMurry, H. E. Swanton, and K. Watanabe (1987), "Search for an Intermediate-Range Interaction," *Phys. Rev. Lett.* **58**, 1070.
- Stacey, F. D., G. J. Tuck, S. C. Holding, A. R. Mahler, and D. Morris (1981), "Constraint on the Planetary Scale Value of the Newtonian Gravitational Constant from the Gravity Profile with a Mine," *Phys. Rev. D* **23**, 1633.
- Thomas, J. (1989), "Testing the Inverse Square Law of Gravity: Error Analysis and Design Using the Upward Continuation Integral," *Phys. Rev. D* **40**, 1735.
- Thomas, J., P. Kasameyer, O. Fackler, D. Felske, R. Harris, J. Kammeraad, M. Millett, and M. Mugge (1989), "Testing the Inverse Square Law of Gravity on a 465-m Tower," *Phys. Rev. Lett.* **63**, 1902.
- Thomas, J., P. Vogel, and P. Kasameyer (1988), "Gravity Anomalies at the Nevada Test Site," in the *Proc. of the XXIIIrd Rencontre de Moriond*, Les Arcs, Savoie, France, O. Fackler and J. Tran Thanh Van, Eds., (585, Editions Frontieres).
- Thomas, J., P. Vogel, P. Kasameyer, J. Hearst, M. Millett, D. Felske, O. Fackler, and M. Mugge (1988), "Measured Free Air Gradients Do Not Agree with Model Gravity Gradients at the Nevada Test Site," in the *Proc. of the 5th Marcel Grossman Conference*, Perth, Australia.
- U. S. Geological Survey 1:24,000 topographic maps, for Jackass Flats, Skull Mountain, Specter Range and Striped Hills 7.5 minute quadrangles, Nye Co., Nevada (revised 1983), **23**.

Tectonic Stress and Lithospheric Structure in the Basin and Range

Howard J. Patton and George Zandt

Seismology and Applied Geophysics Group

We review progress in applying surface-wave techniques to the problem of retrieving focal mechanisms for earthquakes in the western United States. The aim of this research is an improved characterization of the regional stress field to better understand the geophysical processes modifying tectonic evolution, including intraplate sources of stress and structural irregularities affecting plate boundary behavior. This review begins with studies into the attenuation and dispersion of surface waves. We discuss the results of these studies and the inferences about internal earth structure and the variation of structure across the western United States. This is followed by the results of a test of the surface-wave method for retrieving earthquake mechanism on a well-studied Borah Peak, Idaho, earthquake. Finally, we present the results to date of our mapping of the tectonic stress fields in northern California and in the Basin and Range.

The theory of plate tectonics has been applied with great success to reconstruct the tectonic evolution of many areas of the world, especially regions near plate boundaries. Reconstructions of the tectonic evolution of the western United States provide valuable insights into the geophysical processes responsible for shaping the unique continental rift areas making up the Basin and Range of Nevada and western Utah, as well as other geological features of the Pacific-North American plate boundary in California. Information on the earth's internal structure and the tectonic stress field are vital for understanding the nature of plate-boundary interactions and the origins of the driving forces on tectonic plates.

Although geophysicists have mapped the tectonic stress field on a large scale and have improved the global model of plate tectonics, they have also recognized for some time that there can be significant short wavelength or regional variations in

the patterns of tectonic stress that do not fit into a simplified view of plate tectonics. Sources of regional stress can be related to structural irregularities controlling plate boundary behavior and/or intraplate sources of stress such as hot spots, topography, and crustal inhomogeneities. Little is known about the regional stress fields of the western U.S. and the processes that give rise to them. The object of our research is an improved characterization of the regional stress field in the western U.S. to gain a better understanding of the geophysical processes that modify the tectonic evolution.

From a more practical standpoint, there are facilities of vital national interest located in the Basin and Range and in other areas of the western U.S. that will benefit from a more complete understanding of the tectonic stress field. These benefits include better assessments of the long-term structural stability of geologic repositories containing radioactive wastes, more precise

constraints for fluid-flow models of convective hydrothermal systems, and seismic hazard mitigation through improved assessments of seismic risk.

Three ways to measure the orientation of stress in the lithosphere are: (1) in situ measurements from hydrofractures and borehole elongation, (2) geologic inferences, and (3) earthquake focal mechanisms. Earthquake mechanisms are particularly attractive in the western U.S. because the seismicity is so diffuse that many areas, both populated and remote, may be quickly and inexpensively surveyed. This approach has been exploited for years in areas monitored by dense seismic-station networks operated by the United States Geological Survey (USGS) and major universities. Making use of many short-period recordings of *P*-waves from an earthquake located within the network, the *P*-wave first-motion technique has been widely used to find the nodal planes of the

earthquake radiation pattern and the directions of the principal stresses.

Unfortunately, the first-motion technique has limited applicability when the earthquake is located outside of the seismic networks. Because of requirements on station distributions and signal-to-noise ratios, an earthquake located outside networks in the western U. S. must have a magnitude greater than about 5.0 to determine a reliable first-motion solution. This severely restricts the number of analyzable events, particularly in the Basin and Range where the occurrence of large earthquakes is rare. In addition, there can be uncertainties in stress estimates obtained from the first-motion technique in areas where the earth structure is poorly known, which is often the case outside of seismic networks.

We have used a method based on surface-wave excitation and seismic moment-tensor theories to obtain

source mechanisms of moderate-size earthquakes. The method is particularly suited to the study of remote earthquakes with limited seismic station coverage. Surface waves with periods less than 30 s propagate in the crust, avoiding the highly attenuating upper mantle; consequently, they are well-recorded even at distant stations. A typical seismogram from a regional earthquake in the western U. S. illustrates the very clear surface-wave arrivals compared with the small first motions of P_n (Fig. 1). Indeed, using surface waves, we can lower the threshold of analyzable earthquakes to a magnitude of 4.0; hence, more earthquakes are candidates for study. Also, the longer wavelengths in the surface waves permit a "point source" view of the earthquake, smoothing out all of the complexities of the rupture process that may add noise to P -wave first-motion solutions.

The surface-wave method also provides an independent check on the results from P -wave first-motion studies. This is helpful in regions where networks have been recently installed and where the stress fields are unknown.

We review the developmental work in applying surface-wave methodologies to the problem of earthquake mechanism retrieval in the western U. S. Because of the severe effects that the earth's structure has on the propagation of surface waves, this review begins, as did the course of our studies, with investigations into the propagation characteristics, including attenuation and dispersion. These investigations have yielded considerable information about the internal earth structure and the variations of that structure across the western U. S. This is followed by the results of a test of the surface-wave method to recover the source mechanism of a well-studied earthquake. Finally, we present the results to date of our mapping of the tectonic stress fields in northern California and in the Basin and Range.

Q Structure of the Basin and Range

In our investigations of propagation effects, we studied events with known source mechanisms, usually from P -wave first-motion solutions. Theoretical excitation of surface waves in layered media is calculated for the source model of an earthquake. These calculations are used to correct the observations, thereby isolating the part caused by propagation.

The epicenters of the events and the paths used to measure attenuation are shown in Fig. 2. The stations belong to the World-Wide Standard Seismograph Network (WWSSN), and the paths are for Rayleigh waves that left the sources on azimuths well away from nodes

Figure 1. Seismograms of the September 24, 1982, earthquake in southern Nevada recorded by an LLNL-operated station at regional distances. Three components of motion are shown. The arrivals of P_n first motions are indicated by the arrows.

in the radiation pattern. Similarly, we selected Love-wave data that avoided complications due to radiation nodal planes.

We divided the western U.S. into two provinces for the purpose of estimating regional attenuation coefficients. The boundary between the two provinces (Fig. 2) was determined by the 1.5 heat-flow-unit contour from the energy-flux map of Blackwell (1978). This boundary is somewhat arbitrary; however, it does result in defining one province encompassing all of the physiographic Basin and Range and additional areas that, from a rheological standpoint, may be similar to the Basin and Range.

The measurements of Rayleigh-wave attenuation in the Basin and Range are shown in Fig. 3 along with shear-wave attenuation models as a function of depth (Patton and Taylor, 1984). The four models in Fig. 3 were obtained from formal inversions by selectively changing the weighting of the data covariance matrix. Variance between the different models is a measure of the resolution of attenuation at depth. All models are characterized by fairly low Q values in the lower crust (18–31 km; $Q_\beta \sim 120$) and very low Q values at depths greater than 60 km ($Q_\beta < 30$).

Figure 4 shows a comparison of the Q_β^{-1} models versus a Basin and Range S-velocity structure (Priestley and Brune, 1978) and Basin and Range geotherms (Lachenbruch and Sass, 1978). The rapid increase in Q_β^{-1} occurs at about the same depth as the intersection of the Basin and Range geotherms with the dry basalt melting curve (~45 km). This is also the depth at which a rapid increase in electrical conductivity has been observed (Porath, 1971). The shear-velocity model based on surface-wave dispersion is characterized by a constant velocity lid with shear velocity of 4.5 km/s and a sharp lithosphere-asthenosphere

Figure 2. Events, stations, and paths used for measurements of Rayleigh- and Love-wave attenuation coefficients. The heavy dark line corresponds to 1.5 heat-flow-unit energy-flux contour of Blackwell (1978) and was used in the regionalization.

discontinuity at 60 km. Our studies of velocity structure in the Basin and Range illustrate that structural models with negative velocity gradients in the lid are also consistent with the observed dispersion curves. A sudden jump in velocity is not required. We believe that the low Q values required in the lower crust and upper mantle, in conjunction with a host of geophysical evidence, suggest that the lithosphere is poorly developed beneath the Basin and Range and that the lithosphere-asthenosphere boundary, whether gradational or abrupt, may extend to the base of the crust.

Lateral Variations of Shear-Velocity Structure

In the western U.S., we measured Rayleigh-wave phase-velocity dispersion in the 6–60 s period range for more than 80 paths and Love-wave dispersion for about 50 paths. The Rayleigh-wave paths (Fig. 5) provide dense coverage for areas of the Basin and Range, Colorado Plateau, and southern Columbia Plateau and Snake River Plain. Most of the measurements were made on WWSSN data following the single-station method applied to earthquakes with known source

Figure 3. (a) Shear attenuation versus depth from the inversion of surface wave attenuation data. Four different models were obtained from formal inversions by selectively changing the weights of the data covariance matrix. (b) Observed and calculated Rayleigh-wave attenuation for the above models. Open squares represent one standard deviation in the measurements of attenuation, $100/Q$.

mechanisms and depths. In a few instances, we used digital stations in Nevada and California operated by I.L.N.I. and Sandia Laboratory. Two-station dispersion curves were available between I.L.N.I.

stations and between WWSSN stations from the study of Biswas and Knopoff (1974). The total variation of the Rayleigh-wave velocities on these paths was $\sim 10\%$ for a 50-s period and 13% for a 10-s period.

The data set of phase-velocity dispersion curves was analyzed for lateral variations using a pure-path regionalization method. This method has been widely applied to long-period observations in the oceans and the continents, and in numerous global studies. We attempted to remove some subjectivity in the choice of regionalization zones by employing a block-province grid (Fig. 5). We used blocks in areas with dense, criss-crossing paths and tectonic provinces on the perimeter of the study area. This permitted a more objective analysis for the lateral variation of velocity in areas of interest, specifically the Basin and Range and adjacent geologic regions. The block-province regionalization consists of 20 zones (16 are square blocks 300 km on a side and 4 are tectonic provinces). The size and number of the blocks were chosen by taking into consideration the number of paths and wavelengths of the surface waves. Following the standard methodology, the observed phase slownesses for all paths at a given period were inverted for the phase slownesses in each zone (Taylor and Patton, 1986).

The inversion results showing lateral variations of Rayleigh-wave phase velocity in two period ranges are presented in Fig. 5(c) and (d), where percent deviations from a reference dispersion curve for the Great Basin (Priestley and Brune, 1978) are shown. The period range from 25–33 s generally samples the lower crust and upper mantle and the range from 16–24 s mainly samples the mid- to upper-crust. The results indicate significant lateral velocity variation in the Great Basin although the spatial-average velocity agrees quite well with the dispersion obtained by Priestley and Brune. Low velocities are found in areas of the Eureka low heat-flow (block 12) and in parts of

Figure 4. Comparison of shear velocity (Priestley and Brune, 1978) and shear attenuation models with estimated geotherms (Lachenbruch and Sass, 1978) in the Basin and Range.

southeastern Oregon (block 3). High velocities are found in transition areas such as the Intermountain Seismic Belt (blocks 8 and 13) and the Mohave Desert (block 15), and in the Battle Mountain high-heat-flow area (blocks 4, 6, and 7).

The regionalized phase velocity curves for blocks 6, 7, 12, 13, 16, and 17 were inverted for shear-velocity structure in an attempt to develop a structural cross section. For each block, structural information based on results from refraction surveys and from previous surface-wave studies provided constraints on crustal structure, making our crust and upper mantle velocities better determined. By using these constraints and results from sensitivity studies, we can estimate to within 5 km the average crustal thickness for each block. However, given the relatively large size of each block, it is expected that the crustal thickness varies by this much particularly where a tectonic boundary is encountered. The preferred velocity models (Fig. 6) represent a W-NW to S-SE profile for the six blocks extending across the Basin and Range into the Colorado Plateau. Because of limitations in model resolution, small features such as single-layer crustal low-velocity zones are probably not significant.

A principal feature of the profile is the presence of a well-developed, upper-mantle low-velocity zone in the central Basin and Range (block 12). The lid thicknesses (Fig. 6) are quite thin (~10–30 km) relative to that of the Great Basin model (Priestley and Brune, 1978; ~30 km). The top of the upper-mantle low-velocity zone may actually be a negative velocity gradient rather than an abrupt velocity discontinuity. However, resolution calculations indicate

Figure 5. (a) Seismic stations, tectonic provinces, and the block-province grid employed by the phase velocity regionalization method. (b) Rayleigh-wave paths. (c) Percent deviations from the Great Basin dispersion curve of Priestley and Brune (1978). Shading denotes areas with velocities greater than the Great Basin curve, and stippling denotes areas with lower velocities. Velocities in unmarked areas are not significantly different from the Great Basin curve.

that we cannot distinguish between the two possibilities without additional constraints such as S_H velocities.

The crustal thickness was selected primarily to match constraints from regional refraction results and appears to be thick (~35 km) in the central part of the Basin and Range and thin (~25 km) on the outer edges. The central part of the Basin and Range also appears to be characterized by slightly higher velocities in the lower crust compared to the northwest block (block 6) that has uniformly low velocities throughout its thin crust.

The upper-mantle lid appears to be thicker in the northwestern Basin and Range, and its character on the Wasatch Front (block 13) becomes unclear. The location of the Moho in block 13 is either at about 20-km depth or at 45-km depth. This feature is very similar to the "double Moho" described by Pechmann et al. (1984), based on earthquake and quarry-blast travel times in the same region. Surprisingly, the S -velocities in this transitional block are very similar to those located to the east in the stable Colorado Plateau block. However, the S -velocities of 4.0 km/s at depths of 20 to 45 km correspond to P -velocities of about 7.4 km/s (Keller et al., 1979), while those on the Colorado Plateau correspond to P -velocities of about 6.8 km/s. These depths in the transitional block are characterized by very high Poisson ratios (0.29 as opposed to 0.24 in the Colorado Plateau).

The dramatic increase in the Poisson ratio could be due to the effect of partial melt or of some high-temperature relaxation mechanism acting in this transitional region. However, it is not clear if the high Poisson ratio layer between ~20–45-km depth is composed of mantle-derived crustal

Figure 6. Shear-velocity models from the inversion of regionalized Rayleigh-wave dispersion curves for six blocks across the Basin and Range (see Fig. 5). Vertical exaggeration is approximately 10:1.

material or of ultramafic mantle material whose velocities are reduced by high-temperature effects. In regions undergoing crustal underplating, significant amounts (up to 10 km) of mantle-derived crustal material can be emplaced at the base of the crust. Consideration of the resultant seismic velocities suggests that, for many cases, the added material may have velocities intermediate between those typical for crust and mantle petrologies (Furlong and Fountain, 1986).

Borah Peak Earthquake: Test of the Methodology

The Borah Peak, Idaho, earthquake sequence of October 1983, offered the opportunity to study well-recorded events for the purpose of testing our surface-wave methodologies against independent field data. The source mechanism of the aftershock at 19 hr 51 min (GMT) on October 29, 1983 had been studied using (1) P -wave first motions by Richins et al. (1987), (2) digital waveforms of

long-period teleseismic body waves by Ekstrom and Dziewonski (1985), and (3) digital waveforms of regional P_{eff} waves by Patton and Doser (1988). These three independent data sets gave remarkably similar source mechanisms, and as such, this event was ideally suited to test our Q and velocity models and source-parameter retrieval methodology.

Excellent quality surface waves were recorded on a number of networks, both analog and digital, in the western U. S. Complex source spectra were extracted from the observed signals by making path corrections for anelastic attenuation and for propagation phase delay using the model for lateral variation of surface-wave phase velocities discussed in the previous section.

The surface-wave data were inverted using the moment-tensor approach developed by Romanowicz (1982). For Rayleigh waves, this approach reduces observations of complex source spectra to five so-called moment-excitation spectra involving six moment-tensor elements. The five moment-excitation spectra are in turn inverted for the focal depth and the elements of the moment tensor. Because depth enters nonlinearly through Green's functions, the solution method involves repeated linear inversions at trial depths. The preferred depth gives the smallest residual of all trial inversions.

The propagation-phase correction is critical to the success of the moment-tensor inversion, even for relatively short regional distances. This is demonstrated in Fig. 7(a) where a comparison between two residual depth curves is shown. One curve is based on source spectra computed using a laterally homogeneous earth model, and the other is based on spectra for the laterally heterogeneous earth model in Fig. 5. A clear minimum at a depth of 10 km is present in the

residual curve when lateral heterogeneity is accounted for in the path phase corrections. Comparison of the mechanism at the residual minimum with the other source mechanisms is shown in Fig. 7(b), illustrating the excellent agreement between four independent data sets. The agreement between seismic moment estimates of 2.8, 1.3, and 2.4×10^{17} N·m from teleseismic P -waves, P_{eff} waves, and regional surface waves is quite satisfactory. The depth estimate from surface waves is in good agreement with aftershock distributions of the Borah Peak earthquake compiled by Richins et al. (1987) from hypocenter determinations using locally recorded P -waves.

Stress Measurements in Northern California and Nevada

The surface-wave method has been applied to more than 30 earthquakes in the western U. S., and the results are beginning to reveal some interesting characteristics about the regional tectonic stress field. For example, source mechanisms for six earthquakes in the northern Great Basin (Fig. 8) show quite uniform stress tensors. The minimum compressive stress axis (T) is oriented on an average N70°W, and the maximum compressive stress axis (P) is nearly vertical (normal faulting). While the directions of T axes for events in southern Nevada (not shown in Fig. 8) agree well with those in the north, the stress tensors are rotated such that the P axes are horizontal and the intermediate stress axes (B) are vertical (strike-slip faulting). Thus, the relative magnitudes of vertical to horizontal stresses appear to change between northern and southern Nevada; the vertical stress is greater than the horizontal stress in the north and vice versa in the south. Sources of stress

possibly related to the thermal state of the interior Basin and Range may cause this change. On the other hand, this could be reflecting changes in stress patterns along the San Andreas fault in California since compressive stresses can be transmitted well into the interior of the Basin and Range from the plate boundary.

Our stress measurements in northern California along with the findings for central and southern California (Zoback et al., 1987) are evidence for a heterogeneous stress field north-south along the San Andreas fault system. Zoback et al. have compiled an extensive data set of stress measurements for central California. This data set shows that the maximum horizontal compressive stress is oriented nearly perpendicular to the strike of the San Andreas fault. For classical shear faulting, the maximum compressive stress is expected to be oriented 30 to 45° from the fault strike. One explanation is that the fault zone is weak and unable to support shear stresses. Because of a small component of convergent motion between the Pacific and North American plates, the resolved maximum compressional stress is nearly orthogonal to the plate boundary. This "weak fault" hypothesis is consistent with the absence of the heat-flow anomaly that is expected if the shear-stress level is high along the San Andreas.

North of San Francisco, the evidence for fault-normal compression was less convincing in the study by Zoback et al. The USGS seismographic network in northern California has been in operation for less than ten years, and P -wave first-motion solutions by Wong et al. (1988) showed considerable scatter in the stress directions. The surface-wave technique was ideally suited for this region, and offered the promise of more consistent stress-orientation indicators (Patton, 1985).

Figure 7. (a) Residual-depth curves obtained from moment-tensor inversion of surface-wave data for the 1951 Borah Peak aftershock. The dashed line is obtained for a laterally homogeneous earth model and the solid line for the earth model with lateral heterogeneity. (b) Focal sphere showing fault planes and principal stress directions from the surface-wave inversion. Error ellipses around principal stress directions are for two standard deviations. Also shown are the B (squares), T (circles), and P axes (triangles) from waveform modeling of teleseismic body waves (open symbols), first motions studies (half-closed symbols), and P_H waveform modeling (closed symbols).

Our results show a variety of source mechanisms, yet give a consistent north-south orientation for maximum horizontal compressive stress in northern California (Fig. 9). The stress directions plotted in this figure are either the B or P axis, whichever lies closest to the horizontal plane. The mix of B and P axes suggests that the magnitudes of vertical and horizontal stresses are nearly equal in northern California, as opposed to the clear division that we found in northern and southern Nevada. In any case, the observations for the stress directions show a remarkably consistent pattern and suggest a considerable change in the state of stress along the San Andreas fault system.

We believe that this change in stress reflects differences in the tectonics and mechanical behavior of the San Andreas fault system. The fault segment in central California is very linear and cuts vertically through the entire seismogenic zone. Here, the fault is observed to be creeping aseismically, and apparently cannot support shear stresses. In other words, the fault has very low shear strength. North of San Francisco, the tectonics of the plate boundary are very different, as the recent paper by Furlong et al. (1989) has shown.

Model studies by Furlong et al. indicate that the thermal and mechanical evolution of the plate boundary are a direct consequence of the northward migration of the Mendocino Triple Junction and the development of an asthenospheric window beneath the western edge of the North American plate. Specifically, their models predict an offset in the plate boundary north of San Francisco Bay between the surface expression, which is the trace of the San Andreas fault, and the plate boundary at depth. The deep boundary correlates well with the location of surface volcanics east of the fault trace and with the evidence for low P -wave velocities

Figure 8. Focal Mechanisms for six earthquakes in the northern Great Basin. Error ellipses around principal stress directions are for two standard deviations. Also given are estimates of the focal depths from the surface-wave source inversions of each event.

from seismic tomographic inversions. An important feature of their model is the formation of new faults in the crust of the North American plate over the asthenospheric window. Indeed, almost all of the observed seismicity in northern California is located on young faults east of the San Andreas fault. This suggests the transmission of shear stresses into the interior of the North American plate; therefore,

the mechanical behavior of the plate boundary is quite different from that of the San Andreas fault in central California. An estimate of the shear strength in northern California is the strength of the earth's crust itself since new faults are apparently forming there. A north-south maximum compressive stress, as observed from the surface-wave results, is consistent with this interpretation.

Conclusion

We successfully used surface-wave methodologies to retrieve focal mechanisms for earthquakes occurring in the western U.S. Start-up phases of this work involved measuring surface-wave attenuation and dispersion across varied landforms. Interpretation of these measurements yielded information about the internal anelastic and

Figure 9. Directions of maximum horizontal compressive stress from earthquake mechanisms obtained in this study. Shown are just the estimates for earthquakes located in northern California and Nevada. Other events that we have studied or will be studying are shown by small open circles. Large arrows show orientation of compressive stress in central California from numerous geological and geophysical evidences summarized in Zoback et al. (1988).

velocity structures in the Basin and Range, which offer clues to the tectonic development of continental rifting. We tested these focal mechanism methodologies on a Borah Peak, Idaho, aftershock for which independent field data were available. Our results demonstrate that the

propagation corrections derived from our models of earth structures were satisfactory for isolating the effects due to the earthquake source. We are now analyzing earthquakes in northern California and in Nevada, and our results are beginning to reveal interesting patterns

in the regional tectonic stress field. As our work on earthquake mechanisms continues, maps of the regional stress field will be completed and interpretations of the results will offer a better understanding of the internal forces responsible for contemporary tectonic activity.

References

- Biswas, N. N., and L. Knopoff (1974), "The Structure of the Upper Mantle under the United States from the Dispersion of Rayleigh Waves," *Geophys. J. R. Astr. Soc.* **36**, 515-539.
- Blackwell, D. D. (1978), "Heat Flow and Energy Loss in the Western United States, Cenozoic Tectonic and Regional Geophysics of the Western Cordillera," R. Smith and G. Eaton, Eds., *Mem. Geol. Soc. Am.* **152**, 175-208.
- Ekstrom, G., and A. M. Dziewonski (1985), "Centroid-Moment Tensor Solutions for 35 Earthquakes in Western North America (1977-1983), *Bull. Seism. Soc. Am.* **75**, 23-40.
- Furlong, K. P., and D. M. Fountain (1986), "Continental Crustal Underplating: Thermal Considerations and Seismic-Petrologic Consequences," *J. Geophys. Res.* **91**, 8285-8294.
- Furlong, K. P., W. D. Hugo, and G. Zandt (1989), "Geometry and Evolution of the San Andreas Fault Zone in Northern California," *J. Geophys. Res.* **94**, 3100-3110.
- Keller, G. R., L. W. Braille, and P. Morgan (1979), "Crustal Structure, Geophysical Models, and Contemporary Tectonism of the Colorado Plateau," *Tectonophysics* **61**, 131-147.
- Lachenbruch, A. H., and J. H. Sass (1978), "Models of an Extending Lithosphere and Heat Flow in the Basin and Range Province, Cenozoic Tectonic and Regional Geophysics of the Western Cordillera," R. Smith and G. Eaton, Eds., *Mem. Geol. Soc. Am.* **152**, 209-250.
- Patton, H. J. (1985), "P-Wave Fault-Plane Solutions and the Generation of Surface Waves by Earthquakes in the Western United States," *Geophys. Res. Lett.* **12**, 518-521.
- Patton, H. J., and S. R. Taylor (1984), "Q Structure of the Basin and Range from Surface Waves," *J. Geophys. Res.* **89**, 6929-6940.

- Patton, H. J., and D. I. Doser (1988), "Inversion of Regional P_{nl} and Surface-Wave Data for Source Parameters of a Borah Peak Aftershock," *Geophys. Res. Lett.* **15**, 459–462.
- Pechmann, J. C., W. D. Richins, and R. B. Smith (1984), "Evidence for a 'Double Moho' beneath the Wasatch Front Utah," *Trans. Am. Geophys. Un.* **65**, 988.
- Porath, H. (1971), "Magnetic Variation Anomalies and Seismic Low-Velocity Zone in the Western United States," *J. Geophys. Res.* **76**, 2643–2648.
- Priestley, K., and J. Brune (1978), "Surface Waves and the Structure of the Great Basin of Nevada and Western Utah," *J. Geophys. Res.* **83**, 2265–2272.
- Richins, W. C., J. C. Pechmann, R. B. Smith, C. J. Langer, S. K. Guter, J. E. Zollweg, and J. J. King (1987), "The 1983 Borah Peak, Idaho, Earthquake and Its Aftershocks," *Bull. Seism. Soc. Am.* **77**, 694–723.
- Romanowicz, B. A. (1982), "Moment Tensor Inversion of Long-Period Rayleigh Waves: A New Approach," *J. Geophys. Res.* **87**, 5395–5407.
- Taylor, S. R., and H. J. Patton (1986), "Shear-Velocity Structure from Regionalized Surface-Wave Dispersion in the Basin and Range," *Geophys. Res. Lett.* **13**, 30–33.
- Wong, I. G., R. W. Ely, and A. C. Kollmann (1988), "Contemporary Seismicity and Tectonics of the Northern and Central Coast Ranges-Sierran Block Boundary Zone, California," *J. Geophys. Res.* **93**, 7813–7833.
- Zoback, M. D. et al. (1987), "New Evidence on the State of Stress of the San Andreas Fault System," *Science* **238**, 1105–1111.

Earth Sciences Publications List

Aines, Roger

Bruton, C. J., B. E. Viani, W. L. Bourcier, K. J. Jackson, and R. D. Aines (1989), *Geochemical Modeling: An Integrated Approach to Nuclear Waste Disposal Issues*, LLNL, UCRL-102019; submitted to *Proc. 1st Int. High-Level Radioactive Waste Mgmt. Conf.*, Las Vegas, Apr. 1990.

Akella, Jagann

- Akella, J. (1989), *Diamond-Anvil Cell Technique to Study f-Element Metals and Some Materials Relevant to Planetary Interiors*, LLNL, UCRL-99573; *Indian Acad. Sciences*, Prof. D. Lal Vol., p. 249.
- Akella, J., and G. S. Smith (1989), "Static Ultra High Pressure Diamond-Anvil Studies on Thorium and Uranium," *Actinide 89*, Tashkent, USSR (Nauka, Moscow), p. 111.
- Akella, J., Q. Johnson, G. S. Smith, and L. C. Ming (1988), "Diamond-Anvil Cell High Pressure X-ray Studies on Thorium to 100 GPa," *High Pressure Res.* **1**, 91-95.
- Akella, J., G. S. Smith, and A. P. Jephcoat (1988), "High Pressure Phase Transformation Studies in Gadolinium to 106 GPa," *J. Phys. Chem. Solids* **49**, 573-576.
- Olsen, S. J., S. Steenstrup, L. Gerward, U. Benedict, J. Akella, and G. S. Smith (1989), "X-ray Diffraction Studies on Samarium to One Megabar Pressure," *High Pressure Res.* **4**, 366-368.

Ammon, Chuck

- Ammon, C. J., G. E. Randall, and G. Zandt (1989), *On the Non-Uniqueness of Receiver Function Inversions*, LLNL, UCRL-102018; accepted by *J. Geophys. Res.*
- Ammon, C. J., and G. Zandt (1989), "The Receiver Structure beneath the Livermore Nevada Test Site Seismic Network Stations," *EOS* **70**, 1206.
- Ammon, C. J., J. J. Zucca, and P. W. Kasameyer (1989), "An S to P Converted Phase Recorded near Long Valley/Mono Craters Region, California," *J. Geophys. Res.* **94**, 17,721-17,727.
- Zandt, G., T. J. Owens, C. J. Ammon, G. E. Randall, and K. F. Priestley (1988), "The PASSCAL Basin and Range Passive-Source Experiment: Teleseismic Waveform Observations," *EOS* **69**, 1323.
- Zandt, G., S. R. Taylor, and C. J. Ammon (1988), *Medicine Lake Volcano Teleseismic Experiment Field Procedures and Data Analysis*, LLNL, UCID-21470.

Attia, Armand

- Attia, A. (1989), *Numerical Simulation of Shock Response of Fluid-Filled Porous Rocks*, LLNL, UCRL-100909; submitted to *Proc. 1989 APS Topical Conf. on Shock Waves in Condensed Matter*, Albuquerque, NM, Aug. 1989.
- Attia, A., and D. Young (1988), "Comparison of Two Rock Vaporization Models in DYNA-2D," *Proc. Nucl. Explosive Code Developer Conf.*, LLNL, CONF-881093, Vol. 1, p. 201.
- Attia, A. V., and R. P. Swift (1989), "Residual Stresses Calculated Using an Effective Stress Model," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 14-21.
- Swift, R. P., and A. V. Attia (1989), "Application of an Effective Stress Model to Underground Nuclear Explosions," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 3-13.
- Swift, R. P., and A. V. Attia (1989), "Numerical Simulation of Shock Attenuation in Saturated Rock," submitted to *SIAM on Mathematical and Computational Issues in Geophysical Fluid and Solid Mechanics*, Houston, Sept. 1989.

Ballou, Lyn

Ballou, L. (1989), "Current Status of Waste Package Designs for the Yucca Mountain Project," *Proc. Inst. of Nucl. Mater. Mgmt. 30th Annual Mtg.* (Inst. of Nucl. Mater. Mgmt., Northbrook, IL), pp. 195-200.

Beck, Susan

Beck, S. L., and D. H. Christensen (1988), "The Rupture Process of the Feb. 4, 1965, Rat Islands Earthquake," *EOS* **69**, 1303; accepted in *J. Geophys. Res.*

Beck, S. L., and D. H. Christensen (1989), "Asperities and Segmentation of the Overriding Plate along the Western Aleutian Subduction Zone," *IASPEI Abstracts of the 25th General Assembly of Int. Assoc. of Seismology and Physics of the Earth's Interior*, Istanbul, Turkey, p. 255.

Beck, S. L., and L. J. Ruff (1989), "Great Earthquakes and Subduction along the Peru Trench," *Phys. Earth Planet. Int.* **57**, 119.

Beck, S. L., and L. J. Ruff (1989), "Source Time Function Deconvolution: The Danger of Positivity Constraints," accepted by *Bull. Seismol. Soc. Am.*

Christensen, D. H., and S. L. Beck (1988), "Rupture Process and Tectonic Implications of the March 30, 1965, Rat Islands Normal Fault Earthquake," *EOS* **69**, 1303.

Christensen, D. H., and S. L. Beck (1989), "Rupture Process of the Great 1964 Alaska Earthquake," *EOS* **70**, 1125.

Ruff, L. J., S. L. Beck, and B. W. Tichelaar (1989), "Seismotectonics of the Macquarie Ridge Complex," *EOS* **70**, 1196.

Ruff, L., B. Tichelaar, and S. Beck (1989), "Rupture Process of the May 23, 1989 Macquarie Ridge Earthquake," *EOS* **70**, 1196.

Schwartz, S. Y., S. L. Beck, and T. Lay (1989), "Analysis of Broadband S-Waves from Deep and Intermediate Focus Earthquakes: Implications for Deep Slab Structure," *IASPEI Abstracts of the 25th General Assembly of Int. Assoc. of Seismology and Physics of the Earth's Interior*, Istanbul, Turkey, p. 65.

Beeman, Mark

Beeman, M. L., W. B. Durham, and S. H. Kirby (1988), "Friction of Ice," *J. Geophys. Res.* **93**, 7625-7633.

Borch, R. S., H. W. Green, W. B. Durlam, M. L. Beeman, and A. K. Mukherjee (1989), *The Pressure Dependence of Creep: Comparison of Data Obtained in a Heard Gas Apparatus and Griggs Apparatus with Liquid Cell, LLNL, UCRL-100903-Abs.*

Berryman, James

Berryman, J. G. (1988), "Bounds on Decay Constants for Diffusion Through Inhomogeneous Media," *J. Phys. A: Gen. Phys.* **21**, 4423-4441.

Berryman, J. G. (1988), "Interpolating and Integrating Three-Point Correlation Functions on a Lattice," *J. Comput. Phys.* **75**, 86-102.

Berryman, J. G. (1988), *Microgeometry of Porous Media*, presented at the Gordon Research Conference on Modeling of Fluid Flow in Permeable Media, Plymouth State College, Plymouth, NH, August 15-19, 1988.

Berryman, J. G. (1988), *New Applications of Fermat's Principle to Seismic Traveltime Tomography*, presented at the 17th International Conference on Mathematical Geophysics, Blanes, Spain, June 20-25, 1988.

Berryman, J. G. (1988), *Seismic Traveltime Tomography*, presented at the Twenty-Second Annual Asilomar Conference on Signals, Systems, and Computers, Pacific Grove, CA, Oct. 31-Nov. 2, 1988.

Berryman, J. G., and G. W. Milton (1988), "Microgeometry of Random Composites and Porous Media," *J. Phys. D: Appl. Phys.* **21**, 87-94.

Berryman, J. G., L. Thigpen, and R. C. Y. Chin (1988), "Bulk Wave Propagation for Partially Saturated Porous Solids," *J. Acoust. Soc. Am.* **84**, 360-373.

- Berryman, J. G. (1989), "Estimating Effective Moduli of Composites Using Quantitative Image Analysis," *Random Media and Composites*, R. V. Kohn and G. W. Milton, Eds., Proc. SIAM Workshop on Random Media and Composites, Xerox Training Center, Leesburg, VA, December 7-10, 1988 (SIAM, Philadelphia), Chapter 1, pp. 3-12.
- Berryman, J. G. (1989), "Fermat's Principle and Nonlinear Traveltime Tomography," *Phys. Rev. Lett.* **62**, 2953-2956.
- Berryman, J. G. (1989), *Imaging Fluid Flow in Rocks Using Electrical Impedance Tomography*, presented at the Minisymposium on Theoretical and Practical Aspects of Electrical Impedance Tomography, SIAM Conference on Mathematical and Computational Issues in Geophysical Fluid and Solid Mechanics, Houston, Texas, Sept. 25-28, 1989.
- Berryman, J. G. (1989), "Traveltime Tomography and Nonlinear Constrained Optimization," *Proc. Twenty-Second Annual Asilomar Conference on Signals, Systems, and Computers*, Pacific Grove, CA, Oct. 31-Nov. 2, 1988 (Maple Press, San Jose, CA), Vol. 1, pp. 54-57.
- Berryman, J. G. (1989), "Seismic Crosshole Tomography and Nonlinear Constrained Optimization," *Proc. SIAM Workshop on Geophysical Inversion*, September 27-28, 1989, Houston, Texas.
- Berryman, J. G. (1989), *Seismic Traveltime Tomography and Nonlinear Constrained Optimization*, presented at the MIT Earth Resources Laboratory, Third Annual Founding Members Workshop on Seismic Wave Propagation and Inversion in Heterogeneous Media, Aug. 1, 1989.
- Berryman, J. G. (1989), "Weighted Least-Squares Criteria for Seismic Traveltime Tomography," *IEEE Trans. Geosci. Remote Sensing* **27**, 302-309.
- Blair, Steve*
- Blair, S. C. (1989), *Study Plan for Mechanical Attributes of the Waste Package Environment*, YMP-LLNL-SP 8.3.4.2.4.3, RO, submitted to Yucca Mountain Project Office, DOE, Las Vegas, NV.
- Blair, S. C., J. C. Chen, W. R. Ralph, and D. W. Ruddle (1989), *Mechanical Properties of Rocks from the PSA Flight 1771 Crash Site*, LLNL, PATC-IR-89-05.
- Blair, S. C., R. K. Thorpe, and F. E. Heuzé (1988), *Physical Models of Hydrofracturing across Material Interfaces*, LLNL, UCID-21505.
- Blair, S. C., R. K. Thorpe, and F. E. Heuzé (1989), *Propagation of Fluid-Driven Fractures in Jointed Rock, Part 2: Physical Tests on Blocks with Interface or Lens*, LLNL, UCRL-101871; accepted by *Int. J. Rock Mech. and Min. Sci.*
- Blair, S. C., R. K. Thorpe, F. E. Heuzé, and R. J. Shaffer (1989), "Laboratory Observations of the Effect of Geologic Discontinuities on Hydrofracture Propagation," *Proc. 30th U.S. Symp. on Rock Mechanics*, Morgantown, WV (A. A. Balkema, Brookfield, VT), pp. 443-450.
- Heuzé, F. E., R. J. Shaffer, S. C. Blair, and R. K. Thorpe (1989), "Understanding the Effect of Natural Fractures on the Hydrofracture Stimulation of Natural Gas Reservoirs," *Proc. SPE Joint Rocky Mountain Regional/Low Permeability Reservoir Symp.*, Denver, SPE-18956 (SPE, Richardson, TX), pp. 261-268.
- Shaffer, R. J., F. E. Heuzé, S. C. Blair, and R. K. Thorpe (1989), *Models of Stimulation of Sand Lenses*, LLNL, UCRL-100229; presented at the SPE Joint Rocky Mountain Regional/Low Permeability Reservoir Symp., Denver, Mar. 1989.
- Thorpe, R. K., S. C. Blair, and A. E. Brown (1988), "Physical Modeling of Hydraulic Fracture Behavior near Geologic Interfaces," *Proc. 29th U.S. Symp. on Rock Mechanics*, Minneapolis (A. A. Balkema, Brookfield, VT), pp. 745-746.

Bonner, Brian

- Bonner, B. P., and B. J. Wanamaker (1989), "Nonlinear Acoustic Effects in Rocks and Soils," *Review of Progress in Quantitative Non-Destructive Evaluation*, Bowdoin College, Brunswick, ME, July 1989; LLNL, UCRL-102045.
- Bonner, B. P., B. J. Wanamaker, and K. B. Coyner (1988), *Amplitude Dependent Attenuation in Granite*, LLNL, UCRL-99711; presented at the 1988 AGU Fall Mtg., San Francisco.
- Bonner, B. P., B. J. Wanamaker, and S. R. Taylor (1989), "Amplitude Dependent Attenuation and Implications for the Seismic Source," *Proc. DOE/LLNL Symp. Explosion Source Phenomenology*, LLNL, CONF-890398, pp. 37-43.

- Merzbacher, C. I., B. P. Bonner, R. G. Bedford, P. A. Hahn, and C. E. Violet (1989), *Diffuse Reflectance Infrared Spectroscopy as an Indicator of Oxygen and Content and Annealing History of $YBa_2Cu_3O_{7-x}$* , LLNL, UCRL-99507-Abs.; presented at the Materials Research Society, Apr. 1989.
- Umegawa, A., U. Welp, W. K. Kwok, G. W. Crabtree, J. Z. Liu, K. Vandervoort, H. Claus, B. P. Bonner, and M. S. Costantino (1989), "Superconducting and Magnetic Transitions in La_2CuO_{4+x} ," *Bull. Am. Phys. Soc.* **34**, 428.
- Wanamaker, B. J., and B. P. Bonner (1988), "Low Frequency Attenuation and Modulus of Thermally Fractured Granite," *EOS* **69**, 475.
- Wang, H. F., B. P. Bonner, S. R. Carlson, B. J. Kowallis, and H. C. Heard (1989), "Thermal Stress Cracking in Granite," *J. Geophys. Res.* **94**(B2), 1745-1758.
- Boro, Carl*
- Durham, W. B., S. H. Kirby, H. C. Heard, L. A. Stern, and C. O. Boro (1988), "Water Ice Phases II, III, and V: Plastic Deformation and Phase Relationships," *J. Geophys. Res.* **93**, 10,191-10,208.
- Heard, H. C., W. B. Durham, C. O. Boro, and S. H. Kirby (1989), *A Triaxial Deformation Apparatus for Service at 77 $\leq T \leq 273$ K*, LLNL, UCRL-102030.
- Bourcier, Bill*
- Bourcier, W. L. (1989), *Geochemical Modeling of Radioactive Waste Glass Dissolution Using EQ3/6: Preliminary Results and Data Needs*, LLNL, UCRL-101621.
- Bourcier, W. L., K. G. Knauss, and K. J. Jackson (1988), "Aluminum Hydrolysis Constants to 250°C Determined from Boehmite Solubility Measurements," *Experimental Investigations of Hydrothermal Processes: Applications to Ore Deposit Genesis* (Mineral Exploration Institute, Montreal), p. 9.
- Bourcier, W. L., K. G. Knauss, C. I. Merzbacher, S. N. Nguyen, and H. C. Weed (1989), "Hydrothermal Dissolution Measurements and Mechanisms for Borosilicate Glasses," *Third Int. Symp. on Hydrothermal Reactions*, I. L. Khodakovskiy, Ed. (Vernadsky Inst. of Geochem. and Anal. Chem., USSR, Academy of Sciences).
- Bourcier, W. L., K. G. Knauss, and C. I. Merzbacher (1989), "A Kinetic Model for the Dissolution of Borosilicate Glass," *Water-Rock Interaction WRI-6*, D. L. Miles, Ed. (A. A. Balkema, Brookfield, VT), pp. 107-110.
- Bourcier, W. L., D. W. Peifer, K. G. Knauss, K. D. McKeegan, and D. K. Smith (1989), "A Kinetic Model for Borosilicate Glass Dissolution Based on the Dissolution Affinity of a Surface Alteration Layer," *Mat. Res. Soc. Symp. Proc.: Scientific Basis for Nucl. Waste Mgmt. XIII* (Mater. Res. Soc., Pittsburgh), Vol. 176, pp. 209-216.
- Bruton, C. J., B. E. Viani, W. L. Bourcier, K. J. Jackson, and R. D. Aines (1989), *Geochemical Modeling: An Integrated Approach to Nuclear Waste Disposal Issues*, LLNL, UCRL-102019; submitted to *Proc. 1st Int. High-Level Radioactive Waste Mgmt. Conf.*, Las Vegas, Apr. 1990.
- Glassley, W. E., K. J. Jackson, and W. L. Bourcier (1989), "Computer Modeling of the Aqueous Geochemistry of the Archean Hydro sphere and the Formation of Banded Iron Formations," *Proc. Workshop on Geochemical Modeling*, LLNL, CONF-8609134, pp. 146-153.
- Jackson, K. J., T. J. Wolery, W. L. Bourcier, J. M. Delany, R. M. Moore, M. L. Cline, and S. R. Lundeen (1988), *MCRT User's Guide and Documentation*, LLNL, UCID-21406-Rev. 1.
- Jackson, K. J., and W. L. Bourcier, Eds. (1989), *Proc. Workshop on Geochemical Modeling*, LLNL, CONF-8609134.
- Knauss, K. G., W. L. Bourcier, K. D. McKeegan, C. I. Merzbacher, S. N. Nguyen, F. J. Ryerson, D. K. Smith, and H. C. Weed (1989), "Dissolution Kinetics of a Simple Analogue Nuclear Waste Glass as a Function of pH, Time, and Temperature," *Mat. Res. Soc. Symp. Proc.: Scientific Basis for Nucl. Waste Mgmt. XIII* (Mater. Res. Soc., Pittsburgh), Vol. 176, pp. 371-381.
- Merzbacher, C. I., R. L. Ward, K. G. Knauss, W. L. Bourcier, S. N. Nguyen, and H. C. Weed (1989), "The Effect of Boron on Aluminosilicate Glass Structure and Leaching Behavior: An MAS NMR and DRIFTS Study," LLNL, UCRL-101791-Abs.; presented at the 1989 AGU Fall Mtg., San Francisco.

- Sawka, W. N., and W. L. Bourcier (1989), "Application of Geochemical Aqueous Speciation-Solubility Program EQ3/6 to the Preparation of Multi-Element Liquid Standards for X-ray Fluorescence and Other Analytical Methods," LLNL, UCRL-101078-Abs.; submitted to *Anal. Chem. Soc. Proc.*, Denver.
- Viani, B. E., C. J. Bruton, and W. L. Bourcier (1989), "Comparison of Ideal Mixing Models Used to Describe Smectite Solid Solutions for Geochemical Modeling," LLNL, UCRL-100251-Abs.; submitted to the 9th Int. Clay Conf.
- Wolery, T. J., K. J. Jackson, W. L. Bourcier, C. J. Bruton, B. E. Viani, K. G. Knauss, and J. M. Delany (1988), "The EQ3/6 Software Package for Geochemical Modeling," LLNL, UCRL-98729; submitted to *Proc. Amer. Chem. Soc. 196th National Mtg.*, Los Angeles.
- Zolensky, M. E., W. L. Bourcier, and J. L. Gooding (1989), "Aqueous Alteration on the Hydrated Asteroids: Results of EQ3/6 Computer Simulations," *Icarus* 78, 411.

Braun, Robert

- Braun, R. L., and A. K. Burnham (1988), *KINETICS: A Computer Program to Analyze Chemical Reaction Data*, LLNL, UCID-21588.
- Braun, R. L., and A. K. Burnham (1988), *Thermal Cracking of Hydrocarbons*, LLNL, UCID-21507.
- Braun, R. L., and A. K. Burnham (1989), "A Mathematical Model of Oil Generation, Degradation, and Expulsion," *Energy and Fuels* 4, 132-146.
- Braun, R. L., A. K. Burnham, and J. J. Sweeney (1988), *Petroleum Geochemistry Project Annual Report, Oct. 1987-Sept. 1988*, LLNL, UCID-21303-88-4.
- Burnham, A. K., and R. L. Braun (1989), *A Detailed Kinetic and Thermodynamic Model of Petroleum Formation, Destruction, and Expulsion*, LLNL, UCRL-99776; presented at 14th Int. Mtg. on Org. Geochem., Paris, Sept. 1989.
- Burnham, A. K., R. L. Braun, and A. M. Samoun (1988), "Further Comparison of Methods for Measuring Kerogen Pyrolysis Rates and Fitting Kinetic Parameters," *Org. Geochem.* 13, 839-845.
- Burnham, A. K., R. L. Braun, and J. J. Sweeney (1988), *Kinetic Modeling of Petroleum Generation and Destruction*, LLNL, UCRL-98442-Abs.; presented at Am. Assoc. of Petrol. Eng. Res. Conf., Leesburg, VA, Apr. 1988.
- Burnham, A. K., R. L. Braun, and R. W. Taylor (1989), "Comparison of Isothermal and Nonisothermal Pyrolysis Data with Various Rate Mechanisms: Implications for Kerogen Structure," *Div. Petrol. Chem., ACS* 34, 36-42.
- Camp, D. W., R. L. Braun, and J. C. Diaz (1989), "Results of Mathematical Modeling of an Oil Shale Retort Having a Fluidized-Bed Pyrolyzer and a Lift-Pipe Combustor," *Fuel Processing Technol.* 21, 135.
- Walton, O. R., R. L. Braun, R. G. Mallon, and D. M. Cervelli (1988), "Particle-Dynamics Calculations of Gravity Flow of Inelastic, Frictional Spheres," *Micromechanics of Granular Materials*, M. Satake and J. T. Jenkins, Eds. (Elsevier, Amsterdam), pp. 153-161.

Bruton, Carol

- Bruton, C. J., B. E. Viani, W. L. Bourcier, K. J. Jackson, and R. D. Aines (1989), *Geochemical Modeling: An Integrated Approach to Nuclear Waste Disposal Issues*, LLNL, UCRL-102019; submitted to *Proc. 1st Int. High-Level Radioactive Waste Mgmt. Conf.*, Las Vegas, Apr. 1990.
- Viani, B. E., C. J. Bruton, and W. L. Bourcier (1989), "Comparison of Ideal Mixing Models Used to Describe Smectite Solid Solutions for Geochemical Modeling," LLNL, UCRL-100251-Abs.; submitted to the 9th Int. Clay Conf.
- Wolery, T. J., K. J. Jackson, W. L. Bourcier, C. J. Bruton, B. E. Viani, K. G. Knauss, and J. M. Delany (1988), "The EQ3/6 Software Package for Geochemical Modeling," LLNL, UCRL-98729; submitted to *Proc. Amer. Chem. Soc. 196th National Mtg.*, Los Angeles.

Buchholtz-ten Brink, Marilyn

- Buchholtz-ten Brink, M. R., G. Gust, and D. Chavis (1989), "Calibration and Performance of a Stirred Benthic Chamber," *Deep Sea Res.* 36, 1083-1101.

- Buchholtz-ten Brink, M. R., D. Phinney, K. D. McKeegan, and V. M. Oversby (1989), "Uranium Transport in Topopah Spring Tuff: Multiple Diffusion Paths," LLNL, UCRL-102140-Abs.; presented at the 2nd Int. Conf. on Chemistry and Migration Behavior of Actinides and Fission Products in the Geosphere, Monterey, CA, Nov. 1989.
- Gerlach, D. C., C. A. Eddy, R. W. Murray, M. R. Buchholtz-ten Brink, and G. P. Russ, III (1989), "Trace-Element Analysis of Geological Samples by ICP-MS: Case Studies and Examples," *Nuclear Chemistry Annual Report*, LLNL, UCAR-10062.
- McKeegan, K. D., D. Phinney, V. M. Oversby, M. R. Buchholtz-ten Brink, and D. K. Smith (1988), "Uranium Transport in Topopah Spring Tuff: An Ion-Microscope Investigation," *Mat. Res. Soc. Symp. Proc.: Scientific Basis for Nucl. Waste Mgmt. XII* (Mater. Res. Soc., Pittsburgh), Vol. 127, pp. 813-821.
- Murray, R. W., M. R. Buchholtz-ten Brink, D. L. Jones, D. C. Gerlach, and G. P. Russ, III (1989), "Rare-Earth Element Variability in Marine Cherts and Shales: The Dependence on Depositional Environment," *198th ACS Natl. Mtg., ACS Symp. on Global Sedimentary Cycles* (Am. Chem. Soc., Washington, DC).
- Murray, R. W., M. R. Buchholtz-ten Brink, D. L. Jones, D. C. Gerlach, and G. P. Russ, III (1989), *The Use of Rare-Earth Elements in Cherts and Shales as Indicators of Different Marine Depositional Environments*, LLNL, UCRL-101520; accepted by *Geology*.
- Murray, R. W., M. R. Buchholtz-ten Brink, D. C. Gerlach, and G. P. Russ, III (1989), "Rare-Earth, Major, and Trace Element Behavior during Diagenesis of Chert and Shale," *EOS* 71, 90.

Burkhard, Norm

- Burkhard, N. R. (1989), "Physical Properties in LLNL Yucca Flat Areas: The Rock Pile Concept," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 223-273.
- Burkhard, N. R., and J. R. Hearst (1989), "Bound Water Corrections to Epithermal Neutron Derived Water Contents," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 206-222.
- Burkhard, N. R., J. R. Hearst, E. W. Peterson, R. H. Nilson, and K. H. Lie (1989), "Containment of Cavity Gas in Fractured or Rubblized Emplacement Media," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 1, pp. 253-280.
- Burkhard, N. R., and G. A. Pawloski (1988), *U2cu Site Characteristics Report*, LLNL, Containment Rpt. CP 88-148.
- Burkhard, N. R., and J. L. Wagoner (1989), *U20az Site Characteristics Report*, LLNL, Containment Rpt. CP 89-67.
- Hearst, J. R., and N. R. Burkhard (1989), "A Study of the Difference between Gravimetric and Gamma-Gamma Density in Yucca Flat," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 310-336.
- Wagoner, J. L., and N. R. Burkhard (1988), *U4au Site Characteristics Report*, LLNL, Containment Rpt. CP 88-13.

Burnham, Alan

- Braun, R. L., and A. K. Burnham (1988), *KINETICS: A Computer Program to Analyze Chemical Reaction Data*, LLNL, UCID-21588.
- Braun, R. L., and A. K. Burnham (1988), *Thermal Cracking of Hydrocarbons*, LLNL, UCID-21507.
- Braun, R. L., and A. K. Burnham (1989), "A Mathematical Model of Oil Generation, Degradation, and Expulsion," *Energy and Fuels* 4, 132-146.
- Braun, R. L., A. K. Burnham, and J. J. Sweeney (1988), *Petroleum Geochemistry Project Annual Report*, Oct. 1987-Sept. 1988, LLNL, UCID-21303-88-4.
- Burnham, A. K. (1989), "On Solar Thermal Processing and Retorting of Oil Shale," *ENERGY* 14, 667-674.
- Burnham, A. K. (1989), *A Simple Kinetic Model of Petroleum Formation and Cracking*, LLNL, UCID-21664.
- Burnham, A. K. (1989), *Rock-Eval Analysis of LLNL Samples by Industrial Sponsors Part 1: S2 and TMAX*, LLNL, UCID-21665.

- Burnham, A. K. (1989), "On the Validity of the Pristane Formation Index," *Geochim. Cosmochim. Acta* **53**, 1693-1697.
- Burnham, A. K., and R. L. Braun (1989), *A Detailed Kinetic and Thermodynamic Model of Petroleum Formation, Destruction, and Expulsion*, LLNL, UCRL-99776; presented at 14th Int. Mtg. on Org. Geochem., Paris, Sept. 1989.
- Burnham, A. K., R. L. Braun, and A. M. Samoun (1988), "Further Comparison of Methods for Measuring Kerogen Pyrolysis Rates and Fitting Kinetic Parameters," *Org. Geochem.* **13**, 839-845.
- Burnham, A. K., R. L. Braun, and J. J. Sweeney (1988), *Kinetic Modeling of Petroleum Generation and Destruction*, LLNL, UCRL-98442-Abs.; presented at Am. Assoc. of Petrol. Eng. Res. Conf., Leesburg, VA, Apr. 1988.
- Burnham, A. K., R. L. Braun, and R. W. Taylor (1989), "Comparison of Isothermal and Nonisothermal Pyrolysis Data with Various Rate Mechanisms: Implications for Kerogen Structure," *Div. Petrol. Chem., ACS* **34**, 36-42.
- Burnham, A. K., M. S. Oh, and R. W. Crawford (1989), "Activation Energy Distributions and Related Chemistry for Pyrolysis of the Argonne Premium Coals," *Energy and Fuels* **3**, 42-55.
- Burnham, A. K., and J. J. Sweeney (1989), "A Chemical Kinetic Model of Vitrinite Maturation and Reflectance," *Geochim. Cosmochim. Acta* **53**, 2649-2657.
- Burnham, A. K., and J. J. Sweeney (1989), *Modeling the Maturation and Migration of Petroleum*, LLNL, CA, UCRL-102602; submitted to the AAPG Handbook of Petroleum Geology.
- Oh, M. S., A. K. Burnham, and R. W. Crawford (1988), "Evolution of Sulfur Gases during Coal Pyrolysis," *Div. Fuel Chem., ACS* **33**, 274-282.
- Oh, M. S., T. T. Coburn, R. W. Crawford, and A. K. Burnham (1988), "Study of Gas Evolution during Oil Shale Pyrolysis by TQMS," *Proc. 21st Int. Conf. on Oil Shale and Shale Oil. Oil Shale Symp.*, Beijing, China (Chemical Industry Press, China), pp. 295-302.
- Reynolds, J. G., R. W. Crawford, and A. K. Burnham (1989), "Oil Shale Pyrolysis by Triple Quadrupole Mass Spectrometry: Comparison of Gas Evolution at 10°C/min Heating Rate," *Div. of Fuel, ACS* **34**, pp. 1106-1114.
- Sweeney, J. J., and A. K. Burnham (1989), *A Maturation Model of Vitrinite Reflectance Based on Chemical Kinetics: Applications to a Wide Range of Geologic Conditions*, LLNL, UCRL-102020-Abs.; presented at the AAPG Convention, San Francisco.
- Sweeney, J. J., and A. K. Burnham (1989), "Evaluation of a Simple Model of Vitrinite Reflectance Based on Chemical Kinetics," *AAPG Bull.* (in press).
- Sweeney, J. S., S. Talukdar, A. Burnham, and C. Vallejos (1989), *Pyrolysis Kinetics Applied to Prediction of Oil Generation in the Maracaibo Basin, Venezuela*, LLNL, UCRL-99932; presented at 14th Int. Mtg. on Org. Geochem., Paris, Sept. 1989.

Buscheck, Tom

- Buscheck, T. A., and J. J. Nitao (1988), *Estimates of the Hydrologic Impact of Drilling Water on Core Samples Taken from Partially Saturated Densely Welded Tuff*, LLNL, UCID-21294.
- Buscheck, T. A., and J. J. Nitao (1988), *Estimates of the Width of the Wetting Zone along a Fracture Subjected to an Episodic Infiltration Event in Variably Saturated, Densely Welded Tuff*, LLNL, UCID-21579.
- Buscheck, T. A., and J. J. Nitao (1989), "Preliminary Scoping Calculations of Hydrothermal Flow," *Prototype Engineered Barrier System Field Test, Progress Report, Nov. 1, 1988*, LLNL, UCID-21640.
- Buscheck, T. A., and J. J. Nitao (1988), *Preliminary Scoping Calculations of Hydrothermal Flow in Variably Saturated, Fractured, Welded Tuff During the Engineered Barrier Design Test at the Yucca Mountain Exploratory Shaft Test Site*, LLNL, UCID-21571.
- Klavetter, A., D. Hoxie, D. Chesnut, T. Buscheck, and K. Birdsall (1988), *A Suggested Structure for Model Validation for the Nevada Nuclear Waste Storage Investigations Project*, Sandia National Laboratories, Albuquerque, NM, SAND87-3092.
- Nitao, J. J., and T. A. Buscheck (1989), *Movement of a Liquid Front in an Unsaturated, Fractured Porous Medium I: Physical Theory*, LLNL, UCRL-101005.

- Nitao, J. J., and T. A. Buscheck (1989), *Movement of a Liquid Front in an Unsaturated, Fractured Porous Medium II: Mathematical Analysis*, LLNL, UCRL-101006.
- Nitao, J. J., and T. A. Buscheck (1989), "On the Infiltration of a Liquid Front in an Unsaturated, Fractured Porous Medium," *Proc. Nucl. Waste Isolation in the Unsaturated Zone, Focus '89* (Am. Nucl. Soc., La Grange Park, IL), pp. 381-397.
- Ramirez, A., J. Beatty, T. Buscheck, R. Carlson, W. Daily, R. LaTorre, K. Lee, W. Lin, N. Mao, J. Nitao, D. Towse, T. Ueng, D. Watwood, and D. Wilder (1989), "Prototype Engineered Barrier System Field Tests—Progress Report," *Proc. Nucl. Waste Isolation in an Unsaturated Zone, Focus '89* (Am. Nucl. Soc., LaGrange Park, IL), pp. 30-37.
- Carlson, Dick
- Ramirez, A., J. Beatty, T. Buscheck, R. Carlson, W. Daily, R. LaTorre, K. Lee, W. Lin, N. Mao, J. Nitao, D. Towse, T. Ueng, D. Watwood, and D. Wilder (1989) "Prototype Engineered Barrier System Field Tests—Progress Report," *Proc. Nucl. Waste Isolation in an Unsaturated Zone, Focus '89* (Am. Nucl. Soc., LaGrange Park, IL), pp. 30-37.
- Carpenter, Dave
- Carpenter, D. W., J. C. Chen, and G. S. Holman (1989), *An Engineering Geologic Evaluation of the PSA Flight 1771 Crash Site near Paso Robles, California*, LLNL, PATC-TR-89-04.
- Carpenter, D. W., and D. H. Chung (1988), *Seismotectonics of the Wichita-Amarillo Uplift Region: Paleo and Neotectonic Examples*, LLNL, UCID-21449.
- Carpenter, D. W., A. L. Lamarre, N. B. Crow, and P. M. Swearingen (1988), *Closure Plan for the Decommissioned High Explosives Rinse Water Lagoons at Lawrence Livermore National Laboratory Site 300*, LLNL, UCID-21369.
- Denny, Marc
- Denny, M. D. (1988), "Yield Estimation Using On-Site Ground Motion and Empirical Green's Functions," presented at the LYTTBT Yield Monitoring Mtg., Nov. 1988.
- Denny, M. D. (1988), "Seismic Magnitude and A/T," Seismology and Applied Geophysics Group, Memo SAG 88-4.
- Denny, M. D. (1988), *Explosion Source Roll-off; w-2 or w-3?*, LLNL, UCRL-98524; submitted to AFGL/DARPA Seismic Research Symp., Fallbrook, CA, May 1988.
- Denny, M. D. and D. Harris (1989), *On-Site Seismic Yield Estimation*, presented at the Conf. on Technology Research and Development for Arms Control Verification, Los Alamos, NM, Aug. 1989.
- Denny, M. D. (1988), "New Results from a Reevaluation of the Nuclear Events Salmon and Sterling," *Seismol. Res. Lett.* 59(1).
- Denny, M. D. (1989), "Freefield Data and the Seismic Source Function: New Source Parameter Results," *Proc. DOE/LLNL Symp. on Explosion Source Phenomenology*, LLNL, CONF-890398, pp. 44-51.
- Denny, M. D. (1989), *Results from a Re-examination of the Salmon and Sterling Experiments*, LLNL, UCRL-99069; submitted to *J. Geophys. Res.*
- Taylor, S. R., M. D. Denny, E. S. Vergino, and R. E. Glaser (1989), "Regional Discrimination between NTS Explosions and Western U.S. Earthquakes," *Bull. Seismol. Soc. Am.* 79, 1142-1176.
- Taylor, S. R., N. W. Sherman, and M. D. Denny (1988), "Spectral Discrimination between NTS Explosions and Western U.S. Earthquakes at Regional Distances," *Bull. Seismol. Soc. Am.* 78, 1563.
- Vergino, E. S., M. D. Denny, and S. R. Taylor (1988), "A New Look at the Explosion Source Function," *Seismol. Res. Lett.* 59(44).
- Duba, Al
- Constable, S. C., and A. Duba (1988), "Electrical Conductivity of an Olivine Rich Rock: $RSP \times 10^2$ Possibly Not," *EOS* 69, 1506.

- Constable, S. C., and A. Duba (1989), *The Electrical Conductivity of Olivine, a Dumite and the Mantle*, LLNL, UCRL-101087; accepted by *J. Geophys. Res.*
- Constable, S. C., and A. C. Duba (1989), *Electrical Conductivity of Dumite under Controlled Oxygen Fugacity*, LLNL, UCRL-101386-Abs.; presented at the 28th Int. Geologic Congress, Washington, DC, July 1989.
- Duba, A. (1988), "Differentiation of Carbon-Bearing Meteorite Parent Bodies by Electromagnetic Heating: The Effect of Pressure on Pyrolysis," *EOS* **69**, 392.
- Duba, A., E. Huenges, G. Nover, G. Will, and H. Jödicke (1988), "Impedance of Black Shale from Münsterland 1 Borehole: An Anomalously Good Conductor?," *Geophys. J.* **94**, 413.
- Duba, A. G., R. N. Schock, E. L. Arnold, and T. J. Shankland (1989), "An Apparatus for Measurement of Electrical Conductivity to 1500°C at Known Oxygen Fugacity," LLNL, UCRL-102032.
- Duba, A., and G. Will (1988), *Electrical Conductivity of Black Shale: Implications for Crustal Conductivity Anomalies*, LLNL, UCRL-98633-Abs.; presented at the IX Workshop on Electromagnetic Induction in the Earth and Moon, Sochi, USSR, Oct. 1988.
- Duba, A., M. Young, and T. J. Shankland (1988), "Electrical Conductivity of Synthetic Olivine to 1500°C: Products, Promise, and Problems," *EOS* **69**, 1436.
- Schock, R. N., A. G. Duba, and T. J. Shankland (1989), "Electrical Conduction in Olivine," *J. Geophys. Res.* **94**, 5829-5839.
- Shankland, T. J., L. M. Hirsch, and A. G. Duba (1989), "Effect of Iron Content on Mineral Conductivity," *AGA Bull.* **53**, 156.
- Wanamaker, B. J., and A. G. Duba (1989), *The Effect of Temperature-Dependent and -Independent Oxygen Fugacity on Olivine Conductivity*, LLNL, UCRL-101713-Abs.; presented at the 1989 AGU Fall Mtg., San Francisco.
- Durham, Bill*
- Borch, R. S., H. W. Green, W. B. Durham, M. L. Beeman, and A. K. Mukherjee (1989), *The Pressure Dependence of Creep: Comparison of Data Obtained in a Gas Medium Apparatus and Griggs Apparatus with Liquid Cell*, LLNL, UCRL-100903-Abs.
- Beeman, M. L., W. B. Durham, and S. H. Kirby (1988), "Friction of Ice," *J. Geophys. Res.* **93**, 7625-7633.
- Durham, W. B. (1989), *Capabilities for Measuring Physical and Chemical Properties of Rocks at High Pressure*, LLNL, UCID-21754.
- Durham, W. B., S. H. Kirby, H. C. Heard, L. A. Stern, and C. O. Boro (1988), "Water Ice Phases II, III, and V: Plastic Deformation and Phase Relationships," *J. Geophys. Res.* **93**, 10,191-10,208.
- Durham, W. B., S. H. Kirby, and L. A. Stern (1989), "Rheology of Water-Ammonia Ice: First Results," *Proc. 19th Lunar and Planet. Sci. Conf.*, Houston, pp. 285-286.
- Durham, W. B., S. H. Kirby, and L. A. Stern (1989), *Flow of NH₃-H₂O Ice under Planetary Conditions*, LLNL, UCRL-101852-Abs.
- Durham, W. B., S. H. Kirby, L. A. Stern, and K. A. Ragaini (1989), "Brittle and Ductile Behavior of Ice/Rock Mixtures," *Proc. 19th Lunar and Planet. Sci. Conf.*, Houston, pp. 254-255.
- Durham, W. B., H. M. Smith, D. H. Hanson, and H. A. Spetzler (1989), *Creep Testing of Synthetic Olivine Single Crystals*, LLNL, UCRL-102330-Abs.
- Heard, H. C., W. B. Durham, C. O. Boro, and S. H. Kirby (1989), *A Triaxial Deformation Apparatus for Service at 77 ≤ T ≤ 273 K*, LLNL, UCRL-102030.
- Kirby, S. H., W. B. Durham, and L. A. Stern (1989), *The Ice I-II Transformation under Non-Hydrostatic Stress: New Observations Relevant to the Mechanisms of Bulk Transformation, Faulting and Deep Earthquakes*, LLNL, UCRL-102029-Abs.
- Ryerson, F. J., W. B. Durham, D. J. Cherniak, and W. A. Lanford (1989), "Oxygen Diffusion in Olivine: The Effect of Oxygen Fugacity and Implications for Creep," *J. Geophys. Res.* **94**, 4105-4118.

Stern, L. A., S. H. Kirby, and W. B. Durham, *Synthesis and Deformation of CH₄-Clathrate Hydrate for Applications to the Icy Moons of the Outer Planets*, LLNL, UCRL-102170-Abs; presented at the 1988 AGU Fall Mtg., San Francisco.

Glassley, Bill

Glassley, W. E. (1989), "Evaluation of the Post-Emplacement Environment of High-Level Radioactive Waste Packages at Yucca Mountain, Nevada," *Proc. Waste Mgmt. '89 Symposia*, Tucson, Vol. 1, pp. 477-483.

Glassley, W. E., K. J. Jackson, and W. L. Bourcier (1989), "Computer Modeling of the Aqueous Geochemistry of the Archean Hydrosphere and the Formation of Banded Iron Formations," *Proc. Workshop on Geochemical Modeling*, LLNL, CONF-8609134, pp. 146-153.

Glenn, David

Glenn, H. D., and J. T. Rambo (1989), "Sensitivity of the Residual Stress Field to Variation of the Strengths for a Weak Layer Overlaying a Strong Working Point Layer," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 22-50.

Thorpe, R. K., D. B. Larson, R. B. Stout, R. P. Swift, and H. D. Glenn (1988), *A Conceptual Plan for Experiments to Improve Ground Shock Predictions for the EPW Program*, LLNL, UCID-21611.

Glenn, Lew

Glenn, L. A. (1989), "Anomalies in the Results of the Salmon Experiment," *Proc. DOE/LLNL Symp. on Explosion Source Phenomenology*, LLNL, CONF-890398, pp. 184-185.

Glenn, L. A. (1989), *Design Limitations on Ultra-High Velocity Projectile Launchers*, LLNL, UCRL-100496; presented at the Hypervelocity Impact Symp., San Antonio, Dec. 1989.

Glenn, L. A. (1989), *Strain Hardening in Salt—Results of the SALMON Experiment*, LLNL, UCRL-101156; presented at the ASME Energy-Sources Technology Conference, New Orleans, Jan. 1990.

Glenn, L. A. (1988), *Ultra-High Velocity, HE-Driven Projectile Launchers*, LLNL, UCRL-99306; presented at the 5th Nucl. Code Developer's Conf., Boulder, Oct. 1988.

Glenn, L. A., A. L. Latter, and E. A. Martinelli (1989), *Multistage Gasdynamic Launchers*, LLNL, UCRL-100586; presented at 1989 APS Topical Conf. on Shock Waves in Condensed Matter, Albuquerque, Aug. 1989.

Glenn, L. A., B. Moran, M. Kamegai, and W. P. Crowley (1989), *CORREX with Aspherical Sources*, LLNL, UCRL-102022, Rev. 1; presented at the 7th Biennial Nucl. Explosives Design Physics Conference, Livermore, Oct. 1989.

Hannon, Jim

Hannon, W. J. (1989), *Thinking about Nuclear Test Ban Issues*, LLNL, UCRL-100942-Abs.

Judd, B. R., L. W. Younker, W. J. Hannon, R. S. Strait, P. C. Meagher, and A. Sicherman (1988), *Decision Analysis Framework for Evaluating Compliance with the Threshold Test Ban Treaty*, LLNL, UCRL-53830.

Harben, Phil

Harben, P. E., and M. Pihlman (1988), *Thermal Front Tracking with Cross Borehole Electromagnetic Imaging*, LLNL, UCID-21396.

Harben, P. E., and D. B. Harris (1988), *Bearing Estimation Studies with the LLNL Kansas Seismic Array*, LLNL, UCID-21345.

Harben, P. E., and D. W. Rock (1989), *Deployment of the Oklahoma Borehole Seismic Experiment*, LLNL, UCID-21612.

Pihlman, M., and P. E. Harben (1989), "Low Frequency Electromagnetic Cross-Borehole Imaging," *3rd Simposio Int. Sobre Recuperacion Mejorada de Crudo, Trabajos Tecnicos Maricao, Venezuela*, pp. 747-764.

Sweeney, J., P. Harben, J. Hjelme, and E. Hjortenberget (1989), "Broadband Seismic Noise Measurements in North-east Greenland," *EOS* 70, 1224.

Hauk, Terri

- Harris, D. B., A. M. Dainty, and T. F. Hauk (1988), *High Resolution Investigation of Teleseismic P Coda at NORESS*, LLNL, UCRL-97940; presented at Seismological Society of America-Seismological Society of Japan Spring Mtg., Honolulu, May 1988.
- Harris, D., T. Hauk, M. Goldner, and M. Kurtzer (1988), "Distributions for Seismic Signal Representation," *Proc. 22nd Annual Asilomar Conf. on Signals, Systems, and Computers*, (Maple Press, San Jose), Vol. 1, pp. 63-67.
- Hutchings, L. W., S. P. Jarpe, P. W. Kasameyer, and T. F. Hauk (1988), "Microseismicity of the Salton Sea Geothermal Field," *EOS* 69, 1312.
- Jarpe, S. P., L. W. Hutchings, T. F. Hauk, and A. F. Shakal (1989), "Selected Strong- and Weak-Motion Data from the Loma Prieta Earthquake Sequence," *Seismol. Res. Lett.* 60, 167-176.
- Jarpe, S. P., P. W. Kasameyer, L. W. Hutchings, and T. F. Hauk (1988), *Seismic Monitoring of the June 1988, Salton Sea Scientific Drilling Program Flow/Injection Test*, LLNL, UCID-21521.

Hearst, Joe

- Burkhard, N. R., and J. R. Hearst (1989), "Bound Water Corrections to Epithermal Neutron Derived Water Contents," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 206-222.
- Burkhard, N. R., J. R. Hearst, E. W. Peterson, R. H. Nilson, and K. H. Lie (1989), "Containment of Cavity Gas in Fractured or Rubblized Emplacement Media," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 1, pp. 253-280.
- Hearst, J. R. (1989), "Adapting Carbon/Oxygen Logging for Use at the Nevada Test Site," *Nuclear Test—Experimental Science Annual Report, FY 1988*, LLNL, UCRL-53929-88, p. 268.
- Hearst, J. R., and N. R. Burkhard (1989), "A Study of the Difference between Gravimetric and Gamma-Gamma Density in Yucca Flat," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 310-336.
- Hearst, J. R., J. G. Conaway, M. A. Mathews, and J. W. Barber (1989), *Environmental Corrections for a Neutron-Induced Gamma-Ray Spectroscopy Logging System in an Air-Filled Borehole*, LLNL, UCRL-100794; presented at the 3rd Int. Symp. on Borehole Geophysics for Minerals, Geotechnical and Ground Water Applications (Minerals and Geotechnical Logging Soc.), Las Vegas, Oct. 1989.
- Hearst, J. R., J. G. Conaway, M. A. Mathews, and J. W. Barber (1989), "In Situ Equivalent CO₂ Estimates Using a Neutron-Induced Gamma-Ray Spectroscopy Logging System," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 160-185.
- Hearst, J. R., O. Fackler, M. Mugge, and J. Thomas (1988), *Measured Free-Air Gradients of Gravity Do Not Agree with Whole-Earth Models*, LLNL, UCRL-99785; presented at the 1988 AGU Fall Mtg., San Francisco.
- Hearst, J. R., and J. L. Wagoner (1988), *U8n Site Characteristics Report*, LLNL, Containment Rpt. CP 88-101.
- Kasameyer, P. W., and J. R. Hearst (1988), "Borehole Gravity Measurements in the Salton Sea Scientific Drilling Project Well State 2-14," *J. Geophys. Res.* 93(B11), 13,037-13,045.
- McKague, H. L., J. R. Hearst, and B. McKinnis (1989), *U20bc Site Characteristics Report*, LLNL, Containment Rpt. CP 89-48.

Heuzé, François

- Blair, S. C., R. K. Thorpe, and F. E. Heuzé (1988), *Physical Models of Hydrofracturing across Material Interfaces*, LLNL, UCID-21505.
- Blair, S. C., R. K. Thorpe, and F. E. Heuzé (1989), *Propagation of Fluid-Driven Fractures in Jointed Rock. Part 2: Physical Tests on Blocks with Interfacial or Lens*, LLNL, UCRL-101871; accepted by *Int. J. Rock Mech. and Min. Sci.*
- Blair, S. C., R. K. Thorpe, F. E. Heuzé, and R. J. Shaffer (1989), "Laboratory Observations of the Effect of Geologic Discontinuities on Hydrofracture Propagation," *Proc. 30th U.S. Symp. on Rock Mechanics*, Morgantown, WV (A. A. Balkema, Brookfield, VT), pp. 443-450.

- Butkovich, T. R., O. R. Walton, and F. E. Heuzé (1988), "Insights in Cratering Phenomenology Provided by Discrete Element Modeling," *Proc. 29th U.S. Symp. on Rock Mechanics*, Minneapolis, (A. A. Balkema, Brookfield, VT), pp. 359-368.
- Fourney, W. L., T. F. Adams, J. W. Dally, F. E. Heuzé, and D. A. Shockey (1988), "Directions for Future Research and Applications in Dynamic Fracture and Fragmentation of Geologic Materials," *Report of an NSF-Sponsored Workshop*, Keystone, CO (Univ. of Maryland, College Park, MD).
- Heuzé, F. E. (1988), *Indirect Estimates of Rock Mass Strength by Projectile Penetration Tests and Other Methods—An Overview and Discussion of Relevance to the Nuclear Test Program*, LLNL, UCID-21550.
- Heuzé, F. E. (1989), "An Overview of Projectile Penetration into Geologic Materials with Emphasis on Rocks," *AMD (Am. Soc. Mech. Eng., New York)*, Vol. 103, pp. 275-308.
- Heuzé, F. E., R. J. Shaffer, S. C. Blair, and R. K. Thorpe (1989), "Understanding the Effect of Natural Fractures on the Hydrofracture Stimulation of Natural Gas Reservoirs," *Proc. SPE Joint Rocky Mountain Regional/Low Permeability Reservoir Symp.*, Denver, SPE-18956 (SPE, Richardson, TX), pp. 261-268.
- Heuzé, F. E., R. J. Shaffer, A. R. Ingraffea, and R. H. Nilson (1989), *Propagation of Fluid-Driven Fractures in Jointed Rock, Part 1: Development and Validation of Methods of Analysis*, LLNL, UCRL-101870.
- Heuzé, F. E., O. R. Walton, and T. R. Butkovich (1988), "Cratering Phenomenology Revealed through Discrete-Element Modeling," *Energy and Technology Review*, LLNL, UCRL-52000-88-11, pp. 1-8.
- Keusel, T. R., J. M. Duncan, C. A. Heath, F. E. Heuzé, J. K. Mitchell, J. Ramage, K. H. Stokoe, P. Y. Thompson, E. B. Waggoner (1989), "Geotechnology: Its Impact on Economic Growth, the Environment, and National Security," *Report of the Geotechnical Board of the National Research Council/National Academy of Sciences* (National Academy Press, Washington, DC), p. 90.
- Shaffer, R. J., F. E. Heuzé, S. C. Blair, and R. K. Thorpe (1989), *Models of Stimulation of Sand Lenses*, LLNL, UCRL-100229; presented at the SPE Joint Rocky Mountain Regional/Low Permeability Reservoir Symp., Denver, Mar. 1989.
- Walton, O. R., and F. E. Heuzé, "Discrete Element Modeling of Explosion in Jointed Rocks," *Proc. DOE/LLNL Symp. on Explosion Source Phenomenology*, LLNL, CONF-890398, pp. 241-242.

Hudson, Billy

- Hudson, B. C. (1989), "Measuring Cavity Pressure in Nuclear Tests," *Nuclear Test—Experimental Science Annual Report, FY 1988*, LLNL, UCRL-53929-88, p. 266-267.
- Hudson, B. C. (1989), "Plug Evaluation Diagnostics Systems," *Nuclear Test—Experimental Science Annual Report, FY 1988*, LLNL, UCRL-53929-88, p. 271-272.
- Hudson, B., E. Peterson, R. Brownlee, A. Chabai, G. Higgins, and J. LaComb (1989), "Mighty Oak Containment Review," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 1, pp. 107-118.
- Hudson, B., T. Stubbs, R. Nilson, and E. Peterson (1989), "Recent Nuclear Cavity Pressure Measurements," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 133-138.
- Hudson, B., and B. Trent (1989), "The Effect of Cavity Gas Pressure and Porous Flow on Stemming Performance," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 1, pp. 211-230.
- Wheeler, V. E., and B. C. Hudson (1989), "Free-Field Particle Velocity and Yield," *Proc. DOE/LLNL Symp. on Explosion Source Phenomenology*, LLNL, CONF-890398, pp. 100-101.

Hutchings, Larry

- Jarpe, S. P., L. W. Hutchings, T. F. Hauk, and A. F. Shakal (1989), "Selected Strong- and Weak-Motion Data from the Loma Prieta Earthquake Sequence," *Seismol. Res. Lett.* **60**, 167-176.
- Jarpe, S. P., P. W. Kasameyer, L. W. Hutchings, and T. F. Hauk (1988), *Seismic Monitoring of the June 1988, Salton Sea Scientific Drilling Program Flow/Injection Test*, LLNL, UCID-21521.
- Hutchings, L. W., S. P. Jarpe, P. W. Kasameyer, and T. F. Hauk (1988), "Microseismicity of the Salton Sea Geothermal Field," *EOS* **69**, 1312.

Hutchings, L., and F. Wu (1990), "Small Earthquakes as Empirical Green's Functions—A Waveform Study of Locally Recorded Aftershocks of the 1971 San Fernando Earthquake," *J. Geophys. Res.* **95**, 1187–1214.

Isherwood, William

W. F. Isherwood et al. (1988), *Ground Water Project, Monthly Progress Report*, LLNL, UCAR-10160-88 (12 issues).

W. F. Isherwood et al. (1989), *Ground Water Project, Monthly Progress Report*, LLNL, UCAR-10160-89 (12 issues).

Jackson, Ken

Bourcier, W. L., K. G. Knauss, and K. J. Jackson (1988), "Aluminum Hydrolysis Constants to 250°C Determined from Boehmite Solubility Measurements," *Experimental Investigations of Hydrothermal Processes: Applications to Ore Deposit Genesis* (Mineral Exploration Institute, Montreal), p. 9.

Bruton, C. J., B. E. Viani, W. L. Bourcier, K. J. Jackson, and R. D. Aines (1989), *Geochemical Modeling: An Integrated Approach to Nuclear Waste Disposal Issues*, LLNL, UCRL-102019; submitted to *Proc. 1st Int. High-Level Radioactive Waste Mgmt. Conf.*, Las Vegas, Apr. 1990.

Glassley, W. E., K. J. Jackson, and W. L. Bourcier (1989), "Computer Modeling of the Aqueous Geochemistry of the Archean Hydrosphere and the Formation of Banded Iron Formations," *Proc. Workshop on Geochemical Modeling*, LLNL, CONF-8609134, pp. 146–153.

Jackson, K. J. (1988), *Verification and Validation Studies of the Addition of Pitzer's Equations to the EQ3/6 Brine Model*, LLNL, UCRL-53841.

Jackson, K. J., and W. L. Bourcier, Eds. (1989), *Proc. Workshop on Geochemical Modeling*, LLNL, CONF-8609134.

Jackson, K. J., T. J. Wolery, W. L. Bourcier, J. M. Delany, R. M. Moore, M. L. Clinnick, and S. R. Lundeen (1988), *MCRT User's Guide and Documentation*, LLNL, UCID-21406-Rev. 1.

Knauss, K. G., T. J. Wolery, and K. J. Jackson (1989), "A New Approach to Measuring pH in Concentrated Electrolytes," LLNL, UCRL-101403-Abs.; presented at the Geol. Soc. Am. 101st Annual Mtg., St. Louis, Nov. 1989.

Rose, N. M. and K. J. Jackson (1989), "Computation of Coupled Aqueous Organic-Inorganic Equilibria in Hydrothermal Systems," LLNL, UCRL-101527-Abs.; presented at the Geol. Soc. of Am., 101st Annual Mtg., St. Louis, Nov. 1989.

Wolery, T. J., and K. J. Jackson (1988), "Activity Coefficients in Aqueous Salt Solutions. II. Hydration Theory Equations," LLNL, UCRL-98727; submitted to *Proc. ACS 196th Natl. Mtg.*, Los Angeles.

Wolery, T. J., K. J. Jackson, W. L. Bourcier, C. J. Bruton, B. E. Viani, K. G. Knauss, and J. M. Delany (1988), "The EQ3/6 Software Package for Geochemical Modeling," LLNL, UCRL-98729; submitted to *Proc. ACS 196th Natl. Mtg.*, Los Angeles.

Jarpe, Steve

Hutchings, L. W., S. P. Jarpe, P. W. Kasameyer, and T. F. Hauk (1988), "Microseismicity of the Salton Sea Geothermal Field," *EOS* **69**, 1312.

Jarpe, S. P., and F. Dowla (1989), *Performance of High-Frequency Three-Component Stations for Azimuth Estimation from Regional Seismic Phases*, LLNL, UCRL-101181; submitted to *Bull. Seismol. Soc. Am.*

Jarpe, S. P., L. W. Hutchings, T. F. Hauk, and A. F. Shakal (1989), "Selected Strong- and Weak-Motion Data from the Loma Prieta Earthquake Sequence," *Seismol. Res. Lett.* **60**, 167–176.

Jarpe, S. P., P. W. Kasameyer, and C. Johnston (1989), "Passive Seismic Monitoring of a Flow Test in the Salton Sea Geothermal Field," *The Geysers—Three Decades of Achievement: A Window on the Future* (Geothermal Resources Council, Davis, CA), *TRANSACTIONS* **13**, 265–269.

Jarpe, S. P., P. W. Kasameyer, L. W. Hutchings, and T. F. Hauk (1988), *Seismic Monitoring of the June 1988 Salton Sea Scientific Drilling Program Flow/Injection Test*, LLNL, UCID-21521.

Jarpe, S. P. (1989), *LLNL Nevada Test Site Regional Seismic Network*, LLNL, LLL-TB-100.

Kasameyer, P. W., and S. P. Jarpe (1988), "A Detailed Seismic Study in the Salton Sea Geothermal Field," *EOS* **69**, 402.
 Nakanishi, K., and S. P. Jarpe (1988), *Summary of Corrections Needed for Accurate Backazimuth Estimation Using RSTN Data*, LLNL, UCRL-98591; submitted to *Bull. Seismol. Soc. Am.*

Kamegai, Mino (Mike)

Glenn, L. A., B. Moran, M. Kamegai, and W. P. Crowley (1989), *CORTEX with Aspherical Sources*, LLNL, UCRL-102022, Rev. 1; presented at the 7th Biennial Nucl. Explosives Design Physics Conference, Livermore, Oct. 1989.
 Kamegai, M., and B. Moran (1989), *Energy Transport through Pipes of Many Shapes and Geometries*, LLNL, UCRL-101012-Abs.; presented at the Conf. on Technology Research and Development for Arms Control Verification, Los Alamos, NM, Aug. 1989.
 Kamegai, M., and B. Moran (1989), *Energy Transport through Long Pipes*, LLNL, UCRL-101673; presented at the Conf. on Technology Research and Development for Arms Control Verification, Los Alamos, NM, Aug. 1989.
 Kamegai, M., O. Walton, and A. Taylor (1989), *Micro-Scale Simulation of Dynamic Compaction of Oxide and Metal Powder Mixture*, LLNL, UCRL-100792; submitted to *Proc. 1989 APS Topical Conf. on Shock Compression of Condensed Matter*, Albuquerque, NM, Aug. 1989.
 Nellis, W. J., J. B. Holt, M. Kamegai, M. B. Maple and C. L. Seaman (1988), *Shock Compaction of Superconductors*, LLNL, UCRL-99694.
 Nellis, W. J., C. L. Seaman, M. B. Maple, E. A. Early, J. B. Holt, M. Kamegai, and G. S. Smith (1989), *Shock Compaction of $YBa_2Cu_3O_{7-x}$ and $HgBa_2Cu_3O_{7-x}$ Powders in a Metal Matrix*, LLNL, UCRL-100472; presented at 1989 TMS Symp. on High-Temperature Superconducting Oxides, Las Vegas.

Kansa, Ed

Kansa, E. (1989), "The Response of Shocks in Unsaturated Geological Media Under a Wide Range of Permeabilities Wave Propagation in Granular Media," *Wave Propagation in Granular Media*, D. Karamanlidis and R. B. Stout, Eds., AMD (Am. Soc. Mech. Eng., New York), Vol. 101, pp. 95-102.
 Kansa, E. (1989), "Verification of the NIKES3D Structural Analysis Code by Comparison against the Analytic Solution for a Spherical Cavity Under a Far-Field Uniaxial Stress," *Wave Propagation in Granular Media*, D. Karamanlidis and R. B. Stout, Eds., AMD (Am. Soc. Mech. Eng., New York), Vol. 101.
 Kansa, E. J. (1988), "Shock Computations with Adaptive Mesh Refinement and Moving Grids," *Computers Math. Applic.* **15**, 623-634.
 Kansa, E. J. (1988), "Numerical Simulation of Three Phase Porous Flow under Shock Conditions," *Math. Comput. Modelling* **11**, 180-185.
 Kansa, E. J. (1988), "A Comparative Study of Finite Difference and Multiquadric Schemes for the Euler Equations," *Solutions* **51**, 180-183.
 Kansa, E. J. (1988), *Multiquadrics—A Scattered Data Approximation Scheme with Applications to Computational Fluid Dynamics I. Surface Approximations and Partial Derivative Estimates*, LLNL, UCRL-98166; accepted by *Computers Math. Applic.*
 Kansa, E. J. (1988), *Multiquadrics—A Scattered Data Approximation Scheme with Applications to Computational Fluid Dynamics II. Solutions to Parabolic Hyperbolic, and Elliptic Partial Differential Equations*, LLNL, UCRL-98167; accepted by *Computers Math. Applic.*
 Kansa, E. J. (1989), *The Response of Shocks in Unsaturated Geological Media under a Wide Range of Permeabilities*, LLNL, UCRL-100545.
 Kansa, E. J. (1989), *A Strictly Conservative Spatial Approximation Scheme for the Governing Engineering and Physics Equations Over Irregular Regions and Inhomogeneously Scattered Nodes*, LLNL, UCRL-101634; accepted by *Advances in Partial Differential Equations*, Special Ed. of *Computers Math. Applic.*

Kasameyer, Paul

- Ammon, C. J., J. J. Zucca, and P. W. Kasameyer (1989), "An S to P Converted Phase Recorded Near Long Valley/Mono Craters Region, California," *J. Geophys. Res.* **94**, 17,721-17,727.
- Hutchings, L. W., S. P. Jarpe, P. W. Kasameyer, and T. F. Hauk (1988), "Microseismicity of the Salton Sea Geothermal Field," *EOS* **69**, 1312.
- Jarpe, S. P., P. W. Kasameyer, L. W. Hutchings, and T. F. Hauk (1988), *Seismic Monitoring of the June 1988, Salton Sea Scientific Drilling Program Flow/Injection Test*, LLNL, UCID-21521.
- Hutchings, L. W., S. P. Jarpe, P. W. Kasameyer, and T. F. Hauk (1988), "Microseismicity of the Salton Sea Geothermal Field," *EOS* **69**, 1312.
- Jarpe, S. P., P. W. Kasameyer, and C. Johnston (1989), "Passive Seismic Monitoring of a Flow Test in the Salton Sea Geothermal Field," *The Geysers—Three Decades of Achievement: A Window on the Future* (Geothermal Resources Council, Davis, CA), *TRANSACTIONS*, Vol. 13, pp. 265-269.
- Kasameyer, P. W. (1988), "Geophysical Studies of Geothermal Fields," *1988 Geothermal Program Review* (Department of Energy, Washington, DC).
- Kasameyer, P. W., and S. P. Jarpe (1988), "A Detailed Seismic Study in the Salton Sea Geothermal Field," *EOS* **69**, 402.
- Kasameyer, P. W., and J. R. Hearst (1988), "Borehole Gravity Measurements in the Salton Sea Scientific Drilling Project Well State 2-14," *J. Geophys. Res.* **93**(B11), 13,037-13,045.
- Kasameyer, P., J. Thomas, O. Fackler, M. Mugge, J. Kammeraad, M. Millett, B. Harris, and D. Felske (1989), "A Test of Newton's Law of Gravity Using the BREN Tower, Nevada," *Proc. 9th Marionid Workshop: Tests of Fundamental Laws in Physics*, O. Fackler and J. Tran Thanh Van, Eds. (Editions Frontieres, Cedex, France), pp. 529-542.
- Newmark, R. L., and P. W. Kasameyer (1988), "Thermal Sources for Salton Sea Geothermal Field: Results of Thermal Modeling," *EOS* **69**, 480.
- Newmark, R. L., P. W. Kasameyer, and L. W. Younker (1988), *Preliminary Report on Shallow Research Drilling in the Salton Sea Region*, LLNL UCID-21484.
- Newmark, R. L., P. W. Kasameyer, and L. W. Younker (1988), "Shallow Drilling in the Salton Sea Region: The Thermal Anomaly," *J. Geophys. Res.* **93**, 13,005-13,023.
- Thomas, J., P. Kasameyer, O. Fackler, D. Felske, R. Harris, J. Kammeraad, M. Millett, and M. Mugge (1989), "Testing the Inverse-Square Law of Gravity on a 465-m Tower," *Phys. Rev. Lett.* **63**, 1902.
- Thomas, J., P. Vogel, and P. Kasameyer (1988), "Gravity Anomalies at the Nevada Test Site," *Proc. 8th Marionid Workshop*, O. Fackler and J. Tran Thanh Van, Eds. (Editions Frontieres, Cedex, France), p. 585.
- Younker, L. W., J. C. Eichelberger, P. W. Kasameyer, R. L. Newmark, and T. A. Vogel (1988), "Results from Shallow Research Drilling at Inyo Domes, Long Valley, California and Salton Sea Geothermal Field, Salton Trough, California in Deep Drilling" in *Crystalline Bedrock*, A. Boden and K. Eriksson, Eds. (Springer-Verlag, New York) Vol. 2, 172-188.

Knapp, Richard

- Knapp, R. B. (1988), *Reactive Solute Transport: A Review of Current Concepts, Methods and Computer Models*, LLNL, UCID-21516.
- Knapp, R. B. (1989), "Spatial and Temporal Scales of Local Equilibrium in Dynamic Fluid-Rock Systems," *Geochim. Cosmochim. Acta* **53**, 1955.
- Knapp, R. B. (1989), "A Lagrangian Reactive Transport Simulator with Successive Paths and Stationary-States: Concepts, Implementation and Verification," *Mat. Res. Soc. Symp. Proc. Scientific Basis for Nucl. Waste Mgmt. XIII* (Mater. Res. Soc., Pittsburgh), Vol. 176, pp. 695-702.
- Tompson, A. F. B., and R. B. Knapp (1989), "Reactive Geochemical Transport Problems in Nuclear Waste Analyses," *Proc. 1989 Joint Int. Waste Mgmt. Conf.*, S. C. Slate et al., Eds. (ASME, New York), Vol. 2, pp. 573-579.

Tompson, A. F. B., R. B. Knapp, and D. E. Dougherty (1989), *Simulation of Reactive Transport in Natural Porous Media Using Particle Methods*, LLNL, UCRL-100769-Abs.; presented at SIAM Conf. on Mathematical and Computational Issues in Geophysical Fluid and Solid Mechanics, Houston, Sept. 1989.

Yow, Jr., J. R., A. M. Wijesinghe, K. K. Thorpe, and R. B. Knapp (1989), *Repository Technology Program Activities: FY 1988*, LLNL, UCID-21600.

Knauss, Kevin

Bourcier, W. L., K. G. Knauss, and K. J. Jackson (1988), "Aluminum Hydrolysis Constants to 250°C Determined from Boehmite Solubility Measurements," *Experimental Investigations of Hydrothermal Processes: Applications to Ore Deposit Genesis* (Mineral Exploration Institute, Montreal), p. 9.

Bourcier, W. L., K. G. Knauss, C. I. Merzbacher, S. N. Nguyen, and H. C. Weed (1989), "Hydrothermal Dissolution Measurements and Mechanisms for Borosilicate Glasses," *Third Int. Symp. on Hydrothermal Reactions*, I. L. Khodakovskiy, Ed. (Vernadsky Inst. of Geochem. and Anal. Chem., USSR, Academy of Sciences).

Bourcier, W. L., K. G. Knauss, and C. I. Merzbacher (1989), "A Kinetic Model for the Dissolution of Borosilicate Glass," *Water-Rock Interaction WRI-6*, D. L. Miles, Ed. (A. A. Balkema, Brookfield, VT), pp. 107-110.

Bourcier, W. L., D. W. Peifer, K. G. Knauss, K. D. McKeegan, and D. K. Smith (1989), "A Kinetic Model for Borosilicate Glass Dissolution Based on the Dissolution Affinity of a Surface Alteration Layer," *Mat. Res. Soc. Symp. Proc. Scientific Basis for Nucl. Waste Mgmt. XIII* (Mater. Res. Soc., Pittsburgh), Vol. 176, pp. 209-216.

Knauss, K. G., W. L. Bourcier, K. P. McKeegan, C. I. Merzbacher, S. N. Nguyen, F. J. Ryerson, D. K. Smith, and H. C. Weed (1989), "Dissolution Kinetics of a Simple Analogue Nuclear Waste Glass as a Function of pH, Time, and Temperature," *Mat. Res. Soc. Symp. Proc. Scientific Basis for Nucl. Waste Mgmt. XIII* (Mater. Res. Soc., Pittsburgh), Vol. 176, pp. 371-381.

Knauss, K. G., and T. J. Wolery (1988), "The Dissolution Kinetics of Quartz as a Function of pH and Time at 70°C," *Geochim. Cosmochim. Acta* **52**, 43-53.

Knauss, K. G., and T. J. Wolery (1989), "Muscovite Dissolution Kinetics as a Function of pH and Time at 70°C," *Geochim. Cosmochim. Acta* **53**, 1493-1501.

Knauss, K. G., and T. J. Wolery (1989), "Reply to Comment by J. S. Gaffney, N. A. Marley and D. R. Janecky on 'The Dissolution Kinetics of Quartz as a Function of pH and Time at 70°C,'" *Geochim. Cosmochim. Acta* **53**, 1471.

Knauss, K. G., T. J. Wolery, and K. J. Jackson (1989), "A New Approach to Measuring pH in Concentrated Electrolytes," LLNL, UCRL-101403-Abs.; presented at the Geol. Soc. Am. 101st Annual Mtg., St. Louis, Nov. 1989.

Merzbacher, C. I., R. L. Ward, K. G. Knauss, W. L. Bourcier, S. N. Nguyen, and H. C. Weed (1989), "The Effect of Boron on Aluminosilicate Glass Structure and Leaching Behavior: An MAS NMR and DRIFTS Study," LLNL, UCRL-101791-Abs.; presented at the 1989 AGU Fall Mtg., San Francisco.

Wolery, T. J., K. J. Jackson, W. L. Bourcier, C. J. Bruton, B. E. Viani, K. G. Knauss, and J. M. Delany (1988), "The EQ3/6 Software Package for Geochemical Modeling," LLNL, UCRL-98729; submitted to *Proc. ACS 196th Natl. Mtg.*, Los Angeles.

Ladd, Tony

Ladd, A. J. C. (1988), *Hydrodynamic Interactions and the Viscosity of Suspensions of Freely Moving Spheres*, LLNL, UCRL-98907; submitted to *J. Chem. Phys.*

Ladd, A. J. C., and B. J. Alder (1989), *Decay of Angular Correlations in Hard-Sphere Fluids*, LLNL, UCRL-100767; submitted to *J. Stat. Phys.*

Ladd, A. J. C., and D. Frenkel (1989), *Dynamics of Colloidal Dispersions via Lattice-Gas Models of an Incompressible Fluid*, LLNL, UCRL-100997; Workshop on Cellular Automata and Modeling of Complex Physical Systems, Les Houches, France, Feb. 1989.

Ladd, A. J. C., and E. R. Smith (1989), *The Viscosity of a Suspension of Spherical Particles*, LLNL, UCRL-101404; submitted to *J. Chem. Phys.*

- Ladd, A. J. C., and O. R. Walton (1989), "Granular Flow: Numerical Simulation of Dry Granular Flows and Calculation of Hydrodynamic Interactions in Suspensions," *Proc. Joint DOE/NSF Workshop on Fluid-Solids Transport*, Pleasanton, CA, U.S. DOE/PETC, pp. 1-11.
- Walton, O. R., and A. J. C. Ladd (1988), "Granular Solids Flow and Hydrodynamics Forces on Spheres in Suspension," *Proc. Solids Transport Contractor's Review Mtg.*, Pittsburgh, U.S. DOE/PETC, pp. 1-14.
- Larson, Don
- Larson, D. B. (1988), *Material Properties Study of the MJ-2 Grout*, LLNL, UCID-21474.
- Thorpe, R. K., D. B. Larson, R. B. Stout, R. P. Swift, and H. D. Glenn (1988), *A Conceptual Plan for Experiments to Improve Ground Shock Predictions for the EPW Program*, LLNL, UCID-21611.
- Lee, Ken
- Lee, K., and T. Ueng (1989), "Permeability Tests," *Prototype Engineered Barrier System Field Tests (PEBSFT)—Progress Report Through Nov. 1, 1988 (Draft)*, LLNL, UCID-21640.
- Ramirez, A., J. Beatty, T. Buscheck, R. Carlson, W. Daily, R. LaTorre, K. Lee, W. Lin, N. Mao, J. Nitao, D. Towse, T. Ueng, D. Watwood, and D. Wilder (1989), "Prototype Engineered Barrier System Field Tests—Progress Report," *Proc. Nucl. Waste Isolation in an Unsaturated Zone, Focus '89* (Am. Nucl. Soc., LaGrange Park, IL), pp. 30-37.
- Lin, Wiman
- Daily, W. D., and W. Lin (1988), *Laboratory Determined Hydrological Properties of Topopah Spring Tuff under a Thermal Gradient*, LLNL, UCRL-99527-Abs.; presented at the 1988 AGU Fall Mtg., San Francisco.
- Daily, W. D., and W. Lin (1989), *Laboratory Determined Suction Potential of Topopah Spring Tuff*, LLNL, UCRL-102127; submitted to *Water Resources Res.*
- Lin, W., and W. D. Daily (1988), *Fracture Healing of Topopah Spring Tuff Samples*, LLNL, UCRL-99526-Abs.; presented at the 1988 AGU Fall Mtg., San Francisco.
- Lin, W., and W. D. Daily (1988), *Hydrological Properties of Topopah Spring Tuff under a Thermal Gradient—Laboratory Results*, LLNL, UCRL-96926; accepted by *Int. J. Rock Mech.*
- Lin, W., and W. D. Daily (1988), "Laboratory Determined Transport Properties of Core from the Salton Sea Scientific Drilling Project," *J. Geophys. Res.* **93**(B11), 13,047-13,056.
- Lin, W., and W. D. Daily (1989), "Laboratory Study of Fracture Healing in Topopah Spring Tuff—Implications for Near-Field Hydrology," *Nucl. Waste Isolation in the Unsaturated Zone, Focus '89* (Am. Nucl. Soc., LaGrange Park, IL), pp. 443-449.
- Ramirez, A., J. Beatty, T. Buscheck, R. Carlson, W. Daily, R. LaTorre, K. Lee, W. Lin, N. Mao, J. Nitao, D. Towse, T. Ueng, D. Watwood, and D. Wilder (1989), "Prototype Engineered Barrier System Field Tests—Progress Report," *Proc. Nucl. Waste Isolation in an Unsaturated Zone, Focus '89* (Am. Nucl. Soc., LaGrange Park, IL), pp. 30-37.
- Mallon, Dick
- Camp, D. W., and R. G. Mallon (1989), "LLNL Mild Coal Gasification Project Review," *8th Annual Gasification and Gas Stream Cleanup System Contractors Review*, V. P. Kothari and J. R. Longanbach, Eds., U.S. DOE Morgantown Energy Technology Center, Morgantown, WV, DOE/METC, pp. 600-604.
- Camp, D. W., and R. G. Mallon (1989), "Mild Coal Gasification—Development of a Screw Pyrolyzer," *9th Annual Gasification and Gas Stream Cleanup System Contractors Review*, R. A. Johnson and T. P. Dorchak, Eds., U.S. DOE Morgantown Energy Technology Center, Morgantown, WV, DOE/METC, pp. 315-324.
- Walton, O. R., R. L. Braun, R. G. Mallon, and D. M. Cervelli (1988), "Particle-Dynamics Calculations of Gravity Flow of Inelastic, Frictional Spheres," *Micromechanics of Granular Materials*, M. Satake and J. T. Jenkins, Eds. (Elsevier, Amsterdam), pp. 153-161.

Ramirez, A., J. Beatty, T. Buscheck, R. Carlson, W. Daily, R. LaTorre, K. Lee, W. Lin, N. Mao, J. Nitao, D. Towse, T. Ueng, D. Watwood, and D. Wilder (1989), "Prototype Engineered Barrier System Field Tests—Progress Report," *Proc. Nucl. Waste Isolation in an Unsaturated Zone, Focus '89* (Am. Nucl. Soc., LaGrange Park, IL), pp. 30–37.

Martin, Sue

Reichlin, R., K. E. Brister, A. K. McMahan, S. Martin, Y. K. Vohra, and A. L. Ruoff (1989), "Evidence for the Insulator-Metal Transition in Xenon from Optical, X-ray, and Band Structure Studies to 170 GPa," *Phys. Rev. Lett.* **62**, 669.

Reichlin, R., M. Ross, A. K. McMahan, S. Martin, K. E. Brister, Y. K. Vohra, and A. L. Ruoff (1989), "Evidence for the Insulator-Metal Transition in Xenon at 150 GPa from Optical, X-ray, and Band Structure Studies," LLNL, UCRL-98905-Abs.; presented at Am. Phys. Soc. Mtg, Mar. 1989.

Reichlin, R., C. E. Violet, S. R. Bohlen, S. Martin, and Z. Mei (1989), *FE Spin State in Fayalite at High Pressure*, LLNL, UCRL-100621-Abs.; Int. Conf. on Application of the Mössbauer Effect, Budapest, Hungary, Sept. 1989.

Williams, Q., E. Kittle, R. Reichlin, S. Martin, and R. Jeanloz (1989), *Electronic Properties of Fe_2SiO_4 -Fayalite at Ultra-High Pressures: Amorphization and Gap Closure*, LLNL, UCRL-98904; submitted to *J. Geophys. Res.*

McKague, Larry

McKague, H. L., J. R. Hearst, and B. McKinnis (1989), *U20bc Site Characteristics Report*, LLNL, Containment Rpt. CP 89-48.

McKague, H. L., and R. L. Newmark (1989), *U20bd Site Characteristics Report*, LLNL, Containment Rpt. CP 89-167.

McKague, H. L., P. P. Orkild, and S. R. Mattson (1989), *The Geology of the Nevada Test Site and Surrounding Area: A Field Trip Guidebook T18e for the 28th Int. Geologic Congress* (Am. Geophys. Un., Washington, DC).

Newmark, R. L., and H. L. McKague (1988), *U20aw Site Characteristics Report*, LLNL, Containment Rpt. CP 88-201.

Moran, Bill

Glenn, L. A., B. Moran, M. Kamegai, and W. P. Crowley (1989), *CORRTEX with Aspherical Sources*, LLNL, UCRL-102022, Rev. 1; presented at the 7th Biennial Nucl. Explosives Design Physics Conference, Livermore, Oct. 1989.

Holian, B. L., G. Cicciotti, W. G. Hoover, B. Moran, and H. A. Posch (1989), "Nonlinear-Response Theory for Time-Independent Fields: Consequences of the Fractal Nonequilibrium Distribution Function," *Phys. Rev. A* **39**, 5414–5421.

Hoover, W. G., and B. Moran (1989), "Phase-Space Singularities in Atomistic Planar Diffusive Flow," *Phys. Rev. A* **40**, 5319–5326.

Hoover, W. G., C. G. Hoover, I. F. Stowers, A. J. DeGroot, and B. Moran (1989), "Simulation of Mechanical Deformation via Nonequilibrium Molecular Dynamics," LLNL, UCRL-101903.

Hoover, W. G., C. G. Hoover, W. J. Evans, B. Moran, J. A. Levatin, and E. A. Craig (1989), "Irreversible Processes from Reversible Mechanics," LLNL, UCRL-101907; presented at the Conf. on Microscopic Simulation of Complex Flows, Brussels, Belgium, Aug. 1989.

Kamegai, M., and B. Moran (1989), *Energy Transport through Long Pipes*, LLNL, UCRL-101673; presented at the Conf. on Technology Research and Development for Arms Control Verification, Los Alamos, NM, Aug. 1989.

Kamegai, M., and B. Moran (1989), *Energy Transport through Pipes of Many Shapes and Geometries*, LLNL, UCRL-101012-Abs.; presented at Conf. on Technology Research and Development for Arms Control Verification, Los Alamos, NM, Aug. 1989.

Moran, B., and J. C. Goldwire, Jr. (1989), "Effect of Source Modelling on the Inferred Yield from an Underground Nuclear Explosion," LLNL, UCRL-100914; submitted to *Proc. Am. Phys. Soc. Topical Conf.*, Albuquerque, NM, Aug. 1989.

Moss, Willie

- Moss, W. C. (1988), "Method to Estimate the Yield of an Underground Nuclear Explosion," *J. Appl. Phys.* **63**, 4771-4773.
- Moss, W., K. Goettel, and I. Silvera (1989), "Optical Evidence for the Metallization of Xenon at 132(5) GPa," *Phys. Rev. Lett.* **62**, 665-668.
- Moss, V. C., and J. T. Rambo (1988), "Calculations of Underground Nuclear Explosions Using DYNA2D," *Nuclear Test—Experimental Test Annual Report, FY 1988*, LLNL, UCRL-53929-88, pp. 273-274.
- Rambo, J. T., and W. C. Moss (1989), "Residual Stress Simulations of the NASH and BOURBON Events, Buried in Carbonate Rock Below the Tuff-Paleozoic Interface," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL CONF-8909163, p. 22.

Nakanishi, Keith

- Nakanishi, K., and S. P. Jarpe (1988), *Summary of Corrections Needed for Accurate Backazimuth Estimation Using RSTN Data*, LLNL, UCRL-98591; submitted to *Bull. Seismol. Soc. Am.*

Newmark, Robin

- Hanson, J. M., and R. C. Newmark (1988), "Three-Dimensional Geophysical Modeling at Salton Sea Geothermal Field," *EOS* **69**(44).
- McKague, H. L., and R. L. Newmark (1989), *U20bd Site Characteristics Report*, LLNL, Containment Rpt. CP 89-167.
- Morin, R. H., R. C. Newmark, C. A. Barton, and R. N. Anderson (1988), *State of Lithospheric Stress in Borehole Stability at DSDP Site 504B, Eastern Equatorial Pacific*, LLNL UCRL-JC-103613; accepted in *J. Geophys. Res.*
- Morin, R. H., R. C. Newmark, C. A. Barton, and R. N. Anderson (1989), "Thermal Stresses and Borehole Stabilities at DSDP Site 504B, Eastern Equatorial Pacific," *EOS* **70**, 470.
- Newmark, R. L., and P. W. Kasameyer (1988), "Thermal Sources for Salton Sea Geothermal Field: Results of Thermal Modeling," *EOS* **69**, 480.
- Newmark, R. L., P. W. Kasameyer, and L. W. Younker (1988), "Shallow Drilling in the Salton Sea Region: The Thermal Anomaly," *J. Geophys. Res.* **93**, 13,005-13,023.
- Newmark, R. L., P. W. Kasameyer, and L. W. Younker (1988), *Preliminary Report on Shallow Research Drilling in the Salton Sea Region*, LLNL UCID-21484.
- Newmark, R. L., and G. A. Pawloski (1989), *U2gh Site Characteristics Report*, LLNL, Containment Rpt. CP 89-133.
- Newmark, R. L., and C. Schmidt (1988), *U2gg Site Characteristics Report*, LLNL, Containment Rpt. CP 88-89.
- Newmark, R. L., and J. L. Wagoner (1988), *U19ax Site Characteristics Report*, LLNL, Containment Rpt. CP 88-73.
- Newmark, R. L., and J. L. Wagoner (1988), *U14at Site Characteristics Report*, LLNL, Containment Rpt. CP 88-203.
- Newmark, R. L., and H. L. McKague (1988), *U20aw Site Characteristics Report*, LLNL, Containment Rpt. CP 88-201.
- Younker, L. W., J. C. Eichelberger, P. W. Kasameyer, R. L. Newmark, and T. A. Vogel (1988), "Results from Shallow Research Drilling at Inyo Domes, Long Valley, California and Salton Sea Geothermal Field, Salton Trough, California in Deep Drilling" in *Crystalline Bedrock*, A. Boden and K. Eriksson, Eds. (Springer-Verlag, New York) Vol. 2, 172-188.

Nguyen, Son

- Bourcier, W. L., K. G. Knauss, C. I. Merzbacher, S. N. Nguyen, and H. C. Weed (1989), "Hydrothermal Dissolution Measurements and Mechanisms for Borosilicate Glasses," *Third Int. Symp. on Hydrothermal Reactions*, I. L. Khodakovskiy, Ed. (Vernadsky Inst. of Geochem. and Anal. Chem., USSR Academy of Sciences).
- Knauss, K. G., W. L. Bourcier, K. D. McKeegan, C. I. Merzbacher, S. N. Nguyen, F. J. Ryerson, D. K. Smith, and H. C. Weed (1989), "Dissolution Kinetics of a Simple Analogue Nuclear Waste Glass as a Function of pH, Time, and Temperature," *Mat. Res. Soc. Symp. Proc.: Scientific Basis for Nucl. Waste Mgmt. XIII* (Mater. Res. Soc., Pittsburgh), Vol. 176, pp. 371-381.

- Merzbacher, C. I., R. L. Ward, K. G. Knauss, W. L. Bourcier, S. N. Nguyen, and H. C. Weed (1989), "The Effect of Boron on Aluminosilicate Glass Structure and Leaching Behavior: An MAS NMR and DRIFTS Study," LLNL, UCRL-101791-Ads.; presented at the 1989 AGU Fall Mtg., San Francisco.
- Nguyen, S. N., J. E. Andrews, Jr., H. C. Weed, and R. J. Silva (1989), *Free Energies of Formation at 30°C of Four Uranyl Silicates: Sodalite, Uramphane, Sodium Boltwoodite, and Sodium Wecksite*, LLNL, UCRL-99694; submitted to 2nd Int. Conf. on Chemistry and Migration Behavior of Actinides and Fission Products in the Geosphere, Monterey, CA, Nov. 1989.
- O'Hare, P. A. G., B. M. Lewis, and S. N. Nguyen (1988), "Thermochemistry of Uranium Compounds XVII. Standard Molar Enthalpy of Formation at 298.15 K of Dehydrated Schoepite $UO_3 \cdot 0.9 H_2O$. Thermodynamics of (Schoepite + Dehydrated Schoepite + Water)," *J. Chem. Thermodynamics* **20**, 1287-1296.
- Nitao, John
- Buscheck, T. A., and J. J. Nitao (1988), *Estimates of the Hydrologic Impact of Drilling Water on Core Samples Taken from Partially Saturated Densely Welded Tuff*, LLNL, UCID-21294.
- Buscheck, T. A., and J. J. Nitao (1988), *Estimates of the Width of the Wetting Zone along a Fracture Subjected to an Episodic Infiltration Event in Variably Saturated, Densely Welded Tuff*, LLNL, UCID-21579.
- Buscheck, T. A., and J. J. Nitao (1989), "Preliminary Scoping Calculations of Hydrothermal Flow," *Prototype Engineered Barrier System Field Test, Progress Report, Nov. 1, 1988*, LLNL, UCID-21640.
- Buscheck, T. A., and J. J. Nitao (1988), *Preliminary Scoping Calculations of Hydrothermal Flow in Variably Saturated, Fractured, Welded Tuff during the Engineered Barrier Design Test at the Yucca Mountain Exploratory Shaft Test Site*, LLNL, UCID-21571.
- Nitao, J. J. (1988), *Numerical Modeling of the Thermal and Hydrological Environment around a Nuclear Waste Package Using the Equivalent Continuum Approximation: Horizontal Emplacement*, LLNL, UCID-21444.
- Nitao, J. J. (1988), *Simulations of the Near-Field Transport of Radionuclides by Liquid Diffusion at Yucca Mountain—Comparisons With and Without Emplacement Backfill*, LLNL, UCID-21466.
- Nitao, J. J., and T. A. Buscheck (1989), *Movement of a Liquid Front in an Unsaturated, Fractured Porous Medium I: Physical Theory*, LLNL, UCRL-101005.
- Nitao, J. J., and T. A. Buscheck (1989), *Movement of a Liquid Front in an Unsaturated, Fractured Porous Medium II: Mathematical Analysis*, LLNL, UCRL-101006.
- Nitao, J. J., and T. A. Buscheck (1989), "On the Infiltration of a Liquid Front in an Unsaturated, Fractured Porous Medium," *Proc. Nucl. Waste Isolation in the Unsaturated Zone, Focus '89* (Am. Nucl. Soc., La Grange Park, IL), pp. 381-397.
- Ramirez, A., J. Beatty, T. Buscheck, R. Carlson, W. Daily, R. LaTorre, K. Lee, W. Lin, N. Mao, J. Nitao, D. Towse, T. Ceng, D. Watwood, and D. Wilder (1989), "Prototype Engineered Barrier System Field Tests—Progress Report," *Proc. Nucl. Waste Isolation in an Unsaturated Zone, Focus '89* (Am. Nucl. Soc., LaGrange Park, IL), pp. 30-37.
- Owens, Tom
- Owens, T. J. (1988), *Crustal Structure of the Adirondack Determined from Broadband Teleseismic Waveform Modeling*, LLNL, UCRL-91465; submitted to *Bull. Seismol. Soc. Am.*
- Owens, T. J., D. E. McNamara, G. Zandt, K. F. Priestley, and G. E. Randall (1989), "Array Analysis of Teleseismic Receiver Functions Using PASSCAL Basin and Range Passive-Source Experiment Data," *Seismol. Res. Lett.* **60**, 11.
- Randall, G. E., K. F. Priestley, G. Zandt, and T. J. Owens (1988), "The PASSCAL Basin and Range Passive-Source Experiment: Regional Waveform Observations," *EOS* **69**, 1323.
- Zandt, G., T. J. Owens, C. J. Ammon, G. E. Randall, and K. F. Priestley (1988), "The PASSCAL Basin and Range Passive-Source Experiment: Teleseismic Waveform Observations," *EOS* **69**, 1323.

Patton, Howard

- Hough, S. E., J. G. Anderson, and H. J. Patton (1989), "Attenuation in Western Nevada: Preliminary Results from Earthquakes and Explosion," *Geophys. Res. Lett.* **16**, 207.
- Patton, H. J. (1989), *Characterization of Spall from Observed Strong Ground Motions on Pahute Mesa*, LLNL, UCRL-101703; accepted by *Bull. Seismol. Soc. Am.*
- Patton, H. J. (1988), "Application of Nuttli's Method to Estimate Yield of NTS Explosions Recorded on LLNL's Digital Seismic System," *Bull. Seismol. Soc. Am.* **78**, 1759.
- Patton, H. J. (1988), "Earthquake Mechanisms in Northern California and Northwestern Great Basin and Their Implications to the Regional Stress Field," *EOS* **69**, 400.
- Patton, H. J. (1988), "Moment-Tensor Inversion of Pahute Mesa Explosions Using Regional Seismic Data," *EOS* **69**, 1332.
- Patton, H. J. (1988), "Source Model of the Harzer Explosion from Regional Observations of Fundamental Mode and Higher Mode Surface Waves," *Bull. Seismol. Soc. Am.* **78**, 1133-1157.
- Patton, H. J. (1989), "Seismic Moment Estimation of Underground Nuclear Explosions: A Review of Surface-Wave Results and Implications for the Source," *Proc. DOE/LLNL Symp. on Explosion Source Phenomenology*, LLNL, CONF-890398, pp. 128-134.
- Patton, H. J., and D. I. Doser (1988), "Inversion of Regional Pnl and Surface-Wave Data for Source Parameters of a Borah Peak Aftershock," *Geophys. Res. Lett.* **15**, 459.
- Patton, H. J., and S. R. Taylor, Eds. (1989), *Proc. DOE/LLNL Symp. on Explosion Source Phenomenology*, LLNL, CONF-890398.
- Patton, H. J., and W. R. Walter (1989), "Tectonic Release and Explosion Moment Determined from Near Regional Seismic Data for the Soviet Joint Verification Experiment," *EOS* **70**, 1198.
- Patton, H. J., and T. S. Yelini (1989), "Seismotectonics of the Portland, Oregon Region," *EOS* **70**, 1330.
- Patton, H. J., and G. Zandt (1989), "Regional Stress Field Characterization from Seismic Moment Tensors of Earthquakes in North California and Nevada," *Seismol. Res. Lett.* **60**, 19.

Pawloski, Gayle

- Burkhard, N. R., and G. A. Pawloski (1988), *U2cu Site Characteristics Report*, LLNL, Containment Rpt. CP 88-148.
- Newmark, R. L., and G. A. Pawloski (1989), *U2gh Site Characteristics Report*, LLNL, Containment Rpt. CP 89-133.
- Pawloski, G. A. (1989), "Faster, More Efficient Data Processing from Converted Codes," *Nuclear Test—Experimental Science Annual Report, FY 1988*, LLNL, UCRL-53929-88, pp. 275-277.
- Pawloski, G. A. (1989), "A Statistical Analysis of Grain Density Measurements from Cuttings and Percussion Gun Samples," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 372-384.
- Pawloski, G. A., and J. L. Wagoner (1989), "Characterization of Carbonate Content in Yucca Flat Alluvium," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions, Abstracts*, LLNL, CONF-8909163, p. 27.

Peifer, Dennis

- Bourcier, W. L., D. W. Peifer, K. G. Knauss, K. D. McKeegan, and D. K. Smith (1989), "A Kinetic Model for Borosilicate Glass Dissolution Based on the Dissolution Affinity of a Surface Alteration Layer," *Mat. Res. Soc. Symp. Proc.: Scientific Basis for Nucl. Waste Mgmt. XIII* (Mater. Res. Soc., Pittsburgh), Vol. 176, pp. 209-216.

Rambo, John

- Glenn, J. D., and J. T. Rambo (1989), "Sensitivity of the Residual Stress Field to Variation of the Strengths for a Weak Layer Overlaying a Strong Working Point Layer," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 22-50.

- Moss, W. C., and J. T. Rambo (1988), "Calculations of Underground Nuclear Explosions Using DYNA2D," *Nuclear Test—Experimental Test Annual Report, FY 1988*, LLNL, UCRL-53929-88, pp. 273–274.
- Rambo, J. T. (1989), "Geological Models in 1-D and 2-D Nuclear Event Calculations that Influence Surface Motion and Spall," *Proc. DOE/LLNL Symp. on Explosion Source Phenomenology*, LLNL, CONF-890398, pp. 231–232.
- Rambo, J. T., and W. C. Moss (1989), "Residual Stress Simulations of the NASH and BOURBON Events, Buried in Carbonate Rock Below the Tuff-Paleozoic Interface," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions, Abstracts*, LLNL, CONF-8909163, p. 22.
- Taylor, S. R., J. T. Rambo, and R. P. Swift (1989), *Near-Source Effects on Regional Seismograms: An Analysis of the NTS Explosions PERA/QUESO*, LLNL, UCRL-101704; submitted to *J. Geophys. Res.*
- Wheeler, V. E., and J. T. Rambo (1989), "Ground Motion in Multilayered Media: Calculated and Experimental Results from the Hardin Event," *Proc. 5th Symp. on Containment of Underground Nuclear Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 51–64.
- Ramirez, Abe*
- Daily, W., and A. Ramirez (1989), "Evaluation of Electromagnetic Tomography to Map In Situ Water in Heated Welded Tuff," *Water Resources Res.* **25**, 1083–1096.
- Daily, W., A. Ramirez, T. Ueng, and V. R. LaTorre (1989), "High Frequency Electromagnetic Tomography to Study Near-Field Hydrology," *Nucl. Waste Isolation in the Unsaturated Zone, Focus '89* (Am. Nucl. Soc., La Grange Park, IL), pp. 409–416.
- Ramirez, A. (1989), *Prototype Heater Test of the Environment Around a Simulated Waste Package*, LLNL, UCRL-101693-SUM; presented at Int. High-Level Radioactive Waste Mgmt. Conf., Las Vegas, Apr. 1990.
- Ramirez, A., J. Beatty, T. Buscheck, R. Carlson, W. Daily, R. LaTorre, K. Lee, W. Lin, N. Mao, J. Nitao, D. Towse, T. Ueng, D. Watwood, and D. Wilder (1989), "Prototype Engineered Barrier System Field Tests—Progress Report," *Proc. Nucl. Waste Isolation in an Unsaturated Zone, Focus '89* (Am. Nucl. Soc., LaGrange Park, IL), pp. 30–37.
- Ramirez, A. L., and W. D. Daily (1988), *Geotomography of Grout Penetration in Fractured Granite*, LLNL, UCRL-98719; accepted by *Int. J. Rock Mech.*
- Ramirez, A., and D. Wilder, Eds. (1989), *Prototype Engineered Barrier System Field Tests (PEBSFT)—Progress Report through Nov. 1, 1988*, LLNL, UCID-21640.
- Ramspott, Larry*
- Ramspott, Lawrence D. (1989), "Assessment of Engineered Barrier System and Design of Waste Packages," *Radioactive Waste Management and Nuclear Fuel Cycle* **13**(1–4), 147–154; LLNL, UCRL-98029.
- Ramspott, Lawrence D. (1990), "Role of MRS in Reducing Technical Uncertainties in Geological Disposal," *Transactions of the American Nuclear Society* **62**, 57–58; LLNL, UCRL-JC-104547.
- Randall, George*
- Ammon, C. J., G. E. Randall, and G. Zandt (1989), *On the Non-Uniqueness of Receiver Function Inversions*, LLNL, UCRL-102018; accepted by *J. Geophys. Res.*
- Owens, T. J., D. E. McNamara, G. Zandt, K. F. Priestley, and G. E. Randall (1989), "Array Analysis of Teleseismic Receiver Functions Using PASSCAL Basin and Range Passive-Source Experiment Data," *Seismol. Res. Lett.* **60**, 11.
- Priestley, K. F., G. Zandt, and G. E. Randall (1988), "Crustal Structure in Eastern Kazakh, U.S.S.R. Determined from Teleseismic Receiver Functions," *Geophys. Res. Lett.* **15**, 613–616.
- Randall, G. E. (1989), "Efficient Calculation of Differential Seismograms for Lithospheric Receiver Functions," *Geophys. J.* **99**, 469–481.
- Randall, G. E., K. F. Priestley, G. Zandt, and T. J. Owens (1988), "The PASSCAL Basin and Range Passive-Source Experiment: Regional Waveform Observations," *EOS* **69**, 1323.

- Randall, G. E. and G. Zandt (1988), "Lithospheric Receiver Function Modeling by Inversion of Teleseismic SV Seismograms," *Seismol. Res. Lett.* **59**, 51.
- Randall, G. E., G. Zandt, and C. J. Ammon (1989), "Determination of Poisson's Ratio Variations in the Lithosphere from Teleseismic P- and S-Waveforms," *Seismol. Res. Lett.* **60**.
- Taylor, S. R., and G. E. Randall (1989), "The Effects of Spall on Regional Seismograms," *Geophys. Res. Lett.* **16**, 211-214.
- Zandt, G., T. J. Owens, C. J. Ammon, G. E. Randall, and K. F. Priestley (1988), "The PASSCAL Basin and Range Passive-Source Experiment: Teleseismic Waveform Observations," *EOS* **69**, 1323.
- Zandt, G., and G. E. Randall (1988), "Comparison of Crustal Structure in N. Nevada from Teleseismic P-Waveform Inversion and the 1986 PASSCAL Experiment," *Seismol. Res. Lett.* **59**, 50.
- Rard, Joe*
- Albright, J. G., R. Mathew, D. G. Miller, and J. A. Rard (1989), "Isothermal Diffusion Coefficients for NaCl-MgCl₂-H₂O at 25°C. 1. Solute Concentration Ratio of 3:1," *J. Phys. Chem.* **93**, 2176-2180.
- Mathew, R., J. G. Albright, D. G. Miller, and J. A. Rard (1989), "Isothermal Diffusion Coefficients for NaCl-MgCl₂-H₂O at 25°C. 4. Solute Concentration Ratio of 1:3. LLNL, UCRL-102539; submitted to *J. Phys. Chem.*
- Mathew, R., L. Paduano, J. G. Albright, D. G. Miller, and J. A. Rard (1989), "Isothermal Diffusion Coefficients for NaCl-MgCl₂-H₂O at 25°C. 3. Low MgCl₂ Concentrations with a Wide Range of NaCl Concentrations," *J. Phys. Chem.* **93**, 4370-4374.
- Miller, D. G., A. W. Ting, and J. A. Rard (1988), "Mutual Diffusion Coefficients of Various ZnCl₂(0.5M)-KCl-H₂O Mixtures at 298.15 K by Rayleigh Interferometry," *J. Electrochem. Soc.* **135**, 896-904.
- Paduano, L., R. Mathew, J. G. Albright, D. G. Miller, and J. A. Rard (1989), "Isothermal Diffusion Coefficients for NaCl-MgCl₂-H₂O at 25°C. 2. Low Concentrations of NaCl with a Wide Range of MgCl₂ Concentrations," *J. Phys. Chem.* **93**, 4366-4370.
- Rard, J. A. (1988), "Aqueous Solubilities of Praseodymium, Europium, and Lutetium Sulfates," *J. Solution Chem.* **17**, 499-517.
- Rard, J. A. (1989), *Chemical Thermodynamics of Technetium I and II*, LLNL, UCRL-100554.
- Rard, J. A. (1989), "Isopiestic Determination of the Osmotic and Activity Coefficients of $[(1-y)H_2SO_4 + yNa_2SO_4](aq)$ at 298.15 K. 1. Results for $y = 0.5$ (NaHSO₄) and $y = 0.5595$, 0.70189, and 0.84920," *J. Chem. Thermodynamics* **21**, 539-560.
- Rard, J. A. (1989), *Isopiestic Determination of the Osmotic and Activity Coefficients of Aqueous Li₂(SO₄)₃ at 25°C*, LLNL, UCRL-102035; submitted to *J. Solution Chem.*
- Rard, J. A., and D. G. Miller (1989), "Isopiestic Determination of the Osmotic and Activity Coefficients of ZnCl₂(aq) at 298.15 K," *J. Chem. Thermodynamics* **21**, 463-482.
- Rard, J. A., and D. G. Miller (1988), "Ternary Mutual Diffusion Coefficients of NaCl-SrCl₂-H₂O at 25°C. 2. Total Concentrations of 2.0 and 3.0 mol-dm⁻³," *J. Phys. Chem.* **92**, 6133-6140.
- Rard, J. A., D. G. Miller, and C. M. Lee (1989), "Mutual Diffusion Coefficients of NiCl₂-H₂O at 298.15 K from Rayleigh Interferometry," *J. Chem. Soc., Faraday Trans. 1*, 3343-3352.
- Rard, J. A., and D. G. Miller (1989), *Ternary Mutual Diffusion Coefficients of ZnCl₂-KCl-H₂O at 25°C by Rayleigh Interferometry*, LLNL, UCRL-101170; accepted by *J. Solution Chem.*

Reichlin, Robin

- Reichlin, R., K. E. Brister, A. K. McMahan, S. Martin, Y. K. Vohra, and A. L. Ruoff (1989), "Evidence for the Insulator-Metal Transition in Xenon from Optical, X-ray, and Band Structure Studies to 170 GPa," *Phys. Rev. Lett.* **62**, 669.
- Reichlin, R., M. Ross, A. K. McMahan, S. Martin, K. E. Brister, Y. K. Vohra, and A. L. Ruoff (1989), "Evidence for the Insulator-Metal Transition in Xenon at 130 GPa from Optical, X-ray, and Band Structure Studies," LLNL, UCRL-98905-Abs.; presented at Am. Phys. Soc. Mtg., Mar. 1989.
- Reichlin, R., C. E. Violet, S. R. Bohlen, S. Martin, and Z. Mei (1989), *FE Spin State in Fayalite at High Pressure*, LLNL, UCRL-100621-Abs.; Int. Conf. on Application of the Mössbauer Effect, Budapest, Hungary, Sept. 1989.

Williams, Q., E. Knittle, R. Reichlin, S. Martin, and R. Jeanloz (1989), *Electronic Properties of Fe₂SiO₄-Fayalite at Ultra-High Pressures: Amorphization and Gap Closure*, LLNL, UCRL-98904; accepted by *J. Geophys. Res.*

Ryerson, Rick

Hanson, D. R., M. Young, and F. J. Ryerson (1989), *Growth and Characterization of Synthetic Olivine Single Crystals*, LLNL, UCRL-101712-Abs.

Knauss, K. G., W. L. Bourcier, K. D. McKeegan, C. I. Merzbacher, S. N. Nguyen, F. J. Ryerson, D. K. Smith, and H. C. Weed (1989), "Dissolution Kinetics of a Simple Analogue Nuclear Waste Glass as a Function of pH, Time, and Temperature," *Mat. Res. Soc. Symp. Proc.: Scientific Basis for Nucl. Waste Mgmt. XIII* (Mater. Res. Soc., Pittsburgh), Vol. 176, pp. 371-381.

Stein, D. J., F. J. Spera, H. C. Weed, and R. J. Ryerson (1989), "Rheology of Silicate and GeO₂ Melts and Vapor-Melt Emulsions," *EOS* 70, 1416.

Ryerson, F. J., W. B. Durham, D. J. Cherniak, and W. A. Lanford (1989), "Oxygen Diffusion in Olivine: The Effect of Oxygen Fugacity and Implications for Creep," *J. Geophys. Res.* 94, 4105-4118.

Ryerson, F. J., H. C. Weed, and A. J. Piwinski (1988), "Rheology of Subliquidus Magmas 1. Picritic Compositions," *J. Geophys. Res.* 93(B4), 3421-3436.

Shaffer, Ron

Blair, S. C., R. K. Thorpe, F. E. Heuzé, and R. J. Shaffer (1989), "Laboratory Observations of the Effect of Geologic Discontinuities on Hydrofracture Propagation," *Proc. 30th U.S. Symp. on Rock Mechanics*, Morgantown, WV (A. A. Balkema, Brookfield, VT), pp. 443-450.

Heuzé, F. E., R. J. Shaffer, S. C. Blair, and R. K. Thorpe (1989), "Understanding the Effect of Natural Fractures on the Hydrofracture Stimulation of Natural Gas Reservoirs," *Proc. SPE Joint Rocky Mountain Regional/Low Permeability Reservoir Symp.*, Denver, SPE-18956 (SPE, Richardson, TX), pp. 261-268.

Heuzé, F. E., R. J. Shaffer, A. R. Ingraffea, and R. H. Nilson (1989), *Propagation of Fluid-Driven Fractures in Jointed Rock. Part 1: Development and Validation of Methods of Analysis*, LLNL, UCRL-101870.

Shaffer, R. J., F. E. Heuzé, S. C. Blair, and R. K. Thorpe (1989), *Models of Stimulation of Sand Lenses*, LLNL, UCRL-100229; presented at the SPE Joint Rocky Mountain Regional/Low Permeability Reservoir Symp., Denver, Mar. 1989.

Shaw, Henry

Santanam, L., H. F. Shaw, and B. A. Chin (1989), "Modeling of Zircalloy Cladding Degradation Under Repository Conditions," *Proc. Nucl. Waste Isolation in an Unsaturated Zone, Focus '89* (Am. Nucl. Soc., LaGrange Park, IL), pp. 41-45.

Stout, R. B., H. F. Shaw, and R. E. Einziger (1989), "Statistical Model for Grain Boundary and Grain Volume Oxidation Kinetics in UO₂ Spent Fuel," *Mat. Res. Soc. Symp. Proc.: Scientific Basis for Nucl. Waste Mgmt. XIII* (Mater. Res. Soc., Pittsburgh), Vol. 176, pp. 475-488.

Sinz, Kurt

Sinz, K. (1989), *Shock Attenuation in Perfect Absorbers*, LLNL, UCRL-101151.

Smith, Al

Smith, A. T. (1988), *Assessment of Sadovskii's Presentation on Yield Estimation*, LLNL, UCID-21392.

Smith, A. T. (1988), *Estimating High-Frequency Crustal Attenuation in Eastern Kazakhstan, USSR, Using Reversed Spectral Ratios of Pg and Pn*, LLNL, UCRL-99549; submitted to *Geophys. Res. Lett.*

Smith, A. T. (1989), "High-Frequency P-Wave Attenuation near the East Kazakh Test Site Using a New Method with Spectral Ratios," *Earthquake Notes* 59(45).

Smith, A. T. (1989), "High Frequency Seismic Observations and Models of Chemical Explosions: Implications for the Discrimination of Ripple-Fired Mining Blasts," *Bull. Seismol. Soc. Am.* 79, 1089-1110.

Smith, David

Bourcier, W. L., D. W. Peifer, K. G. Knauss, K. D. McKeegan, and D. K. Smith (1989), "A Kinetic Model for Borosilicate Glass Dissolution Based on the Dissolution Affinity of a Surface Alteration Layer," *Mat. Res. Soc. Symp. Proc.: Scientific Basis for Nucl. Waste Mgmt. XIII* (Mater. Res. Soc., Pittsburgh), Vol. 176, pp. 209-216.

Knauss, K. G., W. L. Bourcier, K. D. McKeegan, C. I. Merzbacher, S. N. Nguyen, F. J. Ryerson, D. K. Smith, and H. C. Weed (1989), "Dissolution Kinetics of a Simple Analogue Nuclear Waste Glass as a Function of pH, Time, and Temperature," *Mat. Res. Soc. Symp. Proc.: Scientific Basis for Nucl. Waste Mgmt. XIII* (Mater. Res. Soc., Pittsburgh), Vol. 176, pp. 371-381.

McKeegan, K. D., D. Phinney, V. M. Oversby, M. Buchholtz-ten Brink, and D. K. Smith (1988), "Uranium Transport in Topopah Spring Tuff: An Ion-Microscope Investigation," *Mat. Res. Soc. Symp. Proc.: Scientific Basis for Nucl. Waste Mgmt. XII* (Mater. Res. Soc., Pittsburgh), Vol. 127, pp. 813-821.

Stout, Ray

Stout, R. B. (1989), *A Deformation and Thermodynamic Model for Hydride Precipitation Kinetics in Spent Fuel Cladding*, LLNL, UCRL-100860.

Stout, R. B. (1988), *Microcrack Kinetics Behind a Cylindrical Shock Front*, LLNL, UCRL-97870.

Stout, R. B. (1988), *Triple-Material Stress-Strain-Resistivity Gage*, U.S. Patent No. 4,744,252.

Stout, R. B. (1989), *Statistical Model for Particle-Void Deformation Kinetics in Granular Materials During Shock Wave Propagation*, LLNL, UCRL-101623.

Stout, R. B., D. B. Larson, and L. Thigpen (1988), *Analysis of Inclusion Stress Response in Materials Surrounding a Torpedo Gage Package*, LLNL, UCID-21553.

Stout, R. B., H. F. Shaw, and R. E. Einziger (1989), "Statistical Model for Grain Boundary and Grain Volume Oxidation Kinetics in CO₂ Spent Fuel," *Mat. Res. Soc. Symp. Proc.: Scientific Basis for Nucl. Waste Mgmt. XIII* (Mater. Res. Soc., Pittsburgh), Vol. 176, pp. 475-488.

Thorpe, R. K., D. B. Larson, R. B. Stout, R. P. Swift, and H. D. Glenn (1988), *A Conceptual Plan for Experiments to Improve Ground Shock Predictions for the EPW Program*, LLNL, UCID-21611.

Sweeney, Jerry

Braun, R. L., A. K. Burnham, and J. J. Sweeney (1988), *Petroleum Geochemistry Project Annual Report, Oct. 1987-Sept. 1988*, LLNL, UCID-21303-88-4.

Burnham, A. K., R. L. Braun, and J. J. Sweeney (1988), *Kinetic Modeling of Petroleum Generation and Destruction*, LLNL, UCRL-98442-Abs.; presented at Am. Assoc. of Petrol. Eng. Res. Conf., Leesburg, VA, Apr. 1988.

Burnham, A. K., and J. J. Sweeney (1989), "A Chemical Kinetic Model of Vitrinite Maturation and Reflectance," *Geochim. Cosmochim. Acta* 53, 2649-2657.

Burnham, A. K., and J. J. Sweeney (1989), *Modeling the Maturation and Migration of Petroleum*, LLNL, CA, UCRL-102602; submitted to the AAPG Handbook of Petroleum Geology.

Sweeney, J. (1989), "Application of Maturation Indicators and Oil Reaction Kinetics to Put Constraints on Thermal History Models for the Uinta Basin, Utah, USA," *Advances in Organic Geochemistry 1987, Organic Geochem.* 13(1-3), L. Mattavelli and L. Novelli, Eds. (Pergamon Press, Oxford), pp. 199-215.

Sweeney, J. J. (1989), *BASINMAT:FORTRAN Program Calculates Oil and Gas Generation Using a Distribution of Discrete Activation Energies*, LLNL, UCRL-102515; accepted by *Geophy.*

- Sweeney, J. J. (1989), *An Investigation of the Usefulness of Extremely Low-Frequency Electromagnetic Measurements for Treaty Verification*, LLNL, UCRL-53899.
- Sweeney, J. J., and A. K. Burnham (1989), *Evaluation of a Simple Model of Vitrinite Reflectance Based on Chemical Kinetics*, LLNL, UCRL-101379, Rev. 1; accepted by AAPG Bulletin.
- Sweeney, J., and A. Burnham (1989), *A Maturation Model of Vitrinite Reflectance Based on Chemical Kinetics: Applications to a Wide Range of Geologic Conditions*, LLNL, UCRL-102020-Abs.; presented at the AAPG Convention, San Francisco.
- Sweeney, J., P. Harben, J. Hjelme, and E. Hjortenberg (1989), "Broadband Seismic Noise Measurements in Northeast Greenland," *EOS* 70, 1224.
- Sweeney, J., S. Talukdar, A. Burnham, and C. Vallejos (1989), *Pyrolysis Kinetics Applied to Prediction of Oil Generation in the Maracaibo Basin, Venezuela*, LLNL, UCRL-99932; presented at 14th Int. Mtg. on Org. Geochem., Paris, Sept. 1989.
- Swift, Bob
- Attia, A. V., and R. P. Swift (1989), "Residual Stresses Calculated Using an Effective Stress Model," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 14-21.
- Swift, R. P. (1989), "Shock Attenuation in Saturated Rock Using an Effective Stress Model," submitted to *Shock Compression of Condensed Matter-1989*, S. C. Schmidt et al., Eds. (Elsevier, Amsterdam), pp. 641-644.
- Swift, R. P., and A. V. Attia (1989), "Application of an Effective Stress Model to Underground Nuclear Explosions," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 3-13.
- Swift, R. P., and A. V. Attia (1989), "Numerical Simulation of Shock Attenuation in Saturated Rock," submitted to SIAM on Mathematical and Computational Issues in Geophysical Fluid and Solid Mechanics, Houston, Sept. 1989.
- Taylor, S. R., J. T. Rambo, and R. P. Swift (1989), *Near-Source Effects on Regional Seismograms: An Analysis of the NTS Explosions PERA/QUESO*, LLNL, UCRL-101704; submitted to *J. Geophys. Res.*
- Thorpe, R. K., D. B. Larson, R. B. Stout, R. P. Swift, and H. D. Glenn (1988), *A Conceptual Plan for Experiments to Improve Ground Shock Predictions for the EPW Program*, LLNL, UCID-21611.
- Taylor, Steve
- Bonner, S. R., B. J. Wanamaker, and S. R. Taylor (1989), "Amplitude Dependent Attenuation and Implications for the Seismic Source," *Proc. DOE/LLNL Symp. Explosion Source Phenomenology*, LLNL, CONF-890398, pp. 37-43.
- Costain, J. K., R. D. Hatcher, C. Coruh, T. L. Pratt, S. R. Taylor, J. J. Litehiser, and I. Zietz (1989), "Geophysical Characteristics of the Appalachian Crust," *The Decade of North Geology: The Appalachian-Ouachita Region in the United States*, R. D. Hatcher et al., Eds. (The Geological Society of America, Boulder, CO), Vol. F-2, pp. 385-416.
- Dowla, F., S. R. Taylor, and R. W. Anderson (1989), *Seismic Discrimination with Artificial Neural Networks—Preliminary Results with Regional Spectral Data*, LLNL, UCRL-102310; submitted to *Bull. Seismol. Soc. Am.*
- Patton, H. J., and S. R. Taylor, Eds. (1989), *Proc. DOE/LLNL Symp. on Explosion Source Phenomenology*, LLNL, CONF-890398.
- Taylor, S. R. (1989), "Geophysical Framework of the Appalachians and Adjacent Grenville Province," *Geophysical Framework of the Continental United States: Geological Society of America, Memoir 172*, L. C. Pakiser and W. D. Mooney, Eds. (The Geological Society of America, Boulder, CO), pp. 317-348.
- Taylor, S. R. (1989), "Regional Seismic Observations from NTS Explosions," *Proc. DOE/LLNL Symp. on Explosion Source Phenomenology*, LLNL, CONF-890398, pp. 115-127.
- Taylor, S. R., M. D. Denny, F. S. Vergino, and R. E. Glaser (1989), "Regional Discrimination between NTS Explosions and Western U.S. Earthquakes," *Bull. Seismol. Soc. Am.* 79, 1142-1176.
- Taylor, S. R., J. T. Rambo, and R. P. Swift (1989), *Near-Source Effects on Regional Seismograms: An Analysis of the NTS Explosions PERA/QUESO*, LLNL, UCRL-101704; submitted to *J. Geophys. Res.*
- Taylor, S. R., and G. E. Randall (1989), "The Effects of Spall on Regional Seismograms," *Geophys. Res. Lett.* 16, 211-214.

Taylor, S. R., N. W. Sherman, and M. D. Denny (1988), "Spectral Discrimination between NTS Explosions and Western U.S. Earthquakes at Regional Distances," *Bull. Seismol. Soc. Am.* 78, 1563.

Vergino, E. S., M. D. Denny, and S. R. Taylor (1988), "A New Look at the Explosion Source Function," *Seismol. Res. Lett.* 59, 44.

Zandt, G., S. R. Taylor, and C. J. Ammon (1988), *Medicine Lake Volcano Teleseismic Experiment Field Procedures and Data Analysis*, LLNL, UCID-21470.

Thorpe, Rich

Blair, S. C., R. K. Thorpe, and F. E. Heuzé (1988), *Physical Models of Hydrofracturing across Material Interfaces*, LLNL, UCID-21505.

Blair, S. C., R. K. Thorpe, and F. E. Heuzé (1989), *Propagation of Fluid-Driven Fractures in Jointed Rock, Part 2: Physical Tests on Blocks with Interface or Lens*, LLNL, UCRL-101871; accepted by *Int. J. Rock Mech. and Min. Sci.*

Blair, S. C., R. K. Thorpe, F. E. Heuzé, and R. J. Shaffer (1989), "Laboratory Observations of the Effect of Geologic Discontinuities on Hydrofracture Propagation," *Proc. 30th U.S. Symp. on Rock Mechanics*, Morgantown, WV (A. A. Balkema, Brookfield, VT), pp. 443-450.

Heuzé, F. E., R. J. Shaffer, S. C. Blair, and R. K. Thorpe (1989), "Understanding the Effect of Natural Fractures on the Hydrofracture Stimulation of Natural Gas Reservoirs," *Proc. SPE Joint Rocky Mountain Regional/Low Permeability Reservoir Symp.*, Denver, SPE-18956 (SPE, Richardson, TX), pp. 261-268.

Shaffer, R. J., F. E. Heuzé, S. C. Blair, and R. K. Thorpe (1989), *Models of Stimulation of Sand Lenses*, LLNL, UCRL-100229; presented at the SPE Joint Rocky Mountain Regional/Low Permeability Reservoir Symp., Denver, Mar. 1989.

Thorpe, R. K., S. C. Blair, and A. E. Brown (1988), "Physical Modeling of Hydraulic Fracture Behavior Near Geologic Interfaces," *Proc. 29th U.S. Symp. on Rock Mechanics*, Minneapolis (A. A. Balkema, Brookfield, VT), pp. 745-746.

Thorpe, R. K., D. B. Larson, R. B. Stout, R. P. Swift, and H. D. Glenn (1988), *A Conceptual Plan for Experiments to Improve Ground Shock Predictions for the EPW Program*, LLNL, UCID-21611.

Yow, Jr., J. R., A. M. Wijesinghe, R. K. Thorpe, and R. B. Knapp (1989), *Repository Technology Program Activities: FY 1988*, LLNL, UCID-21600.

Tompson, Andy

Ababou, R., D. McLaughlin, L. W. Gelhar, and A. F. B. Tompson (1989), "Numerical Simulation of Saturated Flow in Randomly Heterogeneous Porous Media," *Transport in Porous Media* 4, 549-565.

Tompson, A. F. B. (1988), "On a New Functional Form for the Dispersive Flux in Porous Media," *Water Resources Res.* 24, 1939-1947.

Tompson, A. F. B., R. Ababou, and L. W. Gelhar (1989), "Implementation of the Three Dimensional Turning Bands Random Field Generator," *Water Resources Res.* 25, 2227-2243.

Tompson, A. F. B., and D. E. Dougherty (1988), "On the Use of Particle Tracking Methods for Solute Transport in Porous Media," *Computational Methods in Water Resources, Vol. 2: Numerical Methods for Transport and Hydrological Processes*, M. Celia et al., Eds. (Elsevier, Amsterdam), pp. 227-232.

Tompson, A. F. B., D. E. Dougherty, and A. Bagtzoglou (1989), *Particle Methods for Reactive Transport: 2. Vector and Parallel Implementation and Examples*, LLNL, UCRL-101707-Abs.; presented at the 1989 AGU Fall Mtg., San Francisco.

Tompson, A. F. B., and L. W. Gelhar (1989), *Numerical Simulation of Solute Transport in Randomly Heterogeneous Porous Media*, LLNL, UCRL-101679.

Tompson, A. F. B., and R. B. Knapp (1989), "Reactive Geochemical Transport Problems in Nuclear Waste Analyses," *Proc. 1989 Joint Int. Waste Mgmt. Conf.*, S. C. Slate et al., Eds. (ASME, New York), Vol. 2, pp. 573-579.

Tompson, A. F. B., R. B. Knapp, and D. E. Dougherty (1989), *Simulation of Reactive Transport in Natural Porous Media Using Particle Methods*, LLNL, UCRL-100769-Abs.; presented at SIAM Conf. on Mathematical and Computational Issues in Geophysical Fluid and Solid Mechanics, Houston, Sept. 1989.

Towse, Don

Ramirez, A., J. Beatty, T. Buscheck, R. Carlson, W. Daily, R. LaTorre, K. Lee, W. Lin, N. Mao, J. Nitao, D. Towse, T. Ueng, D. Watwood, and D. Wilder (1989), "Prototype Engineered Barrier System Field Tests—Progress Report," *Proc. Nucl. Waste Isolation in an Unsaturated Zone, Focus '89* (Am. Nucl. Soc., LaGrange Park, IL), pp. 30–37.

Ueng, Tzou-Shin (Joe)

Daily, W., A. Ramirez, T. Ueng, and V. R. LaTorre (1989), "High Frequency Electromagnetic Tomography to Study Near-Field Hydrology," *Nucl. Waste Isolation in the Unsaturated Zone, Focus '89* (Am. Nucl. Soc., LaGrange Park, IL) pp. 409–416.

Lee, K., and T. Ueng (1989), "Permeability Tests," *Prototype Engineered Barrier System Field Tests (PEBSFT)—Progress Report through Nov. 1, 1988 (Draft)*, LLNL, UCID-21640.

Ramirez, A., J. Beatty, T. Buscheck, R. Carlson, W. Daily, R. LaTorre, K. Lee, W. Lin, N. Mao, J. Nitao, D. Towse, T. Ueng, D. Watwood, and D. Wilder (1989), "Prototype Engineered Barrier System Field Tests—Progress Report," *Proc. Nucl. Waste Isolation in an Unsaturated Zone, Focus '89* (Am. Nucl. Soc., LaGrange Park, IL), pp. 30–37.

Ueng, T-S., Y-M. Tzou, and C-J. Lee (1988), "The Effect of End Restraint on Volume Change and Particle Breakage of Sands in Triaxial Tests," *Advanced Triaxial Testing of Soil and Rock, Am. Soc. for Testing Materials, STP 977* (ASTM, Philadelphia), pp. 679–691.

Vergino, Eileen

Taylor, S. R., M. D. Denny, E. S. Vergino, and R. E. Glaser (1989), "Regional Discrimination between NTS Explosions and Western U.S. Earthquakes," *Bull. Seismol. Soc. Am.* **79**, 1142–1176.

Vergino, E. S. (1989), *A Report on the Paper "Characteristics of 96 Underground Nuclear Explosions at the Semipalatinsk Test Site" Recently Published in the Soviet Journal Atomnaya Energiya*, LLNL, UCRL-102177; submitted to EOS.

Vergino, E. S. (1989), "Soviet Test Yields," *EOS* **70**, 1511.

Vergino, E. S., M. D. Denny, and S. R. Taylor (1988), "A New Look at the Explosion Source Function," *Seismol. Res. Lett.* **59**, 44.

Vergino, E. S., and R. W. Mensing (1989), *Yield Estimation Using Regional $m_b(P_n)$* , LLNL, UCRL-101600; submitted to *Bull. Seismol. Soc. Am.*

Viani, Brian

Bruton, C. J., B. E. Viani, W. L. Bourcier, K. J. Jackson, and R. D. Aines (1989), *Geochemical Modeling: An Integrated Approach to Nuclear Waste Disposal Issues*, LLNL, UCRL-102019; submitted to *Proc. 1st Int. High-Level Radioactive Waste Mgmt. Conf.*, Las Vegas, Apr. 1990.

Viani, B., C. Bruton, and B. Bourcier (1989), "Comparison of Ideal Mixing Models Used to Describe Smectite Solid Solutions for Geochemical Modeling," LLNL, UCRL-100251-Abs.; submitted to the *9th Int. Clay Conf.*

Wolery, T. J., K. J. Jackson, W. L. Bourcier, C. J. Bruton, B. E. Viani, K. G. Klause, and J. M. Delany (1988), "The EQ3/6 Software Package for Geochemical Modeling," LLNL, UCRL-98729; submitted to *Proc. ACS 196th Natl. Mtg.*, Los Angeles.

Wagoner, Jeff

Burkhard, N. R., and J. L. Wagoner (1989), *U208 Site Characteristics Report*, LLNL, Containment Rpt. CP 89-67.

Hawkins, W. L., and J. L. Wagoner (1988), *Obtaining Geologic Data from Large Diameter Holes at the Nevada Test Site*, LLNL, UCRL-98543-Abs.; presented at the Institute for Shaft Drilling Technology.

Hearst, J. R., and J. L. Wagoner (1988), *U8N Site Characteristics Report*, LLNL, Containment Rpt. CP 88-101.

Newmark, R. L., and J. L. Wagoner (1988), *U19ax Site Characteristics Report*, LLNL, Containment Rpt. CP 88-73.

Newmark, R. L., and J. L. Wagoner (1988), *U4at Site Characteristics Report*, LLNL, Containment Rpt. CP 88-203.

- Pawloski, G. A., and J. L. Wagoner (1989), "Characterization of Carbonate Content in Yucca Flat Alluvium," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions, Abstracts*, LLNL, CONF-8909163, p. 27.
- Wagoner, J. L., and N. R. Burkhard (1988), *U440 Site Characteristics Report*, LLNL, Containment Rpt. CP 88-13.
- Walton, Otis
- Butkovich, T. R., O. R. Walton, and F. E. Heuzé (1988), "Insights in Cratering Phenomenology Provided by Discrete Element Modeling," *Proc. 29th U.S. Symp. on Rock Mechanics*, Minneapolis (A. A. Balkema, Brookfield, VT), pp. 359-368.
- Heuzé, F. E., O. R. Walton, and T. R. Butkovich (1988), "Cratering Phenomenology Revealed Through Discrete-Element Modeling," *Energy and Technology Review*, LLNL, UCRL-52000-88-11, pp. 1-8.
- Kamegai, M., O. Walton, and A. Taylor (1989), *Micro-Scale Simulation of Dynamic Compaction of Oxide and Metal Powder Mixture*, LLNL, UCRL-100792; submitted to *Proc. 1989 APS Topical Conference on Shock Compression of Condensed Matter*, Albuquerque, NM, Aug. 1989.
- Ladd, A. J. C., and O. R. Walton (1989), "Granular Flow: Numerical Simulation of Dry Granular Flows and Calculation of Hydrodynamic Interactions in Suspensions," *Proc. Joint DOE/NSF Workshop on Fluid-Solids Transport*, Pleasanton, CA, May 1989, US-DOE, PETC, pp. 1-11.
- Walton, O. R. (1988), *Computer Simulation of Rapidly Flowing Granular Solids*, LLNL, UCRL-99545; presented at the 2nd Int. Symp. for Science on Form, University of Tsukuba, Japan, Oct. 1988.
- Walton, O. R. (1988), "Effects of Frictional Contact Models in Simulated Shear Flows of Spherical Particles," in *Proc. 19th Annual Mtg. Fine Particle Soc.*, Santa Clara, CA, July 1988.
- Walton, O. R. (1989), *Modeling the Flow of Granular Solids*, LLNL, UCRL-101163; presented at Workshop on Dynamics of Concentrated Systems, Los Alamos, NM, June 1989.
- Walton, O. R. (1989), "Rheology of Flowing Dry Granular Solids via Particle-Dynamic Simulation," in *Proc. Workshop on Two Phase Flows in Fluidized Beds, Sedimentation, and Granular Flows*, D. Joseph and D. Schaeffer, Eds., Minneapolis.
- Walton, O. R. (1988), "Understanding Particulate Flow Behavior," *Energy and Technology Review*, LLNL, UCRL-52000-88-9, pp. 6-22.
- Walton, O. R., R. L. Braun, R. G. Mallon, and D. M. Cervelli (1988), "Particle-Dynamics Calculations of Gravity Flow of Inelastic, Frictional Spheres," *Micromechanics of Granular Materials*, M. Satake and J. T. Jenkins, Eds. (Elsevier, Amsterdam), pp. 153-161.
- Walton, O. R., and T. G. Drake (1988), "Granular Flow in a Two-Dimensional Channel: A Comparison of Measurements and Numerical Simulations," *Engineering Mechanics—7th Conf. Abstracts*, ASCE/EMD Specialty Conference, Blacksburg, VA, p. 4.
- Walton, O. R., and F. E. Heuzé, "Discrete Element Modeling of Explosion in Jointed Rocks," *Proc. DOE/LLNL Symp. on Explosion Source Phenomenology*, LLNL, CONF-8909398, pp. 241-242.
- Walton, O. R., and A. J. C. Ladd (1988), "Granular Solids Flow and Hydrodynamic Forces on Spheres in Suspension," *Proc. Solids Transport Contractor's Review Mtg.*, U.S. DOE/PETC, Sept. 1988, Pittsburgh, pp. 1-14.
- Wanamaker, Barbara
- Bonner, B. P., and B. J. Wanamaker (1989), "Nonlinear Acoustic Effects in Rocks and Soils," *Review of Progress in Quantitative Non-Destructive Evaluation*, Bowdoin College, Brunswick, ME, July 1989; LLNL, UCRL-102045.
- Bonner, B. P., B. J. Wanamaker, and K. B. Coyner (1988), *Amplitude Dependent Attenuation in Granite*, LLNL, UCRL-99711; presented at the 1988 AGU Fall Mtg., San Francisco.
- Bonner, B. P., B. J. Wanamaker, and S. R. Taylor (1989), "Amplitude Dependent Attenuation and Implications for the Seismic Source," *Proc. DOE/LLNL Symp. Explosion Source Phenomenology*, LLNL, CONF-8909398, pp. 37-43.

- Wanamaker, B. J., and B. P. Bonner (1988), "Low Frequency Attenuation and Modulus of Thermally Fractured Granite," *EOS* **69**, 475.
- Wanamaker, B. J., and A. G. Duba (1989), *The Effect of Temperature-Dependent and -Independent Oxygen Fugacity on Olivine Conductivity*, LLNL, UCRL-101713-Abs.; presented at the 1989 AGU Fall Mtg., San Francisco.
- Weed, Homer
- Bourcier, W. L., K. G. Knauss, C. I. Merzbacher, S. N. Nguyen, and H. C. Weed (1989), "Hydrothermal Dissolution Measurements and Mechanisms for Borosilicate Glasses," *Third Int. Symp. on Hydrothermal Reactions*, I. L. Khodakovskiy, Ed. (Vernadsky Inst. of Geochem. and Anal. Chem., USSR, Academy of Sciences).
- Knauss, K. G., W. L. Bourcier, K. D. McKeegan, C. I. Merzbacher, S. N. Nguyen, F. J. Ryerson, D. K. Smith, and H. C. Weed (1989), "Dissolution Kinetics of a Simple Analogue Nuclear Waste Glass as a Function of pH, Time, and Temperature," *Mat. Res. Soc. Symp. Proc.: Scientific Basis for Nucl. Waste Mgmt. XIII* (Mater. Res. Soc., Pittsburgh), Vol. 176, pp. 371-381.
- Merzbacher, C. I., R. L. Ward, K. G. Knauss, W. L. Bourcier, S. N. Nguyen, and H. C. Weed (1989), "The Effect of Boron on Aluminosilicate Glass Structure and Leaching Behavior: An MAS NMR and DRIFTS Study," LLNL, UCRL-101791-Abs.; presented at the 1989 AGU Fall Mtg., San Francisco.
- Nguyen, S. N., J. E. Andrews, Jr., H. C. Weed, and R. J. Silva (1989), *Free Energies of Formation at 30°C of Four Uranyl Silicates: Sodalite, Uramphane, Sodium Boltwoodite, and Sodium Wecksite*, LLNL, UCRL-99694; submitted to 2nd Int. Conf. on Chemistry and Migration Behavior of Actinides and Fission Products in the Geosphere, Monterey, CA, Nov. 1989.
- Stein, D. J., F. J. Spera, H. C. Weed, and R. J. Ryerson (1989), "Rheology of Silicate and GeO_2 Melts and Vapor-Melt Emulsions," *EOS* **70**, 1416.
- Ryerson, F. J., H. C. Weed, and A. J. Piwinski (1988), "Rheology of Subliquidus Magmas 1. Picritic Compositions," *J. Geophys. Res.* **93**(B4), 3421-3436.
- Wheeler, Vern
- Wheeler, V. E., and B. C. Hudson (1989), "Free-Field Particle Velocity and Yield," *Proc. DOE/LLNL Symp. on Explosion Source Phenomenology*, LLNL, CONF-890398, pp. 100-101.
- Wheeler, V. E., and J. T. Rambo (1989), "Ground Motion in Multilayered Media: Calculated and Experimental Results from the Hardin Event," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 2, pp. 51-64.
- Wijesinghe, Ananda
- Wijesinghe, A. M. (1989), *A Constitutive Theory for Stress Wave Propagation across Closed Fluid-Filled Rough Fractures*, LLNL, UCRL-101882.
- Wijesinghe, A. M., and I. Kececiglu (1988), "Vertical Interference Pressure Testing Across a Low Permeability Zone with Unsteady Crossflow," *SPE Form. Eval.* **3**, 751-760.
- Yow, Jr., J. R., A. M. Wijesinghe, R. K. Thorpe, and R. B. Knapp (1989), *Repository Technology Program Activities: FY 1988*, LLNL, UCID-21600.
- Wilder, Dale
- Ramirez, A., J. Beatty, T. Buscheck, R. Carlson, W. Daily, R. LaTorre, K. Lee, W. Lin, N. Mao, J. Nitao, D. Towse, T. Ueng, D. Watwood, and D. Wilder (1989), "Prototype Engineered Barrier System Field Tests—Progress Report," *Proc. Nucl. Waste Isolation in an Unsaturated Zone, Focus '89* (Am. Nucl. Soc., LaGrange Park, IL), pp. 30-37.
- Ramirez, A., and D. Wilder, Eds. (1989), *Prototype Engineered Barrier System Field Tests (PEBSFT)—Progress Report through Nov. 1, 1988*, LLNL, UCID-21640.

Wilder, D. G. (1988), *Performance Implications of Waste Package Emplacement Orientation*, LLNL, UCID-21607.

Wolery, Tom

Jackson, K. J., T. J. Wolery, W. L. Bourcier, J. M. Delany, R. M. Moore, M. L. Clineck, and S. R. Lundeen (1988), *MCRT User's Guide and Documentation*, LLNL, UCID-21406-Rev. 1.

Knauss, K. G., and T. J. Wolery (1988), "The Dissolution Kinetics of Quartz as a Function of pH and Time at 70°C," *Geochim. Cosmochim. Acta* **52**, 43-53.

Knauss, K. G., and T. J. Wolery (1989), "Muscovite Dissolution Kinetics as a Function of pH and Time at 70°C," *Geochim. Cosmochim. Acta* **53**, 1493-1501.

Knauss, K. G., and T. J. Wolery (1989), "Reply to Comment by J. S. Gaffney, N. A. Marley and D. R. Janeky on 'The Dissolution Kinetics of Quartz as a Function of pH and Time at 70°C,'" *Geochim. Cosmochim. Acta* **53**, 1471.

Knauss, K. G., T. J. Wolery, and K. J. Jackson (1989), "A New Approach to Measuring pH in Concentrated Electrolytes," LLNL, UCRL-101403-Abs.; presented at the Geol. Soc. Am. 101st Annual Mtg., St. Louis, Nov. 1989.

Price, J. G., J. R. Kyle, J. D. Prikril, W. N. Agee, Jr., S. C. Boardman, and T. J. Wolery (1989), "Calculating Freezing Point Depressions of Multicomponent Aqueous Solutions, with Applications to Fluid Inclusion Research," presented at the Geol. Soc. Am. 101st Annual Mtg., St. Louis, Nov. 1989.

Wolery, T. J. (1989), "EQ3/6—Status and Future Development," *Proc. Workshop on Geochemical Modeling*, LLNL, CONF-8609134, pp. 10-19.

Wolery, T. J., and K. J. Jackson (1988), "Activity Coefficients in Aqueous Salt Solutions. II. Hydration Theory Equations," LLNL, UCRL-98727; submitted to *Proc. ACS 196th Natl. Mtg.*, Los Angeles.

Wolery, T. J., K. J. Jackson, W. L. Bourcier, C. J. Bruton, B. E. Viani, K. G. Knauss, and J. M. Delany (1988), "The EQ3/6 Software Package for Geochemical Modeling," LLNL, UCRL-98729; submitted to *Proc. Amer. Chem. Soc. 196th National Mtg.*, Los Angeles.

Wolery, T. J., and K. J. Jackson (1988), "Activity Coefficients in Aqueous Salt Solutions. II. Hydration Theory Equations," LLNL, UCRL-98727; submitted to *Proc. ACS 196th Natl. Mtg.*, Los Angeles, Sept. 1988.

Wolery, T. J., and N. H. Sleep (1988), "Interactions of Geochemical Cycles with the Mantle," *Chemical Cycles in the Evolution of the Earth*, C. B. Gregor et al., Eds. (John Wiley & Sons, New York), pp. 77-103.

Woodward, Eric

Woodward, E. C. (1989), "More about Breathing on the Mesa," *Proc. 5th Symp. on Containment of Underground Nucl. Explosions*, LLNL, CONF-8909163, Vol. 1, pp. 281-283.

Yunker, Lee

Eichelberger, J. C., and L. W. Yunker (1988), "Inyo Drilling: A Summary," *EOS* **69**, 1472.

Eichelberger, J. C., L. W. Yunker, T. A. Vogel, C. D. Miller, G. H. Heiken, and K. H. Wohletz, "Structure and Stratigraphy Beneath a Young Phreatic Vent: South Inyo Crater, Long Valley Caldera, California," *J. Geophys. Res.* **93** (B11) 13,208-13,220.

Judd, B. R., L. W. Yunker, W. J. Hannon, R. S. Strait, P. C. Meagher, and A. Sichertman (1988), *Decision Analysis Framework for Evaluating Compliance with the Threshold Test Ban Treaty*, LLNL, UCRL-53830.

Newmark, R. L., P. W. Kasameyer, and L. W. Yunker (1988), *Preliminary Report on Shallow Research Drilling in the Salton Sea Region*, LLNL UCID-21484.

Newmark, R. L., P. W. Kasameyer, and L. W. Yunker (1988), "Shallow Drilling in the Salton Sea Region: The Thermal Anomaly," *J. Geophys. Res.* **93**, 13,005-13,023.

Schuraytz, B. C., T. A. Vogel, and L. W. Yunker (1989), "Evidence for Dynamic Withdrawal from a Layered Magma Body, The Topopah Spring Tuff: Southwestern Nevada," *J. Geophys. Res.* **94**(B5), 5925-5942.

- Vogel, T. A., D. C. Noble, and L. W. Younker (1989), "Evolution of a Chemically Zoned Magma Body: Black Mountain Volcanic Center, Southwestern Nevada," *J. Geophys. Res.* **94**(B5), 6041-6058.
- Vogel, T. A., J. C. Eichelberger, L. W. Younker, B. C. Schraytz, J. P. Horkowitz, H. W. Stockman, and H. R. Westrich (1989), "Petrology and Emplacement Dynamics of the Intrusive and Extrusive Rocks at Obsidian Dome, Inyo Craters, Volcanic Chain, Eastern California," *J. Geophys. Res.* **94**(B12), 17,937-17,956.
- Vogel, T. A., J. G. Mills, B. C. Schraytz, T. B. Flood, T. P. Rose, and L. W. Younker (1988), "Zoned Magma Bodies: Fractional Crystallization of Homogeneous Magmas or Melting of Independent Sources?" *Geol. Soc. of Am. Abstracts with Program* **20**(7), A313.
- Wollenberg, H., J. Eichelberger, W. Elders, F. Goff, and L. Younker (1989), "DOE Thermal Regimes Drilling Program through 1988," *EOS* **70**, 697, 706-707.
- Younker, L. W., J. C. Eichelberger, P. W. Kasameyer, R. L. Newmark, and T. A. Vogel (1988), "Results from Shallow Research Drilling at Inyo Domes, Long Valley, California and Salton Sea Geothermal Field, Salton Trough, California in Deep Drilling" in *Crystalline Bedrock*, A. Boden and K. Eriksson, Eds. (Springer-Verlag, New York) Vol. 2, 172-188.
- Zoback, M. D., W. A. Elders, R. W. Van Schmus, and L. W. Younker (1989), "The Role of Continental Scientific Drilling in Modern Earth Sciences Scientific Rationale and Plan for the 1990s," *Report on the Workshop on Continental Scientific Drilling Convened at Stanford University, Aug. 1988*, Stanford University Press, 151 pp.
- Yote, Jesse*
- Axelrod, M. C., S. P. Verrill, W. C. Patrick, and J. L. Yow, Jr. (1988), "A Monte Carlo Investigation of a Proposed Screen for NX Borehole Jack Data," *ASTM Geotechnical Testing Journal* **11**, 20.
- Ubbes, W. F., J. L. Yow, Jr., and C. B. Brunleve (1988), "Development of Instruments for In-Situ Experiments," accepted by *Int. J. Radioactive Waste Mgmt. and the Nucl. Fuel Cycle*.
- Ubbes, W. F., J. L. Yow, Jr., and W. Hustrulid (1988), "Application of the Results of Excavation Response Experiments at Climax and the Colorado School of Mines to the Development of an Experiment for the Underground Research Laboratory," *Proc. OECD/NEA Excavation Response Workshop*, Winnipeg, Canada.
- Yow, Jr., J. R., A. M. Wijesinghe, R. K. Thorpe, and R. B. Knapp (1989), *Repository Technology Program Activities: FY 1988*, LLNL, UCID-21600.
- Zandt, George*
- Ammon, C. J., G. E. Randall, and G. Zandt (1989), *On the Non-Uniqueness of Receiver Function Inversions*, LLNL, UCRL-102018; accepted by *J. Geophys. Res.*
- Ammon, C. J., and G. Zandt (1989), "The Receiver Structure beneath the Livermore Nevada Test Site Seismic Network Stations," *EOS* **70**, i206.
- Furlong, K. P., W. D. Hugo, and G. Zandt (1989), "Geometry and Evolution of the San Andreas Fault Zone in Northern California," *J. Geophys. Res.* **94**, 3100-3110.
- Owens, T. J., D. E. McNamara, G. Zandt, K. F. Priestley, and G. E. Randall (1989), "Array Analysis of Teleseismic Receiver Functions Using PASSCAL Basin and Range Passive-Source Experiment Data," *Seismol. Res. Lett.* **60**, 11.
- Patton, H. J., and G. Zandt (1989), "Regional Stress Field Characterization from Seismic Moment Tensors of Earthquakes in North California and Nevada," *Seismol. Res. Lett.* **60**, 19.
- Priestley, K. F., G. Zandt, and G. E. Randall (1988), "Crustal Structure in Eastern Kazakh, U.S.S.R. Determined from Teleseismic Receiver Functions," *Geophys. Res. Lett.* **15**, 613-616.
- Randall, G. E., K. F. Priestley, G. Zandt, and T. J. Owens (1988), "The PASSCAL Basin and Range Passive-Source Experiment: Regional Waveform Observations," *EOS* **69**, 1323.
- Randall, G. E., G. Zandt, and C. J. Ammon (1989), "Determination of Poisson's Ratio Variations in the Lithosphere from Teleseismic P- and S-Waveforms," *Seismol. Res. Lett.* **60**, 12.

- Randall, G. E. and G. Zandt (1988), "Lithospheric Receiver Function Modeling by Inversion of Teleseismic SV Seismograms," *Seismol. Res. Lett.* **59**, 51.
- Ruppert, S. D., and G. Zandt (1989), "Analysis of Teleseismic Receiver Functions from the PG&E Central California Coast Seismic Network," *EOS* **70**, 1220.
- Zandt, G., T. J. Owens, C. J. Ammon, G. E. Randall, and K. F. Priestley (1988), "The PASSCAL Basin and Range Passive-Source Experiment: Teleseismic Waveform Observations," *EOS* **69**, 1323.
- Zandt, G., and G. E. Randall (1988), "Comparison of Crustal Structure in N. Nevada from Teleseismic P-Waveform Inversion and the 1986 PASSCAL Experiment," *Seismol. Res. Lett.* **59**, 50.
- Zandt G., S. K. Taylor, and C. J. Ammon (1988), *Medicine Lake Volcano Teleseismic Experiment Field Procedures and Data Analysis*, LLNL, UCID-21470.
- Zucca, J. J., G. Zandt, L. K. Steck, and W. A. Prothero, Jr. (1988), *Array Recording of Anomalous Shear Energy in the Teleseismic P-Wave Coda at Long Valley Caldera, California*, LLNL, UCRL-ID-103499.
- Zucca, Jay
- Ammon, C. J., J. J. Zucca, and P. W. Kasameyer (1989), "An S to P Converted Phase Recorded near Long Valley / Mono Craters Region, California," *J. Geophys. Res.* **94**, 17,721-17,727.
- Doll, W. E., and J. J. Zucca (1988), *Results of a Seismic Scattering Study Using Data from Long Valley and Medicine Lake, California*, LLNL, UCID-21464.
- Evans, J., and J. Zucca (1988), "Active High-Resolution Tomography of Compressional-Wave Velocity and Attenuation Structure at Medicine Lake Volcano Northern California Cascade Range," *J. Geophys. Res.* **93**, 15,016-15,036.
- Peterson, S. J., J. J. Zucca, D. W. Ewert, D. J. Moccia, D. W. Rock, and P. K. Stager (1988), *The Configurable Seismic Monitoring System (CSMS): Local Seismic Network (LSN) Data Acquisition User's Manual, Version 1.0*, LLNL, UCID-21174.
- Zucca, J. J. (1989), *Directional Analysis of Seismic Noise at Medicine Lake Volcano*, LLNL, UCRL-100226; submitted to *Bull. Seismol. Soc. Am.*
- Zucca, J. J., and J. R. Evans (1989), "Seismic Imaging for Velocity and Attenuation Structure in Geothermal Fields," *Geothermal Resources Council TRANSACTIONS* **13**, 295-299.
- Zucca, J. J., G. Zandt, L. K. Steck, and W. A. Prothero, Jr. (1988), *Array Recording of Anomalous Shear Energy in the Teleseismic P-Wave Coda at Long Valley Caldera, California*, LLNL, UCRL-ID-103499.

Earth Sciences Professional Staff 1989/90

Administrative Support

Charlene Ferderber, Supervisor

Joanne Clark
Carol Corallo
Tonya Fletcher
Liz Garrett
Rochelle Hostetter
Kathleen Kirk
Athena Kyler
Loraine Marshbank
Jean Miracle
Denise Nakai
Jackie Oberg
Vickie Petersen
Jennifer Peterson
Karen Roland
Linca Salazar
Stacey Sprague
Susan Uhlhorn
Trena Vanervoort
Pat Walden
Janet Welch
Katie Young

Department Head—1990

Lee Younker

Tectonics, geothermal systems, heat transfer in the crust, regional geology, characteristics of high-level crustal magma systems, decision analysis, and analysis of issues associated with a Comprehensive Test Ban Treaty
Ph.D., Geology
Michigan State University

*(415) 422-6472

Department Head—1989

Larry Schwartz

Nuclear chemistry, radioactivity from nuclear explosions, and radiation effects.
Ph.D., Physical Chemistry
Case Western Reserve University

*(415) 422-5861

*Note: Effective Sept. 2, 1991 Area Code 415 will change to 510.

Applied Geophysics

Paul Kasameyer, Group Leader

Heat flow, geothermal systems, geophysical exploration, and continental scientific drilling
Ph.D., Geophysics
Massachusetts Institute of Technology
(415) 422-6487

Susan Beck

Seismology and tectonics: rupture process and source parameters of large earthquakes, plate boundary tectonics and earthquake cycles, and structure of the Earth's mantle
Ph.D., Seismology
University of Michigan

Norm Burr

Geophysics, seismology, and computer modeling
M.S., Geophysics
Massachusetts Institute of Technology
(415) 422-3918

Dick Carlson

Well logging, acoustic and density logging, and in situ physical property measurement
B.A., Physics
San Francisco State University
(415) 422-6439

Marv Denny

Signal processing and analysis of dynamic systems
M.S., Mechanical Engineering
University of Washington
(415) 422-3919

Fred Followill

Solid earth geophysics, seismology, treaty verification, and site safety
B.S., Mathematics
Texas Technical College, Lubbock
(415) 422-3920

Peter Goldstein

Earthquake sources, array signal processing, earth structure, strong ground motion modeling, and volcanic signals and sources
Ph.D., Physics/Seismology
University of California, Santa Barbara
(415) 423-1231

Phil Harben

Seismology and applied geophysics: verification, real-time, tomographic, and instrument development applications
M.S., Applied Geophysics
University of California, Berkeley
(415) 422-3571

Terri Hawk

Seismology
B.S., Geophysics
University of Arizona
(415) 423-7332

Steve Jarpe

Geophysics and seismicity
M.S., Geophysics
New Mexico Institute of Technology
(415) 423-7676

Nai-hsien Mao

Physical properties of rocks and minerals, rock mechanics, and geostatistics
Ph.D., Geophysics
Harvard University
(415) 422-3518

Robin Newmark

Borehole logging, well logging, data synthesis and interpretation, acoustic logging, and marine geophysics
Ph.D., Geophysics
Columbia University
(415) 423-3644

Howard Patton

Seismology, source mechanisms, discrimination, and source characterization
Ph.D., Geophysics
Massachusetts Institute of Technology
(415) 422-3924

Bob Rohrer

Surface motion studies and seismic yield determination
A.B., Physics
Washington University, St. Louis
(415) 422-3913

John Rundle

Geodesy, seismology, continuum mechanics, critical phenomena, and nucleation
Ph.D., Physics/Geophysics
University of California, Los Angeles
(415) 294-5236

Nick Sharp

Seismology technician, and equipment and facilities coordinator
(415) 422-3908

Al Smith

Seismology, tectonophysics, and design and deployment of field experiments
Ph.D., Geophysics
Massachusetts Institute of Technology
(415) 422-9739

Steve Taylor

Seismology and treaty verification
Ph.D., Geophysics
Massachusetts Institute of Technology
(415) 423-0616

Jay Zucca

Test ban treaty verification, seismic imaging of the upper crust, seismic data acquisition equipment
Ph.D., Geophysics
Stanford University
(415) 422-4895

Containment

Norm Burkhard, Group Leader

Applied geophysics, reflection seismology, and inversion theory
Ph.D., Physics
University of California, Los Angeles
(415) 422-6483

Hal Goldwire

Hydrodynamic yield determination and measurements, instrumentation systems, atomic physics calculations, experimental radio astronomy, and remote measurements
Ph.D., Space Physics and Astronomy
Rice University
(415) 423-0160

Bernadette Harter

Resource Manager for Containment Program, for Basic Energy Science, and for Institutional Research and Development in the Earth Sciences Department
Chabot College
(415) 423-3160

Joe Hearst

Well logging (in situ physical property measurements), density and neutron logging, borehole gravimetry, and

design and execution of high explosive experiments
Ph.D., Physics
Northwestern University
(415) 422-6490

Billy C. Hudson

Nuclear test phenomenology and instrumentation
Ph.D., Physics
Kansas State University
(415) 443-1748

Andy Jorgensen

Radiation-hydrocalculations, diagnostics for weapons, and containment phenomena
B.S., Physics
North East Missouri University
(415) 422-0720

Cliff Olsen

Containment evaluation, containment instrumentation, hydrodynamic yield diagnostics, physical chemistry, environmental impact analysis, and strain seismology
Ph.D., Physical Chemistry
University of California, Davis
(415) 422-7434

Paula Tate

Hydrodynamic yield measurements, and containment diagnostics
M.S., Forest Management
Virginia Polytechnic Institute and State University
(415) 423-4858

Vern Wheeler

Containment evaluation, containment instrumentation, prompt diagnostics, and ground motion instrumentation
B.A., Physics
University of California, Berkeley
(415) 422-7436

Erv Woodward

High-resolution spectroscopy, nuclear radiation measurements, and high-speed photography
Ph.D., Physics
University of California, Berkeley
(415) 422-7435

Experimental Geophysics

Al Duba, Group Leader

Physical property measurements
Ph.D., Geophysics
University of Chicago
(415) 422-7305

Jagan Akella

Static high-pressure equation of state of actinides and lanthanides using diamond cell, mineralogy, petrology, and phase equilibria at high pressures and high temperatures
Ph.D., Geochemistry
Indian Institute of Technology (India)
(415) 423-6217

Mark Beeman

Synthesis and rheology of earth materials at elevated pressures and temperatures
Ph.D., Geophysics
Cornell University
(415) 422-7108

Steve Blair

Physical properties of rocks at elevated pressure and temperature, and microstructure of rocks
M.S., Geophysics
University of Washington
(415) 422-6467

Brian Bonner

Ultrasonics, anelasticity, and material properties at high pressures and high temperatures
M.S., Geophysics
Rensselaer Polytechnic Institute
(415) 422-7080

Carl Boro

High pressure systems, experimental problem solving, and fabricating of unusual materials and parts for experimental systems
B.A., Industrial Studies
California State University, San Jose
(415) 422-7016

Bill Durham

Geophysics, rheology, and micro-structure of rocks and minerals
Ph.D., Geophysics
Massachusetts Institute of Technology
(415) 422-7046

Wunan Lin

Physical and hydrological properties of rocks at high pressures and high temperatures
Ph.D., Geophysics
University of California, Berkeley
(415) 422-7162

Sue Martin

Diamond anvil cell technology, electron microscopy, and photon correlation spectroscopy
California State University, Hayward
(415) 422-7338

Annamarie Meike

Ultramicrostructure and micro-mechanics of earth and ceramic materials, mechano-chemical processes in earth and ceramic materials, electron beam optics and analysis of materials, crystallography, and mineralogy
Ph.D., Geology
University of California, Berkeley
(616) 249-3406

Bill Ralph

High pressure system installations and operations, geophysical laboratory testing, and geophysical field explorations
(415) 422-9201

Robin Reichlin

Absorption, reflection, emission and Raman spectroscopy, equation of state, and electrical resistance at extreme pressure using the diamond anvil cell
M.S., Geochemistry
State University of New York—Stoney Brook
(415) 423-0365

Rick Ryerson

Experimental petrology, diffusion kinetics, and rheology
Ph.D., Geochemistry
Brown University
(415) 422-6170

Barbara Wanamaker

Geophysics
Ph.D., Geophysics
Princeton University
(415) 422-7085

Homer Weed

Rock physics, experimental IR spectroscopy, rheology of high temperature melts, and dissolution kinetics of glasses and minerals
Ph.D., Physical Chemistry
Ohio State University
(415) 422-7184

Flow and Transport

Richard Knapp, Group Leader

Applied heat, mass, and chemical transport processes; and coupled processes
Ph.D., Geosciences
University of Arizona
(415) 423-3328

Tom Buscheck

Multiphase heat and fluid flow and contaminant transport in fractured porous media, hydrogeology, petroleum reservoir engineering, numerical reservoir simulation, hydrothermal analysis of aquifer

thermal energy storage, and glacial geology
Ph.D., Geophysical Engineering
University of California, Berkeley
(415) 423-9390

Charles Carrigan

Analytical, numerical, and laboratory modeling of fluid dynamical processes, including magma transport, tectonic-hydrologic coupling, ground water flow, convection, and thermal convection
Ph.D., Geophysics
University of California, Los Angeles
(415) 422-3341

Dwayne Chesnut

Hydrogeology and contaminant transport in porous media; petroleum reservoir engineering, including enhanced oil recovery and unconventional sources; applications of probability and statistical analysis to nuclear and hazardous waste disposal; computer modeling, especially for implementing analytic or semi-analytic methods and interdisciplinary project direction
Ph.D., Physical Chemistry
Rice University
(415) 423-5053

John Nitao

Analytical and numerical modeling of multiphase heat and fluid flow, vadose zone contaminant transport, fracture-matrix fluid interactions, petroleum reservoir engineering stochastic systems, numerical analysis, and high-level simulators

Ph.D., Applied Mathematics
University of California, Berkeley
(415) 423-0297

Leah Rogers

Ground water and hydrogeology
M.S., Ground Water Geology
University of Illinois
(415) 422-3538

Andrew Tompson

Physics of flow and transport in uniform and heterogeneous porous media using continuum and stochastic analyses, fluid mechanics, numerical modeling, computational physics, stochastic processes, and random field theory

Ph.D., Civil Engineering
Princeton University
(415) 422-6348

Ananda Wijesinghe

Applied solid, fluid, and fracture mechanics; constitutive theories for materials with microstructure; multiphase fluid and heat flow and

deformation of single and naturally fractured materials and fluid-particle mixtures; petroleum reservoir engineering; well test development and analysis; well log analysis; wave propagation and attenuation in porous media

Ph.D., Mechanical Engineering,
Massachusetts Institute of Technology
(415) 4, 3-0605

Fossil Energy

Alan Burnham, Group Leader

Applied chemical kinetics, petroleum geochemistry, pyrolysis, and oil shale chemistry

Ph.D., Physical Chemistry
University of Illinois
(415) 422-7304

Robert Braun

Computer modeling of physico-chemical processes, chemical kinetics, heat

and mass transfer, oil shale retorting, and petroleum geochemistry
Ph.D., Physical Chemistry
University of Washington
(415) 422-6650

Tony Ladd

Statistical mechanics, molecular dynamics, and hydrodynamic interactions, and lattice-gas models
Ph.D., Theoretical Chemistry
University of Cambridge (U.K.)
(415) 422-4596

Otis Walton

Material equation-of-state modeling, computational physics, and granular materials

Ph.D., Applied Science
University of California, Davis
(415) 422-3947

Geochemistry

Kevin Knauss, Group Leader

Geochemistry (thermodynamics and kinetics of aqueous systems), hydrothermal experimental methods, isotope geochemistry, and geochronology

Ph.D., Geological Sciences
University of Southern California
(415) 422-1372

Roger Aines

Geochemistry, solid-state chemistry, optical-IR spectroscopy, and leaching and solid-state analysis

Ph.D., Geochemistry
California Institute of Technology
(415) 423-7184

Bill Bourcier

Hydrothermal solution chemistry, hydrothermal experimental methods, and geochemical modeling

Ph.D., Geochemistry and Mineralogy
Pennsylvania State University
(415) 423-3745

Carol Bruton

Geochemical modeling of fluid-rock interactions, and thermodynamics and kinetics of fluid-rock systems

Ph.D., Geology
University of California, Berkeley
(415) 423-1936

Marilyn Bucholtz-ten Brink

Environmental geochemistry, chemical oceanography, radiochemistry, chemical transport processes in sediment and groundwater, and trace element geochemistry, especially lanthanides and actinides

Ph.D., Earth Science
Lamont and Doherty Geophysical Observatory, Columbia University
(415) 423-7662

Bill Glassley

Metamorphic processes in fluid-rock systems, petrologic evolution of archaean and proterozoic crust,

petrology of deep continental crust, and packing material evaluation

Ph.D., Geochemistry, Tectonics
University of Washington
(415) 422-6499

Andrea Goins

Atomic spectroscopy and analytical chemistry
A.S., Chemical Technology
Merritt College
(415) 422-5772

Ken Jackson

Thermodynamics of aqueous electrolytes, geochemical modeling, chemical ecology or methanotrophic bacteria, and aqueous solution chemistry of organic species

Ph.D., Geology
University of California, Berkeley
(415) 422-6053

Jim Johnson

Thermodynamics of chemical equilibria, critical phenomena, heat and mass transfer processes, software engineering, scientific visualization, and relational data base systems
Ph.D., Geosciences
University of Arizona

(415)423-7352

William McKenzie

Low to high temperature mineral-solution interactions, geochemical cycles and the global environment, reactive transport, stable isotope geochemistry, and thermochemical properties

Ph.D., Geology

University of California, Berkeley

(415)423-9248

Son Nguyen

Geochemistry (thermodynamics and kinetics of uranium minerals), aqueous environmental chemistry, radiochemistry, neutron activation analysis, fossil fuel chemistry, and trace element analysis

Ph.D., Analytical Chemistry

Washington State University

(415)423-7400

Dennis Peifer

Engineering geology and subsurface investigation, geochemistry, rock

and water interactions, and environmental monitoring and remediation

B.A., Geology

California State University, Chico

(415)422-5773

Joe Rard

Thermodynamic and transport properties of aqueous solutions, and critical reviews of chemical and thermodynamic properties of inorganic compounds and aqueous species

Ph.D., Physical Chemistry

Iowa State University

(415)422-6872

Nick Rose

Hydrothermal metasomatism in basaltic systems, aqueous organic geochemistry, and tertiary geology of East Greenland

Ph.D., Geology

Stanford University

(415)422-0745

Henry Shaw

Isotope geochemistry, petrology, cosmochemistry, thermodynamics and phase equilibria, and high-level nuclear waste disposal

Ph.D., Geology and Chemistry

California Institute of Technology

(415)423-4645

David Smith

Interrelated field and laboratory studies in igneous and low-temperature metamorphic petrology and in waste disposal; analog studies; microbeam, x-ray, trace-element, and field methods applied to the earth sciences; and materials characterization

M.S., Geological Sciences

University of California, Riverside

(415)423-5793

Brian Viani

Clay mineralogy, x-ray diffraction, and colloid chemistry of clays

Ph.D., Soil Chemistry

University of California, Berkeley

(415)423-2001

Tom Wolery

Geochemical modeling, modeling software development (EQ3.6), thermodynamics and kinetics of aqueous systems, and low-temperature and hydrothermal rock-water interactions

Ph.D., Geophysical Sciences

Northwestern University

(415)422-5789

Geology

Jerry Sweeney, Group Leader

Thermal history modeling of sedimentary basins, thermal maturation studies, resistivity and low frequency EM geophysical methods, geophysical field deployments, structural geology, and general regional geology of California and Nevada

Ph.D., Geology

University of Illinois

(415)422-4917

Dave Carpenter

Well logging, in situ physical property measurement, environmental geology, neotectonics, and field methods

M.S., Geology

Pennsylvania State University

(415)422-3976

Don Emerson

General geology, mineralogy, and petrology

Ph.D., Mineralogy and Petrology

Pennsylvania State University

(415)422-6504

Larry McKague

Geology of southwestern Nevada, geologic interpretation of geophysical data, nuclear explosion phenomenology, volcanic hazards, and geology of serpentinites

Ph.D., Mineralogy and Petrology

Pennsylvania State University

(415)422-6494

Gayle Pawloski

General geology, Nevada Test Site geology, data management, and x-ray diffraction

B.S., Earth Science

California State University, Hayward

(415)423-0437

Donald Towse

Economic geology, structure, and stratigraphy

Ph.D., Geology

Massachusetts Institute of Technology

(415)422-6438

Jeff Wagoner

Sedimentology of alluvial deposits, geology of the Nevada Test Site, and site characterization for underground nuclear testing

M.S., Geology

University of California, Riverside

(415)422-1374

Geomechanics

François E. Heuzé, Group Leader

Geomechanics, field testing and instrumentation, finite element and discrete element analysis, rock engineering/rock structures design, and rock and joint laboratory testing
Ph.D., Civil Engineering/Geological Engineering
University of California, Berkeley
(415) 423-0363

Dave Glenn

Shock physics, instrumentation and experimental designs for measuring effects of shock wave propagation, and technical writing
Ph.D., Physics
Washington State University
(415) 422-3956

Ed Kansa

Computational fluid dynamics in subsoil and in general fluids, multiphase (liquid-vapor-solid) flow, various aspects of computational mathematics and computational physics, and shock waves and very nonlinear physics
Ph.D., General Chemistry and Physics
Vanderbilt University
(415) 423-0151

Ron Shaffer

Code development, and multidimensional elastic continuum models, finite element analysis, and discrete element analysis
Ph.D., Physics
New Mexico Institute of Mining and Technology
(415) 422-3940

Ray Stout

Stress analysis, micromechanics of constitutive equation modeling, diffusion analysis, numerical analysis, fracture mechanics, fluid mechanics, variational principles, similarity analysis, borehole slot stress-displacement sensitivity analysis, kinematics and thermodynamics of chip formation, and computer programming
Ph.D., Engineering Mechanics
Illinois Institute of Technology
(415) 422-3965

Geophysical Imaging and Analysis

Jim Berryman, Group Leader

Inverse problems and tomography, image processing methods for rock analysis, waves in porous and random media, and fluid flow through porous media
Ph.D., Physics
University of Wisconsin, Madison
(415) 423-2905

Geotechnical Engineering

Jesse Yow, Jr., Group Leader

Coupled earth processes and systems, geomechanics, subsurface hydrology, instrumentation and testing, and numerical modeling and data analysis
Ph.D., Civil Engineering
University of California, Berkeley
(415) 422-3521

Bill Isherwood

Contaminant hydrogeology, geothermal systems, potential field geophysics, and seismology
Ph.D., Geologic Sciences
University of Colorado
(415) 423-5058

Kenrick H. Lee

Groundwater hydrology, solute transport, field testing, mining engineering, rock mechanics, and geotechnical engineering
M.S., Mining Engineering and Hydrology
New Mexico Institute of Mining and Technology
(415) 422-6492

Abe Ramirez

In situ heater test, underground imaging, and geophysics
M.S., Engineering Geology
Purdue University
(415) 422-6909

Tzou-Shin (Joe) Ueng

Geotechnical engineering, geotechnical instrumentation, and physical modeling for groundwater treatment
Ph.D., Geotechnical Engineering
University of California, Berkeley
(415) 423-9681

Dale Wilder

Engineering geology, geotechnical engineering, instrumentation, and environmental geology/geohydrology
M.C.E., Civil Engineering
Brigham Young University
(415) 422-6908

Institute of Geophysics and Planetary Physics

George Zandt

Seismic imaging, Institute of Geophysics and Planetary Physics (IGPP), and earth structure
Ph.D., Seismology
Massachusetts Institute of Technology
(415)423-6835

Nuclear Waste Management

Lyn Ballou, Group Leader

Project management, field test engineering, and civil/construction engineering
B.S., Civil Engineering
California State University, San Jose
(415)422-4911

Barbara Bryan

Oversees records, training, and project administrative functions
B.S., Education
Bowling Green State
(415)423-3378

Perpetua Comstock

Resource management, and cost control and reporting system
California State University,
San Francisco
(415) 222-0461

Deborah Kiraly

Technical and periodic management reports and public liaison
Las Positas College
(415)423-4571

John Podobnick

Budgeting, cost schedule control system, fiscal management and planning
B.A., Economics
M.B.A., Business Administration
University of Montana
(415)423-1916

Mike Revelli

Physical chemistry and Nuclear Waste Management Program/Waste Package Project
Ph.D., Chemistry
University of California, Santa Barbara
(415)422-1982

Shock Physics

Lewis Glenn, Group Leader

Shock hydrodynamics, applied mechanics, computational physics, and thermodynamics
Ph.D., Engineering
University of Southern California
(415)422-7239

Armand Attia

Applied mechanics, fluid dynamics, fluid-structure interaction, and constitutive modeling
Ph.D., Applied Mechanics
University of California, Berkeley
(415)423-2225

Mike Kamegai

Computational physics, radiation hydrodynamics, nuclear physics, solid mechanics, and geophysics
Ph.D., Computational Physics
University of Chicago
(415)422-7201

Andre Kusubov

High pressure physics, equation of state, strength of materials, penetration mechanics, and dynamic compaction
B.A., Physics
University of California, Berkeley
(415)422-7183

Donald Maxwell

Continuous mechanics, computational physics, and constitutive modeling
B.A., Physics
Stanford University
(415)422-3210

Bill Moran

Computational physics, fracture mechanics, and constitutive modeling
Ph.D., Applied Science and Engineering
University of California, Davis
(415)422-7250

Willy Moss

Computational physics, shock hydrodynamics, and constitutive modeling
Ph.D., Applied Science and Engineering
University of California, Davis
(415)422-7302

John Rambo

Computational physics, data management, phenomenology of nuclear detonations, and economic modeling
B.S., Physics
University of Portland
(415)422-3944

Miles Rubin

Applied mechanics, plasticity, and constitutive modeling
Ph.D., Mechanical Engineering
University of California, Berkeley
(415)423-5834

Kurt Sinz

Lagrangian and multifluid Eulerian shock hydrodynamics, models including high explosives and strength of materials, and weapons calculations

Ph.D., Physics

Texas A&M University

(415) 422-1669

Bob Swift

Shock wave physics, rock mechanics, constitutive modeling, cratering mechanics, blast wave experimental applications, and static and dynamic experimental applications

Ph.D., Geology

University of Washington

(415) 422-3945

John White

Constitutive modeling, computational physics, modeling response of earth materials to explosive or impact loading, and weapons design

Ph.D., Applied Science and Engineering
University of California, Davis

(415) 422-4587

Special Assignment

Paula Krauter

Research and data analysis on the environmental effects of energy consumption, and creating and updating energy data bases

M.S., Biology

California State University, Hayward

(415) 422-0429

Don Larson

Shock wave physics
Ph.D., Solid State Physics
Brigham Young University

(415) 422-7108

Larry Ramspott

Nuclear waste disposal, environmental and hazards geology, Nevada Test Site geology, and project management

Ph.D., Geology

Pennsylvania State University

(415) 422-4176

Treaty Verification

Jim Hannon, Group Leader

Verification of compliance with nuclear testing limitations, seismology, and decision analysis applications to nuclear testing verification issues

Ph.D., Geophysics

St. Louis University

(415) 422-3921

Keith Nakanishi

Seismology and normal modes

Ph.D., Geophysics

University of California, Los Angeles

(415) 422-3923

Don Springer

Explosion effects, seismology, instrumentation, seismic monitoring for treaty verification, nuclear test practices, seismic detection and discrimination between earthquakes and underground explosions, evasion methods and scenarios, and global exchange of seismic data

B.A., Physics

University of California, Santa Barbara

(415) 422-3520

Elleen Vergino

Explosion seismology and data base applications

B.S., Earth Sciences

Massachusetts Institute of Technology

(415) 422-3907

Robert Geil

Experimental physics, prompt diagnostic measurements for underground nuclear weapons tests, and verification technologies for treaties limiting nuclear testing

M.S., Physics

University of New Mexico

(415) 422-7422

Waste Management—QA

David Short

Materials science and engineering

Ph.D., Philosophy

Ohio State University

(415) 422-1287

Support Personnel

Chemistry and Materials Science

David Camp
John Reynolds

Computations

Ted Bakowsky
Brenda Bowman
Landon Bruce
Kris Chubb
Stephanie Daveler
Maylin Dittmore
Sandy Fisher
Betsy Foote
Mandy Goldner
Robert Herrick
Mary Lou Higuera
Kirk Keller
Mike Kurtzer
Joanne Levatin
Lynn Lewis
Miriam Lohmann
Suzanne Lundeen
Denise Maddix
Don Moccia
Miki Moore
Jim Norman
Terri Quinn
Janet Ricca
Bill Richardson
Adrienne Ridolfi
John Sayer
Cheryl Short
Ken Simerly
Ken Sumikawa
Bill Tapley
Joe Tull
Susan West
John Yio
Lin Zucconi

Containment Engineering

Tom Brown
Ray Cornell
Bill Maranville
John Mercier
Steve Pratuch

Electronic Engineering

Mike Axelrod
Farid Dowla
Dan Ewert
Joe Finkes
Dave Harris
Rowland Johnson
Craig Johnston
Cindy Mason
George Metzger
Don Rock
Bob Searfus
Don Watwood
Larry Weltern

Mechanical Engineering

Liz Campbell
Jim Blink

Technical Information Department

Pam MacGregor
Steve Peterson
Elaine Price
Priscilla Proctor
Sue Stull
Cynthia Talaber
Sandy Wander

END

10-2-91