DOE/ER/13422--T1

CALIFORNIA INSTITUTE OF TECHNOLOGY

SEISMOLOGICAL LABORATORY 252-21

DOE/ER/13422--T1

DE92 013711

FINAL TECHNICAL REPORT

Department of Energy

Contract: DE-FG03-85ER13422

Period: 8/15/88 to 8/14/90

Date: April 24, 1992

Prepared by: Thomas J. Ahrens and Catherine L. Smither

Principal Investigator: Thomas J. Ahrens

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

RECEIVED
MAY 13 1992

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Stress-relief displacements induced by drilling – applications to holographic measurements of in situ stress

1.1 Abstract

The holographic stressmeter is an instrument which has been developed at Caltech [Bass et al. 1986] to allow determination of the complete stress tensor from in situ borehole measurements. The prototype instrument has been used to find the state of stress in a mine pillar [Smither et al. 1987]. The stressmeter uses double-exposure holographic interferometry to record the displacements induced by the drilling of a small (≈ 1 centimeter) sidehole into the borehole wall. The local stresses, which are the result of the far-field stresses, concentrated at the borehole, cause deformation of the surface of the borehole wall in the vicinity of the sidehole. To interpret the data from the stressmeter, it is essential to understand in detail this deformation. The first part of this study uses a thin infinite elastic plate subjected to plane stress at infinity to model the displacements at the borehole wall. However, the existence of

some holograms which were difficult to model closely led us to examine the validity of this model. In order to investigate the problem further, we performed a two-dimensional finite element analysis for an elastic box with a terminated hole. We varied the dimensions of the hole to see what effect the radius and depth of the hole might have on the displacements. The plate model predicts that the depth of the hole should have no effect on the horizontal components of displacement, but the finite element results show that the magnitude of both components of the displacement depends on the depth of the sidehole. After considering these results, we developed a new model for the analysis of stress-relief displacements, following the work of Youngdahl and Sternberg [1965]. For holes with a depth-to-diameter ratio greater than unity, the simple plane stress elastic plate solution breaks down and does not adequately model the displacements at the surface of the body and near the hole. Since these are the areas most critical to calculate accurately with the holographic technique, the revised model does a better job of fitting the observed data.

1.2 Introduction

Detailed knowledge of the state of stress in the earth's crust is vital to the further understanding of many geophysical phenomena. Accurate in situ stress measurements may give information on plate tectonic processes such as the state of the stress acting on faults and plate boundaries or stress due to drag on the base of the lithosphere [Hickman 1991; McGarr and Gay 1978; Richardson et al. 1979; McGarr et al. 1982; Haimson 1975]. We may also wish to measure stresses associated with volcanism at mid-ocean ridges and subduction zones and in the interior of plates. Knowledge of the local in situ state of stress is also important in mining, for the design and safety of underground openings, and in the extraction of petroleum by hydrofracture [Haimson and Fairhurst 1967; Simonsen et al. 1978; Hubbert and Willis 1957].

This work presents results of in situ stress measurements made with the holographic stressmeter in a horizontal borehole in an underground mine in Garfield County, Colorado. All six stress tensor components were determined; previous work with the stressmeter in this mine [Bass et al. 1986; Schmitt 1987] and other sites [Cohn 1983; Schmitt et al. 1986] was able to determine only five of the six components. In addition, we examine the validity of the original method used to analyze the data by examining the initial predictions of the elastic plate model, the predictions of the displacements from a two-dimensional finite element model, and an analytic model for displacements on the surface of a half-space with a through-going hole.

The principles and operation of the holographic in situ stressmeter have been presented elsewhere [Bass et al. 1986, Schmitt 1987]. In brief, the stressmeter records, by holographic interferometry [Vest 1979], displacements induced by the drilling of a small hole of ≈ 1 cm diameter into the borehole wall. The magnitude and direction of the displacements depends on the state of stress at the borehole wall at the point where the sidehole is drilled. By measuring the stresses in several directions in the borehole, we can invert the values of the borehole wall stresses to obtain the far-field state of stress at that depth. (We use "far-field" in this study to indicate the ambient state of stress that would exist in the absence of the borehole. For the mine borehole from which the holograms in this thesis came, this is the state of stress at a given point in the mine pillar; for a conventional borehole, this might be the tectonic stress at a given depth in the crust.)

The interference holograms used for in-situ stress measurements are created by taking two exposures on a single piece of film. These two exposures interfere, and create a pattern of light and dark fringes when the hologram is reconstructed. A dark fringe is produced when the difference in the lengths of the raypath of the illuminating (object) beam reflecting off a certain point on the surface in the initial exposure and the raypath reflecting off the same point in its new location is an odd number of half-

Figure 1.1: Raypaths for a double exposure hologram. Light travels from the source (S), reflecting off the point P to a point on the hologram film plane H. In the second exposure, the point P has been displaced to P'.

wavelengths of the laser light source (in this case, the wavelength of the HeNe laser beam is 632.8 nm). In figure 1.2, the light from the laser travels from the source S to a point on the borehole wall, P. It is reflected up to a point on the holographic film plane, H. For the second exposure, the point originally at P has moved to P'. The difference in the paths SPH and SP'H will determine whether there will be a dark or light fringe at the location P when the hologram is reconstructed from point H. The distance L between points P and P' is typically quite small (microns) compared to the path SPH (centimeters).

Figure 1.2 shows a view looking down into the borehole. Once an area of the borehole, free of cracks and spallation, has been chosen, the instrument is locked into place and the first exposure is taken of the undisturbed borehole wall. After the first exposure, a drill bit advances and drills a small hole into the borehole

wall. The size of the hole relative to the size of the borehole is greatly exaggerated in this figure. With the prototype instrument, the sidehole is 1 cm in diameter, while the borehole itself is 30 cm in diameter. The drill is then retracted, and, after waiting a few minutes for any thermal effects to subside, a second exposure is taken. The change in shape of the small area of the borehole wall around the stress-relief hole is recorded by this second exposure. The instrument is then either turned to face a different direction at the same depth in the borehole, or unlocked and moved to another location. Since the sensitivity of this technique is such that any displacements of more than $10\text{ }\mu\text{m}$ will be enough to cause the hologram to be unreadable due to excessive interference, it is important that motion of the camera between the time of the first and second exposures be limited as much as possible. In practice, we can use holograms in which the camera moved $5\text{ }\mu\text{m}$ or less. The pattern of the interference fringes is dependent on the borehole wall stresses, as well as the movement of the camera and the elastic properties of the rock. To analyze the data, we create "synthetic holograms" to model the displacements, and thus determine the borehole wall stresses. When these are known, we invert to find the far-field stresses.

There are several advantages in using this holographic technique to measure in situ stress. It is not limited to use in short holes, as are overcoring measurements, which are limited to boreholes only tens of meters in length [Wang and Wong 1987, Leeman 1969]. Analysis of the data does not assume that one of the principal stresses is vertical, as hydrofracture [Aggson and Kim 1987] or the USBM borehole deformation gauge [Obert et al. 1962] do. The off-axis component of the stress tensor may be significant in engineering applications, as is shown by our mine pillar results presented below, and it may be of interest as well in vertical boreholes, where the effects of topography may induce an off-vertical component. A set of three measurements at a particular depth is sufficient to determine the far-field stress tensor, unlike the flatjack method [Wareham and Skipp 1974, Rocha et al. 1966] which, since each

First exposure

Second exposure

Figure 1.2: Cartoon of effect of drilling a sidehole into a stressed medium. The size of the side hole and the displacements are greatly exaggerated in this view

measurement determines stress in one direction only, requires at least six properly oriented measurements. This instrument may be used to examine changes in the state of stress at relatively closely spaced (≈ 10 cm) depths in a borehole; other techniques such as hydrofracture measure stresses over a much larger interval of the borehole [Aggson and Kim 1987]. The stressmeter may also be used, with a slight modification, to measure the elastic modulus of the rock in-situ with an indentation technique [Schmitt et al. 1986]. Since knowledge of the elastic properties is required in most stress-measurement techniques, it is advantageous to use an in-situ determination rather than a laboratory measurement, as the two may vary significantly. Moreover, this technique allows us to measure the elastic modulus in the same borehole as we take the stress measurements, and at the same locations, if we do the indentation prior to the drilling of the stress-relief hole. The displacements induced by both the indentation and the stress measurement are on the same micron scale, and so would be the most suitable means of determining the elastic parameters for each stress measurement.

Since the holograms give a picture of the area around the sidehole, we are often able to detect fine cracks and irregularities in the rock mass in the area of interest. This allows us to judge the quality of the measurements, and reject those which show a large amount of distortion by movement along cracks. Stress-measurement methods such as the slotting technique of Azzam and Bock [1987], which use strain gauges to measure the deformation, have no way of filtering out this kind of data.

The work described here was the first complete solution for the six components of far-field stress obtained by analysis of holographic stress-relief interferograms produced by this instrument. Previous work [Bass et al. 1986, Cohn 1983] had only enough data to determine five of the six components; the resulting values were not well constrained. We used the results of analysis of five stress-relief holograms taken at a distance of 4 m into a horizontal N-S oriented borehole in a pillar in a mine in

Garfield County, Colorado. The mine is approximately 180 m below the surface; the borehole is 2.0 m above the floor of the mine and is 30 cm in diameter. A sketch of the experimental set-up is shown in figure 1.3. The pillar is 15 m in height and in width.

1.3 Analysis of Holographic Data

Analysis of the interferograms begins with forward modeling of the displacement field recorded by the fringe pattern on the hologram. A typical stress relief hologram is shown in Figure 1.4. The stress relief hole is just below and to the right of the center of the figure. The long, linear fringes running from top to bottom are due to translation of the optics module of the stressmeter (the module containing the holographic camera) between the two exposures.

When considering double exposure holograms, it is important to keep two things in mind. First, the fringe patterns observed on the final product are the result of displacement arising from two distinct sources: the displacement caused by local relief of stress due to drilling the sidehole, and the rigid body translations caused by movement of the holographic camera between the two exposures. Figure 1.5 sketches the effects of the two sources of displacement. A point P is displaced to the point P_S due to the drilling of the stress-relief hole. Since the time the first exposure was taken, the camera has moved relative to the borehole wall along the vector $-T$. Thus the point P has been moved to P' . These two components of displacement are added together to produce the fringe pattern, as shown in figure 1.6. In this case the camera has moved $-9.2 \mu\text{m}$ to the ϕ -direction of figure 1.9, $1.5 \mu\text{m}$ in the h -direction, and $2.7 \mu\text{m}$ in the ζ -direction, out of the page. This figure shows the fringe patterns that result from each displacement field. The second thing to remember is that the fringe pattern, while caused by the displacement that has occurred between the two

Figure 1.3: Sketch of experimental set-up for the data in this chapter. The stressmeter was placed in a horizontal borehole in a mine pillar. The size of the instrument relative to the length of the borehole is exaggerated.

Figure 1.4: An example of a stress-relief hologram. The long, linear fringes across the picture are due to movement of the holographic camera between exposures. The curved fringes near the stress-relief hole are due to the distortion of the surface due to the hole being drilled.

Figure 1.5: The two components of the displacement field of the borehole wall. The displacements due to camera module translation (T) and due to stress-relief ($P-P'$) sum to create the total displacement field.

exposures, is not a direct representation of the displacement field on the surface, but the result of change in the length of the optical path traveled by the laser light, and depends on factors such as the position of the source of the illumination and the point on the film plane from which the holographic reconstruction was made.

We model the holograms by setting the known parameters (the location of the illumination (object) beam and the reconstruction point of the film plane, as well as the elastic parameters Young's modulus and Poisson's ratio), and varying the camera module translations and the borehole wall stresses until a suitable match is made with the observed fringe pattern. As can be seen from figure 1.6, the character of the two kinds of displacement is quite different. The stress relief displacements are

Stress relief

Rigid translations of camera

Total

Figure 1.6: The two components in the displacement field of a typical hologram. The displacements due to camera module translation and due to stress-relief sum to create the final pattern of interference fringes. The pattern also depends on the optical geometry of the holographic camera.

only significant near the sidehole, while the rigid body translations of the camera affect the entire hologram field of view. In practice, the presence of a small amount of camera movement between the two exposures can greatly aid the analysis, as the stress relief displacements perturb the regular pattern of the translations.

The model initially used to calculate stress relief displacements on the borehole wall [Bass et al. 1986] is that of a throughgoing hole in an infinite flat homogeneous elastic plate subjected to plane stress at infinity. The thickness of the plate is set at twice the depth of the sidehole that was drilled into the borehole wall, on the assumption that the displacements in the rock at the depth of the bottom of the stress relief hole are small, and would thus be similar to the plane of symmetry of a plate that is twice as thick as the stress relief hole is deep. To analyze the holograms we generate a displacement field by superposition of the displacement field induced by stressing a plate with a hole and the displacement field of a stressed plate without a hole. The difference between the two fields is the displacement due to the drilling of the stress relief hole. We assume that the flat plate is subjected to plane stress at infinity; this represents the state of stress on the borehole wall, where there are only three non-vanishing stresses: $\sigma_{\phi\phi}$, the hoop stress (the stress in the direction around the circumference of the borehole), σ_{hh} , the stress in the direction along the axis of the borehole, and $\tau_{\phi h}$, the shear stress on the borehole wall. These stresses are related to the far-field stresses ($\sigma_{xx}, \sigma_{yy}, \sigma_{zz}, \tau_{xy}, \tau_{xz}, \tau_{yz}$) by [Hiramatsu and Oka 1962, Leeman and Hayes 1966]:

$$\sigma_{\phi\phi} = \sigma_{xx} + \sigma_{yy} - 2(\sigma_{xx} - \sigma_{yy}) \cos 2\phi - 4\tau_{xy} \sin 2\phi, \quad (1.1)$$

$$\sigma_{hh} = -\nu[2(\sigma_{xx} - \sigma_{yy}) \cos 2\phi + 4\tau_{xy} \sin 2\phi] + \sigma_{zz}, \quad (1.2)$$

$$\tau_{\phi h} = 2(-\tau_{xz} \sin \phi + \tau_{yz} \cos \phi). \quad (1.3)$$

The stresses $\sigma_{\phi\phi}$, σ_{hh} , and $\tau_{\phi h}$ are the plane stresses applied to the edges of the plate in our model. By convention [Timoshenko and Goodier 1970], compressive normal stresses are negative, and positive shear stress is as shown in Figure 1.7. The far-field

(pillar) stresses are σ_{xx} , σ_{yy} , σ_{zz} , τ_{xy} , τ_{xz} , and σ_{yz} , with the coordinate system as pictured in figure 1.7. The z -axis, which in a vertical borehole would be the vertical axis, is in the case of the mine pillar, the horizontal axis in the direction along the axis of the borehole (N-S; see Figure 1.8). These stresses may also be expressed in terms of the cylindrical coordinate system r, θ, h , as pictured in the same figure. The values of the stresses at the borehole wall depend also on Poisson's ratio (ν) and the azimuth ϕ measured from the direction of the positive x -axis.

Since the hole is small relative to the size of the borehole, and we are interested mostly in the displacements very close to the sidehole, we treat the borehole wall as locally flat and homogeneous in the vicinity of the sidehole. The displacements for an infinite, homogeneous, elastic stressed plate with no hole are, for the cylindrical coordinate system r, θ, ζ pictured in figure 1.9 [Timoshenko and Goodier 1970, Jaeger and Cook 1979]:

$$u_r = \frac{1}{E} [(\sigma_2 - \nu\sigma_1)r \sin^2 \omega + (\sigma_1 - \nu\sigma_2)r \cos^2 \omega], \quad (1.4)$$

$$u_\theta = \frac{1}{E} [(1 + \nu)(\sigma_2 - \sigma_1)r \sin \omega \cos \omega], \quad (1.5)$$

$$u_\zeta = -\frac{\nu}{E}(\sigma_1 + \sigma_2)\frac{t}{2}. \quad (1.6)$$

Where σ_1 and σ_2 are the principal stresses, with the angle ω measured from the direction of the stress σ_1 . For a stressed plate of thickness t with a hole of radius a and depth $t/2$ centered at $r = 0$:

$$u_r = \frac{1}{2E} \left[(\sigma_1 + \sigma_2) \left(r + \frac{a^2}{r} \right) + (\sigma_1 - \sigma_2) \left(r - \frac{a^4}{r^3} + \frac{4a^2}{r} \right) \cos 2\omega \right] - \frac{\nu}{2E} \left[(\sigma_1 + \sigma_2) \left(r - \frac{a^2}{r} \right) - (\sigma_1 - \sigma_2) \left(r - \frac{a^4}{r^3} \right) \cos 2\omega \right], \quad (1.7)$$

$$u_\theta = \frac{1}{2E} \left[-(\sigma_1 - \sigma_2) \left(r + \frac{2a^2}{r} + \frac{a^4}{r^3} \right) \sin 2\omega \right] - \frac{\nu}{2E} [(\sigma_1 - \sigma_2) \left(r - \frac{2a^2}{r} + \frac{a^4}{r^3} \right) \sin 2\omega], \quad (1.8)$$

$$u_\zeta = -\frac{\nu}{E} [(\sigma_1 + \sigma_2) - (\sigma_1 - \sigma_2) \frac{2a^2}{r^2} \cos 2\omega] \frac{t}{2}. \quad (1.9)$$

Figure 1.7: Far-field coordinate systems x, y, z and ζ, ϕ, h , centered on the axis of the borehole. Positive shear stresses are as pictured.

Figure 1.8: Geometry of the borehole coordinate system for these measurements. The borehole is oriented north-south, and the angle ϕ is measured from east.

Hence the displacements of the borehole wall, in terms of the borehole wall stresses $\sigma_{\phi\phi}$, σ_{hh} , and $\tau_{\phi h}$ are given by:

$$u_r = \frac{1}{2E} \left\{ (\sigma_{\phi\phi} + \sigma_{hh})(1 + \nu) \frac{a^2}{r} + (\sigma_{\phi\phi} - \sigma_{hh}) \left[\frac{4a^2}{r} - (1 + \nu) \frac{a^4}{r^3} \right] \cos 2\theta + 2\tau_{\phi h} \left[\frac{4a^2}{r} - (1 + \nu) \frac{a^4}{r^3} \right] \sin 2\theta \right\}, \quad (1.10)$$

$$u_\theta = -\frac{1}{2E} \left\{ [(1 - \nu) \frac{2a^2}{r} + (1 + \nu) \frac{a^4}{r^3}] [(\sigma_{\phi\phi} - \sigma_{hh}) \sin 2\theta - 2\tau_{\phi h} \cos 2\theta] \right\} \quad (1.11)$$

$$u_\zeta = \frac{\nu a^2 t}{Er^2} [(\sigma_{\phi\phi} - \sigma_{hh}) \cos 2\theta + 2\tau_{\phi h} \sin 2\theta]. \quad (1.12)$$

u_r represents displacement in the radial direction, u_θ displacement in the azimuthal direction, and u_ζ displacement in the direction normal to the borehole wall. Note that only the normal displacement depends on the plate thickness. Therefore, in this theory, the depth of the hole does not affect the horizontal displacement. The modeling of the borehole wall displacements requires knowledge of Young's modulus (E) and Poisson's ratio (ν); the value of Young's modulus (25 GPa) used here was the value determined by Schmitt et al. [1986] from in situ holographic elastic modulus measurements made at the same locations in the same mine pillar borehole. Poisson's ratio, not well constrained by the borehole wall indentation technique used to determine Young's modulus, was set at a value of 0.345 [Horino et al. 1982].

Ideally, only three holograms, properly oriented, are needed to determine the complete far-field stress tensor [Leeman and Hayes 1966], but five were analyzed in order to obtain a more accurate fit to the data. In the coordinate system defined in figure 1.8, where azimuths are measured from the positive x -axis (pointing east), these holograms were at azimuths of 90° , 45° , 0° , 180° , and 225° . The values of the three non-vanishing borehole wall stresses ($\sigma_{\phi\phi}$, σ_{hh} , and $\tau_{\phi h}$) were determined by forward modeling of the observed hologram interference patterns; these values are listed in Table 1.1. The rigid body translations for these holograms are given in table 1.2. The holograms are identified by a label that indicates the date, roll

Figure 1.9: The plate coordinate system r, θ, ζ , centered on the stress-relief hole, which has radius a . The applied stresses, corresponding to the borehole wall stresses, are $\sigma_{\phi\phi}, \sigma_{hh}, \tau_{\phi h}$. The directions of positive stresses are as shown by the arrows.

Borehole wall stresses (in MPa)									
Hologram	Azimuth	$\sigma_{\phi\phi}$			σ_{hh}			$\tau_{\phi h}$	
16/1/4	90°	-22.5	±	2.5	5.0	±	5.0	-15.0	± 5.0
16/2/5	45°	-10.0	±	5.0	-16.0	±	8.0	-28.0	± 2.0
16/3/3	0°	-20.0	±	4.0	-7.0	±	5.0	-10.0	± 2.5
15/1/8	180°	-22.0	±	4.0	0.0	±	4.5	5.0	± 5.0
15/1/4	225°	-22.0	±	4.0	3.5	±	6.5	5.0	± 5.0

Table 1.1: Plate model solutions for the borehole wall stresses.

of film, and exposure; we have retained these labels here for ease of reference. All were 4 meters from the free surface of the pillar. The synthetic holograms are shown in figures 1.28 - 1.32. The results from this plate model analysis are the synthetic holograms on the lower left of each figure. The orientation of the holograms in the borehole is as shown in figure 1.27. Due to the geometry of the optical system, the values for the hoop stress ($\sigma_{\phi\phi}$) are the best constrained; all but one are close to -20 MPa. The uncertainties listed in the table are determined by varying the values of the borehole wall stresses until the synthetic fringe pattern is no longer similar to the observed pattern. In some cases, particularly for σ_{hh} and $\tau_{\phi h}$, the uncertainties may be quite large, since with this model, the displacement field is more sensitive to changes in $\sigma_{\phi\phi}$ than to variation of the other two stresses.

1.4 Finite Element Analysis

Since the plate model hologram analysis method described above depends on a stress-relief displacement model which may not accurately reflect the true geometry of the borehole, we developed a two-dimensional finite element model. The displacements predicted by this model were compared to the analytic solution for a hole in a stressed plate that was used in the analysis of the holograms presented above. Possible

Camera module translations (for plate module fits) (μm)			
Hologram	ϕ	h	ζ
15/1/4	3.85	2.2	2.275
15/1/8	2.0	0.8	2.05
16/1/4	3.1	2.6	1.55
16/2/5	-3.525	0.985	4.05
16/3/3	-9.2	1.5	2.7

Table 1.2: Rigid body translations of the camera module for the synthetic holograms modeled by the plate model.

inadequacies of the plate model may arise from the effects of the finite thickness and symmetry of the plate, the shape of a terminated stress-relief hole, and on the assumption of plane stress. The finite element calculations were done in part to see how large any effects might be. Another reason for doing the finite element calculations was to analyze the effects of changing the depth and diameter of the stress-relief hole on the displacements of the borehole wall. The analytic plane stress plate model predicts no change in horizontal displacements with changing hole depth (i.e., changing plate thickness); it was desired to know whether changes in depth would significantly alter the displacements. The analytic plate model uses a plate thickness that is twice the depth of the stress-relief hole, on the assumption that the vertical displacements in the rock mass are small at the depth of the stress relief hole, thus mimicking the symmetry plane of a plate of thickness twice the depth of the hole. Moreover, some holograms are difficult to analyze with the existing plate model, especially in low-stress situations. The finite element analysis was an initial attempt to discover where these problems may arise.

The finite element program used was a two-dimensional code [Hughes et al. 1987] simulating a box with dimensions large relative to the size of the hole. The sides of

the box were 50 cm and 25 cm long, and the hole depth and diameter ranged from 0.25 to 1.5 cm and 0.5 to 1.5 cm respectively. (Actual holograms of the borehole wall view an area as large as 8 cm by 8 cm centered on the stress relief hole.) A stress of 20 MPa was applied to the 25 cm sides and displacements were calculated for all of the 1060 elements in the grid. This grid did not take into account the effects of curvature of the borehole wall, but the analysis presented here only considers the displacements in the area viewed by the hologram, where the effects of curvature are small. The analytic plate model also ignores the curvature of the borehole wall. The analysis was done for a material with the same elastic properties as used in the hologram analysis, with a Young's modulus of 25 GPa and a Poisson's ratio of 0.345. Three different stress configurations were tested: plane stress, plane strain, and biaxial stress (an axisymmetric calculation). The plane stress case corresponds to a case where the intermediate stress is zero; the plane strain case is one in which the intermediate stress is non-zero and smaller in magnitude than the maximum stress and the walls of the box are constrained not to move in the direction normal to the applied stress (out of the page of figure 1.10); the axisymmetric case is one in which the maximum and intermediate stresses are equal. In all three cases the minimum stress, in the direction normal to the free surface of the borehole wall, is zero. This two-dimensional finite element arrangement is unable to model shear stress on the surface of the borehole wall.

Figure 1.10 shows a cartoon of the displacements resulting from drilling a small hole into the stressed finite element box. The plane stress and plane strain cases are shown as boxes with central square cuts; this is due to the geometry of the two-dimensional calculations. The axisymmetric case is a cylinder with a hole in it subjected to a uniform stress; the situation in our experiments, a round hole in a large medium subjected to non-equal principal stresses, is in between these two extremes. In this figure, it should be noted that the magnitude of the displacements

and the size of the hole are greatly exaggerated relative to the size of the finite element box. These stress-relief displacements were calculated in a manner analogous to the method used in the plate model calculations: they are the difference between the displacements of the stressed body with a hole and the stressed body without a hole. By superposition, the difference in the two displacement fields is the displacement due to the drilling of the hole in a prestressed medium. All of the displacements are about $1\mu\text{m}$ meters or less for a 20 MPa compressive stress applied to the sides of the box. In all cases, displacement is greatest near the hole. Generally, horizontal displacements are larger than vertical displacements. Surface points near the hole are displaced down and inward toward the axis of the hole when subjected to compressive stress. The vertical displacements are down toward the bottom of the box from their original location. The plane stress case shows the largest displacements, the axisymmetric case, the smallest.

Figures 1.11 - 1.13 compare the displacements predicted by the finite element calculations and the plate model, for a material with a Young's modulus of 25 GPa and Poisson's ratio of 0.345. The three plots show the displacements on the surface of the borehole wall as it varies with distance from the center of the hole. The distance scale is measured in units normalized by the hole radius, which was in these cases 0.5 cm. Thus the edge of the hole is at a distance equal to unity. For the horizontal displacements, a negative displacement is in the direction toward the center of the stress-relief hole; for the vertical displacements, a negative displacement is directed into the body, normal to the free surface. These figures show the results of calculations for the three stress states mentioned above for a hole of diameter 1.0 cm and depth 0.5 cm, a geometry which closely approximates the actual hole drilled by the stressmeter. Bold lines indicate the plate model calculations; in this case the plate would be 1.0 cm thick. Dashed lines indicate the vertical component. In the plane stress and plane strain cases, the finite element results show almost 1.5

Figure 1.10: Sketch of the two-dimensional finite-element models. Top: the plane-stress and plane-strain models represent an infinite box with a square groove, with stress applied on the left and right ends of the box. The initial state is on the left; the stressed state on the right shows that the sides of the groove have moved inwards and down slightly. Bottom: the axisymmetric case represents a cylinder with a cylindrical hole, with a uniform stress around the circumference of the body.

times as much horizontal displacement as the plate model would predict. For the axisymmetric case the agreement between the two models is closer; the finite element horizontal displacements are actually slightly smaller than those of the plate model. The finite element model shows larger vertical displacements for all three cases. The plate model predicts no vertical displacements for the axisymmetric case, yet the finite element model shows some small movement of the surface. These differences in the magnitude of displacement increase near the hole, where they become large enough to affect the stress relief pattern on the hologram. This difference is enough to show up on a hologram, as is shown in figure 1.14. The fringe patterns in the figure are the result of the interaction of the displacements due to an applied stress of 20 MPa and translations of $-2\ \mu\text{m}$ in the ϕ -direction and $2\ \mu\text{m}$ in the ζ -direction as defined by figure 1.9. While this example was chosen to highlight the possible differences, it is clear that a small change in the displacement field can have a significant effect on the final fringe pattern.

The effects of changing the depth and diameter of the stress-relief hole are shown in Figure 1.15. The light lines are for holes of depth 0.5 cm and radius varying from 0.25 to 0.75 cm; the bold lines represent holes 1.0 cm deep for the same range of radius. As in figures 1.11 - 1.13, the axis is plotted in terms of hole radius. The curves for a given hole depth are similar at the edge of the hole and at large distances from the hole, but vary in the intermediate distance. The depth of the stress-relief hole is clearly a much more important factor than its width. An increase in the depth by a factor of two yields a corresponding increase in both components of displacement, but changing the width by a factor of three will at most double the displacement at an intermediate distance, 4 radii from the center of the hole. The plate model predicts that changing the depth of the hole would have no effect on the horizontal displacements; the finite element calculations suggest that this is not the case. The analytic plate model does predict larger vertical displacements for deeper holes, as

Figure 1.11: Comparison of displacements predicted by the plate model (bold lines) and the finite element model (light lines) the axisymmetric case. The horizontal displacements (solid lines) are larger in the plate model, but the finite element model predicts more vertical (dashed lines) movement.

Figure 1.12: Comparison of displacements for the plane stress case. Light lines identify finite element results; dashed lines represent the vertical component.

Figure 1.13: Comparison of displacements for the plane strain case. Light lines identify finite element results; dashed lines represent the vertical component.

Plate model

Finite element

Figure 1.14: Slight changes in the displacement can have a noticeable effect on the fringe pattern. For an applied, axisymmetric stress of -20 MPa, the fringe pattern predicted by the plate model (above) differs from that predicted by the finite element model. The camera module translations of $-2\text{ }\mu\text{m}$ in the ϕ direction and $2\text{ }\mu\text{m}$ in the ζ direction were chosen to highlight this difference, but it is clear that the effect can be significant.

do the finite element calculations.

The finite element calculations suggest that the effect of hole depth on the horizontal displacements of the borehole wall is much more important than the analytic plate model indicated. This effect is most pronounced near the stress relief hole which is in the region where stress relief displacements become large enough to create interference fringe patterns. The underestimation of total displacements due to a given set of borehole wall stresses leads to an overestimation of borehole wall stresses: more stress is put into the model in order to make up for the underestimated displacement. This in turn leads to an overestimate of the far-field state of stress. In addition, the predictions of the analytic plate model, in not accounting for as much vertical displacement near the hole as the finite element model suggests that there should be, may be the cause of the difficulty in exactly matching the observed fringe pattern by using the analytic plate model. This mismatch is most pronounced in situations where the stress field at that location on the borehole wall has a low value. Some observed fringe patterns have never adequately been modeled using the analytic plate theory.

The results of the finite element analysis may be applied to the results of the analytic plate model estimate of the components of the far-field stress presented above. For most of the holograms, the hoop stress ($\sigma_{\phi\phi}$) is much greater than the normal stress along the axis of the borehole (σ_{hh}), similar to the plane stress case. Thus the values of the borehole wall stresses may be overestimated in these cases by as much as 10%. For one hologram (taken at the azimuth 45°), the $\sigma_{\phi\phi}$ is less than or nearly equal to σ_{hh} , as in the axisymmetric case; the resulting stress values may be slightly underestimated. However, due to the use of a two-dimensional finite element code, it was not possible to take into account the effect of the shear stress ($\tau_{\phi h}$) on the displacements, so the finite element results will not directly allow us to assess the amount of error in this estimate of the state of stress in the mine pillar.

Figure 1.15: The effect of varying hole depth and diameter on the displacements in the finite element model. Results are plotted for the plane stress case. Light lines indicate curves for the case of a hole of depth 0.5 cm. The depth of the hole has a much greater effect than its width.

1.5 Revised Model

In order to determine the displacements on the surface of the borehole wall that occur due to the drilling of the stress-relief hole, we must be able to model the displacement field accurately. Previously, we have modeled the borehole wall as a flat elastic plate of thickness twice the depth of the stress relief hole. The finite element calculations presented above and the existence of holograms which cannot be matched with computed (synthetic) holograms suggest that this model is not fully adequate. Therefore, following the approach of Youngdahl and Sternberg [1965, 1966], we used the model of a cylindrical hole of radius a in an elastic, isotropic half-space. This model should more accurately represent the displacements on the surface of a body with a hole drilled in it.

Our plate model assumes plane stress within the entire plate; however, for a plate with a thickness to hole diameter ratio greater than unity, this assumption is less valid (for the stress-relief hole as drilled by the stressmeter, this ratio is approximately 1.33). Moreover, it is certainly not the case in the area near the surface of the borehole. One consequence of this is the underestimation of displacements in the ζ -direction (the direction perpendicular to the surface of the borehole wall). This effect is most pronounced near the stress-relief hole, which is the area in which these displacements become large enough to be measurable by the holographic technique. In fact, in field experiments we have collected several holograms which show only small displacements near the stress-relief hole that we have been unable to match with synthetics; this is thought to be representative of some inaccuracy in the plate model.

The approach of Youngdahl and Sternberg relaxes the assumption of plane stress within the body. An infinite isotropic elastic half-space with a throughgoing hole is loaded at infinity with plane stresses in the x and y directions (parallel to the bounding plane of the half-space). The stresses and displacements within the body

and on the surface are calculated using Papkovitch stress functions [Papkovitch 1932, Sokolonikoff 1956] and integral transforms. The resulting integrals for the displacements and stresses can then be solved numerically. These results show the existence of a three-dimensional stress boundary layer that occurs near the edges of the hole in the related problem of a plate of finite thickness, as the ratio of the thickness of the plate to the diameter of the hole increases.

The two models are sketched in figure 1.16. Figure 1.16(c) shows the half-space model. The radius of the hole is a ; any point in the half space may be described by the Cartesian coordinates x, y, z or the more convenient cylindrical coordinates r, θ, ζ . The plate model is pictured in fig 1.16(b). The hole of radius a goes all the way through the plate; the thickness of the plate is t . In the modeling of the holograms, the value of t is set at twice the depth of the stress relief hole that was drilled into the borehole wall. Figure 1.16(c) shows the actual geometry of the stress relief hole: it has radius a and depth $t/2$. Hence the real situation is intermediate to the two models – a finite depth hole in an (almost) infinite region.

This study compares the predictions of these two models in order to determine the best method for analysis of the stress relief holograms. As before, we assume plane stress, i.e., stress parallel to the bounding plane of the half-space (the surface $z = 0$). The principal stresses on the plane can be denoted $\sigma_{11} = \sigma_1$ and $\sigma_{22} = \sigma_2$. This can be decomposed into two components:

- a) plane axisymmetric stress σ_H applied at infinity, and
- b) plane pure shear (σ_S),

where $\sigma_H = \frac{1}{2}(\sigma_1 + \sigma_2)$ and $\sigma_S = \frac{1}{2}(\sigma_1 - \sigma_2)$. Case a) has the well known (e.g., [Jaeger and Cook 1979]) solution for the displacements:

$$\frac{2\mu u_r^H}{a\sigma_H} = \frac{1-\nu}{1+\nu}\rho + \frac{1}{\rho}, \quad (1.13)$$

$$\frac{2\mu u_\zeta^H}{a\sigma_H} = -\frac{2\nu}{1+\nu}\psi, \quad (1.14)$$

a)

b)

c)

Figure 1.16: The models used for calculations of stress-relief displacements. a) the actual geometry of the stress-relief hole. b) the plate model. c) the model of Youngdahl and Sternberg (referred to in other figures as the revised model).

$$u_{\theta}^H = 0. \quad (1.15)$$

Where ρ and ψ are the dimensionless coordinates $\rho = r/a$ and $\psi = \zeta/a$. Note that there are no tangential displacements and that there are also no vertical displacements on the surface $\zeta = 0$.

The solution for case b), however, is not as simple. The approach taken is to consider the residual problem created by subtracting the plane strain solution associated with the pure shear problem from the exact solution. The plane strain solution satisfies the field equations as well as the boundary conditions on the surface of the cylindrical hole, but does not satisfy all of the boundary conditions on the surface of the half-space. The displacements obtained from the associated plane strain solution are:

$$\frac{2\mu u_r^P}{a\sigma_S} = \left(\rho + \frac{2\alpha}{\rho} - \frac{1}{\rho^3}\right) \cos 2\theta, \quad (1.16)$$

$$\frac{2\mu u_{\theta}^P}{a\sigma_S} = -\left(\rho + \frac{2(\alpha - 1)}{\rho} + \frac{1}{\rho^3}\right) \sin 2\theta, \quad (1.17)$$

$$u_{\zeta}^P = 0. \quad (1.18)$$

where $\alpha = 2(1 - \nu)$. Note that no ζ -displacements are predicted, since this is a plane strain solution.

The residual problem is therefore

$$u_r^R = u_r^S - u_r^P, \quad (1.19)$$

and similar equations for the other components (where the superscript S denotes the exact solution of the pure shear problem). The solution for the displacements at the surface $\zeta = 0$ is [Youngdahl and Sternberg 1966]:

$$\frac{2\mu u_r^R(\rho, \theta)}{a\sigma_S \cos 2\theta} = \int_0^{\infty} D(\eta) [(1 - \alpha)\eta^3 \Omega_2'(\eta, \rho) + U_{\rho}(\eta, \rho)] d\eta, \quad (1.20)$$

$$\frac{2\mu u_{\theta}^R(\rho, \theta)}{a\sigma_S \sin 2\theta} = \int_0^{\infty} D(\eta) [2(\alpha - 1)\eta^2 \rho^{-1} \Omega_2(\eta, \rho) + U_{\theta}(\eta, \rho)] d\eta, \quad (1.21)$$

$$\frac{2\mu u_{\zeta}^R(\rho, \theta)}{a\sigma_S \cos 2\theta} = \int_0^{\infty} D(\eta) [-\alpha\eta^3 \Omega_2(\eta, \rho)] d\eta \quad (1.22)$$

where $D(\eta)$ satisfies the integral equation:

$$D(\eta)\eta^6 Y(\eta) = \frac{8(2-\alpha)}{\pi} + \int_0^\infty D(\xi)L(\xi,\eta)d\xi.$$

Here $Y(\eta)$ is a function of J'_2 and Y'_2 , the derivatives of the 2nd order Bessel functions of the first and second kind, respectively [13]:

$$Y(\eta) = [J'_2(\eta)]^2 + [Y'_2(\eta)]^2, \quad (1.23)$$

and $L(\xi, \eta)$ is the kernel

$$\begin{aligned} L(\xi, \eta) = & -\frac{32}{\pi_3} \int_0^\infty \frac{\gamma^2}{\Delta(\gamma)} g\left(\frac{\gamma}{\xi}\right) g\left(\frac{\gamma}{\eta}\right) \left\{ \alpha f_1(\gamma) \right. \\ & + 2\alpha \left[g\left(\frac{\gamma}{\xi}\right) + g\left(\frac{\gamma}{\eta}\right) \right] K(\gamma) f_2(\gamma) \\ & \left. + g\left(\frac{\gamma}{\xi}\right) g\left(\frac{\gamma}{\eta}\right) K^2(\gamma) f_3(\gamma) \right\} d\gamma. \end{aligned} \quad (1.24)$$

The functions needed to evaluate $L(\xi, \eta)$ are

$$g(x) = \frac{1}{1+x^2}, \quad (1.25)$$

$$K(\gamma) = \gamma \frac{K'_2(\gamma)}{K_2(\gamma)}, \quad (1.26)$$

$$f_1(\gamma) = \gamma^2[\gamma^2 + 4 - K^2(\gamma)] + 3\alpha K^2(\gamma), \quad (1.27)$$

$$f_2(\gamma) = \gamma^2 - (\gamma^2 + 3)K(\gamma), \quad (1.28)$$

$$f_3(\gamma) = (\gamma^2 + 2)(\gamma^2 + 6) - 2\gamma^2 K(\gamma), \quad (1.29)$$

$$f_4(\gamma) = (\gamma^2 + 3)(\gamma^2 + 4) - \gamma^2 K(\gamma) - \alpha f_2(\gamma) + 3\alpha K(\gamma), \quad (1.30)$$

$$\begin{aligned} \Delta(\gamma) = & [\gamma^2 + 4 - K^2(\gamma)] f_3(\gamma) \\ & + \gamma[-4\gamma^2 + 8(\gamma^2 + 3)K(\gamma) - \gamma^2 K^2(\gamma) - 6K^3(\gamma)]. \end{aligned} \quad (1.31)$$

Here K_2 and K'_2 are the second order modified Bessel function and its derivative.

Also needed to evaluate equations 1.20 - 1.22 are the functions

$$\Omega_2(\gamma, \rho) = Y_2'(\gamma)J_2(\gamma\rho) - J_2'(\gamma)Y_2(\gamma\rho), \quad (1.32)$$

$$\Omega_2'(\gamma, \rho) = Y_2'(\gamma)J_2'(\gamma\rho) - J_2'(\gamma)Y_2'(\gamma\rho), \quad (1.33)$$

and

$$\begin{aligned} U_\rho(\eta, \rho) = & \frac{8}{\pi^2} \int_0^\infty \frac{1}{\rho\Delta} \left[2\alpha g\left(\frac{\gamma}{\eta}\right) \{G(\gamma, \rho)[(\gamma^2\rho^2 + 4)f_2 - 2f_1] \right. \\ & + G'(\gamma, \rho)Kf_4 \} + g^2\left(\frac{\gamma}{\eta}\right)K \{G(\gamma, \rho)[(\gamma^2\rho^2 + 4)f_3 - 8\alpha f_2] \\ & \left. + G'(\gamma, \rho)[-(\gamma^2 + 4 + \alpha K)f_3 + 4\alpha f_2] \} \right] d\gamma, \end{aligned} \quad (1.34)$$

$$\begin{aligned} U_\theta(\eta, \rho) = & \frac{16}{\pi^2} \int_0^\infty \frac{1}{\rho\Delta} \left[\alpha g\left(\frac{\gamma}{\eta}\right) \{-2G(\gamma, \rho)f_4 + G'(\gamma, \rho)K(f_1 - 2f_2)\} \right. \\ & + g^2\left(\frac{\gamma}{\eta}\right) \{G(\gamma, \rho)[(\gamma^2 + 4 + \alpha K)f_3 - 4\alpha f_2] \\ & \left. + G'(\gamma, \rho)K^2[-f_3 + 2\alpha f_2] \} \right] d\gamma, \end{aligned} \quad (1.35)$$

where

$$G(\gamma, \rho) = \frac{K_2(\gamma\rho)}{K_2(\gamma)}, \quad (1.36)$$

$$G'(\gamma, \rho) = \frac{\rho K_2(\gamma\rho)}{K_2'(\gamma)}. \quad (1.37)$$

The equations 1.34 and 1.35 were integrated for the specified values of η and ρ , and are pictured in figures 1.17 - 1.20 as functions of η for ρ fixed at 1 and 1.5.

Note that the value of Poisson's ratio (ν) is involved in many of the functions through the parameter $\alpha = 2(1 - \nu)$. This means that although the magnitudes of the stresses and the values of the shear modulus (μ) or Young's modulus may easily be changed to different values in equations 1.20 - 1.22, changing the value of Poisson's ratio requires recalculation of almost all of the above equations. Hence in application, we fix Poisson's ratio at an acceptable value, either from published data

Figure 1.17: The function U_ρ for $\rho = 1$.

Figure 1.18: The function U_ρ for $\rho = 1.5$.

Figure 1.29: The function U_θ for $\rho = 1$.

Figure 1.20: The function U_θ for $\rho = 1.5$.

or from other experiments, do the required integrations, and vary only the values of the stresses on the half-space to make our synthetic holograms. For the results presented here for the experiments in the oil shale, we set Poisson's ratio at 0.345, from the work of Horino et al. [1982]. The value of Young's modulus (E) used was that determined by in-situ holographic measurements at the site of the stress-relief measurements by Schmitt et al. [1986], a value of 25 GPa.

1.6 Numerical Analysis

Thus the bulk of the work is in evaluating the integrals for u_r^R , u_ζ^R , and u_θ^R (equations 1.20 - 1.22). To do this we need to solve the integral equation 1.5 for $D(\eta)$. First, note that

$$D(0) = \frac{(2 - \alpha)\pi}{8}, \quad (1.38)$$

since at $\eta = 0$, $g(\gamma/\eta) = 0$, $L(\xi, 0) = 0$, and $\eta^6 Y(\eta) = 64/\pi^2$. Then we can determine $D(\eta)$ numerically for some discrete values of η . We will use these values of $D(\eta)$ to interpolate for all other values of η as needed. To allow for more accurate interpolation, we must choose closer spaced values of η in areas where $D(\eta)$ is rapidly varying, i.e., at small values of η , say for η between 0 and 5.

So for N values of η_j , we can approximate

$$D(\eta_j)\eta_j^6 Y(\eta_j) = \frac{8(2 - \alpha)}{\pi} + \sum_{i=1}^N W(\xi_i) D(\xi_i) L(\xi_i, \eta_j), \quad (1.39)$$

$$j = 1, 2, \dots, N. \quad (1.40)$$

Take the $\xi_i = \eta_i$ (i.e., use the same set of values). $W(\xi_i)$ are the weighting factors for the integration scheme used. Writing this in matrix form, we have:

$$[\eta_i^6 Y(\eta_i) \delta_{ij}] \{D(\eta_i)\} = \left\{ \frac{8(2 - \alpha)}{\pi} \right\} + [W(\xi_i) L(\xi_i, \eta_j)] \{D(\eta_i)\}, \quad (1.41)$$

where $[]$ denotes a matrix of dimension $N \times N$, and $\{ \}$ denotes a column vector of dimension $N \times 1$. The expression δ_{ij} has the value 1 when $i = j$, and is equal to 0

otherwise, so the matrix on the left hand side of equation 1.42 is diagonal. We can rewrite the above equation as:

$$0 = \frac{8(2-\alpha)}{\pi} + \left([W(\xi_i)L(\xi_i, \eta_j)] - [\eta_i^6 Y(\eta_i)\delta_{ij}] \right) \{D(\eta_i)\}. \quad (1.42)$$

Now we have a system of N simultaneous equations that can be solved for the $D(\eta_i)$. To determine the values (the entries in the matrix to be inverted), we must obtain the values of $L(\xi, \eta)$ at the ξ_i and η_i 's. We can take advantage of the symmetry $L(\xi, \eta) = L(\eta, \xi)$ to reduce our work somewhat, but the convergence of the integrand is slow; it is hard to find a value γ_0 for which $\int_0^{\gamma_0} F(\gamma)d\gamma$ is a reasonable approximation of $\int_0^\infty F(\gamma)d\gamma$. Therefore the technique used is as follows: We can rewrite equation 1.24 as:

$$\begin{aligned} L(\xi, \eta) = & -\frac{32}{\pi_3} \int_0^\infty g\left(\frac{\gamma}{\xi}\right)g\left(\frac{\gamma}{\eta}\right) \left\{ F_1(\gamma) + [g\left(\frac{\gamma}{\xi}\right) + g\left(\frac{\gamma}{\eta}\right)]F_2(\gamma) \right. \\ & \left. + g\left(\frac{\gamma}{\xi}\right)g\left(\frac{\gamma}{\eta}\right)F_3(\gamma) \right\} d\gamma, \end{aligned} \quad (1.43)$$

where

$$F_1(\gamma, \alpha) = -\alpha\gamma^2 f_1(\gamma, \alpha)/\Delta(\gamma), \quad (1.44)$$

$$F_2(\gamma, \alpha) = -2\alpha\gamma^2 K(\gamma)f_2(\gamma)/\Delta(\gamma), \quad (1.45)$$

$$F_3(\gamma, \alpha) = -\gamma^2 K^2(\gamma)f_3(\gamma)/\Delta(\gamma). \quad (1.46)$$

From the asymptotic expansions of the Bessel functions K_2, K_2', Y_2, Y_2' [Abramowitz and Stegun, 1965], we can derive asymptotic expansions for $K(\gamma)$ and the functions f_1, f_2, f_3, f_4 :

$$K(\gamma) \sim -\gamma - \frac{1}{2} - \frac{15}{8\gamma} - \frac{15}{8\gamma^2} - \frac{135}{128\gamma^3} - \frac{45}{32\gamma^4} + \frac{7425}{1024\gamma^5}, \quad (1.47)$$

$$\begin{aligned} f_1(\gamma, \alpha) \sim & -\gamma^3 + 3\alpha\gamma^2 + \frac{(24\alpha + 15)\gamma}{8} + \frac{48\alpha - 15}{4} \\ & + \frac{-720\alpha + 405}{128\gamma} + \frac{90\alpha + 45}{8\gamma^2}, \end{aligned} \quad (1.48)$$

$$f_2(\gamma) \sim \gamma^3 + \frac{3}{2}\gamma^2 + \frac{39\gamma}{8} - \frac{3}{8} + \frac{855}{128\gamma} - \frac{135}{32\gamma^2}, \quad (1.49)$$

$$f_3(\gamma) \sim \gamma^4 + 2\gamma^3 + 9\gamma^2 + \frac{15\gamma}{4} + \frac{33}{4} + \frac{135}{64\gamma} + \frac{45}{16\gamma^2}, \quad (1.50)$$

$$f_4(\gamma, \alpha) \sim \gamma^4 + (1 - \alpha) + \frac{(15 - 3\alpha)\gamma^2}{2} + \frac{(15 - 63\alpha)\gamma}{8} + \frac{81 - 9\alpha}{8} + \frac{135 - 1575\alpha}{128\gamma} + \frac{45 + 315\alpha}{32\gamma^2}. \quad (1.51)$$

Polynomial multiplication of the above equations gives the expansions for the functions F_1, F_2, F_3 :

$$F_1(\gamma, \alpha) = -\alpha + \frac{2\alpha(2\alpha + 1)}{\gamma} + \frac{\alpha(-4\alpha^2 + 8\alpha + 5)}{\gamma^2} + \dots, \quad (1.52)$$

$$F_2(\gamma, \alpha) = -2\alpha\gamma + 2\alpha^2 + \frac{\alpha}{4\gamma}(-8\alpha^2 + 8\alpha - 3) + \dots, \quad (1.53)$$

$$F_3(\gamma, \alpha) = \gamma^3 + (-\alpha + 1)\gamma^2 + \frac{(8\alpha^2 - 16\alpha + 47)\gamma}{8} + \frac{1}{4}(-4\alpha^3 + 12\alpha^2 - 3\alpha + 15) + \frac{128\alpha^4 - 512\alpha^3 - 432\alpha^2 + 480\alpha + 1815}{128\gamma} + \dots \quad (1.54)$$

Now define the functions $F_1^0(\gamma), F_2^0(\gamma), F_3^0(\gamma)$ to contain the first terms of the asymptotic expansions above, i.e.,

$$F_1^0(\gamma, \alpha) = -\alpha, \quad (1.55)$$

$$F_2^0(\gamma, \alpha) = -2\alpha\gamma + 2\alpha^2, \quad (1.56)$$

$$F_3^0(\gamma, \alpha) = \gamma^3 + (1 - \alpha)\gamma^2 + \frac{\gamma}{8}(8\alpha^2 - 16\alpha + 47) + \frac{1}{4}(-4\alpha^3 + 12\alpha^2 - 3\alpha + 5), \quad (1.57)$$

and let $\tilde{F}_i = F_i - F_i^0$ for $i = 1, 2, 3$. We can express the $\tilde{F}_i$ as power series whose coefficients depend on α :

$$\tilde{F}_i(\gamma, \alpha) \sim \sum_{n=1}^N \frac{a_{in}(\alpha)}{\gamma^n}. \quad (1.58)$$

Youngdahl and Sternberg [1965] give coefficients for the cases of $\alpha = 1$ and 1.5 (corresponding to values of Poisson's ratio of 0.5 and 0.25, respectively). However,

since we are interested in examining the solutions for a broader range of Poisson's ratio, we derived the general expressions for the coefficients $a_{in}(\alpha)$:

$$a_{11} = 2(2\alpha + 1), \quad (1.59)$$

$$a_{12} = -4\alpha^2 - 4\alpha + 5, \quad (1.60)$$

$$a_{13} = (16\alpha^3 - 66\alpha - 91)/4, \quad (1.61)$$

$$a_{14} = (-16\alpha^4 + 16\alpha^3 + 180\alpha^2 + 172\alpha + 17)/4, \quad (1.62)$$

$$a_{15} = (256\alpha^5 - 512\alpha^4 - 4448\alpha^3 - 3328\alpha^2 + 8366\alpha + 11303)/64, \quad (1.63)$$

$$a_{16} = (-64\alpha^6 + 192\alpha^5 + 1440\alpha^4 + 128\alpha^3 - 7176\alpha^2 - 11484\alpha - 5491)/16, \quad (1.64)$$

$$a_{17} = (2048\alpha^7 - 8192\alpha^6 - 54528\alpha^5 + 43520\alpha^4 + 4 + 486832\alpha^3 + 701952\alpha^2 + 70334\alpha - 383825)/512, \quad (1.65)$$

$$a_{18} = (-64\alpha^8 + 320\alpha^7 + 1904\alpha^6 - 3568\alpha^5 - 24964\alpha^4 - 25504\alpha^3 + 38399\alpha^2 + 105122\alpha + 63983\alpha)/16, \quad (1.66)$$

$$a_{21} = (-8\alpha^2 + 8\alpha - 3)/4, \quad (1.67)$$

$$a_{22} = (4 - \alpha^3 - \alpha^2 - 23\alpha + 6)/2, \quad (1.68)$$

$$a_{23} = (-128\alpha^4 + 384\alpha^3 + 1392\alpha^2 - 112\alpha - 2367)/64, \quad (1.69)$$

$$a_{24} = (16\alpha^5 - 64\alpha^4 - 240\alpha^3 + 200\alpha^2 + 934\alpha + 837)/8, \quad (1.70)$$

$$a_{25} = (-1024\alpha^6 + 5120\alpha^5 + 18560\alpha^4 - 36224\alpha^3 - 139928\alpha^2 - 112616\alpha + 11061)/512, \quad (1.71)$$

$$a_{26} = (64\alpha^7 - 384\alpha^6 - 1296\alpha^5 + 4384\alpha^4 + 15036\alpha^3 + 5724\alpha^2 - 20675\alpha - 27891)/32, \quad (1.72)$$

$$a_{31} = (128\alpha^4 - 512\alpha^3 - 432\alpha^2 + 480\alpha + 1815)/(128\alpha), \quad (1.73)$$

$$a_{32} = (-16\alpha^5 + 80\alpha^4 + 104\alpha^3 - 240\alpha^2 - 294\alpha - 375)/(16\alpha), \quad (1.74)$$

$$a_{33} = (1024\alpha^6 - 6144\alpha^5 - 8832\alpha^4 + 37376\alpha^3 + 55512\alpha^2 + 27216\alpha + 23535) / (1024\alpha), \quad (1.75)$$

$$a_{34} = (-64\alpha^7 + 446\alpha^6 + 624\alpha^5 - 4304\alpha^4 - 6676\alpha^3 + 1080\alpha^2 + 5103\alpha + 3240) / (64\alpha). \quad (1.76)$$

Now we can recast equation 1.24 as:

$$L(\xi, \eta) = \frac{32}{\pi^3} [L^0(\xi, \eta,) + \tilde{L}(\xi, \eta, \gamma_0) + \tilde{\tilde{L}}(\xi, \eta, \gamma_0)], \quad (1.77)$$

where

$$L^0(\xi, \eta) = \int_0^\infty g\left(\frac{\gamma}{\eta}\right)g\left(\frac{\gamma}{\xi}\right) \left\{ F_1^0(\gamma, \alpha) + [g\left(\frac{\gamma}{\eta}\right) + g\left(\frac{\gamma}{\xi}\right)] F_2^0(\gamma, \alpha) + g\left(\frac{\gamma}{\eta}\right)g\left(\frac{\gamma}{\xi}\right) F_3^0(\gamma, \alpha) \right\} d\gamma, \quad (1.78)$$

$$\tilde{L}(\xi, \eta, \gamma_0) = \int_0^{\gamma_0} g\left(\frac{\gamma}{\eta}\right)g\left(\frac{\gamma}{\xi}\right) \left\{ \tilde{F}_1(\gamma, \alpha) + [g\left(\frac{\gamma}{\eta}\right) + g\left(\frac{\gamma}{\xi}\right)] \tilde{F}_2(\gamma, \alpha) + g\left(\frac{\gamma}{\eta}\right)g\left(\frac{\gamma}{\xi}\right) \tilde{F}_3(\gamma, \alpha) \right\} d\gamma, \quad (1.79)$$

$$\tilde{\tilde{L}}(\xi, \eta, \gamma_0) = \int_{\gamma_0}^\infty g\left(\frac{\gamma}{\eta}\right)g\left(\frac{\gamma}{\xi}\right) \left\{ \tilde{\tilde{F}}_1(\gamma, \alpha) + [g\left(\frac{\gamma}{\eta}\right) + g\left(\frac{\gamma}{\xi}\right)] \tilde{\tilde{F}}_2(\gamma, \alpha) + g\left(\frac{\gamma}{\eta}\right)g\left(\frac{\gamma}{\xi}\right) \tilde{\tilde{F}}_3(\gamma, \alpha) \right\} d\gamma. \quad (1.80)$$

The equation 1.78 is integrable in closed form, yielding, for $\xi \neq \eta$,

$$L^0(\xi, \eta) = \frac{\pi}{16}(-4\alpha^3 + 36\alpha^2 - 11\alpha - 15) \frac{\xi\eta}{\xi + \eta} + \frac{\pi}{16}(-4\alpha^3 + 12\alpha^2 - 3\alpha - 15) \frac{\xi^2\eta^2}{(\xi + \eta)^2} + \frac{\pi}{4}(1 - \alpha) \frac{\xi^3\eta^3}{(\xi + \eta)^3} - 2\alpha Q(\xi, \eta) \quad (1.81)$$

$$+ \frac{1}{16}(8\alpha^2 - 16\alpha + 47) \frac{\xi^2\eta^2}{(\xi^2 - \eta^2)^2} [\xi^2 + \eta^2 - 4Q(\xi, \eta)] + \frac{\xi^2\eta^2}{(\xi^2 - \eta^2)^2} [(\xi^2 + \eta^2)Q(\xi, \eta) - \xi^2\eta^2], \quad (1.82)$$

where

$$Q(\xi, \eta) = \frac{\xi^2 \eta^2}{\xi^2 - \eta^2} \log\left(\frac{\xi}{\eta}\right). \quad (1.83)$$

For the case $\xi = \eta$, we have

$$\begin{aligned} L^0(\eta, \eta) &= \frac{\pi}{128}(-20\alpha^3 + 156\alpha^2 - 47\alpha - 75)\eta \\ &\quad + \frac{1}{48}(8\alpha^2 - 64\alpha + 47)\eta^2 \\ &\quad + \frac{\pi}{32}(1 - \alpha)\eta^3 + \frac{1}{12}\eta^4. \end{aligned} \quad (1.84)$$

Equation 1.80 may be approximated by substitution of the asymptotic expansions for the $\tilde{F}_i$, equation 1.58, and integrating the resulting power series. This gives, for $\xi \neq \eta$:

$$\begin{aligned} \tilde{L}(\xi, \eta, \gamma_0) &= \frac{\xi^2 \eta^2}{\xi^2 - \eta^2} \left\{ \sum_{n=1}^8 \frac{a_{1n}(\alpha)}{\gamma_0^{n+1}} [-H_n(\frac{\xi}{\gamma_0}) + H_n(\frac{\eta}{\gamma_0})] \right. \\ &\quad + \frac{1}{2\gamma_0} \tilde{F}_2(\gamma_0, \alpha) [g(\frac{\xi}{\gamma_0}) - g(\frac{\eta}{\gamma_0})] \\ &\quad + \sum_{n=1}^6 \frac{(n+3)a_{2n}(\alpha)}{2\gamma_0^{n+1}} [-H_n(\frac{\xi}{\gamma_0}) + H_n(\frac{\eta}{\gamma_0})] \Big\} \\ &\quad + \frac{\xi^4 \eta^4}{(\xi^2 - \eta^2)^3} \sum_{n=1}^4 \frac{2a_{3n}(\alpha)}{\gamma_0^{n+1}} [H_n(\frac{\xi}{\gamma_0}) - H_n(\frac{\eta}{\gamma_0})] \\ &\quad + \frac{\xi^2 \eta^2}{(\xi^2 - \eta^2)^2} \left\{ -\frac{1}{2\gamma_0} \tilde{F}_3(\gamma_0, \alpha) [\eta^2 g(\frac{\xi}{\gamma_0}) + \xi^2 g(\frac{\eta}{\gamma_0})] \right. \\ &\quad + \sum_{n=1}^4 \frac{(n+1)a_{3n}(\alpha)}{2\gamma_0^{n+1}} [\eta^2 H_n(\frac{\xi}{\gamma_0}) + \xi^2 H_n(\frac{\eta}{\gamma_0})] \Big\}. \end{aligned} \quad (1.85)$$

For the case $\xi = \eta$, we have

$$\begin{aligned} \tilde{L}(\eta, \eta, \gamma_0) &= -\frac{\gamma_0}{2} \tilde{F}_1(\gamma_0, \alpha) g(\frac{\gamma_0}{\eta}) + \eta^2 \sum_{n=1}^8 \frac{(n+1)a_{1n}(\alpha)}{2\gamma_0^{n+1}} H_n(\frac{\eta}{\gamma_0}) \\ &\quad - \frac{\gamma_0}{2} \tilde{F}_2(\gamma_0, \alpha) g^2(\frac{\gamma_0}{\eta}) - g(\frac{\gamma_0}{\eta}) \sum_{n=1}^6 \frac{(n+3)a_{2n}(\alpha)}{4\gamma_0^{n+1}} \\ &\quad + \eta^2 \sum_{n=1}^6 \frac{(n+1)(n+3)a_{2n}(\alpha)}{4\gamma_0^{n+1}} H_n(\frac{\eta}{\gamma_0}) \end{aligned}$$

$$\begin{aligned}
& -\frac{\gamma_0}{6} \tilde{F}_3(\gamma_0, \alpha) \sum_{n=1}^4 \frac{(n+3)(n+5)a_{3n}(\alpha)}{48\gamma_0^{n-1}} \\
& -g\left(\frac{\gamma_0}{\eta}\right) \sum_{n=1}^4 \frac{(n+3)(n+5)a_{3n}(\alpha)}{48\gamma_0^{n-1}} \\
& +\eta^2 \sum_{n=1}^4 \frac{(n+1)(n+3)(n+5)a_{3n}(\alpha)}{48\gamma_0^{n+1}} H_n\left(\frac{\eta}{\gamma_0}\right), \tag{1.86}
\end{aligned}$$

where

$$\begin{aligned}
H_{2j+1}(x) &= -\frac{(-1)^j}{x^{2j+2}} \left[\frac{1}{2} \log(1+x^2) + \sum_{i=1}^j \frac{(-1)^i x^{2i}}{2i} \right], \tag{1.87} \\
j &= 0, 1, 2, \dots,
\end{aligned}$$

$$\begin{aligned}
H_{2j}(x) &= \frac{(-1)^j}{x^{2j+1}} \left[\arctan x + \sum_{i=1}^j \frac{(-1)^i x^{2i-1}}{2i-1} \right], \tag{1.88} \\
j &= 1, 2, 3, \dots,
\end{aligned}$$

$$\int_0^\infty F(\gamma) d\gamma = \int_0^\infty F^0(\gamma) d\gamma + \int_0^\infty \tilde{F}(\gamma) d\gamma. \tag{1.89}$$

The function $\tilde{L}(\xi, \eta, \gamma_0)$ (equation 1.79) was integrated numerically for values of ξ from 0.25 to 2000. (Since $g(\gamma/\eta) = 0$ when $\eta = 0$, $L(\xi, 0) = 0$.) Figures 1.22 and 1.23 show $L(0.25, \eta)$ and $L(1.0, \eta)$ respectively. The sum of $L, \tilde{L}, \tilde{\tilde{L}}$ was then used in the matrix equation 1.42 to determine the vector $D(\eta_i)$. The solution was checked against the original equation 1.42 to check its precision. Figure 1.21 shows the function $D(\eta)$ for various values of Poisson's ratio.

Next the functions U_ρ and U_θ (equations 1.34 and 1.35) were evaluated numerically. For large values of the variable of integration γ , the functions $f_1, f_2, f_3, f_4, \Delta$, and Ω were represented by their asymptotic expansions. Near the lower limit of integration $\gamma = 0$, the integrand must be replaced by its limit as $\gamma \rightarrow 0$, since individual terms in the expression blow up. For the integrand of U_ρ , the limit as $\gamma \rightarrow 0$ is $(2 - \alpha)\alpha/\rho$; for U_θ , the limit is $(1 - \alpha)(2 - \alpha)/(2\rho)$.

Once we have the residual displacements $u_r^R, u_\theta^R, u_\zeta^R$ the total displacements may be calculated by adding in the contributions from the plane axisymmetric component

Figure 1.21: The function $D(\eta)$ for various values of Poisson's ratio.

Figure 1.22: The function $L(\xi, \eta)$ for $\xi = 0.25$ for Poisson's ratios from 0.2 to 0.5

Figure 1.23: The function $L(\xi, \eta)$ for $\xi = 1.0$ for Poisson's ratios from 0.2 to 0.5

(equations 1.13 - 1.15) and the pure shear plane strain solution (equations 1.16 - 1.18). Then, subtracting the displacements due to the stressing of an elastic half-space without a hole, we arrive, as before, with the displacements due to the drilling of the stress-relief hole:

$$u_r = \frac{(1 + \nu)a}{E} \left\{ \frac{\sigma_H}{\rho} + \sigma_S \cos 2\phi \left[u_r^R + \frac{2\alpha}{\rho} - \frac{1}{\rho^3} \right] \right\} \quad (1.90)$$

$$u_\theta = -\frac{(1 + \nu)a}{E} \left[-u_\theta^R + \frac{2(\alpha - 1)}{\rho} + \frac{1}{\rho^3} \right] \sin 2\phi \sigma_S \quad (1.91)$$

$$u_\zeta = \frac{(1 + \nu)a}{E} \sigma_S u_\zeta^R \cos 2\phi \quad (1.92)$$

where u_r^R , u_θ^R , and u_ζ^R are the residual components of the solution to the pure shear problem, as defined in equations (1.20 - 1.22), and ϕ is measured from the σ_1 direction. Figures 1.24 - 1.26 show the values of u_r^R , u_θ^R , and u_ζ^R for several values of Poisson's ratio. The importance of the residual term u_ρ^R , etc. is greater for larger Poisson's ratios; in fact, for a Poisson's ratio of 0, all three components of the residual displacements are exactly 0. Thus we would expect to see a greater difference in the fringe patterns of the synthetic holograms from places where the rocks have larger values of this parameter.

1.7 Application

To determine the utility of this technique, it is necessary to know whether using this model will yield any significant improvement in the analysis of the data. To this end, we re-analyzed the holograms that had previously been modeled using the plate theory. For this rock, a dolomitic marlstone, we set the value of Young's modulus at 25 GPa, and used a Poisson's ratio of 0.345 [Horino et al. 1982]. The new model proved to give a better fit to the observed holograms; the results may be seen in figures 1.28 - 1.32. In most cases, the actual values of the stresses obtained by matching the synthetic holograms with the data are not significantly changed;

Figure 1.24: The solution to the residual displacement u_{ρ}^R for various values of Poisson's ratio. The dimensionless values are plotted against the distance from the center of the hole, normalized to the hole radius.

Figure 1.25: The solution to the residual displacement u_{θ}^R for various values of Poisson's ratio. The dimensionless values are plotted against the distance from the center of the hole, normalized to the hole radius.

Figure 1.26: The solution to the residual displacement u_{ζ}^R for various values of Poisson's ratio. The dimensionless values are plotted against the distance from the center of the hole, normalized to the hole radius.

however, the errors associated with each stress determination have been reduced. Figures 1.33 - 1.35 show the magnitude of the stress-relief displacements around the hole, the radial, tangential, and vertical components for both the plate model solution from section 1.3 and for the revised solution from this work. The hologram being modeled here figure is the hologram 16/3/3 of figure 1.32. Figures 1.36 - 1.38 show the displacements predicted by both models for the holograms of figure 1.32. The upper plot in each figure shows the variation of the displacements with radius; distance from the center of the stress-relief hole is here normalized to the radius of the hole. The displacements are those that occur along a line from the center of the hole along the x-axis to the right of the hologram. The diameter of the hole is 0.5 cm. Figure 1.36 shows the radial component of displacement (u_r), which is quite similar in the two models. The real difference between the two models is in the magnitudes of the tangential and vertical components, as can be seen in figures 1.37 and 1.38, respectively. The values of the tangential displacement predicted by the plate model are generally larger than those predicted by the revised model; however, the situation is reversed for the vertical component, which is significantly greater in the revised model. Since, as can be seen in figures 1.33 - 1.35, the azimuthal variation of displacement is different for the tangential and vertical components, any change in the relative magnitude of these components will result in different fringe patterns. Thus a decrease in the magnitude of the tangential component will not be offset directly by an increase in the magnitude of the vertical component.

1.8 Inversion of Data to Obtain Far-field Stresses

The results of both models were inverted to obtain the far-field stresses using equations 1.1 - 1.3. Since the problem is overdetermined, a least squares scheme was used to solve for the six stress components. Equations 1.1 - 1.3 determine the borehole

View north into borehole

Figure 1.27: Orientation of holograms in the pillar borehole. The view into the page is due north.

Plate model

Revised model

Hologram 15/1/4 225 degrees

Figure 1.28: Plate model (left) and revised synthetic holograms for the hologram 15/1/4.

Plate model

Revised model

- 20, 0, 5

Hologram 15/1/8 180 degrees

- 20, 0, 2

Figure 1.29: Plate model (left) and revised synthetic holograms for the hologram 15/1/8.

Figure 1.30: Plate model (left) and revised synthetic holograms for the hologram 16/1/4.

Plate model

Revised model

Hologram 16/2/5 45 degrees

Figure 1.31: Plate model (left) and revised synthetic holograms for the hologram 16/2/5.

Plate model

Revised model

Hologram 16/3/3 0 degrees

Figure 1.32: Plate model (left) and revised synthetic holograms for the hologram 16/3/3.

Figure 1.33: Comparison of the displacement fields for the two models (radial component u_r). The contour interval is $.05 \mu\text{m}$ and dashed lines indicate negative displacements. For this component, contours for displacements greater than $.4 \mu\text{m}$ have been suppressed.

Figure 1.34: Comparison of the displacement fields for the two models (tangential component u_θ). The contour interval is $.05 \mu\text{m}$ and dashed lines indicate negative displacements.

Figure 1.35: Comparison of the displacement fields for the two models (vertical component u_z). The contour interval is $.05 \mu\text{m}$ and dashed lines indicate negative displacements.

Figure 1.36: Radial component of displacements for the plate model (dashed line) and the revised model (solid line). The upper figure shows the displacements along a line from the center of the hole out to a distance of 10 radii at azimuth 0. The lower figure shows the azimuthal variation of the displacements at a distance of two radii from the center of the stress-relief hole. The results are from the hologram 16/3/3.

Figure 1.37: Tangential component of displacements for the plate model (dashed line) and the revised model. The results are from the hologram 16/3/3.

Figure 1.38: Vertical component of displacements for the plate model (dashed line) and the revised model. The results are from the hologram 16/3/3.

wall stresses in terms of the far-field stresses. In matrix form, we can write

$$Ax = b \quad (1.93)$$

Where A is the matrix of coefficients in equations 1.1 - 1.3, x is the 6-component vector containing the values of the far-field stresses, and b is the vector containing the modeled borehole wall stress values. The dimensions of A and b depend on the number of observations. In this case, we had 5 holograms, each with values of the three borehole wall stresses, so A is a 15 x 6 matrix and b is a 15-component vector. We know the values of the components of A and b ; we need to find the best fit x to this overdetermined system. The least squares solution gives us this best fit:

$$x = (A^T A)^{-1} A^T b \quad (1.94)$$

Here A^T is the transpose of the A matrix and A^{-1} is the inverse of A . This solution minimizes the error [Strang 1980]:

$$E^2 = \|Ax - b\|^2 = \sum_{i=1}^n \left\{ \sum_{j=1}^m (A_{ij}x_j) - b_i \right\}^2 \quad (1.95)$$

Due to uncertainties in the borehole wall stresses, a set of calculations were made, varying the borehole wall stresses within the range of their uncertainties; the results are presented in Table 1.8. Of the six components, five are well constrained: four of these have uncertainties of less than 20%; the fifth, the shear stress in the E-W - vertical plane, is shown to be small. Only the normal stress in the N-S direction, parallel to the axis of the borehole, is poorly determined due to wide variations in the observed values of σ_{hh} , the normal stress in the direction along the borehole wall axis. The results show values of about -10 MPa (compressive) in both the vertical and E-W (perpendicular to the axis of the borehole) directions. This vertical normal stress is close to the value -11.2 MPa predicted by the relation

$$\sigma_p = \sigma_v s \quad (1.96)$$

Pillar stresses (in MPa) (plate model)		
σ_{EW}	-10.06	± 0.765
σ_{Vert}	-10.23	± 0.966
σ_{NS}	-2.51	± 2.48
$\tau_{EW-Vert}$	-0.64	± 0.54
τ_{EW-NS}	7.76	± 1.05
$\tau_{NS-Vert}$	-3.64	± 0.71

Table 1.3: Pillar stresses calculated from the values of the borehole wall stresses calculated from the plate model.

where σ_p is the load on the pillar induced by excavations of span s and σ_v is the vertical stress before mine excavation, estimated by mine depth and overburden mass [Brady and Brown 1985, Obert and Duvall 1967]. The values of σ_p predicted by equation 1.96 is, however, an upper bound on the vertical stress in a mine pillar. Rock anisotropy and proximity to the unmined areas can reduce the actual vertical stress in mine pillars [Coates and Ignatieff 1966, Salamon 1974]. This pillar was within 15 meters of the wall of the mine.

The principal stresses and their orientations for these stress components are given in Table 1.4. The maximum principal stress is a compressive stress of -15.35 MPa and is approximately horizontal and in an E-W direction, in the direction perpendicular to the borehole axis. The intermediate stress is nearly vertical, with magnitude -10.68 MPa. The least principal stress is tensile, oriented approximately N-S, along the axis of the borehole. Its magnitude is +3.22 MPa. The small, tensile value of the least principal stress is not surprising, since its orientation is along the axis of the borehole, and since the stress measurements were made near the edge of the pillar face. Measurements in pillars at another mine in the same formation show similar stress regimes, including the presence of a small horizontal tensile stress along the

Principal stresses (in MPa) (Plate model)		
Magnitude	Orientation	Plunge
-15.35	N54°E	17°
-10.68	N83°W	67°
3.22	N31°W	-14°

Table 1.4: Principal stresses, derived from the borehole wall stresses as determined from the plate model.

axis of the borehole in regions near the pillar face [USBM 1973].

The better fit of revised model synthetics to the observed holograms allows for increased precision of the solution for the state of stress acting on the borehole wall at the point of each stress-relief measurement. Tables 1.6 - 1.8 summarize the results of the new analysis. The rigid body translations of the camera module used in these fits are given in table 1.5. The largest principal stress has a magnitude of -11.34 MPa (compressive), close to the predicted value of -11.2 MPa for a pillar of this geometry [Obert and Duvall 1967, Brady and Brown 1985].

The stresses at the five different azimuths at this station, 4 m into the pillar face, may now be used in conjunction with equations (1.1 - 1.3) to obtain the solution for the far-field (in this case, the pillar) state of stress. These results are summarized in Table 1.8. The x -, y -, and z - directions are, respectively, East-West, Up-Down, and North-South. Again, the end result is similar to that obtained with the plate model, but the errors associated with each component of the stress tensor are greatly reduced. This solution yields the principal stresses shown in Table 1.8. Note that there exists a significant off-axis orientation to the stresses, i.e., they are not in-line with the borehole coordinate system. The ability to detect such phenomena is one of the strengths of the holographic method.

Camera module translations (for revised module fits) (μm)			
Hologram	ϕ	h	ζ
15/1/4	3.85	2.2	2.275
15/1/8	1.95	0.9	2.45
16/1/4	3.25	2.85	1.95
16/2/5	-3.525	0.985	4.05
16/3/3	-10.6	1.72	3.5

Table 1.5: Rigid body translations of the camera module for the synthetic holograms modeled by the revised model.

Revised borehole wall stresses (in MPa)							
Hologram	Azimuth	$\sigma_{\phi\phi}$		σ_{hh}		$\tau_{\phi h}$	
16/1/4	90°	-20.0	± 2.0	-5.0	± 4.0	2.0	± 1.5
16/2/5	45°	-12.0	± 2.0	-7.5	± 2.0	-8.5	± 2.0
16/3/3	0°	-21.0	± 1.0	-5.0	± 2.0	-8.0	± 2.0
15/1/8	180°	-20.0	± 2.0	0.0	± 5.0	2.0	± 2.0
15/1/4	225°	-20.0	± 2.0	-5.0	± 4.5	2.0	± 1.5

Table 1.6: Borehole wall stresses as fit by the revised model.

Revised pillar stresses (in MPa)		
σ_{EW}	-10.21	± 0.414
σ_{Vert}	-10.70	± 0.33
σ_{NS}	3.48	± 0.99
$\tau_{EW-Vert}$	0.203	± 0.22
τ_{EW-NS}	0.898	± 0.43
$\tau_{NS-Vert}$	-3.05	± 0.91

Table 1.7: Pillar stresses determined by the revised model.

Principal stresses (in MPa) (revised)		
Magnitude	Orientation	Plunge
-11.45	N55°E	68°
-10.14	E	-18°
4.16	N3°E	12°

Table 1.8: Principal stresses determined by the revised pillar stresses.

1.9 Conclusions

The initial model used to calculate the displacements on the free surface of the borehole wall underestimates the magnitude of the vertical component of displacement and overestimates the tangential component. These two components, while not as significant as the radial component in determining the final fringe pattern, make the accurate modeling of the borehole wall stresses difficult. A two-dimensional finite element analysis suggested that the simple model needed revision. Substitution of the half-space model of Youngdahl and Sternberg for the plate model improved the precision of the determination of the state of stress on the borehole wall and the inversion of these stresses for the far-field state of stress. The greatest part of the work in this new analysis is the numerical calculation of the residual components of displacement u_r^R , u_θ^R , and u_z^R for the appropriate value of Poisson's ratio. These having been obtained, it is easy to generate the displacement field for any state of stress desired, i.e., the new model is no more difficult to use than the old one was. The new model still does not exactly fit the observed fringe patterns, but seems to come closer to the observed state. Therefore in the future, holographic stress analysis will be better served by using the new model.

This method may be applied to techniques other than the holographic stressmeter described above. Any application which involves the measurement of deformation

after drilling a hole into a free surface under stress could use this analysis, assuming the depth of the hole relative to the diameter is greater than unity. Strain gauges could be placed on the surface of a wall or rock face before a hole was drilled. Careful consideration of the placement of the gauges would result in improved estimations of the stresses on the wall or rock face.

Bibliography

- Abramowitz, M. and Stegun, I. *Handbook of Mathematical Functions*, Dover, New York (1965).
- Aggson, J. R. and Kim, K. Analysis of hydraulic fracturing pressure histories: a comparison of five methods used to identify shut-in pressure. *Int. J. Rock Mech. Min. Sci. & Geomech. Abstr.* **24**, 75-80 (1987).
- Azzam, R. and Bock, H. A new modified borehole jack for stiff rock, *Rock Mechanics and Rock Engineering* **20**, 191-211 (1987).
- Bass, J., Schmitt, D. R., and Ahrens, T. J. Holographic in situ stress measurements, *Geophys. J. R. Astr. Soc.* **85**, 13-41 (1986).
- Brady, B. G. H. and Brown, E. T. *Rock Mechanics for Underground Mining*, Allen and Unwin, London (1985).
- Cohn, S. N. Holographic in-situ stress measurement in geophysics, *Ph.D. Thesis*, California Institute of Technology (1983).
- Coates, D. F. and Ignatieff, A. Prediction and measurement of pillar stresses. *Can. Min. J.* **87**, 50-56 (1966).
- Haimson, B. C. The state of stress in the earth's crust. *Rev. Geophys. Space Phys.* **13**, 350-362 (1975).
- Haimson, B. C. and Fairhurst, C. Initiation and extension of hydraulic fractures in rock. *Soc. Petrol. Engrs. J.* **7**, 310-318 (1967).
- Hickman, S. Stress in the lithosphere and the strength of active faults. *Rev. of Geophysics, Supplement*, 759-775 (1991).
- Hiramatsu, Y. and Oka, Y. Stress around a shaft or level excavated in ground with a three-dimensional stress state, *Mem. Fac. Engng, Kyoto*, **24**, 56-76 (1962).

- Horino, F., Dolinar, D. and Tadolini, S. *Mechanical properties of the mahogany zone shale, Garfield County, Colorado*, U.S. Bureau of Mines Internal Report, United States Department of the Interior, Bureau of Mines, Denver (1982).
- Hubbert, M. K. and Willis, D. G. Mechanics of hydraulic fracture. *AIME Trans.* **210**, 153-168 (1957).
- Hughes, T. J. R., Ferencz, R. M. and Raefsky, A. M. DLEARN: A linear static and dynamic finite element analysis program, in *The Finite Element Method: Linear Static and Dynamic Finite Element Analysis*, by Hughes T. J. R. Prentice-Hall, Englewood Cliffs NJ, 631-796 (1987).
- Jaeger, J. C. and Cook, N. G. W. *Fundamentals of Rock Mechanics* Chapman and Hall, London (1979).
- Leeman, E. R. The CSIR doorstopper and triaxial rock stress measuring instruments. *Proc. ISRM Symp. on the Determination of Stresses in Rock Masses*, 578-616, L. N. E. C., Lisbon (1969).
- Leeman, E. and Hayes, D. A technique for determining the complete state of stress in rock using a single borehole, *Proc. 1st Cong. Int. Soc. Rock Mech. Lisbon*, **2**, 17-24 (1966).
- McGarr, A. and Gay, N. C. State of stress in the earth's crust. *A. Rev. Earth Plan. Sci.* **6**, 405-436 (1978).
- McGarr, A., Zoback, M. D. and Hanks, T. C. Implications of an elastic analysis of in situ stress measurements near the San Andreas fault. *J. Geophys. Res.* **87**, 7797-7806 (1982).
- Obert, L. and Duvall, W. I. *Rock Mechanics and the Design of Structures in Rock*. John Wiley & Sons, New York (1967).
- Obert, L., Merrill, R. H. and Morgan, T. A. Borehole deformation for determining the stress in mine rock. *USBM RI 5978* (1962).
- Papkovich, P. F. *Compte rendus hebdomadaires des seances de l'academie des sciences*, Paris **195**, 513-515, 754-756 (1932).
- Richardson, R. M., Solomon, S. C. and Sleep, N. H. Tectonic stress in the plates. *Rev. Geophys. Space Phys.* **17**, 981-1019 (1979).
- Rocha, M., Baptista, Lopes J. and DaSilva, J. A new technique for applying the method of the flatjack in determination of stresses inside rock masses. *Proc. 1st Int. Congr. on Rock Mechanics*, **2**, 57-65, Lisbon (1966).

- Salamon, M. D. G. Rock mechanics of underground excavations, in *Advances in Rock Mechanics, Proc. 3rd Cong. Int. Soc. Rock Mech. IB*, National Academy of Sciences, Washington DC, 951-1099 (1974).
- Schmitt, D. R. Applications of double-exposure holography to the measurement of in situ stress and the elastic moduli of rock from boreholes, *Ph.D. Thesis*, California Institute of Technology (1987).
- Schmitt, D. R., Smither, C. L., Ahrens, T. J., and Jensen, B. Borehole in-situ holographic stress and elastic moduli measurements, *Proc., The Society of Exploration Geophysicists, 56th Annual Meeting*, Houston, 9-12 (1986).
- Schmitt, D. R., Smither, C. L., Ahrens, T. J. and Jensen, B. Holographic measurement of elastic moduli, *Rock Mechanics: Key to Energy Production, Proc. 27th US Symp. Rock Mechanics*, Society of Mining Engineers, Littleton, CO, 185-191 (1986).
- Simonsen, E. R., Abou-Sayed, A. S. and Clifton, R. J. Containment of massive hydraulic fractures. *Soc. Petrol. Eng.* **18** (1978).
- Smither, C. L., Schmitt, D. R., and Ahrens, T. J. Holographic in situ measurements I: Borehole measurements of in situ stress, *EOS, Trans. Am. Geophys. Un.* **68**, 1460 (1987).
- Smither, C. L., Schmitt, D. R. and Ahrens, T. J. Analysis and modelling of holographic measurements of in situ stress, *Int. J. Rock Mech. Min. Sci. & Geomech. Abstr.* **25**, 353-362 (1988).
- Sokolonikoff, I. S. *Mathematical Theory of Elasticity*, McGraw Hill, New York p. 331 (1956).
- Strang, G. *Linear Algebra and Its Applications*, Academic Press, New York (1980).
- Timoshenko, S. and Goodier, J. *Theory of Elasticity*, McGraw-Hill, New York (1970).
- U. S. Bureau of Mines. Rock Mechanics instrumentation for mine design; *Proceedings, Bureau of Mines Technology Transfer Seminar*, Washington, DC. USBM IC 8785 (1973).
- Vest, C. M. *Holographic Interferometry* John Wiley & Sons, New York (1979).
- Wang, Y. and Wong, T.-F. Finite element analysis of two overcoring techniques for in situ stress measurement. *Int. J. Rock Mech. Min. Sci. & Geomech. Abstr.* **24**, 41-52 (1987).

- Wareham, B. F. and Skipp, V. O. The use of the flatjack installed in a saw-cut slot in the measurement of in situ stress. *Proc. 3rd Int. Cong. on Rock Mechanics*, **2A**, 481-488, Denver (1974).
- Youngdahl, C. K. and Sternberg, E. Three-dimensional stress concentration around a cylindrical hole in a semi-infinite elastic body, *Research and Development Report*, Argonne National Laboratory, Argonne, IL ANL 7097 (1965).
- Youngdahl, C. K. and Sternberg, E. Three-dimensional stress concentration around a cylindrical hole in a semi-infinite elastic body, *J. Appl. Mech.* **33**, 855-865 (1966).

END

**DATE
FILMED**

7 / 2 / 92