DOE/ER/25024-2
(FINAL)

DOE grant: Mathematical Software for ODEs

DOE/ER/25024--2

Principal Investigator: L. F. Shampine

DE92 010660

Final Technical Report:

For a period of two years, the grant funded two months of research by the principal investigator (PI) each summer and supported his research throughout the year by partially funding a graduate assistant and by funding computing, travel, and publication costs related to the grant. This research formed part of a program involving the PI and a number of collaborators with independent funding. By chance, every one of the collaborators mentioned in the grant proposal changed his or her job after the grant started. In some cases this ended, or greatly reduced, collaboration, but in the case of Ian Gladwell, who left the University of Manchester, U. K., to join the PI's institution, this enhanced greatly the planned collaboration. Because of these unanticipated developments, the PI did not need all the funds requested for travel.

The grant helped make possible a program of research that was quite productive. Results partially funded by the grant were made generally available in nine papers published (or still in press) in journals and books. Four other papers are in various stages of the refereeing process, and two more are being written. Many of these results were also disseminated by means of reports. In most cases the reports were early versions of papers, but one report was never intended for journal publication. Details about the papers and reports are provided below. Another way of making research results generally available is by means of talks. As it turned out, the principal investigator was invited to address the most important meeting of the year in his specialty in each of 1987, 1988, and 1989. In addition, he spoke on seven other occasions. Some details are provided below. Several collaborators gave a number of talks about joint work; because they received no direct support from the grant, no details are reported. Some mathematical software was partially supported by the grant. Codes for the event location problem are being made widely available in source form in a report, by means of a computer network, and through a non-profit organization that provides a library of mathematical software. A "new generation" of Runge-Kutta codes is far advanced. They will be made available in the same way. In addition, the PI will spend a research/study leave writing a book about the numerical solution of the initial value problem for systems of ordinary differential equations. He will acknowledge DOE support of some of the research that will appear there. In particular, the new Runge-Kutta codes will appear in the book so that they can serve as examples of current research (in addition to making generally available superior software for the solution of the initial value problem).

The number of projects investigated precludes providing much detail about them all. Instead, some detail will be provided about certain major efforts. One such effort concerns "interpolation" for Runge-Kutta methods. Runge-Kutta methods are much more expensive per step than alternatives such as multistep methods, but the step sizes they use are so much bigger that they compete well. If the codes are not permitted to use as big a step size as possible, they are relatively inefficient. The most common reason for such a restriction is a request for answers at specific points because Runge-Kutta methods produce answers only at the end of a step. In contrast, multistep methods like Adams and BDF are based on an interpolating polynomial, and they merely evaluate the polynomial to obtain an answer anywhere in the span of a step. An important task associated with differential equations is to

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

MASTER

find where an event occurs. Runge-Kutta codes can be extremely inefficient for this task because the code must search for the location of an event, producing approximate solutions at each trial point. How to provide an interpolation capability for Runge-Kutta methods has been the subject of intense study by workers in the field. The PI made important early contributions to this matter, and he has continued to make contributions with collaborators like Gladwell and Brankin and with his student P. Bogacki. During the period of the grant the PI and Bogacki have worked on the basic task when both crude and stringent accuracies are requested. At crude tolerances a low order formula is appropriate, and qualitative properties such as monotonicity and convexity of the interpolant are crucial. At stringent tolerances the difficulty is getting an interpolant of high order accuracy at a reasonable cost. A new way of accomplishing this has been proposed. The new capability of interpolating with Runge-Kutta provides opportunities for progress with other tasks, some of which are mentioned below.

A major effort has been devoted to the event location problem. This work, joint with I. Gladwell and R. W. Brankin, is concerned with the integration of an ODE until an event occurs. The task is to determine reliably and efficiently if, and when, an event occurs. There are severe difficulties in both theory and practice. Difficulties of the most fundamental nature are that in general, it is not possible to be certain that one even notices that an event has occurred, and that if an event has been noticed, it is not possible to be sure that the first event is discovered. The PI discovered that for special kinds of events of great practical value, both these difficulties can be overcome, at least in principle. The problems can be quite ill-conditioned, and as a consequence, an event may be located poorly. A way was devised to estimate the accuracy of the location of an event so that users can appraise the accuracy of solution. Software has been prepared implementing the theory. A novel software development is to provide a coroutine that can be used with unaltered versions of popular codes so that they can solve event location problems. Addition of the capability to the Gear line of BDF codes for the solution of stiff initial value problems, Shampine and Gordon's PECE Adams code, and one of the new Runge-Kutta codes with interpolation has been demonstrated.

A number of investigations were concerned with starting an integration. The algorithms for the estimation of the local error and the adjustment of the step size are fundamental to all modern codes for the initial value problem. For these algorithms to be reliable, the step size must be "small enough," and it must change slowly from step to step. The start is critical because somehow a step that is "on scale" must be found. At first users were asked to guess a suitable value. This is not just a great inconvenience, users simply do not have the information at their disposal to do a good job. The PI and his collaborator I. Gladwell made the earliest contributions to the automatic determination of an "on scale" initial step size. Along with a student, R. Brankin, they have considerably increased the reliability of automatic starting procedures. Their approach combines the best elements of previous work with the new idea of estimating (for "free") the Lipschitz constant L and insisting that the step size h be constrained so that hL is bounded in an appropriate way.

Multistep methods are appealing because they exploit previously computed solution values to achieve high accuracy with little work. But where do these "previously

computed" values come from at the start of the integration? When the first variable order, variable step size codes were written, it was realized that there was an easy answer to this question: Just take the first step with a method of order 1 that requires no previously computed values, and let the algorithms for adjustment of step size and order deal with the task of getting up to "optimal" values. Not only is this an easy thing to do in the code, it is usually very effective in practice. The most popular codes based on the Adams methods for non-stiff problems and the BDF for stiff problems start themselves in this way. There is a general impression that all the basic issues in the solution of the initial value problem are understood. In the case of codes that vary their order, this is false. In particular, what is going on in the start has been a complete mystery. The PI and a student, W. Zhang, have now developed a theory for the start as performed in important codes. This new understanding reveals that some of the things done in the codes are incorrect, some work for a reason different than what was believed, and some can be improved. A fundamental issue in starting a code by variation of step size and order is the recognition of the optimal order. What theory exists for the selection of order makes very strong assumptions. They are probably not true of many computations, and they are certainly not true when starting in the way described. The PI and Zhang have shown analytically and by example that one widely used approach for selecting the "optimal" order in the start is incorrect. They have proposed an approach that is rather similar in its mechanics to the usual one, but has the advantage that it can be proven to be correct. The approach is being implemented as a piece of mathematical software appropriate for insertion in popular Adams and BDF codes.

Starting a multistep code by variation of step size and order is easy, but it is not obviously the best way to get started. Besides the theoretical difficulties, the procedure is not always efficient. In fact, many popular BDF codes can be grossly inefficient in the start because of the way they evaluate these implicit formulas. Solving the algebraic equations by a simplified Newton method is expensive because a Jacobian matrix must be formed, usually by finite differences, an iteration matrix formed and decomposed, and several linear systems solved at each step. The Newton method is necessary when the step size is determined by stability, as is usually the case when solving stiff problems, but a waste of effort when the step size is determined by accuracy. In the start phase the step size is virtually always determined by accuracy due to an initial transient where the solution changes very rapidly. Starting at order 1 in these circumstances is also very inefficient. Indeed, if there is any time in the integration of a stiff problem when high order is likely to be beneficial, it is during the initial transient. Building upon earlier work on the automatic selection of an initial step size and on interpolation for Runge-Kutta formulas, the PI and his collaborators have devised a way to determine the optimal order and to obtain the "previously computed" data need to start at this order. The first step is actually taken with one of the new Runge-Kutta formulas with interpolation. By taking as large a step as possible with this formula of moderate order, the start is made both more robust and more efficient. The starting procedure has proved to be quite effective in the Gear line of codes for both stiff and non-stiff problems. An interesting aspect of this work is that by using previous fundamental work of the PI on interpolation for Runge-Kutta formulas, it is easy to justify the selection of the optimal order .

Papers and Reports:

Control of step size and order in extrapolation codes, L. F. Shampine, J. Comp. Appl. Math., 18 (1987) 3 - 16.

Automatic selection of the initial step size for an ODE solver, I. Gladwell, L. F. Shampine, and R. W. Brankin, J. Comp. Appl. Math., 18 (1987) 175 - 192.

Interpolation with variable order Runge-Kutta methods, L. F. Shampine, Comp. & Maths. with Applics., 14 (1987) 255 - 260.

Starting variable order Adams and BDF codes, L. F. Shampine, Appl. Num. Math., 3 (1987) 331 - 337.

Reliable solution of special event location problems for ODEs, L. F. Shampine, I. Gladwell, and R. W. Brankin, Num. Anal. Rept. 138, Math. Dept., Univ. of Manchester, U. K., 1988.

Codes for the reliable solution of special event location problems for ODEs, R. W. Brankin, I. Gladwell, and L. F. Shampine, Num. Anal. Rept. 139, Math. Dept., Univ. of Manchester, U. K., 1988.

Locating special events when solving ODEs, I. Gladwell, L. F. Shampine, and R. W. Brankin, Appl. Math. Letters, 1 (1988) 153 - 156.

Efficient integration of ODEs by transformation, L. F. Shampine and W. Zhang, Comp. & Maths. with Applics., 15 (1988) 213 - 220.

Starting BDF and Adams codes at optimal order, R. W. Brankin, I. Gladwell, and L. F. Shampine, J. Comp. Appl. Math., 21 (1988) 357 - 368.

Diagnosing stiffness for Runge-Kutta methods, L. F. Shampine, Rept. 88-8, Math. Dept., Southern Methodist University, Dallas, 1988.

The next generation of Runge-Kutta codes, L. F. Shampine and I. Gladwell, Rept. 89-10, Math. Dept., Southern Methodist University, Dallas, 1989.

Tolerance proportionality in ODE codes, L. F. Shampine, Proc. Workshop on Num. Meth. for ODEs held in L'Acquila, Italy, Sept., 1987, to appear. (Has appeared as Rept. 87-8, Math. Dept., Southern Methodist University, Dallas, 1987.)

The effect of changing the step size in linear multistep codes, L. F. Shampine and P. Bogacki, SIAM J. Sci., Stat. Comp., to appear.

Convergence of LMM when the solution is not smooth, L. F. Shampine and W. Zhang, Comp. & Maths. with Applics., to appear.

A 3(2) pair of Runge-Kutta formulas, P. Bogacki and L. F. Shampine, Appl. Math.

Letters, to appear.

Papers submitted or in preparation:

Reliable solution of special event location problems for ODEs, L. F. Shampine, I. Gladwell, and R. W. Brankin, being revised for ACM Trans. Math. Soft.

Diagnosing stiffness for Runge-Kutta methods, L. F. Shampine, being revised for SIAM J. Sci., Stat. Comp.

The next generation of Runge-Kutta codes, L. F. Shampine and I. Gladwell, submitted for Proceedings of IMA Conference on Computational Ordinary Differential Equations, London, July, 1989.

Rate of convergence of multistep codes started by variation of order and step size, L. F. Shampine and W. Zhang, submitted to SIAM J. Numer. Anal.

Interpolating high order Runge-Kutta formulas, P. Bogacki and L. F. Shampine, in preparation.

Starting multistep codes at optimal order, W. Zhang and L. F. Shampine, in preparation.

Presentations:

The progress described was presented in a number of talks. The most important were two invited talks presented to a Workshop on Numerical Methods for ODEs held in L'Acquila, Italy in 1987, an invited address to the 1988 Conference on IVPs for ODEs held in Toronto, Canada, and an invited address to the IMA Conference on Computational Ordinary Differential Equations held in London in 1989. Also important were an invited address to a regional SIAM meeting at the University of Texas at Austin, and an invited talk at a special session on numerical analysis at a regional AMS meeting at North Texas State University. Colloquia were given at Southern Methodist University, the University of Texas at Arlington, Trinity University, the University of Texas at Dallas, and Rice University.

DATE
FILMED
5/20/92