FINAL REPORT

THERMALHYDRAULIC ASPECTS OF DECAY HEAT REMOVAL BY NATURAL
CIRCULATION IN FAST REACTOR SYSTEMS

(Contract No. DE-FG07-88ER12816)

DOE/ER/12816--T1

DE92 013729

Chandra M. Roy
Gad Hetsroni
Sanjoy Banerjee

Department of Chemical and Nuclear Engineering
University of California
Santa Barbara, CA 93106

Prepared for:

U.S. Department of Energy
Idaho Operations Office
Contracts Management Division
785 DOE Place
Idaho Falls, Idaho 83402

ATTN: David M. Woodall
Project Officer

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

Natural convection in enclosures have been studied numerically to provide insight into the scaling laws existing for removal of decay heat in Liquid Metal Fast Reactors (LMFR). Specifically, 3-D simulations have been carried out for natural circulation in a cylinder with small aspect ratio (of the order of 0.5). These results have been compared to the results of an experiment conducted by UCSB, in collaboration with GE, to provide benchmark data for code validation. Parametric studies have been conducted to establish the validity of a 3-D Finite difference code that uses body-fitted grids for simulations of complex geometries. Further, numerical simulations have been carried out to demonstrate the importance of 3-D computer codes as tools in the design and scale-up of prototypic LMFRs. It has ben shown that the geometry of the passive safety systems is key to safe operation of LMFRs under shutdown conditions. The key phenomena that occur in such situations have been studied and the available experimental studies have been identified. The future direction for modeling of natural convection recirculating flows in confined enclosures has been proposed.

INTRODUCTION

In the advanced concepts of Fast Reactors "passive safety systems" have been proposed to ensure removal of decay heat under shutdown conditions even in the absence of forced flow or operator intervention. These are natural convection heat removal systems and may be seen in the PRISM reactor of GE, shown in fig.1 and in the SAFR reactor of Rockwell, shown in fig. 2. Experiments on a prototype would be exorbitantly expensive, hence in order to design and verify the efficacy of such "passive safety systems" one must have a proven design tool. Very little pertinent phenomenologic experimental evidence had been available in the past, and even the supercomputers of today are not large enough, or fast enough, to simulate a full scale LMFR, from first principles. Thus currently problem-specific computer models are being used to scale up experimental results acquired on small-scale setups, designed to simulate an LMFR, to the full-scale. Such a practice, especially in the face of an incomplete understanding of the basic physics of the situation, is fraught with uncertainties, because the full range of similitude parameters have not yet been explored.

The motivation for this research comes from the importance given to the concept of "inherent safety" for the LMFR. Most experimental investigations have revealed the presence of stratification and the possibility of more complex adverse flow regimes, such as recirculation in the core (Modi & Torrance, 1987) or stagnation in the cold pool. Experimental studies have shown the existence of striping at the interface of thermal stratification (Fujimoto et al., 1981). Such striping induces thermal stresses in the structures. Stagnation in the cold pool and recirculation in the core may both cause heatup of the core, the former if a layer of cold fluid became unavailable for recirculation. Then there are regions in the reactor where stratification may be beneficial, for example close to the redan it would reduce temperature gradients and hence reduce thermal stresses. Some studies (Kenworthy et al., 1984) have suggested that stratified sodium layers in an "intermediate plenum" be used to insulate reactor internal structures.

The work that is described in this article is part of ongoing research, here at UCSB, to develop a 3-D computer code that may be used with confidence to simulate the flow fields occurring in the large LMFRs under shutdown conditions, and, from numerical experiments using this code, to develop simple scaling laws pertaining to various regimes in the reactor. The main focus of this research is, therefore, to develop turbulence models that are valid for buoyancy driven recirculating flows in liquid metals. The problem is complicated at two levels. At one level buoyancy driven turbulent flows are highly anisotropic, and attempts to model them with the k- ϵ or other simple models have met with less than satisfactory results. Recent investigations have

revealed that in such flows the vertical component of turbulence is suppressed and the horizontal components are enhanced. The presence of density interfaces has an effect similar to the presence of a semi-rigid wall. These complicated effects will have to be modeled in order to simulate the large LMFRs. The other cause of complexity is the fact that any turbulence model that is deemed to be satisfactory has to be introduced into a computer code that can model the extremely complex geometry of the LMFRs.

The code FLOW3D is a computer code that has been selected as the vehicle to develop and test the numerical models to be used in this task. This code is a 3-D Navier Stokes solver and uses body-fitted grids. That makes it suitable for the simulation of complex geometries. Two different studies 3-D natural convection recirculating flows are discussed here. These studies did not include any turbulence model, but were carried out to test if the code captures the large scales of flow adequately, and to gain insight into these flows. The next step in the study is the development of turbulence models from the Direct Simulation and Large Eddy Simulation of some key experiments. This is discussed in detail below.

BACKGROUND

Problems of scaling LMFRS:

If it were possible to conduct experiments in a setup that is an exact thermalhydraulic similitude of an LMFR then it would be possible to use the experimental information directly in simple scaleup models to design an LMFR. By the non-dimensionalization of the appropriate equations one may derive the necessary conditions for exact similitude. Grewal &

Gluekler (1982) have shown that in order that an experimental model represent an exact similitude of the LMFR plena it is essential that:

- (1) the geometry be exactly scaled
- (2) the boundary conditions be the same
- (3) the key dimensionless parameters, which are the Richardson number, the Reynolds number and the Peclet number, be the same for the scaled setup and the prototype.

It turns out that even if the reactors were simple cylinders it would be impossible to meet the third criterion if the first two were adhered to (unless the scale were 1:1). The actual geometry of an LMFR is not that of a simple cylinder, but contains several internal structures (such as heat

exchangers pipes, pumps etc.), and the layout is not even symmetric. Then there is the constraint of the extreme difficulty of conducting experiments with liquid sodium. Add to that the problem of not being able to match both the hydraulic resistance and the Reynolds number in a scaled annular region, and we have a scaled setup where one or more of the key parameters is different by several orders of magnitude from the equivalent parameters in the LMFR. Thus depending on the choice of the investigators, a scaled experimental investigation can only provide data in a small region of the parameter space of interest.

The need for a computer model and the methodology of its development:

In order to acquire the data necessary for direct scaleup of results from small scale experiments one would have to establish a program to systematically conduct experiments to explore the parameter space of interest. The geometry of the key reactor internals would also become a point of study, making the experimental program rather lengthy. On the other hand data acquired in the manner described above can be used for the insight that it provides, and as benchmark for the validation of computer codes. Such a computer model would increase confidence in the scaleup process, and more importantly could guide design. The philosophy of such studies has been depicted with great brevity by Singer et al. (1977), and is reproduced in Figure 3. The development of a computer model would consist of the following steps:

- (1) Identification of the key phenomena, and modeling these.
- (2) Validation of the code against experimental data.
- (3) Scaling up to full LMFR geometry and identifying phenomena that were not observed at the smaller scales.
- (4) Using the code to define experiments that will isolate these phenomena and confirming this thesis.

Experimental investigations in LMFR-like geometries:

There have been a few experimental programs to study the nature of the flows in scaled geometries similar to the geometry of the LMFR. The following are some of the more comprehensive studies:

At the Energy Technology and Engineering Center (ETEC) of Rockwell experiments were conducted with liquid sodium, but geometric similarity was not retained. The experimental setup

includes all the internal features of the prototype. Only temperature data are available in this experiment. The data indicate that the upper plenum is well mixed but the lower plenum is stratified (Banerjee et al., 1989). Fig. 4 shows a set of isotherms in the plena. There is some indication that there may be periods of recirculation of hot sodium back into the core in these experiments.

At GE experiments were carried with water as the working fluid (the SIMONE experiments). Only the upper plenum was studied. Different runs incorporated different internal structures. Two velocity components and temperature data are available. Large recirculation patterns, thermal stratification and recirculation in the core regions was observed (Reeder & Banerjee, 1984). Figures 5 and 6 show streamlines and isotherms from one of the SIMONE runs. Three dimensional numerical analysis was carried out using COMMLX-1A using a constant eddy viscosity model. The predicted temperatures and the experimental values showed good agreement, but the velocity calculations showed poor agreement (Grewal et al., 1979).

Howard & Carbajo (1979) carried out experiments at ANL and reported that if a hot-cold interface exists, thermal fluctuations equivalent to 70% of the total ΔT across the interface can be observed.

Tanaka et al. (1984) conducted an experimental investigation at CRIEPI, Japan, using water to study thermal transients. Their study was not limited to natural circulation, but yields insight into the effect of geometry. They found the position of intake and outflow in the plena to be of great import. They also reported "obvious oscillations" of thermal interfaces where prolonged thermal stratifications are observed.

Modi & Torrance (1987) studied buoyant channel air flows, with Froude numbers in the range that would exist in an LMFR core under shutdown conditions, and reported inflow of cold air into the channel when the Froude number went below a critical value.

Vidil et al. (1988) studied scaled liquid sodium models of the Phenix and Super-Phenix types, at Grenoble, France, and noticed four distinct flow regimes:

- (i) the whole cavity is filled with an isothermal recirculating eddy, with the temperature gradient being confined to the thermal boundary layer.
- (ii) the recirculating eddy has limited height. A thick layer of hot fluid appears at the top giving rise to a temperature gradient.

- (iii) similar to (ii) but more pronounced. There is an isothermal eddy at the bottom, a gradient zone and an isothermal stagnation region at the top.
- (iv) there is a stratified zone throughout the cavity.

As one would expect given the diverse nature of the experimental situations the effects observed were quite diverse. The experiments, therefore, do not provide the sort of conclusive data that would be necessary and sufficient to attempt a direct scale-up.

From the observations of the scaled reactor experiments one must conclude that a vast range of possibilities exist in terms of what flow patterns may emerge in an LMFR under shutdown conditions. None of the adverse situations that may be visualized are ruled out by these experiments. However it does seem that density stratification, in one or more of the plena, is almost certain to be the outcome.

NUMERICAL SIMULATIONS

The numerical simulations were carried out using the code FLOW3D acquired from the U.K.A.E.A, Harwell, U.K.. The work being done here is not expected to be code dependent. The objective of this research is to develop numerical models, which may then be incorporated into any code that fulfills the requirements of low numerical diffusion, and the ability to model complex geometries.

Description of FLOW3D:

FLOW3D solves the entire Navier Stokes equations in three dimensions and uses body-fitted grids. This permits the solution of flows in complex geometries. The time stepping is carried out by a fully implicit backward difference scheme; however the code does have a Crank-Nicolson scheme for advancing time as well. The advection terms are handled by hybrid differencing, with options to use central differencing, higher order upwind differencing or quadratic upwind differencing.

The velocity pressure coupling may be handled by two different methods. The first is the SIMPLE algorithm, due to Patankar and Spalding (1967), in which the coupled system of non-linear equations is solved by linearizing the equations. The velocity pressure coupling yields an equation for correction of pressure. The second algorithm is known as the PISO algorithm and in this method the pressure correction is achieved in two steps. This treatment leads to an improved

solution of the momentum equations while maintaining continuity, but at the cost of increased computations.

The linear equations may be solved by any one of five different methods. However, the algorithm of choice is due to Stone (1968), in which preliminary matrix factorization is combined with the solution of the resulting sparse matrix subproblem using direct Gaussian elimination.

The code permits the setting of under-relaxation factors or the use of false time stepping to reflect the different time scales over which different variables change. In a transient simulation the use of false time steps forces the outer iteration to be carried out twice with the false time steps being used in the first set of inner iterations. The use of false time steps requires a knowledge of the time scales.

The version of the code available currently has an implementation of the k- ϵ model.

The code is highly vectorized and has been tested at various sites for a variety of problems.

The code has been implemented on a CRAY-XMP, a CRAY-YMP, and an Alliant FX-8/4.

Also obtained from the U.K.A.E.A. was a numerical grid generation package for generating body-fitted grids. This code is also running on the CRAY-XMP 48.

FLOW3D was selected as the computer code of choice for several reasons:

1. FLOW3D uses body-fitted grids and hence can be used in flow situations with irregular geometries, which are encountered in most engineering applications.
2. FLOW3D has several solution schemes and also permits false time-stepping for faster (and more physical) computation in problems with different time scales for the different variables.
3. FLOW3D will have in the near future porous-medium formulation which may be useful in future simulations of reactor system rod-bundles.
4. FLOW3D is optimized to take advantage of the vector arithmetic of the CRAYs.
5. FLOW3D is being actively maintained by U.K.A.E.A.

Simple Geometry:

2-D simulations of the ETEC experiments were conducted first to test FLOW3D. The results (Banerjee et al., 1989) were encouraging, but it was obvious that since the phenomena being modeled are inherently three dimensional, modeling of complex systems will have to be carried out in 3-D. The first 3-D simulations were therefore conducted to analyze the data of Reeder (1990). In these experiments natural circulation in water was studied, with a Laser Doppler

Anemometer (LDA), in a right circular cylinder of radius 0.2155m and 0.228m height. The cylinder was filled with water and heated with a concentric disk of 0.175m diameter. Two power input levels were used, 350 watts and 700 watts. Two components of velocity were measured in a vertical plane, the vertical component and the azimuthal component. The temperature was also monitored at twenty locations, however, the temperature measurements were neither continuous nor simultaneous with the velocity measurements. Further the plane of the thermocouple tree was at an angle of 20 degrees to the plane of velocity measurements.

The numerical simulations were conducted using a body-fitted orthogonal grid with 30 grid cells in all three cartesian vector directions. A cylindrical coordinate system was not used since the experimental data exhibited a highly intermittent nature, and thus it was felt that the condition of axisymmetry was overly constraining. The grid is shown in figure 7. A time step of 0.25 seconds was used. The simulations requires about 5 hours of cputime on a CRAY-YMP. The experimental data captured the intermittent nature of the phenomena. In figures 8 through 10, the temporal variation of the velocity close to the plume edge is shown. Also shown are the numerical results. In figures 11 through 13 the temporal variation of the temperature as captured by the numerical simulations is also shown. The large fluctuations in temperature are noteworthy since they are a cause for concern in LMFRs. Figures 14 through 17 show a comparison of the radial and vertical profiles of the vertical velocities. Given the low resolution of the numerical simulations the agreement is very good. Figure 18 shows a typical streamline plot of the experimental data. Figures 19 through 21 show three streamline plots from the numerical simulations at time intervals of sixty seconds. Figures 22 through 24 isotherms at the same three times. Noteworthy is the substantial degree of stratification and the intermittent nature of the plume. Figure 25 shows the interferograms from a study of natural circulation in enclosures by Simpkins (1985). These images are very similar to the isotherms in 22 through 24.

Simple LMFR-like Geometry:

The ability of FLOW3D to capture the essential large scale features of the flows being studies having been established, for the small scales similar to the experiments of Reeder (1990), a series of numerical experiments were carried out to investigate the possible effects of geometry on recirculation flows. The geometry selected is shown in figure 26. The simulations were carried out in cylindrical coordinates with 20 cells in the radial direction, 20 cells in the vertical and 30 cells in the azimuthal direction. A time step of 0.2 seconds was used and water was used as the working fluid. One set of dimensions was used as the base case and is called Run I. This particular simulation was allowed to run for 1200 seconds. Five other geometries were simulated

for 300 seconds each. The details of the geometry are presented in Table I. Fig. 27 through 32 show the temporal variation of the vertical velocities at the heater outlet plane at three different radial distances from the heater rod, and temperature variations at the same locations for Run I. Again the intermittent nature of the flow patterns is more pronounced (in spite of the axisymmetry condition). The large fluctuations in temperature are again evident. Further it can be seen that there are times when there is flow reversal into the core. This is a feature that was missing from the 2-D simulations of the ETEC experiments. Fig. 33 shows the temporal variation of temperatures at the heater outlet for one of the ETEC experiments. Fig. 34 shows the 2-D simulations for the same run. From fig. 33 it is obvious that there is a qualitative change in the flow pattern either at the heater outlet or the heater inlet for a fairly long period. This was not at all captured in the simulations. However, the results of the 3-D simulations conducted so far seem to indicate that a 3-D simulation of the ETEC experiments will be able to capture this effect. Fig. 33 also shows the fluctuations in temperatures that are being captured in these numerical experiments. In fig. 35 through 46 are shown vector plots, streamlines and isotherms for Runs I through VI at 300 seconds. A study of these plots shows that very small changes in the geometry of the LMFR is likely to have rather profound effects on the natures of mixing and temperature profiles in the plena.

Fine Resolution Simulations of the Simple Geometry Natural Convection Experiment:

In light of the differences between the computational results and the experimental data for the simple geometry experiment described earlier, and keeping in mind the severe demands on computational resources of a 3-D transient simulations, the simple geometry experiment was used to validate the usefulness of the differencing schemes being used. Fig. 47 shows the comparison of mean vertical velocity from the experimental data and a 60X60X50 computation using a first order accurate upwind differencing scheme. The mean velocities in the plume are over-predicted in these computations. A third order accurate QUICK difference scheme was also used. This did not improve the prediction of the mean velocities, but it resulted in substantial improvement in the prediction of the turbulence velocities. Fig. 48 shows a comparison of the energy spectra for the data as well as the two different simulations. From these comparisons it was concluded that a finer resolution in the radial direction was required. Therefore a 80X80X52 computation was done with a larger number of meshes in the plume-edge region. The mean velocities from these computations are shown in fig. 49 and it can be seen that the predictions are vastly superior. Turbulence velocities in the axial direction are shown in fig. 50.

Large Scale Geometries:

The following is a discussion of some of the key experimental investigations for flow situations that are likely to be encountered in the complex full scale LMFRs.

STUDIES OF TURBULENCE DOMINATED FLOWS

Kikuchi et al. (1987) and Liburdy et al. (1987) studying the heating of a fluid by a heated disk, reported intermittent release of parcels of high temperature fluid from the edge of the thermal boundary layer above the disk. Further it is known that buoyant plumes do not rise vertically upwards but display a swaying motion.

Britter et al. (1983) observed that the horizontal plume width under various conditions of density stratification is not measurably influenced by the density stratification, but that the vertical growth is attenuated by even the slightest density stratification, the attenuation being systematically greater with decreasing Froude number. They also reported that whereas lateral velocity fluctuations were little influenced, vertical velocity fluctuations were reduced by upto 30% because of the stratification.

Stillinger et al. (1983) reported that buoyancy forces produced anisotropy in the largest scales first, preventing them from overturning, while smaller scale isotropic turbulent motions remain embedded within the larger scale motions. They also found that all isotropic motions disappeared, even the smallest scales of decaying grid turbulence were affected by buoyancy, the original turbulent field being converted to random internal wave motions in a time less than the characteristic time of the largest scale eddies.

Carruthers and Hunt (1986) stated that in the case of large stratification, the stable layer affects the turbulence as if it were a semi-rigid surface; for small stratification the vertical motion in the turbulent region decreases in intensity near the interface and irrotational motions are induced in the stable layer.

Hannoun et al. (1988) reinforced the above study and found that a sharp density interface acts like a semi-rigid plate and attenuates vertical velocity at large scales while increasing horizontal fluctuations at the large scale. For both horizontal and vertical spectra the high frequency end (small scale) was not significantly affected.

Kida and Hunt (1989) studied the interaction of different scales of turbulence over short times (short as compared to the characteristic time of the small scale turbulence) and concluded the large and small scales of turbulent motion interact viz. isotropic large scale turbulent motion increases the isotropy of the small scales of turbulence.

TURBULENCE MODELING

The equations describing the flows being studied here are the continuity, momentum and energy equations:

continuity equation (conservation of mass) :

$$\frac{\partial U_i}{\partial x_i} = 0 \quad (1)$$

momentum equation (Boussinesq approximation for density variation effects) :

$$\frac{\partial U_i}{\partial t} + U_j \frac{\partial U_i}{\partial x_j} = - \frac{1}{\rho_r} \frac{\partial p}{\partial x_i} + \nu \frac{\partial^2 U_i}{\partial x_i \partial x_j} + g_i \frac{\rho - \rho_r}{\rho_r} \quad (2)$$

energy equation :

$$\frac{\partial T}{\partial t} + U_i \frac{\partial T}{\partial x_i} = \lambda \frac{\partial^2 T}{\partial x_i \partial x_i} + S_T \quad (3)$$

where S_T is the source term.

Direct Numerical Simulation (DNS):

These are coupled nonlinear partial differential equations and are not amenable to closed form solutions. However they may be solved numerically. Unfortunately such a solution, with today's computer technology, cannot resolve all scales of motion for typical turbulent flows. Nevertheless such Direct Numerical Solutions are becoming more and more popular with the advent of faster and larger supercomputers. The advantage of such simulations is that no assumptions are introduced, and eddies that are comparable to the size of the numerical grid can be resolved. The results of such simulations are satisfactory for low Reynolds number flows and these results are then used to develop turbulence models of the types described below (Lam & Banerjee, 1988, and Mansour et al., 1989)

Large Eddy Simulation (LES):

Direct Numerical Simulations, it was stated above are not applicable to high Reynolds number flows. The reason for this is that the ratio of the length scale of the larger scales of motion, which is dependent on the flow domain, and the length scale of the energy dissipating small eddies (Kolmogorov scale) increases with Reynolds number. Given the limit of computer memory there is a Reynolds number above which one cannot resolve the small eddies directly. To remedy this, a different approach, Large Eddy Simulation (LES), is being used more and more frequently. In LES, the larger scales of motion are resolved by DNS and the small scale turbulence that cannot be resolved directly is approximated by a model. This approach permits studies of high Reynold's number flows in a manner similar to that in which low Reynolds number flows are studied using DNS. The governing equations are averaged over the volume of the computational grid cell.

This yields the equations (Schumann et al., 1980):

$$\frac{\partial {}^v \overline{U_i}}{\partial x_i} = 0 \quad (4)$$

$$\frac{\partial {}^v \overline{U_i}}{\partial t} + {}^j \overline{U_j} \frac{\partial {}^j \overline{U_i}}{\partial x_j} = - \frac{1}{\rho_r} \frac{\partial P}{\partial x_i} + \nu \frac{\partial^2 {}^j \overline{U_i}}{\partial x_j \partial x_j} - \frac{\partial}{\partial x_j} [{}^j \overline{u_i u_j}] + g_i \frac{\rho - \rho_r}{\rho_r} \quad (5)$$

$$\frac{\partial {}^v \overline{T}}{\partial t} + {}^i \overline{U_i} \frac{\partial {}^i \overline{T}}{\partial x_i} = \lambda \frac{\partial^2 {}^i \overline{T}}{\partial x_i \partial x_i} - \frac{\partial}{\partial x_i} [{}^i \overline{u_i T}] + {}^v \overline{S_T} \quad (6)$$

In these equations the overbars represent averaged quantities and the index on the left superscript signifies the coordinate direction in which the summation convention does not apply. The left superscript "v" signifies volume-averaged quantities.

This set of equations is no longer a closed set - due to the non-linearities in the governing equations the averaging process gives rise to second order correlations that must be modeled. This is a problem of closure similar to that which is faced in the conventional technique of turbulence modeling by temporal averaging. The average quantities in these terms are resolved by the DNS, and the correlation terms only involve the fluctuation terms which are the small scale turbulent motions. The small scales of turbulence are weakly problem dependent, and may therefore be represented by relatively simple models. The models used for these small scales of turbulence are known as Subgrid Scale models. These closure models can be of varying complexity like

conventional closure models discussed below, only their effect on the overall motion is weak. One such model deduced from the Kolmogorov spectrum is due to Deardorff (1970) :

$$-\overline{u_i u_j} = \nu_T \left[\frac{\partial U_i}{\partial x_j} + \frac{\partial U_j}{\partial x_i} \right] - \frac{2}{3} k \delta_{ij} \quad (7)$$

and

$$\nu_T = 0.464 \nu^{2/3} \left[\frac{\partial U_i}{\partial x_j} \left(\frac{\partial U_i}{\partial x_j} + \frac{\partial U_j}{\partial x_i} \right) \right]^{1/2} \quad (8)$$

Large Eddy Simulations are very demanding in terms of computer resources and therefore are not used as engineering tools except for special tasks. However, they are very useful for the purpose of generating information that may be used to develop and to test simpler turbulence models. As discussed later in greater detail we propose to use both DNS and LES to develop Reynolds stress models (closure models), that are applicable to flows that are stratified, are highly anisotropic and include developing unsteady plumes.

Temporal averaging of the Navier Stokes Equations and the problem of closure:

The models described below are of the conventional type arrived at by temporal averaging of the momentum and energy equations. The equations thus arrived at are very similar to the averaged equations derived for Large Eddy Simulations:

$$\frac{\partial U_i}{\partial x_i} = 0 \quad (9)$$

$$\frac{\partial U_i}{\partial t} + U_j \frac{\partial U_i}{\partial x_j} - \frac{1}{\rho_r} \frac{\partial p}{\partial x_i} + \nu \frac{\partial^2 U_i}{\partial x_j \partial x_j} - \frac{\partial}{\partial x_j} \left[\overline{u_i u_j} \right] + g_i \frac{\rho - \rho_r}{\rho_r} \quad (10)$$

$$\frac{\partial T}{\partial t} + U_i \frac{\partial T}{\partial x_i} = \lambda \frac{\partial^2 T}{\partial x_i \partial x_i} - \frac{\partial}{\partial x_i} \left[\overline{u_i T'} \right] + S_T \quad (11)$$

In these equations T' is the fluctuation temperature and the overbars represent averaged quantities as before.

Unlike the original conservation equations, the averaged equations no longer form a closed set of equations, there are now unknown correlation terms that occur because of the nonlinearities in the original equations, and that must be specified. This is the problem of closure. It is possible to write the following exact equations for these correlation terms (Hinze, 1975). Such an exact equation for the Reynold's stress is:

$$\begin{aligned} \frac{\partial \overline{u_i u_j}}{\partial t} + U_l \frac{\partial \overline{u_i u_j}}{\partial x_l} = & - \frac{\partial}{\partial x_l} \left[\overline{u_i u_j u_l} \right] + \frac{P}{\rho} \left(\delta_{jl} \overline{u_i} + \delta_{il} \overline{u_j} \right) - \nu \frac{\partial \overline{u_i u_j}}{\partial x_l} \\ & - \left[\overline{u_i u_l} \frac{\partial U_j}{\partial x_l} + \overline{u_j u_l} \frac{\partial U_i}{\partial x_l} \right] - \beta \left[g_i \overline{u_j T'} + g_j \overline{u_i T'} \right] \\ & - 2\nu \left[\overline{\frac{\partial u_i \partial u_j}{\partial x_l \partial x_l}} \right] + \frac{P}{\rho} \left[\frac{\partial u_i}{\partial x_j} + \frac{\partial u_j}{\partial x_i} \right] \end{aligned} \quad (12)$$

When the three equations for the three normal stresses are summed an exact equation for the turbulent kinetic energy is obtained :

$$\frac{\partial k}{\partial t} + U_l \frac{\partial k}{\partial x_l} = - \frac{\partial}{\partial x_l} \left[\overline{u_l} \left(\frac{\overline{u_i u_i}}{2} + \frac{P}{\rho} \right) - \nu \frac{\partial k}{\partial x_l} \right] - \overline{u_i u_j} \frac{\partial U_i}{\partial x_j} - \beta g_i \overline{u_i T'} - \nu \overline{\frac{\partial u_i \partial u_i}{\partial x_l \partial x_l}} \quad (13)$$

The above equation is exact and each term in the equation is significant and may be separately modeled to close the set of differential equations to be solved. The most general model is also the most complicated one and requires 10 partial differential equations to be solved (6 for the six components of the Reynolds stress, three for the $\overline{u_i T'}$ term and one for the $\overline{T'^2}$ term that is generated). At the other extreme if fairly drastic approximations are made, one arrives at a fairly simple model for turbulence that has found widespread use in engineering applications. This is the k-ε model. This model relates the Reynold's stresses and the turbulent heat fluxes respectively to the gradients of the mean velocity and mean temperature via the eddy-viscosity / diffusivity concept:

$$-\overline{u_i u_j} = \nu_T \left[\frac{\partial U_i}{\partial x_j} + \frac{\partial U_j}{\partial x_i} \right] - \frac{2}{3} k \delta_{ij} \quad (14)$$

$$-\overline{u_i T'} = \Gamma_T \frac{\partial T}{\partial x_i} \quad (15)$$

where

$$\nu_T = c_\mu \frac{k^2}{\varepsilon} \quad (16)$$

$$\Gamma_T = \frac{\nu_T}{\sigma_T} \quad (17)$$

c_μ and σ_T are empirical constants, k is the solution of the equation for the turbulent kinetic energy and ε is the rate of dissipation. The rate of dissipation is obtained from the following equation, that has its roots in order of magnitude arguments applicable to isotropic turbulence originated by Tennekes and Lumley and modified by subsequent investigators (Rodi, 1980) to account for the influence of buoyancy.

$$\frac{\partial \varepsilon}{\partial t} + U_i \frac{\partial \varepsilon}{\partial x_i} = \frac{\partial}{\partial x_i} \left(c_\varepsilon \frac{k}{\varepsilon} u_i u_i \frac{\partial \varepsilon}{\partial x_i} \right) + c_{\varepsilon 1} \frac{\varepsilon}{k} (P+G) (1 + c_{\varepsilon 3} R_f) - c_{\varepsilon 2} \frac{\varepsilon^2}{k} \quad (18)$$

All the constants in the k - ε model have been found by different investigators to be quite problem-specific. More importantly, when it comes to strongly buoyant flows, the k - ε model does not fare as well as it does in shear flow situations, since it attempts to model highly anisotropic flows with isotropic eddy viscosity and diffusivity concepts. It is possible to strike a middle path and to model the Reynolds stresses and the turbulent heat fluxes with algebraic equations instead of partial differential equations. Such models has been proposed in the past (Rodi ,1980).

DIRECTION FOR CURRENT AND FUTURE RESEARCH

The key phenomena involved in the decay heat removal of LMFRs are buoyancy driven recirculating flows, turbulent unsteady developing plumes, and the interaction of the above with stably stratified fluid layers and density interfaces. All of these phenomena are highly anisotropic and current turbulence models are unable to cope with this anisotropy. Yet at the large scales of

LMFRs the turbulence in the flows cannot be ignored. In order to use available data for scaleup one will have to be able to model these turbulent flows well.

These days most turbulence modeling involves the use of DNS and LES to model a flow situation for which experimental data is available to validate the numerical simulations. The large amount of information generated by the simulations is then used to develop turbulence models. This is the approach we plan to take. On the one hand, LES will be introduced into FLOW3D to permit the simulation of complex geometries. On the other hand it is planned to simulate the experiments of Stillinger et al. to develop turbulence models. These turbulence models will then be validated using the data from the ETEC and SIMONE experiments.

ACKNOWLEDGEMENTS

We acknowledge with gratitude computer time made available to us by Cray Research Inc. on the CRAY Y-MP at the San Diego Supercomputer Center, and also computer time made available by the National Center for Supercomputing Applications on their CRAY-XMP.

REFERENCES

1. Banerjee, S., Hetsroni, G. and C. M. Roy, "Numerical Simulation of a Natural Circulation decay heat removal experiment conducted at ETEC - Final Report", ETEC Report no. ETEC-TDR-89-5, 1989.
2. Britter, R. E., Hunt, J. C. R., Marsh, G. L., and W. H. Snyder, "The effects of stable stratification on turbulent diffusion and the decay of grid turbulence", JFM, v127, pp27-44, 1983.
3. Carruthers, D. J., and J. C. R. Hunt, "Velocity fluctuations near an interface between a turbulent region and a stably stratified layer", JFM, v 162, pp 475-501, 1986.
4. Deardorff, J. W., JFM, v41, pp453-480, 1970.
5. Fujimoto, T., Sawada, K., Uragami, K., Tsuge, A., and K. Hanzawa, "Experimental study of striping at the interface of thermal stratification", presented at the 20th National Heat Transfer Conference, Milwaukee, WI, August 2-5, ASME HTD-vol. 15, 1981.
6. Grewal, S., and E. Gluekler, "Water Simulation of Sodium Reactors", Chem. Eng. Commun., vol. 17, pp343-360, 1982.
7. Grewal, S. and R. McGriff, "SIMONE Experiments: Phase I and II results and analysis", GE Report no. GEFR-00708, 1984.
8. Hannoun, I. A., Fernando, H. J. S., and E. J. List, "Turbulence structure near a sharp density interface", JFM, v 189, pp189-209, 1988.
9. Hinze, J. O., "Turbulence", 2nd. Ed., McGraw Hill Book Company, 1975.
10. Howard, P. A., and J. J. Carbajo, "Experimental study of scram transients in generalized liquid-metal fast breeder reactor outlet plenums", Nuclear Technology, v44, pp210-220, 1979.

11. Kenworthy, G., Quarani, G. L., Winters, K. H., Sheriff, N., D. A. Booth, "Study of natural convection phenomena in an LMFBR intermediate plenum", in Liquid Metal Engineering & Technology, Proceedings of the third International Conference held in Oxford, April 9-13, 1984.
12. Kida, S., and J. C. R. Hunt, "Interaction between different scales of turbulence over short times", JFM, v201, pp411-445, 1989.
13. Kikuchi, Y., Kawara, Z., Ebisu, T., and I. Michiyoshi, "Micro-characteristics of turbulent thermal convection in horizontal fluid layers heated internally and from below", ASME-JSME Thermal Engineering Joint Conference, Honolulu, Hawaii, March 22-27, v2, pp203-208, 1987.
14. Lam, K., and S. Banerjee, "Investigation of turbulent flow bounded by a wall and a free surface", in "Fundamentals of Gas-Liquid Flows", E. E. Michaelides and M. P. Sharma eds., ASME FED-vol. 72, pp29-38, 1988.
15. Lam, K., and S. Banerjee, "On the condition of streak formation in a bounded turbulent flow", submitted to Physics of Fluids, 1990.
16. Liburdy, J. A., Dorroh, R., and S. Bahl, "Experimental investigation of natural convection from a horizontal disk", ASME-JSME Thermal Engineering Joint Conference, Honolulu, Hawaii, March 22-27, v3, pp605-611, 1987.
17. Mansour, N. N., Kim, J., and P. Moin, "Near-Wall Kappa-Epsilon-Turbulence Modeling, AIAA Journal, v27, no. 8, pp1068-1073, 1989.
18. Modi, V., and K. E. Torrance, "Experiments and numerical studies of cold inflow at the exit of buoyant channel flows", J. Heat Transfer, v109, pp392-399, 1987.
19. Nakamewa, F., Mawatari, K., Tamamoki, T., and R. Makiura, "Out of pile experimentst for natural circulation decay heat removal in LMFBR fuel assembly - power skew effects upon intra-assembly hydraulic characteristics", in "Decay heat removal and natural convection in fast breeder reactors", A. K. Agrawal & J. G. Guppy ed., Hemisphere, 1981.

20. Patankar, S. V., and D. B. Spalding, "A Finite-Difference Procedure for solving the equations of the two-dimensional boundary layer", *Int. J. Heat Mass Transfer*, vol. 10, pp 1389-1411, 1967.
21. Reeder, D. L., and S. Banerjee, "Analysis of Upper Plenum Velocity Data from SIMONE Natural Circulation Experiments Phase I, II and III," General Electric Report, Sunnyvale, CA, December, 1984.
22. Reeder, D. L., "An Experimental and Numerical Investigation of Turbulence Phenomena in Buoyancy Driven Recirculating Flow," Ph.D. Thesis, University of California, Santa Barbara, expected completion in 1990.
23. Reeder, D. L., Roy, C. M., Hetsroni, G., and S. Banerjee, " Natural convection in a right circular cylinder of low aspect ratio", to be published, *J. Heat Transfer*, 1990.
24. Rodi, W., "Turbulence Models and Their Application in Hydraulics," IAHR Secretariat, Delft, Netherlands, 1980.
25. Schumann, U., Grotzbach, G., and L. Kleiser, "Direct Numerical Simulation of Turbulence", in "Prediction Methods for turbulent flows", W. Kollman, ed., Hemisphere, 1980.
26. Simpkins, P. G., "Convection in enclosures at large Rayleigh Numbers", in "Stability in convective flows", presented at the Winter Annual Meeting of the ASME, Miami Beach, FL, Nov 17-22, 1985.
27. Singer, R. M., Grand, D., and R. Martin, "Natural circulation heat transfer in pool-type LMFBRs", presented at the Winter Annual Meeting of the ASME, Atlanta, Georgia, Nov. 27- Dec. 2, 1977.
28. Stone, H. L., " Iterative solution of implicit approximations of multidimensional partial differential equations", *SIAM J. Numerical Analysis*, vol. 5, no. 3, pp530-558, 1968.
29. Stilling, D. C., Helland, K., N., and C. W. van Atta, "Experiments on the transition of homogeneous turbulence to internal waves in a stratified fluid", *JFM*, v131, pp91-122. 1983.

30. Tanaka, N., Moriya, S., and A. Wada, "Thermal-hydraulic characteristics in a liquid-metal fast breeder reactor hot plenum", Nuc. Sci. & Eng., v88, pp445-463, 1984.
31. Vidil, R., Grand, D., and F. Leroux, "Interaction of recirculation and stable stratification in a rectangular cavity filled with sodium", Nuclear Engineering and Design, v105, pp321-332, 1988.

	RUN I	RUN II	RUN III	RUN IV	RUN V	RUN VI
Vessel Diameter, f (m)	0.508	0.508	0.508	0.508	0.508	0.508
Vessel Height, g (m)	0.610	0.610	0.610	0.610	0.610	0.610
Heater Rod Diameter, a (m)	0.076	0.076	0.076	0.076	0.102	0.076
Annular space between heater rod and shroud, b (m)	0.025	0.025	0.025	0.038	0.025	0.025
Annular space between reactor vessel and overflow liner, c (m)	0.025	0.025	0.038	0.025	0.025	0.025
Elevation of overflow liner, d (m)	0.061	0.183	0.061	0.061	0.061	0.061
Elevation of Redan, e (m)	0.305	0.305	0.305	0.305	0.305	0.183

Table I. Dimensions of model used for simplified geometry simulations (see Fig. 26)

Figure 1. PRISM Reactor Module

Figure 2. SAFR Reactor Module

Figure 3. Method of Investigation

Figure 4. Isotherms during a natural convection cooling ETEC experiment

Figure 5. Streamline during a SIMONE Phase II experiment

Figure 6. Isotherms during a SIMONE Phase II experiment

Figure 7. Grid used in simulations for simple geometry experiment

Figure 8. Temporal variation of vertical velocity at the edge of the plume, close to the lower surface ($Z=15.4$ mm)

Figure 9. Temporal variation of vertical velocity at the edge of the plume, close to the lower surface ($Z=35.4$ mm)

Figure 10. Temporal variation of vertical velocity at the edge of the plume, in the center of the cylinder ($Z=115.4$ mm)

Figure 11. Temporal variation of temperature at the edge of the plume, close to the lower surface ($Z=15.4$ mm)

Figure 12. Temporal variation of temperature at the edge of the plume, close to the lower surface ($Z=35.4$ mm)

Figure 13. Temporal variation of temperature at the edge of the plume, in the center of the cylinder ($Z=115.4$ mm)

Figure 14. Radial profile of the vertical velocity close to the lower surface ($Z=15.4\text{mm}$)

Figure 15. Radial profile of the vertical velocity close to the lower surface ($Z=35.4\text{mm}$)

Figure 16. Radial profile of the vertical velocity in the center of the cylinder ($Z=115.4\text{mm}$)

Figure 17. Axial profile of the vertical velocity at the center of the cylinder

Figure 18. Streamline from experimental data of Reeder (1990)

Figure 19. Streamlines from the simulations at 4000.0sec

Figure 20. Streamlines from the simulations at 4063sec

Figure 21. Streamlines from the simulations at 4125sec

Figure 22. Isotherms from the simulations at 4000sec

Figure 23. Isotherms from the simulations at 4063sec

Figure 24. Isotherms from the simulations at 4125sec

Figure 25. Interferograms showing plume unsteadiness from the work of Simpkins (1985)
The interval between frames is 30 sec.

Figure 26. Sketch of model for simplified geometry experiments

Figure 27. Temporal variation of vertical velocity at heater outlet close to the heater rod for RUN I

Figure 28. Temporal variation of vertical velocity at heater outlet in heater channel for RUN I

Figure 29. Temporal variation of vertical velocity at heater outlet close to the skroud for RUN I

Figure 30. Temporal variation of temperature at heater outlet close to the heater rod for RUN I

Figure 31. Temporal variation of temperature at heater outlet in heater channel for RUN 1

Figure 32. Temporal variation of temperature at heater outlet close to the shroud for RUN 1.

Figure 33. Temperatures at heater core outlet from ETEC Experiment

Figure 34. Temperatures at heater core outlet from 2-D simulation of ETEC Experiment

Figure 36. Streamline for RUN I

Figure 37. Isotherms for RUN II

Figure 38. Streamline for RUN II

Figure 39. Isotherms for RUN III

Figure 40. Streamline for RUN III

Figure 42. Streamline for RUN IV

Figure 43. Isotherms for RUN V

Figure 44. Streamline for RUN V

Figure 45. Isotherms for RUN VI

Figure 46. Streamline for RUN VI

Figure 47. Mean vertical velocity vs. radial position at $Z=55.4$ mm for 700watt input power. Numerical simulations with 60X60X50 grid Upwind Difference.

Figure 48. Energy Spectrum at $Z=55.4$ mm and $R=13.3$ mm for 700watt input power. Numerical simulations with 60X60X50 grid Upwind Difference

Figure 49. Mean vertical velocity vs. radial position at $Z=55.4$ mm for 700watt input power. Numerical simulations with 80X80X50 grid Upwind Difference.

Figure 50. Turbulent vertical velocity vs. radial position at $Z=55.4$ mm for 700watt input power. Numerical simulations with 60X60X50 grid Upwind Difference.

END

**DATE
FILMED**

6 / 30 / 92