**TECHNICAL PROGRESS REPORT
GRANT # DE-FG02-91ER54109
EXPERIMENTAL AND THEORETICAL RESEARCH IN
APPLIED PLASMA PHYSICS**

Submitted to

**OFFICE OF FUSION ENERGY
U.S. DEPARTMENT OF ENERGY
WASHINGTON, D.C. 20545**

Submitted by

**PLASMA FUSION CENTER
MASSACHUSETTS INSTITUTE OF TECHNOLOGY
CAMBRIDGE, MA. 02139**

Duration of Grant # DE-FG02-91ER54109

October 15, 1990 - October 14, 1993

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

RECEIVED 10/15/93

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

**TECHNICAL PROGRESS REPORT
GRANT # DE-FG02-91ER54109**

**EXPERIMENTAL AND THEORETICAL RESEARCH
IN APPLIED PLASMA PHYSICS**

TASK ACTIVITIES

<u>Task #</u>	<u>Task Title</u>	<u>Principal and Co-Principal Investigators</u>
APP-01	Fusion Theory and Computations	Dieter J. Sigmar, Abraham Bers, Jeffrey P. Freidberg, Jay Kesner, Abhay Ram, Jesus Ramos
APP-02	Theory of Thermonuclear Plasmas	Bruno Coppi
APP-03	User Service Center	Martin Greenwald
APP-06A	High Poloidal Beta Studies on PBX-M	Stanley C. Luckhardt, Jay Kesner
APP-06B	Fast ECE Fluctuation Diagnostic for Ballooning Mode Studies	Paul P. Woskov, Stanley C. Luckhardt, Daniel R. Cohn
APP-07	X-Ray Imaging Diagnostic	Richard Petrasso
APP-09	Millimeter/Submillimeter-Wave Fusion Ion Diagnostics	Paul P. Woskov, Daniel R. Cohn
APP-10	Small-Scale Turbulence and Nonlinear Dynamics in Plasmas	Paul S. Linsay
APP-12	Plasma Turbulence and Transport	Dieter J. Sigmar, T. H. Dupree
APP-13	Phase Contrast Interferometer Diagnostic for Long Wavelength Fluctuations in DIII-D	Miklos Porkolab
APP-14	Charged and Neutral Fusion Product Diagnostics for Fusion Plasmas	Richard Petrasso

TECHNICAL PROGRESS REPORT
GRANT # DE-FG02-91ER54109
EXPERIMENTAL AND THEORETICAL RESEARCH
IN APPLIED PLASMA PHYSICS

TABLE OF CONTENTS

	<u>Page</u>
TASK APP-01 Fusion Theory and Computations	1
TASK APP-02 Theory of Thermonuclear Plasmas	22
TASK APP-03 User Service Center	76
TASK APP-06A High Poloidal Beta Studies on PBX-M	78
TASK APP-06B Fast ECE Fluctuation Diagnostic for Ballooning Mode Studies	104
TASK APP-07 X-Ray Imaging Diagnostic	108
TASK APP-09 Millimeter/Submillimeter-Wave Fusion Ion Diagnostics	126
TASK APP-10 Small Scale Turbulence and Nonlinear Dynamics in Plasmas	135
TASK APP12 Plasma Turbulence and Transport	138
TASK APP13 Phase Contrast Interferometer Diagnostic for Long Wavelength Fluctuations in DIII-D	141
TASK APP14 Charged and Neutral Fusion Product for Fusio Plasmas	149

TASK APP-01
FUSION THEORY AND COMPUTATIONS

(i) Subtask Alpha Transport

Principal Investigator: Dieter J. Sigmar

II. Technical Progress in FY92

IIa. Alpha particle losses from toroidicity induced Alfvén eigenmodes (TAE) (D. J. Sigmar, C. T. Hsu)

Fusion born α particles can resonantly interact with and destabilize the TAE mode. In turn, depending on the saturation amplitude these energetic particles will suffer large anomalous diffusion due to stochastic orbit losses. The Hamiltonian guiding center code, ORBIT, was used to analyze the α orbit dynamics and the loss process. It is found that there are two types of losses: (i) the transient near-loss-boundaries losses which scale as $\frac{\tilde{B}_r}{B_0}$, and (ii) the diffusive losses due to orbit stochasticity with onset at $\frac{\delta B}{B} \simeq 10^{-3}$ scaling as $\left(\frac{\tilde{B}_r}{B_0}\right)$. The resulting diffusion coefficient with $\frac{\delta B}{B} \simeq 10^{-3}$ is $D_\alpha \simeq 1.5 \text{ m}^2/\text{sec}$, comparable to the bulk plasma. This work is widely quoted [1,2] in the area of TAE α physics. Related α theory is contained in Refs. [3a,3b].

IIb. Nonlinear interaction between α particle and TAE mode (C. T. Hsu, D. J. Sigmar)

In IIa α particle dynamics were analyzed with a given TAE mode amplitude and large diffusive losses were found when the mode amplitude exceeds the orbit stochasticity threshold $\frac{\delta B}{B} \simeq 10^{-3}$. To arrive at a self-consistent picture it is

thus interesting to investigate the effect on the TAE mode of the α particle response, producing a saturation mechanism corresponding to the nonlinear interaction between α particles and waves. The main question is whether this saturation amplitude exceeds the orbit stochasticity threshold amplitude. This is the crucial point in understanding the α losses. Since the α particle pressure gradient is the energy source and the α particle velocity space gradient is the energy sink (due to Landau damping of the TAE mode), there should exist a saturation state in which the sources and sinks balance with each other.

We have performed a separate study [4] where the particle kinetic energy change and orbit Poincaré surface of section are concomitantly monitored for studying (1) the growth rate of the wave due to the resonant α particles, (2) which classes of alphas are predominantly responsible for the energy exchange, (3) saturation of the wave, (4) stochastic threshold and its effect on energy exchange.

The study allows for the wave amplitude to change according to wave particle energy conservation, but the mode structure is prescribed from the linear Nova-K code. That is, mode-mode coupling and collisional effects are neglected. (Actually, in an independent study by Gang-Sigmar [5] described elsewhere in this proposal, mode-mode coupling is found to be insignificant.) In the present work it is found that

- (a) The growth rate $\gamma \simeq 10^{-3} \rightarrow 10^{-2}\omega_A$ and $\propto \frac{\partial}{\partial r}p_\alpha$ (as predicted in linear theory), for $\frac{\delta B}{B} \simeq 10^{-4}$
- (b) For $\frac{\delta B}{B} \simeq 10^{-4}$, energy exchange is largely due to passing/trapped transition particles with $\xi_0 = \frac{v_{||0}}{v} \simeq -0.5$ which has a stochastic region.
- (c) For $\frac{\delta B}{B} \simeq 2 \times 10^{-3}$, both $\xi_0 = 1$ and $\xi_0 = 0.5$ particles contribute to the energy exchange, and both contain stochastic regions.

- (d) No saturation has been found **before** the global stochasticity occurs. This means the α losses are from stochasticity rather than from (weaker) quasi-linear diffusion.
- (e) After the global stochasticity threshold has been reached, large diffusion losses occur and the density gradient of alphas is quickly flattened. Then the wave is damped.

IIc. Bootstrap current induced by fusion born alpha particles (C. T. Hsu, K. C. Shaing, D. J. Sigmar)

The bootstrap current can provide a large fraction of the plasma current and is thus very important for present and future steady state tokamaks. The bootstrap current induced by α particles has been studied previously by Nocentini et al in which work only the collisional drag effects have been considered. However, it has been recently discovered by us [6] that pitch angle scattering can play an important role in α particle radial transport and thus also for the bootstrap current. We have calculated [7] the α induced bootstrap current by including effects of pitch angle scattering as well as drag, and finite aspect ratio. After deriving the general theory, ITER parameters are used to evaluate the α particle induced bootstrap current.

(ii) Subtask RF Heating and Current Drive — Transport and Chaotic Dynamics

Principal Investigator: A. Bers

Co-Principal Investigator: A. K. Ram

II. Technical Progress in FY92

A. Current Drive by Lower Hybrid and Fast Alfvén Waves

The most effective way of driving current using radio-frequency waves in present day tokamaks has been with lower hybrid waves (LHW). However, as is well known, in a high density and high temperature tokamak (ITER-type) these slow LHWs will not be able to penetrate into the center of the plasma. They would damp away their energy and momentum onto electrons which are towards the edge of the plasma. Consequently, it is important to determine the effectiveness of other rf means of current drive by waves which can penetrate into the center of the plasma. Fast Alfvén waves (FAW) with frequencies below the lower hybrid frequency are able to penetrate into the core of a high temperature plasma and have been proposed as one of the sources for driving currents.

Recent experiments on rf current drive in JET have brought forth some very interesting results. The current drive efficiency was found to be significantly enhanced at higher plasma temperatures when LHWs were used in conjunction with the FAWs. The FAW spectrum was such that by themselves these rf waves would not drive any current. However, the current drive efficiency was enhanced only when the phase velocities of the FAW spectrum overlapped with the phase velocities of the LH spectrum.

We have begun a detailed analysis of current drive by LHWs in combination with FAWs in order to better understand the current drive efficiency in the

presence of both types of waves. Some of the results were presented at the 1991 APS-DPP meeting [1] and, in an invited presentation, at the IAEA meeting in Arles, France [2].

The LHW generated electron tail has an effective perpendicular energy (or perpendicular temperature) which can be an order of magnitude (or more) bigger than the bulk electron temperature [3]. This is due to the pitch angle scattering of the energetic electrons to higher perpendicular momenta. It has been shown that, when these effective increases in perpendicular temperature are taken into account, the theoretically calculated current drive efficiency is more than that evaluated in models where the tail electrons are assumed to have the same perpendicular temperature as the bulk electrons. In our initial calculations we assumed that the effect of the FAW on these tail electrons was to increase their perpendicular energy. This was then shown to lead to an increase in the current drive efficiency. Two-dimensional Fokker-Planck simulations with a model FAW diffusion coefficient and the LHW diffusion coefficient showed that the FAW did enhance the perpendicular tail temperature [1, 2]. This enhancement depended on the strength of the FAW diffusion coefficient, increasing as the diffusion coefficient strength was increased. There was a corresponding increase in the current drive efficiency. Below we present some of these results.

The two-dimensional, relativistic Fokker-Planck code [4] was used to determine the effect of FAW on an electron distribution function which has an asymmetric tail in $p_{\parallel}$ due to LH waves [1]. The FAW diffusion coefficient is taken to be of the form given by Giruzzi and Fidone [5] with the FAW spectrum assumed to be a symmetric Gaussian centered at $n_{\parallel} = 0$ with a half width of $\Delta n_{\parallel} = 2.3$. For the LH waves we assumed $D_o^{LH}/D_c = 50$, where D_c is the collisional diffusion coefficient with the LH spectrum extending from $v_{\parallel}/v_{Te} = v_1$

to v_2 where $v_1 = 4$ and $v_2 = c/(v_{Te}n_a)$ (n_a is the lowest accessible $n_{||}$). For $n_a = 1.6$ and $T_e = 2$ keV, $v_2 = 10$ while for $T_e = 6$ keV, $v_2 = 5.77$. When considering the effect of the FAW, the FAW diffusion coefficient was assumed to be such that $D_0^{FW}/D_c = 0.1$ when $|v_{||}|/v_{Te} \geq 4.0$ and zero, otherwise. [This allows us to consider just the interaction of the FAW with the LH spectrum. The low phase velocity FAW are strongly affected by the existence of magnetically trapped electrons; they can also directly heat bulk electrons which would happen if we allow the FAW diffusion coefficient to extend into the bulk of the electron distribution function. However, our current code does not account for trapped electrons nor does it evolve the bulk temperature, and the conditions for its validity would breakdown if the diffusion coefficient were allowed to extend into the bulk of the distribution function.]

From the numerical code we evaluated the current drive efficiency, η , and the effective perpendicular temperature in the LH induced tail of the distribution function:

$$T_p = \frac{T_{\perp}}{T_e} \quad \text{where} \quad T_{\perp} = \frac{\int dp_{\perp} \frac{p_{\perp}^3}{2} f_0}{\int dp_{\perp} p_{\perp} f_0} \quad (1)$$

The other parameters used in the numerical program were: $Z_i = 1.6$, electron density $= 2.4 \times 10^{19} \text{ m}^{-3}$, $B_0 = 3.3$ Tesla, LH frequency $= 3.7$ GHz, and FAW frequency $= 48$ MHz (parameters similar to those in the JET experiment).

When the Fokker-Planck equation was solved with just the LH diffusion coefficient, we obtained the following results:

$$\text{for } T_e = 2 \text{ keV} : \quad T_p \approx 34, \quad \eta \approx 0.434 \quad (2)$$

$$\text{for } T_e = 6 \text{ keV} : \quad T_p \approx 10, \quad \eta \approx 0.544 \quad (3)$$

When the FAW diffusion coefficient was included along with the LH diffu-

sion coefficient, we obtained:

$$\text{for } T_e = 2 \text{ keV : } T_p \approx 55, \quad \eta \approx 0.608 \quad (4)$$

$$\text{for } T_e = 6 \text{ keV : } T_p \approx 16, \quad \eta \approx 0.683 \quad (5)$$

Comparing (2) with (4), and (3) with (5), we clearly see that the effect of the FAW is to enhance the $T_\perp$ in the LH induced tail of the distribution function. This also gives an enhancement in the current drive efficiency. These increases in $T_\perp$ and η can be understood in terms of a simple analytical model developed primarily for the LH current drive [3]. It must, however, be remarked that this explanation of the observations on current drive by LHWs and FAWs is to be taken as only preliminary. For one thing, in the JET experiments the FAW not only interacts with the LHCD generated electron tail but it also raises the electron temperature of the plasma. Our numerical simulations do not allow for the bulk electron temperature to evolve and thus cannot account for the change in the current drive efficiency due electron bulk heating.

- [1] A.K. Ram, A. Bers, V. Fuchs, and M.M. Shoucri, Bull. Am. Phys. Soc. **36** (1991) 2339.
- [2] A. Bers and A.K. Ram, in *Proceedings of the IAEA Technical Meeting on Fast Wave Current Drive in Reactor Scale Tokamaks (Synergy and Complementarity with LHCD and ECRH)*, Arles, France, September 23-25, 1991.
- [3] V. Fuchs, R.A. Cairns, M.M. Shoucri, K. Hizanidis, and A. Bers, Phys. Fluids **28** (1985) 3619.
- [4] M.M. Shoucri, V. Fuchs, and A. Bers, Comput. Phys. Comm. **46** (1987) 337.

- [5] G. Giruzzi and I. Fidone, in Controlled Fusion and Plasma Heating, (Proc. 17th Eur. Conf., Amsterdam, 1990), Vol. 14B, Part III, pp. 1279-1282, edited by G. Briffod, Adri Nijssen-Vis, and F. C. Schuller, European Physical Society (1990).

B. Spatio-Temporal Chaos in the Saturation of an Unstable Wave

We have continued and completed a major part of our study on spatio-temporal chaos (STC) in the nonconservative, nonlinear three-wave interaction (3WI) [1]. In particular, we have found that STC arises in the saturation of an unstable wave coupled to two damped waves at lower frequencies. The ensuing saturated state exhibits the chaotic behavior of coherent structures and is characterized by a correlation length ξ which is small compared to the system size L ; in turn, the system size is larger than the excitation length ℓ_E (at which energy is injected into the system by the unstable wave) and also larger than the dissipation length ℓ_D (at which energy leaves the system through the damped waves). Thus STC characterized by the conditions $\xi \ll L$ and $L > \ell_E \sim \ell_D$ is a new nonlinear state for a saturated instability in an extended medium, which is very different from either low-dimensional chaos or fully developed turbulence [2]. In the former case $\xi > L$ so that the system is completely spatially correlated, and in the latter case $L > \ell_E \gg \ell_D$ so that energy is injected at some large scale and dissipated at a much smaller length scale (the inertial range lies in between these length scales) with coherent structures existing at a large number of scale lengths.

The main features of the STC that ensues in the saturation of an unstable wavepacket by mode coupling was described in our progress report of last year. During the past year we have attempted to develop an analytical basis for understanding and predicting this STC state. The usual perturbation

analyses that start from linear instability (e.g., weak turbulence theory) cannot be used to access a description of STC. In STC the nonlinearity is not weak, it is rather essential in establishing the coherent structures. The approach we found useful was to start from the nonlinear state of the conservative 3WI and consider the nonconservative aspects as a perturbation. The conservative nonlinear 3WI is exactly integrable by inverse scattering (IST) [3]. In particular, when the high-frequency (hf) wave has the middle group velocity of the three nonlinearly interacting waves, the solutions involve the exchange of envelope solitons between the three waves. In the nonconservative case, assuming the high-frequency wave is unstable for long wavelengths and stable (by diffusion-type damping) at short wavelengths the dynamics proceed as follows. When the unstable wave envelope reaches an area threshold it transfers solitons to the low-frequency (lf) waves, when these are of non-zero amplitude, and by this transfer its envelope wavelengths become shorter; these shorter wavelengths, if not damped, begin to grow until they reach their soliton transfer threshold, and the process of depletion and growth repeats. Thus, from any random initial conditions, small scales are smoothed out by the diffusion-type damping and long scales grow until a depletion soliton threshold is reached which in turn generates smaller scales that may be damped. The steady state is arrived at when one attains a balance between the nonlinear conversion of long length scales to small length scales and the linear damping of the small scales. Thus if the unstable wave has a growth rate γ_1 and its diffusive-type damping is characterized by a diffusion constant D , its steady-state correlation length will be of the order

$$\xi_1 \approx 2\pi \sqrt{\frac{D}{\gamma_1}} \quad (1)$$

The low-frequency damped envelopes are in a state in which they are continu-

ously fed with solitons (by the unstable high-frequency wave) which propagate with their group velocities and are damped; we identify these as quasi-solitons. From IST we can show that the size of these solitons are related to the bound state eigenvalue η of the high-frequency unstable envelope:

$$\xi_2 \approx 2/\eta \quad (2)$$

In the simplest case of an envelope with one extremum the bound state eigenvalue η is given by [3]

$$\int (Q_1^2 - \eta^2) dx = \pi(n + \frac{1}{2}) \quad (3)$$

where Q_1 is the Zakharov-Shabat (ZS) potential (proportional to the unstable wave envelope) and the integral is over the classical turning points of this potential. In the STC state the depleted, unstable high-frequency envelope will have some remaining area (“radiation”) from which it grows before depleting again, and the low-frequency quasi-soliton envelope colliding with the high-frequency envelopes cause their depletion. Thus two questions arise: Given that the hf, unstable envelope depletes from some initial envelope area (i.e., ZS eigenvalue), what is the remaining envelope area after depletion (i.e., the leftover radiation); and what threshold area (i.e. threshold eigenvalue) is required for depletion. To address the first question a multiple-time scale analysis around the IST solution for soliton decay was carried out assuming that growth and dissipation occur on a slower time scale than soliton depletion. The answer to the second question required a perturbation expansion in the Zakharov-Manakov (ZM) scattering space of the 3WI [3]. The mathematical details and results from these IST perturbation analyses [1] gave the perturbed state eigenvalue of the unstable envelope as

$$\eta \approx 4\xi_1\gamma_1 + 2\gamma_2 \quad (4)$$

where γ_2 is the damping rate of the lf wave, and the time required for the hf unstable envelope to grow after soliton depletion to the threshold for depletion as

$$t_g \approx \frac{1}{\gamma_1} \ln \frac{2\eta}{(2 + \gamma_1) \ln 3} \quad (5)$$

With these results one can obtain the quasi-soliton width given by (2) and the characteristic cycling time which is given by (5) plus the (generally very short) soliton depletion time.

The long-time behavior in the STC of this nonlinear 3WI was found to be characterized approximately by the diffusive-type damping associated with the unstable wave. Thus the long-time scale for the hf unstable wave, τ_1 , can be estimated as a diffusion time across the correlation length (1),

$$\tau_1 \approx \frac{D}{\xi_1^2} = \frac{(2\pi)^2}{\gamma_1} \quad (6)$$

and for the lf damped wave, characterized by the quasi-soliton width, (2) with (4),

$$\tau_2 \approx \frac{4}{\eta^2 D} \quad (7)$$

The results (1)-(7) describe all the characteristic scales in the STC ensuing from the saturation of an hf unstable wave by nonlinear coupling to lf damped waves in a soliton transfer interaction (i.e., the hf unstable wave having the middle group velocity). The validity of these results were corroborated by

extensive numerical simulations [1]. Finally there remains only to estimate the average energy densities in the saturated state of the STC. These are obtained from the conservation equations for the nonlinearly interacting waves and the threshold eigenvalue η . With $\langle U_n \rangle \equiv \int_0^L \langle |a_n|^2 \rangle dx$, where a_n is the complex envelope amplitude of wave $n = 1, 2, 3$, the conservation equations show that

$$\langle U_2 \rangle \approx \frac{2}{3} \frac{\gamma_1}{\gamma_2} \langle U_1 \rangle \quad (8)$$

$$\langle U_3 \rangle = \frac{\gamma_2}{\gamma_3} \langle U_2 \rangle \quad (9)$$

with γ_1 the growth rate of the hf wave, and γ_2 and γ_3 the damping rates of the lf waves. In the saturated state the hf unstable envelope has an amplitude related to its threshold eigenvalue η , which together with the eigenvalue quantization rule for a soliton, (3) with $n = 0$, allows us to estimate the average energy density of the saturated unstable wave as

$$\frac{\langle U_1 \rangle}{L} \approx \frac{1}{2} \left[\eta^2 + \left(\frac{\pi}{2\xi_1} \right)^2 \right]$$

These estimates of the average energy densities in STC have been found to correspond closely to the amplitudes of the spectral energy densities determined from the correlation functions in the numerical simulations, [1].

The results of these studies have been presented at last year's Sherwood Theory Conference [4] at the Annual Meeting of the Division of Plasma Physics [5] and at the III Potsdam – V Kiev International Workshop on Nonlinear Processes in Physics [6].

(iii) Subtask MHD and Plasma Engineering

Principal Investigator: J. P. Freidberg

I. Technical Progress

During the past year, while maintaining a substantial effort in traditional MHD theory, we have expanded our activities into the area of plasma engineering and fusion technology. We are motivated by the facts that (1) the next generation of large experiments (e.g. TPX and ITER) are more than ever dominated by engineering and that (2) traditional plasma theory is becoming a mature field. We have found that there exist excellent opportunities in plasma engineering for making quantum leaps of progress using the sophisticated tools developed over the years by plasma theorists. A summary of our progress is as follows.

(a) Alpha Particle Instabilities (with R. Betti)

We have continued our studies of TAE and EAE instabilities. A compact and reasonably general formulation has been developed that allows us to calculate instability thresholds nearly analytically, requiring only a minimal of computation. Following D. J. Sigmar's suggestion we have cast the stability boundary in the form of an n versus T diagram, particularly convenient for overlaying on a POPCON plot. A particularly important result, now widely accepted in the theory community, is the importance of ion Landau damping generated by the $\omega/k_{\parallel} = v_{Alfven}/3$ resonance for the TAE mode. This effect is increasingly important at high β_i and suggests useful directions to consider when choosing a TAE/EAE stable operating point in an ignited or near ignited experiment such as ITER.

(b) Measurement of β_p and ℓ_i from Magnetic Diagnostics (with MHD class)

We have been able to derive theoretically an MHD result well known empirically from experimental measurements and computationally from numerical simulations. The result is as follows: In a circular tokamak it is not possible in a practical sense to separately determine β_p and ℓ_i from a set of poloidal field measurements. By using Shafranov's step model of the plasma profiles, we have analytically solved the Grad-Shafranov equation to second order in the aspect ratio ϵ . In principle, combining first and second order information is sufficient to separately determine β_p and ℓ_i . However, the analytic theory shows that the second order information is so sensitive, that any small errors in the measurements makes it a practical impossibility to separate the β_p and ℓ_i information. The calculation has been generalized to include a finite ellipticity, and here it is shown analytically that, also as is well known, the β_p and ℓ_i information is distinguishable and can be determined from a set of poloidal magnetic measurements.

(c) Fast Time Dependent PF Solver (with J. Wei)

One of the important tasks in the design of a tokamak experiment is the calculation of the PF currents required to generate a desired plasma equilibrium in static and time dependent situations. The time dependent case is particularly difficult because of the eddy currents in the vacuum chamber. Typically there are ten or less PF coils that must be calculated, usually by some standard optimization procedure. The presence of the vacuum chamber usually requires on the order of 100 additional filaments in the modelling, thereby greatly increasing the complexity and CPU time required for the PF optimization. Furthermore, since the vacuum chamber is often made of stainless steel, its L/R time is

approximately ten times faster than that of the PF system. This, in principle, requires a corresponding factor of ten increase in the number of time steps that must be computed compared to the case of no vacuum chamber. We have resolved these difficulties by introducing a multiple time scale analysis into the multi-circuit PF-vacuum chamber system. This allows us to calculate the rapidly varying vacuum chamber response analytically in terms of the slowly varying PF system. Ultimately, our optimization again reduces to the ten or less PF currents calculated on the slow PF time scale. This represents a large savings of CPU time.

(d) Resistive Wall Growth Rates (with G. Berge)

It is well known that the presence of an ideal conducting wall can be very important in the stabilization of external kink modes. It is also known, that a resistive wall reintroduces the kink modes but at a much lower growth rate, comparable to the resistive wall diffusion time. We have developed a convenient variational principle that allows us to calculate the resistive wall growth rates having only a knowledge of the ideal stability with and without a perfectly conducting wall. In addition, we have developed a formulation that allows us to efficiently and accurately evaluate δW_{vac} with and without the wall for an arbitrary n number mode in an axisymmetric torus. The method requires the simultaneous solution of two coupled integral equations derived by means of Green's theorem. These are conveniently solved by Fourier analysis. The use of Green's theorem allows us to treat arbitrarily shaped conducting walls (i.e. they need not be magnifications of the plasma surface) without having to introduce a complex but general numerical grid in the vacuum region.

(e) Quench Protection in Superconductors (with A. Shajii)

An important design requirement for superconducting magnets is that no irreversible damage should occur once a quench is initiated. While the general principles of quench protection are well known it still remains a formidable computational task to model a given magnet configuration with sufficient accuracy and speed to carry out reliable engineering parametric studies. There exist several high quality, multi-purpose codes investigating the behavior of superconductors. However, these are not optimized for quench protection and typically require hours of CRAY CPU time per run, making them obviously unattractive for parametric studies. By using the techniques of plasma theory, including asymptotic analysis, the multiple time scale procedure, and variational techniques we have derived a greatly simplified and optimized model, more accurate in some respects as well, for the specific problem of quench protection. This code runs on the order of a minute CPU on a work station. Our initial version is near completion and we anticipate benchmarking studies in the near future.

(f) Flow Reversal in Helium Cooled Superconductors (with A. Shajii)

Superconducting fusion magnets are often cooled by supercritical helium. Assume such a magnet is operating normally, but slowly starts to uniformly heat up, say for instance due to increased blanket temperatures arising from fusion neutron production. It has been observed experimentally that in some cases the resultant heat transfer to the helium is sufficiently large that the flow actually reverses and the pump driving the helium chokes. Clearly, such an event in a fusion magnet could lead to irreversible damage. We have investigated this problem analytically and determined why this reversal phenomena occurs. We have also calculated the maximum heat load that can be tolerated before

reversal occurs. This provides a useful guide on the pumping requirements for the cooling system.

(iv) Subtask High $\epsilon\beta_p$ Plasmas

Co-Principal Investigator: Jay Kesner

I. Technical Progress FY-92

(a) High $\epsilon\beta_p$ Plasmas

We have collaborated in high $\epsilon\beta_p$ experiments that have been performed on TFTR [1-3] with the goal of illuminating the physical processes at work in high beta plasmas. In particular we are interested in generating plasmas which exhibit a high bootstrap fraction and in understanding stability and transport in high poloidal beta plasmas. Poloidal betas of up to $\epsilon\beta_p \leq 1.3$ have been attained and plasma confinement of up to $3.5 \times$ L-mode is obtained through the use of a current profile control technique [2].

We have performed an experiment [4] in which we obtained bootstrap current fractions of $> 70\%$ and total non-inductive current drive fractions of $> 80\%$. Long beam pulse (4 second) experiments were performed to observe the skin time soak-in of the non-inductive current components.

In the high poloidal beta long-time experiments we can observe q_0 rising above 2 due to the high bootstrap fraction. This has been predicted to have marked effect on plasma stability [5, 6]. In a the circular cross-section plasma like TFTR raising q_0 has been predicted to lead to a reduced Troyon limit and this experiment may demonstrate this prediction.

(b) Development of Lower Hybrid Current Drive Simulation Code

We have have simulated a second stability access experiment that can be performed in the PBX-M facility. In this scenario we utilize plasma current density profile control to obtain a stable path into the second stability region. To perform a detailed simulation of the proposed experiment we have developed

a new simulation tool. This code incorporates the Bonoli lower hybrid current drive code into the BALDUR tokamak simulation code.

The BALDUR code is a widely used $1\frac{1}{2}$ -D tokamak simulation code in which MHD equilibrium and thermal and particle transport are treated. BALDUR is able to treat shaped plasma cross sections, neutral beam injection and calculates both the neutral beam-driven and bootstrap currents. This code checks ballooning stability and is easily interfaced with MHD stability codes developed at PPPL. Inclusion of a lower hybrid current drive package into this code provides an excellent tool for simulation of LHCD in devices like PBX-M or JET.

The Bonoli lower hybrid current drive code [7] incorporates a toroidal ray-tracing code and a one-dimensional Fokker-Planck calculation to calculate current and power deposition resulting from a realistic spectrum of lower hybrid waves. Two dimensional effects are estimated in the Fokker-Planck analysis in the form of a specified hot perpendicular electron temperature tail. This code however assumes circular plasma cross section with equilibrium determined from a Shafranov aspect ratio expansion. Since time-dependence, cross-section shaping and neutral beam effects are important in the analysis of the proposed experiments we have decided to integrate this code with BALDUR.

The BALDUR equilibrium package uses Hirshman's moments expansion solution in flux coordinates and the conversion to the toroidal cylindrical coordinates of the Bonoli code is accomplished through an iterative inversion calculation [8].

(c) Divertor Simulation

We have worked with visiting scientists (D. Rayevski, B. Braams, NYU) in implementing the B2 (Braams) code to simulate VTF. These calculations substantiated that the gas (radioactive) divertor can be tested in a small tokamak.

(v) Subtask Theory of the Tokamak Beta Limit

Co-Principal Investigator: Jesus J. Ramos

I. Technical Progress

During 1991-92 our theoretical work on MHD limits of high beta tokamaks has touched upon three main topics: bootstrap driven configurations in the second stability regime, parametric studies of tokamak geometry (shaping) effects, and numerical convergence of results obtained with the current MHD codes.

We have shown that stable equilibria in the high- q_0 second stability regime can have current density profiles that virtually coincide with those consistently generated by the bootstrap effect in collisionless neoclassical theory, except for the small seed current needed at the magnetic axis. This feature is unique to high- q_0 , second stability equilibria. Our high- β_p , bootstrap driven tokamak concept has been extensively studied as a basis for the ARIES II project and the new TPX initiative.

The performance parameters of tokamak configurations in the second stability regime and at virtually 100% bootstrap current are rather sensitive to the geometrical characteristics of the tokamak cross section. The optimal geometrical conditions for this advanced scenario are different from those in the conventional first stability, high current regime. We have carried out an extensive study of the effects of aspect ratio, elongation and triangularity to elucidate these geometrical issues. It has been shown that optimal operation of a fully bootstrap driven tokamak in second stability requires either small aspect ratio or strong triangular shaping.

The issue of the numerical accuracy of results obtained with the current MHD codes for low- n modes in high- β_p , high- q equilibria was raised after our detailed convergence analyses revealed problems. We are still actively involved in this problem, collaborating closely with colleagues at PPPL with the PEST code and at GA with the GATO code. Serious deficiencies have been identified which may point towards the need for a new generation of numerical codes to properly analyze these high- β_p , high- q equilibria.

In a different area we have provided the theoretical support for a new plasma diagnostic to detect internal MHD modes, based on electron cyclotron emission radiometry. This diagnostic has been successfully implemented in JET as part of an ongoing collaboration, and will also be installed in PBX-M.

TASK APP-02
THEORY OF THERMONUCLEAR PLASMAS

Professor Bruno Coppi
M.I.T. Department of Physics, Rm. 26-217
77 Massachusetts Avenue
Cambridge, MA 02139-4307
Phone: (617)253-2507

II. TECHNICAL PROGRESS IN FY92

II.A CENTRAL CONFINEMENT AND $m^0 = 1$ MODES

Since 1976 we have emphasized the point that α -particle heating, being peaked in the central part of the plasma column, can lead to the excitation of “shark-tooth” oscillations [1]. These oscillations (phenomena which correspond to “sawtooth” oscillation in present experiments) can delay or prevent the occurrence of ignition, as detailed numerical simulations have shown [2], when the relevant temperature crashes have repetition times significantly shorter than the energy confinement time and affect a major fraction of the plasma volume.

We have brought into evidence two factors that are grounds for the belief that sawteeth may be controlled and even suppressed on the way to ignition: there exists a large region in parameter space where ideal and resistive modes with poloidal mode number $m^0 = 1$ are stable [3] and, outside this region, high energy nuclei can suppress [4-6] the instability of these modes. For the purpose of introduction, we recall that the finite diamagnetic frequency of the thermal ions, $\omega_{*i} = -(k_{\theta}c/eBn)(dp_i/dr)$, is the main agent for stabilization of the ideal $m^0 = 1$ instability. This occurs for [7,8] $\omega_{*i} \geq 2\gamma_{MHD} = 2\lambda_H V_A/\sqrt{3}R$ where $\lambda_H \propto (\beta_p^2 - \beta_{pc}^2)/s_1$ is a measure of the “drive” for the ideal instability. γ_{MHD} is the growth rate of the ideal MHD mode, V_A is the Alfvén velocity, R the major radius, and β_{pc} a critical poloidal beta for the ideal instability. A much weaker resistive instability with growth rate $\gamma \simeq \epsilon_{\eta} \gamma_{MHD}^3/\omega_{*i}^2$ remains, but only for certain parameter regimes. Here $\epsilon_{\eta} = \sqrt{3}\eta_{||} s_1^2 c^2 R/4\pi V_A r_1^2$ is a measure of the effect of the electrical resistivity $\eta_{||}$ due to electron-ion collisions. The parameter $s_1 = (rdq/dr)_{r_1}$ is the magnetic shear computed at the radius, r_1 , where the magnetic winding index, $q(r)$, equals unity.

At the same time, an extensive series of experiments has been carried out to explore high electron temperature regimes where the effects of collisional resistivity tends to become unimportant and values of ϵ_{η} as low as 10^{-9} are reached.

These high temperature regimes have been obtained in particular after the ordinary sawtooth oscillations were suppressed and were usually terminated by sudden events, called monster sawteeth, that produced a sharp, fast “crash” of the central plasma pressure.

These circumstances have renewed our interest in the investigation of reconnection processes in collisionless plasmas [9] that we started in 1964 and continued in later years [10,11]. An invited paper on this general subject was in fact given by us at the 1991 Sherwood Conference [12] and a series of papers reporting our analysis are being issued [13-15]. In particular, we have treated regimes characterized by values of the parameter ρ_s/d_e that are relevant to realistic experiments (here, ρ_s is the ion Larmor radius based on T_e , and d_e is the collisionless skin depth). Our results have been confirmed by the numerical simulations on the evolution of collisionless $m = 1$ modes that involve magnetic reconnection [16].

Our present efforts are directed in part toward further developing the linear kinetic theory that is still inadequate for application to, for example, experiments with the objective of reaching fusion burn conditions (in particular, the role of temperature gradients requires careful analysis). Another part is directed at gaining good understanding of the nonlinear evolution of the $m = 1$ modes producing reconnection, both by analytical methods utilizing fluid models and by numerical simulation techniques [17]. For this latter endeavor, we have established a working collaboration with W. Park and the Hybrid MHD- Gyrokinetic group at the Princeton Plasma Physics Laboratory. We are also entertaining fruitful contacts with our colleagues who are working on the same general subject at UCLA and at the National Institute for Fusion Studies in Japan.

i) Finite gyro-radius effects on resistive internal $m^0 = 1$ modes

We are extending the analysis of the stable region discussed previously, incorporating finite gyro-radius effects with the aim to analyze its properties as $\rho_i/r_1\epsilon_\eta^{1/3} \rightarrow 1$. In addition, we are in the process [18] of combining this same finite- ρ_i physics with the stabilizing [19] contributions from ion collisionless viscosity. This leads to an analysis of the stability properties of $m^0 = 1$ resistive modes in the region $\gamma_2 \leq \gamma_{MHD} \leq \gamma_3$ where γ_2 is the value where the resistive kink mode becomes stable ($\lambda_H < -\epsilon_\eta^{1/3}$) (Ref. [3]) and γ_3 is the value at which the ideal instability appears. We find that (i) the two fluid model actually over-estimates the growth rate of the resistive internal kink in regimes where $\rho_i \leq \epsilon_\eta^{1/3} r_1$ and (ii) that a combination of high temperatures (finite ω_{*e}) and densities (finite ion collisional viscosity) can effectively stabilize this mode in the resistive regime. ($\lambda_H < R\omega_{*i}/2V_A$).

The stabilizing effect of energetic trapped particles [4-6] on ideal and resistive $m^0 = 1$ modes is by now well known and accepted, since we pointed out [4] the basic mechanism and conclusively proved [5] that resistive modes can be stabilized. The effect of these particles is especially important in experiments which operate in regimes where none of the other stabilization mechanisms are effective (i.e., $\gamma_{MHD} > \gamma_3$). Some open questions remain concerning the large gyro-radius regime where the width of the singular layer is determined by the size of the gyro-radius. Recent work [20] indicates that the resistive kink instability is much more severe there and less prone to stabilization by energetic particles.

ii) Effects of trapped thermal ions on $m^o = 1$ modes

Following our successful work [4]-[6] on the stabilization of internal kinks by trapped energetic ions, our attention has turned to similar effects provided by thermal trapped ions. The resistive $m^o = 1$ mode, having low frequency ($\omega < \omega_{*i}$), indeed has its growth rate reduced by these particles, though thermal ions are in general unable to completely stabilize this mode as β_p is increased [21].

Of potentially greater importance is the effect on the other root of the existing pair, namely the one with $\omega \sim \omega_{*i}$. We remember that of the two MHD roots that exist naturally [7]-[8], it is this root (the higher frequency one) that can be destabilized by a resonant interaction with particle orbits, e.g. the precession of the guiding centers of trapped particles. It is precisely this precession drift resonance (involving energetic ions from neutral beam heating) which was shown [22] to be responsible for "fishbone oscillations." A similar interaction with the trapped fraction of thermal ions may be expected to cause the instability of this same MHD root. For sufficiently high values of β_p , the energy functional of these thermal trapped ions, $Re\lambda_{ki}$, becomes positive, and the instability becomes reactive rather than resonant. Since the appellation "fishbone oscillation" has been accepted to involve a resonant instability with a characteristic signature on the detectors and which is self-quenching (by scattering the energetic trapped particles out of the interaction region), we feel that a more general appellation of the kinetic instability of this $\omega \sim \omega_{*i}$ root is appropriate. Thus the term "kinetic kink mode" is proposed to cover both the resonant and non-resonant regimes of this instability.

Analysis of the simple case of ideal modes shows that the instability appears for $\beta_p > \beta_{PC}^{KKM}$ (KKM= "kinetic kink mode") [23] where $\beta_{PC}^{KKM} < \beta_{PC}^{FLR}$. The constant β_{PC}^{FLR} is the critical value for destabilization of the conventional ideal kink (cf. [7]-[8]). Moreover, it appears that there exists an interval $\beta_{PC}^{KKM} < \beta_p < \beta_{p*}$ where the mode, though in principle unstable, does not arise as a normal mode

(i.e., is not spatially localized). Thus true instability occurs only for $\beta_p > \beta_{p*}$ where the ideal KKM suddenly appears with *finite linear growth rate* [24]. This is in agreement with observations of the threshold properties for fast sawtooth crashes in the JET experiment [25]. Note that while thermal trapped ions have a destabilizing effect on the higher frequency ($\omega \sim \omega_{*i}$) root they tend to stabilize the lower frequency ($\omega < \omega_{*i}$) root, in the ideal regime (just as they do to the resistive kink, see the opening paragraph) since $Re\lambda_{ki}(\omega < \omega_{*i})$ is negative. Thus, the ideal instability of the “fluid Kink mode” is retarded.

iii) Linear stability and early nonlinear stage of fluid collisionless $m^0 = 1$ modes

The study of the two-fluid MHD model of the $m^0 = 1$ mode in tokamaks [26] has opened new possibilities to make the theory of this mode much closer to experiments. At the present time, there are two basic theoretical approaches. The first is one-fluid MHD and has been developed for both theoretical and numerical studies. It has given the correct topology of the mode development during the nonlinear stage and in the ideal MHD limit supports Kadomtsev's picture of complete helical flux reconnection. Nevertheless, it fails in the explanation of the crash time, stability conditions, and the triggering of sawtooth oscillations. The second approach uses kinetic theory and leads to a more complicated picture of $m = 1$ mode regimes. In particular, the kinetic growth rate becomes comparable with the inverse crash time. Also, due to ω_* -effects, stability conditions appear in the theory. Nevertheless, because the present kinetic theory is a linear one, its applicability is violated practically from the beginning of the mode's development and its results can be considered only as a hint to what can be expected during the nonlinear stage.

The study of the linearized two-fluid model (electrons and ions) has shown that in spite of its simplicity it is able to reproduce nearly most of the linear "kinetic" results. Also, it makes it clear that the plasma motion in the singular layer has a much larger scale length than the perturbed current density, which leads to a faster growth rate than in the one-fluid model. The new reconnection time $\tau_{crash} = r_1 / \rho_s \tau_A^*$, where r_1 is the mode resonant radius, ρ_s is the ion sound Larmor radius (the ratio of the sound speed to the ion-gyrofrequency), and τ_A^* is the characteristic Alfvén time, that can be expected on the basis of two-fluid model is $\sqrt{\beta m_i / m_e}$ times faster than Wesson's estimate [27] and is in excellent agreement with experimental observations of the fast sawtooth crash.

In addition to the fast reconnection time, the two-fluid model exhibits such features as

a) the existence of two characteristic roots for the $m = 1$ mode: (1) the resistive mode, which may play the role of the precursor to the sawtooth oscillations, and (2) the collisionless mode which appears may be responsible for the crash;

b) the existence of marginal stability conditions for the collisionless $m = 1$ mode, which qualitatively are confirmed by the experiments.

It may also be possible to explain the triggering of the sawtooth crash by the stabilizing effect of the electron temperature gradient and the fact that this gradient can be easily destroyed during the nonlinear phase. Although the two-fluid model cannot give a quantitative estimate of this factor (it must be obtained on the basis of kinetic theory), it is able to model this effect by an appropriate adjustment of the parallel electron thermoconductivity.

Finally, the relative simplicity of the two-fluid model gives hope for the development of a theory of the early nonlinear stage, which would provide a new level of understanding of sawtooth oscillations in tokamaks.

iv) The sawtooth repetition cycle

For the long term, we are planning a broadband assessment of our theoretical knowledge in light of the available experimental data. Among the questions to be addressed are: the role of magnetic shear, coupling to sound waves and parallel electron thermal conductivity, the different scenarios occurring in ohmic vs. auxiliary heated discharges, and the nonlinear development of the instability. The last topic is probably the most important one. It is crucial to examine whether or not a finite $m^o = 1$ island leads to temperature flattening, density flattening, or both. This of course has relevance to the topic of partial vs. full sawtooth collapses. This endeavor is at its earliest stage; a review paper is being planned, where at least initially a statement of unanswered questions and problems will be enumerated. Our intent is to answer as many of these questions as possible with the objective of clarifying the physical mechanisms which underline the sawtooth repetition cycle in tokamaks.

During the balance of the period covered by this proposal, we will concentrate on the effect of magnetic shear on these internal modes. As long as the shear is finite (i.e., s_1 greater than $\epsilon_1^2 = r_1^2/R^2$) the quasi-interchange instability of the $m^o = 1$ mode is avoided. Then, with this limitation in mind, low-shear experiments with $\beta_p < \beta_{pc}$ could operate in the favorable regime where λ_H is strongly negative and ω_{*i} strongly positive (see above). We will also study the character of the instability of the resistive kink ($\gamma_{MHD} > \gamma_2$, see above) as the magnetic shear is varied (growth rate, spatial structure of the eigenfunction). We will draw on existing data from present experiments (e.g., JET, TFTR) and from simulation of future ones to derive more precise estimates of λ_H and s_1 . Knowledge of these parameters (along with ω_{*i}) coupled with known occurrence of partial vs. full sawtooth collapse can potentially yield casual relationships between selected parameters and sawtooth characteristics.

v) Numerical modeling of sawtooth oscillations and low mode number instabilities

In the past year we have established a collaboration with the Hybrid Gyrokinetic MHD simulation group at PPPL, lead by Wonchull Park. They have developed a hybrid code MH3D-K [28] that models a resistive MHD plasma in toroidal geometry, keeping all three dimensions, combined with a gyrokinetic model for a small hot ion population. We have contributed the conversion of the resistive MHD part to a resistive two fluid model (ions and electrons), by converting the Ohm's law to a true electron momentum equation (inertialess) by adding the Hall term and an electron pressure. We have also improved the spatial variation of the bulk plasma density to allow more realistic profiles. We intend to first apply the code to the large scale behavior of the sawtooth crash, which has been previously studied with the MHD version. There are two main differences. First, the two fluid equilibrium retains some plasma flows that do not occur in resistive MHD. The most important is the diamagnetic drift that depends on the pressure gradient and plays an important role in the stability of the $m = 1$ mode as ω_{*i} . Second, the two fluid approach decoupled the current density variation from that of the fluid plasma in the vicinity of the reconnecting layer for the sawtooth crash. The plasma layer width should then never be smaller than the ion gyro-radius, while the current can vary on a much smaller scale that depends on the resistivity just as in resistive MHD [29] (see Section II.B-1 iii)). This should permit a much faster reconnection (crash) since the basic limiting process for the nonlinear phase of the crash is the rate at which the plasma can be forced through the narrow reconnection layer.

We intend to devote the first part of the year to the effects of the Hall terms on the equilibrium and the study of the sawtooth crash. In the long run, we hope that the existence of the electron model will facilitate the conversion of the code to a full 3D toroidal gyrokinetic code, or gyrokinetic/drift kinetic code, by providing an intermediate step in which the ions can be made fully gyrokinetic

and tested, while the much more complex electron motion is represented simply. This step will require the use of parallel processing computer, since even the small hot particle population is difficult to follow on a Cray computer.

We also intend to begin work on the problem of the detailed electron dynamics in the linearly perturbed and eventually in the nonlinear stage of the sawtooth crash. Our previous work [29,13] has shown that there are important effects on the linear stability of the $m = 1$ mode that are associated with scales intermediate between ρ_i and ρ_e that are difficult to handle analytically. Initial simulation work by other groups [16] has since confirmed some of these results, although in a cylindrical geometry. This is a long term problem, and will be first approached by modeling the reconnection layer only, to be numerically tractable.

Starting this year we hope to involve a graduate student, in a project that may eventually use the CM-5 (Connection Machine) parallel processing computer that is to be acquired by M.I.T. in the next year.

REFERENCES

- [1] B. Coppi, A. Taroni, and G. Cenacchi in *Plasma Physics and Controlled Nuclear Fusion Research 1978* (IAEA, Vienna, 1979), Vol. 1, 487.
- [2] B. Coppi, P.T. Bonoli, G.B. Crew, R. Englade, J.J. Ramos, N. Sharky, L. Sugiyama, F. Pegoraro, in *Plasma Physics and Controlled Nuclear Fusion Research, 1982* (I.A.E.A., Vienna, 1983), vol. 3, p. 307; R. C. Englade, *Nucl. Fusion* **29**, 999 (1989).
- [3] S. Migliuolo, F. Pegoraro, and F. Porcelli, *Phys. Fluids* **B3**, 1338 (1991).
- [4] B. Coppi, R.J. Hastie, S. Migliuolo, F. Pegoraro, and F. Porcelli, *Phys. Lett. A* **132**, 267 (1988).
- [5] B. Coppi, P. Detragiache, S. Migliuolo, F. Pegoraro, and F. Porcelli, *Phys. Rev. Lett.* **63**, 2733 (1989).
- [6] B. Coppi, S. Migliuolo, F. Pegoraro, and F. Porcelli, *Phys. Fluids*, **B2**, 927 (1990).
- [7] B. Coppi, R. Galvão, R. Pellat, M.N. Rosenbluth, and P.H. Rutherford, *Fiz. Plazmy* **6**, 961 (1976) [*Sov. J. Plasma Phys.* **2**, 533 (1976)].
- [8] G. Ara, B. Basu, B. Coppi, G. Laval, M.N. Rosenbluth, and B. V. Waddell, *Ann. Phys. (N.Y.)* **112**, 443 (1978).
- [9] B. Coppi, *Phys. Lett.* **11**, 226 (1964).
- [10] B. Coppi, J. W-K. Mark, L. Sugiyama and G. Bertin, *Phys. Rev. Lett.* **42**, 1058 (1979).
- [11] B. Basu and B. Coppi, *Phys. Fluids* **24**, 471 (1981).
- [12] B. Coppi and P. Detragiache, Paper 3B-4 in 1991 International Sherwood Fusion Theory Conference, Seattle, WA.
- [13] B. Coppi and P. Detragiache, Massachusetts Institute of Technology, Report PTP-90/14, (R.L.E.), Cambridge, MA (1990), submitted to *Phys. Rev. Letters*.
- [14] B. Coppi and P. Detragiache, in *Controlled Fusion and Plasma Physics* (Proc. 14th Eur. Conf. Berlin 1991) Vol. 15C, Part IV, p. 53 [Publ.

European Phys. Soc. 1991].

- [15] P. Detragiache and B. Coppi, Paper 2C-43 in 1992 International Sherwood Fusion Theory Conference, Sante Fe, NM [Publ. Los Alamos National Laboratory, Los Alamos, NM, 1992].
- [16] R. Sydora, H. Naitou, J.M. Dawson, *Bull. Am. Phys. Soc.* **36**, 2347 (1991).
- [17] L. Sugiyama and W. Park, Paper 3C-29, in 1992 International Sherwood Fusion Theory Conference, Sante Fe, NM Publ. Los Alamos National Laboratory, Los Alamos, NM 1992].
- [18] S. Migliuolo, *Nucl. Fusion* **31**, 365 (1991).
- [19] F. Porcelli and S. Migliuolo, *Phys. Fluids* **29**, 1741 (1988).
- [20] F. Pegoraro, F. Porcelli, and T.J. Schep, *Phys. Fluids* **B3**, 1319 (1991).
- [21] R. Betti, S. Migliuolo and J.P. Freidberg, *Bull. Am. Phys. Soc.* **36**, 2346 (1991).
- [22] B. Coppi and F. Porcelli, *Phys. Rev. Lett.* **57**, 2272 (1986).
- [23] R. Betti, PhD thesis, Massachusetts Institute of Technology (1991).
- [24] R. Betti, J.P. Freidberg and S. Migliuolo, in preparation (1992).
- [25] J.A. Wesson, A.W. Edwards and R.S. Granetz, *Nucl. Fusion* **31**, 111 (1991).
- [26] L.E. Zakharov, B. Rogers and B. Coppi, submitted to *Phys. Fluids* (1992).
- [27] J.A. Wesson, *Nucl. Fusion* **30**, 2545 (1990).
- [28] W. Park, *Bull. Am. Phys. Soc.* **36**, 2455 (1991) and W. Park, S. Parker, H. Bigliari, M. Chance, L. Chen, C.Z. Cheng, T.S. Hahm, W.W. Lee, R. Kulsrud, D. Monticello, L. Sugiyama, R. White, *Phys. Fluids* (1992) to appear.
- [29] L. Zakharov, B. Rogers, B. Coppi, M.I.T./R.L.E. Report PTP-92/2, submitted to *Phys. Fluids*, 1992.
- [29] B. Coppi, J.W.-K. Mark, L. Sugiyama and G. Bertin, *Ann. Phys. (NY)* **119**, 379 (1979) and B. Coppi, B. Basu, *Phys. Fluids* **24**, 465 (1982).

II.B MICROTURBULENCE AND ANOMALOUS TRANSPORT

The relationship between microturbulence and the anomalous transport of particles and thermal energy is a topic long considered to be central to our understanding of plasma behavior in toroidal experiments.

i) Ion temperature gradient modes

One of the most important types of microturbulence arises from modes driven unstable by the ion temperature gradient (so-called "ITG", " η_i ", or "ion mixing" modes) [1-3]. From the initial pellet injection experiments in Alcator C [4] to the latest peaked density profile experiments in ASDEX (so-called P-mode operation) [5,6], the evidence strongly suggests that lowering the parameter $\eta_i = (d \ln T_i / dr) / (d \ln n / dr)$ leads to improved confinement. We are continuing our long standing commitment to the study of these modes in two major areas.

First, regarding their linear stability, we are analyzing the effects of non-uniform radial equilibrium electric fields, which induce a sheared $\mathbf{E} \times \mathbf{B}$ rotation of the plasma. Such a situation can occur, e.g. near the plasma edge, where this rotation can influence, through transport, the recycling and fuelling properties of the discharge. Indeed, these questions are relevant to experiments with off-center pellet deposition (e.g., JET and D-III-D) in which a strong density perturbation is seen to propagate inward, starting from a reversed density profile ($\eta_i < 0$). One must ask basic questions regarding particle transport by these drift-like modes (in the simplest models they transport thermal energy but not particles). Near the edge, impurities create a multi-ion species plasma that may permit particle transport and lead to isotopic modifications (see the next subsection). Our analysis [7] of the effects of nonuniform radial equilibrium electric fields is being carried out in collaboration with A. K. Sen of Columbia University, who is principal investigator on a linear experiment dedicated to the study of η_i -modes. This collaboration includes both theoretical work [8] as well as the modelling [9] of the linear experiment that is being carried out there.

Second, following experiments in both TFTR and JET that apparently

failed to confirm a correlation between “theoretically predicted ITG thresholds” and observed energy transport, we have begun an analysis [10] of linear stability properties in multi-ion species plasmas in shaped geometries e.g., elliptical cross sections. It is already known that, through a combination of dilution of the primary ions (which provide the free energy for the instability) and their own dissipation, the impurities can raise the threshold value of η_i , sometimes dramatically [10], for the slab branch. We recall that the toroidal branch of the ion temperature gradient mode was first investigated by us [11] and shown to arise both as an even parity mode (i.e., a mode with even symmetry about the $\theta = 0$ plane), which can be also driven unstable by trapped electrons [12], and an odd parity mode, driven unstable solely by the ion temperature gradient. Analyses concerning effects of impurities on the toroidal branch of the instability have so far been done [13,14] using semi-local approximations in circular cross sections. The research proposed here will treat the problem via a full non-local analysis and will establish each effect (shaping vs. impurities) independently to arrive at a unified picture of the linear stability of ITG modes in high temperature experiments.

Two further initiatives are being carried out with respect to the toroidal ion temperature gradient mode. One concerns the relevant theory to explain the experiments, for which we are associated with colleagues of the IFS, as reflected by the abstract corresponding to Ref. [15]. In particular, we are interested in trying to explain why the effective ion thermal conductivity decreases as a function of the ion temperature in experiments operating in the hot ion mode. The possible explanation that we are considering at present is that of finite- β effects. Further, together with Dr. B. Basu of the Phillips Laboratory, we have pointed out that η_i -modes can be converted from absolute to convective instabilities (non-normal modes) when a sheared $\mathbf{E} \times \mathbf{B}$ drift velocity is introduced. The transition from the L-regime of confinement to the H-regime can be interpreted in terms of this process [16].

ii) The isotopic effect

The question of an isotopic effect has remained open for a long time, since experiments in Alcator indicated that energy confinement times increase with the mass of the main ion species, e.g. for deuterium plasmas $\tau_E \sim \sqrt{2}\tau_E$ for hydrogen plasmas. This can be explained [17] if the spectrum of fluctuations that contributes the most to the electron and ion thermal energy transport is influenced by impurity driven modes [18-19], excited at the plasma edge. Then, for a larger main ion mass, the phase velocity window $v_Z^2 \leq (\omega/k_{\parallel})^2 \leq v_i^2$, where the subscripts Z and i refer to impurities and main ions, available for instability decreases and the fluctuation spectrum is reduced. An example of such a reduction of the unstable spectrum has been given for the collisionless case, where Landau damping from both species of ions plays an important role. Note that the presence of impurities permits particle transport of ions, even though the electrons respond adiabatically to the perturbations: one ion species moves inward while the other moves outward, preserving ambipolarity, hence the name "ion mixing mode".

Recently [20-21] we have revisited the fluid and kinetic theory of drift-type fluctuations driven unstable by the combination of impurities and the temperature gradient of the primary ions. This drift-like wave is driven by ∇T_i but propagates in the electron direction ($\omega \propto -dn_Z/dr \propto \omega_{*e}$) and appears at relatively short perpendicular wavelengths ($k_{\perp}\rho_i \sim 1$). The analysis, performed in a sheared slab geometry, quickly establishes that $D \sim \gamma/k_{\perp}^2 \propto \sqrt{m_Z/m_i}$, yielding a candidate mechanism for the isotopic effect. We are currently planning a nonlinear analysis of the fluid equations (in collaboration with a group at the University of Maryland), in order to more accurately establish the nonlinear spectrum and effective spatial scales affected by this mode (i.e., the scales over which it transports energy and particles).

iii) Approaches to the transport problem

Given the importance of making inroads into the transport problem we have adopted three different approaches: -one that starts from the theory of microinstabilities and of their simplest nonlinear evolution in order to gain an in depth understanding of the elementary processes upon which a global theory can be built. -another that attempts to identify the characteristics of relevant transport coefficients from the numerical simulation of significant experiments. -a third that is directed at constructing global transport equations that include both the indicators derived from the analysis of the experiments and those of the basic theory. The formulation of the principle of profile consistency [22] and the consequent early recognition [23] of the existence of thermal energy inflow processes are the result of this approach.

Recently, we have adopted the latter point of view in order to attempt to make a connection, in regimes where a significant population of trapped electrons is present, among the current density transport [24] the electron thermal energy transport the thermal energy inflow and the degradation of confinement that occurs in general when a form of subjected heating is applied to the plasma column.

In particular [25], the anomalous transport of the electron thermal energy and the longitudinal current density are assumed to be interdependent and to be described by a common matrix diffusion equation. The transport matrix is taken to be symmetrical in the case where the applied electric field is responsible both for driving the current and for heating the plasma. The transport coefficients that appear in the matrix diffusion equation are an electron thermal conductivity and a "thermo-viscous" coefficient that are of non-collisional origin. The latter coefficient describes the energy and current transport arising from the combined gradients of the electron temperature and current density. The energy transport related to the thermo-viscous coefficient can take the form of a thermal energy inflow when the effect of the current density gradient prevails, and provides a

clue to the nature of the so called "heat pinch".

We interpret the energy degradation that occurs in the case where externally injected heating is dominant over Ohmic heating in terms of the breaking of the symmetry of the transport equations. This changes the relationship between the electron temperature and the current density profiles, to a nonlinear dependence of the electron heat flow on the temperature gradient, and, most important, to an enhancement of the effective thermal conductivity which can account for the observed degradation of the energy transport.

We intend to investigate the effects of the predicted terms on the current density profile, through transport code simulation. A full test may be difficult, since it requires rewriting a code to handle a current evolution equation to avoid using fourth order operators in the standard magnetic field evolution equation. We intend to make good use, however, of an algorithm that already exists in the TSC code (Tokamak Simulation Code) for treating the effects of hyperresistivity. A simpler model that rearranges the current density profile has already been tested.

iv) Electron thermal energy transport by microinstabilities

The electron thermal transport is of considerable importance for toroidal plasmas. In order to qualify as a good candidate for driving this transport, a microinstability should have the following properties:

- 1) it should be driven by an electron temperature gradient
- 2) it should be active over a significant portion of the plasma column
- 3) its wavelength should be long enough to cause energy transport over macroscopic scales
- 4) it should produce a particle transport that is smaller than the energy transport.

We have analyzed the linear and quasilinear theory of the "ubiquitous" mode [11-12],[26-27], which is driven unstable by the combined effects of the electron temperature (pressure) gradient and the magnetic curvature drift of the trapped electrons. The integro-differential dispersion relation has been solved in toroidal geometry, including the effect of collisional detrapping of electrons. The instability persists with little change in growth rate over three orders of magnitude in $b_i = k_{\perp}^2 v_{Ti}^2 / 2\Omega_i^2$ and four orders in the effective collisionality $\nu_e^* = \nu_e / \epsilon \omega_{be}$ (ω_{be} is the electron bounce frequency, $\epsilon = r/R$ is the inverse aspect ratio) and has an increasing growth rate as $\eta_e = d \ln T_e / d \ln n$ increases. Quasilinear theory indicates that the heat flux is typically an order of magnitude larger than the particle flux. Thus this type of instability is a likely candidate to explain the electron thermal transport in present experiments covering a wide parameter range.

Having formulated [28] thermal diffusion coefficients based on this instability, we intend to continue testing them for auxiliary heated discharges using numerical transport codes. The strong $T_e^{3/2}$ temperature dependence requires the total electron diffusion to include a different diffusion coefficient to connect to the lower temperature ohmic regime, such as Coppi-Mazzucato-Gruber. We have recently begun to carry out Transport Studies of a D-T ignition [29-32]

using such a combination of coefficients in the transition regime between predominately ohmic and nonohmic (fusion and/or auxiliary) heating. This work will be continued in the next year.

REFERENCES

- [1] L. I. Rudakov and R. Z. Sagdeev, *Sov. Phys. Dokl.* **6**, 415 (1961).
- [2] B. Coppi, M. N. Rosenbluth, and R. Z. Sagdeev, *Phys. Fluids* **10**, 582 (1967).
- [3] T. M. Antonsen, Jr., B. Coppi, and R. C. Englade, *Nucl. Fusion* **19**, 681 (1979).
- [4] S. M. Wolfe *et al.*, *Nucl. Fusion* **26**, 329 (1986).
- [5] O. Gehre *et al.*, *Phys. Rev. Lett.* **60**, 1502 (1988).
- [6] F. X. Söldner *et al.*, *Phys. Rev. Lett.* **61**, 1109 (1988).
- [7] O. Mathey, A.K. Sen, and S. Migliuolo, in *Proceedings of the 1989 International Sherwood Theory Conference* (San Antonio, TX), paper 1D30.
- [8] S. Migliuolo and A.K. Sen, *Phys. Fluids* **B2**, 3047 (1990).
- [9] J. Chen, A.K. Sen and S. Migliuolo, *Phys. Fluids* **B4**, 512 (1992).
- [10] S. Migliuolo, submitted to *Nucl. Fusion* (1991).
- [11] B. Coppi and F. Pegoraro, *Nucl. Fusion* **17**, 960 (1977).
- [12] B. Coppi and G. Rewoldt, *Phys. Rev. Lett.* **33**, 1329 (1974).
- [13] R.R. Dominguez and M.N. Rosenbluth, *Nucl. Fusion* **29**, 844 (1989).
- [14] R. Paccagnella, F. Romanelli and S. Briguglio, *Nucl. Fusion* **30**, 545 (1990).
- [15] J.Y. Kim, W. Horton, and B. Coppi, in *Proceedings of the 1992 International Sherwood Theory Conference* (Sante Fe, NM), paper 3150.
- [16] B. Basu and B. Coppi, M.I.T./R.L.E. report PTP-92/1 (1992).
- [17] B. Coppi, *Bull. Am. Phys. Soc.* **34**, 2085 (1989).
- [18] B. Coppi, H.P. Furth, M.N. Rosenbluth, and R.Z. Sagdeev, *Phys. Rev. Lett.* **17**, 377 (1966).
- [19] B. Coppi, G. Rewoldt, and T. Schep, *Phys. Fluids* **19**, 1144 (1976).
- [20] B. Coppi, in *Plasma Physics and Controlled Nuclear Fusion Research 1990* (IAEA, Vienna), vol. 2, p. 413, (1991).
- [21] B. Coppi and S. Migliuolo, MIT/RLE Report PTP-91/11 (1991).
- [22] B. Coppi, *Comm. Plasma Phys. Cont. Fusion* **5**, 261 (1980).

- [23] B. Coppi, *Bull. Am. Phys. Soc.* **30**, 1631 (1985).
- [24] B. Coppi and F. Pegoraro, "Symmetries and Global Transport Equations," *Phys. Fluids* **B3** 2582 (1991).
- [25] B. Coppi and F. Pegoraro, "Energy and Current Transport: Symmetry Breaking and Degradation," M.I.T. Report PTP-92/2, Invited Paper to be published in the Proceedings of the International Conference on New Ideas in Tokamak Confinement, La Jolla, CA (April 1992).
- [26] B. Coppi and G. Rewoldt, *Phys Lett.* **A49**, 36 (1974).
- [27] B. Coppi, S. Migliuolo, and Y-K. Pu, *Physics Fluids* **B2**, 2322 (1990)
- [28] B. Coppi, *Comm. Plasma Phys. Cont. Fusion* **12**, 319 (1989).
- [29] M. Nassi, L. Sugiyama, S. Jardin and N. Pomphrey, *Bull. Am. Phys. Soc.* **35** 2133 (1990).
- [30] L. Sugiyama and M. Nassi, "Free Boundary Current Ramp and Current Profile Control in a D-T Ignition Experiment," M.I.T./R.L.E. Report PTP-90/8, to appear *Nucl. Fusion* (1992).
- [31] B. Coppi, M. Nassi and L.E. Sugiyama, "Physics Basis for a Compact D-T Ignition Experiment," to appear *Physica Scripta* (1992).
- [32] B. Coppi, M. Nassi and L.E. Sugiyama, invited paper, International Sherwood Theory Meeting, Sante Fe, NM (1992).
- [33] M.C. Kelley and C.W. Carlson, *J. Geophys. Res.*, **82**, 2343 (1977).
- [34] B. Basu and B. Coppi, *Geophys. Res. Lett.*, **15**, 417 (1988).
- [35] B. Basu and B. Coppi, *J. Geophys. Res.*, **94**, 5316 (1989).
- [36] B. Basu and B. Coppi, *J. Geophys. Res.*, **95**, 21213 (1990).
- [37] S.D. Scott, et al., in *Phys. Rev. Lett.* **64**, 531 (1990).
- [38] J.W. Connor, S.C. Cowley, R.J. Hastie and L.R. Pan, *Plasma Phys. and Cont. Fusion* **29**, 919 (1987).
- [39] S.D. Scott et al., in *Plasma Physics and Controlled Nuclear Fusion Research 1988*, Paper I.A.E.A.-CN-50/E-3-5 (publ. I.A.E.A., Vienna, 1989).
- [40] B. Coppi, M.I.T./R.L.E. Report PTP 89/2 (1989).

II.C BALLOONING MODES AND GLOBAL ALFVÉN WAVES IN FUSION BURNING PLASMAS

We have had a long term interest in investigating the nature of ballooning modes and of the global shear Alfvén modes from which they arise in toroidal plasmas where a population of fusion produced high energy particles is present [1]. Subsequently, the spectral properties of shear Alfvén modes in a toroidal plasma have been investigated by several authors [2,3]. Most of this analysis has been carried out within the framework of ideal MHD theory, though some extensions include resonances with high energy particle populations. Although the effects of toroidicity, ellipticity and triangularity have been separately included in recent works [4], an overall theoretical investigation of the combination of all of the above mentioned effects has yet to be undertaken. We propose to study the Alfvén modes from such a viewpoint in order to obtain a more realistic picture of the modes that can be excited in actual experimental settings and in particular in proposed experiments on fusion burning plasmas [5].

In this process, we will be collaborating with A. Turnbull of General Atomics, who has generated a numerical simulation code that produces the spectra of Alfvén waves when toroidicity, ellipticity and triangularity are included, and with H. Berk of the IFS (Institute for Fusion Studies), who is also interested in pursuing an analytic interpretation of the modes.

REFERENCES

- [1] B. Coppi and F. Pegoraro, *Comments, Plasma Physics Controlled Fusion* **5**, 131 (1979) and *Annals of Physics* **134**, 376 (1981).
- [2] S. Riyopolous and S. Mahajan, *Phys. Fluids* **29**, 731 (1986).
- [3] C.Z. Cheng and M.S. Chance, *Phys. Fluids* **29**, 3659 (1986).
- [4] R. Betti, Ph.D. Thesis, MIT (1992).
- [5] B. Coppi, M. Nassi and L. Sugiyama, *Physica Scripta*, in press.

II.D TRANSPORT SIMULATIONS AND THEORETICAL DEVELOPMENT OF TRANSPORT COEFFICIENTS

Starting with one of the first predictive transport codes, our group has been one of the few that have been able to carry out extensive numerical transport simulations and a combined program of theory and transport code development that has been primarily motivated by a desire to understand the physical principles underlying existing experiments rather than by contractual obligations to attempt to predict the behavior of proposed ones. During this time, transport simulation in "analysis" mode has become an accepted, even required, part of experimental analysis, but "predictive" codes have remained relegated primarily to trying to extrapolate the performance of proposed future machines. The situation is gradually changing with the increased interest in understanding plasma transport [1]. From the beginning, our group has maintained close contact between theoretical and simulation work. Simulation has provided means to test theories of thermal and particle transport and auxiliary heating; it has also provided valuable and even essential information for theoretical progress on these questions. The simulation of proposed ignition experiments, in D-T and also for advanced fuels such as D-³He or D-D, has indicated many of the areas of uncertain knowledge that are the most important for the ignition process.

Starting with Alcator A [2], the transport simulation work has dealt extensively with explaining the Alcator and related Frascati Torus (FT) series of experiments. The results have included a partly heuristic model of particle transport that involves an anomalous inward pinch and outward diffusion proportional to χ_e [3] that has been partly confirmed experimentally and has been generally accepted among transport modellers until very recently, for lack of a better description, the Coppi-Mazzucato-Grüber thermal transport model [4,5] that has been shown to apply in detail to many experiments, and the analysis of lower hybrid heating on Alcator C [6,7]. We have also carried out an extensive analysis of the transport in ohmic experiments such as TFTR [8] and

many others, including the improved confinement regimes due to pellet injection on Alcator C and ASDEX and the improved ohmic confinement (OC) regime with reduced particle recycling on ASDEX [9], high current discharges in JET [10], and the effects of neutral beam injection on transport in TFTR [11]. This work has given us an intimate appreciation for the difficulties of working with experimental data and the problems and uncertainties involved in comparing theoretical models to experiment. In particular, the fit of a given χ_e coefficient proved [8] to be difficult to verify on the basis of the fits to individual discharges within the uncertainties of the experimental data, even for a large range of discharge parameters in a well-diagnosed experiment; complete comparison also required a statistical analysis of the set of data.

We continue [12] to place importance on trying to understand the transport during ohmic heating, an area which has remained surprisingly obscure, but which is crucial [13] to the success of proposed D-T ignition experiments with high current and field.

We have also developed some of the first numerical models of sawtooth oscillations [2] and been the first to emphasize their potential importance for ignition [13,14], a now accepted fact. Numerical work [8] has shown the qualitative agreement of magnetic helical flux conservation during the sawtooth crash (Kadomtsev [15]) with soft X-Ray inversion radii in TFTR and the correlation of very flat or even hollow q profiles with partial reconnections.

Our use of numerical codes has allowed us to appreciate [13] the strong time dependent nature of the D-T ignition process (as well as the ignition of any other plasma mixture). This fact has still not been generally recognized. (Our work in this area is summarized in Section II.E)

We have extensively tested the concept of "profile consistency" [4] of the electron temperature radial distribution, which is linked with the toroidal current density in ohmically heated discharges, in many experiments. The question of the mechanisms that sustain the profile shape in the presence of auxiliary heating, as usually observed, has been the subject of ongoing investigation on the basis

of a slow and a fast diffusion process [16,17].

Based on our transport and statistical analysis of experimental data for ohmic heating in TFTR [8] and other experiments [9], we have refined our ideas about profile consistent electron thermal transport coefficients for ohmic heating. We have proposed a model [12], based on the observed surface loop voltage scaling and an assumption on the primary processes responsible for the transport, that reproduces the observed total energy confinement time scaling. For the TFTR discharges considered, a large amount of radiation loss due to impurity ions, relative to the ohmic heating, breaks one of the degeneracies in the electron energy balance for purely ohmically heated plasmas, since the radiation loss comes primarily from the edge of the plasma and depends on the concentration of impurities rather than the central T_{e0} . The experimental data shows that it is indeed the voltage that has a good statistical regression, power law scaling with the global plasma parameters such as $\bar{n}_e$, I_p , B_T , R , a , and Z_{eff} . In such a case the electron thermal diffusion must be proportional to the net electron heating, e.g., $P_{He} \simeq P_{OH} - P_{Rad} - P_{ie}$. This quantity does not have a scaling with the global plasma parameters [8]. Any diffusion coefficient for ohmic heating must also imply a suitable voltage scaling as well as a τ_E scaling. Analysis [12] of commonly used ohmic, profile consistent electron thermal diffusion coefficients, shows, in the case of Tang-Redi [18], that it does not have a reasonable voltage scaling. Furthermore, when energy losses such as radiation are strong, it attempts to impose a scaling on P_{He}/P_{OH} , which does not exist experimentally. On the other hand, a form like that of Mukhovatov-Merezhkin [19] can be seen to be similar to Coppi-Mazzucato-Grüber in general principle.

An additional conclusion can be made about the behavior of χ_e^{an} . The general form of a profile consistent electron thermal diffusion coefficient in steady state, given the existence of a good voltage scaling, is

$$\chi_e^{an}(r) = \frac{\epsilon \bar{V}}{4\pi R^2} \frac{a^2 I_\phi(r)}{\alpha_T r^2} \frac{1}{n_e(r) T_e(r)} \frac{P_{He}(r)}{P_{OH}(r)}$$

where $\bar{V}$ is the voltage scaling, $\epsilon \sim O(1)$ is a constant, $I_\phi(r)$ is the toroidal

plasma current within rad r , and for concreteness we have assumed the canonical electron temperature profile to be $T_e(r) = T_{eo} \exp(-\alpha_T r^2/a^2)$, where $\alpha_T \simeq$ constant. Then χ_e^{an} can have a scaling with the plasma parameters only where $P_{He}(r)/P_{OH}(r)$ does, that is, when $P_{He} \simeq P_{OH}$. In general, the ion thermal diffusion coefficient $\chi_i^{neo} > \chi_e^{an}$ near the magnetic axis. In plasmas with significant impurity-induced radiation this condition may be roughly satisfied at mid-radius, $r \simeq a/2$.

We note that this lack of scaling for χ_e^{an} is still consistent with the existence of a scaling for $\tau_E = W/P_{HEAT}$ as is generally observed.

The anomalous ion thermal diffusion has also been investigated, particularly for "ion mixing" [20,21] (temperature gradient or η_i) modes. The models incorporate the expected parameter dependence of the transport, inferred in part from the dependences of the quasilinear coefficient [21] and a critical η_i that is a local function [22,23].

In a few years, we have expanded our transport capabilities from one dimensional, circular model geometries to general axisymmetric geometries in two dimensions, with a fixed or freely evolving plasma boundary, with the acquisition of the BALDUR 1 1/2D transport code from Glenn Bateman of PPPL and the TSC code [24] from S.C. Jardin and N. Pomphrey of PPPL. The BALDUR has been used to study the effects of the geometry, including paramagnetism on low temperature, high density D-T ignition. The question of the appropriate characteristics for a profile consistent thermal diffusion coefficient in a general flux surface geometry have also been addressed [12,23]. The Baldur code has been modified to study the D-³He ignition problem with multiple ion species. We are also using the free boundary TSC code [24], with strong support of its authors, S.C. Jardin and N. Pomphrey of PPPL. Work so far has included the problem of vertical control in a D-T experiment [25] and the problem of the volt-second requirement [26] as well as the problem of D-T ignition [27-30] described in Section II.E. We have compared the TSC code against our other, well tested codes and uncovered some major errors in TSC. We have also added and intend to

add the numerical models for some important plasma process. For example, the neoclassical ion thermal transport, additional models for the electron thermal transport have already been added and in the future we will consider the particle transport, a high temperature synchrotron radiation model, and tests for the stability of the plasma to various modes. Our corrections have been incorporated into the standard version of TSC that is available for general distribution.

One of the primary objectives of work that has been carried out over the past year and is still actively in progress is to characterize and optimize the initial current ramp phase in a D-T ignition experiment with respect to maximizing the plasma heating and controlling the internal modes that are associated with sawtooth oscillations and other reconnection instabilities [27-30]. Sawtooth control is a difficult problem because of the high current, which tends to force the central q_0 below unity fairly quickly. In the past year, we have shown that a significant degree of control over the central q is possible [28,29], and that the plasma can be maintained with monotonic q and toroidal current density profiles if the current ramp, plasma location, size and shaping, and particle density distribution are appropriately controlled, in the presence of neoclassical resistivity alone.

We are also investigating the effects of an anomalous component to the neoclassical resistivity, which rearranges the local current density and to a lesser extent the pressure distribution, but keeps the total effect neoclassical as generally observed [31] (Section II.B).

As a complement to this approach, we have used a simple phenomenological model in a transport code to investigate the plasma evolution in general axisymmetric geometry. The model is consistent with existing experimental information concerning the current penetration, including the evolution of the central q_0 in experiments as diverse as JET heated with ICRH and ohmically heated TEXTOR. At the same time it reproduces well-behaved profiles of the current density in steady state.

Another objective is to incorporate the important axisymmetric geometry

effects into a fast, simple 1D transport code [32] that can be used to study both high and low beta regimes (discussed in detail in Section II.E).

We intend to continue work on testing theoretical models for the thermal diffusion of both electrons and ions, applicable to both ohmic and auxiliary heating. The new versions of profile consistent ohmic coefficients were planned to be tested in the past year, paying particular attention to the meaning of profile consistency in a shaped, axisymmetric plasma. Unfortunately, we have not been able to obtain sufficient access to good data from JET, consisting of both flux surface geometry and measured profiles. Newer theories modify the electron and ion thermal transport and the particle transport simultaneously and tend to link effects that in the past were treated as isolated. The “ubiquitous” mode [33] (Section II.E) depends upon η_e as well as η_i and is a strong candidate for explaining much of presently observed transport [34]. We have implemented such a model for the nonohmic heating regime of a D-T ignition experiment [29,30] and we intend to test these diffusion coefficients against experimental data. We will also look at the isotopic effect on plasma energy confinement, which explains [35] why plasmas consisting of a heavier main ion species should have better confinement, based on the effect of impurity gradient driven modes (Section II.B). We will also continue to develop the theory [36] (Section II.B) and numerical models [29,30] for transport associated with η_i and other modes for the ion anomalous thermal diffusion.

We expect to look into transport in the transition region from ohmic to auxiliary heating in more detail, since this is crucial to high field D-T ignition. In the past two years, we have been investigating the effect of the nonohmic degradation of confinement on D-T ignition. We have studied the modeling of the transition regime between ohmic and nonohmic heating, for D-T ignition plasmas where the total nonohmic heating $P_\alpha + P_{INJ} \leq (3 - 4) P_{OH}$ and for reasonable parameters, $P_\alpha \leq 2P_{OH}$ with $P_{INJ} = 0$. We have proposed [29,30] a form for the electron thermal diffusion coefficient,

$$\chi_e = \chi_e^{OH} \left(\frac{V_{\phi*}}{V_\phi} \right)^{2/3} + \gamma_i \left(\frac{P_\alpha + P_{INJ}}{P_\alpha + P_{INJ} + P_{OH}} \right) \chi_e^{UB},$$

where χ_e^{OH} is a standard ohmic coefficient, such as Coppi-Mazzucato-Grüber, that predicts a loop voltage for ohmic steady state conditions, $(V_{\phi*}/V_\phi)$ is the ratio of the predicted to the actual voltage, which ensures that the ohmic term increases with temperature above the steady state. In the second term, γ_i is a weighting constant, and χ_e^{UB} is a “nonohmic” coefficient that is based on a combination of the trapped electron “ubiquitous” mode [33] and the collisional impurity driven mode [37] and reproduces observed “L-mode” confinement scalings [38]. At ignition in a high field plasma, the second term is assumed to dominate the transport. We hope to test this form against experimental data in the near future, although there has been relatively little work done on the transition regime where $P_{INJ} \leq 2P_{OH}$.

We intend to continue to study the transport properties of the improved confinement regimes, such as achieved in the central, strongly peaked profile region of discharges with pellet injection seen on JET. We expect to work on particle transport in general, in light of the recent new results from perturbative and impurity measurements.

REFERENCES

- [1] W.A. Houlberg, D.W. Ross, G. Bateman, S.C. Cowley, P.C. Efthimion, W.W. Pfeiffer, G.D. Porter, D.E. Shumacher, L.E. Sugiyama, J.C. Wiley, *Phys. Fluids* **B2** 2913 (1990).
- [2] B. Coppi, A. Taroni, and G. Cenacchi, in *Plasma Physics and Controlled Nuclear Fusion Research*, 1978 (I.A.E.A, Vienna, 1979) Vol. 1, p. 487.
B. Coppi and A. Taroni, "Numerical Simulation of High Density Regimes in Alcator," in *Proc. Varenna Symp. on Heating in Thermonuclear Plasmas*, 1976 (Editrice Compositori, Bologna, Italy, 1977), p. 192.
- [3] B. Coppi and N. Sharky, *Nucl. Fusion* **21** 1363 (1981).
- [4] B. Coppi and E. Mazzucato, *Phys. Rev. Lett.* **71A** 337 (1979).
- [5] O. Gruber, *Nucl. Fusion* **22** 1349 (1982).
- [6] P.T. Bonoli and R.C. Englade, *Phys. Fluids* **29** 2937 (1986).
- [7] P.T. Bonoli, M. Porkolab, Y. Takase, S.F. Knowlton, *Nucl. Fusion* **28** 991 (1988).
- [8] L.E. Sugiyama and P.C. Efthimion, "Predictive Transport Simulation of TFTR Ohmic Discharges," M.I.T./R.L.E Report PTP-89/14 (1989).
- [9] L.E. Sugiyama, "Electron Thermal Transport in Ohmic Discharges," M.I.T./R.L.E. Report PTP-89/3 (1989), to be submitted to *Nucl. Fusion*.
- [10] R.C. Englade, "Transport Simulation of 7 MA JET Ohmic Discharges," M.I.T./R.L.E. Report PTP-89/10 (1989).
- [11] R.C. Englade, "Electron and Ion Thermal Transport in the Transition Regime", M.I.T./R.L.E. Report PTP-89/5 (1989).
- [12] B. Coppi and L.E. Sugiyama, "Transport Coefficient for Well-Confined Plasmas," M.I.T./R.L.E. Report PTP-89/19 (1989).
- [13] B. Coppi and L.E. Sugiyama, *Comm. Pl. Phys. Cont. Fusion* **10** 43 (1986).
- [14] B. Coppi, P.T. Bonoli, G.B. Crew, R. Englade, J.J. Ramos, N. Sharky, L. Sugiyama, in *Plasma Physics and Controlled Nuclear Fusion Research*, Baltimore, 1982 (I.A.E.A., Vienna, 1983) Vol. 3, p. 307.

- [15] B.B. Kadomtsev, *Fiz. Plazmy* **1** 710 (1975).
- [16] B. Coppi, *Phys. Lett.* **A128** 193 (1988).
- [17] B. Coppi, P. Detragiache, R. Englade, S. Migliuolo, F. Pegoraro, F. Porcelli, Y.K. Pu, and L. Sugiyama, in *Plasma Physics and Controlled Nuclear Fusion Research*, Nice, 1988 (I.A.E.A., Vienna, 1989), Vol. 2., p. 201.
- [18] W.M. Tang, C.Z. Cheng, J.A. Krommes, et al., in *Plasma Physics and Controlled Nuclear Fusion Research*, London, 1984 (I.A.E.A., Vienna, 1985), Vol. 2, p. 213; M.H. Redi, W. Tang, et al., *Nucl. Fusion* **27** 2001 (1987).
- [19] V.G. Merezhkin and V.S. Mukhovatov, *Pis'ma Zh. Ehksp. Teor. Fiz.* **33** 463 (1981) [*JETP Lett.*, **33** 446 (1981)].
- [20] B. Coppi and C. Spight, *Phys. Rev. Lett.* **41** 551 (1981).
- [21] B. Coppi, S. Cowley, P. Detragiache, R. Kulsrud, F. Pegoraro, and W. Tang, in *Plasma Physics and Controlled Nuclear Fusion Research*, London, 1984 (I.A.E.A., Vienna, 1985) Vol. 2, p. 93.
- [22] T. Antonsen, Jr., B. Coppi, and R. Englade, *Nucl. Fusion* **19** 641 (1979).
- [23] R.C. Englade, *Nucl. Fusion* **29** 999 (1989).
- [24] S.C. Jardin, N. Pomphrey, and J. DeLucia, *J. Comp. Phys.* **66** 481 (1986).
- [25] M. Nassi, J.C. Jardin, C. Kessel, and N. Pomphrey, "Vertical Stability Analysis for the Ignitor," M.I.T./R.L.E. Report PTP-91/10 (1991).
- [26] M. Nassi, "Volt-Second Requirement and Relevant Ignition Margin for the Ignitor Device," M.I.T./R.L.E. Report PTP-90/1, final version March 1992.
- [27] B. Coppi, R. Englade, M. Nassi, F. Pegoraro, L. Sugiyama, in *Plasma Physics and Controlled Nuclear Fusion Research, 1990*, Washington, D.C., paper CN-53/D-4-14.
- [28] L.E. Sugiyama and M. Nassi, to appear, *Nucl. Fusion* (1992).
- [29] B. Coppi, M. Nassi, L. Sugiyama, "Physics Basis for Compact Ignition Experiments," to appear *Physica Scripta* (1992).
- [30] B. Coppi, M. Nassi, L. Sugiyama, invited paper at International Sherwood Fusion Theory Conference, Sante Fe, NM, 1992.
- [31] B. Coppi and F. Pegoraro, *Phys. Fluids* **B3** 2582 (1991).

- [32] L.E. Sugiyama, 17th IEEE International Conf. on Plasma Science, Oakland, 1990.
- [33] B. Coppi and G. Rewoldt, *Phys. Rev. Lett.* **33** 1329 (1974) and B. Coppi, F. Pegoraro, *Nucl. Fusion* **17** 963 (1977).
- [34] B. Coppi, S. Migliuolo, and Y.K. Pu, *Phys. Fluids* **B2** 2322 (1990).
- [35] B. Coppi, *Bull. Am. Phys. Soc.* **34** 2085 (1989)
- [36] B. Coppi, in *Plasma Physics and Controlled Nuclear Fusion Research 1990*, Washington D.C., paper CN-53/I-2-6, and B. Coppi, S. Migliuolo, M.I.T. /R.L.E. Report PTP-91/11 (1991).
- [37] B. Coppi, H.P. Furth, M.N. Rosenbluth, R.Z. Sagdeev, *Phys. Rev. Lett.* **17** 377 (1966).
- [38] K. Lackner, N.A.O. Gottardi, *Nucl. Fusion* **30** 767 (1990).

II.E TRANSPORT SIMULATION OF DETERIUM-TRITIUM IGNITION

Since tight aspect ratio, high current and field ignition experiments were first proposed [1], our group has emphasized the development of time dependent, numerical transport models for the study of ignition. Early transport studies of Ignitor [2-4] served as part of the basis for the initial studies of CIT/BPX. The importance of sawtooth oscillations during ignition ("sharktooth oscillations") first was shown in this context in 1976 [2].

The importance [5] of the transient nature of the ignition process, and of the accompanying spatial variation — for example, of the toroidal loop voltage V_ϕ , that causes the maximum ohmic heating to occur away from the magnetic axis, even during the constant current "flattop" phase of the discharge — has even now not been universally recognized. The importance of the initial phase of the discharge, when the plasma current is raised to its maximum value (the current ramp) and the plasma brought to its final size and shape, in the ignition of a high current machine has been investigated extensively during the past two years [6]. These are issues vital to all ignition experiments, not just high field ones, and we intend to continue this investigation in the current year. Our work is the first detailed study of the current ramp for ignition experiments and the first current ramp study performed using a free boundary plasma model.

Much of our transport work has focused on high field, tight aspect ratio configurations, which are exemplified by the Ignitor [7] and to a lesser extent, the design that was proposed for the CIT/BPX. We have shown, previously [e.g., 4,5,8,9,10] and in work that continues through the present [11-15], that ohmic ignition is possible in designs with maximum ratios of magnetic field to major radius B_T/R , if the thermal transport does not increase too much over ohmic levels for typical levels of the fusion heating $P_\alpha \leq 2P_{OH}$, the ohmic heating, at ignition and if sawtooth oscillations are either restricted to a small spatial region or have a repetition time that is not too much smaller than the energy confine-

ment time of the plasma. A sawtooth period that increases with temperature, which might be expected on the basis of the known stabilizing effects of high temperature on internal instabilities, discussed in a previous section, has also been shown to allow ignition [10].

In the past two years [11-15] we have obtained results from free boundary simulations on the effects of the current ramp, the evolution of the toroidal current distribution, and control of sawtooth oscillations. They have shown that very low temperature ignition, $T_{eo} \simeq T_{io} \simeq 11-12$ keV, with $P_\alpha \leq 2P_{OH}$ is likely to be possible in this type of configuration, for central densities $n_{eo} \simeq 10^{15}$ cm⁻³ in a relatively peaked density profile. The low temperature and fusion power has favorable consequences for reduced wall loading due to fusion reactions and better plasma stability at low β .

Recent and ongoing work also includes the effects of injected (lower hybrid and electron cyclotron radio frequency) heating, pellet injection, and the issues of burn control and vertical stability control for D-T ignition experiments. We have also been working on the development of a simple, fast 1D transport code that reproduces the important effects of axisymmetric geometry. We expect to continue to work on many of these subjects in the coming year.

i) Role of the Current Ramp Phase and the Current Density Evolution

We are investigating [11-15] the plasma dynamics of the current ramp phase and the role of the evolution of the toroidal current density in the complete evolution of a plasma discharge in a deuterium-tritium ignition experiment. Results have been obtained using the TSC [16] code developed by S.C. Jardin, N. Pomphrey, and co-workers, and we have received strong support from the authors on the problems of running the code. The code models the plasma evolution, positional stability, and control properties of axisymmetric, free boundary tokamaks. This problem is very complex, due to the disparate time scales of diffusion- and wave-like phenomena, and to the anisotropy introduced by the magnetic field. The code solves the plasma momentum and magnetic field evolution equations

on a two-dimensional X-Z grid and the plasma energy and particle density evolution equations in a one dimensional flux coordinate. All the external magnetic field coils are explicitly included, while a set of poloidal conductors model the passive structure of the plasma chamber.

Our results, obtained over the past two years, constitute the first free boundary investigation of ignition and are the first to look in detail at the effect of the current ramp on D-T ignition in plasmas dominated by ohmic heating (a study focussing on sawtooth effects has previously been carried out, with a fixed boundary code [17]). In a compact, high field experiment that operates at relatively high plasma current and low q , the current ramp phase plays an important role in determining the time to ignition and in maintaining the stability of the plasma. We have shown that the ohmic heating P_{OH} increases continuously during the current ramp if the plasma density is raised simultaneously with the current, as the plasma is grown in size, and can reach high values by the end of the ramp, even if the central temperatures become large. The ohmic heating then decays relatively slowly during the current flat-top, because it depends upon the decay of the hollow voltage V_ϕ profile, which is large near the plasma edge, rather than on the central $V_{\phi 0}$ or equivalently, T_{eo} .

For an ohmically heated plasma, we define ignition to be the time when the fusion alpha particle heating of the plasma, P_α , equals the plasma thermal losses P_L . The time to ignition is limited from above by the time it takes to develop instabilities associated with the relaxation of the current profile, such as large radius sawtooth oscillations, and from below by the amount of nonfusion heating.

In the proposed Ignitor experiment, designed to have $I_p = 12\text{MA}$, $B_T = 13\text{T}$, $R = 1.3\text{ m}$, $a = 0.48\text{ m}$, $\kappa = 1.8$, low temperature D-T ignition ($T_{eo} \simeq T_{io} \simeq 11\text{--}12\text{ keV}$ at density $n_{eo} \simeq 10^{15}\text{ cm}^{-3}$) should be attainable within a short time after the end of the ramp when the fusion heating by α -particles $P_\alpha \leq 2P_{OH}$. In this regime the thermal energy confinement has not degraded completely from its maximum ohmic levels and the required values appear to

be compatible with both predicted ohmic behavior and with the empirically derived behavior of degraded “L-mode” confinement for nonohmically heated plasmas. The current density evolution and therefore plasma stability has also been found to be sensitive to the energy confinement. We have considered several forms for thermal energy transport coefficient that reproduce the magnitude and presumed radial form of the transport when injected heating is applied, to study the importance of the transition regime between ohmic and fusion heating.

Lower temperatures allow the current, deposited at the edge of the plasma during the current ramp, to penetrate faster into the interior, leading to larger $q \leq 1$ regions in the center of the plasma and possibly also to hollow current density profiles, which are susceptible to magnetic reconnection. The central peaking of the radial profiles of both the electron temperature and the plasma particle density are also important. Simulation shows that there is a level of energy confinement that should allow stability to the modes associated with magnetic reconnection to be maintained until past ignition, according to the stability theory described in Section II.C, when all these factors are taken into account.

To investigate the plasma stability, we have compared the TSC calculation of the current evolution in Ignitor to the empirically-determined, experimental stability criteria for localized electromagnetic mode activity in the interior of the JET experiment [18]. These modes are believed to be triggered by the development of hollow current density profiles in the interior of the plasma. The speed of the occurrence of hollow profiles in the simulation was found to correspond to the degree of violation of the l, q_ψ , (internal inductance – edge magnetic safety factor), stability boundary, when the current density was assumed to diffuse under a collisional electrical resistivity that includes trapped particle effects. The latest results from JET suggest that the potentially dangerous “locked” or “quasi-stationary” modes that are often associated with eventual plasma disruptions initially result from the interaction of an edge mode at integral q and a non-monotonic q profile with multiple rational surfaces at the same q in the plasma

interior. The JET stability prescription, rigorously followed for the Ignitor, prevents the development of nonmonotonic q profiles and so should be expected to prevent the occurrence of locked modes. This also proved to be physically consistent with our assumption of a generally neoclassical resistive diffusion of the plasma current, since experimental evidence now strongly associates anomalous current penetration with instabilities triggered by hollow q profiles.

Our results also point out the importance of the temperature in the outer region of the plasma column to the current evolution and thus to ignition. The results are compatible with previous current ramp experiments, such as those using gas puffing to control the temperature [19]. The temperature in the outer part of the tokamak could be used to control the rate of current penetration during and after the ramp, if the profile can be adjusted. The exact rate of penetration in an ignition plasma remains uncertain, since the edge temperature is controlled partly by processes external to the plasma proper.

We have considered the problem of checking the current ramp simulation against experiment, but the prospects for using a shaped plasma are not bright. The TSC cannot be applied directly to JET, since TSC cannot model its iron core transformer; the other shaped tokamak, D-III-D, is sensitive to error fields, usually runs with a divertor, and does not normally ramp the current at a constant value of the edge q_a . In addition, plasma diagnostics are not usually set up to measure the shifted, small size plasmas that exist during the ramp.

In addition to the work reported above, we have recently refined and updated our study of the volt-second requirements for the Ignitor [20]. In particular, recent numerical simulations have shown that by programming the plasma density evolution, it is possible to reduce the dissipative volt-second consumption. This is accomplished by slowly increasing the plasma density during the first part of the current ramp, in order to reach a relatively high peak plasma temperature ($T_{eo} \geq 4$ keV), and thus a low plasma resistivity as soon as possible. This procedure must allow an adequate current penetration rate in order to satisfy plasma stability criteria and to guarantee a sufficient level of ohmic

heating.

ii) Particle Density Profile and Ignition

Work performed in the past year has suggested that the effects of broad particle density profiles on the evolution of the current density and the associated plasma stability may not be as bad as we had originally suggested [13]. If the central density is allowed to drop below 10^{15}cm^{-3} , ignition may still be possible. We must assume, however that no additional strong thermal transport is triggered by the large density scale length associated with a flattened density profile. Recent results obtained by W. Houlberg [21], that model the pellet deposition and particle transport, suggest that ignition is possible even with relatively low velocity pellets that do not penetrate completely into the plasma. In this case, small pellets were injected regularly throughout the current ramp to produce the desired rate of plasma density rise. Because the pellets did not penetrate to the center, the density profile was, on the average, almost flat until some time after the current flattop was reached and pellet injection ceased. Again, ignition could be achieved if the thermal transport did not fall too far.

The possibility of using broad density profiles and their effects on ignition will be a topic of investigation for the coming year. Our earlier results [22], using a standard pellet ablation model in a transport code, have shown that pellets should penetrate well into the interior of a high field (Ignitor-like) plasma, even at velocities well below those now considered attainable.

iii) Auxiliary Heating and Heating During the Current Ramp

In the past year, we have found that a small amount of auxiliary heating (such as 5 MW of ion cyclotron radio frequency heating (ICRH) in an Ignitor-like plasma) applied during the latter part of the current ramp, can be sufficient to keep the $q \leq 1$ region very small, or even prevent its existence, depending upon the exact variation of the neoclassical electrical resistivity near the magnetic axis. This effect is achieved if the central electron temperature can be brought to the level of about 10 keV or greater before the end of the current ramp,

to effectively "freeze-in" the central toroidal current density at relatively low levels, when it penetrates resistively. While the low level of auxiliary heating also provides a boost to ignition, the major effect on cases with degraded parameters is through the prevention of a large $q \leq 1$ region, which can otherwise easily extend over half of the plasma minor radius. The $q \leq 1$ region remains small until well past ignition. Larger amounts of injected power, for example 15 MW, can significantly extend the plasma parameters that allow ignition. The potential stability problem then becomes the appearance of regions of low magnetic shear (constant q) at values of q significantly above unity and below 2. Analyses [11] that we have performed with the PEST-1 and PEST-2 codes [23,24], obtained courtesy of J. Manickam of PPPL, show that these profiles are usually stable to ideal MHD modes, until the q in this region drops to near unity, but resistive modes should also be considered.

Our earlier work [25] on lower hybrid heating for tight aspect ratio, high field ignition experiments therefore becomes of greater interest, since the LH waves will penetrate significantly better in the lower magnetic field of the current ramp, and only a relatively small amount of heating appears to have a strong effect on the current profile.

We intend to continue the study of this problem in the coming year.

iv) **A Simple, Fast, 1D Transport Model for Axisymmetric Geometries**

Elongation and shaping of the plasma cross section provide many advantages, including increased plasma current for a given R , and lower beta, as well as better control of MHD instabilities at low beta. Proposed tight aspect ratio D-T ignition experiments rely on elongations of 1.8–2. Shaping also has important effects on the plasma evolution, through modifications of the ohmic heating, transport coefficients, and other geometrical and finite beta effects on the plasma processes. At present these effects are modelled using 1 1/2D transport codes, which compute the axisymmetric magnetic flux surfaces. These codes are relatively large, time consuming, and complicated to use. In addi-

tion, many theories and models have been developed for simplified geometries, such as circular cylindrical or even slab configurations, and the generalization to noncircular, axisymmetric configurations introduces additional free parameters that must be determined either from physical considerations or comparison to experiment. D-T ignition, in particular, has proven to be sensitive to the details of some 1 1/2D models. Advanced fuel ignition, such as D-³He or D-D, is also affected, because most plasma equilibrium solvers incorporated into existing 1 1/2 D codes are numerically sensitive to high beta. For these reasons, a simpler one-dimensional transport model, based on a flux surface variable, is being developed [26] that attempts to include the two dimensional effects in a simplified way that still reflects their physical origins. Previous work on transport modelling of present day and future D-T and advanced fuel ignition experiments, some of which is described in other sections, provides the basis for the code. It will be checked against fixed and free boundary 1 1/2 D codes and against available experimental data. This work is expected to continue in the coming year.

v) D-T Burn Control

The ignition of advanced fuels and associated issues of burn control are considered separately in Section II.F. The fixed boundary transport models contain high temperature effects such as the complete set of fusion reactions important for the energy balance, a "local" synchrotron radiation model, and bremsstrahlung radiation that should be valid at temperatures of D-T burning. The thermal transport and the particle and impurity behavior is much more uncertain. As a first step, a study of D-³He burning in Ignitor has been carried out [27] (see Section II.F). Burn control will be a major topic this year. In particular, we will study the role of a current ramp down, after ignition is achieved, in extending the fusion burning time of the discharge and in controlling the level of fusion burning for a tight aspect ratio, high field D-T experiment.

vi) Vertical Control

The elongated plasma configuration in Ignitor-like experiment is potentially unstable to vertical motion. An extensive numerical simulation [28] of the plasma dynamics has been carried out using the TSC code. The stability behavior of the plasma/vacuum vessel/poloidal field coils system has been analyzed, taking into account, in a two dimensional (axisymmetric) space, the geometry of the machine, the position of the diagnostic magnetic pick up coils, and the characteristics of the power supplies in terms of voltage limitations and response times. The minimal plasma vertical growth time (τ_v), defined as the reciprocal of the linear exponential growth rate of the plasma vertical position, has been estimated to be about 15 ms when the presence of the thick vacuum vessel is taken into account and the poloidal field coils are connected in such a way that antisymmetric current can be induced in the up and down symmetric coils. The toroidal magnet coils can be expected to have an additional beneficial effect in slowing the plasma motion. This factor will be considered in the next analysis.

The best results, in terms of fast plasma position control and lower power requirement, use a combination of one inboard coil and one outboard coil. The inboard coil is less coupled to the plasma and cannot control the plasma motion by itself. However, it can produce a radial magnetic field that diffuses rapidly into the plasma and slows the vertical motion, reducing the power requirement on the outboard coil. Both proportional and derivative gains are used in the feedback algorithm for the current in the inboard and outboard coils, while a simple proportional gain is used to determine the voltage.

Some simulations have been carried out to evaluate the influence on τ_v of the small variation around the reference value of some plasma parameters, such as β_p , the normalized internal inductance l_i and the vertical elongation κ . The results show that β_p and κ have a very weak effect on the plasma vertical motion. The relatively mild influence of κ (for variation $\Delta\kappa = \pm 10\%$) on τ_v is due [29] to the presence of a close-fitting vacuum vessel. In particular, if κ is increased, a larger field index ($n_v \equiv -(R_o/B_z)(\partial B_z/\partial x)$, where x and z are

the horizontal and vertical coordinates) is required for the equilibrium and the plasma becomes more unstable. However, at the same time a more elongated plasma is closer to the vacuum vessel whose stabilizing effect is therefore stronger. Lower values of l_i give rise to lower values of τ_v because narrow toroidal plasma current distributions mean that the plasma current lies on average farther from the vacuum vessel, and the equilibrium configuration at lower l_i requires a larger value of the field index for the same elongation.

REFERENCES

- [1] B. Coppi, *Comm. Plasma Phys. Cont. Fusion* **3** 2 (1977).
- [2] B. Coppi, A. Taroni, and G. Cenacchi, in *Plasma Physics and Controlled Nuclear Fusion Research*, Berchtesgaden, 1976 (I.A.E.A., Vienna, 1977) Vol. 1, p. 487.
E. Bittoni, B. Coppi, M. Haegi, and A. Taroni, in *Theoretical and Computational Plasma Physics*, Trieste, 1977, (I.A.E.A., Vienna, 1978), p. 117.
- [3] B. Coppi, P.T. Bonoli, G.B. Crew, R. Englade, J.J. Ramos, N. Sharky, L. Sugiyama, in *Plasma Physics and Controlled Nuclear Fusion Research*, Baltimore, 1982 (I.A.E.A., Vienna, 1983) Vol. 3, p. 307.
- [4] L.E. Sugiyama, "Transport Simulation of a Burning Core Experiment," M.I.T./R.L.E. Report PTP-84/2 (1984).
- [5] B. Coppi and L.E. Sugiyama, *Comm. Pl. Phys. Cont. Fusion* **10** 43 (1986).
- [6] L.E. Sugiyama and M. Nassi, International Sherwood Theory Meeting, Williamsburg, VA, 1990.
- [7] B. Coppi and the Ignitor Design Team, in *Plasma Physics and Controlled Nuclear Fusion, Nice, 1988* (IAEA, Vienna, 1989) Vol. 3, p. 357.
- [8] B. Coppi, P. Detragiache, R. Englade, S. Migliuolo, F. Pegoraro, F. Porcelli, Y.K. Pu, and L. Sugiyama, in *Plasma Physics and Controlled Nuclear Fusion, Nice, 1988* (IAEA, Vienna, 1989) Vol. 2, p. 201.
- [9] R.C. Englade, *Nucl. Fusion* **29** 999 (1989).
- [10] R.C. Englade, M.I.T./R.L.E Report PTP-89/12 (1989).
- [11] L. Sugiyama and M. Nassi, "Free Boundary Current Ramp and Current Profile Control in a D-T Ignition Experiment," M.I.T./R.L.E. Report PTP-90/8 (1990), to appear *Nucl. Fusion* (1992).
- [12] B. Coppi, R.C. Englade, M. Nassi, F. Pegoraro, and L. Sugiyama, in *Plasma Physics and Controlled Nuclear Fusion Research 1990*, 1990 (I.A.E.A., Vienna, 1991) paper D-4-14.
- [13] B. Coppi, M. Nassi, L. Sugiyama, "Physics Basis for a Compact D-T Ignition

- Experiment,” M.I.T./R.L.E. Report PTP-90/15 (1990), to appear *Physica Scripta* (1992).
- [14] M. Nassi, B. Coppi and L.E. Sugiyama, *Bull. Am. Phys. Soc.* **36**, 2371 (1991); M. Nassi, L. E. Sugiyama, S. C. Jardin, N. Pomphrey, *Bull. Am. Phys. Soc.* **35**, 2131 (1990); L. E. Sugiyama and M. Nassi, *Bull. Am. Phys. Soc.* **35**, 2131 (1990).
 - [15] B. Coppi, M. Nassi, L.E. Sugiyama, invited paper at the International Sherwood Fusion Theory Meeting 1992, Sante Fe, NM.
 - [16] S. C. Jardin, N. Pomphrey, and J. DeLucia, *J. Comp. Phys* **66**, 481 (1986).
 - [17] W.A. Houlberg, *Nucl Fusion* **27** 1009 (1987).
 - [18] P.J. Lomas, B.J. Green, J. How, and the JET Team, *16th European Physical Society Conference on Controlled Fusion and Plasma Physics, 1989*.
 - [19] K. Toi, S. Itoh, K. Kadota, et al., *Nucl. Fusion* **19** 1643 (1979).
 - [20] M. Nassi, “Voltsecond Requirement and Relevant Margin in the Ignitor Device”, M.I.T./R.L.E. Report PTP-90/1, final version March (1992).
 - [21] W.Houlberg, private communication (1991).
 - [22] R.C. Englade, M.I.T./R.L.E. Report PTP-89/7B (1989).
 - [23] R.C. Grimm, J.M. Greene, J.L. Johnson, *Methods Comput. Phys.* **16** 253 (1976).
 - [24] R.C. Grimm, R.L. Dewar, J. Manickam, *J. Comput. Phys.* **49** 94 (1983).
 - [25] L.E. Sugiyama, M.I.T./R.L.E Report PTP-89/11 (1989) to appear in *Fusion Technology* (1992).
 - [26] L.E. Sugiyama, 17th IEEE International Conf. on Plasma Science, Oakland, 1990.
 - [27] L.E. Sugiyama, M.I.T./R.L.E Report PTP-89/11 (1989).
 - [28] M. Nassi, S. C. Jardin, C. F. Kessel, and N. Pomphrey, “Vertical Stability Analysis for Ignitor”, M.I.T./R.L.E. Report PTP-91/10 (1991).
 - [29] C. E. Kessel and S. C. Jardin, “Vertical and Radial Plasma Position Control for BPX”, in *Proc. 14th Symp. on Fusion Engr.* (San Diego, CA, 1991).

II.F ADVANCED FUEL FUSION - IGNITION AND BURN WITH FEWER NEUTRONS

Magnetic confinement geometries employing tight aspect ratios, with high current densities and magnetic fields, have long been proposed for the purpose of studying deuterium-tritium ignition and the plasma heating due to 3.5 MeV alpha particles [1]. The use of such configurations for studying the ignition of plasma mixtures that produce significantly fewer fast neutrons, such as deuterium and helium-3, was first proposed in 1980 [2-4], as an experiment that could be built with current technology. (The $D-^3He$ fusion reaction sequence produces only a small fraction of its net fusion power in the form of neutrons, compared to 80% for D-T.) Recent developments in the design of D-T ignition experiments based on the same philosophy [5,6] have made the possibility of $D-^3He$ ignition even more attractive. Simultaneously, worldwide interest in the possibilities of $D-^3He$ and other "clean" fusion reactions and the desirability of an experiment devoted to them has increased considerably.

In the past few years we have been actively developing a potential design for an advanced fusion experiment, the Candor [7-11], in a combined program of physics and engineering. A one dimensional transport simulation code [9-11] has been developed to model the general $D-^3He$ and D-D reaction sequences over the range of conditions up to and including thermonuclear burning. In the past two years, a 1 1/2D model [13-15], based on the BALDUR transport code [16], that includes separate time evolution equations for each of the nuclear species, in addition to one impurity species, has been developed. A steady state burning code based on fixed radial profiles, which contains many of the same models as the transport code, has also been written [9]. The important property of $D-^3He$ ignition, however, is its strong time dependence, particularly if fusion product slowing down, ash removal, and particle fuelling are not complete and instantaneous. Simultaneously, we have been carrying out engineering studies of the machine, guided by the results of the simulations. Further, since the studies

show that the plasma must approach or even exceed the limits of the first MHD stable region (to ballooning modes) under burning conditions, we intend to renew an old interest in the theory of these instabilities when the total plasma beta, as well as the poloidal beta, is relatively high.

Both numerical transport models take into account the sequence of fusion reactions associated with D-³He or D-D that are important for the energy balance (D+T, D+³He, D+D (both), and T+T). They incorporate a simple slowing down model for the fusion particles and their energy, that assumes that the particles remained confined to the flux surfaces on which they are born. A simplified, approximate model of multiple ion species transport has been used in the 1D code, and, for the moment, an assumption of similar transport coefficients that satisfies ambipolarity for all ion species in the 1 1/2 D code. Varying rates of thermal ash removal and particle fuelling are allowed. Synchrotron radiation is included [12] and also relativistic bremsstrahlung radiation.

The fairly realistic synchrotron model shows [9] that synchrotron radiation remains small relative to bremsstrahlung losses even at ignition, for reasonable wall reflectivities (in this type of machine). The numerical synchrotron loss model has been improved in the past two years to eliminate certain instabilities in the radial distribution of the radiation loss. In the past year, an extensive review of the problem of synchrotron radiation has been written [17].

With the help of G. Bateman at Princeton Plasma Physics Laboratory, the D-³He package will become a standard part of BALDUR some time this year (1992).

The results from the 1D model [9] are confirmed by preliminary 1 1/2 D studies [13-15, and ongoing work]. They indicate that steady state fusion burning can occur at volume averaged and central values of the toroidal β_T near 0.13 and 0.5-0.6 respectively. These numbers are slightly higher than those indicated by earlier work [3,4], which used somewhat more optimistic estimates of the thermal transport losses. On the other hand, experiments intended to ignite D-T mixtures can reach values of the mean poloidal magnetic field $\overline{B}_p$ as high as

4 tesla. In this case D-³He mixtures can be brought to ignition conditions with values of $\beta_p = 8\pi\langle n_e T_e + n_i T_i \rangle / \overline{B}_p^2$ less than the aspect ratio a/R [8].

The results show that the major obstacle to ignition is being able to bring the plasma to sufficiently high temperatures ($T_{eo} \sim T_{io} \sim 60\text{--}70$ keV) in a relatively short time interval. Adding the required ³He at the beginning adds enormously to the amount of plasma that must be heated. Fortunately, the optimum burning conditions for D-³He have particle density ratios of ³He:D $\sim 0.4\text{--}0.5$. On the other hand, steady state results show that the so-called “catalyzed D-D” reaction, in which the ³He and tritium that are produced by the D+D reactions are assumed to be completely burned, is more difficult to establish at the temperatures required to balance a realistic amount of transport and radiation losses because the power lost by synchrotron radiation increases more rapidly with temperature than the fusion reaction rates of D-D. Using the initial ignition and burn of D-T was found to give a good boost toward D-³He ignition. The helium ash buildup from initial D-T heating is a serious potential problem if it cannot be effectively removed and, at the levels considered, could easily quench the D-³He burn even if other conditions were favorable.

The 1D code has been used to investigate the possibility of D-³He ignition in a larger machine ($R = 3$ m [18]) and also to study [19] the possibility of attaining an unmistakable, measurable rate of D-³He burning in a proposed tight aspect ratio D-T ignition experiment, the Ignitor. In this case, approximately 1 MW of charged particle (proton and ⁴He) fusion power from the D-³He reaction alone can be expected if the plasma can reach full D-T burning conditions, $T_{eo} \sim 30$ keV. There are two main constraints apart from questions of energy confinement and stability — the rate at which ³He can be added after the plasma reaches T_{eo} of a few keV and the effect of the accumulation of ⁴He ash from the D-T reaction.

In the past year [14,15], we have begun to consider the role of the current ramp phase in the ignition of D-³He mixtures, for a tight aspect ratio, relatively high magnetic field configurations with limited discharge lengths. The results

show that the plasma must be heated strongly during the ramp, to approach ignition by the end of the ramp, if enough time is to be available to study the burning state. Auxiliary heating with a tritium assist (e.g., 10–15% initial tritium in a deuterium plasma) and fuelling of deuterium, some tritium, and all the ^3He was found necessary to reach the desired ignition density and temperature by the end of the ramp. (The ramp was ~ 7 sec for final parameters $B_T = 13$ T, $I_p = 18$ MA, $R = 1.8$ m, $a \simeq 0.65$ m, and elongation $\kappa \simeq 1.8$.) Deuterium and tritium were fuelled strongly for the first 4 sec of the ramp, to raise the deuterium density to its final value, while the ^3He fuelling was started at around 4 sec, to prevent it from quenching the initial discharge with excessive radiation losses. Injected heating was started at 2.4 sec (10 MW) and increased at 4 sec (30 MW). Under the assumed thermal transport, near ignition conditions could be reached near the end of the ramp. A major problem however, was the inadequacy of the MHD equilibrium solver at higher beta, which prevented the attainment of true ignition. An improved version, incorporated into BALDUR late last year (1991) may provide better results, although this is a generic problem with most equilibrium calculations.

Some control of the toroidal current profile was found to be possible, by growing the plasma and programming the current rise. Appropriate measures appeared to show that $q > 1$ could be maintained at all times during the ramp (and presumably afterwards, since the current profile changes very slowly under resistivity at ignition temperatures). The q profile, however, usually became slightly nonmonotonic at some point between $1 < q < 2$, at mid radius. The profile, in fact, bears an intriguing similarity to those observed [20] in the recent, highest beta D-III-D discharges, where sawtooth oscillations stabilized and part of the plasma was considered to be in the second stability regime.

This work has been delayed for several months recently by the changeover of the MFE computers to the UNICOS operating system, which required major changes in the transport code, which is now mostly completed. We are currently working on the package that provides the graphical output on the Cray comput-

ers, which will become part of the basic, publicly distributed BALDUR package, since the PPPL Baldur users have decided to use their own local computers for their graphics.

We intend to continue all aspects of this work, with the goal of being able to propose a complete conceptual design for a viable advanced fuel ignition experiment. We have completed many aspects of the 1 1/2D transport model and begun to compare it to results from the simpler, faster 1D code. Simultaneously, we hope to improve the 1D code so that it incorporates in some form the geometrical and finite β effects appearing in general geometry.

One of the major questions for D-³He ignition raised so far include the differential heating of the various hydrogenic and helium isotopes, their differential transport, and the problems of fuel depletion (deuterium, tritium, and ³He) and the unwanted confinement of the fusion ash (⁴He and protons). The effects of anomalous ion thermal transport, such as due to the ion temperature gradient or η_i driven modes with their dependence on the relative magnitude of T_e and T_i will be considered, as well as the possible electron thermal transport models.

We therefore intend to start on the development of a useful model for the thermal particle transport of multiple ion species of similar charge and mass, which is crucial to the ash and fuelling problems. This problem can now be addressed with the 1 1/2D transport model, but no good theoretical model yet exists. The JET team has studied the properties of ⁴He in hydrogenic plasmas, aimed toward understanding D-T ignition, and used a neutral beam line to inject fast helium ³He, to simulate fast fusion alpha particles.

In the longer term, using in-house MHD equilibrium and stability codes and axisymmetric transport codes, we will first examine the details of the poloidal field coil configurations required to maintain the expected discharges. For a free boundary equilibrium, the optimal positioning of the coils and their current in order to maintain the desired magnetic configuration, in a well conditioned and robust manner, is a difficult problem [21]. Equally important, small changes in the coils can lead to large improvements in the plasma parameters. The possible

spatial profiles of plasma pressure and toroidal current density consistent with a given equilibrium will then be analyzed with regard to the MHD stability to high toroidal mode number n MHD ballooning modes and low n internal and external modes. At this point, theoretical and computational questions related to choosing an appropriate pathway from first to second stability as the plasma evolves from startup conditions with additional heating to advanced fuel ignition and burn will be examined, and the effects of macroscopic modes associated with finite β will be considered. Some of these analyses also could be applied to discharge stability and control for D-T ignition experiments, which experience a similar temperature excursion without external heating and could be run in the same type of machine.

The problem of control of a D-³He burning mixture will also be addressed — like DT fusion, D-³He burning at the lower steady state temperature is unstable. Unlike DT burning, most plasma configurations considered so far are unlikely accommodate the stable burning point, where the plasma beta is very high. In the time and spatially dependent analysis carried out so far, direct control of burning does not appear easy. However, this is an area that benefits greatly from careful optimization and is sensitive to small perturbations applied at the proper time.

REFERENCES

- [1] B. Coppi, *Comm. Plasma Phys. Cont. Fusion* **3** 2 (1977).
- [2] B. Coppi, Invited paper, *1980 International Conference on Plasma Physics*, Nagoya, Japan, (1980).
- [3] S. Atzeni and B. Coppi, *Comm. Plasma Phys. Cont. Fusion* **6** 77 (1980).
- [4] B. Coppi and G. Vlad, "Ignition Conditions for Tritiumless Plasma Mixtures," M.I.T. Report R.L.E. PTP-82/16 (1982) and G. Vlad, *Il Nuovo Cimento* **84B** 41 (1984).
- [5] B. Coppi and L. Lanzavecchia, *Comm. Plasma Phys. Cont. Fusion* **11** 47 (1987).
- [6] B. Coppi and the Ignitor Design Team, in *Plasma Physics and Controlled Nuclear Fusion, Nice, 1988* (IAEA, Vienna, 1989) Vol. 3, p. .
- [7] B. Coppi, *Physica Scripta* **T2:2** 592 (1982).
- [8] B. Coppi, *Nucl. Instr. Methods Phys. Research* **A271** 2 (1988).
- [9] B. Coppi and L.E. Sugiyama, "Questions in Advanced Fuel Fusion," M.I.T. Report R.L.E. PTP-88/6 (1988) submitted to Nucl. Fusion.
- [10] B. Coppi and F. Pegoraro, "Near Term Experiments on Advanced Fusion," invited lecture at the 1990 E. Fermi International School of Physics, Varenna, Italy, July 1990. (M.I.T./R.L.E. Report PTP-90/16 (1990)).
- [11] B. Coppi, Invited paper on Anentronic Nuclear Fusion at the Royal Netherlands Academy of Arts and Sciences, Colloquium on "Energy Technologies and sustainable development: long-range R &D opportunities," Dec. 1991, Noordwijkerhout, the Netherlands.
- [12] S. Tamor, "A Simple Fast Routine for Computation of Energy Transport by Synchrotron Radiation in Tokamaks and Similar Geometries," Science Applications, Inc, Report SAI-023081-189-LJ (1981); S. Tamor, *Nucl. Instr. and Methods* **A 271**, 37 (1988).
- [13] L.E. Sugiyama, *Bull. Am. Phys. Soc.* **34** 2171 (1989).
- [14] L.E. Sugiyama, IEEE International Conference on Plasma Science,

Williamsburg, VA, June (1990).

- [15] L.E. Sugiyama and B. Coppi, *Bull. Am. Phys. Soc.* **36** 2371 (1991).
- [16] G. Bateman, Princeton Plasma Physics Laboratory, Princeton NJ.
- [17] C. Riconda, M.I.T./R.L.E. Report PTP-91/8 (1991).
- [18] L.E. Sugiyama, M.I.T. R.L.E Report PTP-89/11 (1989).
- [19] L.E. Sugiyama, M.I.T. R.L.E. Report PTP-89/17 (1989).
- [20] E.A. Lazarus, et al., *Bull. Am. Phys. Soc.* **36** 2324 (1991).
- [21] F. J. Helton, J. M₂ Greene, and J. W. Helton, General Atomics Report GA-A19323 (1988).

TASK APP 03

USER SERVICE CENTER

Principal Investigator

Dr. Martin Greenwald

MIT Plasma Fusion Center, NW17-107

175 Albany St.

Cambridge, MA 02139

(617) 253-6053

Technical Progress in FY92

Support for the User Service Center (PFC-USC) is an on-going effort to maintain and improve the resources and facilities for the MIT Plasma Fusion Center computational community. At present, these facilities support over 300 staff and student users. Major components of our task include: provision and maintenance of high speed reliable communication facilities between the PFC-USC and the NERSC Cray computers, support for associated I/O facilities and remote processing capabilities; maintenance and improvement of local hardware and software to provide capabilities for pre-processing and post-processing of data associated with NERSC use; network communications with other MFE facilities including foreign collaborators, and the ITER design groups; provision and maintenance for local computational applications which are unsuited for remote, large mainframe computers; support for Local Area VAXclusters (LAVC); acquisition, support, and development of software and equipment for expanding the research capabilities of the PFC-USC; support of data acquisition hardware and software for several of the smaller groups at the PFC. The USC staff also provides management for computer related activities at the PFC as well as coordination with outside computer and network organizations.

To support these activities, the PFC-USC maintains a complement of computer and communications equipment. The buildings of the PFC are interconnected by a 10 Mbps, ethernet based, Local Area Network (LAN) which links all the computers and users at the center. Offices and labs at the PFC are wired to terminal servers which allow users to log onto any PFC computer on which they have an account. The PFC-LAN is bridged to the LAN of MIT's Laboratory for Nuclear Science (LNS) which serves as a gateway to the

MIT campus network (MITnet) and for the high speed Wide Area Networks (WAN) of the U.S. DOE and other government agencies. Users at the PFC have access to the CRAYs at NERSC through ESnet and to other laboratories in the U.S. and overseas through the ES DECnet, NSI, and the Internet. The USC maintains a local computing facility consisting of two VAX mini-computers and a number of VAX workstations.

We have made a number of improvements in the last year. The overloaded boot node for a PFC Computer Services (PCS)-supported LAVC was upgraded from a VAXstation II to a VAXstation 3100 model 76. Multinet TCP/IP software was made available site-wide, giving all users direct access to the INTERNET. The MITnet backbone was upgraded to FDDI, using multi-protocol cisco routers. We are making TCP/IP available on the desktop to PC owners with the public domain NCSA package for the Mac or with the proprietary DEC Pathworks package for VAX, PC, and Mac. We have purchased terminal servers that use both the LAT protocol and the TCP/IP protocol allowing users to connect directly to off-site computers (like the Cray's) without loading our local computers. Though we were required, due to lack of funds, to lay off one of our system managers, we were able to share employment of a newly hired network manager with the Alcator project. This brings us some needed expertise, particularly in the area of PC networking. PFC personnel have also participated in organizing an OER wide DECnet, facilitating a number of national and international collaborations. In June of this year, DECnet/OSI should finally be released. Plans have begun for PFC expansion into a fourth building, scheduled for May of this year. Because PCS was able to begin its work in parallel with the building renovation, network and data cabling and network support in that building will be far more complete than in our other buildings. A fiber-optic link will connect that building with our ethernet fiber-optic star coupler in one of our other buildings. The new ethernet connections will be via twisted pair cables instead of coax. There will also be an extensive AppleTalk network.

TASK APP-06A
HIGH POLOIDAL BETA STUDIES ON PBX-M

Principal Investigator

Dr. Stanley C. Luckhardt
MIT Plasma Fusion Center, NW16-266
167 Albany Street
Cambridge, MA 02139
Tel. (617) 253-8606

Co-Principal Investigator

Dr. Jay Kesner
MIT Plasma Fusion Center, NW16-256
167 Albany Street
Cambridge, MA 02139
Tel. (617) 253-8662

I. PROJECT SUMMARY

The goal of this project is to carry out experiments to access the tokamak second stability regime by means of current profile control and plasma shaping. We plan to accomplish this in three steps: (1) Demonstrate current profile broadening in elongated modestly triangular or indented, low current plasmas and attain $q(0) \sim 1.5-2.0$. (2) Compare attained plasma profiles: $p(r)$, $q(r)$, and shape with MHD stability analysis and confirm that stable access to the second stable region has been achieved. (3) Use available heating power on PBX-M to raise beta, identify MHD pressure driven modes, and the influence of the current profile on these modes.

These experiments are being carried out in two collaborative arrangements between MIT/PPPL and MIT/JET with experimental activities on both the JET tokamak at Culham Laboratory, UK and the PBX-M tokamak at PPPL.

Schedule for PBX-M/JET experiments

MIT COLLABORATIONS	FY91	FY92	FY93
MIT/PBX-M	LHCD MODELING, STABILITY CALCULATIONS	BEGIN LHCD EXP.S, BEGIN HIGH $\epsilon\beta p$ EXPS., q(r) MEASUREMENT, BALLOONING MODE DETECTION	CONTINUE HIGH $\epsilon\beta p$ AND LHCD q- PROFILE CONTROL EXPERIMENTS
MIT/JET	BALLOONING MODE DETECTION EXPERIMENTS	COMPLETE BALLOONING MODE STUDIES	DATA ANALYSIS AND INTERPRETATION. (CONTINUE JET COLLABORATION)

Table 1. Work on ballooning mode diagnostic development and detection on JET during CY91 can support PBX-M experiments scheduled for FY92 and FY93.

The JET work has helped to make up for lost time caused by the unavailability of PBX-M during FY91.

II. TECHNICAL PROGRESS FY-92

II.a MIT/JET COLLABORATION

During FY91-92 the JET collaboration activities (see Table 1) consisted of: (1) Setup fast stand-alone data acquisition system and interface to JET heterodyne radiometer (see Figure on p. 06A-5) (2) Carryout measurements of ECE fluctuations on JET plasmas including:

- a) High poloidal beta, high bootstrap current plasmas
- b) High beta plasmas near or exceeding the Troyon limit
- c) PEP (pellet enhanced performance) high $q(0)$ plasmas.
- d) H-mode plasmas, spatial resolution of ELMS.
- e) MHD fluctuations during JET Deuterium/Tritium operation
- f) MHD fluctuations during lower hybrid current drive on JET

(3) Model JET lower-hybrid current drive plasmas, and compare code modeling with well diagnosed JET plasmas. These activities were carried out by the following MIT personnel: S.E. Jones (post doctoral scientist), J. Kesner, S.C. Luckhardt, C. Rost (graduate RA), J.J. Ramos, P.P. Woskov, A.M. Zolfaghari (graduate RA). Dr. Jones and Mr. Zolfaghari were at JET for 6 months and 12 months respectively.

The MIT/JET collaboration is recognized by the JET team as a successful collaboration and has been very productive, the work there has so far generated eight publications and conference papers. The following section contains a report of this activity. A detailed description of the ECE fluctuation diagnostic activity is included in the companion report for grant APP-06B.

Progress Report of Collaborative Efforts at JET and PBX-M

SUMMARY

Since joining MIT as a postdoctoral fellow last July, Dr. Stephen Jones has participated in research efforts at MIT, JET, and Princeton. The first period, at MIT, lasted five weeks and consisted of helping MIT write the VTF-D

proposal, and helping Jay Kesner initiate LHCD simulations of PBX-M using his new code¹. The second period, at JET, lasted 6 months and centered on two projects: the first project was to help setup MIT's collaborative experimental development of the ECE ballooning mode diagnostic (see also the companion write up for APP-06B Fast ECE Fluctuation Diagnostic of MHD Modes by P.P. Woskov et al.) and the second project was to initiate LHCD simulations by using the Bonoli lower hybrid current drive code on JET's well-diagnosed plasma. The third, and current period of two weeks, has focused on helping the PBX-M team with the new hard X-ray imaging diagnostic. This effort, and others, will continue at Princeton for the next 18 months.

The next two sections will further detail (1) results of work done at JET, and (2) current activities at Princeton.

COLLABORATIVE WORK AT JET

As mentioned above, efforts at JET centered on two projects: (1) setting up and taking measurements with an upgraded, fast ECE diagnostic; and (2) simulating a LHCD shot using Bonoli's code. These two projects are discussed separately in the following two sub sections.

MIT/JET FAST ECE DATA SYSTEM

(12 ECE CHANNELS 1MHz SAMPLE RATE/CHANNEL)

KK3-F: MIT/JET's fast ECE fluctuation diagnostic

KK3-F is an MIT collaborative upgrade of JET's existing 44-channel ECE heterodyne radiometer, KK3. The goal of this device is to detect and spatially resolve MHD ballooning modes, which are predicted to produce ECE fluctuations². Successful measurement of these modes is important for PBX-M second stability experiments, and JET collaboration represents a valuable opportunity for the "proof of principal" of this diagnostic.

The initial efforts of Dr. Jones in this project were to assist in setting up both the hardware and software so that the diagnostic could begin to take data as the JET tokamak began the operating period. Subsequently, efforts were aimed at using the diagnostic to observe any edge fluctuations, particularly ELMs: this effort is described in the remainder of this subsection.

ELMs (Edge Localized Modes) are brief, violent edge disruptions seen in many tokamaks during H-modes, particularly with high auxiliary heating. Fig. 1 shows a JET H-mode shot with ELMs, whose characteristic signature is spikes in the edge H-alpha emission, ostensibly due to the expulsion of edge particles. To date, the cause and mechanism of ELMs is not understood. Yet, an understanding of ELMs is important since it may offer insight into the L-H transition, and deliberate control of ELMs may offer a route to steady-state H-mode by controlling transport of particles from the plasma. ECE measurements offer an additional tool for studying ELMs, complementing such other diagnostics as magnetics, reflectometry, and scattering. In particular, the MIT/JET fast ECE

Flux Reconstruction

Blow-up of D-Alpha Emission

Figure 1. Examples of ELMs at JET (shot #27228).

diagnostic KK3-F offers a unique contribution due to (1) its speed of data acquisition [up to 5 MHz sampling rate], (2) its large capacity for data collection [up to 2.62 seconds at 200 kHz], and (3) its ability to spatially localize fluctuations.

To maximize the advantage of these abilities, initial efforts centered on (1) searching for any fast ECE precursor oscillation to an ELM; (2) examining any radial structure and propagation of ELMs by observing their ECE signature from neighboring positions in the plasma edge; and (3) searching for any statistical behavior of ELMs by comparing their ECE signatures within one shot (particularly during the L-H and H-L transition), and between many shots.

These investigations are ongoing, and only a small fraction of the data has been examined to date. However, more than 3000 Megabytes of ECE fluctuation data has been collected by our diagnostic so far. The remainder of this section discusses initial results from this effort.

Fig. 2 shows a "close-up" of one ELM seen on KK3-F at four different radial locations at the edge collected during one of the two D-T shots (#26148) that occurred at JET on November 10, 1991. Note the rapid rise and fall (within 10 microseconds), and rich structure seen within each channel. In general, we believe these fast large amplitude signals to be non-thermal in origin, particularly due to the rapid signal decay time that is inconsistent with a thermal relaxation time scale. (Although in some other cases ELM ECE signals may be interpreted as thermal fluctuations, as discussed below). These plots can also reveal the

Figure 2. Fast time example of an ELM's ECE emission from four different radii.

relative timing of the various channels (representing different radii in the JET plasma), and early statistical surveys of these large ELMs show an outward radial "propagation" velocity of about 10^4 m/sec.

Fig. 3 shows results from the spectral analysis of one ELM, exhibiting our use of personal computers and MATLAB software for data analysis on KK3-F. The series of figures shows, in successively finer time resolution or "blow up", the ELM signal. This allows us to search for ELM precursor signals. Although this particular example may show a long time scale precursor at about 50 kHz, and a short wide band precursor, in other cases no clear ECE precursor signal is seen. Analysis of this data is continuing.

Fig. 4 shows an example of a second class of ELMs, whose amplitudes are much smaller than those in Fig.3. These ELMs were collected during JET's long H-mode shots where ELMs were deliberately triggered using mid-plane gas injection. Note the existence of a "negative" ELM. Statistical comparison of many of these edge ELMs show a definite correlation of negative ELMs inboard of the outer edge to positive ELMs nearer the outer (larger major radius) edge of the plasma. If these ELMs are thermal, they could represent a sudden local radial displacement (i.e., outward vs inward) of plasma, as suggested by the theory of Luckhardt, et al².

Although initial results will be presented this summer at the EPS meeting³, we again remark that the data analysis is not complete and will continue, particularly now that JET is down for a 12 month divertor upgrade. Nearly 3 Gigabytes of

Figure 3. Successive blow-ups of a spectral-time plot of ECE from one ELM at one radius.

Figure 4. Example of second class of ELMs at six different radii.

data has been collected, and only a small fraction has been examined. However, the time spent on this examination has guided the thinking for the complete examination that will be carried out during FY92-93.

Comparisons between LHCD modeling and JET shot #24918

A crucial part of the PBX-M effort is the application of LHCD for current profile control, for which computer simulations are a helpful guide. The Bonoli code is an established LHCD simulation, although its drawbacks include (1) the inability to use arbitrarily shaped plasmas, and (2) the lack of a sophisticated transport model. Jay Kesner in our group has approached this problem by combining the Bonoli Lower-hybrid code with the successful transport code BALDUR. Initial use of this simulation began during late summer of 1991 and included modeling LHCD on PBX-M.

As with any large code, it is very important to compare the code to experiments, and this was the goal for trying to model the JET LHCD experiment, whose plasmas are well diagnosed. Since these codes are large and machine dependent, this effort required running the LHCD codes remotely from England. Unfortunately, at the present time JET is not directly connected to the USA via computer links, and a connection had to be established. To date, this connection is only through the use of computers at Culham Laboratories, whose site is juxtaposed to JET's site. We have used this connection for the present work.

A further difficulty related to the US computers, which are CRAYs on the NERSC system located at LLNL: the operating system was scheduled for a change from the existing Cray system to UNIX. This meant that the Bonoli and BALDUR codes had to be modified. Due to the smaller size of the Bonoli code, its modification was undertaken first, and was completed a few months after the arrival of Dr. Jones at JET. Thus, it was decided to initiate modeling of JET using the original Bonoli code, while waiting for modification of the Bonoli-BALDUR code by Jay Kesner. This would limit simulations to those JET plasmas of nearly circular cross section, and would risk the use of the simple transport model. The rest of this sub-section describes the results from modeling JET shot #24918 using the full Bonoli code.

Fig. 5 shows the plasma current, lower hybrid power, loop voltage, maximum electron temperature, density profile, and flux reconstruction of JET shot #24918. This shot was of particular interest for these simulations for the following reasons: (1) the plasma is nearly circular with an elongation of 1.15; (2) after reaching a maximum plasma current of 1.5 MA, the ohmic drive was turned off, and the plasma decayed on an L/R time scale; (3) the ICRH failed to engage, thus the only auxiliary power is Lower Hybrid. Note that at 48 seconds, when the plasma current has decayed to about 400 kA, 1.8 MW of LHRF is coupled to the plasma, thereby stopping the decay and sustaining that current for about 3 seconds. This is an ideal shot for modeling because (1) the loop voltage is zero and full current drive is engaged; (2) lower hybrid power is the only input power; and (3) the Bonoli code is directly applicable for this

Plasma Current (MA)

Plasma Current (MA)

Lower Hybrid Power (MW)

Loop Voltage (V)

Max Electron Temp (keV)

TIME (s)

Density Profile (LIDR)

Flux Reconstruction

Figure 5. JET shot # 24918 used for Bonoli simulation.

approximately circular cross section plasma. Since this is such a simple, ideal shot, the chances for a successful simulation are enhanced.

Fig. 6 shows the results of a simulation run which came closest to replicating the data. Note that this simulation is different from the actual shot in that the total plasma current is kept fixed in the code, using the ohmic drive as a variable. In the simulation, as the RF power is increased producing an RF driven current, the loop voltage decreases. Specifically, with 2.3 MW of coupled RF power, the loop voltage drops to 0.03 V, and 86% of the current is RF driven. Thus the current efficiency in the simulation ($NIR/P = 0.08$) is about 25% lower than the experiment, work is continuing on these simulations, and it is possible that better agreement will be found in future runs. The results are compared in the table below:

Comparison between JET data and simulation code

	Simulation	JET Shot #24918
LH Power	2.3 MW (Input) 1.7 MW (Landau damped)	1.8 MW (Input)
RF Current	0.38 MA	0.38 MA
Internal Inductance	1.6	1.44 (MHD reconstruction)
Major Radius	3.0 m	3.0 m
Average Density	$0.17 (10^{20} \text{ m}^{-3})$	$0.17 (10^{20} \text{ m}^{-3})$
Electron Central Temp.	1.8 keV	1.5 keV
FWHM $T_e(r)$	0.9 m	0.8 m
NIR/P	0.084	0.108

Overall, the agreement between the experiment and simulation is within 15-20% for most measured quantities, which represents satisfactory agreement.

However, there are two noticeable differences between this simulation and the

Figure 6. Results from Bonoli simulation of JET shot #24918.

Inverted Profiles

Figure 7. Experimental results from JET's fast electron bremsstrahlung camera.

experiment. It has been very difficult to lower the simulation's final electron temperature to the experimental value of about 1.4 keV. Attempts to lower the temperature by using either less RF power or enhanced transport result in a sudden change in the RF power absorption profile whereby most RF power is absorbed in the plasma edge and very little power reaches the interior; thus the electron temperature hardly raises and the driven current is insignificant. It remains to determine whether this "competition" between absorption at the edge and in the middle is a computational artifact, or is real physics.

The second noticeable difference concerns the current density profiles, and their comparison with experimental observations of hard X-rays from JET's FEB (Fast Electron Bremsstrahlung) camera. Note that the simulation, Fig. 6, predicts a "hollow" current profile, with a peak located 28 cm off axis. Fig. 7 shows both raw data from JET's FEB camera, and Abel inverted profiles which suggest a peaked profile which may be inconsistent with the code results. We note that the hollow RF current profile appeared consistently over all variations of the simulation. However, to further investigate this discrepancy, and since Abel inversions can be inaccurate, we are currently calculating the "forward" problem of what JET's FEB camera would detect, assuming a current profile from the simulation, and how consistent this is with the errors from the observed data. One possible source of discrepancy is the current diffusion model used in the code; thus this investigation may lead to further understanding of this relevant topic, and is of course relevant to our planned current profile modification experiments on PBX-M.

The next task is to redo this simulation using Jay Kesner's Bonoli-BALDUR code. The UNICOS modification is nearly complete as of this writing, and new simulations will be shortly underway. This collaborative effort with JET will continue and further shots will be simulated, thereby adding to the confidence in the code. This simulation work is important for PBX-M since the BALDUR-LHCD code will also be used to model those current profile control experiments.

COLLABORATIVE ACTIVITIES AT PBX-M

As mentioned in the above summary, Dr. S. Jones has returned from JET, and is now residing at Princeton, NJ, and is collaborating full time with the efforts at PBX-M. Initial work will concentrate on the continued development and operation of PBX-M's novel 2-D hard X-ray imaging camera, allowing tangential 2-D views of the fast electron Bremsstrahlung profile. With further study, this new device has a unique opportunity to contribute significantly to the tokamak community's on-going efforts to understand fast electron diffusion. This will be a key diagnostic for determination of the LHCD current profile modification is successful on PBX-M. These results will also be compared with further efforts to simulate the PBX-M current profile experiments.

References

- 1) S.E. Jones, J. Kesner, S.C. Luckhardt, Bulletin of the American Physical Society, Tampa Bay, FL, Nov. 1991.

- 2) S.C. Luckhardt, et al., Theory of Electron Cyclotron Emission Fluctuations Caused by Coherent Ideal MHD Ballooning Modes, PFC Report # PFC/JA-91-16, 1991.
- 3) D.V. Bartlett, A.E. Costley, S.E. Jones, L. Porte, R. Smith, A. Zolfaghari, to be presented at the 1992 EPS Conference.

II. b LOWER-HYBRID MODELING CODE DEVELOPMENT

II. Technical Progress FY-92

Development of Lower Hybrid Current Drive Simulation Code: **BBK**

We have developed a code which can simulate the experiments which we want to carry out in PBX-M. More specifically these simulations will indicate whether in terms of available LHCD power, antenna phasing, resistive skin time current diffusion and interaction with neutral beam current drive, a current profile compatible with second stability access can be generated in the PBX-M facility. Initial simulations substantiate the feasibility of these experiments and further simulations are planned. In this scenario we utilize plasma current density profile control to obtain a stable path into the second stability region. This code incorporates the Bonoli lower hybrid current drive code into the BALDUR tokamak simulation code. We call this combined code **BBK**.

The BALDUR code is a widely used 1.5-D tokamak simulation code in which MHD equilibrium and thermal and particle transport are treated. BALDUR is able to treat shaped plasma cross sections, neutral beam injection and calculates both the neutral beam-driven and bootstrap currents. The code checks

ballooning stability and is easily interfaced with MHD stability codes developed at PPPL. Inclusion of a lower hybrid current drive package into this code provides an excellent tool for simulation of LHCD in devices like PBX-M or JET.

The Bonoli lower hybrid current drive code [P. Bonoli, R. Englade, Phys. Fluids **29**, 2937(1986)] incorporates a toroidal ray-tracing code and a one-dimensional Fokker-Planck calculation to calculate current and power deposition resulting from a realistic spectrum of lower hybrid waves. Two dimensional effects are estimated in the Fokker-Planck analysis in the form of a specified hot perpendicular electron temperature tail. This code however assumes circular plasma cross section with equilibrium determined from a Shafranov aspect ratio expansion. Since time-dependence, cross-section shaping and neutral beam effects are important in the analysis of the proposed experiments we have decided to integrate this code with BALDUR. An interface between BALDUR and the Bonoli code has been put in place which utilizes the interface from the TORAY code (BALDUR-ECRF code) [P. Bonoli, R. Englade, M. Porkolab, A. Kritz, European Conf. on Controlled Fusion and Plasma Heating, Amsterdam, **14B**, Pt. 3, 1100 (1990).] which was developed at MIT.

The BALDUR equilibrium package uses Hirshman's moments expansion solution in flux coordinates and the conversion to the toroidal cylindrical coordinates of the Bonoli code is accomplished through an iterative inversion calculation [S. Attenberger, W. Houlberg and S. Hirshman, J. Comp. Phys., **72**, 435 (1987)].

Preliminary calculations have simulated a PBX bean geometry run with low plasma current (200 KA). Some results are as follows:

- 1) 100 % current drive can be achieved in an ohmic plasma with 1 MW of absorbed LHCD power.
- 2) The driven current peaks off axis $r/a \sim 0.3$.
- 3) The current profile will significantly relax within 300 ms in an ohmic plasma.
- 4) Neutral beam injection can increase the current drive efficiency if the electrons heat. However the degree of electron heating depends on the density rise that accompanies neutral beam heating as well as the auxiliary heat driven transport that results.
- 5) For $n_{\parallel} \sim 4$ the waves that drive the current have multiple passes through the plasma before being absorbed and so current drive depends on multiple bounce confinement of the rays.
- 6) A comparative study indicates that D and bean shaping tends to produce absorption further out in radius.

The figure shows equilibria for 3 cross sections (having similar cross-sectional areas). We see below that the power is absorbed further out in radius in the

Effect of Cross Section Shaping

D and bean shaped plasma.

Shape	n-parallel	Position of LH Current Peak	A	NIR/P
Circle	2.3	0.33	3.9	0.12
D	2.3	0.40	4.7	0.072
Bean	2.3	0.47	5.5	0.072

We also have considered the effect of varying n-parallel and of utilizing a more realistic spectrum which includes some backward going waves.

We consider here an ohmic plasma with $n_{e0}=1.7 \times 10^{19} \text{ m}^{-3}$, $\langle n_e \rangle = 1.1 \times 10^{19} \text{ m}^{-3}$, $T_e=1.3 \text{ keV}$, $T_i=0.7 \text{ keV}$, $Z_{\text{eff}}=3$.

The results are shown in table 2 below:

N-parallel	ΔN	I/P (kW/kW)	η_{CD}	V_{loop}
6.8	0.5	317/996	0.058	-0.29
2.3	0.5	151/381	0.072	0.04
2.3, -6.8	0.5	250/988	0.044	-0.27

IIc MHD ANALYSIS AND MODELING

During the past year we have investigated the compatibility of second stability equilibria with the current profiles that would result if a large fraction of the plasma current is produced by collisionless bootstrap effects. We have shown that the current profiles of our proposed path to second stability at high $q(0)$ can match the bootstrap current profiles calculated consistently with the equilibrium temperature and density. Only a small "seed current" near the magnetic axis must be driven by external means. The magnitude of this seed current is of the order of magnitude of 5% of the total current. This feature is unique to second stability configurations at high poloidal beta and high $q(0)$, and highlights their importance as the basis for advanced tokamak studies.

The second subject of our MHD stability analysis has been the numerical convergence of results derived with the PEST code for low- n , external modes. We have unambiguously shown serious problems with the numerical convergence of the PEST $n=1$ kink-mode stability calculation for equilibria in the ballooning second stability regime at high $q(0)$. [J.J. Ramos in Proc. on the 1991 Sherwood Theory Conf., p. 1e23 (1991). This result underscores the importance of testing experimentally these configurations in a present day device such as PBX-M, DIIID or JET before they can be seriously considered for the next generation tokamak designs.

Task APP-06B

FAST ECE FLUCTUATION DIAGNOSTIC FOR BALLOONING MODE STUDIES

Principal Investigators

Paul P. Woskov
MIT Plasma Fusion Center, NW16-134
167 Albany Street
Cambridge, MA 02139
Tel. 617-253-8648

Stanley C. Luckhardt
MIT Plasma Fusion Center, NW16-266
167 Albany Street
Cambridge, MA 02139
Tel. 617-253-8606

Daniel R. Cohn
MIT Plasma Fusion Center, NW16-140
167 Albany Street
Cambridge, MA 02139
Tel. 617-253-5524

Technical Progress (FY92)

The goal of this project is to develop and experimentally demonstrate a new diagnostic capability for spatially and wavelength resolved measurements of long wavelength (>1 cm) plasma fluctuations in tokamaks. In particular, the goal is to demonstrate a capability to study possible ballooning modes in tokamaks. This project complements a companion project, Task APP-06A, for physics studies of high beta tokamak operation and stability.

Significant progress was made toward the stated goals during fiscal year 1992. During this time this project has been involved in two collaborations. One collaboration was with the JET Joint Undertaking in Europe to take advantage of an existing 75-140 GHz radiometer diagnostic system to test the basic concept of using electron cyclotron emission (ECE) for fluctuation studies. This collaboration has been highly successful. The other collaboration was with the Princeton Plasma Physics Laboratory to implement a 112-137 GHz radiometer system for ballooning mode studies.

JET Collaboration

The primary focus of this project during the first half of FY92 was to the JET collaboration. An MIT graduate student was supported at the JET site with several extended visits by senior personnel. The JET tokamak was operational up to February 22, 1992. During this time there were preliminary tritium experiments. A list of the major accomplishments is as follows:

1. Initial ECE fluctuation measurements were carried out at JET using their unmodified radiometer system which was limited to low frequency (<10 kHz) fluctuations. Correlation techniques were introduced to analyze the data. Spatially resolved large scale plasma fluctuations were observed during pellet enhanced plasma (PEP) discharges. These preliminary measurements established the potential of this new diagnostic technique.
2. A stand alone fast data acquisition system was designed and implemented for the JET ECE radiometer system. Eight channels of wide bandwidth video amplifiers and fast data digitizers (up to 5 MHz) were assembled. These fast channels could be connected to any of the 40 existing radiometer channels to be able to optimize the location of the fast channels for a given tokamak operating field. This fast data acquisition system used a PC controlled CAMAC crate based system. Frequency selectable anti-aliasing filters and a trigger module for synchronization to JET pulses were constructed. Software was set up and debugged. A WORM optical disk drive was set up for data storage. Finally, the system was debugged for electrical noise and channel cross-talk.
3. Fast ECE data was acquired on a variety of plasmas during the period of October 1991 through February 1992. These plasmas included: (a) hot ion mode (H-mode) plasmas

including the Preliminary Tritium Experiments (PTE), (b) low field high toroidal beta H-mode discharges near or exceeding the Troyon limit, (c) high current high poloidal beta discharges, and (d) high poloidal beta PEP discharges. High frequency ECE fluctuations were observed in many of these plasmas which would not otherwise have been detected without the MIT fast data acquisition system.

4. Preliminary data analysis and interpretation was carried out on a few interesting discharges. Using computational spectral analysis tools such as fast fourier transforms, auto and cross correlations, etc., the existence of large scale fast coherent MHD modes has been established. In particular, these modes are present in the highest toroidal beta discharges near or beyond the Troyon limit. A 25 kHz mode was observed just before a disruption when the beta peaked. This is suggestive of the existence of ballooning modes; however more data will be needed to confirm this. It does confirm the feasibility of fast ECE radiometry for localized long wavelength fluctuation studies.
5. Anticipated progress in the second half of FY92 will primarily be focused on extending the data analysis. This will include an absolute calibration of the fast data system so that the true radial amplitude distribution of the fluctuations can be determined. Many more discharges with high frequency activity will be analyzed. Phase correlations will be carried out to determine radial wave numbers. The data will also be correlated with other diagnostics including x-ray, reflectometer, and magnetic diagnostics.

PBX-M Collaboration

Progress was also made with the PBX-M collaboration during FY92. The main activity here has been to plan, design, and implement a fast multi-channel radiometer. As the collaboration activity with JET winds down during the second half of FY92 the graduate student will be relocated to Princeton toward the end of the year. The main accomplishments are as follows:

1. A 13 channel, 112-137 GHz heterodyne receiver has been designed for PBX-M. This receiver is optimized to view 3rd harmonic ECE for central tokamak fields of 1.5-1.7 Tesla. Approximately 60% of the midplane plasma diameter can be simultaneously viewed. Spatial resolution in a thermal plasma of each channel will be approximately 1.5 cm by 2.0 cm, radially and vertically, respectively. The receiver noise temperature will vary from about 1 to 7 eV across its 25 GHz bandwidth.
2. All the components for constructing the receiver with 8 channels covering 112-130 GHz have been ordered. Starting with 8 channels is necessary due to budgetary constraints, and it also matches well with the existing fast data acquisition system that will be brought over from JET. The most challenging component to be acquired for this receiver was the 25 GHz instantaneous bandwidth mixer. It is anticipated that this receiver will be assembled and installed by late spring 1992.
3. Anticipated progress will be to make operational the fast radiometer system on PBX-M. This will include calibration and commencement of plasma measurements. These measurements will support high beta stability experiments of the companion proposal APP-06A.

1. TASK APP-07

X-Ray Imaging Diagnostic Development

2. Principal Investigator

Richard Petrasso
MIT Plasma Fusion Center, NW16-132
167 Albany Street
Cambridge, MA 02139
Tel.: (617) 253-8458

3. Technical Progress in FY 92

3.A. Overview of Technical Progress in FY 92.

Many of the properties of high-temperature plasmas can be inferred from plasma x-ray emissions. These properties include the electron temperature and density profiles; the spatial distribution of impurities and their ionization states; the size, shape, and location of magnetic island structures; the growth, saturation and decay of various plasma instabilities; and the determination of background-particle and impurity particle transport.

In the context of these problems, and in order to enhance the quantitative capabilities of our x-ray imaging work – which has included x-ray arrays on Alcator-A [1,2,3], Alcator-C [4,5,6], and now includes 3 x-ray imaging arrays on TEXT [7,8] – we have undertaken the design and construction of 3 new x-ray sources which will be used to carefully characterize the individual diodes of the x-ray arrays for TEXT. These sources, XI, XII, and PIXE, each have unique features needed for a complete x-ray calibration. In the following sections, we describe these sources and show some preliminary x-ray diode data obtained through their use.

3.B. X-Ray Source XI

Fig. 1 shows a schematic of the x-ray source XI. It is a high intensity, quasi-DC electron impact source (in contrast to the PIXE source) with a large vacuum chamber that allows for the simultaneous cross-calibration of several x-ray detectors. Fig. 1 shows a “monitor” surface barrier detector

(SBD) (top port), 2 SBDs that are being calibrated (bottom, right), and a Si(Li) detector that measures the x-ray spectrum. Since all x-ray detectors can be mounted inside the vacuum chamber, the softest x rays extend down to ~ 0.1 keV. This is an extremely important feature since x emissions from the tokamak plasma edge region have similar energies.

In addition to energy dispersive detectors (*e.g.*, the Si(Li) detector) used to measure the x-ray spectrum, various filters can be inserted between the source and detectors to eliminate or greatly reduce the thick target bremsstrahlung component; this enhances the characteristic radiation of the anode (target).

As an example, Fig. 2 shows a preliminary x-ray calibration of a NIST photodiode at energies of 1.5, 4.5, 5.9 and 8.0 keV [9]. (The K lines of Al, Ti, Mn and Cu). Fig. 3 shows the quality of the x-ray spectrum obtained with a Si(Li) detector for a Cu anode and a thin ($12.5\ \mu\text{m}$) Cu filter (used to reduce the bremsstrahlung component).

Because XI is limited to 120 Hz or less in the modulation of the x rays, it cannot be used to determine the frequency response of x-ray detector/electronics, which in some cases need to operate in the 100 kHz range (or greater). This circumstance is motivated by the fact that many plasma instabilities, such as major disruptions, have x-ray precursors with such high frequencies. It is through the use of XII, to be described next, that we investigate the frequency response of x-ray detector/electronics.

3.C. X-Ray Source XII

Fig. 4 shows a picture of XII. As mentioned in the previous section, the primary function of XII is to generate modulated x rays in order to measure the frequency response of the x-ray detector/electronics used in the imaging arrays [10]. We briefly describe some of the unique features of XII.

The XII electron-gun is of the gridded, post-acceleration type. The gridded e-gun allows the advantage of simple structure and high transconductance, together with a frequency limit to the order of 1 GHz. The high transconductance allows large beam currents to be controlled with minimum grid voltage swing, and the ultimate frequency limit is determined only by the gun geometry and the accelerating potential, *i.e.*, the transit time for electrons to pass the grid before the grid swings to opposite polarity. The XII e-gun, shown in Figure 5, is cantilevered off a 6" conflat flange and operates from 2 kV to 25 kV, with beam currents up to 10 mA. It employs a

telefocus filament housing, and both a pulse grid and an accel grid for pulse tailoring. The gun can be pulsed to the order of 1 MHz, with pulse widths of 100 - 10 ns, delivering an electron "spot" on target of 1 cm diameter when a conventional tungsten V-filament is employed. The gun can also be run DC.

The XII control panel (see Fig. 4) provides direct control of five Variacs which power five identical 60 Hz-50 kV isolation transformers which in turn drive the circuits for the e-gun. The five panel-driven circuits are: filament heating; +5 volts (ref); -pulse volts; +pulse volts; and accel volts. The high voltage (i.e. filament housing voltage) is set directly from the control on the HV supply chassis. The panel-controlled power is supplied through a 6-connector relay controlled by an interlock system, which also powers the high-voltage supply interlock. The control panel also incorporates an optical emitter driver. This converts a pulse from an external generator and converts it to an optical pulse, which drives the switching grid via a fiberoptic cable.

Figs. 6a and 6b show preliminary x-ray data obtained with XII. The x-rays were detected with a surface barrier detector (SBD) (6a and 6b) and a diamond photoconductor (6b). In this case the ringing in the SBD signal is due to the SBD preamplifier; this problem will need to be corrected since x-ray plasma oscillations often have comparable frequencies.

3.D. PIXE X-Ray Source

The third x-ray source we have constructed for x-ray diagnostic development is called a PIXE source (For Particle-Induced X-Ray Emission). For our work, the fluorescing particles are either protons or ^4He ions accelerated to ~ 170 kV by a Cockcroft-Walton accelerator [11]. For this project, a substantial fraction of our work involved rebuilding large sections of the Cockcroft-Walton (Fig. 7) and the target chambers (Figs. 8 and 9) [11,12,13].

The distinct advantage PIXE has over conventional electron-beam sources (such as XI and XII), is that the x-ray spectrum has little bremsstrahlung continuum since the bremsstrahlung intensity scales like $1/m$ (m the projectile mass). Thus very clean fluorescent lines can be generated. The downside of PIXE is that the apparatus is a more complicated than a conventional electron beam x-ray source. A brief description of the experimental arrangement follows.

Figure 9 shows the target chamber arrangement. X rays fluoresced by the energetic ions striking the target are detected through the two diagnostic

arms, each at an angle of 116 degrees relative to the incident beam direction. Each chamber has a 24-position aperture wheel and a 24-position filter wheel.

Target preparation is one of the central issues for the PIXE experiment. Thick targets are used because of the detection geometry of the system, and the targets are made using one of 6 methods: 1) direct machining for materials such as Al, Cu,...; 2) vacuum deposition for materials such as Cr, Ti,...; 3) epoxy-bonding of pure metal foils such as Be, Zn, Ta,...; 4) electric discharge machining (ECM) for unmachinable materials like W, Mo,...; 5) pressed powders on a metal substrate using a man-powered press or a locomotive crusher (such as Li, B, Si,...); or 6) special vacuum deposition performed at Lawrence Livermore National Laboratory (such as B, U, Ti,...).

Three detectors (two Si(Li) spectrometers and a flow proportional counter) have been used to characterize the PIXE source: 1) an ORTEC Si(Li) spectrometer with an 8 μm beryllium window and energy resolution $R \sim 160$ eV (for ^{55}Fe), which can measure photons of energy between ~ 0.6 keV to ~ 30 keV (the efficiency for 30 keV X rays is about 40%); 2) a KeVex Si(Li) spectrometer with thicker beryllium window ($\simeq 25$ μm); and 3) a flow proportional counter with an ultra-thin window (for example, we have used a 0.5 μm mylar foil coated with ~ 100 Å thick aluminium as a window). Using this proportional counter, we have measured very low energy x rays, such as the Be K line ($E=0.111$ keV), B K line ($E=0.183$ keV), and the C K line ($E=0.277$ keV) (see Fig. 10). A leak valve and a manometer have been used to control and measure the flowing gas pressure, which is set to either atmospheric or sub-atmospheric. A microcomputer based ADC and MCA have been utilized for data acquisition.

In Figs. 10 and 11 we show examples of our PIXE data [11]. With such results and this new PIXE tool, it will greatly facilitate the characterization of different x-ray detectors needed for the development of plasma x-ray imaging diagnostics when spectral purity is of critical importance.

3.E. References

1. R. D. Petrasso, M. Gerassimenko, F. H. Seguin, J. Ting, R. Krogstad, P. Gauthier, W. Hamilton, A. T. Ramsey, P. Burstein, and R. Granetz, "A Soft X-Ray Imaging Camera for the Alcator-A Tokamak", *Rev. Sci. Instrum.*, **51** 585 (1980).

2. R. C. Chase, F. H. Seguin, M. Gerassimenko, and R. D. Petrasso, "Application of Computerized Tomography Techniques to Tokamak Diagnostics", *Optical Eng.* **20** 486 (1981).
3. R. D. Petrasso, M. Gerassimenko, F. H. Seguin, R. Krogstad, and E. Marmor, "X-Ray Imaging Studies of Alcator-A Radiation and Internal Disruptions", *Nucl. Fus.* **21** 881 (1981).
4. R. D. Petrasso, F. H. Seguin, N. G. Loter, E. Marmor, and J. Rice, "Fully Ionized and Total Silicon Abundances in the Alcator-C Tokamak", *Phys. Rev. Lett.* **49** 1826 (1982).
5. F. H. Seguin, R. D. Petrasso, and E. S. Marmor, "Effects of Internal Disruptions on Impurity Transport in Tokamaks", *Phys. Rev. Lett.* **51** 455 (1983).
6. R. D. Petrasso, D. J. Sigmar, K. W. Wenzel, J. E. Hopf, M. Greenwald, J. L. Terry, and J. Parker, "Observations of Centrally Peaked Impurity Profiles Following Pellet Injection in the Alcator C Tokamak", *Phys. Rev. Lett.* **57** 707 (1986).
7. K. W. Wenzel and R. D. Petrasso, "X-Ray Response of Silicon Surface-Barrier Diodes at 8 and 17.5 keV: Evidence that the X-Ray Sensitive Depth is not Generally the Depletion Depth", *Rev. Sci. Instrum.* **59** 1380 (1988).
8. K. W. Wenzel and R. D. Petrasso, "X-Ray Imaging Arrays for Impurity Transport Studies on the Texas Experimental Tokamak", *Rev. Sci. Instrum.* **61** 693 (1990).
9. K. W. Wenzel, C. K. Li, R. D. Petrasso, and D. H. Lo, "X-Ray and α -particle Response of NIST Photodiodes", to be submitted for publication (1992).
10. J. W. Coleman, K. W. Wenzel, R. D. Petrasso, D. H. Lo, C. K. Li, J. R. Lierzer, and T. Wei, "MIT Modular X-Ray Source Systems for the Study of Plasma Diagnostics", submitted for publication in *Rev. Sci. Instrum.* (1992).

11. C. K. Li, K. W. Wenzel, R. D. Petrasso, D. H. Lo, J. W. Coleman, J. R. Lierzer, E. Hsieh, T. Bernat, "PIXE X Rays: From $Z=4$ to $Z=92$ ", submitted for publication in Rev. Sci. Instrum. (1992).
12. J. W. Coleman, M. P. J. Gaudreau, C. Niessen, K. W. Wenzel, R. D. Petrasso, C. K. Li, and D. H. Lo, "A Linear Accelerator for Neutron, γ -Ray, and Charged Particle Generation", Bull. Am. Phys. Soc. **35** 2045 (1990).
13. K. W. Wenzel, D. H. Lo, R. D. Petrasso, J. W. Coleman, C. K. Li, J. R. Lierzer, C. Borrás, T. Wei, E. Hsieh, and T. Bernat, "The MIT Cockcroft-Walton Fusion Product and PIXE X-Ray Source", submitted for publication in Rev. Sci. Instrum. (1992)

X-RAY SOURCE SCHEMATIC

Fig. 1. The x-ray source XI is an electron-beam impact source. The interchangeable anode is water cooled to allow high emission currents. The large vacuum chamber allows several x-ray detectors to view the source simultaneously, which enables cross calibrations to be reliably determined. Furthermore, several movable filters allow spectral purity and filter transmissivities to be experimentally measured.

Fig. 2. The absolute x-ray response of a NIST photodiode (UDT model XUV-35) was measured with XI by comparing its response to that of an absolutely calibrated SBD [3,7,9]. The solid line represents the calculated response for a "generic" silicon detector with a 100 Å SiO_2 "dead layer" and 40 μm active thickness. This thickness determines the "roll-off" of the x-ray response at high energies.

Fig. 3. The spectrum from XI with a copper anode ($HV=12$ kV and $I_{em}=2$ mA) was obtained with a KeVex Si(Li) spectrometer. The detector was filtered with $12.5\text{ }\mu\text{m}$ copper foil and apertured with a 0.16 diameter Pb collimator, the latter principally to reduce the x-ray flux on the detector to a desirable level. Noise pulses dominate the channels below about 700.

HIGH VOLTAGE CONTROLLER

GRIDDED e-GUN X-RAY SOURCE (XII)

Fig. 4. The x-ray source XII is an electron beam x-ray generator with fast pulsing capabilities. The gridded e-gun x-ray source employs a tungsten filament and operates in the range from 2 to 25 kV, with beam currents up to 10 mA. The electron spot on target is about 1 cm diameter. Having both a *pulse* grid and an *accel* grid for pulse tailoring, the gun can be pulsed to higher than 1 MHz repetition rates, with pulse widths of 100 to 10 ns. Four ports for x-ray detectors view the air cooled target. The complete system, including electronics, is housed on the cart as shown.

GRIDDED e-GUN
for
X-RAY SOURCE XII
SECTION SCALE 1:1

Fig. 5. The gridded e-gun for x-ray source XII is a tetrode, shown here schematically in cross section. The axial spacings between the cathode and the *pulse* and *accel* grids allow pulsing up to 1 MHz for beam energies as low as 2 kV. This limit is determined by the electron time-of-flight between electrodes. Four detector ports view the target. Port 1 is permanently occupied by an SBD, port 2 is occupied at present by a Type II Diamond Photoconductor Detector, and ports 3 and 4 are available for other x-ray detectors.

Fig. 6. X-Ray detector signals were measured on XII. a) The signal shown is the SBD output resulting from a copper target in the gridded e-gun x-ray source chamber. The ringing is from the SBD preamplifier. The e-gun high voltage is 18 kV, and the emission current I_{em} is 0.5 mA. b) The lower trace is the same as in a), but with reduced gain. The upper trace is from a diamond photoconductor, which we are beginning to study.

Fig. 7. The 170 kV Cockcroft-Walton linear accelerator is used as a source of Particle-Induced X-Ray Emission (PIXE). PIXE generates very clean characteristic x-ray line radiation by accelerating a proton or ^4He beam onto a solid target. The PIXE x rays are detected by either solid state spectrometers or gas proportional counts (see also Figs. 8 and 9).

Fig. 8. The KeVex Si(Li) was used on the Cockcroft-Walton generator to measure PIXE x-rays. This spectrometer was used to measure x-ray lines with energies $\gtrsim 2$ keV (see data in Fig. 11, for example). The spectrometer viewed the target from an angle of 116° relative to the incident beam direction.

Fig. 9. This schematic illustrates the experimental setup for PIXE experiments. Two diagnostic arms allow different detectors to simultaneously view the target. Each arm contains separate filter and aperture wheels. These wheels can be used to control the count rate in a given detector, or to insert filters for spectral purity checks or filter transmission measurements.

Fig. 10. PIXE spectra from a) beryllium ($Z=4$), b) boron ($Z=5$), c) carbon ($Z=6$), and d) fluorine ($Z=9$). The K lines are at 0.108 keV, 0.183 keV, 0.277 keV, and 0.68 keV respectively. These spectra were measured by a flow proportional counter with a $0.5\ \mu\text{m}$ mylar window. The flow gases used were either a mixture of 99.05% He + 0.95% isobutane or P10. The proton beam energy was 150 keV. It is important to note that the maximum secondary electron energy from impact of a proton beam of this energy is 0.3 keV.

Fig. 11. PIXE spectra from a) aluminum ($Z=13$), b) vanadium ($Z=23$), c) cobalt ($Z=27$), and d) copper ($Z=29$). The K_{α} lines are at 1.485, 4.95, 6.95, and 8.05 keV respectively. As described in the text, two different Si(Li) detectors were used to measure these spectra. As in the case of other low- Z materials (see Fig. 10), the proton beam was run with an accelerating potential of 150 kV.

Task APP-09
MILLIMETER/SUBMILLIMETER-WAVE FUSION ION DIAGNOSTICS

Principal Investigators

Paul P. Woskov
MIT Plasma Fusion Center, NW16-134
167 Albany Street
Cambridge, MA 02139
Tel. 617-253-8648

Daniel R. Cohn
MIT Plasma Fusion Center, NW16-140
167 Albany Street
Cambridge, MA 02139
Tel. 617-253-5524

Technical Progress (FY92)

The primary goal of this project is to develop and experimentally demonstrate collective Thomson scattering (CTS) as a localized diagnostic of confined energetic ions in a tokamak. In particular the goal is to develop a diagnostic capability for the study of alpha particles in D-T burning tokamak experiments. Both the mean energy and the partial fraction of energetic ions to energies greater than 4 MeV can be diagnosed by CTS.

Progress during Fiscal Year 1992 has been made and is anticipated on a number of fronts. During this time this project has been involved in two major collaborations. One was with the JET Joint Undertaking in Europe to implement a 140 GHz gyrotron CTS system on JET and the other with the Princeton Plasma Physics Laboratory to implement a 60 GHz CTS system on TFTR. In addition, modeling calculations were advanced at MIT.

JET Collaboration

The main focus of the project effort during the first half of FY92 was in collaborating with the JET Joint Undertaking in Europe. An aggressive effort was made to make operational a 140 GHz gyrotron CTS system before a major shutdown of the JET tokamak on February 22, 1992. MIT contributed gyrotron power supplies and a Post-Doctorate scientist to this collaboration. Unfortunately, the gyrotron tube was not made operational in time before the shutdown to obtain plasma scattering measurements. However significant progress was made in making operational other subsystems of this CTS

diagnostic system. This included calibrations of waveguide and receiver systems and background plasma emission measurements. A list of the accomplishments in which MIT participated is as follows:

1. The universal polarizer, which is a mirror assembly for controlling the polarization state of the gyrotron beam, was experimentally calibrated. The universal polarizer is located between the Vlasov launcher above the gyrotron and the input to the transmission line to the tokamak. It can convert the linear polarized beam from the Vlasov launcher to any linear orientation or to any degree of ellipticity, right or left handed. A millimeter-wave test setup using a quartz quarter-wave plate and custom teflon lenses was designed and implemented for the calibration. The resulting data will be used with the computer control of the polarizer to launch the correct plasma propagating mode during JET runs.
2. The universal polarizer was installed and aligned with the Vlasov launcher. MIT personnel assisted W. Kasperek, designer of the universal polarizer and Vlasov launcher, with alignment of these two components in the gyrotron beam line. This involved the injection of a low power 140 GHz klystron beam backward through the universal polarizer and Vlasov launcher to the gyrotron window. A mirror at the gyrotron window then reflected this beam back through the launcher and polarizer. They were then adjusted for maximum reflected signal.
3. MIT personnel also advised in a similar calibration of the polarization control optics at the receiver input.
4. The rotation of the scattered signal polarization by the receiver transmission line and the orientation of the transmission line output signal polarization relative to x or o mode polarization in the tokamak was experimentally determined. This calibration was accomplished by launching a low power signal

of known linear polarization from the tokamak test cell through the receiver waveguide.

5. A method was developed and carried out for the calibration of the receiver transmission line losses and for receiver noise temperature measurements. A unique feature of JET was taken advantage of to determine the receiver system noise temperature. The JET vacuum chamber is heated to 300-350° C and closely monitored. The vacuum chamber was therefore used as a calibrated hot black body source to calibrate the receiver system. The advantages of this are that the entire receiver front end, including vacuum window and launch optics, is included in the calibration. In addition, a black body source is known to be spectrally flat over the 12 GHz receiver bandwidth so that the relative calibration of the 32 receiver channels could, in principle, be accomplished. Use of plasma emission for calibration is also being investigated.
6. A preliminary optimization was made of the receiver dynamic range. One of the primary problems in the JET receiver system is that the background plasma emission is many orders of magnitude higher than the black body calibration signal levels. If the receiver is optimized for the calibration source, it will be saturated when viewing the plasma. If it is optimized for viewing the plasma, the calibration signal will be well below the receiver noise floor requiring unreasonably long integration times. A compromise must be made for the acceptable receiver gain. Also any non-linearity in signal detection between strong and weak signals needs to be taken into account. Receiver optimization was carried out for the last JET run days in February.
7. Background electron cyclotron emission (ECE) measurements were carried out during 3.4 Tesla shots before JET shutdown. The JET CTS system is designed for optimum operation at a central tokamak field of 3.4 Tesla. Therefore, the background

plasma emission levels at this field are of critical importance. Three days of data were taken, and at the time of this writing it was being analyzed. Preliminary estimates are that the background levels are several hundred eV, a high level for this type of diagnostic but about what was expected.

8. Lacking a gyrotron beam, a low power klystron beam was launched into the plasma, and a preliminary attempt was made to scatter from nonthermal plasma fluctuations. None were observed. However, stray klystron power was observed for all orientations of the scanning gyrotron launch optics. This could be an indication of a potential future problem when the 60 mW klystron beam is replaced with a 400 kW gyrotron beam. JET has no beam or viewing dumps installed.

Anticipated progress in the JET collaboration during the second half of FY92 will include completion of analysis of the ECE background measurements, contributing to the redesign of the receiver launch optics, and consulting on system improvements in preparation for return of JET to operational status in 1993. JET will be down for approximately 14 months to install a new bottom divertor. This new divertor will block the existing receiver port requiring a new receiver launch optics design on another port. It is also probable that the scanning mechanisms for the gyrotron launch optics will also have to be redesigned because of deficiencies discovered during this past operational phase.

TFTR Collaboration

The main focus of the project effort during the second half of FY92 will be the collaboration with TFTR. At this time, major hardware installation of the 60 GHz gyrotron CTS system will be taking place with the goal for first operation in the summer of 1992. MIT will contribute a Post-Doctorate scientist and the heterodyne receiver system. Progress was made in the first half of FY92 in planning, design, and fabrication of in-vacuum vessel components. A list of accomplishments are as follows:

1. The in-vacuum vessel, scanning, gyrotron launch optics assembly was designed, fabricated, and tested. The challenge

here was to launch a diffraction limited Gaussian beam through an 8 inch diameter port and allow for 25° scanning in the poloidal direction and 10° scanning in the toroidal direction without having the beam clipped by the port. A clever mechanical linkage was designed that simultaneously translates and rotates the final launch mirror, keeping the gyrotron beam centered on the port as it is steered. At the time of this writing this launch optics assembly was being installed on TFTR.

2. The gyrotron beam focusing, off axis elliptical mirror was designed, fabricated, and tested. The next to last mirror in the launch optics assembly is a fixed off axis elliptical mirror for focusing the gyrotron beam into the plasma. The computer code for manufacturing this mirror was written at MIT. The mirror was made in stainless steel to minimize eddy current forces. Tests at 60 GHz showed a $1/e$ spot size of 7 cm will be achieved at plasma center.
3. Gyrotron beam and receiver field of view dumps were designed, fabricated, tested, and installed inside TFTR. Beam and viewing dumps are important to minimize stray gyrotron power and reflected plasma emission from reaching the receiver. Silicon carbide tiles with a pyramidal surface structure were designed for absorbing 60 GHz radiation. About 800, two inch square tiles have been installed inside TFTR opposite the gyrotron and receiver ports. Ray tracing calculations were carried out at MIT for high performance super shot plasmas to ensure that all the relevant surfaces of the vacuum vessel are covered.
4. The gyrotron beam and receiver signal waveguide transmission line designs were completed. General Atomics provided the detailed design and is fabricating the components. MIT personnel were involved in specifying the transmission line requirements and reviewing the final design. Both

transmission lines will use corrugated aluminum waveguide to transmit the HE_{11} mode and will incorporate mode converters between this transmitting mode and the operating modes of the gyrotron (TE_{02} cir.) and receiver (TE_{01} rect.). Polarization control will be by grooved rotating mirrors in a miter bend of each transmission line.

5. The heterodyne receiver design was completed, and all major parts ordered. MIT will be supplying this receiver which includes a 38 channel filter bank for analyzing the scattered spectrum. This receiver also includes a varactor controlled local oscillator (LO) which will be phased locked to the gyrotron frequency. The phase locking electronics circuit has already been built by Princeton engineers. Phase locking the LO will make possible measurements of the bulk ion velocity distribution as well as that of the energetic ions. MIT personnel are also working with PPPL engineers to design the data acquisition electronics that will acquire the signal following the filter bank.

Anticipated progress in the TFTR collaboration will be to complete installation of the diagnostic system and make it operational. At the time of this writing it appears that the 60 GHz gyrotron tube will not be delivered to Princeton until the end of FY92. However all the other subsystems including the gyrotron power supply, gyrotron and receiver transmission lines, the receiver system, and the data acquisition electronics will be made operational. This will include calibration work with which experience was gained at JET.

A key milestone will be to make background plasma emission measurements with the viewing dumps installed. Earlier measurements in the fall of 1990 showed a 20 eV background level during TFTR super shots. It is believed that even this relatively low level is due to wall reflections. If the viewing dumps lower this background level it will be a good test of the dumps and it will increase our confidence in detecting plasma scattered signals with high signal to noise ratio.

Modeling Calculations

Progress was made in improved modeling of the expected scattered signal spectra and in the error analysis of expected diagnostic performance. Two main areas of accomplishment are listed as follows:

1. An electromagnetic code was written for calculating the shape of the scattered spectrum. An earlier electrostatic code made a longitudinal approximation which ignored transverse components to the plasma dielectric tensor. The old and new codes give the same result except when near perpendicular to the magnetic field. A lower hybrid resonance peak which is present in the scattered spectrum when the diagnostic scattering geometry is near perpendicular to the magnetic field can now be more accurately predicted. A by product of our ability to accurately model the lower hybrid resonance is a new diagnostic capability to measure the localized magnetic field pitch angle. The sensitivity of the lower hybrid resonance frequency to pitch angle is greater than 1 GHz per degree making possible a very sensitive q profile diagnostic that requires only a relatively straightforward frequency measurement and knowledge of scattering diagnostic orientation.
2. An error analysis was carried out to estimate the accuracy for determining the alpha-particle fraction and temperature. Experimental spectra were simulated using a Monte Carlo technique to add noise to calculated spectra. The error analysis was then performed using a non-linear fitting code. For TFTR parameters, 20 eV background emission, and 100 ms signal integration times, it was shown that the alpha-particle fraction could be determined with less than 5% error and the temperature, assuming the velocity distribution is given, to less than 10% error.

Anticipated progress will be to refine the error analysis for different alpha-particle velocity distribution assumptions, explore the number of adjustable parameters that can be used for alpha-particle fits, and explore the optimum method for fitting to the bulk ion part of the scattered spectrum. Another area will be to model neutral ion beam scattered spectra which will be studied when the diagnostic first becomes operational.

TASK APP-10

SMALL SCALE TURBULENCE AND NONLINEAR DYNAMICS IN PLASMAS CONTINUATION PROPOSAL

PRINCIPAL INVESTIGATOR

Paul S. Linsay, Principal Research Scientist
M.I.T. Plasma Fusion Center, NW17-241
175 Albany Street
Cambridge, Massachusetts 02139
617-253-8072

I. TECHNICAL PROGRESS FY92

This past year was spent understanding and improving the performance of my nonlinear forecasting algorithm so that it can distinguish between high dimensional deterministic systems (chaos) and noise. This is particularly important when dealing with plasma data which is inevitably a combination of chaos and random noise. Much of this work involved highly technical questions of function approximation, data sampling, and so forth. As an example, Figure 1a shows the forecasting algorithm applied to experimental data from an experiment with 8 inductively coupled diodes. This is a high dimensional system, about 10 dimensions, and is known to be chaotic by independent means[1]. The figure shows the error distributions for forecasts made with embedding dimensions of 3, 5, 10, 15, and 20 (the distributions have been offset from zero for clarity). The smooth curves are best fit Lorentzians. An embedding of 10 dimensions models the data best. This can be interpreted to mean that the equations of motion for this system would require coupled ordinary differential equations in 10 independent variables. For comparison, Figure 1b shows the error distribution of the same data when modeled by a linear autoregression (AR) of 2, 3, 5, and 10 terms. (Again, the smooth curves are best fit Lorentzians.) This type of model assumes that the data is simply linearly correlated noise that can be forecast with an equation of the form

$$X_{n+1} = a_0 X_n + a_1 X_{n-1} + \cdots + a_d X_{n-d}$$

with constant coefficients, a_i . The nonlinear forecast is clearly better.

I also spent time developing a second discriminant for distinguishing chaos from noise, surrogate data[2]. One way of forming a surrogate generates a Gaussian random process from the data of interest by Fourier transforming the interesting time series, randomizing the phases of the transform uniformly in the interval $[0, 2\pi)$, and then executing an inverse Fourier transform. The new time series has the same power spectrum and autocorrelation function as the original data but is now randomized. The results of applying the nonlinear forecast to surrogate data of this form can be seen in Figure 1c, and its AR is shown in Figure 1d. (The best fit curves here are Gaussians, a consequence of the phase randomization.) The results of the different analyses are shown in Figure 1e. The half width at half maximum of the fitted error distributions are plotted versus embedding dimension for the nonlinear forecasts, and versus number of terms for the AR's. A smaller width is better and the nonlinear forecast for 10 dimensions is clearly the best. It is about 50% better than the linear predictions and more than a factor of 2 better than predictions made on the randomized data. Prior to my improvements, I was unable to identify this time series as chaotic. In fact, it had been identified as noise since the AR made consistently better predictions than the nonlinear forecast.

I have used the improved algorithm to reanalyze plasma data which I had previously concluded was random noise. Figures 2a through 2e apply the same analysis as above to JET reflectometer data from a high beta shot [3]. The data appears to have a large chaotic component and can be modeled with the surprisingly low embedding dimension of 5 (Figure 2e). The analysis also shows that the fluctuations have the character of a Gaussian random process since the best fit error distributions are Gaussians in this case (Figures 2a and 2b). I have reanalyzed all the JET reflectometer data available to me and 7 of the 12 data sets have a strong chaotic component. Most of the fluctuations can be attributed to low dimensional deterministic dynamics rather than a statistical noise process.

An analysis of some Versator II Tokamak (M.I.T.) magnetic fluctuation data [6] produces more ambiguous results (Figures 3a through 3e). The linear autoregression (Figure 3b) has a predictability that is as good as the best nonlinear forecast (Figure 3a), but both are better than any predictions made on the surrogate data generated by dephasing the Fourier transform (Figures 3c and 3d). Inspection of the summary in Figure 3e shows that if the system is chaotic, the dimension is quite low, somewhere between 3 and 5. But this is not a strong conclusion and must be treated with care. The principal difference between the Versator time series and the diode and JET data lies in the autocorrelation function (AC). The Versator II AC falls to zero after a time delay of about 8 time steps and then oscillates about zero thereafter. The other two time series do not fall to zero, and in fact have a significant positive AC for very large time delays.

REFERENCES

- [1] Daniel T. Kaplan and Leon Glass, Direct Test For Determinism In A Time Series, Physical Review Letters 68, 427(1992); Physica D, to be published; and private communication
- [2] James Theiler, Bryan Galdrikian, Andre Longtin, Stephen Eubank, and J. Doyne Farmer, Using Surrogate Data To Detect Nonlinearity In Time Series, Los Alamos National Laboratory, LA-UR-91-2615
- [3] courtesy F. C. Schüller, FOM-Institute of Plasma Physics
- [4] E. Ott, C. Grebogi, and J.A. Yorke, Controlling Chaos, Phys. Rev. Lett. 64, 1196 (1990)
- [5] R. Roy, T. W. Murphy Jr., T. D. Maier, Z. Gills, and E. R. Hunt, Phys. Rev. Lett. 68, 1259 (1992)
- [6] J. Squire, M.I.T., private communication (1992)

FIGURE CAPTIONS

- 1. (a) Nonlinear forecast error distributions for an experiment with 8 inductively coupled diodes. The embedding dimensions are 3, 5, 10, 15, and 20. The peaks have been offset from zero for clarity. (b) Linear forecast error distributions using 2, 3, 5, and 10 term best fit linear autoregression. (c) Nonlinear forecast error distributions for surrogate data generated by dephasing the original diode data. (d) Linear forecast error distributions for surrogate data generated by dephasing the original diode data. (e) Half width at half maximum for the error distributions of a - d, plotted versus embedding dimension for the nonlinear forecasts and versus number of terms for the linear autoregression.
- 2. (a) - (e) same as for Figure 1 but for JET high beta reflectometer data.
- 3. (a) - (e) same as for Figure 1 but for Versator magnetic fluctuation data.

TASK APP-12
PLASMA TURBULENCE AND TRANSPORT

II. Technical Progress in FY92

(a) Simulation and theory of energetic alpha particle driven Alfvén Wave Turbulence (F. Y. Gang, J. N. Leboeuf, and D. J. Sigmar)

The primary objective of this research is to develop physical understandings of energetic alpha particle driven Alfvén wave turbulence and associated anomalous alpha particle transport.

The technical progress made in the first half of FY92 and anticipated to be made in the second half of FY92 is summarized as follows:

1. The finite β hybrid particle-fluid code developed in FY91 in collaboration with ORNL has been used in the study of nonlinear evolution of energetic alpha particle driven Alfvén wave turbulence. A number of important results have been obtained. First, the saturation mechanism has been identified to be the quasi-linear alpha particle phase space profile modification rather than nonlinear mode coupling of MHD turbulence. Second, the subdominance of MHD mode coupling is attributed to the strong correlation between the electrostatic potential $\tilde{\phi}$ and magnetic potential $\tilde{\psi}$ developed by Alfvén wave excitation. The strong correlation between $\tilde{\phi}$ and $\tilde{\psi}$ leads to cancellation of MHD nonlinearities. Third, the phase space profile modification involves a flattening of the spatial gradient (decreasing instability drive) and a steepening of the velocity gradient (increasing alpha Landau damping) of the resonant alphas. While our numerical code fixes the spatial gradient of the alphas, the steepening of the velocity gradient is clearly demonstrated.

2. A separate nonlinear analytical calculation has been carried out to investigate the nonlinear effect of bulk ion Compton scattering, which has not been included in the hybrid code simulation studies, on the nonlinear dynamics of the Alfvén wave turbulence. The calculation is in a shearless slab but includes essential features of a sheared geometry. The crucial point here is that the Alfvén wave eigenfunction is composed of a radially fast varying part and a slowly varying envelope for which fluctuations with radial wavenumber $k_r \rho_i \leq 1$ develop for large $x = r - r_s$, where r_s is the radial position of the Alfvén resonance. Therefore, the usual cancellation between the scattering by a bare particle and that by its polarization cloud does not occur. Ion Compton scattering has been shown to transfer the fluctuation energy from small k_θ to large k_θ . This spectral flow induces a turbulent spectrum shift away from the linear alpha growth rate, thus reducing the power transfer between energetic alphas and Alfvén wave turbulence. Nonlinear saturation is achieved when this nonlinear power transfer is balanced by the electron Landau damping. For typical ITER parameters, saturation levels of $e\tilde{\phi}/T_e \sim 5 \times 10^{-2}$ and $\tilde{B}_r/B_0 \sim 2.5 \times 10^{-4}$ are obtained. Such a fluctuation level will produce stochasticity if more than one toroidal mode is excited. Particle transport due to Alfvén wave turbulence for both alpha particles and bulk plasmas is also calculated. The alpha particle flux is found to be much smaller than the mixing length estimate. The electron particle flux is approximately equal to that of alpha particles. For typical ITER parameters, an estimate of alpha particle diffusivity $D_\alpha \sim 10^4 \text{ cm}^2/\text{s}$ is obtained, i.e. anomalous alpha transport is of the same magnitude as bulk plasma transport!

3. Based on these works, we expect that both quasi-linear profile modification and nonlinear ion Compton scattering play important roles in the nonlinear evolution of Alfvén wave turbulence. Therefore, in the second half of FY92,

we plan to study the coupled nonlinear evolution of the alpha density profile $n_\alpha(r, t)$ in the presence of fusion alpha particle source $S^f(r, t)$ and the turbulence spectrum $|\tilde{\phi}|_k^2(t)$ in the presence of both quasi-linear profile modification and nonlinear ion Compton scattering based on the following equations:

$$\begin{aligned}\frac{\partial}{\partial t} n^\alpha(r, t) + \frac{\partial}{\partial r} \Gamma^\alpha(r, t) &= S^f(r, t) \\ \frac{\partial}{\partial t} |\tilde{\phi}|_k^2(t) &= 2(\gamma_\alpha^l + \gamma_e^l + \gamma_i^{nl}) |\tilde{\phi}|_k^2(t)\end{aligned}$$

where $\Gamma^\alpha(r, t)$ is the quasi-linear alpha particle flux which depends on both the alpha particle density profile and turbulence spectrum, γ_α^l is the linear alpha growth rate, γ_e^l is the linear electron growth rate, and γ_i^{nl} is the ion Compton scattering rate. These equations will be solved numerically, and conditions for nonmonotonic temporal behavior of $n^\alpha(r, t)$ will be explored.

TASK APP-13

Phase Contrast Interferometer Diagnostic for Long Wavelength Fluctuations on DIII-D

Principal Investigator:

Prof. Miklos Porkolab
MIT Plasma Fusion Center,
167 Albany Street, NW16-106
Cambridge, MA 02139
Tel. 617 253-8448

Technical Progress in FY92

The Phase Contrast Interferometer (PCI) diagnostic was installed on the DIII-D toroidal device in FY91. This diagnostic effort addresses the strong emphasis in current fusion research on the understanding of anomalous transport, which is generally believed to be linked with edge turbulence, particularly at long wavelengths (a few cm) [1]. While studies of edge turbulence are commonly carried out with scattering or reflectometry, such methods lack spatial and wavenumber resolution, respectively. Such inadequacies are not shared by imaging techniques, which can map the temporal evolution of radial density perturbations in their natural real space representation. The Phase Contrast imaging technique offers both long-wavelength capability (up to 7.5 cm) and spatial resolution (2-3 mm), in addition to high sensitivity ($\delta n \geq 10^7 \text{ cm}^{-3}$), and broad frequency response (1 KHz to 100 MHz). This diagnostic is also ideally suited to studying externally induced RF waves, such as those associated with the Fast Wave Current Drive experiments [2]. This apparatus represents a novel application of a technique that is well established in optical microscopy, but has only one, very successful, precedent on a tokamak [3]. Because it detects exclusively radially propagating perturbations, the PCI diagnostic is immune to the substantial Doppler shifts induced by poloidal plasma rotation on the DIII-D far infrared scattering spectra [4], and it is thereby not subject to the inherent ambiguity of such results. The PCI apparatus fills an important gap in the study of DIII-D edge fluctuations, completing a roster of diagnostics

which also includes the UCLA FIR scattering apparatus, the UCLA reflectometer, and the upcoming lithium beam fluctuation diagnostic.

The measurement performed by the PCI can best be described as a multi-chordal measurement of density fluctuations, integrated along 16 adjacent vertical chords in the proximity of the outer edge of the plasma. A 7.5 cm diameter CO₂ laser beam is launched vertically into the plasma (Fig. 1), where it undergoes a phase variation proportional to the line integral of the plasma density. Spatial filtering is required at the receiving end in order to convert the phase variation into a measurable intensity variation (hence the name "phase contrast"), which is then detected by a detector array. The detected signal is then directly proportional to the original density fluctuation, as a function of the major radius. The high sensitivity is made possible by the fact that this interferometer does not rely on an external reference arm, and hence it is not susceptible to loss of fringes caused to mechanical disturbances. Owing to the high sensitivity the PCI can detect acoustic waves in air, which then provide a simple means of testing and absolutely calibrating the diagnostic.

After completion of the fabrication and installation stage, a lengthy trouble-shooting phase ensued, which occupied most of CY91. Not all of the technical challenges we encountered could be anticipated in the design phase. The most arduous problem has been the elimination of the effects of mechanical vibrations. The phase contrast method hinges upon a spatial filter located at the receiving end of the optics, on which the CO₂ laser beam must be focused with great accuracy. The experimental observation has been that mechanical vibrations in the numerous optics mounted on and around the machine cause the focal spot to move up to 100 times the acceptable tolerance, with a typical repetition rate of 20 cycles per second during a plasma discharge. To counteract such displacements, an active feedback system was built, which relied on a colinear visible HeNe laser beam to measure the position of the focal spot on the focal plane, and on two rotatable mirrors to keep that spot centered (see Fig. 2). The high gain required for a damping factor of 100 at 20 Hz made it necessary to tailor the response function of the frequency compensation network in order to avoid high-frequency resonances. We adopted an iterative approach, and eventually reached the optimal response by modelling the system with a computer

code which ran on the Cray. At this point it was discovered that slight fluctuations in the HeNe laser power and line shape were disturbing the system, and it was necessary to reconfigure the feedback system to detect the position of the CO₂ laser spot itself. It is fortunate that a quadrant LN₂-cooled HgCdTe sensor had just become available for the first time on the market. The addition of this component eliminated the vibration problem completely.

Once stabilization had been achieved, we started collecting plasma data. We have operated the apparatus for four weeks thus far. Data analysis is underway and has already provided interesting insight into the spectrum of long-wavelength fluctuations at the edge. Each plasma discharge can provide a large wealth of data, consisting of spatial amplitude and phase profiles for *each frequency* from 1 KHz to 1 MHz, as they evolve in time, for a total interval of 60 msec (or more if the bandwidth is reduced). An example of a typical cross-correlation plot is shown in Fig. 3, exhibiting a dominant wavelength of $\lambda_{\perp} \simeq 4$ cm. Fig. 4 shows the time evolution of the frequency spectrum at one particular radial location, displaying a marked peak around 95 KHz.

To date a considerable amount of software development has been carried out to aid with the design of the feedback compensation network and also to optimize the optical design at various stages of the installation. We have also carried out extensive code-work to generate dispersion relations for linear ICH and IBW waves, and non-linear parametric decay instabilities (PDI) [5], including decay into ion Bernstein waves and quasi-modes. We expect to look for such waves in FY93. In particular, edge RF probe data has already detected substantial PDI during fast wave current drive experiments.

References

- [1] H. Biglari, P.H. Diamond, and M.N. Rosenbluth, Phys. Fluids B **1**, 109 (1989).
- [2] M.J. Mayberry, S.C. Chiu, M. Porkolab, V. Chan, R. Freeman, R. Harvey, R. Pinsker, "60 MHz Fast Wave Current Drive Experiment for DIII-D", Proc. 8th Topical Conf. on RF Power in Plasmas, Irvine, CA (1989), AIP Conf. Proceedings **190**, 298 (1989).
- [3] H. Weisen, Rev. Sci. Instrum. **59**, 1544 (1988).

- [4] R. Philipona, E.J. Doyle, N.C. Luhmann, Jr., W.A. Peebles, C. Rettig, K.H. Burrell, R.J. Groebner, H. Matsumoto, and the DIII-D Group, Rev. Sci. Instrum. **61**, 3007 (1990).
- [5] M. Porkolab, "Parametric Instabilities in the Tokamak Edge Plasma in the Ion Cyclotron Heating Regimes", Fusion Engineering and Design **12**, 93 (1990).

Figure 1. Location of PCI diagnostic on DIII-D.

Figure 2. Schematics of imaging optics.

Figure 3. Two-point correlation function of density fluctuations, at given frequency and at given time. Wavelength is inferred from plot.

Figure 4. Time evolution of frequency spectrum of fluctuations at given spatial location.

1. TASK APP-14

Charged and Neutral Fusion Product Diagnostics for Fusion Plasmas

2. Principal Investigator

Richard Petrasso
MIT Plasma Fusion Center, NW16-132
167 Albany Street
Cambridge, MA 02139
Tel.: (617) 253-8458

3. Technical Progress in FY 92

3.A. Overview of Technical Progress in FY 92.

The generation of copious fusion products – alphas (3.5 and 3.6 MeV), protons (14.7 and 3.0 MeV), neutrons (2.5 and 14.1 MeV), and γ rays (~ 3 MeV) – are issues of paramount importance to the fusion energy program. The thrust of our fusion-product effort is to develop diagnostics based on these radiations. To accomplish this goal, we have rebuilt substantial sections of a fusion product source that generates these radiations [1,2]. In turn we are using these emissions to design, test, and build diagnostics for the next generation of tokamak experiments (such as Alcator C-MOD).

In the following, we briefly describe, first, the fusion-product source (i.e. Cockcroft-Walton accelerator); second, our progress in the detection of energetic charged products (3.0 and 14.7 MeV protons; 1.0 MeV tritons; 0.8 MeV ^3He ; and 3.7 MeV ^4He); third, the detection of fusion neutrons; and fourth, the detection of fusion γ rays. We also briefly describe our critique, to be published in 23 March Phys. Rev. Letters, of the Brookhaven cluster-impact fusion experiments.

3.B. Cockcroft-Walton Accelerator

The cornerstone of our fusion-product diagnostic development is a Cockcroft-Walton accelerator (Fig. 1) of which we have rebuilt substantial sections [1,2].

The Cockcroft-Walton can accelerate select ions into specific targets resulting in various fusion reactions, which include:

To achieve reactions (1) and (2), for example, deuterons from the plasma ion bottle are accelerated to $\lesssim 170$ kV and directed onto either a titanium or erbium target previously saturated with deuterium. In order to observe the resultant charged fusion products, we built two different target chambers, one of which is shown in Fig. 2. Each target chamber can accomodate several surface barrier detectors (*i.e.*, charged-particle detectors), either directly in the vacuum or just outside thin vacuum windows. For example, Fig. 3a shows the spectrum of the charged products that were so obtained [3]. The corresponding neutrons from these reactions are, in this case, detected with a ${}^3\text{He}$ proportional counter (Fig. 3b) [2].

If instead we accelerate ${}^3\text{He}$ ions into a deuterated target we obtain the spectrum shown in Fig. 4 [3]. The 14.7 MeV protons from this reaction are of great interest since, for Alcator C-MOD, they will be unconfined. Most importantly, ${}^3\text{He}$ -minority heating is the principal heating scheme for Alcator C-MOD; thus diagnostics that measure the D- ${}^3\text{He}$ reactivity will be crucial. Consequently we are developing two diagnostics to study the flux of these 14.7 MeV protons from Alcator. The first is based on the surface barrier technology [3]. (*e.g.*, see Fig. 4). From this diagnostic we should be able to measure the D- ${}^3\text{He}$ fusion reactivity and its evolution. A second diagnostic

method we are developing is based on activating select targets with the 14.7 MeV protons [4]. Specifically, this proton undergoes a (p,n) reaction with many materials, leaving telltale γ -emission activity in the sample. This can be detected and measured to very high resolution with our HPGe detector; this provides then a simple passive means of measuring the D- 3 He proton fluences and integrated reactivity.

For example, Fig. 5 shows the γ spectrum of titanium before and after bombardment by 14.7 MeV protons. In this instance the reaction is $^{48}\text{Ti}(p,n)^{48}\text{V}$. ^{48}V subsequently decays back to ^{48}Ti with a 16-day half life, emitting γ rays at 0.98 and 1.31 MeV. From our experiments, the measured activity matches very well that expected from the simulations [4]; therefore, from these results and other simulations done for Alcator, we expect this to be a very effective diagnostic for measuring the integrated D- 3 He reactivity on Alcator C-MOD.

A third diagnostic development effort concerns high energy γ rays (Eqs. 4, 6, 8, and 10) [5]. Although the γ branching ratios are small ($\sim 5 \times 10^{-5}$) [6], this diagnostic has been successfully used on JET for measuring the D- 3 He reactivity. Currently we are using the p- ^{11}B reaction, shown in Eq. (4), to develop and calibrate our γ ray detectors. Fig. 6 shows the resultant γ spectrum thus obtained. In this instance, a 3" $\times$ 3" NaI(Tl) detector was used to obtain these data. From such measurements and simulations for Alcator C-MOD, we expect that a 6" $\times$ 6" NaI(Tl), with proper shielding, should allow for the detection of the 16 MeV γ rays from D- 3 He.

As a result of our work with charged fusion products, in particular the D-D reactions (see Fig. 3a), we became interested in the claims by the Brookhaven group [7,8] that, through cluster fusion, they obtained fusion rates 20 orders of magnitude in excess of that predicted by the standard S-factor fusion cross-section formalism [9]. Our analysis/critique, to be published in 23 March Physical Review Letters [10], points to beam contamination, rather than cluster-impact fusion, as the likely cause of their fusion rates. We summarize here the main points of our argument and their experiment.

Beuhler et al. (BFF) reported anomalously huge D-D fusion rates while bombarding deuterated targets with $(\text{D}_2\text{O})_N^+$ clusters ($N \simeq 25$ -1000) accelerated to $\simeq 325$ keV. For a D lab energy of ~ 0.3 keV [e.g. ~ 300 keV $(\text{D}_2\text{O})_{100}^+$], they estimated 20 orders of magnitude enhancement of the fusion rate.

However, BFF show D-D proton spectra (3 MeV), obtained with a surface

barrier detector, with widths (FWHM) of about 11% [7,8]. The FWHM gives an energy width of $\simeq 330$ keV. BFF [7] attributed this width to differential energy loss of 3 MeV protons passing through the $50 \mu\text{g}/\text{cm}^2$ Al front layer of the SBD at various angles. However, we calculate this effect to be only ~ 1 keV [11]. Broadening due to energy straggling is ~ 5 keV [12]. About 20 keV is the electronic noise specified by the manufacturer [13], however, in our experience, $\simeq 50$ keV is easily obtained. Thus, a broadening of still $\simeq 330$ keV must be attributed to some other process, which we discuss henceforth.

In the BFF experiments, the cluster beam hits a deuterated target $\simeq 1.5$ cm from a 300 mm^2 SBD (Fig. 7). Thus the SBD subtends an angle (at its extreme) of about 60° . The D-D proton energy in the lab frame depends on the D-D center-of-mass velocity (a function of the initial D energy) and the angle (θ) between the proton and the initial deuteron directions (see Table 1 and Fig. 7). From Table 1 and the extent of the BFF proton peak, we conclude that the fusing deuterons have lab energy of $\gtrsim 50$ keV (a smaller effective angle, which should apply to BFF, would imply a higher energy. This is the reason for the ">" in $\gtrsim 50$ keV).

As a test for beam contaminants, Beuhler *et al.* argued that ranging their cluster beam through $500 \mu\text{g}/\text{cm}^2$ of Au before impacting a $(\text{C}_2\text{D}_4)_n$ target will eliminate "cluster fusion" but not light-ion contaminant fusion (from D^+ , D_2^+ , D_3^+), assuming the latter were responsible for their observed rate [8]. As we henceforth discuss, this argument is not generally valid. A contaminant of e.g. ~ 100 keV D^+ will indeed penetrate $500 \mu\text{g}/\text{cm}^2$ of Au; however, it loses 70 keV in ranging through [11], and the fusion yield is reduced by ~ 20 times [the same reduction in fusion yield holds for $\text{D}_2^+(\text{D}_3^+)$ at $\simeq 200$ keV (300 keV)]. Indeed BFF did observe in such an experiment very roughly an order of magnitude decrease in the fusion rate (the experiment statistics are poor), but they interpret this as proof that light contaminants are not causing their observed rate. We disagree. Furthermore, while BFF believe they have eliminated oxygenated light contaminants from the ion source up to the first stages of their accelerator [14], we feel that contaminants formed by, for example, ionization in the accelerator tube subsequent to splash-back from the apertures have not been convincingly precluded. Finally, we note that with a ~ 100 keV D^+ (~ 300 keV D_3^+) contaminant, for instance, only of order 1 D^+ (D_3^+) per 3000 (10000) clusters [$(\text{D}_2\text{O})_{100}^+$ at 1 nA] is needed to produce the BFF fusion rate.

Therefore, from our analyses of the BFF data, from the negative theoretical results [15,16], and from the negative cluster experiment with post-acceleration mass and energy analyses [17], we conclude that a light-ion contaminant has not been ruled out as the cause of BFF fusion reactions. To do such will probably require post-acceleration mass and energy analyses.

3.E. References

1. J. W. Coleman, K. W. Wenzel, C. K. Li, D. H. Lo, and R. D. Petrasso, "γ-Ray and Neutron Calibration Facility", *Rev. Sci. Instrum.* **61** 3234 (1990).
2. K. W. Wenzel, D. H. Lo, R. D. Petrasso, J. W. Coleman, C. K. Li, J. R. Lierzer, C. Borrás, T. Wei, E. Hsieh, and T. Bernat, "The MIT Cockcroft-Walton Fusion Product and PIXE X-Ray Source", submitted for publication in *Rev. Sci. Instrum.* (1992).
3. D. H. Lo, R. D. Petrasso, K. W. Wenzel, J. W. Coleman, C. K. Li, J. R. Lierzer, E. Hsieh, and T. Bernat, "Response of SBDs to MeV Protons, Tritons, and Alphas: Evidence that the Charged Particle Sensitive Depth is not Generally the Depletion Depth", submitted for publication in *Rev. Sci. Instrum.* (1992).
4. J. R. Lierzer, R. D. Petrasso, K. W. Wenzel, D. H. Lo, J. W. Coleman, C. K. Li, E. Hsieh, and T. Bernat, "A D-³He Diagnostic for Tokamaks which uses 14.7 MeV Protons to Activate Titanium or Chromium", submitted for publication in *Rev. Sci. Instrum.* (1992).
5. K. W. Wenzel, R. D. Petrasso, D. H. Lo, C. K. Li, J. W. Coleman, J. R. Lierzer, E. Hsieh, and T. Bernat, "Fusion γ-Ray Diagnostic Development at MIT", submitted for publication in *Rev. Sci. Instrum.* (1992).
6. F. E. Cecil, D. M. Cole, and R. Philbin, "Reaction $^2\text{H}(^3\text{He},\gamma)^5\text{Li}$ at Center-of-Mass Energies between 25 and 60 keV", *Phys. Rev. C* **32** 690 (1985).
7. R. J. Beuhler, G. Friedlander, and L. Friedman, "Cluster-Impact Fusion", *Phys. Rev. Lett* **63** 1292 (1989).

8. R. J. Beuhler, Y. Y. Chu, G. Friedlander, L. Friedman, and W. Kunmann, "Deuteron-Deuteron Fusion by Impact of Heavy-Water Clusters on Deuterated Surfaces", *J. Phys. Chem.* **94** 7665 (1990).
9. H. Bosch, "Review of Data and Formulas for Fusion Cross Sections", Max Planck Institute Report #Ipp I/252 (1990).
10. D. H. Lo, R. D. Petrasso, and K. W. Wenzel, "Comment on Cluster-Impact Fusion", to be published in *Phys. Rev. Lett.* March 23 (1992).
11. H. Anderson and J. Ziegler, *Hydrogen: Stopping Powers and Ranges in all Elements* Pergamon Press (1977).
12. R. D. Evans, *The Atomic Nucleus* Kriger (1982).
13. EG&G ORTEC, *Detectors and Instruments for Nuclear Spectroscopy* Oak Ridge, TN (1991/1992).
14. R. J. Beuhler, Y. Y. Chu, G. Friedlander, and L. Friedman, "Cluster-Impact Fusion: Time-of-Flight Experiments", *Phys. Rev. Lett.* **67** 473 (1991).
15. M. H. Shapiro and T. A. Tombrello, "Simulation of Cluster Impacts on Metallic Surfaces", *Phys. Rev. Lett.* **65** 92 (1990).
16. C. Carraro, B. Q. Chen, S. Schramm, and S. E. Koonin, "Estimates of Cluster-Impact Fusion Yields", *Phys. Rev. A* **42** 1379 (1990).
17. M. Fallavier, J. Kemmler, R. Kirsch, J. C. Poize, J. Remillieux, and J. P. Thomas, "Search for Nuclear Fusion in Deuterated Targets under Cluster-Beam Impact", *Phys. Rev. Lett.* **65** 621 (1990).

Fig. 1. The 170 kV Cockcroft-Walton generator (background, left) is capable of generating all the fusion products of reactions (1) through (10). The Cockcroft-Walton acts not only as a well calibrated source of charged particles and neutrons, but also of fusion γ rays as well. Graduate student Daniel Lo is shown next to the generator. It typically accelerates a $150 \mu\text{A}$ beam of either deuterium or ^3He onto a deuterated target to generate copious fusion products. (For beam-loaded targets, a D^+ beam of $150 \mu\text{A}$ at 150 kV yields 5×10^7 D-D reactions per second; a gas-loaded target results in rates an order of magnitude higher.) The various charged particles (e.g., protons, tritons, alphas, etc...) and neutrons are all monoenergetic, and their energies can easily be varied by "viewing" the target from different angles relative to the incident beam direction, or by changing the beam voltage. (This is due to kinematics of the beam energy and the reaction Q.) This Cockcroft-Walton generator is an invaluable tool for developing and testing all charged particle and neutron diagnostics (e.g., SBDs, track CR-39, and ^{48}Ti and ^{63}Cu activation). The generator is situated in a radiation vault, sealed by the 3-foot thick concrete door visible in the background.

Fig. 2. The "Ferris Wheel" target chamber was, in part, designed for radiation damage studies of CCD x-ray imaging devices. The flat face allowed a CCD chamber to be directly interfaced with the target chamber in order to maximize the proton flux on the CCD. The target chamber has six diagnostic arms to allow detectors to view the target from several different angles. We are presently using this chamber to measure fusion-product kinematic effects [3].

Fig. 3. Fusion product spectra were obtained by running a deuteron beam onto a deuterated titanium target. a) An "unfiltered" surface-barrier diode (SBD) was used to measure all the charged fusion products from D-D reactions: the 0.8 MeV ^3He , the 1.0 MeV triton, and the 3.0 MeV proton. In this case, the beam was run with an accelerating potential of 25 kV in order to minimize the number of backscattered beam particles impacting the SBD. The SBD viewed the target at an angle of 120° relative to the beam direction. b) The fast (2.5 MeV) neutrons from the D-D reaction, Eq. (2), were measured using a ^3He proportional counter. The peak at 765 keV is due to capture by the ^3He of thermal neutrons, the peak at about 3.2 MeV is due to capture of fast neutrons, and the shoulder at 1.7 MeV is due to elastic scattering of the neutrons by the ^3He nuclei. The ^3He detector views the target at an angle of 90° relative to the beam direction.

Fig. 4. This charged fusion D-³He product spectrum was taken with a fully depleted SBD with thickness of 2000 μm . The range of the 14.7 MeV proton in silicon is about 1360 μm , so a thick SBD is required to measure its full energy. The particles are measured with less than their nominal energies, because of beam/target kinematics (the SBD was at 120° relative to the beam) and some energy loss in a thin plastic filter covering the detector.

Fig. 5. A titanium target was activated by the 14.7 MeV D- ^3He protons while running a ^3He beam onto a deuterium-loaded titanium target. a) The γ -ray spectrum of the titanium target, taken with our HPGe detector before activation, showed only background lines. b) The γ -ray spectrum taken after accelerating a ^3He beam onto a deuterated titanium target shows additional lines at 0.984 MeV and 1.312 MeV. These lines originate from the radioactive decay of ^{48}V , which is produced when a high energy proton charge exchanges with a ^{48}Ti neutron.

Fig. 6. Reaction products from the $p\text{-}^{11}\text{B}$ reactions are shown. a) The α particles were measured with an SBD in the target vacuum chamber over one hour during which the Cockcroft-Walton generator was run with a proton beam of 170 kV and a beam current of $25\ \mu\text{A}$. b) The γ rays were measured with a $3'' \times 3''$ NaI(Tl) detector while running the generator with similar conditions for a period of two hours. Similar data were used to determine the absolute peak efficiency of the γ -ray detector. The 4.44 and 11.5 MeV γ rays are emitted when reaction (8) proceeds through the first excited level of the ^{12}C nucleus, and the 15.9 MeV γ ray is emitted when reaction (8) proceed through the ground state of the ^{12}C nucleus.

Table 1: D-D proton energy (MeV) depends on the D-D CM velocity as a function of the D lab energy, E_D and the lab angle, θ (Fig. 1). ΔE is the energy (MeV) extent of protons collected by an SBD at 90° when it subtends an angle of $\approx 60^\circ$, a value appropriate for the BNL experiments.

E_D (keV)	0°	60°	90°	120°	180°	ΔE
1	3.062	3.042	3.023	3.003	2.984	.039
10	3.151	3.087	3.025	2.964	2.904	.123
50	3.323	3.176	3.035	2.900	2.772	.276
100	3.464	3.249	3.048	2.858	2.681	.391

Fig. 7 This schematic illustrates the target/detector geometry of the cluster-impact experiments of BFF [7,8]. Because the detector viewed a large solid angle, the kinematics of high-energy deuterons reacting in the target caused a broad proton peak to be measured.

END

**DATE
FILMED**

6 / 19 / 92