BNL--46483

DE91 016999

ALTERNATING GRADIENT SYNCHROTRON FACILITY AND PHYSICS
PROGRAM

Derek I. Lowenstein
Brookhaven National Laboratory
Alternating Gradient Synchrotron Department
Upton, NY 11973

Received by OSTI
AUG 19 1991

ABSTRACT

We present a description of the present and future plans for the BNL Alternating Gradient Synchrotron accelerator complex and its concomitant physics program.

The Alternating Gradient Synchrotron (AGS) has been in operation for 30 years providing proton and polarized protons for the high energy physics program, and in addition for the past 5 years providing heavy ions for the nuclear physics program. With the enviable record of three Nobel Prize experiments: J/ψ discovery (1976), CP violation (1980), 2 neutrinos discovery (1989), the AGS has embarked on an ambitious physics program to look for physics beyond the Standard Model. The major emphasis has been on rare kaon decay experiments of which the first round was completed at the end of the 1991 running cycle and the second phase preparations have been initiated. As an example, the present experiments have published

BNL Rare K Decay Program

branching ratio sensitivities of 5×10^{-11} for the decay $K^0 \rightarrow \mu e$ and have measured a branching ratio of $\sim 7 \times 10^{-9}$ (750 events) for the decay $K^0 \rightarrow \mu \mu$. Figure 1 summarizes the present status of both the completed and to be run second generation kaon decay experiments. The experiment that is measuring the Standard Model allowed decay $K^+ \rightarrow \pi \nu \bar{\nu}$ is

Fig. 1. Branching ratio sensitivities for AGS rare kaon decay experiments. Solid lines are reported results, dashed lines are expected results.

*Work performed under the auspices of the U.S. Department of Energy.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED
MASTER

expected to reach the range of Standard Model predictions during their next phase and the experiment that has measured the decay $K^0 \rightarrow \pi e e$ indicates that an irreducible background from the internal bremsstrahlung in K^0 Dalitz decays, $K^0 \rightarrow \gamma \gamma e e$, will limit the search to sensitivities to the order of 10^{-10} . This is one to two orders of magnitude greater than theoretical predictions.

The high energy physics program is not just limited to the study of kaons. A significant effort is being expended to measure the muon anomalous magnetic moment to an accuracy of 0.35 ppm. This is a factor of 20 greater sensitivity than the previous CERN measurement and will place serious limitations on theoretical constructs within and beyond the Standard Model. The major construction effort is a 3 GeV/c storage ring. This storage ring consists of a single 15 meter diameter superferric dipole magnet. Figure 2 is a photograph of one of 4 superconducting coils that will make up this magnet/storage ring, the largest continuously wound superconducting magnet ever fabricated.

Fig. 2. Photograph of one of four 15 m diameter g-2 storage ring superferric coils.

In addition, the program includes experiments (see Figure 3) to search for glueballs and other exotica in both charged and neutral final states, hypernuclear spectroscopy, color transparency measurements, H dibaryon search, kaon scattering, spin physics with polarized protons, antiproton-nucleus reactions, muonium to antimuonium conversion, antiproton imaging for medical applications and muon spin rotation for condensed matter physics.

conversion, antiproton imaging for medical applications and muon spin rotation for condensed matter physics.

In the area of nuclear physics the heavy ion physics program has entered a virgin physics domain and is in the process of characterizing the nature of the interactions and searching for evidence of the quark gluon plasma and the production of strangeness enriched matter (strangelets). This part of the experimental program is the natural lead-in to the next generation of experiments to be performed at the Relativistic Heavy Ion Collider (RHIC) starting in 1997.

The future AGS and RHIC programs are very dependent on the performance of the new AGS injector, the Booster synchrotron, which has completed its initial commissioning studies. During the extremely short running time available this year for accelerator operations, the Booster has been brought on in less than 7 days of beam time. In this short period, the injection, beam capture, acceleration to full energy and extraction aspects have been brought to an operational state. The calculated machine parameters such as tune, natural chromaticity, passive eddy current sextupole correction compensation, etc. have been confirmed by measurement. During the next running cycle in 1992, we expect to complete the injection into the AGS, to accelerate gold ions for the first time, and to begin proton operations with an emphasis of increased AGS beam intensity. All of the initial work this year was accomplished with protons. The Booster was designed to accomplish three major objectives. These are to increase the AGS proton intensity by a factor of 4 to a minimum of 6×10^{13} protons per second, to accelerate all ion species and to increase the polarized proton intensity by a factor of twenty to the order of 10^{12} per pulse. The Booster specifications are described in Table 4. The Booster is the linchpin of the future development of the AGS and RHIC accelerator facility. See Figure 5 for an aerial overview of the accelerator complex.

Table 4

BOOSTER MAJOR DESIGN PARAMETER LIST

CIRCUMFERENCE	201.78 m (1/4 AGS)								
AVG. RADIUS	32.114 m								
MAGNETIC BEND RADIUS	13.75099 m								
NO. OF PARTICLES/PULSE	Protons, 1.5×10^{13} (AGS 6×10^{13} ppp) Polarized Protons, 10^{12}								
	<table><tr><td>C</td><td>S</td><td>I</td><td>Ar</td></tr><tr><td>54</td><td>15</td><td>6.6</td><td>3.2×10^9 ions</td></tr></table>	C	S	I	Ar	54	15	6.6	3.2×10^9 ions
C	S	I	Ar						
54	15	6.6	3.2×10^9 ions						
LATTICE TYPE	Separated function, FODO								
NO. OF SUPERPERIODS	6								
NO. OF CELLS	24								
BETATRON TUNE, X, Y	4.82, 4.83								

NUMBER OF MAGNETS	36 Dipoles, 48 Quads
MAGNET TYPE	Iron-Dominated, Water-Cooled Cu Conductor
DIPOLE LENGTH (Magnetic/Physical)	2.4/2.34 m
MAXIMUM DIPOLE FIELD	5.46KG (for Protons)
MAXIMUM DIPOLE FIELD	12.74KG (for heavy ions)
QUAD LENGTH (Magnetic/Physical)	0.50375/0.472 m,
VACUUM CHAMBER DIMEN.	70 X 152 mm, Dipoles 152 mm (Circular), Quads
ACCELERATION TIME	62 ms, Protons and Polarized Protons 500 ms Heavy Ions
REPETITION RATE	7.5Hz (4 Pulse/AGS Pulse), Protons 1Hz (1 Pulse/AGS Pulse), Polarized Protons 1Hz (1 Pulse/AGS Pulse), Heavy Ions
INJECTION KINETIC ENERGY	206 MeV (Proton) 4.688 MeV/Nuc (S) 1.066 MeV/Nuc (Au)
EJECTION KINETIC ENERGY	1.5 GeV (Proton) 0.367 GeV/Nuc (S) 0.350 GeV/Nuc (Au)

Fig. 5. AGS and RHIC accelerator facility aerial view.

With this marked increase in accelerator capabilities and a large and growing user demand, the experimental areas have been undergoing a major rebuild over the past several years. A new 2 GeV/c separated kaon beam and surface muon beam have recently been completed. A new low energy separated beam (< 1 GeV/c), a 6 GeV/c kaon beam, a new primary proton target station and 3 GeV/c pion beam, a new neutral kaon beam and a new heavy ion primary beam are under construction. In parallel with the beam transport are the new detectors such as for the rare kaon decays, muon g-2, color transparency, strangelet production, etc. The basic beam parameters are summarized in Figure 6.

After the first 30 years, where does the AGS facility go from here? We believe that the approved and anticipated high energy and nuclear physics program will continue to at least the initial operations of RHIC (1997), whereupon the AGS will serve an additional role as the injector to the collider. The expectations by the Laboratory and funding agencies is that the fixed target program would continue beyond that time provided that the physics merits it. We expect to also enhance the spin physics efforts at the AGS with the introduction of a partial Siberian snake to eliminate the presently too costly and time consuming process of tuning out depolarizing resonances. This would then naturally lead to the introduction of Siberian snakes in RHIC to provide for colliding polarized proton beams at total energies of 500 GeV. Finally, should the Canadian KAON initiative not be realized, we are prepared to submit a proposal to construct a 30 GeV/c Stretcher ring to provide for 10 μ A of proton current with 100% duty factor. This AGS kaon factory would be a cost effective alternative for the physics community.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

AGS BEAMS (January 1991)
Separated Beams for General Use

Separated Beams for General Use					Flux/10 ¹² protons on target								
Beam	GeV/c	p/p(K) (FVM)	Prod. Angle	(mrad)	K ⁺	K ⁻	p	$\bar{p}$	p1 ⁺	p1 ⁻	0 GeV/c	Purity	Remarks
B2,B4	1.5-8(K) 1.5-8(B)	5	3°	0.3	2.7x10 ⁵	1.2x10 ⁶	2x10 ⁷	10 ⁵	4x10 ⁷	3x10 ⁷	4	p1-/K-3 p1/p1- 3/4	To MPS
C2,C4	<1.1	4	10.5°	2.8	8x10 ⁴	3.2x10 ⁴	2x10 ⁷	2x10 ³	8x10 ⁷	8x10 ⁷	0.75	p1-/K-10	L=15m.Remove after FY91 run
C2',C4'	<0.8	4	0	12	3x10 ⁵	1x10 ⁶	1x10 ⁸	1.4x10 ⁴	6x10 ⁸	6x10 ⁸	0.80	p1+/K < 1	L=16m.Construction FY91-92
C6,C8	<0.8	5	5°	10.0	3x10 ⁵	1.0x10 ⁶	1.0x10 ⁸	1.4x10 ⁴	8x10 ⁸	8x10 ⁸	0.7	p1-/K- -5	L=15m.
D9,D8	1.0-2.0	6	5°	1.8	1.1x10 ⁶	0.5x10 ⁶	2x10 ⁷	5x10 ⁵	8x10 ⁷	8x10 ⁷	1.8		L=31m.Commission in FY91
Unseparated Charged Beams													
A1	5-28	3	0°	0.2						10 ⁶	22		To MPS:L=130m
A2	1-10	5	12°	0.3			3x10 ⁶		3x10 ⁶		2		Test Beam.
A3	1-28	4	0°	0.10			6x10 ⁷		1x10 ⁷	4x10 ⁶	14		Test Beam,commission in FY91
B1	5-28	3	0°	0.05			3x10 ⁷		6x10 ⁶	2x10 ⁶	14		Alternates with A1, can transport heavy ions
C1	1-20	5	0°	0.8	6x10 ⁶	7x10 ⁵	2x10 ⁸	1.4x10 ³	7x10 ⁷	5x10 ⁷	13		Primarily heavy ions.
C5	1-28	2	0°	0.15			1x10 ⁷						L=61m, or with C5
													L=81m. Primarily heavy ions
Neutral Beams													
					K _x		n						
B5	2-15		1-4.5(V)	0.1			3x10 ⁷	3x10 ⁸			2-15		Based on FY91 est.;L=10m.
Muon Channel													
D2,D4	.028-	9(p1 [±])	135°	24(p1 [±])	mu ⁺								Possible commissioning in FY91
	.15(mu)	30(mu)	(p1 [±])		10 ³ surface						0.20	e ⁻ /mu ⁻ = 8	
Neutrino Beams													
					Neutrinos		Antineutrinos						
U line					2x10 ⁹ /m ² 10 ⁷ /m ²		1.4x10 ⁹ /m ²					1.4x10 ¹³ ppp typical on target	Fast spill,flux avg over 1.5m radius Wide Band Horn,<E _{nu} >=1.4GeV/c Narrow Band Horn, <E _{nu} >=1.38GeV/c deltaE/E = ± 15%
					p1 ⁺		mu ⁺						
V1 line 3.0	0.8	0°			3.2x10 ⁷		4x10 ⁸				3.0		Fast spill for injection into g-2 ring, available FY1993

Note that 0° beams can be used for polarized protons and/or heavy ion beams.

Fig. 6. AGS experimental area beamline specifications.