154
2-1-82
(82)

LA-9107-MS

(1)
I-1178

DR 240
MASTER

Los Alamos National Laboratory is operated by the University of California for the United States Department of Energy under contract W-7405-ENG-36.

Shipping Containers for Small Samples of High Explosives

Los Alamos Los Alamos National Laboratory
Los Alamos, New Mexico 87545

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Reviewed by R. Dreicer

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

LA-9107-MS

UC-71

Issued: December 1981

LA--9107-MS

DE82 010042

Shipping Containers for Small Samples of High Explosives

Richard A. Hildner
Manuel J. Urizar

DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Los Alamos Los Alamos National Laboratory
Los Alamos, New Mexico 87545

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

SHIPPING CONTAINERS FOR SMALL SAMPLES OF HIGH EXPLOSIVES

by

Richard A. Hildner and Manuel J. Urizar

ABSTRACT

Two sizes of shipping containers for high explosives have been designed and tested at the Los Alamos National Laboratory. The containers have been tested by detonating a powerful, HMX-based explosive in the containers. The containers were approved for shipping 70% of the minimum weight of explosive that could cause vessel failure.

I. INTRODUCTION

In the explosives field, it is imperative that there be a method for shipping small quantities of explosives. These explosives may be uncharacterized materials sent for laboratory evaluation or standard explosives for test comparisons. In the past, small samples (up to 25 g) have been shipped in steel pipes and have been classified as Class C explosives. This is an unsafe practice, because the pipe could be shattered by detonation of the explosive.

The Los Alamos National Laboratory design criteria provide for safe shipment of high explosives by requiring containers capable of complete confinement of a possible detonation of the contents. The Los Alamos containers use stand-off distance and absorption of the detonation energy to reduce the shock to the container walls to a level below the failure strength of the walls.

II. CONTAINER DESIGN

A cutaway view of a Los Alamos container is shown in Fig. 1. The inner aluminum tube keeps the explosive away from the container walls and produces small, low-mass fragments if an explosion occurs. Vermiculite* is used as a filler around the inner tube to absorb explosion energy. The stainless steel outer cylinder wall absorbs the remaining energy by a rapid deformation. The container is shipped in a styrofoam-lined wooden box and the styrofoam prevents the container wall from reaching the box shell during expansion.

*Vermiculite is any of a group of micaceous hydrated silicates of different compositions. It is dehydrated for use as insulation.

The outer wooden box* is manufactured to meet Department of Transportation (DOT) specification No. 173.25.** The styrofoam liners are fabricated from 0.016 g/cm (4.4 lb/ft³) foam. The vessel end plugs are a modified 1/2-in. NPT stainless steel pipe plug and a 7/8-14 hex-head machine bolt. The stainless steel vessel is a modified Hoke DOT gas sampling bottle Model LD-1000 or Model LD-2250, depending on the size required. The vermiculite is insulation-grade No. 4, 60 mesh or finer. The inner aluminum tube is 1.91-cm (3/4-in.)-o.d., 0.09-cm (0.035-in.)-wall 6061-T6 tubing.

The components of the shipping vessel and the assembly are shown in Fig. 2. The Hoke vessel is modified for this use. One 1/2-in. NPT port is retapped to a standard 7/8-14 straight machine thread, and then the port threads on both ends of the vessel are relieved on the inside for 0.16 cm (1/16 in.). The length of the inner tube is measured between the bottoms of the thread reliefs, and the inner aluminum tube is cut to length. The inner tube is inserted from the bottom through the 7/8-14 port with the vessel in a vertical position. Vermiculite is added around the inner tube and lightly tamped until the space is filled. The inner tube is now worked up from the bottom until it seats on the bottom of the thread relief area of the 1/2-in. NPT port. The vessel is turned over and the inner tube is swaged into the thread relief on the 7/8-14 end using a 10° tapered punch. The vessel is again turned over, and the inner tube is expanded to the diameter of the thread relief on the 1/2-in NPT port. This completes the assembly.

Figure 2 shows the components and assembly of the closure plugs. A standard 7/8-14 machine bolt is modified to receive the hollow, vermiculite-filled absorber cap, and the assemblies are rolled together. A standard 1/2-in. NPT pipe plug is modified by bolting an adapter stud to the plug and rolling a vermiculite-filled absorber cap in place. The finished vessels are shown in Fig. 3.

III. TEST RESULTS

Five-gram pellets of PBX 9404,[†] 1.59 cm (5/8 in.) in diameter by 1.27 cm (1/2 in.) long, were pressed to a density of about 1.7 g/cm³ for use in the firing tests of the vessels. The explosive was detonated using a RP-1^{††} electric bursting-bridge-wire detonator. The leads for the detonator were threaded through a 7/8-14 machine bolt with a 0.48-cm (3/16-in.)-diam hole through it and the bolt was used to close one end of the vessel. The test setup is shown in Fig. 4.

*The box shown in Fig. 1 was not made to DOT specifications. It was used for testing only.

**Graziano's Tariff, Bureau of Explosives.

†PBX 9404 is 94/3/3 wt% HMX/nitrocellulose/tris(B-chloroethyl)-phosphate.

††Sold by Reynolds Industries Inc., P. O. Box 1170, Marina Del Rey, California 90291.

The minimum weight of detonating explosive that caused failure of the test vessels was determined. The LD-1000 vessel failed with the detonation of a minimum of 26 g of PBX 9404; the LD-2500 vessel failed at a minimum of 40 g of the same explosive. The LD-1000 was rated acceptable for shipping 15 g of explosive; the LD-2500 vessel was rated acceptable for shipping 25 g of explosive.

The vessels were then tested with these explosive weight limits. After these tests, the vessels were sawed apart and examined to verify that the diameter and the wall thinning at the bulge were uniform, as shown in Figs. 5 and 6, and to verify that the calculated strains were less than published yield values.

The vessels were tested at ambient temperature only. Stainless steel does not exhibit any significant loss of ductility or strength at any of the temperatures the containers would encounter during transportation and handling. High temperatures, such as those in a fire, would decompose the explosive before any great strength loss in the container. The 7/8-14 port is not gas-tight, so gases would be vented before high internal pressures could occur.

IV. CONCLUSION

Group WX-2 has designed and tested shipping containers of two sizes that will ensure safety of the shipment of up to 15-g or 25-g samples of any high explosive. These containers can be used safely for any shipping classification of explosives. Therefore, the problems and costs in the shipment of small samples of explosives are greatly reduced.

Fig. 1. Cut Away View of Shipping Container and Box.

Fig. 3. Fifteen and Twenty-five Gram Shipping Container.

Fig. 4. Testing Configuration of Shipping Container.

Fig. 5. Shipping Container After Testing.

Fig. 6. Shipping Container After Testing.

Printed in the United States of America
 Available from
 National Technical Information Service
 US Department of Commerce
 5285 Port Royal Road
 Springfield, VA 22161
 Microfiche \$3.50 (A01)

Page Range	Domestic Price	NTIS Price Code	Page Range	Domestic Price	NTIS Price Code	Page Range	Domestic Price	NTIS Price Code	Page Range	Domestic Price	NTIS Price Code
001-025	\$ 5.00	A02	151-175	\$11.00	A08	301-325	\$17.00	A14	451-475	\$23.00	A20
026-050	6.00	A03	176-200	12.00	A09	326-350	18.00	A15	476-500	24.00	A21
051-075	7.00	A04	201-225	13.00	A10	351-375	19.00	A16	501-525	25.00	A22
076-100	8.00	A05	226-250	14.00	A11	376-400	20.00	A17	526-550	26.00	A23
101-125	9.00	A06	251-275	15.00	A12	401-425	21.00	A18	551-575	27.00	A24
126-150	10.00	A07	276-300	16.00	A13	426-450	22.00	A19	576-600	28.00	A25
									601-up	†	A99

† Add \$1.00 for each additional 25-page increment or portion thereof from 601 pages up.

Los Alamos