12
4-20-92 GSD

PNL-8028

UC-403

**Research, Development,
Demonstration, Testing, and
Evaluation Characterization
Technology Project FY90 Year-End
Report on Subsurface Detection
Methods**

**G. A. Sandness
T. L. Stewart**

March 1992

**Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute**

PNL-8028

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor Battelle Memorial Institute, nor any of their employees, makes **any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights.** Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or Battelle Memorial Institute. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

PACIFIC NORTHWEST LABORATORY
operated by
BATTELLE MEMORIAL INSTITUTE
for the
UNITED STATES DEPARTMENT OF ENERGY
under Contract DE-AC06-76RLO 1830

Printed in the United States of America

Available to DOE and DOE contractors from the
Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831;
prices available from (615) 576-8401. FTS 626-8401.

Available to the public from the National Technical Information Service,
U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

PNL--8028

DE92 011510

RESEARCH, DEVELOPMENT, DEMONSTRATION,
TESTING, AND EVALUATION CHARACTERIZATION
TECHNOLOGY PROJECT FY90 YEAR-END REPORT
ON SUBSURFACE DETECTION METHODS

G. A. Sandness
T. L. Stewart

March 1992

Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Richland, Washington 99352

MASTER

THIS IS A COPY OF THE DOCUMENT IS ORIGINALLY
JP

SUMMARY

In FY89, researchers at Pacific Northwest Laboratory^(a) constructed a digital data acquisition system (DAS) to be used in geophysical surveys of hazardous waste burial sites. The DAS is essentially a specialized micro-computer that has been ruggedized to permit operation on a moving off-road vehicle. It was designed primarily to record and display ground-penetrating radar (GPR) data, but it is capable of simultaneously or separately recording data produced by other types of geophysical sensors. Our work in FY90 focused primarily on improving certain hardware components of the DAS and on writing the software needed to process and display the recorded data on a personal computer (PC)-based data processing system.

The hardware improvements included installing a ramdisk, a liquid crystal display and controller, and a rugged hand-held keyboard. The ramdisk replaced a fixed Winchester disk that was initially installed as the system disk. The ramdisk provides improved resistance to shock and temperature extremes and reduces the electrical power requirements of the system. The display unit permits GPR data to be displayed in real time, either in bright daylight or in darkness. The keyboard is a weatherproof alphanumeric device that permits the system operator to input commands and parameter values to the DAS.

In the past, all of our GPR data processing and display operations were performed on a Digital Equipment Corporation (DEC) PDP or VAX computer system. The software developed during the past year permits those operations to be performed on a desktop PC, thereby gaining speed, efficiency, convenience, and reduced cost. Programs have been written to construct, edit, and display data descriptor files; to display the raw and processed GPR data in the form of grey-scale or color-coded video images; to perform various image enhancement and data manipulation operations; and to make hard-copy gray-scale images on film or paper.

(a) Pacific Northwest Laboratory is operated for the U.S. Department of Energy by Battelle Memorial Institute.

A secondary aspect of our work during the past year was constructing and testing a breadboard version of a time-domain metal detector. Metal detectors are commonly used in site characterization surveys to detect and map metallic wastes such as 55-gal drums, storage tanks, pipes, and cables. However, currently available instruments tend to be unstable, difficult to use, and generally unsuitable for quantitative site characterization measurements. The particular device that we investigated uses rapidly switched currents to induce transient magnetic signals. These signals contain potentially usable information about the size, shape, and location of buried conductive objects. In its fully developed form, this sensor is intended to function much like a GPR system, using digital data recording and data processing to provide improved sensitivity and a quantitative target recognition capability. As an initial test of this concept, we interfaced the breadboard sensor to our GPR DAS and digitally recorded signals produced by various metallic targets. The data were then processed by the software described above. The resulting transient-decay functions for the various targets showed substantial differences that might be exploited by an operational, digital, target detection/recognition system.

CONTENTS

SUMMARY	iii
1.0 INTRODUCTION	1.1
1.1 BACKGROUND	1.1
1.2 TASK OBJECTIVES	1.2
1.3 ORGANIZATION OF REPORT	1.4
2.0 DATA ACQUISITION SYSTEM	2.1
2.1 OVERVIEW OF THE SYSTEM	2.1
2.2 HARDWARE IMPROVEMENTS	2.1
2.2.1 Display Unit	2.1
2.2.2 Ramdisk	2.2
2.2.3 Keyboard	2.3
2.2.4 Other Hardware Modifications	2.3
3.0 SOFTWARE	3.1
3.1 DATA PROCESSING/DISPLAY ENVIRONMENT	3.1
3.2 PROGRAM REL -- R(adar) E(diting) and L(isting)	3.2
3.3 PROGRAM DR -- D(isplay) R(aw data)	3.7
3.4 PROGRAM PROCESS	3.8
3.5 PROGRAM DP -- D(isplay) P(rocessed data)	3.8
3.6 PROGRAM HC -- H(ard)C(opy)	3.9
4.0 METAL DETECTOR	4.1
4.1 DISCUSSION	4.1
4.2 APPROACH	4.2
4.3 SYSTEM DESIGN	4.4
4.3.1 Coils	4.4

4.3.2	Circuits	4.5
4.4	TEST RESULTS	4.7
5.0	CONCLUSIONS AND RECOMMENDATIONS	5.1
5.1	GROUND-PENETRATING RADAR	5.1
5.2	TIME-DOMAIN METAL DETECTOR	5.2
5.3	RECOMMENDATIONS	5.3
6.0	REFERENCES	6.1

FIGURES

3.1	Major Hardware Components for Collecting and Processing Ground-Penetrating Radar	3.1
3.2	Listing of the First Part of a Data Descriptor File	3.5
3.3	Partial Listing of the Second Part of the Sample Data Descriptor Files	3.6
3.4	Example of a Data Listing on the Monitor Screen	3.7
3.5	Photograph of the Monitor Screen Showing 15 Processed Ground-Penetrating Radar Profiles	3.10
3.6	Slightly Reduced Photograph of a Hard-Copy Print Produced by the Laser Image Recorder	3.11
4.1	Transmitter Coil Current and Induced Transient Voltages in a Time-Domain Metal Detector	4.3
4.2	Configuration of the Metal Detector Coils	4.5
4.3	Sensor Response as a Function of Target Position Relative to the Center of the Transmitter Coil	4.6
4.4	Metal Detector Transmitter Circuit	4.7
4.5	Metal Detector Receiver Circuit	4.8
4.6	Sensor Result as a Function of Time for Nine Target Locations Relative to the Center of the Transmitter Coil	4.9
4.7	Normalized Signal Amplitudes as a Function of Time for Four Targets of Different Sizes and Shapes	4.10

1.0 INTRODUCTION

1.1 BACKGROUND

Most of the site cleanup projects to be conducted at U.S. Department of Energy (DOE) facilities will include subsurface investigations using geophysical sensors. The purpose of these investigations is to detect, map, and characterize buried waste materials, waste-related structures, and natural stratigraphic features. When performed at an early stage of a site characterization effort, they will help define site boundaries and waste distributions, provide guidance for the optimization of subsurface sampling plans, reduce the cost of site exploration tasks, and enhance the safety of personnel involved in sampling and excavation activities.

The surface-based geophysical sensing methods that are generally accepted as being most effective in this type of application are ground-penetrating radar, magnetometry, metal detection, acoustics, and ground conductivity measurements by electromagnetic induction methods. Each of these sensing methods has proven to be a useful tool for subsurface investigations at some waste burial sites, but each exhibits technical deficiencies that reduce its effectiveness or prevent its use at certain sites. This task is intended to address some of those deficiencies and to lead to the development of improved instruments, software, and subsurface sensing methods. Work under this task in FY88 focused on the development of an acoustic imaging system, including a vacuum-ram thumper, a computer-controlled data acquisition system, and associated software. Work in FY89 primarily involved the development of an improved digital data acquisition system (DAS) for ground-penetrating radar (GPR) and other types of geophysical measurements. The main part of our work during FY90 involved enhancements of the hardware components of the DAS as well as the development of the software needed to process data recorded by the DAS. A secondary aspect of the FY90 work was the construction and initial testing of a prototype time-domain metal detector.

A key factor in achieving a high level of quality and interpretability in geophysical site characterization surveys is the use of digital methods of data collection, data processing, and image display. The initial requirement

is the ability to record survey data in a digital form. The DAS that was constructed in FY89 was designed primarily to record GPR data, although it is also capable of recording data from other types of sensors. It represents the third generation in a series of digital data recording systems that have been constructed and used by the Pacific Northwest Laboratory (PNL). The earlier versions of this system have been used in many subsurface site investigations at Hanford and elsewhere since 1975. The data recorded by those devices have been routinely processed, enhanced, and displayed with the aid of computers and graphics devices such as video monitors, film recorders, and plotters. The efficiency, versatility, and power of this approach have become widely recognized; as a result, analog data recording and hand operations in producing hard-copy products are rapidly becoming obsolete.

Most of the work performed under this task has focused on the GPR method, which is the most powerful sensing method currently available for the investigation of hazardous waste burial sites. Its principal advantage over any other available subsurface sensing method is that it provides a quasi-victorial image of buried waste materials, waste burial structures (e.g., trenches, pits, and cribs), and natural geologic features. When displayed as amplitude-modulated profiles (images showing vertical cross-sectional views of the subsurface), in either gray-scale or color-coded form, the GPR data can be visually examined and readily interpreted with a high degree of accuracy. In earlier work at PNL, we demonstrated that computer-generated maps showing the areal distribution of buried waste materials can also be an effective means of displaying and interpreting GPR data at many sites.

1.2 TASK OBJECTIVES

The design objectives that were addressed in the design of the DAS in FY89 were

- to ensure that the device could be interfaced with our current GPR units (Geophysical Survey Systems, Inc., Models SIR 7 and 8)
- to allow for interfacing other digital and analog sensing devices
- to provide a real-time data display capability

- to provide an efficient means of transporting data to laboratory computers for processing and display
- to achieve a high degree of operational reliability
- to ensure that the new DAS would have sufficient sampling speed and computational capability to be compatible with a proposed improved radar unit. The latter would require two input channels and a data sampling rate approximately 100 times greater than that needed for available radar units.

Most of these objectives were met in FY89; however, follow-on work was needed to improve certain aspects of the hardware and to provide the software needed to make the DAS fully operational. Therefore, the following DAS-related objectives were defined for FY90:

- to enhance the real-time data display capability
- to improve the ruggedness of the system
- to write software to edit, process, and display the digital data provided by the DAS.

A major part of the software development effort involved rewriting programs that were originally written for DEC (Digital Equipment Corporation) PDP- and VAX-class minicomputers. The objective was to move all data processing and display operations from those machines to personal microcomputers (PCs). The benefits gained are improved ease of use (user friendliness), greater flexibility in computations and data manipulation, reduced costs, faster turnaround of output products, and easier access to data processing and display equipment.

A final objective for FY90, made possible by a supplement to the original funding, was the construction of a prototype, digital, time-domain metal detector. In comparison to the types of metal detectors used to date for waste site characterization surveys, this device offers potential improvements in mechanical and electronic stability, target identification capability, ease of use, and cost effectiveness.

1.3 ORGANIZATION OF REPORT

In the remainder of this report, Section 2.0 describes the DAS hardware and Section 3.0 discusses the software. The metal detector design and test results are discussed in Section 4.0. Section 5.0 presents recommendations and conclusions.

2.0 DATA ACQUISITION SYSTEM

2.1 OVERVIEW OF THE SYSTEM

The principal component of the DAS is a compact, rugged, special-purpose computer, incorporating state-of-the-art components for high-speed data conversion, display, and storage. The central processing unit (CPU) is an Intel 80386 microprocessor and is IBM PC/AT-compatible.

The hardware unit was designed to be mounted on a small all-terrain vehicle (ATV). Its electrical power consumption is less than 200 W, so it can be powered by 24-V batteries or by a small DC generator mounted on the ATV.

Ruggedized, portable, hard disks provide fast internal read/write capability as well as a mechanism for fast, reliable transfer of the recorded data to an external computer system. The software components of the DAS reside on an internal system disk and provide turnkey operation of the system. A small, real-time, graphics display unit was planned to be mounted on the ATV to allow the operator to monitor the operation of the radar system, but could not be implemented in FY89 because of the unavailability of a suitable display device and a PC/AT-compatible interface.

A set of switches mounted on the handlebars of the ATV enable the system operator to control the data collection process. A small removable keyboard was planned as the primary user interface for the system, but was not acquired in FY89. The keyboard will allow the operator to alter operational parameters, enter file names, and interact with the system when it is not collecting data.

2.2 HARDWARE IMPROVEMENTS

2.2.1 Display Unit

Several graphics display devices were tested to identify products that fit the specific needs of the system. The main problem was to determine the type of display that would be most visible in sunlight. Our expectation was that a reflective or transreflective liquid crystal display (LCD) device would be most readable. This was confirmed by tests of monochrome and color cathode

ray tubes (CRTs), a Finlux Model 640.350 (EGA) electroluminescent display, a Sharp Model LM64148Z transmissive-mode LCD, and an AND Model 1013 transfective-mode LCD. The last of these devices was the only one that proved to be acceptable. In addition to being unreadable in sunlight, the electroluminescent display exhibited a streaking problem on nonilluminated areas of the screen. The transmissive-mode LCD display, with cold-cathode backlighting, worked well indoors, but also washed out in sunlight.

An Epson Model EG9002B-FS transfective LCD module was ordered. This is a gray-scale, (VGA)-compatible device that provides 640- x 480-pixel resolution. Unfortunately, in spite of the vendor's promise of delivery in August, this device was not delivered in time to permit its installation during the past fiscal year. To drive the display, we purchased a Yamaha Model YDM6448 interface board. This unit, which became available at mid-year, can interface to a wide variety of output devices, including the Epson unit that we plan to use.

2.2.2 Ramdisk

The collection of data in field surveys involves mechanical shock, vibration, and temperature extremes on the equipment. These conditions are potentially damaging to rotating disk drives, even if they are ruggedized. Solid-state memory, configured as a ramdisk, has greater tolerance to these factors. In addition, a (CMOS) ramdisk requires less electrical power than a mechanical disk drive. The main drawback to the total use of ramdisks in the DAS (as system disk and as removable data storage) is that they are much more expensive than rotary disks, even for a much smaller data storage capacity. Our approach, therefore, was to improve the overall ruggedness of the DAS by installing a 3-Mbyte Texas Microsystems Model SSWD5.0 ramdisk as the system disk, while retaining the ruggedized 20-Mbyte Winchester disks as the removable bulk data storage media. The ramdisk, configured as a plug-in board on the PC/AT bus, initially exhibited compatibility problems with the CPU. However the manufacturer of the CPU solved the problem by replacing the original Award BIOS with a Phoenix BIOS on the CPU card. In field use over the past several months, the system has performed very reliably.

2.2.3 Keyboard

As mentioned above, the primary user interface device for the DAS is a small, weatherproof, hand-held terminal. We had hoped to locate a unit that could be plugged directly into a standard PC keyboard port, but we were not able to do so. A Two Technologies Model 8045R2-1BLNL terminal provides the necessary input/output (I/O) functions via an RS-232 port and has proven to be sufficiently durable for field use. It is interfaced to the CPU via a Vetra Systems Model VIP-331-SBAT-A-NRE converter that links the RS-232 output of the terminal to the PC keyboard port.

2.2.4 Other Hardware Modifications

A Tanaka Model QEG-250D DC generator was modified and mounted on the front of our field survey vehicle. The generator was rewound to convert its output from 12 V to 28 V. The latter is the nominal input voltage required by the DC-DC converters that power the DAS and the radar unit. In addition, the generator's original 1-quart gas tank was replaced by a 2.8-gal tank. This modification permits the generator to run at least 20 hr without refueling.

A cover-protected main power switch was installed. This switch allows the system operator to start the generator without having the DAS active. The cover prevents accidental system shutdown during operation.

3.0 SOFTWARE

3.1 DATA PROCESSING/DISPLAY ENVIRONMENT

Figure 3.1 is a block diagram that illustrates the major hardware components that are used to collect and analyze geophysical survey data. Analog GPR waveforms and digital footage counter data are the primary inputs to the DAS in our survey mode. The footage counter provides a digital record of the location of the sensor in the direction of the survey line. A second digital input port has been provided in the DAS for a digital magnetometer. Alternative sensors that produce analog output signals (e.g., certain magnetometers and metal detectors) can be interfaced to the DAS via one or both channels of the two-channel GPR port.

The data recorded by the DAS are transferred to our microcomputer-based data processing system via a removable hard disk as described above. The

FIGURE 3.1. Major Hardware Components for Collecting and Processing Ground-Penetrating Radar

microcomputer, a Compaq Deskpro 386/33, contains an interface board that allows the portable disk to be accessed in the normal manner (drive D:).

A Pixelworks Model UA1280 high-resolution (1280 x 1024) video graphics board permits data to be displayed on the system's CRT monitor at any time during the data analysis process. The monitor is a Mitsubishi Model HL6905 with (RGB) inputs.

Hard-copy displays of GPR profiles are produced by means of a Laser-metrics Model 300D laser printer. This unit produces 256-level gray-scale images on paper or film at a resolution of 300 pixels/inch.

The data processing system includes three significant components that are not shown in Figure 3.1. The first two, a Hewlett-Packard Deskjet Plus printer and a Hewlett-Packard Draftmaster II plotter, are used to produce hard-copy listings, graphs, site maps, and line drawings. The third, a Qualstar Model 1260 9-track tape drive, is used for long-term data storage and hard-disk backup.

Software development efforts during the past year resulted in a set of computer programs that permit GPR data to be edited, processed, and displayed by the hardware components described above. These programs are briefly described below. The first three of these programs were written in Borland Turbo C; the fourth was written in Microsoft C.

3.2 PROGRAM REL -- R(adar) E(diting) and L(isting)

The GPR data recorded by the DAS are contained in one or more binary disk files. Each of these files corresponds to a single survey line and contains a number of GPR scans. Each scan is a 1- to 512-element time series representing a signal that has been backscattered from subsurface objects. The number of scans contained in the file is determined by the length of the survey line, the speed at which the survey line is traversed, the scan rate of the radar unit, and the number of scans that are averaged by the DAS. For example, if the line length = 200 ft, if the traverse speed = 4 ft/s, if the

radar scan rate = 50 scans/s, and if 4 scans are averaged by the DAS to produce each output (recorded) scan, the data file will contain 625 scans or data records.

Files intended to be processed as a group are identified by a common base name or data set name. Each file in the set is identified by a unique three-digit file number that is appended to the base name as a standard MS-DOS file extension. For example,

DATASET1.001

DATASET1.002

|

|

DATASET1.00N

is a list of data file names that denotes a data set consisting of files 1 to N. (Note, however, that this program does not require an unbroken sequence of file numbers.)

The first record in each file is a file header that contains information about the data. The rest of the records contain the radar data. Each digital amplitude value is represented by a byte (an 8-bit binary number). Eight bytes at the end of each record are reserved for footage counter data and for data produced by another sensor (e.g., a magnetometer).

The purpose of this program is to perform four functions that need to be performed at the beginning of the data analysis process. A summary of these functions is as follows:

1. Read and display the file descriptor information (header records) for all of the raw data files that are associated with the specified data set and that are present on the data disk.
2. Combine the descriptive information that was read from the data files with additional information that is input by the operator via a screen editing routine. Create two data descriptor files (DDFs) and write them to the data disk. These files are identical in their information content, but different in format. The first is a binary copy of the data structures that contain the descriptive information in the computer's memory. This file is read and utilized by all of the other programs that process or display data from the current data set. The second DDF

is an ASCII text file. It is used only to transfer information about the GPR survey to the Hanford Environmental Information System (HEIS) data base.

The name of the binary DDF is formed by appending the extension '.DDF' to the data set name. The name of the ASCII DDF is created by adding the extension '.HIS' to the data set name (to indicate that it is the HEIS-compatible version).

3. Print the information contained in the DDFs (i.e., make a hard-copy record). Each DDF consists of two parts. The first part contains information that pertains to all of the data files in the current data set. The second part consists of records that explicitly describe each of the data files (one record per file) in the set. Figures 3.2 and 3.3 are sample listings that illustrate the contents of the two parts of the DDF.

The column headings in Figure 3.3 are defined below:

SEQ	File sequence number.
FILE	File number.
TRK LOC	The Y coordinate of the survey line in a gridded survey area with an XY coordinate system. The direction of the survey line is defined to be parallel to the X axis.
BEGIN	The X coordinate of the starting point of the survey line.
END	The X coordinate of the end point of survey line.
LENGTH	The length of the survey line.
DIR	The N(ormal)/R(everse) direction of movement as the GPR sensor is moved along the survey line. The direction is normal if it corresponds to the defined orientation of the X axis. For example, if the X coordinate increases from south to north, the normal direction of movement is S-N.
SCANS	The number of scans in the data file.
STA	The status of the file: G = good, B = bad, P = processed, C = calibration file.
TIME, DATE ...	The time and date of data collection.
LOW, HI	Amplitude values representing display thresholds. These are derived from a histogram of the amplitudes of the data in the file.
COMMENT	A 50-character text string.

4. Display (list) data records on the monitor screen. This allows the operator to quickly examine the recorded data in numerical form. Figure 3.4 illustrates the appearance of the data on the screen.

```
-----  
Data Set: \TANK4\TANK4      178 Data/Scan      Time: 17:12  
          105 Files          8 Scans Avgd       Date: 10/23/1990  
-----
```

```
Site ..... 130-B-1  
Contractor ..... PNL  
Crew ..... GS TP  
Survey type ..... GP  
Sensor mfg/model(s) ... GSSI/3105P, 3102  
Serial number(s) ..... 033, 008 (antennas)  
Nominal frequency ..... 300, 500  
Transport mode ..... Manual  
Distance units ..... ft  
X-axis increment ..... 0.22222  
Track spacing ..... 2 ft  
Z-axis scale factor ....  $z=1.25+.259*(I-1)$  ft (300 MHz)  
Data units ..... na  
Data conversion factor . na  
Grid orientation ..... S-N, E-W  
Data set number ..... Tank4  
Record custodian ..... GA Sandness  
Record location ..... Rm 61, 2400 Stevens, PNL
```

FIGURE 3.2. Listing of the First Part of a Data Descriptor File

SFQ FILE	TRK I/C	BEGIN	END	LENGTH	DIR	SCANS	STA	TIME	DATE	LCW	HI	COMMENT
1 001	0 E	0	80	80	H	360	P	13:26	09/12/90	93	162	Start S H trks in SW corner of site.
2 002	2 E	0	80	80	R	360	P	13:28	09/12/90	87	163	
3 003	4 E	0	80	80	H	360	P	13:30	09/12/90	93	157	
4 004	6 E	0	80	80	R	360	P	13:32	09/12/90	90	171	
5 005	8 E	0	80	80	H	360	P	13:34	09/12/90	101	161	
6 006	10 E	0	80	80	R	360	P	13:36	09/12/90	93	164	
7 007	12 E	0	80	80	H	360	P	13:38	09/12/90	93	171	
8 008	14 E	0	80	80	R	360	P	13:39	09/12/90	83	181	
9 009	16 E	0	80	80	H	360	P	13:41	09/12/90	86	176	
10 010	18 E	0	80	80	R	360	P	13:42	09/12/90	86	172	
11 011	20 E	0	80	80	H	360	P	13:43	09/12/90	94	163	
12 012	22 E	0	80	80	R	360	P	13:45	09/12/90	97	160	
13 013	24 E	0	80	80	H	360	P	13:46	09/12/90	99	165	
14 014	26 E	0	80	80	R	360	P	13:47	09/12/90	79	170	
15 015	28 E	0	80	80	H	360	P	13:49	09/12/90	92	166	
16 016	30 E	0	80	80	R	360	P	13:50	09/12/90	96	161	
17 017	32 E	0	80	80	H	360	P	13:51	09/12/90	99	162	
18 018	34 E	0	80	80	R	360	P	13:53	09/12/90	99	159	
19 019	36 E	0	80	80	H	360	P	13:54	09/12/90	101	155	
20 020	38 E	0	80	80	R	360	P	13:56	09/12/90	90	174	
21 021	40 E	0	80	80	H	360	P	13:58	09/12/90	88	173	
22 022	42 E	0	80	80	R	360	P	13:59	09/12/90	94	168	
23 023	44 E	0	80	80	H	360	P	14:00	09/12/90	91	169	
24 024	46 E	0	80	80	R	360	P	14:02	09/12/90	98	158	
25 025	48 E	0	80	80	H	360	P	14:04	09/12/90	97	160	
26 026	50 E	0	80	80	R	360	P	14:10	09/12/90	100	155	
27 027	52 E	0	80	80	H	360	P	14:11	09/12/90	97	161	
28 028	54 E	0	80	80	R	360	P	14:13	09/12/90	98	157	
29 029	56 E	0	80	80	H	360	P	14:14	09/12/90	98	157	
30 030	58 E	0	80	80	R	360	P	14:15	09/12/90	103	151	
31 031	60 E	0	80	80	R	347	R	16:09	09/12/90	0	255	Switch problem.
32 032	60 E	0	80	80	H	7	R	14:18	09/12/90	0	255	
33 033	60 E	0	80	80	H	360	P	14:20	09/12/90	103	152	
34 034	62 E	0	80	80	R	360	P	14:21	09/12/90	102	153	
35 035	64 E	0	80	80	H	360	P	14:22	09/12/90	104	150	

FIGURE 3.3. Partial Listing of the Second Part of the Sample Data Descriptor Files

```

\TANK5\TANK5
SEQ FILE   TRK LOC   BEGIN   END   LENGTH DIR SCANS STA   TIME   Data Type: GP
-----
  4   004           6 E       0     60     60  R   371   :  11:07  09/14/90

```

```

Scan No.  12
  2    -1    -1    -8     2     8    59     6     2     5    13     9    -4
-16     4    17    12     9    35    -4    -22    -8    -17   -25     0   -15
-24   -11     3    28    27     4     0     0     6    -16   -24   -25   -25
 22    38    19    -2     1    -8   -51   -57   -46   -25    31    71    34
-29   -54    11     6     1    19    32   -28   -27   -25    54    24   -11
  -8     0   -19    24    23    18   -45    12    12   -24     6    31   -40
-31    40    34    -7    10   -14   -47    -2     0   -22    27    -2   -63
-35     2    12    29    69    65    48    33    11   -31   -30   -22    -6
-17    19    28    -5   -14    23    17   -32     2    20   -29   -13     5
-37   -13    11   -10    11    20     3   -28     5    11    -1    18    20
-14    14    30     7     4    30    30     3    12    -1   -11     5    -2
-12   -16     6     8     0    18     7    -2    -2    11   -14   -12     1
  6   -13    -3     4    13    13     5    -9    10    10     0    -2     6
  5   -4     6     4    -1     1     0     8     2
Scan No.  13
  1    -1     0    -7     2     7    58     5     0     4    17    21     0
-22

```

Press ESC to quit, any other key to continue.

FIGURE 3.4. Example of a Data Listing on the Monitor Screen. The data are scrolled upward across the screen. The scrolling can be interrupted by pressing any key.

3.3 PROGRAM DR -- D(isplay) R(aw data)

This program displays the raw GPR profiles on the high-resolution graphics monitor. Given the name of a data set and the numbers of the data files to be displayed, it searches for and reads the appropriate DDF from the data disk. Using the information provided in the DDF, it then displays the specified files in the form of color-coded or gray-scale-coded profiles. The DDF provides values for the number of scans in each data file and the number of data in each scan. The program uses these values to calculate the location of each profile on the video screen. The profiles are displayed sequentially in one or more columns; the number of columns depends on the number and lengths of the profiles.

3.4 PROGRAM PROCESS

This program reads the DDF and a specified sequence of raw data files from a specified data set. It performs several data processing operations on those data files, then writes the processed data files and an updated DDF to an output disk drive and directory. The following operations are performed on each input data file:

1. Adjust the length of the data file by linear interpolation. The number of scans in the output file is equal to the desired number of scans per unit length times the length of the survey line.
2. Construct a histogram of the amplitude values in the processed data file, then calculate upper and lower amplitude thresholds. The threshold values are used later to adjust the contrast of video and hard-copy displays of the processed data files.
3. Remove unchanging signal components. These are a form of clutter that result from internal and external reflections of the transmitted radar signal. They remain constant as the radar unit moves across the ground and are thus superimposed on the signals of interest and expressed as horizontal stripes in the raw data profiles. They can be effectively removed by any one of several filtering procedures. The procedure that is currently used by this program is a two-step process that is applied to each data row in the data file (the number of rows in a data file is the number of data per scan; each row corresponds to a small increment of depth or signal travel time). The first step is to find the amplitude value that occurs most often in a given data row. The second step is to subtract that value from each datum in the row.
4. Reverse the scan order in data files that were recorded while the radar unit was being moved in the "reverse" direction along the survey line (see the explanation of the DDF column label 'DIR' in the list of definitions for Figure 3.3).
5. Rearrange the data in the output data file so the data can be written to disk as a sequence of rows rather than as the original sequence of scans. This rearrangement of data is done to facilitate the later transmission of data to the Lasermetrics hard-copy printer (the printer buffer stores the data as rows or columns rather than as scans).

3.5 PROGRAM DP -- D(isplay) P(rocessed data)

This program is identical to Program DR except that it reads and displays processed data files (i.e., files written to disk by Program PROCESS). Figure 3.5 is a photograph of the monitor screen showing 15 processed GPR

profiles. Any of the five program options shown at the bottom of the screen (Toggle Color/BW, New Tracks, New Data Set, New Thresholds, and Exit) can be selected.

3.6 PROGRAM HC -- H(ard)C(opy)

This program reads selected processed data files and transfers them to the Lasermetrics laser printer via a (GPIB) interface. As in Programs DR and DP, the profiles are arranged in columns on the paper or film page. This vertical alignment of sequential profiles permits reflection patterns to be easily traced from one profile to the next, thereby facilitating the interpretation of the data set. Some of the additional features of this program are as follows:

- a text line can be written at the top of the image page to label and describe the picture
- an interactive routine allows the operator to construct a depth-dependent gain function that enhances the contrast of the gray-scale images
- vertical and horizontal expansion factors can be specified to increase the size of the profiles on the image page.

Figure 3.6 is a reduced-size example of a hard-copy print produced by the laser printer. The original image was printed on standard 8.5- x 11-in. paper. The hyperbolic reflection patterns in the first 15 profiles show the locations of three large underground fuel tanks.

FIGURE 3.5. Photograph of the Monitor Screen Showing 15 Processed Ground-Penetrating Radar Profiles

FIGURE 3.6. Slightly Reduced Photograph of a Hard-Copy Print
Produced by the Laser Image Recorder

4.0 METAL DETECTOR

4.1 DISCUSSION

A metal detector is an electromagnetic induction sensor designed for relatively short-range detection of highly conductive objects or materials. Devices of this general type have been developed to detect many types of targets, including concealed weapons, rebar and electrical conduits in concrete, metallic objects in conveyor belt streams of coal, and a wide variety of objects that might be buried in the ground. The development of instruments for detecting buried targets has been inspired largely by objectives such as military mine detection, treasure hunting, and tracing underground utilities (pipes and cables). The recent need to detect buried waste materials at hazardous waste burial sites has, for the most part, been addressed by pressing existing pipe and coin detectors into service.

Waste site characterization investigations are often initiated by performing a rapid reconnaissance of the site with the aid of a metal detector. A few traverses of a site with a hand-held instrument will often yield the approximate locations of major deposits of waste materials. This information can be helpful in optimizing a plan for subsequent detailed surveys that might involve a more intensive metal detector survey as well as other geophysical survey methods. A detailed metal detector survey can help define the boundaries of the major deposits (trenches, pits, etc.) and locate secondary waste deposits. A more extensive summary of the capabilities of currently available metal detectors in site characterization applications follows:

- often effective in reconnaissance surveys at sites which contain metallic waste materials
- can detect large metallic bodies at depths of 2 to 6 m and individual 55-gal drums at depths of 1 to 3 m at most sites
- can often define the boundaries of metallic waste deposits (e.g., 55-gal drums) to an accuracy of ± 0.5 m
- can detect and trace pipes and cables which may constitute sources of contamination, pathways for the migration of contaminants, or hazards to drilling and excavation.

A summary of the limitations of currently available metal detectors follows:

- commercially available instruments produce analog output which must be interpreted by the operator
- the data are, at best, only semiquantitative
- the useful sensitivity of existing sensors is limited by sensitivity to surface debris, by mechanical and electronic instabilities, and by an inability to compensate for variations in the electrical conductivity of the ground
- detailed surveys of large sites are prohibitively time-consuming and costly unless towed or vehicle-mounted sensors are used
- instruments designed specifically for waste site characterization are not widely available and, to the best of our knowledge, still exhibit some of the deficiencies that limit the performance of the more common commercial instruments.

Cleanup activities at U.S. Department of Energy (DOE) facilities would benefit from the availability of an improved metal detector designed specifically for fast, large-scale surveys of hazardous waste burial sites. This device should be vehicle- or wheel-mounted to permit the use of relatively large coils (for detection of deep targets), to permit a high rate of areal coverage, and to facilitate the use of automated data recording. It should also collect, process, and record data in digital form, have target recognition capabilities, and be able to measure and compensate for variations in soil conductivity. The data should be digitally recorded and formatted in such a way that it can be processed, analyzed, and displayed by methods similar to those used for magnetic or GPR data.

4.2 APPROACH

A metal detector uses one or more transmitter coils to generate a time-varying magnetic field. This field induces eddy currents in nearby electrically conductive materials that, in turn, produce secondary magnetic fields that can be detected by a receiver circuit. Many coil configurations and sensing modes are possible (Bakmutskii 1970). Most commercial metal detectors transmit a continuous-wave, or oscillatory, magnetic field. They detect

the presence of a conductive object by means of a receiver that is sensitive to a change in the impedance or resonant frequency of a coil, to an induced voltage in a coil, or to the perturbation of a null in the coupling between the transmitter and receiver coils.

An alternative approach, illustrated in Figure 4.1, is to transmit magnetic fields that have the form of a square wave or a step function in the time domain. In this approach, eddy currents are produced in a conductive body during each transition period when the intensity of the primary magnetic

FIGURE 4.1. Transmitter Coil Current and Induced Transient Voltages in a Time-Domain Metal Detector

field is increasing or decreasing. The eddy currents, and the secondary magnetic fields that they produce, decay at a rate that depends on the conductivity, size, and shape of the conductive body (Corbyn 1980; Bridges ca 1983; Das et al. 1985; NASA 1988). Thus, a time-domain metal detector offers the possibility of at least rudimentary target characterization. In addition, the decay time constants of the transient signals to be expected from typical waste-related targets are in the microsecond to millisecond range. Thus, with a simple adjustment of the sample rate, they can be recorded by the DAS in the same way that GPR signals are recorded. Further, once recorded, they can be processed, at least in part, by the software described in Section 3.0.

It seems feasible to design a time-domain metal detector that could be operated like a GPR system in the field and that would produce data that would be amenable to digital data analysis. Therefore, we constructed a breadboard instrument that allowed us to test the basic concept.

4.3 SYSTEM DESIGN

4.3.1 Coils

Figure 4.2 illustrates the configuration of the transmitter and receiver coils. The transmitter coil has 6 turns and is wound around the periphery of a 30- x 20-in. sheet of plywood. The receiver coil has 10 turns and is wound around a set of dowels that are inset 0.5 in. from the edges of the plywood. The time constant (the ratio of inductance to resistance) of each coil is less than 5 μ s. The figure-eight pattern of the receiver coil eliminates (for the most part) the high-voltage transient that would be induced in a simple rectangular receiver coil when the current in the transmitter coil is switched on and off. However, as illustrated in Figure 4.3, this configuration produces a bipolar signal as the coils are moved across a small target. The X-Y location of the target corresponds to the location of the zero crossing of the received signal rather than to a well-defined peak or null.

FIGURE 4.3. Sensor Response (arbitrary units) as a Function of Target Position Relative to the Center of the Transmitter Coil

pulse at the input of the first LF357 amplifier stage. (Although the switching transient is largely canceled by the figure-eight coil pattern, a residual pulse with an amplitude of a few volts is produced at the output terminals of the receiver coil due to a slight asymmetry in the coil.) The pulse amplitude is further clipped by a second resistor/diode limiter at the output of the first amplifier stage. In a more sophisticated circuit, the second limiter, at least, would probably be replaced by an analog switch or time gate.

FIGURE 4.4. Metal Detector Transmitter Circuit

4.4 TEST RESULTS

The sensor was tested in the laboratory. Its sensitivity and its response to targets of different shapes and sizes were tested by moving the targets across the sensor at several fixed distances. This procedure did not allow us to measure the effects of soil conductivity, but calculations based on the analytical methods of Corbyn (1980) indicated that those effects would be small. The decay time constant associated with the worst-case Hanford soil would be less than 5 μ s; i.e., at least 10 times shorter than the time constants of most of the targets to be tested.

The output of the metal detector's receiver and the sync output of the transmitter were connected to the GPR input port of the DAS. One scan, consisting of 64 digital amplitude values, was recorded during each cycle of the

FIGURE 4.6. Sensor Response (arbitrary units) as a Function of Time for Nine Target Locations Relative to the Center of the Transmitter Coil

were varied in accordance with the sizes of the targets to ensure that the received signals would be of reasonable amplitude. The peak amplitudes of the plotted curves have been normalized to facilitate a comparison of the shapes, or time-dependent characteristics, of the signals. The actual peak amplitudes, relative to the peak amplitude of the box cover, were:

Target	Depth	Amplitude
12 in. x 24 in. x 4 in. Box cover	18 in.	1.00
20 in. x 30 in. Garbage can	30 in.	0.81
7 in. dia x 0.75 in. Steel disk	12 in.	0.30
2.5 in. x 2.5 in. x 0.25 in. Ferrite plate	8 in.	0.06

FIGURE 4.7. Normalized Signal Amplitudes as a Function of Time for Four Targets of Different Sizes and Shapes

The curves plotted in Figure 4.7 differ markedly in shape as well as in amplitude. This suggests that the time-domain signals produced by this sensor might be interpretable in terms of target characteristics such as size and shape. However, these results represent only a preliminary investigation of the response of the sensor to the wide range of targets that might be of interest in site characterization surveys. Additional experimental and

analytical work is needed to determine the effects of target size, shape, and composition on the amplitude and shape of the transient signals.

The breadboard instrument was reasonably sensitive. It was able to detect a hacksaw blade at a distance of 2 ft and an 18-in. square metal plate at a distance of 6 ft. These distances can be extended by optimization of the coils and by further development of the electronic circuits. It is particularly important to increase the dynamic range of the receiver. This can be accomplished in part by further reducing the residual switching transient at the input of the receiver. Additional range can be gained by employing a logarithmic amplifier, an amplifier with time-varying gain, or a digital-to-analog feedback loop. The feedback loop would permit a selected fraction of the preceding scan to be subtracted from the current signal, thus allowing the receiver to be operated as a high-gain differential sensor.

5.0 CONCLUSIONS AND RECOMMENDATIONS

5.1 GROUND-PENETRATING RADAR

Although ground-penetrating radar is an inherently powerful and effective sensing method for a broad range of applications, the performance of currently available GPR systems has proven to be marginal or inadequate at many waste burial sites. The reason is that the spatial resolution and effective target detection depth of a GPR system are limited by rapid attenuation of the radar signals as they travel through the ground materials. The rate of attenuation varies greatly from site to site, depending on the amounts of moisture and clay minerals in the soil. At some DOE facilities (e.g., Idaho National Engineering Laboratory [INEL] and Oak Ridge National Laboratory [ORNL]), the attenuation rate is so high that the GPR method is almost completely ineffective. At other facilities (e.g., Hanford), useful data can be obtained from a depth of 6 to 7 m.

Many hazardous waste burial sites have been investigated by geophysical survey methods over the past decade. A large body of experience with the GPR method and with currently available GPR systems has been developed from those investigations. A significant outcome of that experience is the virtually unanimous view within the GPR user community that the task of cleaning up the nation's hazardous waste burial sites would benefit greatly from improvements in all aspects of GPR technology.

Most of the work performed under this Subsurface Detection Methods Task during the past 2 years has been directed toward meeting that need. Two significant steps have already been taken. The first step, largely completed in FY89, was the construction of a digital DAS that permits real-time video data display and that provides an efficient mode of data transfer to a PC-based data processing system. The second step, completed during the past fiscal year, provided the essential software components for processing and displaying the recorded GPR data and for making hard-copy graphical output products. In recent field surveys performed at Hanford by PNL, the DAS, the associated software, and the data processing system have provided significantly improved levels of efficiency and cost effectiveness.

The next major step in PNL's multiyear plan for the development of geophysical survey technology under this RDDT&E program is to construct an advanced GPR sensor (transmitter/receiver) system. The completion of this step will provide an operational GPR survey capability for DOE's site cleanup program that will far exceed today's standards in terms of efficiency, cost effectiveness, and the ability to detect and define buried waste materials.

Our design concept for an advanced GPR system has already been largely developed by previous work. It involves a system that can be constructed with a reasonable engineering effort, largely utilizing existing electronic equipment and techniques. The most innovative elements of this design concept involve the use of a microcomputer to directly control and optimize the operating parameters of the radar unit. This aspect of the design addresses the need to achieve a large dynamic range and to cope with a wide range of operating conditions.

5.2 TIME-DOMAIN METAL DETECTOR

The construction of an operational time-domain metal detector would be another significant step toward the achievement of an enhanced capability for geophysically characterizing DOE's hazardous waste burial sites. A system based on the concept that we have tested in breadboard form will have several advantages in comparison with the types of metal detectors that are currently available:

- Its electronic and mechanical design will permit it to be operated like a GPR system; i.e., mounted on a vehicle, towed by a vehicle, or pulled manually. This will dramatically reduce the time and manpower required to perform detailed metal detection surveys of large waste burial sites.
- The simple, rugged, mechanical design will require little or no field adjustment. This will eliminate the delays, sensitivity variations, and uncertainties associated with metal detectors that must be manually adjusted.
- The sensor can be interfaced to our digital DAS. This will allow real-time display of the along-track distribution of metallic waste materials. It will also make it possible to enhance, process, and display the data by means of a PC-based data processing system.

- The amplitude and shape of the transient signals received by the sensor seem to have a well-behaved dependence on the size, shape, and composition of the buried objects or materials. This offers the possibility of some degree of automated target recognition or characterization.

5.3 RECOMMENDATIONS

The work completed under this task during the past 2 years has resulted in products that are already being employed in field investigations at Hanford. The resulting gains in efficiency and cost effectiveness are significant benefits to DOE. Additional gains in speed, cost reduction, data quality, and personnel safety will result from the completion and deployment of the advanced GPR and metal detector sensors as outlined above. Under the proposed plan for continued work that PNL has submitted to the Office of Technology Development, these goals will be realized in a 2- to 3-year time frame. This schedule is reasonable in view of apparent funding limitations and is consistent with the long-term character of DOE's environmental restoration program. It should be mentioned, however, that the proposed sensors could be completed within 1 year, given adequate funding. This more aggressive approach would maximize the benefits to DOE from an operational point of view.

6.0 REFERENCES

Bakhmutskii, V. F. 1970. "Investigation of Induction Devices for Detecting Underground Communications." Document No. 49683, Joint Publication Research Service, Washington, D.C. Translation from Russian.

Bridges, J. E. ca 1983. "Backhoe Pipeline Damage Prevention by MIDDARS." Source unknown. Author at ITT Research Institute, Chicago, Illinois.

Corbyn, J. A. 1980. "Pulse Induction Metal Detector." Wireless World 86:40-44.

Das, Y., J. E. McFee, and R. H. Chesney. 1985. "Determination of Depth of Shallowly Buried Objects by Electromagnetic Induction." IEEE Transactions on Geoscience and Remote Sensing GE-23, No. 1:60-66.

NASA. 1988. "Multiple-coil, Pulse-Induction Metal Detector." NASA Tech Briefs September, pp 24-26.

DISTRIBUTION

No. of
Copies

No. of
Copies

OFFSITE

12 DOE/Office of Scientific and
Technical Information

D. Eastwood
Advanced Technology Project
Office
Lockheed Engineering and
Sciences Company
Environmental Programs Office
1050 E. Flamingo Road,
Suite 120
Las Vegas, NV 89119

J. Mathur
U.S. Department of Energy
DP-123 (GTN)
Washington, DC 20545

F. Wobber
U. S. Department of Energy
Office of Health and
Environmental Research
ER-75
Washington, DC 20545

N. E. Rothermich
Oak Ridge National Laboratory
HAZWRAP Support Contractor
Office
Oak Ridge, TN 37831

F. Fong
U.S. Department of Energy
San Francisco Operations
Wells Fargo Bank Building
1333 Broadway
Oakland, CA 94612

G. Coffey
E. I. duPont de Nemours and
Co.
Savannah River Plant
P.O. Box A
Aiken, SC 29808

ONSITE

5 DOE Richland Field Office

P. K. Clark, A5-21
R. E. Gerton, A4-02
J. M. Hennig, A5-21
G. W. Rosenwald, A4-02
K. M. Thompson, A5-19

5 Westinghouse Hanford Company

M. R. Adams, H4-55
J. W. Cammann, H4-14
L. C. Hulstrom, H4-55
A. G. Law, H4-56
S. J. Phillips, L4-26

34 Pacific Northwest Laboratory

J. C. Evans, K6-81
J. W. Falco, K6-78
T. J. Gilmore, K6-96
M. S. Hanson, K1-51
P. C. Hays, K6-86
P. E. Long, K6-84
S. P. Luttrell, K6-96
D. R. Newcomer, K6-96
K. B. Olsen, K6-81
R. G. Riley, K6-81

No. of
Copies

A. C. Rohay, K6-84
G. A. Sandness (10), K5-25
R. Schalla (2), K6-96
R. L. Skaggs, K6-77
R. M. Smith, B1-40
T. L. Stewart (2), K5-25
J. A. Stottlemire, K6-75
Publishing Coordination
Technical Report Files (5)

END

**DATE
FILMED**

5 / 29 / 92