DOE/PC/91281--T1

MAY 1 0 1992

LOW SEVERITY COAL LIQUEFACTION PROMOTED BY CYCLIC OLEFINS

DE-FG22-91PC 91281

DOE/PC/91281--T1

DE92 013789

Quarterly Report

October, 1991 to December, 1991

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Christine W. Curtis
Chemical Engineering Department
Auburn University, AL 36849

MASTER

REPRODUCTION OF THIS DOCUMENT IS UNLIMITED

EP

MAR 02 1992

ACKNOWLEDGEMENTS

The research of Madhu Perandurai and An Ping Huang is gratefully acknowledged.

TABLE OF CONTENTS

Introduction	1
Literature Review	1
Low Severity Coal Liquefaction Processing	1
Low Severity Liquefaction Reaction Products	7
References	9

INTRODUCTION

The objective of this project is to evaluate the efficacy of low severity coal liquefaction in the presence of highly reactive hydrogen donors, cyclic olefins. The work that was performed this quarter involved performing a literature search in which different aspects of low severity coal liquefaction were examined. In addition, two new master's graduate students learned the fundamental differences between high severity coal liquefaction and low severity coal liquefaction by examining the literature and reading texts on coal liquefaction.

The literature review presented for the first quarter's work is a compilation of the material which we have found to date involving low severity coal liquefaction. Additional review of low severity liquefaction literature is being conducted this quarter and will be reported in the next quarterly report. In addition, a summary of the work involving the reactivity of cyclic olefins in the absence and presence of coal will be presented next quarter.

LITERATURE REVIEW

Low Severity coal Liquefaction Processing. Incentives for evaluating low severity coal liquefaction as discussed by Miller et al (1988) include

- Reduction in hydrocarbon gas make and consequent reduction in hydrogen gas consumption.
- Enhanced distillate and residuum product quality because retrogressive reactions of the primary liquefaction products are lowered.
- Production of a higher quality residuum which is more easily upgraded.
- Utilization of less capital intensive reactors and processing equipment and lowered operating costs from less severe operating conditions.

Miller and coworkers (1988) hypothesized that basic nitrogen compounds which have been shown to be effective for dissolution in high severity coal liquefaction but detrimental because of adduction problems should be effective in low severity reactions. To test their hypothesis, Kentucky No. 9 bituminous and Wyodak subbituminous coals were used in low severity coal liquefaction reactions. A Cold Lake vacuum residuum was used as the coprocessing solvent. Seven different nitrogen compounds, 1,2,3,4-tetrahydroquinoline, dipropylamine, 7,8-benzoquinoline, piperidine, 4-piperidinopyridine, 6,6-benzoquinoline, and diphenylamine, were used as solvents. The low severity reaction conditions for reactions being performed in a 300 cm³ Autoclave batch reactor were reaction temperature of 344°C, feed gas of CO/H₂O, H₂ of an initial pressure of 850 psig and a maximum pressure of 1500 psig, reaction time at temperature of 30 minutes and a coal resid to nitrogen compound feed ratio of 1 to 1.5 to 0.5. For comparison, high severity reactions were performed at the conditions of 440°C and a hydrogen atmosphere of 1000 psig initial hydrogen pressure and a maximum pressure of 2000 psig.

Low severity coal liquefaction reactions with nitrogen showed enhanced coal conversion when 1,2,3,4-tetrahydroquinoline and dipropylamine were used as solvents. The other nitrogen compounds showed little effect as solvents. The yield of C₄-454°C liquids was enhanced by 1,2,3,4-tetrahydroquinoline and dipropylamine while the other five nitrogen compounds reduced the liquid yield somewhat. A direct correlation between coal conversion and liquid yield could not be developed.

Increased reaction severity affected coal conversion from the 1,2,3,4-tetrahydroquinoline reaction more than the dipropylamine reactions. The liquid yield was much more sensitive,

showing increased yields with the increased reaction severity. Increased adduction of the nitrogen compounds was observed at high severity.

Miller and Baldwin (1986) performed a series of low severity coprocessing reactions using Wyodak subbituminous coal and shale oil derived from medium grade Colorado oil shale. The reducing agent used was carbon monoxide and water. The reaction conditions employed were a reaction temperature of 600 to 650°C, initial carbon monoxide and water pressure at ambient of 1000 to 1500 psig and a reaction time of 15 to 16 minutes. Distilled water was added to the reactor at a level of 50 wt% of the dry feed. The parameters monitored to evaluate the effect of the processing were C₄-850°F distillate yield and conversion to pyridine solubles. For some reactions, the shale oil was prehydrotreated. The factors that influenced the monitored parameters most were the prehydrotreatment of the oil shale, lower reaction temperature and higher initial CO pressure. An enhancement of the product was observed where coprocessing of shale oil and coal was performed simultaneously rather than each one individually.

Research by Olson et al. (1988) evaluated the two-stage processing concept for low-rank coals that consisted of a relatively low-temperature reaction in the first stage followed by upgrading in the second stage. Catalytic hydrotreatment of a low severity first stage product from the liquefaction of Wyodak coal at 384°C in CO and H₂ using tetralin as a solvent was examined. The product was fractionated into a methylene chloride soluble fraction and a methylene chloride insoluble fraction. A second stage high severity liquefaction of the methylene chloride soluble fraction under various reaction conditions and tetralin as the solvent was evaluated. Two reaction temperatures of 425°C and 450°C were used for reaction of two

hours in length. The hydrogen pressure was varied but an equivalent amount of sulfided cobalt-molybdenum catalyst was used. Reactions were performed in tubing bomb reactors.

The product from the low severity liquefaction reaction was predominantly methylene chloride soluble. This material was composed of a high molecular weight pentane insoluble fraction that composed two-thirds of the material and a distillate oil fraction that composed one-third of the material. High severity reactions using this material converted it primarily into distillate oil. The authors postulated that the high molecular aromatics that were observed in the distillate from the high severity liquefaction reactions were a consequence of large polycondensed aromatics not being in the low severity product.

Stenberg and coworkers (1989) have used temperature programming as a methodology for achieving high conversions of Indian Head lignite. Temperature programs varied but times up to 60 minutes and temperatures up in the range of 300 to 350°C were used. The goal of the temperature programming was to match the rates of hydrogen release from the H₂S-H₂O solvent system with the rate of hydrogen uptake by the lignite as it starts to dissolve. Pyrrhotite and CO plus H₂ were also used as part of the liquefaction medium. The production of THF, toluene and cyclohexane soluble fractionated products was increased with temperature programming compared to liquefaction reactions performed for the same length of time for 350°C. The most effective temperature programs were developed by monitoring the reaction products by electron spin resonance, thermal gravimetric analysis, and differential scanning calorimetry.

The study performed by Chakrabraity (1985) evaluated methods for increasing the extractability of coal, particularly the carbon-hydrogen structured materials that compose the coal matrix. Solvolysis reactions of an Alberta subbituminous coal were performed in tetralin at

various temperatures ranging from 300 to 450°C and ambient pressure. In the second set of reactions, coal was swelled and then treated with phenol in the presence of p-toluene sulfonic acid. On the basis of the results from these experiments suggested that the surface reactions affected when reactions occurred and the yield and chemistry of the liquefaction reaction.

Research by Snape and coworkers (1991) has evaluated the effect of the organic structure and composition of coal on liquefaction behavior under low severity coal liquefaction conditions. Liquefaction reactions were performed with hydrogen donor and nondonor solvents. For the first set of reactions, a Lummus process-derived distillate with a boiling point range of 340 to 400°C and containing 91.1% C, 8.7% H and ~ 1% donable hydrogen was used as well as tetralin in short contact time (SCT) reactions of 10 minutes. The coals used in this part of the study were Wyodak subbituminous, Illinois No. 6 bituminous and Point of Ayr coal from the United Kingdom. The reaction were performed at 450°C without a hydrogen overpressure. The product work-up from the coal - Lummus solvent reactions used n-heptane and THF to fractionate the process distillate.

A second set of reactions was conducted with two UK coals, Linby and Point of Ayr with model donors and a nondonor at 400°C and reaction times up to 30 minutes to investigate their effect on the initial stages of coal dissolution. The model systems used were 9,10-dihydrophenanthrene, phenanthrene, pyrene, tetralin and naphthalene. Some coal/solvent slurries were presoaked at 250°C prior to reaction. The effect of extracting Linby coal with THF prior to liquefaction was also examined. After liquefaction reaction, the coal/solvent mixtures were extracted with pyridine or quinoline. The amount of hydrogen transferred from the hydroaromatic donors was determined.

The results from this work gave some surprising results. Pre-extraction of Linby coal with THF increased its conversion in the polynuclear aromatic (PNA) compound solvents. Snape et al (1991) suggested that the coal mobile phase limited accessibility to the PNA's. Once the mobile phase was removed, then the PNA's converted the low-rank coal better. Conversions of non-extracted Linby coal that had not been THF extracted were higher with naphthalene than with pyrene (PYR) or phenanthrene (PHEN) while conversions of extracted Linby coals were equivalent with naphthalene (NAP) and PYR. Tetralin (TET) and dihydrophenanthrene (DHP) gave higher THF-soluble yields of coal pre-extracted with THF than did the PNA's. Substantial improvement because of pre-extraction of SCT conversion with DHP was observed. The differences between the yields obtained with TET and DHP or even PYR and PHEN were attributed to the volatility of TET and, hence, lack of contact between TET and the coal. Since the process solvent achieved yields of THF-soluble materials increased with increasing rank, the authors concluded that solvents that provide good contact with the coal are essential for minimizing retrogressive reactions. DHP resulted in substantially more coal conversion than did TET which led the authors to also conclude that the cleavage of C-C bonds via hydrogen radical transfer occurred more in DHA than TET.

The effect of these low severity reactions on oil yields was also evaluated. Two sets of experiments were examined: (1) dry hydrogenation experiments at 400°C using a sulfided Mo catalyst and (2) solvent extraction experiments at 450°C. For both experimental conditions, the oil yields increased with decreasing rank. However, retrogressive reactions must be limited particularly in low-rank coals either by adding a catalyst or an effective hydrogen donor.

Low Severity Reaction Products. An investigation of the structure of the products from low severity coal liquefaction reactions was undertaken by Mastral and Cobolla (1985). The analyses of the low severity reaction products were performed using

- anisole, m-methylanisole and 1,3-dimethoxybenzene as solvents
- BF_3 , AlCl_3 , ZnCl_2 , SbCl_3 as catalysts
- Catalyst to lignite ratios of 1/1 and 4/1.

The products were analyzed by different methods; asphaltenes were analyzed by column adsorption chromatography using solvent elution chromatography. The characteristics of asphaltenes were determined by molecular weight determination, elemental analysis and spectroscopic analyses. Structural parameters of the oils were determined by $^1\text{H-NMR}$, $^{13}\text{C-NMR}$ and IR. The coal used in this study was a Spanish lignite from Utrillas.

The reaction products obtained by coal depolymerization were fractionated into oils and asphaltenes. The asphaltenes from the low severity reactions were further fractionated into an aromatic and two polar subfractions by column chromatography. High recovery of the asphaltenes was obtained. A strong similarity existed between the aromatics in the asphaltenes and those in the oils. The THF fractions from all of these reactions was the largest for all the processes used and also had the highest percentage of nitrogen compounds. Both a low degree of substitution and condensation can be postulated from the structural parameters obtained from the analysis of the products from low severity Utrillas lignite.

Moroni (1986) summarized recent work in low severity coal liquefaction and stated that the products obtained from low severity reactions were different from those from high severity reactions. The low severity products tended to maintain the aromatic condensed structure

present in the coals. These products have a lower number of condensed aromatic rings than those present in high severity products. The products from low severity coal liquefaction are in the boiling point range and have the chemical structure of "high density gasoline".

Research in low severity coal liquefaction by Farooque and coworkers (1991) evaluated the feasibility of converting coal at low severity conditions by using electroreduction. The process reacts hydrogen ions at the coal surface resulting in hydrogenation reactions of the coal molecules. The reactions were conducted at low severity conditions: at 1 atm, at 150 to 250°C, and at cathodic overpotentials of 0 to 900 m V/RHE with phosphoric acid as the electrolyte. Five different coals, charcoal, and a devolatilized coal were tested. The reaction products from these reactions depended upon the type of coal used and particularly on the volatile material in coal. The products were composed of a variety of aliphatic and aromatic compounds. Phenolic aromatic species were the predominant species present. All of the products were in a low molecular weight range.

REFERENCES

1. Chakrabarty, S. K. "Search for Low Severity Coal Liquefaction Concept," *Liquid Fuels Technology*, 3, 1985, 1-13.
2. Farooque, M., Kush, A., Maw, H., MacDonald, J. "Low Severity Coal Conversion by an Electroreduction Route," *J. Applied Electrochemistry*, 21, 1991, 143-150.
3. Mastral, A. M., Cobolla, V. L. "Characterization of Lignite Low-Severity Depolymerization Products," *Fuel Processing Technology*, 11, 1985, 87-95.
4. Miller, R. L., Balwin, R. M. "Liquefaction Co-Processing of Crude Oil at Low Severity Conditions," *ACS Fuel Chemistry Preprint*, 31(4), 1986, 152-156.
5. Miller, R. L., Giacomelli, G. F., Baldwin, R. M. "Low Severity Co-Processing Using Homogenous Basic Nitrogen Promoters," *ACS Fuel Chemistry Preprints*, 33(1), 1988, 154-162.
6. Moroni, E. C. "Low Severity Coal Liquefaction: A Challenge to Coal Structure Dependency," *ACS Fuel Chemistry Preprints*, 31(4), 1986, 1-4.
7. Olson, E. S., Diehl, J. W., Sharma, R. "Studies of Catalytic Upgrading of Low-Severity Liquefaction Products from Low-Rank Coals," *ACS Fuel Chemistry Preprints*, 33(1), 1988, 332-228.
8. Snape, C. E., Derbyshire, F. J., Stephens, H. P., Kottenstett, R. J., Smith, N. W. "Influence of Organic Coal Structure on Liquefaction Behavior Under Low Severity Conditions," *Coal Science*, 2, 1991, 182-192.

**DATE
FILMED**

7 / 9 / 92