DOE/MC/28131-92/C0028

**Methane Hydrate Potential and Development of a Shallow Gas Field in the Arctic:
The Walakpa Field, North Slope, Alaska**

Authors:

Glenn, R.K.

Contractor:

North Slope Borough
Barrow Gas Fields Development Project
P.O. Box 1120
Barrow, Alaska 99723

Contract Number:

DE-FG21-91MC28131

Conference Title:

Natural Gas Research and Development Contractors Review Meeting

Conference Location:

Morgantown, West Virginia

Conference Dates:

May 5-6, 1992

DOE/NE/28131-92/C0028

MAY 26 1992

Conference Sponsor:

U.S. Department of Energy, Morgantown Energy Technology Center

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

Methane Hydrate Potential and Development of a Shallow Gas Field in the Arctic: The Walakpa Field, North Slope, Alaska

CONTRACT INFORMATION

Contract Number DE-FG21-91MC28131

Contractor North Slope Borough
Barrow Gas Fields Development Project
P.O. Box 1120 Barrow Alaska, 99723
(907) 852-0395

Contractor Project Manager Richard K. Glenn

Principal Investigator Richard K. Glenn

METC Project Manager Rodney D. Malone

Period of Performance August 02, 1991 to April 30, 1992

Schedule and Milestones

FY92 Program Schedule

	S	O	N	D	J	F	M	A	M	J	J	A	S
Preliminary Mapping	-----												
NSB Drilling						-----							
Follow-Up Mapping							-----						
Reservoir Testing								-----					
Analysis and Completion										-----			

OBJECTIVES

The goal of the North Slope Hydrate Study is to evaluate the methane hydrate potential of the Walakpa gas field, a shallow gas field located near Barrow, Alaska. Observing, understanding, and predicting the production characteristics of the Walakpa field will be accomplished by the analysis of the reservoir geology, and of the individual well production data, derived from reservoir engineering studies conducted in the field.

BACKGROUND INFORMATION

In the winter of 1990-1991, Alaska's North Slope Borough (NSB) began the drilling development of the Walakpa gas field to supply the nearby city of Barrow with a long-term natural gas source. The drilling development of this accumulation was a two-year project, and was accomplished during the winters of 1990-1991 and 1991-1992.

The Walakpa accumulation was

discovered in the early 1980's by the U.S. NPR-A exploration program with the drilling of the Walakpa No. 1 well. This well encountered the methane-bearing, Lower Cretaceous Walakpa sandstone at 2020 feet below sea level. Drilling of a downdip confirmation well 4.75 miles to the south encountered the same formation, with increased thickness, porosity, and permeability, and identified a gas column of at least 550 feet (Patterson and others, 1982).

The Walakpa gas accumulation is situated on the south side of an elongate, east-west trending domal structure, and is overlain by permafrost. Permafrost thicknesses in the region range from 600 to 1500 feet. The relatively cold thermal regime of the Walakpa area could allow the presence of naturally occurring methane hydrates, which are crystalline substances, composed of water and methane, in which a solid-water lattice accommodates gas molecules in a cage-like structure (Collett and Bird, 1988). The presence of methane hydrates would affect all aspects of natural gas development, from drilling to production. The presence of methane hydrates could also significantly increase the reserves of a gas field, because a given volume of methane hydrate contains as much as 160 times more methane as the same volume of free natural gas (Sloan, 1990).

In spite of their reserve potential, past production problems in the nearby Barrow gas fields have been thought to be caused in part by in situ methane hydrates, or by the formation of methane hydrates from reservoirs at or near the hydrate freezing point. Hence, the drilling strategy of the NSB was a sequential updip and lateral stepout from the structurally lower confirmation well. This process tested the

lateral continuity of the thicker and warmer methane-bearing sandstone encountered in the Walakpa No. 2 well.

Geologic and reservoir engineering data derived from the first year of drilling were used to plan the remainder of the drilling program, as well as to begin to evaluate the methane hydrate potential of the Walakpa field. As of the writing of this report, the second drilling season has been completed. Reservoir testing of the second season's wells is in progress; this report summarizes what the NSB has determined to date regarding the methane hydrate potential of the Walakpa field.

PROJECT DESCRIPTION

Geological Characteristics of the Walakpa Reservoir

Reservoir Continuity. Drilling development of the Walakpa field was designed to prove up the lateral continuity of the Walakpa sandstone. With only two wells drilled initially, the NSB needed to maximize the possibility of encountering reservoir conditions with the greatest gas deliverability along with the longest producing life. Drilling began as sequential updip stepout from the Walakpa No. 2 well, which had the more favorable reservoir conditions of the two initial wells.

Prior to drilling, regional trends in the Walakpa reservoir were estimated as part of the overall geologic evaluation of the Walakpa accumulation. Reservoir mapping of lithology, gross pay, net pay, and porosity and permeability analyses were conducted after the first drilling season and criteria were set for the second season's well locations. Follow-up mapping after the second drilling season yielded the most

complete inventory of reservoir trends in the Walakpa sandstone.

Thermal Regime. Wireline temperature surveys in each of the Walakpa field wells determine the depth to permafrost and the zones of methane hydrate stability, if any. Temperature surveys are conducted during production tests of each new well, approximately one month after drilling. Temperature surveys were also planned for the Walakpa Nos. 1 and 2 wells. Temperature readings are taken at 500 foot stations, and near the bottom of the tubing string, located just above the top of the well perforations. Each temperature survey yields a geothermal gradient, depth to base of permafrost, and calculated reservoir temperature for each well.

Based on reservoir pressure and gas chemistry data acquired from the Walakpa Nos. 1 and 2 wells, a hydrate formation temperature of 56.3 degrees Fahrenheit was calculated by Dr. V. Kamath of the University of Alaska Petroleum Engineering Department (pers. comm., 1990). Part of the development strategy of the NSB was to estimate reservoir temperatures and locate drilling targets whose reservoir temperature would be above the hydrate formation temperature.

Well Log Analysis

A standard suite of resistivity, acoustic porosity, neutron porosity, density porosity, and gamma ray logs were run on each of the NSB wells. These logs were analyzed to determine the petrophysical properties of the reservoir throughout the Walakpa field.

The presence of in situ methane hydrates can also be detected by well log analysis, provided that downdip well logs

encounter the free-methane portion of the reservoir for comparison. Well log analysis was planned examine the differences between the updip and downdip NSB wells to evaluate the well log response to methane hydrates, if any were encountered.

Trapping Mechanism

Free-gas/Hydrate Contact. Reservoir temperature, pressure, and gas chemistry data were analyzed for each NSB well in the Walakpa field. This information, along with well log analyses, serves as an locator for the methane hydrate stability field.

Seismic/Well Correlation. Following drilling, each well was correlated with NSB seismic data, yielding the most complete map of the Walakpa structure.

Production Feasibility

Drilling, completion and production all have significant effects on the producibility of reservoirs containing methane hydrates. A task of this study is to determine future opportunities in hydrate production engineering, and to assess the effects of development on reservoirs containing methane hydrates.

RESULTS

Reservoir Continuity

In all, eight wells were drilled, and the Walakpa confirmation well was worked over, in the 1990-1991 and 1991-1992 winter drilling seasons. Lateral continuity of the reservoir sandstone was established, as the producing formation was encountered in each well, and was seen to change only very gradually throughout the field. Tables 1a and 1b summarize the

important characteristics of the Walakpa sandstone.

Table 1a. Summary of Reservoir Data: Walakpa Nos. 1-5, Walakpa Gas Field, Alaska

Well No.	1	2	3	4	5
Subsea Depth (ft), Walakpa Sandstone	2020	2555	2325	2120	2121
Thickness (ft), Walakpa Sandstone	20	37	28	26	25
Net Pay (ft)	16	29	24	23	22
Avg. Porosity (%)	21	21	21	21	21
Avg. Permeability (md)	62	116	187	175	171

Table 1b. Summary of Reservoir Data: Walakpa Nos. 6-10, Walakpa Gas Field, Alaska

Well No.	6	7	8	9	10
Subsea Depth (ft), Walakpa Sandstone	2401	2210	2350	2346	2180
Thickness (ft), Walakpa Sandstone	30	30	33	32	28
Net Pay (ft)	25	23	26	28	24
Avg. Porosity (%)	20	24	23	22	23
Avg. Permeability (md)	*	*	*	*	*

* - Not Available

The Walakpa sandstone is a fine- to very fine-grained, moderately sorted calcareous to sideritic sandstone. In general, the Walakpa sandstone averages about 30 feet thick. The formation thickens gradually to the south. This trend is corroborated by the Arco Brontosaurus well, which was drilled 14 miles south of the Walakpa field, where the Walakpa sandstone is about 50 feet thick. At this location the formation was water wet. Porosity and permeability trends are nearly uniform. In all Walakpa wells, the Walakpa sandstone was gas-bearing, and no fluid contacts were encountered. A minimum gas column of 550 feet has been established for this laterally continuous reservoir.

Thermal Regime

Wireline temperature and reservoir engineering studies were conducted in all wells completed during the first drilling season. Geothermal gradients for each well were calculated from the temperature surveys. In all wells the gradient was constant above and below the base of the permafrost. This was expected, since the sedimentary section is predominantly shale, whose thermal conductivity is affected the least by freezing temperatures.

Mean annual surface temperatures for the area were obtained from Lachenbruch and others (1987). Given the measured geothermal gradient and a mean annual surface temperature, a depth to the base of the hydrate stability zone (depth to the 56 degree Fahrenheit isotherm) could be calculated. Geothermal data are summarized in Table 2.

Temperature surveys were run on the Walakpa Nos. 1 and 2 wells during drill stem tests performed immediately after

they were drilled. These surveys are interpreted to be unreliable as they may be affected by the heat associated with drilling. For example, the temperature measured in this study for the Walakpa No. 2 well (72 degrees Fahrenheit) is more than two degrees lower than the temperature measured during the drill stem test of the well (Patterson and others, 1982). In the Walakpa No. 1 well, the formation temperature is estimated to be 50 - 55 degrees Fahrenheit, more than 10 degrees lower than the 65 degrees Fahrenheit measured during the drill stem test of that well (Husky, 1982). Attempts are now being made to re-enter the No. 1 well with a wireline unit and measure the geothermal gradient of the well.

Trapping Mechanism

Gas chemistry data from the NSB wells is nearly identical to the Walakpa No. 2 well and reservoir pressures are also nearly constant, despite a structural relief of about 500 feet. Reservoir pressures average 1027 psia; maximum deviation from this average is 10 psia. This is another good indicator of lateral continuity of the reservoir. Hydrate formation temperature for the entire gas field, then, is assumed to be about 56 degrees Fahrenheit.

Well Log Analysis

Well log analysis of the standard suite of logs provided porosity and lithology data described above. However, as none of the producing intervals were within the methane hydrate stability field, the well log response to formation hydrates could not be documented.

Table 2. Geothermal Data for the Walakpa Gas Field, Alaska

Well No.	2	3	4	5	6
Depth to Base of Permafrost (ft, subsea)	896	898	928	1004	914
Reservoir Temperature (Degrees F)	72.0	64.5	60.4	57.4	66.1
Geothermal Gradient (Degrees F/100 ft)	2.32	2.25	2.36	2.25	2.27
Mean Annual Surface Temperature (Degrees F)	10	10	10	10	10
Calculated Depth to Base of Hydrate Stability Zone (ft, subsea)	1943	1971	1955	2079	1981

Production Feasibility

In the drilling development of the Walakpa field, steps were taken by the contracted petroleum engineers (Allen and Crouch, Petroleum Engineers, of Casper Wyoming) to minimize formation damage to the reservoir. Any damage would cause an increase in the pressure drop across the perforations, which results in increased Joule-Thomson cooling. In reservoirs with already cool temperatures, this cooling could cause methane hydrate accumulation at the perforation surface and result in freezing of the well. The wells were drilled with near-balance mud weights to minimize mud filtrate invasion. Cement columns were high enough to safely isolate

the producing zone, but not too high to cause formation breakdown. Perforations were high-density (12 shots per foot) to maximize communication with the reservoir.

Wells were designed to produce through the tubing/casing annulus. Production of the wells through the greater cross-sectional area of the annulus results in overall lower gas velocities toward the wellhead. This lower velocity allows production hydrates, if any, to fall to the bottom of the well and dissociate. The wells are then periodically blown through the tubing. This production technique has proven to be effective in combating the formation of production hydrates in the nearby Barrow gas fields.

**DATE
FILMED**
7/22/92