NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

April 1992

BNL--47504

04

DE92 014692

JUN 0 21

ANALYSIS OF INDIVIDUAL MICROSCOPIC PARTICLES BY MEANS OF SYNCHROTRON RADIATION INDUCED X-RAY MICRO FLUORESCENCE

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

K. H. Janssens and F. C. Adams
University of Antwerp (U.I.A.), B-2610 Wilrijk/Antwerp, Belgium

M. L. Rivers
The University of Chicago, Chicago, Illinois 60637 USA

K. W. Jones
Brookhaven National Laboratory, Upton, New York 11973 USA

Presented at

50th Annual Meeting of the Electron Microscopy Society of America
Held Jointly with 27th Annual Meeting of the Microbeam Analysis Society
and 19th Annual Meeting of the Microscopical Society of Canada

Boston, Massachusetts

August 16-21, 1992

By acceptance of this article, the publisher and/or recipient acknowledges the US Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TITLE →

ANALYSIS OF INDIVIDUAL MICROSCOPIC PARTICLES BY MEANS OF SYNCHROTRON RADIATION INDUCED X-RAY MICRO FLUORESCENCE.

K. Janssens, F. Adams, M.L. Rivers* and K.W. Jones*

Department of Chemistry, University of Antwerp, Universiteitsplein 1, B-2610 Wilrijk, Belgium.

* Department of Applied Physics, Brookhaven National Laboratories, 11973 Upton, New York, USA.

Micro-SXRF (Synchrotron X-ray Fluorescence) or micro-SRIXE (Synchrotron Radiation Induced X-ray Emission) is a microanalytical technique which combines the sensitivity of more conventional microchemical methods such as Secondary Ion Microscopy (SIMS)¹ and μ -PIXE (Proton Induced X-ray Emission)² with the non-destructive and quantitative character of x-ray fluorescence analysis. The detection limits attainable at current SXRF-facilities are situated in the ppm (and in favourable cases the sub-ppm) range.³ The sensitivity of SRIXE can be used advantageously in individual particle analysis. This type of analysis is used, e.g., for studying sources of atmospheric pollution. Analysis of standard NIST micro-spheres at the NSLS-SRIXE facility yielded minimum detection limits in the 1 to 100 ppm range for particle sizes of around 10 to 30 μm .⁴

An interesting approach to individual particle characterisation is by means of electron microprobe analysis (EPMA). By using the backscattered electron signals, in an automated fashion, particles can be easily located on a filter substrate and their size and shape determined. From each individual particle, also an (electron-induced) x-ray emission spectrum can be collected, yielding information on the particle's chemical composition.⁵ Via the use of suitable pattern recognition techniques, the morphological and compositional information obtained from a large number of particles analyzed on each filter can be used to classify the particles into groups.^{6,7} This method is useful, e.g., in atmospheric chemistry investigations, but can also be applied to more industrially oriented studies such as metal-wear analysis. A limitation of EPMA, however, is its limited sensitivity. From electron-induced x-ray spectra only information on the major composition (> 0.1 %w) of the particles can be obtained.

By using a photon micro-beam instead of an electron beam to induced x-ray emission, this limitation can be removed. However, associated with the use of SRIXE instead of EPMA for individual particle analysis are also a number of other problems of fundamental and/or practical nature. In order to assess these and compare the merits and disadvantages of both methods, the techniques were used to analyze a number of particle-loaded filters of different origin. Nuclepore filters containing aerosols sampled in the Antarctic during the austral winter and summer were analyzed; particulate material filtered from motor-oil and extracted from river-bed sediment were studied. In addition, aerosols sampled by dry-deposition in a sub-urban area were characterized. Using automated EPMA, in each sample, about 500 to 1000 particles were analyzed, taking in total ca. 6 hours instrument time per sample. Using SRIXE, in about the same time, x-ray spectra of ca. 100 particles per filter were collected.

In comparing the results obtained using both methods, a number of differences are readily observed. The main difference stems from the higher sensitivity of SRIXE, allowing the determination of trace element constituents of the particles. For instance for the case of the Antarctic aerosol samples, by considering the trace element 'fingerprint' of the NaCl microcrystals, a clear distinction between the samples collected in the austral summer and winter could be made. Fig. 1 shows a typical SRIXE-spectrum of a NaCl micro crystal collected during the summer period. The seasonal differences were not visible with EPMA analysis. In the case of the suburban aerosol, the same major groups were found with SRIXE as with EPMA and could be identified as originating from e.g. soil dust, car exhaust etc. In many particles, using SRIXE, minute quantities of Pb could be determined; using EPMA only in a few cases the presence of Pb was detected. In contrast to EPMA, however, by means of which aerosols with diameters larger than 0.2 μm can be straightforwardly analyzed, in view of the currently available photon beam cross sections (typically around or above 5 μm) SRIXE is limited to the size fraction above $\pm 10 \mu\text{m}$. Below, either too much scattered radiation is detected originating from the filter or too long counting times need to be employed.

The Government reserves for itself and others acting on its behalf a royalty free, nonexclusive, irrevocable, world-wide license for governmental purposes to publish, distribute, translate, duplicate, exhibit, and perform any such data copyrighted by the contractor.

Whereas for EPMA, counting times of the order of 20 to 50 seconds per particle suffice to obtain an acceptable estimate of the particle's major composition, in order to detect with sufficient statistics trace elements constituents (e.g., Sr, Pb in NaCl, see Fig. 1), collection times up to 15 minutes per particle are necessary. Another, though less fundamental disadvantage of SRIXE (in its present form) is the fact that the particle search and data collection is not automated. Combined with relatively long counting times, this results in very time-intensive measurement sessions. This obstacle, however, could readily be removed by establishing the positions of the particles via light microscopy and using these to control the position of the sample in the photon beam.

A complementary scheme of particle characterisation in which the two methods are used appears most promising. In this way automated EPMA could be used to identify and determine the major composition and relative importance of the various groups in the aerosol population. In a next step, in order to obtain more accurate quantitative information on the (major and trace level) composition of some or all particle classes, a limited number of particles could then be analyzed by SRIXE. A systematic analysis of all (or large numbers of) particles on a filter by SRIXE only is not practical in view of the beam time required and the cost of and limited access to the instrumentation.⁸

References

1. R. Castaing, G. Slodzian, *J. Microscopy*, (1962)1, 395.
2. S. Johansson and J. Campbell, *PIXE, a novel technique for elemental analysis*, New York: Wiley, 1988.
3. K.W. Jones, B.M. Gordon, *Anal. Chem.*, (1989)61, 341A.
4. K. Janssens et al., *Adv. X-ray Anal.*, (1992)38, in press.
5. X.D. Liu et al., *Anal. Chem.*, (1987)59, 930.
6. H. Storms et al., *X-ray Spectrometry*, (1989)18, 45.
7. C.M. Rojas et al., *Sci. Tot. Env.*, (1990)91, 251.
8. This work was supported by the Belgian National Science Fund NFWO, by the US Department of Energy, Office of Basic Energy Sciences, Chemical Sciences Division under Contract No. DE-AC02-76CH0016. M.R. wishes to thank the National Science Foundation (NSF) for support through grant No. EAR89-17000. We would like to thank P. Antao, W. Dorné and V. Van Alsenoy for providing some of the samples.

FIG. 1.-- Synchrotron Radiation induced X-ray fluorescence spectrum obtained from a NaCl microcrystal sampled in the Antarctic in March 1988 on the King George Island. The Fe, Zn and Pb intensities correspond to absolute detected amounts of resp. 51, 7 and 25 fg. The Pb signal is close to the lower limit of detection (ca. 5 ppm in this case). Counting time is 600 sec.

END

**DATE
FILMED**

7 / 20 / 92

NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

April 1992

BNL--47504

04

DE92 014692

JUN 0 21

ANALYSIS OF INDIVIDUAL MICROSCOPIC PARTICLES BY MEANS OF SYNCHROTRON RADIATION INDUCED X-RAY MICRO FLUORESCENCE

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

K. H. Janssens and F. C. Adams
University of Antwerp (U.I.A.), B-2610 Wilrijk/Antwerp, Belgium

M. L. Rivers
The University of Chicago, Chicago, Illinois 60637 USA

K. W. Jones
Brookhaven National Laboratory, Upton, New York 11973 USA

Presented at

50th Annual Meeting of the Electron Microscopy Society of America
Held Jointly with 27th Annual Meeting of the Microbeam Analysis Society
and 19th Annual Meeting of the Microscopical Society of Canada

Boston, Massachusetts

August 16-21, 1992

By acceptance of this article, the publisher and/or recipient acknowledges the US Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TITLE →

ANALYSIS OF INDIVIDUAL MICROSCOPIC PARTICLES BY MEANS OF SYNCHROTRON RADIATION INDUCED X-RAY MICRO FLUORESCENCE.

K. Janssens, F. Adams, M.L. Rivers* and K.W. Jones*

Department of Chemistry, University of Antwerp, Universiteitsplein 1, B-2610 Wilrijk, Belgium.

* Department of Applied Physics, Brookhaven National Laboratories, 11973 Upton, New York, USA.

Micro-SXRF (Synchrotron X-ray Fluorescence) or micro-SRIXE (Synchrotron Radiation Induced X-ray Emission) is a microanalytical technique which combines the sensitivity of more conventional microchemical methods such as Secondary Ion Microscopy (SIMS)¹ and μ -PIXE (Proton Induced X-ray Emission)² with the non-destructive and quantitative character of x-ray fluorescence analysis. The detection limits attainable at current SXRF-facilities are situated in the ppm (and in favourable cases the sub-ppm) range.³ The sensitivity of SRIXE can be used advantageously in individual particle analysis. This type of analysis is used, e.g., for studying sources of atmospheric pollution. Analysis of standard NIST micro-spheres at the NSLS-SRIXE facility yielded minimum detection limits in the 1 to 100 ppm range for particle sizes of around 10 to 30 μm .⁴

An interesting approach to individual particle characterisation is by means of electron microprobe analysis (EPMA). By using the backscattered electron signals, in an automated fashion, particles can be easily located on a filter substrate and their size and shape determined. From each individual particle, also an (electron-induced) x-ray emission spectrum can be collected, yielding information on the particle's chemical composition.⁵ Via the use of suitable pattern recognition techniques, the morphological and compositional information obtained from a large number of particles analyzed on each filter can be used to classify the particles into groups.^{6,7} This method is useful, e.g., in atmospheric chemistry investigations, but can also be applied to more industrially oriented studies such as metal-wear analysis. A limitation of EPMA, however, is its limited sensitivity. From electron-induced x-ray spectra only information on the major composition (> 0.1 %w) of the particles can be obtained.

By using a photon micro-beam instead of an electron beam to induced x-ray emission, this limitation can be removed. However, associated with the use of SRIXE instead of EPMA for individual particle analysis are also a number of other problems of fundamental and/or practical nature. In order to assess these and compare the merits and disadvantages of both methods, the techniques were used to analyze a number of particle-loaded filters of different origin. Nuclepore filters containing aerosols sampled in the Antarctic during the austral winter and summer were analyzed; particulate material filtered from motor-oil and extracted from river-bed sediment were studied. In addition, aerosols sampled by dry-deposition in a sub-urban area were characterized. Using automated EPMA, in each sample, about 500 to 1000 particles were analyzed, taking in total ca. 6 hours instrument time per sample. Using SRIXE, in about the same time, x-ray spectra of ca. 100 particles per filter were collected.

In comparing the results obtained using both methods, a number of differences are readily observed. The main difference stems from the higher sensitivity of SRIXE, allowing the determination of trace element constituents of the particles. For instance for the case of the Antarctic aerosol samples, by considering the trace element 'fingerprint' of the NaCl microcrystals, a clear distinction between the samples collected in the austral summer and winter could be made. Fig. 1 shows a typical SRIXE-spectrum of a NaCl micro crystal collected during the summer period. The seasonal differences were not visible with EPMA analysis. In the case of the suburban aerosol, the same major groups were found with SRIXE as with EPMA and could be identified as originating from e.g. soil dust, car exhaust etc. In many particles, using SRIXE, minute quantities of Pb could be determined; using EPMA only in a few cases the presence of Pb was detected. In contrast to EPMA, however, by means of which aerosols with diameters larger than 0.2 μm can be straightforwardly analyzed, in view of the currently available photon beam cross sections (typically around or above 5 μm) SRIXE is limited to the size fraction above $\pm 10 \mu\text{m}$. Below, either too much scattered radiation is detected originating from the filter or too long counting times need to be employed.

The Government reserves for itself and others acting on its behalf a royalty free, nonexclusive, irrevocable, world-wide license for governmental purposes to publish, distribute, translate, duplicate, exhibit, and perform any such data copyrighted by the contractor.

Whereas for EPMA, counting times of the order of 20 to 50 seconds per particle suffice to obtain an acceptable estimate of the particle's major composition, in order to detect with sufficient statistics trace elements constituents (e.g., Sr, Pb in NaCl, see Fig. 1), collection times up to 15 minutes per particle are necessary. Another, though less fundamental disadvantage of SRIXE (in its present form) is the fact that the particle search and data collection is not automated. Combined with relatively long counting times, this results in very time-intensive measurement sessions. This obstacle, however, could readily be removed by establishing the positions of the particles via light microscopy and using these to control the position of the sample in the photon beam.

A complementary scheme of particle characterisation in which the two methods are used appears most promising. In this way automated EPMA could be used to identify and determine the major composition and relative importance of the various groups in the aerosol population. In a next step, in order to obtain more accurate quantitative information on the (major and trace level) composition of some or all particle classes, a limited number of particles could then be analyzed by SRIXE. A systematic analysis of all (or large numbers of) particles on a filter by SRIXE only is not practical in view of the beam time required and the cost of and limited access to the instrumentation.⁸

References

1. R. Castaing, G. Slodzian, *J. Microscopy*, (1962)1, 395.
2. S. Johansson and J. Campbell, *PIXE, a novel technique for elemental analysis*, New York: Wiley, 1988.
3. K.W. Jones, B.M. Gordon, *Anal. Chem.*, (1989)61, 341A.
4. K. Janssens et al., *Adv. X-ray Anal.*, (1992)38, in press.
5. X.D. Liu et al., *Anal. Chem.*, (1987)59, 930.
6. H. Storms et al., *X-ray Spectrometry*, (1989)18, 45.
7. C.M. Rojas et al., *Sci. Tot. Env.*, (1990)91, 251.
8. This work was supported by the Belgian National Science Fund NFWO, by the US Department of Energy, Office of Basic Energy Sciences, Chemical Sciences Division under Contract No. DE-AC02-76CH0016. M.R. wishes to thank the National Science Foundation (NSF) for support through grant No. EAR89-17000. We would like to thank P. Antaxo, W. Dorné and V. Van Alsenoy for providing some of the samples.

FIG. 1.-- Synchrotron Radiation induced X-ray fluorescence spectrum obtained from a NaCl microcrystal sampled in the Antarctic in March 1988 on the King George Island. The Fe, Zn and Pb intensities correspond to absolute detected amounts of resp. 51, 7 and 25 fg. The Pb signal is close to the lower limit of detection (ca. 5 ppm in this case). Counting time is 600 sec.

END

**DATE
FILMED**

7 / 20 / 92