1990 Washington State Directory of Biomass Energy Facilities

809 Legion Way SE / FA-11 / Olympia, WA 98504-1211

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

WAOENG --90-07

WAOENG--90-07

DE92 011829

1990 Washington State Directory of Biomass Energy Facilities

Prepared by
Joyce A. Deshayé
Bioenergy Program Assistant
(206) 586-8079

James D. Kerstetter, Ph.D.
Bioenergy Program Manager
(206) 586-5034

Desktop Publishing & Design by
Charlotte A. Gruessing

Maps by
Steve Zubalik

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Acknowledgements

The authors wish to thank the U.S. Department of Energy and the Bonneville Power Administration for their financial contribution to this effort. We also want to thank Steve Zubalik, the Washington State Energy Office, for preparing the maps included in this directory.

Special thanks are due to the facility managers that took the time to respond to the survey. Without their cooperation, this report could not have been completed.

Disclaimer

This report was prepared by the Washington State Energy Office (WSEO) as an account of work sponsored by the U. S. Department of Energy. Neither the United States, the state of Washington, the Washington State Energy Office, nor any of their employees, nor their contractors, subcontractors, nor their employees, make any warranty, expressed or implied, or assumes legal responsibility for the accuracy, completeness, or the usefulness of any information, apparatus, product, or process disclosed within this report.

Table of Contents

Table of Abbreviations iv

Introduction 1

Summary Table 2

Biogas Production

Biogas Facilities Map 3

Summary Table 4

Biogas Facilities 5

Listing Changes From 1987 Edition 12

Wood Combustion

Wood Combustion Facilities Map 13

Summary Table 14

Forest Products Industry Facilities 16

Other Facilities 33

Listing Changes From 1987 Edition 36

Ethanol Fuel,

Municipal Solid Waste (MSW), and Solid Fuel Processing

Ethanol, MSW, and Solid Fuel Facilities Map 37

Summary Tables 38

Ethanol Fuel Production Facilities 39

MSW Combustion Facilities 39

Solid Fuel Processing Facilities 40

Listing Changes From 1987 Edition 41

Conversion Table 43

Glossary 45

Index 49

Table of Abbreviations

BDMT	bone dry metric ton
BDT	bone dry ton
BDT/yr	bone dry ton per year
BDU	bone dry unit
bhp	boiler horse power
Btu	British thermal unit
hp	horse power
kW	kilowatt
kWh	kilowatt-hour
lb/hr	pound per hour
lbs/hr	pounds per hour
MGD	million gallons per day
MSW	municipal solid waste
MW	electric capacity, megawatts
MWh	electric production, megawatt-hour
psi	pounds per square inch
psig	pounds per square inch, gauge
RDF	refuse derived fuel
scf	standard cubic feet
STP	sewage treatment plant

Introduction

Introduction

This is the second edition of the Washington Directory of Biomass Energy Facilities, the first edition was published in 1987. It is an update of biomass energy production and use in Washington State for 1989. The purpose of this directory is to provide a listing of known biomass users within the state and some basic information about their facilities. The data can be helpful to persons or organizations considering the use of biomass fuels.

The directory is divided into three sections of biomass facilities with each section containing a map of locations and a data summary table. In addition, a conversion table, a glossary and an index are provided in the back of the directory.

The first section deals with biogas production from wastewater treatment plants.

The second section provides information on the wood combustion facilities in the state. This section is subdivided into two categories. The first is for facilities connected with the forest products industries. The second category include other facilities using wood for energy.

The third section is composed of three different types of biomass facilities—ethanol, municipal solid waste, and solid fuel processing.

As shown in Table 1 on page 3, biomass facilities included in this directory produce over 64 trillion Btu (British thermal units) per year. Wood combustion facilities account for 91 percent of the total. Biogas and ethanol facilities each produce close to 800 billion Btu per year, MSW facilities produce 1,845 billion Btu, and solid fuel processing facilities produce 2,321 billion Btu per year. To put these numbers in perspective, Washington's industrial sector uses 200 trillion Btu of fuels per year. Therefore, biomass fuels used and/or produced by facilities listed in this directory account for nearly 32 percent of the state's total industrial fuel demand. This is a sizable contribution to the state's energy needs.

Table 1 also shows significant increases in biomass energy production for biogas and ethanol production, MSW combustion, and solid fuel processing.

2 - Directory of Biomass Energy Facilities

Summary Table 1 Washington State Biomass Energy Production

**Comparison for 1987 and 1989
(Billion Btu - Gross)**

Type of Facility	1987		1989	
	Billion Btu/Year	% of Total	Billion Btu/Year	% of Total
Biogas	600	1.02	810	1.25
Wood Combustion	57,496	97.45	58,834	91.06
Ethanol Production	600	1.02	798	1.24
MSW Combustion	300	0.51	1,845	2.86
Solid Fuel Processing	<1	0.00	2,321	3.59
Total	59,000		64,608	

Biogas Production

Summary Table 2
Washington State Biogas Production Facilities
Sorted by Biogas Output

Facility	City	Sewage Capacity Million Gal./Day	Avg. Biogas Output Million Cubic Ft./Yr.	Gross Energy Equivalent** Million Btu/Yr.
▲ Renton Treatment Plant	Renton	72.00	339 *	203,400
■ West Point Treatment Plant	Seattle	125.00	256	153,600
Spokane Wastewater Treatment Plant	Spokane	44.00	200	120,000
▲ Tacoma STP-1, City of	Tacoma	28.00	80	48,000
Port Orchard/Kitsap County Sewer Dist. #5	Port Orchard	2.80	55	33,000
■ Lacey, Olympia, Tumwater, Thurston (LOTT)	Olympia	22.00	45	27,000
Pierce Co. Chambers Creek Treatment Plant	Tacoma	12.00	32	19,200
Puyallup Wastewater Plant	Puyallup	10.70	30	18,000
Newport, City of	Newport	0.50	30	18,000
Pasco, City of	Pasco	4.25	24	14,400
Des Moines Creek Treatment Plant	Des Moines	6.00	21	12,600
SW Suburban Sewer District - Salmon Creek	Seattle	5.80	15	9,000
SW Suburban Sewer District - Miller Creek	Seattle	4.70	15	9,000
METRO/Aiki Treatment Plant	Seattle	15.00	15	9,000
Walla Walla Wastewater Treatment Plant	Walla Walla	15.00	14	8,400
■ Bremerton, City of	Bremerton	15.00	14 ***	8,400
Chehalis, City of	Chehalis	2.00	13	7,800
Central Kitsap Treatment Plant	Poulsbo	4.80	9	5,400
Ellensburg, City of	Ellensburg	15.00	8	4,800
Federal Way Water & Sewer	Redondo	13.80	8	4,800
Wenatchee Water Pollution Control Plant	Wenatchee	5.00	8	4,800
■ Centralia, City of	Centralia	4.30	8	4,800
Anacortes, City of	Anacortes	2.20	8	4,800
Sunnyside Wastewater Treatment Plant	Sunnyside	2.18	8	4,800
Douglas County Sewer District	East Wenatchee	1.60	8	4,800
Prosser, City of	Prosser	1.50	8	4,800
Toppenish Wastewater Treatment Plant	Toppenish	1.35	8	4,800
Chelan Treatment Plant	Chelan	1.20	8	4,800
Oak Harbor, City of	Oak Harbor	0.85	8	4,800
Dayton, City of	Dayton	0.60	8	4,800
Rainier State School	Buckley	NA	8	4,800
Pullman Wastewater Treatment Plant	Pullman	4.30	8	4,800
■ Richland Wastewater Treatment Plant	Richland	8.90	8	4,800
Tacoma STP-3, City of	▲ Tacoma	10.00	5	3,000
Port Angeles, City of	Port Angeles	3.20	5	3,000
Richmond Beach Treatment Plant	Seattle	3.20	5	3,000
Carkeek Park Treatment Plant	Seattle	3.50	4	2,400
Mount Vernon, City of	Mount Vernon	4.50	4	2,400
McCleary Sewage Treatment Plant	McCleary	0.75	<1	276
Total		477.48	1,350	810,276

NA - Information Not Available

*Calculated at 600 Btu per scf instead of 1,000 Btu reported for this facility

**Average output calculated at 600 Btu per cubic foot

***Calculated by WSEO

▲ Supplies Washington Natural Gas Pipeline

■ Electrical generation capacity

Biogas Facilities

Anacortes Public Works/Operations Division, City of

2201 - 37th Street
Anacortes, WA 98221
Phone: (206) 293-5175
Contact: Mike Foster

Plant Design Capacity:
Sewage (MGD): 2.2**
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): Less than 10 million per year
Electrical Generation (MW): None

End Use(s): Space and process heat

**Presently in pre-design phase for secondary treatment. Final design capacity unknown at this time.

Bremerton Wastewater Treatment Plant, City of

Bremerton, WA
Phone: (206) 479-4646
Contact: Pat J. Coxon

Plant Design Capacity:
Sewage (MGD): 15
Electrical Generation (MW): 140 kW

Average Plant Output:
Biogas (cubic feet):
Electrical Generation (MW): 70 kWh

End Use(s): Process heat

Central Kitsap Treatment Plant

12350 State 303 NE
Poulsbo, WA 98370
Phone: (206) 876-7197
Contact: Ralph DeClements

Plant Design Capacity:
Sewage (MGD): 4.8
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): 9,320,000 per year
Electrical Generation (MW): None

End Use(s): Space and process heat

Centralla Wastewater Treatment Plant, City of

1401 W Mellen Street
Centralla, WA 98531
Phone: (206) 736-2853
Contact: Denise Lahmann, Administrator, or
Ron Davis, Manager

Plant Design Capacity:
Sewage (MGD): 4.3
Electrical Generation (MW): Standby generator 250 kW three phase, 277/480 volts

Average Plant Output:
Biogas (cubic feet): Less than 10 million per year (anaerobic digestion)
Electrical Generation (MW): None

End Use(s): Space and process heat

Chehalis Wastewater Treatment Plant, City of

1191 NW Shoreline Drive
Chehalis, WA 98532
Phone: (206) 748-7187
Contact: Robert Pinkerton

Plant Design Capacity:
Sewage (MGD): 2.0 (average dry weather)
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): Less than 15 million per year
Electrical Generation (MW): None

End Use(s): Process heat

Chelan Treatment Plant

S Robinson Street
Chelan, WA 98816
Phone: (509) 682-2211
Contact: Howard Merchant

Plant Design Capacity:
Sewage (MGD): 1.2 (new R.B.C. plant)
Electrical Generation (MW): None

Average Plant Output: Unknown
Biogas (cubic feet): Less than 10 million per year
Electrical Generation (MW): None

End Use(s): Flared

**Dayton Wastewater Treatment Plant,
City of**

Route 1
Dayton, WA 99328
Phone: (509) 382-2937
Contact: Duane Lowe

Plant Design Capacity:
Sewage (MGD): 0.60
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): Less than 10 million per
year
Electrical Generation (MW): None

End Use(s): Space heat, flared, automatic burn
off

Des Moines Creek Treatment Plant

1200 S 216th Street
Des Moines, WA 98198
Phone: (206) 824-2760
Contact: Clint Read, Superintendent

Plant Design Capacity:
Sewage (MGD): 6.0
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): 60,000 per day, 20-22
million per year
Electrical Generation (MW): None

End Use(s): Space and process heat

Douglas County Sewer District

P.O. Box 7129
East Wenatchee, WA 98801
Phone: (509) 884-2484
Contact: Dale G. O'Neal

Plant Design Capacity:
Sewage (MGD): 1.6
Electrical Generation (MW): None

Average Plant Output: 1 MGD
Biogas (cubic feet): Less than 10 million
per year
Electrical Generation (MW): None

End Use(s): Process heat

**Ellensburg Wastewater Treatment
Plant, City of**

Route 2, Box 13
Ellensburg, WA 98926
Phone: (509) 962-7277
Contact: Stan Miller

Plant Design Capacity:
Sewage (MGD): 15
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): Less than 10 million
per year
Electrical Generation (MW): None

End Use(s): Process heat and digester
mixing

**Federal Way Water & Sewer Redondo
Treatment Plant**

515 S 288th Street
Redondo, WA 98054
Phone: (206) 839-7441
Contact: Chuck Babel, Assistant Supervisor

Plant Design Capacity:
Sewage (MGD): 4.32 average
annual, 13.80 peak hydraulic, and 5.47
average wet weather
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): Less than 10 million
per year
Electrical Generation (MW): None

End Use(s): Space and process heat

**Lacey, Olympia, Tumwater, Thurston
County (LOTT) Wastewater
Treatment Plant**

500 N Adams Street
Olympia, WA 98501
Phone: (206) 753-8386
Contact: Tom Kolby

Plant Design Capacity:
Sewage (MGD): 22
Electrical Generation (MW): Back-up

Average Plant Output:

Biogas (cubic feet): 44.8 million per year
Electrical Generation (MW): 1,307,642 kWh

End Use(s): Power generation and process heat

McCleary Sewage Treatment Plant

Maple Street
McCleary, WA 98557
Phone: (206) 495-3217
Contact: Jim Wright

Plant Design Capacity:

Sewage (MGD): 0.75 max., 0.25 avg., 0.15 min.
Electrical Generation (MW): None

Average Plant Output:

Biogas (cubic feet): Less than 1 million per year
Electrical Generation (MW): None

End Use(s): Process heat

Mount Vernon Sewer Department, City of

1401 Britt Road
Mount Vernon, WA 98273
Phone: (206) 336-6219
Contact: Chuck Saunders

Plant Design Capacity:

Sewage (MGD): 4.5
Electrical Generation (MW): None

Average Plant Output:

Biogas (cubic feet): 4 million per year
Electrical Generation (MW): None

End Use(s): Space heat and process heat

Newport Wastewater Treatment Plant, City of

5200 Washington Street
Newport, WA 99156
Phone: (509) 447-3012
Contact: Raymond D. King

Plant Design Capacity:

Sewage (MGD): 0.5
Electrical Generation (MW): None

Average Plant Output:

Biogas (cubic feet): 30 million per year
Electrical Generation (MW): None

End Use(s): Process heat

Oak Harbor, City of

3075 - 300 Avenue W
Oak Harbor, WA 98277
Phone: (206) 679-5551, ext. 230
Contact: Jim Croft

Plant Design Capacity:

Sewage (MGD): .85
Electrical Generation (MW): None

Average Plant Output:

Biogas (cubic feet): Less than 10 million per year
Electrical Generation (MW): None

End Use(s): Process heating. Digested sludge is used as fertilizer.

Pasco Sewage Treatment Plant, City of

D & Grey Streets
P.O. Box 293
Pasco, WA 99301
Phone: (509) 545-3468
Contact: Harold Posthuma

Plant Design Capacity:

Sewage (MGD): 4.25
Electrical Generation (MW): None

Average Plant Output:

Biogas (cubic feet): 65,000 per day
Electrical Generation (MW): None

End Use(s): Space and process heat

Port Angeles, City of

1509 E Columbia Street
Port Angeles, WA 98362
Phone: (206) 451-0411, ext. 165
Contact: Jim Abernathy

Plant Design Capacity:

Sewage (MGD): 3.2
Electrical Generation (MW): None

Average Plant Output:

Biogas (cubic feet): 5,000,000 per year
Electrical Generation (MW): None

End Use(s): Process heat

Port Orchard/Kitsap County Sewer District No.5

Wastewater Treatment Facility

1165 Beach Drive
Port Orchard, WA 98366
Phone: (206) 895-2440
Contact: Douglas W. Martin, Plant Manager

Plant Design Capacity:
Sewage (MGD): 2.8
Electrical Generation (MW): None

Average Plant Output: 1.2 MGD
Biogas (cubic feet): 50-60 million per year
Electrical Generation (MW): None

End Use(s): Space and process heat, digester mixing

Prosser Wastewater Treatment Facilities, City of

Box 271
Prosser, WA 99350
Phone: (509) 786-3831
Contact: Walter Titus

Plant Design Capacity:
Sewage (MGD): 1.5 (wastewater)
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): Less than 10 million per year
Electrical Generation (MW): None

End Use(s): Process heat

Pullman Wastewater Treatment Plant

1025 Guy Street
Pullman, WA 99163
Phone: (509) 334-4555, ext. 233
Contact: Terry Dokken

Plant Design Capacity:
Sewage (MGD): 4.3
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): 7,839,000 per year
Electrical Generation (MW): None

End Use(s): Space and process heat

Puyallup Wastewater Plant

218 W Pioneer Street
Puyallup, WA 98371
Phone: (206) 841-5511
Contact: B. Michael Webb

Plant Design Capacity:
Sewage (MGD): 10.7
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): 10 - 50 million per year
Electrical Generation (MW): None

End Use(s): Space and process heat.
Sludge is used as compost mixed with sawdust and used by nurseries for flowering plants and trees.

Rainier State School Sewage Treatment Plant

P.O. Box 600
Buckley, WA 98321
Phone: (206) 829-1734, ext. 280
Contact: Roy Campbell

Plant Design Capacity:
Sewage (MGD):
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): Less than 10 million per year
Electrical Generation (MW): None

End Use(s): Heating the digester, supplemented with natural gas

Renton Treatment Plant

1200 Monster Road SW
Renton, WA 98055
Phone: (206) 684-2412
Contact: Dick Finger, Process Control Supervisor

Plant Design Capacity:
Sewage (MGD): 72
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): 560,000 @ 1,000 Btu/SCF
Electrical Generation (MW): None

End Use(s): Pipeline gas

Richland Wastewater Treatment Plant

P.O. Box 190
Richland, WA 99352
Phone: (509) 943-9161, ext. 416
Contact: David Nelsen

Plant Design Capacity:
Sewage (MGD): 8.9 average
flow
Electrical Generation (MW): 95 kW contin-
uously, May-October

Average Plant Output:
Biogas (cubic feet): 21,000 per day
Electrical Generation (MW): None

End Use(s): Space and process heat

Seattle — Carkeek Park Treatment Plant

1201 NW Carkeek Park Road
Seattle, WA 98177
Phone: (206) 684-1800
Contact: Bill Berry

Plant Design Capacity:
Sewage (MGD): 3.5
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): 4.2 million per year
Electrical Generation (MW): None

End Use(s): Space and process heat

Seattle — Metro Alki Treatment Plant

3380 Beach Drive SW
Seattle, WA 98116
Phone: (206) 684-2412
Contact: Dick Finger

Plant Design Capacity:
Sewage (MGD): 15
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): 40,000 per day, 14.6 million
per year
Electrical Generation (MW): None

End Use(s): Space and process heat

**Seattle — Miller Creek Sewage
Treatment Plant**

Southwest Suburban Sewer District

1015 SW 174th Street
Seattle, WA 98166

Phone: (206) 244-2202
Contact: Tim Yokers

Plant Design Capacity:
Sewage (MGD): 4.7 (peak
month)
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): 42,000 per day
Electrical Generation (MW): None

End Use(s): Space and process heat,
excess flared off

**Seattle — Richmond Beach Treatment
Plant**

20001 Richmond Beach Drive NW
Seattle, WA 98177
Phone: (206) 546-2826
Contact: Bill Berry

Plant Design Capacity:
Sewage (MGD): 3.2
Electrical Generation (MW): None

Average Plant Output:
Biogas (cubic feet): 5 million per year
Electrical Generation (MW): None

End Use(s): Space and process heat

**Seattle — Salmon Creek Sewage
Treatment Plant**

Southwest Suburban Sewer District

12550 Shorewood Drive SW
Seattle, WA 98146

Phone: (206) 243-7770
Contact: Phil Baga

Plant Design Capacity:
Sewage (MGD): 5.8 (peak
month)
Electrical Generation (MW): None

Average Plant Output:

Biogas (cubic feet): 42,000 per day

Electrical Generation (MW): None

End Use(s): Process and building heat, excess flared off

Seattle — West Point Treatment Plant

821 Second Avenue

Seattle, WA 98104

Phone: (206) 477-6801

Contact: Gordon Gabrielson

Plant Design Capacity:

Sewage (MGD): 125

Electrical Generation (MW): Gas production is no longer adequate to power three 1.3 MW generator. Gas production should be adequate again in 1996.

Average Plant Output:

Biogas (cubic feet): 700,000 per day

Electrical Generation (MW): 1.3

End Use(s): Space and process heat, electricity, equipment drives

Note: In 1988, solids were transferred to the Renton Treatment Plant reducing the biomass available for digesters by nearly 50% creating a corresponding reduction in biogas.

Spokane Wastewater Treatment Plant

N 4401 White Park Way

Spokane, WA 99205

Phone: (509) 456-4305

Contact: Ray D. King

Plant Design Capacity:

Sewage (MGD): 44,000,000

Electrical Generation (MW): None

Average Plant Output:

Biogas (cubic feet): 100 - 300 million

Electrical Generation (MW): None

End Use(s): Space and process heat, air conditioning, absorption chiller

Sunnyside Wastewater Treatment Plant

S Fourth Street

Sunnyside, WA 98944

Phone: (509) 837-5206

Contact: Charles Kennedy

Plant Design Capacity:

Sewage (MGD): 2.18

Electrical Generation (MW): None

Average Plant Output:

Biogas (cubic feet): Less than 10 million per year

Electrical Generation (MW): None

End Use(s): Process heat

Tacoma - Pierce County Chambers Creek Treatment Plant

10311 Chamber Creek Road

Tacoma, WA 98467

Phone: 565-3013

Contact: Steve Thompson, Lab Supervisor

Plant Design Capacity:

Sewage (MGD): 12

Electrical Generation (MW): None

Average Plant Output: 8.5 MGD

Biogas (cubic feet): 32,665,800 per year

Electrical Generation (MW): None

End Use(s): Space and process heat, heat digesters

Tacoma Sewage Treatment Plant-1, City of

2201 Portland Avenue

Tacoma, WA 98421

Phone: (206) 591-5587

Contact: David Hufford

Plant Design Capacity:

Sewage (MGD): 28

Electrical Generation (MW): None

Average Plant Output:

Biogas (cubic feet): 80 million per year

Electrical Generation (MW): None

End Use(s): Space and process heat, hot water, autos, Washington Natural Gas pipeline

**Tacoma Sewage Treatment Plant-3,
City of**

4002 Waterview Street
Tacoma, WA 98507
Phone: (206) 591-5587
Contact: David Hufford

Plant Design Capacity:

Sewage (MGD): Less than 10
Electrical Generation (MW): None

Average Plant Output:

Biogas (cubic feet): 5 million per year
Electrical Generation (MW): None

End Use(s): Space and process heat

Toppenish Wastewater Treatment Plant

Germantown Road
Toppenish, WA 98948
Phone: (509) 865-4089
Contact: Ed Martindale

Plant Design Capacity:

Sewage (MGD): 1.35
Electrical Generation (MW): None

Average Plant Output:

Biogas (cubic feet): Less than 10 million
per year
Electrical Generation (MW): None

End Use(s): Process heat

**Walla Walla Wastewater
Treatment Plant**

571 Hatch Street
Walla Walla, WA 99362
Phone: (509) 529-2859
Contact:

Plant Design Capacity:

Sewage (MGD): 10.8 dry flow,
15.00 wet flow
Electrical Generation (MW): None

Average Plant Output:

Biogas (cubic feet): 14,235,000 per year
Electrical Generation (MW): None

End Use(s): Space and process heat,
8,395,000 cubic feet

**Wenatchee Water Pollution
Control Plant**

201 N Worthen Street
P.O. Box 519
Wenatchee, WA 98801
Phone: (509) 663-8416
Contact: Mel Heckler

Plant Design Capacity:

Sewage (MGD): 5
Electrical Generation (MW): None

Average Plant Output:

Biogas (cubic feet): Less than 10 million
per year
Electrical Generation (MW): None

End Use(s): Process heat

Biogas Production Facilities

**Listing Changes
From 1987 Edition**

New Listings

Des Moines Creek Treatment Plant
Port Orchard/Kitsap County Sewer District #5
Southwest Suburban Sewer District - Miller Creek
Southwest Suburban Sewer District - Salmon Creek

Location

Des Moines
Port Orchard
Seattle
Seattle

Deletions

City of Grand Coulee
City of Tacoma STP-2

Reason

No biogas production
Facility closure

Location

Grand Coulee
Tacoma

Wood Combustion

- ***Forest Products
Industry Facilities***
- ***Other Facilities***

Summary Table 3
Washington State Wood Combustion
Facilities Sorted by Wood Consumption

Facility Name	City	Source	Biomass Wood Consumption BDT/yr.	Biomass Energy Output Million** Btu/hr.	Gross Energy Equivalent*** Million Btu/yr.
▲ Weyerhaeuser Company	Longview	In-house & purchased	500,000	832	8,500,000
▲ Washington Water Power Co.	Kettle Falls	Purchased	350,000	509	5,950,000
▲ Longview Fibre Company	Longview	Purchased	232,812	235	3,957,804
▲ ITT Rayonier, Inc. - Grays Harbor	Hoquiam	Purchased	220,460	391	3,747,820
▲■ Omak Wood Products, Inc.	Omak	In-house	192,720	193	3,276,240
▲ Simpson Tacoma Kraft Company	Tacoma	Purchased	174,000	247	2,958,000
▲ Georgia-Pacific Corporation	Bellingham	In-house & purchased	157,000	209	2,669,000
▲ Scott Paper	Everett	In-house & purchased	154,000	301	2,618,000
▲ Boise Cascade Corporation	Stellacoom	Purchased	153,973	137	2,617,541
▲■ Boise Cascade Corporation	Kettle Falls	In-house	138,975	194	2,362,575
▲ Boise Cascade Corporation	Yakima	In-house	118,000	180	2,006,000
▲ ITT Rayonier, Inc.	Port Angeles	In-house & purchased	92,493	254	1,574,081
▲ Boise Cascade Corporation	Walla Walla	Purchased	88,176	241	1,498,992
▲ Simpson Timber Company	Shelton	In-house	83,772 *	156	1,424,124
▲ Weyerhaeuser Company	Cosmopolis	In-house & purchased	80,000	120	1,360,000
▲ Weyerhaeuser Company	Snoqualmie Falls	In-house	73,939 *	147	1,341,963
▲ Port Townsend Paper	Port Townsend	Purchased	77,713	160	1,321,121
▲ Dalshowa America	Port Angeles	Purchased	63,600	90	1,081,200
▲ James River	Camas	Purchased	51,552 *	96	876,384
▲■ Fort Vancouver Plywood	Vancouver	In-house	38,500	54	654,500
▲ Summit Timber Power House	Darrington	In-house	33,653	54	572,101
■ K-Ply, Inc.	Port Angeles	In-house	24,000	48	408,000
▲ Weyerhaeuser Company	Raymond	In-house	23,091 *	43	392,547
▲ Simpson Door Company	McCleary	In-house	22,440	30	381,480
▲ Colville Indian Precision Pine Co.	Omak	In-house	21,420	24	364,140
▲ Mt. Baker Plywood	Bellingham	In-house	19,332 *	36	328,644
▲ W.I. Forest Products	Spokane	In-house	19,332 *	36	328,644
▲ San Poll Lumber Company	Republic	In-house	18,795 *	35	319,515
▲ Vaagen Brothers Lumber, Inc.	Colville	In-house	17,885	72	304,045
▲ Cowlitz Stud Company	Morton	In-house	16,647	31	282,999
■ Buffelen Woodworking	Tacoma	In-house	15,573 *	29	264,741
■ Hardel Mutual Plywood	Olympia	In-house	15,573 *	29	264,741
▲ Pacific Wood Treating	Ridgefield	In-house & purchased	13,750	23	233,750
▲ Champion International	Morton	In-house	12,579	22	213,843
▲ Stevenson Co-Ply Inc.	Stevenson	In-house	12,485	42	212,245
▲■ Goodyear Nelson Hardwood Lumber Co., Inc.	Sedro Woolley	In-house	12,351 *	23	209,967
● Western State Hospital	Stellacoom	Purchased	12,000	64	204,000
■ Puget Sound Plywood	Tacoma	In-house & purchased	11,900	35	202,300
■ Northwest Hardwoods	Arlington	In-house	11,277 *	21	191,709
■ Allen Logging Company	Forks	In-house	10,752	9	182,784
▲ Cowlitz Stud Company	Randle	In-house	10,740	20	182,580
▲ Jeld-Wen Fiber of Washington	White Swan	In-house	8,750	18	148,750
▲ Louisiana Pacific Company	Walla Walla	In-house	8,400	15	142,800
▲ Bennett Lumber Products	Clarkston	In-house	8,030	23	136,510
▲ E. A. Nord	Everett	In-house	7,000	17	119,000
▲ Vaagen Brothers Lumber, Inc.	Ione	In-house	6,643	35	112,931
■ West Coast Forest Products, Inc.	Arlington	In-house	4,720	23	80,240
● Washington State Penitentiary	Walla Walla	Purchased	3,000	25	51,000
▲■ Strauser Manufacturing	Walla Walla	In-house	3,000	6	51,000
▲ Layman's Lumber Company	Naches	In-house	2,100	17	35,700

**Summary Table 3
(Continued)**

Facility Name	City	Source	Biomass Wood Consumption BDT/yr.	Biomass Energy Output Million Btu/hr.	Gross Energy Equivalent Million Btu/yr.
● Maple Lane School	Centralia	Purchased	2,043	4	34,731
● Washington Soldiers Home & Colony	Orting	Purchased	1,930	3	32,810
■ DeGoede Bulb Farms	Mossyrock	Purchased	1,625	3	27,625
■ Kinnear of Washington	Centralia	In-house	770	10	13,090
▲ Oeser Company, The	Bellingham	In-house	280	11	4,760
■ Fred Tebb & Sons, Inc.	Tacoma	In-house	153	17	2,601
■ Coastcraft, Incorporated	Tacoma	In-house	NA	NA	NA
▲ Plum Creek Manufacturing, Inc.	Colville	In-house	NA	NA	NA
▲ Smith Street Mill, Inc.	Everett	In-house	NA	NA	NA
Total			3,460,804	5,699	58,833,668

Biomass Type:

- ▲ Hog Fuel
- Mill Residue
- Wood Pallets

NA - Information not available

*Estimated by Washington State Energy Office

**Calculated from reported average steam output

***Calculated at 8,500 Btu per pound of biomass wood consumed

Forest Products Industry Facilities

Allen Logging Company

HC 80, Box 736
Forks, WA 98331
Phone: (206) 374-6000
Contact: Gerry Lane

Type of Business: Lumber and veneer
Type of Biomass Fuel: Mill residue
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 15,360 green tons
Back-up Fuel: None
End Use(s): Kiln dryers
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 10,000 lbs/hr @ 110 psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr):
Steam: 7,500 lbs/hr @ 110 psig
Electrical Generation (MW): None
Type of Combustor/Furnace: Fuel cell
Manufacturer: Wellons
Type of Boiler: Erie water tube - modified VL
Boiler Manufacturer: Erie
Type of Pollution Control: Multicone
Reason for Using Wood Fuel: Cost, availability

Bennett Lumber Products

1785 Elm Street
Clarkston, WA 99403
Phone: (509) 758-5558
Contact: Don Fairley

Type of Business: Lumber
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 7,300 units
Back-up Fuel: None
End Use(s): Heat for dry kilns
Plant Design Capacity:
Heat (million Btu/hr): 22,425,000
Steam: 19,500 lbs/hr @ 100 psig
Electrical Generation (MW):

Average Plant Output:

Heat (million Btu/hr): 2,070,000
Steam: 8,000 lbs/hr @ 100 psig
Electrical Generation (MW):

Type of Combustor/Furnace: Water tube
Manufacturer: Kipper
Type of Boiler: Water tube
Boiler Manufacturer: Kipper
Type of Pollution Control: Multicone & electric precipitator
Reason for Using Wood Fuel: Generated during manufacturing

Boise Cascade Corporation Kettle Falls Lumber — Steam Boiler

P.O. Box 310
Kettle Falls, WA 99141
Phone: (509) 738-6421
Contact: Rod Smith

Type of Business: Lumber
Type of Biomass Fuel: Hog fuel, planer shavings and sawdust
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 57,451 green tons
Back-up Fuel: None
End Use(s): Dry kilns and unit heaters
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 50,000 lbs/hr @ 125 psig
Electrical Generation (MW):

Average Plant Output:

Heat (million Btu/hr):
Steam: 35,700 lbs/hr @ 125 psig
Electrical Generation (MW):

Type of Combustor/Furnace: 3 Cell Cyclo-Blast
Manufacturer: Wellons
Type of Boiler: Water tube
Boiler Manufacturer: Nebraska Boiler Company
Type of Pollution Control: Dry type mechanical multicone collector
Reason for Using Wood Fuel: Economics

**Bolse Cascade Corporation
Kettle Falls Plywood — Fluid
Bed Burners**

P.O. Box 310
Kettle Falls, WA 99141
Phone: (509) 738-6421
Contact: Rod Smith

Type of Business: Plywood
Type of Biomass Fuel: Hog fuel, sawdust
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 95,000 green tons

Back-up Fuel: Gas
End Use(s): Plywood veneer dryers (direct heat source)

Plant Design Capacity:
Heat (million Btu/hr): 160
Steam: _____ lbs/hr @ _____ psig
Electrical Generation (MW):

Average Plant Output:
Heat (million Btu/hr): 80
Steam: _____ lbs/hr @ _____ psig
Electrical Generation (MW):

Type of Combuster/Furnace: Fluid bed
Manufacturer: Energy Products of Idaho (E.P.I.)
Type of Boiler: None
Boiler Manufacturer:
Type of Pollution Control: 6" Multicone collector & wet scrubber
Reason for Using Wood Fuel: Economics

**Bolse Cascade Corporation
Kettle Falls Plywood & Small Log Mill —
Steam Boiler**

P.O. Box 310
Kettle Falls, WA 99141
Phone: (509) 738-6421
Contact: Rod Smith

Type of Business: Lumber & plywood
Type of Biomass Fuel: Hog fuel, sawdust & plywood dry trim
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 46,084 green tons
Back-up Fuel: None
End Use(s): Steam vats, plywood hot press, unit heaters

Plant Design Capacity:
Heat (million Btu/hr):
Steam: 60,000 lbs/hr @ 125 psig
Electrical Generation (MW):

Average Plant Output:
Heat (million Btu/hr):
Steam: 28,640 lbs/hr @ 125 psig
Electrical Generation (MW):

Type of Combuster/Furnace: Field erected stationary water cooled grate

Manufacturer: Riley Stoker Corporation

Type of Boiler: Water tube, type "VO"

Boiler Manufacturer: Riley Stoker Corporation

Type of Pollution Control: Dry type 9" Mechanical Multicone Collector

Reason for Using Wood Fuel: Economics

Bolse Cascade Corporation

4302 Chamber Creek Road
Stellacoom, WA 98388
Phone: (206) 588-2115
Contact: Ken Campbell

Type of Business: Pulp and paper

Type of Biomass Fuel: Hog fuel

Source of Fuel: Various lumber companies (all purchased)

Annual Biomass Fuel Consumed: 153,973 BDT hogged fuel plus 17,472 tons sludge primary clarifier

Back-up Fuel: Industrial #6 oil

End Use(s): Process steam, dryers

Plant Design Capacity: No 5 Hogged fuel boiler

Heat (million Btu/hr): None
Steam: 150,000 lbs/hr @ 140 psig
Electrical Generation (MW): None

Average Plant Output:
Heat (million Btu/hr):
Steam: 120,000 lbs/hr @ 140 psig
Electrical Generation (MW): None

Type of Combuster/Furnace:

Manufacturer: Kipper & Sons

Type of Boiler: Traveling grate, water wall

Boiler Manufacturer: Kipper & Sons

Type of Pollution Control: Multicone collectors/fly ash reinjection, AER POL high energy wet scrubber

Reason for Using Wood Fuel: Cost/availability vs fossil fuel Also firm is equipped with a Cascade (Bacho design) fuel dryer utilizing flue gas.

Bolse Cascade Corporation

P.O. Box 500
Wallula, WA 99363
Phone: (509) 545-3213
Contact: Anders Ohlsson, Production Manager

Type of Business: Pulp and paperboard
Type of Biomass Fuel: Hog fuel
Source of Fuel: Purchased
Annual Biomass Fuel Consumed: 73,480 BDUs
Back-up Fuel: Natural gas
End Use(s): Process steam, dryers
Plant Design Capacity: 1 hog fuel boiler
Heat (million Btu/hr): 193
Steam: 201,000 lbs/hr @ 250 psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr): 172
Steam: 179,000 lbs/hr @ 250 psig
Electrical Generation (MW): None
Type of Combuster/Furnace: Sterling type, pin hole grate
Manufacturer: Kipper
Type of Boiler: Sterling type pinhold grate
Boiler Manufacturer: Kipper
Type of Pollution Control: Mechanical, multi-cone scrubber, Riley ventri-rod wet scrubber
Reason for Using Wood Fuel: Economics

Bolse Cascade Corporation

P.O. Box 51
Yakima, WA 98901
Phone: (509) 453-3131
Contact: Dick Godfrey

Type of Business: Lumber
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 118,000 dry tons
Back-up Fuel: None
End Use(s): Dry kilns, dryers

Plant Design Capacity:
Heat (million Btu/hr):
Steam: 200,000 lbs/hr @ 250 psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr):
Steam: 150,000 lbs/hr @ 250 psig
Electrical Generation (MW):
Type of Combuster/Furnace: 3 Dutch ovens, 1 spreader stoker
Manufacturer:
Type of Boiler: Water tube
Boiler Manufacturer:
Type of Pollution Control: Multicone and wet scrubber
Reason for Using Wood Fuel: Economics

Buffelen Woodworking

P.O. Box 1383
Tacoma, WA 98481
Phone: (206) 627-1191
Contact: Roger Lay

Type of Business: Door
Type of Biomass Fuel: Mill residue
Source of Fuel: In-house
Annual Biomass Fuel Consumed:
Back-up Fuel: Propane
End Use(s): Dry kiln
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 55,000 lbs/hr @ _____ psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr):
Steam: 25,000 lbs/hr @ _____ psig
Electrical Generation (MW):
Type of Combuster/Furnace:
Manufacturer:
Type of Boiler: Water tube
Boiler Manufacturer: Riley Stoker
Type of Pollution Control: Wet scrubber
Reason for Using Wood Fuel: Cost, availability

Champion International

Drawer A
Morton, Washington 98356
Phone: (206) 496-6333
Contact:

Type of Business: Lumber, veneer
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 11,435 units
Back-up Fuel: None
End Use(s): Dry kilns, hot water vats
Plant Design Capacity: 20,000
Heat (million Btu/hr): 23.1
Steam: 20,000 lbs/hr @ 125 psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr): 21.2
Steam: 18,333 lbs/hr @ 125 psig
Electrical Generation (MW): None
Type of Combuster/Furnace: Dutch oven
Manufacturer: Zinda
Type of Boiler: Double drum, water tube,
type RO
Boiler Manufacturer: Riley
Type of Pollution Control: Ash separator,
Lear Sigler Monitor
Reason for Using Wood Fuel: Economics

Colville Indian Precision Pine Company

P.O. Box 3293
Omak, Washington 98841
Phone: (509) 826-1921
Contact: Dan Brudevold

Type of Business: Lumber
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 21,420
BDT
Back-up Fuel: None
End Use(s): Dry kilns
Plant Design Capacity:
Heat (million Btu/hr):
Steam: _____ lbs/hr @ _____ psig
Electrical Generation (MW):

Average Plant Output:
Heat (million Btu/hr):
Steam: 21,000 lbs/hr @ _____ psig
Electrical Generation (MW):

Type of Combuster/Furnace:
Manufacturer: Wellons
Type of Boiler: 20,000 lbs/hr single cell
Boiler Manufacturer: Wellons
Type of Pollution Control: Dry scrubber
Reason for Using Wood Fuel: Economics

Coastcraft, Incorporated

1002 E "F" Street
Tacoma, WA 98421
Phone: (206) 272-1154
Contact: Bill Rigby

Type of Business: Woodwork, windows,
doors
Type of Biomass Fuel: Mill residues,
sawdust
Source of Fuel: In-house
Annual Biomass Fuel Consumed:
Back-up Fuel: None
End Use(s): Dry kiln & heating
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 500 lbs/hr @ _____ psig
Electrical Generation (MW):

Average Plant Output:
Heat (million Btu/hr):
Steam: _____ lbs/hr @ _____ psig
Electrical Generation (MW):

Type of Combuster/Furnace:
Manufacturer:
Type of Boiler: Fire tube
Boiler Manufacturer:
Type of Pollution Control: None
Reason for Using Wood Fuel: By-product

Cowlitz Stud Company

P.O. Box 219
Randle, WA 98377
Phone: (206) 497-5030
Contact: Lloyd Cook or Charlie Allen

Type of Business: Lumber
Type of Biomass Fuel: Hog fuel

Source of Fuel: In-house
Annual Biomass Fuel Consumed:
Back-up Fuel: None
End Use(s): Dry kilns
Plant Design Capacity:
Heat (million Btu/hr):
Steam : 25,000 lbs/hr (Randle)
40,000 lbs/hr (Morton) @ 300 psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr):
Steam: 16,250 lbs/hr (Randle); 26,000 lbs/hr
(Morton) both @ 300 psig
Electrical Generation (MW): None
Type of Combuster/Furnace:
Manufacturer:
Type of Boiler: Water tube and fire tube
Boiler Manufacturer: Seattle
Type of Pollution Control: Water scrubber
Reason for Using Wood Fuel: Economics

Dalshowa America

P.O. Box 271
Port Angeles, WA 98362
Phone: (206) 457-4474
Contact: T. Allen

Type of Business: Pulp and paperboard
Type of Biomass Fuel: Hog fuel
Source of Fuel: Purchased
Annual Biomass Fuel Consumed: 53,000
BDUs
Back-up Fuel: No. 6 fuel oil
End Use(s): Process steam, drying
Plant Design Capacity: 1 hog fuel boiler
Heat (million Btu/hr):
Steam: 105,000 lbs/hr @ 255 psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr):
Steam: 75,000 lbs/hr @ 255 psig
Electrical Generation (MW): None
Type of Combuster/Furnace: Spreader stoker
Manufacturer: Combustion Engineering
Type of Boiler: Model VU-40
Boiler Manufacturer: Combustion Engineering
Type of Pollution Control: Venturi Scrubber
Reason for Using Wood Fuel: Economics

E. A. Nord Company

300 W Marine Drive
Everett, WA 98201
Phone: (206) 259-9292, ext. 445
Contact: Ted Davis

Type of Business: Doors
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 10,000
tons/year
Back-up Fuel: None
End Use(s): Dry kiln and slicer tank
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 55,000 lbs/hr @ _____ psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr):
Steam: 15,000 lbs/hr @ _____ psig
Electrical Generation (MW):
Type of Combuster/Furnace:
Manufacturer:
Type of Boiler: Fire tube
Boiler Manufacturer: Wyatt Kipper
Type of Pollution Control: Multi-clone
Reason for Using Wood Fuel:

Fort Vancouver Plywood

P.O. Box 289
Vancouver WA 98660
Phone: (206) 694-3368
Contact: Duane Grover

Type of Business: Plywood
Type of Biomass Fuel: Hog fuel, sawdust
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 35,000
units
Back-up Fuel: None
End Use(s): Process heat
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 75,000 lbs/hr @ 300 psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr):
Steam: 45,000 lbs/hr @ 290 psig
Electrical Generation (MW): None

Type of Combuster/Furnace: None
Manufacturer:
Type of Boiler: Hog fuel fired, water tube
Boiler Manufacturer: Kipper & Sons
Type of Pollution Control: Wet scrubber
Reason for Using Wood Fuel: By-product of manufacturing

Fred Tebb & Sons, Incorporated

1906 Mall Street
Tacoma, WA 98421
Phone: (206) 272-4107
Contact: Charles Hoffman

Type of Business: Remanufacture of lumber products

Type of Biomass Fuel: Sawdust

Source of Fuel: In-house

Annual Biomass Fuel Consumed: 219 tons

Back-up Fuel: Natural gas, oil

End Use(s): Drying of lumber

Plant Design Capacity:

Heat (million Btu/hr):

Steam: 15,000 lbs/hr @ 10 psig

Electrical Generation (MW):

Average Plant Output:

Heat (million Btu/hr):

Steam: 15,000 lbs/hr @ 10 psig

Electrical Generation (MW):

Type of Combuster/Furnace: Oil, gas, wood

Manufacturer: Rayburn

Type of Boiler: Fire tube

Boiler Manufacturer: Cleaver

Type of Pollution Control: Baghouse

Reason for Using Wood Fuel: Economics

Georgia-Pacific Corporation

P.O. Box 1236
Bellingham, WA 98225
Phone: (206) 733-4410
Contact: E. H. Dahlgren

Type of Business: Pulp and paper

Type of Biomass Fuel: Hog fuel

Source of Fuel: Purchased & generated

Annual Biomass Fuel Consumed: 157,000 bone dry tons

Back-up Fuel: Natural gas/No. 6 oil

End Use(s): Process steam, drying

Plant Design Capacity:

Heat (million Btu/hr): 232

Steam: 220,000 lbs/hr @ 200 psig

Electrical Generation (MW): None

Average Plant Output:

Heat (million Btu/hr): 185

Steam: 175,000 lbs/hr @ 175 psig

Electrical Generation (MW): None

Type of Combustion/Furnace: Dutch oven boilers

Manufacturer: Babcock & Wilcox

Type of Boiler: Sterling

Boiler Manufacturer: Babcock & Wilcox

Type of Pollution Control: Baghouse

Reason for Using Wood Fuel: Economics

Goodyear Nelson Hardwood Lumber Company, Incorporated

1215 Highway 9 S
Sedro Woolley, WA 98284
Phone: (206) 856-0816
Contact: Rod Remington

Type of Business: Hardwood lumber

Type of Biomass Fuel: Hog fuel and shavings

Source of Fuel: Western hardwood residue and surfacing

Annual Biomass Fuel Consumed:

Back-up Fuel:

End Use(s): Steam for dry kilns

Plant Design Capacity:

Heat (million Btu/hr):

Steam: 25,000 lbs/hr @ 110 psig

Electrical Generation (MW): N/A

Average Plant Output:

Heat (million Btu/hr):

Steam: 19,500 lbs/hr @ 110 psig

Electrical Generation (MW): None

Type of Combuster/Furnace:

Manufacturer: G&S Retrofit Auto Mini-Stoker System

Type of Boiler: Fire tube

Boiler Manufacturer: Brownell

Type of Pollution Control: None

Reason for Using Wood Fuel: Availability

Hardel Mutual Plywood

1515 West Bay Drive
Olympia, WA 98502
Phone: (206) 754-6030
Contact: Vic Durham

Type of Business: Plywood
Type of Biomass Fuel: Sander dust & hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed:
Back-up Fuel: Natural gas
End Use(s): Dryers and presses
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 28,000 lbs/hr @ 250 psig
Electrical Generation (MW):
Average Plant Output:
Heat (million Btu/hr)
Steam: 25,000 lbs/hr @ _____ psig
Electrical Generation (MW):
Type of Combuster/Furnace: Suspension burner
Manufacturer: Coen
Type of Boiler: Fire tube
Boiler Manufacturer: Pacific Marion
Type of Pollution Control: Joy multicone
Reason for Using Wood Fuel:

ITT Rayonier, Incorporated - Grays Harbor Division

23rd and Railroad Streets
Hoquiam, WA 98550
Phone: (206) 532-1410

Type of Business: Pulp
Type of Biomass Fuel: Hog fuel (wood refuse, bark)
Source of Fuel: Area sawmills and chip facilities
Annual Biomass Fuel Consumed: 200,000 bone dry metric tons
Back-up Fuel:
End Use(s):
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 325,000 lbs/hr @ 350 psig
Electrical Generation (MW): 0

Average Plant Output:
Heat (million Btu/hr):
Steam: 300,000 lbs/hr @ _____ psig
Electrical Generation (MW):
Type of Combuster/Furnace: 2 Hog fuel boilers
Manufacturer: Riley and Bomstead Wolford
Type of Boiler:
Boiler Manufacturer:
Type of Pollution Control: Fly ash multicones and wet scrubbers
Reason for Using Wood Fuel:

ITT Rayonier, Incorporated

P.O. Box 191
Port Angeles, WA 98362
Phone: (206) 457-3391
Contact: D. E. Collings

Type of Business: Pulp
Type of Biomass Fuel: Hog fuel, primary & secondary sludge mix
Source of Fuel: Purchased and produced
Annual Biomass Fuel Consumed: 84,000 bone dry metric tons
Back-up Fuel: Fuel oil
End Use(s): Process steam, dryers
Plant Design Capacity:
Heat (million Btu/hr): 290
Steam: 200,000 lbs/hr @ 425 psig
Electrical Generation (MW): 12.0
Average Plant Output:
Heat (million Btu/hr): 254
Steam: _____ lbs/hr @ 425 psig
Electrical Generation (MW): 2.7
Type of Combuster/Furnace:
Manufacturer: Bumstead Woolford
Type of Boiler: Pin hole stationary grate
Boiler Manufacturer: Riley
Type of Pollution Control: Barron Cinder Collectors and Combustion Power Gravel Scrubbers
Reason for Using Wood Fuel: By-product of pulp production

James River

NE Fourth & Adams Street
Camas, WA 98607
Phone: (206) 834-8161
Contact: W. W. Vautzeldfen

Type of Business: Pulp and paperboard
Type of Biomass Fuel: Hog fuel
Source of Fuel: Purchased
Annual Biomass Fuel Consumed: 20 MM
Btu/hr.

Back-up Fuel: Gas/oil

End Use(s): Process steam, dryers

Plant Design Capacity:

Heat (million Btu/hr): 138
Steam: 130,000 lbs/hr @ 400 psig
Electrical Generation (MW): 9

Average Plant Output:

Heat (million Btu/hr): 84
Steam: 80,000 lbs/hr @ 400 psig
Electrical Generation (MW): 7

Type of Combuster/Furnace: Dutch oven

Manufacturer: Puget Sound Machinery
Depot (PSMD)

Type of Boiler: PSMD

Boiler Manufacturer: PSMD

Type of Pollution Control: Centricleaner

Reason for Using Wood Fuel: Cost

Jeld-Wen Fiber of Washington

Corner of Wesley & Fort Roads
White Swan, WA 98952
Phone: (509) 874-2255
Contact: Tom Wilson

Type of Business: Fiberboard doorskins

Type of Biomass Fuel: Wood

Source of Fuel: Plant waste

Annual Biomass Fuel Consumed: 10,000 -
15,000 tons

Back-up Fuel:

End Use(s): Plant space heat, process heat

Plant Design Capacity:

Heat (million Btu/hr):
Steam: 30,000 lbs/hr @ 200 psig
Electrical Generation (MW): None

Average Plant Output:

Heat (million Btu/hr):
Steam: 13,000 - 17,000 lbs/hr @ 200 psig
Electrical Generation (MW): None

Type of Combuster/Furnace: 2 cell forced
draft

Manufacturer: Wellons

Type of Boiler: Water tube

Boiler Manufacturer: Nebraska

Type of Pollution Control: Mechanical, multi-
cone scrubber

Reason for Using Wood Fuel: Availability of
wood waste

Kinnear of Washington

2001 Industrial Drive
Centralia, WA 98531
Phone: (206) 736-7651
Contact: Greg Penley

Type of Business: Doors, mouldings

Type of Biomass Fuel: Mill residues

Source of Fuel: In-house

Annual Biomass Fuel Consumed: 1,100 tons

Back-up Fuel: None

End Use(s): Drying lumber

Plant Design Capacity:

Heat (million Btu/hr): Unknown
Steam: 10,300 lbs/hr @ 100 psig
Electrical Generation (MW): None

Average Plant Output:

Heat (million Btu/hr): Unknown
Steam: 8,250 lbs/hr @ 80 psig
Electrical Generation (MW): None

Type of Combuster/Furnace: Firebox

Manufacturer: Frye Shaving Feeder

Type of Boiler: Fire tube

Boiler Manufacturer: Kewanee #590

Type of Pollution Control: Wet scrubber

Reason for Using Wood Fuel: Available/low
cost

K-Ply Inc.

439 Marine Drive
Port Angeles, WA 98362
Phone: (206) 457-4421
Contact: John Doane

Type of Business: Plywood
Type of Biomass Fuel: In-house
Source of Fuel: Bark, veneer trim, plywood trim
Annual Biomass Fuel Consumed: 24,000 BDTs (estimate)
Back-up Fuel: None
End Use(s): Drying, veneer
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 50,000 lbs/hr @ 150 psig (2 boilers 25,000 hr ea.)
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr):
Steam: 40,000 lbs/hr @ 140 psig
Electrical Generation (MW): None
Type of Combuster/Furnace:
Manufacturer: Riley
Type of Boiler: "RO"
Boiler Manufacturer: Riley
Type of Pollution Control: Wet E.S.P.
Reason for Using Wood Fuel: Availability

Layman's Lumber Company

15930 Highway 12
Naches, WA 98937
Phone: (509) 653-2221
Contact: George Layman

Type of Business: Lumber
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 3,000 tons
Back-up Fuel:
End Use(s): Dry kilns
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 17,250 lbs/hr @ 15 psig
Electrical Generation (MW):

Average Plant Output:
Heat (million Btu/hr):
Steam: 15,000 lbs/hr @ 15 psig
Electrical Generation (MW):

Type of Combuster/Furnace:
Manufacturer: Wellons
Type of Boiler: Fire tube
Boiler Manufacturer:
Type of Pollution Control: Recycle
Reason for Using Wood Fuel:

Longview Fibre Company

P.O. Box 3000
Longview, WA 98632
Phone: (206) 425-1550
Contact: R. W. Williams

Type of Business: Pulp and paperboard
Type of Biomass Fuel: Hog fuel
Source of Fuel: Purchased
Annual Biomass Fuel Consumed: 232,812 dry tons
Back-up Fuel: Fuel oil, natural gas
End Use(s): Process steam, dryers
Plant Design Capacity: 3 hog fuel boilers
Heat (million Btu/hr): 1,160
Steam: 850,000 lbs/hr @ 800 psig (2 boilers @ 275,000, 1 boiler @ 300,000)
Electrical Generation (MW): 30 (Hog fuel portion of total)
Average Plant Output: Calendar 1989 (hog fuel 38% fuel used in above boilers)
Heat (million Btu/hr): 265 (hog fuel portion) 696 total
Steam: 196,296 lbs/hr @ 800 psig (hog fuel portion)
Electrical Generation (MW): 23 (hog fuel portion)
Type of Combuster/Furnace: N/A
Manufacturer: N/A
Type of Boiler: 2 Dutch ovens, 1 Stoker-Traveling Grate
Boiler Manufacturer: 2 Babcock & Wilson, 1 Combustion Engineering
Type of Pollution Control: Multicone & wet scrubbers
Reason for Using Wood Fuel: Lowest cost fuel

Louisiana Pacific Company

P.O. Box 1575
Walla Walla, WA 98362
Phone: (509) 529-0200
Contact:

Type of Business: Lumber
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 12,000 tons
Back-up Fuel: 0
End Use(s): Dry kilns
Plant Design Capacity:
Heat (million Btu/hr): 21,000,000
Steam: 20 to 25,000 lbs/hr @ _____ psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr): 14,060,000
Steam: 13,400 lbs/hr @ _____ psig
Electrical Generation (MW): None
Type of Combuster/Furnace:
Manufacturer: Seattle Boiler Works
Type of Boiler: Dutch oven 84-20 hrt 125 lbs.
Boiler Manufacturer: Seattle Boiler Works
Type of Pollution Control: Proper fuel & air ratio
Reason for Using Wood Fuel: Cost

Mt. Baker Plywood

P.O. Box 997
Bellingham, WA 98225
Phone: (206) 733-3960
Contact: Harley Willis

Type of Business: Plywood
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed:
Back-up Fuel: Natural gas
End Use(s): Drying and pressing
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 35,000 lbs/hr @ _____ psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr):
Steam: 31,500 lbs/hr @ _____ psig
Electrical Generation (MW):

Type of Combuster/Furnace:
Manufacturer:
Type of Boiler:
Boiler Manufacturer:
Type of Pollution Control:
Reason for Using Wood Fuel:

Northwest Hardwoods

20015 - 67th NE
Arlington, WA 98223
Phone: (206) 435-8502
Contact: Roy Popper

Type of Business: Lumber
Type of Biomass Fuel: Sander dust
Source of Fuel: In-house
Annual Biomass Fuel Consumed: Unknown
Back-up Fuel: Natural gas
End Use(s): Dry kilns
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 18,000 lbs/hr @ 22 psig
Electrical Generation (MW):
Average Plant Output:
Heat (million Btu/hr):
Steam: 18,000 lbs/hr @ 22 psig
Electrical Generation (MW):
Type of Combuster/Furnace:
Manufacturer:
Type of Boiler: Fire tube
Boiler Manufacturer: Cleaver Brooks
Type of Pollution Control: 3 cell bag house
Reason for Using Wood Fuel: It is produced in our lumber finishing process

Oeser Company, The

730 Marine Drive
Bellingham, WA 98225
Phone: (206) 733-5184
Contact: Ronald S. Durbin, Plant Manager

Type of Business: Wood treating
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 400 tons (est.)
Back-up Fuel: Natural gas

End Use(s): Steam heat for treating processes

Plant Design Capacity:

Heat (million Btu/hr): 250 - 400 bhp

Steam: _____ lbs/hr @ 120 psig

Electrical Generation (MW): None

Average Plant Output:

Heat (million Btu/hr): 150 bhp

Steam: _____ lbs/hr @ 120 psig

Electrical Generation (MW): None

Type of Combuster Furnace: Dutch oven

Manufacturer: Constructed on sight by plant personnel

Type of Boiler: Water tube

Boiler Manufacturer: Sterling

Type of Pollution Control: Visual at stack/mix with natural gas

Reason for Using Wood Fuel: Because it is a manufacturing by-product, economical, a reliable supply, and otherwise wasted if not used for fuel

Omak Wood Products, Incorporated

Route 2, Box 54

Omak, WA 98841

Phone: (509) 826-1460, ext. 238

Contact: W. C. Dufton, P.E., Engineering Manager

Type of Business: Lumber and plywood

Type of Biomass Fuel: Hog fuel, sawdust

Source of Fuel: In-house

Annual Biomass Fuel Consumed: 175,200 units

Back-up Fuel: Natural gas

End Use(s): Dry kilns and veneer presses, power generation

Plant Design Capacity:

Heat (million Btu/hr):

Steam: 240,000 lbs/hr @ 675 psig

Electrical Generation (MW): 7.5

Average Plant Output:

Heat (million Btu/hr):

Steam: 160,000 lbs/hr @ 600 psig

Electrical Generation (MW): 7.5

Type of Combuster/Furnace: 2 air suspension type burners

Manufacturer: Riley Boiler

Type of Boiler: Water tube

Boiler Manufacturer: Riley Stoker, 2 units

Type of Pollution Control: Wet scrubber

Reason for Using Wood Fuel: By-product of production, disposes production residues

Pacific Wood Treating

111 W Division

Ridgefield, WA 98642

Phone: (206) 887-3562

Contact: Al Dwyer

Type of Business: Treated lumber & re-manufacturing in wood products

Type of Biomass Fuel: Hog fuel

Source of Fuel: In-house and other wood fabrication industries

Annual Biomass Fuel Consumed: 12,500 units

Back-up Fuel: Diesel and natural gas

End Use(s): Process heat

Plant Design Capacity:

Heat (million Btu/hr):

Steam: 40,000 lbs/hr @ _____ psig

Electrical Generation (MW): None

Average Plant Output:

Heat (million Btu/hr):

Steam: 20,000 lbs/hr @ _____ psig

Electrical Generation (MW): None

Type of Combuster/Furnace:

Manufacturer: Wellons

Type of Boiler: Trame water tube

Boiler Manufacturer: Trame

Type of Pollution Control: Baghouse

Reason for Using Wood Fuel: Price

Plum Creek Manufacturing, Incorporated

Arden Lumber Operations

634 Highway 395 S

Colville, WA 99114

Phone: (509) 684-5084

Contact: John Chopot

Type of Business: Lumber

Type of Biomass Fuel: Hog fuel

Source of Fuel: In-house, sawmill

Annual Biomass Fuel Consumed:

Back-up Fuel: None

End Use(s): Dry kilns
 Plant Design Capacity:
 Heat (million Btu/hr):
 Steam: _____ lbs/hr @ 150 psig
 Electrical Generation (MW): None
 Average Plant Output:
 Heat (million Btu/hr):
 Steam: _____ lbs/hr @ _____ psig
 Electrical Generation (MW): None
 Type of Combustion/Furnace:
 Manufacturer: Kipper & Son
 Type of Boiler: Water tube
 Boiler Manufacturer: Kipper & Son
 Type of Pollution Control: Wet scrubber
 Reason for Using Wood Fuel: Availability cost

Port Townsend Paper

P.O. Box 3170
 Port Townsend, WA 98368
 Phone: (206) 385-3170
 Contact: Dick D'Agostino

Type of Business: Pulp and paper
 Type of Biomass Fuel: Hog fuel
 Source of Fuel: Purchased
 Annual Biomass Fuel Consumed: 77,713 dry tons
 Back-up Fuel: Residual oil
 End Use(s): Process steam and dryers
 Plant Design Capacity:
 Heat (million Btu/hr):
 Steam: 250,000 lbs/hr @ 600 psig
 Electrical Generation (MW): 18.5
 Average Plant Output:
 Heat (million Btu/hr):
 Steam: 133,000 lbs/hr @ 400 psig
 Electrical Generation (MW): 6.1
 Type of Combustion/Furnace:
 Manufacturer: Combustion Engineering
 Type of Boiler: VU 40
 Boiler Manufacturer:
 Type of Pollution Control: Mechanical collectors plus wet scrubber
 Reason for Using Wood Fuel: Cost

Puget Sound Plywood

230 F Street
 Tacoma, WA 98421
 Phone: (206) 627-4111
 Contact:

Type of Business: Plywood
 Type of Biomass Fuel: Sawdust, mill residues
 Source of Fuel: In-house & purchased
 Annual Biomass Fuel Consumed: 17,000 tons
 Back-up Fuel: Natural gas
 End Use(s): Dryers
 Plant Design Capacity:
 Heat (million Btu/hr):
 Steam: 500 hp @ _____ psig
 Electrical Generation (MW):
 Average Plant Output:
 Heat (million Btu/hr): 35
 Steam: _____ lbs/hr @ 180 psig
 Electrical Generation (MW):
 Type of Combustion/Furnace: Dutch oven
 Manufacturer: Sterling
 Type of Boiler: Water tube
 Boiler Manufacturer: Sterling
 Type of Pollution Control: Joy Multicone
 Reason for Using Wood Fuel: Economics

San Poll Lumber Company

P.O. Box 3577
 Republic, WA 99166
 Phone: (509) _____
 Contact:

Type of Business: Lumber
 Type of Biomass Fuel: Hog fuel
 Source of Fuel: In-house
 Annual Biomass Fuel Consumed:
 Back-up Fuel:
 End Use(s): Dry kiln
 Plant Design Capacity:
 Heat (million Btu/hr):
 Steam: 50,000 lbs/hr @ _____ psig
 Electrical Generation (MW):
 Average Plant Output:
 Heat (million Btu/hr):
 Steam: 30,000 lbs/hr @ _____ psig
 Electrical Generation (MW):

Type of Combuster/Furnace: 1D-FD
Manufacturer: Wellons
Type of Boiler: Woodwaste fired (bark, etc.)
Boiler Manufacturer: Nebraska
Type of Pollution Control: 8 - 10 CO₂
Reason for Using Wood Fuel: On plant wood waste

Scott Paper

2600 Federal Avenue
Everett, WA 98220
Phone: (206) 259-7333
Contact: Alex M. Hood

Type of Business: Pulp and paper
Type of Biomass Fuel: Hog fuel
Source of Fuel: Purchased and In-house
Annual Biomass Fuel Consumed: 140,000 units
Back-up Fuel: #6 oil
End Use(s): Process steam, drying
Plant Design Capacity: 11 boilers of which 5 are hog fuel
Heat (million Btu/hr):
Steam: 5 @ 50,000 lbs/hr @ _____ psig (hog fuel), 1 @ 120,000 lbs/hr, 3 @ 150,000 lbs/hr, 1 @ 380,000 lbs/hr
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr):
Steam: 650,000 lbs/hr @ 225 & 300 psig
Electrical Generation (MW): None
Type of Combuster/Furnace: Dutch oven
Manufacturer: Puget Sound Machinery Depot, B&W Modification
Type of Boiler: 4 drum Stirling
Boiler Manufacturer: Same as above
Type of Pollution Control: Baghouse
Reason for Using Wood Fuel: Economics

Simpson Door Company

McCleary Operations
McCleary, WA 98557
Phone: (206) 495-3291
Contact: Robert K. Horton

Type of Business: Doors
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house

Annual Biomass Fuel Consumed: 20,400 units

Back-up Fuel: Purchased hog fuel
End Use(s): Steam for wood drying and heating

Plant Design Capacity:
Heat (million Btu/hr): N/A
Steam: 45,000 lbs/hr @ 250 psig;
Electrical Generation (MW): None

Average Plant Output:
Heat (million Btu/hr): N/A
Steam: 25,000 lbs/hr @ 150 psig
Electrical Generation (MW): None

Type of Combuster/Furnace: Dutch oven
Manufacturer: Batenhauser

Type of Boiler: Water tube - 3 pass
Boiler Manufacturer: Batenhauser
Type of Pollution Control: All dry fuel -
Baghouses on fuel handling

Reason for Using Wood Fuel: By product of manufacturing doors

Simpson Tacoma Kraft Company

801 Portland Avenue
Tacoma, WA 98421
Phone: (206) 572-2150 or 596-0257
Contact: David McEntee

Type of Business: Pulp and paper
Type of Biomass Fuel: Hog fuel
Source of Fuel: Purchased
Annual Biomass Fuel Consumed: 182,000 Units (approx. equal to 174,000 BDT)

Back-up Fuel: Bunker C
End Use(s): Process steam, dryers
Plant Design Capacity: 1 hog fuel
Heat (million Btu/hr): 254
Steam: 225,000 lbs/hr @ 425 psig
Electrical Generation (MW): None

Average Plant Output:
Heat (million Btu/hr): 231,000
Steam: 205,000 lbs/hr @ 425 psig
Electrical Generation (MW): None

Type of Combuster/Furnace: Distributor/Detroit
Hyord-Grate

Manufacturer: Detroit, Stoker
Type of Boiler: 2 drum natural circulation
Boiler Manufacturer: Riley

Type of Pollution Control: Electro Static
Precipitator
Reason for Using Wood Fuel: Economics

Simpson Timber Company

Waterfront Street
Shelton, WA 98584
Phone: (206) 426-3381
Contact: Charlie Swenson

Type of Business: Lumber and plywood
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed:
Back-up Fuel: None
End Use(s): Drying, lumber and plywood
veneers
Plant Design Capacity: 6 fuel cells
Heat (million Btu/hr): 140, approx.
Steam: 140,000 lbs/hr @ 300 psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr): 130 approx.
Steam: 130,000 lbs/hr @ 300 psig
Electrical Generation (MW): None
Type of Combuster/Furnace: Fuel cell
Manufacturer: Wellons
Type of Boiler: Water tube
Boiler Manufacturer: Wellons
Type of Pollution Control: Two stage combustion plus multi-cones
Reason for Using Wood Fuel: Lowest cost, in-house fuel

Smith Street Mill, Incorporated

3600 Smith Street
Everett, WA 98201
Phone: (206) 252-7179
Contact: Bob Buse

Type of Business: Alder sawmill and planing mill
Type of Biomass Fuel: Alder sawdust and dry shavings
Source of Fuel: Sawmill
Annual Biomass Fuel Consumed:
Back-up Fuel: None
End Use(s): Heat dry kilns

Plant Design Capacity:
Heat (million Btu/hr):
Steam: _____ lbs/hr @ 15 psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr):
Steam: _____ lbs/hr @ 15 psig
Electrical Generation (MW): None
Type of Combuster/Furnace: Dutch oven
Manufacturer: In-house
Type of Boiler: Low pressure, 15 lbs.
Boiler Manufacturer: Brownell
Type of Pollution Control:
Reason for Using Wood Fuel: Economics

Stevenson Co-Ply, Incorporated

P.O. Box F
Stevenson, WA 98648
Phone: (509) 427-5620
Contact: Pat Sweeney

Type of Business: Plywood
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 11,350 units
Back-up Fuel: None
End Use(s): Drying
Plant Design Capacity:
Heat (million Btu/hr): None
Steam: 40,000 lbs/hr @ 250 psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr): None
Steam: 35,000 lbs/hr @ 250 psig
Electrical Generation (MW): None
Type of Combuster/Furnace:
Manufacturer:
Type of Boiler: Dutch oven
Boiler Manufacturer: Wyatt & Klipper
Type of Pollution Control:
Reason for Using Wood Fuel: Availability, cost

Strauser Manufacturing Company

2921 Melrose Street
Walla Walla, Washington 99362
Phone: (509) 529-6284
Contact: Beverly Strauser

Type of Business: Lincoln Logs
Type of Biomass Fuel: Hogfuel, sawdust, shavings
Back-up Fuel:
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 3000 dry tons
End Use(s): Space and process heat
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 6,000 lbs/hr @ 250 psig
Electrical Generation (MW):
Average Plant Output:
Heat (million Btu/hr):
Steam: 4,800 lbs @ _____ psig
Electrical Generation (MW):
Type of Combuster/Furnace: Suspension Gasifier
Manufacturer:
Type of Boiler: 250 hp Cleaver Brooks
Manufacturer:
Type of Pollution Control: Flash collector
Reason for Use : Economics

Summit Timber Power House

29917 Bennittville Store Road
Darrington, WA 98241
Phone: (206) 259-4185, ext. 121
Contact: Ed McDaniel, Power House Superintendent

Type of Business: Wood Products
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 36,500 tons
Back-up Fuel: Bunker C Fossil (oil)
End Use(s):
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 45,000 lbs/hr @ 150 psig
Electrical Generation (MW): None

Average Plant Output:
Heat (million Btu/hr):
Steam: lbs/hr @ _____ psig
Electrical Generation (MW): None

Type of Combuster/Furnace:
Manufacturer: Puget Sound Boiler
Type of Boiler: Water tube
Boiler Manufacturer:
Type of Pollution Control: Broslove Separator
Reason for Using Wood Fuel: Cut fuel costs, Incinerate wood waste

Vaagen Brothers Lumber, Incorporated

565 W Fifth
Colville, WA 99114
Phone: (509) 684-5071
Contact: Jim Winniges, Supt.

Type of Business: Lumber
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 25,550 tons
Back-up Fuel: No
End Use(s): Dry kilns, generator
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 60,000 lbs/hr @ 510 psig
Electrical Generation (MW): 4,000 kW
Average Plant Output:
Heat (million Btu/hr):
Steam: 60,000 lbs/hr @ 510 psig
Electrical Generation (MW): 4,000 kW
Type of Combuster/Furnace: Fuel cell 4 cells
Manufacturer: Wellons
Type of Boiler: Water tube
Boiler Manufacturer: Nebraska
Type of Pollution Control: Multiclones
Reason for Using Wood Fuel: Economics

Vaagen Brothers Lumber, Incorporated

P.O. Box 257
Ione, WA 99139
Phone: (509) 442-3511
Contact: Don Curry, Plant Manager

Type of Business: Lumber
Type of Biomass Fuel: Hog Fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed: 9,490 tons
Back-up Fuel:
End Use(s): Dry kilns
Plant Design Capacity:
Heat (million Btu/hr): 12.5
Steam: 40,000 lbs/hr @ 150 psig
Electrical Generation (MW):

Average Plant Output:
Heat (million Btu/hr):
Steam: 30,000 lbs/hr @ 150 psig
Electrical Generation (MW):

Type of Combuster/Furnace: Radiant furnace
heating surface
Manufacturer: Nebraska Boiler Company
Type of Boiler: Water tube
Boiler Manufacturer: Nebraska Boiler Company
Type of Pollution Control: Cleveland Controls
Reason for Using Wood Fuel: Cost efficient

**West Coast Forest Products,
Incorporated**

19406 68th Drive NE
P.O. Box 365
Arlington, WA 98223
Phone: (206) 435-2175
Contact: Jim Reece

Type of Business: Lumber remanufacturer
Type of Biomass Fuel: Shavings
Source of Fuel: Planer
Annual Biomass Fuel Consumed: 4,720 dry
tons
Back-up Fuel: None
End Use(s): Dry kilns
Plant Design Capacity:
Heat (million Btu/hr): 22.5
Steam: _____ lbs/hr @ _____ psig
Electrical Generation (MW): N/A

Average Plant Output:
Heat (million Btu/hr):
Steam: _____ lbs/hr @ 100 psig
Electrical Generation (MW): None

Type of Combuster/Furnace:
Manufacturer:
Type of Boiler: Fire tube
Boiler Manufacturer: Titusville
Type of Pollution Control: Mikropul
baghouse
Reason for Using Wood Fuel: Cost and
availability

Weyerhaeuser Company

P.O. Box 1000
Cosmopolis, WA 98537
Phone: (206) 532-7110
Contact: Paul W. Kelso, P&R Superintendent

Type of Business: Pulp
Type of Biomass Fuel: Hog fuel
Source of Fuel: Purchased & In-house
generated
Annual Biomass Fuel Consumed: 80,000
BDT
Back-up Fuel: No. 6 fuel oil
End Use(s): Process steam

Plant Design Capacity:
Heat (million Btu/hr): 220
Steam: 160,000 lbs/hr @ 850 psig
Electrical Generation (MW): 15.0

Average Plant Output:
Heat (million Btu/hr): 138
Steam: 100,000 lbs/hr @ 850 psig
Electrical Generation (MW): 11

Type of Combuster/Furnace: Fixed, water
cooled, pin hole grate
Manufacturer: Babcox & Wilcox
Type of Boiler: Two Drum Sterling
Boiler Manufacturer: Babcox & Wilcox
Type of Pollution Control: Venturi wet scrub-
ber
& multicones
Reason for Using Wood Fuel: By-product of
company-owned facilities

Weyerhaeuser Company

P.O. Box 188
Longview, WA 98632
Phone: (206) 425-2150
Contact: Bob Lusk

Type of Business: Pulp and paperboard
Type of Biomass Fuel: Hog fuel
Source of Fuel: Purchased and in-house
Annual Biomass Fuel Consumed: 500,000 BDT
Back-up Fuel: Coal, oil, natural gas
End Use(s): Process steam, dryers
Plant Design Capacity: 7 hog fuel
Heat (million Btu/hr): 1,180
Steam: 550,000 lbs/hr @ 1,250 psi & 300,000
lbs/hr @ 300 psi
Electrical Generation (MW): 30 (hog fuel portion
of total)
Average Plant Output:
Heat (million Btu/hr): 1,000
Steam: 500,000 lbs/hr @ 1,250 psi & 200,000
lbs/hr @ 300 psi
Electrical Generation (MW): 30
Type of Combuster/Furnace:
Manufacturer: 6 Erie City, 1 Foster Wheeler
Type of Boiler: Erie City Fixed Grate, Foster
Wheeler Traveling Grate
Boiler Manufacturer:
Type of Pollution Control: Wet Scrubber,
Electrostatic Precipitator
Reason for Using Wood Fuel: By-product of
company mills

Weyerhaeuser Company

P.O. Box 666
Raymond, WA 98577
Phone: (206) 942-2442
Contact: Jerry Dillayou, Plant Engineer

Type of Business: Lumber
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed:
Back-up Fuel: None - propane used to pre-
heat on cold start-up
End Use(s): Dry kilns
Plant Design Capacity:
Heat (million Btu/hr): 70,000,000 (reduced to
55 MM Btu/hr)

Steam: 40,000 lbs/hr @ 150 psig
Electrical Generation (MW): None

Average Plant Output:

Heat (million Btu/hr): 48,000,000 est.
Steam: 37,000 lbs/hr @ _____ psig
Electrical Generation (MW): None

Type of Combuster/Furnace:

Manufacturer: EPI 18 ft. dia. fluid bed burner
(reduced to 16 ft. dia.) built in 1974

Type of Boiler: Combustion Engineering
water tube boiler

Boiler Manufacturer:

Type of Pollution Control: Zurn multicone

Reason for Using Wood Fuel: Cost residual
of lumber plant operation

Weyerhaeuser Company

7001 - 396th Street SE
Snoqualmie Falls, WA 98065
Phone: (206) 888-2511
Contact: Leon Clark, Facility Supervisor

Type of Business: Lumber

Type of Biomass Fuel: Hog fuel

Source of Fuel: In-house

Annual Biomass Fuel Consumed:

Back-up Fuel: Residual oil

End Use(s): Dry kilns

Plant Design Capacity: 2 boilers, 270,000
ppH, saturated steam total

Heat (million Btu/hr):

Steam: 270,000 lbs/hr @ _____ psig

Electrical Generation (MW): None

Average Plant Output:

Heat (million Btu/hr): 247,800 Btu both
boilers

Steam: 128,000 lbs/hr @ _____ psig (both
boilers included)

Electrical Generation (MW): None

Type of Combuster/Furnace: Dutch oven
and spreader stocker

Manufacturer: One 1969 F.E. Riley 250 lbs
sat. steam 150,000 ppH, one 1930 F.E.
PSMD-155 lb sat. steam 120,000 ppH.

Type of Boiler: Water tube

Boiler Manufacturer: Riley

Type of Pollution Control: Combustion Power
Co., Inc. Model DS-800 dry scrubber
Reason for Using Wood Fuel: By-product

W.I. Forest Products

2302 E Mallon
Spokane, WA 99202
Phone: (509) 534-1561
Contact:

Type of Business: Lumber
Type of Biomass Fuel: Hog fuel
Source of Fuel: In-house
Annual Biomass Fuel Consumed: Unknown
Back-up Fuel: Natural Gas
End Use(s): Dry kilns
Plant Design Capacity:
Heat (million Btu/hr):
Steam: 30,000 lbs/hr @ 125 psig
Electrical Generation (MW): None
Average Plant Output:
Heat (million Btu/hr):
Steam: 30,000 lbs/hr @ 125 psig
Electrical Generation (MW): None
Type of Combuster/Furnace:
Manufacturer: Combustion Engineering
Type of Boiler: Sterling 3-drum water tube
Boiler Manufacturer: Combustion Engineering
Type of Pollution Control: Mikro-Pur Baghouse
Reason for Using Wood Fuel: Inexpensive,
readily available

Other Facilities

DeGoede Bulb Farms

409 Mossyrock Road W
Mossyrock, WA 98564
Phone: (206) 983-3773
Contact: Bob DeGoede

Type of Business: Greenhouse and nursery
Type of Biomass Fuel: Mill residue
Source of Fuel: Purchased
Annual Biomass Fuel Consumed: Approx-
imately 65 truck loads (45' vans)
Back-up Fuel: Propane forced air unit heaters
End Use(s): Greenhouse heating
Plant Design Capacity:
Heat (million Btu/hr): 4,500,000 (depending
on fuel moisture content)
Steam: _____ lbs/hr @ _____ psig N/A
Electrical Generation (MW): N/A
Average Plant Output:
Heat (million Btu/hr): 3,000,000 Btu/hr.
Steam: _____ lbs/hr @ _____ psig N/A
Electrical Generation (MW): N/A
Type of Combuster/Furnace: Bio-Combuster
(gasification process)
Manufacturer: Bio-Mass Burner
Type of Boiler: Hot water - 210°F
Boiler Manufacturer: Vaagen Timber
Products
Type of Pollution Control: Gasificaion/cyclone
Reason for Using Wood Fuel: Least cost

Maple Lane School

20311 Old Highway 99 SW
Centralia, WA 98537
Phone: (206) 736-1361
Contact: Lonnie Bauman

Type of Business: School
Type of Biomass Fuel: Wood pellets
Source of Fuel: Purchased, Northwest Pellet
Mills, Manke Fuel Lignetics
Annual Biomass Fuel Consumed: 2,043 tons
Back-up Fuel: Oil, coal, natural gas
End Use(s): Space heat domestic hot water

Plant Design Capacity: 2 boilers at 250 HP each

Heat (million Btu/hr): 17,500,000

Steam: 20,000 lbs/hr @ 100 psig

Electrical Generation (MW): None

Average Plant Output:

Heat (million Btu/hr): 4,197,945

Steam: 16,300 lbs/hr @ 90 psig (winter - 12,000 summer)

Electrical Generation (MW): None

Type of Combuster/Furnace: Underfed stoker

Manufacturer: Combustion Service and Equipment

Type of Boiler: Fire tube

Boiler Manufacturer: Combustion Service and Equipment

Type of Pollution Control: Baghouse

Reason for Using Wood Fuel: Pollution control (air & ash disposal), labor & maintenance costs on fuel conveyor systems

Washington Soldiers Home & Colony

P.O. Box 500

Orting, WA 98360

Phone: (206) 593-2045

Contact: John Buffington

Type of Business: Service

Type of Biomass Fuel: Wood pellets

Source of Fuel: Purchased

Annual Biomass Fuel Consumed: 1,930 tons (back-up fuel)

Back-up Fuel: Biomass (natural gas is the primary fuel)

End Use(s): Space heat and hot water

Plant Design Capacity:

Heat (million Btu/hr):

Steam: 24,500 lbs/hr @ 100 psig

Electrical Generation (MW): None

Average Plant Output:

Heat (million Btu/hr):

Steam: 3,000 lbs/hr @ _____ psig

Electrical Generation (MW): None

Type of Combuster/Furnace: Spreader-Stoker

Manufacturer: Wyatt & Kipper and ONB Tri-Fuel

Type of Boiler: Water tube and fire tube

Boiler Manufacturer:

Type of Pollution Control: Cyclone

Reason for Using Wood Fuel:

Washington State Penitentiary

P.O. Box 520

Walla Walla, WA 99362

Phone: (509) 525-3610

Contact: Jim Blodgett

Type of Business: State Penitentiary

Type of Biomass Fuel: Wood Pellets

Source of Fuel: Purchased, Lignetics of Idaho

Annual Biomass Fuel Consumed: 3,000 dry tons

Back-up Fuel: Natural gas

End Use(s): Space heat, laundry, kitchen

Plant Design Capacity: 3 boilers

Heat (million Btu/hr):

Steam: 75,000 lbs/hr @ 125 psig

Electrical Generation (MW): None

Average Plant Output:

Heat (million Btu/hr)

Steam: 32,000 lbs/hr @ 125 psig October -

April; 10,000 lbs/hr May - September

Electrical Generation (MW): None

Type of Combuster/Furnace: Stoker

Manufacturer: Wyatt & Kipper

Type of Boiler: Water wall

Boiler Manufacturer:

Type of Pollution Control: Multicones

Reason for Using Wood Fuel: Emissions problems with coal

Washington Water Power Company

Kettle Falls, WA 99141

Phone: (509) 738-2449

Contact:

Type of Business: Electric Utility

Type of Biomass Fuel: Hog fuel

Source of Fuel: Purchased mill residue

Annual Biomass Fuel Consumed: 500,000 green tons

Back-up Fuel: Natural gas
End Use(s): Electrical generation

Plant Design Capacity:
Heat (million Btu/hr): N/A
Steam: 415,000 lbs/hr @ 1,500 psig
Electrical Generation (MW): 48 gross

Average Plant Output:
Heat (million Btu/hr): N/A
Steam: 435,000 lbs/hr @ 1,525 psig
Electrical Generation (MW): 50.3

Type of Combuster/Furnace: Spreader stoker,
moving grate

Manufacturer: Combustion Engineering

Type of Boiler: Water tube

Boiler Manufacturer: Combustion Engineering

Type of Pollution Control: ESP and mechanical
collector

Reason for Using Wood Fuel: Availability

Reason for Using Wood Fuel: Emission
problems with coal

Western State Hospital

P.O. Box 94999
Fort Steilacoom, WA 98494
Phone: (206) 756-2519
Contact: Ronald Hansen

Type of Business: State Hospital

Type of Biomass Fuel: Wood Pellets

Source of Fuel: Purchased, Northwest Pellet
Mills

Annual Biomass Fuel Consumed: 12,000 tons

Back-up Fuel: Natural gas

End Use(s): Space heat, kitchen, laundry

Plant Design Capacity: 3 boilers
Heat (million Btu/hr): 28,311,140 - 77,212,200 -
51,474,800
Steam: 22,000; 60,000; 22,000 lbs/hr @ 130
psig
Electrical Generation (MW): None

Average Plant Output:
Heat (million Btu/hr): 64,343,500
Steam: 50,000 lbs/hr @ 120 psig (Fall, Winter,
Spring)
Electrical Generation (MW): None

Type of Combuster/Furnace: Stoker

Manufacturer: Hoffman

Type of Boiler: Water tube

Boiler Manufacturer: Garet & Shater; Wyatt-
Kipper; Puget Sound Machine

Type of Pollution Control: None

Wood Combustion Facilities **Listing Changes from 1987 Edition**

New Listings

Location

Colville Indian Precision Pine Company	Omak
Fred Tebb & Sons, Inc.	Tacoma
Goodyear Nelson Hardwood Lumber Co., Inc.	Sedro Woolley
ITT Rayonier, Inc. - Hoquiam	Hoquiam
Jeld-Wen Fiber of Washington	White Swan
Smith Street Mill, Inc.	Everett
Strauser Manufacturing	Walla Walla
Summit Timber Power House	Darrington
West Coast Forest Products	Arlington
Weyerhaeuser	Cosmopolis

Deletions

Cause

Location

Boise Cascade	Closure	Goldendale
Howard Manufacturing	Switched to Natural Gas	Kent
Lacey Plywood	Closure	Lacey
Paxport Mills, Inc.	Sold	Tacoma
Seattle Door	Sold - New facility does not use biomass	Seattle
W.I. Forest Products	Closure	Cashmere
White Swan Lumber	Closure	White Swan

Facility Name Changes

Former Name

Location

Allen Logging Company	Allen Logging & Vaneer	Forks
Daishowa America	Crown Zellerbach	Port Angeles
James River	Crown Zellerbach	Camas
K-Ply Inc.	Peninsula Plywood Company	Port Angeles
Omak Wood Products, Inc.	Cavenham Forest Industries	Omak
Plum Creek Manufacturing, Inc.	Plum Creek Lumber	Colville

***Ethanol,
Municipal Solid Waste
and
Solid Fuel***

WASHINGTON STATE

ETHANOL, MUNICIPAL SOLID WASTE & SOLID FUEL FACILITIES

SOURCE: WSEO, 1990 Washington State Directory of Biomass Energy Facilities

Washington State Biomass Summary Tables

Summary Table 4

Ethanol Production
Facilities Sorted by Output

<u>Facility Name</u>	<u>City</u>	<u>Plant Capacity Gal./Yr.</u>	<u>Average Plant Output Gal./Yr.</u>	<u>Gross Energy Equivalent Million Btu/Yr.*</u>
Georgia-Pacific Corporation	Bellingham	9,000,000	9,000,000	761,490
Olympia Brewing Company	Olympia	<u>1,000,000</u>	<u>435,000</u>	<u>36,805</u>
Total		10,000,000	9,435,000	798,295

*Based on 84,610 Btu per gallon ethanol output

Summary Table 5

MSW Combustion
Facilities Sorted by MSW Consumption

<u>Facility Name</u>	<u>City</u>	<u>Annual MSW Consumption Tons/Yr.</u>	<u>Average MSW Consumption Tons/Day</u>	<u>Gross Energy Equivalent Million Btu/Yr.*</u>
Tacoma Steam Plant #2	Tacoma	98,000	268	980,000
Skagit Co. Resource Recovery Facility	Mount Vernon	50,000	137	500,000
Thermal Reduction Company	Bellingham	<u>36,500</u>	<u>100</u>	<u>365,000</u>
Total		184,500	505	1,845,000

*Based on annual MSW consumption at 5,000 Btu per pound

Summary Table 6

Solid Fuel Processing
Facilities Sorted by Plant Output

<u>Facility Name</u>	<u>City</u>	<u>Plant Design Capacity Tons/Yr.</u>	<u>Average Plant Output Tons/Yr.</u>	<u>Gross Energy Equivalent Million Btu/Yr.*</u>
Manke Lumber Company	Tacoma	74,880	74,880	1,272,960
Spokane Pres-To-Logs	Spokane	69,000	52,000	884,000
CD Pellet Company	Omak	6,000	6,000	102,000
Wood Pellet Company	Oakville	<u>36,500</u>	<u>3,650</u>	<u>62,050</u>
Total		186,300	135,450	2,321,010

*Based on average plant output at 8,500 Btu per pound

Ethanol Production Facilities

Georgia-Pacific Corporation

P.O. Box 1236
Bellingham, WA 98225
Phone: (206) 733-4410
Contact: Jan Draut

Type of Business: Pulp paper, chemicals

Type of Biomass Fuel: Ethanol

Source of Fuel: Spent pulping liquor

Plant Design Capacity:

Gallons per year: 6,000,000 @ 190 proof,
3,000,000 @ 200 proof

Average Plant Output:

Gallons per year: 6,000,000 @ 190 proof,
3,000,000 @ 200 proof

Olympia Brewing Company

P.O. Box 947
Olympia, WA 98507
Phone: (206) 754-5010 or 754-5057
Contact: Paul D. Knight or Larry L. Sidor

Type of Business: Beer

Type of Biomass Fuel: Ethanol

Source of Fuel: Spillage, tank wash outs

Plant Design Capacity:

Gallons per year: 1,000,000 @ 200 proof

Average Plant Output:

Gallons per year: 435,000 @ 200 proof

Municipal Solid Waste Combustion Facilities

Skagit County Resource Recovery Facility

1200 W Ovenell Street
Mount Vernon, WA 98273
Phone: (206) 336-9400
Contact: William H. Ness, P.E.

Type of Biomass Fuel: Municipal Solid Waste

Source of Fuel: Skagit County

Annual Biomass Fuel Consumed: 50,000
tons

End Use(s): Provide electricity to Puget
Power

Plant Design Capacity: 178 tons per day

Heat (million Btu/hr):

Steam: 40 lbs/hr @ 450 psig

Electrical Generation (MW): 2.3

Average Plant Output:

Heat (million Btu/hr):

Steam: 40 lbs/hr @ 450 psig

Electrical Generation (MW): 2.3

Type of Combustor/Furnace: Rotary Kiln

Manufacturer: Tecnitalia

Type of Boiler:

Boiler Manufacturer: Zurn

Type of Pollution Control: Acid gas scrubber
& baghouse

Tacoma Steam Plant No. 2

Tacoma City Light

P. O. Box 11007
Tacoma, WA 98411
Phone: (206) 593-8336
Contact: Patrick D. McCarty, P.E.

Type of Biomass Fuel: Refuse derived fuel
and hog fuel

Source of Fuel: City of Tacoma

Annual Biomass Fuel Consumed: 98,000
tons

End Use(s): Electricity

Plant Design Capacity: 3,168 tons RDF/day,

820 tons hog fuel/day, 494 tons coal/day

Heat: (million Btu/hr):

Steam: 528,000 lbs/hr @ 382 psig

Electrical Generation (MW): 43 MW net

Average Plant Output: 3,169 tons RDF/day,

820 tons hog fuel/day, 494 tons coal/day

Heat (million Btu/hr):

Steam: 528,000 lbs/hr @ 382 psig

Electrical Generation (MW): 43 MW

Type of Combustor/Furnace: Fluidized bed

Manufacturer: Energy Products of Idaho

Type of Boiler:

Boiler Manufacturer:

Type of Pollution Control: Limestone in bed,
baghouses

Thermal Reduction Company

1524 Slater Road
Bellingham, WA 98226
Phone: (206) 676-0660
Contact: James R. Anderson

Type of Biomass Fuel: Municipal Solid Waste

Source of Fuel: City of Bellingham

Annual Biomass Fuel Consumed: 100 tons
per day

End Use(s): Electricity

Plant Design Capacity:
Heat (million Btu/hr):
Steam: 25,000 lbs/hr @ 400 psig
Electrical Generation (MW): 2.0

Average Plant Output:
Heat (million Btu/hr):
Steam: 25,000 lbs/hr @ 400 psig
Electrical Generation (MW): 2.0

Type of Combustor/Furnace: Modular Starved
Air

Manufacturer: Consumat

Type of Boiler: Water tube

Boiler Manufacturer:

Type of Pollution Control: Electrostatic
precipitator

Solid Fuel Processing Facilities

CD Pellet Company

P. O. Box 3185
Omak, WA 98841
Phone: (509) 826- 2059
Contact: Cherie or Dick Peterson

Type of Feedstock: Shavings

Source of Feedstock: Local mill

Plant Design Capacity: 6,000 tons per year

Average Plant Output: 6,000 tons per year

Type of Products: Wood pellets

Product Storage Capacity: 2,000 tons

Manke Lumber Company

1717 Marine View Drive
Tacoma, Washington 98422
Phone: (206) 572-6252
Contact: Milton Farbour

Type of Feedstock: Sawdust and Shavings

Source of Feedstock: Local mills

Plant Design Capacity: 240 tons/day X 312
days/year = 74,880 tons/year

Average Plant Output: 10 tons/hr @ 24
hrs/day = 74,880 tons/yr

Type of Products: Pellets

Product Storage Capacity: 6,000 tons

Spokane Pres-To-Logs

3124 Flora Road N
Spokane, WA 99216
Phone: (509) 924-2807
Contact: Dan Armstrong

Type of Feedstock: Dry Planner Shavings

Source of Feedstock: Local mills

Plant Design Capacity: 33,000 tons/yr
pellets, 36,000 tons/yr logs

Average Plant Output: 26,000 tons/yr pellets,
26,000 ton/yr logs

Type of Products: 1/4" diameter 1" long
pellets (bulk and bags) 8# logs

Product Storage Capacity: 4,000 tons

Wood Pellet Company

P.O. Box 87
Oakville, WA 98568
Phone: (206) 273-6982
Contact: Dick Rathvon

Type of Feedstock: Mill residue

Source of Feedstock: Local mills

Plant Design Capacity: 100 tons per day

Average Plant Output: 10 tons per day

Type of Products: 1/4" pellets, bagged

Product Storage Capacity: 500 tons

**Ethanol Production, MSW Combustion, and
Solid Fuel Processing Facilities**

Listing Changes from the 1987 Edition

Ethanol Production Facilities

No additions or deletions

Municipal Solid Waste Combustion Facilities

New Listings

Skagit County Resource Recycling Facility

Tacoma Steam Plant No. 2

Location

Mount Vernon

Tacoma

No deletions

Solid Fuel Processing Facilities

New Listings

CD Pellet

Manke Lumber Company

Location

Omak

Tacoma

No deletions

Conversion Table

Conversion Table

<u>Multiply</u>	<u>By</u>	<u>To Obtain</u>
Bone Dry Metric Ton	1.1023	Bone Dry Ton
Bone Dry Unit	1.2	Bone Dry Ton
Green Ton	(1 - moisture content)	Bone Dry Ton
One Gallon Ethanol	84,610	Btu
One Pound Bone Dry Hog Fuel	8,500	Btu
One Pound MSW	5,000	Btu
One Ton	2,000	Pounds
Unit	1.1	Bone Dry Tons

Glossary

GLOSSARY*

Anaerobic: Pertaining to the absence of free oxygen.

Anaerobic digestion: A biochemical degradation process that converts complex organic materials to methane and other by-products.

Bioenergy: The conversion of the complex carbohydrates in organic matter into energy, either by using it directly as a fuel or by processing it into liquids and gases that are more efficient.

Biogas: A combustible gas derived from decomposing biological waste.

Biomass: Any organic matter which is available to be used as a fuel on a renewable basis including forest residues, agricultural crops and wastes, wood and wood wastes, animal wastes, livestock operation residue, aquatic plants, and municipal wastes.

Biomass fuel: Any liquid, solid, or gaseous fuel produced by conversion from biomass.

Boiler horsepower: An arbitrary unit in the English system of measure for the equivalent of 33,480 Btu gross output or evaporation of 34.5 pounds of water per hour at 212°F.

Bone dry (oven dry): Having zero percent moisture content. Wood heated in an oven at a constant temperature of 212°F. or above until its weight stabilizes.

Bone dry unit (BDU): A quantity of wood residue which weighs 2,400 pounds at zero percent moisture content.

British Thermal Unit (Btu): The amount of heat required to raise the temperature of one pound of water one degree Fahrenheit.

Capacity: The maximum instantaneous output of a resource, often expressed in kilowatts or megawatts.

Chips: Woody material cut into short, thin wafers, used as a raw material for pulping, fiberboard, or for energy use.

Chip vans: Special construction bottom dump trucks (grain trucks) or conventional tractor-trailer vans used for hauling pulp chips, mill residues, hog fuel, and other biomass of smaller piece sizes.

Cogeneration: The technology of producing electric energy and forms of useful energy (thermal or mechanical) for industrial, commercial, heating, or cooling purposes, through the sequential use of an energy source.

Combustion: A chemical process, especially oxidation, accompanied by the production of heat and light.

Cord: A stack of wood consisting of 128 cubic feet with standard dimensions of 4' x 4' x 8', including air space and bark; typically 1.2 bone dry tons per cord.

Cubic Foot (CF): 12" x 12" x 12" or 1' x 1' x 1'.

Digester: A vessel in which carbon containing biomass is reacted in water in absence of air to produce biogas.

Dry ton: 2,000 pounds of material dried to a constant weight.

Dutch oven furnace: One of the earliest types of furnaces that is a large, rectangular box, lined on the sides and top with fire brick (refractory) that is commonly used for wood firing. Heat is stored in the refractory and radiated to the conical fuel pile in the center of the furnace.

Ethanol: Ethyl alcohol produced by fermentation and distillation.

Feedstock: Any material which is converted to another form or product.

Fly ash: Small ash particles carried in suspension in combustion gases.

Forest residues: Wasted and unutilized wood in the forest, including logging residue, rough, rotten, and dead trees, and annual mortality.

Fossil fuel: A solid, liquid, or gaseous fuel material formed in the ground by chemical and physical changes in plant and animal residues under high temperature and pressure.

Fuel-cell furnace: A variation of the Dutch oven design, that usually incorporates a primary and secondary combustion chamber. The primary is a vertical refractory-lined cylinder with a grate at the bottom in which combustion is partially completed. Combustion is completed in the secondary cell.

Fuel handling system: The delivered wood fuel is unloaded from vans or trucks and transported to a storage pile or bin. From storage, the wood fuel is conveyed mechanically or pneumatically to the energy conversion system.

Gasification: A chemical or heat process used to convert a feedstock to a gaseous form.

Gasifier: A device for converting solid fuel into gaseous fuel. In biomass systems, the process is referred to as pyrolytic distillation. See pyrolysis.

Green ton: 2,000 pounds of undried material, e.g., wood residue including moisture content.

Hogged (hog) fuel: Wood waste such as sawdust, planer shavings, and wood chunks normally used for fuel purposes.

Horsepower: Electrical: A measure of time rate of mechanical energy output. The term is usually applied to electric motors to describe maximum output. 1 electrical horsepower = 0.746 kilowatts = 2,545 British thermal units per hour. Also see Boiler Horsepower.

Kilowatt: 1,000 watts, a measure of electrical power.

Logging residues: The unused portions of saw timber and pole timber trees cut or dilled during the harvesting process.

Megawatt (MW): An electrical generation unit of one million watts or 1,000 kilowatts.

Methane: An odorless, colorless, flammable gas that is the primary constituent of natural gas.

MGD: Million gallons per day.

Mill residue: Wood and bark residues produced in processing lumber.

Molsture content, dry basis (MCDB): Expressed as a percentage of the weight of the oven-dry wood.

$$\text{MCWB} = \frac{(\text{weight wet sample} - \text{weight dry sample})}{\text{weight dry sample}} \times 100$$

Molsture content, wet basis (MCWB): Expressed as a percentage of the weight of the wood as received.

$$\text{MCDB} = \frac{(\text{weight wet sample} - \text{weight dry sample})}{\text{weight wet sample}} \times 100$$

Molsture content (MC): The moisture content is the amount of water contained in the fuel.

Oven dry: See bone dry.

Oven dry ton (ODT): An amount of wood that weighs 2,000 pounds at zero percent moisture content.

Pounds: Pound mass = A unit of mass equal to 0.454 kilograms.

Pound of steam: One pound mass of water converted to steam.

Power conversion factors (rate of flow of energy): Watts = 3.413 British thermal units per hour; kilowatts = 1,000 watts = 1.341 horsepower = 3,413 British thermal units per hour; horsepower = 745.7 watts, etc.

Psi: Pounds of pressure per square inch.

Psig: Pounds/force per square inch gauge.

Pyrolysis: A process of burning at less than stoichiometric conditions involving the physical and chemical decomposition of solid organic matter by action of heat in the absence of oxygen.

RDF: Refuse-derived fuel; the combustible portion of solid waste that has been processed to remove heavier, noncombustible materials.

Renewable energy resource: Any energy resource which has recently originated in the sun, including direct and indirect solar radiation and intermediate solar energy forms such as wind, ocean thermal gradients, ocean currents and waves, hydropower, photovoltaic energy products of photosynthetic processes, organic wastes, and others.

Saturated steam: Steam at the temperature which corresponds to its boiling temperature at the pressure.

SCF: Standard cubic foot.

SCFM: Standard cubic foot per minute.

Scrubber: A device in which combustible or stack gas is cleaned by the spraying of water.

Spreader stoker furnace: Fuel is automatically or mechanically spread across the furnace. A portion is suspension burned, but large pieces fall on a grate.

Steam Turbine: A device for converting energy of high-pressure steam (produced in a boiler) into mechanical power which can then be used to generate electricity.

Turbine: A machine for converting heat energy in steam or high temperature gas into mechanical energy as the high velocity flow of steam or gases passes through successive rows of radial blades fastened to a central shaft.

Unit: 200 cubic feet, bulk measure, used to measure hog fuel, pulp chips, etc. Contains varying amounts of solid material depending on the amount of compaction. It is now more customary to weigh material, correct for moisture, and calculate the number of bone dry tons.

Watt: The common base unit of power in the metric system. 1 kilowatt = 1,000 watts; 1 kWh (kilowatt hour) = the amount of power consumed for one hour. 1 megawatt = 1,000,000 watts.

*Excerpted from: *Pacific Northwest and Alaska Bioenergy Program Glossary (1985)*, and the Department of Energy *Biomass Energy Project Development Guidebook*.

Index

INDEX

- Allen Logging & Vaneer 36
- Allen Logging Company 14, 16, 36
- Anacortes Public Works/Operations Division, City of 4, 5
- Bennett Lumber Products 14, 16
- Boise Cascade Corporation - Goldendale 36
- Boise Cascade Corporation - Kettle Falls 14, 16, 17
- Boise Cascade Corporation - Steilacoom 14, 17
- Boise Cascade Corporation - Wallula 14, 18
- Boise Cascade Corporation - Yakima 14, 18
- Bremerton Wastewater Treatment Plant, City of 4, 5
- Buffelen Woodworking 14, 18
- Carkeek Park Treatment Plant 4, 9
- Cavenham Forest Industries 36
- Central Kitsap Treatment Plant 4, 5
- Centralia Wastewater Treatment Plant, City of 4, 5
- CD Pellet Company 38, 40, 41
- Champion International 14, 19
- Chehalis Wastewater Treatment Plant, City of 4, 5
- Chelan Treatment Plant 4, 5
- Coastcraft, Incorporated 15, 19
- Colville Indian Precision Pine Company 14, 19, 36
- Cowlitz Stud Company 14, 19
- Crown Zellerbach 36
- Daishowa America 16, 20, 36
- Dayton Wastewater Treatment Plant, City of 4, 6
- DeGoede Bulb Farms 15, 33
- Des Moines Creek Treatment Plant 4, 6, 12
- Douglas County Sewer District 4, 6
- E. A. Nord Company 16, 20
- Ellensburg Wastewater Treatment Plant, City of 4, 6
- Federal Way Water & Sewer Redondo Treatment Plant 4, 6
- Fort Vancouver Plywood 16, 20
- Fred Tebb & Sons, Incorporated 17, 20, 36

Georgia-Pacific Corporation **16, 21, 38, 39**
Goodyear Nelson Hardwood Lumber Company, Incorporated **14, 21, 36**
Grand Coulee, City of **12**
Hardel Mutual Plywood **14, 22**
Howard Manufacturing **36**
ITT Rayonier, Incorporated - Grays Harbor Division **14, 22, 36**
ITT Rayonier, Incorporated - Port Angeles **14, 22**
James River **14, 23**
Jeld-Wen Fiber of Washington **14, 23, 36**
Kinnear of Washington **15, 23**
K-Ply, Inc. **14, 24, 36**
Lacey Plywood **36**
Lacey, Olympia, Tumwater, Thurston County (LOTT) **4, 6**
Layman's Lumber Company **14, 24**
Longview Fibre Company **14, 24**
Louisiana Pacific Company **14, 25**
Manke Lumber Company **38, 40, 41**
Maple Lane School **15, 33**
McCleary Sewage Treatment Plant **4, 7**
Metro Alki Treatment Plant **4, 9**
Miller Creek Treatment Plant **4, 9, 12**
Mount Vernon Sewer Department, City of **4, 7**
Mt. Baker Plywood **14, 25**
Newport Wastewater Treatment Plant, City of **4, 7**
Northwest Hardwoods **14, 25**
Oak Harbor, City of **4, 7**
Oeser Company, The **15, 25**
Olympia Brewing Company **38, 39**
Omak Wood Products, Incorporated **14, 26, 36**
Pacific Wood Treating **14, 26**
Pasco Sewage Treatment Plant, City of **4, 7**
Paxport Mills, Inc. **36**
Peninsula Plywood Company **36**
Pierce County Chambers Creek Treatment Plant **4, 10**
Plum Creek Lumber **36**
Plum Creek Manufacturing, Incorporated **26, 36**

Port Angeles, City of 4, 7
Port Orchard/Kitsap County Sewer District #5 WTP 4, 8, 12
Port Townsend Paper 14, 27
Prosser Wastewater Treatment Facilities, City of 4, 8
Puget Sound Plywood 14, 27
Pullman Wastewater Treatment Plant 4, 8
Puyallup Wastewater Plant 4, 8
Rainier State School Sewage Treatment Plant 4, 8
Renton Treatment Plant 4, 8
Richland Wastewater Treatment Plant 4, 9
Richmond Beach Treatment Plant 4, 9
Salmon Creek Sewage Treatment Plant 4, 9, 12
San Poll Lumber Company 14, 27
Scott Paper 14, 28
Seattle Door 36
Simpson Door Company 14, 28
Simpson Tacoma Kraft Company 14, 28
Simpson Timber Company 14, 29
Skagit County Resource Recovery Facility 38, 39, 41
Smith Street Mill, Inc. 15, 29, 36
Southwest Suburban Sewer District 4, 9, 12
Spokane Pres-To-Logs 38, 40
Spokane Wastewater Treatment Plant 4, 10
Stevenson Co-Ply, Inc. 14, 29
Strauser Manufacturing Company 30, 36
Summit Timber Power House 30, 36
Sunnyside Wastewater Treatment Plant 4, 10
Tacoma Sewage Treatment Plant-1, City of 4, 10
Tacoma Sewage Treatment Plant-2, City of 12
Tacoma Sewage Treatment Plant-3, City of 4, 11
Tacoma Steam Plant #2 38, 39, 41
Thermal Reduction Company 34, 40
Toppenish Wastewater Treatment Plant 4, 11
Vaagen Brothers Lumber, Incorporated - Colville 14, 30
Vaagen Brothers Lumber, Incorporated - Ione 14, 31
W.I. Forest Products - Cashmere 36

52 - Directory of Biomass Energy Facilities

W.I. Forest Products - Spokane **14, 33**
Walla Walla Wastewater Treatment Plant **4, 11**
Washington Soldiers Home & Colony **15, 34**
Washington State Penitentiary **14, 34**
Washington Water Power Company **14, 34**
Wenatchee Water Pollution Control Plant **4, 11**
West Coast Forest Products, Incorporated **14, 31, 36**
West Point Treatment Plant **4, 10**
Western State Hospital **14, 35**
Weyerhaeuser Company - Cosmopolis **14, 31, 36**
Weyerhaeuser Company - Longview **14, 32**
Weyerhaeuser Company - Raymond **14, 32**
Weyerhaeuser Company - Snoqualmie Falls **14, 32**
White Swan Lumber **36**
Wood Pellet Company **38, 40**

END

**DATE
FILMED**

6/02/92