2
1/16/92 Q-1

ORNL/ENG/TM-39

**OAK RIDGE
NATIONAL
LABORATORY**

MARTIN MARIETTA

**Comparison of Experimental
and Analytical Temperatures
Achieved by DT-18 and PC-1
Shipping Containers During
Hypothetical Thermal
Accident Tests**

J. C. Anderson

**MANAGED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY**

THIS DOCUMENT IS UNCLASSIFIED

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ORNL/ENG/TM-39

ORNL/ENG/TM--39

DE92 014922

**Martin Marietta Energy Systems, Inc., Engineering
Process Engineering**

**Comparison of Experimental and Analytical
Temperatures Achieved by DT-18 and PC-1
Shipping Containers During Hypothetical
Thermal Accident Tests**

J. C. Anderson

Date Published - March 1992

MASTER

MARTIN MARIETTA ENERGY SYSTEMS, INC.

Oak Ridge, Tennessee 37831

managing the

Oak Ridge National Laboratory

Oak Ridge K-25 Site

Oak Ridge Y-12 Plant

Paducah Gaseous Diffusion Plant

for the

U.S. DEPARTMENT OF ENERGY

under Contract No. DE-AC05-84OR21400

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

CONTENTS

	Page
LIST OF FIGURES	v
LIST OF TABLES	vii
ACKNOWLEDGMENTS	ix
ABSTRACT	xi
INTRODUCTION AND SUMMARY	1
DESCRIPTION OF THE PACKAGES ANALYZED	3
DT-18 SHIPPING PACKAGE	3
PC-1 SHIPPING PACKAGE	3
FURNACE TESTS	7
DT-18 UNIT A6 THERMOCOUPLE DATA	7
DT-18 UNIT A7 THERMOCOUPLE DATA	11
PC-1 UNIT A THERMOCOUPLE DATA	11
ANALYTICAL MODELING	15
DT-18 HEATING MODEL	15
PC-1 HEATING MODEL	19
DISCUSSION OF RESULTS	21
CONCLUSIONS	31
REFERENCES	33
APPENDICES	
Appendix A HEATING OF CELOTEX™	35
Appendix B HEAT TRANSFER TO THE INNER CONTAINER	41
Appendix C HEATING 7.1 INPUT FOR DT-18 PACKAGE WITHOUT HEAT GENERATION	51
Appendix D HEATING 7.1 INPUT FOR DT-18 PACKAGE WITH HEAT GENERATION	57
Appendix E HEATING 7.1 INPUT FOR PC-1 PACKAGE WITHOUT HEAT GENERATION	63
Appendix F HEATING 7.1 INPUT FOR PC-1 PACKAGE WITH HEAT GENERATION	71

LIST OF FIGURES

	Page
1. DT-18 shipping container	4
2. PC-1 shipping container	5
3. Locations of thermocouples on the DT-18 package	8
4. Locations of thermocouples on the PC-1 package	9
5. DT-18 Unit A6 outer container thermocouple data	10
6. DT-18 Unit A6 inner container thermocouple data	10
7. DT-18 Unit A7 outer container thermocouple data	12
8. DT-18 Unit A7 inner container thermocouple data	12
9. PC-1 Unit A outer container thermocouple data	13
10. PC-1 Unit A inner container thermocouple data	13
11. DT-18 HEATING model geometry	16
12. PC-1 HEATING model geometry	20
13. Comparison of experimental and analytical DT-18 outer container side temperatures	22
14. Comparison of experimental and analytical DT-18 outer container top temperatures	22
15. Comparison of experimental and analytical DT-18 outer container bottom temperatures	23
16. Comparison of experimental and analytical DT-18 inner container side temperatures	23
17. Comparison of experimental and analytical DT-18 inner container top temperatures	24
18. Comparison of experimental and analytical DT-18 inner container bottom temperatures	24

19.	Temperatures in the DT-18 package as a function of depth	26
20.	Comparison of experimental and analytical PC-1 outer container side temperatures	27
21.	Comparison of experimental and analytical PC-1 outer container top temperatures	27
22.	Comparison of experimental and analytical PC-1 outer container bottom temperatures	29
23.	Comparison of experimental and analytical PC-1 inner container side temperatures	29
24.	Comparison of experimental and analytical PC-1 inner container top temperatures	30
25.	Comparison of experimental and analytical PC-1 inner container bottom temperatures	30
A2.1	DT-18 volumetric heat generation rate	47

LIST OF TABLES

	Page
1. Thermal properties of materials used in the analyses	17
2. Natural convection correlation constants	18
A1.1 Pyrolytic products of cellulose	38
A2.1 Butyric acid condensation parameters	44
A2.2 Butyric acid properties	44
A2.3 Convection parameters	46
A2.4 Pyrolysis gas properties at 600 K	46

ACKNOWLEDGMENTS

The author acknowledges the help and influence of several individuals who aided in the preparation of this document. M. R. Feldman and W. R. Williams of the Engineering Analysis Department were especially instrumental in providing original ideas, support, and comments as this work progressed.

The members of the Energy Systems Independent Review Group Committee and the Packaging Group of the Y-12 Plant Systems Safety Engineering Division and the Weapons Support Group of the Mechanical Design Division were most helpful throughout this project. E. Stumpfl of the Y-12 Packaging Program and S. D. Moses of the System Safety Engineering Division gave continuous input as well as support during this project.

This project was performed at the request of and was funded exclusively by the Y-12 Packaging Program.

ABSTRACT

Temperatures were monitored at various locations on DT-18 and PC-1 shipping packages during furnace tests at the Y-12 Plant in Oak Ridge, Tennessee. The furnace tests are intended to simulate hypothetical thermal accident conditions specified in Title 10 CFR, Pt. 71.73 (c)(3).¹ Maximum temperatures of the outer containers ranged from 750 to 965°C while typical maximum temperatures recorded on the inner containers were 60 to 77°C. One exceptionally high temperature of 196°C occurred on the PC-1 inner container.

HEATING 7.1 models of both the DT-18 and PC-1 packages were developed. Models with and without heat generation in the inner containers were developed for each shipping package. The models with heat generation are intended to simulate condensation and convection of hot vapors generated during the heating of the CelotexTM insulating material used in the packages. In general, the analytical models calculate temperatures for the outer containers which agree well with the test data. The HEATING models with and without heat generation bound the inner container test data. These findings are significant in that they lead to the conclusion that heat is transferred to the inner containers through a mechanism other than conduction alone. The high temperature of 196°C recorded at the PC-1 inner container is within 4°C of the maximum temperature calculated by the PC-1 HEATING model with heat generation.

INTRODUCTION AND SUMMARY

This report presents the thermocouple data from two DT-18 packages and a PC-1 package for hypothetical accident condition thermal tests defined in Title 10 CFR, Pt. 71.73(c)(3).¹ These tests were performed in conjunction with the characterization studies of the B-1023 furnace at the Y-12 Plant in Oak Ridge, Tennessee, to support certification review comments. Temperatures were monitored at 12 locations on each package during the furnace tests and the cooling periods using Alumel-Chromel Type K thermocouples. Maximum temperatures on the outer containers were 750 to 965°C. The typical maximum temperatures of the inner containers were 60 to 77°C. One exceptionally high temperature of 196°C was recorded at the top of the PC-1 inner container. This high temperature may have been caused by the condensation of vapor at the inner container or localized flaming.

This report also presents comparisons of experimentally obtained temperature values and values calculated by analytical models for the DT-18 and PC-1 packages. The computer software used was HEATING 7.1. HEATING calculates temperatures for the outer container that agree with the test data. HEATING models, with and without heat generation which simulates condensation of CelotexTM off-gas at the inner container, bound the test data. In general, the model without the heat generation function underpredicts the temperatures achieved at the inner container, and the model with the heat generation function overpredicts the inner container temperatures.

DESCRIPTION OF THE PACKAGES ANALYZED

Two shipping packages, the DT-18 and the PC-1, were considered in the analyses. These two packages, which are similar in construction and materials, are described below.

DT-18 SHIPPING PACKAGE

The DT-18 packaging includes a 55-gal stainless steel drum (outer container) and a stainless steel inner container. The inner container has an outer diameter of 40 cm and a height of 57 cm. The space between the inner and outer containers is filled with stacked rings and disks of CelotexTM fiberboard insulating material. The DT-18 package also contains two rings of plywood. The packing material inside the inner container is polyurethane foam. A sketch of the DT-18 package with relevant dimensions is shown in Fig. 1.

PC-1 SHIPPING PACKAGE

The PC-1 package consists of a stainless steel, 146-gal drum (outer container) and a stainless steel inner container. The inner container has an outer diameter of 51 cm and a height of 103 cm. The space between the inner and outer containers is filled with alternating layers of CelotexTM insulating material and 3/8-in.-thick (0.95-cm) plywood (Fir, Grade A-C). The packing material inside the inner container is polyurethane foam. A sketch of the PC-1 package with relevant dimensions is shown in Fig. 2.

Note : All dimensions are in cm.

Fig. 1. DT-18 shipping container.

Note : All dimensions are in cm.

Fig. 2. PC-1 shipping container.

FURNACE TESTS

Two DT-18 packages (Units A6 and A7) and a PC-1 package (Unit A) were subjected to furnace thermal tests at the Y-12 Plant in Oak Ridge, Tennessee, to simulate fire accident scenarios specified by 10 CFR 71.¹ A total of 12 thermocouples (Alumel-Chromel Type K) was placed on each package, six on the outer container and six on the inner container. The locations of these thermocouples on the DT-18 and PC-1 packages are shown in Figs. 3 and 4, respectively. A thermocouple was placed at the top and bottom of the inner and outer containers. Four thermocouples were evenly spaced around the sides of both the inner and outer containers. The furnace was set at 835°C for DT-18 Unit A6 and for PC-1 Unit A. The furnace was set at 800°C for DT-18 Unit A7. Both DT-18 packages remained in the furnace for 30 min. The PC-1 package remained in the furnace for 42 min.

After being removed from the furnace, visible flaming was observable from both DT-18 packages for about 5 min. After cooling, both DT-18 packages and the PC-1 package were opened and the amount of CelotexTM that had charred was measured. The DT-18 Unit A6 package experienced heavier CelotexTM damage near the top than did Unit A7 or the PC-1 package. Prior to the furnace test, Unit A6 had sustained significant damage to the lid which caused the lid to fit and seal improperly. No attempt was made to repair the previously sustained damage since similar damages typically result from drop tests. About 7/8 to 1 1/4 in. of the CelotexTM in contact with the outer containers was charred. No charring was observed on the CelotexTM in contact with the inner containers. A minimal amount of streaking or tar condensation was observed on the inner containers. This indicates that some condensible vapors generated by CelotexTM pyrolysis reach the inner container. A more detailed discussion of CelotexTM charring is presented in another report, "Investigation of CelotexTM Charring Depths in the DT-18 Shipping Container." ²

DT-18 UNIT A6 THERMOCOUPLE DATA

The thermocouple data from DT-18 Unit A6 are plotted in Figs. 5 and 6. The four side temperatures were averaged to obtain a single side temperature value. Except for a few minutes after placement in and removal from the furnace, the four side thermocouple data are very similar. Less than 10°C separate the maximum and minimum side temperature data.

A maximum temperature of 965°C was achieved on the top of the DT-18 Unit A6 outer container during the furnace test (Fig. 5). This high temperature was probably due to flaming from the package. Unit A6 had sustained appreciable damage near the top which may have led to excessive flaming of exposed CelotexTM insulation. The maximum temperatures on the side and bottom of the DT-18 Unit A6 outer container were 794 and 770°C, respectively. On removal from the furnace, the top of the package cooled rapidly, reaching a temperature within 2°C of the ambient in 32 min. The bottom of the container cooled at a slower rate than the top or the side since the package remained on the steel frame during the entire cooling period.

The maximum temperature achieved on the sides of the DT-18 Unit A6 inner container was 76°C at a time of 68 min. This is 37 min following removal from the furnace (Fig. 6). After 3 1/2 h, the temperature of the top and bottom of the DT-18 Unit A6 inner container had leveled off near 74 and 60°C, respectively.

DT-18 OUTER
CONTAINER

DT-18 INNER
CONTAINER

Fig. 3. Locations of thermocouples on the DT-18 package.

PC-1 OUTER
CONTAINER

PC-1 INNER
CONTAINER

Fig. 4. Locations of thermocouples on the PC-1 package.

Fig. 5. DT-18 Unit A6 outer container thermocouple data.

Fig. 6. DT-18 Unit A6 inner container thermocouple data.

DT-18 UNIT A7 THERMOCOUPLE DATA

The thermocouple data from DT-18 Unit A7 are plotted in Figs. 7 and 8. The four side temperatures were averaged to obtain a single side temperature value. The maximum temperature achieved at the top of the DT-18 Unit A7 outer container was approximately 792°C (Fig. 7). In contrast to Unit A6, no sharp temperature peaks indicating flaming were observable from the Unit A7 data. The maximum temperatures on the side and bottom of the DT-18 Unit A7 outer container were 768 and 748°C, respectively. The outer container temperatures for Unit A7 (800°C test) were 20 to 25°C lower than those for Unit A6 (835°C test). The sides and top of the DT-18 Unit A7 outer container cooled at almost exactly the same rate as Unit A6. The bottom of the DT-18 Unit A7 outer container cooled at a slower rate than the top because it remained on the hot steel frame during cooling.

The maximum temperature on the side of the DT-18 Unit A7 inner container was 77°C at a time of 52 min (Fig. 8); this was 22 min after removal from the furnace. The maximum temperature achieved on the top of the DT-18 Unit A7 inner container was 76°C at a time of 107 min or 77 min following removal from the furnace. After a time of 3 1/2 h, the temperature of the bottom of the DT-18 Unit A7 inner container had leveled off near 60°C.

Based on the thermocouple data, it can be concluded that varying the furnace thermostat temperature from 800 to 835°C has very little effect on the temperatures achieved at the inner container near the seal or near the O-rings.

PC-1 UNIT A THERMOCOUPLE DATA

The thermocouple data from PC-1 Unit A are plotted in Figs. 9 and 10. The four side temperatures were averaged to obtain a single side temperature value. A maximum temperature of 891°C occurred on the top of the PC-1 package. This temperature occurred during a relatively short temperature peak and was probably due to flaming. The maximum temperatures on the side and bottom of the PC-1 package were 828 and 792°C, respectively. The slower increase in temperature of the outer container bottom indicates that the view of the furnace surfaces from the container bottom is restricted when compared to the view from the top and sides of the container due to the location of the package near the furnace floor. Following removal from the furnace, all monitored locations on the outer container cooled rapidly (see Fig. 9).

The maximum temperature of the side of the PC-1 inner container was 66°C at a time of 142 min into the test or 100 min following removal from the furnace (see Fig. 10). The maximum temperature recorded at the top of the inner container was 196°C at a time of 44 min into the test or 2 min following removal from the furnace. This sharp temperature peak at the top of the inner container is unexplained. Three possibilities for this temperature peak are localized vapor condensation, flaming, or thermocouple malfunction. The maximum temperature at the bottom of the inner container was 65°C at a time of 132 min into the test or 90 min after removal from the furnace.

Fig. 7. DT-18 Unit A7 outer container thermocouple data.

Fig. 8. DT-18 Unit A7 inner container thermocouple data.

Fig. 9. PC-1 Unit A outer container thermocouple data.

Fig. 10. PC-1 Unit A inner container thermocouple data.

ANALYTICAL MODELING

Two-dimensional (r-z) models of the DT-18 and PC-1 shipping packages were constructed on HEATING 7.1. HEATING 7.1 is a multidimensional finite difference transient heat transfer code which has been formally verified and documented.³

DT-18 HEATING MODEL

A sketch of the DT-18 HEATING model is shown in Fig. 11. The DT-18 HEATING model consists of two materials, stainless steel and CelotexTM. Both the outer drum and the inner container are modeled as stainless steel. CelotexTM is a fiberboard insulation used between the outer drum and the inner container. The two plywood rings seen in Fig. 1 were not included in the analytical model since they are not in close proximity to monitored locations. Thermal properties for both stainless steel and CelotexTM are presented in Table 1.

Polyurethane foam is commonly used as insulation inside the inner container. However, since the thermal conductivity of polyurethane foam is relatively low, approximately 0.05 to 0.06 W/m-K, most of the heat absorbed by the inner container will be stored rather than transferred through to the polyurethane. Therefore, as a conservative measure, the contents of the inner container which would normally include the polyurethane insulation and the payload were not modeled, and the inner surface of the inner container is modeled as an insulated boundary.

The boundary conditions applied are those specified in 10 CFR 71.¹ An emissivity of 0.9 for the furnace and an absorptivity of 0.8 for the exterior surface of the package were used. A package-to-furnace-surface-area ratio of 1.0 was used. The DT-18 package was modeled as being subjected to an 800°C radiant environment for 30 min. Following the 30-min radiant heat source exposure, the container was cooled by natural convection from exposure to a constant ambient temperature of 21°C throughout the duration of cooling.

The natural convection heat transfer over the sides, top, and bottom of the package can be determined from

$$Q_{\text{conv}} = hA_{\text{package}}(T_{\text{furnace}} - T_{\text{package}}), \quad (1)$$

where
$$h = a(T_{\text{furnace}} - T_{\text{package}})^b, \quad (2)$$

with values of a and b given in Table 2 for different surface configurations.

CelotexTM is known to char and release condensible vapors at high temperatures. A discussion of the pyrolysis (charring) process of CelotexTM is presented in Appendix A. The possibility exists for the condensible vapors generated from the heating of CelotexTM to reach and condense on the inner container. This problem was first addressed in 1990 when unusually high temperatures (400 to 500°F) were recorded at the inner containers of DOT 6M packages during furnace tests.⁴ Observation of inner containers from previous and current tests show some streaking tar residue. This indicates that some vapors which are generated during the heating and subsequent pyrolysis or charring of CelotexTM do condense on the inner container.

Fig. 11. DT-18 HEATING model geometry.

Table 1. Thermal properties of materials used in the analyses

Material	Temperature (K)	Thermal conductivity (W/m-K)	Density (kg/m³)	Specific heat (J/kg-K)
Stainless Steel¹	200	12.6	7900 *	402
	300	14.9		477
	400	16.6		515
	600	19.8		557
	800	22.6		582
	1000	25.4		611
	1200	28.0		640
Celotex^{TM 2}	298	0.053	270 *	1280
	359	0.059		1506
	419	0.063		1745
	499	0.065		2046
	551	0.051		2063
Plywood (Fir)³	27	0.11	415	2720

* For modeling purposes, density was considered constant (temperature independent).

- Sources:
1. *Safety Analysis Report for Packaging, Oak Ridge Y-12 Plant, Model DT-23 Package with Subassembly Contents (U)*, Y/LF-51-IA/R1, October 26, 1990.
 2. L. C. Sanchez, R. S. Longenbaugh, M. Moss, G. M. Haseman, W. E. Fowler, and E. P. Roth, *Thermal Analysis of the 10-Gallon and the 55-Gallon DOT-6M Containers with Thermal Boundary Conditions Corresponding to 10 CFR 71 Normal Transport and Accident Conditions*, Sandia Report SAND87-1896 TTC-0748, 1988.
 3. F. P. Incropera and D. P. DeWitt, *Fundamentals of Heat and Mass Transfer*, John Wiley & Sons, New York, 1985.

Table 2. Natural convection correlation constants

Configuration	a	b
Vertical surface	1.37	0.25
Horizontal: Hot surface facing up or cold surface facing down	1.86	0.25
Horizontal: Hot surface facing down or cold surface facing up	0.88	0.25

Source: R. H. Perry and D. W. Green, *Perry's Chemical Engineers' Handbook*, 6th ed., McGraw-Hill, New York, 1984.

HEATING models with and without heat generation in the inner container were constructed. The model without heat generation allows heat to reach the inner container through conduction alone. The model with heat generation attempts to simulate the heat transferred to the inner container through condensation of combustion vapors and natural convection of hot vapors. A brief synopsis of the development of the heat generation function used in this model is presented in Appendix B.

The approach described above to model the heat transfer to the inner container through condensation and natural convection is an approximation. Actually, some of the vapor will condense before reaching the inner container and some will escape from the package. This approach, although unrealistic, provides an upper bound for the temperatures achieved at the inner container. Likewise, the model with no heat generation which is based on conduction alone provides a lower limit for the inner container temperatures.

Since initial temperature gradients are extremely sharp at the package surface, the mesh size used in the HEATING model is small, approximately 1/16 in., for a depth of 1 in. into the package. The mesh size is increased to 1/8 in. at the intermediate region before being increased to 1/4 in. near the inner container. The progressive mesh sizing, determined from preliminary one-dimensional (radial) analyses on the DT-18 package, is employed in both the r and z directions.

HEATING input files for both DT-18 models are presented in the Appendices C and D.

PC-1 HEATING MODEL

A sketch of the PC-1 HEATING model is shown in Fig. 12. The PC-1 HEATING model consists of three materials: stainless steel, CelotexTM, and plywood. Thermal properties used for these materials are presented in Table 1.

As with the DT-18 models, the inner surface of the inner container was conservatively modeled as an insulated boundary. Boundary conditions applied to the PC-1 package are identical to those specified for the DT-18 package with the exception of the duration of the radiant 800°C heat exposure. Since the PC-1 Unit A package remained in the furnace for 42 min, the duration of the radiant exposure for the PC-1 analytical models was extended from 30 to 42 min.

The heat generation applied to the PC-1 inner container was developed in a similar manner as for the DT-18 package (see Appendix B for details). HEATING input files for PC-1 models with and without heat generation are presented in Appendices E and F.

Note : All dimensions are in cm.

Fig. 12. PC-1 HEATING model geometry.

DISCUSSION OF RESULTS

The outer container side temperatures for the DT-18 Unit A6 test agree well with the values predicted by HEATING 7.1 for the 30-min thermal accident scenario, as seen in Fig. 13. The outer container side temperatures for DT-18 Unit A7 are about 25°C lower than the calculated HEATING values. HEATING overpredicts the outer container side temperature by as much as 75°C during the initial cooling period. These data seem to indicate that either enhanced cooling (cooling in addition to the modeled radiative heat loss and natural convection) occurs following removal from the furnace, that the correlations used to calculate the natural convection heat transfer coefficients are inaccurate, or the loss of Celotex™ mass has a significant effect on the heat transfer. Further analyses will be performed in an attempt to obtain better agreement between experimental and analytical outer container temperatures following the removal of the package from the furnace. The experimental and analytical results are very similar at times beyond 120 min. It should be noted that the difference between the outer container temperatures calculated by the HEATING models with and without heat generation is insignificant. Therefore, a single analytical solution is presented for all outer container locations.

The outer container top temperatures calculated by HEATING agree well with DT-18 Unit A7 test data (see Fig. 14). Outer container top thermocouple data for DT-18 Unit A6 are significantly higher than calculated values because the lid was previously damaged which allowed more exposure and subsequently more burning of the Celotex™ insulating material to occur. The sharp temperature peaks evident in Fig. 14 are due to localized flaming near the top of the package. HEATING overpredicts the outer container top temperature during the first hour of cooling by as much as 150°C. Once again, this difference may be explained by the presence of enhanced cooling following removal from the furnace, inaccurate convection correlations, or charring effects. Temperatures calculated by HEATING agree well with experimental data at times beyond 90 min.

Data presented in Fig. 15 indicate that the outer container bottom temperature is overestimated by HEATING for the 30-min fire and underestimated for the cooling period. The frame is preheated in the furnace to eliminate conduction losses from the package to the frame. Although there are no heating elements on the floor, a large steel plate was placed on the furnace floor to hold heat and maintain the floor at a temperature comparable to that of the side walls. However, it has been shown that furnace floor temperatures can be significantly cooler (i.e., 5-15°C) than other furnace surfaces.⁵ The discrepancy between the experimental and analytical outer container bottom temperatures during the cool-down period exists primarily because the package remains on the hot steel frame after removal from the furnace. The analytical models employ near uniform cooling over the package surface [see Eq. (2) and Table 2].

Figures 16, 17, and 18 show the comparison of experimental and analytical DT-18 inner container side, top, and bottom temperatures, respectively. It is evident from these data that the actual inner container temperatures have been bounded by the two analytical models (with and without heat generation). The actual temperatures are much lower than those calculated by the maximum condensation and natural convection heat transfer model. The HEATING model with heat generation predicts a maximum inner container side temperature of 185°C and a maximum inner container top and bottom temperature of 195°C. The lower maximum inner container side temperature is a result of the greater steel thickness used on the side of the inner container. The actual inner container temperatures are also significantly higher than the values calculated by the

Fig. 13. Comparison of experimental and analytical DT-18 outer container side temperatures.

Fig. 14. Comparison of experimental and analytical DT-18 outer container top temperatures.

Fig. 15. Comparison of experimental and analytical DT-18 outer container bottom temperatures.

Fig. 16. Comparison of experimental and analytical DT-18 inner container side temperatures.

Fig. 17. Comparison of experimental and analytical DT-18 inner container top temperatures.

Fig. 18. Comparison of experimental and analytical DT-18 inner container bottom temperatures.

simple conduction model. This information indicates that heat is transferred to the inner container by some mechanism other than conduction alone. Also, observation of Figs. 16, 17, and 18 leads to the conclusion that the inner container temperature is not significantly affected by a 35°C change in the radiating furnace temperature. In fact, in some instances the inner container temperatures from Unit A7 (800°C) are higher than the inner container temperatures from Unit A6 (835°C). This is most evident for the inner container top (Fig. 17), which could be due to the increased exposure resulting from the damaged lid of the Unit A7 package. These data support the idea that package temperatures achieved during thermal tests may vary from package to package depending on the type and amount of damage sustained prior to the tests.

Figure 19 presents the temperature profiles (corresponding to a time of 30 min) through the Celotex™ insulation in the DT-18 container calculated by HEATING for both models (with and without heat generation). Currently, the model with heat generation dumps heat into the inner container which subsequently heats the surrounding insulation. This explains why the temperature at the inner container is higher than the temperature of the Celotex™ surrounding the inner container. In actuality, the hot pyrolysis gases evolved during the heating of Celotex™ move through the insulation, heating it up as it goes. Therefore, the actual temperature of the inner container should lie between the two values shown in Fig. 19. Although the temperature of the Celotex™ was not monitored at locations between the outer and inner containers, the dotted curve in Fig. 19 represents an approximate temperature profile through the Celotex™. The temperature would be expected to be slightly higher than the calculated value through much of the outer insulation. However, at some point the temperature calculated by the model including heat generation in the inner container would exceed the actual temperature. At the inner container, the actual temperature would lie between the calculated values.

Experimental and analytical (HEATING 7.1) PC-1 outer container side temperatures are plotted in Fig. 20. Thermocouple data for the side of the outer container are 25°C higher than the temperatures calculated by HEATING throughout most of the 42-min. thermal test. HEATING overpredicts the outer container side temperature by as much as 75°C during the initial cooling period. The data presented in Fig. 20 for the cooling period are very similar to data presented for the DT-18 packages. These results suggest that enhanced cooling (cooling in addition to the modeled radiative heat loss and natural convection) occurred following removal from the furnace. The discrepancy between the experimental and analytical temperatures diminishes as time increases and the two temperature values are in fact very close after 3.5 h. As explained earlier for the DT-18 package, a single analytical solution is presented in Figs. 20-22 since HEATING models with and without heat generation predict nearly identical outer container temperatures.

Figure 21 presents a comparison of experimental and calculated PC-1 outer container top temperatures. Thermocouple data for the top of the PC-1 outer container are 35°C higher than the temperatures calculated by HEATING throughout much of the 42-min thermal test. These data, along with data presented for the DT-18 package, indicate that the highest temperatures on the outer containers should be expected to occur at the top of the package. Although not calculated by analytical models, temperature peaks (resulting from flaming from the tops of the packages) are also a possibility. Outer container top temperatures during the cooling period are very similar to outer container side temperatures for the cooling period discussed above.

The maximum outer container bottom temperature calculated by HEATING agrees well with the temperature recorded by the thermocouple at this location (see Fig. 22). This indicates

Fig. 19. Temperatures in the DT-18 package as a function of depth.

Fig. 20. Comparison of experimental and analytical PC-1 outer container side temperatures.

Fig. 21. Comparison of experimental and analytical PC-1 outer container top temperatures.

that the bottom of the PC-1 package probably experiences a radiating temperature of about 800°C. However, the rate at which the PC-1 package bottom is heated in the furnace is much slower than the rate calculated by HEATING. This slower heating rate may be due to the fact that the view of the furnace surfaces from the package bottom is restricted when compared to the view from the top and sides of the package due to the location of the package near the furnace floor.

Figures 23, 24, and 25 show the comparison of experimental and calculated PC-1 inner container side, top, and bottom temperatures, respectively. Figures 23 and 25 (data from the side and bottom of the inner container) contain trends similar to those observed from DT-18 data. For these two cases, the HEATING models with and without heat generation bound the test data. The HEATING model without heat generation underpredicts temperatures by as much as 40°C, whereas the model with heat generation overpredicts temperatures by as much as 160°C.

Figure 24 indicates that a maximum top inner container temperature of 196°C occurred at 44 min or 2 min after removal from the furnace. The maximum top inner container temperature calculated by HEATING is 192°C at 42 min. Since the sharp temperature peak occurs over a period of approximately 10 min, it is probably not due to a thermocouple malfunction. More reasonable explanations might be that, perhaps in the removal process from the furnace, a path was opened for condensible vapors to reach the inner container and subsequently condense there resulting in temperatures very close to those calculated by the HEATING model with heat generation, or direct flame impingement on the thermocouple sheath near the thermocouple junction.

Fig. 22. Comparison of experimental and analytical PC-1 outer container bottom temperatures.

Fig. 23. Comparison of experimental and analytical PC-1 inner container side temperatures.

Fig. 24. Comparison of experimental and analytical PC-1 inner container top temperatures.

Fig. 25. Comparison of experimental and analytical PC-1 inner container bottom temperatures.

CONCLUSIONS

Based on the thermocouple data and on the analytical results presented in this report, the following conclusions can be made:

1. Analytical models with and without heat generation to simulate condensation and convection of vapors generated during the heating of Celotex™ have been shown to bound test data.
2. The effect of raising the furnace operating temperature from 800 to 835°C on the temperatures achieved at the inner container is insignificant.
3. Experimental data suggest that temperatures exceeding expected values may be produced during furnace tests due to localized flaming of the insulation especially near the top of the package (see Figs. 14 and 21).
4. Thermocouple data suggest that the frame on which the packages rest following removal from the furnace has a significant effect on the cooling rates of the package bottom (see Figs. 5, 7, and 9).
5. Thermocouple data suggest that the heating rate of the package bottom during furnace tests is slower than the heating rates of the package top and sides due to the fact that the view of the furnace surfaces from the package bottom is restricted when compared to the view from the top and sides of the package as a result of the location of the package near the furnace floor (see Figs. 5, 7, and 9). Also, it has been shown that furnace floor temperatures can be significantly cooler (i.e., 5-15°C) than other furnace surfaces.⁵
6. Comparison of thermocouple and analytical data following removal from the furnace indicates that either enhanced cooling (cooling in addition to the modeled radiative heat loss and natural convection) occurs following removal from the furnace, correlations used to calculate the natural convection heat transfer coefficient are inaccurate, or loss of Celotex™ mass has a significant effect on the heat transfer (see Figs. 13, 14, 20, 21, and 22).
7. The introduction of heat generation in the inner container of the analytical models has an insignificant effect on the outer container temperatures.
8. The possibility of vapor condensation leading to inner container temperatures approaching 200°C exists based on PC-1 inner container thermocouple data (see Fig. 24).

REFERENCES

1. *Packaging and Transportation of Radioactive Materials*, U. S. Nuclear Regulatory Commission, Title 10, Code of Federal Regulations, Part 71, Washington, D. C., 1987.
2. J. C. Anderson, *Investigation of Celotex™ Charring Depths in the DT-18 Shipping Container*, ORNL/ENG/TM-38, March 1992.
3. K. W. Childs, *HEATING 7.1 User's Manual*, K/CSD/TM-96, July 1991.
4. J. C. Anderson and J. P. Belk, *Thermal Analysis of the 55-Gal DOT-6M Container with Thermal Boundary Conditions Corresponding to 10 CFR 71 Fire Accident Conditions*, March 1990.
5. M. R. Feldman, *Characterization of the B-1023 Furnace for Use in Hypothetical Thermal Accident Testing of Shipping Containers in Accordance with 10 CFR, Part 71*, ORNL/ENG-10, January 1992.

Appendix A
HEATING OF CELOTEX™

HEATING OF CELOTEX™

Celotex™ is known to char and release flammable vapors at high temperatures. Since information about Celotex™ charring is limited, the process by which Celotex™ is charred will be assumed to closely follow the processes involved in charcoal formation. Charcoal formation involves pyrolysis, which is the decomposition of organic material at high temperatures in the absence of oxygen. As wood is heated to about 110°C, the wood absorbs heat, giving off its moisture as water vapor.¹ As the wood is heated beyond 110°C, other gases including carbon monoxide, carbon dioxide, acetic acid, and methanol are given off.¹ Exothermic decomposition of the wood, or pyrolysis, begins at about 300°C.¹ At this point, the combustible gases carbon monoxide, hydrogen, and methane are given off along with the condensible vapors water, acetic acid, methanol, and acetone.¹ As the temperature approaches 500°C, the transformation of the wood to charcoal is practically complete.¹

Several technical papers on cellulose pyrolysis were used to obtain a comprehensive list of possible pyrolysis products.²⁻⁷ Of the 38 possible pyrolysis products, 8 have boiling-point temperatures above 100°C. The high boiling-point vapors produced from cellulose pyrolysis include water, formic acid, toluene, acetic acid, propionic acid, acetol, furfural, and butyric acid. Butyric acid has the highest boiling point temperature value at 163.5°C.⁸ Several noncondensable gases such as carbon monoxide, carbon dioxide, methane, and hydrogen are also evolved during pyrolysis at temperatures in the range of 300 to 400°C.¹ Levoglucosan, a tarry substance, may also be a major product obtained from slow pyrolysis of cellulose.³ Table A1.1 contains an estimation of the mass fractions of the pyrolytic products obtained from cellulose.

In order to avoid confusion, the distinction between the charring and pyrolysis processes should be noted. Charring, or blackening, of Celotex™ has been observed to begin around a temperature of 150 to 175°C.⁹ Pyrolysis, or the actual decomposition of Celotex™, may not begin until temperatures of about 300°C are reached.¹

Table A1.1. Pyrolytic products of cellulose

Product	Mass (%)
Organic liquid (tar) Methanol, acetaldehyde, acrolein, furan, acetone, benzene, toluene, furfural, ethylene, butyric acid, acetylene, ethane, propylene, propane, cyclopropane, butene, butane, pentene, pentane, acetic acid, propionic acid, acetol, levoglucosan, formic acid	80
Water	8
Gas CO CO ₂	8 (4) (4)
Char	4

REFERENCES

1. *Industrial Charcoal Making*, Food and Agricultural Organization of the United Nations, Paper Number 63.
2. T. Funazukuri, R. R. Hudgins, and P. L. Silveston, "Product Distribution for Flash Pyrolysis of Cellulose in a Coil Pyrolyzer," *Journal of Analytical and Applied Pyrolysis*, **10**, pp. 225-249 (1987).
3. T. Funazukuri, R. R. Hudgins, and P. L. Silveston, "Production Distribution in Pyrolysis of Cellulose in a Microfluidized Bed," *Journal of Analytical and Applied Pyrolysis*, **9**, pp. 139-158 (1986).
4. T. Funazukuri, R. R. Hudgins, and P. L. Silveston, "Product Yield Correlations for Cellulose Flash Pyrolysis," *Journal of Analytical and Applied Pyrolysis*, **13**, pp. 103-122 (1988).
5. J. Piskorz, D. Radlein, and D. S. Scott, "On the Mechanism of Rapid Pyrolysis of Cellulose," *Journal of Analytical and Applied Pyrolysis*, **9**, pp. 121-137 (1986).
6. J. Piskorz, D. Radlein, and D. S. Scott, "Pretreatment of Wood and Cellulose for Production of Sugars by Fast Pyrolysis," *Journal of Analytical and Applied Pyrolysis*, **16**, pp. 127-142 (1989).
7. R. Rodriguez, P. Magne, and X. Deglise, "Sugar Cane Bagasse as a Feedstock for an Industrial Fast Pyrolysis Process Under Development," *Journal of Analytical and Applied Pyrolysis*, **12**, pp. 301-318 (1987).
8. *Handbook of Chemistry and Physics*, Chemical Rubber Company, 53rd ed., CRC Press, Cleveland, Ohio, 1972.
9. G. G. Chalfant, *Safety Analysis Report - Packages USA/9965-9968 (DOE-SR) (Packaging of Fissile and Other Reactive Materials)*, DPSPU 83-124-1, 1984, pp. 3-65.

Appendix B

HEAT TRANSFER TO THE INNER CONTAINER

HEAT TRANSFER TO THE INNER CONTAINER

Due to the complexities and uncertainties involved in the heating of Celotex™ and the subsequent release and possible condensation of vapors at the inner container, a simplified model was developed which can be used to approximate the actual phenomena that occur. The only condensible modeled is butyric acid, which has the highest boiling point temperature (163.5°C) of the possible condensible vapors and can effectively raise the inner container temperature to the highest value possible through condensation alone. The condensation heat transfer coefficient, h_{cond} , can be determined from the following correlation for laminar film condensation on a vertical plate:¹

$$h_{\text{cond}} = 0.943 \{ [g\rho_l(\rho_l - \rho_v)k_l^3 h'_{fg}] / [\mu_l(T_{\text{sat}} - T_s)] \}^{1/4}, \quad (1)$$

where
$$h'_{fg} = h_{fg}(1 + 0.68\text{Ja}), \quad (2)$$

and

- h_{fg} = latent heat of evaporation,
- ρ_l = density of liquid phase,
- ρ_v = density of gas phase,
- k_l = thermal conductivity of liquid,
- μ_l = dynamic viscosity of liquid,
- T_{sat} = saturation temperature,
- T_s = surface temperature.

The Jakob number, Ja, is defined by

$$\text{Ja} = c_{p,l}(T_{\text{sat}} - T_s)/h_{fg}. \quad (3)$$

The condensation rate, $\dot{m}$, is determined from

$$\dot{m} = Q/h'_{fg}, \quad (4)$$

where Q, the condensation heat transfer, is determined from

$$Q = h_{\text{cond}}A(T_{\text{sat}} - T_s), \quad (5)$$

where A = surface area.

The heat transfer due to condensation may be converted into a volumetric heat generation rate by assuming it is uniformly distributed throughout the inner container volume. Table A2.1 contains values of the heat transfer coefficient, the condensation heat transfer rate, and the volumetric heat generation rate for butyric acid condensation at various surface temperatures for the DT-18 package. Values of these parameters for the PC-1 package are slightly different from the values presented in Table A2.1. However, they are obtained in the same manner as discussed above. The thermal properties of butyric acid are given in Table A2.2.²

Table A2.1. Butyric acid condensation parameters

Surface temperature (°C)	Heat transfer coefficient (W/m ² -K)	Heat transfer (kW)	Volumetric heat generation (W/m ³)
20	912.7	123.9	1.681E07
30	929.3	117.4	1.592E07
40	947.6	110.8	1.502E07
50	967.8	104.0	1.410E07
60	990.3	97.01	1.315E07
70	1016	89.90	1.219E07
80	1045	82.58	1.120E07
90	1079	75.05	1.017E07
100	1119	67.25	9.118E06
110	1168	59.14	8.018E06
120	1230	50.64	6.865E06
130	1313	41.63	5.644E06
140	1435	31.91	4.326E06
150	1648	21.06	2.855E06
160	2309	7.650	1.037E06

Table A2.2. Butyric acid properties

Thermal conductivity (W/m-K)	Density (kg/m ³)	Viscosity (Pa-s)	Enthalpy of evaporation (kJ/kg)	Specific heat (J/kg-K)
0.17134	957.7	3.0E-04	476.8	2.1547

When the temperature of the inner container reaches 163°C, the boiling point of butyric acid, condensation will no longer occur. From this point, heat is assumed to be transferred to the inner container by natural convection of the hot gases produced during pyrolysis. Information on cellulose pyrolysis indicates that at moderate pyrolysis temperatures, approximately 500°C, the noncondensable gas composition is approximately 50% carbon dioxide and 50% carbon monoxide.³ The free convection heat transfer coefficient may be approximated from the following correlation for the Nusselt number:¹

$$Nu_L = 0.825 + ((0.387Ra_L)/\{[1 + (0.492/Pr)^{9/16}]\}^{8/27})^2, \quad (6)$$

where Pr = Prandtl number.

The Rayleigh number, Ra_L , is defined as

$$Ra_L = g\beta(T - T_s)L^3/\nu\alpha, \quad (7)$$

where β = thermal expansion coefficient,
 T = hot gas temperature,
 ν = kinematic viscosity,
 α = thermal diffusivity,
 L = length.

The convection coefficient, h_{conv} , can be found from

$$h_{conv} = Nu_L k/L, \quad (8)$$

Table A2.3 contains values of the free convection heat transfer coefficient, the corresponding heat transfer rate, and the uniform heat generation rate within the DT-18 inner container for various inner container surface temperatures. These values were obtained assuming a gas temperature of 350°C, the average temperature documented for the evolution of noncondensable gases (see Appendix A).⁴ The gas properties used were taken as the average of carbon monoxide and carbon dioxide properties at 600 K (327°C) presented in Table A2.4.¹

The data points in Fig. A2.1 represent the volumetric heat generation rate in the DT-18 inner container due to condensation and convection as a function of the inner container temperature. Preliminary studies have shown that the sudden change in slope at the boiling point (163.5°C) can lead to rather large oscillations in inner container temperatures if the time step becomes too large. In order to eliminate this effect, the data were divided into three regions: Region I between 20 and 160°C, Region II between 160 and 170°C, and Region III between 170 and 345°C. Third-order polynomial curve fits were established for each region and the endpoints and the slopes were matched at 160 and 170°C. The following equations are used to calculate the value of the volumetric heat generation in the DT-18 inner container:

$$\text{I:} \quad q = 7.454 - 1.554E-02T_s + 2.295E-04T_s^2 - 1.179E-06T_s^3, \quad (9)$$

$$\text{II:} \quad q = -5887 + 107.6T_s - 6.538E-01T_s^2 + 1.323E-03T_s^3, \quad (10)$$

$$\text{III:} \quad q = 16.13 - 1.471E-01T_s + 6.470E-04T_s^2 - 9.567E-07T_s^3. \quad (11)$$

Table A2.3. Convection parameters

Surface temperature (°C)	Heat transfer coefficient (W/m ² -K)	Heat transfer (W)	Volumetric heat generation (W/m ³)
170	5.781	984.9	1.335E05
180	5.682	914.3	1.240E05
190	5.579	844.9	1.145E05
200	5.472	776.9	1.053E05
210	5.359	710.1	9.627E04
220	5.241	644.9	8.743E04
230	5.116	581.1	7.878E04
240	4.985	519.0	7.037E04
250	4.844	458.5	6.216E04
260	4.694	399.9	5.421E04
270	4.532	343.2	4.652E04
280	4.355	288.5	3.912E04
290	4.160	236.2	3.203E04
300	3.942	186.6	2.529E04
310	3.691	139.7	1.895E04
320	3.392	96.31	1.306E04
330	3.014	57.06	7.735E03
340	2.468	23.36	3.167E03

Table A2.4. Pyrolysis gas properties at 600 K

Gas	α (m ² /s)	ν (m ² /s)	k (W/m-K)	Pr
CO	51.0E-06	72.1E-06	44.0E-03	0.707
CO ₂	30.6E-06	42.7E-06	40.7E-03	0.717

Fig. A2.1. DT-18 volumetric heat generation rate.

Equations 9 to 11 represent the analytical functions for internal heat generation used in the HEATING 7.1 models. These equations for the DT-18 internal heat generation are plotted against the actual analytical solution in Fig. A2.1.

These models are conservative in that they allow the maximum possible rate of condensation to occur. The models also assume that the hot gases have a relatively unobstructed pathway to the payload container. The effect of reevaporation and, hence, cooling of the inner container, was not considered.

REFERENCES

1. F. P. Incropera and D. P. DeWitt, *Fundamentals of Heat and Mass Transfer*, John Wiley and Sons, New York, 1985.
2. *Handbook of Chemistry and Physics*, Chemical Rubber Company, 53rd ed., CRC Press, Cleveland, Ohio, 1972.
3. T. Funazukuri, R. R. Hudgins, and P. L. Silveston, "Production Distribution in Pyrolysis of Cellulose in a Microfluidized Bed," *Journal of Analytical and Applied Pyrolysis*, **9**, pp. 139-158 (1986).
4. *Industrial Charcoal Making*, Food and Agricultural Organization of the United Nations, Paper Number 63.

Appendix C

HEATING 7.1 INPUT FOR DT-18 PACKAGE WITHOUT HEAT GENERATION

HEATING 7.1 INPUT FOR DT-18 PACKAGE WITHOUT HEAT GENERATION

OPTIONS

MAXPTS=8750

@MAXPBT=1

@MWIDTH=37

@MAXCP=0

DT-18 - WITHOUT HEAT GENERATION - REGULATORY CASE -11/1/91

* SPECIFY THE CPU TIME ALLOWED, THE GEOMETRY TYPE (r-z), THE

* INITIAL TIME, AND THE TEMPERATURE UNITS (C)

10000 3 0. 1

* DEFINE THE REGIONS

REGIONS

1 1 0.2858 0.2873 0. 0. 0. 0.8317

1 0 0 1 0 0 2 3

2 1 0. 0.2858 0. 0. 0. 0.0015

1 0 0 0 0 0 2 0

3 1 0. 0.2858 0. 0. 0.8302 0.8317

1 0 0 0 0 0 0 3

4 2 0. 0.2604 0. 0. 0.0015 0.0269

1 0 0 0 0 0 0 0

5 2 0.2604 0.2858 0. 0. 0.0015 0.8302

1 0 0 0 0 0 0 0

6 2 0. 0.2604 0. 0. 0.8048 0.8302

1 0 0 0 0 0 0 0

7 2 0. 0.2318 0. 0. 0.0269 0.0904

1 0 0 0 0 0 0 0

8 2 0.2318 0.2604 0. 0. 0.0269 0.8048

1 0 0 0 0 0 0 0

9 2 0. 0.2318 0. 0. 0.7651 0.8048

1 0 0 0 0 0 0 0

10 2 0. 0.2032 0. 0. 0.0904 0.1539

1 0 0 0 0 0 0 0

11 2 0.2032 0.2318 0. 0. 0.0904 0.4587

1 0 0 0 0 0 0 0

12 2 0.1778 0.2318 0. 0. 0.4587 0.7651

1 0 0 0 0 0 0 0

13 2 0. 0.1778 0. 0. 0.7254 0.7651

1 0 0 0 0 0 0 0

14 3 0. 0.1984 0. 0. 0.1539 0.1698

1 0 0 0 0 0 0 0

15 3 0.1984 0.2032 0. 0. 0.1539 0.4365

1 0 0 0 0 0 0 0

16 3 0.1730 0.2032 0. 0. 0.4365 0.4587

1 0 0 0 0 0 0 0

17 3 0.1730 0.1778 0. 0. 0.4587 0.7095

```

1 0 0 0 0 0 0
18 3 0. 0.1778 0. 0. 0.7095 0.7254
1 0 0 0 0 0 0
* DEFINE THE MATERIALS USED IN THE MODEL
MATERIALS
1 STEEL1 1 7900 1 -1 0 -2 0
2 CELOTEX1 1 270 1 -3 0 -4 0
3 STEEL2 1 7900 1 -1 0 -2 0
* SPECIFY THE INITIAL TEMPERATURES
INITIAL TEMPERATURES
1 21.11
* SPECIFY THE BOUNDARY CONDITIONS
BOUNDARY CONDITIONS
1 1 0.0 -5 0 0 0
0.0 1.0 1.37 0.25 0.0 1
0 -8 0 0 0
2 1 0.0 -6 0 0 0
0.0 1.0 1.0 0.25 0.0 1
0 -9 -10 0 0
3 1 0.0 -7 0 0 0
0.0 1.0 1.0 0.25 0.0 1
0 -11 -12 0 0
* ESTABLISH THE NODE SPACING IN THE X (r) DIRECTION
XGRID
0.0 0.1000 0.1730 0.1778 0.1984 0.2032 0.2318 0.2604 0.2858 0.2873
16 11 1 3 1 5 9 16 1
* ESTABLISH THE NODE SPACING IN THE Z DIRECTION
ZGRID
0.0 0.0015 0.0269 0.0904 0.1539 0.1698 0.2397 0.4365 0.4587 0.6396
@0.7095 0.7254 0.7651 0.8048 0.8302 0.8317
1 16 20 10 3 11 31 3 28 11 3 6 13 16 1
TABULAR FUNCTIONS
* ENTER THE THERMAL CONDUCTIVITY DATA FOR STAINLESS STEEL
1
-73 12.6
@27 14.9
@127 16.6
@327 19.8
@527 22.6
@727 25.4
@927 28.0
* ENTER THE SPECIFIC HEAT DATA FOR STAINLESS STEEL
2
-73 402
@27 477
@127 515
@327 557
@527 582
@727 611

```

@927 640
 * ENTER THE THERMAL CONDUCTIVITY DATA FOR CELOTEX
 3
 25 0.053
 @86 0.059
 @146 0.063
 @226 0.065
 @278 0.051
 * ENTER THE SPECIFIC HEAT DATA FOR CELOTEX
 4
 25 1280
 @86 1506
 @146 1745
 @226 2046
 @278 2063
 * SPECIFY THE TIME DEPENDENT BOUNDARY TEMPERATURE FOR BOUNDARY
 * CONDITION #1
 5
 0.0 800
 @1800 800
 @1800.000001 21.11
 @12600 21.11
 * SPECIFY THE TIME DEPENDENT BOUNDARY TEMPERATURE FOR BOUNDARY
 * CONDITION #2
 6
 0.0 800
 @1800 800
 @1800.000001 21.11
 @12600 21.11
 * SPECIFY THE TIME DEPENDENT BOUNDARY TEMPERATURE FOR BOUNDARY
 * CONDITION #3
 7
 0.0 800
 @1800 800
 @1800.000001 21.11
 @12600 21.11
 * ENTER THE TIME DEPENDENT RADIATION FACTOR FOR BOUNDARY CONDITION
 * #1
 8
 0.0 4.166E-08
 @1800 4.166E-08
 @1800.000001 2.948E-08
 @12600 2.948E-08
 * ENTER THE TIME DEPENDENT RADIATION FACTOR FOR BOUNDARY CONDITION
 * #2
 9
 0.0 4.166E-08
 @1800 4.166E-08
 @1800.000001 2.948E-08

@12600 2.948E-08
 * ENTER THE TIME DEPENDENT CONVECTION COEFFICIENT FOR BOUNDARY
 * CONDITION #2
 10
 0.0 1.86
 @1800 1.86
 @1800.000001 0.88
 @12600 0.88
 * ENTER THE TIME DEPENDENT RADIATION FACTOR FOR BOUNDARY CONDITION
 * #3
 11
 0.0 4.166E-08
 @1800 4.166E-08
 @1800.000001 2.948E-08
 @12600 2.948E-08
 * ENTER THE TIME DEPENDENT CONVECTION COEFFICIENT FOR BOUNDARY
 * CONDITION #3
 12
 0.0 0.88
 @1800 0.88
 @1800.000001 1.86
 @12600 1.86
 * SPECIFY THE PRINTOUT TIMES
 PRINTOUT TIMES
 60 120 180 240 300 600 900 1200 1500 1800 1860 1920 1980 2040
 @2100 2400 2700 3600 4500 5400 6300 7200 8100 9000 9900
 @10800 11700 12600
 TRANSIENT
 * SPECIFY THE TRANSIENT SOLUTION TECHNIQUE AND THE FINAL TIME
 1 12600
 * SPECIFY THE INITIAL TIME STEP AND THE LEVY FACTOR
 0.0 1
 %

Appendix D

HEATING 7.1 INPUT FOR DT-18 PACKAGE WITH HEAT GENERATION

HEATING 7.1 INPUT FOR DT-18 PACKAGE WITH HEAT GENERATION

OPTIONS

MAXPTS=8750

@MAXPBT=1

@MWIDTH=37

@MAXCP=0

DT-18 - WITH HEAT GENERATION - REGULATORY CASE -11/1/91

* SPECIFY THE CPU TIME ALLOWED, THE GEOMETRY TYPE (r-z), THE

* INITIAL TIME, AND THE TEMPERATURE UNITS (C)

10000 3 0. 1

* DEFINE THE REGIONS

REGIONS

1 1 0.2858 0.2873 0. 0. 0. 0.8317

1 0 0 1 0 0 2 3

2 1 0. 0.2858 0. 0. 0. 0.0015

1 0 0 0 0 0 2 0

3 1 0. 0.2858 0. 0. 0.8302 0.8317

1 0 0 0 0 0 0 3

4 2 0. 0.2604 0. 0. 0.0015 0.0269

1 0 0 0 0 0 0 0

5 2 0.2604 0.2858 0. 0. 0.0015 0.8302

1 0 0 0 0 0 0 0

6 2 0. 0.2604 0. 0. 0.8048 0.8302

1 0 0 0 0 0 0 0

7 2 0. 0.2318 0. 0. 0.0269 0.0904

1 0 0 0 0 0 0 0

8 2 0.2318 0.2604 0. 0. 0.0269 0.8048

1 0 0 0 0 0 0 0

9 2 0. 0.2318 0. 0. 0.7651 0.8048

1 0 0 0 0 0 0 0

10 2 0. 0.2032 0. 0. 0.0904 0.1539

1 0 0 0 0 0 0 0

11 2 0.2032 0.2318 0. 0. 0.0904 0.4587

1 0 0 0 0 0 0 0

12 2 0.1778 0.2318 0. 0. 0.4587 0.7651

1 0 0 0 0 0 0 0

13 2 0. 0.1778 0. 0. 0.7254 0.7651

1 0 0 0 0 0 0 0

14 3 0. 0.1984 0. 0. 0.1539 0.1698

1 1 0 0 0 0 0 0

15 3 0.1984 0.2032 0. 0. 0.1539 0.4365

1 1 0 0 0 0 0 0

16 3 0.1730 0.2032 0. 0. 0.4365 0.4587

1 1 0 0 0 0 0 0

17 3 0.1730 0.1778 0. 0. 0.4587 0.7095

```

1 1 0 0 0 0 0
18 3 0. 0.1778 0. 0. 0.7095 0.7254
1 1 0 0 0 0 0
* DEFINE THE MATERIALS USED IN THE MODEL
MATERIALS
1 STEEL1 1 7900 1 -1 0 -2 0
2 CELOTEX1 1 270 1 -3 0 -4 0
3 STEEL2 1 7900 1 -1 0 -2 0
* SPECIFY THE INITIAL TEMPERATURES
INITIAL TEMPERATURES
1 21.11
* SPECIFY THE HEAT GENERATIONS USED IN THE MODEL
HEAT GENERATIONS
1 1.0 -13 1
* SPECIFY THE BOUNDARY CONDITIONS
BOUNDARY CONDITIONS
1 1 0.0 -5 0 0 0
0.0 1.0 1.37 0.25 0.0 1
0 -8 0 0 0
2 1 0.0 -6 0 0 0
0.0 1.0 1.0 0.25 0.0 1
0 -9 -10 0 0
3 1 0.0 -7 0 0 0
0.0 1.0 1.0 0.25 0.0 1
0 -11 -12 0 0
* ESTABLISH THE NODE SPACING IN THE X (r) DIRECTION
XGRID
0.0 0.1000 0.1730 0.1778 0.1984 0.2032 0.2318 0.2604 0.2858 0.2873
16 11 1 3 1 5 9 16 1
* ESTABLISH THE NODE SPACING IN THE Z DIRECTION
ZGRID
0.0 0.0015 0.0269 0.0904 0.1539 0.1698 0.2397 0.4365 0.4587 0.6396
@0.7095 0.7254 0.7651 0.8048 0.8302 0.8317
1 16 20 10 3 11 31 3 28 11 3 6 13 16 1
ANALYTICAL FUNCTIONS
1

TABULAR FUNCTIONS
* ENTER THE THERMAL CONDUCTIVITY DATA FOR STAINLESS STEEL
1
-73 12.6
@27 14.9
@127 16.6
@327 19.8
@527 22.6
@727 25.4
@927 28.0
* ENTER THE SPECIFIC HEAT DATA FOR STAINLESS STEEL
2

```

-73 402
 @27 477
 @127 515
 @327 557
 @527 582
 @727 611
 @927 640
 * ENTER THE THERMAL CONDUCTIVITY DATA FOR CELOTEX
 3
 25 0.053
 @86 0.059
 @146 0.063
 @226 0.065
 @278 0.051
 * ENTER THE SPECIFIC HEAT DATA FOR CELOTEX
 4
 25 1280
 @86 1506
 @146 1745
 @226 2046
 @278 2063
 * SPECIFY THE TIME DEPENDENT BOUNDARY TEMPERATURE FOR BOUNDARY
 * CONDITION #1
 5
 0.0 800
 @1800 800
 @1800.000001 21.11
 @12600 21.11
 * SPECIFY THE TIME DEPENDENT BOUNDARY TEMPERATURE FOR BOUNDARY
 * CONDITION #2
 6
 0.0 800
 @1800 800
 @1800.000001 21.11
 @12600 21.11
 * SPECIFY THE TIME DEPENDENT BOUNDARY TEMPERATURE FOR BOUNDARY
 * CONDITION #3
 7
 0.0 800
 @1800 800
 @1800.000001 21.11
 @12600 21.11
 * SPECIFY THE TIME DEPENDENT RADIATION FACTOR FOR BOUNDARY
 * CONDITION #1
 8
 0.0 4.166E-08
 @1800 4.166E-08
 @1800.000001 2.948E-08
 @12600 2.948E-08

* SPECIFY THE TIME DEPENDENT RADIATION FACTOR FOR BOUNDARY
 * CONDITION #2
 9
 0.0 4.166E-08
 @1800 4.166E-08
 @1800.000001 2.948E-08
 @12600 2.948E-08
 * SPECIFY THE TIME DEPENDENT CONVECTION COEFFICIENT FOR BOUNDARY

 * CONDITION #2
 10
 0.0 1.86
 @1800 1.86
 @1800.000001 0.88
 @12600 0.88
 * SPECIFY THE TIME DEPENDENT RADIATION FACTOR FOR BOUNDARY
 * CONDITION #3
 11
 0.0 4.166E-08
 @1800 4.166E-08
 @1800.000001 2.948E-08
 @12600 2.948E-08
 * SPECIFY THE TIME DEPENDENT CONVECTION COEFFICIENT FOR BOUNDARY
 * CONDITION #3
 12
 0.0 0.88
 @1800 0.88
 @1800.000001 1.86
 @12600 1.86
 * SPECIFY THE TIME DEPENDENCE OF THE HEAT GENERATION FUNCTION
 13
 0.0 0
 @60 1.0
 @1800 1.0
 @1800.000001 0
 @12600 0
 * SPECIFY THE PRINTOUT TIMES
 PRINTOUT TIMES
 60 120 180 240 300 600 900 1200 1500 1800 1860 1920 1980 2040
 @2100 2400 2700 3600 4500 5400 6300 7200 8100 9000 9900
 @10800 11700 12600
 TRANSIENT
 * SPECIFY THE TRANSIENT SOLUTION TECHNIQUE AND THE FINAL TIME
 1 12600
 * SPECIFY THE INITIAL TIME STEP AND THE LEVY FACTOR
 0.0 1
 %

Appendix E

HEATING 7.1 INPUT FOR PC-1 PACKAGE WITHOUT HEAT GENERATION

HEATING 7.1 INPUT FOR PC-1 PACKAGE WITHOUT HEAT GENERATION

OPTIONS

MAXPTS=14000

@MAXPBT=0

@MWIDTH=37

@MAXCP=0

PC-1 - WITHOUT HEAT GENERATION - JCA - 11/5/91

* SPECIFY THE CPU TIME ALLOWED, THE GEOMETRY TYPE (r-z), THE

* INITIAL TIME, AND THE TEMPERATURE UNITS (C)

10000 3 0. 1

* DEFINE THE REGIONS

REGIONS

1 1 0. 0.381 0. 0. 0. 0.0015

1 0 0 1 0 0 2 0

2 1 0.3795 0.381 0. 0. 0.0015 1.2606

1 0 0 1 0 0 0 0

3 1 0. 0.381 0. 0. 1.2606 1.2621

1 0 0 1 0 0 0 3

4 4 0. 0.2547 0. 0. 0.1048 0.1096

1 0 0 0 0 0 0 0

5 4 0.2547 0.2596 0. 0. 0.1048 1.1367

1 0 0 0 0 0 0 0

6 4 0. 0.2547 0. 0. 1.1318 1.1367

1 0 0 0 0 0 0 0

7 2 0. 0.3795 0. 0. 0.0015 0.0445

1 0 0 0 0 0 0 0

8 2 0. 0.3795 0. 0. 0.0445 0.0699

1 0 0 0 0 0 0 0

9 2 0. 0.3795 0. 0. 0.0699 0.0953

1 0 0 0 0 0 0 0

10 3 0. 0.3795 0. 0. 0.0953 0.1048

1 0 0 0 0 0 0 0

11 2 0.2596 0.3795 0. 0. 0.1048 0.2064

1 0 0 0 0 0 0 0

12 3 0.2596 0.3795 0. 0. 0.2064 0.2159

1 0 0 0 0 0 0 0

13 2 0.2596 0.3795 0. 0. 0.2159 0.3175

1 0 0 0 0 0 0 0

14 3 0.2596 0.3795 0. 0. 0.3175 0.3270

1 0 0 0 0 0 0 0

15 2 0.2596 0.3795 0. 0. 0.3270 0.4286

1 0 0 0 0 0 0 0

16 3 0.2596 0.3795 0. 0. 0.4286 0.4382

1 0 0 0 0 0 0 0

17 2 0.2596 0.3795 0. 0. 0.4382 0.5398

```

1 0 0 0 0 0 0
18 3 0.2596 0.3795 0. 0. 0.5398 0.5493
1 0 0 0 0 0 0
19 2 0.2596 0.3795 0. 0. 0.5493 0.6509
1 0 0 0 0 0 0
20 3 0.2596 0.3795 0. 0. 0.6509 0.6699
1 0 0 0 0 0 0
21 2 0.2596 0.3795 0. 0. 0.6699 0.7684
1 0 0 0 0 0 0
22 3 0.2596 0.3795 0. 0. 0.7684 0.7779
1 0 0 0 0 0 0
23 2 0.2596 0.3795 0. 0. 0.7779 0.8763
1 0 0 0 0 0 0
24 3 0.2596 0.3795 0. 0. 0.8763 0.8858
1 0 0 0 0 0 0
25 2 0.2596 0.3795 0. 0. 0.8858 0.9843
1 0 0 0 0 0 0
26 3 0.2596 0.3795 0. 0. 0.9843 0.9938
1 0 0 0 0 0 0
27 2 0.2596 0.3795 0. 0. 0.9938 1.1271
1 0 0 0 0 0 0
28 3 0.2596 0.3795 0. 0. 1.1271 1.1367
1 0 0 0 0 0 0
29 3 0. 0.3795 0. 0. 1.1367 1.1462
1 0 0 0 0 0 0
30 2 0. 0.3795 0. 0. 1.1462 1.1827
1 0 0 0 0 0 0
31 2 0. 0.3795 0. 0. 1.1827 1.2192
1 0 0 0 0 0 0
32 2 0. 0.3069 0. 0. 1.2192 1.2606
1 0 0 0 0 0 0
33 2 0.3069 0.3541 0. 0. 1.2192 1.2606
1 0 0 0 0 0 0
34 2 0.3541 0.3795 0. 0. 1.2192 1.2606
1 0 0 0 0 0 0
* DEFINE THE MATERIALS USED IN THE MODEL
MATERIALS
1 STEEL1 1 7900 1 -1 0 -2 0
2 CELOTEX 1 270 1 -3 0 -4 0
3 WOOD 0.11 415. 2720.
4 STEEL2 1 7900 1 -1 0 -2 0
* SPECIFY THE INITIAL TEMPERATURES
INITIAL TEMPERATURES
1 21.11
* SPECIFY THE BOUNDARY CONDITIONS
BOUNDARY CONDITIONS
1 1 0.0 -5 0 0 0
0.0 1.0 1.37 0.25 0.0 1
0 -8 0 0 0

```

2 1 0.0 -6 0 0 0
0.0 1.0 1.0 0.25 0.0 1
0 -9 -10 0 0
3 1 0.0 -7 0 0 0
0.0 1.0 1.0 0.25 0.0 1
0 -11 -12 0 0

* ESTABLISH THE NODE SPACING IN THE X (r) DIRECTION

XGRID

0. 0.2547 0.2596 0.3069 0.3541 0.3795 0.381

40 1 7 15 16 1

* ESTABLISH THE NODE SPACING IN THE Z DIRECTION

ZGRID

0. 0.0015 0.0445 0.0699 0.0953 0.1048 0.1096 0.2064 0.2159

@0.3175 0.3270 0.4286 0.4382 0.5398 0.5493 0.6509 0.6699

@0.7684 0.7779 0.8763 0.8858 0.9843 0.9938 1.1271 1.1318

@1.1367 1.1462 1.1827 1.2192 1.2606 1.2621

1 27 8 4 1 1 15 1 16 1 16 1 16 1 16 3 16 1 15 1 16 1 21 1 1

@1 6 11 26 1

TABULAR FUNCTIONS

* ENTER THE THERMAL CONDUCTIVITY DATA FOR STAINLESS STEEL

1

-73 12.6

@27 14.9

@127 16.6

@327 19.8

@527 22.6

@727 25.4

@927 28.0

* ENTER THE SPECIFIC HEAT DATA FOR STAINLESS STEEL

2

-73 402

@27 477

@127 515

@327 557

@527 582

@727 611

@927 640

* ENTER THE THERMAL CONDUCTIVITY DATA FOR CELOTEX

3

25 0.053

@86 0.059

@146 0.063

@226 0.065

@278 0.051

* ENTER THE SPECIFIC HEAT DATA FOR CELOTEX

4

25 1280

@86 1506

@146 1745
 @226 2046
 @278 2063
 * SPECIFY THE TIME DEPENDENT BOUNDARY TEMPERATURE FOR BOUNDARY
 * CONDITION #1
 5
 0.0 800
 @2520 800
 @2520.000001 21.11
 @12600 21.11

 * SPECIFY THE TIME DEPENDENT BOUNDARY TEMPERATURE FOR BOUNDARY
 * CONDITION #2
 6
 0.0 800
 @2520 800
 @2520.000001 21.11
 @12600 21.11
 * SPECIFY THE TIME DEPENDENT BOUNDARY TEMPERATURE FOR BOUNDARY
 * CONDITION #3
 7
 0.0 800
 @2520 800
 @2520.000001 21.11
 @12600 21.11
 * SPECIFY THE TIME DEPENDENT RADIATION FACTOR FOR BOUNDARY
 * CONDITION #1
 8
 0.0 4.166E-08
 @2520 4.166E-08
 @2520.000001 2.948E-08
 @12600 2.948E-08
 * SPECIFY THE TIME DEPENDENT RADIATION FACTOR FOR BOUNDARY
 * CONDITION #2
 9
 0.0 4.166E-08
 @2520 4.166E-08
 @2520.000001 2.948E-08
 @12600 2.948E-08
 * SPECIFY THE TIME DEPENDENT CONVECTION COEFFICIENT FOR BOUNDARY
 * CONDITION #2
 10
 0.0 1.86
 @2520 1.86
 @2520.000001 0.88
 @12600 0.88
 * SPECIFY THE TIME DEPENDENT RADIATION FACTOR FOR BOUNDARY
 * CONDITION #3
 11

0.0 4.166E-08
 @2520 4.166E-08
 @2520.000001 2.948E-08
 @12600 2.948E-08
 * SPECIFY THE TIME DEPENDENT CONVECTION COEFFICIENT FOR BOUNDARY
 * CONDITION #3
 12
 0.0 0.88
 @2520 0.88
 @2520.000001 1.86
 @12600 1.86
 * SPECIFY THE PRINTOUT TIMES
 PRINTOUT TIMES
 60 120 180 240 300 600 900 1200 1500 1800 2100
 @2400 2520 2580 2640 2700 3000 3300 3600 4500 5400 6300
 @7200 8100 9000 9900 10800 11700 12600
 TRANSIENT
 * SPECIFY THE TRANSIENT SOLUTION TECHNIQUE AND THE FINAL TIME
 1 12600
 * SPECIFY THE INITIAL TIME STEP AND THE LEVY FACTOR
 0.0 1
 %

Appendix F

HEATING 7.1 INPUT FOR PC-1 PACKAGE WITH HEAT GENERATION

HEATING 7.1 INPUT FOR PC-1 PACKAGE WITH HEAT GENERATION

OPTIONS

MAXPTS=14000

@MAXPBT=0

@MWIDTH=37

@MAXCP=0

PC-1 - WITH HEAT GENERATION - JCA - 11/5/91

* SPECIFY THE CPU TIME ALLOWED, THE GEOMETRY TYPE (r-z), THE

* INITIAL TIME, AND THE TEMPERATURE UNITS (C)

10000 3 0. 1

* DEFINE THE REGIONS

REGIONS

1 1 0. 0.381 0. 0. 0. 0.0015

1 0 0 1 0 0 2 0

2 1 0.3795 0.381 0. 0. 0.0015 1.2606

1 0 0 1 0 0 0 0

3 1 0. 0.381 0. 0. 1.2606 1.2621

1 0 0 1 0 0 0 3

4 4 0. 0.2547 0. 0. 0.1048 0.1096

1 1 0 0 0 0 0 0

5 4 0.2547 0.2596 0. 0. 0.1048 1.1367

1 1 0 0 0 0 0 0

6 4 0. 0.2547 0. 0. 1.1318 1.1367

1 1 0 0 0 0 0 0

7 2 0. 0.3795 0. 0. 0.0015 0.0445

1 0 0 0 0 0 0 0

8 2 0. 0.3795 0. 0. 0.0445 0.0699

1 0 0 0 0 0 0 0

9 2 0. 0.3795 0. 0. 0.0699 0.0953

1 0 0 0 0 0 0 0

10 3 0. 0.3795 0. 0. 0.0953 0.1048

1 0 0 0 0 0 0 0

11 2 0.2596 0.3795 0. 0. 0.1048 0.2064

1 0 0 0 0 0 0 0

12 3 0.2596 0.3795 0. 0. 0.2064 0.2159

1 0 0 0 0 0 0 0

13 2 0.2596 0.3795 0. 0. 0.2159 0.3175

1 0 0 0 0 0 0 0

14 3 0.2596 0.3795 0. 0. 0.3175 0.3270

1 0 0 0 0 0 0 0

15 2 0.2596 0.3795 0. 0. 0.3270 0.4286

1 0 0 0 0 0 0 0

16 3 0.2596 0.3795 0. 0. 0.4286 0.4382

1 0 0 0 0 0 0 0

17 2 0.2596 0.3795 0. 0. 0.4382 0.5398

```

1 0 0 0 0 0 0
18 3 0.2596 0.3795 0. 0. 0.5398 0.5493
1 0 0 0 0 0 0
19 2 0.2596 0.3795 0. 0. 0.5493 0.6509
1 0 0 0 0 0 0
20 3 0.2596 0.3795 0. 0. 0.6509 0.6699
1 0 0 0 0 0 0
21 2 0.2596 0.3795 0. 0. 0.6699 0.7684
1 0 0 0 0 0 0
22 3 0.2596 0.3795 0. 0. 0.7684 0.7779
1 0 0 0 0 0 0
23 2 0.2596 0.3795 0. 0. 0.7779 0.8763
1 0 0 0 0 0 0
24 3 0.2596 0.3795 0. 0. 0.8763 0.8858
1 0 0 0 0 0 0
25 2 0.2596 0.3795 0. 0. 0.8858 0.9843
1 0 0 0 0 0 0
26 3 0.2596 0.3795 0. 0. 0.9843 0.9938
1 0 0 0 0 0 0
27 2 0.2596 0.3795 0. 0. 0.9938 1.1271
1 0 0 0 0 0 0
28 3 0.2596 0.3795 0. 0. 1.1271 1.1367
1 0 0 0 0 0 0
29 3 0. 0.3795 0. 0. 1.1367 1.1462
1 0 0 0 0 0 0
30 2 0. 0.3795 0. 0. 1.1462 1.1827
1 0 0 0 0 0 0
31 2 0. 0.3795 0. 0. 1.1827 1.2192
1 0 0 0 0 0 0
32 2 0. 0.3069 0. 0. 1.2192 1.2606
1 0 0 0 0 0 0
33 2 0.3069 0.3541 0. 0. 1.2192 1.2606
1 0 0 0 0 0 0
34 2 0.3541 0.3795 0. 0. 1.2192 1.2606
1 0 0 0 0 0 0
* DEFINE THE MATERIALS USED IN THE MODEL
MATERIALS
1 STEEL1 1 7900 1 -1 0 -2 0
2 CELOTEX 1 270 1 -3 0 -4 0
3 WOOD 0.11 415. 2720.
4 STEEL2 1 7900 1 -1 0 -2 0
* SPECIFY THE INITIAL TEMPERATURES
INITIAL TEMPERATURES
1 21.11
* SPECIFY THE HEAT GENERATIONS USED IN THE MODEL
HEAT GENERATIONS
1 1.0 -13 1
* SPECIFY THE BOUNDARY CONDITIONS
BOUNDARY CONDITIONS

```

1 1 0.0 -5 0 0 0
0.0 1.0 1.37 0.25 0.0 1
0 -8 0 0 0
2 1 0.0 -6 0 0 0
0.0 1.0 1.0 0.25 0.0 1
0 -9 -10 0 0
3 1 0.0 -7 0 0 0
0.0 1.0 1.0 0.25 0.0 1
0 -11 -12 0 0

* ESTABLISH THE NODE SPACING IN THE X (r) DIRECTION

XGRID

0. 0.2547 0.2596 0.3069 0.3541 0.3795 0.381

40 1 7 15 16 1

* ESTABLISH THE NODE SPACING IN THE Z DIRECTION

ZGRID

0. 0.0015 0.0445 0.0699 0.0953 0.1048 0.1096 0.2064 0.2159

@0.3175 0.3270 0.4286 0.4382 0.5398 0.5493 0.6509 0.6699

@0 7684 0.7779 0.8763 0.8858 0.9843 0.9938 1.1271 1.1318

@1.1367 1.1462 1.1827 1.2192 1.2606 1.2621

1 27 8 4 1 1 15 1 16 1 16 1 16 3 16 1 15 1 16 1 21 1 1

@1 6 11 26 1

ANALYTICAL FUNCTIONS

1

TABULAR FUNCTIONS

* ENTER THE THERMAL CONDUCTIVITY DATA FOR STAINLESS STEEL

1

-73 12.6

@27 14.9

@127 16.6

@327 19.8

@527 22.6

@727 25.4

@927 28.0

* ENTER THE SPECIFIC HEAT DATA FOR STAINLESS STEEL

2

-73 402

@27 477

@127 515

@327 557

@527 582

@727 611

@927 640

* ENTER THE THERMAL CONDUCTIVITY DATA FOR CELOTEX

3

25 0.053

@86 0.059

@146 0.063

@226 0.065

@278 0.051

* ENTER THE SPECIFIC HEAT DATA FOR CELOTEX

4

25 1280

@86 1506

@146 1745

@226 2046

@278 2063

* SPECIFY THE TIME DEPENDENT BOUNDARY TEMPERATURE FOR BOUNDARY

* CONDITION #1

5

0.0 800

@2520 800

@2520.000001 21.11

@12600 21.11

* SPECIFY THE TIME DEPENDENT BOUNDARY TEMPERATURE FOR BOUNDARY

* CONDITION #2

6

0.0 800

@2520 800

@2520.000001 21.11

@12600 21.11

* SPECIFY THE TIME DEPENDENT BOUNDARY TEMPERATURE FOR BOUNDARY

* CONDITION #3

7

0.0 800

@2520 800

@2520.000001 21.11

@12600 21.11

* SPECIFY THE TIME DEPENDENT RADIATION FACTOR FOR BOUNDARY

* CONDITION #1

8

0.0 4.166E-08

@2520 4.166E-08

@2520.000001 2.948E-08

@12600 2.948E-08

* SPECIFY THE TIME DEPENDENT RADIATION FACTOR FOR BOUNDARY

* CONDITION #2

9

0.0 4.166E-08

@2520 4.166E-08

@2520.000001 2.948E-08

@12600 2.948E-08

* SPECIFY THE TIME DEPENDENT CONVECTION COEFFICIENT FOR BOUNDARY

* CONDITION #2

10

0.0 1.86

@2520 1.86
 @2520.000001 0.88
 @12600 0.88
 * SPECIFY THE TIME DEPENDENT RADIATION FACTOR FOR BOUNDARY
 * CONDITION #3
 11
 0.0 4.166E-08
 @2520 4.166E-08
 @2520.000001 2.948E-08
 @12600 2.948E-08
 * SPECIFY THE TIME DEPENDENT CONVECTION COEFFICIENT FOR BOUNDARY
 * CONDITION #3
 12
 0.0 0.88
 @2520 0.88
 @2520.000001 1.86
 @12600 1.86
 * SPECIFY THE TIME DEPENDENCE OF THE HEAT GENERATION FUNCTION
 13
 0.0 0
 @60 1.0
 @2520 1.0
 @2520.000001 0
 @12600 0
 * SPECIFY THE PRINTOUT TIMES
 PRINTOUT TIMES
 60 120 180 240 300 600 900 1200 1500 1800 2100
 @2400 2520 2580 2640 2700 3000 3300 3600 4500 5400 6300
 7200 8100 9000 9900 10800 11700 12600
 TRANSIENT
 * SPECIFY THE TRANSIENT SOLUTION TECHNIQUE AND THE FINAL TIME
 1 12600
 * SPECIFY THE INITIAL TIME STEP AND THE LEVY FACTOR
 0.0 1
 %

INTERNAL DISTRIBUTION

1-5.	J. C. Anderson	23.	T. L. Ryan
6.	H. C. Beeson	24.	J. C. Salyers
7.	J. P. Belk	25.	W. C. Stoddart
8.	R. W. Bieniek	26.	E. Stumpfl
9.	B. B. Bowden	27.	A. J. Szady, Jr.
10.	J. F. DeClue	28.	P. A. Tabor
11.	J. R. Dixon	29.	D. A. Tollefson
12.	D. A. Dyslin	30.	M. S. Walker
13.	B. F. Elam	31.	J. C. Walls
14.	M. R. Feldman	32.	D. E. Welch
15.	C. P. Frew	33.	W. R. Williams
16.	R. W. Glass	34-35.	Central Research Library
17.	R. F. Holdaway	36.	Y-12 Technical Reference Section
18.	K. G. Kahl	37.	Y-12 Plant Records
19.	C. D. Liles	38.	Laboratory Records
20.	S. D. Moses	39.	Laboratory Records - Record Copy
21.	W. O. Nobles	40.	ORNL Patent Section
22.	R. D. Poor		

EXTERNAL DISTRIBUTION

- 41. Assistant manager for Energy Research and Development, DOE-OR, P.O. Box 2001, Oak Ridge, TN 37831-8600
- 42. Frank Punch, U.S. Department of Energy, EH-33.3 GTN, Washington, D.C. 20585
- 43. Roger W. Carlson, Lawrence Livermore National Laboratory, P. O. Box 808, Mail Code L-197, Livermore, CA 94551
- 44. Larry E. Fischer, Lawrence Livermore National Laboratory, P. O. Box 808, Mail Code L-197, Livermore, CA 94551
- 45. James H. VanSant, Lawrence Livermore National Laboratory, P. O. Box 808, Mail Code L-197, Livermore, CA 94551
- 46-57. Office of Scientific and Technical Information, Bldg. 1916-T1, Oak Ridge Turnpike, Oak Ridge, TN 37830

END

**DATE
FILMED**

7 / 27 / 92