DOE/NV/10872--T16

DE92 014674

**SIX MONTH PROGRESS REPORT ON THE WASTE PACKAGE PROJECT AT THE
UNIVERSITY OF NEVADA, LAS VEGAS**

JULY 1991 - JANUARY 1992

PRESENTED TO:

**THE U.S. DEPARTMENT OF ENERGY
LAS VEGAS, NEVADA**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Table of Contents

I.	Introduction and Overview.	1-2
II.	Task Assignments for the Waste Package Project	2-3
III.	Equipment Acquisitions	3
IV.	Staff meetings with DOE Personnel, TPO Meetings and Travels on Behalf of the Project	4
V.	Papers Published by Project Staff.	4-5

Attached Documents

Papers Accepted for Publications in the Proceedings of the High Level Nuclear Fuel Conference, Las Vegas, Nevada

Task A.2 -- Waste Container Design -- Drs. R. Skaggs and S. Moujaes, Y. Lei and V. Veeramachaneni

Task A.3 -- ASME Pressure Vessel Code -- Dr. M. Trabia and M. Kiley

Task A.4 -- Waste Package Labeling -- Dr. W. Culbreth and A.K. Chagari

Supplemental Task B.1 -- Structural Analysis and Design Waste Package Container -- Dr. S. Ladkany and B. Kniss

Supplemental Task B.2 -- Design Requirements of Various Rock Tunnel Shapes for Long Term Storage of High Level Waste -- N.K.-Ladkany and Dr. R. Wyman

Supplemental Task B.3 -- Transport Phenomena in the Near Field -- Dr. J. Cardle and M. Joseph

**DOE WASTE PACKAGE PROJECT
STAFF DIRECTORY**

Project Office TBE, Room B120
Graduate Assistant's Office TBE, Room B107

Administration, Faculty and Staff

Richard V. Wyman	Project Manager Professor of Civil Engineering TBE Room A-218; 739-3940/3701
Samaan G. Ladkany	Director, Co-Projector Investigator Professor of Civil Engineering TBE Room B-114; 739-3438/3701
William Culbreth	Associate Professor of Civil Engineering Co-Project Investigator TBE Room B-136; 739-3426/4153
Phyllis J. Norris	Management Assistant II TBE Room B-120; 597-4328; FAX Number 739-0962
James Cardle	Associate Professor of Civil Engineering TBE Room B-128; 739-3941
Samir Moujaes	Associate Professor of Mechanical Engineering TBE Room B-134; 739-3265
Robert Skaggs	Professor of Mechanical Engineering TBE Room B-112; 739-3139
Mohamed Trabia	Assistant Professor of Mechanical Engineering TBE Room B-124; 739-0957

Adjunct Faculty, Graduate Assistants and Students

Moses Karakouzian	Associate Professor of Civil Engineering TBE Room B-132; 739-0959
Woosoon Yim	Assistant Professor of Mechanical Engineering TBE Room B-126; 739-0957
Ping Gan (Visiting Scholar)	
Joseph Bosse	
Martin Joseph (GA)	Rajkumar Rajagopalan (GA)
Mark Kiley	Amritraj Singh (GA)
Yao Lei	Gina Vaughan
Vijayachander Musukula	Venugopal Veeramachaneni
Michael Nalley (GA)	Paige Zielinski

**SIX MONTH PROGRESS REPORT ON THE WASTE PACKAGE PROJECT AT THE
UNIVERSITY OF NEVADA, LAS VEGAS
JULY 1991 - JANUARY 1992
MANAGEMENT, QUALITY ASSURANCE AND OVERVIEW**

**DR. SAMAAAN G. LADKANY, P.E.
PROJECT DIRECTOR, CO-PI**

I. Introduction and Over View

The Waste Package Project was renewed for a second year by the DOE on June 17, 1991 under the five-year UNLV/DOE cooperative agreement. The present period will cover one calendar year.

The UNLV project staff will concentrate their research efforts on analytical studies, design considerations, literature surveys and data collection pertaining to the various design aspects of a waste package and its near field considered in the Engineered Barrier System to be used for the long-term storage of high level nuclear waste in a geologic formation.

The project staff includes:

Dr. Samaan G. Ladkany, Professor, Director and Co-PI
Dr. Richard Wyman, Professor and Manager
Dr. William Culbreth, Associate Professor and Co-PI
Dr. Mohamed Trabia, Assistant Professor
Dr. Robert Skaggs, Professor
Dr. James Cardle, Associate Professor
Dr. Samir Moujaes, Associate Professor
Ten graduate students and two seniors
Phyllis Norris, Project Secretary

Studies of the metal container structure and a novel designs along with the package near field phenomena, such as fluid transport and heat transfer through porous media, and the design and layout of rock tunnels will also be attempted by the project research staff.

II. Task Assignments for the Waste Package Project

The following personnel have been assigned to the various tasks outlined in the cooperative agreement document. Supplemental tasks listed in section B were agreed upon in the DOE/UNLV meeting held at 9:00-12:00 a.m., 11 July 1990 at UNLV and were formally included in the proposal this year.

A. Required Tasks

1. Management, Quality Assurance, and Overview

Project Manager: Dr. Wyman

Project Director: Dr. Ladkany

a. Insure training and quality requirements met. [Wyman, Ladkany]

b. Overview of task #2 [Ladkany]

- c. Overview of task #3 [Trabia]
- d. Overview of task #4 [Culbreth]
- e. Overview of task #B.1 [Ladkany]
  - Overview of task #B.2 [Wyman]
  - Overview of task #B.3 [Cardle]

2. Container design and performance

Team Leader: Dr. Ladkany

Drs. Skaggs, Moujaes

3. ASME Pressure Vessel Code Review for Waste Package Application

Team Leader: Dr. Trabia

Drs. Moujaes, Cardle

4. Waste Package Labeling

Team Leader: Dr. Culbreth

5. Criticality and heat transfer in the Waste Package

Team Leader: Dr. Culbreth

B. Supplemental Tasks

1. Structural Analysis and Design of Waste Package Container

Team Leader: Dr. Ladkany

2. Optimum Design of Rock Tunnel Shapes

Team Leader: Dr. Wyman

3. Fluid transport and heat transfer through porous media in the waste package near field environment.

Team Leader: Dr. Cardle

Drs. Culbreth and Cardle

III. **Equipment Acquisitions**

The project acquired a Unix based Spark Station II Desk Top computer, one GB hard disk, two 80-486 AT's and two H.P. printers.

IV. Staff meetings with DOE personnel, TPO meetings and travels on behalf of project

Drs. Ladkany and Wyman attended the TPO meetings held regularly by the YMP at the DOE headquarters in Las Vegas.

Drs. Ladkany and Trabia attended the World Robotics Conference in Pittsburgh, Pennsylvania where Dr. Trabia chaired a session and Dr. Ladkany presented a paper entitled "The Dynamic Response of a Three-Link Flexible Robot Using Strain Gauges and Lagrange Polynomials." Dr. Cardle attended the sessions on fluid transport through porous media at the ASME Winter annual meetings.

Project staff attended the hearings held by the DOE at the San Tropez Hotel in Las Vegas.

Drs. Stahl and Morrisette met with the project staff in November 1991, and discussed issues relevant to the project research tasks.

A half day meeting between the project staff and our DOE counterparts will be held in early March 1992, in which the project researchers will present summaries of their work.

V. Papers Published by Project Staff

Five papers written by the project staff have been accepted for publication in the proceedings of the High Level Nuclear Waste Conference in Las Vegas, Nevada, March 1992. They are:

1. Trabia, M.B. and Kiley, M. "ASME Pressure Vessel Code Application To Nuclear Waste Container Design" (paper #69)
2. Ladkany, S.G. and Kniss, B. "Critical Stresses in Pintle, Weldment & Tophead of Nuclear Waste Container" (paper #119)
3. Culbreth, W. and Chagari, A.K. "Labeling of the Spent Fuel Waste Package" (paper #120)

4. Yfantis, A., Miel, G., Gallitano, G.M. "Theory of Chaos and Radionuclide Distribution" (paper #121)
5. Kandalaft-Ladkany, N., R. Wyman "Stress Analysis and Design of Rock Tunnels Under Thermal Loading" (paper #144)
6. Skaggs, R., Moujaes, S., Lei, Y., Veeramachaneni, V. "Thermal and Metallurgical Considerations of a Novel Design for the Nuclear Waste Container."

Task A.2 - Waste Container Design

**THERMAL AND METALLURGICAL CONSIDERATIONS OF A NOVEL DESIGN FOR THE
NUCLEAR WASTE CONTAINER**

Dr. Robert Skaggs and Dr. Samir Moujaes

Graduate Students: Yao Lei and Venugopal Veeramachaneni

THERMAL AND METALLURGICAL CONSIDERATIONS OF A NOVEL DESIGN FOR THE NUCLEAR WASTE CONTAINER

Dr.R.Skaggs, Dr.S.Moujaes, Y.Lei, V.V.Gopal
Department of Civil and Mechanical Engineering
University of Nevada, Las Vegas, NV 89154
P.No. (702) 739 3701

Abstract

The Departments of Civil and Mechanical Engineering at University of Nevada, Las Vegas are involved in the *high level nuclear waste project*. Designing containers for long term disposal of spent nuclear fuel and high level radioactive waste, is one of the project tasks. A multi-barrier robust waste containment scheme is being, actively researched, as preliminary work, has shown that, this scheme would better resist the degradation mechanisms set up by phenomena such as *geological activity, water immersion, occurrence of mechanical loading, dry oxidizing conditions and wet reducing conditions*. The physical configuration of the waste canister, has an inner shell of *copper base alloy*, to resist a wet reducing environment, an outer shell of *nickel base alloy*, to resist dry and oxidizing conditions and a *nonconducting oxide barrier* to separate the two metallic barriers. *Cement concrete* is being considered for this role. With 10cm of concrete between the metal alloy shells and the maximum allowable thermal loads reaching 4740W, the possibility of reaching temperatures, that could be detrimental to concrete is real (i.e 300°C and above). The temperature of the inner shell, to a great degree is a function of the thickness of the *oxidic concrete layer*. Another possible option being studied is the use of *alumina* as a sandwich, between the two metal shells. With the 10cm alumina the maximum inner shell temperature will be 230°C. To maintain the inner shell at a relatively lower temperature, only a single *copper base* container will be used at the time of emplacement. After a period of 50 years, the waste is either retrieved for processing or the system is upgraded to a permanent multi-barrier system

1 Introduction

All canisters, under consideration in current concepts are cylindrical and consist of thin walled stainless steel, thin walled titanium, thick walled steel, thick walled copper and thick walled concrete containers. Most of the proposed designs include special features, such as *corrosion resistance, thermal and structural stability*. Very few of the above are multi-barriered designs, the German Pollux design being an exception. It has a *manganese* and *nickel* steel inner shell, with an 8mm *Hastalloy* coating for corrosion resistance, a 100mm polyethylene sandwich liner, and an outer shell made of *GGG40* ductile cast iron. The Canadian and the U.S reference designs are single barrier. The Canadian uses a thin titanium shell¹. The U.S reference design has evolved, from an analysis of several proposed designs. It is a vertically emplaced, overpacked thin austenitic stainless steel cylindrical container, measuring 300cm in length and 32cm in diameter (*figure.1*)².

According to the research work done by Lawrence Livermore National Laboratory (LLNL), the thermal constraints for the container is to keep the inside temperature, below 350°C, at the same time maintain the borehole wall temperature above 97°C (the boiling point of water at *Yucca Mountain Site*) for 1000 years^{4,5,6}. One of the highest thermal load waste package, contains a hybrid mix of PWR and BWR spent fuel rods, the initial thermal load for this 10 year old fuel rod is 4.74kW per container. All containers are emplaced 300m below the ground surface, in an infinite array of equivalently loaded containers on 8 x 30 m spacings. For a single shell container, the borehole wall surface temperature reaches 204°C at 18 years after emplacement and remains above 97°C for the entire 1000 years. This result is under the assumption of no heat removed by ventilation in the drift tunnels or by evaporation of the moisture in the *tuff*.

The proposed multi-barrier waste containment system is different from other site specific and generic designs, in that it has three layers engineered to isolate the nuclear waste. It has two metal alloy shells to sustain the integrity of the package, it has a proven material like concrete as a metal-metal sandwich and it is a *Copper- Nickel* alloy system(*figure.2*).

2 Physical description and modelling

The proposed waste containment scheme is a multi-barrier, vertically emplaced, *copper-nickel* alloy system. It has a *Cu-Ni 70/30 (CDA 715)* inner shell, a nickel base(*Incalloy 825*) outer shell and an oxidic nonconducting sandwich layer between the two metal alloy shells, which could be cement concrete or *alumina*. The inner and outer shells are provided with *lifting collars* for facilitating their handling. The *lifting collars* are made of a relatively electronegative element, such as *magnesium* or *aluminum*. This configuration would make the containment system *cathodically protected* as the lifting collars would also act as *sac-*

rificial anodes because of their electronegativity. The criteria for the selection of the cannister materials are :

- Compared to other metals, *Cu-Ni 70/30* has excellent engineering properties in all important categories, and is one of the few alloys on the priority list of candidate metal alloys for the cannister.
- *Incalloy 825* is an austenitic alloy, designed for use in extremely corrosive environments. This alloy is stabilized with titanium to resist intergranular corrosion and intergranular stress corrosion cracking. The nickel content makes it very resistant to transgranular stress corrosion cracking. Molybdenum and copper give this alloy resistance to pitting and stress corrosion, while the high chromium content gives it resistance to various types of oxidizing environments^{2,3}.
- Concrete retains its stability at relatively high temperatures (300°C), which can be further enhanced by using *high alumina cement*. It creates a passive environment, due its basicity (*high pH*), thus retarding the corrosion mechanism. High lime concrete has the ability to heal cracks under aqueous conditions. Concrete is an insulator and inhibits the formation of *dissimilar electrode cell gradient* between the outer and the inner dissimilar metal shells.

The third of the above criteria can be elaborated by looking at the *Pourbaix diagram*. Pourbaix describes the chemical behavior of metals in water on a *potential-vs-pH* map. In general three areas are observed.

- *Immunity* : In here, the metal is thermodynamically stable.
- *Passivity* : In here, corrosion occurs, but produces an insoluble product.
- *Corrosion* : In here, corrosion produces a soluble product.

Simplified *Pourbaix diagrams* of copper and nickel are presented here (*figure.3*). As shown immunity occurs at low *potential*, while corrosion occurs at high *pH*. The practical implications are obvious.

- *Alkalinity* contributes to the passivity of the metal, thus enhancing the resistance of the system, this is amply demonstrated in reinforced concrete. Cement concrete will be an excellent choice, in this regard.
- High lime cement concrete, heals cracks in an aqueous environment.
- Structures maintained, at a sufficiently low *potential*, by a *sacrificial anode* are immune to corrosion.

- From the evidence discussed above, one might expect that an extremely durable containment system, might be formed, using corrosion resistant alloys, in an *alkaline* environment, protected by *sacrificial anodes*.

The imposition of an *electrical insulation barrier*, would mean, the imposition of a *thermally insulated barrier*, which raises questions, concerning the adequacy of heat dissipation. The interest of this paper is also to examine the temperature distribution, within the containment vessel, as a function of *insulation type, thickness and boundary conditions*. The optimizing analysis of the scheme, has the temperature of the concrete sandwich barrier (250°C), as its constraint.

Since the temperature of the concrete layer is critical for the multi-barrier container design, considering containers emplaced 300m, below the ground surface, with spacing of 8x30m, each nuclear waste package, has an initial thermal load of 4.74kW, therefore, finding the temperature distribution is a three dimensional transient heat transfer problem. To solve such a problem, requires heavy computation. To provide an approximate temperature profile of each container layer and to support this multi-barrier container design, we use certain information, already available to us, from previous work ^{4,5,6}. The assumption was made that the wall temperature history for the case of the multi-barriered container, is similar to that of a thin walled container. It is predicted, on the fact that, the time response, for both these container geometries to a step in temperature, will have a much smaller value, than the response time will be in the rock. Hence, the use of a steady state one dimensional temperature profile in the container is reasonable.

As this multi layer container will be used at the time of emplacement, we model it as conduction heat transfer through all the different container layers, and heat convection plus radiation, across the air gap between the outer container shell to the borehole wall. Because the height of the container (4.75m) is much greater than its diameter (0.71m), we can assume that, most of the heat dissipated, through the wall of the container, hence the heat dissipation through the top and the bottom, can be neglected. Therefore, we can solve the temperature, at the outer surface of the container as free convection and radiation in vertical concentric cylinders, with the inner cylinder being heated. Due to the lack of data on heat transfer coefficients inside annular spaces, we are only able to approximate this by treating the air gap, as a rectangular cavity, in regard to convective heat transfer.

The first approximation, is that, the heat convection coefficient may be obtained, from correlation proposed by *Globe and Dropkin*⁷.

$$h_{ave} = 0.069.Ra_L^{\frac{1}{4}}.Pr^{0.074} \cdot \frac{k}{L} \quad (1)$$

where

h_{ave}	Average heat convection coefficient, $\frac{W}{m^2 \cdot K}$
Ra_L	Raleigh number
Pr	Prandtl number
k	Heat conductivity of the air, $\frac{W}{m \cdot K}$
L	Thickness of the air gap, m

All the properties are evaluated at average temperature of the two surfaces. The heat transfer rate across the air gap can be calculated as

$$Q_g = Q_{conv} + Q_{rad} \quad (2)$$

the heat generating rate being, $Q_g = 4740W$, initially a decaying function with time (figure 4). while, the heat transfer rate for convection, Q_{conv} is

$$Q_{conv} = h_{ave} \cdot A \cdot (T_{s,1} - T_{ave}) \quad (3)$$

and the heat transfer rate for radiation, Q_{rad} is

$$Q_{rad} = \frac{\sigma \cdot A_1 \cdot (T_{s,1}^4 - T_{s,2}^4)}{\frac{1}{\epsilon_1} + \frac{1 - \epsilon_2}{\epsilon_2} \cdot \left(\frac{r_1}{r_2}\right)} \quad (4)$$

where

$T_{s,1}$	Temperature of the outer container surface, K
$T_{s,2}$	Temperature of the borehole wall, K
T_{ave}	Average temperature of the air gap $\frac{T_{s,1} + T_{s,2}}{2}$, K
A_1	Surface area of the outer shell wall, m^2
ϵ_1, ϵ_2	Emissivities of the two wall surfaces
σ	Stefan-Boltzmann constant $5.67 \times 10^{-8} \frac{W}{m^2 \cdot K^4}$

From the heat transfer rate equation across the air gap, we can find the temperature at the outer shell wall. The equation is non-linear and the *iterative method of bisection* is used, to compute the temperature of the outer shell surface. After this temperature is found, the rest of the container layer surface temperature, can be calculated (figure 5), from the heat conduction equation.

$$Q_g = \frac{2 \cdot \pi \cdot H \cdot k \cdot (T_1 - T_2)}{\ln\left(\frac{r_2}{r_1}\right)} \quad (5)$$

The second phase of the multi-barrier container design, is to place concrete layers, and to fill the air gap, after 50 years of emplacement. It was found that the heat flux is low enough, that the outer shell temperature will not rise significantly, above its value after the initial 50 years, although heat transfer through the container, is mainly by conduction. Figure 6, shows the results of different temperature profiles, when a parametric variation of concrete thickness is made.

3 Results and Discussion

As a result of this analysis, a two stage emplacement system was selected. During the first 50 years of storage, a single barrier *Cu-Ni* (CDA 715) cylinder allows adequate heat dissipation and also permits the retrieval of the waste for reprocessing. If at that time, it is decided upon a multi-barrier *Cu/Ni-Concrete-Incalloy-concrete* system is achieved.

For the first multi-barrier container design, with the 10cm concrete sandwich layer and an air gap of 12.5cm, the inner metal shell could reach a temperature of 260°C (figure 5). If the thickness of the concrete sandwich layer is reduced to 5.08cm, the maximum temperature of the inner shell could be lowered to 245°C (figure 6). If an oxide of higher thermal conductivity, such as *alumina* is used instead of concrete as a sandwich layer, the maximum temperature of the inner shell would be 230°C (figure 6). This is mainly, due to the fact that *alumina* has a higher conductivity than *concrete*.

For the second multi-barrier container design, the maximum thermal output would be only 1922.6W, compared to a maximum of 4740W in the previous case. This would reduce the maximum temperature on the inner shell and would be subjected to 200°C, using a concrete sandwich layer thickness of 5cm (figure 7).

4 Future work

Further study for the long term high level nuclear waste repository container design, would be directed towards, upgrading the thermal model of this problem to a *three dimensional transient heat transfer case*, coupled with a detailed model for heat transfer mechanisms in the air gap. If we could solve this problem as a whole, we can better predict the thermal performance of the container, and have better control on the simulation error. Accurate thermal modeling would ensure a stable and sturdy waste containment scheme.

5 References

1. K.J.Schneider, S.J.Mitchell, L.T.Lakey, A.B.Johnson, R.F.Hazelton, D.J.Bradley, *Comparison of Selected Foreign Plans and Practices for Spent Fuel and High Level Waste Management*, Report PNL-7293, UC-810, Pacific Northwest Laboratory, April 1990
2. W.C.O'Neal, D.W.Gregg, J.N.Hockman, E.W.Russell, and W.Stein, *Pre-closure Analysis of Conceptual Waste Package Designs for a Nuclear Waste Repository in Tuff*, Report UCRL- 59595 Lawrence Livermore National Laboratory, November 1, 1984

3. L.B.Ballou, *Current Status of Waste Package Designs for the Yucca Mountain Project*, Proceedings of the Institute of Nuclear Materials Management 30th Annual Meeting, Orlando, Florida, July 9-12, 1989
4. G.L.Johnson, D.N.Montan, *Thermal Calculations Pertaining to a Proposed Yucca Mountain Nuclear Repository*, Report UCRL-ID-103534, Lawrence Livermore National Laboratory, February 1990
5. G.L.Johnson, *Thermal Performance of a Buried Nuclear Waste Storage Container Storing a Hybrid Mix of PWR and BWR Spent Fuel Rods*, Report UCID 21414, Lawrence Livermore National Laboratory, September 1988
6. W.Stein, J.N.Hockman, W.C.O'Neal, *Thermal Analysis of NNWSI Conceptual Waste Package Designs*, Report UCID-20091, Lawrence Livermore National Laboratory, April 1984
7. F.P.Incropera, D.P.De Witt, *Introduction to heat transfer*, ISBN 0-471-80126-7, John Wiley and Sons, Inc., 1985

Figure 1. U.S. Reference design of a container for High Level Waste disposal.

Figure 2. Proposed multi-barrier container for High Level Waste disposal.

Figure 3. Pourbaix diagrams of Copper & Nickel in fresh water

Figure 4 Spent fuel unit thermal output

Figure 5 Transient temperature at the rock wall, outer metal shell, and inner metal shell

Figure 6 Transient temperature at the inner metal shell

Figure 7 Transient temperature at the rock wall, outer metal shell, and inner metal shell +50 YEARS

DOE PROJECT MID-YEAR REPORT

Task 2.a

From: Dr.mojaes and Y.Lei

date: Feb. 6, 1992

This report presents our progress for the continuation of research on the thermal effects of heat generation from the nuclear waste on the container material and surrounding rock.

In the last report, one of major research problems for the thermal performance of the container and surrounding rock is the heat transfer in the air-gap between the waste container and the surrounding rock-wall. In this air-gap, there is a combination of free convection and radiation heat transfer. The resulting heat transfer problem could affect the peak temperature of the waste container and the nuclear waste temperature which are the main concerns in designing the container and selecting its materials along of course corrosion concerns.

Recently, a thermal analysis was performed for one of the nuclear waste container design using a multi-barrier system. The main goal of this study is to learn what kind of thermal distribution would be on this multi-barrier system. It was assumed that the initial thermal load 4.74kW per container (this is the highest thermal load per container which is provided in the previous literature).^{1,2,3} Using previous data which include the history of spent fuel unit thermal output, and the temperature on the rock wall as input data.^{1,2,3}, was possible to predict the temperature history on the different barrier layers.

The container design for this study is a copper-nickel alloy system. It has a Cu-Ni 70/30 (CDA 715) inner shell, a nickel base (Incalloy 825) outer shell and an oxidic nonconducting sandwich layer between the two metal alloy shells, which could be cement, concrete or alumina (Fig. 1).

The imposition of an electrical insulation barrier, would mean,

the imposition of a thermally insulated barrier, which raises the questions, concerning the adequacy of heat dissipation. The aim of this work is to examine the temperature distribution, within the containment vessel, as a function of insulation type, thickness and boundary conditions (air-gap between the container and the borehole wall). The maximum temperature allowed for the concrete sandwich barrier is 250 degree C.

Since the temperature of the concrete layer is critical for the multi-barrier container design, considering containers emplaced 300m, below the ground surface, with spacing of 8x30m, each nuclear waste package has an initial thermal load of 4.74kW, (Fig. 2) therefore, finding the temperature distribution over the whole field is a three-dimensional transient heat transfer problem. To solve such a problem, requires heavy computation. To provide an approximate temperature profile of each container layer and to support this multi-barrier container design, we used certain information, already available to us, from previous work (work done by LLNL for the single barrier design).^{1,2,3} The assumption was made that the borehole wall temperature history for the case of the multi-barrier container, is similar to that of a thin walled container. It is predicated, on the fact that the time response, for both these container geometries, to a step in temperature, will have a much smaller value, than the response time needed in the rock. Hence, the use of a steady state, one dimensional temperature profile in the container seems reasonable for approximation purposes.

As this multi layer container will be used at the time of emplacement, it was modeled as a conduction heat transfer through all the different container layers, and heat convection with radiation, across the air gap between the outer container shell to the borehole wall, the thermal properties of the air were also left as a variable and were part of the solution. Because the height of the container (4.75m) is much greater than its diameter (0.71m), it was assume that, most of the heat dissipates, through the wall of the container, hence the heat dissipation through the top and the bottom, can be neglected. Therefore, we can solve the temperature, at the outer surface of the container as a free convection and radiation in vertical concentric cylinders, with the inner cylinder being heated. Due to the lack of data on heat transfer coefficients inside annular spaces, we are only able to approximate this by treating the air gap, as a rectangular cavity, in regard to convective heat transfer.

The first approximation, is that, the heat convection coefficient may be obtained, from correlation proposed by Globe and Dropkin.⁴

$$h_{ave} = 0.069 \cdot Ra_L^{1/3} \cdot Pr^{0.074} \cdot k/L \quad (1)$$

where

h_{ave} Average heat convection coefficient, $W/(m^2 \cdot K)$

Ra_L Raleigh number

Pr Prandtl number

k Heat conductivity of the air, $W/(m \cdot K)$

L Thickness of the air gap, m

All the properties are evaluated at average temperature of the two surfaces. The heat transfer rate across the air gap can be calculated as

$$Q_g = Q_{conv} + Q_{rad}$$

The heat generating rate being. $Q_g = 4740W$, initially is a decaying function with time (Fig. 2) while, the heat transfer rate for convection, Q_{conv} is

$$Q_{conv} = h_{ave} \cdot A \cdot (T_{s1} - T_{ave}) \quad (3)$$

and the heat transfer rate radiation, Q_{rad} is

$$Q_{rad} = \frac{\sigma \cdot A_1 \cdot (T_{s,1}^4 - T_{s,2}^4)}{\frac{1}{\epsilon_1} + \frac{1 - \epsilon_2}{\epsilon_2} \cdot \left(\frac{r_1}{r_2}\right)} \quad (4)$$

where

T_{s1}	Temperature of the outer container surface, K
T_{s2}	Temperature of the borehole wall, K
T_{ave}	Average temperature of the air gap $0.5*(T_{s1}+T_{s2})$, K
A_1	Surface area of the outer shell wall, m^2
ϵ_1, ϵ_2	Emissivities of the two wall surfaces
σ	Stefan-Boltzmann constant, $5.67 \times 10^{-8} \text{ W/(m}^2 \cdot \text{K}^4)$

From the heat transfer rate equation across the air gap, we can find the temperature at the outer shell wall. The equation is non-linear and the iterative method of bisection is used, to compute the temperature of the outer shell surface. After this temperature is found, the rest of the container layer surface temperature, can be calculated (Fig. 3), from the heat conduction equation.

$$Q_1 = \frac{2\pi \cdot H \cdot k \cdot (T_1 - T_2)}{\ln(\frac{r_2}{r_1})} \quad (5)$$

Fig. 4, show the results of different temperature profiles of the inner concrete layer surface, when a parametric variation of its thickness is made.

The second phase of the multi-barrier container design, is to place concrete layers, and fill the air gap, after 50 years of emplacement. It was found that the heat flux is low enough that the outer shell temperature will not rise significantly above its value after the initial 50 years. This would be true although heat transfer through the container, is now mainly by conduction and the effect of radiation and convection have stopped.

As a result of this analysis, a two stage emplacement system was selected. During the first 50 years of storage, a single barrier Cu-Ni (CDA 715) cylinder allows adequate heat dissipation and permits the retrieval of the waste for reprocessing. If at that time, it is decided a multi-barrier is needed then a Cu/Ni-Concrete-Incalloy -Concrete System is used

For the first multi-barrier container design, with the 10cm concrete sandwich layer and an air gap of 12.5cm, the inner shell could reach a temperature of 260 degree C (Fig. 3). If the thickness of the concrete is reduced to 5cm, the maximum temperature of the inner shell could be lowered to 245 degree C (Fig. 4). If an oxide that has a higher thermal conductivity, such as alumina is used instead of concrete as a sandwich layer, the maximum temperature of the inner shell would be 230 degree C (Fig. 4). This is mainly, due to the fact that alumina has a higher conductivity than concrete.

For the second multi-barrier container design, the maximum thermal output for each container would be only 1922.6W, compared to a maximum of 4740W in the previous case. This would reduce the maximum temperature on the inner shell and would be subjected to 200 degree C, using a concrete sandwich layer thickness of 5cm (Fig. 5).

Since last September, we have been working with a finite elements software package call FIDAP (fluid dynamics analysis package). This program is capable of simulating a wide range of heat transfer and fluid dynamic problems. These include:

1. Laminar and turbulent flows. Turbulent flows are modeled with either a Prandtl mixing-length model or a $k-\epsilon$ model
2. Newtonian or non-Newtonian flows. Non-Newtonian fluids are described by a prescribed relation between viscosity and shear rate
3. Flows in fully saturated porous media. Both Brinkman and Forchheimer extensions of Darcy's law are available
4. Flows with mass transport. Advection and diffusion of a dispersed phase in a fluid flow can be modeled
5. Steady-state or transient flows
6. Forced convection problems
7. Free convection problems

8. Mixed convection problems
9. Advection-diffusion problems (energy equation and/or species transport equations only)
10. Flows driven by body forces (gravitational, centrifugal, coriolis, electromagnetic)
11. Periodic, separating or recirculating flows
12. Swirling flows
13. Flows in rotating or translating frames of reference
14. Flows with a free or moving surface, including moving contact points
15. Surface tension driven thermal flows. Flows driven by thermal surface tension gradients
16. Solidification and melting, with latent heat release and mass transfer across phase-change boundaries
17. Mass transport due to homogeneous and heterogeneous chemical reactions
18. Diffuse gray-body surface radiation, including view factor calculations
19. Heat transfer in solid regions bounding the flow can be modeled; i.e., conjugate heat transfer problems

FIDAP accepts either two-dimensional, axi-symmetric or three-dimensional, transient or steady-state form of the above problems.

Beside the air-gap problem, the heat transfer in the rock (tuff) also can be modeled and simulated by FIDAP. The various capabilities and option in the FIDAP package will give us a opportunity to set-up a more realistic model for a better detail study of over all thermal performance in this Yucca Mountain nuclear waste repository project.

Now we are in the stage of running a simple problem (flow in a circular pipe) to get familiar with the FIDAP program. We have run the simple FLOW IN PIPE problem successfully (Three of the problem plots, element mesh plot, velocity vector plot, and time step history plot are attached in the addendum). We are going to do an example problem of Developing Flow in a Vertical Channel, this problem is similar to our Air-Gap problem. After we learn how to input and run some simple problems correctly, we will setup our Air-Gap problem for the simulation.

In Feb. 20 1992, we are going to attend a FIDAP seminar in Sunnyvale, CA. This is a basic two-day introductory FIDAP class. Since we are using FIDAP to do computer simulations, attend this seminar would help us to use the program more efficiently.

References

1. G.L.Johnson, D.N.Montan, Thermal Calculations Pertaining to a Proposed Yucca Mountain Nuclear Repository, Report UCRL-ID-103534, Lawrence Livermore National Laboratory, February 1990
2. G.L.Johnson, Thermal Performance of a Buried Nuclear Waste Storage Container Storing a Hybrid Mix of PWR and BWR Spent Fuel Rods, Report UCID 21414, Lawrence Livermore National Laboratory, September 1988
3. W.Stein, J.N.Hockman, W.C.O'Neal, Thermal Analysis of NNWSI Conceptual Waste Package Designs, Report UCID-20091, Lawrence Livermore National Laboratory, April 1984
4. F.P.Incropera, D.P.De witt, Introduction to heat transfer, ISBN 0-471-80126-7, John Wiley and Sons, Inc., 1985

Figure 1 Proposed multi-barrier container for High Level Waste disposal.

Figure 2 Spent fuel unit thermal output

Figure 3 transient temperature at the rock wall, outer metal shell, and inner metal shell

Figure 4 Transient temperature at the inner metal shell

Figure 5 Transient temperature at the rock wall, outer metal shell, and inner metal shell

identification is required to be consistent with the methods used to maintain the repository records and the label must be applied "in such a way that the information on 99% of the waste packages shall remain attached and legible at least to the end of the period of retrievability". The draft document noted that the term "legible" was yet to be determined.

C. ASME/ANSI Standards

The professional engineering organizations have a number of codes that may be applied to the waste package labeling. The ANSI/ASME NQA-1-1989, "Quality Assurance Requirements for Nuclear Facilities" ⁴ specify standards for identification of items (II.8) and traceability (III.2). Identification markings are required to clearly and legibly identify items used in the nuclear industry. The labels must not adversely affect the function or service life of the item.

part by labeling inadequacies (46% by operators, 36% by instrumentation and control technicians, and 12% by maintenance personnel). The industry set plant-wide labeling standards to decrease these errors. The standards define label placement, visibility, and contrast.

1. Character Specifications

Character fonts are defined including spacing, style, height, width, and case. The following points were noted:

1. The guidelines suggest that a hierarchical labeling scheme be employed that uses larger characters to stress main headings and avoids repetitious information
2. Labels must be done in upper case or capital letters. Additional information may be in lower case.
3. Characters must be simple sans serif fonts, such as

Figure

Task A.3 - ASME Pressure Vessel Code

**ASME PRESSURE VESSEL CODE APPLICATION TO NUCLEAR WASTE CONTAINER
DESIGN**

Dr. Mohamed Trabia

Graduate Student: Mark Kiley

ASME PRESSURE VESSEL CODE APPLICATION TO NUCLEAR WASTE CONTAINER DESIGN

Mohamed B. Trabia, Ph.D. and Mark Kiley

Department of Mechanical Engineering
University of Nevada, Las Vegas
4505 South Maryland Parkway
Las Vegas, Nevada 89154

ABSTRACT

It would be highly desirable if a widely accepted standard could be applied to the design of permanent nuclear waste storage containers, to ensure their integrity. One such standard is the ASME Pressure Vessel Code. In this paper, we have explored the applicability of this code to the design process of spent nuclear fuel storage containers. We have identified a list of the major sections of the code that are related to the waste container design. These sections have been investigated and then applied to a preliminary spent fuel container design. A comparison of the six candidate materials performance is presented.

DISCLAIMERS

Any opinions, findings, conclusions, or recommendations expressed herein are those of the author(s) and do not necessarily reflect the views of the Department of Energy (DOE).

The authors of this paper have written it in handbook format, to simplify possible future use of the ASME Pressure Vessel and Boiler Codes to waste package design. The authors give full credit for the contents of the codes to the ASME committees that authored them. The authors in no way claim any credit for the portions of

does not claim to be a substitute for the ASME codes; it merely organizes the process of reviewing the codes nuclear waste package application.

INTRODUCTION

The design of nuclear waste containers presents a challenging problem. The container has to maintain integrity over an extended period. It is advantageous if the design follows a widely accepted standard such as the ASME Pressure Vessel Code. Our first objective is to compile a list of the ASME Pressure Vessel Codes that can be applied to waste package container design and manufacturing processes. Our second objective is to explore the use of these applicable codes to the preliminary waste package container designs. This application of the ASME codes to the preliminary waste container design is very generalized and thus, it may be applied to any final design.

The authors realize that the waste packages contained within the waste package containers are not likely to create high pressures. However, the ASME pressure vessel code is still a widely accepted and informative document with a broad range of design criterion based on past experience (e.g. acceptable pressure vessel materials, maximum acceptable design temperature, minimum acceptable container wall thicknesses, vessel inspection criterion, nondestructive

The remainder of this paper discusses the following topics:

1. an introduction to the ASME pressure vessel and boiler codes,
2. a discussion of certain sections of the code relevant to the nuclear waste container design,
3. an application of the ASME pressure vessel and boiler codes to the nuclear waste container design.

I. INTRODUCTION TO ASME PRESSURE VESSEL CODES

The ASME code (which consists of eleven sections plus code cases) addresses the following topics: power boilers, material specifications, general requirements for nuclear power plant components and structures, heating boilers, nondestructive examination, recommended rules for care and operation of heating boilers, recommended guidelines for the care of power boilers, pressure vessels, welding and brazing qualifications, fiberglass-reinforced-plastic pressure vessels, and rules for inservice inspection of nuclear power plant components.

There are three main sections of the ASME boiler and pressure vessel code that are applicable to the preliminary nuclear waste container design. The first is section II which clearly identifies known pressure vessel materials and includes rules for the ASME identification of new materials. The second applicable portion of the code is section VIII which gives the general requirements for pressure vessel design. The third is section IX which discusses the brazing and welding qualifications for all ASME identified materials.

We originally thought that we would have had a fourth applicable ASME section (namely, section III - Rules for Construction of Nuclear Power Plant Components), but a closer inspection revealed the following. This section (section III) consistently provided higher allowable stress values than section VIII for the same material. Thus, the pressure vessel section was more conservative (safer) and section III would not contribute to a more desirable design.

this paper.

II. INTRODUCTION TO ASME PRESSURE VESSEL CODE RULES FOR MATERIAL SELECTION AND PRESSURE VESSEL DESIGN

The first step that one should take, when designing a pressure vessel, is to select the building material(s). The material must be selected on the basis of its suitability for the intended service with respect to:

- a. retention of satisfactory mechanical properties.
- b. resistance to corrosion, erosion, oxidation, and other deterioration factors during their intended service life.

The second step is to check the pressure vessel design using the formulae contained in section VIII

A. Material Selection Procedure Using ASME Code Section II

The following is a description how to identify materials in section II. The first step is to determine the chemical composition of the metal break the material down into one of the following three categories:

1. Section A (Ferrous Materials)
2. Section B (Nonferrous Materials).
3. Section C (Welding Rods, Electrodes and Filler Metals)

The second step is to look through the index that precedes the applicable subsection and turn to the indicated pages for the corresponding chemical composition. Then the researcher must turn to the table at the end of the above subsection and look through to verify that the material that is looking up has the chemical composition which is included in the table.

Once the above search is complete the researcher has access to the following information about the material under consideration: see referenced documents, ordering information, chemical composition, mechanical properties, test methods, inspection, certification, product marking, and other categories too numerous to list here.

B. Design Procedures Using ASME Code Section VIII

ASME Code section VIII consists mainly of part UG (pages 9 - 94) which is entitled "General Requirements for All Methods of Construction [of pressure vessels] and All Materials". "The requirements of part UG are applicable to all pressure vessels and vessel parts and shall be used in conjunction with the specific requirements in Subsections B and C and the Mandatory Appendices that pertain to the method of fabrication and the material used" (sec. VIII¹, p.13). The remainder of the section (pages 95 - 805) consists of supporting tables, appendices, and indices for part UG.

III. APPLICATION OF THE ASME PRESSURE VESSEL CODE TO THE PRELIMINARY DESIGN OF THE NUCLEAR WASTE CONTAINER

Although the final design of the nuclear waste container has not been decided, several preliminary designs are available^{2,3,4,5, and 6}. Six candidate materials have also been selected². We used the container design from the cost estimate study⁶ (see Figure 1), and each of the six candidate materials, for the following analysis. However, this analysis is of generic nature and may be applied to any final design.

Figure 1 - One Possible Container Design⁶. (All dimensions are in inches.)

A. Identification of the Nuclear Waste Container Candidate Materials in ASME Code Section II

We began our search in ASME Code section II, by attempting to locate each of the six candidate materials

composition of these materials as listed in paper². For each material listed in the code, the chemical composition is also identified. We ensured that we had identified the correct material by comparing these two chemical compositions.

Each of the candidate materials or its closest match (see Tables 1, 2 and 3), is listed in the ASME codes section XIII, subsection C (Tables UNF-23.2, UNF-23.3, and UHA-23). The tables list the maximum allowable stress values in tension (over the acceptable design temperature range) for each respective material. Table lists the candidate materials (or their closest match, as explained above) and the maximum allowable design temperature for that material.

B. Design Temperature for Nuclear Waste Container

The temperature is expected to rise considerably during the first 1 years of nuclear material storage. The magnitude of this temperature rise will depend upon the particular fuel that is used and the amount of time that the fuel has been in temporary storage before it is deposited into permanent storage. In paper⁷, LLNL provided extensive information about the temperature rise of stored fuel and the corresponding container and borehole temperatures, over time. The maximum container temperature will be approximately 263 degrees Celsius (500 F) and will occur approximately 12 years after emplacement in host rock.

Subsection UG-20 (Design Temperature), specifies that an operating temperature higher than those listed in the tables of subsection C, for a specific material is not permitted. Studying Table 4, it is thus clear that both CDA-102 (pure copper) and CDA-614 (Aluminum-Bronze) are not permitted by the ASME pressure vessel and boiler code. For either of these two materials to be used, one or more of the following factors has to be changed.

1. spent fuel rods temperature at the time of loading into waste container and/or the number of rods loaded into each container.
2. waste container wall-thickness

DOE IDENTIFIED MATERIAL	SAME (OR MOST SIMILAR) ASME IDENTIFIED MATERIAL
<u>AISI-304L</u> (Chromium-Nickel stainless steel)	UNS-S30403
<u>AISI-316L</u> (Chromium-Nickel stainless steel)	UNS-S31603
<u>Incoloy-825</u> (Nickel-Iron-Chromium-molybdenum-Copper alloy)	UNS-N08825
<u>CDA-102</u> (99.95% pure Copper)	not found but closely approximated by UNS-C11000
<u>CDA-613</u> (Aluminum-Bronze alloy)	not found but closely approximated by UNS-C61400
<u>CDA-715</u> (Copper-Nickel alloy)	UNS-C71500

TABLE 1 - ASME IDENTIFICATION OF THE SIX DOE SPECIFIED CANDIDATE MATERIALS

MATERIAL	SPECIFIED CONTENT % (CDA-102)	ASME CONTENT % (UNS-C11000)
Copper	99.95	99.90
Oxygen	0.0	(not listed)

TABLE 2 - DOE SPECIFIED CONTENT FOR COPPER Vs. ASME IDENTIFIED MATERIAL

MATERIAL	SPECIFIED CONTENT % (CDA-613)	ASME CONTENT % (CDA-614)
Iron	3.5 (max)	1.5-3.5
Lead	0.0	0.01 (max)
Tin	0.2-0.5	0.0
Aluminum	6.0-8.0	6.0-8.0
Manganese	0.5 (max)	1.0 (max)
Nickel	0.5 (max)	0.0
Zinc	0.0	0.20 (max)
Phosphorus	0.0	0.015 (max)
Copper (pure)	92.7 (nom) (pure)	remainder (incl. silver)

TABLE 3 - DOE SPECIFIED CDA-613 Vs. THE MOST SIMILAR ASME IDENTIFIED MATERIAL (CDA-614)

3. waste container material grade.

C. Corrosion

The ASME Pressure Vessel Codes require that a corrosion allowance be calculated for a container over its useful life. This corrosion allowance is to be subtracted from the nominal thickness prior to any calculations (wall-thickness, pressure, etc.). However, the codes also specify (in UG-25) that the designer can perform subsequent calculations (wall-thickness, pressure, etc.) if he/she specifies that these calculations have been performed without the necessary corrosion thickness allowance.

The most extensive study of expected corrosion rates on the six candidate materials for waste containers is in paper⁵. In this study, overall corrosion in various environments ranging from arid desert regions to sea water were conducted. These environments represent the best and the worst case scenarios, respectively. However, this is a short term study (1 to 30 years) and it usually supplies only one or two data points for each corrosion case. The authors feel that it is inappropriate to extrapolate any useful long-range (on the order of 300-1000 years) results from such limited data. Thus, the authors have chosen to perform subsequent calculations (wall-thickness, allowable pressures, etc.) without including corrosion allowance effects, until more extensive corrosion data is available.

D. Design Pressure

Section (UG-21) requires that all vessels must at the least be designed for the most severe conditions of pressure and temperature that are to be expected during normal use of the pressure vessel. This section is closely related to UG-27 and UG-28 which deal with vessel wall thickness calculations due to internal and external pressures, respectively. The internal pressure value that we have used does not take any nuclear factors into consideration; it is based solely on temperature and thermodynamic considerations.

The maximum internal pressure that

following formula and the fact that the fuel temp will be about 644 degrees fahrenheit when the contain temp is 505 degrees fahrenheit⁷.

$$\frac{P_1 \cdot V_1}{T_1} = \frac{P_2 \cdot V_2}{T_2}$$

E. Calculations of Nuclear Waste Container Shell Stresses

The container design that we are analyzing can be divided into three parts: a flat top plate, a hollow circular cylinder, and a flat bottom (again, see Figure 1). The container pintle is not considered in this study. The analyses in this section apply to the shell (hollow cylinder portion of the nuclear waste container, as formatted in the code. The head and bottom of the container will be analyzed in section 4 below. The ASME codes provide separate design formulas for various head shapes e. spherical, ellipsoidal, etc..

1. Maximum Allowable Stress Values

Section (UG-23) contains the rules under which the maximum allowable stress value for a particular container material shall be determined using the ASME codes. This process is based primarily on the dimensions of the container, the candidate material strength at the maximum expected temperature, and the design formula in section UG-23 of section VIII. Section UG-23 provides step by step instructions which are briefly delineated as follows (with the values shown in Table 5):

Step 1: Find the maximum allowable tensile stress permitted in the applicable tables of subsection C (section VIII).

Step 2: Find the "B" value determined by using the "A" factor. The "A" factor is:

$$A = \frac{0.125}{\left(\frac{R}{t}\right)}$$

where,
R is the outside radius of

MATERIAL	MAX. ALLOWABLE DESIGN TEMP. (F):	MAX. ALLOWABLE STRESS AT THIS TEMP. (ksi)
AISI 304L (ASME = SA-240)	850	9.4
AISI 316L (ASME = SA-240)	850	9.4
Incoloy 825 (ASME = SB-424)	1000	16.6
CDA 102 (ASME = SB-11)	400	3.0
CDA 613 (614) (ASME = SB-169)	500	16.5
CDA 715 (ASME = SB-402)	600	6.0
Notes: 1. The maximum design temperature is 505 degrees F. 2. For several of the above materials, the design temperatures and strength may depend on the thickness, product form, or grade. In the above table, the values were listed for 3/8" thick plate. Where two strength values were listed in the ASME codes, the lowest strength value of the corresponding material was chosen. 3. It is noted that the maximum allowable strength remains the same or <u>decreases</u> as the plate thickness increases.		

TABLE 4 - DESIGN TEMPERATURE AND STRESS OF CANDIDATE MATERIALS

CONTAINER MATERIAL	Step 1: MAXIMUM ALLOWABLE TENSILE STRESS (psi)	Step 3: MAXIMUM ALLOWABLE COMPRESSIVE STRESS (psi)	Step 4: LOWEST STRESS VALUE (psi)	Step 5: MAXIMUM PRIMARY MEMBRANE STRESS (psi)
AISI 304L	B = 9,546	10,875	9,546	11,455
AISI 316L	B = 12,569	13,265	12,569	15,083
Incoloy 825	B = 11,028	18,275	11,028	13,234
CDA 102	[note 1]	(400 F MAX)	NOT LISTED	N/A
CDA 614	B = 9,517	(500 F MAX)	NOT LISTED	N/A
CDA 715	B = 3,190	7,900	3,190	3,828
Notes: 1. All of the above maximum allowable compressive stress values were calculated using 505 degrees fahrenheit as the design temperature value. No extra safety factor was used in these calculations. 2. The maximum allowable tensile stress values (tabulated above) reflect the smallest value that was listed in subsection C (of section VIII). [We have adopted this convention because the table lists many stress values for many of the DOE candidate materials]. 3. Annealed copper only goes up to 400 degrees fahrenheit on the applicable ASME table in subsection C.				

TABLE 5 - MAXIMUM ALLOWABLE STRESS VALUES

inches).

t is the minimum thickness of the cylindrical shell or tube after the corrosion allowance has been subtracted.

Step 3: The "A" value is used in conjunction with the applicable graph or table in appendix #5 (section VIII) to determine the "B" value.

Step 4: Determine the smallest value from steps 1 & 3.

Step 5: The maximum primary membrane stress is 1.2 multiplied by the value obtained in step 4.

The final stress calculations may be modified to account for any additional stress factors.

2. Thickness of Shells Under Internal Pressure

This section (UG-27) contains calculations to determine the minimum allowable wall thickness that is required for the worst internal pressure conditions that are expected over the life of the vessel. This is done by comparing the results of i and ii:

i. the circumferential membrane stress:

$$P_{cir} = \frac{S \cdot E \cdot t}{r + (0.6 \cdot t)} \quad (3)$$

where,

S is the lowest stress value from Table 5, step #4.

E is the joint efficiency for the applicable joint method (E=0.9).

r is the inside radius of the shell under consideration.

and,

ii. the longitudinal membrane stress:

$$P_{long} = \frac{2 \cdot S \cdot E \cdot t}{r - (0.4 \cdot t)} \quad (4)$$

The maximum allowable working pressure of cylindrical shells shall be the

11 ABOVE.

3. Thickness of Shells and Tubes Under External Pressure

This section (UG-28) contains calculations for determining the minimum allowable wall thickness due to the greatest external pressure that is expected over the life of the vessel. The formula for maximum allowable external pressure is:

$$P_{ext} = \frac{4 \cdot B}{3 \left(\frac{2 \cdot R}{t} \right)}$$

where,

B is to be taken off Table 5, step #1.

4. Unstayed Flatheads and Covers

This section (UG-34) contains calculations which are used to determine the minimum required thickness for unstayed flat heads, cover plates and blind flanges. These requirements apply to both circular and noncircular heads and covers. So acceptable types of flat heads and covers are shown in ASME section VII page 37. The bottom of the container has to withstand the payload during manipulation of the container. The formula for maximum allowable internal pressure on the flat head of a pressure vessel is:

$$P = \frac{S \cdot E \cdot h^2}{C(2R)^2}$$

where,

C is an ASME determined factor which depends on the method of attachment of the head, the shell dimensions, and other factors listed in the ASME codes.

h is the thickness of the heads.

IV. COMPARISON OF MATERIAL PERFORMANCE

We will introduce a performance index, to evaluate the suitability of the candidate materials. This index is:

$$Per. Index = \sum_{i=1}^n (a_i \cdot k_i)$$

- a, is a weight factor which can have a range between 0 and 1, depending on the relative importance of a particular design factor.
- k₁ is a dimensionless number which describes one of the factors affecting the container design. The value of k₁ must always be greater than 1.0.
- n is the number of design factors which contribute to the performance index.

In this paper, the performance index is based on the stresses and the temperature effects. However, the performance index can be expanded to include areas such as corrosion, weldability, and/or cost, etc.

For stresses, we considered the case when the container is carrying 18 of the heaviest consolidated BWR assemblies that we could identify (namely - eighteen Exxon/ANF 7x7 assemblies)⁹. The total weight of the eighteen consolidate assemblies is equal to, 11144 lb. The canister weight varies from 1999 to 2233 lb, depending to the material it is made of. Thus the performance index that we have chosen is:

$$\text{Per. Index} = (a_1 \cdot k_1) + (a_2 \cdot k_2) \quad (8)$$

where,

a₁ = 1.0 = a₂. (Thus, the design factors are equally weighted).

k₁ is the lowest factor of safety due to the longitudinal, circumferential, and head stresses (including container weight and fuel rod loading, i.e. 18 consolidated BWR assemblies).

k₂ is calculated as follows:

$$k_2 = \left(\frac{T_{\text{allowable}}}{T_{\text{operating}}} \right) \quad (9)$$

where,

T_{allowable} is the maximum allowable working temperature according to Table 4.

T_{operating} is the maximum operating temperature of the waste container during the initial emplacement years (505 F).

The result of this material performance comparison are shown in Table 7.

MATERIAL	PERFORMANCE INDEX
AISI-304L	2.85
AISI-316L	3.22
Incoloy-825	3.33

note:

1. CDA-102 and CDA-614 were not included in the above table because it is not meaningful to include material in a performance index where these materials are not permitted due to temperature restrictions.

2. CDA-715 was also not included because the lowest factor of safety (longitudinal stress) was less than

Table 7 - PERFORMANCE INDEX FOR THE CANDIDATE MATERIALS AT 505 F.

V. CONCLUSIONS AND RECOMMENDATIONS

The ASME Pressure Vessel and Boiler Code is relevant to the design process of the spent nuclear fuel containers, for the Waste Package Project. See section II.B to understand the enormous potential of the codes (i.e. the codes cover many procedures from ordering information about materials to final inspections of the finished product). Unless the spent fuel rod temperature, at the time of final storage container closure, is lower than (and will remain lower than) the temperature indicated in paper⁷, the use of UNS C11000, pure copper, (almost identical to CDA-102, see Table 2) is not recommended. The temperature stated paper⁶ is approximately 263 degrees celsius which is 505 degrees fahrenheit. The ASME codes do not permit the use of pure copper (CDA-102) above 400 degrees fahrenheit. Similarly, the CDA 613, Aluminum-Bronze alloy, (almost identical to CDA-614, see Table 3) is not permitted by the ASME codes above temperatures of 500 degrees fahrenheit. Although this is only a five degree temperature infraction in the CDA-614 case, the possibility of this infraction lasting on the order of twenty years or more makes this temperature infraction a major design concern.

All of the ASME pressure vessel calculations herein were performed without subtracting the corrosion allowance of material from the nominal thickness of the container over its design-life. The authors feel that

be conducted before a corrosion allowance can be calculated. An area of special concern is the study of localized corrosion on each candidate material.

For the portion of the design that was completed in section III of this paper, the current 3/8" shell thickness appears to ensure shell integrity (except where noted above) under normal circumstances which are expected at a permanent storage site in tuff.

A flat headed design may not be an efficient design because this design will use far more material to obtain stress levels which are easily obtained (with far less material) using curved heads.

Our study of the current preliminary design using the six candidate materials suggests that the best candidate material to use in the construction of the nuclear waste containers construction is Nickel-Iron-Chromium-Molybdenum-Copper Alloy also known as Incoloy-825. This material was chosen due to its superior performance index.

Acknowledgement:

The authors would like to acknowledge the U.S. Department of Energy for their support under DOE contract # [DE-FC08-90NV10872].

REFERENCES

1. 1988 ASME Boiler and Pressure Vessel Code.

Fabrication and Closure Development Nuclear Waste Containers for Storage at Nevada's Yucca Mountain. Lawrence Livermore National Laboratory.

3. J.N. Nass. May, 1989. Evaluation of Copper, Aluminum Bronze, and Copper-Nickel for Yucca Mountain Project (YMP) Container Material. Lawrence Livermore National Laboratory.

4. L.B. Ballou. July, 1989. Current Status of Waste Package Designs for the Yucca Mountain Project. Lawrence Livermore National Laboratory.

5. J.C. Farmer & R.D. McCright. November, 1989. Review of Models Relevant to the Prediction of Performance of High-Level Radioactive Waste Disposal Containers. Lawrence Livermore National Laboratory.

6. Cost Estimate of High Level Radioactive Waste Container for the Yucca Mountain Project. Report #UC 21863, Lawrence Livermore National Laboratory.

7. O'Neal et al. November 1, 1988. Preclosure Analysis of Conceptual Waste Package Designs for a Nuclear Waste Repository in Tuff. Lawrence Livermore National Laboratory

8. G.E. Gdowski & D.B. Bullen. August, 1988. Survey of Degradation Modes of Candidate Materials for High Level Radioactive-Waste Disposal Containers. -Vol. 2. Lawrence Livermore National Laboratory.

9. LWR Radiological Database (supplement to DOE/RW-0184) December 1987.

MATERIAL	ALLOWABLE INT. PRESS.	ALLOWABLE EXT. PRESS.	ALLOWABLE HEAD PRESS.
AISI-304L	251	184	99
AISI-316L	330	242	131
Incoloy 823	290	212	115
CDA-702	84	61	33

Task A.4 - Waste Package Labeling

LABELING OF THE SPENT FUEL WASTE PACKAGE

Dr. William Culbreth

Graduate Student: Anil Kumar Chagari

LABELING OF THE SPENT FUEL WASTE PACKAGE

W. G. Culbreth and A. K. Chagari

Department of Civil and Environmental Engineering
University of Nevada
Las Vegas, NV 89154
(702) 739-3426

ABSTRACT

The containers used to store spent fuel in an underground repository must meet federal guidelines that call for unique labels that identify the contents and processing history. Existing standards in the nuclear power industry and relevant ASME/ANSI codes have been reviewed for possible application to the spent-fuel container labeling. An array of labeling techniques were found that include recommendations for: fonts, word spacing, color combinations, label materials and mounting methods, placement, and content. The use of bar code, optical character recognition, and RF labels were also studied to meet the requirement that the container labels be consistent with the methods used to maintain the repository records.

I. INTRODUCTION

The high-level spent fuel waste package intended for underground storage will require accurate labeling to meet the guidelines specified by Federal Regulation 10 CFR 60.135. The labeling system must be designed to ensure that each package has a unique identification traceable to its contents that must be consistent with the permanent records maintained by the repository. The label must be designed in such a way that it does not impair the integrity of the waste package. The regulations also have requirements that have yet to be determined relating to the legibility of the waste package label. Both the body and the lid of the container must be labeled.

In this study, a survey of available labeling techniques was conducted to determine the methods currently used by the industry. Information was solicited from the national laboratories regarding the current labeling technology applied to transportation containers, fuel assemblies, and other spent fuel storage devices. Maintaining records on the estimated 10,000 spent-fuel containers to be placed in an underground repository will be expedited if the reading of labels can be

automated. Advanced labeling methods were studied for possible application to the waste package including bar coding, RF labels, and other computer-integrated techniques.

Various metals and alloys, including steels, nickel and copper alloys, and aluminum bronze are being investigated for use as disposal container materials¹. The use of labels that could be welded directly onto the container were, therefore, investigated.

II. RELATED CODES

A. NRC Requirements

Waste package labeling is described in Part 60.135(b)(4) of the USNRC rules and regulations¹ governing the disposal of high-level radioactive waste. This section states:

"Unique identification. A label or other means of identification shall be provided for each waste package. The identification shall not impair the integrity of the waste package and shall be applied in such a way that the information shall be legible at least to the end of the period of retrievability. Each waste package identification shall be consistent with the waste package's permanent written records."

B. U.S. DOE Requirements

The U.S. Department of Energy, in a recent draft of its waste package requirements document¹, made several references to the waste package label to satisfy the NRC rules. The waste package label must be unique, the label must provide an external identification that is traceable to the container's contents, and both the body and the lid must be labeled to document the process history of the container. The container

Identification is required to be consistent with the methods used to maintain the repository records and the label must be applied "in such a way that the information on 99% of the waste packages shall remain attached and legible at least to the end of the period of retrievability". The draft document noted that the term "legible" was yet to be determined.

C. ASME/ANSI Standards

The professional engineering organizations have a number of codes that may be applied to the waste package labeling. The ANSI/ASME NQA-1-1989, "Quality Assurance Requirements for Nuclear Facilities" ⁴ specify standards for identification of items (II.8) and traceability (III.2). Identification markings are required to clearly and legibly identify items used in the nuclear industry. The labels must not adversely affect the function or service life of the item. Provisions must be made to ensure that labels are not damaged during handling, due to aging, or subject to environmental deterioration. Supplement 8S-1 documents the requirements for identification and control of items in the nuclear industry. This section calls for physical identification to be used to the maximum extent possible. Markings must be applied to each part of the item when subdivided, obscured, or other means of identification is substituted.

ANSI/ASME N45.2.2-1978 ⁵ documents the marking of items to be used in nuclear power plants. Section A3.9 mandates the use of the English language on labels and the use of avoirdupois units for weight. ISO pictorial markings and other units may be added. The etching of identification tags is forbidden on sensitized areas of stainless steel or weld areas.

In addition to the ANSI/ASME codes, the Electric Power Research Institute (EPRI) has been very active in power plant labeling standards. Their recommendations are presented in the next section.

III. INDUSTRY STANDARDS

A. EPRI Studies

J. L. Seminara ⁶ in EPRI NP-6209, "Effective Plant Labeling and Coding," gave an excellent summary of related work funded by the Electric Power Research Institute. This work and five other EPRI studies addressed the problems experienced by the operators and maintenance staffs at nuclear power plants due to inadequate labeling.

The nuclear power industry has standardized labels to decrease the misidentification of components. Seminara noted that in a five year period beginning in 1981, 220 incidents reported to the NRC involving personnel errors were caused in

part by labeling inadequacies (46% by operators, 36% by instrumentation and control technicians, and 12% by maintenance personnel). The industry set plant-wide labeling standards to decrease these errors. The standards define label placement, visibility, and contrast.

1. Character Specifications

Character fonts are defined including spacing, style, height, width, and case. The following points were noted:

1. The guidelines suggest that a hierarchical labeling scheme be employed that uses larger characters to stress main headings and avoids repetitious information.
2. Labels must be done in upper case or capital letters. Additional information may be in lower case.
3. Characters must be simple sans serif fonts, such as Helvetica or Univers. Figure 1 demonstrates acceptable and unacceptable fonts.
4. Character width-to-height ratios should be 1:1 to 3:5 and legibility is stressed.
5. Desired viewing distance affects the size of the font to be used. A 4.3 mm (0.168 in) high character font is readable at 0.71 m (28 in), but a 91 mm (3.6 in) font would be preferred for viewing at 15 m (50 ft). Figure 2 demonstrates data obtained from Seminara related to visibility. Character sizes are commonly referred to in points where 72 points is equivalent to 25.4 mm (1 in).

Figure 1. Examples of a Sans Serif Font (Helvetica) and Two Unacceptable Fonts

Figure 2. Suggested Character Sizes

Standard fonts for consistent labeling are also defined by the military that stress simplicity and readability⁵.

2. Label Colors

Nuclear power plants employ color schemes to highlight different areas of the plant or pumps and devices associated with separate units. EPRI NP-4350⁷ expresses the concern that incorrect identification has led to fatalities in power plants and color enhances the ability to discern differences in similar equipment. It is suggested that black characters on a white background provide the best contrast and readability. This is especially true in areas where illumination is limited. White characters on a black background do not fare as well since dirt tends to accumulate in the letters making them unreadable.^{6,7,8} If colors are used for the labeling of spent-fuel containers, color combinations that can be interpreted by color-impaired personnel must be used.

3. Label Materials and Mounting

EPRI NP-4350 indicates that as many as 50% of the labels in older nuclear power plants are missing and unavailable to maintenance personnel. Label materials that may be suitable to the spent-fuel container are summarized below:

1. Embossed metal tags have been used on valves and pumps. Contrast between characters and the background is limited.
2. Stenciled characters have been used. They are easier to apply to curved surfaces, but do not conform to acceptable fonts.
3. Coated stainless steel labels with black characters on a white background have been used. These labels manufactured by Electromark have been shown to withstand temperatures of over 900 K for two hours.⁶ Bar code can be included on the label.

4. Brass plates have been used with good contrast between characters and the background.
5. Vinyl pressure sensitive labels have been used, but distort above 338 K.
6. Fiberglass tags with clear gelcote coatings have been employed, but deteriorate above 394 K.
7. Labels have been glued, bolted, welded, affixed with metal chains, or be attached with double-sided tape to surfaces.

B. Power Plant Standards

Turkey Point has been progressive in labeling as it moves towards becoming a "visually instructive" plant. Both Turkey Point and Susquehanna are examples of sites that have carefully prepared internal procedures to ensure that all items are properly labeled in a manner consistent with existing standards.

IV. LABELING OF SPENT FUEL CONTAINERS

Standard labeling is employed by Westinghouse, Savannah River for the DWPF (Defense Waste Processing Facility) canister¹⁰. The labels are composed of bead welded characters on austenitic stainless steel plates attached to both the side and top of the canister. Figure 3 demonstrates the location of the labels. Attachment to the canister is by welding. The required character font is 92 point Megaron Bold Condensed, or equivalent. This is a sans serif font character with individual character sizes of 30 mm by 20 mm. A 6 character alphanumeric code is used on the labels referenced to the canister contents. Tests were conducted to ensure the visibility of the labels.

V. OTHER LABELING TECHNIQUES

The labeling methods discussed so far use alphanumeric characters and numerals. Although optical character recognition could be explored to automate the identification of these characters, bar code is already employed in the nuclear industry. Turkey Point¹¹ uses a bar code system to maintain records concerning test equipment. The system ensures that the test equipment is calibrated as required by the NRC and errors have been significantly reduced.

A. Bar Coding

Bar coding is standardized and used widely under the Universal Product Code. A bar code system includes the bar code symbol, a scanner, and a bar code reader. The symbol is composed of 30 dark and 29 light parallel lines that contain 10 numeric characters of data¹². To increase the visibility of a bar coded label on the waste package, the symbol size is infinitely variable and can be expanded. The labels are scanned with He-

Figure 3. DLHW Labeling Scheme

Ne or solid state lasers. The light source usually emanates from the scanner, but regular background lighting is possible. Scanners have been designed into wands that are passed over the symbol, or moving beam devices that only require the operator to point the scanner at the code. A review of the technology is presented by K. R. Sharp¹³. The common bar code symbolologies are public domain and are maintained by the Universal Code Council (UCC) and the Automatic Identification Manufacturers, Inc. (AIM).

Various techniques are used to increase the accuracy of bar code reading. Check characters have been shown to prevent 97% of the errors commonly encountered by scanner/reader systems. Print quality, including uniformity of inking and the contrast between dark and white spaces, also affects the readability of the symbols.

The Turkey Point nuclear power plant included bar coding to manage measurement and test equipment¹¹. They reported a significant decrease in errors in damage repair and calibration of such equipment as a result of the bar code system. A portable computer/reader and an IBM-PC/AT system were used to reduce their two-week annual inventory of testing equipment to a single 8-hour shift.

Bar coding lends itself to automated inventory control and decreases the errors associated with the reading of labels. This technology should be explored further for application to the spent-fuel container.

B. Optical Character Recognition

In cases where humans and machines must read the same labels, optical character recognition (OCR) may be a suitable alternative to bar coding. A labeling system based on OCR requires a high-quality printer, a scanner, a computer, and suitable software. Several problems exist in the application of OCR to the spent-fuel container.

1. Print quality must be very high for reliable interpretation.
2. Print on curved surfaces introduces errors.
3. Damaged or obscured labels will be difficult to interpret.
4. Errors are high if different fonts or font sizes are used.

OCR systems work best when a limited number of standard fonts are used. It is suggested that spelling checkers and check characters be used to verify accuracy.

As the price of OCR systems and the error rate decreases, these systems may be useful in the present application. OCR software for IBM-PC and Apple computers is common and often work with common PCX and TIFF file formats¹⁴.

C. RF Labels

Radio Frequency tagging has special advantages in applications where labels are obscured from view. RF labeling systems require readers, programmers, and special tags. The tags may be active and require battery power to operate, or passive and receive power from the reader. Passive tags tend to work better in hostile environments including high temperatures. The tags range in size from 15 to 100 millimeters in diameter and only transmit their information under special circumstances. The tags may be read-only or read-write and may contain thousands of characters of information.

Tags are read by a transponder/interrogator system. The transponder consists of an antenna that is designed to receive a signal from only one tag at a time. Larger antennas cover larger areas. Interrogators control the transponders and maintain high quality communication with the tags. Data can be transferred from the interrogator to a computer system to maintain records.

Licensing must be considered with the Federal Communications Commission before any RF system is used. Standards for RF tags are under development by the Automotive Industry Action Group, the Canadian and American Association of Railroads, and the Automatic Identification Manufacturers, Inc.

RF tags may be well suited to the spent-fuel container labeling since they will not require line-of-sight to interrogate. Passive tags may function well in the high temperature environment of the container. The operator of an RF reader will not need to closely approach the container to determine its process history and identification. This may reduce the radiation and heat exposure to such personnel. Further studies should determine whether RF tags will work on the surface of a container where temperatures in excess of 373 K will be encountered and radiation levels may be high.

D. Miscellaneous Labeling Methods

Other labeling methods have been considered, but do not seem suitable to the container. Magnetic stripes, for example, require a magnetic reader to be passed directly over the stripe. They do not function well in harsh (high temperature) environments and do not appear suitable to the container.

VI. CONCLUSIONS AND RECOMMENDATIONS

Standard labeling schemes are outlined by government, industry, and professional organizations. The existing standards can be used to specify the labeling scheme for waste package identification. Labeling concerns relating to the spent-fuel container are shown in figure 4. The following recommendations for the labeling of the container are made:

Figure 4. Possible Container Labeling Methods

1. Use existing standards wherever possible.
2. The placement of the labels as employed on the DLHW container should be considered. The welded characters on the DLHW container may not be as readable as other labeling methods, however.
3. The use of a standard font (Helvetica or another sans serif font), font size, and character spacing as documented in EPRI NP-6209 is advised.
4. Redundant labeling methods may be necessary to meet the proposed 99% reliability requirement for label retention.
5. A labeling technique that enhances visibility should be used. This may require the use of a stainless steel label with black characters on a white background. The use of such a label as documented in EPRI NP-6209 will also accommodate bar coding.
6. Bar coding or another automated technique should be used to reduce errors in retrieving container information.
7. The use of passive RF labels should be further explored. These devices can be sensed in areas where visibility is impeded and their use may help decrease radiation exposure to personnel retrieving container information. The use of RF labels may be limited by the high temperatures on the surface of the spent-fuel container.
8. The spent-fuel container labeling should be a part of an overall labeling plan for the entire repository as is currently done at nuclear power plants.
9. A mockup should be developed to test the viability and readability of any proposed labeling method.

VII. ACKNOWLEDGEMENTS

This work was conducted by the Waste Package Research Group within the Howard R. Hughes College of Engineering at the University of Nevada, Las Vegas.

"This report was prepared with the support of the U.S. Department of Energy, Grant No. DE-FC08-89NV10872. However, any opinions, findings, conclusions, or recommendations expressed herein are those of the authors and do not necessarily reflect the views of DOE."

REFERENCES

1. UNITED STATES NUCLEAR REGULATIONS COMMISSION, Title 10, Chapter 1, Part 60, "Disposal of High-Level Radioactive Wastes in Geologic Repositories," (1989).
2. U.S. DOE, "Progress Report on the Scientific Investigation Program for the Nevada Yucca Mountain Site," DOE/RW-0217P, no. 1, pp. 39-40, (1990).
3. U.S. DOE, "Waste Package Design Requirements Document (WPDR)," Draft Revision B, Yucca Mountain Project, (1989).
4. ASME, "Quality Assurance Program Requirements for Nuclear Facilities," ASME NQA-1-1989, (1989).
5. ANSI/ASME, "Packaging, Shipping, Receiving, Storage, and Handling of Items for Nuclear Power Plants," N45.2.2-1978, (1979).
6. J. L. SEMINARA, "Effective Plant Labeling and Coding," EPRI NP-6209, (1988).
7. EPRI, "Human Engineering Design Guidelines for Maintainability," NP-4350, Project 2166-4, (1985).
8. EPRI, "Control Room Deficiencies: Remedial Options and Human Factors Research Needed," NP-5195, (1988).
9. S. KALISZ and K. BRUNELL, "Turkey Point becomes a 'visually instructive plant,'" Nuclear News, October, pp. 34-36, (1987).
10. WESTINGHOUSE SAVANNAH RIVER COMPANY, "Waste Form Qualification Report," WSRC-TR-90-304, section 2.3, (1990).
11. R. C. SONTAG, "Using bar code technology at Turkey Point to manage measuring and test equipment," Nuclear News, pp. 33-34, (1987).
12. WU, "Omnidirectional laser scanner for supermarkets," Optical Engineering, vol 20, no 1, pp. 123-128, (1981).
13. K. R. SHARP, Automatic Identification. Making it Pay, Van Nostrand Reinhold, pp. 11-36, (1985).
14. D. CRUPNICOFF and M. SUSEVICH, "Advanced Optical Character Recognition for Any Scanner," Olduvai Corp., (1989).

**Supplemental Task B.1 - Structural Analysis and Design Waste
Package Container**

**CRITICAL STRESSES IN PINTLE, WELDMENT & TOPHEAD OF NUCLEAR WASTE
CONTAINER**

Dr. Samaan Ladkany

Brett Kniss, MSCE

CRITICAL STRESSES IN PINTLE, WELDMENT AND TOP HEAD OF NUCLEAR WASTE CONTAINER

Samaan G. Ladkany, Ph.D., P.E.
Professor of Civil Engineering
University of Nevada, Las Vegas
4505 Maryland Parkway
Las Vegas, Nevada 89154
(702)-597-4328

Brett R. Kniss, MSCE.
Principal Research Engineer
Los Alamos National Laboratory
Los Alamos, New Mexico 87545
(505)-667-4010

ABSTRACT

Critical stresses in the pintle, the weldment, and the top heads (flat and curved), of a high level nuclear waste container are evaluated under an annular loading. This loading is three times larger than the expected normal operating load. Results show that the shape and the thickness of the pintle and the top head, along with the thickness of the weldment, substantially affect the magnitude of the critical stresses and distortions in the various components (i.e. pintle, shell, and heads) when they are supporting a load. Stiffer top heads and pintles and larger weldment sizes reduce the critical stresses in all welded joints. Various shapes of curved top heads were investigated. An ASME flanged and dished top head, which has the same thickness as the canister, is analyzed.

I. INTRODUCTION

Designs of selected components for a long term high level nuclear waste storage containers have been evaluated, based on conservative loads and assumptions. The analysis is parametric in nature and the technique may be used to evaluate other types of containers, having different design thicknesses,

sizes, and top head shapes.

The contents of the container (it's payload) can be one of four nuclear waste forms :

1. intact fuel assemblies.
2. consolidated fuel rods from Boiling Water Reactors (BWR).
3. consolidated fuel assemblies from Pressurized Water Reactors (PWR).
4. Defense High Level Nuclear Waste (DHLW)

This fourth waste form (DLHW) is consolidated into borosilicate glass and poured into a pour canister. Then, the pour canister is placed inside a standard waste container for long term disposal.

The principal design concern is the prevention of crack initiation which may lead to stress corrosion cracking over long periods of time. These stresses may occur in: the weldments, the top head, the pintle joint, or the cylindrical container. This effect may be minimized by limiting the stresses (which occur under operating or accidental conditions) to acceptable levels.

A. Payload

A study conducted at Lawrence Livermore National Laboratory¹ suggests that as many as 18 consolidated BWR assemblies could be placed into a single waste container. Following this approach, we simulated the load which would occur from this configuration by calculating the load due to placing 882 consolidated fuel rods from 18 Exxon/ANF BWR 7x7 fuel assemblies (the heaviest that we found), into a waste container. These eighteen consolidate assemblies weigh a total of 49 kN (11,000 lb). The estimated average weight of a storage container² is 15.6 kN (3500 lb.). The initial estimate for the actual payload (i.e. waste canister plus 18 consolidated waste assemblies) is 64.5 kN (14,500 lb.).

B. Safety Factors

A safety factor of 3.0 is used in this analysis, as suggested by the Nuclear Regulatory Commission². Therefore, the total load applied to the container for stress analysis is three times the actual expected payload. This total load is 194 kN (43,500 lb.).

C. Strength

The yield strength of the selected container material (304L stainless steel) is 220 MPa (32,000 psi.); the ultimate strength is 586 MPa (85,000 psi.). These high strength values delineate the selection of 304L stainless steel for the long term storage of nuclear waste, in part because 304L displays high ductility and a high resistance to crack initiation.

II - CONTAINER DESIGN

An existing container design with flat top head and a pintle, Figure 1, is evaluated under a severe axial load. The results show that the pintle is adequate with the existing design (to a safety factor of at least three). Improvements are suggested which raises this safety factor to approximately six. Several flat top head designs are evaluated for stress under an annular loading in the axial direction.

The parameters selected for evaluation are the thickness of the circular plate (head) and the thickness of the required weldment. Results from

the stress analysis of a .0381 m (1.5 inch) thick top head plate indicate a safety factor less than three. Results from the analysis of a .0508 m (2 inch) top head plate show an improved, but marginal safety factor. Analysis results indicate that a thicker pintle or a stiffer plate will improve the design.

Several curved top head shapes are analyzed under an annular load. The ASME flanged and dished shape, Figure 2, displays more desirable properties than others. The top head radius of curvature as a critical parameter, is identified and changed to provide acceptable stress levels.

III - Design Considerations

This study is applied to 304L stainless steel cylindrical canisters with pintle and top head for high level nuclear waste. The container design³ and material⁴ are candidates in current studies and they have been used in previous structural studies. In addition to existing flat top head designs, we have evaluated the performance of several curved top heads and pintle combinations in an attempt to reduce the overall weight of the vessel and the maximum critical stresses in the weldment and in the structures themselves (i.e. top head, bottom head, pintle, and shell)

The integrity of the sealed container during very long term storage (500 to 10,000 years) may depend on the ability of the welded regions to resist the phenomena of stress corrosion cracking. This phenomena may initiate due to microscopic cracks in: the canister, the pintle, the top head, or the welded regions.

Severe axial loads may result from an accidental dropping of the canister while it is being lowered by its pintle. This situation would greatly increase the axial stresses if the lowering cable were suddenly stopped, thus jerking the canister to a stop by its pintle. Similar severe loading conditions may result if the container is being pulled from a collapsed hole in a geological formation. Other loading conditions may not affect the jointed regions

Major Dimensions

L_t = Total Length
 L_c = Cylinder length
 L_p = Pintle Length
 T_w = Wall thickness
 T_b = Bottom Head thickness
 T_t = Top Head thickness
 D_p = Pintle diameter
 D_c = Canister diameter

Notes

- 1) Material: 304L Stainless
- 2) All Dimensions are in inches
- 3) Wall thickness: 0.375

Figure 1 - Geometry and Major Dimensions of Flat Top Head Nuclear Waste Container.

Figure 2 - Geometry and Major Dimensions of an ASME Flanged and Dished Top Dead Nuclear Waste Container.

Table 1 - Computed Deflections of the Container Top Plate by Finite Element Compared with Timoshenko's Exact Solutions.

LOCATION	FIXED END CONDITION	FLAT 3	FLAT 5	FLAT 6	SIMPLY SUPPORTED
Center	0.0174	0.0317	N/A	0.0355	0.0465
Under Load	0.0171	0.0293	N/A	0.0322	0.0477

1a. - 1.5 Inch Top Plate Thickness (CASE 1)

LOCATION	FIXED END CONDITION	FLAT 3	FLAT 5	FLAT 6	SIMPLY SUPPORTED
Center	0.0074	N/A	0.0154	N/A	0.0196
Under Load	0.0072	N/A	0.0142	N/A	0.1887

1b. - 2.0 Inch Top Plate Thickness (CASE 2)

Figure 3 - Cross Sections of Finite Element Mesh of a Deformed and Undeformed Pintle with Top Plate.

Figure 4 - VonMises Stress Distribution in a Pintle with Top Plate Due to Annular loading Conditions (Stresses are Measured in PSI).

with the same severity.

IV - STRESS ANALYSIS OF WASTE CONTAINERS (using the finite element method)

Finite element analysis was used in the evaluation of the stress patterns in the containers⁵. Axisymmetric elements were used in the 3-D analysis. However, Figures 3 and 5 show a 2-D axial section of the finite element grid.

The grids were changed and refined extensively during the analytical work to allow for a very close evaluation of the stress patterns. The high stress regions in the weldment and in the structural components were first identified then the finite element grids were patterned and refined accordingly. When a container design was deemed to be inadequate, as a result of the stress analysis, one or more of its design parameters were changed and a new cycle of finite element^{6,7} stress analysis was performed. This approach is nonlinear in nature and time consuming. However, it was deemed necessary for a critical study of the container⁵.

A. Pintle Design

Three separate models of the pintle have been analyzed:

1. one having a cylindrical base without a weld chamfer.
2. one having a small 0.0635 m by 0.0635 m (0.25 x 0.25 in) chamfer.
3. and a third design having both chamfer and an added welded plate 0.0127 m (0.5 in) thick, on top of the pintle.

Results of the analysis indicate that all three designs are conservative. However, the maximum stresses were progressively reduced by adding chamfer at the base and by introducing a plate, welded to the top of the pintle. Therefore, it is possible to design a lighter, safer, and less costly pintle by carefully studying the stress patterns in each design due to the selected loading conditions. Figure 4 shows the von Mises stress distribution in the axial cross section through pintle and the weldment regions. The von Mises-Huber-Hensky stress [S] is calculated in three dimensional space from the three principal stresses S_1 , S_2 , and S_3 as follows:

$$S^2 = 0.5[(S_1^2 - S_2^2) + (S_2^2 - S_3^2) + (S_3^2 - S_1^2)]$$

B. Flat Top Head

Two flat circular plate models having thicknesses of 0.0508 m and 0.0381 m (2 in and 1.5 in, respectively) are analyzed. These plates are welded to the 0.71 m (28 in) diameter and 0.0095 m (0.375 in) thick canister using a continuous weld bead having the same thickness as the canister (0.0095 m).

The axial load is applied to the pintle. Analysis of the models (by finite element⁵) indicate that the failure mode for a flat top head will be at the connection between the top head and the pintle. However, the critical bending stresses are reduced when the stiffness of the flat top is increased. Even though this failure mode does not directly affect the integrity of the container itself (because the weld does not penetrate the top plate), the weldment does melt the base metal and thus becomes an integral part of it. Thus, a crack initiated in the weldment may in the long run lead to stress corrosion cracking through the entire thickness of the canister top. Such progressive stress corrosion cracking conditions, have been observed in the massive welded plate girders supporting long span bridges. Figure 6 shows the stress distribution in the axial cross section through the 2 inch thick flat top head plate and it's weldment regions (from the cylinder on the bottom to the pintle on the top). The accuracy of the finite element solutions were checked against the exact solutions for annularly loaded plates by S. Timoshenko⁸. As expected, Table 1 shows that the computed deflections for the top head plate fall between the exact deflections for a circular plate, with either a fixed or a simply supported outer circular boundary.

Since thick flat top heads are heavy and rather costly, our investigation lead to the analysis of (cheaper) curved top heads for storage canisters.

C. Curved Top Head Shapes

Various curved top head shapes which minimize bending stresses and carry most of the loading via membrane stresses, were investigated.

Figure 5 - Finite Element Mesh, Having 1397 Elements and 2964 Nodes, of the Deformed 2 in. Thick Top Head Plate Under Annular Loading Transmitted by the Pintle.

Figure 6 - VonMises Stress Distribution in the Plate and Weldment of a 2 in. Thick Top Plate (Stresses are Measured in PSI).

Figure 8 - Radial Displacement of an ASME Flanged and Dished Top Head Under Annular Loading.

Figure 9 - Meridional Stresses (Membrane and Bending) in an ASME Flanged and Dished Top Head

Figure 10 - Circumferential Stresses (Membrane and Bending) in an ASME Flanged and Dished Top Head

Figure 11 - Radial Displacement of an ASME Flanged and Dished Top Head Under Annular Loading

The most promising design is the ASME flanged and dished top head⁹, Figure 2, which has the same thickness as the cylinder body and the pintle base 0.0095 m (0.375 in). This ASME design makes weld connections easy and economical to perform. This shape was used for the DLHW container from Savannah River Plant¹⁰. The radius of curvature in the pintle (to top head) is negative. The critical dimension in the design is the radius of the transition knuckle between the pintle and the top head. A radius of 0.1778 m (7.00 in) produced an acceptable combination of bending and membrane stresses. Figures 7 and 8 show the radial displacement of the curved top head. Figures 9 and 10 show the meridional and circumferential stresses, respectively.

VI - CONCLUSIONS

Various designs of pintles, flat and curved top heads, to be used in the construction of high level nuclear waste storage containers, were investigated. Our results show that the shape and thickness of the components and the thickness of the weldment greatly affect the magnitude of the critical stresses.

Thicker and more expensive top head plates undergo lower deflections and curvatures (due to loading). This reduces the critical bending stresses in the weldment, at the pintle level and the junction between the pintle and curved top head shapes. Thus, the overall integrity of the container is increased, during long term storage.

An ASME flanged and dished top head (having the same thickness as the cylindrical canister) proved to be the most economical and convenient to manufacture. Future research work will evaluate the integrity of the container designs under various loading conditions (such as impact, lateral crushing, or high thermal stress).

ACKNOWLEDGEMENT

This research work was done under a grant by U.S. Department of Energy #DE-FC08-90NV10872.

Joe Bosse¹ is hereby acknowledged for his help typing and preparing the figures used in this paper. Mark Kiley is also acknowledged for his editing and typing assistance.

REFERENCES

1. L. B. Ballou, "Current Status of Waste Package Project Designs for the Yucca Mountain Project," UCID-100790, Lawrence Livermore National Laboratories, July (1989).
2. Nuclear Regulatory Commission, "Packing of Radioactive Material for Transport and Transportation of Radioactive Material Under Certain Conditions," 10CFR part 71, Federal Regulations, (1982).
3. C.L. Wu, J. Lee, D.L. Wu, and L.J. Jardine, Bechtel National, Inc., "Effects of a Potential Drop of a Shipping Cask, a Waste Container and a Bare Fuel Assembly during Waste-Handling Operations," SAND87-8082, Sandia National Laboratory, May (1990).
4. D.W. Gregg and W.C. O'Neal, "Initial Specifications for Nuclear Waste Package External Dimensions and Materials," UCID-19926, Lawrence Livermore National Laboratory, September (1983).
5. S.G. Ladkany and B.R. Kniss, "A Study of a Container for Long Term Storage of High Level Waste Using Finite Elements," Report to the U.S. Department of Energy, University of Nevada, Las Vegas, June (1991).
6. O. C. Zienkiewicz, The Finite Element Method, Third Edition, McGraw Hill, Inc., New York (1985).
7. M. Lashkari, Cosmos/M User Guide, Volume II, release 1.6, Structural Research and Analysis Corp., California (1990).
8. S. Timoshenko, Theory of Plates and Shells, Second Edition, McGraw Hill, Inc., New York (1959).
9. Henry H. Bednar, Pressure Vessel Design Handbook, Van Nostrand Reinhold Co., Inc., New York (1986).
10. Office of Civilian Radioactive Waste Management, "Characteristics of Spent Fuel, High level Waste and Other Radioactive Wastes Which May Require Long Term Isolation", DOE/RWW-0184, USDOW, December (1987).

**Supplemental Task B.2 - Design Requirements of Various Rock
Tunnel Shapes For Long Term Storage of High Level Waste**

STRESS ANALYSIS AND DESIGN OF ROCK TUNNELS UNDER THERMAL LOADING

Dr. Richard Wyman

Nadia Kandalaft-Ladkany, MSCE

DESIGN MANAGEMENT AND STRESS ANALYSIS OF A CIRCULAR ROCK TUNNEL AND EMPLACEMENT HOLES FOR STORAGE OF SPENT NUCLEAR FUEL

Nadia Kandalaft-Ladkany
Graduate Student in Civil Engineering
Department of Civil and Environmental Engineering
Howard R. Hughes College of Engineering
University of Nevada Las Vegas
Las Vegas, Nevada 89154
(702) 739-3701

Richard V. Wyman
Professor of Civil Engineering
Department of Civil and Environmental Engineering
Howard R. Hughes College of Engineering
University of Nevada Las Vegas
Las Vegas, Nevada 89154
(702) 739-3701

ABSTRACT

A critical Path Method (CPM) diagram and logic net are used for the design cycle of the rock tunnel system for a high level nuclear waste repository. In the analysis the design tunnel is subjected to pre-existing temperature and overburden loads at time of construction. High thermal stresses develop later due to the long term influx of heat from the canisters stored in vertical emplacement holes. Results indicate that thermal stresses reach a critical level for the rock in the vicinity of the canisters which could lead to local collapse of the rock and damage to the canisters.

INTRODUCTION

In developing a tunnel system design there are a large number of variables which affect the spacing, diameters, configuration and construction methods to be employed. In order to arrive at a workable configuration it was necessary to obtain from the D.O.E. the anticipated length and diameter of storage containers and proposed thermal energy output, which in turn depends on the anticipated time out-of-reactor for the fuel.

The proposed spacing in the storage drifts determines the necessary rate of tunnel excavation, which in turn governs the methods of tunnel excavation and canister emplacement. The spacing of canisters also determines the long term heat influx which determines the ultimate size and capacity of the repository.

Considerations of these changes in the aspect ratios and tunnel system geometry, placement and spacing for canisters, heat diffusion and heat transfer analysis, stress analysis and tunnel boring techniques are included in the Logic Net (Figure 1) and CPM Diagram (Figure 2).

Stress analysis was done by finite element analysis, using quadrilateral isoparametric four node elements for linear strain variations and

triangular three node elements for constant strain.

PROPOSAL FOR DESIGN OF ROCK TUNNEL SYSTEMS

The variable aspects of tunnel design at construction of a tunnel system in hard rock including access ramps, emplacement drifts and emplacement hole drilling are handled on the Logic Net in Figure 1.

The canisters are transported down the to the emplacement drifts in a horizontal position. They may be inserted in emplacement holes either vertically or horizontally. The length and weight of the individual canisters determine both their method of emplacement and the diameter of the storage drifts.

The shape of the tunnel is determined by the proposed mining method adopted, while the length, diameter and orientation of emplacement hole will determine the type of equipment used to them.

The amount of heat diffusion and heat transfer determine the spacing between emplacement drifts and between canisters along these drifts. Tunnel ventilation will also function of the heat produced by canisters already in place, and will also influence the temperature of the tunnel walls and near field rock temperatures.

Site investigation of the specific site repository horizon is necessary to determine material, hydrologic and thermal properties of the rock and the depth of the tunnel system. This investigation will also determine the thickness of the zone to be disturbed.

The method and rate of canister loading together with the mining method selected affect the required boring velocity and number of tunnel boring machines that will be required to provide storage for a predetermined amount of spent

LOGIC NET - Figure 1

nuclear fuel and rate of loading. These will determine the completion date of the repository.

We must assume from the large amount of material expected (30,000 canisters) that part of the repository will be under construction while other parts of the repository are receiving spent fuel. This fact will also greatly affect the ventilation system design and required horsepower of operation.

Finite element stress analysis, taking into consideration the geometry of tunnels and emplacement holes, their spacing, overburden and temperature distribution determines the stability of the tunnel system.

The CPM diagram titled "Project Management Method" shows an orderly progress of the design cycle tasks. Our research has not determined the units of time required for completion of each task. This will require an input from completion of the site characterization studies and several research laboratories.

Once the time units for the various activities are determined, a CPM program may be used to execute the proposed project management scheme in an orderly and timely manner allow for checking of each design parameter and feedback to give the best design for optimum

TUNNEL DESIGN CONSIDERATIONS

The following parameters of design were considered in analysis by finite element:

1. Size of canister hole
2. Spacing of canister hole
3. Tunnel size and shape
4. Tunnel spacing
5. Gravity (overburden)
6. Geothermal temperature
7. Temperature distribution in the near field rock
8. Rock material properties
9. Tunnel ventilation

Gravity data for the first approximate loading are tabulated on Table 1.

TABLE 1
Physical Properties

Bulk density	2.34 g/cc	Tuff unit TSW2
Grain density	2.55 g/cc	Tuff unit TSW2
Dry density	2.25 g/cc	Tuff unit TSW2

Overburden:

Unit	Density g/cc	Thickness m	Pressure MPa
UO		9.14	0.5 (assumed)
TCW	2.31	26.8	0.61
PT	1.58	38.1	0.59
TSW1	2.25	130.1	2.87
TSW2	2.32	82.01	1.865
		<u>286.15</u>	<u>6.435</u>

The geothermal temperature for the first approximation of heat stress is based on the gradient published by Szabo⁸. Initial surface temperature is assumed at 14° C. The average geothermal gradient of 34° per km corresponds to the graph in Figure 3:

b. Rock mass thermal properties
Thermal expansion coefficient

$$\alpha = 8.8 \times 10^{-6} \text{ k}^{-1} \text{ (T < 200 C)}$$

$$\alpha = 24.0 \times 10^{-6} \text{ k}^{-1} \text{ (T > 200 C)}$$

Note:

1. Thermal expansion coefficient extrapolated between two α points as these were the only available.

2. Rock material properties were taken at ambient temperature. For future work we need data points for rock at series of elevated temperatures.

3. Future work should also determine the thickness of the disturbed zone at elevated temperature and what the rock properties may within the disturbed zone.

4. Determine where the zone of confined rock starts (outside the disturbed zone).

Geothermal Gradient - Figure 3

Ref: Szabo and Kyser, 1990

ROCK MATERIAL PROPERTIES

- a. Mechanical properties for rock mass
- Young's modulus $E = 15.2 \text{ GPa}$
  - Poisson's ratio $\nu = 0.22$
  - unconfined compressive strength $G_c = 75.4 \text{ MPa}$
  - cohesion $c = 22.1 \text{ MPa}$
  - angle of internal friction $\phi = 29.2 \text{ degree}$

FINITE ELEMENT MODEL

Analysis by finite element method by B. utilized two types of elements:

- Quadrilateral isoparametric four node element (linear strain variations)
- Triangular three node element (constant strain)

The analysis proceeded using plain-strain analysis with one meter thick elements. The

analysis accounts for temperature dependent material properties, gravity and geothermal stresses, and gravity and temperature due to stored fuel.

The results of the finite element analysis are shown on Figures 4, 5 and 6.

RESULTS OF FINITE ELEMENT ANALYSIS

The heat load applied at canister loading points was specified by D.O.E. as 3 kw/canister. This load is applied at a spacing of 20 meters per canister in emplacement drifts 38 meters apart. Using a canister length of 400.47 cm and diameter of 70 cm, the tunnel diameter for emplacement in vertical holes is 6.8 meters clear diameter, 7.2 meters bored diameter. Waste emplacement would be at 318.2 meters below the surface.

Finite element analysis was done using normal gravity and geothermal gradient, plus thermal loading from waste canisters at the rate shown above.

Figure 4 shows the near field finite element net applied to the tunnel configuration with holes drilled in the floor to accommodate the canisters. Figure 5 shows the stresses on elements at the bottom of the canister hole after 11 years where failure is expected to occur.

The analysis showed that the construction design would be stable as loaded, but that stress due to the combination of gravity and temperature will eventually exceed the unconfined shear strength of the rock at places of stress concentration. Figure 6 shows the near field temperature distribution after 11 years.

Additional analyses were made leaving a one meter opening below the canister in order to increase the distance from the heat. This also failed.

RECOMMENDATIONS

1. Canister Hole
  - a. The authors recommend further investigation with increased diameter of the canister hole (larger air gap).
  - b. Increase the depth of the hole to transfer the area of critical stress to lower temperature zone and provide a filler of loose sand or composite material to support the canister and minimize any effect of wall rock failure.
  - c. Modelling with a 3-D model of the canister and multiple heat sources.
2. Tunnel and Canister Spacing

The authors recommend parametric studies to establish optional spacing of tunnels and canisters.

3. Design of Tunnels

- a. In order to proceed with the tunnel system design, it is necessary to have more data on the physical properties of the proposed host rock and consequent heat transfer studies. These can be

Finite Element Model - Figure 4

Figure 5
Effect of thermal loading after
11 years.
Elements correspond to those in
Figure 4.

b. Ventilation needs to be included in order to understand the heat/moisture removal and attendant cooling of the repository. Studies must be done in both cases with and without ventilation.

Additional work is anticipated including consideration of the semi-saturated nature of the work, loading by earthquakes and variable spacing of canisters.

LIST OF REFERENCES

1. BATHE, KLAUS-JURGEN; WILSON, EDWARD L. and PETERSON, Fred E. (SAP IV, a structural analysis program for static and dynamic responses of linear systems); College of Engineering, University of California - Berkley, California, 1974.
2. COOK, ROBERT D.; "Concepts and Applications of Finite Element Analysis", Third Edition; John Wiley & Sons, 1988.
3. COSTIN, LAWRENCE S. and BAUER, STEPHEN; "Thermal & Mechanical codes, Part I: Thermal Analysis"; Sandia National Laboratories, Sandia Report SAND 88 - 1221. UC-814; June 1990.
4. HARRISON - GIESLER, DIANE J.; (Engineered Barrier System Workshop); Department of Energy; March 1, 1991.
5. O'NEAL, W.C., GREGG, D.W., HOCKMAN, J.N.; RUSSELL, E.W. and STEIN, W.; "Preclosure Analysis of Conceptual Waste Package Designs for a Nuclear Waste Repository in Tuff"; Lawrence Livermore National Laboratory; November 1, 1984.
6. Organization of the Waste Package plan; Department of Energy, D.O.E. order 4700.1.
7. Civilian Radioactive Waste Management; December 1988.
8. SZABO, B.J. and KYSER, T.K.; "Ages and Stable-Isotope Compositions of Secondary Calcite and Opal in Drill Cores From Tertiary Volcanic Rocks"; Geological Society of American Bulletin December, 1990.

Supplemental Task B.3 - Transport Phenomena in the Near Field

TRANSPORT PHENOMENA IN THE NEAR FIELD

Dr. James Cardle

Graduate Student: Martin Joseph

Task II

Supplemental task B - 3. Transport Phenomena in the Near Field

Personnel

Dr. J. Cardle

Mr. Martin Joseph

General Discussion

The focus of the current work is on the development of a better understanding of thermal and fluid transport in the near field rock in order to determine a mechanism for rewetting of the spent fuel package. The goal is to determine if a mechanism exists that can drive moisture back into the vicinity of a waste package.

Under undisturbed conditions, the rock is partially saturated. Input of a thermal source, the waste package, initiates a complex transient interaction between thermal transport and fluid flow in the rock. Three regions exist. Next to the waste package, the moisture has been driven from the rock, and the heat transport is due to conduction in the rock matrix. A relatively undisturbed region exists further out in the rock where there is little fluid transport and the heat transport is due to conduction in the partially saturated rock. This region is separated from the dry region by a heat pipe region. In this heat pipe region, liquid transport occurs in the direction toward the heat source and counter to the air-vapor transport. Heat is transferred in this region both by conduction through the rock and by convection of the liquid and, much more importantly, by convection of the air-vapor mixture. As the transient progresses, the dry region and the heat pipe region move further into the rock from the heat source.

If moisture is to be driven back into the vicinity of the waste package, this heat pipe region must be held close to the waste package. In this study, the factors that control the extent of the heat pipe region are focused upon. A simple heat pipe system involving a rock matrix with a fracture extending from a heat source is being modelled using the computer code TOUGH. In this heat pipe system, vapor flows down the fracture away from the heat source, condenses, and is sucked into the rock matrix and back toward the heat source by capillary effects. The properties of the rock such as the intrinsic permeability, thermal conductivity, specific heat, relative permeability, and capillary pressure functions are being changed in a systematic fashion and the resulting effects on the length and positions of heat pipe region noted. Similarly, the fracture properties are also being changed and the resulting effects on the heat pipe region noted. The relative importance of heat transfer by convection as opposed to conduction, especially at low intrinsic permeabilities, is being examined. The transient response between the capillary pressure in the fracture and the adjacent rock matrix is also being observed. Effective continuum models assume equality of these pressures. A pulsating disequilibrium between these pressures during the initial transient phase has been observed. This pressure

difference does eventually decay into an equilibrium condition, which indicates that the effective continuum approximation is poor during the initial transient, but as the flow becomes more stable this approximation is valid.

As will be discussed in the following section, mass injection/withdrawal can play a major role in destabilizing the heat pipe and hence either force the heat pipe back toward the container or move the heat pipe region further out into the rock.

Analysis

Liquid and gas (air-vapor mixture) transport in an unsaturated porous medium can be described by the equation:

$$\frac{\partial M_{l,g}}{\partial t} + \nabla \cdot \mathbf{J}_{l,g} = 0 \quad (1)$$

where $M_{l,g}$ is the mass of liquid or gas and $\mathbf{J}_{l,g}$ is the flux of liquid or gas. It has been observed in the simple fracture matrix flow model discussed above, that after some initial transients, the thermal-fluid field stabilizes, and any further changes are quite slow in occurring. At this time the thermal flow conditions are approximately in equilibrium.

Consider a control volume containing both liquid and gas. Conservation of mass requires that

$$\int_V \frac{\partial M_{l,g}}{\partial t} dV + \int_{\Omega} (\mathbf{J}_l + \mathbf{J}_g) \cdot \mathbf{n} d\Omega = \dot{M}_i \quad (2)$$

where $\dot{M}_i$ represents sources or sinks of mass. The second integral represents the flux of fluid over the surface of the control volume V . Assuming that the flow is essentially in equilibrium leads to:

$$\int_{\Omega} (\mathbf{J}_l + \mathbf{J}_g) \cdot \mathbf{n} d\Omega = \dot{M}_i \quad (3)$$

or, because the control volume is arbitrary:

$$\mathbf{J}_g = \dot{M}_i - \mathbf{J}_l \quad (4)$$

This shows that the vapor flux in the general system is opposite to the liquid flux, which is the essential feature of the heat pipe. The energy conservation for a porous media is:

$$\frac{\partial E}{\partial t} = \nabla \cdot (K_T + (h_g - h_l) J_l - S_l h_g) \quad (5)$$

where E is the thermal energy, K_T is the thermal conductivity, $h_{l,g}$ is the enthalpy of the liquid or gas. If thermal equilibrium exists, then:

$$\nabla \cdot (K_T + (h_g - h_l) J_l - S_l h_g) = 0 \quad (6)$$

If there are no sources or sinks, then the net convective heat transport balances the conductive heat transfer. On the other hand, if fluid is either injected into or withdrawn from the cycle, the injection shifts the energy balance and the point of equilibrium will shift. Obvious sources and sinks of mass in the actual system include water flow down a fracture, vapor withdrawal through the tunnel, and air flow by convection through the fracture system in the mountain.

Mathematical model

A variety of mathematical models have been formulated at the national laboratories. One set of models, such as the COYOTE model developed at Sandia Laboratories, simulate heat transport by solution of the unsteady heat conduction equation. The thermal conductivity is varied depending upon the whether the temperature is less than or greater than 100 °C in order to take into account the liquid saturation. Other more complex models also exist. TOUGH is based upon the solution of liquid, gas, and thermal conservation equations (3 equations) by the finite volume method. In this model, the additional assumption is made that the gas is saturated. The model NORIA solves four conservation equations, liquid, gas, vapor, and heat, by finite element method. The purely conductive models lack sufficient physics to be able to adequately model the heat pipe region. The other models such as NORIA and TOUGH have a highly complex physical basis and are quite capable of modeling complex flow phenomena such as the heat pipe region, but require the solution of a system of complex non-linear equations at each computational point. These models are thus computationally intensive and can exhibit convergence problems. The analysis discussed above suggests that there may be an intermediate approach that can model the heat pipe phenomena without the number of equations used in TOUGH or NORIA. Two such models are currently under development.

The first model is based on the observation that the gas pressure is approximately constant and that period of the phenomena of interest is quite long so that the vapor phase is in equilibrium with the liquid phase and that the gas transport is in local equilibrium with the liquid transport. If in a system over a long period of time the liquid saturation is basically a function of temperature, a quite simple model can be produced. These assumptions can be stated:

$$1. \quad p_g = p_{air} + p_v$$

$$2. \quad p_v = p_{sat}(T) \text{ if } T < 100 \text{ }^{\circ}\text{C} \quad \text{else} \quad p_v = p_{sat}(100 \text{ }^{\circ}\text{C}) \text{ if } T > 100 \text{ }^{\circ}\text{C}$$

$$3. \quad J_g = -J_l$$

$$4. \quad S_l = S_l(T)$$

Substitution of these assumptions into the thermal transport equation, eqn 5, eliminates all of the unknowns except temperature. Thus the model is a one equation model that incorporates the heat pipe effect.

In order to improve the physics, assumption 4 above can be replaced with the liquid transport equation, eqn 1. This produces a two-equation model with two unknown conditions, temperature and liquid saturation.

Finite element versions of both of these suggested approaches are currently being developed. It is intended to test these against more complex codes such as TOUGH in order to determine if these simpler models can replicate the essential results of the more complex models without the attendant computational problems.

Other Activities

- Dr. J. Cardle attended special sessions on thermal and fluid transport in porous media at the Winter Annual Meeting of the American Society of Engineers in Atlanta.

- The latest version of TOUGH has been ordered.

- Finite element codes LUSAS and MYSTRO have been acquired for use in the modeling effort discussed above.

END

**DATE
FILMED**

7 / 8 / 92