UNCLASSIFIED (CLASSIFICATION)		DOCUMENT NO. BNWL-CC-576		BNWL-CC--576
ISSUING FILE	COPY NO. 13-	DATE March 30, 1966		DE92 013470
	PROJECT			
	<div style="font-size: 1.5em; font-weight: bold; margin: 0;">BATTELLE-NORTHWEST</div> <div style="font-size: 0.8em; margin: 0;">RICHLAND, WASHINGTON</div>			
TITLE WSEP 30-TON LIQUID TRANSFER CASK "DESIGN CRITERIA AND PERFORMANCE TESTS"				
AUTHOR C. R. Cooley and M. E. Spaeth				
DISTRIBUTION				
NAME <u>BNW</u> EA Berreth 325 300 CR Cooley (4) 324 300 RL Junkins Fed. Bldg., Rm. 220 CE King (2) 324 300 HM Parker 3201 3000 AM Platt 324 300 ME Spaeth 324 300 MT Walling 324 300 Central Files (3) 3760 300		NAME <u>ITT Federal Support Services</u> SF Campbell, Jr. Fed. Bldg., Rm. G38 AP Mitchell 1171 1100 MF Rice 1170 1100		
AEC CL Robinson Fed. Bldg., Rm. 618 <u>Isochem</u> SJ Beard 271-B 200-E MK Harmon (2) 2704-E 200-E OV Smiset (2) 271-B 200-E RE Tomlinson 2704-E 200-E		<div style="font-size: 1.2em; font-weight: bold; margin: 0;">DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED</div>		
ROUTE TO		PAYROLL NO.	LOCATION	FILES ROUTE DATE
UNCLASSIFIED (CLASSIFICATION)				
(TO BE USED ON UNCLASSIFIED AND OFFICIAL USE ONLY DOCUMENTS)				

WSEP 30-TON LIQUID TRANSFER CASK
"DESIGN CRITERIA AND PERFORMANCE TESTS"

by

C. R. Cooley and M. E. Spaeth
Chemical Development Section
Chemistry Department

March 30, 1966

Classified by: A. M. Platt

INFORMATION CONCERNING USE OF THIS REPORT

PATENT STATUS

This document copy, since it is transmitted in advance of patent clearance, is made available in confidence solely for use in performance of work under contracts with the U. S. Atomic Energy Commission. This document is not to be published nor its contents otherwise disseminated or used for purposes other than specified above before patent approval for such release or use has been secured, upon request, from the Chief, Chicago Patent Group, U. S. Atomic Energy Commission, 9800 So. Cass Ave., Argonne, Illinois.

PRELIMINARY REPORT

This report contains information of a preliminary nature prepared in the course of work under Atomic Energy Commission Contract AT(45-1)-1830. This information is subject to correction or modification upon the collection and evaluation of additional data.

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or

B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

PACIFIC NORTHWEST LABORATORY
RICHLAND, WASHINGTON
operated by
BATTTELLE MEMORIAL INSTITUTE
for the

UNITED STATES ATOMIC ENERGY COMMISSION UNDER CONTRACT AT(45-1)-1830

WSEP 30-TON LIQUID TRANSFER CASK
"DESIGN CRITERIA AND PERFORMANCE TESTS"

I. INTRODUCTION

Shipment of radioactive wastes in shielded transfer casks is a continuing practice between the 300 Area and the 200 Areas. However, the Waste Solidification Engineering Prototypes (WSEP) located in 324 Building, 300 Area, require the transfer of significant quantities of radioactive wastes. Two new 30-ton casks are being placed in service to accommodate the increased number of shipments.

The purpose of this report is to document the design criteria, tests and calculations performed on the casks and modifications to the original cask design to insure its safe use. The design criteria was developed in January 1963 by an ad hoc committee comprised of representatives of the Chemical Processing Department, Hanford Laboratories, and Construction Engineering and Utilities of General Electric Company. The various tests, calculations and modifications of the cask were conducted by the Chemistry Department of Pacific Northwest Laboratory.

II. DISCUSSION

A. Cask Description

The WSEP 30-ton shielded transfer casks were fabricated by North West Copper Company, Portland, Oregon, in 1964. The casks (see Figures 1, 2, and 3) are spherical in shape (75 inches OD) and have a hollow interior (55.5 inches ID). The inner (3/4-inch thick) and outer (1 inch thick) spheres are made of 304-L stainless steel with eight (8) inches of lead shielding (cast slowly for good bonding). The inner sphere is wrapped with 1/2-inch OD x 0.035-inch

FIGURE 11

30 TON LIQUID CASK ASSEMBLY

27 28 29 30 4

SPARE 1" SCH 80 SST BORE TO 1.000 DIA AFTER WELDING 1/2" VAC VENT

1" EMPTY LINE

8 TUBING 1/2" O.D. x .035" WALL ASTM A213-G17 TYPE 304L SST

9

13

1 1/2" DIA C BORE x 1/4" DEEP 1" LONG 28 THRU PLUG & SEAL WELD PLATE FLUSH AFTER ADJUSTMENT TYPICAL (6) PLACES

1" PLATE BAIL 2. REQ'D DIAMETRICALLY OPPOSITE

3/8" R BOTH SIDES OF PLATE ALL AROUND OPENING

26

37 1/2" R

3/4" LEAD

27 1/2" R

NOTCH R TO CLEAR COILS & WELD AFTER COILS ARE IN PLACE ON INNER VESSEL

1" DIA BAR

3/8" PL

3/8" CONT RING STIFFENER

PL 6" x 1/2" x 0.125"

C BORE 1 1/2" DIA x 1/4" DEEP

(TYPICAL FOR 6) VIEW "H-H"

QTY	ITEM NO.	DESCRIPTION
X	1	CASK ASSEMBLY
1	2	INNER VESSEL
1	3	OUTER VESSEL
1	4	TOP PLATE H-3-21112 PT2
1	5	LID PT3
1	6	COVER PT1
1	7	BASE
1	8	UPPER COOLING COIL
1	9	LOWER COOLING COIL
1	10	HINGE PIN H-3-21112 PT4
4	11	EXPANDING DOWEL PIN 1/2" x 3/4" LG S.S.T.
2	12	SPRING
6	13	SPACER PLUG H-3-21112 PT5
1	14	VALVE DOUBLE SEAL BALL 1/2" DIA 304L SST
1	15	MALE ELBOW 1/2" x 1/2" x 304L
1	16	MALE ADAPTER 1/2" TO PIPE 3/4" x 1/2" x 304L
1	17	TO BUTT WELD ELBOW 1/2" x 1/2" x 304L
1	18	TO BUTT WELD MALE CONNECTOR 1/2" x 1/2" x 304L
1	19	BULKHEAD UNION 1/2" x 1/2" x 304L
4	20	TO BUTT WELD MALE CONNECTOR 1/2" x 1/2" x 304L
2	21	TO BUTT WELD MALE CONNECTOR 1/2" x 1/2" x 304L
2	22	BULKHEAD UNION 1/2" x 1/2" x 304L
1	23	RUPTURE DISC
4	24	SPRING 304L SST 1/2" x 1/2" x 1/2" LG S.S.T.
4	25	LID CLAMP BASE H-3-21112 PT6
4	26	LID CLAMP END H-3-21112 PT7
4	27	EXPANDING DOWEL PIN 1/2" x 3/4" LG S.S.T.
4	28	SPRING H-3-21112 PT10
4	29	WING NUT 1/2" x 1/2" x 1/2" S.S.T.
4	30	HEX NUT 1/2" x 1/2" x 1/2" S.S.T.
1	31	PLUG H-3-21112 PT8
1	32	PLUG H-3-21112 PT9
1	33	LEAD ASTM B29-55
2	34	BULKHEAD UNION 1/2" x 1/2" x 304L S.S.T.
1	35	LID H-3-21112 PT11
1	36	HINGE PIN PT12
1	37	QUAD RING SEAL #Q13 NEOPRENE HANFORD ATOMIC
1	38	QUAD RING SEAL #Q83 NEOPRENE HANFORD ATOMIC
4	39	SCREW 1/2" x 1/2" x 1/2" x 1/2" S.S.T.

GENERAL NOTES

- WELDING FABRICATION OF THE INNER VESSEL SHALL BE IN ACCORDANCE WITH HANFORD WORKS STANDARDS HW-900'S "QUALIFYING WELDERS" & HW-900'S "WELDING OF 304L STAINLESS STEELS".
NOTE: WELDS MAY BE REWELDED (ASME SEC III 1962 SUBSECTION B) SHALL BE REWELDED IF UN-12 100% RADIOGRAPHED (EXCEPT PIPE PENETRATION WELDS MAY REQUIRE SPECIAL TECHNIQUES TO DETERMINE FULL WELD PENETRATION).
- INNER VESSEL SHALL BE PRESSURE TESTED TO 1000 PSIG BEFORE ASSEMBLY INTO OUTER SHELL.
- MATERIAL CERTIFICATION AND IDENTIFICATION PER ASME SEC III REQUIRED FOR INNER VESSEL PIPING.
- USE TYPE 304L FILLER FOR ALL WELDS.
- INNER VESSEL SHALL BE GIVEN A HALOGEN LEAK TEST.
- TOLERANCES: FRACTIONAL DIMS $\pm \frac{1}{16}$ (UNLESS OTHERWISE NOTED).
ANGLES $\pm \frac{1}{2}^\circ$.
TOLERANCES SHALL BE NON-ACCUMULATIVE.
- REMOVE ALL BURRS BREAK ALL SHARP CORNERS.

30 TON LIQUID CASK ASSEMBLY

324 3902

H-3-21110

U. S. ATOMIC ENERGY COMMISSION
HANFORD ATOMIC PRODUCTS OPERATION
GENERAL ELECTRIC

APPROVED FOR CONSTRUCTION
APPROVED FOR PURCHASE
APPROVED FOR DESIGN
APPROVED FOR FABRICATION

SCALE NONE

DATE 1/2/61

DESIGNER
CHECKED
APPROVED

REFERENCE DRAWINGS

NOT LATER ON

5 HW-900'S HANFORD WORKS STANDARDS
4 HW-900'S HANFORD WORKS STANDARDS
3 H-3-21112 CASK DETS
2 H-3-21111 CASK SECTIONS & DETS
1 H-3-200 DRAWING LIST

Q	DESCRIPTION
X 1	CASK ASSEMBLY
1 2	INNER VESSEL
1 3	OUTER VESSEL
1 4	TOP PLATE H-3 21112 P12
1 5	LID PTF
1 6	COVER PTF
1 7	BASE
1 8	UPPER COOLING COIL
1 9	LOWER COOLING COIL
1 10	HINGE PIN H-3 21112 P14
4 11	EXPANDING DOWEL PIN $\frac{1}{8}$ " $\frac{1}{2}$ " LG S ST
2 12	SPRING
6 13	SPACER PLUG H-3 21112 PTF
1 14	VALVE DOUBLE SEAL BALL 1" DIA. 316 304L H-3 21112 P15
1 15	MALE ELBOW "910-2-B-304L 1" DIA. 316 304L H-3 21112 P16
1 16	MALE ADAPTER TUBE TO PIPE "911A-B-304L 1" DIA. 316 304L H-3 21112 P17
1 17	WELDED ELBOW "910-9-B-304L 304L H-3 21112 P18
1 18	TO BUTT WELD MALE CONNECTOR "400-1-1/4-304L 1" DIA. 316 304L H-3 21112 P19
1 19	BULKHEAD UNION 1" DIA. 316 304L H-3 21112 P20
4 20	TO BUTT WELD MALE CONNECTOR "910-1-1/4-304L 1" DIA. 316 304L H-3 21112 P21
2 21	TO BUTT WELD MALE CONNECTOR "1610-1-1/4-304L 1" DIA. 316 304L H-3 21112 P22
2 22	BULKHEAD UNION 1" DIA. 316 304L H-3 21112 P23
1 23	RUPTURE DISC
4 24	SPRING 1/2" DIA. 1/2" LG S ST
4 25	LID CLAMP BASE H-3 21112 P24
4 26	LID CLAMP END H-3 21112 P25
4 27	EXPANDING DOWEL PIN $\frac{1}{8}$ " $\frac{1}{2}$ " LG S ST
4 28	SPRING H-3 21112 P26
4 29	WING NUT $\frac{1}{2}$ " 16UNC 2B S ST
4 30	HEX NUT $\frac{1}{2}$ " 16UNC 2B S ST
1 31	PLUG H-3 21112 P27
1 32	PLUG H-3 21112 P28
1 33	LEAD ASTM B29-55
2 34	BULKHEAD UNION 1" DIA. 316 304L H-3 21112 P29
1 35	LID H-3 21112 P30
1 36	HINGE PIN PTF
1 37	QUAD RING SEAL "Q13 NEOPRENE 1" DIA. 316 304L H-3 21112 P31
1 38	QUAD RING SEAL "Q23 NEOPRENE 1" DIA. 316 304L H-3 21112 P32
4 39	SCREW $\frac{1}{2}$ " 16UNC 2A $\frac{1}{2}$ " LG S ST

GENERAL NOTES

1. WELDING FABRICATION OF THE INNER VESSEL SHALL BE IN ACCORDANCE WITH HANFORD WORKS STANDARDS HW-4900'S "QUALIFYING WELDERS" & HW-4900'S "WELDS" & "WELDING STEELS"
NOTE: WELDS CANNOT BE BED WELDS (ASME SEC III 1962 SUBSECTION B) SHALL BE HELD (W/12) OF UW-12 100% RADIOGRAPHED (EXCEPT PIPE PENETRATION WELDS MAY REQUIRE SPECIAL TECHNIQUES TO DETERMINE FULL WELD PENETRATION)
2. INNER VESSEL SHALL BE PRESSURE TESTED TO 1000PSIG BEFORE ASSEMBLY INTO OUTER SHELL
3. MATERIAL CERTIFICATION AND IDENTIFICATION PER ASME SEC III REQUIRED FOR INNER VESSEL & PIPING
4. USE TYPE 300L FILLER FOR ALL WELDS
5. INNER VESSEL SHALL BE GIVEN A HALOGEN LEAK TEST
6. TOLERANCES: FRACTIONAL DIMS $\pm \frac{1}{16}$ (UNLESS OTHERWISE NOTED)
ANGLES $\pm \frac{1}{2}^\circ$
TOLERANCES SHALL BE NON ACCUMULATIVE
7. REMOVE ALL BURRS BREAK ALL SHARP CORNERS

H-3-21110

[illegible]

FIGURE 2

1 MAT'L: 14 GA S ST
ASTM A240-61T TYPE 304-L

2 HOLES 2 DIA ON
18 DIA FITCH CIRCLE
PLUG & WELD AFTER
POURING OF LEAD AT ASSY

PART NO.	E	F	G	H
3	8	5	3	78
11	6 1/2	4 1/2	2 1/2	58

(4) 1/2 STUDS (WELD OR THQ)
1/2 UNC 2A 1" THD LG

1/4 W. 1/2 DEEP
SLOT

5 MAT'L: GENERAL
METALL DETROIT
(OR AP)

2 MAT'L: S ST ASTM A240-61T
TYPE 304-L

SECT' P-P

FIGURE 3

wall stainless steel tubing with a spacing of approximately 1-7/8 inches. The outer sphere is equipped with lifting ears and a support pallet made of stainless steel.

The cask is equipped with a series of lines for filling, emptying and venting, etc. All are made of stainless steel pipe which passes through the shielding from the top-wells to the inner sphere. All connections terminate in one of two recessed wells. The smaller well contains only the vent line and the vent valve. The other contains all of the empty and fill connections. It also contains a one-inch vertical opening filter with a capacitance liquid level probe and another normally plugged one-inch opening for a spare. The wells are covered by hinged lids which are sealed by O-ring gaskets. For shipment the two lids are covered by an additional stainless steel cap.

Other auxiliaries include cooling water and temperature connections on the outside sphere. Two thermocouple probes are provided. One thermocouple measures the inner sphere temperature and the other measures the temperature one inch inside the outer sphere.

B. Design Criteria

The major objectives of the design were structural strength, heat transfer, and safety.

The casks are designed to:

1. Withstand a fall (full or empty) from four feet on a non-yielding surface.
2. Be lifted and tied down (for shipping) by the use of two (2) lifting ears welded to the cask.

3. Withstand a fire fueled by 100 gallons of gasoline or a 20-30 minute exposure to a gasoline fire, whichever is least severe.
4. Withstand a head-on impact with a pickup truck at a maximum speed of 30 mph without rupture.
5. Withstand an internal heat of 16 kw for eight hours before the cask contents reach greater than 200°F (without the use of the installed cooling coils).
6. Withstand an internal pressure of 1000 psi. A rupture disk on the cask is rated to fail at 750 psi and withstand full vacuum without changing its rating.
7. Reduce surface radiation to 10 mr/hr when filled with 40 gal/ton Purex 1WW waste at 90 day cooling from the reactor.
8. Avoid overfilling by the use of a vacuum dip leg located 12-3/4 inches below fill level.
9. Gradually bleed off any pressure to a vent system by use of a 1/2-inch vacuum vent line and valve.

C. Modifications

Several modifications were completed to insure safe use of the cask.

1. An optional all-welded, stainless steel, three-point connector is provided to interconnect the vacuum-dip leg, empty line, and spare empty line. Individual Swagelok blanks can also be used. When the cask becomes significantly pressurized during shipment, a leak in the blanks could allow liquid to enter the well. Use of the three-point connector equalizes the pressure in all connections and prevents an external leak of liquid.
2. A piece of 1" x 6" x 3" high SST was welded to the lifting ears near the cask to assure structural stability and good tie-down on the trailer for shipping. These aid in keeping extra chains from slipping. The extra chains can be used to pull the cask down tightly to the trailer floor.
3. An emergency cooling connector is supplied with the casks for easy connection to a fire tanker. This connector goes with the cask while in transit. Emergency cooling may be required if a truck breakdown occurs.

4. A capacitance probe which records the level of the cask at any point was substituted for the conductance alarm probe to avoid potential ignition of the gases produced by radiolysis and to give a full span of liquid level readings to assure emptying or filling of the casks at specified levels.

D. Tests

The following results were determined with one of the casks to assure its safe use.

1. Heating tests were made on one of the casks to determine the actual heat transfer characteristics of the casks. The results of the tests are given in Figures 4 and 5. The results show that without auxiliary cooling, and at a heat input estimated as equivalent to Purex waste, the cask contents require about 16 hours to heat up from 125°F to 200°F.
2. Calibrations were made of the cask volumes using a capacitance probe and known incremental volumes of water. The results of the tests showed the cask cannot be overfilled and the normal shipping volume of waste should be 320 gallons. (The liquid level when filled with 323 gallons is two inches below the vacuum dip leg.) Similar calibrations were run on both casks.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

FIGURE 5

TIME REQUIRED FOR CASK CONTENTS TO HEAT
FROM 125°F TO 200°F WITH NO COOLING

FIGURE 4

INITIAL HEATING RATES FOR

UNCOOLED 400 GALLON CASK

END

DATE
FILMED

6 / 22 / 92