**Pacific Northwest Laboratory
Annual Report for 1991 to the
DOE Office of Energy Research**

Part 2: Environmental Sciences

Staff Members
of Pacific Northwest Laboratory

February 1992

Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Richland, Washington 99352

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED *EP*

Preface

This 1991 Annual Report from Pacific Northwest Laboratory (PNL) to the U.S. Department of Energy (DOE) describes research in environment and health conducted during fiscal year 1991. This year the report consists of four parts, each in a separate volume.

The four parts of the report are oriented to particular segments of the PNL program, describing research performed for the DOE Office of Health and Environmental Research in the Office of Energy Research. In some instances, the volumes report on research funded by other DOE components or by other governmental entities under interagency agreements. Each part consists of project reports authored by scientists from several PNL research departments, reflecting the multidisciplinary nature of the research effort.

The parts of the 1991 Annual Report are:

Part 1: Biomedical Sciences

Program Manager: J. F. Park

J. F. Park, Report Coordinator
S. A. Kreml, Editor

Part 2: Environmental Sciences

Program Manager: R. E. Wildung

D. A. Perez, Editor

Part 3: Atmospheric Sciences

Program Manager: W. R. Barchet

L. K. Grove, Editor

Part 4: Physical Sciences

Program Manager: L. H. Toburen

L. H. Toburen, Report Coordinator
R. C. Pedersen, Editor

Activities of the scientists whose work is described in this annual report are broader in scope than the articles indicate. PNL staff have responded to numerous requests from DOE during the year for planning, for service on various task groups, and for special assistance.

Credit for this annual report goes to the many scientists who performed the research and wrote the individual project reports, to the program managers who directed the research and coordinated the technical progress reports, to the editors who edited the individual project reports and assembled the four parts, and to Ray Baalman, editor in chief, who directed the total effort.

T. S. Tenforde
Health and Environmental Research Program

Previous reports in this series:

Annual Report for:

1951	HW-25021, HW-25709
1952	HW-27814, HW-28636
1953	HW-30437, HW-30464
1954	HW-30306, HW-33128, HW-35905, HW-35917
1955	HW-39558, HW-41315, HW-41500
1956	HW-47500
1957	HW-53500
1958	HW-59500
1959	HW-63824, HW-65500
1960	HW-69500, HW-70050
1961	HW-72500, HW-73337
1962	HW-76000, HW-77609
1963	HW-80500, HW-81746
1964	BNWL-122
1965	BNWL-280, BNWL 235, Vol. 1-4; BNWL-361
1966	BNWL-480, Vol. 1; BNWL-481, Vol. 2, Pt. 1-4
1967	BNWL-714, Vol. 1; BNWL-715, Vol. 2, Pt. 1-4
1968	BNWL-1050, Vol. 1, Pt. 1-2; BNWL-1051, Vol. 2, Pt. 1-3
1969	BNWL-1306, Vol. 1, Pt. 1-2; BNWL-1307, Vol. 2, Pt. 1-3
1970	BNWL-1550, Vol. 1, Pt. 1-2; BNWL-1551, Vol. 2, Pt. 1-2
1971	BNWL-1650, Vol. 1, Pt. 1-2; BNWL-1651, Vol. 2, Pt. 1-2
1972	BNWL-1750, Vol. 1, Pt. 1-2; BNWL-1751, Vol. 2, Pt. 1-2
1973	BNWL-1850, Pt. 1-4
1974	BNWL-1950, Pt. 1-4
1975	BNWL-2000, Pt. 1-4
1976	BNWL-2100, Pt. 1-5
1977	PNL-2500, Pt. 1-5
1978	PNL-2850, Pt. 1-5
1979	PNL-3300, Pt. 1-5
1980	PNL-3700, Pt. 1-5
1981	PNL-4100, Pt. 1-5
1982	PNL-4600, Pt. 1-5
1983	PNL-5000, Pt. 1-5
1984	PNL-5500, Pt. 1-5
1985	PNL-5750, Pt. 1-5
1986	PNL-6100, Pt. 1-5
1987	PNL-6500, Pt. 1-5
1988	PNL-6800, Pt. 1-5
1989	PNL-7200, Pt. 1-5
1990	PNL-7600, Pt. 1-5

Foreword

This report summarizes progress in environmental sciences research conducted by Pacific Northwest Laboratory (PNL) for the U.S. Department of Energy's (DOE) Office of Health and Environmental Research in FY 1991. Research is directed toward increasing the knowledge needed to guide government policy and technology development for two of the world's most important environmental problems: environmental restoration and global change. The report is organized by major research areas contributing to resolution of these problems. In addition, outstanding contributions are being made in fundamental research in individual disciplines encompassed by these areas. These, in turn, are contributing directly to national scientific goals such as the new Presidential Initiative in Biotechnology. Additional sections of the report summarize laboratory-directed research and development, educational institution interactions, technology transfer, and publications and presentations.

Each project in the PNL research program is a component in an integrated laboratory, intermediate-scale, and field approach designed to examine multiple phenomena at increasing levels of complexity. This approach, in conjunction with the strong emphasis on multidisciplinary teaming, provides system-level insights into critical environmental processes. Examples include definition of the role of fundamental geochemical and physical phenomena on the diversity and function of microorganisms in the deep subsurface, and determination of the controls on nutrient, water, and energy dynamics in arid ecosystems and their response to stress at the landscape scale. University liaisons continue to be expanded to include more than 30 universities nationwide. These relationships markedly strengthen the research and help train the scientists needed to address long-term environmental problems.

The Environmental Science Research Center has enabled PNL to extend fundamental knowledge of subsurface science to develop emerging new concepts for use in natural systems and in environmental restoration of DOE sites. New PNL investments have been made in developing advanced concepts for addressing chemical desorption kinetics, enzyme transformations and redesign, the role of heterogeneity in contaminant transport, and modeling of fundamental ecological processes. This report reflects the results of past investments and the growth of PNL's technical strengths, strong multidisciplinary interactions, and rapidly developing facilities for simulating and evaluating environmental phenomena.

Raymond E. Wildung
Program Manager
Environmental Sciences

Contents

Preface	iii
Foreword	v
Subsurface Science	1
Subsurface Chemistry of Organic Ligand-Radionuclide Mixtures, <i>J. M. Zachara, C. C. Ainsworth, J. P. McKinley, E. M. Murphy, J. C. Westall, and P.S.C. Rao</i>	1
Chemical Desorption, Dissolution, and Partitioning, <i>C. C. Ainsworth</i>	13
Chemistry/Microbiology Controlling Chelated Radionuclide Transport, <i>D. C. Girvin and H. Bolton, Jr.</i>	18
Subsurface Microbial Processes, <i>J. K. Fredrickson, F. J. Brockman, and T. O. Stevens</i>	28
Microbial Sequestration and Bioaccumulation of Radionuclides and Metals, <i>H. Bolton, Jr.</i>	42
Improving the Biodegradative Capacity of Subsurface Bacteria, <i>F. J. Brockman and M. F. Romine</i>	46
Hydrogeologic and Geochemical Controls on Microorganisms in Subsurface Formations, <i>P. E. Long, S. A. Rawson, E. M. Murphy, and B. N. Bjornstad</i>	49
Pore Water Chemistry and Its Relationship to Microbial Distribution, <i>J. P. McKinley</i>	71
Intermediate-Scale Subsurface Transport of Co-Contaminants, <i>G. P. Streile, J. E. Jzecsody, B. D. Wood, and F. J. Brockman</i>	75
Manipulation of Natural Subsurface Processes: Field Research and Validation, <i>J. S. Fruchter, J. M. Zachara, J. K. Fredrickson, C. R. Cole, J. E. Amonette, T. O. Stevens, D. J. Holford, L. E. Eary, G. D. Black, and V. R. Vermeul</i>	88
Modeling Radon Transport in Soils, <i>D. J. Holford, P. C. Owczarski, G. W. Gee, and H. D. Freeman</i>	106
Subsurface Organic Fluid Flow Research, <i>C. S. Simmons, R. J. Lenhard, J. W. Cary, and J. F. McBride</i>	111
Terrestrial Science	117
Nitrogen Dynamics of Arid Ecosystems, <i>H. Bolton, Jr., and S. O. Link</i>	117
The Effects of Nitrogen and Water on <i>Bromus tectorum</i> Biomass in the Field, <i>S. O. Link, J. L. Downs, M. E. Thiede, and H. Bolton, Jr.</i>	122

Natural Runoff in the Shrub-Steppe: Implications for Groundwater Recharge, <i>L. L. Cadwell, G. W. Gee, and V. D. Parks</i>	127
Landscape Ecological Studies: Net Radiation and the Relationship Among Surface Temperature, Normalized Difference Vegetation Index, and Elevation on the Arid Lands Ecology Reserve, <i>S. O. Link, G. M. Petrie, L. G. McWethy, R. R. Kirkham, and L. E. Rogers</i>	128
Landscape Ecological Studies: Validation of the Supervised Land-Cover/Vegetation Classification for the Arid Lands Ecology Reserve, <i>J. L. Downs, L. G. McWethy, S. O. Link, D. E. Gibbons, and G. M. Petrie</i>	133
Designs for Environmental Field Studies, <i>J. M. Thomas, L. L. Eberhardt, M. A. Simmons, and V. I. Cullinan</i>	136
National Environmental Research Park Intersite Data Synthesis, <i>W. H. Rickard</i>	139
Laboratory-Directed Research and Development	143
Chemical Desorption/Dissolution Kinetics, <i>C. C. Ainsworth</i>	143
Enzymatic Transformation of Inorganic Chemicals, <i>Y. A. Gorby and H. Bolton, Jr.</i>	143
Biodegradative Enzyme Design, <i>R. L. Ornstein</i>	145
DNA Sequence and Fragment Analysis, <i>R. J. Douthart</i>	148
Hollaender Fellowship in Applied Mathematics and Contaminant Transport Modeling, <i>C. R. Cole and T. R. Ginn</i>	149
Educational Outreach	151
Publications	157
Presentations	165
Author Index	171

Subsurface Science

The contamination of subsurface environments by mixed waste chemicals is a major concern on DOE lands and many waste sites nationally. The scientific community is now being asked to 1) predict the rates at which these contaminants migrate through subsurface environments to estimate health risks and to assist in cleanup activities and 2) develop more effective in situ remediation techniques to degrade, immobilize, or mobilize contaminants. Transport predictions and contaminant remediation are especially difficult on DOE lands where the codisposal of radionuclides, metal ions, salts, organic solutes, and organic liquids to the ground has created unique environmental questions.

These basic scientific studies address the fundamental chemical, microbiologic, and hydrologic processes that control the behavior of mixed waste contaminants in subsurface environments. Focus is on DOE-site contaminants, but broader scientific benefits are being realized that will assist in predicting the subsurface behavior of organic/inorganic mixtures and organic liquids generally under different geochemical and hydrogeologic conditions. Subsurface chemistry studies are investigating multisolute sorption phenomena, cosolvent effects and complexation, and the relationship between surface sorption and microbial degradation on subsoil and aquifer materials. Microbiological research is investigating the nature of microorganisms in different deep hydrogeologic environments; the physical, geochemical, and hydrologic factors governing the distribution and function of these microorganisms; and their ability to alter radionuclide chemistry and degrade complexing ligands. Hydrologic investigations are defining the flow physics of organic-liquid/water multiphase mixtures in saturated and unsaturated porous media, and systematically examining the effects of subsurface heterogeneities on transport.

Multidisciplinary transport studies are being performed in columns and in a unique Subsurface Environmental Research Facility where the combined effects of microbiology, chemistry, and hydrology on chemical transport can be assessed at a scale that is intermediate between the laboratory and the field. Planning has been completed on a manipulative experimental site at Hanford that can be used to selectively validate hypotheses and concepts. This experimental design will now be transferred to the DOE Office of Environmental Restoration and Waste Management. In other field research, planning is under way to complete the final phase of the Hanford deep microbiological exploration effort. This effort will address the role of electron acceptors and donors in governing the presence and function of microorganisms in deep saturated zones. The overall research is playing a key role in the development of improved contaminant migration models and effective new strategies to reduce migration rates and remove contaminants from groundwater.

Subsurface Chemistry of Organic Ligand-Radionuclide Mixtures

J. M. Zachara, C. C. Ainsworth, J. P. McKinley, E. M. Murphy, J. C. Westall (Oregon State University), and P.S.C. Rao (University of Florida)

Geochemical interactions between inorganic contaminants and codisposed organic chemicals, as well as natural organic substances, influence the subsurface mobility of radionuclide and metal contaminants. These interactions, which include aqueous complexation, cosolvation, and solid-phase cosorption, have led to cases of enhanced

subsurface mobility that exceed predictions based on current knowledge. Therefore, the nature of organic-radionuclide interactions and their effects on other geochemical processes must be better understood to enable more accurate predictions of contaminant mobility and to assess new ways that organic substances may be used for environmental restoration.

The goal of this research project is to investigate the thermodynamics and kinetics of geochemical reactions that occur between organic substances and radionuclides/metal ions on mineral surfaces

and to clarify the chemical and microbiologic factors controlling these reactions in multimineral subsurface material. Such geochemical reactions control the aqueous concentrations, the distribution between aqueous and solid phases, and consequently the transport velocities of radionuclides in groundwaters. The project focuses on chemical mixtures containing Co, U, humic substances, and various organic acids combined in binary mixtures and their interaction via adsorption reactions (i.e., ion exchange, surface complexation) with subsurface mineral material from DOE sites. The importance of these specific chemical mixtures has been identified through a thorough review of contaminant inventories at DOE waste sites (Zachara and Riley 1991).

The project is investigating geochemical reactivity at the microscopic scale, with an overall emphasis on surface-chemical reactions at the solid-liquid interface, their influence on the rates of microbiologic reactions, and their manifestation during contaminant transport through porous media. Three major research areas are being pursued during an approximately 3-year period: 1) influence of mineral-bound humic substances and organic acid ligands (propionate, oxalate, citrate) on the multicomponent sorption chemistry of Co, U, and Am on subsurface material; 2) influence of adsorption reactions on the microbiological degradation rates of organic acid-radionuclide complexes; and 3) microaquifer transport experiments of organically bound radionuclides through heterogeneous porous media. Surface-chemical and geochemical models are used extensively in the research as a basis for identifying dominant surface reactions and complexes; incorporating the complex effects of pH, ionic strength, and competing ions; and predicting the contributions of adsorption reactions in multiprocess experiments involving microbiology and water flow.

In FY 1991, resources were directed toward research areas 1 and 2 above, and progress is summarized in the following sections. This research summary is not intended to be comprehensive.

Influence of Mineral-Bound Humic Substances on Co Sorption by Subsurface Material

Sorption is a complex multimechanistic process occurring between aqueous species and solid surfaces. In subsurface environments, sorption

exerts an important control on the migration velocities of radionuclides and is influenced by a host of geochemical variables, including solution pH and ion composition of the groundwater, and mineralogic and surface properties of the porous media. At present, scientific understanding of sorption processes of metal ions and radionuclides in heterogeneous mineral material is inadequate to allow accurate predictions of sorption behavior on subsurface materials. Humic substances, present as a component of the dissolved organic carbon in groundwater, are believed to coat mineral surfaces in subsurface environments and impart complex surface and sorption properties to subsurface solids in ways that are not well understood.

In the previous year, we described initial studies designed to investigate the sorption behavior of humic coatings for metal ions. Past research has shown that humic substances can augment metal ion sorption on individual Al and Fe oxides, but comparable data for mineralogically complex subsurface materials are nonexistent. Co^{2+} was used to probe such phenomena because it is an important contaminant on DOE sites and, as ^{60}Co , has exhibited cases of enhanced subsurface mobility as a result of complexation by organic ligands. Two model humic substances from the International Humic Substances Society, the leonardite humic acid (LHA) and the peat humic acid (PHA), were used as coating materials. The terrestrial origin of these reference humic acids makes them valid surrogates for subsurface organic materials.

Research in FY 1990 demonstrated that humic substances can adsorb to subsurface mineral material containing kaolinite, Fe oxide, and Al oxides, enhancing the material's sorption capacity for Co. The humic substances appeared to augment Co sorption regardless of their location of isolation (i.e., LHA or PHA) or the nature of the inorganic electrolyte (i.e., Na or Ca) (Figure 1). In FY 1990, we proposed a series of surface and solution reactions between inorganic and organic ligands (Figure 2) that we speculated were controlling Co sorption on the uncoated mineral material and the humate-coated solid. Research in FY 1991 has continued to investigate the reactivity of humate coating and has focused on quantifying the contributions of specific reactions identified in Figure 2.

FIGURE 1. Fractional Sorption of Co^{2+} on the Subsurface Isolate Without and With the Sorbed Leonardite Humic Acid (LHA) and Peat Humic Acid (PHA). Calcium electrolyte and high Na concentrations (0.1 M) suppress ion exchange. Both humic substances increase Co sorption.

FIGURE 2. Surface and Solution Reactions Effecting Co Sorption on a Humate-Coated Subsurface Mineral Isolate

Attention has been directed toward understanding/modeling the sorption behavior of the uncoated subsurface material and the dissolved humic substance as a basis for understanding the complex combined system where humic acids partially coat the mineral surfaces and compete with inorganic surface complexation sites. The experimental and modeling steps being undertaken to understand the humate coating are to

1. develop a modeling approach to describe effects of pH and electrolyte concentration on Co sorption by the untreated soil material
2. establish the acidity of ligand sites (L^-) on the humic substance and their affinity for electrolyte cations by acid-base titration at different ionic strengths (I)
3. determine Co complexation constants for the humic substance over a range in pH and I and reconcile with the acid-base behavior of the humic substance at different ionic strengths
4. quantify the consumption of inorganic surface sites and organic ligand sites during humic substance sorption by acid-base titration as a basis for modeling the combined system.

The remaining discussion in this section will provide examples of research activities for steps 1, 2, and 3 above.

A chemical-equilibrium surface complexation model was used to estimate the importance of reactions 1 through 4 (see Figure 2) in the untreated soil material (Figure 3). This model forms the basis for later incorporation of reactions describing metal complexation by the sorbed humic substance. The present calculations were performed with the code FITEQL (Westall 1982a, 1982b) using a nonelectrostatic adaptation of the model described by Schindler et al. (1987). Sorption constants (K_{a1} , K_{a2} , and K_{Co}) for FeOH and AlOH sites were derived from nonelectrostatic surface complexation modeling of acid-base titration data and Co sorption data on Al-goethite and kaolinite. Site concentrations were obtained from ^{22}Na isotopic exchange measurements and acid-base titration. Ion exchange constants for reaction 1 (i.e., CoX_2 , Figure 2) were determined by curve fitting to Co sorption data over a range in I and pH

on the subsurface material that had been stripped of Fe oxides with a dithionite-citrate-bicarbonate (DCB) buffer.

The trend in sorption with pH was calculated to result from three independent surface reactions that competed with one another for Co (see Figure 3). The increased adsorption between pH 5 and 7 at $I = 0.01$ was consistent with the presence of an ion exchange complex (CoX_2 , reaction 1). This complex was calculated to decrease 1) at higher pH because of competition with stronger surface coordination complexes (AlOCo , FeOCo) and 2) at higher ionic strength because of competition of Na for weakly binding X^- sites. These calculations, when compared with experimental data in Figure 1, indicate that the humic substance enhances Co sorption regardless of whether ion exchange or surface complexation to Al and Fe oxide sites is the dominant inorganic sorption reaction. In FY 1992, this multisite surface reaction model will be 1) augmented with mass action equations describing the geochemical reactivity of the humic substance and 2) used to predict the extent of Co sorption enhancement caused by the humic substance. These mass action equations for the humic substance will be extracted from data shown in Figures 4 and 5, as discussed below.

Information on the aqueous complexation of Co by the LHA (as described generally by reaction 7 in Figure 2) was sought to determine whether this organic phase had the potential to augment Co sorption when mineral bound. The extent of complexation of Co by dissolved LHA was a function of both Na concentration (ionic strength) and pH (see Figure 4). Co complexation increased with pH in response to the ionization of the LHA ($\text{HL} = L^- + \text{H}^+$) and possibly to other factors including metal ion hydrolysis. Sodium apparently influenced Co binding by competing for ionized LHA sites (i.e., $L^- + \text{Na}^+ = \text{NaL}$) and possibly by effecting the conformation of the LHA via electrostatic effects. An increase of one order of magnitude in Na caused a uniform decrease in the Co/LHA distribution coefficient (K_d) of 0.5 log unit (see Figure 4), suggesting 1:1 mass action replacement of Co^{2+} by Na^+ on a charge basis. The magnitude of Co complexation by the dissolved LHA, as measured by K_d s of 10 to 100 L g^{-1} (see Figure 4), was sufficiently high to

FIGURE 3. Nonelectrostatic Surface Complexation Modeling of Co Sorption on the Uncoated Subsurface Mineral Isolates at a) I (ionic strength) = 0.01 and b) I = 0.1. Symbols are data points; textured lines represent contributions of different surface species.

explain the enhancement in Co sorption that occurs when the LHA is surface bound (i.e., Figure 1).

Acid-base titrations in a CO_2 -free atmosphere were performed on the LHA in solutions of different ionic strengths (see Figure 5) to enable calculation of thermodynamic complexation constants for Co

with ionized carboxylate and phenolate sites (L^-) on the humic substance. The titrations allow calculation of the free ligand concentration (i.e., L^-) at each pH, data from which acidity constants (K_{HL}) and electrolyte binding constants (K_{NaL}) for the LHA can be extracted via chemical modeling. The lines in Figure 5 represent the best-fit prediction of a three-site model (HL_1 , HL_2 , HL_3)

FIGURE 4. Aqueous-Phase Complexation of Co^{2+} by the LHA Measured by Equilibrium Dialysis: a) Percent Co^{2+} Complexed with $10^{-6} \text{ M } \text{Co}^{2+}$ and 10 mg C L^{-1} LHA and b) Co^{2+} /LHA Distribution Coefficient

undergoing acid dissociation and electrolyte association according to the following reactions:

where $n = 1, 2$, or 3 . Six constants (K_{HL1} , K_{HL2} , K_{HL3} , K_{NaL1} , K_{NaL2} , and K_{NaL3}) and three site concentrations ($\text{L}_{1-\text{TOT}}$, $\text{L}_{2-\text{TOT}}$, and $\text{L}_{3-\text{TOT}}$, where $\text{TOT} = \text{L}^- + \text{HL} + \text{NaL}$) describe the titration data.

Chemical modeling calculations in FY 1992 will utilize the data in Figure 4, along with K_{HLn} , K_{NaLn} , and $\text{L}_{n-\text{TOT}}$ for the three conceptual ligand sites in Figure 5, to calculate complexation constants for Co binding:

FIGURE 5. Acid-Base Titration of the LHA at Ionic Strengths of 0.001, 0.01, and 0.1. Lines represent model calculation with a three-site, pK_a spectrum model. Shifts with ionic strength occur because of Na^+ competition with H^+ for ionized carboxylate sites.

where $n = 1, 2$, or 3 and K is the equilibrium complexation constant for the respective ligand moiety. Acid-base titration studies will be performed on the humate-coated solids, and the acidity, electrolyte association, and Co complexation constants for the LHA will be integrated into the model used in Figure 3. The integrated model will be used to assist in interpreting and understanding the complex sorption behavior of the humate-coated subsurface material.

Effect of Organic Acid Ligands on Uranium Sorption by Subsurface Clays

Uranium is a ubiquitous subsurface contaminant at DOE sites. Although the aqueous chemistry of uranium at earth-surface conditions has been a subject of research for several decades, little information has been reported on the surface chemical interaction of dissolved uranium with subsurface clay material or on mixtures of these phases with organic complexing agents. Organic complexants are found naturally in the subsurface (e.g., humic acid) and have been used extensively at DOE facilities during decontamination activities, in the form of compounds such as citric acid. A useful understanding of the subsurface chemical

behavior of uranium requires experimental and field investigation of its interaction with monomineralic and multiminerallc solids and with complexing agents in the presence of these solids.

Uranium in oxygen-rich environments is dissolved and transported in the U(VI) form as uranyl ion, UO_2^{2+} (Allard et al. 1980). Uranyl forms aqueous hydroxide complexes under slightly acidic to alkaline conditions; where dissolved carbonate is available, a carbonate complex is formed (Baes and Mesmer 1976). An investigation of uranyl adsorption to ferric oxyhydroxides in the presence of dissolved carbonate (Hsi and Langmuir 1985) resulted in a successful model fit of experimental data using a surface complexation-site binding model. The uranyl complexes applied in that study were UO_2^{2+} , UO_2OH^+ , and $(\text{UO}_2)_3(\text{OH})^{5+}$. A recent review of published data on uranium experiments (Grenthe et al. 1990), however, suggests that the actual dissolved species over the concentration and pH range studied are different from those modeled, casting doubt on the conclusions of this earlier study.

Experimental investigations within this task in FY 1991 were directed toward geochemical interaction studies of the uranyl ion with clay minerals (phyllosilicates) representative of those existing at groundwater zones at DOE sites, and the interpretation of these data in light of new information on the aqueous speciation of uranium. Phyllosilicates are a high-surface-area, chemically reactive phase common to soils and geologic materials, and must be investigated as part of a comprehensive effort to understand and model the behavior of uranium in the subsurface. Because of the complexity of the geochemistry involved, these experiments were performed in the absence of organic acids. Organic ligands will be introduced in FY 1992 research.

The research was conducted with well-characterized clay-mineral separates from subsurface materials at DOE sites (the Kenoma, Cape Fear, and Ringold formations) and a specimen smectite purchased from the Clay Minerals Society (SWy-1). Sediments containing these clays were treated as follows to enable isolation of a $<2\text{-}\mu\text{m}$ fraction. Fractions smaller than $2\text{ }\mu\text{m}$ were separated gravimetrically in aqueous suspensions, sodium saturated and dialyzed in deionized water,

and freeze-dried. Prior to experimentation, clays were resuspended and treated with DCB buffer and hydrogen peroxide to remove amorphous ferric hydroxides and organic contaminants. These suspensions were sparged with pure oxygen for 24 hours following extraction to reoxidize structural iron that may have been reduced by DCB treatment. Physical characterization, which is not complete currently, included mineral identification by x-ray diffraction analysis, cation exchange capacity (CEC), N_2 surface area, and total composition.

The sorption experiments were performed in an inert-atmosphere glovebox to eliminate carbonate complexation effects. Either NaClO_4 or $\text{Ca}(\text{ClO}_4)_2$ was employed as the electrolyte. Clay suspensions (≈ 1 meq of charge L^{-1} suspension) were held at pH 4.5 for 16 hours, then spiked with uranyl nitrate to a concentration of 2 mg L^{-1} . Acidity was adjusted by addition of sodium hydroxide over the pH range of 4.5 to 9.0. Samples at each pH were collected and sealed in inert atmosphere and shaken overnight. Suspensions were centrifuged and an aliquot removed for uranium analysis by laser fluorimetry; pH was determined from the remaining supernatant.

Mineralogy, specific surface area, and cation exchange capacity of the phyllosilicate sorbents are presented in Table 1. The Kenoma and Ringold (R-9) are smectite clays; the Cape Fear consists of approximately 60% kaolinite and 40% smectite. Also indicated in the table is whether cation exchange capacity is pH dependent, if known. The pH-dependent CEC has not yet been measured for clays R-9 and Cape Fear; however,

TABLE 1. Chemical and Physical Properties of the Clay Minerals

Name	Mineralogy	Surface Area ($\text{m}^2\text{ g}^{-1}$)	CEC ^(a) (meq g^{-1} at pH 6)	pH Dependent
Ringold (R-9)	Smectite	112	0.59	Unknown
Kenoma	Smectite	99	0.45	Yes
Cape Fear	60% Kaolinite/ 40% Smectite	-- ^(b)	--	--

(a) CEC = cation exchange capacity.

(b) Data not available.

the Cape Fear smectite may be assumed to have a pH dependence by reference to other kaolinitic samples.

Uranium sorption on the Kenoma (a clay isolate from a subsoil near Fernald) shows a strong dependence on ionic strength (Figure 6). The results are opposite those expected for simple competitive sorption between U and the electrolyte cation. As shown in Figure 6, increasing the electrolyte concentration enhances U sorption. This behavior was unanticipated and has not been previously reported. It may possibly be explained by the ionic strength dependence of the uranyl ion hydrolysis. Preliminary investigation of this dependence by reference to Grenthe et al. (1990) indicates that the hydrolysis constant for the reaction:

varies with ionic strength. For an ionic strength of 0.0 to 0.1, the log formation constants of UO_2OH^+ and $\text{UO}_2(\text{OH})_2^{2+}$ have been reported to vary over the ranges -5.9 to -6.1 and -5.6 to -5.8, respectively. These two species are believed to be important below pH of about 5; above pH 5.5, the uncharged species $\text{UO}_2(\text{OH})_2$ is proposed to

predominate (Grenthe et al. 1990). The shift toward increased adsorption at higher ionic strength may thus be explained by a shift toward hydrolyzed species with higher charge at higher ionic strength or possibly by enhanced formation of the uranyl dimer.

Uranium sorption on R-9 (a subsurface clay isolate from the Ringold Formation at Hanford) (Figure 7) showed both similarities to and differences from the Kenoma clay. At relatively low pH, sorption was slightly depressed with increasing ionic strength. At higher pH, sorption increased with increasing ionic strength, but to a lesser extent than for the Kenoma. Also, sorption at lower ionic strength was less steep than at higher ionic strength, and 100% sorption was not achieved. These apparent contrasts in sorption behavior are believed to reflect proportional differences in the concentration of basal surface fixed-charge sites and variable-charge sites on the crystallite edges in the smectitic clay isolates. R-9 is hypothesized to have smaller edge surface area and more fixed charge than does the Kenoma. As a result, edge complexation of U in the R-9 clay is less important and sorption is less respondent to changes in pH.

A comparison of U sorption on the Kenoma, the Cape Fear (from the Cape Fear Formation

FIGURE 6. Fractional Sorption of UO_2^{2+} on the Kenoma Clay Isolate with Ca^{2+} Electrolyte

FIGURE 7. Fractional Sorption of UO_2^{2+} on the Ringold (R-9) Clay Isolate with Ca^{2+} Electrolyte

underlying the Savannah River Site), and the R-9 clays (at $I = 0.01$) is presented in Figure 8. In the absence of aqueous carbonate complexation, UO_2^{2+} is strongly sorbed by all the clays. U sorption on the Cape Fear and Kenoma clays is virtually identical in spite of their differences in geologic origin, reinforcing the commonality in the sorption process/reaction. The sorption edge for R-9 exhibits a slope comparable to the others with respect to pH, implying a similar surface reaction mechanism, but the edge is positioned to the right (i.e., at higher pH) for reasons that are not yet well understood.

Interpretations and hypotheses to date are preliminary and will be refined as additional research is completed. The interaction of the uranyl ion with natural clays is complex, and is hypothesized to be a function of concentrations of fixed- and variable-charge sites on the clays, uranyl aqueous speciation and its ionic strength dependence, and the surface-reactive species of uranyl ion (e.g., uranyl ion versus uranyl dimer). Increasing ionic strength is hypothesized to increase adsorption by increasing the proportion of higher-charged uranyl species at a given pH. The surface speciation of uranyl ion may be an important part of the macroscopic expression of sorption as well because sorption of dimeric and monomeric species will have different experimental effects.

FIGURE 8. Comparative Sorption of UO_2^{2+} on Subsurface Layer Silicates from DOE Sites

Research in FY 1992 will yield a better understanding of uranyl speciation over the range of relevant conditions (uranium concentration, ionic strength, acidity). This will be accomplished by literature search or by direct measurement, if necessary. Physical and chemical characterization of clay minerals will be completed, particularly with regard to the concentrations of fixed-charge and variable-charge sites. Additional adsorption edge measurements will be undertaken, when required, to more precisely define the behavior of the uranyl ion under varying conditions of ionic strength, pH, and surface site concentrations and to determine the effects of the organic acid complexants propionate, oxalate, and citrate on U sorption. Cooperative arrangements for collaborative experimentation have been made with Los Alamos National Laboratory to directly determine the chemical nature of surface-bound U in the clay-sorbent suspensions using various surface-sensitive spectroscopies. Such direct chemical evidence of surface speciation can greatly assist in the formulation of more accurate geochemical models of the U sorption process.

Effect of Sorption on the Microbiological Degradation of Aromatic Acids

The sorption of organic compounds on subsurface materials influences the transport velocities of such compounds. Sorption may also influence the persistence of organic contaminants that are microbiologically degraded. Sorption may decrease microbial degradation rates if the sorbed compounds are unavailable as a carbon source. Additionally, the mechanism of sorption (i.e., hydrophobic partitioning, cation exchange, or surface complexation) may influence the bioavailability of sorbed compounds and the rate-limiting degradation reaction. Degradation measurements made in the absence of subsurface materials also could significantly overestimate the actual degradation rates in the vadose and saturated zones.

Research has continued this year (FY 1991) to investigate how the sorption of organic aromatic acids [salicylic (2-hydroxybenzoic) acid, $\text{pK}_{a1} = 2.97$, $\text{pK}_{a2} = 13.40$; pyrocatechol (1,2-dihydroxybenzene), $\text{pK}_{a1} = 9.2$, $\text{pK}_{a2} = 13.0$; phthalic (1,2-benzenedicarboxylic) acid, $\text{pK}_{a1} = 2.8$, $\text{pK}_{a2} = 4.9$] controls their degradation rates in monocultural suspensions. Preliminary studies of

salicylic acid degradation in the presence and absence of alumina ($\gamma\text{-Al}_2\text{O}_3$) suggested that sorbed salicylate was protected from degradation, and that the desorption process is limiting the degradation rate of the substrate. Alumina has been employed as a sorbent in these experiments because it 1) is representative of a class of sorption sites (AlOH) that are ubiquitous in subsurface materials and 2) allows direct interrogation by luminescence spectroscopy.

The sorption of catechol, salicylate, and phthalate to $\gamma\text{-Al}_2\text{O}_3$ proceeds by a surface complexation reaction. The degree of sorption is controlled by pH, surface charge, sorbate aqueous speciation, and other aqueous- and solid-phase phenomena. The degradation of salicylate (at 10^{-6} M) by *Pseudomonas putida* (1901) is substantially altered by the presence of $\gamma\text{-Al}_2\text{O}_3$; degradation of the sorbed substrate is considerably slower (Figure 9). Salicylate mineralization studies with and without $\gamma\text{-Al}_2\text{O}_3$ and over a range in *P. putida* (1901) populations [10^7 to $10^{9.4}$ colony-forming units (CFU) mL^{-1}] demonstrated that 1) the salicylate mineralization rate in solution is dependent on the microbial population, 2) the mineralization rate of

salicylate in the presence of $\gamma\text{-Al}_2\text{O}_3$ is approximately five times slower than in the absence of sorbent, and 3) the mineralization rate of salicylate in the presence of $\gamma\text{-Al}_2\text{O}_3$ is independent of isolate population. Catechol degradation shows a similar response to microbial population, but degradation of the sorbed substrate is more rapid than that observed for salicylate.

Direct measurements of microbial uptake of salicylate and sorbed-phase desorption were accomplished using fluorescence spectroscopy. The rate of salicylate disappearance from solution as a result of microbial uptake was the same in the presence and absence of $\gamma\text{-Al}_2\text{O}_3$ (Figure 10a). However, in the presence of $\gamma\text{-Al}_2\text{O}_3$, the rate of salicylate disappearance decreased by more than an order of magnitude (about $10^{1.5}$) when the aqueous-phase salicylate was exhausted (see Figure 10a, later time periods). This latter phenomenon occurred because desorption was controlling the microbial uptake rate of salicylate. This conclusion was demonstrated by following the change in the salicylate wavelength (ν) at maximum intensity (Figure 10b). In aqueous solution, salicylate exhibited a ν_{max} at 410 nm, but in the sorbed state, ν_{max} was blue shifted by approximately 27 nm. As the aqueous-phase salicylate was exhausted, the ν_{max} decreased to the ν_{max} of the sorbed salicylate. These data demonstrated that 1) salicylate was at least partially protected from microbial attack in the sorbed state, 2) desorption was limiting degradation, and 3) desorption was limited by a surface-chemical-controlled reaction.

FIGURE 9. Variation in Salicylate Mineralization (^{14}C Evolution) as a Function of *Pseudomonas putida* (1901) Population and the Presence or Absence of $\gamma\text{-Al}_2\text{O}_3$ as a Function of Time

Different microbial isolates [*P. putida* (NMH102-2) and *P. cepacia* (ATCC-29424)] were used for phthalate degradation studies because *P. putida* (1901) could not utilize phthalate as a sole carbon source. Hence, comparability of the phthalate data with those for salicylate and catechol is limited. Phthalate mineralization by the above two organisms was very different from one another and unexpectedly different from that observed for the other two organic acids with *P. putida* (1901). The mineralization of phthalate by *P. putida* (NMH102-2) (as measured by $^{14}\text{CO}_2$ evolution studies) showed evidence of desorption rate

FIGURE 10. Variation in Salicylate Fluorescence Intensity (a) and Wavelength at Maximum Intensity (b) in the Presence and Absence of *Pseudomonas putida* (1901) and $\gamma\text{-Al}_2\text{O}_3$ as a Function of Time

imitations. The reduction in mineralization rate was not as great as would be expected based on the binding strength of phthalate to $\gamma\text{-Al}_2\text{O}_3$ or the results from the other organic acid studies (Figure 11a). Even more unexpected, however, was the fact that sorption to $\gamma\text{-Al}_2\text{O}_3$ did not greatly affect the utilization rate of phthalate by *P. cepacia* (ATCC-29424) (Figure 11b). These results suggested that 1) significant differences exist between microbial species and their ability to utilize sorbed compounds as substrate and 2) although both

phthalate degraders utilize identical pathways for phthalate metabolism, significant differences exist in their ability to scavenge substrate. Research is ongoing to identify the differences between these organisms.

In FY 1992, we will continue these sorption-degradation studies focusing on surface complexation reactions and bioavailability of the sorbed species. Research will be directed toward the aliphatic organic acids propionate, oxalate, and citrate when sorbed to 1) Fe and Al oxides as free ligands and 2) Fe and Al oxides and layer silicates as complexes with Co and U. Hypotheses relating organic-metal complex charge, sorption strength, and surface bonding environment to the microbial degradation rate will be evaluated.

Future Directions

Research in FY 1992 will continue to address the three topical areas discussed in this synopsis. The specific activities planned include 1) surface-chemical modeling of Co sorption to humate-coated mineral solids; 2) identification of U sorption reactions on subsurface clays and evaluation of the geochemical effects of the organic acid complexants; and 3) investigation of the effects of sorption on the microbial degradation of mono-, di-, and tricarboxylic acid ligands complexed to Co and U.

Additional efforts will commence in FY 1992 on a microaquifer experiment with Co involving geochemical and mineralogical heterogeneity in the porous media. Experiments will be performed in collaboration with other Subsurface Science Program projects at PNL. Our tentative schedule for the microaquifer experiment involves 1) a planning phase during the first third of the fiscal year to establish the objectives, hypotheses, and nominal conceptual design for the experiment; 2) a preparational period during the second third of the fiscal year to obtain background data on reaction and kinetics for the Co-organic mixture in one-dimensional column systems that simulate stream tubes in the two-dimensional flow cell; and 3) an initiation phase during the final third of the fiscal year to perform tracer experiments in the flow cell and to start the first reactive transport experiment with Co.

FIGURE 11. Variation in Phthalate Mineralization (^{14}C Evolution) as a Function of Microbial Isolate and the Presence or Absence of $\gamma\text{-Al}_2\text{O}_3$ as a Function of Time

References

- Allard, B., H. Kipatsi, and J. O. Liljezin. 1980. Expected Species of Uranium, Neptunium, and Plutonium in Neutral Aqueous Solutions. *Journal of Inorganic Nuclear Chemistry* 42:1015-1027.
- Baes, C. F., and R. E. Mesmer. 1976. *The Hydrolysis of Cations*. John Wiley and Sons, Inc., New York.
- Grenthe, I., J. Fuger, R. J. Lemire, A. B. Muller, C.N.T. Cregu, and H. Wanner. 1990. *Chemical Thermodynamics of Uranium, Final Draft for Peer Review*. Nuclear Energy Agency Organisation for Economic Co-operation and Development, Gif-Sur-Yvette, France.
- Hsi, C-K., and D. Langmuir. 1985. Adsorption of Uranyl onto Ferric Oxyhydroxides: Application of the Surface Complexation Site-Binding Model. *Geochimica et Cosmochimica Acta* 49:1931-1941.
- Schindler, P. W., P. Liechti, and J. C. Westall. 1987. "Adsorption of Copper, Cadmium, and Lead from Aqueous Solution to the Kaolinite/Water Interface." *Netherlands Journal of Agricultural Science* 35:219-230.
- Westall, J. C. 1982a. *FITEQL. A Computer Program for Determination of Equilibrium Constants from Experimental Data. Version 1.2*. Report 82-01, Department of Chemistry, Oregon State University, Corvallis, Oregon.
- Westall, J. C. 1982b. *FITEQL. A Computer Program for Determination of Equilibrium Constants from Experimental Data. Version 2.0*. Report 82-02, Department of Chemistry, Oregon State University, Corvallis, Oregon.
- Zachara, J. M., and R. G. Riley. 1991. *Nature of Chemical Contaminants on DOE Lands and Identification of Generic Chemical Mixtures for Basic Subsurface Science Research*. PNL-7791, prepared for the Office of Energy Research, U.S. Department of Energy, by Pacific Northwest Laboratory, Richland, Washington.

Chemical Desorption, Dissolution, and Partitioning

C. C. Ainsworth

Contributors

J. Zachara, D. Sparks (University of Delaware),
P. Grossl (University of Delaware), and J. Pilon
(University of Montana)

A variety of solid and liquid waste materials has been discharged to the ground at DOE production sites over a 50-year period. Unplanned releases and direct discharges have contaminated soils and groundwaters at many DOE sites. Pumping and treatment of groundwater seldom affect significantly the contaminants sorbed to the solid matrix, which can act as a source for future contaminant plumes and may involve a much larger quantity of contaminant than that observed in a plume. However, the interactions and reactions that control the mobilization of solid-phase contaminants are not well understood. Reactions that control the release of sorbed contaminants from subsurface materials (e.g., desorption, dissolution) must be understood to facilitate better predictions of contaminant mobility and to identify rational geochemical strategies to enhance contaminant mobilization and hasten restoration of waste sites.

Research in this project emphasizes desorption/dissolution of contaminants that associate with the solid matrix and, with time, become increasingly difficult to displace to the aqueous phase. Reversion of contaminants to less extractable forms is the result of at least four mechanisms that incorporate contaminants into or within many geologic and soil materials: 1) recrystallization, 2) lattice penetration, 3) crystal overgrowth, and 4) micropore diffusion. Experiments are being performed using 1) subsurface materials from contaminated and uncontaminated DOE sites, 2) natural mineral phases isolated from subsurface materials, and 3) reference mineral phases of known properties that control contaminant mobility. A combination of batch- and flow-type kinetic techniques is being employed to determine the rate-controlling reactions involved in contaminant desorption/dissolution; the influence of variables such as pH, ionic strength, and aqueous composition; the presence of co-contaminants modifying single-contaminant reactions; the residence time on

these rate-controlling reactions; and the ability of chemical additives (e.g., complexants, surfactants) or geochemical manipulation to influence the rate of mobilization and the partitioning of contaminants.

In FY 1991, PNL research on the desorption/dissolution of contaminants from selected solid phases concentrated on the effect of recrystallization of calcite and amorphous iron oxide on the binding and desorption of selected contaminants as a function of time. Important contaminants identified at a number of DOE sites are being investigated; these contaminants include Pb, Co, Cd, and U. In addition to these metals, Cu and Mn have been included as probes because they are electron paramagnetic resonance (EPR) active. This characteristic allows direct monitoring of Cu^{2+} and Mn^{2+} reactions with calcite and other solids in situ and in real time. The selection of the solid phases and the contaminants used in the initial experimentation was based on their relevance to a variety of DOE sites. This research synopsis presents the results to date of ongoing research directed at 1) the influence of calcite recrystallization on the sorption/desorption of Mn, Cd, Co, Cu, and Pb as a function of residence time and 2) the sorption/desorption of metals Co, Cd, and Pb from a recrystallizing amorphous iron oxide.

Effect of Calcite Recrystallization on the Sorption of Metals as a Function of Residence Time

In the environments surrounding DOE waste sites, in particular at the Hanford Site, sorption of aqueous divalent metal contaminants by calcite (CaCO_3) represents a potentially significant mineral phase for scavenging contaminant metals in calcareous surface, subsurface, and groundwater environments. Likewise, calcareous materials that in the past have scavenged contaminant metals could act as a source of groundwater contamination by the same metals.

Scavenging of divalent metal cations (Me^{2+}) by CaCO_3 is generally a surface-localized process. The sorption process to the calcite surface typically occurs via exchange with the surface Ca or by complexation to the carbonate groups bound in the hydrated layer. However, the sorption process varies for different sorbate metals and

is not necessarily straightforward. Zachara et al. (1991) found that 1) a series of divalent metals sorbed to calcite in the order $\text{Cd} > \text{Zn} \geq \text{Mn} > \text{Co} > \text{Ni}$; 2) desorption was correlated to the metal hydration energies (the lower the hydration energy, the less desorbable); 3) Cd and Mn behaved in a manner suggestive of a surface precipitate or solid solution; and 4) Zn, Co, and Ni appeared to remain on the calcite surface as a hydrated complex. The aforementioned study did not follow the sorption process beyond 48 hours; however, the magnitude of sorption for all the metals studied was sufficiently large, suggesting that calcite could act as an important sorbent. Although several studies have addressed metal-calcite interactions during relatively short periods, little is known about the sorption process beyond the initial rapid uptake of metals. This long-term process is hypothesized to occur at similar rates for all the metals tested and will follow the recrystallization rate of the calcite itself.

Laboratory metal-adsorption studies are being performed to quantify the influence of pH, metal ionic radii, and free energy of hydration ($\Delta^\circ G_{\text{hyd}}$) on long-term adsorption/desorption behavior on calcite. The pH adsorption edge experiments are designed to observe the sorption of Cd, Cu, Co, Mn, and Pb to calcite from solutions that are in equilibrium with CaCO_3 at a constant ionic strength (0.1 M) and over a range in pH (7.2 to 9.5); the sorption process is being followed over a 4-month period. In addition, adsorption/desorption isotherms are being created at three pH levels and at metal concentrations ranging from $10^{-8.5}$ to 10^{-4} M. These experiments are designed to test the hypotheses that 1) long-term sorption processes for a variety of metals are due to recrystallization of calcite and 2) the rate of long-term uptake by calcite is a function of calcite recrystallization rate and metal surface concentration.

The fractional sorption of divalent Mn, Co, and Cu to calcite as a function of pH (Figure 1) exhibits a pH dependency that differs markedly from that observed for metal sorption to iron oxides. Mn and Co fractional sorption increases with increasing pH. Cu sorption, on the other hand, increases with pH until about pH 8; the decreasing sorption beyond pH 8 observed for Cu is believed to be

FIGURE 1. Fractional Adsorption of Selected Divalent Metal Cations to Calcite as a Function of pH and Residence Time: a) Mn, b) Co, c) Cu

the result of the increasing dominance of the aqueous $\text{Cu}(\text{CO}_3)_2^{2-}$ species. In all cases, however, the fractional increase parallels the decrease in the aqueous Ca concentration.

Although the sorption behavior of the metals shown in Figure 1 could arise from precipitation of Me-carbonate, -hydroxide, or -hydroxycarbonate solid, the final concentrations (and, in fact, the initial concentrations of all metals except Pb) were well below that required for precipitation of the above type of solid phases. In addition, the pH edge data for all metals except Pb are totally consistent with a surface exchange reaction:

where only the uncomplexed divalent metal exchanges with surface Ca.

With time, the aqueous-phase concentrations of the three metals tend to decrease as a result of a slow sorption process that is believed to be related to the recrystallization of the calcite (see Figure 1). The increase in fractional sorption of the metals beyond 24 hours appears to be different for each of the metals; however, this difference is probably a reflection of the surface Me^{2+} concentration and its dependence on pH. For instance, the rate of Co and Mn disappearance from solution (after 24 hours) at a given pH may be modeled as a first-order process whose rate constants exhibit parallel behavior as a function of pH (Figure 2). The behavior of $\text{Cu}^{2+}(\text{aq})$ rate constants through 7 days, though preliminary, suggests a pH dependence similar to that of Mn and Co.

These preliminary results suggest that the initial sorption of Cu, Co, and Mn is 1) fast and related to the pH, 2) dependent on the aqueous metal speciation, and 3) dependent on the aqueous Ca concentration. After the initial sorption process has occurred, however, further uptake of Co, Mn, and Cu appears dependent on pH (and hence the surface concentration of the Me^{2+} species) and the rate of calcite recrystallization but independent of the metal itself. This latter point may be the result of the fact that all of the metals examined to date have similar ionic radii and therefore would

FIGURE 2. Pseudo-First-Order Rate Constant for the Disappearance of Mn(aq) and Co(aq) from a Calcite Suspension ($t > 24$ hours) as a Function of pH

not be limited by size constraints. Incorporation of Co and Mn into the calcite structure suggests that dehydration of the divalent metal cation is required as an initial step for metal incorporation. As discussed earlier, however, Co is suggested to interact with the calcite surface as a hydrated complex, whereas Mn interaction has been characterized as a dehydrated complex; both desorption hysteresis and the exchange constants ($^{\circ}K_{ex}$) for six metals have been related to their $\Delta^{\circ}G_{hyd}$ (Zachara et al. 1991). These data suggest that, in the present system, the rate of calcite recrystallization is the rate-limiting step for Co and Mn incorporation.

Research in FY 1992 will continue to explore long-term metal sorption on calcite and will emphasize three major activities: 1) spectroscopic determination of sorbed-metal chemical changes with time, 2) effect of calcite recrystallization rate on metal incorporation, and 3) desorption processes governing metal sorbate release from calcite. These activities will be focused on the specimen calcite, but will also utilize recently collected natural calcareous materials (contaminated and uncontaminated) from a DOE disposal site; contaminants present in this material include Cu, Co, Pb, and U.

The Effect of Residence Time on the Sorption of Co, Cd, and Pb to $\text{Fe}_2\text{O}_3 \cdot \text{H}_2\text{O}(\text{am})$

Oxides of Fe have long been recognized as major sorbents for a variety of contaminants. Adsorption of trace metals, inorganic anions, and organic compounds to the oxide and hydroxide surface/water interface has been well characterized. These studies have followed the adsorption/desorption process for short periods (hours) and rarely have observed nonsingularity between the adsorption and desorption processes. If longer aging times are used (i.e., sorbent and sorbate contact for prolonged periods), nonsingularity or hysteresis between the adsorption and desorption processes is often observed. Although the sorption of trace metals to oxide surfaces is well understood, there is little information on long-term residence time and its effect on 1) the fate of the trace metals, 2) the model calculations of sorption, and 3) the desorption/dissolution processes.

This study, therefore, was designed to investigate the effects on the desorption of three trace metals (Cd, Pb, and Co) when they are aged with amorphous iron oxide. Amorphous iron oxide is aged in the presence and absence of Cd, Co, and Pb for periods of up to 4 months. The effects of aging on the ability of the oxide to sorb trace metals as a function of pH, to desorb the same trace metals with no aging time, and to desorb metals aged with the iron oxide will be quantified by 1) determination of pH adsorption edges, 2) subsequent desorption of the sorbed metals, 3) desorption of aged metal/oxide suspensions, and 4) determination of oxide crystallinity changes with time.

Three separate aliquots of amorphous iron oxide were spiked at time = 0 with Cd, Pb, or Co. These aliquots are being aged with the metal contaminant for up to 4 months. Desorption of these metals as a function of pH is determined after aging for 2 weeks, 1 month, 2 months, and 4 months. The change in desorption reversibility (hysteresis) is quantified by comparison of metal fractional adsorption/desorption with pH, using material aged with and without the contaminant present. The results from these studies are expected to yield valuable information on the effects of contaminant residence time and the

desorption reversibility of the metals investigated and to expand our understanding of the processes controlling contaminant uptake as a function of natural recrystallization processes.

Fractional sorption of Cd, Pb, and Co to $\text{Fe}_2\text{O}_3 \cdot \text{H}_2\text{O}(\text{am})$ increased sharply from 0% to 100% as pH increased from 4 to 7. In addition, when the $\text{Fe}_2\text{O}_3 \cdot \text{H}_2\text{O}(\text{am})$ was aged, the pH adsorption edge did not shift appreciably and sorption was completely reversible. However, when the $\text{Fe}_2\text{O}_3 \cdot \text{H}_2\text{O}(\text{am})$ was aged in the presence of Co, Cd, or Pb, desorption exhibited substantial hysteresis that increased as aging time increased (Figure 3).

Desorption hysteresis as a function of residence time increased in the order of $\text{Co} > \text{Cd} > \text{Pb}$. After 60 days, the percentage of metal that was not desorbable at pH 3 was 55%, 20%, and 5% for Co, Cd, and Pb, respectively. Regardless of residence time, the hysteresis order remained constant and well correlated to the ionic radii of the three metals (1.20 Å, 0.98 Å, and 0.72 Å for Pb, Cd, and Co, respectively). Although the studies have been followed for only 60 days to date, the rate at which desorption hysteresis is increasing for the three metals appears to parallel the rate of change in the crystallinity of the $\text{Fe}_2\text{O}_3 \cdot \text{H}_2\text{O}(\text{am})$. Crystallinity in the present context is defined by the difference between Fe extractable by ammonium oxalate (AO) and Fe extractable by dithionate-citrate-bicarbonate (DCB), expressed as a percentage of total iron; DCB extraction dissolves all the Fe, while AO dissolves only "poorly crystalline material." Figure 4 shows the change in the Fe oxide crystallinity with time. In addition, x-ray diffractograms of the material with time would suggest that goethite ($\alpha\text{-FeOOH}$) content is increasing with time, although the intensity and peak widths of the diffractograms would suggest that the goethite being formed is a poorly crystalline material.

Goethite is formed from $\text{Fe}_2\text{O}_3 \cdot \text{H}_2\text{O}(\text{am})$ through a dissolution and recrystallization process that would lend itself to trace-metal incorporation. Although Al^{3+} most often is found to be isomorphically substituted for Fe (ionic radius is 0.64 Å)

FIGURE 3. Fractional Adsorption and Desorption of a) Co, b) Cd, and c) Pb as a Function of pH and Metal/Fe Oxide Aging

in the Fe oxide structure, other metals such as Ni, Mn, Co, Cr, Cu, and Zn are also commonly incorporated. Size of the substituting ion in relation to the matrix ion is often the primary factor governing substitution. Size differences between Co, Cd, and Pb and the Fe matrix ion are believed to be related to the desorption hysteresis observed with residence time for the metals used in this study,

FIGURE 4. increase in Crystallinity of the $\text{Fe}_2\text{O}_3 \cdot \text{H}_2\text{O}(\text{am})$ Suspension with Time; % Crystallinity = $(\text{Fe}_{(\text{DCB})} - \text{Fe}_{(\text{AO})}) / \text{Fe}_{(\text{DCB})}$

and to the trace metals being incorporated through crystallization of the goethite structure rather than through micropore diffusion.

The above Fe oxide study will be completed in FY 1992, and no additional studies investigating recrystallization of Fe oxides are contemplated. Future research within this project will be focused on the kinetic phenomena associated with metal desorption from surfaces. Our emphasis will be on 1) investigating desorption mechanisms from oxides and calcite using spectroscopic techniques, stirred flow reactors, and pressure-jump/relaxation techniques; 2) determining the desorption rate-limiting step under specific conditions; and 3) examining the effect of geochemical parameter variation on desorption rate. Contaminants will continue to be selected based on their relevance to DOE sites and the requirements necessary to test scientific hypotheses regarding contaminant desorption behavior.

Reference

Zachara, J. M., C. E. Cowan, and C. T. Resch. 1991. "Sorption of Divalent Metals on Calcite." *Geochimica et Cosmochimica Acta* 55:1549-1562.

Chemistry/Microbiology Controlling Chelated Radionuclide Transport

D. C. Girvin and H. Bolton, Jr.

Synthetic chelating agents such as ethylenediaminetetraacetic acid (EDTA), diethylenetriamine pentaacetic acid (DTPA), and nitrilotriacetic acid (NTA) form strong water-soluble complexes with a wide range of radionuclide and metal ions. They have, therefore, been used to decontaminate nuclear reactors and for various nuclear waste processing procedures. The codisposal of these synthetic chelating agents with radionuclides resulted in an increase in radionuclide transport in the subsurface environment. At specific DOE sites, enhanced ^{60}Co migration has been reported in soil and subsoil pore waters. The dissolved ^{60}Co in these pore waters exists predominantly as anionic species, with up to 90% of the cobalt associated with EDTA. This enhanced radionuclide transport at these mixed waste disposal sites is presumably caused by the reduced adsorption of the chelated radionuclide by subsurface materials relative to the adsorption of the unchelated radionuclide. Under these conditions, a decrease in chelate concentration via biodegradation would be beneficial and would result in a decrease in radionuclide migration. However, subsurface conditions can exist where chelation of radionuclides would increase radionuclide adsorption and lead to a decrease in radionuclide mobility. Under these conditions, biodegradation of the chelate would be undesirable.

The current limited scientific understanding of both chelated radionuclide adsorption and biodegradation and the physicochemical and microbiological parameters that influence these processes prevents an assessment of their role in controlling chelated radionuclide transport at DOE mixed waste sites. This lack of knowledge precludes manipulating the geochemical and microbiological conditions in the subsurface environment to limit radionuclide migration when synthetic chelating agents are present. Also, synthetic chelates can be used as models of native organic compounds, which also complex radionuclides and metals. Understanding the interactions of synthetic chelate adsorption and biodegradation, for which thermodynamic data are readily available for modeling purposes, can aid in interpreting data for native

organic complexants, where limited thermodynamic data are available. This project focuses on the adsorption of synthetic chelates and chelated radionuclides, the subsurface physicochemical conditions influencing microbial biodegradation and transformations of synthetic chelates, and the synergistic influence adsorption and microbial processes have on each other. The modeling of the aqueous speciation is an integral part of all aspects of this project.

Chelated Radionuclide Adsorption

The goal of this segment of the research is to mechanistically describe chelated radionuclide adsorption for a range of subsurface materials and conditions present at DOE waste sites. The current focus of this research is on the adsorption of Co(II)EDTA , Co(III)EDTA , and Co(II)NTA by aluminum oxides (namely, $\gamma\text{-Al}_2\text{O}_3$ and gibbsite) in the absence of microbiological activity. Cobalt and EDTA were selected for study because of their comigration in pore waters at specific DOE sites. Aluminum oxides were chosen because in many subsurfaces and subsurface materials they are important sorbents and may exert a significant influence on radionuclide attenuation and mobility. The CoNTA -gibbsite system is being used in chelated radionuclide adsorption-biodegradation interactive studies discussed in a later section. In the following discussion, selected results for the $\text{CoEDTA-}\gamma\text{-Al}_2\text{O}_3$ systems will be presented.

Analysis of pore waters from trenches at a DOE waste site suggests that trivalent cobalt [Co(III)] is present in association with EDTA. Divalent cobalt is stable in aqueous systems, with Co(III) being rapidly reduced at room temperature by water. However, in the presence of nitrogen donor groups (e.g., NH_3 , amines such as ethylenediamine and EDTA), aqueous Co(III) complexes can be formed in the presence of molecular oxygen and surface-active catalysts and are highly stable as a function of time. The tentative identification of Co(III)EDTA complexes in pore waters suggests that Co(III)EDTA , in addition to Co(II)EDTA complexes, may play a role in the observed ^{60}Co migration in groundwater at specific DOE sites. Based on this information, the differences in the adsorption behavior of the Co(II) and Co(III)EDTA complexes are being investigated on $\gamma\text{-Al}_2\text{O}_3$ as a function of pH and adsorbate and

sorbent concentrations to mechanistically describe adsorption using the surface coordination reaction approach. This approach couples specific surface coordination reactions of CoEDTA and surface hydroxyls of the oxide (XOH) with aqueous speciation reactions, and thus provides a generalized description of the adsorption process.

Adsorption experiments were conducted in 0.01 M NaClO_4 solutions unless stated otherwise, with equal molar Co and EDTA concentrations, under a CO_2 -free N_2 atmosphere. Aluminum oxide concentrations of 1 g L^{-1} were used yielding an XOH adsorption site concentration of 1.3 mM . Adsorption reached equilibrium in less than 6 hours; however, all experiments were conducted for 24 hours.

The adsorption of Co(III)EDTA was significantly reduced from that of Co(II)EDTA over the pH and adsorbate range (0.2 to $10 \text{ }\mu\text{M}$) examined (Figure 1). Adsorption edge data are shown only for the lowest adsorbate concentration; however, the edges for both Co(II)EDTA and Co(III)EDTA at other concentrations are nearly identical. In addition, the Co(II)EDTA and Co(III)EDTA edges are displaced to lower pH, and the adsorption maximum is reduced as the ionic strength of the supporting electrolyte increases from 0.01 to 0.1 M NaClO_4 [see Figure 1; data for Co(III)EDTA at 0.1 M NaClO_4 not shown]. This dependence on ionic strength indicates that the surface reactions responsible for the adsorption of Co(II)EDTA and Co(III)EDTA have significant electrostatic contributions. This observation strongly supports the

FIGURE 1. Comparison of Co(II)EDTA and Co(III)EDTA Adsorption on $\gamma\text{-Al}_2\text{O}_3$ at 0.01 M NaClO_4 and Co(II)EDTA Adsorption at 0.1 M NaClO_4

hypothesis that the bonding of both of these cobalt chelates to surface hydroxyls is by means of the formation of outer-sphere ion-pair complexes rather than inner-sphere surface coordination complexes. This is of major importance for the mechanistic modeling of the surface coordination reactions describing Co(II)EDTA and Co(III)EDTA adsorption. Although the formation of outer-sphere complexes is a reasonable interpretation of the shifts in the adsorption edges observed with increasing ionic strength in this study, the nature of the surface CoEDTA species must be substantiated by future molecular examination of solution and surface chelate species. For example, in the case of CoEDTA chelates, extended x-ray absorption fine structure (EXAFS) spectroscopy may prove useful for determining oxidation state and nearest-neighbor binding as it was for Co(II) adsorption by $\gamma\text{-Al}_2\text{O}_3$. The usefulness of EXAFS in the current study is being investigated collaboratively with Los Alamos National Laboratory investigators within the Co-Contaminant Chemistry Subprogram of DOE's Subsurface Science Program.

The Co(II)EDTA and Co(III)EDTA adsorption data, the ionic strength shifts, and the aqueous speciation calculations support the hypothesis that the following reactions describe the observed adsorption behavior:

The ability of these reactions, and if necessary others, to describe the observed CoEDTA adsorption data will be tested in FY 1992 using the Triple Layer model of surface coordination.

The difference between Co(III)EDTA and Co(II)EDTA adsorption can be understood in terms of difference in structure of these chelates in solution; that is, the greater tendency of a free carboxylate group to form for Co(II)EDTA than for Co(III)EDTA in the pH range considered in this study. In solution, CoEDTA chelates can exist in a quinquedentate and/or a sexidentate configuration (Figure 2). In the sexidentate configuration, all four carboxylate oxygen atoms are coordinated with the central cobalt atom; while in the quinquedentate configuration, a water molecule replaced one of the carboxylate oxygens in an approximate octahedral configuration about the central cobalt atom, leaving an uncoordinated or "free" carboxylate group.

In the literature, some debate persists regarding the exact ratio of sexidentate versus quinquedentate Co(II)EDTA²⁻; however, both conformations [Co(II)EDTA²⁻ and Co(II)(H₂O)EDTA²⁻] exist simultaneously for the pH range of this study. It is the free carboxylate that is protonated (i.e., the protonated species, Co(II)HEDTA⁻, is Co(II)(H₂O)HEDTA⁻). It is, therefore, reasonable to assume that aqueous Co(II)EDTA²⁻ in the adsorption reactions above represents a mixture of Co(II)(H₂O)EDTA²⁻, with a free carboxylate group, and Co(II)EDTA²⁻, with no free carboxylate. The protonated aqueous species, Co(II)HEDTA⁻, is the quinquedentate form, Co(II)(H₂O)HEDTA⁻, because

FIGURE 2. Configuration of Co(II)EDTA and Co(III)EDTA Chelates in Solution

it is the free carboxylate that is protonated. The predominant aqueous Co(III)EDTA^- species exists in a sexidentate conformation and does not have an associated free carboxylate group. The protonated species, Co(III)HEDTA^0 , is considered to be quinque-dentate, $\text{Co(III)(H}_2\text{O)HEDTA}^0$, where the free carboxylate was protonated. This quinque-dentate Co(III)EDTA species is unstable for $\text{pH} > 1$ and reverts to the sexidentate configuration within minutes. In summary, aqueous Co(II)EDTA exists both with and without a free carboxylate, while aqueous Co(III)EDTA has no free carboxylate group.

The working hypothesis for the reduction in Co(III)EDTA adsorption relative to Co(II)EDTA is as follows. The hydrogen bonding of the free (quinque-dentate) carboxylate oxygen with surface hydroxyls (Figures 3a and b) is stronger than the carboxylate oxygen-surface hydroxyl bond of the sexidentate chelate (Figure 3c). The presence of a free carboxylate group in Co(III)EDTA is greatly reduced from that of the Co(II)EDTA because of the reduced size and increased electronegativity of the Co(III) atom. This increased electronegativity reduces the strength of the hydrogen bond between the carboxylate oxygen of the sexidentate Co(III)EDTA and surface hydroxyls relative to the strength of the hydrogen bond between sexidentate Co(II)EDTA and surface hydroxyls (see Figure 3c). Thus, the ability of Co(III)EDTA to coordinate with the surface is greatly reduced.

The ability of this conceptual model of chelate surface coordination, together with coupled adsorption reactions [Equations (1) through (4)] and aqueous speciation reactions, to simulate the

observed adsorption behavior is currently under way. Because of the reduced ability of Co(III)EDTA to adsorb to $\gamma\text{-Al}_2\text{O}_3$ and, by analogy, Al oxides in soils and subsoils, either the presence of the Co(III)EDTA , or conditions promoting the oxidation of Co(II)EDTA to Co(III)EDTA , may enhance the mobility of $^{60}\text{CoEDTA}$ chelates in pore waters at field sites.

Chelate Biodegradation

The goal of this research is to quantify chelate persistence in the subsurface environment and to determine what are the biological and geochemical limitations for the degradation of synthetic chelates. Research focused on using subsurface sediment samples from the Deep Subsurface Microbiology component of the Subsurface Science Program to provide initial estimates of chelate persistence. Previously isolated synthetic chelate degraders are being used to provide information useful for these enrichments, including the optimal environmental conditions necessary for chelate biodegradation. Also, basic information will be forthcoming on chelate degradation metabolites and how geochemical conditions influence chelate persistence and chelated metal and radionuclide fate. These isolates or consortia are also being used in joint studies of chelated radionuclide adsorption and biodegradation from which combined adsorption-biodegradation models will be developed.

A *Pseudomonas* species (ATCC-29600), previously isolated from subsoil, is being used to study NTA degradation and, subsequently, the influence of NTA adsorption on biodegradation. An underlying hypothesis of this work is that the complexed metal will influence chelate degradation because the metal-chelate complex forms a three-dimensional structure with the metal surrounded by the chelate. One hypothesis that we tested this fiscal year was that the stability of the metal-chelate complex will dictate the rate of degradation. Thus, metals with larger thermodynamic formation constants for forming the metal-chelate complex will degrade more slowly than metals with smaller formation constants. Therefore, the CoNTA complex should degrade faster than FeNTA because the formation constant for CoNTA is much less than FeNTA .

FIGURE 3. Coordination of Quinque-dentate (a and b) and Sexidentate (c) Cobalt-EDTA Chelates with Surface Hydroxyls, XOH

During FY 1991, we demonstrated that the NTA degrader, *Pseudomonas* sp. 29600, offered a nice model system to test our hypothesis. A mass balance of NTA-C during degradation demonstrated that $^{14}\text{CO}_2$ produced from ^{14}C -labeled NTA was a good indicator of NTA degradation (i.e., NTA disappearance from solution). The NTA degrader could degrade NTA at concentrations ranging from 10 to $0.001\ \mu\text{g NTA mL}^{-1}$. This degradation followed first-order kinetics, with the degradation of NTA directly proportional to its aqueous concentration. As the NTA concentration increased, the rate of degradation (i.e., mass degraded as a function of time) also increased, so that the percent of the added NTA degraded was the same at all concentrations. Thus, the degradation rate was equal to the first-order rate constant times the concentration of NTA in solution. This was important because a decrease in the amount of NTA available for degradation via adsorption or the formation of a slowly degradable metal-NTA complex would be detected by a slower degradation rate. The ability to mineralize low concentrations of NTA in the $10^{-6}\ \text{M}$ range ($0.19\ \mu\text{g NTA mL}^{-1}$) is relevant to groundwater concentrations at some DOE waste sites and is within the concentration range that will be used in joint adsorption-biodegradation interactive studies described below. The concentration of *Pseudomonas* sp. 29600 cells used in this study was $10^8\ \text{cells mL}^{-1}$. This cell concentration was within the range necessary for first-order kinetics because cell density was not a factor limiting the degradation of NTA. As cell density decreased below 10^5 to $10^6\ \text{cells mL}^{-1}$, NTA degradation ceased to be first order and cell density limited the rate of NTA degradation. Finally, if the NTA degrader was induced on NTA (i.e., grown on NTA plates), the degradation of NTA in solution occurred in very simple aqueous systems such that nutrients were not necessary. This meant that very simple aqueous systems could be used to investigate NTA degradation, thus greatly simplifying the aqueous chemistry for aqueous speciation modeling.

To test our hypothesis that the stability of the metal-chelate complex will dictate the rate of degradation, it was evident the free acid of NTA and the Fe, Al, and CoNTA complexes would not provide a sufficient range in formation constants to adequately address this hypothesis. So, for this

experiment, we also added Cu and NiNTA complexes. This experiment used $10^8\ \text{cells mL}^{-1}$ in $0.001\ \text{M}$ Piperazine-N,N'-bis[2-ethane-sulfonic acid] (PIPES) buffer at pH 6. PIPES buffer has a low capacity for metal complexation and good buffering ability at pH 6. All solutions were assayed by inductively coupled plasma-Augur electron spectroscopy to arrive at actual metal concentrations and to detect possibly competing metal contaminants in our solutions. The assay revealed that there were none. We used the metal nitrates and $0.01\ \text{M KNO}_3$ as an ionic buffer. The metal-NTA complexes were made by mixing equal molar concentrations of chelate and metal ($5.23\ \mu\text{M}$) at low pH and slowly raising the pH to 6. Aqueous speciation calculations of our simple aqueous system using the MINTEQA computer code indicated that the predominant form of NTA in all cases was as the metal-NTA complex (except for the free acid of NTA that was present as HNTA^{2-}). In other words, the acid form of NTA was at a minimum when any of the metals were present. The acid form of NTA (HNTA) degraded faster than the metal-NTA complexes, as demonstrated by the greater slope of its degradation curve (Figure 4). The relative order of NTA degradation was $\text{H} > \text{Fe} > \text{Co} > \text{Al} > \text{Cu} > \text{Ni}$. Table 1 shows the thermodynamic stability constants of the metal chelates and the kinetic data derived from nonlinear regression of the curves in Figure 4. An increase in the log of the stability constant did not have a relationship with the first-order rate constants, the asymptotic maximum values, or the maximum initial rates of degradation. The Ni, Cu, and AlNTA curves were significantly lower than the other curves as indicated by their lower rate constants and asymptotes relative to the other metal-NTA complexes (see Table 1). The data in Table 1 would suggest that our hypothesis should be rejected. However, some of the metals we used, such as Ni and Cu that had the lowest rates of degradation, could have been toxic to the NTA degrader. We disproved that metal toxicity was contributing to varying rates of NTA degradation by adding the free metals at $5.23\ \mu\text{M}$ and measuring ^{14}C -labeled glucose degradation under the same conditions as the previous experiment. The degradation of NTA is hypothesized to occur through the oxidation of the N-C bond and the formation of glyoxylate. The glyoxylate would then be degraded via the tricarboxylic acid (TCA) cycle. Glucose enters the

FIGURE 4. Degradation of Various Metal-NTA Complexes at 5.23 μM . The aqueous system was PIPES buffer at pH 6 and 0.01 M KNO_3 . Metal-NTA complexes were the dominant form in solution as determined by aqueous speciation modeling.

TABLE 1. Thermodynamic Formation Constants ($\log K_f$) for Various Metal-NTA Complexes and First-Order Rate Constants (k), Asymptotes (A), and Initial Rates (kA) for the Degradation of Various Metal-NTA Complexes

Metal	$\log K_f$	$k \text{ (h}^{-1}\text{)}^{(a)}$	$A \text{ (\%)}^{(a)}$	$kA \text{ (\% h}^{-1}\text{)}$
H	0	$0.67a^{(b)}$	59ab	40
Co	11.7	0.26b	57b	15
Ni	12.8	0.06d	34d	2
Al	13.7	0.12c	60ab	7
Cu	14.2	0.11c	41c	4
Fe	17.8	0.21b	65a	14

(a) A first-order product curve [$P = P_0(1 - \exp^{-kt})$] provided the first-order rate constants and the asymptotes by nonlinear least squares regression.

(b) Numbers followed by the same letter in the same column are not significantly different (95% confidence level).

TCA cycle after the Entner-Doudoroff pathway. Glucose would, therefore, be a "good" indicator of the effects of metals on the generation of CO_2 . No inhibitory effects on glucose degradation were found when the metals were present. This indicates that if the free metal was taken up by the cell, the metal itself did not inhibit cellular respiration or the generation of $^{14}\text{CO}_2$. However, the amount and/or location of the metal in the cell may be different when taken up as the metal-NTA complex as compared with the free metal, so we added metals as the metal-NTA complex to cells induced on NTA and again measured ^{14}C -labeled glucose degradation. Because the cells were induced on NTA, both NTA and glucose would be taken up into the cells. No inhibition of glucose degradation occurred, further indicating that the

metal itself is not inhibiting general cellular metabolism but, rather, it is the nature of the complexed metal that influences NTA degradation by influencing either cellular uptake of the NTA or the initial enzymatic cleavage of the NTA.

Our new hypothesis is that it is the lability of the metal-NTA complex that influences NTA degradation. Lability is a kinetic variable and is the ability of the complexed metal to exchange with free metal in solution, where the complexed-free metal exchange is related to the ability and frequency of breaking the carboxyl-metal bond. Data are limited for NTA, but data for EDTA suggest that various metal-EDTA complexes can have varying labilities for metal exchange. The NiEDTA and CuEDTA complexes are very nonlabile because of the electronic structure of the metal atom. Because lability is dictated by the electron structure of the metal ion and not the chelate, we would expect these metals to also be nonlabile with NTA.

Chelate Adsorption-Biodegradation Interactions

The goal of this research is to investigate the mutual interactions of chelate adsorption on biodegradation and the influence of microbial activity on chelate and radionuclide adsorption. During FY 1991-1992, these interaction studies have focused on the limitation imposed on chelate degradation rates by chelate adsorption and desorption. The hypothesis being tested is that adsorbed chelates are unavailable for degradation. Only through desorption of the chelate into the aqueous phase is the chelate available for degradation. Thus the rate of chelate desorption is limiting the degradation rate. To test this hypothesis, we selected a model system consisting of NTA or CoNTA, the subsurface NTA degrader *Pseudomonas* sp. 29600, and the naturally occurring mineral gibbsite as the adsorbent.

In FY 1991, experiments were conducted to determine 1) the degradation rates of NTA and metal-NTA chelates by the *Pseudomonas* sp. in the absence of chelate adsorption and 2) the adsorption of NTA and CoNTA by gibbsite in the absence of microbial activity. Integration of this information is essential for the design and future interpretation of interaction experiments that address the hypothesis being tested for the combined aqueous NTA-gibbsite-*Pseudomonas* sp. system. This

integration of chemical and biological information and the design of interaction experiments for this system was a major activity during FY 1991 and is discussed below.

For the NTA-gibbsite system, the adsorption of NTA as a function of solution pH increases from 65% to 90% as the pH decreases from 8 to 6, while for the CoNTA-gibbsite system, similar NTA adsorption behavior occurs (Figure 5, Table 2). In this same pH range, the aqueous speciation of NTA is changing from predominantly the free acid form, HNTA^2 , at pH 8 to 100% AINTA species at pH 6 (see Figure 5, Table 2). Dissolved Al was present because of the pH-dependent solubility of the gibbsite solid phase. As part of the adsorption experiments (see Figure 5), dissolved Al (18A filter) was measured as a function of pH and these total dissolved Al values were used in the NTA aqueous speciation calculations (see Figure 5). For the CoNTA-gibbsite system, the aqueous speciation is more complex, with AINTA, CoNTA, and the free acid of NTA occurring (see Figure 5, Table 2). With decreasing pH, the dominant NTA species changed from a mixture of the acid HNTA^2 and CoNTA^- at pH 8 to predominantly CoNTA^- and AINTA species at pH 7 and 6, respectively.

Thus, in the interaction studies, the dominant aqueous NTA species available for degradation by *Pseudomonas* sp. will change considerably over the 6 to 8 pH range being considered for study. The degradation rates for the acid form of NTA and several metal-NTA complexes (in the absence of gibbsite) were found to be first order with the first-order rate constants, k , decreasing in the following order: $k_{\text{HNTA}} > k_{\text{CoNTA}} > k_{\text{AlOHNTA}}$ (see Table 1). The rate constant for the acid form of NTA is independent of pH between 6 and 8; however, in the NTA-gibbsite-*Pseudomonas* sp. or the CoNTA-gibbsite-*Pseudomonas* sp. system, a change in pH will alter the speciation and thus the degradation rates. Thus, depending on the pH and solution species present, the NTA degradation rate will vary.

The interaction experiments must be performed at a constant pH to minimize changes in 1) adsorption/desorption induced by changes in pH and 2) aqueous speciation of the NTA available for degradation by the *Pseudomonas* sp. In

FIGURE 5. NTA Only and CoNTA Adsorption on Gibbsite (a) and NTA Aqueous Speciation for NTA = 1 μM (b) and Co = NTA = 1 μM (c) and Measured Al Concentrations from Adsorption Experiments (a)

TABLE 2. NTA and CoNTA Adsorption on Gibbsite and Aqueous Speciation as a Function of pH

Chelate	pH	Adsorption	Solution Species
		(%)	
NTA	6.0	90	AIOHNTA (85%), AINTA (15%)
	7.0	83	AIOHNTA (45%), HNTA (45%)
	8.0	65	HNTA (90%)
CoNTA	6.0	90	AIOHNTA (60%), CoNTA (20%), AINTA (20%)
	7.0	85	CoNTA (85%), AIOHNTA (8%), HNTA (7%)
	8.0	70	CoNTA (35%), HNTA (65%)

addition, the comparison of NTA degradation in systems with adsorption (i.e., gibbsite present) with those with no sorbent present (i.e., controls) requires that the pH and aqueous speciation in our controls be identical to those of the gibbsite system. The aqueous speciation of the AINTA system without gibbsite present is very similar to that of the NTA-gibbsite system; thus, we can use a simple aqueous AINTA system as our control. Finally, any comparison of adsorption control of NTA degradation rates in the NTA-gibbsite-*Pseudomonas* sp. system at different fixed pH values must consider 1) the difference in degradation rates among aqueous NTA species and 2) possible differences in desorption rates with pH. The latter possibility may arise because the NTA desorption process involves exchange of hydrogen ions at the oxide surface. The measurement of NTA desorption rates and possible pH dependence of these rates will be investigated in the absence of biological activity in FY 1992 and used in the interpretation of interaction study results.

Based on these findings, two desorption-degradation experiments (pH 8 and 6) will be conducted during FY 1992 using the NTA-gibbsite-*Pseudomonas* sp. system. Our experimental approach will be to use a zero-head-space, well-stirred, stop-flow cell containing the gibbsite suspension. Rapid stirring of the suspension and a 0.2- μ m exit port filter will prevent loss of the 2- μ m gibbsite particles and the *Pseudomonas* sp. when solution is flowing through the cell. Before the start of the desorption-degradation experiment ($t < 0$), NTA adsorption equilibrium of the gibbsite suspension will be obtained by pumping an

electrolyte solution through the cell containing a fixed concentration of ^{14}C -labeled NTA, C_0 , at a fixed pH. At $t = 0$, the cell will be rapidly flushed with an identical solution containing no NTA; thus dropping the NTA concentration in the cell to zero, flow through the cell is stopped, *Pseudomonas* sp. will be injected into the cell, and NTA will start desorbing from the gibbsite. The appearance of NTA in solution along with the NTA degradation product, $^{14}\text{CO}_2$, will be measured over the 12- to 24-hour duration of the experiment. NTA degradation, as measured by $^{14}\text{CO}_2$ evolution (curve A, Figure 6), will be compared with $^{14}\text{CO}_2$ evolution in the absence of the gibbsite adsorbent but otherwise identical conditions (curve B, Figure 6) to determine the extent to which NTA desorption limits its degradation. Curve B is observed HNTA degradation data at pH 8 (see Figure 4). Curve A is derived from model calculations based on 1) the measured value of $k_{\text{HNTA}} = 0.67 \text{ hour}^{-1}$ at pH 8 (see Table 1), 2) an assumed NTA desorption rate constant at pH 8 of $k_d = 0.01 \text{ hour}^{-1}$, and 3) a simple first-order process model represented by

$$\begin{aligned} \text{NTA}_{\text{adsorbed}} &\xrightarrow[\text{(desorption)}]{(k_d)} \\ \text{NTA}_{\text{aqueous}} &\xrightarrow[\text{(degradation)}]{(k_{\text{HNTA}})} \text{CO}_2 \end{aligned} \quad (5)$$

The value of k_d used is considered to represent the upper limit for NTA desorption from oxides and yields a desorption rate indicated by curve C (see Figure 6). Thus, curve A does not represent a model calculation based completely on observed data but, rather, represents the type of observation expected in the interaction experiments. Observed NTA degradation data of the type indicated by curve A will be modeled with experimental desorption rate data and, if necessary, a more sophisticated process model than that shown in Equation (5).

Future Research

The continued investigation of chelated radionuclide adsorption on oxides, smectitic clays, and subsoils dominated by oxides and/or clays, along

FIGURE 6. First-Order Model Simulation of the Effect of NTA Adsorption by Gibbsite on the Degradation of NTA by *Pseudomonas* sp. at pH 8 (curve A) Based on Measured NTA Degradation Rate at pH 8 (curve B) and an Assumed Upper Limit for NTA Desorption Rate (curve C)

with biodegradation studies of synthetic chelates and microbial-driven geochemical modifications of the subsurface environment, will extend the applicability of this research to several DOE sites. In addition, surface-catalyzed oxidation of Co(II)EDTA to Co(III)EDTA by Fe and Mn oxides will be investigated to determine the mechanisms and conditions under which cobalt oxidation may be occurring at DOE field sites. Finally, adsorption-biodegradation interactive studies are being initiated using NTA as the synthetic chelate, *Pseudomonas* sp. 29600 as the chelate degrader, and gibbsite as the model subsurface sorbent. Subsequently, the addition of Co to this system will introduce additional complexity in both the

aqueous speciation and the adsorption of the CoNTA complex. The objective of the combined studies on progressively more complex systems is to quantify the effects of each process on the other and to incorporate these effects into a coupled mathematical model of synthetic chelate adsorption-biodegradation interactions. This mathematical description can be incorporated into transport codes for simulation and prediction of radionuclide and chelate mobility. Research results and model development will also aid in the evaluation of effective remediation strategies at DOE sites where chelates and radionuclides are codisposed.

Subsurface Microbial Processes

*J. K. Fredrickson, F. J. Brockman, and
T. O. Stevens*

Contributors

*P. Long, E. Murphy, B. Bjornstad, S. Rawson,
M. Truex (Washington State University), and
T. Kieft (New Mexico Institute of Mining and
Technology)*

This project continues to explore the microbial ecology of the subsurface environment. Microbiological processes in the subsurface, and their interactions with the surrounding geologic strata, are central to solving problems of contaminant transport and designing treatment systems for contaminated aquifers and subsoils. In addition to their utility for bioremediation, subsurface microbial communities represent an important, largely unexplored segment of the biosphere.

Before the Subsurface Science Program began, little was known about the distribution, abundance, and potential activity of microorganisms below the top few meters of soil. Initial studies in the deep Cretaceous-age marine sediments below the Savannah River Site showed that extensive microbial populations possessing diverse metabolic potentials can exist in the deep subsurface. During the past year, drilling and sampling at the Hanford and Idaho National Engineering Laboratory sites were completed as part of the Transition Phase of the Deep Subsurface Microbiology Subprogram. Because the geology of the new sites differed markedly from that of Savannah River, these studies are extending our current knowledge of the interactions of microorganisms with subsurface environments. In addition, these field investigations have resulted in the discovery of several novel microorganisms and suggest that in some deep sediments the microorganisms may have been present and functioning for thousands of years or longer.

In addition to fundamental investigations of the ecology of microorganisms in deep subsurface environments, studies are continuing on the basic biodegradative mechanisms utilized by subsurface bacteria, the role of the physiological state of subsurface bacteria in their response to organic contaminants, and the interactions between biodegradation and physical and chemical

processes. The research summaries presented herein will include 1) microbiology of Hanford Site vadose zone sediments and implications of the results for origins of the microorganisms, 2) fate of tetraphenyl boron in sediment and soil, 3) nonspecific induction of aromatic substrate oxidation in the subsurface bacterium F199, 4) influence of starvation on the biodegradation of organic contaminants by a subsurface bacterium, and 5) optimization of cultural media for heterotrophic subsurface bacteria.

Microbiology of Hanford Vadose Zone Sediments and Implications for Microbial Origins

Diverse microbial communities have been found in saturated shallow terrestrial subsurface environments and are of interest because of the influence the microorganisms have on geochemical processes and the potential for in situ biodegradation of organic contaminants. That terrestrial and aquatic environments are the sources of microorganisms in shallow aquifers is readily rationalized as microorganisms can migrate through soil and sediment via mass flow. As the geologic strata become increasingly isolated from the surface environment with depth, the distances required for microbial transport from the surface increase, and the issue of the origins of the indigenous microbiota becomes clouded. The source of microorganisms in deep saturated subsurface environments could be the mass transport of cells with water from the surface through extended periods, survivors or progeny of microorganisms associated with the original deposits, organisms introduced as a result of well drilling and installation activities, or a combination of the above.

The saturated deep subsurface sediments of the Southeast Coastal Plain have been shown to harbor diverse heterotrophic bacterial populations whose metabolic activities have been estimated to be very low. These environments have been characterized as extremely oligotrophic, and the resident microflora may be remnants of populations present at the time of deposition 70 to 80 myBP or possibly from populations transported with groundwater movement during the past 10,000 to 50,000 years. We report herein on the microbiology of vadose zone sediments in the arid

region of eastern Washington and on the implications of the results for the origin of the extant microorganisms in those sediments.

Core samples were collected from the vadose zone on DOE's Hanford Site in southcentral Washington at depths ranging from 30 to 90 m using a split-spoon sampler in combination with cable tool drilling. Cable tool drilling is a somewhat archaic drilling method by modern standards but one that is attractive for obtaining uncompromised core samples for microbiological and chemical analyses because it requires no circulating fluids. Drilling fluids can carry microorganisms and solutes that can contaminate cores during drilling. Sample depths and stratigraphy are shown in Figure 1. Samples were obtained from glaciofluvial deposits referred to as the Hanford formation that were deposited during catastrophic flood events that occurred between 13,000 and 800,000 yBP (Bjornstad and Fecht 1989). A depositional unconformity exists between the Hanford formation and the underlying Ringold Formation at a depth of approximately 55 m. The Ringold Formation comprises fluvial-lacustrine deposits from the ancestral Columbia and Snake rivers and ranges in age from 3.9 to 8.5 myBP (DOE 1988). Within the Ringold Formation, core samples were also obtained from sediments with characteristics of paleosols (i.e., ancient soils), including accumulation of CaCO_3 and clay cutans. A sample of surface soil was included for comparison.

With the exception of the surface soil sample, which had $10^{7.2}$ colony-forming units g^{-1} dry soil, the populations of aerobic heterotrophic microorganisms were below detection using dilution plate-count procedures. Direct deposition of a small amount of sediment on the surface of agar plates allowed for semiquantification of culturable aerobic bacteria. Few or no culturable bacteria were present in the samples from the glaciofluvial sands of the Hanford formation, but in the underlying Ringold Formation several of the samples averaged one or more outgrowths per plate (Figure 2). In one sample, from 73.3 m, the number of outgrowths per plate was between 4 and 5, which was substantially higher than for other samples. Of the bacteria isolated from these samples, 28 were gram-positive, 16 were gram-negative, and 9 were gram-variable. Gram-positive bacteria as a

group are, in general, more resistant to desiccation and associated effects such as starvation.

Aerobic microbial activity potentials were determined by measuring the mineralization of a mixture of readily metabolizable organic compounds including acetate, succinate, and glucose added to sediment samples. Little or no mineralization of the organic substrates to $^{14}\text{CO}_2$ occurred during short-term incubations (3 days) (Figure 3), indicating that microbial populations in these sediments, except for the surface soil, were metabolically inactive. With extended incubation (40 days), more than 10% of the substrate mixture was mineralized in five out of eight Ringold sediment samples. In only one sample, from 71.7 m, was the mineralization of substrates during the extended incubation equivalent to that of the surface soil. There was generally good correspondence between the number of culturable heterotrophs (see Figure 2) and the extent of $^{14}\text{CO}_2$ release during extended incubations (see Figure 3). Sediments from the 71.7-m and 73.3-m depths mineralized the substrates to the greatest extent and had the highest population of culturable heterotrophs, respectively. These sediments had characteristics of pedogenic development, including CaCO_3 accumulation, root traces, and blocky structure. We assume that at the time these sediments were undergoing pedogenesis approximately 5 million years ago, an active soil microbial community was also established. In contrast, the overlying Hanford formation lacked pedogenic characteristics and, being of glaciofluvial origin, probably never supported a large microbial community.

Two possible mechanisms may account for the microorganisms in these vadose zone sediments. The first possible mechanism is the transport or movement of microorganisms from overlying soil or subsoil where the availability of water and nutrients is sufficient to sustain a heterotrophic microbial community. Because none of the sediments sampled in the Hanford formation had significant populations of culturable microorganisms, these sediments likely would not have been the source of microorganisms in the Ringold Formation. Thus, the source of organisms, if transported, would have been the surface soil. The second possible mechanism is the long-term

FIGURE 1. Stratigraphy and Depth of Samples Obtained from the Vadose Zone of the Hanford Site In Southcentral Washington

FIGURE 2. Number of Viable Microorganisms Associated with the Vadose Zone Sediments. Numbers were estimated by placing between 0.2 and 0.8 g of subsurface sediment directly on the surface of 1% peptone-trypticase-yeast extract-glucose agar and enumerating the number of microbial outgrowths after incubation at 15°C.

FIGURE 3. Mineralization of the Organic Substrates to ¹⁴CO₂. Numbers were determined by adding 0.5 μCi each of [¹⁴C(U)] glucose, [1-¹⁴C] acetate, and [1,4-¹⁴C] succinate to 8 to 10 g of sediment in a total volume of 200 μL. Vials were incubated in the dark at 22°C, evolved ¹⁴CO₂ was trapped in 1 N KOH, and the total amount of ¹⁴C was measured by liquid scintillation counting. Each value is the average of measurements made on triplicates.

maintenance of a portion of the microbial population or community associated with the materials at the time of deposition or, in the case of the paleosol, the community that developed during pedogenesis.

The current average annual precipitation at the drill site is approximately 20 cm. Concentrations of chlorine in the vadose zone samples and estimates of historical atmospheric deposition of chlorine suggest that essentially no moisture is vertically recharged through the vadose zone. Bacterial movement in porous media can occur under unsaturated conditions but is limited to short distances (i.e., microenvironments); therefore, significant transport of microorganisms would be limited to conditions of mass water flow. The most recent conditions of vertical mass water flux through the Ringold Formation would have been the last of the catastrophic floods that occurred approximately 13,000 years ago. Thus, during the past 13,000 years, there was little opportunity for vertical transport of microorganisms from the surface to the depths where currently found.

Microorganisms in the vadose zone sediments were in an inactive state probably because of severe nutrient limitation. At volumetric water contents of 20%, the diffusion of solutes rapidly limits microbial activity in unsaturated sediments, particularly when the concentration of nutrients is low. The gravimetric water contents of the vadose sediments in this study were between 1 and 10%. Therefore, the microorganisms in these sediments were existing under conditions of extreme oligotrophy but were not subjected to extreme desiccation.

The fact that the highest number of microorganisms in the Ringold Formation were present in a sediment with characteristics indicative of a paleosol and that metabolic activity was observed with extended incubation suggests some low level of in situ microbial activity in those samples. Thus, these microorganisms may be remnants of the original soil microbial populations that colonized the soil during the Neogene approximately 5 million years ago. The fact that few or no viable bacteria were present in overlying flood deposits of the Hanford formation indicates that microorganisms in the Ringold Formation likely did not originate from infiltrating water at the time of deposition or during postdeposition. Microorganisms in the Ringold Formation, particularly those in the paleosol, could have maintained integrity through geologic time by metabolizing, at an extremely slow rate, organic carbon that accumulated during pedogenesis. The longevity of

microbial cells is essentially unknown, although some bacteria have a remarkable capacity to remain viable for extended periods under starvation conditions. The potential for survival of microorganisms in unsaturated subsurface sediments would be higher than in other environments because of 1) the lack of predators such as protozoa that can be present in many aquatic and moist soil environments; 2) protection from ultraviolet radiation; and 3) limited diagenesis and, hence, limited fossilization of cells resulting from lack of moisture.

Fate of Tetraphenyl Boron in Hanford Site Soils

Tetraphenyl boron (TPB) is a chelating agent that has been proposed for large-scale use in reducing the volume of liquid high-level radioactive waste prior to the grouting process. Industrial-scale use of such a reagent could result in accidental release to the environment. Although TPB is not considered hazardous, its potential association with radionuclides raises concerns about any possible release to soil.

Previous studies of the fate of TPB in soil have concluded that TPB is subject to rapid abiological degradation on contact with soil. These studies, however, were done in a limited range of acidic, sandy, Southeast Coastal Plain soils. In addition, these soils were all autoclaved, which complicated interpretation of the results. The current study was undertaken to determine the fate of TPB in Hanford Site soils, which are neutral or alkaline, and to attempt to elucidate the role, if any, of microorganisms in TPB degradation.

Soil slurries were prepared containing 300 ppm TPB and were incubated at 22°C for 100 days. One third of the slurries were sterilized by autoclaving prior to addition of TPB, to serve as sterile controls. One third of the slurries were sterilized, but then reinoculated with 1 g fresh soil, to determine possible artifacts of the autoclaving process. At each measurement time point, four tubes of each treatment were extracted and analyzed for TPB content. The effect of pH on TPB degradation was studied by incubating a duplicate set of slurries adjusted to pH 4, which was the pH of the Southeast Coastal Plain soils studied previously. The effect of reducing conditions on TPB degradation was studied by preparing a duplicate set of slurries in an

anaerobic chamber, using deoxygenated reagents, and incubating them in sealed tubes.

As shown in Figure 4, TPB degradation occurred only in soils that had been acidified. Clearly, abiological degradation took place; however, degradation was faster in nonsterilized soil. Reduced degradation in the sterilized but reinoculated soils showed that this rate difference was most likely an artifact of autoclaving. From this experiment, it was unclear whether microorganisms played a part in TPB degradation. The reactions that TPB undergoes in the presence of acidic soil can be complex, with many unidentified products. The major product appears to be a polar aromatic compound. Mass balances suggested that production of this compound accounted for most of the abiotic reaction of TPB in autoclaved slurries; however, in live slurries, the amounts of this product were not sufficient to account for the missing TPB.

These experiments demonstrated that TPB probably will not degrade if spilled in Hanford Site soils. Breakdown of TPB contamination could best be promoted by acidifying the contaminated soil. Stimulating the microbial populations of such soils might promote further degradation of the reaction products, but the ultimate fate of the compound probably would be incorporation into the amorphous soil organic matter.

Nonspecific Induction of Aromatic Substrate Oxidation in the Subsurface Bacterium F199

In earlier studies, we described the isolation of a gram-positive bacterium, designated F199, from subsurface sediment from the Middendorf Formation in the Southeast Coastal Plain. This bacterium was novel in that it grew on toluene, xylene isomers, *p*-cresol, naphthalene, and dibenzothiophene as a sole carbon and energy source under microaerobic conditions. Naphthalene mineralization in F199 was induced by toluene, but toluene mineralization was not induced by naphthalene. These results demonstrated that F199 had a wide aromatic substrate range and suggested either that multiple pathways were being coinduced or that the catabolic enzymes had a broad substrate range. During FY 1991, additional research with F199 was conducted to determine the extent of specificity of enzyme induction and substrate oxidation.

FIGURE 4. Fate of Tetraphenyl Boron (TPB) in Hanford Soils

The oxidation of indigo to indole by bacteria induced with aromatic compounds is indicative of oxidation of the aromatic nucleus to its respective *cis*-dihydrodiol. When F199 was induced with naphthalene, xylene, or toluene, the bacterium produced indigo from indole (Table 1), suggesting F199 oxidizes the aromatic nucleus of these compounds to their respective *cis*-dihydrodiols. Studies are being conducted to determine whether

dihydrodiol dehydrogenase activity is present in aromatic-induced F199 cells.

Polarographic (i.e., O₂ consumption rate) studies confirmed that aromatic catabolism by F199 was inducible and that there was significant cross-specificity with regard to induction by, and oxidation of, toluene, xylene isomers, naphthalene, and salicylate (Table 2). The similar patterns of O₂

TABLE 1. Production of Indigo from Indole by F199 Cultures

Bacterium	Inducer	Indigo Concentration in CHCl ₃ Culture Extracts (μ M)
F199	toluene	32
	<i>o</i> -xylene	62
	<i>m</i> -xylene	129
	<i>p</i> -xylene	125
	<i>o</i> -cresol	nd ^(a)
	<i>m</i> -cresol	nd
	<i>p</i> -cresol	11
	naphthalene	184
	salicylate	34
	benzoate	0
	uninduced	0
PpG1901	naphthalene	145

(a) nd = not done.

uptake by toluene-, *m*-xylene-, and *p*-xylene-induced cells in the presence of the various assay substrates suggest that the early steps in their catabolism may be through a common pathway analogous to the degradation of these compounds by the toluene (TOL) catabolic pathway. However,

catabolism of toluene, *m*-xylene, and *p*-xylene by wild-type TOL bacteria (e.g., containing plasmid pWWO) proceeds initially through oxidation of methyl substituents and when such cells were grown on toluene or xylenes, indigo was not produced from indole. In addition, *Pseudomonas putida* TOL does not degrade *o*-xylene although F199 can grow on this compound, and cultures induced with toluene, *m*-xylene, *p*-xylene, or *o*-xylene all were capable of oxidizing the other substrates. Neither benzene nor phenol supports growth of F199. The relaxed specificity of induction by and oxidation of toluene, xylene isomers, naphthalene, and salicylate suggests that F199 possesses a broad-specificity dioxygenase capable of oxidation of a variety of aromatic compounds to *cis*-dihydrodiol intermediates. Analysis of metabolites will be required for confirmation. All isomers of cresol were inducers at the genetic level for the oxidation of *p*-cresol and 4-methylcatechol, despite the fact that F199 could grow only on the *para* isomer, indicating that regulator(s) of aromatic induction in F199 have broad effector specificity.

Ring cleavage in F199 was predominantly *meta*, although *ortho* cleavage of catechol was observed in benzoate-induced cells (Table 3). In addition,

TABLE 2. Oxygen Consumption by Resting F199 Cultures Induced with Aromatic Hydrocarbons with Various Aromatic Substrates^(a)

Assay Substrate	Compound Used as Inducer ^(b) (μ L O ₂ mg ⁻¹ protein h ⁻¹)										
	unind	tol	<i>o</i> -xyl	<i>m</i> -xyl	<i>p</i> -xyl	nah	sal	benz	<i>p</i> -cre	<i>m</i> -cre	<i>o</i> -cre
naphthalene	0	61	10	59	30	380	200	20	6	nd ^(c)	nd
toluene	0	38	41	52	31	253	72	4	6	nd	nd
salicylate	4	23	4	23	26	158	125	26	6	nd	nd
<i>o</i> -xylene	0	27	46	47	25	274	91	10	3	nd	nd
<i>m</i> -xylene	0	45	nd	60	47	222	213	16	4	nd	nd
<i>p</i> -xylene	7	28	41	80	40	237	163	nd	7	nd	nd
<i>o</i> -cresol	0	17	nd	nd	nd	71	0	nd	13	12	6
<i>m</i> -cresol	nd	nd	nd	nd	0	30	nd	nd	92	62	9
<i>p</i> -cresol	2	23	10	0	4	127	61	nd	348	324	138
benzoate	9	89	4	33	26	142	120	185	nd	nd	nd
lactate	118	nd	140	nd	nd	nd	nd	110	nd	nd	nd

(a) All values are corrected for endogenous cell respiration.

(b) unind = uninduced, tol = toluene, *o*-xyl = *o*-xylene, *m*-xyl = *m*-xylene, *p*-xyl = *p*-xylene, nah = naphthalene, sal = salicylate, benz = benzoate, *p*-cre = *p*-cresol, *m*-cre = *m*-cresol, and *o*-cre = *o*-cresol.

(c) nd = not done.

TABLE 3. Catechol-2,3-Dioxygenase (C23O) and Catechol-1,2-Dioxygenase (C12O) Activities in Cell Extracts of F199 Cultures Induced with Various Aromatics

Organism	Inducer	Relative Enzyme Activity (induced activity/uninduced activity)			
		C23O (catechol)	C23O (3-CH ₃ catechol)	C23O (4-CH ₃ catechol)	C12O (catechol)
F199	uninduced	(38) ^(a)	(62)	(31)	(22)
	toluene	38.8	nd ^(b)	nd	2.9
	<i>o</i> -xylene	15.5	11.5	17.8	0.4
	<i>m</i> -xylene	16.0	nd	nd	0.6
	<i>p</i> -xylene	5.8	5.1	5.7	0.2
	benzoate	0.7	nd	nd	8.8
	naphthalene	12.7	6.3	7.8	1.2
	salicylate	39.4	nd	nd	0.3
	<i>p</i> -cresol	1.0	1.0	1.0	nd
PpF1	toluene	(747)	nd	nd	(9)

(a) Values in parentheses are actual enzyme activities expressed as nmoles product min⁻¹ mg⁻¹ protein.

(b) nd = not done.

the catechol-2,3-dioxygenase (C23O) activities in F199 were also nonspecific, in that naphthalene-, toluene-, or xylene-induced cells can cleave catechol, 3-methylcatechol, or 4-methylcatechol. O₂ uptake by *p*-cresol-induced cells was significant only in the presence of *p*-cresol, *m*-cresol, *p*-hydroxybenzoate, protocatechuate, and 4-methylcatechol, suggesting that the pathway for *p*-cresol degradation in F199 proceeds through protocatechuate. Although *o*- and *m*-cresol were inducers for *p*-cresol and 4-methylcatechol oxidation, neither could serve as a growth substrate for F199. The predominant ring fission pathway used by F199 for all the methylaromatics (except for *p*-cresol), naphthalene, and salicylate was *meta*. Ring cleavage was inducible and, in addition to catechol, 3- and 4-methylcatechol were also readily cleaved. Other bacteria have also demonstrated a relaxed specificity with regard to ring cleavage by C23O. In toluene-induced cells, catechol oxidation was unaffected by lysis, whereas 3- and 4-methylcatechol oxidation was decreased four- to fivefold, suggesting that the enzyme(s) responsible for oxidation were distinct from those that oxidized catechol.

These results indicate that F199 has at least two pathways for aromatic catabolism: one is

nonspecific and involves a dioxygenase-like oxidation of the aromatic nucleus of compounds such as toluene, xylene, and naphthalene (Figure 5), and a second, more specific pathway for *p*-cresol involves an initial oxidative attack on the methyl group (Figure 6).

Effect of Starvation on the Induction of Quinoline Degradation

Deep subsurface aquifer sediments are highly oligotrophic, or nutrient limited, often containing less than 10 mg organic carbon L⁻¹. The ability of subsurface microbial communities to degrade a variety of recalcitrant compounds in continuous-flow column experiments that simulate in situ aquifer conditions has demonstrated the potential for using indigenous microbial communities to remove contaminants from groundwater (i.e., in situ bioremediation). However, a variable that has been largely neglected in these experiments is the physiological state of indigenous bacteria. The morphology and chemical structure of cells recovered from the subsurface and estimates of in situ subsurface microbial activity indicate that the microorganisms are under severe nutrient stress with very low metabolic activity.

FIGURE 5. Hypothesized Pathway for Degradation of Toluene (shown) and Other Methylaromatics by the Subsurface Bacterium F199. The initial attack is a direct dioxygenation of the aromatic nucleus to a *cis*-dihydrodiol, which undergoes dehydrogenation to 3-methylcatechol, which subsequently undergoes *meta* ring fission via catechol dioxygenase.

FIGURE 6. Hypothesized Pathway for *p*-cresol Degradation by F199. In this pathway, the initial attack is on the methyl group oxidizing *p*-cresol to *p*-hydroxybenzoate, which is further oxidized to protocatechuic acid. 4-methylcatechol is also oxidized by *p*-cresol-induced cells by *meta* ring cleavage, but products are not generated.

To simulate the suite of physiological stresses experienced by bacteria existing in the environment, cells of a subsurface bacterium able to degrade quinoline were grown under nutrient limitation prior to starvation. The use of succinate as a sole carbon source, an oxidized form of nitrogen (NO_3^-), and nitrogen-limited growth conditions (200:1 carbon to nitrogen ratio) resulted in sub-optimal growth, as indicated by a 59% smaller cell size compared with cells grown on 10% tryptic soy broth. Cells were then starved for 2 days or for 60 to 80 days. Sterile glass beads (100 to 150 μm diameter) were inoculated to obtain a final density of 10^8 colony-forming units g^{-1} glass beads.

Inoculated beads were packed in glass chromatography columns and constrained to a length of 1.0 cm with 60- μm filters. Experiments designed to check bacterial adhesion under the conditions described below showed that less than 0.001% of the bacterial inoculum was eluted from the column.

The performances of continuous-flow columns containing long-term (60- to 80-day) and short-term (2-day) starved bacterial cultures were compared. For both short-term starved (STS) and long-term starved (LTS) cells, three replicate experiments were performed at 39- μM , 155- μM ,

and 775- μ M quinoline influent concentrations. The induction response and the initial two reactions of quinoline degradation were examined to better understand how long-term starvation affects the ability of a bacterial culture to respond to the appearance of a recalcitrant biodegradable substrate, and the efficiency by which the culture processes quinoline through the initial, non-energy-yielding reactions. The time required for induction of a biodegradative pathway can be conceptualized as a measure of the ability of the bacteria to realign their physiology (i.e., regulation and production of the appropriate macromolecules) in response to an environment containing a usable carbon and energy source. The time from induction to steady-state degradation can be conceptualized as the time required for the bacteria to come into a physiological equilibrium with this environment. The maximum rate of change in the concentration of the initial substrate and metabolites can be conceptualized (as a first approximation) as the cellular concentration and/or activity of the appropriate enzyme(s).

LTS cells required significantly ($P=0.01$) more time to induce than STS cells did at all quinoline input concentrations (Figure 7). For LTS cells, time to induction increased with increasing quinoline concentration; however, quinoline concentration did

not have a marked effect on induction time for STS cells. Thus, the longer times to induction in LTS cells (relative to STS cells) were the result of starvation and, as concentration increased, inhibition by higher quinoline concentrations.

LTS cells progressed from induction to steady state at 39- μ M quinoline in a significantly ($P=0.02$) shorter time than did STS cells (Figure 8). The relationship was reversed at 775- μ M quinoline: the time from induction to steady state was significantly ($P=0.01$) longer for LTS cells than for STS cells. For LTS cells, time from induction to steady state increased with increasing quinoline concentration; however, quinoline concentration did not have a marked effect on time from induction to steady state for STS cells. Thus, LTS cells were more efficient than were STS cells at exploiting available substrate at low quinoline concentrations, but the efficiency decreased markedly in LTS cells as quinoline concentration increased.

At 39- μ M quinoline, only "other metabolites" [those metabolites beyond 2-hydroxyquinoline (2OHQ)] were present in the effluent at steady state (Figure 9). The maximum rate of change of the 2OHQ concentration in the effluent was significantly ($P=0.02$) greater for LTS cells than for STS cells at 39- μ M quinoline (Table 4). The greater

FIGURE 7. Time Required to Induce Quinoline Degradation. Asterisk denotes statistically significant difference between LTS and STS cells.

FIGURE 8. Time Required to Progress from Induction to Steady-State Degradation. Asterisk denotes statistically significant difference between LTS and STS cells.

FIGURE 9. Constituents in the Column Effluent at Steady-State Degradation. Constituents are shown as the average percent and the corresponding concentration (standard deviation).

TABLE 4. Maximum Rate of Change of Effluent Constituent Concentrations During the Progression from Induction to Steady-State Degradation

Concentration, Cell Type	Quinoline nmol mL ⁻¹ h ⁻¹ (average, sigma)	2OHQ nmol mL ⁻¹ h ⁻¹ (average, sigma)	Other nmol mL ⁻¹ h ⁻¹ (average, sigma)
39 μ M, STS	-1.25, 0.38	0.39, 0.09	1.30
39 μ M, LTS	-1.68, 0.83	1.10, 0.50	1.55
155 μ M, STS	-3.56, 0.85	3.34, 1.02	0.83
155 μ M, LTS	-3.02, 0.95	1.47, 0.79	1.33
775 μ M, STS	-3.50, 0.83	2.83, 0.88	2.5
775 μ M, LTS	-2.99, 0.74	2.31, 0.72	0.4

rate of change in 2OHQ in LTS cells resulted partly from the more rapid progression from induction to steady state in LTS cells and partly from an apparent delay in synthesis (or activity) of proteins that allow for transformation of 2OHQ to other metabolites during this progression. However, as discussed above, even with this delay the time from induction to steady-state degradation was more rapid than in STS cells.

At 155- μ M quinoline, the concentration of other metabolites in the effluent at steady state was significantly ($P=0.01$) greater for LTS cells than for STS cells (see Figure 9). The maximum rate of change of the 2OHQ concentration in the effluent was significantly ($P=0.02$) smaller for LTS cells than for STS cells at 155- μ M quinoline (see Table 4). The maximum rate of change of the concentration of other metabolites in the effluent was 60% higher for LTS cells than for STS cells. These three observations indicate that LTS cells were more efficient than were STS cells in regard to producing optimal enzyme concentrations (or activities) to maximize the flow of substrate through the initial two non-energy-yielding reactions.

At 775- μ M quinoline, quinoline was the major constituent in the effluent, and effluent constituents at steady state were similar for LTS and STS cells (see Figure 9). The maximum rate of change of the concentration of other metabolites in the effluent of columns containing LTS cells was only 16% that of columns containing STS cells (see Table 4). This difference is explained by the fact that LTS cells were able to only slowly increase

rates of production of other metabolites throughout much of the progression to steady state, whereas STS cells rapidly produced other metabolites beginning relatively quickly after induction. The different response of LTS cells versus STS cells during the progression from induction to steady state at high quinoline concentrations may be due to either greater cellular toxicity or a different strategy of enzyme regulation that is not related to toxicity.

In summary, at 39- μ M quinoline, LTS cells required more time than did STS cells to respond to the environment and mobilize cell reserves to synthesize enzymes. However, after induction was initiated, LTS cells exploited the available carbon and energy source and reached steady-state degradation more quickly than did STS cells. At 155- μ M and 775- μ M quinoline, LTS cells took approximately three to four times longer than did LTS or STS cells at 39- μ M quinoline to respond to the environment and mobilize cell reserves to synthesize enzymes, indicating that inhibition/toxicity was occurring as a result of the higher quinoline concentration. However, after induction was initiated, LTS cells at 155- μ M quinoline displayed more efficient processing of substrate through the initial two non-energy-yielding reactions (relative to STS cells at the same quinoline concentration) during the progression to steady state. In contrast, after induction was initiated, LTS cells at 775- μ M quinoline were less capable than were STS cells in processing substrate during the progression to steady state.

The use of cells that have undergone long-term starvation is an important improvement in modeling contaminant biodegradation in column experiments designed to simulate subsurface aquifer conditions. Several conclusions can be inferred from this study relative to in situ biodegradation of environmental contaminants. First, contaminant concentration appears to be very important in controlling the time required for induction of catabolic pathways, the time required from induction to steady-state degradation, and the efficiency of degradation in starved bacteria. Second, bacteria indigenous to the subsurface may initiate more complete or more rapid degradation of a substrate, because of their more depleted

endogenous energy reserves, than is indicated by standard laboratory testing with nonstarved cells. Such degradation could result in lower concentrations of metabolites that may be toxic themselves. Finally, characteristics of in situ contaminant degradation must be carefully studied under conditions that closely simulate the physiological state of bacteria in the environment to construct successful predictive models of biodegradation in subsurface environments.

Optimization of Growth Medium for Subsurface Microorganisms

Viable plate-count techniques to enumerate microorganisms in environmental samples suffer from inherent selectivity that results from the choice of culture medium and conditions. Microbiologists have long noted the discrepancy between the population size of microorganisms that can be determined by direct microscopic observation and the population size as determined by viable plate-count techniques. Microorganisms in deep subsurface core samples studied in the Subsurface Science Program appear to be no exception.

The phenomenon of nonculturability can be expressed as a recovery ratio (culturable population g^{-1} /direct microscopic counts g^{-1}). A decrease in the recovery ratio from 1 can be attributed to two general factors: 1) the inherent inability of cells (e.g., because they are stressed or nonviable) to form visible colonies on agar and 2) inappropriate culture conditions. It is an axiom of microbiology that *all* culture media are selective. Many well-characterized heterotrophic microorganisms can regulate their interior environments to allow for growth under a range of nutrient regimes. However, the range of conditions that allow for growth of subsurface microorganisms is not well known. While recognizing that a universal medium is not likely to be attainable, we believe that maximizing the recovery ratio is possible by identifying one or more sets of optimal culture conditions for heterotrophic subsurface bacteria.

The first phase of the study was a screening process to identify variables that had a significant effect on plate-count numbers (Table 5). Differences in these effects between different subsurface samples, as well as between subsurface and surface samples, were determined. A Plackett-Burman experimental design was used to test the

effect of 12 different variables with a reduced set of treatments. Although this method was not capable of distinguishing possible confounding two-factor interactions, it allowed the experiment to be repeated with a number of different samples. The purpose of this technique was to determine whether subsurface microorganisms had significantly different nutritional requirements than did surface soil microorganisms, and whether a medium optimized for organisms at one particular site would be of any use for enumerating microorganisms at other subsurface sites.

The second phase of the study will be a surface response experiment to determine optimal levels of the significant variables identified in phase one. Community richness parameters will also be determined by analyzing isolated colonies with the Microbial Identification, Inc. (MIDI) microbial identification system. This analysis will show whether the response to changing media formulations is purely numerical or whether it is qualitative as well. These data could reveal more than one optimal formulation.

Results to date have identified a number of supplements that significantly increase recovery of subsurface microorganisms, including B-group vitamins and compounds that scavenge toxic forms of oxygen. In contrast, varying concentrations of carbon and nitrogen sources had little effect. Decreasing the water potential of the media had a significant negative effect.

This project was able to provide laboratory research experience for two undergraduate students participating in the DOE Environmental Management Career Opportunities Research Experience (EMCORE) and Northwest Colleges and Universities Association for Science (NORCUS) programs.

Future Directions

In FY 1992, Deep Subsurface Microbiology Subprogram research will focus on completing drilling into the saturated zone at the Yakima Barricade on the Hanford Site to explore hypotheses pertaining to the spatial distributions of microbial, geochemical, and geophysical properties with depths. Research will also continue on vadose zone microbiology, for which there is currently a lack of information. These studies will

TABLE 5. Variables in Medium Optimization Experiment, Phase One and Preliminary Results

Variable	High Value	Low Value	Rationale for Variable	Significance Level
Complex concentration ^(a)	2 g	0.2 g	effect of complex nutrients	0.2
Glucose concentration	1 g	0.1 g	a typical sugar substrate	0
Fatty acid concentration ^(b)	1 mM	100 μ M	a different trophic level of substrate	0.5
B vitamin addition	+	-	stimulate numerous metabolic pathways	0.9
Ammonium chloride	1 g	0.1 g	inorganic nitrogen source	0.5
Glutamate	1 g	0.1 g	organic nitrogen source	0.4
Toxox scavs ^(c)	+	-	relieve O ₂ toxicity in agar plates	0.99
pH	6.5	7.5	optima for subsurface unknown	0.8
Water potential	0.94	1	subsurface environment may be low	(0.95) ^(d)
Temperature	20°C	30°C	optima for subsurface unknown	0.5
Plate technique	pour	spread	different diffusional environments	0.2
Trace minerals	+	-	cofactors for various enzymes	0.5

(a) Mixture of peptone, tryptone, and yeast extract.

(b) Pyruvate, lactate, and acetate.

(c) Compounds to scavenge toxic oxygen forms (e.g., charcoal).

(d) Parentheses signify negative effect.

emphasize identification of mechanisms controlling the increase in microbial populations and activities following sampling of vadose zone sediments. If the mechanisms promoting increases in in situ microbial activity in the vadose zone can be ascertained, the information may be useful for predicting how microbial activities may change during recharge events or during in situ bioremediation. Finally, research on the microbiology and geochemistry of the deep confined aquifers on the Hanford Site will continue, focusing on mechanisms of microbial Fe(III) reduction at high pH and on the distribution of phylogenetic groups in Hanford Site confined aquifers using 16S rRNA-targeted DNA signature probes.

Research in the Biodegradation/Microbial Physiology Subprogram area will continue to concentrate on microbial-chemical-physical processes that influence contaminant fate in the subsurface, but the emphasis will be changed from aromatic compounds to metal- and radionuclide-organic complexes. Organic acids such as citrate, oxalate, and propionate are readily metabolized by numerous microorganisms, but

much less is known of the fate of these organic acids and their metal and radionuclide complexes in vadose zone and saturated subsurface sediments. Also, these ligands can form various complexes on the surfaces of minerals that may radically alter their availability for microbial degradation. Joint experimentation with the PNL subsurface chemistry project will investigate the influence of sorption of these complexes on biodegradation of these organic acids and metal-organic complexes.

References

- Bjornstad, B. N., and K. R. Fecht. 1989. "Pre-Wisconsin Glacial-Outburst Floods: Pedogenic and Paleomagnetic Evidence from the Pasco Basin and Adjacent Channeled Scabland." *Geological Society of America, Abstracts with Programs*, p. 58. Spokane, Washington.
- DOE. 1988. *Consultation Draft, Site Characterization Plan, Reference Repository Location, Hanford Site, Washington*. DOE/RW-0164, Vol. 1, U.S. Department of Energy, Washington, D.C.

Microbial Sequestration and Bioaccumulation of Radionuclides and Metals

H. Bolton, Jr.

Contributor

A. Summers (University of Georgia)

In the past, inorganic contaminants, including radionuclides and toxic metals, were disposed at DOE sites. In some instances, these inorganic contaminants migrated into the subsurface environment and may migrate farther to contaminate domestic groundwater supplies. Currently, economic approaches to remediate or stabilize these deep contaminated zones are limited because there is a lack of understanding of the geochemical and biological factors that affect these wastes. Radionuclide and metal inorganic wastes must be either immobilized before further subsurface migration occurs or removed from the contaminated subsurface environment by pumping and surface treatment. These pump-and-treat technologies are costly and not always feasible for deep sediments with limited accessibility. One promising process for radionuclide and metal immobilization is bioimmobilization or bioaccumulation of radionuclides and metals by subsurface microorganisms.

Bioaccumulation is a specific microbial sequestering mechanism where mobile radionuclides and metals become associated with the microbial biomass with both intra- and extracellular sequestering ligands. In laboratory studies, microorganisms have been shown to bioaccumulate a wide range of radionuclides, including cesium, cobalt, plutonium, thorium, and uranium. Also, there have been numerous studies on the microbial bioaccumulation of various metals. Microorganisms can also promote the formation of minerals and metal precipitates. Radionuclides and metals can accumulate either intra- or extracellularly in association with various components of the cell wall or exopolymers (capsules or slime layers).

Because most of the microorganisms in the subsurface are associated with stationary strata, bioaccumulation of mobile radionuclides and metals would initially result in a decrease in

inorganic waste transport; however, the information on this microbially mediated process is limited. How long the inorganic wastes would remain immobilized, the selectivity of the bioaccumulation process for specific inorganic wastes, the mechanisms involved, and how the geochemistry and growth conditions of the subsurface environment influence bioaccumulation are not currently known. By stimulating the growth and activity of subsurface microorganisms, the transport of radionuclides and metals in subsurface environments may be effectively reduced because of bioaccumulation. Although subsurface microorganisms may be able to reduce radionuclide and metal transport, these contaminants may be subsequently remobilized as the microorganisms are starved and/or degraded. Therefore, this research is determining the selectivity of the bioaccumulation process for specific metals, the mechanisms and kinetics of bioaccumulation and any remobilization of inorganic wastes during growth and starvation, the maintenance requirements (carbon, electron acceptors, and nutrients) to prevent remobilization, and the influence of varied geochemical conditions on these processes.

Prior to this project, there had been limited information on the ability of subsurface microorganisms to immobilize inorganic contaminants. The goal of our research this first year was to determine inorganic contaminant bioaccumulation by a wide variety of subsurface microbial isolates during cellular resting stage and to start testing two hypotheses. The first hypothesis tested was that subsurface microorganisms have developed unique processes to sequester and bioaccumulate radionuclides and metals. The subsurface environment can be low in nutrients (i.e., oligotrophic), and essential nutrients may be concentrated by subsurface microorganisms. Select radionuclides and metals would be analogues of these nutrient elements and would also be bioaccumulated. Also, subsurface microorganisms may have developed general, nonspecific sequestering mechanisms that allow bioaccumulation of both nutrients and inorganic contaminants.

The second hypothesis tested in FY 1991 was that gram-positive and gram-negative subsurface microorganisms would have different abilities to

bioaccumulate inorganic contaminants. The eubacteria can be divided into two main cell wall types, distinguished by the Gram stain to be either gram-positive or gram-negative. It is convenient to study these two cell wall types because they have different mechanisms to biosorb radionuclides and metals. Gram-positive walls usually contain large amounts of peptidoglycan and anionic polymers such as teichoic or teichuronic acid. The negatively charged sites are predominantly carboxylate and phosphate from peptidoglycan and teichoic-teichuronic acids. In some instances, the amount of metal biosorbed by the cell wall was greater than the charge density would suggest. It has been hypothesized that there is a two-stage process in which the metal interacts with the charges moieties on the cell wall followed by the deposition of more metal using the initially bound metal as a nucleation site. The cell walls of gram-negative bacteria are distinctly different from gram-positive bacteria, with gram-negative bacteria having an outer membrane consisting of lipids and proteins outside of the peptidoglycan layer. The hydrophilic groups of the lipids, which contain carboxylate and phosphate groups, are located on the outside of the membrane in contact with the external solution, and metal binding to these groups is necessary and actually stabilizes the cell membrane. The most abundant metal-binding sites on the cell membrane are the phosphate groups of the lipopolysaccharides and phospholipids.

Microorganisms used in these studies were isolated (as part of the Subsurface Science Program, Deep Subsurface Microbiology Subprogram) from sediments obtained from boreholes drilled at the Idaho National Engineering Laboratory (INEL) (37 strains), the Hanford Site (68 strains), and the Savannah River Site (48 strains). Bacterial isolates from INEL and Hanford boreholes were chosen for study, based on isolate purity and Gram stain, and to provide isolates from a wide variety of geologic formations and depths. Bacterial isolates from Savannah River borehole P24 were selected based on discussions with Dr. David Balkwill at Florida State University (curator of the Subsurface Microbial Culture Collection) and included isolates from various geologic formations that also varied in Gram stain, C utilization, and cluster analysis. Some of these same isolates from Savannah River were also analyzed by Dr. Anne Summers for their

resistance to various metals. To determine whether subsurface microorganisms might have unique properties and processes related to radionuclide/metal uptake bioaccumulation, we also included *Escherichia coli* K12 (AB264) and *Bacillus subtilis* 168 from Dr. Terry Beveridge (University of Guelph, Guelph, Ontario); these microbial isolates, well characterized for metal uptake, are gram-negative and gram-positive, respectively.

We selected four elements to investigate radionuclide and metal bioaccumulation, including ^{109}Cd , ^{57}Co , ^{63}Ni , and $^{85,90}\text{Sr}$. These metals have different specificities for ligand-binding sites: Sr prefers N and O, Cd prefers P and S, and Co and Ni are not quite as selective. The use of these metals with different specificities for ligand-binding sites would provide an initial indication of the possible dominant ligands associated with subsurface microorganisms. Microorganisms were all grown on the same medium [peptone-trypticase-yeast extract-glucose (PTYG) plates], rinsed off the plates, washed several times, and suspended in 0.001 M Piperazine-N,N'-bis[2-ethane-sulfonic acid] (PIPES) buffer at pH 6. PIPES is a pH buffer with very low metal complexation capability. The cell suspensions were adjusted to the same absorbance, so cell density in the suspensions was similar for the various strains. The cells were stored overnight in PIPES buffer with no C source to ensure that resting cells were used in our assays. Aqueous speciation modeling of our experimental system ensured that the metals used in these studies were present as the free metal ion with a valance of two. Because of the limits on metal solubility and possible toxic effects from the metals, our initial experiments were all conducted at 1- μM metal concentrations.

Initial experiments with some of the Savannah River microbial isolates demonstrated that traditional approaches to quantifying metal uptake by microorganisms (i.e., shaking and filtering cells through a 47-mm filter or removing cells via centrifugation) were too time consuming. We were unsure how long it would take for metal uptake (i.e., bioaccumulation) by resting cells to reach an equilibrium value, so we conducted our experiments over several sampling times. A novel approach was developed to screen for metal bioaccumulation and it worked so well in the initial

screening that it is currently being used and will be used in the later phases of the project. This approach used a 96-well microtiter plate format (12 wells by 8 wells), where the cells and metal solutions were mixed in 2-mL tubes arrayed in a 96-well format and were then shaken. At specific sampling times, the solution in the tubes containing the cells and metals was transferred to a 96-well filtration unit containing 96 0.22- μ m filters. A vacuum was applied to remove the solution, the cells trapped on the filter were washed two times with PIPES buffer, and the filters were punched out and assayed for radioactivity to determine metal uptake by the cells.

Results indicated that subsurface strains varied in the time required for maximum metal uptake or the time it took to reach a steady-state condition. Strains also had different patterns of metal bioaccumulation, with some strains having an increase in metal uptake as a function of time while others had no change or a decrease in metal associated with the cell as a function of time (during 24 hours). The screening of all strains for metal uptake was, therefore, conducted with several sampling times (1, 4, 8, and 24 hours), rather than a one-point sampling as originally planned. Examples of the patterns of metal bioaccumulation are presented in Figure 1 for Ni, Co, Cd, and Sr. *Escherichia coli* K12 (AB264) and *Bacillus subtilis* 168 are well-characterized surface isolates included for comparison that are gram-negative and gram-positive, respectively. Strains B69 and G8-013 are gram-negative, while strain G8-042 is gram-positive.

For the strains included in Figure 1 for the various metals and for most of the strains assayed, there was a rapid association of the metals with the cells. Some strains had a decrease in metal associated with the cell as a function of time (e.g., G8-013 and *B. subtilis* with Co and Ni), others had an increase (e.g., G8-042 with Ni and Cd), while others had no change (e.g., B69 with Ni and Co; G8-042 with Sr). Some of the Savannah River isolates, which were resistant to the metals (Dr. Summers' data), had a decrease in cell-associated metal as a function of time. One mechanism of metal resistance is the efflux of metal out of the cell. Our data would indicate that these resistant strains may in fact be using an efflux mechanism. Experiments planned for

FIGURE 1. Metal Bioaccumulation by Subsurface Microorganisms (B69, G8-013, and G8-042) and Surface Bacteria [*Escherichia coli* K12 (AB264) and *Bacillus subtilis* 168]. Bioaccumulation is presented as the percent of the total metal added that was associated with cells. Metals were present at 1- μ M concentration in 0.001 M PIPES buffer at pH 6. Bacteria were present at the same density in all assays.

FY 1992 will test this hypothesis. Some strains from both Hanford and INEL also decreased in cell-associated metal as a function of time. These strains will be sent to Dr. Summers to determine whether they are metal resistant.

All the strains (147 total) were used to determine the relationship between preference for metals tested, influence of Gram strain on the ability to bioaccumulate metal, and influence of the location (i.e., INEL, Hanford, Savannah River) or the geologic formation from which the strains were initially isolated. Data analysis indicates the strains had a preference for the metals in the following order: $Cd > Ni + Co > Sr$ for all three locations (Figure 2). The maximum amounts of metal bioaccumulated by select strains after 4 hours were 82%, 68%, 59%, and 42% of a $1\text{-}\mu\text{M}$ metal solution of Cd, Ni, Co, and Sr, respectively. The minimum amount of metal bioaccumulated by select strains was $<1\%$ for all metals. This demonstrated the wide range in the ability of subsurface microorganisms in a resting physiological stage to bioaccumulate metals. There was no difference in metal bioaccumulation by two distinct microbial cell wall types (i.e., gram-positive and gram-negative) when all the strains for the various locations were analyzed together. This disproved our hypothesis that gram-positive and gram-negative subsurface microorganisms would have different abilities to bioaccumulate inorganic contaminants. However, our assay was conducted with only resting cells. We will determine in FY 1992 whether there is a difference between gram-negative and gram-positive strains for metal bioaccumulation during active metabolism or starvation. There were some significant differences among locations for metal bioaccumulation after 4 hours when all the strains from the three locations were statistically analyzed together (see Figure 2). Co and Ni uptake was significantly higher ($p < 0.1$ and $p < 0.05$, respectively) for strains from Hanford than INEL. Strains from Hanford and Savannah River had the same mean values of Co and Ni uptake. For Cd uptake, isolates from Hanford were significantly higher ($p < 0.001$) than Savannah River or INEL. Savannah River and INEL isolates had the same mean value for Cd uptake. Savannah River isolates had greater Sr uptake than INEL but the same as Hanford. Hanford isolates were the same as INEL for Sr uptake. The reason for the

FIGURE 2. Average Values of Cobalt, Nickel, Cadmium, and Strontium Bioaccumulation by Subsurface Microbial Isolates from the Various Subsurface Locations. Averages are computed from 68, 48, and 37 microbial isolates from Hanford, Savannah River, and INEL sites, respectively. Bioaccumulation is presented as the percent of the total metal added that was associated with cells. Metals were present at $1\text{-}\mu\text{M}$ concentration in 0.001 M PIPES buffer at pH 6. Bacteria were present at the same density in all assays.

differences among the three different subsurface sites for metal bioaccumulation is not currently known. The results shown in Figure 2 should be interpreted with caution because in some of the specific geologic formations at these three locations, the variation in the ability of isolates to bioaccumulate metals, which were isolated from the same formation, was greater than the variation between locations. This demonstrates that the ability of subsurface microorganisms to bioaccumulate metals can be very heterogeneous in relation to both geologic formation (and even within the same sediment sample) and location across the United States.

Future Research

A subset of the strains used in the screening has been selected for more in-depth studies in FY 1992 on bioaccumulation by metabolically active cells (C source added) and by metabolically inhibited cells (sodium azide and/or nitrophenol added). This will differentiate the portion of bioaccumulation caused by active uptake (requires cellular metabolism) versus passive processes (no metabolic activity required). This

same subset will also be starved 30 to 60 days both before and after exposure to the metals to determine how starvation influences the prebound metal and the microorganisms' ability to bind metal after starvation. A subset of these cultures will be used to determine whether the presence of the inorganic contaminant during growth enhances radionuclide or metal bioaccumulation or the production of aqueous sequestering ligands under both traditional (nutrients nonlimiting) and oligotrophic (low C and nutrients) growing conditions.

Metals-contaminated sediment located at the Hanford Site's 300 Area processing pond will be sampled in collaboration with the Chemical Desorption, Dissolution, and Partitioning project described previously. These sediments will offer an environment where microorganisms have been exposed to select metals for many years. The hypothesis to be tested is that metal exposure will result in altered abilities of microorganisms to bioaccumulate radionuclides and metals.

Improving the Biodegradative Capacity of Subsurface Bacteria

F. J. Brockman and M. F. Romine

Contributor

R. L. Ornstein

Subsurface environments have been contaminated with large volumes of complex mixtures that are commonly dilute, highly dispersed, and inaccessible. Metabolically active and diverse microbial populations have been found in deep subsurface environments, suggesting that the indigenous microflora may be exploited to assist in the degradation or immobilization of subsurface contaminants. However, the biological degradation of contaminants in the subsurface can be limited by a number of factors, including:

- Several catabolic enzymes require induction by compounds that are toxic or are not commonly present in subsurface sediments and aquifers.
- Bacteria that degrade a specific contaminant may require a specific set of environmental conditions to survive or to produce the enzyme.

Thus, appropriate bacteria may not be present in many sediments or may occur in populations so small that adequate removal of the contaminant will not occur.

- Extant catabolic pathways in subsurface bacteria able to degrade specific contaminants may have very low throughput, so that timely removal of compounds is not adequate from an environmental perspective.
- Some compounds may be extremely recalcitrant, and their degradation may require extensive evolution of one or many enzymes. Specific degradative enzymes may not have evolved or been selected for in the subsurface because of very slow generation times resulting from nutrient limitation. In addition, the ability to survive and function in the presence of complex mixtures of contaminants may require co-evolution of multiple traits.
- Large-scale inoculation of contaminated aquifers with bacteria able to degrade the contaminant of interest may be a means to achieve in situ degradation. However, survival and/or sustained enzymatic activity of bacteria inoculated in new environments is often poor.

An attractive solution to these problems is to introduce appropriate biodegradative genes (from other bacterial sources) into bacteria that are native to specific subsurface strata or environments. Useful traits could include the ability to degrade specific contaminants; the ability to bioaccumulate heavy metals and radionuclides (thus attenuating their transport); or resistance to heavy metals, radioactive fields, or pH conditions. The advantage of this approach is that indigenous bacteria are adapted to the groundwater, solid-phase chemistry, and oligotrophic conditions, and thus are more likely to survive and express the novel gene(s) in the subsurface environment. In addition, the regulation of enzyme production can be modified by genetic engineering to enable expression of degradation in a variety of conditions. The objective of this research is to 1) expand the degradative capacity of indigenous subsurface bacteria by genetic engineering for the purpose of extending their substrate range or improving their efficiency at degrading DOE-site

contaminants and 2) determine the ability of engineered subsurface bacteria to survive and function in a variety of simulated subsurface environments.

Genetic Approach to Engineering Subsurface Bacteria

We have identified plasmid vectors that allow for the introduction and expression of recruited enzymes in subsurface bacteria. We initially tested the mobilizable, broad host-range, incompatibility group Q plasmid vectors pKT230, pNM185, and pMMB66 in a variety of bacteria isolated from the subsurface at DOE's Savannah River Site under the auspices of the Subsurface Science Program, Deep Subsurface Microbiology Subprogram. pKT230 contains a constitutive promoter, which drives expression of a streptomycin resistance gene. pNM185 contains the *xytS* activator protein and the *Pseudomonas Pm* promoter, which drives expression of a kanamycin resistance gene in the presence of the inducer benzoate. pMMB66 contains the *lacIq* repressor protein and the *Escherichia coli tac* promoter, which drives expression of an ampicillin resistance gene in the presence of the gratuitous inducer IPTG. All three promoters are known to be active in a very broad range of bacterial types. Tri-parental matings using the mobilizing plasmid pRK2013 were used to transfer vectors to subsurface bacterial recipient strains. Gram-negative recipient strains included 8 isolates identified as *Pseudomonas* species and 11 isolates of unknown taxonomy. The ability of the vector to be mobilized to and maintained in these strains and the ability of the promoter to drive high levels of transcription of downstream genes were assayed by testing for growth of recipient strains on high concentrations of antibiotic (and inducer where appropriate). Preliminary results show that 3 of the 8 *Pseudomonas* isolates and 2 of the 11 other isolates were able to receive an incompatibility group Q vector and drive high levels of transcription from the constitutive pKT230, the *Pm*, or the *tac* promoter. Thus, these vectors will enable the introduction and regulatable expression of recruited enzymes in subsurface bacteria from the Savannah River Site, one of several locations in which metabolically active microbial populations have been found in the deep subsurface.

Toluene dioxygenase and toluene-4-monooxygenase, which cometabolically dechlorinate trichloroethylene (TCE) in the presence of the inducer toluene, were selected as the initial model systems for enzyme recruitment. Both enzymes are being investigated because the chemistries of the reactions are different, and inhibition of bacterial growth and activity varies depending on the bacterial type. Because toluene, which is toxic to humans, cannot be injected into groundwater, the requirement for induction is a severe limitation to the application of these bacteria for the degradation of TCE. Therefore, we are altering the regulation of the cloned genes by placing them under the control of a different regulatable promoter whose inducer is known and can be used in the environment (e.g., the *Pm* promoter, induced by benzoate). Thus, production of the enzyme has been uncoupled from the requirement for the original toxic inducer, enabling the cometabolic reaction to be expressed under a wide variety of environmental conditions.

The DNA encoding the *Pseudomonas mendocina* toluene-4-monooxygenase genes (*tmoABCDE*) and the *Pseudomonas putida* toluene dioxygenase genes (*todC1C2BA*) has been cloned into the pMMB66EH and pNM185 vectors as follows.

Plasmid pMY402 (Figure 1) was constructed by inserting a genomic 4.7-kb *XhoI* fragment, containing the *tmoABCDE* genes, into the unique *Sall* site of pMMB66EH.

Plasmid pMR404 (Figure 2) was constructed in two steps. The 4.4-kb *EcoRI-SspI* fragment encoding the *tmoABCDE* genes was removed from pMY402 and inserted into the *EcoRI-SmaI* sites of pBCSK+ to generate pMR403. The *tmoABCDE* genes were then removed as an *EcoRI-SstI* fragment from pMR403 and inserted into the *EcoRI-SstI* sites of pNM185 to generate pMR404.

The *todC1C2BA* genes were removed from pDTG601 as a 4.0-kb *EcoRI-BamHI* fragment and inserted into the *EcoRI-BamHI* sites of pMMB66EH to generate pMR601 (Figure 3).

Plasmid pMR604 (Figure 4) was constructed in the following manner. The unique *SstI* site in pMR601

FIGURE 1. Toluene-4-Monooxygenase Genes Under the Control of the *tac* Promoter and the *lacIq* Repressor Protein in the Vector pMMB66EH. Arrow shows direction of transcription.

FIGURE 3. Toluene Dioxygenase Genes Under the Control of the *tac* Promoter and the *lacIq* Repressor Protein in the Vector pMMB66EH. Arrow shows direction of transcription.

FIGURE 2. Toluene-4-Monooxygenase Genes Under the Control of the *Pm* Promoter and the *xylS* Activator Protein in the Vector pMM185. Arrow shows direction of transcription.

FIGURE 4. Toluene Dioxygenase Genes Under the Control of the *Pm* Promoter and the *xylS* Activator Protein in the Vector pMM185. Arrow shows direction of transcription.

was eliminated by digesting with *SstI*, creating blunt ends with T4 polymerase, and re-ligating the ends to generate pMR602. The 4.0-kb *EcoRI*-*BamHI* fragment of pMR602 containing the *todC1C2BA* genes was inserted into the *EcoRI*-*BamHI* sites of pBCSK+ to generate pMR603. The *todC1C2BA* genes were then removed as an *EcoRI*-*SstI* fragment and inserted into the *EcoRI*-*SstI* sites of pNM185 to generate pMR604.

The pMMB66EH and pNM185 vectors will also be used to place the *tmoABCDE* and *todC1C2BA* genes under the control of a third promoter that is inducible under nutrient deprivation and other chemical and physical stress.

Future Activities

Future research will be directed toward:

- introduction, via tri-parental mating or electroporation, of the above recombinant plasmids into subsurface bacteria from the Savannah River Site, the Idaho National Engineering Laboratory, and the Hanford Site
- quantitation of toluene and TCE degradation by recombinant bacterial cultures
- quantitation of toluene and TCE degradation by recombinant bacteria under simulated subsurface environmental conditions with hydrodynamic flow in sterile artificial porous media and in sterile subsurface sediments and groundwater - Nutrient conditions and contaminant concentrations representative of those used/encountered in in situ bioremediation will be simulated.
- quantitation of toluene and TCE degradation by recombinant bacteria, and survival of recombinant bacteria, under simulated subsurface environmental conditions with hydrodynamic flow and additional parameters such as nutrient deprivation and competition with indigenous microbiota (i.e., nonsterile subsurface sediments and groundwater) - Nutrient conditions and contaminant concentrations representative of those used/encountered in in situ bioremediation will be simulated.
- chromosomal integration of the degradative genes and regulatory system to stabilize the genes and to determine the effect of gene copy number on the level of degradative activity
- experimentation in larger intermediate-scale flow cells in the PNL Subsurface Environmental Research Facility to provide the basis for quantifying induction, degradation, and transport that occur dynamically and interactively.

This project is currently associated with Dr. R. L. Ornstein's rational enzyme design project (see Contents), which is using molecular modeling and simulations to modify the biodegradative enzyme P450cam for activity against halogenated hydrocarbons and other contaminants at DOE sites. Following discovery of putative novel enzyme activity by P450cam based on molecular modeling and simulations, derivative genes will be constructed and the derivative enzyme expressed.

If the redesigned P450 enzyme is active against the targeted contaminant in vitro, the genes will be subcloned into a vector as discussed above and will be introduced into subsurface bacteria to assay in vivo activity.

While cloning of catabolic genes and their expression in laboratory systems is common, a void exists in the application of these methods to remediation problems, largely because of regulatory issues and the problem of maintaining survival and functioning of nonindigenous organisms in poorly understood and oligotrophic subsurface environments. This research is expected to provide important information on the potential for using engineered subsurface bacteria for improving the degradation of contaminants in situ.

Hydrogeologic and Geochemical Controls on Microorganisms in Subsurface Formations

P. E. Long, S. A. Rawson, E. M. Murphy, and B. N. Bjornstad

Contributors

J. Fredrickson, F. Brockman, S. Birnbaum (University of Texas—San Antonio), C. Bishop (INEL), R. Colwell (INEL), J. McKinley, S. McKinley, T. Stevens, J. Szescody, and S. Phillips (Westinghouse Hanford Company)

Ongoing studies continue to demonstrate that the occurrence, numbers, and diversity of microbial communities found in geologically distinct subsurface environments beneath several DOE sites vary significantly, apparently as a function of hydrologic and geochemical parameters. The fundamental hypothesis underlying these studies is that aquifer hydraulic properties, especially permeability and effective porosity, interact with nutrient type and availability as major contributors to subsurface microbial diversity and abundance. The purpose of this project is to determine the hydrogeologic and geochemical factors that are the most important influences on subsurface microbial abundance and diversity. The ultimate goal is to predict the in situ abundance and diversity of microorganisms based on data about the hydrogeologic and geochemical characteristics of a site. Development of a predictive capability will

establish the validity of our understanding of the scientific principles underlying subsurface microbial ecology and will eventually be used to provide information on the suitability of a site for in situ bioremediation.

Background

Earlier studies in Southeast Coastal Plain sediments at DOE's Savannah River Site (SRS) demonstrated the presence of diverse chemoheterotrophic bacteria associated with high-permeability sandy aquifers with a measurable quantity of total organic carbon. Unsaturated and saturated basalts and sediments were collected under sterile conditions during 1990 and 1991 to characterize the subsurface microbial ecology at DOE's Idaho National Engineering Laboratory (INEL) and at DOE's Hanford Site. At Hanford (Figure 1), special protocols have been employed to obtain samples for characterization of indigenous microorganisms from three cable-tooled boreholes, up to 100 m deep, and from three outcrop areas for a total of approximately 30 sample intervals. Most of these samples were fluvial or lacustrine sediments of the Ringold Formation. A few of the samples were sands and gravels from the Pleistocene Hanford formation. Thirteen of the samples were collected from a single borehole dedicated to subsurface microbiology sampling, the Yakima Barricade borehole (Long et al. 1991). This borehole has been completed to a depth of approximately 100 m (the top of the water table). At INEL, sampling was conducted during FY 1990 in a pair of boreholes that penetrated Snake River Plain basalt flows and interbedded eolian sediments.

During FY 1991, analysis of data from the INEL and Hanford samples provided further insight into the most important factors controlling microorganisms in the vadose zone. These data provided direct comparison of microbial abundance and diversity with the hydrogeologic and geochemical characteristics of the samples and extended the range of environments for which in situ microbiological data are available to include DOE sites in the arid west.

Methods

Obtaining microbially representative samples from depths greater than a few meters requires special drilling techniques and careful attention to sample handling. DOE's Subsurface Science Program, through its Drilling and Sampling Technologies Steering Committee, has established minimum requirements for obtaining microbially representative samples. The techniques used are described by Russell et al. (1989) and Long and Rawson (1991), and the drilling and sample handling methods are outlined in the Sample Acquisition subsections for the Hanford and INEL sites below.

Summary of Results from Hanford

Sample Acquisition in the Yakima Barricade Borehole. Thirty-four 0.3- to 0.6-m (1- to 2-ft), 10-cm (4-in.)-diameter core samples were collected via the percussion, cable tool (i.e., split-barrel) drilling method from a 100-m (340-ft)-deep borehole located near the Yakima Barricade on the Hanford Site (see Figure 1; and Figure 1 in Fredrickson et al., this volume). The strategy was to obtain microbial, physical, and chemical samples from a wide distribution of sediment types within the vadose zone and to core as continuously as possible in the vicinity of the water table. The 34 cores were collected from 13 general distribution intervals (GD-1 through GD-14), starting at about 30 m (100 ft). The hole was advanced using a cable tool rig, principally via the core-barrel method without adding any drill fluids, except at two bouldery zones [12 to 18 m (40 to 60 ft) and 76 to 87 m (250 to 285 ft)] where the hard-tool method had to be used. During hard-tool drilling, water was added to the borehole to form a slurry that could be bailed out of the borehole. Lithium bromide tracer was mixed with this water to determine whether this water was infiltrating core samples. The hole was kept open by advancing a continuous string of carbon steel casing during drilling.

To minimize contamination with surface microbes, the split-barrel assembly was sterilized by alcohol flaming before collecting each core sample.

FIGURE 1. Location Map for Sampling Sites at Hanford

Autoclaved plastic liners, used to contain and transport the core samples, were placed inside the split barrel, and the whole assembly was wrapped and sealed in autoclaved paper wrapping until ready to use. Before collection of a core sample, all personnel handling sampling apparatus changed into clean cotton gloves. After the hole was cleaned out with a drive-barrel sampler, several hundred grams of a solid, dry tracer (i.e., a mixture of tungsten carbide, microspheres, and glass beads) was placed at the bottom of the borehole with a bailer. Next, the sterilized split-barrel assembly was lowered into the hole and driven downward via jars attached to the sampler until the split barrel stopped advancing or was full. Upon withdrawal, the split barrel was disassembled and the sediment-filled liner immediately capped with sterilized end caps and placed into a

polyurethane bag. The bag was flushed with argon gas several times, sealed, placed into a cooler on Blue Ice, and transported to the laboratory.

Once at the laboratory, the core sample was immediately transferred through an air lock into a nitrogen-filled glovebox, where the core was opened and subsampled. Subsamples were collected in the glovebox for microbiological, physical, and chemical analyses. Geologic and sampling logs were obtained at this time. Geologic characteristics noted during logging included texture, sorting, moisture content, mineralogy, roundness, consistency (i.e., consolidation), cementation, sedimentary structure, and maximum particle size. The relative amount of CaCO_3 was tested using dilute HCl.

Analytical techniques used included standard methods for particle-size distribution, moisture content, soil water potential, and total organic carbon (TOC), as well as several inorganic chemical constituents (S, P, N, CaCO_3). Mineralogy, hydraulic conductivity, porosity, and bulk density were measured on selected samples. Microbiological measurements included plate counts, acridine-orange direct counts (AODC), mineralization of ^{14}C -labeled compounds, and phospholipid fatty acid (PLFA) analyses.

Scanning electron microscopy (SEM) was used to directly observe microorganism-mineral associations. Basalt cores or sediments (consolidated to unconsolidated) were received in the laboratory within 72 hours of recovery from the borehole. Upon receipt, the cores were aseptically subsampled by removing the outer portions of the core. Specimens were critical-point dried for electron microscopy (i.e., water was miscibly replaced with a graded series of alcohol followed by liquid CO_2). The liquid CO_2 replacement was accomplished using a critical-point drying apparatus where the sample was immersed in liquid CO_2 . The temperature was then raised above the critical temperature for CO_2 , and the sample was dried and stabilized. Samples were coated with a 50/50 gold-palladium coating before viewing with SEM. Energy dispersive x-ray microanalysis was used to identify the elemental composition of features with the morphology of microorganisms.

Hydrogeologic Setting of the Hanford Site. The Hanford Site lies within the Pasco Basin, one of many topographic and structural basins within the Columbia Plateau. The basin is filled with up to 370 m (1200 ft) of unconsolidated to semiconsolidated late-Cenozoic sediments, which overlie Columbia River basalts (Myers/Price et al. 1979; Tallman et al. 1981). Principal geologic units within the Pasco Basin and Hanford Site include, in ascending order, the Columbia River Basalt Group, the Ringold Formation, and a series of glaciofluvial deposits informally referred to as the Hanford formation (see Figure 1 in Fredrickson et al., this volume). The suprabasalt sediments at Hanford are differentiated primarily on the basis of texture, color, natural-gamma log response, and basalt and calcium carbonate content (DOE 1988; Baker et al. 1991). Paleosols, recognized by the

presence of root traces, soil structures, and/or soil horizons (Retallack 1988), are common within the suprabasalt sedimentary sequence.

Within the central Columbia Plateau, emplacement of Columbia River basalt flows was followed by fluvial-lacustrine sedimentation associated with the Miocene-Pliocene Ringold Formation in southcentral Washington (Myers/Price et al. 1979; Smith et al. 1989). The Ringold Formation represents deposits from the ancestral Columbia and Salmon-Clearwater rivers (Fecht et al. 1985) that accumulated in response to basin subsidence during Ringold time (Bjornstad 1985). The youngest basalt flow in the Pasco Basin is the Ice Harbor Member, dated at 8.5 Ma (McKee et al. 1977).

In late-Pliocene time (~3.9 million years ago), deposition of the Ringold Formation ended, followed by an almost 3-million-year hiatus (DOE 1988). During this time, Ringold sediments were incised over most of the Pasco Basin, although some sediments may have accumulated intermittently. Beginning about 1 million years ago (Bjornstad and Fecht 1989), cataclysmic floods eroded farther into the Ringold Formation and blanketed the Hanford Site with flood deposits, locally referred to as the Hanford formation (Myers/Price et al. 1979). Floods occurred when large volumes of water were suddenly released behind ice dams along the northern Columbia Plateau (Waitt 1980; Baker and Bunker 1985). Flood waters, after inundating most of eastern Washington, converged in the Pasco Basin and exited through a single outlet at the southeast end of the basin. The thickest accumulations (up to 60 m) of flood deposits are present along flood bars in the western Pasco Basin. Cataclysmic flood deposits accumulated intermittently until the end of the last ice age, or about 13,000 years ago (Mullineaux et al. 1978). During the Holocene, only localized minor erosion and deposition via alluvial and eolian processes have occurred.

Groundwater in the shallow aquifers within the Pasco Basin is recharged along the surrounding uplands and flows toward the Columbia River. Over much of the Hanford Site, the groundwater in the unconfined aquifer flows from west to east, discharging into the Columbia River. Depths to groundwater vary from a few meters to 130 m

because of the topography within the basin, most notably the arid plateau in the central part of the Hanford Site known as the 200 Areas plateau. This area is several kilometers or more from recharge areas and stands a few hundred feet above the river level.

A dedicated borehole was drilled for microbiological characterization on the extreme western edge of the Hanford Site. This site met several selection criteria: 1) within the boundaries of the Hanford Site, 2) in an uncontaminated natural state, 3) underlain by heterogeneous strata necessary to test several hypotheses on controlling factors of microbial distribution, and 4) near other boreholes needed for geologic control. The Yakima Barricade site lies hydraulically upgradient from the waste management facilities at Hanford. Corehole DH-28, which was drilled in 1983 for the Basalt Waste Isolation Project and lies 300 m to the north, was used for stratigraphic control. Depth to the water table at the Yakima Barricade is 100 m (see Figure 1 in Fredrickson et al., this volume).

Two geologic formations are represented at the Yakima Barricade: the Ringold Formation and the Hanford formation. In other parts of the basin, these formations are differentiated based on mineralogy, consolidation, sorting, and color. The characteristics of the Ringold Formation (significantly older than the Hanford formation) are that it usually shows some consolidated and weathered shades of red and orange (e.g., hues 7.5YR, 10YR), has an arkosic (i.e., quartz and feldspar) matrix, and is better sorted. Compared with the Ringold Formation, the characteristics of the Hanford formation are general unconsolidation (except for cementation associated with calcic soil horizons), higher mafic content, less sorting, and mostly gray colors (e.g., hues 2.5Y, 5Y).

The contact between the Ringold and Hanford formations at the Yakima Barricade was originally uncertain because arkosic (predominantly quartz and feldspar matrix) Ringold-appearing sediments are interbedded with sediments containing a highly basaltic matrix, which is more characteristic of the Hanford formation. Because of this uncertainty, bulk chemical data on samples between the depths of 55 and 72 m (180 and 235 ft) were

examined, and the conclusion was reached that these materials are chemically most similar to those of the Hanford formation. We therefore have interpreted the sediments in the zone between 55 and 72 m (180 and 235 ft) to represent cataclysmic flood deposits with basalt-poor, reworked Ringold sediments incorporated between more mafic strata.

Specific Lithologic Characteristics of Yakima Barricade Borehole. The Ringold Formation is characterized by a coarse-textured, clast-supported, pebble-cobble gravel, often in a matrix of well-sorted, fine-to-medium sand with varying amounts of silt and clay. Most Ringold gravel clasts are rounded to well rounded, and sand particles are angular to subangular. A couple of thin (≤ 1 -m-thick), well-sorted, arkosic sand beds occur near the bottom of the borehole, just below the water table.

Two well-developed paleosols are present at depth in the Ringold Formation. One paleosol [at 84 to 90 m (275 to 295 ft)] is represented by a moderately to strongly consolidated, weathered gravel in a dark-colored, mottled, very poorly sorted matrix of sand, silt, and clay. This interval has the characteristics of an argillic soil horizon and thus may be classified as a vertisol (Retallack 1990). The other paleosol, which lies at about 73 m (240 ft), is also very poorly sorted and weathered, but is strongly consolidated with a light-colored CaCO_3 cement that, in places, completely fills voids between sedimentary particles. Blocky to platy pedogenic structures are also present. This type of soil development is comparable to stage II-IV calcic soil development (Gile et al. 1966; Gile 1975; Machette 1985) and would be classified as an aridisol.

The Ringold Formation in the zone between 55- and 72-m (180- and 235-ft) depth contains multiple graded beds up to several meters thick, ranging from matrix-supported gravelly, medium-to-coarse sand at the base to well-sorted, silty fine sand on top. The tops of most graded beds were unweathered, except for a single, thin (5-cm-thick), stage I-II calcic soil horizon developed at 63 m (207.5 ft) (subinterval GD-4B). Elsewhere, carbonate-cemented sand nodules were found dispersed within well-sorted sand intervals.

Carbonate nodules are often associated with calcic soil development; however, no other associated soil structures or horizons accompanied these nodules. An alternative mechanism for nodule formation is postburial precipitation via the interaction with groundwater.

The Hanford formation, the base of which lies at 55-m (180-ft) depth, possesses a wide range of sediment textures from silty sand to bouldery sandy gravel. Grain size within the Hanford formation generally increases upward. The base of the Hanford formation consists of mostly graded beds of well-sorted, matrix-supported gravelly sand to silty fine sand. The upper Hanford formation sequence consists of mostly poorly sorted, clast-supported, pebble to boulder gravel in a poorly sorted silty sand matrix. Multiple weakly to strongly developed calcic soil horizons, representing soil development within an arid environment between episodes of cataclysmic flooding, are present to a depth of ~30 m. No microbiological samples were collected from Hanford formation paleosols, however.

Hydrogeology of the Yakima Barricade Site.

Vertical recharge from the surface at the borehole has been extremely low ($<0.02 \text{ mm year}^{-1}$) during the last several thousand years. This conclusion is based on the soil water chloride profile shown in Figure 2. The chloride ion profile shows an accumulation of meteoric chloride in the first 5 to 6 m that probably occurred during the last 13,000 years. The elevation at the top of this borehole (240 m) is well below the elevation of the high-water mark associated with this last flood event (385 m). Based on the low chloride content, sediments below this chloride peak have probably not been exposed to meteoric water during that time period. Therefore, glacial flood waters are still responsible for water drainage in the major portion of the unsaturated zone in this area. Because the geology of this site is well defined, the cumulative chloride versus cumulative water content was used to calculate the long-term input of atmospheric chloride rather than age-dating the profile segments. Because the cable tool drilling method was used, the majority of samples were not recovered intact and, therefore, actual bulk densities are not available. Values of bulk density typically encountered in the Hanford formation range from 1.27 to 1.97 g cm^{-3} (Bjornstad 1990).

Although individual bulk densities could be estimated for each lithology based on the detailed geologic log, we have used the reported range of bulk density as a first approximation. The age-dating calculation requires the additional assumption of piston flow. Cumulative chloride is calculated as

$$\sum_i (\theta_{vi} \times Cl_{swi}) d_i \quad (1)$$

where θ_{vi} is the volumetric water content at depth i ($\text{m}^3 \text{ m}^{-3}$), Cl_{swi} is the chloride content in the soil water at depth i (g m^{-3}), and d_i is the sample interval length at depth i (m).

Cumulative water content is calculated as

$$\sum_i (\theta_{vi} \times d_i) \quad (2)$$

The volumetric water content is equal to the gravimetric water content times the bulk density. Plots of cumulative chloride content versus cumulative water content will give a straight line unless there has been a change in precipitation, chloride input, and/or recharge, in which case the line will curve. The curve is a series of straight-line segments that represent periods of constant conditions. The date represented by the end points of each straight-line segment, or the travel time t to soil-depth interval, can be estimated by

$$t = \sum_i \left(\frac{\rho_B M d_i}{Cl_o P} \right) \quad (3)$$

where ρ_B is the dry bulk density, M is the chloride concentration (in $\text{mg chloride kg}^{-1}$ soil), d is the interval length, Cl_o is the atmospheric input of chloride, and P is the annual precipitation (Phillips et al. 1988). The term $\rho_B M d_i$ is essentially the same as Cl_{swi} , the cumulative chloride content of the soil water in the unsaturated zone at that point.

Assuming that $t = 13,000$ years and $P = 0.16 \text{ m year}^{-1}$, the value for Cl_o ranges from 0.24 to 0.38 mg L^{-1} for the assumed bulk densities of 1.27 g cm^{-3} and 1.97 g cm^{-3} , respectively. The higher value for Cl_o (0.38 mg L^{-1}) is very similar to the value reported by Phillips et al. (1988) for New

FIGURE 2. Moisture Content and Chloride Profile for the Yakima Barricade Borehole

Mexico soils. The chloride concentration in rainfall at Hanford is generally reported to be below 0.1 mg L^{-1} (the ion chromatograph detection limit), suggesting that the major portion of chloride input occurs as dry fallout. The suggestion that dry fallout is much more significant than wet fallout is

consistent with findings by the Hanford Environmental Dose Reconstruction project.

Net recharge can be determined by applying a mass balance argument on the chloride ion, where the difference between the chloride concentration

of the soil water and the atmospheric input concentration is due to evapotranspirative enrichment.

This approach typically does not require the assumption of piston flow; however, because we calculated Cl_o by Equation (3), we are indirectly assuming piston flow. Recharge is determined by the relationship

$$R = \left(\frac{Cl_o}{Cl_{sw}} \right) * P \quad (4)$$

where R is recharge (cm year^{-1}), Cl_o is average chloride concentration in local precipitation (mg L^{-1}) and dry fallout, Cl_{sw} is average chloride concentration (mg L^{-1}) in the soil water, and P is average annual precipitation (cm year^{-1}). The average Cl^- value (Cl_{sw}) at the peak concentration was $\sim 4000 \text{ mg L}^{-1}$. If precipitation is assumed to be 0.16 m year^{-1} and we use Cl_o as calculated above (0.24 to 0.38 mg L^{-1}), then the estimated long-term recharge would range from 0.0096 to $0.0152 \text{ mm year}^{-1}$ in this soil profile.

The low vertical recharge implies viable microorganisms present in the sediments today may have been relatively inactive since development of the present vadose zone after the last major recharge event (i.e., catastrophic flood) 13,000 years ago. The vertical distribution of matric potentials (Long and Rawson 1991) is consistent with low recharge and with the interpretation that the vadose zone developed as a result of long-term subsurface drainage after the last major recharge event.

The Yakima Barricade borehole was drilled to a depth just beyond the water table, where the hydrogeology is very different from that of the unsaturated zone. The unconfined aquifer at this site is recharged by surface runoff, precipitation, and possibly irrigation practices, all of which occur only a few kilometers to the west of the Yakima Barricade. Groundwater flow velocities are relatively high (on the order of centimeters to meters per day). The groundwater appears not to have been affected by anthropogenic chemical pollution (nitrate and tritium are at background levels), but the combination of irrigation practices to the west and industrial waste-water disposal to the east

strongly influences the water table. A hydraulic mound to the east has had the effect of damming groundwater flow from the west, in effect backing up the subsurface flow and raising the water table. In the vicinity of the borehole, the water table has risen approximately 9 m since 1948, when water-level measurements were first taken (Newcomer 1990, page 47).

Comparison of Microbiologic Data with Hydrogeologic and Geochemical Parameters. Relatively low numbers of aerobic and microaerophilic heterotrophs [$\sim 10^2$ to 10^4 colony-forming units (CFU) g^{-1} dry weight of sediment] are present in the silts, sands, and gravels composing the Ringold and Hanford formation sediments. Empirically, higher microbial abundances appear to be associated with calcic paleosols, but otherwise no strong correlation is apparent between individual hydrogeologic and geochemical parameters on one hand and microbial abundance on the other (Long et al. 1991).

A number of geologic parameters (texture, sorting, color, consolidation, mineralogy, reaction to HCl) observed during logging of the core were evaluated with respect to independent biomass or microbial activity measurements (AODC, PLFA, percent ^{14}C mineralization, direct microbial cultures). The results fail to identify a strong correlation among any of the microbial measurements or among geologic parameters and microbial measurements. Figures 3, 4, and 5 are examples that illustrate the lack of correlation among physical and microbial parameters of the sediments.

Preliminary data from samples in the upper 3 m of the aquifer suggest that total culturable bacteria are similar in abundance to those in the unsaturated zone. In particular, an anticipated increase in microbial abundance at the water table did not occur, possibly because of the 9-m rise in the water table during the last 40 years at the location of the borehole. Given the low water contents and low nutrient levels of the vadose zone, the vadose zone microbial communities may not have been able to respond to saturated conditions that would have occurred during only the last 10 or so years at the Yakima Barricade location.

FIGURE 3. Degree of Sediment Consolidation (arbitrary scale) Plotted Versus Culturable Microbes (direct contact plate method)

FIGURE 5. Saturated Hydraulic Conductivity (m s^{-1}) Plotted Versus Culturable Microbes (direct contact plate method)

FIGURE 4. Percentage of Mafic Minerals in Sand Fracture Plotted Versus ^{14}C Mineralization Potential on Glucose Acetate Succinate Substrate

Results of Scanning Electron Microscopy Studies. Studies on samples from Hanford and INEL continue to point to the importance of localized environmental niches within units where microorganisms occur. SEM analyses of samples

that have undergone critical-point drying to maintain original pore-scale texture suggest that mineral surfaces are an important ecological niche and can act as possible nutrient sources. This conclusion is corroborated in a recent SEM study of bacteria-mineral interactions reported by Hiebert (1991).

SEM observations of samples from the Yakima Barricade borehole to date have yielded only limited results in terms of clear identification of microorganisms attached to grain surfaces. Typically, grain surfaces of the sediment are rough compared with those of the INEL basalt samples, making unequivocal identification of individual microorganisms difficult. Filamentous structures are observed but are less common than in the INEL samples. It is possible that microorganisms present are not well attached in the Yakima Barricade samples and are removed during the critical-point drying process. Alternatively, microorganisms may simply be difficult to detect on irregular grain surfaces using SEM methods. We are currently evaluating the use of alternative microscopic detection techniques to provide positive identification of microorganisms in a way that will preserve grain attachment relationships. Moreover, use of SEM for characterization of rock

textures and spatial relationships between organic matter (e.g., lignitic root remnants) and surrounding sediment is still very promising even if microorganisms cannot be directly identified with this method.

Microbiological Significance of Paleosols. The physical, chemical, and microbiological characteristics of paleosols are being evaluated to determine their impact on deep, in situ bioremediation. As noted above, they also may contain higher concentrations of viable microbes and/or more nutrients available to sustain microbial growth than do the surrounding strata (Bjornstad et al. 1991). Paleosols are common between catastrophic flood sequences and the fluvial-lacustrine, Neogene Ringold Formation, where most of Hanford's unconfined aquifer resides. Within the Ringold Formation, paleosols are typically associated with fine-grained, floodplain-overbank facies. Evidence of weathering and soil development in Ringold paleosols includes secondary structures such as granular, blocky, and prismatic ped development, mottling, calcareous glaebules and stringers, root traces, and animal burrows; these may occur within calcic, argillic, and/or cambic soil horizons in various shades of gray, olive, and brown. While aridisols, similar to modern soils developing in a semiarid climate, are common in the Ringold Formation, other soil types such as entisols and vertisols are also present, suggesting more humid climatic conditions also existed during Ringold time.

Grain-size distribution and geochemical parameters such as pH, Eh, TOC, CaCO_3 , Cl, and Kjeldahl phosphorus, which may affect microbial activity, differ between pedogenic horizons and adjacent unweathered strata. Microbiological studies performed to date suggest that the greatest microbial activity in the Ringold Formation is associated with calcic soil horizons and that these horizons may serve as zones of enhanced microbial growth during in situ bioremediation. Recent findings suggest precipitation of pedogenic calcium carbonate may be induced by microbial activity (Monger et al. 1991).

A fundamental hypothesis we have been testing is that paleosols may be preferred sites for microbial activity because of a higher total organic carbon content than in surrounding strata. The results of

biomass measurements performed on paleosols at the Yakima Barricade borehole, however, are inconclusive with respect to this hypothesis. TOC values are generally below detection (0.05%) in both paleosols and unaltered sediments. The highest TOC value (0.07%) was from a nonpedogenically altered sandy gravel from core interval GD-8. Nevertheless, one biomass measurement (percent mineralization) appears to be higher for the calcic paleosols than for unaltered sediments (Figure 6). In addition, direct contact plate culturing techniques yield higher numbers of microbial colonies than do nonpaleosols. To summarize, the lack of a clear correlation between geologic characteristics and biomass suggests differences in microbial activity occur at a smaller scale than the relatively coarse sampling interval. This concept is supported by the observation for one finely sampled interval (GD-4) in the vadose zone: microbial activity differs greatly in samples as close as several centimeters apart. Furthermore, the lack of correlation among the various biomass parameters may indicate that these parameters are measuring different aspects of the microbiological population or that significant differences in microbial biomass occur on a scale of centimeters. Data from sample interval GD-4 support the hypothesis of centimeter-scale variability in microbial activity.

Discussion. Data indicate that microbes are initially inactive and largely unculturable but, following sampling and subsequent storage, metabolic activity and numbers of culturable microorganisms increase while microbial diversity decreases (Long et al. 1991). Microbes in the vadose zone appear to be in a "resting" state that may be imposed by the limited availability of nutrients (see Fredrickson et al. article in this volume). We hypothesize that large portions of the initial microbial populations were unable to survive because of nutrient limitations associated with low water potentials and lack of available nutrient sources. Episodic enhancement of microbial metabolic activity or growth may have occurred in some strata as a result of short-term increases in vadose zone water flux and associated redistribution of nutrients. Moribund cells or cells that require lengthy periods to recover from dormancy may also contribute to the low numbers of culturable heterotrophs compared with direct counts.

FIGURE 6. Stratigraphy and Associated ^{14}C Mineralization Versus Depth, Hanford Yakima Barricade Drilling Site

The lack of apparent correlation between hydrogeologic parameters (other than the occurrence of paleosols) and microbiology is at first puzzling. However, we believe that two factors explain the lack of correlation: 1) the numbers of microorganisms at both INEL and Hanford are relatively low and thus are more uncertain than for materials with larger populations and 2) the microorganisms are apparently in an inactive or resting state and, as such, are nonresponsive to present environmental conditions. For example, metabolic by-products are not significant and, hence, the flow rate of pore water past the microorganisms is not an important factor in controlling or limiting microbial growth. Under these circumstances, one would not expect a strong correlation between saturated or unsaturated hydraulic conductivity and microbial abundance or activity. It is also possible to view the loss of microbial cell populations (as a result of starvation) as a stochastic process. Simple population dynamics considerations suggest that, although the likelihood of microorganism survival is dependent in part on the initial population size, there is a finite probability of the extinction of any population. Given this stochastic view under condition of limited survivability, little if any correlation between hydrogeologic parameters and microbial abundance or activity would be expected. A correlation between microbial abundance and nutrient levels would be expected. Initial TOC data were not sensitive enough to detect any correlation, and even when more sensitive data are available, the effect of centimeter-scale variation in microbial abundance may still confound detailed correlation.

Summary of Results from INEL Samples

Sample Acquisition at INEL. Between June and October 1990, fifteen 1- to 2-m-long core samples and a surface soil sample were acquired from two INEL boreholes at the New Production Reactor (NPR) site (Figure 7). The boreholes (NPR W01 and NPR W02) afforded sampling opportunities primarily in the unsaturated zone above the Snake River Plain aquifer, although some samples of basalt were taken across the water table and two sedimentary interbeds were sampled within the aquifer (Figure 8). Dense or vesicular basalt, fractured basalt, fracture infilling, and flow-top/bottom rubble zones were collected in NPR W01 at the capillary fringe to test the importance of more permeable zones in localizing

microorganisms and to evaluate the effect of the fluctuating water table. Samples of a sand and a silty clay sedimentary interbed were recovered from below the water table in NPR W02.

A sampling scheme was developed that coupled determination of microbial numbers, diversity, and activity with measurement of hydrologic and geochemical parameters. Bulk hydrologic and physical properties were determined on samples with lithologies similar to those sampled for microbiological analysis and located within 0.3 m of microbiological samples. Pore water chemistry and sample mineralogy were determined on similarly located samples to ensure comparability of physical and chemical properties with microbiological findings. As part of fieldwork conducted prior to sampling, a survey of the water-level data for an existing aquifer well near the deep microbiology borehole site was completed. The data indicated that the water table had fluctuated approximately 0.6 m within the past 6 years. It was hypothesized that the microbial activity at the water table would reflect the variation, and plans were made to concentrate on sampling across the water table.

Subsurface samples for microbiological, chemical, and physical analyses were obtained using aseptic sampling procedures developed to ensure that surface contamination was not introduced to the subsurface during sampling and that cross-contamination from a stratigraphically shallower unit was not carried to a deeper horizon during sample acquisition. Detailed protocols developed during sample acquisition at SRS (Phelps et al. 1989) were adapted to the types of drilling and sampling techniques used at INEL and Hanford (Russell et al. 1989).

Sampling techniques for basalts and sediments encountered at the INEL boreholes involved air rotary drilling. Argon gas was used as the drilling fluid during sampling intervals to reduce the exposure of the subsurface to air used in drilling between sampled intervals. To ensure that microorganisms recovered from the samples represented subsurface communities, stringent protocols were followed to maintain aseptic conditions during sample acquisition, handling, and distribution to investigators (Long et al. 1990). The potential introduction of microorganisms

FIGURE 7. Location Map for the INEL Sampling Site (after Pittman et al. 1988)

FIGURE 8. Stratigraphy and Sampling Depths, NPR Site, INEL

during sampling and handling was traced by several means. At INEL, air and argon were traced using perfluorocarbons, and particle and moisture movement was traced using a lithium bromide solution containing 1- μ m-diameter latex microspheres.

All drilling and sampling equipment was sterilized by steam cleaning before use in the borehole. Down-hole core samples were retrieved in sterilized core barrels, which were handled only with clean cotton gloves at land surface. Core barrels were transferred to an aseptic glovebox with an inert argon atmosphere within 1 hour of drilling. Tools that came in contact with cores were autoclaved and wiped with a dilute bleach solution. Outer portions of samples were pared away to reduce tracer concentrations by at least two orders of magnitude before the material was sampled for microbiological analyses. Samples were distributed for receipt by microbiologists, geochemists, and hydrologists within 72 hours of removal from the boreholes.

Hydrogeologic Setting of the INEL Site. The INEL occupies 2320 km² in southeastern Idaho and is located on the Snake River Plain, a broad structural downwarp composed of 600 to 3000 m of Quaternary-age basalts intercalated with minor sedimentary interbeds. Basalt flows of the Snake River Plain province are thin, areally extensive olivine tholeiites that have highly vesiculated flow tops and bottoms. Near-vertical cooling fractures are common in outcropping flows. The flows sampled for microbiological samples ranged in age from approximately 650,000 to 230,000 years before present.

Sedimentary interbeds are primarily eolian silts (loess), although fluvial gravels and sands occur locally. Basalts are initially erupted and flow at land surfaces at temperatures in excess of 1100°C, rendering them essentially sterile until cooling. Long exposure at land surface is assumed to be required for basalts to become colonized by microorganisms. Likewise, wind-deposited sedimentary interbeds are not expected

to host large numbers of microorganisms on initial deposition, due to transport of air-suspended sediments and low organic carbon concentrations in loess, unless significant soil development or organic carbon was associated with bioturbation.

The Snake River Plain basalts host the very productive Snake River Plain aquifer, which flows from northeast to southwest beneath the INEL and stores an estimated 200 million acre-feet of water. The basaltic aquifer may be more than 1 km thick in the middle of the plain, but the upper 200 m is assumed to be the most permeable. In much of the eastern Snake River Plain, the regional aquifer system is unconfined. The broken and rubbly nature of the flows is associated with relatively high hydraulic conductivities (Lindholm 1988), and flow velocities beneath the INEL have been estimated to range from 1.5 to 6 m day⁻¹ (Barraclough et al. 1981).

The INEL is located in a semiarid environment where the annual precipitation ranges from 10 to 30 cm year⁻¹. The majority of recharge for the eastern regional Snake River Plain aquifer has been demonstrated to occur as a result of drainage from tributary basins and irrigated agriculture surrounding the INEL site (Lindholm 1988). Only a small percentage of the recharge is assumed to occur from infiltration of precipitation.

An aquifer test was performed on the NPR W01 borehole to determine the borehole-scale saturated hydraulic conductivity; the measured value in the borehole at the water table was approximately 0.4 m day⁻¹. This value was approximately a factor of two lower than the average velocity for the Snake River Plain aquifer at the INEL estimated from previous tracer studies conducted between boreholes separated by several kilometers. The variation in hydraulic conductivity as a function of scale within the Snake River Plain aquifer is the focus of ongoing study by INEL collaborators.

Aqueous samples were collected from the existing NPR Test well and the NPR W01 borehole for dissolved organic carbon analyses and determination of major, minor, and trace elements; analyses were performed as part of the pore water chemistry research conducted by J. P. McKinley (described elsewhere in this volume). Additional

aqueous samples from NPR Test and NPR W01 were collected and sent out to fulfill requests made by several off-site investigators.

Lithologic Characteristics of the INEL Boreholes. Samples from the INEL boreholes included two major textural classifications of basalts and several types of sedimentary material. Basalt samples were characterized as either 1) homogeneously dense or vesicular across their 1- to 2-m sampled interval or 2) heterogeneous, with a mixture of textures ranging from dense and nonfractured to vesicular and highly fractured by near-vertical fracture planes. Some of the heterogeneous basalt samples contained friable rubble zones related to flow-top development. Vesicular basalts were gray (hue 5YR4/1) through reddish gray (hue 10R4/1) to weakly red (hue 10R5/1), indicating variable oxidation on cooling. Vesicles ranged in size from <1 mm to approximately 2 cm, with most basalts containing vesicles in the range of 0.5 to 1.0 cm. Olivine (a ferromagnesian silicate) and plagioclase phenocrysts from 1 to 5 mm were observed in hand specimens and thin sections. Some basalts contained numerous groundmass pyroxene crystals as well.

Sediments were classified by grain size and by location relative to basalts. Interbed sediments sampled within the vadose zone consisted of reddish-brown silts and sands. A sandy interbed and a silty clay interbed were sampled within the aquifer. Fine-grained, reddish sediments within fractures in basalt were also characterized for microbial communities and physical and chemical properties.

Basalt Hydraulic and Physical Properties. Measurement of saturated hydraulic conductivities for rock cores and sediments was performed in a constant-head permeameter. Determination of unsaturated hydraulic properties was conducted by measurement of moisture characteristic curves. The one-step outflow method used to measure moisture characteristic curves for soils or sediments was modified to a multistep approach for application to rock cores.

For INEL basalts, the wet and dry masses and dry volumes of cores, saturated hydraulic conductivities, moisture retention curves, and unsaturated hydraulic conductivities were measured. Effective

porosities and bulk and skeletal densities were calculated from these measurements. The average basaltic bulk density was 2.45 g cm^{-3} , and the average skeletal density was 2.95 g cm^{-3} . These values are within the expected range for olivine tholeiitic basalt and provide a credible basis for the calculated porosities. Effective porosities were calculated from saturated mass and volume data to range from approximately 8.5 to 20%, with an average of approximately 16.4%. These values indicate good interconnectivity of the pores and vesicles, with concomitant potential for vertical, unsaturated-zone transport of microorganisms at INEL.

Laboratory-measured values of saturated hydraulic conductivity ranged from 0.0003 to 0.02 m day^{-1} . Field measurements indicated a value of approximately 0.3 to 0.5 m day^{-1} . Comparisons of average laboratory-scale saturated hydraulic conductivity with borehole-scale hydraulic conductivity indicate agreement within an order of magnitude, which is within the variability associated with the laboratory measurements.

INEL Sedimentary Interbeds. Most INEL sediments were very fine- to medium-grained sands, with low silt and clay fractions. The sands were predominantly quartzofeldspathic, with minor ferromagnesian silicates (primarily pyroxene) and calcite. The deepest interbed sampled within NPR W02 was a silty clay dominated by illite and smectite, with minor kaolinite. For one sample that was sufficiently intact, a saturated hydraulic conductivity of approximately 1 m day^{-1} was determined with the constant-head method. In the case for which only disturbed samples were available, saturated hydraulic conductivities of INEL sediments were determined by a falling-head method for repacked sediments. Values were approximately 0.1 to 0.3 m day^{-1} at a series of bulk densities that ranged from 1.45 to 1.65 g cm^{-3} .

Comparison of Hydraulic Properties Across Sites. Because of thick unsaturated zones associated with arid western sites, sampling during FY 1990-1991 resulted in the collection of only one saturated sand from INEL and four saturated samples from Hanford (three of which showed

microbial evidence of introduced contamination). At SRS, the majority of samples were from subsurface aquifers. The paucity of data for the comparison is obvious. However, the numbers of microorganisms detected at INEL and Hanford were notably lower than numbers observed at SRS. If hydraulic conductivity is important in controlling numbers, as hypothesized by other investigators, then microbial numbers in INEL and Hanford saturated sands might be expected to be similar to numbers observed in SRS sands. Data shown in Table 1 suggest no direct correlation between hydraulic conductivity and microbial abundance because K_{sat} values are within an order of magnitude and microbial numbers vary over several orders of magnitude. This preliminary finding suggests that nutrient availability may be an important parameter. Organic carbon concentrations do vary by approximately an order of magnitude between SRS and the western sites.

Isolation of Subsurface Microorganisms. INEL samples were directly contacted with 1% peptone-trypticase-yeast extract-glucose (PTYG) agar to allow enumeration and possible isolation of outgrowths after incubation. Thirteen of the 17 INEL samples that exhibited growth on sprinkle plates grew on the first and second transfers to fresh 1% PTYG. Of these 13 samples, 7 showed an indefinite number of colony types. Of the remaining 6 samples, 1 sample had one colony type, 2 samples had two types, 2 samples had three types, and 1 sample had four types. Samples positive for growth on sprinkle plates ranged in depth from 73 to 180 m (240 to 600 ft) and came from sediments and fracture infill materials within saturated and unsaturated zones.

Enrichments were performed for low-pH autotrophs and heterotrophs. In three samples, fungi capable of growing in glycerin at pH 3 were found. No evidence of heterotrophic bacteria was found in the glycerin salts. One fungus grew in Fe(II) salts, and six samples indicated Fe(II) oxidation. All of the samples showing evidence of iron oxidation were sediments, except one sample that consisted of silty material from within a fracture in basalt. Motile bacteria were not observed. Yeast was evident in the clay sediment within the aquifer but probably played no role in iron oxidation.

TABLE 1. Comparative Samples from INEL, Hanford, and SRS

Site	Depth (ft below land surface)	Lithology	Ksat (m s ⁻¹)	Log ₁₀ CFU (PTYG/25°C)	TOC (mg kg ⁻¹)
INEL	560 - 564	sand	9.0E-6	<2.0	500
Hanford	329.7 - 329.9	muddy sandy gravel	4.3E-7	<2.0	
SRS (C10) ^(a) Middendorf aquifer	1198	sands	3.2E-7	4.3 - 6.4	3000

(a) SRS data taken from earlier work by J. M. Zachara and coworkers on borehole C10. Plate counts performed with 1% PTYG. Plate counts for INEL and Hanford samples that used 1% PTYG also showed numbers at or below detection.

Eleven of 16 PNL samples showed bacterial growth on sprinkle plates, 4 exhibited no growth, and 1 exhibited fungal growth. As with INEL samples, colonies on sprinkle plates did not necessarily transfer to 1% PTYG medium. Transfers of 7 samples showed no growth. Isolates from Hanford samples 0805a, 0905, 1005, 1132, 1205, 1232, 1332, and 1432 have been transferred numerous times, each sample having from one to three colony types. Other Hanford samples exhibited growth on transfers from the sprinkle plates to 1% PTYG medium.

Results of enrichments of Hanford samples in Fe(II) and glycerin media were similar to those of INEL samples. Six samples exhibited fungal growth in glycerin. Two samples had fungi growing in iron salts. Eleven samples showed evidence of Fe(II) oxidation, but no motile bacteria were evident. Two samples (0105b and 0532) contained yeast.

Results indicated the presence of microbes in subsurface materials from INEL and Hanford. The data also indicated that the numbers of microbes at INEL are exceedingly low compared with other subsurface and surface environments. This observation corroborates the findings of other Deep Subsurface Microbiology Subprogram investigators studying samples from INEL. Presumptive evidence indicates the presence of iron-oxidizing bacteria in some samples from INEL and Hanford; however, further work is in process with the pH 3 enrichments containing iron and glycerin to verify the presence of autotrophs. All positive enrichments for iron oxidation at INEL were obtained on samples from sediments or fracture infill material.

Results of Scanning Electron Microscopy Studies. The most ubiquitous features of probable microbial origin observed with the SEM are filamentous networks of low-atomic-number materials (possibly carbon based). These materials are interpreted to be the remnants of collapsed polysaccharide and peptidoglycan biofilms produced by bacteria (Figure 9). The effect of such biofilms may be twofold. In the saturated zone, biofilms may reduce porosity through obstruction of pores and pore throats; in the unsaturated zone, these fibers may act as bridges over cracks and fractures, thereby permitting fluid migration across otherwise nonviable pathways.

We have observed numerous morphological variations of microorganisms, including rods, cocci, segmented arms, and spiral rods, occurring individually or in clumps interpreted to be colonies (Figure 10). Individuals within colonies often reveal complex morphological diversity, which may represent mixed microbiological communities. Sizes of individual organisms range from 0.1 to 1 μm , and colonies range up to 10 μm in size. Some microorganisms appear to be strongly attached and to have preferentially dissolved the mineral surface adjacent their point of attachment. The ability of microorganisms to etch mineral surfaces via organic acids has been recently documented by Hiebert (1991) and by 1991 studies conducted at the University of South Carolina by Paul Ehrlich.

Thus far, the examination of samples from six different basalt flows at INEL reveals consistent relationships that suggest specific microecology

FIGURE 9. SEM Photomicrograph of Filamentous Structure Interpreted to be Biofilm Remnants

controls on microbial abundance and metabolic function. Within the basalts collected in Idaho, the vesicles provide the best habitats for microorganisms. Furthermore, microorganisms have been most commonly observed attached to, or associated with, ferromagnesian minerals, such as the olivines and pyroxenes that are common constituents of these basalts.

Discussion. Aseptic sampling techniques and tracer technologies were used to ensure the collection of microbiologically representative subsurface samples. Basalt and sediment samples from INEL were analyzed for a suite of physical and chemical properties, including bulk density, effective porosity, saturated hydraulic conductivity, particle-size distribution, TOC, and several inorganic constituents related to microbial nutrient cycles (total P, S, N, and carbonate as

CaCO_3). These parameters were examined for correlation with several indicators of biomass, including absolute microbial numbers determined by standard plate counts, AODC, and PLFA analyses. Very few correlations were observed.

The relationship between microbial communities and moisture content was difficult to evaluate for the INEL boreholes. Assessing the in situ moisture content or soil water potential for vadose zone samples taken in the NPR boreholes was not possible because microbial tracers were introduced in a bromide solution that wetted samples immediately on commencement of drilling. Gravimetric moisture contents measured immediately on retrieval of cores showed broad variation (2 to 20 wt.%) in samples at the top of the water table where near-saturation conditions were expected.

FIGURE 10. Typical Microorganism Observed Using SEM. Note spiral morphology.

Samples from within the aquifer were expected to have greater numbers of microorganisms than were samples in the unsaturated zone. The only biomass indicator that substantiated such an assumption was the PLFA biochemistry, shown as a function of depth in Figure 11. The sample showing detectable PLFAs was a sandy interbed at approximately 170-m (560-ft) depth.

Results from INEL can be summarized as follows: 1) very low numbers of microorganisms (10^{-2} CFU g^{-1} dry material) were found in unsaturated basalts and sediments; 2) autotrophic, iron-oxidizing bacteria were associated with eolian-deposited sediments and fractures within basalts at or below the water table, but were not detected in analyses of basalt; 3) the correlation observed at other sites between hydraulic conductivity and microbial numbers was not apparent for INEL samples; and 4) levels of

TOC within sandy sediments and basalts were approximately an order of magnitude lower than in sands from SRS (Figure 12), as were numbers of heterotrophic microorganisms in the sands.

Preliminary Comparison of Microbial Activity at INEL, Hanford, and SRS

The observed low microbial abundances at INEL and Hanford ($\sim 10^1$ to 10^4 CFU g^{-1} dry weight of sample) are consistent with the relatively low TOC contents (<0.05 to 0.07%), which are approximately an order of magnitude less than in sediments at SRS, where microbial abundances are $\leq 10^7$ CFU g^{-1} . This general relationship between aerobic microbial activity and available organic carbon is illustrated in Figure 12, where microbial activity (^{14}C mineralization of acetate) is plotted versus the maximum measured TOC in solid subsurface samples from the respective sites. Wide

FIGURE 11. Plot of Depth Versus Phospholipid Fatty Acid (PLFA) Concentration for INEL

FIGURE 12. ^{14}C Mineralization of Acetate Plotted Versus the Maximum Measured Total Organic Carbon in Solid Subsurface Samples from INEL, Hanford, and SRS

scatter in the mineralization data, typical of heterogeneity in subsurface systems, results in large error bars. However, the general grouping of INEL and Hanford at low TOC compared with SRS is clear; this difference in TOC clearly may be

a key reason for the generally large difference in microbial abundance. This concept needs to be tested further to see whether the relationship suggested by Figure 12 holds up on a sample-by-sample basis.

Conclusions

Conclusions from our research to date are as follows:

- Relatively low microbial abundances typical of samples obtained from the unsaturated zones at INEL and Hanford can be explained by a combination of low nutrient levels (particularly TOC) and low water contents, which limit microbial access to any nutrients that are present.
- Calcic paleosols are exceptional at Hanford, in that they appear to harbor higher numbers of microorganisms than do surrounding strata. Confirmation of this result is needed, as is an understanding of the underlying reasons for the observation.
- At Hanford, it has been possible to constrain the hydrogeologic history in such a way that allows us to postulate the development of the microbial community in the following manner:
 - Prior to vadose zone drainage, microorganisms were randomly distributed (except for paleosols).
 - As low water contents were achieved, microorganisms became inactive as a result of starvation associated with a decrease in moisture.
 - Episodic enhancement of growth occurred because of increased water flux during cataclysmic flood episodes and associated redistribution of nutrients.
 - Microorganism populations were locally unable to survive because of nutrient limitations associated with low water contents and lack of nutrient sources.
- Very low numbers of microorganisms were detected in the few saturated-zone samples collected from western arid sites at INEL and

Hanford. Microorganisms in the subsurface at INEL are associated with sediments and the more permeable zones in INEL basalts, suggesting net downward transport by infiltration.

- Comparison of microbial numbers in predominantly sandy layers in aquifers at INEL, Hanford, and SRS suggests that similar hydraulic conductivities do not necessarily produce similar microbial numbers and activity.
- Comparison of microbial numbers among INEL, Hanford, and SRS further suggests that the concentration of available nutrients may be more important than physical properties as a controlling environmental parameter.
- Microbial isolates from INEL basalts and sediments may include autotrophic iron-oxidizing bacteria, which use inorganic rather than organic nutrients and therefore can have increased probability of survival in a low-carbon environment.

Our success at understanding the microbial status of the unsaturated zone with the limited number of samples obtained suggests the value of continuing the research effort and supports the long-term goal of developing the ability to predict subsurface microbial abundance and diversity given limited microbial data and extensive site hydrogeologic and geochemical data.

Future Research

Future research will focus on Hanford and will be designed to test specific hypotheses that have arisen from research conducted to date or that remain unresolved based on current research. Key issues are:

- What is the centimeter-scale variability of microbial occurrence in Hanford sediments?
- What aspect of calcic paleosols causes enhanced microbial abundance; are paleosol microorganisms indigenous or have they colonized the paleosol by being transported from surface environments?
- How does microbial activity in the saturated zone differ from that in the unsaturated zone?

- How does the Eh change with depth in the unconfined aquifer at Hanford, and how is the change related to microbial abundance, type, and diversity?

Answers to these questions are key not only to the basic understanding of subsurface microbial ecology but also to the ultimate implementation of in situ bioremediation. These questions will be addressed in 1992 and 1993 by deepening the Yakima Barricade borehole into the unconfined aquifer to the top of the Columbia River basalts. We will sample the borehole in such a way as to provide a detailed sampling profile [Geochemical, Microbiological, and Hydrological Experiments (GEMHEX)] that will address all of the above issues. We also will continue to perform selected analyses on existing sample material and will selectively sample Ringold Formation outcrops to provide details of spatial variability in chemical and physical properties that ordinarily cannot be obtained from borehole samples.

References

- Baker, V. R., B. N. Bjornstad, A. J. Busacca, K. R. Fecht, E. P. Kiver, U. L. Moody, J. G. Rigby, D. F. Stradling, and A. M. Tallman. 1991. "Quaternary Geology of the Columbia Plateau." In *Quaternary Nonglacial Geology; Conterminous U.S.*, v. K-2 of *The Geology of North America*, ed. R. B. Morrison. Geological Society of America, Boulder, Colorado.
- Baker, V. R., and R. C. Bunker. 1985. "Cataclysmic Late Pleistocene Flooding from Glacial Lake Missoula: A Review." *Quaternary Science Reviews* 4:1-41.
- Barraclough, J. T., B. D. Lewis, and R. G. Jensen. 1981. *Hydrologic Conditions at the Idaho National Engineering Laboratory, Idaho: 1974-1978*. U.S. Geological Survey Water Resources Investigation Open File Report 81-526, Idaho Falls, Idaho.
- Bjornstad, B. N. 1985. "Late-Cenozoic Stratigraphy and Tectonic Evolution Within a Subsiding Basin, South-Central Washington." *Geological Society of America, Abstracts with Programs* 17(7):524.

- Bjornstad, B. N. 1990. *Geohydrology of the 218-W-5 Burial Ground, 200-West Area, Hanford Site*. PNL-7336, Pacific Northwest Laboratory, Richland, Washington.
- Bjornstad, B. N., and K. R. Fecht. 1989. "Pre-Wisconsin Glacial-Outburst Floods: Pedogenic and Paleomagnetic Evidence from the Pasco Basin and Adjacent Channeled Scabland." *Geological Society of America, Abstracts with Programs* 21(5):58.
- Bjornstad, B. N., P. E. Long, and J. P. McKinley. 1991. "Paleosols of the Ringold Formation: Significance for Hazardous Waste Bioremediation and Paleoclimatic Assessment." *Geological Society of America, Abstracts with Programs* 23(5):376.
- DOE. 1988. *Consultation Draft, Site Characterization Plan, Reference Repository Location, Hanford Site, Washington*. DOE/RW-0164, Vol. 1. U.S. Department of Energy, Washington, D.C.
- Fecht, K. R., S. P. Reidel, and A. M. Tallman. 1985. *Paleodrainage of the Columbia River System on the Columbia Plateau of Washington State: A Summary*. RHO-BW-SA-318P, Rockwell Hanford Operations, Richland, Washington.
- Gile, L. H. 1975. "Holocene Soils and Soil-Geomorphic Relations in an Arid Region of Southern New Mexico." *Quaternary Research* 5:321-360.
- Gile, L. H., F. F. Peterson, and R. B. Grossman. 1966. "Morphological and Genetic Sequences of Carbonate Accumulations in Desert Soils." *Soil Science* 101:347-360.
- Hiebert, F. K. 1991. "SEM Study of Bacteria-Mineral Interactions in Microcosms That Model the Shallow Sub-Surface." *Geological Society of America, Abstracts with Programs* 23(5):A290.
- Lindholm, G. F. 1988. "Snake River Plain Aquifer System Study." In *Regional Aquifer Systems of the United States: Aquifers of the Western Mountain Area*, eds. J. S. McLean and I. A. Johnson, pp. 15-36. AWRA Monograph Series No. 14, Idaho Falls, Idaho.
- Long, P. E., J. F. Fredrickson, E. M. Murphy, S. A. Rawson, J. P. McKinley, F. J. Brockman, and B. N. Bjornstad. 1991. "Geohydrologic and Geochemical Controls on Subsurface Microorganisms in Late Cenozoic Sediments, South-Central Washington." *Geological Society of America, Abstracts with Programs* 23(5):377.
- Long, P. E., and S. Rawson. 1991. "Hydrogeologic and Geochemical Controls on Microorganisms in Subsurface Formations." In *Pacific Northwest Laboratory Annual Report for 1990 to the DOE Office of Energy Research, Part 2: Environmental Sciences*, pp. 22-30. PNL-7600 Pt. 2, Pacific Northwest Laboratory, Richland, Washington.
- Long, P. E., S. A. Rawson, F. S. Colwell, G. J. Stormberg, J. K. Fredrickson, D. L. Balkwill, and F. J. Wobber. 1990. "Progress of Sample Acquisition for the Deep Microbiology Program, U.S. Department of Energy." *EOS* 71:1326.
- Machette, M. N. 1985. "Calcic Soils of the Southwestern United States." In *Soils and Quaternary Geology of the Southwestern United States*, ed. D. L. Weide, pp. 1-21. Geological Society of America Special Paper 203, Boulder, Colorado.
- McKee, E. H., D. A. Swanson, and T. L. Wright. 1977. "Duration and Volume of Columbia River Basalt Volcanism: Washington, Oregon and Idaho." *Geological Society of America, Abstracts with Programs* 9(4):463-464.
- Monger, H. C., L. A. Daugherty, W. C. Lindemann, and C. M. Liddell. 1991. "Microbial Precipitation of Pedogenic Calcite." *Geology* 19:997-1000.
- Mullineaux, D. R., R. E. Wilcox, W. F. Ebaugh, R. Fryxell, and M. Rubin. 1978. "Age of the Last Major Scabland Flood of the Columbia Plateau in Eastern Washington." *Quaternary Research* 10:171-180.

Myers, C. W./S. M. Price, J. A. Caggiano, M. P. Cochran, W. J. Czimer, N. J. Davidson, R. C. Edwards, K. R. Fecht, G. E. Holmes, M. G. Jones, J. R. Kunk, R. D. Landon, R. K. Ledgerwood, J. T. Lillie, P. E. Long, T. H. Mitchell, E. H. Price, S. P. Reidel, and A. M. Tallman. 1979. *Geologic Studies of the Columbia Plateau: A Status Report*. RHO-BWI-ST-4, Rockwell Hanford Operations, Richland, Washington.

Newcomer, D. R. 1990. *Evaluation of Hanford Site Water-Table Changes - 1980 to 1990*. PNL-7498, Pacific Northwest Laboratory, Richland, Washington.

Phelps, T. J., C. B. Fliermans, T. R. Garland, S. M. Pfiffner, and D. C. White. 1989. "Methods for Recovery of Deep Terrestrial Subsurface Sediments for Microbiological Studies." *Journal of Microbiological Methods* 9:267-279.

Phillips, F. M., J. L. Mattick, T. A. Duval, P. W. Kubik, and D. D. Elmore. 1988. "Chlorine-36 and Tritium from Nuclear Weapons Fallout as Tracers for Long-Term Liquid and Vapor Movement in Desert Soils." *Water Resources Research* 24(11):1877-1891.

Pittman, J. R., R. G. Jensen, and P. R. Fischer. 1988. *Hydrologic Conditions at the Idaho National Engineering Laboratory: 1982 to 1985*. U.S. Geological Survey Water Resources Investigation Report 89-4008 (DOE/ID-22078), Idaho Falls, Idaho.

Retallack, G. J. 1988. "Field Recognition of Paleosols." In *Paleosols and Weathering Through Time*, eds. J. Reinhart and W. R. Sigleo, pp. 1-20. Geological Society of America Special Paper 216, Boulder, Colorado.

Retallack, G. J. 1990. *Soils of the Past*. Unwin Hyman, Winchester, Massachusetts.

Russell, B. F., P. E. Long, D. Balkwill, T. J. Phelps, R. Colwell, G. Stormberg, R. L. Jacobsen, J. H. Kitchen, and H. Bledsoe. 1989. "Obtaining Microbially Representative Geologic Samples from Boreholes: DOE Proposed Requirements." *EOS* 70(43):1079.

Smith, G. A., B. N. Bjornstad, and K. R. Fecht. 1989. "Neogene Terrestrial Sedimentation on and Adjacent to the Columbia Plateau; Washington, Oregon, and Idaho." In *Volcanism and Tectonism in the Columbia River Flood-Basalt Province*, eds. S. P. Reidel and P. R. Hooper, pp. 187-198. Geological Society of America Special Paper 239, Boulder, Colorado.

Tallman, A. M., J. T. Lillie, and K. R. Fecht. 1981. "Suprabasalt Sediments of the Cold Creek Syncline Area." Chapter 2 in *Subsurface Geology of the Cold Creek Syncline*, eds. C. W. Myers and S. M. Price. RHO-BWI-ST-14, Rockwell Hanford Operations, Richland, Washington.

Waitt, R. B., Jr. 1980. "About Forty Last-Glacial Lake Missoula Jokulhlaups Through Southern Washington." *Journal of Geology* 88:653-679.

Pore Water Chemistry and Its Relationship to Microbial Distribution

J. P. McKinley

This project conducts research into the relationship between subsurface pore water chemistry and microbial activity. Included within this area are geochemical investigations in collaboration with projects on Subsurface Microbial Processes and Hydrogeologic and Geochemical Controls on Microorganisms in Subsurface Formations. Activities completed or ongoing during FY 1991 included 1) investigation of the regional carbon isotopic compositions of Columbia Plateau groundwaters and their relation to microbial populations sampled by the Deep Subsurface Microbial Investigations Project; 2) analysis and interpretation of results from chemical tracer introduction at the deep microbiology Yakima Barricade borehole at the Hanford Site; and 3) development of a method for estimating pore water compositions in very low moisture samples from the unsaturated zone, followed by estimation of compositions of waters within Yakima Barricade samples.

Investigation of $\delta^{13}\text{C}_{\text{HCO}_3}$ Variations in Deep Groundwaters of the Hanford Site

The work summarized here is the subject of a report submitted for publication. Groundwater flow in the Columbia Plateau is controlled by regional patterns of recharge, stratigraphy, and geologic structure (DOE 1988). Waters at different depths may be of local or distant origin; are enclosed in sediments or porous zones between massive, wholly inorganic confining beds; and may have moved laterally as well as downward or upward to their present position. Mixing of water during transport may have occurred, and compositional evolution was influenced by interaction with basalt. Systematic variations in stable isotopic compositions nevertheless exist and may indicate the influence of microbial activity on groundwater compositions and chemical evolution. The abundance ratio of the stable isotopes of carbon, ^{13}C and ^{12}C , is of particular interest because this parameter is sensitive to specific metabolic processes; its relative sign and magnitude may indicate the predominance of a single microbial metabolic process at depth.

Most data analyzed were collected as part of a broader effort to determine and monitor groundwater and surface-water compositions (Early et al. 1986). Aquifers were sampled to a maximum depth of 1300 m (4300 ft) by pumping, except for springs and a few boreholes that penetrated artesian aquifers where pumping was not necessary. In some wells, multiple samples were collected from selected intervals by setting packers at the interval boundaries. Stable isotope ratios are expressed in standard notation as described by Hoefs (1980): for any isotope of interest, $\delta = (R_A/R_S - 1) \times 1000$ (per mil); R_A and R_S are the ratios of ^{13}C to ^{12}C , the sample and the reference standard, respectively.

Seventeen wells and nine springs were sampled to yield 81 groundwater and spring-water compositions. Near-surface groundwater compositions, represented by spring waters, were relatively rich in calcium, magnesium, and carbonate. Dissolved inorganic carbon varied over a range of 2.6 to 3.4 mM to a depth of 550 m (1800 ft), then decreased over a broadly variable range to a minimum of 0.8 mM at depth. Spring-water pH was within the range of 7 to 8; this range in the

shallow subsurface increased to values of 9 to 10 at depths greater than 1 km.

Spring-water bicarbonate $\delta^{13}\text{C}$ values varied over a narrow range of -11.6 to -16.0‰ (Figure 1). This range in values was unchanged in confined aquifer groundwater samples to depths of 550 m (1800 ft). $\delta^{13}\text{C}_{\text{HCO}_3}$ in samples from depths of 300 to 550 m (980 to 1800 ft) is relatively invariant, between -12 and -20‰. This approximate constancy in $\delta^{13}\text{C}_{\text{HCO}_3}$ values indicates that microbial processes do not modify $\delta^{13}\text{C}_{\text{HCO}_3}$ values at depths less than 550 m (1800 ft). At depths greater than 550 m (1800 ft), $\delta^{13}\text{C}_{\text{HCO}_3}$ increased steadily, from -12 to +20‰ at a depth of 1250 m (4100 ft). These values were consistent with addition of relatively heavy CO_2 during methanogenesis.

A subset of the $\delta^{13}\text{C}_{\text{HCO}_3}$ values was more negative than the values near the surface. Samples within the more negative group all contained sulfate at a concentration of 0.7 mM or higher. The coincidence of elevated sulfate with anomalously negative values in $\delta^{13}\text{C}_{\text{HCO}_3}$ is consistent with sulfate reduction as the dominant microbial mechanism for consumption of organic carbon.

The microbial contributions to changes in $\delta^{13}\text{C}_{\text{HCO}_3}$ may be examined by treating the study area as a closed system with regard to organic

FIGURE 1. $\delta^{13}\text{C}$ Versus Depth

and inorganic carbon and its isotopic composition. The following assumptions apply. First, as groundwater migrates to depth, it is removed from interaction with the atmosphere. Second, the degradation of organic matter trapped in sediments during deposition progresses through multiple steps, of which reduction of CO_2 accompanying methanogenic dissimilation of acetate is the final step influencing $\delta^{13}\text{C}_{\text{HCO}_3}$ (Games et al. 1978). The overall degradation process supplies CO_2 and hydrogen for CO_2 reduction along with acetate fermentation. Third, the total amount of carbon present is equal to the sum of carbon held in organic matter, calcite, dissolved inorganic carbon, and methane. Fourth, nonmethanogenic processes, represented by isotopic compositions at depths above 550 m (1800 ft), result in dissolved inorganic carbon that is equal in isotopic composition to the bulk composition of decomposed organic matter (Klass 1984).

The maximum attainable $\delta^{13}\text{C}_{\text{HCO}_3}$ may be estimated from the above assumptions, data determined in this study, and published fractionation and mass flux ratios. Finally, the model and equations presented by Wigley et al. (1978, 1979) may be rearranged to yield an estimate of CO_2 input by microbial activity and output by methanogenesis and CaCO_3 precipitation. These calculations serve to evaluate the magnitude of microbial influence on overall groundwater chemistry. Applying the input-output ratio end members to initial and final concentrations of carbon then gives carbon input and output limits of 0.16 to 7.93 mM (input) and 1.56 to 9.33 mM (output). The amount of calcite precipitated over these ranges is nearly constant (0.70 to 0.85 mM), and the same effect on the isotopic signature of groundwater may be produced by the methanogenic consumption of a widely varying quantity of organic carbon.

Chemical Tracers at the Yakima Barricade Borehole

Drilling at the Yakima Barricade was within the unsaturated zone, using a cable tool drilling technique. Addition of fluids during drilling was avoided, except where the addition of water was required to remove cuttings from the advancing hole. When water addition was necessary,

autoclaved water containing lithium bromide was added. This addition was necessary above core interval 6 at the 290-ft depth, and above core interval 12 at the 332-ft depth. All core samples were subsampled and analyzed for bromide tracer.

Bromide (Br) in Yakima Barricade samples was quantified as follows. Subsamples were oven dried at 60°C ; then approximately 20 g of each sample was weighed into a centrifuge tube, and an equal weight of deionized water was added. Tubes were sealed and shaken overnight. Supernatant solution was drawn from each sample suspension, filtered, and analyzed by ion chromatography for Br^- ; the conductivity detection limit for this analysis was 0.1 mg L^{-1} .

Results of tracer analysis are presented in Figure 2. Approximately 55 mg kg^{-1} of Br was present in samples from interval 6 (sample 612, 290 ft). Lithium bromide tracer apparently seeped to lower core intervals 7 (sample 714, 296 ft) and 8 (sample 818, 317 ft); samples 912 (324 ft) and 1012 (329 ft) are tracer free. After addition of

FIGURE 2. Bromide Tracer Results at the Yakima Barricade

tracer-laden water above core interval 12 (sample 1212, 336 ft), samples collected below this depth showed the effects of water addition.

These results indicate that significant seepage of added water to core zones occurred, but that the effects of adding water extend to a limited depth below the point of addition. Because the added water was sterile, this inclusion of chemical contaminant does not indicate compromise of microbiological samples.

Estimation of Pore Water Compositions

Drilling at the Yakima Barricade borehole on companion projects yielded samples containing as little as 2.5 wt.% moisture. The relative dryness of these samples presented a challenge to estimating pore water compositions. Direct immiscible displacement of pore waters using Freon TF (E. I. Du Pont de Nemours, Wilmington, Delaware) under centrifugation (Kinniburgh and Miles 1983) was not successful for most samples. Addition of water in a fixed mass:mass ratio (e.g., 1:1) and subsequent displacement and calculation of aqueous chemistry was not considered because the effects on composition of adding 40 times the inherent moisture to some samples could not be evaluated. Addition of a large relative amount of water could cause unintentional and undetected dissolution of solid phases, for example.

Pore water compositions were estimated in the following way. Gravimetric moisture contents were measured. Approximately 250 g of sediment was weighed into each of four centrifuge bottles, then 10%, 20%, 30%, and 40% water by weight was added to individual bottles. Mixtures were shaken for 1 hour, after which the water was expressed by immiscible Freon displacement. Analyte ions were regressed to yield an equation from which ion compositions at intrinsic moisture contents could be calculated (Figure 3). This method allowed the direct evaluation of results for the effects of leaching because leaching would produce positive departures from a straight line at higher added moistures. Where this effect was apparent, results from larger additions of water were eliminated from the regressed data.

FIGURE 3. Regression of Analyte Ions from the Yakima Barricade 204-ft Depth. Sodium content at an innate moisture content of 2.6 wt.% is approximately 12.3 mg L⁻¹.

An example of composite ion compositions, for sulfate and sodium along with moisture content, is included as Figure 4. Sulfate, sodium, and moisture increase as the water table is approached at a depth of 328 ft.

References

- DOE. 1988. *Consultation Draft, Site Characterization Plan, Reference Repository Location, Hanford Site, Washington*. DOE/RW-0164, Vol. 2, U.S. Department of Energy, Washington, D.C.
- Early, T. O., G. D. Spice, and M. D. Mitchell. 1986. *A Hydrochemical Data Base for the Hanford Site*. SD-BWI-DP-061, Rockwell Hanford Operations, Richland, Washington.
- Games, L. M., J. M. Hayes, and R. P. Gunsalus. 1978. "Methane-Producing Bacteria: Natural Fractionations of the Stable Carbon Isotopes." *Geochimica et Cosmochimica Acta* 42:1295-1297.

FIGURE 4. Moisture and Selected Ion Composition Versus Depth at the Yakima Barricade

Hoefs, J. 1980. *Stable Isotope Geochemistry*. 2nd ed. Springer-Verlag, New York.

Kinniburgh, D. G., and D. L. Miles. 1983. "Extraction and Chemical Analysis of Interstitial Water from Soils and Rocks." *Environmental Science and Technology* 17:362-368.

Klass, D. L. 1984. "Methane from Anaerobic Fermentation." *Science* 223:1021-1028.

Wigley, T.M.L., L. N. Plummer, and F. J. Pearson, Jr. 1978. "Mass Transfer and Carbon Isotope Evolution in Natural Water Systems." *Geochimica et Cosmochimica Acta* 42:1117-1139.

Wigley, T.M.L., L. N. Plummer, and F. J. Pearson, Jr. 1979. "Errata." *Geochimica et Cosmochimica Acta* 43:1395.

Intermediate-Scale Subsurface Transport of Co-Contaminants

G. P. Streile, J. E. Szecsody, B. D. Wood, and F. J. Brockman

Contributors

A. J. Valocchi (University of Illinois),
B. E. Rittmann (University of Illinois), and
M. J. Truex (Washington State University)

Subsurface environmental contamination commonly consists of complex mixtures of compounds that are subjected to simultaneous chemical, microbiological, and hydrologic phenomena. Furthermore, the natural subsurface environment is often highly spatially heterogeneous in its physical, chemical, and biological properties. Design of effective disposal practices, prediction of the spatial extent and temporal development of subsurface contaminant plumes, and design and testing of contamination remediation methodologies are necessary to protect the public health. The ability to predict accurately the subsurface transport, transformation, and fate of contaminant mixtures in complex environments is critical to the success of these endeavors. Previous field experimentation has shown that predictive capability is hampered by a lack of understanding of microbiological, chemical, and hydrologic processes (and their interaction) on a mechanistic level. This mechanistic understanding can best be gained through controlled laboratory experimentation that can focus on specific processes or interactions. The goal of this project is to conduct such experiments to identify, elucidate the mechanisms of, and quantify 1) synergistic interactions between sorption, biodegradation, and transport processes; 2) processes occurring only in spatially heterogeneous porous media systems; and 3) competitive effects occurring in contaminant mixtures.

The research approach is to conduct laboratory experiments in one-dimensional flow columns as well as in multidimensional flow cells containing controlled porous media heterogeneities (i.e., intermediate-scale systems). The experiments begin with simpler systems and progress to more complex systems as phenomena occurring in the simpler systems become better understood. Reactive transport modeling is used interactively with

experimentation to resolve scientific issues regarding process mechanisms and their quantification.

The research of this project has been designed to build from the results of research done on other OHER subsurface science projects (summarized elsewhere in this volume). The projects are Subsurface Chemistry of Organic Ligand-Radionuclide Mixtures, Subsurface Microbial Processes, Chemistry/Microbiology Controlling Chelated Radionuclide Transport, and Hydrogeologic and Geochemical Controls on Microorganisms in Subsurface Formations. The first three of the companion projects are conducting mechanistic experimental investigations (and mathematical simulations) of the single processes of chemical sorption or microbiological degradation in static (batch reactor) systems. In addition, those projects are also investigating sorption/degradation interactions in batch systems. The last companion project is investigating the factors controlling the diversity and spatial variability of subsurface microflora, the correlation between microbial populations and key physical and chemical environmental variables of the stratigraphic unit in which they occur, and the degradative capabilities of microflora in various hydrogeologic environments. Research from this project extends the mechanistic understanding of processes and process interactions to dynamic transport systems, and further investigates this reactive transport and transformation behavior in laboratory systems with macroscopic-scale spatial heterogeneity in physical, chemical, and microbiological properties.

Through this year, compounds used for study on this project have been a subset of the organic chemical solutes chosen for study on the first two of the aforementioned companion projects. Quinoline, naphthalene, and aminonaphthalene were selected because they exhibit a range of chemical sorption and microbial degradation characteristics suitable for relevant transport experiments and because a significant base of information already existed on small-scale processes that affect them in batch systems. Quinoline undergoes hydrophobic sorption and pH-dependent sorption by ion exchange of the positively charged species and is associated with a relatively rapid rate of metabolic pathway induction and microbial transformation. Aminonaphthalene undergoes predominantly pH-dependent sorption by ion exchange of the

positively charged species, followed by a surface-catalyzed abiotic transformation on the clay surface, and is associated with a relatively slow rate of metabolic pathway induction and microbial transformation. Naphthalene undergoes only hydrophobic sorption and is associated with a relatively slow rate of metabolic pathway induction and microbial transformation. A fourth compound that has been extensively studied is 2-hydroxyquinoline, the primary transformation product of quinoline. Future research will focus on the behavior of organic/radionuclide mixtures. Therefore, the research of this project over the past year, summarized here, represents a move to completion of studies in several related areas using the initial suite of solely organic compounds.

The project began in FY 1989. Research efforts to date were divided into four areas: 1) one-dimensional transport with sorption, 2) one-dimensional transport with biodegradation, 3) one-dimensional transport with sorption and biodegradation, and 4) multidimensional transport in homogeneous and layered porous media systems. Initial year research concentrated on column studies with quinoline and tracer transport studies in multidimensional flow cells. In FY 1990, the column work was expanded to include studies with quinoline, 2-hydroxyquinoline, naphthalene, and aminonaphthalene, both singly and in selected combinations. FY 1990 efforts also included initial experiments on tracer and quinoline transport in multidimensional flow cells. In FY 1991, multisolute sorption/transport experiments in columns were completed and additional small-scale (i.e., batch and column) experiments on microbial growth and organic solute biodegradation were conducted. In addition, tracer transport and organic solute transport and biodegradation experiments were conducted in both homogeneous and multilayer intermediate-scale flow cells. FY 1991 effort also included the development of a new model for multidimensional reactive transport in layered porous media systems and its use in modeling experimental data.

Reactive Transport Model Development

In FY 1991, refinements and modifications were made to a two-dimensional model/code that accounts for coupled transport, chemical sorption,

microbial growth, and biodegradation. The numerical computer model uses a Principal Direction Finite Element Method (PDFEM) and an operator time-splitting technique that solves the differential equations of transport by decoupling the advection/dispersion steps from the chemical/microbial reaction steps. This results in a modular code structure that facilitates future code modifications to accommodate updated submodels of sorption and degradation as they are developed through project experimental research. Conceptual/mathematical reaction submodels that have been implemented in the code thus far describe linear equilibrium sorption and microbial growth and biodegradation by either single-Monod, dual-Monod, or biofilm kinetics.

In FY 1991, the numerical accuracy of the computer code was further examined, and it was found that there is inherent mass balance error associated with operator splitting for problems involving continuous mass input boundary conditions. A variant of the operator-splitting algorithm was developed that reduces mass balance errors by more than a factor of 10 for a wide range of conditions. The code was further modified to accommodate sequential (rather than single) biodegradation reactions involving up to four organic electron donors. Initial verification tests of this capability have shown close agreement between code predictions and analytical solutions of the one-dimensional test problem. Furthermore, even though this computer code is a research code rather than a user application code, it was modified to be more user friendly and an informal user's guide was written.

Two-dimensional simulations of a physically relevant example scenario were run to investigate differences in predictions that use multiplicative versus minimum-rate formulations of the dual-Monod biodegradation kinetics. Significant differences were shown to occur between the two formulations when the half-velocity coefficients (i.e., the concentration at which the biodegradation rate is half its maximum value) are on the same order of magnitude as the substrate input or background concentration.

Test simulations in a physically relevant example scenario (with layered porous media) were continued in FY 1991 to determine the importance of

interlayer mass transfer of substrate and electron acceptor on predictions of microbial growth and biodegradation. Model simulations predicted that the most rapid microbial biomass growth and biodegradation activity occurred at the layer interfaces. Furthermore, the biomass growth and substrate biodegradation were enhanced in simulations that used increased interlayer transfer (caused by higher values of transverse dispersivity). This indicates that interlayer transfer in heterogeneous media can play an important role in overall biodegradation of contaminants in the field.

One-Dimensional Transport with Multisolute Sorption

Column experiments were performed to investigate the simultaneous and interactive sorption and transport of a mixture of quinoline, naphthalene, and aminonaphthalene. The objectives of the experiments were to determine 1) the existence and magnitude of competition for sorption sites in a flowing pore solution of organic solutes, where some of the solutes sorb to the porous medium by similar mechanisms and others sorb by dissimilar mechanisms; and 2) whether surface-chemical reactions involving an organic solute flowing through a packed porous medium can irreversibly alter the mobility of both that solute and other organic solutes in the affected porous media system. The columns used in the experiments were packed with clay-coated alumina particles (the clay being the sole sorbent phase) and contained no microbes that degraded the organic compounds injected into the columns (to eliminate possible complications in evaluating multisolute sorption behavior caused by microbial processes). The rationale for using and the methodology for producing clay-coated alumina, as well as the experimental protocol for conducting column experiments, were discussed in PNL (1990).

Figure 1 shows results from one set of experiments that consists of five separate pulse injections of different aqueous mixtures of organic compounds into the steadily flowing column influent solution. These five pulses were injected into the same column sequentially over time. Figure 1a shows the concentrations of naphthalene, quinoline, and (in some cases) aminonaphthalene in each of the five injection solutions. After each

FIGURE 1. Effects of Sorption Competition and Irreversibility on Solute Mobility During Five Consecutive Multisolute Pulse Injection Column Experiments: a) Composition of the Injection Solution for Each Pulse Injection; b) Observed Dynamic Sorption Coefficient (K_d) for Naphthalene, Quinoline, and Aminonaphthalene Calculated from Solute Breakthrough Curves

injection, the solute mixtures were allowed to migrate completely through the column, and effluent concentrations were measured. Dynamic sorption coefficients for each solute were calculated by analyzing the effluent breakthrough curves. Figure 1b gives the observed sorption coefficients (K_d) for each solute as calculated after each injection experiment. This figure shows that the sorption and retarded migration of naphthalene are unaffected by the presence of the other compounds, as expected from previous batch and column experimental results, because naphthalene undergoes only hydrophobic (non-site-specific) sorption, while the other compounds sorb by (site-specific) ion exchange of the protonated species. The results of the first two injections show that quinoline sorption and mobility are also unaffected by naphthalene and that the sorptive properties of the porous media system containing only these

two solutes do not change with time. In contrast, injection experiments 3 and 4 show that aminonaphthalene and quinoline compete for ion exchange sites, as expected from previous research results, and that for each solute, the effective sorption is decreased and the effective mobility is increased. Furthermore, these two injections also show that the changes in effective sorption and mobility intensify over time in this system. This is because aminonaphthalene undergoes a surface-catalyzed transformation reaction into an irreversibly sorbed compound that progressively reduces the number of available ion exchange sites in the system. The results of injection experiment 5, which again contains only quinoline and naphthalene, show that this alteration persists even after aminonaphthalene has been flushed through the system.

This behavior has significant ramifications for field-scale migration of mixtures of organic contaminant with similar characteristics. If the field site has a relatively low density of porous media sorption sites and relatively high concentrations of compounds like aminonaphthalene in the contaminant plumes (as is the case in these column experiments), the mobilities of all ion exchanging contaminants in the plume may all be irreversibly increased (with respect to what would be predicted from the results of single-solute research). However, in contrast, if the sorption site density is relatively high and the solute concentrations are relatively low, the irreversible binding of transformation products to ion exchange sites may serve to eventually remove all of these compounds from the flowing pore water, thereby effectively reducing the mobility of these compounds to zero.

Batch Biodegradation and One-Dimensional Transport with Biodegradation

Microbial processes in porous media can be affected by the flow of water and substrates and potentially by the physiological differences between an attached rather than planktonic mode of growth. Microbial kinetic parameters, however, have conventionally been determined without the presence of porous media. Microbial kinetic experiments were conducted in batch reactors and in columns of porous media subjected to water flow to determine 1) whether there were any detectable differences between the kinetic

parameters for microorganisms in batch systems compared with those in flow systems and 2) the proper kinetic parameters to use in related biodegradation experiments in porous media. This information provided a basis for planning, interpretation, and simulation of intermediate-scale experiments involving microorganisms.

Kinetic parameters (i.e., maximum specific growth rate and yield) for microorganisms in batch reactor systems (without porous media) were investigated in a series of experiments. Batch reactors were inoculated with a quinoline-degrading bacterium used in previous experiments. Initial inoculation densities were low, and microbial numbers and substrate (2-hydroxyquinoline) concentrations were monitored in the reactor over time. Batch kinetic parameters were determined for organisms given two treatments. In the first treatment, the enzymatic pathway needed to degrade 2-hydroxyquinoline had been preinduced before the kinetic experiments began; in the second treatment, it had not. The purpose of these two treatments was to determine whether there was a detectable difference in the specific growth rate or yield between the preinduced and uninduced organisms. The kinetic parameters determined from these experiments are given in Table 1. There was no statistical difference between the two treatments at a 1% level of significance.

Kinetic parameters for microorganisms grown in porous media subjected to water flow were investigated in a series of column experiments. For each experiment, glass columns were packed with glass beads inoculated with the quinoline-degrading bacterium used in the batch experiments. Again, the inoculation density was low and the enzymatic pathway for quinoline degradation was preinduced before the start of the experiment. Substrate (2-hydroxyquinoline) was continuously

injected into each column in an influent solution of constant substrate concentration. Microbial growth was monitored over time by periodically destructively sampling the porous media in one of a series of replicate column set-ups. Column effluent samples were also taken and analyzed for the substrate so that the yield coefficient (i.e., mass of cells produced per mass of substrate degraded) could be calculated. The change in microbial mass was determined by protein analysis of the porous media. Results of these experiments also appear in Table 1. Analysis of the yield coefficient for these experiments is still under way. These experiments show that the maximum specific growth rate in porous media subjected to flow was approximately 10 times lower than that in batch reactors. This suggests that the conventional means of determining microbial kinetic parameters (i.e., in batch reactors) may not be applicable to microbes present in porous media. Some possible explanations for the slower observed growth rate in the column system are: 1) substrate uptake may be reduced because attachment to the solid phase reduces the surface area exposed to the aqueous phase, and 2) attached organisms may have a thicker capsule that reduces the diffusion rate of substrate to the cell wall.

Continued experimentation will include batch growth experiments with starved organisms. The growth kinetics of organisms in a starved state have not been investigated in detail. Because organisms in the subsurface may exist in highly oligotrophic environments, understanding the kinetic responses of starved organisms may be important to the use of native communities for remediating sites contaminated with organic chemicals.

Intermediate-Scale Organic Solute Transport with Biodegradation in a Homogeneous System

Processes that were studied at a small scale this year and in previous years were studied at a larger scale to determine the effects of macroscopic-scale spatial variation in porous media properties on the coupled processes. However, to increase our ability to mechanistically analyze coupled sorption and biodegradation during transport in porous media systems with physical heterogeneity, studies began with

TABLE 1. Microbial Kinetic Parameters Obtained from Batch Reactor and Flow Column Experiments

Experiment Type	Specific Growth Rate (h ⁻¹)	Yield (colony-forming units mg ⁻¹)
Batch reactor - induced	0.234	1.13 x 10 ⁹
Batch reactor - uninduced	0.235	8.24 x 10 ⁸
Flow column - induced	0.024	---

experiments focusing on fewer processes in simpler intermediate-scale transport systems. Thus, the experimental sequence accomplished this year began with studies of biodegradation in a single homogeneous layer and then progressed to studies of tracer transport in multiple layers and biodegradation in multiple layers.

The intermediate-scale transport experiments in spatially homogeneous porous media systems used the same flow cells and experimental protocols as the experiments in heterogeneous systems described in the following sections. These flow cells are 100 cm long by 20 cm high by 10 cm wide and are constructed of stainless steel with Teflon seals to minimize interactions with solutes. The dimensions of the flow cell allow for transport in multiple layers of porous media with diffusion between layers on the timescale of several hundred hours. Larger flow systems would allow for greater diffusion time between layers, but this was not necessary for the timescales of the sorption and biodegradation processes of interest. Pore solution within the flow cell can be sampled through a multidimensional array of ports on the side of the cell. Point sampling of solution in the flow cell is automated, and the solution volume extracted from the system is minimized. Typically, the rate of flow through the detection system is less than 0.25% of the flow through the flow cell and the fluid removal is discontinuous (continually switching to different locations). This minimizes perturbation of the flow within the cell caused by sampling. A second set of sampling ports and multiplexers was connected to a pressure transducer to monitor fluid pressures within the cell at different locations. In situ monitoring of chemical transport is also possible with microelectrode (pH, calcium, chloride, oxygen, and carbon dioxide) emplacement directly in the flow path through the sampling ports. The flow cells also have one glass side to facilitate visualization during dye transport experiments. Although the velocity along a wall is typically 40 to 60% slower than the average velocity, visual experiments are extremely useful because of the large quantity of information that can be collected in a short time.

The intermediate-scale experiments involved horizontal water flow and organic solute-front injection into the water inlet end of saturated one-, two-, or

three-layer porous media systems. Solute concentrations were sampled at multiple points longitudinally and laterally in the flow cell, especially near layer interfaces. Typically, 8 to 20 points in the flow cell were intensively sampled at multiple times during the 100 to 500 hours of a single experiment. Solution samples from these points were analyzed for one to three solutes or tracers. Each biodegradation experiment had associated tracer experiments designed to collect hydrologic information about the system. Tracer was injected either as a solute front or as continuous or discrete point injections. Intermediate-scale biodegradation experiments required additional effort to minimize microbial contamination in the experimental apparatus. The inlet system of the intermediate-scale system contained a high-pressure 0.1-mm filter to prevent upstream migration of the microbes into the feed solution. Microbes were mixed with the porous media as a slurry, then packed into the flow cell. For more details of the experimental protocol, as well as schematic diagrams of the flow cell experimental setup, see PNL (1990, 1991).

Two intermediate-scale experiments with biodegradation in a single layer were conducted in FY 1991. The purpose of the first experiment was to quantify the oxygen limitation of the biodegradation reaction observed at a smaller scale and to collect base-line data to compare to transport with biodegradation in a multilayered system. It was hypothesized that oxygen-limited biodegradation would be observed at some downgradient locations in the transport path when reactive transport occurred over this spatial scale. Sampling at multiple locations in the flow cell (as opposed to only effluent sampling of previous column experiments) would facilitate quantification of the process. Microbial growth was minimized by using a high initial population density. This was confirmed after the 250-hour experiment by measurements of microbial protein densities in sections of the porous media. Ten in situ points were sampled over the course of the experiments (longitudinal and transverse arrays).

Figure 2 shows concentration profiles along the longitudinal flow path at three times. Quinoline and 2-hydroxyquinoline (the first degradation product of quinoline) were measured at seven

FIGURE 2. Concentration Profiles Along a Longitudinal Section of the Intermediate-Scale Flow Cell During Solute Transport with Biodegradation: Quinoline ($\blacklozenge$), 2-Hydroxyquinoline ($\circ$)

longitudinal points. The microbes in the system initially did not have the metabolic pathway for quinoline biodegradation induced. The profile at 0.5 hour (see Figure 2a) shows advective breakthrough of quinoline before biodegradation had begun in the flow cell. Quinoline breakthrough was complete by 4 hours. The profile at 40 hours (see Figure 2b) shows a decrease of quinoline concentration and the increase of 2-hydroxyquinoline concentration across the cell, indicating that the degradation pathway had been induced and that biodegradation is occurring. By 95 hours (see Figure 2c), the microbes had acclimated to quinoline degradation and an overall steady-state degradation rate was achieved (i.e., profiles at later times are similar). Note that almost all of the degradation takes place in the first few centimeters of the flow cell. The fact that appreciable concentrations of quinoline still exist in the down-gradient locations of the flow cell implies that lack of an electron acceptor (oxygen) may be limiting further degradation at those locations, a fact confirmed in subsequent small-scale batch and column experiments. The size of the intermediate-scale experiment enabled measurement of a decrease in oxygen concentration across the cell that was consistent with the oxygen limitation hypothesis. Solute concentrations measured in

transverse arrays of points confirmed that degradation behavior at points of constant horizontal location was similar. This verifies that a fairly uniform microbial population and flow field was created at this scale.

Data from these experiments are in the process of being analyzed with a multidimensional reactive solute transport model. Figure 3 gives an example of model simulations of time variation in quinoline and microbial concentrations at a fixed location using a single-Monod conceptualization for biodegradation and varying the value of q_m , a parameter that determines the maximum substrate biodegradation rate as well as the microbial growth rate. The curves on Figure 3 demonstrate how quinoline concentration decreases faster and how microbial biomass increases faster but levels off sooner as q_m increases. After modeling experimental data, the model will be used as a simulation tool, as in Figure 3, to investigate the sensitivity of the predicted system behavior to the values chosen for the input parameters.

A second intermediate-scale biodegradation experiment was conducted in a homogeneous packing of porous material for the purpose of determining the effect of biodegradation on hydraulic properties. Pressure was monitored at 18 locations over the 350-hour experiment and was found to decrease slightly (<2%) with time at almost all positions. Thus, there was no recorded increase in pressure at 5 cm or greater in the flow cell, even though there was an order of magnitude increase in microbe concentration at the inlet. Subsequent calculations of the additional pore volume the microbes would occupy, based on the growth of microbes near the inlet of the flow cell, indicate that only pore space in the first 2 to 3 cm of the flow cell would have been affected. Because the experiment was maintained at a constant water flux, significant microbial clogging of porous media at the inlet would have required a pressure increase at that end. This pressure increase at the inlet would have caused a corresponding increase in pressure and pressure gradient at locations farther downgradient. Because this was not observed, the uniform pressure decrease at downgradient locations was instead possibly caused by a slight grain rearrangement or movement of microbes.

FIGURE 3. Model Simulations of Quinoline Breakthrough and Microbial Biomass Changes During Transport with Biodegradation Showing the Effect of Variation in Maximum Specific Substrate Degradation Rate, q_m ($q_m = \mu/0.388$)

Intermediate-Scale Tracer and Organic Solute Transport with Biodegradation in a Layered System

Several field investigations by other researchers have noted increased microbial activity near hydraulic layer interfaces. To investigate this phenomenon in the laboratory, a two-dimensional flow system in layered media was created in which dispersion could be quantified within layers and between layers. The objectives of this research were to 1) quantify the microbial and hydraulic processes that occur in a two-dimensional flow field near hydraulic layer interfaces and 2) determine to what extent microbes can actively move across layer interfaces (i.e., microbial taxis) to reach zones of increased substrate or electron acceptor concentration. A series of intermediate-scale experiments was conducted in flow cells

(described above) packed with two layers of saturated porous media. Relatively fast horizontal transport was established in the upper (high-hydraulic-conductivity) layer, and relatively slow horizontal transport was established in the lower (low-hydraulic-conductivity) layer (Figure 4). In addition, interlayer mass transfer from the upper layer into the lower layer occurred as a result of transverse dispersion. Figure 4 shows the approximate tracer fronts at various times, including the effect of lateral (vertical) mass transfer of the tracer. Tracer advective breakthrough time was approximately 20 hours in the high-conductivity layer and 400 hours in the low-conductivity layer.

To fully characterize the two-dimensional flow field, a series of five tracer experiments was conducted in the two-layer system. The series included tracer injection as a vertical front and at a point

FIGURE 4. Conceptualization of an Intermediate-Scale Experiment for Solute Transport with Biodegradation in a Physically Heterogeneous (layered) Flow Field Showing Tracer Front Positions at Different Times

Before and after the biodegradation experiment, and tracer front injection during the biodegradation experiment. The repeat tracer experiments after the biodegradation experiment were used to compare the effect of biodegradation during the course of the experiment on hydraulic properties. Typical tracer breakthrough curves at three locations that differ in their proximity to the layer interface are shown in Figure 5. Figure 5a shows fast breakthrough at the sampling point in the high-conductivity layer and Figure 5c shows slow breakthrough at the sampling point in the low-conductivity layer. Both of these curves have the smooth sigmoidal shape associated with one-dimensional advection and dispersion in columns. Tracer breakthrough at a point in the low-conductivity layer near the interface shows mixed breakthrough (see Figure 5b). The early arrival of the tracer mass results from transfer by transverse dispersion from the high-conductivity layer, while the later breakthrough results from the horizontal advection in the low-conductivity layer. The curves shown in Figure 5 are two-dimensional model fits to the data and are used to quantify the mass transfer rates within and between layers. The same two-dimensional reactive transport model, as well as the results of modeling the tracer data, was also used to model the associated organic solute transport/biodegradation experiments.

Prior to the flow cell experiments of organic solute transport and biodegradation, the flow cell was packed in such a way as to inoculate the lower (low-conductivity) layer with microbes, while

leaving the upper (high-conductivity) layer without microbes that could degrade the organic solute used for the study. The experiment consisted of solute (quinoline) and tracer injection into the two-layer system as a uniform vertical front for 515 hours. Pore fluid was sampled at 20 locations during the experiment, and microbial populations in the porous media were sampled at 53 locations at the end of the experiment. Fluid samples were analyzed for quinoline, 2-hydroxyquinoline (first degradation product), oxygen, and carbon dioxide.

Quinoline concentrations throughout a two-dimensional vertical cross section of the flow cell are presented in the shaded plots of Figure 6 for five different times during the experiment. Higher quinoline concentration is shown as a darker color. The plots at 5 hours and 30 hours show the faster breakthrough in the high-conductivity layer (top portion of each plot) and the slower breakthrough in the low-conductivity layer. As contact time between the microbes and the quinoline plume increases, the microbes induce a metabolic pathway for quinoline degradation and the degradation rate increase to its steady-state value. As this happens, quinoline concentration at that location decreases. Although quinoline is still being continuously injected, by 70 hours the concentration has decreased at all locations because of this degradation process. Of specific interest is the plot at 85 hours, where there is increased degradation at the layer interface, as shown by a lower quinoline concentration at the layer interface.

FIGURE 5. Tracer Breakthrough Data and Model Simulations for a Two-Layer System at Three Vertical Locations Within the Flow Cell: a) in High-Conductivity Layer, b) Near the Interface Between Layers, and c) in Low-Conductivity Layer

FIGURE 6. Quinoline Concentrations in a Vertical Cross Section of a Layered Flow Cell at Five Different Times During a Solute Transport Experiment with Biodegradation (darker shading corresponds to higher concentration)

Increased degradation at the layer interface was initially facilitated by early development of steady-state degradative capability in the microbes near the interface because of early arrival of substrate through interlayer transfer. This initial degradation activity resulted in more rapid growth of the microbes at the interface (initial protein concentration was $3 \mu\text{g g}^{-1}$ throughout the lower layer), which in turn led to further increases in substrate utilization. The spatially variable microbial growth during the experiment is illustrated in the shaded contour plot of microbial population density presented in Figure 7. Also of interest is the fact that there are microbes in the high-conductivity layer at

the end of the experiment (see Figure 7). Because there were no microbes in this layer initially and because this layer is upgradient in the water flow field, chemotaxis of the microbes must have occurred.

Quantification of the microbial growth and biodegradation processes in this two-dimensional flow system was possible given the separate analyses of associated tracer experiments quantifying physical transport processes, earlier small-scale biodegradation experiments quantifying the biological process, and a two-dimensional transport code incorporating a dual-Monod formulation of

FIGURE 7. Distribution of Microbes (measured as microbial protein concentration) Throughout the Flow Cell at the End of the Two-Layer Transport/Biodegradation Experiment

the biodegradation process. The simulation of coupled transport, microbial growth, and biodegradation in a two-dimensional transport field is illustrated in Figure 8, which shows comparisons of data and model simulations at three locations in the flow cell that differ in their proximity to the layer interface. In the high-conductivity layer (see Figure 8a), quinoline breakthrough was relatively fast (10 hours), with degradation reaching steady state by 140 hours. This is in contrast to the quinoline behavior in the low-conductivity layer (see Figure 8c), where breakthrough occurs after 60 hours and reaches a steady state by 100 hours. The effect of early metabolic pathway induction in the microbes near the layer interface is illustrated in Figure 8b, where the quinoline breaks through in 20 hours (because of interlayer transfer from the high-conductivity layer) and steady-state degradation is reached by only 90 hours. In addition, the peak concentration of quinoline at the layer interface (see Figure 8b) is smaller because the microbes at the layer interface can degrade quinoline at a higher rate by the time the advective front of quinoline reaches them.

Future Directions

Compounds to be used for study on this project in the future will be select mixtures of organic chemicals and radionuclides [e.g., ethylenediaminetetraacetic acid (EDTA), nitrilotriacetic acid (NTA), organic acids, humic substances, Co, and U]. This represents a realignment in the focus of the Subsurface Science Program that has occurred because radionuclides are major contaminants at DOE sites, they are often codisposed with organic contaminants, and their behavior when interacting with natural or anthropomorphic organic compounds is poorly understood. Over the last year, companion projects have initiated investigations of the mechanistic behavior of organic/radionuclide mixtures in batch reactor systems. Understanding of the small-scale behavior of organic/radionuclide mixtures gained from these investigations is now sufficient to allow the transport research of this project to transition into studies using these new compounds.

FIGURE 8. Data and Model Simulations of the Breakthrough of Quinoline (♦ and solid lines), 2-Hydroxyquinoline (▲ and dotted lines), and Oxygen (○ and dashed lines) During Transport with Biodegradation at Three Vertical Locations Within the Flow Cell: a) in High-Conductivity Layer, b) at Interface Between Layers, and c) in Low-Conductivity Layer

References

PNL. 1990. *Pacific Northwest Laboratory Annual Report for 1989 to the DOE Office of Energy Research, Part 2: Environmental Sciences.* PNL-7200 Pt. 2, Pacific Northwest Laboratory, Richland, Washington.

PNL. 1991. *Pacific Northwest Laboratory Annual Report for 1990 to the DOE Office of Energy Research, Part 2: Environmental Sciences.* PNL-7600 Pt. 2, Pacific Northwest Laboratory, Richland, Washington.

Manipulation of Natural Subsurface Processes: Field Research and Validation

J. S. Fruchter, J. M. Zachara, J. K. Fredrickson, C. R. Cole, J. E. Amonette, T. O. Stevens, D. J. Holford, L. E. Eary, G. D. Black, and V. R. Vermeul

The subsurface environment is a chemically dynamic system in which naturally occurring processes control the mobility of chemical substances. These natural processes, which include precipitation/dissolution, adsorption/desorption, and chemical degradation, may be mediated by microorganisms, by purely abiotic processes in nature, or by a combination of both.

One of the system variables in the subsurface environment that has a considerable effect on these natural processes, and therefore on the persistence and mobility of chemical species, is the redox potential. Affected chemical species include organic molecules, through effects on both mobility and degradation, and a number of multivalent inorganic species, including chromium, uranium, technetium, selenium, mercury, and arsenic. Thus, manipulation of the redox potential in the subsurface environment is a possible avenue for control of the behavior of these species in groundwater aquifers and other subsurface environments.

Through long periods of time, the redox potential of subsurface environments is controlled by the rate at which atmospheric oxygen enters the system, and whether this rate is sufficiently fast to overcome reducing and/or oxygen-consuming processes in the system. However, it is possible that short-term changes of the redox potential of the subsurface system could be achieved by the introduction of chemical reagents or microbial nutrients, which may facilitate irreversible degradation or precipitation of select contaminants for periods that extend beyond the manipulation period.

A series of field injection experiments has been proposed to investigate the mechanisms by which redox manipulation of an unconfined aquifer at the

Hanford Site might be achieved. The goal of the experiments is to provide data for validation of concepts and models derived from laboratory and intermediate-scale investigations under way to predict the effects of alterations in chemical and microbial parameters in saturated strata in the subsurface. These experiments will investigate the rates and mechanisms of abiotically and microbiologically facilitated water/rock electron transfer reactions and the effects of such processes on the geochemistry of the groundwater system.

Design of a field injection experiment requires a knowledge of fundamental geochemical, microbiological, and hydrologic processes operating simultaneously and interactively in the subsurface. This synopsis summarizes initial investigations to 1) define the effectiveness of abiotic reducing agents; 2) determine the type, abundance, function, and nutrient requirements of microorganisms capable of altering redox in situ at the proposed experimental site; and 3) model and visualize the effects of key subsurface phenomena and determine their sensitivity to natural system heterogeneity and experimental parameters.

Proposed Approach

The proposed approach for these field experiments is to actively control site conditions by pumping water containing specific reagents or nutrients into the subsurface, and subsequently withdrawing the water through the same well ("push-pull test"). A simplified conceptual layout for the proposed field site is shown in Figure 1. The proposed approach allows examination of the system's response to these relatively rapid changes and has the following additional advantages:

- well-defined initial conditions - Because the constituents to be studied are injected at the beginning of the experiment, the initial mass, volume, location, chemical, and hydraulic parameters are better defined.
- minimized characterization problems - Because a relatively short time will have elapsed between injection/withdrawal and sampling, a relatively small volume will have to be sampled.

FIGURE 1. Simplified Conceptual Diagram of the Proposed Push-Pull Field Experiment

- ability to control the movement of the solutes - By forcing a hydraulic gradient through pumping/withdrawing, the pathway taken by the reactive solutes can be better controlled.

This approach also lessens the difficulty of the sampling problem.

Chemical Reduction

As shown recently by Barcelona and Holm (1991) for a sand and gravel aquifer, most of the oxidizing or reducing capacity of an aquifer system is incorporated in the aquifer solid phases. However, the most practical avenue for altering the aquifer redox is to alter the chemistry of the groundwater that contacts the solid phase. Thus, the problem centers on defining and estimating the mechanisms and kinetics of electron transfer reactions between constituents in the aqueous phase and redox-sensitive species in the heterogeneous solid phase.

Research was directed toward estimating the rate of reductive dissolution of goethite and reduction of structural Fe in smectite, principal mineral phases at the proposed experimental site with potential for poisoning groundwater. Reducing agents selected were sulfite ion, dithionite ion, and hydroxylamine. Reductive dissolution of both natural and synthetic goethites by sulfite was examined in sealed reaction vessels at $25 \pm 1^\circ\text{C}$. The procedure involved adding an aliquot of a concentrated Na_2SO_3 solution to a goethite suspension that was initially saturated with dissolved oxygen and then following the subsequent changes in the concentrations of $\text{O}_2(\text{aq})$, $\text{Fe}(\text{II})$, total Fe, Eh, and pH with time.

Smectite was isolated from R-9, a beidellite clay from an exposed fine-grained lens in the Ringold Formation at the Hanford Site, and from BB-90-14, a well core sample from the Yakima Barricade test well also in the Ringold Formation at the Hanford Site. A $<2\text{-}\mu\text{m}$ fraction of each sample was used and was shown to be at least 95% smectite by x-ray diffraction. The elemental analysis of BB-90-14 was very similar to that for R-9 shown in Table 1.

For the smectite experiments, smectite (50 mg) was measured into polypropylene bottles (125 mL), and a 0.9 M NaHCO_3 -1% Na-citrate

TABLE 1. Elemental Oxide Composition of the Ca-Saturated, $<2\text{-}\mu\text{m}$ Fraction of Sediment R-9 from a Fine-Grained Lens in the Ringold Formation, Hanford Site

Oxide	Weight %
Na_2O	0.63
MgO	1.86
Al_2O_3	22.18
SiO_2	57.97
K_2O	1.31
CaO	1.43
TiO_2	0.65
FeO	0.11
Fe_2O_3	7.12

solution (10 mL) was added to buffer the pH and to complex soluble Fe. Next, the reductant was added either in H_2O (20 mL) containing sulfite or hydroxylamine or, in the case of dithionite, as a solid in 500-mg portions, and the bottles were capped tightly and incubated for different periods of time. Because of the slow rate of reaction in the goethite experiments, it was decided to incubate the smectite samples at 60°C . At the end of each prescribed period, the bottles were removed, the smectite was separated from the solution by centrifugation, and the content of $\text{Fe}(\text{II})$ and total Fe was determined by the complexometric method of Komadel and Stucki (1988). For the treatments with hydroxylamine, the total reductive capacity was determined by the oxidimetric method of Amonette and Scott (1991) because the complexometric method did not have sufficient precision.

Typical goethite reductive dissolution is shown in Figure 2 (natural goethite). The pH initially rose to a stable value because of the protonation of SO_3^{2-} ($\text{SO}_3^{2-} + \text{H}^+ = \text{HSO}_3^-$), while the Eh rapidly decreased because of the consumption of dissolved oxygen by reaction with the HSO_3^- ($\text{HSO}_3^- + 1/2 \text{O}_2(\text{aq}) \rightarrow \text{SO}_4^{2-} + \text{H}^+$). The $\text{O}_2(\text{aq})$ concentrations decreased rapidly during the first 15 min of the reaction and remained at low values for the remainder of the experiment. The concentration of $\text{Fe}(\text{II})$ rose to slightly above the detection limit of 50 ppb after 1 hour and increased slightly thereafter to 125 ppb. All dissolved Fe was determined to be $\text{Fe}(\text{II})$, indicating that some reductive dissolution of the goethite had occurred but at a very slow rate. Increasing the initial ratio of SO_3^{2-} to $\text{O}_2(\text{aq})$ produced a slightly greater rate of

FIGURE 2. Natural Goethite Dissolution (0.5 g L^{-1}) in $12.6 \text{ mmol L}^{-1} \text{ Na}_2\text{SO}_3$ Solution at 25°C and Ionic Strength = 0.15 M

reduction dissolution of the natural goethite, as indicated by higher Fe(II) concentrations (not shown), but the effect was small and has not been investigated in detail.

Similar results were obtained for reduction of Fe in smectites by 0.07 M sulfite solutions during periods of 48 hours at 60°C (not shown). Saturation of the cation exchange sites on the smectite with Zn^{2+} ions to promote electron transfer between the solution and the structural Fe had no effect on the reaction. Attempts to reduce structural Fe in smectites with hydroxylamine were inconclusive because of hydroxylamine sorption to clay surfaces.

Treatments of the smectite with dithionite proved successful in reducing the structural Fe (Table 2). Although these experiments were not performed at room temperature, there seems little doubt that dithionite acts as an efficient and aggressive reductant of structural Fe in neutral or slightly alkaline solutions at these temperatures (Stucki

TABLE 2. Fractions of the Total Fe in the R-9 Smectite Reduced by Successive Dithionite Treatments at 60°C in Aerated and Nonaerated (capped) Systems

Number of Treatments	Structural Fe Reduced (% of total Fe)	
	Nonaerated	Aerated
1	47	25
2	56	35
3	57	27
4	61	36

et al. 1984). Successive treatments with dithionite increased the amount of structural Fe reduced, up to a limit of about 60% of the total Fe present in the clay. Whether this value represents a fundamental limit to structural Fe reduction or reflects reoxidation during the preparatory and dissolution stages of the Fe(II) analysis is unclear. At temperatures of 70°C , Stucki et al. (1984) were able to reduce only 78% of the total Fe in a high-Fe smectite using dithionite, even after treatments under an inert atmosphere for periods up to 1 week.

To gauge the sensitivity of the clay to reoxidation by air, one set of samples was reduced without capping the bottles. The amount of reduction obtained was only about half as much as when the caps were left on. It seems clear, then, that the smectites, once reduced in an aquifer, will readily react with oxygenated water flowing into the zone.

The results of these preliminary investigations suggest that dithionite will reduce structural Fe in the aquifer minerals present at the prepared experimental sites. Carefully controlled experiments with both smectites and iron oxides at different temperatures and under controlled atmospheres must be performed to quantitate the reaction rates. Dithionite is a promising reagent because 1) it does not persist in aqueous solution (dithionite undergoes a rapid disproportionation reaction to bisulfite and thiosulfate ions) and 2) neither dithionite or its products precipitate readily or are toxic at neutral or higher pH. Experiments to measure the kinetics of the disproportionation reaction under conditions comparable to those in the aquifer need to be performed. These results must then be combined with those for the heterogeneous reduction

reactions with structural Fe to model the effective lifetime of dithionite in the aquifer.

The use of hydroxylamine should also be re-examined as an adsorbable reductant. The pK_b of hydroxylamine is 8.3, indicating that equal amounts of its protonated and neutral moieties exist in solutions at pH 5.7. The combination of adsorption and structural Fe reduction might be used to advantage in creating an in situ zone poised at a given redox potential.

Other possible reductants that should be investigated include phosphinic acid or Ca-phosphinate, ascorbate ion at neutral pH, and possibly NaS. Several gaseous reductants (SO_2 , H_2S , etc.) offer potential for efficient delivery; however, their poor adhesion to charged solid surfaces in aqueous solutions suggests that the aqueous ions in equilibrium with the dissolved gas (e.g., sulfite ion) will be the actual heterogeneous reductants.

Once the effective reductant systems have been selected, the reaction kinetics with the aquifer groundwater and solids must be carefully determined so these parameters can be incorporated into reaction models for the field test experiment.

Microbiological Reduction

Before design and implementation of experiments to investigate redox manipulation in the field, it is necessary to determine the types of indigenous microorganisms present and their nutritional requirements. Because of expected heterogeneities in these parameters, core samples were collected from the unconfined aquifer, taking advantage of regulatory characterization at a borehole (300-FF-5, #4c) drilled near the 300 Area in proximity to the proposed field test site. A total of five core samples were obtained, the first of which was an intact fine-grained sediment of very high quality. The other four samples had obviously been physically disturbed (e.g., fractured gravels, cobbles, and mixing of sediments) during drilling. Because no water was added to the borehole, it was expected that microbiological integrity was maintained.

Two types of measurements were conducted. Specific functional groups of bacteria were enumerated based on the terminal electron acceptor used, and the potential for degradation of

different types of organic carbon sources was assessed. The functional groups examined included 1) aerobic heterotrophs, 2) fermentors, 3) denitrifiers, 4) Fe(III) reducers, 5) sulfate reducers, and 6) methanogens. Given that the upper portion of the confined aquifer on the Hanford Site is oxic, few, if any, strict anaerobic bacteria were expected. The results were in good agreement with this prediction. The most numerous functional group in all samples was the aerobic heterotrophic bacteria, which ranged between 10^4 and 10^7 colony-forming units g^{-1} sediment (Table 3). Bacteria capable of fermenting glucose were also present in every sample, albeit at lower populations than were aerobic heterotrophs. Denitrifiers, bacteria that can grow anaerobically and reduce nitrate, were also abundant. Fe(III)-reducing bacteria were above detection in only one sample, but the analyses were confounded by the presence of high concentrations of Fe(II) in the samples that were physically disturbed. Enrichments are being repeated with a different culture medium. Sulfate-reducing bacteria and methanogens were not detected in any of the samples.

Microbial utilization of organic substrates was determined using an automated respirometer that measures both CO_2 evolution and O_2 consumption. The aerobic respiration was measured on the basis that before fermentation reactions can proceed, the dissolved O_2 in the groundwater first must be utilized by aerobic respiration. Little aerobic respiration was observed with any of the substrates in a fine-grained sediment from 15.0 m, except for oxalate (Figure 3). However, when sediments were amended with nitrogen, a respiration response with most of the substrates was observed. Samples were preincubated with substrate for a minimum of 24 hours to stimulate microbial activity, so some of the more readily metabolizable substrates already may have been depleted before measuring respiration. These results indicate that microbial activity in the unconfined aquifer is nitrogen limited and that the addition of nitrogen will likely be required to stimulate microbial activity and reduction. The likely reason that oxalate promoted respiration in the sediment not amended with nitrogen was that it was added as the ammonium salt. In the samples physically disturbed by hard-tool drilling, significant consumption of O_2 was accompanied

TABLE 3. Populations of Functional Groups of Bacteria in Core Samples Obtained from Hanford Redox Field Manipulation Site

Sample Depth (m)	Aerobes (log CFU g ⁻¹) ^(a)	Fermentors (log MPN g ⁻¹) ^(b)	Denitrifiers (log MPN g ⁻¹)	Fe(III) Reducers (log MPN g ⁻¹)	Sulfate Reducers (log MPN g ⁻¹)	Methanogens (log MPN g ⁻¹)
15.0	4.9	>1.0	3	BD ^(c)	BD	BD
22.4	5.7	0.7	<4	>1	BD	BD
27.6	5.8	0.5	<5	BD	BD	BD
30.0	6.9	0.7	<4	BD	BD	BD
38.1	3.6	1.2	3.3	BD	BD	BD

(a) CFU = colony-forming units.

(b) MPN = most probable number.

(c) BD = below detection.

FIGURE 3. Respiratory (O₂ consumption and CO₂ evolution) Response of Sediment Samples from 15.0 m Amended with Various Carbon Sources With and Without Nitrogen (CMC = carboxymethyl cellulose)

by little CO_2 evolution (Figure 4), likely a result of increased exposure of Fe(II) on mineral surfaces, which acted as a reductant. Although this abiotic reduction complicated interpretation of the results, CO_2 evolution was still clearly stimulated by the addition of nitrogen.

A summary of the results and their implications are as follows: 1) active aerobic and facultative anaerobic bacterial populations are present in the subsurface sediments in the vicinity of the proposed field site; in situ stimulation of the indigenous microbiota to reduce O_2 and NO_3 is feasible; 2) the native microbial populations can utilize a variety of carbon sources but are nitrogen limited; any attempt at in situ stimulation of the microbiota will require addition of a nitrogen source; and 3) strict anaerobic bacteria were not detected; addition of an electron donor in stoichiometric

excess of O_2 and NO_3 is unlikely to lead to rapid reduction of sulfate.

Future microbiological research should proceed along two avenues. The first should involve experiments to obtain a mechanistic understanding of the microbiological reduction of Fe(III) . Known Fe(III) -reducing bacteria and several Fe(II) reducers should be isolated from subsurface sediments and utilized in experiments with Fe(III) -bearing clays and minerals from the Ringold Formation and other sources. The second avenue of research should include the use of representative unconfined aquifer sediment samples to determine whether Fe(III) -reducing bacteria are present and whether the indigenous microbiota in these sediments can be stimulated to reduce O_2 , NO_3 , and Fe(III) .

FIGURE 4. Respiratory (O_2 consumption and CO_2 evolution) Response of Sediment Samples from 22.4 m Amended with Various Carbon Sources With and Without Nitrogen (CMC = carboxymethyl cellulose)

Experimental Design and Interpretation - Modelling and Visualization

Modelling analysis and visualization were undertaken to develop an understanding of the complex, often interrelated factors that affect the design of abiotic and biotic field redox manipulation experiments. Research was directed toward

- determination of necessary experimental site characteristics (e.g., geology and facies, nature and scales of heterogeneity, location of confining and injection layers, injection zone size, mean hydraulic conductivity, ambient hydraulic gradient)
- quantitation of the rate and direction of key processes that give rise to the change in redox (e.g., time required for the chemical reactions and/or microbiological processes that effect the change, stability of the changed system when subjected to ambient geochemical conditions during the different phases of the experiment)
- development of methodology required to interpret the results of the redox manipulation experiments (e.g., how the field measurements are interpreted to obtain model-equivalent parameters and/or observations, how models are calibrated and validated, how the various competing and interacting models are used to describe the important physical, chemical, and microbiological mechanisms)
- determination of the overall requirements and feasibility of the experiment (e.g., volume of reagent, volume of recovered waste fluids, number and kind of sampling wells and their construction).

FY 1991 modeling analysis and visualization activities advanced in two separate areas: 1) sensitivity studies with simple models to provide input to site selection and aid development of a better conceptual understanding (or model) of the experiment and 2) preliminary simulations with a high-resolution, three-dimensional flow and particle-tracking transport model and state-of-the-art visualization techniques using Stardent Computer Corporation's Application Visualization System (AVS) to examine the effects of various scales of heterogeneity on the experiment and thus its design.

Sensitivity Studies. A two-dimensional, homogeneous, hydrologic flow and transport model using the CFEST code (Gupta et al. 1987) was used to develop a better conceptual model of the experiment and to aid preliminary design efforts. Once a tentative site location was selected, a base case (i.e., nominal experiment) was defined based on 1) assumed nominal site characteristics (estimated from nearby wells); 2) preliminary reagent selection; 3) assumed reactivity parameters; and 4) other nominal design parameters based on costs of wells, reagent, and handling of withdrawn fluids. Modeling was used to examine the effects of a range in site characteristics, chemical reactivity, and experimental design parameters on a variety of system response functions, including predicted plume shape, volume of aquifer affected, mass of reagent required, volume of waste fluids recovered, and conservative tracer recovery.

The relationships between timescales and driving forces for the three phases of the push-pull experimental design (see Figure 1) are illustrated in Figure 5. Injection and withdrawal times for the simulated experiment are measured in hours (12) and days (7), respectively; residence times between injection and withdrawal are measured in tens of days (30). Injection ($22.5 \text{ gal min}^{-1}$) and withdrawal ($22.5 \text{ gal min}^{-1}$) forces induce radial groundwater velocities ranging from tens to hundreds of feet per day. Using parameters typical of the Ringold Formation at Hanford, natural head gradients of 0.002 ft ft^{-1} , mean hydraulic conductivity of 200 ft day^{-1} , and porosity of 0.3 result in lateral velocities toward the Columbia River of only a few feet per day (1.3) during the residence phase of the experiment. These differences in velocities between the three phases can pose difficulties in certain kinds of heterogeneous systems, as will be discussed below.

Figure 6 illustrates the shapes and scales of a conservative tracer plume at the end of the injection, at the end of the residence phase, and after 48 hours of withdrawal pumping for the nominal or base-case system and design calculated with the two-dimensional homogeneous model. The plume was compact, nearly circular, and centered on the injection/withdrawal well at the end of the injection phase (see Figure 6a). However, the plume was transformed into a more diffuse elliptical shape that nearly drifted past the injection/withdrawal

FIGURE 5. Timescale and Driving Force Relationships for the Three Phases of the Push-Pull Experiment

FIGURE 6. Plumes for a Conservative Tracer for the Nominal System and Experiment: (a) End of the Injection Phase, (b) End of the Residence (or drift) Phase, and (c) After 48 Hours of Withdrawal-Phase Pumping

well as a result of the 30 days of drift and dispersive forces (nominal values for the longitudinal and lateral dispersivity are 2.5 ft and 0.5 ft, respectively), as shown in Figure 6b. The radially convergent withdrawal forces transformed the receding tracer plume into a teardrop shape as the tracer was diluted with ambient groundwaters in the withdrawal well.

Figures 7 and 8 illustrate the results of an analysis undertaken to determine the sensitivity of the field experiment outcome to various experimental parameters. Figure 7 illustrates the effect on withdrawal-phase pumping duration and volume from halving the withdrawal pumping rate. Although more than double the pumping time was required to reach 90% or 95% recovery of the conservative tracer, there was only a 19% increase in the pumped volume. Figure 8 illustrates the calculated conservative tracer and reagent concentrations at the injection/withdrawal well as a function of time from the start of the experiment for the base case and two variations. Figures 8a, c, and d illustrate conservative tracer concentrations

for the base case, the half-injection-rate variation, and the half-pumping-rate variation, respectively. Figure 8b illustrates the nominal reagent concentration (15-day time constant for the first-order reaction rate) for the base case. Halving the injection rate had little effect, but halving the withdrawal rate resulted in less dilution and higher injection/withdrawal well concentrations during the withdrawal phase; these results may be important for those reagents and tracers that may be harder to detect.

Some aspects of the push-pull experiment important to reagent selection, final design, and interpretation of results elucidated by this sensitivity analysis and modeling are shown in Figure 9. As illustrated, the time required for reagent reaction (residence time), other design parameters, and site characteristics interact to determine three volumes of aquifer material exposure, including the 1) volume initially exposed to reagent and subject to re-equilibration forces before the withdrawal phase, 2) volume exposed continuously to reagent, and 3) volume exposed

Base Case

Injection:

Injection Rate = 22.5 gal min⁻¹
 Injection Duration = 12 h
 Volume Injected = 16,000 gal

Pumping:

Pumping Rate = 22.5 gal min⁻¹
 For 95% Recovery
 Pumping Duration = 9.1 d
 Volume Pumped = 293,900 gal
 For 90% Recovery
 Pumping Duration = 7.1 d
 Volume Pumped = 229,300 gal

Half Pumping Rate

Injection:

Injection Rate = 22.5 gal min⁻¹
 Injection Duration = 12 h
 Volume Injected = 16,000 gal

Pumping:

Pumping Rate = 11.25 gal min⁻¹
 For 95% Recovery
 Pumping Duration = 21.6 d
 Volume Pumped = 348,800 gal
 For 90% Recovery
 Pumping Duration = 16.5 d
 Volume Pumped = 266,500 gal

FIGURE 7. Pumping Duration (a) and Volume Pumped (b) as a Function of Percent of Conservative Tracer Removed During Withdrawal Phase for the Base Case and the Half-Pumping-Rate Variation

to reagent only during the residence phase as a result of plume drift. Sensitivity studies indicate, as expected, that the relationship between the reagent reaction times for the chemical reduction experiment (or the time required to stimulate microbiological activity and effect redox changes for the biotic experiment) significantly affects the volume of the aquifer continuously exposed to redox-altering conditions.

Improved conceptual understanding of the experiment resulted in changes in the initial proposal for the relative locations of the injection, monitoring, and coring wells (Figure 10). In this conceptual diagram of sampling well locations, the main line of wells is located along the expected direction of plume drift and longitudinal spreading. Some of the wells along the expected drift line establish the locations of the leading and trailing edges of the

FIGURE 8. Concentration Versus Time Since the Start of the Experiment for (a) a Conservative Tracer (base case) and (b) the Nominal Reagent (decay half-life of 15 days), and Conservative Tracer Concentration Versus Time for (c) the Half-Injection-Rate Variation and (d) the Half-Pumping-Rate Variation

plume and sample the re-equilibration and residence-phase zones; but a majority of the wells sample the continuously exposed zone. The wells located off the main line provide for the uncertainty in the actual direction of plume drift and/or heterogeneity that would cause deviations from the mean or expected behavior.

Early estimates of a 15-day time constant for reagent reactivity that resulted in the 30-day nominal residence phase now appear overly optimistic for both the abiotic and the biotic experiments. Sensitivity studies performed thus far indicate that residence phases beyond 30 days begin to significantly decrease the volume of the aquifer materials continuously exposed to reagent or to stimulated microbiological processes that can effect redox changes. As a result, alterations to the standard push-pull experimental design that will keep the same volume of aquifer material continuously exposed to redox-altering conditions must be examined. One alternative is the

emplacement of a series of gradient-controlling pumping and injection wells around the single push-pull injection/withdrawal well. A second alternative is a sequence of push-pull pulses through either one or several wells. These and other alternatives will need to be investigated through modeling analysis and sensitivity methods to determine how to attain the required longer residence phase that has an appropriate volume of aquifer material continuously exposed to redox-altering reagent or stimulated biological activity.

Heterogeneity and Visualization. In conjunction with evaluation and refinement of the conceptual experimental design, it is necessary to simulate the various scales of heterogeneities known to exist in the Ringold Formation and the vertical gradients that may be induced by the injection and withdrawal. Vertical gradients may result from a well that is not fully penetrating, from vertical stratification, or from heterogeneity in the medium. These effects are illustrated in Figure 11, which

FIGURE 9. Conceptual Diagram of the Push-Pull Experiment, Indicating the Different Categories of Reagent Interactions with the Subsurface

shows the basic conceptual differences between homogeneous and heterogeneous models for both a fully and a partially penetrating injection/withdrawal well.

To better define the effects of different scales of heterogeneity in a complex, three-dimensional, time-varying system, an advanced visualization system was used in conjunction with a high-resolution computer code capable of representing the various scales of heterogeneity. A three-dimensional push-pull experiment was simulated in FY 1991 by coupling the output of the three-dimensional, finite-difference, hydrologic flow code (MGRID3D), which uses the multigrid solution method (Cole and Foote 1989), to a PNL-modified

version of the AVS particle tracker to simulate transport. The coupling was accomplished using a PNL-developed AVS velocity-field calculation module that reads three-dimensional hydraulic conductivity, porosity, and potential scalar data sets and calculates the three-dimensional vector field of pore water velocities.

The synthetic, heterogeneous, hydraulic conductivity distribution used to simulate the three-dimensional push-pull experiment was generated using a simple convolution filtering technique. With this technique, a uniformly spaced three-dimensional grid of normally or lognormally distributed hydraulic conductivity values having the desired distribution mean, variance, and

FIGURE 10. Relationship Between Conceptual Understanding of the Phases of the Experiment and the Relative Locations of the Injection/Withdrawal, Monitoring, and Coring Wells

FIGURE 11. Conceptual Differences Between Fully and Partially Penetrating Injection/Withdrawal for Homogeneous and Heterogeneous Models of the Push-Pull Experiment

spatial correlation length can be generated. The steps in this convolution filtering process were as follows:

- A random number generator was used to develop a 33 by 33 by 33 grid of hydraulic conductivity values between 1 and 1000 with a uniform distribution.
- This grid of values was then filtered three times with a 3 by 3 by 3 box filter to create a normal (or Gaussian) distribution of hydraulic conductivity values with a spatial correlation scale of approximately 4 grid blocks.
- This 33 by 33 by 33 grid was then scaled to have a mean hydraulic conductivity of 100 ft day^{-1} and a standard deviation of 49 ft day^{-1} .

Results of this heterogeneous push-pull simulation during the residence (or drift) phase of the experiment are shown in Figure 12. The color-coded visualization shown in Figure 12 contains the following:

- an outline of the 33 by 33 by 33 cube of heterogeneous aquifer surrounding the injection/withdrawal well
- a color-coded plot of the hydraulic conductivity distribution for a 33 by 33 horizontal slice along the base of the system - The colors ranging from red (through yellow and green) to blue represent the hydraulic conductivity highs through hydraulic conductivity lows, respectively.
- rendered three-dimensional contour- or iso-surfaces (the white three-dimensional surfaces) that essentially display shells that surround the blue (i.e., low-hydraulic-conductivity) zones
- flow visualization lines in a horizontal slice near the top of the system - The flow visualization lines in this slice have a length proportional to the velocity magnitude and a direction oriented along the direction of flow.

- a number of rendered tracer particles that are color coded according to their velocity magnitude - Color coding for these particles ranges from red (through yellow and green) to blue as the velocity ranges from the highest through lowest values, respectively.

This visualization illustrates that the slow-moving particles are associated with the conductivity lows: the blue (or slower) particles are near the white shells of lower hydraulic conductivity. The flow visualization lines indicate that the main part of the flow moves, for the most part, around the low-conductivity zones. Although this figure is useful in illustrating many of the complexities of heterogeneous flow and transport, it illustrates only a small portion of the total power of the AVS.

When the transport simulation is executed, the temporal nature of the tracer movement can be visualized dynamically. One can observe the tracer particles move into and out of the system along radially divergent and convergent flow paths during the injection and withdrawal phases and the pathways that are used. The system can also be rotated and viewed from various angles. During any of the phases, the tracer particles can be color-coded according to various spatial or temporal properties. Typically, however, particles are color-coded according to their velocity magnitudes, as illustrated in Figure 12. From observations of the velocity of the color-coded tracer particles during the drift phase, the majority of the particles apparently move along the high-conductivity channels, while a smaller number move into the lower-conductivity zones. The numbers that move into a low-conductivity zone appear to be dependent on the shape and location of the lower-conductivity heterogeneity, the gradient, and the relative hydraulic conductivity contrast between the high- and low-conductivity zones.

These observations of simulated tracer behavior (even for this slightly heterogeneous simulation of the push-pull experiment) support the concerns and issues regarding this proposed manipulation experiment that were raised by participants in the

FIGURE 12. Computer Visualization of the Heterogeneous, Push-Pull Experiment During the Residence Phase (derived from three-dimensional finite-difference hydrologic flow code coupled to AVS particle tracker)

DOE Field Experimentation Workshop held in Richland, Washington, in July 1991. Concerns were that smaller-scale variations in hydraulic conductivity (which can span several orders of magnitude even in simple depositional systems) could give rise to preferential flow of injected conservative and reactive tracers in the highly conductive zones during the injection phase that would bypass the hydraulic conductivity lows. This expected effect would also be further exacerbated by the large differences in both magnitude

and direction between the driving forces during the injection/withdrawal phases and those during the residence phase, as illustrated in Figure 5. Additional concerns were related to the location of the reducible species (i.e., chemical heterogeneity) relative to the hydrologic heterogeneity.

Figure 13 is a conceptual diagram illustrating postulated interactions between heterogeneity and the characteristics of the different phases of the push-pull experiment that could give rise to the

FIGURE 13. Conceptual Illustration of the Relationships Between Heterogeneity and the Various Phases of the Push-Pull Experiment. Relationships were derived from three-dimensional transport modeling (Figure 12).

above issues and concerns. This diagram illustrates 1) a plan view of the experiment and setting, 2) an expanded-scale plan view of the aquifer condition near the end of the injection phase, 3) a detailed-scale plan view of a portion of the aquifer (from the expanded view shown for the injection phase) near the end of the residence phase, and 4) the same detailed-scale plan view but during the midpoint of the withdrawal phase of the experiment. The aquifer in this diagram is composed of interconnected zones of higher hydraulic conductivity (high-k zones) and lower hydraulic conductivity (low-k zones). The low-k zones (i.e., the outlined areas) are of various shapes, scales, hydraulic conductivity, and facies compositions.

The shaded areas represent areas of high and/or low k that have been invaded by the injected tracer.

As illustrated in the expanded-scale plan view (Figure 13), the high gradients and short duration of the injection period result principally in invasion of the connected high-k zones. The lowest-conductivity zones are bypassed (e.g., zones 4 through 8). The k of zones 1 through 3 is not as low as the k in zones 4 through 8. As a result, zones 1 through 3 are invaded to varying degrees during the injection phase, as illustrated by the shading. However, the differences in the degrees to which these zones are invaded are as much

dependent on their size, shape, and orientation (relative to the gradients) as to their differences in k . At the end of the injection period, estimated effective porosity for the system would be too low if determined only from the extent of invasion of the tracer. In addition, if the reducible species were located in either the larger low- k zones or the smaller low- k zones having the lowest k , the injected tracer apparently would not be in contact with the reagent for quite some time (if at all) during the entire duration of the experiment.

The detailed-scale plan view for the drift phase (Figure 13) shows that both the magnitude and the direction of the advective driving force (i.e., the drift velocity) change. Although the magnitude is decreased, it is applied for a much longer period (30 days or more). During the drift phase, invasion of the low- k zones continues by advective driving forces as before, but now diffusive forces also have time to act. Low- k zones 1 through 8 conceptually illustrate a sequence that progresses from essentially advection-dominated to diffusion-dominated invasion. The types (advection or diffusion dominated) and scales of the low- k zones are postulated to be very important in determining the fraction of the pore system that is reached by the reagent and tracer.

The withdrawal-phase detailed-scale plan view (Figure 13) illustrates the last concern and the issues that give rise to it. The common concern is that all of the tracer (and/or unreacted reagent) will not be recovered. The first postulated reason is related simply to the shorter timescale of the withdrawal phase. However, a second postulated reason is illustrated by low- k zone 3. The interactions between shape and orientation of the low- k zones relative to the injection, residence, and withdrawal gradient magnitudes and directions are postulated to result in a hysteresis effect. Because of these interactions, the withdrawal driving forces do not reverse the loading driving forces of the residence phase, as illustrated for low- k zone 3. A contaminant that was loaded by advection during injection and residence must take a different path (and, in this case, a new and much longer path in time) before again reaching the well-connected high- k zones.

These issues and concerns should be investigated through a combination of modeling analysis and field outcrop strata studies. Initial outcrop studies should identify typical scales of heterogeneity and associated contrast ratios. Initial modeling efforts will systematically evaluate various contrast ratios and scales of low- k heterogeneity to determine those giving rise to the phenomena described above for this experimental design.

Future Research

Recently, the scope of activities of the DOE Office of Environmental Restoration and Waste Management (EM) has expanded to include research on in situ manipulation of coupled chemical-microbial processes. This organization may be in a position to begin implementation of the effort in the near future and to build on the extensive scientific base that was developed through the Subsurface Science Program (SSP). For this reason, responsibility for implementing the manipulation project will be transferred to EM from the SSP as part of the Environmental Science Research Center outreach effort.

The results of the research in FY 1991 to develop and evaluate a conceptual experimental design and the Field Experimentation Workshop cited above will be encompassed in a final report for use by EM.

References

- Amonette, J. E., and A. D. Scott. 1991. "Determination of Ferrous Iron in Non-Refractory Silicate Minerals--1. An Improved Semi-Micro Oxidimetric Method." *Chemical Geology* 92(4):329.
- Barcelona, M. J., and T. R. Holm. 1991. "Oxidation-Reduction Capacities of Aquifer Solids." *Environmental Science and Technology* 25:1565-1572.
- Cole, C. R., and H. P. Foote. 1989. "Multigrid Methods for Solving Multiscale Transport Problems." In *Dynamics of Fluids in Hierarchical Porous Formations*, ed. J. H. Cushman. Academic Press, Inc., New York.

Gupta, S. K., C. R. Cole, C. T. Kincaid, and A. M. Monti. 1987. *Coupled Fluid, Energy, and Solute Transport (CFEST) Model: Formulation and User's Manual*. BMI/ONWI-660, Battelle Project Management Division, Office of Nuclear Waste Isolation, Columbus, Ohio.

Komadel, P., and J. W. Stucki. 1988. "The Quantitative Assay of Minerals for Fe^{2+} and Fe^{3+} Using 1,10-phenanthroline--III. A Rapid Photochemical Method." *Clays and Clay Minerals* 36:379-381.

Stucki, J. W., D. C. Golden, and C. B. Roth. 1984. "Preparation and Handling of Dithionite-Reduced Smectite Suspensions." *Clays and Clay Minerals* 32:191-197.

Modeling Radon Transport in Soils

D. J. Holford, P. C. Owczarski, G. W. Gee, and H. D. Freeman

Radon transport in soils is a complex phenomenon controlled by many competing factors that will enhance or decrease radon flux relative to the generation rate in the soil. Although large amounts of radon may be produced in the soil, soils with a low diffusivity or permeability will prevent the radon from migrating into buildings before it decays radioactively. A numerical model has been developed to simulate radon generation and transport in soils and radon fluxes into buildings. The computer code, called Rn3D, is currently being used to simulate methods of reducing radon fluxes into buildings, including sealing cracks in concrete basements and placing a gravel bed beneath a building's foundation to improve subslab ventilation. Because experimental facilities are expensive to construct and their results apply only to the particular type of soil on which they are constructed, numerical models such as Rn3D provide a cost-effective way to test new ideas for radon mitigation in a variety of soil types. This report details a study undertaken in FY 1991 to determine which soil and meteorological factors are dominant in controlling radon migration from soil into homes.

Statistical Uncertainty Analysis of Radon Transport in Nonisothermal, Unsaturated Soils

Transient radon flux from soil is affected by soil properties, as well as meteorological factors such as air pressure and temperature changes at the soil surface and the infiltration of rainwater. Natural variations in meteorological factors and soil properties contribute to uncertainty in subsurface model predictions of radon flux, which, when coupled with a building transport model, will also add uncertainty to predictions of radon concentrations in homes. A statistical uncertainty analysis using the Rn3D finite-element numerical model was conducted to assess the relative importance of these meteorological factors and the soil properties affecting radon transport.

The Rn3D model has been enhanced to simulate the nonisothermal transport of radon by diffusion and advection in both the liquid (water) and the gas (air) phase. This three-dimensional finite-element code was used to simulate the effect of air pressure, water pressure, and temperature gradients on radon concentration in partially saturated soil with parallel, partially penetrating cracks. For this uncertainty analysis, a two-dimensional steady-state scenario was assumed, as shown in Figure 1. A number of the model variables, including permeability, air-filled porosity, bulk diffusion coefficient, and radon emanation, are dependent on soil pore saturation with water.

The properties of water and air are treated as functions of temperature and pressure in Rn3D. The viscosity of water, viscosity of air, and density of water as functions of temperature were implemented tabular functions for temperatures between 0 and 100°C. The density of air as a function of temperature and pressure was calculated from the ideal gas law. The diffusion of radon in pure water was calculated as a function of temperature and pressure (Bird et al. 1960). The solubility of radon in water/air at atmospheric pressure was implemented as a tabular function of temperatures between 0 and 100°C.

If some input variables are very influential on Rn3D's prediction of radon flux to the atmosphere,

FIGURE 1. Schematic Diagram Showing Model and Boundary Conditions

those input variables should be measured with the highest degree of spatial and temporal accuracy in the field. An uncertainty analysis attempts to quantify the uncertainty of model output, giving an indication of the probable range of possible outcomes. A schematic diagram (Figure 2) shows the statistical method used to perform this uncertainty analysis. Each input variable was treated as a random variable, with a certain range and a uniform, loguniform, normal, or lognormal distribution (Table 1).

Latin Hypercube Sampling (Iman and Shorten-carier 1984) was used to select random combinations of the model input variables within the

ranges listed in Table 1. Each random combination of input variables was used for one run of Rn3D. A suite of such runs composes a Monte Carlo simulation. The advantage of Latin Hypercube Sampling is that, rather than running the model many times (as with the traditional Monte Carlo technique), the model must be run only two or three times the number of input variables.

Most of the input variables were given either uniform or loguniform distributions to evenly sample the entire ranges. The soil properties of permeability, porosity, and tortuosity were assumed to be less uncertain than the rest of the input variables and were given normal or lognormal distributions. In addition, the moisture-characteristic, relative-permeability, diffusion-versus-moisture, and emanation-versus-moisture curves were assumed to be known for three soil types. These four curves are shown in Figures 3, 4, 5, and 6, respectively, where moisture content is defined as the product of soil saturation and porosity. Monte Carlo simulations, each consisting of 35 runs of Rn3D, were conducted for three soils (sand, loam, and clay) to assess uncertainties for different soil types. The base-case soil properties for each of the three Monte Carlo simulations are listed in Table 2.

Figure 7 is a probability plot of the results of the three Monte Carlo simulations. The predicted radon flux varies over five orders of magnitude. The variability between soil types is much less than the total variability for each soil type.

Sensitivity Analysis

The results of the Monte Carlo simulations can be used to determine the sensitivity of the radon flux to each input variable, expressed as sensitivity coefficients. The sensitivity coefficient represents the percentage change in flux that results from a percentage change in an input variable. The sensitivity coefficients can be estimated using multiple linear regression by assuming a first-order model for the relationship between the radon flux and the input variables. The sensitivity coefficient can be standardized so that input variables with widely varying ranges can be compared. This standardized sensitivity coefficient is regarded to be significant if its absolute value is larger than two

FIGURE 2. Schematic Diagram Showing Latin Hypercube Sampling, Monte Carlo Simulation, and Sensitivity Analysis Using Multiple Linear Regression

TABLE 1. Input Variables and Their Ranges and Distributions

Variable	Range	Units	Distribution
atmospheric radon	0.1 to 100	Bq m ⁻³	loguniform
atmospheric pressure	8.5x10 ⁴ to 10 ⁵	Pa	uniform
capillary pressure	10 ³ to 5x10 ⁴	Pa	loguniform
gas pressure gradient	10 ⁻³ to 1	Pa m ⁻¹	loguniform
liquid pressure gradient	10 ⁻¹ to 10 ²	Pa m ⁻¹	loguniform
temperature gradient	-0.9 to 0.5	°C m ⁻¹	uniform
intrinsic permeability	±1 order mag.	m ²	lognormal
porosity	±5%	---	normal
tortuosity	±10%	---	normal
radium content	10 to 200	Bq kg ⁻¹	loguniform
crack width	10 ⁻⁴ to 10 ⁻²	m	loguniform
crack depth	0.3 to 6	m	loguniform
crack spacing	0.6 to 20	m	loguniform
water table depth	-30 to -10	m	uniform

FIGURE 3. Matric Suction Versus Moisture Content for Three Soil Types

FIGURE 5. Bulk Diffusion Coefficient Versus Moisture Content for Three Soil Types

FIGURE 4. Liquid Permeability Versus Moisture Content for Three Soil Types

FIGURE 6. Emanation Versus Moisture Content for Three Soil Types

(representing variability larger than two standard deviations of the sensitivity coefficient). A negative coefficient indicates that the radon flux increases as the input variable's value decreases; a positive coefficient indicates the converse.

The standardized sensitivity coefficients for the three Monte Carlo simulations are shown in Figure 8. Input variables that have standardized sensitivity coefficients larger than two are width of cracks (or other macropores), radium content, gas pressure gradient, and capillary pressure (soil saturation). Variables with sensitivity coefficients

TABLE 2. Base-Case Soil Properties for Three Monte Carlo Simulations

Property	Sand	Loam	Clay
permeability (m^2)	1×10^{-10}	1×10^{-13}	1×10^{-16}
porosity	0.2526	0.4491	0.5631
tortuosity	0.6	0.4	0.2
van Genuchten (Mualem)			
residual saturation	0.1229	0.2299	0.5409
n	4.886	2.502	1.8133
alpha (m^{-1})	2.37	1.66	0.83
emanation			
wet	0.3	0.3	0.3
dry	0.1	0.1	0.1
minimum saturation	0.3	0.4	0.6

FIGURE 7. Normal Probability Plot of Radon Fluxes Predicted by Monte Carlo Simulations

between one and two and that are therefore marginally significant are permeability, atmospheric pressure, depth to water table, and crack spacing.

The differences in sensitivity coefficients calculated for the different soil types are not great, although some trends are apparent. For instance, the sensitivity coefficient for crack width is larger for a clay than for a sand because of the larger permeability contrast between cracks in a low-permeability clay than in a high-permeability sand. For the same reason, the clay scenario is more sensitive to variations in the soil permeability than is the sand scenario. Because of higher gas velocities, the gas pressure gradient is a more significant factor in the higher-permeability sand simulations.

FIGURE 8. Standardized Sensitivity Coefficients for Monte Carlo Simulations

Conclusions

This analysis indicates several input variables to the Rn3D model that should be carefully measured to accurately predict radon fluxes from soils. Obviously, nondestructive field measurements of crack width, spacing, and depth are not practical. But the sensitivity of radon flux to the presence of cracks in the soil suggests that using the laboratory-measured properties of a small soil sample to predict radon fluxes into a house is an insufficient technique if cracks are indeed present. Field methods for measuring the bulk permeability and porosity of a large, in situ soil sample are necessary to accurately predict the radon gas transport properties of the soil.

Future Research

Future work will include sensitivity and uncertainty analyses of more realistic scenarios with time-varying atmospheric pressure, temperature, and rainfall. In these cases, neither the pressure and temperature gradients nor the soil saturation will be uniform in the soil. In summary, the Rn3D radon transport code has been developed to simulate the competing effects of the meteorological factors and soil properties in enhancing or decreasing radon flux from the soil into buildings. This computer code provides a cost-effective way to devise methods of reducing radon fluxes into buildings and is useful for making sense of the large amounts of data collected at research facilities.

References

- Bird, R. B., W. E. Stewart, and E. N. Lightfoot. 1960. *Transport Phenomena*. John Wiley & Sons, Inc., New York.
- Iman, R. L., and M. J. Shortencarier. 1984. *A FORTRAN 77 Program and User's Guide for the Generation of Latin Hypercube and Random Samples for Use with Computer Models*. NUREG/CR-3624, SAND-83-2365, Sandia National Laboratories, Albuquerque, New Mexico.

Subsurface Organic Fluid Flow Research

C. S. Simmons, R. J. Lenhard, J. W. Cary, and J. F. McBride

Dissolved solvents in groundwater beneath DOE sites stem from organic fluids that are mostly immiscible with water, are highly volatile, and move by multiphase flow processes when released into the subsurface environment. To model the movement of such immiscible fluids in the subsurface, an accurate formulation of the constitutive theory underlying model parameters is essential. This project has therefore emphasized developing a firm foundation for constitutive theory.

Large quantities of organic solvents are not accounted for on some DOE sites and may be residing undetected in the subsurface as pools of nonaqueous-phase liquids (NAPL), still dissolving continuously into the groundwater. The possibility that rapidly moving organic solvents may have mobilized radioactive contaminants is also a special concern for DOE. Accurate multiphase compositional flow and transport models based on a validated constitutive theory will be needed to help locate contaminants and to design effective cleanup strategies.

This research is directed toward hypothesized fluid-media scaling. Fluid-media scaling is the theoretical means for predicting the constitutive theory for NAPL, water, and air systems held in a porous medium. Fluid-media scaling is used to predict, starting from basic physical quantities (interfacial tension, wettability, and viscosity), the fluid-retention relations and conductivities that compose constitutive theory. A review of most of the physical concepts that this research is experimentally examining was provided by Simmons et al. (1991). Therefore, this report is limited to describing research progress, and a reader should refer to that previous report for additional technical explanations.

Hysteresis

The fact that fluid-retention relations (expressed in terms of functional relations between capillary pressures and saturations) are not single valued and depend on previous saturation path history is referred to as "hysteresis." A mathematical description for hysteretic multiphase flow behavior has been developed by Robert Lenhard. Unless hysteresis is included in multiphase flow modeling, the flow of organic liquid in water-saturated or unsaturated subsurface systems is not likely to be accurately predicted (Lenhard et al. 1991). These investigators showed that the water content at any depth above a water table that is changing in height (both up and down) could not be predicted accurately unless hysteresis and the associated air entrapment were accounted for. A gamma-ray attenuation scanning device used at Virginia Polytechnic Institute and State University to measure water content through time at each depth in an experimental column was indispensable for acquiring the appropriate data.

Also in FY 1991, a three-phase hysteretic retention model was validated based on fluid-media scaling. A previously developed special three-phase retention cell was used to make measurements for Soltrol in glass bead and sand porous media. These are the model organic liquid and porous media used in previous research to test constitutive theory. A research paper was submitted and accepted for publication.

Figure 1 illustrates results from the research on hysteresis. It shows the fit of the mathematical model to measurements of capillary pressure and total liquid saturation (water and Soltrol). Scaling is used in Figure 1 to put measurements for both two- and three-phase fluid systems on a single retention relation that exhibits dependence on previous saturation path history. The figure shows that the saturation cannot be predicted unless the appropriate curve branch is known. The model tracks which curve branch must be employed as liquid contents change.

Spreading Behavior and Unstable Channelling

Most organic liquids that have a positive spreading coefficient will spread spontaneously on a water-coated surface. But oils such as mineral oil, with a negative spreading coefficient, do not

FIGURE 1. Hysteretic Retention Relation for Scaled Capillary Pressure Head and Total Liquid Saturation for Soltrol and Water in Sand. Solid and open squares are measurements connected by dashed line, and solid-line curve is model fit to data. Main drainage and imbibition branches are shown with an internal scanning loop.

spread because they are essentially repelled by water. The presence of a contact angle reflects this reduced wettability of the water surface by an oil. A substantial contact angle is associated with reduced capillary force for holding an organic liquid in a porous medium. Figure 2 shows the equilibrium rise height scaled to water-equivalent values for mineral oil, Soltrol, and Soltrol plus a surfactant called Lubrizol. The liquid distributions were obtained by allowing the fluids to imbibe at the bottom of a column packed with glass beads. The scaling was done by using ratios of interfacial tension and density to convert to water-equivalent height. Essentially, the data in Figure 2 represent the imbibition branch of the retention relationship. Mineral oil displays a sharply defined front edge well below the other oils (see Figure 2), as a result of a nearly 70-degree wetting angle. The wetting angle and negative spreading coefficient of mineral oil are connected with its tendency to exhibit unstable downward infiltration behavior.

FIGURE 2. Capillary Rise Height of Oils and Water in a Column Packed with Glass Beads. Height is expressed in water-equivalent rise by scaling with interfacial tension and density ratios. The glass bead column contained initially 10% water saturation so that porous medium was water wet.

Because of the reduced capillary force for holding mineral oil in a moist porous medium against the downward force of gravity, this oil tends to channel through larger pores and exhibits macroscopic fingering by unstable channeling flow in an unsaturated porous medium. The consequence is that an oil like mineral oil infiltrates deeper and faster than expected from prevailing multiphase flow models. Past intermediate-scale experiments (Simmons et al. 1991) have shown this behavior in three dimensions in uniform porous media. We have become aware that this form of unstable channeling is analogous to that seen for water entering a dry or hydrophobic soil that does not wet uniformly. Future research will examine the possible connection between these phenomena. We believe this phenomenon for either water or oil is an important concern for DOE mixed wastes because the behavior may aggravate downward contaminant movement in the subsurface.

A paper on a simple method for using imbibition experiments to estimate the values of constitutive parameters under dynamic conditions was

completed and submitted for publication. The method and some results were discussed also by Simmons et al. (1991).

Electro-Optic Sensor

Progress with developing the electro-optic sensor for application continued in FY 1991, and a paper describing its use as a water-content sensing switch was accepted for publication. The sensor configuration (shown in Figure 3 and constructed by including a nylon filter paper in an optical switch) could be set to turn on at a specific soil-water pressure set by the pore size of the filter paper used. The concept provides a new type of sensor for potentially controlling irrigation water application. The same concept, using porous polyethylene, could be applied to detect oil instead of water.

The electro-optic sensor for oils has been patented and successfully transferred for use by private industry. A company that purchased a license on the patent has manufactured an array of sensors connected to a computer monitor system for detecting oil pipeline leaks. The sensor concept received the prestigious R&D 100 Award, presented by *R&D Magazine*, as one of the best inventions of 1991.

Also in FY 1991, an array of these sensors was connected to a standard field data logger and demonstrated how an organic liquid front could be tracked. This demonstration was recorded in a videotape about the sensor's use.

Thermal Effects Research

It is well known that thermal gradients can influence the distribution of water and volatile organic contaminants in the subsurface. Generally, the largest natural thermal gradients that might affect wastes at DOE sites occur near the surface in the unsaturated zone. However, the use of heating by certain remediation technologies (e.g., in situ vitrification, steam injection) can also introduce thermal gradients. Moreover, thermal energy may need to be applied to make biodegradation of dissolved organic contaminants more efficient. Therefore, thermal gradients may be quite important in cleaning up organic contaminants in the subsurface.

FIGURE 3. Diagram for Electro-Optic Sensor for Detecting Water in a Porous Medium

Under funding provided by the Environmental Science Research Center through the Northwest Colleges and Universities Association for Science (NORCUS), Dr. Lyle Prunty (at PNL while on a year's sabbatical from North Dakota State University) performed experiments showing the influence of a thermal gradient on simultaneous redistribution of a volatile organic liquid (octane) and water in an unsaturated porous medium (sandy loam). Figure 4 shows the combined final equilibrium distributions over 5 cm, between 7°C and 40°C applied at the two ends of the gradient. In contrast, Figure 5 shows the separate distributions. (Note the amounts present in Figures 4 and 5 were not the same.) Each experiment started with a completely uniform fluid distribution

before being compelled by the thermal gradient to accumulate near the coldest end. Dr. Prunty used the modern Fourier transform infrared spectrometer to quantify amounts of organic contaminants present in volume samples instead of using the simple field-applicable assay method previously devised by John Cary. The separate distributions in Figure 5 show a characteristic accumulation of liquids near the cold end, similar for both fluids. However, Figure 4 shows the octane reaching a maximum away from the cold end, probably because the build-up of water has expelled octane. This conclusion would be consistent with the greater capillary force holding water in smaller pores near the cold end. The distributions are a complex manifestation of the balance between

FIGURE 4. Simultaneous Equilibrium Distributions of Water and Octane in Sandy Loam Under a Steady Thermal Gradient Imposed by 7°C at the Cool End and 40°C at the Other End. Note that the octane amount near the cool end is reduced compared with that shown in Figure 5.

FIGURE 5. Separate Equilibrium Distributions of Water and Octane in Sandy Loam Under a Steady Thermal Gradient Imposed by 7°C at the Cool End and 40°C at the Other End. Note that the total quantity of fluids is different in Figures 4 and 5.

simultaneous liquid and vapor flow under nonisothermal conditions. The experiment demonstrates that thermal gradients are important and any adequate multiphase flow model should include the capability to examine the impact of nonisothermal conditions. This research on nonisothermal phenomena is planned to end this year because it is outside the present project's scope.

Progress and Future Research

A significant effort in FY 1991 was expended on preparing for a DOE Energy Research Peer Review administered by the Office of Program Assessment. This project involved two oral descriptions of project research, given by Steve Simmons and Robert Lenhard, and a written overview for examination by the Peer Review Panel and DOE. The project received a good rating and was recommended for continued priority support. John McBride and John Cary left the project in FY 1991. A new team will be formed with the help of Steve Simmons, Robert Lenhard, and Tim Ginn. Dr. Ginn, the newest team member, was a DOE Hollaender Fellow in FY 1991 with support from the Environmental Science Research Center. He is an expert in mathematical modeling theory and is attacking the problem of introducing a representation of heterogeneity and the influence of spatial scale into future multiphase flow models. He will also help examine the question of unstable channeling behavior and how to model it. This effort is consistent with the recommendation of the Peer Review Panel to proceed as rapidly as possible with study of the influence of subsurface heterogeneity on multiphase flow behavior and with the research plan to study organic liquid flow in heterogeneous intermediate-scale systems.

The departure of John McBride (to pursue a Ph.D.) and John Cary (to retire), however, did delay planned experiments on oil infiltration into heterogeneous layered porous media because results from earlier work were not yet fully interpreted and the in situ probe instrumentation needed in the more complex study was not yet fully tested. The experiments should proceed in FY 1992.

To improve collaboration within the Multiphase Flow Subprogram of the Subsurface Science Program, two new cooperative efforts will begin in FY 1992. Robert Lenhard is collaborating with Dr. John Wilson of the New Mexico Institute of Mining and Technology to investigate organic liquid retention and flow in etched glass plate micromodels of pore networks. This work will provide a more detailed examination of pore-scale processes influencing macroscopic behavior. Steve Simmons will collaborate with Dr. Avery Demond of the University of Michigan to develop

an improved theoretical capillary pore distribution model for fluid permeability, especially for the organic liquid phase. Plans include support for a graduate student to study with Dr. Demond. FY 1992 activities also will include a one-time experiment directed by Robert Lenhard to study the vapor flow behavior of a dense, volatile organic liquid representative of chlorohydrocarbon solvents found on DOE sites. The experiment should determine to what extent such vapors are driven by gas diffusion or convective gravity flow in the unsaturated subsurface.

References

Lenhard, R. J., J. C. Parker, and J. J. Kaluarachchi. 1991. "Comparing Simulated and Experimental Hysteretic Two-Phase Transient Fluid Flow Phenomena." *Water Resources Research* 27:2113-2124.

Simmons, C. S., J. W. Cary, R. J. Lenhard, and J. F. McBride. 1991. "Subsurface Organic Fluid Flow Research." In *Pacific Northwest Laboratory Annual Report for 1990 to the DOE Office of Energy Research, Part 2: Environmental Sciences*, pp. 37-50. PNL-7600 Pt. 2, Pacific Northwest Laboratory, Richland, Washington.

**Terrestrial
Science**

Terrestrial Science

Changes in arid and semiarid landscapes in response to stress are of major concern for DOE lands, as well as for the nation. It will be necessary to predict the response of natural systems to a variety of factors, including global climate change, contamination, and restoration activities, on local to regional scales.

PNL is performing basic scientific studies of the fundamental mechanisms that control ecosystem functioning. The dynamics of soil nutrients, water, gas flux across interfaces, and energy are being examined to understand how stress influences the efficiency with which an ecosystem processes its essential resources. Quantitative remote-sensing techniques are being developed to provide estimates of fundamental ecological properties for landscape-sized areas. Expert systems are being developed to provide new perspectives and methods for resolving environmental problems. Research on sampling and scaling methodology is being conducted to ensure an appropriate theoretical basis for these new research areas.

Nitrogen Dynamics of Arid Ecosystems

H. Bolton, Jr., and S. O. Link

Contributors

J. J. Halvorson (NORCIS), J. L. Smith (USDA Agricultural Research Service), and D. L. Mummey (NORCIS)

Ecosystems have dynamic efficiencies for processing and/or utilizing limiting essential resources. When a resource is no longer limiting or when stress is applied, the efficiency with which an ecosystem processes and utilizes that resource may change. Efficient utilization of resources has obvious implications to an ecosystem's productivity, ability to sustain impacts, and ability to act as a source/sink for contaminants. We are initially studying the N cycle because N is the nutrient most limiting to plant growth and microbial activity. Also, the N cycle involves a consortium of microorganisms, plants, and chemical and physical transformations with processes and pools in the soil, plant, and atmosphere that are integral to the functioning of the ecosystem. The main objectives of our work are to measure, understand, and predict biogeochemical cycles of arid ecosystems and determine how alterations of the environment such as energy development, DOE-site activities, or global climate change will influence these cycles. Our current objectives include determining the spatial distribution of N pools and microbial processes underneath *Artemisia tridentata* (sagebrush), the dominant shrub in the perennial shrub-steppe, and determining the parameters

controlling the loss of gaseous N as nitrous oxide from *Bromus tectorum*-dominated old fields.

Measurement of Resource Islands Underneath *Artemisia tridentata*: A Geostatistical Approach

The soil near plants typically contains greater concentrations of limiting resources such as N and exhibits higher rates of soil microbial activity than soil outside the influence of plants. These small-scale, enriched zones have been described as "isles of fertility" (Whitford 1986), "resource islands" (Reynolds et al. 1990), or "ecotessara" (Jenny 1980). Knowledge of the size and internal dynamics of resource islands is important for understanding local energy and mass transport and processes like N cycling. Individual resource islands may also connote a tier in a progressive, hierarchical mosaic of plant and animal habitats, resource distributions, and biogeochemical processes. Knowledge of the distribution and numbers of resource islands in the landscape may aid in understanding population-level processes and can be used to refine regional estimates of energy and mass transfer such as nutrient budgets. Further, the emergent properties resulting from the interrelationships of large numbers of individual resource islands may influence ecosystem-scale degradation like desertification (Schlesinger et al. 1990) or development (Halvorson et al. 1991). However, despite being conceptually simple, the shape, size, and orientation of resource islands have not been studied in detail. Previous work has relied either on a binary

sampling scheme (i.e., samples collected from beneath the plant compared to samples collected "away" from the plant) or on samples collected along a transect passing from plant to bare soil. Unfortunately, neither approach allows for a detailed mapping of resource islands and, for comparative purposes, both are constrained by the assumption that samples are independent and identically distributed.

At the Hanford Arid Lands Ecology (ALE) Reserve in Washington State, Bolton et al. (1990) measured significantly greater N and higher rates of N mineralization in soil beneath *Artemisia tridentata*, a dominant shrub of cool desert environments such as those found at ALE, than in soil away from sagebrush. However, their sampling regime precluded detailed mapping of these resources and processes. The objective of our current work is to delineate the spatial patterns of soil resources under individual sagebrush plants. We hypothesized that sagebrush would influence the distribution of soil properties such as inorganic N and microbial biomass resulting in clearly delineated resource islands.

Our approach was to sample the surface soil (0 to 5 cm) at specific locations within 2-m by 2-m plots centered on five individual sagebrush. We collected 41 soil samples from each of the five plots in early spring (March 12, 1991) when soil microbial activity would be optimal for measurement. Each soil sample (205 total) was analyzed for as many as 14 attributes, including inorganic forms of N (i.e., nitrate, ammonium), soil microbial biomass-C, and potential C and N mineralization rates. Data were analyzed with both univariate and spatial statistics (geostatistics).

Univariate statistics were used to evaluate the relationship between average values of soil properties and radial distance from sagebrush. For properties like soil inorganic N and soil microbial biomass-C, a systematic pattern was revealed, with the highest values appearing about 25 cm away from the plant axis and significantly lower values at distances beyond 60 cm (Figure 1). Note that mean values of samples collected from directly beneath the sagebrush plants appear lower than average values at 25 cm away. We interpret this unexpected finding to be either an anomaly resulting from the small number of

FIGURE 1. Mean Soil Inorganic N and Soil Microbial Biomass-C as a Function of Distance Away from Sagebrush

data points used to compute the mean directly beneath the sagebrush ($n=5$) or an indication of a "hole" in the center of resource islands deserving further investigation. These simple univariate statistical analyses limit our model of a resource island to an identically sized, directionally symmetrical concentration of soil resources under each sagebrush.

Geostatistics were also used to detect, model, and estimate spatial patterns of soil properties under sagebrush. Geostatistical methods are especially appropriate for determining the spatial correlation among ecological data and for estimating values at unsampled locations (such as used in recent work by R. E. Rossi and coworkers at Stanford University). Unlike univariate methods, geostatistics do not assume that individual samples are independent and identically distributed. The soil nitrate data from a single plot (Figure 2) show that soil properties, like nitrate, are not independent and that samples taken close to each other are more similar than samples lying farther apart. For each soil attribute, we calculated the average "similarity" for samples separated by different distances, or "lags," using techniques classified as diagnostic variography. Then we used these relationships to estimate values at unsampled locations using a process known as kriging to produce detailed maps of biological, chemical, and physical

FIGURE 2. Soil Nitrate-N Levels at 41 Sampling Points in a 2-m by 2-m Grid Surrounding Sagebrush. The sagebrush was located in the center of the grid.

properties in the soil lying directly under and near sagebrush. Our work differed from some geostatistical approaches in that we used relatively small data sets, filtered out the confounding effects of changes in local mean and variance by calculating nonergodic covariance and correlograms (Isaaks and Srivastava 1989), and considered the differences in spatial continuity as a function of direction.

Geostatistical analysis uncovered significant spatial relationships for soil properties like total inorganic N, soil microbial biomass-C, and soil C mineralization potential, particularly when changes in local mean and variance were accounted for (i.e., through the use of an autocorrelogram) (Figure 3). Our autocorrelograms show the degree of the similarity between samples on the y-axis (depicted as 1 minus a correlation coefficient) as a function of the average distance or lag between sampling points on the x-axis. Samples separated by a distance of more than 70 cm were statistically uncorrelated, resulting in a value of about 1. With decreasing separation distance, samples were more alike and increasingly correlated with each other. At small lags, autocorrelogram values declined to an estimated 0.2, meaning that two samples adjacent to each other would be, on average, about 80% correlated with each other. Additional analysis revealed greater spatial continuity (correlation over a longer distance) in

FIGURE 3. Autocorrelograms for Inorganic Soil N, Soil Microbial Biomass-C, and C Mineralization Rate. The lag is the distance between samples. The dotted line represents no spatial correlation.

directions corresponding to peak wind directions. This finding suggests soil resource distributions are not symmetrical around sagebrush and illustrates how environmental factors might influence the size or shape of resource islands. We hypothesize that this asymmetry is related to the direction of peak wind speed through the pattern of litter deposition, which would influence both soil N pools and soil microbial biomass.

The spatial relationships revealed in the autocorrelograms were modeled and used to produce estimates for locations that had not been sampled. The resulting maps (see Figure 4 for soil microbial biomass-C) clearly show the resource island effect under sagebrush. These maps reveal sharp transition boundaries in some instances, but suggest that asymmetrical distribution of soil resources around individual plants may sometimes be encountered. The maps also indicate that resource islands do not always have a discernible sagebrush at the center and that annual and perennial grasses or dead plant material may also be associated with high concentrations of soil N and microbial biomass-C.

Our results show how geostatistics can be successfully used to define the boundaries of the

FIGURE 4. Kriged Map of Estimated Soil Microbial Biomass-C ($\mu\text{g biomass-C g}^{-1}$ dry soil) in Association with Sagebrush Showing the Resource Island Effect. North is at the top of the plot.

"zone of influence" surrounding an individual plant. Our maps of resource islands associated with sagebrush are among the most detailed in existence and will be used to further our understanding of the ecology of sagebrush, to refine N budgets for shrub-steppe ecosystems, to guide sampling designs of soil process studies like denitrification and wintertime decomposition, and to plan future experiments using stable isotopes. Besides two-dimensional space, this approach can be expanded to consider soil depth (i.e., a third dimension) or time (via repeated measurements). Future research efforts will probe for the existence of nested structures by sampling soil at larger as well as smaller scales. This approach may reveal the existence of resource- and process-dependent patterns and help provide a rationale for the creation of monitoring and remediation units based on natural boundaries.

Nitrous Oxide Emission from Intact Soil-Core Microcosms Sampled from *Bromus tectorum*-Dominated Old Fields

Very little is known on the gaseous loss of N from native grasslands or semiarid soils; the resultant lack of data precludes development of source-sink

relationships for gaseous N species. Volatile N species have received considerable attention in agroecosystems because the N that is lost is no longer available for plant growth. One dominant gaseous form of N is nitrous oxide (N_2O), which is evolved from soil through the microbiological processes of denitrification and nitrification. Nitrous oxide is a biogenic trace gas that has an atmospheric residence time of approximately 120 years and is increasing in atmospheric concentration at a rate of about 0.2 to 0.4% annually (Yoshinari 1990). There is an interest in determining N_2O emissions from various ecosystems to the atmosphere because of the loss of N for soil N cycling processes. Also, N_2O is a natural source of nitric oxide (NO) in the atmosphere, which is involved in the catalytic destruction of ozone. Destruction of the ozone layer results in an increased health hazard caused by the increased penetration of more intense ultraviolet radiation (Cicerone 1987). Nitrous oxide is also a greenhouse gas, which is 180 times as effective as CO_2 at absorbing infrared radiation and contributes to an increase in the average surface temperature of the earth.

The objectives of our current studies were to investigate how moisture, N, and soluble C additions affect N_2O evolution from a semiarid annual grassland ecosystem. A gas chromatographic procedure was used to measure N_2O flux from intact soil cores (15 cm long by 7.1 cm in diameter), which were covered with a static chamber. The intact soil cores were collected on July 29, 1991, from a *Bromus tectorum*-dominated old field on the ALE Reserve at the Hanford Site. Soil cores were incubated at seven gravimetric water contents ranging from 4% (native soil moisture at sampling) to 66% (oversaturated, with water ponding on the soil surface). Saturated cores (53% water content) were also incubated with five nitrate levels ranging from no addition (native soil nitrate levels at sampling) to an addition of $0.2 \mu\text{g NO}_3\text{-N g}^{-1}$ soil added as KNO_3 . Saturated cores (53% water content) were also incubated with a glucose addition ($2 \text{ mg glucose g}^{-1}$ soil) to cores containing native soil N levels to determine whether soluble C was limiting N_2O production. All incubations were conducted with diurnal temperature fluctuations of 25°C during the day and 15°C at night with no plant growth. There were four replicates for each treatment.

Intact soil cores had relatively low gravimetric water contents (4%) and a low N_2O flux on analysis (Figure 5). Most soil cores that had an addition of water exhibited a sharp and rapid increase in N_2O flux on wetting, reaching maximum values at around 6 hours after wetting and gradually declining thereafter (see Figure 5). The soil core with 66% water content took 24 hours to reach maximum N_2O production and declined thereafter. The rapid flux of N_2O from these arid soils on wetting demonstrates that these soils respond very rapidly to water addition. Nitrous oxide is a loss of N from this ecosystem, and the rapid loss of N_2O on wetting implies rapid loss of N may occur in the field when water additions such as intermittent rain occur. The addition of $\text{NO}_3\text{-N}$ resulted in enhanced N_2O flux from the soil cores (Figure 6). The addition of $0.2 \mu\text{g NO}_3\text{-N g}^{-1}$ soil in the saturated soil cores (53% water content) increased N_2O flux to about 2.8 times that of saturated cores without N addition for a 6-hour incubation time. The increased flux of N_2O was transient and, within 24 hours, N_2O flux for the N treatments dropped to the treatment receiving only water (see Figure 6). The addition of glucose to the plus water (53% water content) and native soil N treatment significantly increased N_2O flux when compared to the water addition for more than 24 hours (see Figure 6). This demonstrated that soluble C may also be a factor limiting N_2O flux from these arid ecosystems. We are unsure of the cause of this increase with soluble C, but the time frame of the experiment (120 hours) and the rapid increase in N_2O suggest that an increase in microbial activity, and perhaps a rapid decrease in dissolved oxygen, may have played a role. These results indicate that the input of soluble C into the surface soil via decomposition or rhizosphere exudation may be a major factor influencing N_2O flux from this ecosystem.

Spatial variability in N_2O production was found in this annual grassland ecosystem as demonstrated by variability among soil cores in each treatment. The greater flux of N_2O from the 35% water treatment, as compared to the saturating water contents (53% and 66% water contents) (see Figure 5), was caused by the high rate from a single core. This high variability may be related to the abundance of wildlife found in this ecosystem and the possible addition of N as feces or urine in

FIGURE 5. Nitrous Oxide Flux from Intact Soil Cores from a *Bromus tectorum*-Dominated Old Field Incubated at Various Soil Moisture Contents

FIGURE 6. Nitrous Oxide Flux from Intact Soil Cores from a *Bromus tectorum*-Dominated Old Field Saturated with Water (53% water content) and Incubated with Various Nitrate-N Additions and with an Addition of Glucose-C at 2 mg Glucose g^{-1} Soil Added to the Native Soil N Treatment

some of the cores. Previous research conducted at this same site suggests that feces deposition can significantly influence the flux of N_2O in this ecosystem (Schwarz et al. 1991).

The ultimate goal of this present research is to produce a reliable model for estimates of N_2O flux and total N losses through denitrification and nitrification processes in the shrub-steppe ecosystem at the landscape level. This study demonstrates that the mechanisms responsible for N_2O evolution are a complex combination of environmental and substrate conditions, all of which must be addressed if a satisfactory model that accounts for spatial variability is to be produced. Future research will address the relationship between denitrification processes and variables such as temperature fluctuations, N mineralization rates and C availability associated with the prominent vegetation types found in this ecosystem, precipitation, and landscape variables.

References

- Bolton, H., Jr., J. L. Smith, and R. E. Wildung. 1990. "Nitrogen Mineralization Potentials of Shrub-Steppe Soils with Different Disturbance Histories." *Soil Science Society of America Journal* 54:887-891.
- Cicerone, R. J. 1987. "Changes in Stratospheric Ozone." *Science* 237:35-42.
- Halvorson, J. J., J. L. Smith, and E. H. Franz. 1991. "Lupine Influence on Soil Carbon, Nitrogen and Microbial Activity in Developing Ecosystems at Mount St. Helens." *Oecologia* 87:162-170.
- Isaaks, W. H., and R. Mohan Srivastava. 1989. *An Introduction to Applied Geostatistics*. Oxford University Press, Inc., New York.
- Jenny, H. 1980. *The Soil Resource, Origin and Behavior*. Springer-Verlag, Berlin.
- Reynolds, J. F., R. A. Virginia, and J. M. Cornelius. 1990. "Resource Island Formation Associated with the Desert Shrubs, Creosote Bush (*Larrea tridentata*) and Mesquite (*Prosopis glandulosa*) and its Role in the Stability of Desert Ecosystems: A Simulation Analysis." *Bulletin of the Ecological Society of America* 70:299-300.
- Schlesinger, W. H., J. F. Reynolds, G. L. Cunningham, L. F. Huenneke, W. M. Jarrell, R. A. Virginia, and W. G. Whitford. 1990. "Biological Feedbacks in Global Desertification." *Science* 247:1043-1048.
- Schwarz, L., S. O. Link, J. M. Klopatek, H. Bolton, Jr., B. D. McVeety, and L. E. Rogers. 1991. "The Effect of Fire on Nitrous Oxide Flux from *Bromus tectorum* Dominated Old-Fields." In *Pacific Northwest Laboratory Annual Report for 1990 to the DOE Office of Energy Research, Part 2: Environmental Sciences*, pp. 77-78. PNL-7600 Pt. 2, Pacific Northwest Laboratory, Richland, Washington.
- Whitford, W. G. 1986. "Decomposition and Nutrient Cycling in Deserts." In *Patterns and Processes in Desert Ecosystems*, ed. W. G. Whitford, pp. 93-117. University of New Mexico Press, Albuquerque, New Mexico.
- Yoshinari, T. 1990. "Emissions of N_2O from Various Environments - The Use of Stable Isotope Composition of N_2O as Tracer for the Studies of N_2O Biogeochemical Cycling." In *Denitrification in Soil and Sediment*, eds. N. P. Revsbech and J. Sorensen, pp. 129-150. Plenum Publishing Corporation, New York.

The Effects of Nitrogen and Water on *Bromus tectorum* Biomass in the Field

S. O. Link, J. L. Downs, M. E. Thiede, and H. Bolton, Jr.

The availability of limited resources such as nitrogen and water in arid ecosystems strongly influences ecosystem and plant productivity. Consequently, ecosystem biogeochemical cycling processes and water and nitrogen use efficiencies are also strongly influenced by the availability for these limited resources. Resource availability can be affected by human-induced perturbation such as global warming and air pollution and by physical disturbance. To better understand how arid ecosystems process water, carbon, and nitrogen, we have conducted experiments in the field to determine how such ecosystems respond to additional water and nitrogen. The models developed from the field experiments allowed us to hypothesize how the ecosystem responds to global climate change scenarios.

Water and nitrogen are limiting to plant growth in arid ecosystems (West and Skujins 1978). Most arid land plants respond to increased water by using more water (Campbell and Harris 1977) and increasing biomass (Lauenroth et al. 1978).

Nitrogen amendment studies have given mixed results with respect to increased growth of arid land plants. Variable results with additional nitrogen have been attributed to the availability of water. Many researchers have observed that additional nitrogen has no effect on productivity when water is limited (Romney et al. 1978).

Bromus tectorum, an introduced winter annual grass, has successfully invaded many areas of the arid Great Basin and Columbia Plateau of North America, radically changing plant community structure. Cline and Rickard (1973) found that nitrogen was a strong predictor and water was a weak predictor of *B. tectorum* shoot biomass production. Uresk et al. (1979) in further studies at Lower Snively Field found soil temperature and nitrogen to be the stronger predictors of *B. tectorum* shoot biomass production, while soil water was a weak predictor. Rickard (1985) also reports that soil water was a weak predictor of *B. tectorum* shoot biomass production. In our past research on the effects of water and nitrogen on *B. tectorum* shoot biomass production, we found conflicting results. In the field, we found a significant increase with added water and no effect of added nitrogen on shoot biomass relative to controls, which differs with the suggestion that nitrogen is the stronger predictor of biomass production compared with water. Because the previous studies were simple analysis-of-variance designs, we felt that a complete investigation of the effects of nitrogen and water on *B. tectorum* shoot biomass production would more clearly define how production depends on nitrogen and water.

The experimental site is located at Lower Snively Field on the Arid Lands Ecology Reserve. The experimental design consisted of six levels of water, six levels of nitrogen, and five replicate plots for a total of 180 experimental units. Each experimental plot was approximately 1 m in diameter. The plots were aligned along six drip irrigation lines that were randomly placed in the field, and each line represents a water treatment level. The nitrogen treatment levels were randomly chosen in each irrigation line for a total of 30 plots. The natural precipitation (control water treatment level) was 13.23 cm from October 1, 1990, until

May 30, 1991. Added irrigation water was 7.93, 13.75, 17.54, 22.63, and 29.85 cm, respectively, for the other five water treatment levels. Nitrogen, as NH_4NO_3 , was added in a 1-L solution of water to the additional N treatment levels. An additional liter of water was applied to the control N plots to maintain comparability among all experimental units. The control level of N in the top 15 cm of soil was 0.937 g m^{-2} (Bolton et al. 1990). Additional N, in the form of NH_4NO_3 , yielded levels of 3.3, 6.6, 10, 20, and 30 g m^{-2} for the other five N treatment levels. The water treatments were applied on March 6-8 and March 18-20, 1991. The N treatments were applied in the last week of February 1991. Plants were harvested over a 2-week period in May 1991 when the plants were senescent. The senescence occurred earlier for the low-water treatments and later for the higher-water treatments. The staggered harvesting was done so that the plants would be at their maximum biomass development for all treatments. The harvested area was 0.1 m^2 . Plants were placed in plastic bags and taken to the laboratory for processing. From each bag, 10 shoots were randomly chosen for allocation analysis. These shoots were analyzed for single-sided leaf area on a LiCor 3100 leaf area meter. The shoots were then separated into leaves, stems, and reproductive components. The allocation and bulk samples were then oven dried at 55°C for 48 hours and weighed.

The model used to describe the relation between biomass and water and nitrogen was based on modified Michaelis-Menton (rectangular hyperbola) equations as described by Thornley and Johnson (1990). The relationship between water and biomass is as follows:

$$Y = \frac{Y_{\max} \times W}{(h + W)} \quad (1)$$

where Y is the oven-dried green shoot biomass, $Y_{\max}$ is the estimated maximum biomass, W is the water level, and h is a parameter describing the water level that yields a half-maximum biomass. The relationship between nitrogen and biomass is as follows:

$$Y = \frac{(Y_{\max} \times N)}{(b + N)} \times \frac{(a - N)}{a} \quad (2)$$

where N is the nitrogen level and a and b are empirical parameters. The term $(a - N)/a$ of this equation allows for a description of the reduction in biomass at high N levels. The prediction of biomass as a function of water and N was obtained by multiplying Equations (1) and (2) and is given as follows:

$$Y = \frac{Y_{\max} \times W \times N \times (a - N)}{(h + W) \times (b + N) \times a} \quad (3)$$

where $Y_{\max}$ is estimated maximum biomass for the response surface. The parameters were obtained using nonlinear regression.

Bromus tectorum biomass is dependent on the level of water and nitrogen. The estimated maximum biomass using Equation (3) for all treatment conditions was 857 g m^{-2} . The level of N yielding maximum biomass was 10.937 g m^{-2} (Figure 1), and the level of water yielding maximum biomass was 43.08 cm (Figure 2). The optimum level of water for biomass production was not applied in this experiment. We hypothesize that the optimum level of water is greater than 43.08 cm because the predicted lines for biomass were still increasing for all but the lowest level of N (see Figure 2).

The relationship between biomass and water at the N level of 20.937 g m^{-2} is presented in Figure 3. The predicted curve was determined using Equation (1). The typical variations in the observed biomass can be seen in these data. The predicted curves for the six N levels are presented in Figure 2, with parameter and R^2 values for each N level given in Table 1. The most striking similarity is the apparent lack of a relationship ($R^2 = 0.00$) between water and biomass at the control or natural level of N in the soil ($N = 0.937 \text{ g m}^{-2}$). When N was added to this ecosystem, increasing biomass with increasing water was observed.

FIGURE 1. The Relationship Between *Bromus tectorum* Predicted Biomass and Nitrogen at Six Water Levels. The predicted values were generated from Equation (2) using parameters given in Table 2.

FIGURE 2. The Relationship Between *Bromus tectorum* Predicted Biomass and Water at Six Nitrogen Levels. The predicted values were generated from Equation (1) using parameters given in Table 1.

FIGURE 3. The Relationship Between *Bromus tectorum* Biomass and Water at Optimal Nitrogen Levels ($20.937 \text{ g N m}^{-2}$). The predicted values were generated from Equation (1) ($R^2 = 0.84$).

TABLE 1. Parameter Estimates and Regression Statistics Using Equation (1) to Describe the Relationship Between *Bromus tectorum* Biomass and Water at Six Levels of Nitrogen

Nitrogen Level (g m^{-2})	$Y_{\max}$ (g m^{-2})	h (cm)	R^2
0.937	212	0	0.00
4.237	589	19	0.45
7.537	605	16	0.50
10.937	807	29	0.72
20.937	952	40	0.84
30.937	643	24	0.59

The relationship between biomass and nitrogen at the water level of 26.98 cm is presented in Figure 4. The predicted curve was determined using Equation (2). The predicted curves for the six water levels are presented in Figure 1, with parameter and R^2 values for each water level given in Table 2. Again, there is an apparent lack of a relationship ($R^2 = 0.01$) between N and biomass at the control or natural level of water ($W = 13.23 \text{ cm}$). When water was added to this ecosystem, there was increased biomass with increased N. Unlike the water curves (see Figure 2), biomass was maximum at $10.937 \text{ g N m}^{-2}$, and biomass decreased at higher N levels in all water treatments.

FIGURE 4. The Relationship Between *Bromus tectorum* Predicted Biomass and Nitrogen at the 26.98-cm Water Level. The predicted values were generated from Equation (2) ($R^2 = 0.84$).

TABLE 2. Parameter Estimates and Regression Statistics Using Equation (2) to Describe the Relationship Between *Bromus tectorum* Biomass and Nitrogen at Six Levels of Water

Water Level (cm)	$Y_{\max}$ (g m^{-2})	a	b	R^2
13.23	242	799	0.065	0.01
21.16	472	98	1.584	0.68
26.98	602	65	2.415	0.80
30.77	473	213	1.023	0.73
35.86	565	107	1.663	0.70
43.08	587	156	1.792	0.72

The results of this experiment indicate that N and water at natural levels are both severely limiting to *B. tectorum* shoot biomass production. Therefore, the addition of water and N is required to yield increased shoot production. This result conforms to Liebig's (1840) law of the minimum, where processes are controlled by a single dominant controlling factor, as discussed by Odum (1971) and Woodmansee (1978). The purpose of this research was to determine which factor, water or N, was the stronger predictor of shoot biomass, considering the conflicting results of past research (Cline and Rickard 1973; Uresk et al. 1979). On the basis of this experiment, we concluded that both water and N are significant predictors of

shoot biomass production. The basis of some of the differences observed in past experiments may be the result of the timing of the addition of water and N. In the current experiment, water and N were added in March. If water and N had been added in early November when *B. tectorum* germinates, perhaps the effects would have been different. We hypothesize that if additional water were added at the beginning of the growing season, we would observe increased biomass without additional N. This could result if root growth were accelerated through the winter in a soil with deeper water, which could perhaps allow the uptake of more N from the soil. In our experiment, if the soils were wet only to a shallow depth, then additional water added late in the growing season may not yield a comparable increase in rooting depth and subsequent N uptake.

The estimated maximum biomass using Equation (3) compares well with the highest observed biomass. The estimated maximum biomass using Equation (3) was 857 g m^{-2} , which is slightly greater than the highest observed ($\sim 800 \text{ g m}^{-2}$) by Rickard and Vaughan (1988), and a little less than four times greater than the average production of 225 g m^{-2} . A value of this experimental design is that equations can be written to describe the effects of water and N on shoot biomass production for incorporation into ecosystem models for the Arid Lands Ecology Reserve. Future research on *B. tectorum* shoot biomass production should address the effect of the timing of additions of water and N. Also, that research should include an investigation of the effect of N tied up in litter on current year's growth. This last idea may help explain why there is year-to-year variation in *B. tectorum* shoot biomass production that is not correlated with precipitation levels, as discussed in Rickard and Vaughan (1988). We are in the process of analyzing data collected to determine the influence of water and N on carbon allocation and N and water use efficiencies for *B. tectorum*.

Future research efforts will be to understand elemental processes in the more complex sagebrush-bunchgrass ecosystems common on the Arid Lands Ecology Reserve. We will continue to develop gas-exchange models linking them to growth and carbon-allocation models to quantify

the fate of carbon in this ecosystem. The value in model development other than prediction is that it allows us to formulate and test (in terms of the model) hypotheses that are difficult to test experimentally, such as global climate change effects on ecosystems. Additionally, we plan to develop linkages between the ecosystem models and our remote-sensing capabilities that will allow us to predict elemental dynamics at the landscape scale.

References

- Bolton, H., Jr., J. L. Smith, and R. E. Wildung. 1990. "Nitrogen Mineralization Potentials of Shrub-Steppe Soils with Different Disturbance Histories." *Soil Science Society of America Journal* 54:887-891.
- Campbell, G. S., and G. A. Harris. 1977. "Water Relations and Water Use Patterns for *Artemisia tridentata* in Wet and Dry Years." *Ecology* 58:652-660.
- Cline, J. F., and W. H. Rickard. 1973. "Herbage Yields in Relation to Soil Water and Assimilated Nitrogen." *Journal of Range Management* 26:296-298.
- Lauenroth, W. K., J. L. Dodd, and P. L. Sims. 1978. "The Effects of Water- and Nitrogen-Induced Stresses on Plant Community Structure in a Semi Arid Grassland." *Oecologia* 36:211-222.
- Liebig, J. 1840. *Chemistry in Its Application to Agriculture and Physiology*. Taylor and Walton, London.
- Odum, E. P. 1971. *Fundamentals of Ecology*. 3rd ed. W. B. Saunders Company, Philadelphia.
- Rickard, W. H. 1985. "Shoot Production and Mineral Nutrient Assimilation in Cheatgrass Communities." *Northwest Science* 59:169-179.
- Rickard, W. H., and B. E. Vaughan. 1988. "Plant Communities: Characteristics and Responses." In *Shrub-Steppe Balance and Change in a Semi-Arid Terrestrial Ecosystem*, eds. W. H. Rickard, L. E. Rogers, B. E. Vaughan, and S. F. Liebetrau, pp. 109-179. Elsevier, Amsterdam.

Romney, E. M., A. Wallace, and R. B. Hunter. 1978. "Plant Response to Nitrogen Fertilization in the Northern Mohave Desert and Its Relationship to Water Manipulation." In *Nitrogen in Desert Ecosystems*, eds. N. E. West and J. J. Skujins. Dowden, Hutchinson and Ross, Stroudsburg, Pennsylvania.

Thornley, J.H.M., and I. R. Johnson. 1990. *Plant and Crop Modelling - A Mathematical Approach to Plant and Crop Physiology*. Oxford University Press, Inc., New York.

Uresk, D. W., J. F. Cline, and W. H. Rickard. 1979. "Growth Rates of a Cheat Grass Community and Some Associated Factors." *Journal of Range Management* 32:168-170.

West, N. E., and J. Skujins, eds. 1978. *Nitrogen in Desert Ecosystems*. Dowden, Hutchinson and Ross, Stroudsburg, Pennsylvania.

Woodmansee, R. G. 1978. "Critique and Analysis of the Grassland Ecosystem Model ELM." In *Grassland Simulation Model*, ed. G. W. Innis. Springer-Verlag, New York.

Natural Runoff in the Shrub-Steppe: Implications for Groundwater Recharge

L. L. Cadwell, G. W. Gee, and V. D. Parks

Natural runoff in the Hanford shrub-steppe has the potential to concentrate surface water and contribute to local groundwater recharge. The areal distribution and extent of recharge have major implications for driving contaminant leaching and for the transport of nuclear and hazardous chemicals should they reach groundwater. Natural precipitation occurring in both winter and summer provided the opportunity to measure the quantities of runoff occurring on undisturbed silt loam soils on the Arid Lands Ecology (ALE) Reserve. The study site lies upslope from and approximately 8 km south-southwest of the 200 Areas, where much of Hanford's contaminant inventory is located.

The study site consists of 3-m by 10-m plots that were established in 1986 within the native sagebrush-bunchgrass community. The plot surfaces are gently to moderately sloped (8 to 10%) and are representative of large land areas below and northeast of Rattlesnake Ridge. Observations on natural runoff were made by measuring runoff volumes collected in large catchment vessels directly below each of 12 plots. Six of the plots have undisturbed natural vegetation, and the other six had vegetation removed in 1986 and were maintained vegetation-free through the 1988 growing season. Since the spring of 1989, the plots have been allowed to revegetate naturally. There has been no physical disturbance to the soils of either the naturally vegetated or the recovering successional-vegetation (recovery) plots.

During the winter of 1990-1991, a cold air mass settled over the Columbia Basin that resulted in sustained subfreezing temperatures, frozen soil to depths beyond 20 cm, and intermittent snowfall. Five winter storms occurred during this cold period between December 18, 1990, and January 12, 1991. Because air temperatures remained below freezing and surface soil was frozen, snow remained on the ground. The total precipitation equivalent from the snowfall was 2.8 cm as measured by weighing lysimeters located at the site. Because the amount of surface moisture lost by sublimation was not determined, the 2.8 cm is an upper limit to the amount of accumulated moisture in the snowpack. Approximately midday on January 12, 1991, wind velocities increased substantially and temperatures rose rapidly from approximately -2°C to 14°C; this phenomenon is known locally as a "Chinook" wind. The snow melted rapidly, but much of the meltwater was prohibited from infiltrating because the soil was frozen. Runoff collected during the snowmelt is contrasted in Table 1 with measured quantities of runoff subsequent to a 1.4-cm rain that occurred on June 20, 1991. A minimum of 12% (actual moisture may have been slightly less than the assumed 2.8 cm as a result of losses by sublimation) of the winter snowmelt was lost from the naturally vegetated plots, whereas 50% was lost from plots having recovery vegetation. By

TABLE 1. Percent Runoff Computed for Winter and Summer 1991 Runoff Events on Undisturbed Soils of the Shrub-Steppe Having Natural Climax and Early Successional Stage Recovery Vegetation

<u>Plot Pair</u>	<u>Winter Natural Vegetation</u>	<u>Winter Recovery Vegetation</u>	<u>Summer Natural Vegetation</u>	<u>Summer Recovery Vegetation</u>
1	11.2	36.1	0.03	0.17
2	25.8	64.9	0	0.29
3	18.0	54.9	0	0
4	9.3	85.9	0	0.12
5	3.5	45.3	0	0.07
6	3.9	16.4	0.01	0.41
Mean (S.E.) ^(a)	12.0 (8.6)	50.6 (24.0)	0.01 (0.01)	0.18 (0.06)

(a) S.E. = standard error.

comparison, runoff from the summer thunder-shower that occurred on June 20, 1991, was insignificant, with an estimated 0.01% runoff on the naturally vegetated plots and 0.2% on the recovery vegetation plots.

This research demonstrates that significant runoff in the shrub-steppe does occur and that the combination of factors present during the winter (including the opportunity for moisture to accumulate as snowpack, frozen soil, and rapid warming) provides the potential for greatest runoff. These observations, coupled with the fact that removal of soil moisture by plants during the winter is limited, demonstrate a considerable potential for localized recharge, particularly near the base of slopes and within drainages. These data further suggest that loss of natural vegetative cover greatly enhances both the potential for runoff and recharge. Fully 50% (1.4 cm) of the snowmelt was lost as runoff from the recovery vegetation plots.

The results provide clear implications for management of the large, sloped land areas adjacent to Hanford waste management areas. Land use practices that minimize disturbance to the natural vegetation will also minimize the potential for enhanced recharge of groundwater by localized surface runoff, which is most likely to occur during the winter.

Landscape Ecological Studies: Net Radiation and the Relationship Among Surface Temperature, Normalized Difference Vegetation Index, and Elevation on the Arid Lands Ecology Reserve

S. O. Link, G. M. Petrie, L. G. McWethy, R. R. Kirkham, and L. E. Rogers

The ability to predict the consequences of global climate change requires that processes be modeled at landscape scale. We investigated the possibilities of predicting evapotranspiration on a landscape scale in natural ecosystems. Our experimental landscape is the Arid Lands Ecology (ALE) Reserve, which is a semiarid shrub-steppe ecosystem. Evapotranspiration for this landscape was predicted using empirical models based on ground-based and Landsat Thematic Mapper (TM) satellite data (Gibbons et al. 1991). To make these models more general and transferable, we have been working toward the use of mechanistic models to predict processes such as evapotranspiration at the landscape scale. The classic approach to the prediction of evapotranspiration makes use of the energy budget equation given as

$$LE = R_N - G - H \quad (1)$$

where LE is the latent heat flux (evapotranspiration), R_N is the net radiant flux, G is the soil heat flux, and H is the sensible heat flux, all in energy units ($W m^{-2}$). Sensible heat flux is a function of air temperature, surface temperature (T_s), wind speed, aerodynamic resistance (r_{ae}), and other surface characteristics. If we can predict values of R_N , G, and H across the landscape, then we can predict LE across the landscape.

We have made significant progress in predicting R_N across ALE (Figure 1) as described in Gibbons et al. (1991). Net radiation is given as

$$R_N = R_{SI} - R_{SO} + R_{LI} - R_{LO} \quad (2)$$

where R_{SI} is short-wave incoming radiation, R_{SO} is short-wave outgoing radiation from ground reflectance, R_{LI} is long-wave incoming radiation from the atmosphere, and R_{LO} is long-wave outgoing radiation from T_s . Applying the methods used to predict R_N (Gibbons et al. 1991) yielded the map depicted in Figure 1. Most of the variation in net radiation can be attributed to T_s . Net radiation is lower at the lower elevations because of higher T_s and is higher at the higher elevations because of lower T_s . Soil heat flux (G) is usually considered to be an empirical function of R_N and is small compared with magnitudes of R_N and H.

The more difficult variable to predict across the landscape is sensible heat flux (H) because it is strongly dependent on surface characteristics and surface meteorology. Surface characteristics that are important in the prediction of H are related to the roughness of the surface. Surface roughness is dependent on plant community characteristics. Downs et al. (this volume) have produced a supervised classification map of the major plant communities found on ALE. This map will allow more accurate location of latent heat flux because surface roughness characteristics associated with each plant community type can now be mapped.

Surface meteorology, in terms of air temperature and wind speed, is not easily obtained from satellite data. As a consequence, surface data are required but are generally difficult to obtain and model with reliability. One way to simplify this effort is to consider r_{ae} to be empirically related to T_s and the normalized difference vegetation index (NDVI), which can be obtained from satellites as described by Running (1990). We found strong linear relationships among T_s , NDVI, and elevation. We found T_s to decrease with increasing elevation (Figure 2) and with increasing values of NDVI (Figure 3). A decrease in T_s with increasing elevation is expected with the associated decreasing air temperature. The decrease in T_s with increasing NDVI is associated with increased green vegetation. More green vegetation causes the surface to be cooler because less warm bare ground contributes to the observed surface temperature and green vegetation is cool because of the evaporation of water (transpiration).

Future progress in the prediction of latent heat flux from arid landscapes will make use of surface measures and modeling efforts to predict air temperature, wind speed, and r_{ae} .

References

- Gibbons, D. E., S. O. Link, B. A. LeBaron, R. R. Kirkham, and G. W. McWethy. 1991. "Landscape Ecological Studies: Quantitative Remote Sensing of Evapotranspiration." In *Pacific Northwest Laboratory Annual Report for 1990 to the DOE Office of Energy Research, Part 2: Environmental Sciences*, pp. 64-70. PNL-7600 Pt. 2, Pacific Northwest Laboratory, Richland, Washington.
- Running, S. W. 1990. "Estimating Terrestrial Primary Productivity by Combining Remote Sensing and Ecosystem Simulation." In *Remote Sensing of Biosphere Functioning*, eds. R. J. Hobbs and H. A. Mooney. Springer-Verlag, New York.

NET RADIANT FLUX DENSITY MAP : MAY 8, 1989 , 11:16 PDT
 ALE Reserve, Hanford Site, Washington
 Derived from Landsat TM and Meteorological Data

COLOR KEY (W/m ²)		
430		570
450		590
470		610
490		630
510		650
530		670
550

FIGURE 1. Net Radiant Flux Density Map for the Arid Lands Ecology Reserve

FIGURE 2. The Relationship Between Elevation and Surface Temperature for Several Normalized Difference Vegetation Index (NDVI) Classes on the Arid Lands Ecology Reserve

FIGURE 3. The Relationship Between Normalized Difference Vegetation Index and Surface Temperature for Three Elevation Classes on the Arid Lands Ecology Reserve

Landscape Ecological Studies: Validation of the Supervised Land-Cover/Vegetation Classification for the Arid Lands Ecology Reserve

*J. L. Downs, L. G. McWethy, S. O. Link,
D. E. Gibbons, and G. M. Petrie*

During FY 1990, a supervised classification land-cover map was produced using Landsat Thematic Mapper reflectance and thermal band data to map the distribution of plant communities on the Arid Lands Ecology (ALE) Reserve. Fourteen bands of data from two images (May 8 and June 9, 1989) were analyzed using the National Aeronautics and Space Administration's Land Analysis System. Using a Bayesian maximum likelihood algorithm and areas of known vegetation as training sites, 24 initial categories were identified. Consideration of topographic characteristics (such as slope) and staff expertise allowed these initial categories to be combined into seven vegetation cover types to describe the ALE landscape. These seven classifications were disturbed/cheatgrass, bluebunch wheatgrass, Sandberg's bluegrass, sagebrush, old fields, disturbed/playa, and riparian (Figure 1).

During FY 1991, efforts were directed to assess the accuracy of the mapping exercise and to verify these land-cover classifications. The first efforts involved the statistical determination of the necessary number of ground-truth points and then randomly locating these within the land area of each vegetation cover type. Using Hord criteria (Hord 1986), we determined the number of ground-truth points necessary to validate the classification. Fifty-six points were mapped on the ALE landscape using the Geographical Resources Analysis Support System (GRASS) Geographic Information System (GIS). The number of points in each category was assigned using stratified random sampling, and the points were then randomly distributed in that vegetation category using the GRASS GIS. For example, the bluebunch wheatgrass category consists of 14,317 ha (46.5%) of the total 30,813 ha of land cover on ALE. Therefore, 46.5% of the 56 points (26 points) were randomly mapped in the bluebunch wheatgrass category. The three vegetation types covering a very small percentage of the site (old fields,

disturbed/playa, and riparian) were assigned one verification point each, as shown in Table 1.

The longitude and latitude of each of the ground-truth verification points were transferred onto 7.5-min U.S. Geological Survey topographic maps of ALE. During ground-truth verification, each point was physically visited by staff botanists and geologists to identify the plant community classification at that location and ensure the accuracy of the location. A global positioning system was used when available to aid in locating the points in the field. Canopy-cover data were collected at a number of the points using the line-intercept method. Shrub density measurements were also gathered as ancillary data for some of the ground-truth sites.

Examination of the ground-truth information led to minor redistribution of the original 24 computer classification categories to the final seven categories. In particular, one category in the supervised classification with two ground-truth points was changed from Sandberg's bluegrass to bluebunch wheatgrass, and one area on the map was changed to sagebrush to account for a small locational error and the effects of including a firebreak in the pixel.

Data gathered during ground-truth verification were used to generate an error matrix for the land-cover classifications. One axis of this matrix is the computer classification of the land cover, and the other axis is the staff classification of the land cover (Table 2). The shading in this table indicates the number of ground-truth points where the computer and staff agreed on classifications. The total number of points along the shading divided by the total number of ground-truth verification points gives the classification accuracy $[(40/56) * 100 = 71.4\%]$. The accuracy of classification varied between vegetation types: agreement between field observations and computer classifications was greatest for the bluebunch wheatgrass community (81.5%) and lowest for the sagebrush community (44%). Further evaluation of the classification process indicated that sagebrush stands with low-percentage canopy cover were incorrectly classified using the computer.

FIGURE 1. Map of Vegetation Classifications for ALE (classifications were made using remote-sensing data)

TABLE 1. Listing of Ground-Truth Verification Points Assigned in Each Land-Cover Classification

Verification Point	Vegetation Cover Type	Percent ALE Landscape
1 - 6	Disturbed/cheatgrass	11.26
7 - 30	Bluebunch wheatgrass	43.18
31 - 43	Sandberg's bluegrass	24.13
44 - 53	Sagebrush	17.41
54	Old fields	0.34
55	Disturbed/playa	2.28
56	Riparian	1.40

Reference

Hord, R. M. 1986. *Remote Sensing: Methods and Applications*. John Wiley & Sons, Inc., New York.

TABLE 2. Error Matrix for the ALE Land-Cover/Vegetation Map

Ground-Truth Computer Class	Disturbed/Cheatgrass	Bluebunch Wheatgrass	Sandberg's Bluegrass	Sagebrush	Old Fields	Disturbed/Playa	Riparian	Total	Producer Accuracy (%)
Disturbed/Cheatgrass	6							6	100.0
Bluebunch Wheatgrass		22	2	2				26	84.6
Sandberg's Bluegrass	2		5	3				10	50.0
Sagebrush		5	2	4				11	36.4
Old Fields					1			1	100.0
Disturbed/Playa						1		1	100.0
Riparian							1	1	100.0
Total	8	27	9	9	1	1	1	56	
User Accuracy (%)	75.0	81.5	55.6	44.4	100	100	100		

User Accuracy = Percent of points in the map categories that are correctly classified.

Producer Accuracy = Percent of points in a class that are correctly classified by the producer.

S9112065.10

Designs for Environmental Field Studies

J. M. Thomas, L. L. Eberhardt, M. A. Simmons, and V. I. Cullinan

During FY 1991, we continued research in the areas of observational sampling and sampling for pattern. These are two of the six areas identified in a recent paper (Eberhardt and Thomas 1991). In the case of observational sampling, our methods were developed and based on long-term large mammal data sets, while the scaling and sampling for pattern methods were formulated using plant cover measurements.

In the current national emphasis on global climate change, there is a distinct tendency to ignore or neglect the animal components of ecosystems. Reasons include the relatively small global biomass of animals, the presumed major role of components of lower stages (e.g., phytoplankton) in trophic diagrams, and the severe difficulties in assessing animal populations and their role in ecosystem dynamics. On the other hand, large mammals are perceived by the public and many policymakers as being of primary interest. In some more sensitive ecosystems, particularly the arctic and antarctic regions, large mammals do have a key role in ecosystem dynamics, as evidenced by the short food chains involving large whales and the emerging understanding of how predation by marine mammals controls some ecosystems.

Research on observational sampling conducted in this project has also served to develop the technology for assessing large animal populations. This effort has had two major components. One concerns methods of sampling and measuring abundance (a summary of our work along those lines was recently published; Eberhardt and Thomas 1991). The second deals with the analysis of the dynamics of animal populations. Such studies require large expenditures for fieldwork and decades of effort, which cannot be provided by any single research project. We have thus concentrated on cooperative efforts with a variety of management agencies who have direct statutory responsibility for management of the species, but often lack expertise and resources needed for data analysis. Through this cooperation, we have been able to provide advice and analyses in exchange for access to long-term data sets.

Publications resulting from these efforts include papers on bowhead whales and feral horses (see Publications and Presentations). Data sets in various stages of analysis on which future papers will be based include bowhead whales, brown bears, caribou, fur seals, walrus, and wolves.

Observational Studies

Research results submitted for publication during FY 1991 that can be classed within observational sampling techniques include trend analysis, models of ungulate population dynamics, and a study of methods for assessing density dependence. Trend analysis was used to study the growth of populations of three species and was simulated to assess methods of estimating rates of change from population trend data. Results indicated that the trend record of an individual population may provide a relatively unbiased estimate of the underlying rate of change but does not appear to contain the information needed to make statements about the likely behavior of similar populations or to compare trends in different populations. Projections of future individual population trends may be most satisfactory if obtained by simple linear regression on count logarithms. In some examples, confidence limits on such projections were satisfactory for short-term projections.

Studies of ungulate population dynamics resulted in a useful theory in the form of equations based on the work of A. J. Lotka. Because the Leslie matrix model yields identical results and is widely known, it is convenient to label the resulting equations as the Lotka-Leslie model. The approach is useful for assessing population trends and attempting to predict the outcomes of various management actions. A broad list of applications to large mammals and two examples specific to caribou were developed based on a simple spreadsheet approach to calculations.

Studies of density dependence included the method of implementing the dynamic response method, which was developed in an attempt to use time-series data on relative population sizes to satisfy the requirements of the Marine Mammal Protection Act of 1972 for maintaining an "optimum sustainable population" of marine mammals. We studied three methods of implementing this

approach using a computer simulation of stochastic population growth with density dependence operating on first-year survival in the form of a generalized logistic function. Methods developed by two other investigators appeared to be less sensitive than desirable when used with the simulated population data. Our method offers better protection against Type II errors (i.e., failing to identify populations in the optimum sustainable population range).

Current research includes methods for using the Lotka-Leslie model in population studies, reconstructing population trends, estimating reproductive rates, analyzing predator-prey systems (caribou and wolves), and assessing the status of populations. In a longer time frame, we are working to further assess a test for density dependence, develop the use of the bootstrapping technique in population studies, improve quantitative techniques for the study of grizzly bears, and examine various population models.

Sampling for Pattern

A fundamental principle of ecology is that components of ecosystems are interrelated and that an understanding of these relationships will allow scientists to predict community, ecosystem, or global change caused by human disturbance. A method for determining the level of resolution needed to study components of ecosystems and their interrelations has been proposed by Carlile et al. (1989). The objective of this research is to provide further justification of the importance of considering scale in the design and analysis of ecological research.

Many large-scale models have been and are being developed to predict the response of ecological systems and species to global climate change. An indirect implication of these modeling efforts is that we can detect such change before the loss of biological integrity and in time to mitigate or adapt to such losses or change. In arid land systems, global warming compounded with current land and water use practices will exacerbate desertification. Changes in the spatial distribution of vegetation, including invasion of generalists and loss of entire patches of endemic species, are indicators of increasing desertification. The ability to detect and monitor slight changes in the spatial distribution of vegetation before these changes

are visually apparent is key to addressing and potentially minimizing large-scale ecological change. We believe that using a resolution appropriate to the spatial heterogeneity under investigation is the key to quick detection.

A comparison of the efficiency of an array of statistical analyses for detecting change in the spatial distribution of vegetation through simulation was conducted. The analyses under consideration include Hill's patch-size analysis, spectral analysis, fractal analysis, and variance ratio and correlation analysis; all are methods for describing landscape pattern and scale. The simulation used for this comparison currently considers removal of vegetation using random and cluster removal of percent cover data from transects. Extensions planned for the simulation model include random and cluster invasion in conjunction with both removal patterns using two-dimensional or map data generated from satellite images.

Simulations were run on data collected from a 2050-m line-intercept transect across the Arid Lands Ecology (ALE) Reserve on DOE's Hanford Site in southcentral Washington. For both random and cluster removal patterns, the simulation model mimics organisms being dropped onto the transect and allowing them each to remove 10% of the vegetative cover in a 1-m cell. If there is less than 10% vegetative cover within an animal's cell, the model forces the organism to move randomly into adjacent cells until sufficient vegetation is located within a single cell. More than one organism can be dropped into a cell, but each organism eats in order of arrival. Thus, any organisms arriving after all the vegetation in a cell is removed must search the adjacent cells. For example, a cell with 83% cover can accommodate only eight organisms.

Thus far, simulation results are encouraging for the variance ratio analysis developed by Carlile et al. (1989). This variance method appears to be more efficient at detecting cluster removal patterns than the other methods of analysis. The variance ratio analysis was able to detect changes as small as 0.5% in the spatial distribution of vegetation (Figure 1). In terms of the simulation, a change of approximately 0.5% can be generated by dropping 100 organisms in four randomly located clusters. All methods could detect changes of 5% (e.g.,

FIGURE 1. Results from a Variance Ratio Analysis of Bluebunch Wheatgrass, *Agropyron spicatum*, Both Before and After the Simulated Removal of 0.5% of the Vegetation Using a Cluster Removal Pattern. Note that for nearly all transect segment lengths (TSL), cluster removal would be detected by the variance ratio method (Carlile et al. 1989).

1000 organisms in four clusters). Interestingly, none of the methods appears to be more efficient in detecting random removal of vegetation. In fact, as the number of clusters was increased (i.e., increasing the random component of the cluster removal pattern), the differences in efficiency between the methods was reduced.

Conclusive results on the detection of change are still premature. Simulations using different numbers of organisms with variable cluster sizes still need to be evaluated. Different removal patterns and still smaller vegetative changes have yet to be explored. Expansion of both the simulation model and the analysis to two dimensions will provide even further evidence for the efficiency of the methods for detecting change.

Our research on the detection and measurement of scale has progressed to the examination of multiple species. Research was conducted on two questions: Could we quantify the relationship between the scale for individual species and the scale for the whole community? Does the scale calculated from spectral data recorded by Landsat

Thematic Mapper correspond to the ground-based scale for multiple species? To address these questions, the percent cover for juniper trees and four shrub species was measured for two transects in central Oregon. All grasses had been eaten by free-ranging cattle.

The scale (defined as the transect or area that provides the most information at the greatest efficiency or smallest error) for transects containing multiple species can be calculated as the weighted average of the scale detected for individual species. Weights were the variance for unit transect lengths and zero lag. Variances, calculated according to the methods of Carlile et al. (1989), are the error mean square from an analysis of variance. Calculations are shown in Table 1 for one transect; the calculated scale (295 m) is similar to the scale (240 m) interpolated from a plot of interclass correlation versus transect segment length (see, for example, Figure 4 in Carlile et al. 1989). Thus, we were able to estimate the scale for the entire community from the scale for individual species in the Oregon transect.

The relationship between the scale for individual species and the scale for the combined data in Table 1 was confirmed using percent cover from the transect at the ALE site, which consisted of four species of perennial grasses. Again, the overall scale could be estimated as the weighted average of scales for individual species. The scale for all species combined for the transect at

TABLE 1. Scales and Variances for Individual Plant Species on a 4000-m Transect in the Juniper Forest of Central Oregon. A calculation for estimating the scale for a transect containing all species is also included.

Species	Variance (V)	Scale (S) (m)	V*S
Juniper	228	128	29,184
Sagebrush	119	128	15,232
Green Rabbitbrush	33	240	7,920
Bitterbrush	90	960	86,400
Grey Rabbitbrush	1	240	240
Total	471		138,976

Weighted Average = $138,976/471 = 295$ m.

ALE was similar to that calculated using spectral data from Landsat Thematic Mapper remote images. This agreement supports our hypothesis that the scale detected from remote-sensing images is a composite of the scale for the entire plant community.

References

Carlisle, D. W., J. R. Skalski, J. E. Batker, J. M. Thomas, and V. I. Cullinan. 1989. "Determination of Ecological Scale." *Landscape Ecology* 2:203-214.

Eberhardt, L. L., and J. M. Thomas. 1991. "Designing Environmental Field Studies." *Ecological Monographs* 61:53-73.

National Environmental Research Park Intersite Data Synthesis

W. H. Rickard

Contributors

V. I. Cullinan, S. O. Link, M. A. Simmons, L. E. Eberhardt, J. M. Thomas, and J. C. Chatters

National Environmental Research Park (NERP) workshops were developed to facilitate the analysis of research data collected from multiple sites. Where possible, intersite comparisons or data synthesis across sites is desired. Most of the land on the research parks is undeveloped, without cultivation agriculture and without human residents, so the parks function as quasi natural areas, resulting in some exceptional long-term data sets. Because of the long history of research, the available data sets, and the investigator experience at the Hanford park site, the scientific staff participated in five (and organized one) computational/synthesis workshops during FY 1991. The following is a report of those activities.

The population dynamics workshop was held at the Savannah River Ecology Laboratory in January 1991. Included were representatives from three DOE laboratories. The primary goal of the workshop was to assess the value of long-term studies in understanding the population processes of ungulates. Long-term data sets obtained on populations residing on research parks (including

elk data from PNL) and ungulate population data from other locations were assessed in this workshop. Topics discussed included the use of long-term data sets in interpreting cause and effect, identifying density-dependent relationships, managing ungulate populations, and understanding populations processes. The workshop resulted in a preliminary manuscript on the value of long-term data sets to wildlife ecologists and a possible special session at the 1992 North American Wildlife Conference.

The landscape scale and pattern workshop was held in March 1991 at New Mexico State University's Workbench Laboratories, which include computer facilities and work areas. The workshop brought together a small number of scientists actively exploring landscape pattern and scale, their data, and the computational capability to pose real-time questions. This computational workshop allowed data exploration, examination of theories, and increased understanding of landscape pattern and scale.

The workshop resulted in the discovery that there were many unknown relationships among the methods available for describing landscape pattern and scale. Methods studied and evaluated included Hill's analysis, spectral analysis, and variance ratio and correlation analysis. Two hierarchical models were generated using sinewaves (periodic data) and curdles (not periodic) for comparison with field data. Exploration with these models and subsequent analysis allowed the prediction of the scales of pattern for data generated from sinewaves but not for curdled data. Multiple scales were detected for both sets of simulated data. At the close of the workshop, several ideas (including wavelet analysis, histograms of gaps or clusters, and edge analysis) were proposed to determine original scales from analysis of the curdled data. Another workshop will be necessary before a journal paper can be prepared.

A computational workshop was held in May 1991 at New Mexico State University. The workshop provided an overview of the model for computational workshops, in theory and practice, and included an introduction to generalized data archiving so data would be readily available for use at all ParkNet workshops. These sessions are designed to introduce ParkNet participants to a

format for conducting computational workshops, as well as providing methodology for common data base systems.

The purpose of the June 1991 landscape workshop held at Oak Ridge National Laboratory was to organize a much larger 1992 workshop where landscape pattern models could be applied to classified Landsat images of research parks and their surroundings. The analysis would quantitatively determine how connected each park is to its surrounding landscape. The six workshop participants suggested that the remote-sensing vegetation map (data set) of the Hanford park could be sent to the computational laboratory at New Mexico State University for analysis and to Oak Ridge National Laboratory to test connectedness theories. The participants also agreed that a journal article could be the product of the next workshop.

The Hanford workshop entitled "Past Rates of Ecological Change" was also held in June 1991. Experts on the measurement of change in the paleoecological record were assembled to assess evidence for the rapidity of climatic and ecosystemic responses in the past and to explore the role of paleoecology in identifying and predicting regional impacts caused by global climate change. Attendees included an ostracod specialist, a paleontologist, two university palynologists, an ecologist and coordinator of NERP workshops, a statistician, and the NERP manager for DOE's Office of Health and Environmental Research. James Chatters (PNL paleoecologist) organized and facilitated the workshop.

Participants presented evidence of change rates in their own paleoecological research, manipulated 13,000-year-old pollen and algae records from two Washington lakes and small mammal data from an Idaho cave, and discussed applications of the paleorecord to the perception of climate change. The conclusion was that, where the sedimentation rate of a site is rapid and the sampling interval is close, major ecological changes in the early Holocene consistently occurred in the space of a century or less. This timescale is consistent with rates of change suggested by general circulation modelers, leading to the observation that the paleorecord provides examples of change analogous to possible future changes.

Participants noted that apparent response of an ecosystem to climatic forcing will vary with the generation time of the organisms used as indicators. The data bases studied during the workshop showed that algae tended to show a change before a shift in vascular plants (especially trees) was evident. Therefore, either short-lived species or long-lived species that grow incrementally will be the best indicators of the actual timing of climatic events. Changes in water chemistry and the proportions of stable isotopes in biogenic compounds will be faster still, because these properties are often directly determined by meteorological conditions.

The conclusion of the workshop was that patterns of change in the paleoecological record could be used to identify the harbingers of large-scale ecological change, such as algal species, water chemistry, or tree rings. These phenomena could then be monitored in present-day water bodies and forests to forecast ecosystemic response to climatic changes. The NERP sites, Long-Term Ecological Research sites, and National Parks, where climate-induced changes can potentially be isolated from direct anthropogenic effects, could be the sites from which these harbingers were monitored. A journal article advocating this approach is planned.

A workshop on variability in ecosystems was held at Idaho State University in August 1991. A group of five scientists evaluated population data submitted primarily by Idaho National Engineering Laboratory, PNL, and Savannah River Ecology Laboratory; each data set covered at least 5 years. Based on long-term PNL data sets on nesting geese and bald eagles [as the basis for a Monte Carlo simulation of the coefficient of variation (CV) as a function of years of data collected], the participants demonstrated a significant difference in CVs for herbivores, omnivores, predators, and cyclers. Using a second data set based on long-term plant, small mammal, and insect abundance data from a Minnesota site, participants found a statistically significant negative linear regression between CV and mean species richness for plants and small mammals but not for grasshoppers. Precipitation had no effect on these conclusions. Each of these studies has been outlined for possible journal publication.

Dr. Richard Inouye, workshop convenor, will be senior author.

Two papers have been prepared detailing inter-park comparisons of bird populations, resulting from scientific collaboration initiated at workshops during FY 1990. In the first paper, surveys of avian species composition and relative abundance, conducted in arboreal habitats in winter and spring at research parks in contrasting

ecoregions (Washington and Tennessee), are compared using species diversity indexes and rarefaction calculations. In a second paper, the authors demonstrate the value of the research parks in shrub-steppe and grassland ecoregions in Illinois, Idaho, and Washington as habitat for wild birds. The parks provided breeding habitat suitable for birds because of conservative land use practices and low levels of toxic contaminants in bird foods.

**Laboratory-
Directed
Research and
Development**

Laboratory-Directed Research and Development

Laboratory-directed research and development is conducted to develop new and promising scientific concepts that have a high potential for advancing the state of knowledge in environmental sciences. This section describes innovative research on the forefront of science that offers opportunities for significant contributions in the future.

Chemical Desorption/Dissolution Kinetics

C. C. Ainsworth

The primary objectives of this research are to develop 1) advanced techniques (stir-flow kinetic systems, pressure jump/relaxation) for measurement of the kinetic constraints on the desorption/dissolution processes and 2) new capability to combine electron spin resonance (ESR) spectroscopy with stop-flow kinetic reaction techniques to understand important solid/liquid-interface reactions in real time.

A postdoctoral appointment has been filled to conduct research on the kinetic mechanisms of adsorption/desorption on natural mineral surfaces. Emphasis is on determining the feasibility of utilizing a pressure-jump/relaxation technique in conjunction with a stir-flow reaction chamber to determine the universality of the metal (e.g., U, Cd, Co) adsorption/desorption kinetic mechanisms. Concurrently, advanced ESR spectroscopic techniques are being investigated for verification of hypothesized reaction mechanisms through a measurement of surface adsorbed species. This capability has potential for real advances of direct relevance to future studies of geochemical surface reactions that control the fate of many groundwater contaminants.

In FY 1991, a stop-flow system was successfully combined with ESR to measure reactant species in situ on a microsecond timescale in aqueous suspensions. The oxidation-reduction reactions between Cr^{3+} and a common Mn oxide were followed by observing the increasing Mn^{2+} ESR signal as Cr^{3+} was oxidized at the Mn oxide surface according to the following reaction: $1.5 \text{MnO}_2 + \text{Cr}^{3+} + \text{H}_2\text{O} = \text{HCrO}_4^- + 1.5 \text{Mn}^{2+} + \text{H}^+$. Several metals (Mn, Cu, V) and many organic

free radicals and radical cations are ESR probes. Through the use of appropriate probes, the reaction kinetics of important geochemical reactions may be discerned at timescales that will allow a more complete understanding of mechanisms and pathways.

In FY 1992 and FY 1993, we plan to determine the effectiveness of pressure-jump techniques in discriminating rate-limiting reactions at solid/liquid interfaces and to delineate the factors that can be used to manipulate rate-limiting reactions. These measurements will be linked to spectroscopic measurements (e.g., ESR) in an attempt to isolate important rate parameters.

Enzymatic Transformation of Inorganic Chemicals

Y. A. Gorby and H. Bolton, Jr.

In the past, inorganic contaminants, including radionuclides and toxic heavy metals, have been disposed of at DOE sites. In some instances, these inorganic contaminants have migrated and may threaten the quality of domestic groundwater supplies. To predict the fate of these toxic inorganic contaminants, it is vital to understand the factors influencing their solubility and migration. Microbial activity can directly influence the oxidation state and, thus, the solubility of some multivalent metals. Some anaerobic bacteria, called iron reducers, can couple the complete oxidation of reduced organic matter to the reduction of Fe(III) to Fe(II). These iron-reducing bacteria also have recently been demonstrated to reduce uranium for growth. As a result of uranium respiration, soluble U(VI) is converted to the insoluble U(IV) precipitate uraninite. Hence, this novel metabolism provides potential for the remediation of water contaminated with uranium.

The objective of this study was to determine the range of heavy metals that can serve as potential terminal electron acceptors for an iron-reducing bacterium. Such information is vital for understanding processes that may effect changes in the oxidation state and the solubility of inorganic contaminants in the environment and for exploiting these processes as bioremediative tools. The iron-reducing bacterium we used was *Shewanella putrefaciens*, a gram-negative bacterium capable of anaerobic growth with Fe(III) or U(VI) as sole terminal electron acceptors. *S. putrefaciens* was tested for its ability to couple the complete oxidation of lactate to the reduction of a variety of heavy metals. Cells cultured in a chemically defined anaerobic growth medium with Fe(III) as the electron acceptor and lactate as the electron donor were washed three times in sodium bicarbonate buffer that was previously made anaerobic by flushing with an N₂-CO₂ gas mixture. Washed cells were added to sealed anaerobic tubes containing a mixture of sodium bicarbonate and ¹⁴C-labeled lactate. Anaerobic solutions of various metals were added to each of the tubes with a syringe and needle to a final concentration of 100 μM. To detect the complete oxidation of lactate, the tubes were incubated for 18 hours, made acidic with H₂SO₄, and tested for the presence of ¹⁴CO₂. Tubes containing Fe(III) served as positive controls, and those lacking added metals served as negative controls for the oxidation of ¹⁴C-labeled lactate.

The results demonstrate that *S. putrefaciens* converted ¹⁴C-labeled lactate to ¹⁴CO₂ under anaerobic conditions with Fe(III), U(VI), Cr(VI), or V(IV) serving as electron acceptors (Figure 1). The presence of endogenous oxidant stores in the cell probably accounted for the background amount of lactate oxidation in tubes that lacked added metal (the "None" in Figure 1). Cu(II), Ag(I), and Au(III) did not function as terminal electron acceptors and actually inhibited background levels of lactate oxidation.

These results expand the known range of suitable electron acceptors for anaerobic respiration by *S. putrefaciens*. Preliminary evidence from experiments designed to monitor chromate reduction

FIGURE 1. The Effect of Added Metals on ¹⁴C-Labeled Lactate Oxidation to ¹⁴CO₂ by Anaerobic Cell Suspensions of *Shewanella putrefaciens*. Error bars indicate standard deviation about the mean (n=3).

directly suggests that *S. putrefaciens* effectively reduces Cr(VI) to Cr(III) under anaerobic conditions. Because Cr(III) forms insoluble hydroxides at circumneutral pH and is less toxic than its soluble oxidized counterpart, this metabolism may be an effective means for removing chromate from contaminated waste waters and for determining its fate in natural anaerobic environments.

Microbial chromate reduction has been demonstrated in a number of bacterial systems; however, in no case was this process related to cellular bioenergetics or growth. Because *S. putrefaciens* can grow with other heavy metals (e.g., iron and uranium) as terminal electron acceptors, chromate likely can also serve in a similar capacity. Immediate research efforts will focus on the physiological mechanisms of heavy metal reduction and how these mechanisms relate to cellular energy transduction. We hypothesize that similar, if not identical, enzyme systems exist for the reduction of the various inorganic electron acceptors. We intend to identify and purify these novel bacterial components in an effort to more fully understand the microbial processes that govern the fate of many multivalent inorganic heavy metals in the environment at DOE sites.

Biodegradative Enzyme Design

R. L. Ornstein

The objective of this research is to develop advanced concepts and PNL capabilities for improving subsurface bioremediation of DOE-site contaminants through rational redesign and genetic engineering of enzyme-mediated microbial biodegradation.

During the last 50 years, large quantities of wastes have been disposed of at DOE sites, and much of this waste is in the deep subsurface. Contamination in the deep subsurface is commonly dilute, highly dispersed, inaccessible, and in large volume. Thus, the nature of subsurface contamination substantially limits or precludes many remediation strategies currently being applied to surface and near-surface contamination. On the one hand, cost-effective remediation in deep subsurface environments, where synthetic substances (e.g., halogenated hydrocarbons like carbon tetrachloride) tend to be widely dispersed, is for the most part limited to bioremediation alternatives. On the other hand, the ability of microorganisms to adequately degrade the growing array of synthetic compounds generated by human activities is uncertain. Although microorganisms have tremendous capacity to evolve to meet new selection pressures, the timescale required to do so, depending on the complexity of the required underlying metabolic modifications, may be unacceptably long (as measured by human timescales) when hazardous substances are involved. The unique advantage of rational design is its ability to foster discovery of new enzymic forms that would otherwise have an extremely low probability of evolving biologically under either laboratory-controlled or natural conditions (such a low probability is to be expected for an enzyme requiring many simultaneous amino acid changes to accept a significantly different substrate). With the growing number of three-dimensional structures of enzymes determined by x-ray crystallography and the prospects of high-field nuclear magnetic resonance (NMR) enzyme-structure determination, rational design can be expected to play an increasing role in enzyme engineering for enhanced remediation. Although enzyme structures determined by x-ray crystallography or solution NMR methods are invaluable for rational design, they generally suffer from the following limitations:

- The structural image obtained is an average in time and space, and therefore some atomic positions may be "virtual reality" as a result of mathematical averaging.
- Conformational details are usually unrecoverable for structures less than 5 to 10% in population. Understanding these lower-populated conformations is important because bioactivity is not necessarily correlated with percent (of structural) population.
- Molecular surface properties are often significantly deformed as a result of crystal packing in the solid state or solution differences from those of in vivo conditions, such as when the pH is significantly lowered or raised or when various agents are added to reduce precipitation at high concentrations of protein.

Computational simulation methods, starting from a high-resolution experimental structure, may help resolve these experimental structural limitations, as well as lead to a better understanding of the dynamic mobilities and fluctuations inherent in enzyme structure and function.

Cytochromes P450 are a superfamily of monooxygenase enzymes that have been identified in prokaryotes, lower eukaryotes, insects, fish, higher eukaryotes, and plants, as well as many mammalian tissues and cell types. The ubiquitous distribution of cytochromes P450 is equaled by the variety of molecules that are their substrates and the variety of reactions they are capable of catalyzing. A wide range of alkane and aromatic compounds, including environmental toxins and chemical carcinogens, are hydroxylated by P450 in mammals; this enzyme class may catalyze the widest variety of reactions of any known enzyme. The functional enzyme system consists of a cytochrome P450 heme protein and two or more proteins that convey electrons from NADPH or NADH to the cytochrome. The active center of the P450 is the iron protoporphyrin moiety and an adjoining apoprotein. The mechanistic pathways and intermediates for P450 catalysis are reasonably well understood, having been explored experimentally and by theoretical quantum-chemical studies. Sequence data from several dozen P450 sequences indicate that the P450 gene superfamily diverged more than 2 billion years ago from a

single ancestral gene. The emergence of many new genes during the last 800 million years most likely reflects "animal-plant warfare." As animals began to ingest plants, plants developed new noxious metabolites; animals responded by developing novel enzymes to degrade the new plant metabolites. New synthetic compounds can be viewed as a continuation of this warfare that has been waged for almost 1 billion years.

In general, the P450 system in animals is bound to an intracellular membrane and is thus refractory to extensive solubilization, whereas the *Pseudomonas* camphor hydroxylase (P450cam) system is soluble and easily purified. Because of the difficulty in handling the vertebrate protein, much of what is known about the details of cytochrome P450 structure and function stems from studies with cytochrome P450cam obtained from the soil bacteria *Pseudomonas putida*, which initiates the conversion of camphor to 5-exo-hydroxycamphor. P450cam from *P. putida* has been cloned and expressed in *Escherichia coli*. Recent site-directed mutagenesis studies have been successfully applied to P450cam. The only available crystal structure of substrate-free P450 is that of P450cam from *P. putida* refined at 2.20 Å; in the substrate-bound form, it has been refined to 1.63 Å and compared with the substrate-free form. In addition, crystal structures have been determined for P450cam complexed with each of four different enzyme inhibitors; these inhibitors bind to and deform the active site and alter dynamic fluctuations as seen in changes of the Debye-Waller or temperature factor. The crystal structures of P450cam with the alternative substrates norcamphor and adamantanone have recently been refined at 2.0-Å resolution, and those of a ternary complex with camphor and carbon monoxide have been refined at 1.9-Å resolution (all crystal structures solved by Professor Tom Poulos and coworkers, formerly of the Center for Advanced Research in Biotechnology at the University of Maryland, now at the University of California—Irvine). This rich body of x-ray data makes the P450cam system ideal for rational enzyme engineering. Cytochrome P450cam is unlike many other enzymes in that its active center does not contain any acidic or basic amino acids or additional metal centers; therefore, successful enzyme-substrate interactions are not dependent on many directionally sensitive hydrogen bonds and charge

relay interactions. Instead, P450cam is thought to be catalytically competent for a large array of substances, as long as they are sterically acceptable to the active center and spend adequate time near the iron atom of the active center heme group. Conformational flexibility and large-scale motions of globular enzymes are often critical to their functional role. A similar situation is likely to be critical to P450cam activity because the x-ray crystal structure for P450cam with bound substrate does not exhibit an obvious pathway for ligand movement into or out of the active site. Thus, we plan to use the available detailed information of the P450cam system as a guide for rational design studies focused on altering the specificity for targeted contaminants.

The halogenated hydrocarbon, carbon tetrachloride, is recalcitrant and of considerable concern at Hanford as well as other sites around the nation. Degradation of carbon tetrachloride has been studied in *P. putida* and in in vitro systems and appears to involve cytochrome P450. Under anaerobic reducing conditions, various halogenated hydrocarbons are known to be reductively dehalogenated by cytochrome P450, while agents that selectively destroy P450 are known to hinder anaerobic reduction of halogenated hydrocarbons. Recently, cytochrome P450cam has been shown to be capable of dehalogenating 1,1,2-trichloroethane oxidatively and reductively under the same conditions, although the rate of dehalogenation is very modest and build-up leads to toxicity. The mechanism and products resulting from oxidative and reductive transformation of halogenated hydrocarbons are generally different. Although cytochromes P450 have enormous catalytic versatility, active site regioselectivity and other factors are usually rate limiting in P450 dehalogenation pathways; for camphor, however, the rate-limiting step is the second electron transfer event. There is ample evidence that complementarity between the enzyme's active site and the substrate is critical to the observed efficiency of dehalogenation and not to dehalogenation per se. Thus, 5-exo-bromocamphor is readily metabolized by P450cam to 5-ketocamphor at rates similar to those of the normal substrate, camphor. Thus, one important goal of the current research is to design P450cam mutants that are stereochemically, dynamically, and quantum-chemically engineered to readily

accept synthetics such as carbon tetrachloride as substrate for dehalogenation. Mutants that still look promising after visual and theoretical analysis will then be constructed, expressed, and tested for in vitro activity in the laboratory of Professor Stephen G. Sligar at the University of Illinois—Urbana/Champaign. X-ray crystal structure determination will then be attempted. Mutants that exhibit adequate in vitro activities will then be tested under laboratory-simulated environmental conditions at PNL.

In FY 1991, there were three areas of accomplishments for this project, as described below.

Molecular Basis for Regiospecificity and Efficiency of Catalysis: While cytochrome P450cam catalyzes the hydroxylation of camphor to 5-exo-hydroxycamphor with 100% stereospecificity and 100% efficiency, norcamphor is hydroxylated by this enzyme and yields 45% 5-exo-, 47% 6-exo-, and 8% 3-exo-hydroxynorcamphor with only 15% overall efficiency (Professor Sligar and coworkers). In FY 1991, we performed and compared simulations with camphor-bound and norcamphor-bound P450cam to better understand the underlying factors controlling P450cam regiospecificity and catalytic efficiency. These data suggest the following:

- Product specificity is, at least partially, due to the mobility of the substrate within the active site.
- The high mobility of norcamphor in the active site leads to an average increase in separation between the heme iron and the substrate of about 1.0 Å; this increase in separation may be the cause of the uncoupling of electron transfer (reduced efficiency) when norcamphor is the substrate.
- The active site water located in the norcamphor-bound crystal structure possesses mobility that correlates well with the spin-state equilibrium of this enzyme-substrate complex.

Testing Theoretical Predictions: In FY 1991, a prediction was made and tested experimentally. We had noticed in our simulations on camphor-bound and norcamphor-bound P450cam that the sidechain of Phe-87 exhibited unexpectedly large

conformational mobility for a deeply buried and bulky active site residue. In addition, when the active site was filled with water, but without substrate, Phe-87 was dynamically quiet. On the basis of these results and preliminary modeling and simulations, we proposed replacing Phe-87 by Trp. This mutation was designed to increase the coupling between electrons flowing into P450cam and substrate hydroxylation. The simulation on the mutant showed reduced mobility of norcamphor and Trp-87 in the active site when compared with the wild-type simulation. The prediction, when no experimental evidence was available, suggested that norcamphor would be more tightly coupled to electron transfer. The mutant was then constructed and results on coupling measured in Professor Sligar's laboratory. The theoretical prediction had been tested and confirmed; the mutant had twice the coupling exhibited by the wild-type enzyme when the substrate was norcamphor. This result demonstrates the validity of computational methods in characterizing and predicting the metabolism of small substrates by cytochrome P450cam.

Overcoming Serious Experimental Data Limitations:

In FY 1991, an automated computer program and a method were developed for the optimal placement of polar hydrogens in a protein structure. This method treats the polar, sidechain hydrogens of lysine, serine, threonine, and tyrosine and the amino terminus of a protein. The program, called NETWORK, divides the potential hydrogen bonding pairs of a protein into groups of interacting donors and acceptors. A search is conducted on each of the local groups to find an arrangement that forms the most hydrogen bonds. The polar hydrogens of the histidyl sidechain are specifically treated, and the ionization state of this residue is allowed to change if the change results in additional hydrogen bonds for the local group. The predictions from this method have compared excellently to known hydrogen positions for bovine pancreatic trypsin inhibitor, insulin, RNase-A, and trypsin for which the neutron diffraction structures have been determined. The usefulness of this program was further demonstrated by a comparison of molecular dynamics simulations for the enzyme cytochrome P450cam with and without the use of NETWORK. This work, aside from resulting in one publication, has been of much value; we can now start molecular dynamics

simulations from structures virtually free of hydrogen-bonded defects.

In FY 1992, we plan to continue recently started research focused on altering the regiospecificity of P450cam toward the substrate norcamphor. In view of the large body of supporting experimental data and our recently gained theoretical understanding, we are attempting the ambitious proof-of-principle goal of obtaining at least 90% 3-hydroxy product. In addition, we are simultaneously seeking to increase the overall efficiency from 15% to at least 90%. We have begun evaluating several mutations in the enzyme that are designed to alter the product specificity by changing the geometric orientation of the only hydrogen bond formed between norcamphor and the enzyme (involving Tyr-96). Current work suggests that, in addition to moving the hydrogen bond, decreasing the free volume of the active site will be necessary to help stabilize the new hydrogen bond.

In FY 1992, we plan to expend more effort on redesigning the substrate specificity of P450cam to dehalogenate one or more heavily chlorinated one- or two-carbon compounds such as carbon tetrachloride, chloroform, and trichloroethylene. As noted above, both oxidative and reductive pathways are generally possible. Using molecular modeling and molecular dynamics simulations, we will attempt to redesign mutants of P450cam that exhibit a "lock-and-key" complementarity ideal for an oxidative (aerobic) and/or reductive (anaerobic) pathway. Because chloroform is a product of a single dehalogenation of carbon tetrachloride, it will be interesting to see whether a single P450cam mutant can effectively dehalogenate both substances. Coupled experimental binding studies and x-ray crystal-structure determination will be performed. We also plan to continue constructing models of various other cytochrome P450 enzymes. Modeling other sequences will give us additional knowledge of the variations possible for this enzyme class. Such knowledge will help in the redesign efforts described above. For example, to substantially change the size of the active site, it may be necessary to alter the position of one or more of the helices that border the active site. Single-point mutations will not allow an investigation of large change in the position of whole helices. Study of independent

structures may well provide this information and show which set of mutations will bring about a desired expansion or contraction of the active site. Using principles learned from our related effort, focusing on detailed molecular simulation studies of P450cam, we plan to assess the level of specificity observed in the modeled cytochromes P450 for their native substrates versus that for the "wrong" substrate. This work is expected to lead to important structure/function relationships involving active site stereospecificity that will be useful in our attempt to rationally design optimal P450 mutant proteins specific for key recalcitrant pollutants on DOE sites.

DNA Sequence and Fragment Analysis

R. J. Douthart

The objective of this project is to develop stable automated systems for DNA sequencing and fragment analysis that will allow a number of DNA samples to be analyzed rapidly. The system entails a unique direct blotting electrophoresis device with a movable drum in the lower buffer chamber to which a membrane is attached and on which a DNA sequencing ladder or restriction enzyme fragments can be deposited. This device, coupled with a new-concept gel assembly called a ribbon channel plate, should eventually allow characterization of very small quantities of DNA, as well as throughput increased by orders of magnitude. If proven feasible, this concept will be used to rapidly characterize and study the genome of microorganisms of relevance to environmental transformations of contaminants.

Previous investigations demonstrated the feasibility of sequencing DNA using gel-filled capillaries. A family of 20 synthetic fragments differing by a single base was resolved. Use of a channeled plate was also conceived and investigated. The plate contains a series of small channels with appropriate machined or etched wells. With proper design of a cooling unit, it was envisioned that the nearly insurmountable problem of reliably manufacturing banks of individual capillaries could be achieved.

Previous studies with a drum electrophoresis apparatus also indicated that a vertical device

(reduced leakage, easier to load) was feasible, with the current being carried by the liquid interface between the drum and the nylon screen.

FY 1992 funds will support a chemical engineering student [Northwest Colleges and Universities Association for Science (NORCUS) appointment] to test a prototype apparatus constructed in FY 1991. Initial investigations suggest a DNA sequencing run with resolution to 400 bases is possible, compared with standard technology that gives a maximum resolution of 250 bases. At the end of this period, the concept will be included in proposals to distinguish the origins of microorganisms in deep subsurface environments through characterization of microbial DNA.

Hollaender Fellowship in Applied Mathematics and Contaminant Transport Modeling

C. R. Cole and T. R. Ginn

This project provided continuing PNL support for Dr. Ginn's research on subsurface flow and transport model calibration during his second and final year under the DOE Alexander Hollaender Distinguished Postdoctoral Fellowship Program. The primary focus of the work was the characterization of aquifer heterogeneities via the solution of inverse problems of hydrology. An answer was provided, in a publication accepted in *Water Resources Research*, to a question posed in the previous year of the research: under what hydrologic conditions are we able to effectively characterize an aquifer for flow-modeling purposes?

Subsurface flow and transport models of heterogeneous aquifers typically require careful calibration of a large set of effective parameters. These parameters, in addition to representing physical characteristics of the aquifer (e.g., conductivity), depend on the model resolution and the scale of heterogeneities. These dependencies, combined with the limitations of sampling an aquifer, render direct geologic evaluation of these parameters practically impossible. Consequently, the accuracy and validity of flow models (and our confidence in their use in developing

remediation strategies) depend very heavily on our ability to use hydrologic data (e.g., water table elevations) to identify effective flow parameters for these models.

From this perspective, the importance of the question posed above is clearly apparent. The area of inverse modeling is controversial primarily because a general answer to this question is difficult to find. The approach taken in this research was to restrict the investigation to finding conditions for the unique identifiability of flow models that take the form of a system of linear ordinary differential equations. Such systems are used to model many processes other than groundwater flow and transport, such as population dynamics, physical diffusion, and biological system response. Techniques in linear systems analysis were found and/or developed to obtain the solution to this problem based on a spectral decomposition of a matrix operator. The result discovered gives the conditions necessary and sufficient for finding a unique set of model parameters in terms of initial conditions and the pumping functions.

This result is of both practical and theoretical importance for inverting linear systems of ordinary differential equations (e.g., finite element or finite difference transient flow and transport models) of either homogeneous (e.g., no pumping or boundary fluxes) or nonhomogeneous (e.g., with pumping or boundary fluxes) type. The work is a significant breakthrough in inverse modeling.

Some previously determined example cases of identifiable and nonidentifiable systems already have been independently confirmed with the theory emerging from the result obtained. Research in this direction is continuing with the goal of developing methods for designing pumping tests for aquifer characterization and methods for measuring the uniqueness of parameter values.

Other related research initiated during the work includes the application of the result to models wherein the parameters are viewed as random variables (a paper on this stochastic perspective is in preparation), and the incorporation of the result into a continuous-time inversion algorithm as a tool for laboratory (numerical) synthetic

modeling studies. Such studies are directed to investigating the dependence of effective parameter identifiability on the scale(s) of aquifer heterogeneity.

Collaboration at PNL and Purdue University on the research was instrumental in the success of the investigation and is continuing in a greater degree. C. R. Cole and H. P. Foote contributed to the study, and cooperative discussions on the design of the synthetic model inversion scheme (utilizing their expertise in advanced scale-conscious numerical methods) continue. J. H. Cushman at Purdue University has contributed to the study since its inception. Finally, to facilitate information transfer among university researchers and others in the same field, a series of seminars was given during the year. Three consecutive talks were

presented at PNL, and a comprehensive seminar on the inverse problem and the new result was given in the form of invited lectures at six universities (Michigan Technological University, Oregon State University, Texas A&M University, University of Virginia, University of Wyoming, and West Virginia University).

Plans for the next year involve the continuation of the new research directions opened: the planning of a synthetic numerical laboratory and the completion of a stochastic inverse theory. Also to be initiated in the next year are communication and collaboration with PNL staff in the area of sub-surface biological and chemical processes to examine uses of the new theory in modeling these dynamics.

**Educational
O itreach**

Educational Outreach

PNL has become a leader in developing science education programs for students and faculty at the university and pre-university levels. During FY 1991, PNL established and strengthened partnerships with major universities and public schools. The partnerships provide a unique setting for laboratory research participation, curriculum enhancement, and educational training.

Pre-university programs are coordinated by PNL's Science Education Center. The Office of University Programs coordinates minority institution and university programs. The Northwest Colleges and Universities Association for Science (NORCUS) and the Associated Western Universities serve as the mechanisms for student and faculty appointments to university and pre-university programs.

Pre-University Interactions

PNL scientists participate in pre-university education activities such as 1) classroom instruction and demonstrations; 2) student apprenticeships, workshops, and field days in the laboratory; 3) teacher workshops and research participation; and 4) technical support and assistance to local and regional schools. The Arid Lands Ecology (ALE) Reserve provides an important part of environmental education activities for pre-university students and teachers.

Each summer, secondary school science teachers are assigned to work on environmental research projects as part of DOE's Teacher Research Associates Program. These 8-week assignments are based on the educational background and teaching experience of program participants. This year, 13 of 34 national/regional appointees were assigned to projects in earth and environmental sciences.

Projects included activities such as 1) evaluating the utility of modular systems for testing the efficiency of biochemical insecticides; 2) collecting and analyzing field and laboratory data on plants, soils, and vegetation in sagebrush-bunchgrass communities; and 3) conducting radiotelemetry studies of sage grouse, mule deer, and Hanford Site elk and analyzing the field data using the Geographic Information System (GIS). Each teacher participating in the program developed instructional strategies to use in their classroom based on their field and laboratory experiences.

Scientists explored the process of discovery with middle school students and teachers as part of the OPTIONS program, a national effort to get and keep female and minority students in the math/science pipeline. PNL scientists participated in meet-a-scientist sessions at schools in the Yakima Valley/Tri-Cities and in Spokane and Portland as part of the effort to interest students in science and technology.

Environmental scientists also worked with 26 teachers in SCIENCE ALIVE, a teacher enhancement program in environmental sciences for elementary teachers in schools in the Yakima Valley/Tri-Cities having high populations of Hispanic, American Indian, and black students. Teachers participated in hands-on problem-solving field and laboratory experiences led by PNL scientists. Using ALE as an outdoor laboratory, PNL researchers led teachers through activities designed to help them understand arid land ecosystems, specifically how the elements interrelate and change. Teachers learned about habitat diversity, adaptation strategies, population study methods, ecosystem dynamics, remote sensing, and water balance.

During FY 1991, PNL hosted 57 high school students from 49 U.S. states and territories and 6 foreign countries as part of the DOE High School Student Honors Research Institute. This intensive 2-week environmental research experience, led by PNL scientists, devotes a full week of field research to arid ecosystems. Using ALE as

a study site, students conducted plant, wildlife, atmospheric, stream and river, and earth science research activities. Scientists worked with students to observe, analyze, and measure environmental change—both natural and human induced—and then use their findings to understand the past and predict the future.

Also in FY 1991, 18 students traditionally under-represented in science and engineering fields received 8-week appointments to the laboratory under the Student Research Apprenticeship Program to work with a scientist, engineer, or technical specialist in a field of interest. Some of these students worked on research projects at ALE. Students assisted in collecting field and laboratory data on plants, wildlife, and soils.

Researchers also made presentations on desert ecosystems at area schools through the Sharing Science with Schools program. They discussed characteristics of the shrub-steppe environment and how wildlife adapt to it.

University Interactions

Through NORCUS, PNL provides university undergraduate and graduate students and postdoctoral scientists and faculty an opportunity to work with PNL staff in research activities and to participate in seminars, scientific meetings, and symposiums.

During FY 1991, a number of university faculty and graduate and undergraduate students participated in environmental sciences programs; some of their involvement is described in this section. More details are available in the research progress reports. The Environmental Sciences Program also hosted many visiting scientists representing universities nationally and internationally during the year for workshops, seminars, and DOE program reviews.

Subsurface Science

In subsurface chemistry, subcontracts were continued with J. C. Westall, Department of Chemistry, Oregon State University (OSU), and P.S.C. Rao, Soils Department, University of Florida (UF). Westall and two graduate students collaborated with PNL on studies of cobalt-organic ligand sorption processes using subsurface materials from DOE sites. The OSU investigators have

established new approaches to model organic-metal interactions on mineral surfaces, developed a multicomponent transport model (COLUMQL) incorporating surface complexation and ion exchange reactions, and revised the FITEQL model. Rao and two graduate students at UF completed research on the effects of miscible organic solvents on organic acid sorption by subsurface material and have recently initiated column experiments with organic acids to investigate sorption/microbial-degradation interactions during transport. The UF group will be developing a transport model that includes mechanistic sorption, mass transfer kinetics, and microbial degradation of organic ligands.

University interactions in the past year for the deep subsurface microbial investigations project have included three graduate students and Anne Summers, University of Georgia, investigating metal-resistance mechanisms and genetics in subsurface bacteria. Summers gave a seminar on her metal-resistance work with subsurface microorganisms during the past year. Her data was used in selecting the Savannah River microbial strains used in this project. Collaboration will continue on the Hanford and Idaho National Engineering Laboratory strains that demonstrated a loss of metal associated with the cell to determine whether these strains are metal resistant and have active metal-efflux mechanisms. NORCUS graduate support was provided for Michael Truex, Washington State University (Don Johnstone), to investigate the influence of long-term starvation on biodegradation of organic contaminants in porous media. NORCUS also supported Yimin Zhang, University of Arizona (Raina Miller), to investigate the role of biosurfactants on enhanced biodegradation of poorly soluble organic contaminants in sediments, and Ken Wagnon, Eastern Washington University (Don Lightfoot), to evaluate microbial community structure in deep anaerobic groundwaters of the Hanford Site using 16S rRNA-directed signature DNA probes.

Cooperative research in the intermediate-scale transport of co-contaminants is being conducted with professors A. J. Valocchi and B. E. Rittmann of the University of Illinois (UI). Jointly, studies are under way to develop and apply a multidimensional modeling capability for analyzing intermediate-scale experiments to investigate

chemically and microbiologically reactive organic solute transport in heterogeneous porous media systems. In addition, four university students have worked on this project at PNL during FY 1991. Some of the work done by Michael Truex on quantifying differences between starved versus active and induced versus uninduced bacterial cells during biodegradation experiments in flow columns will be part of his master's thesis requirements. John Barton, a Ph.D. candidate from the University of Virginia on a 3-month appointment as an Oak Ridge Associated Universities fellow, assisted with intermediate-scale experiments of tracer transport and biodegradation in layered porous media. Bill Giffen, an undergraduate student from Wright State University (Ohio) on a 4-month science and engineering research semester (SERS) appointment, assisted with modeling column and multi-dimensional intermediate-scale experiments on biodegradation during transport using the computer code developed in conjunction with UI. Jennifer Walker, an undergraduate student from Kansas State University on a 2-month NORCUS appointment, assisted with flow experiments on coupled sorption and transport.

This project also had certain responsibilities for the management, promotion, and scheduling of experiments in the Subsurface Environmental Research Facility (SERF) at PNL. These responsibilities included giving SERF tours to visiting administrators, faculty, and students from universities (approximately 50% of the 50 tours in FY 1991 were to university groups), and networking with university professors who are principal investigators on OHER's Subsurface Science Program for the purpose of determining intermediate-scale experimental needs and SERF scheduling requirements program-wide.

The subsurface pore water chemistry studies served as a basis for interactions with other Deep Subsurface Microbiology Subprogram participants (including researchers at universities throughout the United States) through interdisciplinary collaboration on research and contacts between individual researchers. Results from this effort have been disseminated to all university participants in Deep Subsurface Microbiology drilling projects, including Florida State University,

University of Texas—San Antonio, New Mexico Institute of Mining and Technology, University of Tennessee, and Memphis State University.

In the past year, researchers improving the biodegradative capacity of subsurface bacteria utilized one postdoctoral scientist and one graduate student to perform biochemical and biophysical experiments on wild-type and mutant P450cam enzymes. These experiments include substrate/product binding and catalytic efficiency analyses. In addition, site-directed mutants are being constructed and expressed, and in vitro measurements of enzyme coupling and kinetics are being determined.

On laboratory-directed research and development, the bioremediation/biodegradative enzyme design project began a coupled theory-experimental collaboration with S. G. Sligar (Departments of Biochemistry and Chemistry of the University of Illinois—Urbana/Champaign) in the area of site-directed mutagenesis and biochemical mechanistic experiments for P450cam mutants. Also, a joint theoretical effort was continued with Dr. Robert Rein (State University of New York—Buffalo and Roswell Park Memorial Institute) to develop major extensions and improvements to the capabilities of molecular-dynamics simulation programs for studies of enzymes. In FY 1991, PNL hosted and supported several SERS/NORCUS pre- and postdoctoral students. In FY 1992, we plan to initiate a collaboration with Professor Thom Poulos (University of California—Irvine), the leader in x-ray crystal-structure determination of cytochrome P450cam and its complexes.

The applied mathematics and contaminant transport modeling project was carried on with continual collaboration with J. Cushman, Purdue University. More general university interaction came about through invited lectures on the research given at several institutions (Michigan Technological University, Oregon State University, Texas A&M University, West Virginia University).

University interactions at PNL related to the research on hydrogeologic and geochemical controls on microorganisms in subsurface formations occurred in two areas: 1) collaboration with university investigators as part of the Deep

Subsurface Microbiology Subprogram of the Subsurface Science Program (OHER) and 2) collaboration with Stuart Birnbaum at the University of Texas—San Antonio. Collaborations with university investigators typically involved sharing data and joint analysis of data obtained from drill cores collected as part of the program. Pacific Northwest Laboratory geoscientists were involved in the drilling, sample collection, sample processing, and sample analysis for geoscientific data. Microbiologists at PNL and several universities were involved in determining the abundance and diversity of microorganisms in samples received from PNL. Universities involved included Memphis State University (Ed Stevens), Florida State University (David Balkwill), University of Tennessee (David White and Tom Phelps), and Cornell University (William Ghiorse).

Stuart Birnbaum (University of Texas—San Antonio) conducted specialized scanning electron microscopy on Deep Subsurface Microbiology Subprogram samples. Birnbaum used critical-point drying and rapid freezing techniques to preserve microorganisms in subsurface samples. These techniques resulted in the direct observation of microorganisms attached to mineral surfaces. Results from such observations suggest that microorganisms preferentially attach to ferromagnesian minerals. This information, if corroborated, will aid our understanding of subsurface microbial ecology.

The Rn3D code is being used by Thomas Borak and Milan Gadd of Colorado State University (CSU) to simulate radon entry rates into their miniature basements as part of PNL's modeling of radon transport in soils. Time-series data of radon concentrations in soil, soil properties, building material properties, barometric pressure, wind speed, and ventilation rates will all be assimilated into computer simulations in an attempt to reproduce radon concentrations in the structures. In this way, experimentalists will be better able to determine the sensitivity of indoor radon concentrations to the many competing factors affecting radon transport into buildings. At the same time, data from the CSU experiment can be used to validate the physical processes assumed in the Rn3D radon transport model.

The current version of the model, Rn3D, is being validated against measurements of meteorologic and soil conditions and radon concentrations made at the Poamoho Tropical Agriculture Station on Oahu. These measurements are being made by Don Thomas of the Hawaii Institute of Geophysics, University of Hawaii. In addition, measurements of basic soil parameters such as air permeability, bulk density, porosity, radium content, and emanation coefficient were made and used as input parameters in the radon transport model. Soil water retention data obtained from previous soil studies at the Poamoho site were used to estimate the radon diffusion coefficient as a function of soil water saturation.

Terrestrial Science

The dynamics of arid land ecosystems research interacts extensively with Jeffrey L. Smith, a U.S. Department of Agriculture (USDA) Agricultural Research Service Soil Scientist at Pullman, Washington, on nitrogen dynamics of arid ecosystems. A postdoctoral fellow (Jay Halvorson) and a graduate student (Dan Mummey) conducted research on nitrogen dynamics. Future interactions will include long-term ^{15}N -labeled nitrogen cycling studies in the arid annual grassland, gaseous nitrogen losses, and the temporal and spatial distribution of nitrogen across and underneath the shrub-steppe landscape.

The ecosystem dynamics project also interacted with four graduate students who were funded from this project in FY 1991. Raymond D. Evans worked under R. A. Black at Washington State University and is now with James Ehleringer of the University of Utah. Doug Jeffries worked under J. M. Klopatek at Arizona State University and has taken a faculty position at the College of the Ozarks in Arkansas. Lenny Schwarz is working under J. M. Klopatek at Arizona State University.

Jerry Bromenshenk, University of Montana (UM), participated as a faculty research fellow in the new Environmental Management Career Opportunities Research Experience (EMCORE) program along with five undergraduate students. Bromenshenk and the students, recipients of EMCORE undergraduate scholarships, teamed with PNL host

scientists to address environmental restoration problems at Hanford. At PNL, the team's approach to environmental restoration has been twofold: 1) to conduct a group project and 2) to conduct individual projects. As part of the group project, each member of the team gained practical experience with the Geographical Resources Analysis Support System, an integrated set of programs for digitizing, image processing, and mapping geographic information. The objective of the group project was to learn how to use GIS technology to assess the cumulative effects of a wide array of activities. For individual projects,

each student was matched with a host scientist and developed a collaborative research project according to the student's background and interests compared with those of scientists and ongoing restoration programs at PNL. The student/mentor relationship that developed during the initial 10-week summer session is continuing during the current academic year to enrich and educate the students, contribute to the solution of important environmental problems, and promote cooperative study between DOE/PNL, UM, and the Montana College of Mineral Science and Technology.

Publications and Presentations

Publications

Subsurface Science

Bolton, H., Jr., S. W. Li, D. J. Workman, and D. C. Girvin. 1991. "Biodegradation of Synthetic Chelates in Subsurface Sediments." In *Proceedings of the First International Symposium on Microbiology of the Deep Subsurface*, eds. C. B. Fliermans and T. C. Hazen, pp. 4-81. January 15-19, 1990, Orlando, Florida. WSRC Information Services, Aiken, South Carolina.

Bolton, H., Jr., S. W. Li, D. J. Workman, and D. C. Girvin. (In press.) "Biodegradation of Synthetic Chelates in Subsurface Sediments from the Southeast Coastal Plain." *Journal of Environmental Quality*.

Bolton, H., Jr., and R. E. Wildung. (In press.) "Bioaccumulation of Radionuclides and Metals by Microorganisms: Potential Role in the Separation of Inorganic Contaminants and for the In Situ Treatment of the Subsurface." In *First Hanford Separations Science Workshop Proceedings*. July 25, 1991, Richland, Washington.

Bolton, H., Jr., D. J. Workman, D. C. Girvin, and S. W. Li. 1991. "Effect of Chemical Speciation on the Degradation of NTA by a *Pseudomonas* sp." *Abstracts of the Annual Meeting of the American Society for Microbiology*, p. 304.

Brandt, C. A., W. H. Rickard, and N. A. Cadoret. 1990. *Reclamation Project, Basalt Waste Isolation Project, Boreholes 1990*. PNL-7585, Pacific Northwest Laboratory, Richland, Washington.

Brandt, C. A., W. H. Rickard, N. A. Cadoret, and M. G. Hefty. 1990. *Interim Reclamation Report, Basalt Waste Isolation Project, Near Surface Test Facility*. PNL-7558, Pacific Northwest Laboratory, Richland, Washington.

Brockman, F. J., T. L. Kieft, J. K. Fredrickson, B. N. Bjornstad, S. W. Li, W. Spangenburg, and P. E. Long. (In press.) "Microbiology of Vadose Zone Paleosols in South-Central Washington State." *Microbial Ecology*.

Brockman, F. J., and R. L. Ornstein. 1991. "Enhanced Bioremediation of Subsurface Contamination: Enzyme Recruitment and Redesign." In *Hazardous Materials Control/Superfund '91*, Proceedings of the 12th National Conference, pp. 264-266. Hazardous Materials Control Research Institute, Greenbelt, Maryland.

Brockman, F. J., D. J. Workman, C. M. Spadoni, and J. K. Fredrickson. (Submitted.) "Evidence for Plasmid-Encoded Hydrocarbon Catabolic Genes in a Quinoline-Degrading *Pseudomonas cepacia* Strain Isolated from a Deep Subsurface Sediment." *Applied Environmental Microbiology*.

Cary, J. W., G. W. Gee, and C. S. Simmons. (In press.) "Using an Electro-Optical Switch to Measure Soil-Water Suction." *Soil Science Society of America Journal*.

Cary, J. W., G. W. Gee, and G. A. Whyatt. (In press.) "Waste Storage in the Vadose Zone Affected by Water Vapor Condensation and Leaching." In *Proceedings of the International Symposium on the Scientific Basis for Nuclear Waste Management*. Boston, Massachusetts.

Cary, J. W., J. F. McBride, and C. S. Simmons. 1991. "Assay of Organic Liquid Contents in Predominantly Water-Wet Unconsolidated Porous Waste." *Journal of Contaminant Hydrology* 8(2):135.

Cary, J. W., and G. P. Streile. 1990. "Discussion on 'Condensation and Isothermal Water Transfer in Cement Mortar: Part II, Transient Condensation of Water Vapor' by J. F. Daian." *Transport Porous Media* 5:207-208.

Fredrickson, J. K., D. L. Balkwill, J. M. Zachara, S. W. Li, F. J. Brockman, and M. A. Simmons. 1991. "Physiological Diversity and Distributions of Heterotrophic Bacteria in Deep Cretaceous Sediments of the Atlantic Coastal Plain." *Applied Environmental Microbiology* 57(2):402-411.

- Fredrickson, J. K., F. J. Brockman, R. J. Hicks, and B. A. Denovan. 1991. "Biodegradation of Nitrogen-Containing Aromatic Compounds in Deep Subsurface Sediments." In *Proceedings of the First International Symposium on Microbiology of the Deep Subsurface*, eds. C. B. Fliermans and T. C. Hazen, pp. 6-27 to 6-44. January 15-19, 1990, Orlando, Florida. WSRC Information Services, Aiken, South Carolina.
- Fredrickson, J. K., F. J. Brockman, D. J. Workman, S. W. Li, and T. O. Stevens. 1991. "Isolation and Characterization of a Subsurface Bacterium Capable of Growth on Toluene, Naphthalene, and Other Aromatic Compounds." *Applied Environmental Microbiology* 57(3):796-803.
- Girvin, D. C., C. J. Chisholm-Baruse, P. A. Gassman, and H. Bolton, Jr. (In preparation.) "Adsorption of Co(II)EDTA and Co(III)EDTA Chelates by γ - Al_2O_3 : Surface Complexation Modeling."
- Girvin, D. C., P. L. Gassman, and H. Bolton, Jr. 1991. "Adsorption of Aqueous ^{60}Co -EDTA by γ - Al_2O_3 : Effect of Oxidation State and Ionic Strength." *Abstracts in Soil Science Society of America, Agronomy Abstracts*, p. 243.
- Girvin, D. C., P. L. Gassman, and H. Bolton, Jr. (Submitted.) "Adsorption of Aqueous Cobalt Ethylenediaminetetraacetate by γ - Al_2O_3 ." *Soil Science Society of America Journal*.
- Holford, D. J., G. W. Gee, P. C. Owczarski, and H. D. Freeman. (In press.) "Statistical Uncertainty Analysis of Radon Transport in Nonisothermal, Unsaturated Soils." In *Indoor Radon and Lung Cancer: Reality or Myth?*, Proceedings of the 29th Hanford Symposium on Health and the Environment, ed. F. T. Cross. October 15-19, 1990, Richland, Washington. Battelle Press, Columbus, Ohio.
- Lenhard, R. J. (In press.) "Measurement and Modeling of Three-Phase Saturation-Pressure Hysteresis." *Journal of Contaminant Hydrology*.
- McBride, J. F., F. J. Brockman, J. E. Szecsody, and G. P. Streile. (In press.) "Kinetics of Quinoline Degradation, Sorption, and Desorption in a Clay-Coated Model Soil Containing a Quinoline-Degrading Bacterium." *Journal of Contaminant Hydrology*.
- McBride, J. F., and C. S. Simmons. (Submitted.) "Interfacial Spreading Effects on One-Dimensional Organic Liquid Imbibition in Unsaturated Water-Wetted Porous Media." *Journal of Contaminant Hydrology*.
- McKinley, J. P., T. O. Stevens, J. K. Fredrickson, and T. E. Jones. (Submitted.) "Microbial Control of Regional $\delta^{13}\text{C}_{\text{HCO}_3}$ Variations in Deep Groundwaters of the Columbia Plateau, Washington."
- Murphy, E. M., J. A. Schramke, J. K. Fredrickson, H. W. Bledsoe, A. J. Francis, D. S. Sklarew, and J. C. Linehan. (In press.) "The Influence of Microbial Activity and Sedimentary Organic Carbon on the Isotope Geochemistry of the Middendorf Aquifer." *Water Resources Research*.
- Odencrantz, J. E., A. J. Valocchi, and B. E. Rittmann. 1990. "Modeling Two-Dimensional Solute Transport with Different Biodegradation Kinetics." In *Proceedings of Petroleum Hydrocarbons and Organic Chemicals in Ground Water: Prevention, Detection, and Restoration*, pp. 355-368. National Water Well Association, Dublin, Ohio.
- Owczarski, P. C., D. J. Holford, K. W. Burk, H. D. Freeman, and G. W. Gee. 1991. "Effect of Winds in Reducing Sub-Slab Radon Concentrations Under Houses Laid Over Gravel Beds." In *Proceedings of the 1991 International Symposium on Radon and Radon Reduction Technology*. April 2-5, 1991, Philadelphia, Pennsylvania.
- Owczarski, P. C., D. J. Holford, K. W. Burk, H. D. Freeman, and G. W. Gee. (In press.) "Radon Transport from the Subsurface: The Roles of Certain Boundary Conditions at Subsurface/Environment Boundaries." In *Indoor Radon and Lung Cancer: Reality or Myth?*, Proceedings of the 29th Hanford Symposium on Health and the Environment, ed. F. T. Cross. October 15-19, 1990, Richland, Washington. Battelle Press, Columbus, Ohio.

Owczarski, P. C., D. J. Holford, H. D. Freeman, and G. W. Gee. 1990. "Effects of Changing Water Content and Atmospheric Pressure on Radon Flux from Surfaces of Five Soil Types." *Geophysical Research Letters* 17(6):817-820.

Robertson, D. E., L. J. Kirby, A. P. Toste, C. W. Thomas, W. H. Rickard, H. L. Neilson, R. M. Campbell, M. C. McShane, and C. L. Wilker. 1990. *Radionuclide Distributions and Migration Mechanisms at Shallow Land Burial Sites: Final Report of PNL Research Investigations on the Distribution, Migration, and Containment of Radionuclides at Maxey Flats, Kentucky*. PNL-7582, Pacific Northwest Laboratory, Richland, Washington.

Sheehan, P. J., D. Johnstone, and J. K. Fredrickson. (Submitted.) "Long-Term Effects on the Morphology and Physiology of *Pseudomonas putida*."

Simmons, C. S., J. F. McBride, R. J. Lenhard, and J. W. Cary. (In press.) "Organic Liquid Infiltration into Unsaturated Porous Media." In *Proceedings of International Association of Hydrogeologists Conference on Subsurface Contamination by Immiscible Fluids*. International Association of Hydrogeologists, Calgary, Alberta, Canada.

Stevens, T. O., J. P. McKinley, and J. K. Fredrickson. (Submitted.) "Bacteria Associated with Deep, Alkaline, Anaerobic Groundwaters in SE Washington."

Stewart, D. L., B. L. Thomas, R. M. Bean, and J. K. Fredrickson. 1990. "Colonization and Degradation of Oxidized Bituminous and Lignite Coals by Fungi." *Journal of Industrial Microbiology* 6:53-60.

Streile, G. P., J. W. Cary, and J. K. Fredrickson. (In press.) "Innocuous Oil and Small Thermal Gradients for In Situ Remediation." In *Proceedings of the National Research and Development Conference on the Control of Hazardous Materials*.

Szecsody, J. E., and G. P. Streile. (Submitted.) "Mechanism of Quinoline Sorption to Clay During Transport in Columns." *Chemosphere*.

Szecsody, J. E., and G. P. Streile. (Submitted.) "Transport of Aminonaphthalene with a Limited Transformation Reaction." *Environmental Science and Technology*.

Truex, M. J., F. J. Brockman, D. Johnstone, and J. K. Fredrickson. (Submitted.) "Effect of Starvation on the Induction of Quinoline Degradation for a Groundwater Bacterium in a Continuous-Flow Column."

Valocchi, A. J., and M. Malmstead. (Submitted.) "A Note on the Accuracy of Operator Splitting for Advection-Dispersion-Reaction Problems." *Water Resources Research*.

Zachara, J. M., C. E. Cowan, and C. R. Rusch. (In press.) "The Surface Exchange of Divalent Metallic Cations on Calcite." *Geochimica et Cosmochimica Acta*.

Terrestrial Science

Bolton, H., Jr., and J. K. Fredrickson. (Submitted.) "Microbial Ecology of the Rhizosphere." In *Soil Microbial Technologies*, ed. B. Metting. Marcel Dekker, Inc., New York.

Bromenshenk, J. J., S. R. Carlson, J. M. Thomas, J. L. Gudatis, M. A. Simmons, and J. C. Simpson. (Submitted.) "Field Validation of Pollution Monitoring Around Puget Sound with Honey Bees." *Apidologie*.

Bromenshenk, J. J., J. L. Gudatis, S. R. Carlson, J. M. Thomas, and M. A. Simmons. 1991. "Population Dynamics of Honey Bee Nucleus Colonies Exposed to Industrial Pollutants." *Apidologie* 22:359-370.

Cataldo, D. A., M. W. Ligothe, H. Bolton, Jr., R. J. Fellows, P. Van Voris, J. P. McKinley, S. W. Li, and K. M. McFadden. 1990. *Evaluation and Characterization of Mechanisms Controlling Fate and Effects of Army Smokes*. PNL-7459, Pacific Northwest Laboratory, Richland, Washington.

- Cataldo, D. A., M. W. Ligothke, S. D. Harvey, R. J. Fellows, S. W. Li, P. Van Voris, and R. S. Wentzel. 1990. *Acute Environmental Toxicity and Persistence of DEM, a Chemical Agent Simulant: Diethylmalonate*. PNL-7618, Pacific Northwest Laboratory, Richland, Washington.
- Cullinan, V. I., and J. M. Thomas. (Submitted.) "An Intercomparison of Quantitative Methods for Examining Landscape Pattern and Scale." *Landscape Ecology*.
- Downs, J. L., S. O. Link, R. A. Black, and G. W. Gee. (Submitted.) "A Study of Hydraulic Resistance in *Bromus tectorum*." *Plant, Cell, and Environment*.
- Driver, C. J., M. W. Ligothke, P. Van Voris, B. D. McVeety, B. M. Greenspan, and D. B. Drown. 1991. "Routes of Uptake and Their Relative Contribution to the Toxicologic Response of Northern Bobwhite (*Colinus virginianus*) to an Organophosphate Pesticide." *Environmental Toxicology and Chemistry* 10:21-33.
- Eberhardt, L. L. 1990. "A Fur Seal Population Model Using Age Structure Data." *Canadian Journal of Fisheries and Aquatic Science* 47:122-127.
- Eberhardt, L. L. 1990. "Survival Rates Required to Sustain Bear Populations." *Journal of Wildlife Management* 54:587-590.
- Eberhardt, L. L. 1990. "Using Radio Telemetry for Mark-Recapture Studies with Edge Effects." *Journal of Applied Ecology* 27:259-271.
- Eberhardt, L. L. 1991. "Experimental Ecology. Review of Ecological Experiments: Purpose, Design and Execution, by N. G. Hairston." *Ecology* 72:1904-1906.
- Eberhardt, L. L. (In press.) "An Analysis of Procedures for Implementing the Dynamic Response Method." *Marine Mammal Science*.
- Eberhardt, L. L. (In press.) "Models of Ungulate Population Dynamics." *Arctic*.
- Eberhardt, L. L., and J. M. Breiwick. (In press.) "Impact of Recent Population Data on Inferred Historical Population Trends of Bowhead Whales." *Report of the International Whaling Commission*.
- Eberhardt, L. L., and M. A. Simmons. (In press.) "Assessing Rates of Increase from Trend Data." *Journal of Wildlife Management*.
- Eberhardt, L. L., and J. M. Thomas. 1991. "Designing Environmental Field Studies." *Ecological Monographs* 6:53-73.
- Evans, R. D., R. A. Black, and S. O. Link. 1990. "Reproductive Allocation in a Drought-Tolerant Shrub During Water Stress." *Bulletin of the Ecological Society of America* 71:149 (Abstract).
- Evans, R. D., R. A. Black, and S. O. Link. (In press.) "Reproductive Allocation During Drought in *Artemisia tridentata*." *Functional Ecology*.
- Garrott, R. A., D. B. Siniff, and L. L. Eberhardt. 1991. "Growth Rates of Feral Horse Population." *Journal of Wildlife Management* 55(4):641.
- Gee, G. W., M. D. Campbell, and S. O. Link. 1991. "Arid Site Water Balance Using Monolith Lysimeters." In *Lysimeters for Evapotranspiration and Environmental Measurements*, Proceedings of the International Symposium on Lysimetry, eds. R. G. Allen, T. A. Howell, W. O. Pruitt, I. A. Walter, and M. E. Jensen, pp. 219-227. American Society of Civil Engineers, New York.
- Halvorson, J. J., H. Bolton, Jr., and J. L. Smith. (In preparation.) "Measuring Resource Islands Under Plants: A Geostatistical Approach."
- Halvorson, J. J., H. Bolton, Jr., and J. L. Smith. (In preparation.) "Soil Biological and Chemical Heterogeneity Under *Artemisia tridentata* in an Arid Shrub-Steppe Ecosystem."
- Jeffries, D. L., J. M. Klopatek, H. Bolton, Jr., and S. O. Link. (In press.) "Acetylene Reduction of Cryptogamic Crusts from a Blackbrush Community as Related to Resaturation/Dehydration." *Soil Biology and Biochemistry*.

- Jeffries, D. L., S. O. Link, and J. M. Klopatek. (In press.) "CO₂ Fluxes of Cryptogamic Crusts. I. Response to Resaturation." *New Phytologist*.
- Jeffries, D. L., S. O. Link, and J. M. Klopatek. (In press.) "CO₂ Fluxes of Cryptogamic Crusts. II. Response to Dehydration." *New Phytologist*.
- Link, S. O., H. Bolton, Jr., and M. E. Thiede. (Submitted.) "A Microcosm Level Gas Exchange Study on the Effects of Nitrogen and Water on *Bromus tectorum* L." *Journal of Range Management*.
- Link, S. O., D. E. Gibbons, G. M. Petrie, R. R. Kirkham, L. E. Rogers, and P. A. Beedlow. (Submitted.) "Estimation of Latent Heat Flux Using Quantitative Landsat Thematic Mapper Satellite Data in a Shrub-Steppe Ecosystem." *Journal of Arid Environments*.
- Link, S. O., W. J. Waugh, J. L. Downs, J. C. Chatters, M. E. Thiede, P. B. Test, L. C. Cadwell, and G. W. Gee. (Submitted.) "The Effect of Surface Topography and Associated Vegetation and Soil Characteristics on Soil Water Dynamics in a Shrub Dominated Arid Ecosystem." *Journal of Arid Soils Research and Rehabilitation*.
- O'Neill, R. V., S. J. Turner, V. I. Cullinan, D. P. Coffin, T. Cook, W. Conley, J. Brunt, J. M. Thomas, and M. R. Conley. 1991. "Multiple Landscape Scales: An Intersite Comparison." *Landscape Ecology* 5:137-144.
- Poston, T. M., D. C. Klopfer, and M. A. Simmons. 1990. "Short-Term Bioconcentration Studies of Np in Freshwater Biota." *Health Physics* 39(6):869-877.
- Rickard, W. H., and L. E. Eberhardt. 1990. "Strontium-90 in Canada Goose Eggshells: Nonfatal Monitoring for Contamination in Wildlife." In *Environmental Monitoring, Restoration and Assessment: What Have We Learned?*, Proceedings of the 28th Hanford Symposium on Health and the Environment, ed. R. H. Gray, pp. 25-31. Battelle Press, Columbus, Ohio.
- Rickard, W. H., and K. R. Price. 1990. "Strontium-90 in Canada Goose Eggshells and Reed Canary Grass from the Columbia River, Washington." *Environmental Monitoring and Assessment* 14:71-76.
- Rickard, W. H., T. D. Reynolds, and V. S. Byre. (Submitted.) "Energy Facility Sites as Protected Habitats for Wild Birds in Shrub-Steppe and Grassland Ecoregions."
- Rickard, W. H., and C. A. Schuler. 1990. "Mineral Composition of Eggshells of Wild Birds from the Columbia Basin, Washington." *Northwestern Naturalist* 71:5-8.
- Rickard, W. H., and M. A. Simmons. (Submitted.) "Seasonal Variation in Bird Communities Inhabiting Arboreal Habitats in Contrasting Ecoregions."
- Rossi, R. E., D. J. Mulla, A. G. Journel, and E. H. Franz. (In press.) "Geostatistical Tools for Modeling and Interpreting Ecological Spatial Dependence." *Ecological Monographs*.
- Simmons, M. A., V. I. Cullinan, and J. M. Thomas. (In press.) "Satellite Imagery as a Tool to Evaluate Ecological Scale." *Landscape Ecology*.
- Smith, J. L., J. J. Halvorson, and H. Bolton, Jr. (In preparation.) "Measurement and Use of Microbial Biomass Values in Ecological Research."
- Smith, J. L., J. J. Halvorson, and H. Bolton, Jr. (In preparation.) "Spatial Relationships of Microbial Processes in an Arid Shrub-Steppe Ecosystem."
- Soldat, J. K., K. R. Price, and W. H. Rickard. 1990. *Methodology Used to Compute Maximum Potential Doses from Ingestion of Edible Plants and Wildlife Found on the Hanford Site*. PNL-7539, Pacific Northwest Laboratory, Richland, Washington.
- Thiede, M. E., S. O. Link, R. J. Fellows, and P. A. Beedlow. (In press.) "Analysis of an Acute Dose of Gamma Radiation on Stem Diameter Growth, Carbon Gain, and Biomass Partitioning in *Helianthus annuus*." *Experimental and Environmental Botany*.

Van Voris, P., L. E. Rogers, D. E. Gibbons, S. O. Link, and J. M. Thomas. (In press.) "Remote Detection of Changes in Terrestrial Ecosystems." *Society of Environmental Toxicology and Chemistry*.

Laboratory-Directed Research and Development

Arnold, G. E., and R. L. Ornstein. (In preparation.) "T4 Lysozyme Hinge-Bending from a 2 Nano-second Molecular Dynamics Simulation Analysis."

Bass, M. B., D. Filipovic, S. G. Sligar, and R. L. Ornstein. (In preparation.) "Altering the Coupling Between Cytochrome P450cam: A Theoretical Prediction with Experimental Evidence."

Bass, M. B., D. F. Hopkins, W. A. Jaquysh, and R. L. Ornstein. (In press.) "A Method for Determining the Positions of Polar Hydrogens Added to a Protein Structure That Maximizes Protein Hydrogen Bonding." *PROTEINS: Structure, Function, and Genetics*.

Bass, M. B., and R. L. Ornstein. (In preparation.) "Comparison of Cytochrome P-450cam Dynamics with Bound L- and D-Norcamphor."

Bass, M. B., M. D. Paulsen, and R. L. Ornstein. (In press.) "Molecular Dynamics Simulations of Norcamphor-CytochromeP-450cam and Mutations of P-450cam Designed to Alter the Product Specificity." In *Proceedings of the 7th International Conference on Biochemistry and Biophysics of Cytochrome P450: Structure & Function, Biotechnological & Ecological Aspects*, ed. A. I. Archakov, Moscow.

Bass, M. B., M. D. Paulsen, and R. L. Ornstein. (In press.) "Substrate Mobility in a Deeply Buried Active Site: Analysis of Norcamphor Bound to Cytochrome P-450_{cam} as Determined by a 201 psec Molecular Dynamics Simulation." *PROTEINS: Structure, Function, and Genetics*.

Braatz, J. A., M. D. Paulsen, and R. L. Ornstein. (In press.) "3 nsec Molecular Dynamics Simulation of the Protein Ubiquitin and Comparison with X-ray Crystal and Solution NMR Structure." *Journal of Biomolecular Structure and Dynamics*.

Brockman, F. J., and R. L. Ornstein. 1991. "Enhanced Bioremediation of Subsurface Contamination: Enzyme Recruitment and Redesign." In *Hazardous Materials Control/Superfund '91*, Proceedings of the 12th National Conference, pp. 264-266. Hazardous Materials Control Research Institute, Greenbelt, Maryland.

Dunning, T. H., Jr., S. S. Xantheas, A. C. Hess, D. F. Feller, R. A. Kendall, and R. L. Ornstein. 1991. "Modeling Molecular Processes in the Environment." Chapter 6 in *Proceedings of the First Energy Research Power Supercomputer Users Symposium*. CONF-9105202, U.S. Department of Energy, Washington, D.C.

Filipovic, D., M. D. Paulsen, P. J. Loida, S. G. Sligar, and R. L. Ornstein. (Submitted.) "Ethylbenzene Hydroxylation by Cytochrome P450cam."

Filipovic, D., M. D. Paulsen, J. D. Ropp, R. L. Ornstein, and S. G. Sligar. (In preparation.) "Prediction of the Three Dimensional Structure of Cytochrome P450lin Using Homology Modeling and Molecular Dynamics."

Ginn, T. R., and J. H. Cushman. (In press.) "A Continuous-Time Inverse Operator for Groundwater and Contaminant Transport Modeling, II: Model Identifiability." *Water Resources Research*.

Gladstone, B. G., M. B. Bass, and R. L. Ornstein. (In preparation.) "Effect of Crystal Packing Forces on the Structure and Mobility of Proteins."

Gladstone, B. G., and R. L. Ornstein. (In preparation.) "2 Nanosecond Molecular Dynamics Simulation of the Protein Erabutoxin b."

Ornstein, R. L. 1991. "Rational Redesign of Biodegradative Enzymes for Enhanced Bioremediation: Overview and Status Report for Cytochrome P450." In *Proceedings of National Research & Development Conference on the Control of Hazardous Materials*, pp. 314-319. Hazardous Materials Control Research Institute, Greenbelt, Maryland.

Ornstein, R. L. 1991. "Why Timely Bioremediation of Synthetics May Require Rational Enzyme Redesign: Preliminary Report on Redesigning Cytochrome P450cam for Trichloroethylene Dehalogenation." In *On Site Bioreclamation: Processes for Xenobiotic and Hydrocarbon Treatment*, eds. R. E. Hinchee and R. F. Offenbuttel, pp. 509-514. Butterworth-Heinemann, Boston, Massachusetts.

Ornstein, R. L., M. B. Bass, M. D. Paulsen, and G. E. Arnold. 1991. "Rational Redesign of the Biodegradative Enzyme Cytochrome P450cam: A Progress Report on Engineering Specificity for Halogenated Hydrocarbon Substrates." In *Proceedings of HAZMACON 91*, vol. II, ed. T. Bursztynsky, pp. 470-480. JT Litho, Concord, California.

Paulsen, M. D., M. B. Bass, and R. L. Ornstein. 1991. "Analysis of Active Site Motions from a 175 psec Molecular Dynamics Simulation of Camphor-Bound Cytochrome P450cam." *Journal of Biomolecular Structure & Dynamics* 9:187-205.

Paulsen, M. D., and R. L. Ornstein. 1991. "A 175 psec Molecular Dynamics Simulation of Camphor-Bound Cytochrome P450_{cam}." *PROTEINS: Structure, Function, and Genetics* 11:184-204.

Paulsen, M. D., and R. L. Ornstein. (Submitted.) "Molecular Dynamics Simulation of Substrate-Free Cytochrome P-450cam and Comparison with Camphor-Bound Simulation."

Paulsen, M. D., and R. L. Ornstein. (In preparation.) "Molecular Dynamics Simulations of Camphor-Bound Cytochrome P450cam with Active Site Mutation Tyr 96 -> Phe."

Paulsen, M. D., and R. L. Ornstein. (In preparation.) "Predicting Product Specificity and Coupling for Catalysis by Cytochrome P450cam."

Paulsen, M. D., and R. L. Ornstein. (In preparation.) "Why X-ray Crystal Structure of Thiocamphor-Bound Cytochrome P450cam is Inconsistent with Observed Product Specificity: An Explanation Based on Molecular Dynamics Simulations."

Sokalski, W. A., J. Lai, N. Luo, S. Sun, M. Shibata, R. L. Ornstein, and R. Rein. (In press.) "Ab Initio Study of the Electrostatic Multipole Nature of Torsional Potentials: Hydrogen Peroxide and Methyl Disulfide (CH₃SSCH₃).²" *International Journal of Quantum Chemistry*.

Sokalski, W. A., M. Shibata, R. L. Ornstein, and R. Rein. (Submitted.) "Correcting Deficiencies of Atomic Charges Using the Cumulative Atomic Multipole Approach."

Sokalski, W. A., M. Shibata, R. L. Ornstein, and R. Rein. (Submitted.) "Point Charge Representation of Multicenter Multipole Moments in Calculation of Electrostatic Properties."

Sun, S., N. Luo, R. L. Ornstein, and R. Rein. (In preparation.) "Protein Secondary and Tertiary Structure Prediction by a Reduced Representation Method: Test Case for Seven Small Proteins."

Sun, S., N. Luo, R. L. Ornstein, and R. Rein. (Submitted.) "Protein Structure Prediction: Reduced Representation Approach."

Thomson, L. A., J. A. Braatz, and R. L. Ornstein. (In preparation.) "Comparison of Molecular Dynamics Simulations for the Protein Ubiquitin with and without an Explicit 7 Å Shell of Water."

Presentations

Subsurface Science

Ainsworth, C. C., J. M. Zachara, and C. E. Cowan. 1990. "Sorption of N-Containing Aromatic Compounds to Silica." Presented at the 1990 Annual Meetings of the Soil Science Society of America, October 21-26, 1990, San Antonio, Texas.

Ainsworth, C. C., J. M. Zachara, and S. C. Smith. 1990. "The Effect of Sorption on Degradation of Quinoline and Salicylate." Presented at the Fall Meeting of the American Geophysical Union, December 3-7, 1990, San Francisco, California.

Bjornstad, B. N., F. J. Brockman, T. L. Kieft, and P. E. Long. 1990. "Subsurface Microbial Distribution in the Vadose Zone, Hanford Site, South-Central Washington." Presented at the Fall Meeting of the American Geophysical Union, December 3-7, 1990, San Francisco, California.

Bolton, H., Jr. 1991. "Bioaccumulation of Radionuclides and Metals by Microorganisms: Potential Role in the Separation of Inorganic Contaminants and for the In Situ Treatment of the Subsurface." Presented at the First Hanford Separations Science Workshop, July 25, 1991, Richland, Washington.

Bolton, H., Jr. 1991. "Chemical/Microbiological Factors Controlling the Subsurface Transport of Chelated Radionuclides." Presented at the Biodegradation/Microbial Physiology Subprogram Meeting of the Subsurface Science Program, January 22, 1991, Gaithersburg, Maryland.

Bolton, H., Jr. 1991. "Effect of Chemical Speciation on the Degradation of Nitrotriacetic Acid by a *Pseudomonas* sp." Presented at the American Society for Microbiology Annual Meetings, May 7, 1991, Dallas, Texas.

Bolton, H., Jr. 1991. "Influence of Aqueous Speciation and Adsorption on the Degradation of Synthetic Chelates." Presented at the U.S. Department of Energy Review of the Subsurface Science Program, April 23, 1991, Salt Lake City, Utah.

Brockman, F. J. 1991. "Expression of Cloned Biodegradative Genes in Isolates from Deep Subsurface Environments." Presented at the Fourth Chemical Congress of North America, Biochemical Technology session, August 1991, New York.

Brockman, F. J., T. L. Kieft, J. K. Fredrickson, B. N. Bjornstad, and P. E. Long. 1991. "Moisture Recharge and Organic Carbon as Factors Controlling Vadose Zone Microbial Communities at the Hanford Site." Presented at the Northwest Regional Meeting of the American Geophysical Union.

Brockman, F. J., T. L. Kieft, W. Spangenburg, S. Li, and D. Workman. 1991. "Microbiological Characterization of Vadose Zone Sediments at the Hanford Site in South-Central Washington State." Presented at the 91st Meeting of the American Society of Microbiologists, Dallas, Texas.

Cary, J. W., G. W. Gee, and G. A. Whyatt. 1990. "Waste Storage in the Vadose Zone Affected by Water Vapor Condensation and Leaching." Presented at the International Symposium on the Scientific Basis for Nuclear Waste Management, November 1990, Boston, Massachusetts.

Fredrickson, J. K. 1991. "Microorganisms in Deep Cretaceous Sediments of the Atlantic Coastal Plain: Vertical Variations in the Middendorf and Cape Fear Formations." Presented at an invited seminar at the University of Arizona, Tucson, Arizona.

Fredrickson, J. K., F. Brockman, S. Li, T. Stevens, C. Spadoni, and D. Workman. 1991. "Metabolism of Naphthalene, Toluene, and Isomers of Xylene by the Subsurface Bacterium F199." Presented at the 91st Meeting of the American Society of Microbiologists, Dallas, Texas.

Girvin, D. C. 1991. "Adsorption of Aqueous ^{60}Co -EDTA by $\gamma\text{-Al}_2\text{O}_3$: Effect of Oxidation State and Ionic Strength." Presented at the Soil Science Society of America Annual Meeting, October 31, 1991, Denver, Colorado.

Girvin, D. C. 1991. "Chelated Radionuclide Adsorption-Desorption: Interfacial Reactions with Subsurface Materials." Presented at the U.S. Department of Energy Review of the Subsurface Science Program, April 23, 1991, Salt Lake City, Utah.

Holford, D. J., P. C. Owczarski, G. W. Gee, and H. D. Freeman. 1990. "Radon Transport from the Subsurface: The Roles of Certain Boundary Conditions at Subsurface/Environment Boundaries." Presented at the 29th Hanford Symposium on Health and the Environment, October 15-19, 1990, Richland, Washington.

Li, S. W., J. K. Fredrickson, W. Spangenburg, D. J. Workman, F. J. Brockman, T. O. Stevens, and P. E. Long. 1991. "Microbial Activities of Two Dedicated Deep Subsurface Boreholes." Presented at the 91st Meeting of the American Society of Microbiologists, Dallas, Texas.

Long, P. E., S. A. Rawson, D. L. Balkwill, J. K. Fredrickson, and F. J. Wobber. 1990. "Progress of Sample Acquisition for the Deep Microbiology Transitional Program, U.S. Department of Energy." Presented at the Fall Meeting of the American Geophysical Union, December 3-7, 1990, San Francisco, California.

Murphy, E. M., J. K. Fredrickson, D. S. Sklarew, and J. C. Linehan. 1990. "The Assessment of Microbial Origin, Diversity, and Activity in the Middendorf Aquifer Using Isotopic Geochemistry of the Sedimentary Organic Carbon and Groundwater." Presented at the Fall Meeting of the American Geophysical Union, December 3-7, 1990, San Francisco, California.

Stevens, T. O., and J. K. Fredrickson. 1991. "Bacteria Associated with Deep, Alkaline, Anaerobic Groundwaters in SE Washington." Presented at the 91st Meeting of the American Society of Microbiologists, Dallas, Texas.

Szecsody, J. E., G. P. Streile, and W. J. Pavalko. 1990. "Sorption and Transformation of Aminonaphthalene on Clay." Presented at the American Geophysical Union Fall Meeting, December 3-7, 1990, San Francisco, California.

Szecsody, J. E., and B. D. Wood. 1991. "Processes Affecting Biodegradation in a Layered Flow System." Presented at the Pacific Northwest American Geophysical Union Meeting, September 17-20, 1991, Richland, Washington.

Wood, B. D., J. E. Szecsody, and C. N. Dawson. 1991. "Predictive Modeling of Solute Transport with Biodegradation in Layered 2-Dimensional System." Presented at the Pacific Northwest American Geophysical Union Meeting, September 17-20, 1991, Richland, Washington.

Zachara, J. M., and C. C. Ainsworth. 1990. "Effect of Sorption on the Abiotic and Microbiologic Transformation of Organic Compound in Subsurface Materials." Presented at the Fall Meeting of the American Geophysical Union, December 3-7, 1990, San Francisco, California.

Terrestrial Science

Bolton, H., Jr. 1991. "Arid Biogeochemical Processes: N Cycling." Presented at the U.S. Department of Energy Review of the Terrestrial Ecology Program, June 12, 1991, Las Vegas, Nevada.

Bolton, H., Jr. 1991. "The Influence of Vegetation on Soil Resource Distribution in a Shrub-Steppe Ecosystem." Presented to the Crops and Soils Department, Washington State University, November 8, 1991, Pullman, Washington.

Gee, G. W., M. D. Campbell, and S. O. Link. 1991. "Arid Site Water Balance Using Monolith Lysimeters." Presented at the ASCE International Symposium on Lysimetry, July 22-26, 1991, Honolulu, Hawaii.

Link, S. O. 1991. "Dynamics of Arid Lands: Landscape Level Studies." Presented at the U.S. Department of Energy Review of the Terrestrial Ecology Program, June 12, 1991, Las Vegas, Nevada.

Link, S. O. 1991. "Dynamics of Arid Lands: Plant Process Studies." Presented at the U.S. Department of Energy Review of the Terrestrial Ecology Program, June 12, 1991, Las Vegas, Nevada.

Link, S. O., D. E. Gibbons, G. M. Petrie, R. R. Kirkham, L. E. Rogers, and P. A. Beedlow. 1991. "Estimation of Latent Heat Flux Using Quantitative Landsat Thematic Mapper Satellite Data in a Shrub-Steppe Ecosystem." Presented at a meeting of the Ecological Society of America, August 4-9, 1991, San Antonio, Texas.

Thomas, J. M. 1990. "Methods for Siting Groundwater Monitoring Wells." Presented at the U.S. Department of Energy's Low-Level Waste Workshop, December 13, 1990, Las Vegas, Nevada.

Thomas, J. M. 1990. "Scale-Up from Leaf to Landscape Level Processes." Presented at the National Science Foundation Symposium, December 2, 1990, Snowbird, Utah.

Thomas, J. M. 1991. "Variability in Ecological Systems." Presented at the U.S. Department of Energy's Office of Health and Environmental Research Workshop, August 14, 1991, Idaho Falls, Idaho.

Thomas, J. M., and L. L. Eberhardt. 1991. "Designs for Environmental Field Studies." Presented at the U.S. Department of Energy's Theoretical Ecology Meeting on Progress and Prospects, April 30, 1991, Gaithersburg, Maryland.

Van Voris, P., L. E. Rogers, D. E. Gibbons, S. O. Link, and J. M. Thomas. 1990. "Remote Detection of Changes in Terrestrial Ecosystems." Presented at the Annual Meeting of the Society of Environmental Toxicology and Chemistry, November 12-15, 1990, Arlington, Virginia.

Waugh, W. J., B. H. Werle, and S. O. Link. 1991. "Plant Water Relations in Small Monolith Lysimeters." Presented at a meeting of the Soil Science Society, October 27 - November 1, 1991, Denver, Colorado.

Laboratory-Directed Research and Development

Arnold, G. E., and R. L. Ornstein. 1991. "A Molecular Dynamics Analysis of T4 Lysozyme." Presented at the Fifth Annual Symposium of the Protein Society, June 1991, Baltimore, Maryland.

Arnold, G. E., and R. L. Ornstein. 1991. "Molecular Dynamics Simulations of T4 Lysozyme." Presented at the UCLA Keystone Conference on Protein Folding, Structure and Function, April 1991, Keystone, Colorado.

Bass, M. B., and R. L. Ornstein. 1991. "Molecular Basis of Substrate Specificity for Cytochrome P-450cam by Molecular Dynamics Simulations." Presented at the International Symposium on Cytochrome P-450 of Microorganisms, July 1991, Berlin.

Bass, M. B., and R. L. Ornstein. 1991. "Mutations Designed to Affect the Product Specificity of Cytochrome P450cam as Studied by Molecular Dynamics Simulations." Presented at the Regional American Chemical Society Meeting: Molecular Design & Modeling, Indiana University—Purdue University at Indianapolis, May 1991, Indianapolis, Indiana.

Bass, M. B., M. D. Paulsen, and R. L. Ornstein. 1991. "Molecular Dynamics Simulations of Norcamphor-Cytochrome P-450cam and Mutations of P-450cam Designed to Alter the Product Specificity." Presented at the 7th International Conference on Biochemistry and Biophysics of Cytochrome P450: Structure & Function, Biotechnological & Ecological Aspects, July/August 1991, Moscow.

Douthart, R. D. 1991. "Computer Graphics as a Tool in Understanding Genomic Structures." Presented at the workshop: Computer-Based Analysis of Nucleic Acids and Protein Sequences, University of Washington Medical Center, January 19, 1991, Seattle, Washington.

Douthart, R. D. 1991. "Computer Visualization of Large Genomic Structures." Presented at BBN, Inc., March 4, 1991, Cambridge, Massachusetts.

Douthart, R. D. 1991. "Metacodes in DNA and Protein Sequence." Presented at the Telluride Workshop on Open Problems of Computational Molecular Biology, June 2-8, 1991, Telluride, Colorado.

- Filipovic, D., P. J. Loida, S. G. Silgar, M. D. Paulsen, M. B. Bass, and R. L. Ornstein. 1991. "Approaches to the Rational Design of the Cytochrome P450cam Active Site." Presented at the President's Meeting of the International Society of Quantum Biology and Pharmacology, Stanford University, September 1991, Palo Alto, California.
- Gladstone, B. G., and R. L. Ornstein. 1991. "Molecular Dynamics Simulation of Erabutoxin B." Presented at the Fifth Annual Symposium of the Protein Society, June 1991, Baltimore, Maryland.
- Ornstein, R. L. 1991. "Enhancing Biodehalogenation by Redesigning Cytochrome P450cam Specificity." Presented at HAZMACON '91: Hazardous Materials Technical Conference, April 1991, Santa Clara, California.
- Ornstein, R. L. 1991. "Environmental Remediation: Current & Future Role of Biological Sciences." Presented at the HBCU/MI Curriculum Development Workshop, Jackson State University, June 1991, Jackson, Mississippi.
- Ornstein, R. L. 1991. "Molecular Dynamics Simulations of Proteins: Validation Studies & Cytochrome P-450cam Regiospecificity and Active Site Dynamics." Presented to the Department of Chemistry, Pennsylvania State University, February 1991, University Park, Pennsylvania.
- Ornstein, R. L. 1991. "Molecular Dynamics Simulations of Proteins: Validation Studies & Cytochrome P-450cam Regiospecificity and Active Site Dynamics." Presented to the Department of Pharmaceutical Chemistry, University of California—San Francisco, April 1991, San Francisco, California.
- Ornstein, R. L. 1991. "Molecular Modeling & Simulation Studies to Redesign the Substrate Specificity of Biodegradative Enzymes to Enhance Remediation of DOE-Site Contaminants." Presented at the National Research & Development Conference on the Control of Hazardous Materials, February 1991, Anaheim, California.
- Ornstein, R. L., M. B. Bass, M. D. Paulsen, and G. E. Arnold. 1991. "Rational Redesign of Substrate Specificity for the Biodegradative Enzyme Cytochrome P-450_{cam}." Presented at In Situ and On-Site Bioreclamation: An International Symposium, March 1991, San Diego, California.
- Ornstein, R. L., and J. A. Braatz. 1991. "3 Nanosecond Molecular Dynamics Simulation of the Protein Ubiquitin." Presented at the 7th Conversation in the Discipline Biomolecular Stereodynamics, State University of New York—Albany, June 1991, Albany, New York.
- Ornstein, R. L., and F. J. Brockman. 1991. "Enhanced Bioremediation of Subsurface Contamination: Enzyme Recruitment and Redesign." Presented at the Hazardous Materials Control Research Institute 12th Annual National Conference: Hazardous Materials Control/Superfund '91, December 1991, Washington, D.C.
- Ornstein, R. L., M. D. Paulsen, and M. B. Bass. 1990. "Molecular Dynamics Simulations: Validation Studies and Simulations of Cytochrome P450cam." Presented at the University of Oregon, Institute of Molecular Biology & Institute of Materials, October 1990, Eugene, Oregon.
- Ornstein, R. L., M. D. Paulsen, and M. B. Bass. 1991. "Biodegradation of Halogenated Hydrocarbons by Rational Redesign of Cytochrome P450cam." Presented to the American Chemical Society Division of Biochemical Technology: Biodegradation of Organic Wastes: Molecular Approaches & Field Applications, August 1991, New York.
- Ornstein, R. L., M. D. Paulsen, M. B. Bass, G. E. Arnold, J. A. Braatz, and B. G. Gladstone. 1991. "Molecular Dynamics Simulations of Proteins: Validation Studies & Cytochrome P-450cam Regiospecificity and Active Site Dynamics." Presented at the 46th Northwest Regional Meeting of the American Chemical Society, Eastern Oregon State College, June 1991, La Grande, Oregon.

Paulsen, M. D., M. B. Bass, G. E. Arnold, and R. L. Ornstein. 1991. "Active Site Dynamics and Regio-specificity of Cytochrome P450cam as Determined by Molecular Dynamics Simulations." Presented at the 35th Annual Biophysical Society Conference, February 1991, San Francisco, California.

Paulsen, M. D., M. B. Bass, and R. L. Ornstein. 1991. "Active Site Dynamics and Regiospecificity of Cytochrome P450cam as Determined by Molecular Dynamics Simulations." Presented at the President's Meeting of the International Society of Quantum Biology and Pharmacology, Stanford University, September 1991, Palo Alto, California.

Sokalski, A., M. Shibata, R. L. Ornstein, and R. Rein. 1991. "*Ab Initio* Study of the Electrostatic Multipole Nature of Torsional Potentials: Hydrogen Peroxide and Methyl Disulfide (CH_3SSCH_3)." Presented at the 35th Sanibel Symposia, March 1991, St. Augustine, Florida.

Author Index

Author Index

Ainsworth, C. C., 1, 13, 143
Amonette, J. E., 88
Bjornstad, B. N., 49
Black, G. D., 88
Bolton, H., Jr., 18, 42, 117,
122, 143
Brockman, F. J., 28, 46, 75
Cadwell, L. L., 127
Cary, J. W., 111
Cole, C. R., 88, 149
Cullinan, V. I., 136
Douthart, R. J., 148
Downs, J. L., 122, 133
Eary, L. E., 88
Eberhardt, L. L., 136
Fredrickson, J. K., 28, 88
Freeman, H. D., 106
Fruchter, J. S., 88

Gee, G. W., 106, 127
Gibbons, D. E., 133
Ginn, T. R., 149
Girvin, D. C., 18
Gorby, Y. A., 143
Holford, D. J., 88, 106
Kirkham, R. R., 128
Lenhard, R. J., 111
Link, S. O., 117, 122, 128,
133
Long, P. E., 49
McBride, J. F., 111
McKinley, J. P., 1, 71
McWethy, L. G., 128, 133
Murphy, E. M., 1, 49
Ornstein, R. L., 145
Owczarski, P. C., 106
Parks, V. D., 127

Petrie, G. M., 128, 133
Rao, P.S.C., 1
Rawson, S. A., 49
Rickard, W. H., 139
Rogers, L. E., 128
Romine, M. F., 46
Simmons, C. S., 111
Simmons, M. A., 136
Stevens, T. O., 28, 88
Streile, G. P., 75
Szecsody, J. E., 75
Thiede, M. E., 122
Thomas, J. M., 136
Vermeul, V. R., 88
Westall, J. C., 1
Wood, B. D., 75
Zachara, J. M., 1, 88

Distribution

Distribution

PNL-8000 Pt. 2
UC-407

OFFSITE

W. R. Albers
EH-12, GTN
Department of Energy
Washington, DC 20545

D. Anderson
ENVIROTEST
1108 NE 200th Street
Seattle, WA 98155-1136

Assistant Secretary
Environment, Safety
& Health
EH-1, FORS
Department of Energy
Washington, DC 20585

S. I. Auerbach
Oak Ridge National Laboratory
Building 1505, MS-6036
P.O. Box 2008
Oak Ridge, TN 37831-6036

J. A. Auxier
IT Corporation
312 Directors Drive
Knoxville, TN 37923

F. Badgley
13749 NE 41st Street
Seattle, WA 98125

D. L. Balkwill
Department of Biological
Sciences
309 Nuclear Research Bldg.
Florida State University
Tallahassee, FL 32306

R. M. Baltzo
Radiological Safety Division
University of Washington
Seattle, WA 98105

R. W. Barber
EH-131, GTN
Department of Energy
Washington, DC 20545

A. D. Barker
Battelle Columbus Laboratories
505 King Avenue
Columbus, OH 43201

J. R. Barker
Office of Environmental
Audit and Compliance
Department of Energy
Washington, DC 20545

W. W. Barker, Chairman
Department of Biology
Central Washington University
Ellensburg, WA 98926

N. F. Barr
EM-40, GTN
Department of Energy
Washington, DC 20545

J. E. Baublitz
EM-40, GTN
Department of Energy
Germantown, MD 20545

J. R. Beall
ER-72, GTN
Department of Energy
Washington, DC 20545

P. A. Beedlow
U. S. Environmental
Protection Agency
200 SW 35th Street
Corvallis, OR 97333

M. H. Bhattacharyya
BIM Division, Bldg. 202
Argonne National Laboratory
9700 South Cass Avenue
Argonne, IL 60439

R. A. Black
Department of Botany
Washington State University
Pullman, WA 99164

L. Bliss
Department of Botany
University of Washington
Seattle, WA 98105

H. S. Bolton
National Oceanic &
Atmospheric Administration
HG Hoover Building,
Room 5222
Department of Commerce
LAX 1
Washington, DC 20230

T. Borak
Colorado State University
Dept. of Radiation &
Radiation Biology
Fort Collins, CO 80523

C. M. Borgstrom
EH-25, FORS
Department of Energy
Washington, DC 20585

L. C. Brazley, Jr.
NE-22, GTN
Department of Energy
Washington, DC 20545

A. Brodsky
16412 Kipling Road
Derwood, MD 20855

W. Broecker
Lamont Geological
Observatory
Columbia University
Palisades, NY 10964

D. R. Buhler, Chairman
Toxicology Program
Oregon State University
Corvallis, OR 97331

G. Burley
Office of Radiation Programs,
ANR-458
Environmental Protection
Agency
Washington, DC 20460

L. K. Bustad
College of Veterinary Medicine
Washington State University
Pullman, WA 99164-7010

S. Calcese
Water Resources Center
University of Wisconsin
1975 Willow Drive
Madison, WI 53706

M. Caldwell
Department of Range Science
Utah State University
Logan, UT 84322

J. T. Callahan
Associate Program Director
Ecosystems Studies Program
National Science Foundation
Washington, DC 20545

R. J. Catlin, President
Robert J. Catlin Corporation
701 Welch Road, Suite 1119
Palo Alto, CA 94304

H. H. Cheng, Head
Department of Soil Science
University of Minnesota
1991 Upper Buford Circle
St. Paul, MN 55108

G. Chesters, Director
Water Resources Center
University of Wisconsin
1975 Willow Drive
Madison, WI 53706

Chief
Game Management Division
Department of Game
600 North Capitol Way
Olympia, WA 98501

J. S. Coleman
ER-15, GTN
Department of Energy
Washington, DC 20545

W. Conley
ER-75, GTN
Department of Energy
Washington, DC 20545

J. Corey
Environmental Sciences
Savannah River Laboratory
Drawer E
Aiken, SC 29801

Council on Environmental
Quality
722 Jackson Place, NW
Washington, DC 20503

R. Crawford, Director
IMAGE
University of Idaho
Moscow, ID 83843

T. V. Crawford
Atomic Energy Division
Savannah River Laboratory
E. I. duPont de Nemours
& Company
Aiken, SC 29808

J. H. Cushman
Water Resources Research
Center
Purdue University
Lilly Hall
West Lafayette, IN 47907

G. Davis, Chairman
Medical & Health Sciences
Division
Oak Ridge Associated
Universities
P.O. Box 117
Oak Ridge, TN 37831-0117

J. T. Davis
San Francisco Operations
Office
Department of Energy
1333 Broadway
Oakland, CA 94612

J. F. Decker
ER-1, FORS
Department of Energy
Washington, DC 20585

R. S. Denning
Battelle Columbus
Laboratories
5050 King Avenue
Columbus, OH 43201

Department of Energy
Environment & Health
Division
P.O. Box 5400
Albuquerque, NM 87115

G. DePlanque, Director
Department of Energy-EMEL
375 Hudson Street
New York, NY 10014

Director
New England Marine
Laboratories
Washington Street
P.O. Box 1637
Duxbury, MA 02332

Director
Washington State
Department of Ecology
Olympia, WA 98501

K. R. Dixon
Washington Department
of Wildlife
600 North Capital Way
Olympia, WA 98504

T. J. Dobry, Jr.
DP-221, GTN
Department of Energy
Washington, DC 20545

DOE/Office of Scientific &
Technical Information (12)

H. Drucker
Argonne National Laboratory
9700 South Cass Avenue
Argonne, IL 60439

A. P. Duhamel
ER-74, GTN
Department of Energy
Washington, DC 20545

S. Echols
U.S. Environmental Protection
Agency
Pacific Ecosystems Branch,
ERL-N
Hatfield Marine Science Center
2111 S.E. Marine Science Drive
Newport, OR 97365-5260

D. N. Edgington
University of Wisconsin
Center for Great Lakes Studies
P.O. Box 413
Milwaukee, WI 53201

C. W. Edgington, Director
National Research Council
2101 Constitution Avenue, NW
Washington, DC 20418

W. H. Ellett
BRER--National Research
Council, MH-370
2101 Constitution Avenue, NW
Washington, DC 20418

L. E. Elliott
U.S. Cotton Research Station
USDA-ARS
17053 Shafter Avenue
Shafter, CA 93263

R. D. Evans
Department of Botany
Washington State University
Pullman, WA 99164

S. J. Farmer
17217 77th Avenue W.
Edmonds, WA 98020

B. H. Fimiani
Battelle, Pacific Northwest
Laboratories
Washington Operations
901 D Street, SW, Suite 900
Washington, DC 20024

W. O. Forster
ER/OHER/ERD
Department of Energy
Washington, DC 20545

Arnold Gahler
Environmental Protection
Agency
Region X Laboratory
P.O. Box 549
Manchester, WA 98353

D. J. Galas
ER-70, GTN
Department of Energy
Washington, DC 20545

C. George
DP-12, GTN
Department of Energy
Germantown, MD 20545

T. F. Gesell
Idaho Operations Office
Department of Energy
785 DOE Place
Idaho Falls, ID 83402-4149

W. C. Ghiorse
Microbiology Department
415 Stocking Hall
Cornell University
Ithaca, NY 14853

R. D. Gilmore, President
Environmental Health
Sciences, Inc.
Nine Lake Bellevue Building
Suite 220
Bellevue, WA 98005

T. Ginn
21820 Meridian Ave. SW
Bothell, WA 98021

E. D. Goldberg
Scripps Institute of
Oceanography
La Jolla, CA 92039

M. Goldman
Department of Radiological
Sciences (VM)
University of California
Davis, CA 95616

G. Goldstein
ER-74, GTN
Department of Energy
Washington, DC 20545

F. B. Golley
Institute of Ecology
University of Georgia
Athens, GA 30601

D. J. Grimes
ER-74, GTN
Department of Energy
Washington, DC 20545

K. Grossman
P.O. Box 1680
Sag Harbor, NY 11963

J. D. Hair
National Wildlife Federation
1400 16th Street, NW
Washington, DC 20036

D. H. Hamilton, Jr.
ER-72, GTN
Department of Energy
Washington, DC 20545

W. R. Hansen
MS-F643
Los Alamos National
Laboratory
P.O. Box 1663
Los Alamos, NM 87545

W. Happer
ER-1, FORS
Department of Energy
Washington, DC 20585

F. Harrison
Biomedical & Environmental
Research Program
Lawrence Livermore National
Laboratory, C-523
University of California
P.O. Box 808
Livermore, CA 94550

D. W. Hayne
Department of Statistics
North Carolina State
University
Box 8203
Raleigh, NC 27695-8203

F. Hutchinson
Department of Molecular
Biophysics & Biochemistry
Yale University
260 Whitney Avenue
P.O. Box 6666
New Haven, CT 06511

H. Ishikawa, General Manager
Nuclear Safety Research
Association
P.O. Box 1307
Falls Church, VA 22041

K. L. Jackson, Chairman
Radiological Sciences
Group SB-75
University of Washington
Seattle, WA 98195

A. Janetos
Environmental Protection
Agency
401 M Street, SW
Washington, DC 20460

A. W. Johnson
Vice President for
Academic Affairs
San Diego State University
San Diego, CA 92182

L. J. Johnson
Idaho National Engineering
Laboratory
IRC MS 2203
P.O. Box 1625
Idaho Falls, ID 83415

R. Johnson
Office of Radiation
Programs (ANR-460c)
Environmental Protection
Agency
401 M Street, SW
Washington, DC 20460

D. Johnstone
Department of Civil and
Environmental Engineering
Washington State University
Pullman, WA 99164

G. Y. Jordy, Director
ER-30, GTN
Department of Energy
Washington, DC 20545

C. K. Keller
Department of Geology
Washington State University
Pullman, WA 99164-2812

B. J. Kelman
Failure Analysis Associates,
Inc.
P.O. Box 3015
Menlo Park, CA 94025

R. F. Kendall
National Institute for Petroleum
& Energy Research
P.O. Box 2128
Bartlesville, OK 74005

H. Kibby
Environmental Protection
Agency
200 SW 35th Street
Corvallis, OR 97333

J. Klopatek
Department of Botany
Arizona State University
Tempe, AZ 85287

M. Kosorok
Department of Statistics
Brigham Young University
Provo, UT 84602

R. T. Kratzke
NP-40, GTN
Department of Energy
Washington, DC 20545

D. Krenz
DOE-Albuquerque Operations
Office
P.O. Box 5400
Albuquerque, NM 87115

S. V. Krupa
Dept. Plant Pathology
495 Borlaug Hall
1991 Upper Buford
University of Minnesota
St. Paul, MN 55108

R. T. Lackey
Environmental Protection
Agency
200 SW 35th Street
Corvallis, OR 97333

Librarian
Brookhaven National
Laboratory
Research Library, Reference
Upton,
Long Island, NY 11973

Librarian
Colorado State University
Documents Department--The
Libraries
Ft. Collins, CO 80523

Librarian
Department of Fisheries/
Oceanography
151 Oceanography
Teaching Building
University of Washington
Seattle, WA 98195

Librarian
Electric Power Research
Institute
3412 Hillview Avenue
P.O. Box 10412
Palo Alto, CA 94303

Librarian
Environmental Research
Laboratory
Environmental Protection
Agency, ORD
200 SW 35th Street
Corvallis, OR 97333

Librarian
Environmental Research
Laboratory
Environmental Protection
Agency
Sabine Island
Gulf Breeze, FL 32561

Librarian
Environmental Research
Laboratory
Environmental Protection
Agency, ORD
Narragansett, RI 02882

Librarian
Environmental Research
Laboratory-Duluth
N. A. Jaworski, Director
6201 Congdon Blvd.
Duluth, MN 55804

Librarian
Frances Penrose Owen
Science & Engineering
Library
Washington State University
Pullman, WA 99164-3200

Librarian
Health Sciences Library,
SB-55
University of Washington
Seattle, WA 98195

Librarian
Los Alamos National
Laboratory
Report Library, MS P364
P.O. Box 1663
Los Alamos, NM 87545

Librarian
Northwest and Alaska
Fisheries Center
National Marine Fisheries
Service, NOAA
2725 Montlake Blvd., East
Seattle, WA 98112

Librarian
Robert S. Kerr Environmental
Research Laboratory
Environmental Protection
Agency, ORD
Ada, OK 74320

Librarian
Southeast Fisheries Center
National Marine Fisheries
Services, NOAA
75 Virginian Beach Drive
Miami, FL 33149

Librarian (Serials Section)
University of Washington
Seattle, WA 98195

Librarian
Washington State University
Pullman, WA 99164-6510

Library
Holcomb Research Institute
Butler University
Indianapolis, IN 46208

Library
Serials Department
(#80-170187)
University of Chicago
1100 East 57th Street
Chicago, IL 60637

O. R. Lunt
Laboratory of Biomedical
& Environmental Sciences
University of California
900 Veteran Avenue
Los Angeles, CA 90024-1786

J. N. Maddox
ER-73, GTN
Department of Energy
Washington, DC 20545

J. R. Maher
ER-65, GTN
Department of Energy
Washington, DC 20545

C. R. Mandelbaum
ER-32, GTN
Department of Energy
Washington, DC 20545

J. Mangeno
Department of the Navy
Nuclear Propulsion
Directorate
0808 National Center ND2,
3rd Floor Mail Room
Washington, DC 20362-5101

B. Manowitz
Energy and Environment
Division
Brookhaven National
Laboratory
Upton,
Long Island, NY 11973

R. S. Marianelli
ER-14, GTN
Department of Energy
Washington, DC 20545

O. D. Markham
Radiological and
Environmental Sciences
Laboratory
Department of Energy
785 DOE Place
Idaho Falls, ID 83402

S. Marks
8024 47th Place West
Mukilteo, WA 98275

K. Marsh
Lawrence Livermore
National Laboratory
P.O. Box 808
Livermore, CA 94550

W. H. Matchett
Graduate School
New Mexico State University
Box 3G
Las Cruces, NM 88003-0001

H. M. McCammon
ER-75, GTN
Department of Energy
Washington, DC 20545

R. O. McClellan, President
Chemical Industry Institute
of Toxicology
P.O. Box 12137
Research Triangle
Park, NC 27709

C. B. Meinhold
Radiological Sciences Division
Bldg. 703M
Brookhaven National
Laboratory
Upton, Long Island, NY 11973

M. L. Mendelsohn
Biomedical and Environmental
Research Program
Lawrence Livermore National
Laboratory, L-452
University of California
P.O. Box 5507
Livermore, CA 94550

F. M. Molz
Department of Civil
Engineering
Auburn University
238 Harbert Engineering
Center
Auburn, AL 36849

D. B. Moore-Shedrow
Section Manager
Environmental Sciences, SRL
Westinghouse Savannah
River Company
Aiken, SC 29803

J. J. Morgan
California Institute of
Technology
Mail Code 138-78
Pasadena, CA 91125

W. F. Mueller
New Mexico State University
Box 4500
Las Cruces, NM 88003-4500

I. Murarka
Electric Power Research
Institute
3412 Hillview Avenue
P.O. Box 10412
Palo Alto, CA 94304

T. Murphy, Director
Environmental Research
Laboratory
Environmental Protection
Agency
200 SW 35th Street
Corvallis, OR 97333

J. R. Naidu
Safety and Environmental
Protection Division
Brookhaven National
Laboratory
Building 535-A
Upton, Long Island, NY 11973

T. Nash III
Department of Botany
Arizona State University
Tempe, AZ 85287

N. S. Nelson
Office of Radiation Programs
(ANR-461)
Environmental Protection
Agency
401 M Street, SW
Washington, DC 20460

J. M. Nenhold
Department of Wildlife
Resources
Utah State University
Logan, UT 84322-5200

W. R. Ney, Executive Director
National Council on Radiation
Protection and Measurements
7910 Woodmont Avenue
Suite 1016
Washington, DC 20014

C. R. Nichols
Idaho Operations Office
Department of Energy
785 DOE Place
Idaho Falls, ID 83404

Nuclear Regulatory
Commission
Advisory Committee on
Reactor Safeguards
Washington, DC 20555

E. O'Donnell
Mail Stop NLS-260
Nuclear Regulatory
Commission
Washington, DC 20555

P. C. Owczarski
Science Applications
International Corp.
1845 Terminal Drive
Richland, WA 99352

R. E. Pacha
Department of Biological
Sciences
Central Washington University
Ellensburg, WA 98926

A. Patrinos
ER-76, GTN
Department of Energy
Washington, DC 20545

G. Petersen
Department of Agriculture
Pennsylvania State University
University Park, PA 16802

G. F. Pinder
University of Vermont
College of Engineering
and Mathematics
Office of the Dean
101 Votey Building
Burlington, VT 05405-0156

W. Piver
National Institutes of
Environmental Health
Sciences
P.O. Box 12233
Research Triangle
Park, NC 27709

R. Rabson
ER-17, GTN
Department of Energy
Washington, DC 20545

D. P. Rall, Director
National Institutes of
Environmental Health
Sciences
P.O. Box 12233
Research Triangle
Park, NC 27709

Regional Director
EPA Regional Office
1200 6th Avenue
Seattle, WA 98101

D. E. Reichle
Environmental Sciences
Division
Oak Ridge National
Laboratory
P.O. Box 2008
Oak Ridge, TN 37831-6037

C. A. Reilly, Jr.
Argonne National Laboratory
Bldg. 203
9700 South Cass Avenue
Argonne, IL 60439

C. R. Richmond
Oak Ridge National
Laboratory
4500N, MS-62523
P.O. Box 2008
Oak Ridge, TN 37831-6253

C. Riordan
Office of Research &
Development
Environmental Protection
Agency
Washington, DC 20460

B. E. Rittmann
Department of Civil
Engineering
University of Illinois
Urbana, IL 61801

J. S. Robertson
ER-73, GTN
Department of Energy
Washington, DC 20545

S. L. Rose
ER-73, GTN
Department of Energy
Washington, DC 20545

R. D. Rosen, Tech. Librarian
Environmental Measurements
Laboratory
Department of Energy
376 Hudson Street
New York, NY 10014

D. M. Ross
EH-121, GTN
Department of Energy
Washington, DC 20545

E. J. Rykiel, Jr.
Center for BioSystems
Modeling
Dept. of Industrial Engineering
Texas A&M University
College Station, TX 77843-3131

L. Sagan
Electric Power Research
Institute
3412 Hillview Avenue
P.O. Box 10412
Palo, Alto, CA 94304

M. Schulman
ER-70, GTN
Department of Energy
Washington, DC 20545

R. S. Scott, Acting Director
EH-24, FORS
Department of Energy
Washington, DC 20585

G. H. Setlock
Hockwell International
North American Space
Operations
Rocky Flats Plant, MS-250
P.O. Box 464
Golden, CO 80402

R. B. Setlow
Brookhaven National
Laboratory
Upton, Long Island, NY 11973

R. Shikar
Battelle - Seattle
4000 NE 41st Street
Seattle, WA 98105

P. H. Silverman
Lawrence Berkeley Laboratory
Bldg. 50A/5104
Berkeley, CA 94720

J. Simmons
Bioeffects Analysis Branch
Environmental Protection
Agency
401 M Street, SW
Washington, DC 20460

R. Simon
AC-1, FORS
Department of Energy
Washington, DC 20585

W. K. Sinclair, President
National Council on
Radiation Protection
7910 Woodmont Avenue
Suite 1016
Bethesda, MD 20814

J. Skalski
Center for Quantitative Science
HR-20
3737 15th Avenue, N
Seattle, WA 98195

S. Sligar
Department of Biochemistry
415 Roger Adams Laboratory
1209 W. California Street
Urbana, IL 61801

D. A. Smith
ER-72, GTN
Department of Energy
Washington, DC 20545

G. S. Smith
New Mexico State University
Box 3-I
Las Cruces, NM 88003-0001

J. L. Smith
USDA-ARS
215 Johnson Hall
Washington State University
Pullman, WA 99164

M. Smith
Department of Ecology
NUC-MIX-WASTE Library
PV-II, Bldg. 99-So. Sound
Olympia, WA 98504

M. Smith, Director
Savannah River Ecology
Laboratory
University of Georgia
Savannah River Plant
P.O. Box A
Aiken, SC 29801

L. E. Sommers
Department of Agronomy
Colorado State University
Ft. Collins, CO 80523

J. N. Stannard
University of California
17441 Plaza Animado #132
San Diego, CA 92128

R. W. Starostecki
NS-1, FORS
Department of Energy
Washington, DC 20585

R. J. Stern
EH-10, FORS
Department of Energy
Washington, DC 20585

D. K. Stevens
ER-11, GTN
Department of Energy
Washington, DC 20545

L. F. Stickel
Patuxent Wildlife Research
Center
Laurel, MD 20810

E. T. Still
Kerr-McGee Corporation
P.O. Box 25861
Oklahoma City, OK 73125

P. M. Stone
ER-6, FORS
Department of Energy
Washington, DC 20585

J. M. Suflita
Department of Botany &
Microbiology
University of Oklahoma
Norman, OK 73019

A. Swartzman
Center for Quantitative Studies
University of Washington
3737 15th Avenue
Seattle, WA 98115

J. Swinebroad
EH-12, GTN
Department of Energy
Washington, DC 20545

Technical Information
Service
Savannah River Laboratory
Room 773A
E.I. duPont de Nemours
& Company
Aiken, SC 29801

D. Thomas
Hawaii Institute of Geophysics
University of Hawaii
2525 Correa Road
Honolulu, HI 96822

R. G. Thomas
ER-72, GTN
Department of Energy
Washington, DC 20545

L. O. Tiffin
Swan Valley Route
Seeley Lake, MT 59868

M. J. Truex
Dept. of Civil & Environmental
Engineering
Washington State University
Pullman, WA 99164

University of Washington
Department of Biostatistics
School of Public Health and
Com. Med.
SC-32
Seattle, WA 98195

A. J. Valocchi
Department of Civil
Engineering
University of Illinois
Urbana, IL 61801

P.K.M. van der Heijde
Colorado School of Mines
Institute for GW Res. & Ed.
Golden, CO 80401

C. R. Vest
Battelle, Pacific Northwest
Laboratories
Washington Operations
901 D Street, SW, Suite 900
Washington, DC 20024

G. L. Voelz
Los Alamos National
Laboratory
MS-K404
P.O. Box 1663
Los Alamos, NM 87545

B. W. Wachholz
Radiation Effects Branch
National Cancer Institute
EPN, Room 530
8000 Rockville Pike
Bethesda, MD 20892

R. A. Walters
Assistant to the Associate
Director
Los Alamos National
Laboratory
MS-A114
P.O. Box 1663
Los Alamos, NM 87545

W. W. Weyzen
Electric Power Research
Institute
3412 Hillview Avenue
P.O. Box 10412
Palo Alto, CA 94303

R. W. Whicker
Department of Radiology &
Radiation Biology
Colorado State University
Ft. Collins, CO 80521

R. P. Whitfield
EM-40, FORS
Department of Energy
Washington, DC 20585

F. J. Wobber
14 Goshen Court
Gaithersburg, MD 20882-1016

R. W. Wood
ER-74, GTN
Department of Energy
Washington, DC 20545

R. G. Woodmansee
Department of Range Science
Colorado State University
Fort Collins, CO 80523

S. R. Wright
Savannah River Operations
Office
P.O. Box A
Aiken, SC 29801

Zhu Zhixian
Laboratory for Energy-Related
Health Research
University of California
Davis, CA 95616

FOREIGN

E. L. Alpen
University of California Study
Center
21 Stratton Ground
London SW1 P2HY
ENGLAND

M. Anderson
Library
Department of National Health
& Welfare
Ottawa, Ontario
CANADA

D. C. Aumann
Institut für Physikalische
Chemie
Universität Bonn
Abt. Nuklearchemi
Wegelerstrabe 12
5300 Bonn 1
GERMANY

M. R. Balakrishnan, Head
Library & Information Services
Bhabha Atomic Research
Centre
Bombay-400 085
INDIA

A. M. Beau, Librarian
Département de Protection
Sanitaire
Commissariat à l'Énergie
Atomique
BP No. 6
F-92265 Fontenay-aux-Roses
FRANCE

G. Bengtsson,
Director-General
Statens Stralskyddsinstitut
Box 60204
S-104 01 Stockholm
SWEDEN

D. J. Beninson
Gerencia de Protección
Radiológica y Seguridad
Comisión Nacional de
Energía Atómica
Avenida del Libertador 8250
2º Piso Of. 2330
1429 Buenos Aires
ARGENTINA

A. Bianco
ENEA, Dipart. Protezione
Via le Regina Margherita 125
I-00198 Roma
ITALY

Cao Shu-Yuan, Deputy Head
Laboratory of Radiation
Medicine
North China Institute of
Radiation Protection
P.O. Box 120
Tai-yuan, Shan-Xi
THE PEOPLE'S REPUBLIC
OF CHINA

M. Carpentier
Commission of the European
Communities
200 rue de la Loi
J-70 6/16
B-1049 Brussels
BELGIUM

M. A. Carregado
Gerencia de Protección
Radiológica y Seguridad
Comisión Nacional de
Energía Atómica
Casilla de Carreo 40
1802 Aeropuerto Int.
Ezeiza
ARGENTINA

Chen Xing-An
Laboratory of Industrial
Hygiene
Ministry of Public Health
2 Xinkang Street
Deshengmenwai, Beijing
THE PEOPLE'S REPUBLIC
OF CHINA

R. Clarke
National Radiological
Protection Board
Harwell, Didcot
Oxon OX11 0RQ
ENGLAND

Commission of the European
Communities
DG XII - Library SDM8 R1
200 rue de la Loi
B-1049 Brussels
BELGIUM

H.A.M. DeGruyf
Head, Laboratory of
Ecotoxicology
National Institute of Public
Health and Environmental
Hygiene
P. O. Box 1, 3720 BA Bilthoven
THE NETHERLANDS

Deng Zhicheng
North China Institute of
Radiation Protection
Tai-yuan, Shan-Xi
THE PEOPLE'S REPUBLIC
OF CHINA

G. M. Desmet
Commission of the
European Communities
DG XII
200 rue de la Loi
B-1049 Brussels
BELGIUM

Director
Commissariat à l'Énergie
Atomique
Centre d'Etudes Nucléaires
Fontenay-aux-Roses (Seine)
FRANCE

Director
Commonwealth Scientific and
Industrial Research
Organization
Aspendal, Victoria
AUSTRALIA

Director
Laboratorio di Radiobiologia
Animale
Centro di Studi Nucleari Della
Casaccia
Comitato Nazionale per
l'Energia Nucleare
Casella Postale 2400
I-00100 Roma
ITALY

D. Djuric
Institute of Occupational and
Radiological Health
11000 Beograd
Deligradoka 29
YUGOSLAVIA

Estacao Agronómica Nacional
Biblioteca
2780 Oeiras
PORTUGAL

L. Feinendegen, Director
Institut für Medizin
Kernforschungsanlage Jülich
Postfach 1913
D-5170 Jülich
GERMANY

R. M. Fry, Head
Office of the Supervising
Scientist for the Alligator
Rivers Region
P.O. Box 387
Bondi Junction NSW 2022
AUSTRALIA

A. Geertsema
Saso Technology (Pty), Ltd.
P.O. Box 1
Sasolburg 9570
REPUBLIC OF SOUTH
AFRICA

G. B. Gerber
Radiobiology Department
Commission of the European
Communities
200 rue de la Loi
B-1049 Brussels
BELGIUM

A. R. Gopal-Ayengar
73-Mysore Colony
Mahul Road, Chembur
Bombay-400 074
INDIA

A. Grauby
Service d'Etudes at
de Recherches
sur l'Environnement
Commissariat à l'Énergie
Atomique
Caderache, No. 1
BAT 153 13115
St. Paul Les Durance
FRANCE

J. L. Head, Director
Department of Nuclear Science
& Technology
Royal Naval College,
Greenwich
London SE10 9NN
ENGLAND

M. D. Hill
Assessments Department
National Radiological
Protection Board
Chilton, Didcot
Oxon OX11 0RQ
ENGLAND

International Atomic Energy
Agency
Documents Library
Attn: Mrs. Javor
Kaerntnerring 11
A-1010 Vienna 1
AUSTRIA

K. E. Lennart Johansson
Radiophysiska Inst.
Regionsjukhuset
S-901 85 Umeå
SWEDEN

H.-J. Klimisch
BASF Aktiengesellschaft
Abteilung Toxikologie, Z470
D-6700 Ludwigshafen
GERMANY

G. H. Kraft
c/o GSI Postbox 110541
Planck Str.
D-6100 Darmstadt
GERMANY

T. Kumatori
National Institute of
Radiological Sciences
9-1, Anagawa-4-chome
Chiba-shi 260
JAPAN

Li De-Ping
Professor and Director of
North China Institute of
Radiation Protection, NMI
Tai-yuan, Shan-Xi
THE PEOPLE'S REPUBLIC
OF CHINA

Librarian
Australian Nuclear Science &
Technology Organization
Private Mail Bag 1
Menai NSW 2234
AUSTRALIA

Librarian
Centre d'Etudes
Nucléaires de Saclay
P.O. Box 2, Saclay
Fig-sur-Yvette (S&O)
FRANCE

Librarian
CSIRO
314 Albert Street
P.O. Box 89
East Melbourne, Victoria
AUSTRALIA

Librarian
CSIRO
Division of Atmospheric
Research
Station Street
Aspendal, Victoria 3195
AUSTRALIA

Librarian
CSIRO
Division of Wildlife and
Ecology
P.O. Box 84
Lyneham, ACT 2602
AUSTRALIA

Librarian
Department of Fisheries
and Oceans
Freshwater Institute
501 University Crescent
Winnipeg, Manitoba R3T 2N6
CANADA

Librarian
Department of Fisheries
and Oceans
Pacific Biological Station
P.O. Drawer 100
Nanaimo, British Columbia
V9R 5K6
CANADA

Librarian
HCS/EHE
World Health Organization
CH-1211 Geneva 27
SWITZERLAND

Librarian
Kernforschungszentrum
Karlsruhe
Institut für Strahlenbiologie
Postfach 3640
D-75 Karlsruhe 1
GERMANY

Librarian
Max-Planck-Institut
für Biophysics
Forstkasstrabe
D-6000 Frankfurt/Main
GERMANY

Librarian
Ministry of Agriculture,
Fisheries & Food
Fisheries Laboratory
Lowestoft, Suffolk NR33 OHT
ENGLAND

Librarian
National Institute of
Radiological Sciences
9-1, Anagawa-4-chome
Chiba-shi 260
JAPAN

Librarian
Supervising Scientist for the
Alligator Rivers Region
Level 23, Bondi Junction
Plaza
P.O. Box 387
Bondi Junction NSW 2022
AUSTRALIA

Library
Atomic Energy of Canada, Ltd.
Whiteshell Nuclear Research
Establishment
Pinawa, Manitoba ROE 1L0
CANADA

Library (Serials Section)
British Geological Survey
Nicker Hill, Keyworth
Nottingham NG12 5GG
ENGLAND

Library
Department of Fisheries
and Oceans
West Vancouver Laboratory
4160 Marine Drive
West Vancouver, BC V7V 1N6
CANADA

Library
Department of Meteorology
University of Stockholm
Arrhenius Laboratory
S-106 91 Stockholm
SWEDEN

B. Lindell
National Institute of
Radiation Protection
Fack S-104 01
Stockholm 60
SWEDEN

A. M. Marko
9 Huron Street
Deep River, Ontario
K0J 1P0
CANADA

H. Matsudaira,
Director-General
National Institute of
Radiological Sciences
9-1, Anagawa-4-chome
Chiba-shi 260
JAPAN

H. J. Metivier
Institut de Protection
et de Sûreté Nucléaire
Centre d'Études de Service
de Fontenay-aux-Roses
BP No. 6
F-92265 Fontenay-aux-Roses
FRANCE

S. F. Mobbs
National Radiological
Protection Board
Chilton, Didcot
Oxon OX11 0RQ
ENGLAND

C. Myttenaere
Laboratoire de Physiologie
Végétale (VYVE)
Place Crois du Sud, 4
B-1348 Louvain-La-Neuve
BELGIUM

J. C. Nénot, Deputy Director
Département de Protection
Centre d' Etudes Nucléaires
BP No. 6
F-92260 Fontenay-aux-Roses
FRANCE

R. Osborne
Atomic Energy Commission
of Canada, Ltd.
Chalk River Nuclear
Laboratories
Chalk River, Ontario K0J 1J0
CANADA

O. Pavlovski
Institute of Biophysics
Ministry of Public Health
Givopisnaya 46
Moscow D-182
RUSSIA

V. Prodi
Department of Physics
University of Bologna
Via Irnerio 46
I-40126 Bologna
ITALY

Reports Librarian
Harwell Laboratory, Bldg. 465
UKAEA
Harwell, Didcot
Oxon OX11 0RB
ENGLAND

P.J.A. Rombout
Inhalation Toxicology
Department
National Institute of Public
Health and Environmental
Protection
P.O. Box 1
NL-3720 BA Bilthoven
THE NETHERLANDS

M. Rzekiecki
Commissariat à l'Énergie
Atomique
Centre d'Études
Nucléaires de Cadarache
BP No. 13-St. Paul
Les Durance
FRANCE

H. Smith
International Commission on
Radiological Protection
P.O. Box 35
Didcot
Oxon OX11 0RJ
ENGLAND

J. W. Stather
National Radiological
Protection Board
Building 383
Chilton, Didcot
Oxon OX11 0RQ
ENGLAND

Sun Shi-Quan, Head
Radiation-Medicine
Department
North China Institute of
Radiation Protection, NMI
P.O. Box 120
Tai-yuan, Shan-Xi
THE PEOPLE'S REPUBLIC
OF CHINA

G. Tarroni
ENEA-PAS-FIBI-AEROSOL
Laboratorio Fisica Sanitaria
Via Ercolani 8
I-40138 Bologna
ITALY

J. W. Theissen
Radiation Effects Research
Foundation
5-2 Hijiyama Park
Minami-Ku
Hiroshima 732
JAPAN

K. W. Timmis, Director
Division of Microbiology
National Centre for
Biotechnology
Mascheroder Weg
D-3300, Braunschweig
GERMANY

D. Van As
Atomic Energy Corporation
P.O. Box 582
Pretoria 0001
REPUBLIC OF SOUTH AFRICA

Vienna International Centre
Library
Gifts and Exchange
P.O. Box 100
A-1400 Vienna
AUSTRIA

Wang Hengde
North China Institute of
Radiation Protection
P.O. Box 120
Tai-yuan, Shan-Xi
THE PEOPLE'S REPUBLIC
OF CHINA

Wang Renzhi
Institute of Radiation Medicine
11# Tai Ping Road
Beijing
THE PEOPLE'S REPUBLIC
OF CHINA

Wang Ruifa,
Associate Director
Laboratory of Industrial
Hygiene
Ministry of Public Health
2 Xinkang Street
P.O. Box 8018
Deshengmenwai, Beijing
100088
THE PEOPLE'S REPUBLIC
OF CHINA

Wang Yibing
North China Institute of
Radiation Protection
P.O. Box 120
Tai-yuan, Shan-Xi
THE PEOPLE'S REPUBLIC
OF CHINA

Wei Lü-Xin
Laboratory of Industrial
Hygiene
Ministry of Public Health
2 Xinkang Street
Deshengmenwai, Beijing
100088
THE PEOPLE'S REPUBLIC
OF CHINA

B. C. Winkler, Director
Licensing
Raad Op Atomic
Atoomkrag Energy Board
Privaatsk X 256
Pretoria 0001
REPUBLIC OF SOUTH AFRICA

Wu De-Chang
Institute of Radiation Medicine
27# Tai Ping Road
Beijing
THE PEOPLE'S REPUBLIC
OF CHINA

ONSITE

DOE Richland Field Office (4)

W. W. Bixby A7-30
R. D. Freeberg A6-95
P. W. Kruger A5-90
M. W. Tiernan A5-55

Hanford Environmental Health Foundation

M. J. Swint H1-02

Westinghouse Hanford Co. (4)

M. R. Adams H4-55
L. C. Brown H4-51
R. M. Mitchell H4-55
D. E. Simpson B3-55

Pacific Northwest Laboratory (152)

C. C. Ainsworth K3-61
R. W. Baalman K1-50
J. F. Bagley K1-64
W. J. Bair K1-50 (2)
R. M. Bean P8-08

M. P. Bergeron K6-77
H. Bolton K4-06
C. J. Brandt K6-04
F. J. Brockman K4-06
T. M. Brouns P7-41
L. L. Cadwell P7-54
D. A. Cataldo K4-12
T. D. Chikalla P7-75
T. T. Claudson B1-40
C. R. Cole K6-77
S. D. Colson K2-14
E. A. Crecelius SEQUI
R. J. Douthart K4-13
J. L. Downs P7-54
D. W. Dragnich K1-46
T. H. Dunning K2-18
L. L. Eberhardt P7-54
R. M. Ecker SEQUI
C. E. Elderkin K6-03
R. A. Elston SEQUI
J. W. Falco K6-78
R. J. Fellows K4-12
R. M. Fleischman K1-43
J. K. Fredrickson K4-06
J. S. Fruchter K6-81
T. R. Garland K3-61
G. W. Gee K6-77
E. S. Gilbert P7-82
D. C. Girvin K3-61
W. A. Glass K4-13
M. J. Graham K6-80
R. H. Gray K1-33
P. C. Hays K6-86
D. J. Holford K6-77

L. A. Holmes K1-29
C. J. Hostetler K6-81
J. R. Houston A3-60
E. A. Jenne K6-81
J. R. Johnson K3-53
R. N. Kickert P7-54
M. L. Knotek K1-48
W. W. Laity K2-50
M. W. Ligothe P7-54
S. O. Link P7-54
P. E. Long K6-84
J. A. Mahaffey P7-82
J. F. McBride K6-77
J. L. McElroy P7-46
J. P. McKinley K3-61
G. L. McVay K2-45
B. D. McVeety K4-12
F. B. Metting P7-54
J. R. Morrey P7-14
G. P. O'Connor P7-54
R. L. Ornstein K2-18
T. L. Page B1-40
J. F. Park P7-52
W. T. Pennell K6-04
D. A. Perez K6-86
R. W. Perkins P7-35
W. H. Rickard P7-54
R. G. Riley K6-81 (5)
K. R. Roberson K6-77
J. T. A. Roberts K1-73
L. E. Rogers P7-54 (5)
M. F. Romine K4-06
J. L. Ryan P7-25
G. F. Schiefelbein P8-38

R. P. Schneider P7-56
D. B. Shipler K6-89
B. D. Shipp K1-73
C. S. Simmons K6-77
M. A. Simmons P7-54
R. L. Skaggs K6-77
T. L. Stewart K1-25
G. M. Stokes K1-74
J. A. Stottlemire K6-75
G. P. Streile K6-77
J. E. Szecsody K6-77
W. L. Templeton K1-30
T. S. Tenforde K1-50 (15)
M. E. Thiede P7-54
J. M. Thomas P7-54
R. C. Thompson P7-58
L. H. Toburen P8-47
P. Van Voris K4-12
B. E. Vaughan K1-66
W. C. Weimer P7-22
R. E. Wildung P7-54 (20)
L. D. Williams K1-41
B. D. Wood K6-77
J. V. Wright K6-84
G. E. Wukelic K6-84
J. S. Young K6-81
J. M. Zachara K3-61
J. D. Zimbrick P7-58
Health Physics Department
Library
Life Sciences Library (2)
Publishing Coordination
Technical Report Files (5)

END

**DATE
FILMED**

8 / 6 / 92