#27.
5/8/80

SAND80-0249
Unlimited Distribution
UC-2

A REVIEW OF UPDATED SANDIA WAVECODES FOR PENETRATION WORK

MASTER

Frederick R. Norwood

Prepared by Sandia Laboratories, Albuquerque, New Mexico 87115
and Livermore, California 94550 for the United States Department of
Energy under Contract AT(29-1)-789

Printed February 1980

Sandia National Laboratories

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Issued by Sandia Laboratories, operated for the United States
Department of Energy by Sandia Corporation.

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Printed in the United States of America

Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161

Price: Printed Copy ~~\$4.50~~ 6.00 Microfiche ~~\$3.00~~ 5.00

SAND80-0249
Unlimited Distribution
Printed February 1980

UC-2

A REVIEW OF UPDATED SANDIA WAVECODES
FOR
PENETRATION WORK

by

Frederick Reyes Norwood
Computational Physics and Mechanics Division II 5533
Sandia National Laboratories, Albuquerque, New Mexico 87185

ABSTRACT

For the special needs of the Sandia penetrator program, the codes TAUTQ, NORML, and OBLIK were written as modifications of the wavecodes WONDY and TOODY. This report presents a brief outline of the new codes, together with a set of instructions for running them.

DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

CONTENTS

I. Introduction	5
II. TAUTQ.	6
III. NORML.	11
IV. OBLIK.	18
APPENDIX	22
REFERENCES	25

LIST OF FIGURES

Figure 1. Schematics for the Definition of Conical and Ogival Regions.	27
---	----

I. Introduction

The main objective of the numerical effort within the Sandia penetration project is to provide predictions of effects related to the performance and survivability of the penetrator and its internal components. In particular, predictions of deceleration history and stress histories at various locations are desired for suggesting improvements in the design of the penetrator and its components. Also, predictions of separation and reattachment of the target medium to the penetrator are desired to analyze target-penetrator interaction. Comparison of these predictions with experimental data permits evaluation of current theoretical prediction capabilities and, in addition, provides insights into the primary mechanisms and relevant phenomena governing projectile penetration into various target materials.

It seems pertinent for this report to state briefly some of the goals of the computational effort: (1) to develop methods for confidently predicting loads on the penetrator structure, (2) to develop an understanding of the detailed mechanisms involved in target penetration to the extent that the empirical soil factor in [1] may be correlated with appropriate target medium properties, and (3) to establish the degree of complexity in the description of target medium properties necessary for accurate calculation of projectile decelerations, loads, and depths of penetration. The code development efforts described here were made in accordance with these objectives, and will be presented in terms of the codes created: TAUTQ, NORML, and OBLIK. A brief description of TAUTQ is presented in Section II, followed by instructions for running the code. Sections III and IV, respectively, contain the corresponding information for NORML and OBLIK.

II. TAUTQ

In the past, the TOODY Lagrangian code [2] has been used to predict penetration performance of both a rigid and a deformable projectile. However, since the deformable case is covered by the description of the standard version of the code, no further comments will be made here. For the rigid penetrator, it has been indicated [3] that, with the projectile considered as a rigid body, the finite difference code is capable of more efficient operations than when the projectile is taken to be a deformable body. Rigid body calculations then permit examination of penetration to deeper projectile depths in reasonable amounts of computer time. For soil media and many rock media this is an acceptable assumption as long as the impedance of the projectile is greater than the shock impedance of the target.

In TOODY, the nodes of the calculational grid move in response to the local stress gradients. The specific motion is found by solving finite difference analogs of the partial differential equations describing the balance of momentum, mass, and energy, and the constitutive relations. The process is executed at each node of the grid, the time is then advanced, and the whole process repeated until the desired final time of the calculation is reached.

Improvement 1. Since the time-step with which the calculation advances is controlled by the minimum mesh dimension over the entire grid, large distortions can result in an inefficient calculation. These large distortions can also degrade the accuracy of the numerical methods used in the code, which then would yield unrealistic results.

For these reasons, the TOOREZ code [4] was developed to permit continuing Lagrangian code calculations past the point where they would

otherwise have to be abandoned. TOOREZ allows the user to redistribute the nodes of the calculational grid (i.e., rezone the problem), then partitions the mass, momentum, and energy in such a way that all these quantities are conserved. Using the output from the rezoning code, the calculation can then be resumed. However, this process requires a large amount of user time devoted to fairly repetitive redefinitions of input, and also a large amount of elapsed time because of the many job submissions necessary. In an effort to automate the earth penetration calculations the automatic rezoning code AUTOREZ was developed. By the use of this code, a penetration event calculation may be accomplished in only one submission. A detailed discussion of this code may be found in [5].

Improvement 2. The positions of the nodes in the calculational grid which originally lie on the axis of rotational symmetry are prevented from entering the space occupied by the penetrator, which is assumed to be a rigid body. The motion of each of these nodes is first calculated in the standard way from the stress divergence, including the effects of soil-penetrator friction, if any. If the standard motion calculation for the node yields a position on the surface of, or outside, the projectile, no adjustments are necessary. When a node position is calculated to lie inside the penetrator, adjustments to the velocity and position are made so that the normal velocity relative to the penetrator is zero, the tangential velocity has the value already calculated, and the position is on the penetrator surface. In resolving the velocity into normal and tangential components on an ogival nose, the position of the node at the previous time step is used to evaluate the local normal direction. The areas and volumes for material and momentum zones adjacent to the penetrator are adjusted, where necessary, to include the effect of the penetrator surface.

At the beginning of each time step of the calculation, surface tractions for all soil zones in contact with the penetrator are integrated to give the total axial force acting to decelerate the penetrator. For a zone in contact with the penetrator surface the stress is assumed constant, and the axial contributions of the normal stress and frictional stress, if any, are expressed as functions of position on the penetrator surface. These stresses are integrated over the range covered by the zone so that, on the nose, changes in the local normal direction and surface area are accounted for in the analysis.

The two improvements may be obtained by using the sequence of control cards shown below, where both auxiliary disc and extended core are required.

```

REDUCE
ATTACH,FXSCORS.
LIBRARY,FXSCORS.
ATTACH,P1,TAUTQ,CY=1.
ATTACH,P2,TAUTQ,CY=2.
ATTACH,P3,TAUTQ,CY=3.
COPYCR(INPUT,TAPE50)
REWIND(TAPE50)
UPDATE,P=P1,F.
FTN,T,L=0.
LGO.
UPDATE,P=P2,N=N3,Q.
UPDATE,P=P3,N=N5,Q.
UPDATE,P=N5,M=N3,F,C=FINAL.
RFL(160000)
FTN,I=FINAL,B=TOODY,L=0.
REDUCE.
RFL,L=1000.
REWIND,OUTPUT.
TOODY(PL=377777)
EXIT(U)
FICHE,OUTPUT.          CONICAL NOSE PENETRATOR TUNGSTEN
CATALOG,TAPE30,TUNG,CN=TUNG,CY=1.
CATALOG,TAPE1,PUN,CN=PUN,CY=1.

```

The rigid projectile coding accepts data for cylindrical projectiles with either a conical or an ogival nose.

The first card of the input data must contain information on the rigid penetrator by the format (8E10.3) as shown:

ZPB	ZPC	ZPP	XPC	RHOP	UZPROJ	XMUPRJ	PENSW
-----	-----	-----	-----	------	--------	--------	-------

where these quantities are defined by

ZPB = Z-position of rear penetrator surface

ZPC = Z-position of the intercept of the nose with the penetrator
body (assumed as a cylindrical surface)

ZPP = $\begin{cases} \text{Z-position of the nose tip for a conical nose, or} \\ \text{CRH for an ogival nose} \end{cases}$

XPC = $\begin{cases} \text{radius of a conical nose projectile (a positive quantity), or} \\ \text{minus the radius of an ogival nose projectile (a negative} \\ \text{quantity)} \end{cases}$

RHOP = average density of the penetrator

UZPROJ = initial penetrator velocity

XMUPRJ = friction coefficient at penetrator-target interface

PENSW = $\begin{cases} d, \text{ where } d \text{ is a positive quantity, signals the program} \\ \text{to decelerate the projectile, or} \\ 0, \text{ maintain total load on a constant velocity projectile} \end{cases}$

This first card is followed by the usual set of cards for TOODY input [2], where, for the definition of shape option 7, the labelling of points 1 and 3 is interchanged. As described in [5], the input cards for the automatic rezoner follow the TOODY deck setup.

The plotting programs PLOTSM76 and A6FF60 written by D. Holdridge are used by TAUTQ for plotting the results [6]. For time histories at specified points, PLOTSM76 is used, with the following control cards:

LAS,MC7,T100,EC700.
ATTACH,TAPE30,OSC1,CY=1.
ATTACH,FXSCORS,FXSCORS.
LIBRARY,FXSCORS.
FILE,OLDPL,RT=S.
ATTACH,OLDPL,PLOTSM76.
UPDATE,F.
FIN,I,L=0.
RFL,L=700.
LGO.

The first card shows the EC requirement (the account card is needed). The input instruction for PLOTSM76 appear in the appendix. A6FF60 is a slightly modified version of FF60, with the same input instructions [6]. The control cards required are shown below.

ATTACH,TAPE11,FIN2,CY=1.
ATTACH,FXSCORS,FXSCORS.
LIBRARY,FXSCORS.
ATTACH,OLDPL,A6FF60,CY=1.
UPDATE,P,F.
FIN,I,L=0.
LGO.

III. NORML

For the special requirements of the penetration project, the wavecode WONDY was modified to include a velocity boundary condition and also a material model representative of soil behavior.

Improvement 1. WONDY is a general-purpose, Lagrangian, finite difference wavecode, in which a calculational grid is set up to model a region of the target, and the local balance equations, in finite difference forms, are solved at each grid point [7]. Considering the penetration problem, it was assumed that (a) each infinitesimal layer in the target deforms in plane strain (radial motion only), and (b) the penetrator is a rigid body. The geometry and impact velocity of the penetrator determine the boundary conditions on material motion in each infinitesimal target layer. These boundary conditions insure that target material remains on, or outside, the penetrator boundary.

The main result of calculations with NORML is the stress history necessary to open a (circular) cavity in the target according to the prescribed boundary conditions [8]. This cavity stress is interpreted, then, as the radial component of the normal stress which is exerted on the penetrator. The stress at any particular axial position on the penetrator can be related directly to the stress at a particular time in the calculated history through the penetrator velocity (i.e., position = velocity x time). It is implicitly assumed that there is no "communication" between infinitesimal target layers, or that axial stress gradients are negligible compared with radial stress gradients. It is also assumed that the penetrator velocity does not change significantly during a nose length of penetration. Thus, the code calculates, essentially, a "steady state" distribution of stress on the penetrator at the given velocity. In addition, Coulomb friction is assumed at the penetrator/target interface, from which

the frictional stress is found by multiplying the normal stress at any point by the Coulomb coefficient. Normal stress and frictional stress are then superimposed to give the total traction at that point on the penetrator.

Improvement 2. A variety of material models is available in WONDY, including a standard elastic-plastic model (with various hardening and yield surface options), and a porous material model based on Herrmann's P- α model [9]. For the present application, these two models were combined to provide a P- α model with strength. This was effected by the following considerations (for the notation used here, refer to [7]).

In the elastic-plastic model, the pressure is computed according to the equation

$$p = p_H + \Gamma p (\epsilon - \epsilon_H) , \quad (1)$$

where p_H is selected from the expressions

$$p_H = \frac{\rho_0 c_0^2 \eta}{(1 - 5\eta)^2} ,$$

$$p_H = K_0 \eta (1 + k_1 \eta + k_2 \eta^2 + \dots) ,$$

and

$$\eta = 1 - \rho_0 / \rho .$$

For such a material which can support shear stresses, the deviatoric stresses are computed via the relation

$$\frac{\partial \sigma_i^d}{\partial t} = 2G d_i^d , \quad i = x, y, z . \quad (2)$$

where

$$G = G_0(1 + g_1\eta_1 + g_2\eta_1^2) . \quad (3)$$

If the material exhibits plasticity, the deviator stresses have an upper limit determined by a yield condition, for example, by the von Mises yield condition

$$f_y = (\sigma_x^d)^2 + (\sigma_y^d)^2 + (\sigma_z^d)^2 \leq \frac{2}{3} Y^2 , \quad (4)$$

where the yield function is given by

$$Y = Y_0(1 + y_1\eta)(1 - \varepsilon/y_2) \geq 0 . \quad (5)$$

In the standard P- α model, the material lacks shear strength, and can only support a hydrodynamic stress field. For this model the pressure is related to the distention ratio $\alpha = \rho_s/\rho$ by the equation

$$\alpha = 1 + (\alpha_e - 1) \left(\frac{p_s - p}{p_s - p_e} \right)^2 \quad (6)$$

The P- α model with strength may be described quite easily by referring to equations (1) - (6). In fact, this model is quite similar to the elastic-plastic model, and may be obtained from it by calculating the pressure through the use of equation (6). Then, the deviatoric stresses are calculated by equation (2). The shear modulus in this model was assumed to vary as a linear function of the distention ratio α according to the formula

$$G = G_0 + \frac{\alpha_0 - \alpha}{\alpha_0 - 1} (G_s - G_0) , \quad (7)$$

where G_0 is the initial (undisturbed) shear modulus and G_s is the modulus of the material when all pores have been collapsed. Finally, instead of equation (5), the yield function is assumed to be a function of pressure.

The options are

$$\left. \begin{aligned} (1) \quad Y &= y_0 \\ (2) \quad Y &= \begin{cases} A + (C - A)p/B, & 0 \leq p \leq B, \\ C, & B \leq p, \end{cases} \\ (3) \quad Y &= A - C \exp(-Bp) \end{aligned} \right\} \quad (8)$$

For running NORML with these two improvements, the following control cards, together with the updates shown, are required:

```
ATTACH,OLDPL,NORML,CY=1.
UPDATE,F.
FTN,I,I=0.
LGO(PL=377777)
FICHE,OUTPUT.                P-ALPHA MT. HELEN TUFF
CATALOG,TAPE23,HELEN,CN=HELEN,CY=1,RP=777.
789
*D PENET1.18
    UN=(XN-X)/DELT(1)
*D PENET1.17
    STORE(11)=DRDZ
*D PENET1.5,6
    TANT=STORE(11)
    STORE(15)=STORE(15)*SQRT(TANT**2+1.)
    STORE(1)=STORE(1)+STORE(15)*STORE(12)*TANT/SQRT(TANT**2+1.)
    STORE(2)=STORE(2)+ADDATA(25)*STORE(15)*STORE(12)/SQRT(TANT**2+1.)
789
```

Tape 23 is cataloged for plotting purposes, as will be indicated at the end of the next section. The coding allows for conical, ogival, and cylindrical regions of the penetrator. The definition of each region is given by the constants PC1 to PC4 illustrated in Fig. 1. The penetrator nose tip is assumed to be located at the origin. A cylindrical section is a special case of a conical section which is obtained by setting ϕ equal to zero. Thus, for a cylindrical section,

PC1 = 0,
 PC2 = radius of the surface
 PC3 = 0,
 PC4 = length of section.

Behind the penetrator, PC1, PC2, and PC3 are set equal to zero, and PC4 is set equal to 10^{100} .

The penetrator parameters are stored in the array ADDATA, beginning with ADDATA(22), by the format (2I5,4E10.3). A typical arrangement of the data would be as follows:

9	I	A	B	C	D	
---	---	---	---	---	---	--

where $I = 22 + 7m$; $m = 0,1,2,---,NREG$, and NREG is the number of geometrical regions needed to describe the penetrator. Also,

ADDATA(I) = A,
 ADDATA(I+1) = B,
 ADDATA(I+2) = C,
 ADDATA(I+3) = D.

The data for the k-th section correspond to the values for $I = 22 + 7k$.

A set-up for a penetrator with three geometrical sections may be represented by*

9	22	NREG	VEL	MASS	FR. COEFF.	
9	29	PC1	PC2	PC3	PC4	
9	36	PC1	PC2	PC3	PC4	
9	43	PC1	PC2	PC3	PC4	

where VEL is the initial velocity, MASS is the penetrator mass, and FR. COEFF. is the Coulomb coefficient of friction.

The input needed for the P- α model with strength will be described briefly, using the style of [7].

* FORMAT (2I5,4E10.3)

CARD 12

31^{RZERO}₄₀ - initial density of target material, ρ_o

CARD 15

11^{CES(1)}₂₀ - density of poreless material, ρ_s

21^{CES(2)}₃₀ - sound speed of poreless material, c_s

CARD 18

11^{CES(??)}₂₀ - initial sound speed of target material, c_o

21^{CES(23)}₃₀ - initial distention ratio, $\alpha_o = \rho_s / \rho_o$

31^{CES(24)}₄₀ - elastic pressure limit, p_e

41^{CES(25)}₅₀ - compaction pressure, p_s

CARD 20

11^{CES(36)}₂₀ - value of option for equation 8(1.,2.,or 3.)

21^{CES(37)}₃₀ - value of parameter A for yield function

31^{CES(38)}₄₀ - value of parameter B for yield function

41^{CES(39)}₅₀ - value of parameter C for yield function

51^{CES(40)}₆₀ - initial shear modulus, G_o

61^{CES(41)}₇₀ - shear modulus of poreless material, G_s

For NORML output, the time is selected in card 7, where no effort has been made to change the message printed. The information will appear as follows

N=	T=TIME	INT=	LEFTX=	U=	S=TAUR	E=GAP	R=RAD
			RIGHT		S=	E=STRESS	R=DISTANCE

where only the items of interest have a value. TAUR is radial component of stress, GAP is the penetrator/target gap, RAD is the penetrator radius, STRESS is the normal stress acting on the penetrator, and DISTANCE is the axial distance from the nosetip. There will also be a line giving the normal force, the frictional force, the total force, and the deceleration, corresponding to the time T. This output is activated by card 9 with the format

Card 9

1 CARDNO₅ = 9
6 PLATENO₁₀ = 1
11 ADDATA(1)₂₀ = 1.0

IV. OBLIK

As a direct extension of the code NORML for normal penetration, the code OBLIK was developed for treating oblique impact (nonzero angle of attack and impact angle), where any combination of impact angle and angle of attack can be treated. However, due to the methods used in the analysis, the accuracy of the results is expected to be better for small angles of obliquity than for large angles. The code calculates the distribution of traction on the penetrator boundary and, by integrating this distribution, provides histories of the axial and lateral loads.

OBLIK is based to a large extent on the NORML program, which treats the case of normal, or axisymmetric, penetration. In particular, OBLIK uses the same target material models, and the same numerical schemes as those used in NORML. In OBLIK, however, boundary conditions on the governing equations are not assumed to be axisymmetric, but may vary around the circumference of the penetrator. The nature of this variation is determined in a consistent manner from the geometry of the penetrator and the obliquity of the impact.

For running OBLIK, the following control cards are required:

```
FILE,PLOT1,RT=S.  
ATTACH,OLDPL,OBLIK,CY=2.  
UPDATE,F.  
FTN,I,L=0.  
IDSET(PRESET=NGINF)  
LGO(PL=377000)  
EXIT(U)  
FICHE(OUTPUT)  
CATALOG,TAPE23,PEDROS,CN=PEDROS,CY=1,RP=777.  
CATALOG,TAPE22,PEDROS,CN=PEDROS,NC=2,RP=777.  
789
```

Tapes 22 and 23 are cataloged for plotting purposes as will be indicated at the end of this Section.

The input cards for OBLIK are the same as those for NORML except that ADDATA(26), ADDATA(27), and ADDATA(28) are used to input the quantities BETA, THETA, and NANG. These quantities are defined by

THETA = angle included between the axis of the penetrator and the target normal,

BETA = angle included between the velocity vector and the target normal,

NANG = integer used for defining the number of sections into which the penetrator surface is divided.

OBLIK in essence computes, by the use of NORML, the stresses in (NANG+1) sectors around the penetrator. That is, calculations are made for values of Ω equal to 0, ω , 2ω , ---, 180° , where $\omega = 180^\circ/\text{NANG}$ and Ω is measured around the penetrator from the side tilted into the target. The contributions from each sector are added to give the total deceleration. The scheme followed in this code is similar to the scheme for the code PENOB [10] which also treats oblique impact.

In analogy to the input for NORML, the OBLIK set-up for a penetrator with three geometrical sections may be represented by

9	22	NREG	VEL	MASS	FR. COEFF.	BETA	THETA	NANG
9	29	PC1	PC2	PC3	PC4			
9	36	PC1	PC2	PC3	PC4			
9	43	PC1	PC2	PC	PC4			

which must follow the format (2I5,7E10.3).

For each sector, OBLIK provides printed output similar to the output from NORML. Thus, the variation of stress distribution on the penetrator and soil separation from the penetrator may be seen as a function of azimuthal angle.

The plotting program WONPLT [11] is used with data TAPE23, where the variable numbers are as follows:

- 1 radius of cavity wall
- 2 penetrator radial coordinate
- 3 penetrator axial coordinate
- 4 normal stress
- 5 gap

This program is run by using the control cards

```
ATTACH,FXSCORS,FXSCORS.
LIBRARY(FXSCORS)
FILE,OLDPL,RT=S.
ATTACH,OLDPL,WON7A,CY=5.
UPDATE,F.
ATTACH,TAPE23,STONE,CY=1.
FTN,I,L=0.
LGO.
789
*I WONDPLT.9
    CALL HDCOPY(10)
    NANG-1
    1 CONTINUE
*D WONDPLT.95
*D WONDPLT.96
    65 CONTINUE
*I WONDPLT.212
    NANG=NANG-1
    IF(NANG.NE.0) GO TO 1
789
```

where requisite update cards are also shown. The update card NANG=1 is to be used when TAPE23 is generated by NORML. For the case when TAPE23 is created by an OBLIK run, then NANG in this update must be one more than the value used to run the code; that is

$$NANG_p = NANG_o + 1,$$

where the subscripts p and o denote plotting program and OBLIK program, respectively.

For the OBLIK calculations, the penetrator length was subdivided into 1000 sections of length DZAX given by $DZAX=ALGTH/1000.$, where ALGTH is the

total length of the penetrator. This subdivision was used in writing TAPE22 according to the format

```
WRITE(22),DELT,NTOP,(AXF(NP),NP=1,NTOP),(FLAT(NP),NP=1,NTOP)
```

where DELT is the time for one section to enter the target, $DELT = DZAX/V$, NTOP is the number of sections which have entered the target in the time TMAX, $NTOP = TMAX * V / DZAX$ (TMAX is the input for card 3 in WONDY), and V is the velocity of the penetrator. AXF(NP) and FLAT(NP) are the axial and lateral forces contributed by the NP-th section. With this information, it is possible to plot force distribution and also force histories. No program has yet been written for this purpose.

In addition to the codes presented in the previous Sections, the penetration codes PENAP and PENOB were written. The reader is referred to references 10 and 12 for a description of these codes.

APPENDIX

PLOTSM76

PLOTSM76 plots ordinate vs abscissa parameters specified by the user.

Data is read from Tape 30, Tape 31... Available parameters are:

<u>Parameter</u>	<u>Code</u>
Time	1
KEY	2
KEZ	3
ETOT	4
PW	5 -
KEPROJ	6
DTXX	21
DTXZ	22
DTZZ	23
P	24
DX	25
DZ	26
UX	27
UZ	28
Magnitude of Velocity	29
ETA	30
J2	31
I2	32
TXX	33
TXZ	34
TZZ	35

Input Instructions

Card 1

1 ^{NPL} ₅	Number of plot types
6 ^{INGRID} ₁₀	0 tic marks are drawn on plot 1 grid is drawn on plot

Card 2 Format (16I5)

1 ^{IPARAM(1,1)} ₅	IPARAM array consists of NPL pairs
6 ^{IPARAM(1,2)} ₁₀	of codes identifying the ordinates
11 ^{IPARAM(2,1)} ₁₅	and abscissas for the desired plots.
16 ^{IPARAM(2,2)} ₂₀	

Card 3 Format (3I5, 5X, 3E10.0)

1 ^{NPT} ₅	Number of points of interest.
6 ^{NTAPE} ₁₀	Number of tapes. Blank is OK when using one tape.
11 ^{IRSC} ₁₅	0 means the data will determine the scaling. 1 means the scaling will be supplied by the user.
21 ^{TIMBEG} ₃₀	Beginning time
31 ^{TIMEND} ₄₀	Ending time
41 ^{TIMDEL} ₅₀	Time increment

Card 4 Format (16I5)

1 ^{IPLACE(1)} ₅	Points of interest. NPT of them are read
6 ^{IPLACE(2)} ₁₀	here.

Card 5 Format (8E10.0)

Scales read here only if IRSC=1.

SCALE(1,1,1) Minimum for ordinate of first plot type
for first point of interest.

SCALE(1,1,2) Maximum for ordinate as above.

SCALE(1,1,3) Minimum for abscissa as above.

SCALE(1,1,4) Maximum for abscissa as above.

Read all points of interest for each plot
type.

REFERENCES

1. C. W. Young, Empirical Equations for Predicting Penetration Performance in Layered Earth Materials for Complex Penetrator Configurations, Sandia Laboratories, SC-DR-72-0523, December 1972.
2. J. W. Swegle, TOODY IV - A Computer Program for Two-Dimensional Wave Propagation, Sandia Laboratories, SAND-78-0552, September 1978.
3. R. K. Byers, A. J. Chabai, and R. T. Walsh, Predictions of Projectile Penetration Phenomena and Comparison with Experiments in a Soil Medium Sandia Laboratories, final report for period February 1974-January 1975, published October 1975.
4. B. J. Thorne and D. B. Holdridge, The TOOREZ Lagrangian Rezoning Code, Sandia Laboratories, SLA-73-1057, April 1974.
5. P. Yarrington and R. K. Byers, AUTOREZ: A Two-Dimensional, Lagrangian, Automatic Rezoning Wavecode (Preliminary Version), Sandia Laboratories, SAND-79-1914, to appear.
6. D. B. Holdridge, TOODY Plotting Program, FF60, Sandia Laboratories, RS 5162/042, October 1974.
7. R. J. Lawrence and D. S. Mason, WONDY IV --- A Computer Program for One-Dimensional Wave Propagation with Rezoning, Sandia Laboratories, SC-RR-71 0284, Reprinted November 1975.
8. P. Yarrington, D. E. Grady, and F. R. Norwood, Comparison of Experimental and Computational Results for Scaled Reverse Ballistic Tests in Foundry Stone, in preparation.
9. W. Herrmann, "Constitutive Equation for the Dynamic Compaction of Ductile Porous Materials," Journal of Applied Physics, Vol. 40, pp. 2490-2499, May 1969.

10. P. Yarrington, F. R. Norwood, and N. K. Ruiz, PENOB: A Modification of the PENAP Code to Treat Oblique Impact of Earth Penetrators, Sandia Laboratories, SAND78-1154, to appear.
11. R. J. Lawrence, WONPLT: Plotting Program for WONDY, Sandia Laboratories, private communication.
12. P. Yarrington and N. K. Ruiz, PENAP: An Interactive Computer Program for Calculating Surface Loads on Conical- and Ogival-Nosed Earth Penetrators, Sandia Laboratories, SAND77-1359, February 1978.

Figure 1. Schematics for the Definition of Conical and Ogival Regions.

DISTRIBUTION:

Picatinny Arsenal (4)
Dover, New Jersey 07081
Attn: P. Harris
E. Zimpo
A. Garcia
Technical Library

U. S. Army Advanced Ballistic (2)
Missile Defense Agency
Huntsville Office
P. O. Box 1500
Huntsville, Alabama 35807
Attn: CRDABH-S
CRDABH-X

University of California (3)
Lawrence Livermore Laboratory
P. O. Box 808
Livermore, CA 94550
Attn: Technical Library
M. Wildings
G. L. Goudreau

Los Alamos Scientific Laboratory
P. O. Box 1663
Los Alamos, NM 87544
Attn: Reports Library

Department of Aerospace
Engineering and Engineering
Mechanics
University of Texas
Austin, TX 78712
Attn: Prof. C. H. Yew

Atomic Weapons Research
Establishment
Aldermaston
Berkshire, England
Attn: B. D. Lambourn

California Research and (2)
Technology, Inc.
6269 Variel Avenue, Suite 200
Woodland Hills, CA 91364
Attn: K. Kreyenhagen
Technical Library

RDA (6)
P. O. Box 9695
Marina del Rey, CA 90291
Attn: J. Lewis
W. Wright
Technical Library

Science Applications, Inc., (3)
1250 Prospect Street
La Jolla, CA 92037
Attn: D. Maxwell
D. Bernstein
Technical Library

U. S. Army Engineer Waterways (5)
Experiment Station
Soils and Pavements Laboratory
Vicksburg, MS 39180
Attn: G. Jackson
P. Hadala
B. Rohani
R. Bernard
Technical Library

Avco Corporation (4)
Research and Systems Group
201 Lowell Street
Wilmington, MA 01887
Attn: D. Henderson
J. Atanasoff
F. Lasher
Research Library-A830
Room 217

Martin Marietta Aerospace (4)
Orlando Division
P. O. Box 5837
Orlando, FL 32805
Attn: N. Singletory
A. Gowan
M. Anthony
Technical Library

Stanford Research Institute (3)
333 Ravenswood
Menlo Park, CA 94025
Attn: G. Abrahamson
SRI Library, Rm. G021
L. Seaman

DISTRIBUTION (cont'd):

Physics International Company 2700 Merced Street San Leandro, CA 94577 Attn: Technical Library	(4)	Pacifica Technology P. O. Box 148 Del Mar, CA 92014 Attn: R. L. Bjork	
Systems, Science, and Software, Inc. P. O. Box 1620 La Jolla, CA 92037 Attn: E. Gaffney D. Grine Technical Library	(3)	Northwestern University Chicago, IL 60680 Attn: T. B. Belytscho	
Terra Tek, Inc. University Research Park 420 Wakara Way Salt Lake City, UT 84108 Attn: S. Green A. Jones Technical Library	(3)	Defense Nuclear Agency Headquarters DNA Washington, DC Attn: STTL DDST SPSS	(3)
Texas A&M University College Station, TX 77843 Attn: J. Handin		Naval Surface Weapons Center Dahlgren Laboratory Dahlgren, VA 22448 Attn: M. Weiland T. Williams W. Wisherd Technical Library	(4)
Washington State University Department of Physics Pullman, WA 99164 Attn: G. Duvall		U. S. Department of Energy Division of Military Application Washington, DC 20545 Attn: Library	
Weidlinger Associates, Consulting Engineers 110 E. 59th Street New York, NY 10022 Attn: J. Wright M. Baron	(2)	University of New Mexico Albuquerque, NM 87106 Attn: G. Triandafilidis H. Southward	(2)
Air Force Armament Laboratory, AFSC Eglin AFB, FL 32542 Attn: J. Collins J. Osborne Technical Library	(3)	U. S. Army Ballistic Res. Laboratory Aberdeen Proving Ground, Maryland 21005 Attn: Technical Library E. Baicy	(2)
Air Force Weapons Laboratory, AFSC Albuquerque, NM Attn: M. Plamondon SUL	(2)	Massachusetts Institute of Technology Dept. of Earth and Planetary Sciences Cambridge, MA 02139 Attn: W. Brace	

DISTRIBUTION (cont'd):

Penetrator Study Team
Theoretical and Planetary
Studies Branch
Ames Research Center
Moffett Field, CA 94035
Attn: Maxwell B. Blanchard

Mail Stop 183B-365
Jet Propulsion Laboratory
4800 Oak Grove Drive
Pasadena, CA 91103
Attn: Geoffrey Briggs

California Institute of
Technology
Division of Earth and
Planetary Sciences
Pasadena, CA 91025
Attn: Dr. J. G. Wasserburg

Planetology Programs Manager
NASA Headquarters
Washington, DC 20546
Attn: D. H. Herman

Science Applications, Inc.
5005 Newport Dr., Suite 305
Rolling Meadows, IL 60008
Attn: John Niehoff

Space Systems Division
P. O. Box 92960 World Postal
Center
Los Angeles, CA 90009
Attn: Maj. Phillip A. Terry

Aerospace Corporation
P. O. Box 92957
Los Angeles, CA 90009
Attn: W. P. Thompson
R. L. Strickler

University of Rhode Island
Dept. of Ocean Engineering
Kingston, RI 02881
Attn: A. J. Silva

1760
4000

4340
4342
4342
4342
4360
4361
4361
4361
4443
4536
4536
5000

5500
5510
5520
5521
5522
5523
5523
5524
5524
5530
5531
5531
5532
5532
5533
5533
5533
5533
5541
5612
5620
5621
5621
5621
5621
5621
5640

W. F. Hartman
A. Narath
Attn: G. Yonas, 4200
R. Peurifoy, 4300
A. W. Snyder, 4400
E. H. Beckner, 4500
J. H. Scott, 4700
H. W. Schmitt
W. R. Reynolds
M. J. Forrestal
W. J. Patterson
J. A. Hood
E. M. Austin
R. C. Hartwig
R. P. Kutarnia
J. M. Parvin
P. Yarrington (5)
D. R. Anderson
D. M. Talbert
J. K. Galt
Attn: F. L. Vook, 5100
G. A. Samara, 5130
J. Schirber, 5150
R. S. Claassen, 5800
O. E. Jones
D. B. Hayes
T. B. Lane
S. W. Key
T. G. Priddy
R. C. Reuter
D. B. Longcope
R. T. Othmer
P. P. Stirbis
W. Herrmann
L. D. Bertholf
M. E. Kipp
B. M. Butcher
D. E. Grady
A. J. Chabai
T. K. Bergstresser
W. R. Davey
F. R. Norwood (30)
W. C. Luth
J. W. Keizur
M. M. Newsom
C. E. Dalton
M. M. Hightower
A. D. Foster
C. W. Young
E. C. Rightley
G. J. Simmons

DISTRIBUTION (cont'd):

8110	J. F. Barham	
8120	W. E. Alzheimer	
8266	Technical Library	(2)
3141	T. L. Werner	(5)
3151	W. L. Garner	(3)
	for DOE/TIC Unlimited Release	
3154-3	R. P. Campbell	(25)
	(For DOE/TIC)	

3151

Recipient must initial on classified documents.