**ENVIRONMENTAL
RESTORATION
PROGRAM****Identification of Groundwater-Producing
Fractures by Using an Electromagnetic
Borehole Flowmeter in Monitoring
Wells on the Oak Ridge
Reservation,
Oak Ridge, Tennessee**

**G. K. Moore
S. C. Young**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MANAGED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY

UCN-17560 (6 7-91)

ENERGY SYSTEMS

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from 615-576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

ORNL/ER--91

DE92 010873

Environmental Restoration Division
ORNL Environmental Restoration Program

**Identification of Groundwater-Producing Fractures by Using an
Electromagnetic Borehole Flowmeter in Monitoring Wells
on the Oak Ridge Reservation, Oak Ridge, Tennessee**

G. K. Moore
S. C. Young

Date Issued—March 1992

Prepared by
Environmental Sciences Division
Oak Ridge National Laboratory
ESD Publication 3857

Prepared for
U.S. Department of Energy
Office of Environmental Restoration and Waste Management
under budget and reporting code EW 20

OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37831-6285
managed by
MARTIN MARIETTA ENERGY SYSTEMS, INC.
for the
U.S. DEPARTMENT OF
under contract DE-AC05-84OR21400

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Author Affiliations

G. K. Moore is a research associate at The University of Tennessee, Knoxville. S. C. Young is a hydrologist with the Engineering Laboratory, Tennessee Valley Authority, Norris, Tennessee.

CONTENTS

FIGURES	v
TABLES	vii
EXECUTIVE SUMMARY	ix
INTRODUCTION	1
BACKGROUND	2
OPERATING PRINCIPLES	3
FLOWMETER DATA	5
DATA ANALYSIS AND INTERPRETATION	7
CONCLUSIONS	24
REFERENCES	26
APPENDIX—RECORDS OF ELECTROMAGNETIC BOREHOLE FLOWMETER SURVEYS ON PIEZOMETER WELLS AND COREHOLES	A-1

FIGURES

1	Typical borehole flowmeter surveys on piezometer wells	6
2	Cumulative probability graph showing fracture height or thickness of permeable fracture intervals in wells and coreholes	13
3	Hydrogeologic zones and directions of groundwater flow	15
4	Diagram showing geometry for calculation of orthogonal fracture spacing	16
5	Cumulative probability graph of transmissivity data for piezometer wells in Melton Valley	20
6	Cumulative probability graph of hydraulic conductivity data for permeable fractures in piezometer wells	21
7	Cumulative probability graph of fracture apertures	22

TABLES

1	Summary results of borehole flowmeter surveys and water table depths (depths are below top of inner casing)	9
2	Results from injection tests and flowmeter surveys (T_f is transmissivity, K is hydraulic conductivity, b is fracture aperture)	18
A.1	Records of borehole flowmeter surveys on piezometer wells near ORNL; flows produced by water injection	A-4
A.2	Records of borehole flowmeter surveys on piezometer wells near the Oak Ridge Y-12 Plant; flows produced by water injection	A-18
A.3	Records of borehole flowmeter surveys on coreholes near ORNL and the Oak Ridge Y-12 Plant	A-22

EXECUTIVE SUMMARY

The electromagnetic borehole flowmeter, newly developed by Tennessee Valley Authority, measures the flow of water up or down a well. These flows may be natural or may be induced by water pumping or water injection. The instrument is sensitive to a water velocity as small as 0.10 ft/min, and sequential flow rates within impermeable sections of the wells generally differ by <0.005 gallons per minute. The flowmeter data obtained on the Oak Ridge Reservation near Oak Ridge, Tennessee, have been used to select monitoring depths in newly constructed wells, to check the accuracy of screen depths in well-construction archives, to evaluate the potential for cross contamination (a flow of pollutants in a well from one level to another), to characterize permeable fractures, and to obtain information needed for numerical modeling of groundwater flow and contaminant transport.

Natural flows of water were detected in all long, open coreholes that were surveyed. These results show a potential for cross contamination. On the other hand, the flowmeter surveys of piezometer wells show that cross contamination is not a concern for screen lengths of 1.5–6.1 m, if the borehole annulus is sealed from the surface to the water table.

The flowmeter surveys have been interpreted to show that about 65% of the permeable intervals are <1.2 m thick and transmit water chiefly toward cross-cutting tributary streams. The other 35% of the permeable intervals are >1.2 m thick; these fractures occur only within 6 m of the water table and transmit water downslope to main-valley streams. Several previous studies have suggested that a large majority of all groundwater is transmitted to nearby streams in a thin, permeable zone at the water table. This hypothesis, however, was based only on logical reasoning and indirect evidence. The flowmeter results provide the first direct evidence for a difference in the fracture characteristics of the permeable zone near the water table and the fracture characteristics at deeper levels. Information on fracture spacing and on effective porosity is necessary for the modeling of matrix diffusion and sorption, as well as for calculations of contaminant velocity and concentration. A combination of results from borehole surveys and injection tests show that orthogonal fracture spacing is about 0.15–0.44 m near the water table and 0.44–0.73 m at deeper levels. Average effective fracture porosity is about 1.3×10^{-4} .

INTRODUCTION

This report describes the results of electromagnetic borehole flowmeter surveys taken on the Oak Ridge Reservation (ORR) with an instrument developed by the Engineering Laboratory of Tennessee Valley Authority (TVA). The borehole flowmeter can be used during water injection or pumping to determine the depth, vertical extent, and relative permeability of fractures that are intercepted by the wells. The flowmeter can also be used to measure any natural water flows, up or down an openhole interval, from one permeable fracture to another. These and other data have been used to select screen intervals or sampling ports in newly constructed wells on the ORR, to evaluate the potential for cross-contamination (the flow of dissolved pollutants from one level to another in a well or corehole), and to characterize permeable fractures and permeable intervals in wells.

Both English and metric units are used in this report. English units were used for well construction and for these archives; English units were also used for data collection during the flowmeter surveys. Some of these data would not be easily understood if the units were converted to the metric system. The calculated results of data analysis are presented in metric units.

BACKGROUND

As part of a groundwater research program in 1983-90, TVA evaluated various alternative, in situ methods for measuring the hydraulic conductivity of rocks in wells. The transmissivity of the entire screened or open-hole interval in a well can be measured with a pumping test, but these data provide no information on the relative permeability of layers within the interval. One conclusion of the studies was that borehole flowmeter measurements were the most promising and cost-effective method of determining relative permeability. Tests showed, however, that the best mechanical impeller has a sensitivity of only about 4.6 cm/s and that calibration is not constant because of wear and corrosion of the bearings. Two other types of borehole flowmeters were considered. One type uses a heated wire and measures the temperature drop between the wire and a thermistor. The other type releases a small amount of tracer and times the appearance of the tracer at a detector. Both alternative flowmeters have calibration problems in field use. TVA thus undertook the development of a sensitive electromagnetic borehole flowmeter with no moving parts.

The first prototype electromagnetic flowmeter was made by TVA in 1987, and the design and sensitivity were improved by field testing in the period 1987-90. The present model of the flowmeter has been extensively tested at various well fields in the southeastern United States and produces excellent results under nearly all field conditions. One of the present models has a sensitivity of 0.05 cm/s, nearly two orders of magnitude better than the impeller meter. Under the present interagency agreement between TVA and the U.S. Environmental Protection Agency, the commercial availability of the electromagnetic flowmeter is being expedited.

Oak Ridge National Laboratory (ORNL) has needed a sensitive borehole flowmeter for some years. The top of the first water-producing interval can generally be determined during well construction, but the bottom of this interval and deeper permeable intervals are commonly obscure. Also, the potential for cross-contamination was unknown, and information on fracture size, orientation, and spacing was needed for digital modeling of contaminant transport. Cooperative agreements between TVA and ORNL in FY 1990 and 1991 have been used for flowmeter surveys on about 70 wells on ORR, thereby testing the sensitivity and reliability of the instrument as well as obtaining useful data for the Environmental Restoration Program.

OPERATING PRINCIPLES

The borehole flowmeter consists of a metal cylinder about 8 in. long and about 2 in. in diameter with a center hole for water flow; the hole is 0.5 or 1.0 in. in diameter and is flared at the top and bottom to reduce turbulence. Two chloride electrodes contact the water in the center hole, and a magnetic coil is contained in the body of the cylinder. A multiconductor electrical cable is used to supply power to the coil and to carry the signal to the surface for processing. A flow of water through the center hole acts as a conductor, and the interaction of the conductor and the coil is measured as a voltage. The water must have some dissolved solids, but the constituents and concentrations of these solutes do not affect the measurements.

The flowmeter fits tightly in a 2-in.-ID (inside diameter) well casing, but for larger diameter wells, a packer is used to fill the annulus between the instrument and the casing or the borehole wall. The packer ensures that all vertical flows pass through the center hole in the flowmeter. The time for inflation and deflation of the packer is much longer than that for a flow measurement. Thus, about four well surveys per day were completed for 2-in.-ID wells with 5 to 20 ft of screen, but an entire day or longer was generally required for a survey of a 3- to 4-in. corehole with a long open interval.

The borehole flowmeter produces an absolute measurement of the flow rate up or down a well at a selected depth position; the relative change in flow between two depth positions indicates whether or not a pervious fracture occurs in the interval. If a well has no natural flow, flows are induced by pumping or injecting water. Measurements of flow are more reliable if water velocity is much larger than the minimum detectable signal. For this reason, it is desirable to select a water injection rate (or pumping rate) that is as large as possible. Most surveys were made by water injection, and the water level was raised to a point near the top of the inner casing or >10 ft above the static level, whichever was less.

The first task at a well, which has no natural flow, is to begin injection or pumping at a constant rate. In response to water injection, the water level rises, rapidly at first and then progressively more slowly with time. A nearly constant water level, which generally occurs after 15-30 min of injection, is indicative of a nearly steady water velocity at any depth in the well. These are the conditions needed for a reliable borehole flowmeter survey. In order to maintain the nearly constant water level and water velocity, the injection rate can be changed slightly during the flowmeter survey.

Perturbations in water velocity and instrument signal are produced by moving the flowmeter up or down the well. After positioning the instrument at a selected depth, it is necessary to wait 1-3 min for instrument readings to stabilize. The voltage signal is then sampled repetitively; the samples are averaged over a selected period of time; the average reading is converted to flow in gallons per minute; and the depth and flow rate are recorded in digital form and on paper. Some signals have little fluctuation and need to be averaged over only a 15- to 30-s interval. Noisy signals can be averaged for 30-60 s or longer. The variance of the signal can be recorded as can the flow rate in both gallons per minute and volts.

Natural flows within a well require head differences between permeable intervals. Differences of this type were not detected in screened intervals of 5-20 ft. However, all of the deep, open coreholes that were surveyed showed measurable natural flows (Appendix, Table A.3). In boreholes with long, open intervals, a survey for natural flows is recommended before beginning a survey that uses water injection or pumping.

Problems in conducting the flowmeter surveys were encountered at only two sites. Steady signals could not be obtained at Corehole 6 in the ORNL Main Plant area, apparently because of nearby high voltage lines. A similar problem at Corehole 9 near White Oak Creek resulted in an aborted survey on the first day and an incomplete survey on a second day; a third day was required to complete the survey.

FLOWMETER DATA

With one exception, all data acquired by the borehole flowmeter surveys are included in the Appendix of this report; data for well GW722 near Scarboro Road at the Oak Ridge Y-12 Plant are presently not available. Most data obtained in 1990 are reported to the nearest 0.01 gpm (gallon per minute). An improved instrument was used for the 1991 surveys, and these data are reported to the nearest 0.001 gpm. Most borehole surveys used depth spacings of 1–2 ft. However, spacings of 0.25–0.5 ft were used in some intervals where there were large changes in flow rate, and spacings of 5–20 ft were used in deep coreholes where there was little or no change in flow rate.

There are various possible sources for error in the measurement of borehole flow rates, and the precision of the data is difficult to quantify. One problem at a few locations was noisy data, probably caused by water turbulence or external electrical currents. Another possible problem is a bypass of water around the instrument. Water bypass can be caused by poor packer seals and by permeable pathways in fractures and sandpacks adjacent to the borehole. Despite the possible problems, many sequential flow rates within impermeable sections of the wells differ by <0.005 gpm, and wells with sandpacks generally show abrupt changes in the first derivative of flow rate at the top and bottom of permeable fractures (Appendix) rather than the gradual changes that would be expected for significant amounts of water bypass. The surveys also show nearly the same change of flow rate with depth (a nearly constant first derivative) within the permeable intervals of the wells (Fig. 1., bottom). These data characteristics indicate a good precision and a satisfactory accuracy for the flowmeter surveys.

Fig. 1. Typical borehole flowmeter surveys on piezometer wells.

DATA ANALYSIS AND INTERPRETATION

One use of the flowmeter data is a determination of the thickness (vertical extent) of permeable intervals for the selection of screen lengths or monitoring depths in new wells and for the checking of construction data for older wells. A flowmeter survey of well GW722 near the Y-12 Plant, for example, was to select the depths of sampling ports in a multiport monitoring well. The utility of this type of information is shown by a borehole flowmeter survey of piezometer well 703 at ORNL. Well 703 is screened at depths of 59–79 ft, but the flowmeter survey shows that the only permeable interval occurs at depths of 75–77.5 ft (Fig. 1, top); about 90% of the screen is ineffective. Also, for example, the archival data for piezometer well 575 indicate a well screen at depths of 10–15 ft; the borehole flowmeter survey shows that the screen occurs at depths of 6–11 ft and that the only permeable interval occurs at depths of 6–8 ft (Fig. 1, middle). The other flowmeter surveys showed that well construction depths are correct or have errors of <2.0 ft.

Another use of the borehole flowmeter is the measurement of natural flows in deep coreholes. Flows between widely spaced intervals are caused by differences in potentiometric head. The flowmeter survey of corehole 2, for example, shows downward flow from a permeable interval above a depth of 20 ft to a permeable interval at 20–30 ft as well as upward flow from an interval below 120 ft to a permeable interval at 76–77 ft (Appendix, Table A.3). These flowmeter data also suggest a permeable fracture in the interval 40–50 ft; this fracture may be a sink for both upward and downward flows.

The permeability of a fracture is assumed to be constant. Potentiometric head, however, may change with time. The flowmeter surveys on corehole 9 (Appendix, Table A.3) show 2–3 times more flow up the corehole on October 16 than on November 5, 1991. Also, the survey of November 5 shows permeable fractures in the interval 190–220 ft and at 221–223 ft; these fractures are not apparent in the earlier survey. If both survey results are correct, potentiometric heads in the fractures on October 16 were nearly the same as those in the borehole at both levels.

The borehole flowmeter surveys show that packers are required to obtain reliable water samples from selected depths in long, open boreholes; otherwise, some of the water in the samples may come from different levels. The results also show a potential for cross-contamination in these boreholes. Conversely, natural flows were not detected in piezometer wells with screen lengths of 5–20 ft; cross-contamination is not a concern for these wells if they are sealed from the surface to the water table.

Borehole flowmeter data also provide some information about the number, size, orientation, and spacings of the fractures that produce the permeable intervals. The nearly constant first derivative of flow rate within a permeable interval probably indicates a single fracture with a uniform hydraulic conductivity. Previous fractures, as is shown later, have a range of about three orders of magnitude in hydraulic conductivity; it is very unlikely that multiple fractures would produce a constant change in flow rate across each of many permeable intervals. However, other data or observations are needed to confirm this interpretation.

Permeable fractures transmit groundwater to discharge locations in the streams. Where referenced to the groundwater system, water flows in the direction of fracture length, aperture is gap width, and the third dimension, for the purposes of this report, is termed fracture height. For a single fracture, hydraulic conductivity is determined by aperture, and transmissivity is the product of hydraulic conductivity and fracture height. In this context, the vertical extent of a permeable interval in a well is approximately equal to the height of the fracture in a hydrologic section that is orthogonal to the direction of groundwater flow.

The height of fractures in wells and coreholes has a range of 0.8–11.5 ft (Table 1). A cumulative probability graph (Fig. 2) shows that these data are lognormally distributed. The geometric mean of the heights is 2.2 ft, and the range from the mean minus one to the mean plus one standard deviation is 0.9–4.8 ft. The abrupt changes in the first derivative of flow rate at the ends of a permeable interval probably indicate that the fracture terminates at bedding planes.

As shown by the data below, the heights of permeable fractures >20 ft below the water table generally are smaller than those of fractures <10 ft below the water table.

Depth below water table (ft)	Number of fractures	Geometric mean	Fracture height (ft)	
			Mean minus one standard deviation	Mean plus one standard deviation
0–10	56	2.8	1.4	5.6
>20	38	1.6	1.0	2.5

Although the difference in fracture heights is not statistically significant, nearly all fractures heights of >3 ft occur near the water table. About 40% of permeable fractures within 10 ft of the water table have heights of 4–10 ft, but only 5% of the fractures >20 ft below the water table have a height of 4 ft, and none are higher. Processes that could result in higher permeable fractures at shallow depths include unloading stress, slump on hillslopes, earth tides, and volume changes produced by dissolution.

Nearly all flowmeter surveys were run on wells in the Conasauga Group. A recent geologic study in these areas documented four fracture sets with average strikes and dips of N5°E and 88°NW, N60°E and 55°NW, N30°W and 88°SW, and N65°W and 80°SW. The strikes and dips of these sets are somewhat variable, and for the purposes of this paper, the sets are grouped into (1) fractures that have north-south and northwest-southeast trends and dips of 70°–90° and (2) fractures that have northeast-southwest trends and dips of 45°–65°.

Table 1. Summary results of borehole flowmeter surveys and water table depths (depths are below top of inner casing)

Well	Number of fractures	Fracture depth (ft)	Permeability fraction ^a	Water table depth (ft)
531	2	60-63	0.75	3-6
		70-71	0.25	
575	1	6-8	1.0	3-7
636	2	39-42	0.82	29-35
		43-54	0.18	
637	2	54-56	0.24	53-58
		62-64	0.76	
638	1	57.5-59	1.0	46-50
639	1	56-57.5	1.0	46-48
641	1	45.5-47	1.0	25-31
668	2	11-13	0.79	5-9
		13-15	0.21	
669	1	7.5-8.5	1.0	5-9
703	1	75-77.5	1.0	30-34
705	1	19-27	1.0	14-20
739	1	25-27.5	1.0	14-17
740	1	15-24.5	1.0	18-22
741	1	15-21	1.0	13-16
743	1	15-23	1.0	16-21
747	1	16-24	1.0	9-11
748	1	14.5-23.5	1.0	10-12
749	2	14-16	0.15	14-15
		18-21	0.85	
756	1	18-20.5	1.0	7-11
757	2	12-16	0.21	5-8
		16-22	0.79	
758	1	14-23	1.0	7-9
759	2	14-15.5	0.54	5-7
		20-23	0.46	
760	1	14-23	1.0	6-9

Table 1 (continued)

Well	Number of fractures	Fracture depth (ft)	Permeability fraction ^a	Water table depth (ft)
765	1	68-72	1.0	4-7
766	1	10-13.5	1.0	4-8
767	1	38-40	1.0	1-4
768	1	7-15	1.0	6-9
774	1	8-10	1.0	2-6
775	2	39-40	0.63	3-7
		40-42	0.37	
777	1	37-38	1.0	8-12
779	2	39-41	0.81	2-4
		41-43	0.19	
781	2	29-33	0.22	3-7
		33-35	0.78	
782	1	12-14	1.0	3-8
783	1	28-29	1.0	2-8
790	1	39-41	1.0	38-42
904	1	41-44	1.0	8-11
905	1	36-37.5	1.0	20-28
1053	2	26-28	0.84	19-24
		33-35	0.16	
1055	2	16-17	0.84	14-16
		17-21	0.16	
1058	3	46-48	0.22	13-16
		51-52	0.11	
		53-54	0.67	
1060	2	13-15	0.22	7-9
		20-22	0.78	
1062	2	23-24	0.30	21-24
		24-31	0.70	
1118	1	8-12	1.0	5-11
1119	2	24.5-27	0.59	5-11

Table 1 (continued)

Well	Number of fractures	Fracture depth (ft)	Permeability fraction ^a	Water table depth (ft)
		30.5-33	0.41	
1121	2	8.5-9.5	0.62	2-5
		9.5-11.5	0.38	
1122	3	38-41	0.20	
		41-42.5	0.63	
		44-46	0.17	
1126	2	48-49.5	0.80	12-18
		56-57	0.20	
1127	2	17.5-19	0.54	13-20
		20.2-21	0.46	
1128	2	46-52	0.89	21-48
		56-57	0.11	
1129	2	32-33	0.22	20-27
		35.5-36.5	0.78	
GW477A	1	56.5-58.5	1.0	
GW477B	2	23.5-25	0.46	
		25-32	0.54	
GW477C	1	14-16	1.0	
GW484	2	15.5-18	0.58	
		22-24	0.42	
GW486	2	10-11	0.14	
		15-20	0.86	
GW487	2	10-16	0.29	
		16-20	0.71	
GW488	2	10-12	0.09	
		15-19	0.91	
GW491	2	10-11	0.24	
		14-20	0.76	
GW496	1	7-9	1.0	
GW499C	1	11-13	1.0	

Table 1 (continued)

Well	Number of fractures	Fracture depth (ft)	Permeability fraction*	Water table depth (ft)
GW499D	1	9-12	1.0	
GW499E	1	11-15	1.0	
GW499I	1	7-11	1.0	
GW499N	1	11-15	1.0	
CH2	3	20-30	0.33	
		76-77	0.28	
		>120	0.39	
CH3	2	7-12	0.50	
		>240	0.50	
CH9	4	134-135		
		169-171		
		221-223		
		338-339		
CH12	3	30-31	0.44	
		302-304	0.41	
		>310-<315	0.15	
WOL2	5	55-56		
		58-59		
		60-61		
		>140-<160		
		>220-<240		
GW404	3	124-125		
		135-137		
		>160-<170		

*Relative permeability of each fracture in a well.

Fig. 2. Cumulative probability graph showing fracture height or thickness of permeable fracture intervals in wells and coreholes.

Because the piezometer wells have an average diameter of 6.5 in., fractures with dips of 45° – 65° would have heights of 0.5–1.2 ft in the flowmeter surveys, and fractures with dips $>70^{\circ}$ would have heights >1.5 ft. Based on this geometry, the flowmeter results show that about 20% of the fractures have dips of 45° – 65° (northeast-southwest trends), about 65% of the fractures have dips of 70° – 90° (north-south or northwest-southeast trends), and about 15% of the fractures cannot be explained. This interpretation is unlikely. Previous studies have shown that water level drawdown patterns are elongated in the northeast-southwest direction during pumping tests and that a tracer arrives first in a well that is northeast or southwest of the injection well (e.g., Davis et al. 1984, p. 81). These previous studies show that most permeable fractures have northeast-southwest trends.

As noted above, fractures <4.0 ft high occur both near the water table and at deeper levels, whereas fractures >4.0 ft high only occur within 20 ft of the water table. An alternative explanation of the flowmeter results is that fractures <4.0 ft high have northeast-southwest trends and that higher fractures have north-south or northwest-southeast trends. If this hypothesis is correct, about 65% of the permeable fractures have northeast-southwest trends and dips of 45° – 82° . About 35% of the permeable fractures have north-south or northwest-southeast trends and dips of $>82^{\circ}$. Also, if fractures with northeast-southwest trends are equally abundant in the permeable zone near the water table and in deeper permeable intervals, the spatial frequency of all permeable fractures may be nearly twice as large near the water table as at deeper levels. As shown later, however, the transmissivity and hydraulic conductivity of fractures near the water table are about the same as at somewhat deeper levels.

The permeable fractures with northeast-southwest trends are probably stratiform; the fractures occur within a single layer or the same several layers, and the fracture network, which includes a few cross-cutting or intersecting fractures, has the same strike and dip as do the rock layers. This network transmits water mainly toward cross-cutting tributary streams; some groundwater also flows downdip and then seeps upward through the nearly impermeable rock matrix to discharge locations in main-valley streams (Fig. 3). The permeable fractures with north-south and northwest-southeast trends are not stratiform and thus transmit groundwater downslope to main-valley streams. The flowmeter results suggest that nearly all groundwater flows to main-valley streams occur in a thin zone near the water table, as was first suggested by Webster (1976, pp. 16–17) and Webster and Bradley (1988, p. 29).

The orthogonal spacing of fractures within permeable intervals can be estimated from the thickness of matrix (relatively impermeable) intervals in wells and from fracture dips (Fig. 4). The geometric mean of matrix thickness in wells with two or more permeable fractures is 1.6 ft; this value may be a minimum because some wells that intercept only one fracture might have intercepted two fractures if the screen had been longer. The geometric mean of matrix thickness for the thickest matrix interval in all wells is 2.8 ft; this value may be a maximum because some wells would not have intercepted a second fracture with a longer screen. If the thickness of matrix intervals is 1.6–2.8 ft, well diameter is 6.5 in., and fracture dip is 45° – 90° , orthogonal fracture spacing has a range of 0.5–2.4 ft; the steeply dipping, higher fractures have the closest spacing.

Dip Section

Strike Section

NOT TO SCALE

Fig. 3. Hydrogeologic zones and directions of groundwater flow.

Fig. 4. Diagram showing geometry for calculation of orthogonal fracture spacing.

About 30% of the wells intercept two or more fractures within a single permeable interval. In this group of 28 wells, about 30% (8 wells) intercept 1 fracture higher than 4.0 ft, and about 30% (8 wells, including 2 wells that intercept 3 fractures) intercept the fractures >20 ft below the water table. These results indicate that (1) average fracture spacing may increase with depth but some fractures are closely spaced at deeper levels, (2) some wells intercept both one fracture with a northeast-southwest trend and one fracture with a north-south or northwest-southeast trend, and (3) none of the wells intercept two fractures with north-south or northwest-southeast trends.

The flowmeter surveys show that the vertical distance between permeable intervals in coreholes ranges from about 10 to 250 ft, but these data are too few and variable for a reliable determination of mean distance. Analyses of drillers' logs and comparisons of completion depths in paired shallow and deeper wells show that the geometric mean of the vertical distances between permeable intervals is 33 ft in Melton Valley (Moore 1988, p. 46) and 40 ft in Bear Creek Valley (unpublished data). Additional data in the latter area show that the geometric mean of the difference in the depths of well pairs increases from about 20 ft near the water table to about 120 ft below a depth of 200 ft. These results are probably typical of conditions on ORR.

If two or more permeable fractures occur in a well, the relative flow rate measured during a borehole survey is a measure of the relative permeability of each fracture (Table 1). However, the maximum flow rate during the borehole survey is only approximately correlated with the transmissivity of the fractures. Thus, additional information can be obtained from injection tests (reverse pumping tests). Although it is possible to combine a flowmeter survey and an injection test, more accurate and more reliable data can be obtained from separate tests. As is described below, the hydraulic conductivity of each permeable fracture can be calculated from a transmissivity value obtained from an injection test and a measurement of fracture height obtained from a borehole flowmeter survey. Fracture aperture can be calculated from these data and an estimate of orthogonal fracture spacing.

Hydraulic conductivity values in Table 2 are calculated as

$$K = \frac{T}{h} \quad (1)$$

where K is hydraulic conductivity, T is transmissivity, and h is fracture height. If more than one permeable interval occurs in a well, the separate transmissivity of each interval was first calculated from

$$T = T_i (f)$$

where T_i is total transmissivity of the screened interval and f is the permeability fraction in Table 1.

Table 2. Results from injection tests and flowmeter surveys (T is transmissivity, K is hydraulic conductivity, and b is fracture aperture)

Well	Fracture depth (ft)	Fracture height (m)	T (m ² /d)	K (m/d)	b (m)
668	11-13	0.61	0.028	0.045	6.9×10^{-5}
	13-15	0.61	0.0074	0.0012	4.4×10^{-5}
669	7.5-8.5	0.30	0.026	0.085	8.5×10^{-5}
739	25-27.5	0.76	0.31	0.41	1.4×10^{-4}
741	15-21	1.83	0.37	0.20	1.1×10^{-5}
747	16-24	2.44	0.081	0.033	6.2×10^{-5}
748	14.5-23.5	2.74	0.12	0.044	6.8×10^{-5}
749	14-16	0.61	0.011	0.017	5.0×10^{-5}
	18-21	0.91	0.060	0.066	7.8×10^{-5}
756	18-20.5	0.76	1.7	2.2	2.5×10^{-4}
757	12-16	1.22	0.029	0.024	5.6×10^{-5}
	16-22	1.83	0.11	0.060	7.6×10^{-5}
758	14-23	2.74	0.023	0.0084	3.9×10^{-5}
759	14-15.5	0.46	0.16	0.35	1.4×10^{-4}
	20-23	0.91	0.14	0.15	1.0×10^{-4}
760	14-23	2.74	0.15	0.055	7.4×10^{-5}
766	10-13.5	1.07	0.20	0.19	1.1×10^{-4}
767	38-40	0.61	0.027	0.044	6.8×10^{-5}
768	7-15	2.44	0.023	0.0094	4.1×10^{-5}
774	8-10	0.61	3.6	5.9	3.5×10^{-4}
775	39-40	0.30	0.076	0.25	1.2×10^{-4}
	40-42	0.61	0.044	0.073	8.1×10^{-5}
777	37-38	0.30	0.0096	0.031	6.1×10^{-5}
779	39-41	0.61	0.18	0.29	1.3×10^{-4}
	41-43	0.61	0.042	0.069	7.9×10^{-5}
781	29-33	1.22	0.040	0.032	6.1×10^{-5}
	33-35	0.61	0.14	0.23	1.2×10^{-4}
782	12-14	0.61	0.33	0.51	1.5×10^{-4}
783	28-29	0.30	0.12	0.39	1.4×10^{-4}
904	41-44	0.91	1.3	1.4	2.2×10^{-4}
905	36-37.5	0.46	0.11	0.24	1.2×10^{-4}
1118	8-12	1.22	0.069	0.057	7.4×10^{-5}
1119	24.5-27	0.76	0.17	0.22	1.2×10^{-4}
	30.5-33	0.76	0.11	0.15	1.0×10^{-4}
1121	8.5-9.5	0.30	0.19	0.62	1.6×10^{-4}
	9.5-11.5	0.61	0.11	0.19	1.1×10^{-4}
1122	38-41	0.91	0.026	0.029	5.9×10^{-5}
	41-42.5	0.46	0.082	0.18	1.1×10^{-4}
	44-46	0.61	0.022	0.036	6.4×10^{-5}
1126	48-49.5	0.46	0.35	0.77	1.8×10^{-4}
	56-57	0.30	0.088	0.29	1.3×10^{-4}
1127	17.5-19	0.46	0.13	0.28	1.3×10^{-4}
	20.2-21	0.24	0.11	0.45	1.5×10^{-4}
1128	46-52	1.83	0.098	0.053	7.3×10^{-5}
	56-57	0.30	0.012	0.040	6.6×10^{-5}
1129	32-33	0.30	0.016	0.054	7.3×10^{-5}
	35.5-36.5	0.30	0.057	0.19	1.1×10^{-4}

The cubic law, which is a form of Darcy's law for flow in a Hele-Shaw (parallel plate) model, can be stated as

$$Q = KIA = \left(\frac{gb^2}{12\nu} \right) I(bh) \quad (2)$$

where Q is flow rate, I is hydraulic gradient, A is cross-sectional area, g is acceleration of gravity, b is fracture aperture, and ν is kinematic viscosity of water (Snow 1968, pp.79-80). For a flow rate in cubic meters per day, the acceleration of gravity is 7.32×10^{10} m/d², and kinematic viscosity at the average groundwater temperature (58°F) is 0.100 m²/d. Thus,

$$Q = 6.07 \times 10^{10} b^3 Ih \quad (3)$$

For a hydrologic section, the flow through an equivalent continuum (ideal aquifer) is

$$Q = KIhs \quad (4)$$

where s is fracture spacing. If average fracture spacing is 0.44 m, which is the middle of the estimated range, Eqs. (3) and (4) produce

$$6.07 \times 10^{10} b^3 Ih = 0.44KIh \quad (5)$$

$$b = (7.24 \times 10^{-12} K)^{\frac{1}{3}} \quad (m) \quad (6)$$

Equation (5) was used to calculate the values for fracture aperture in Table 2.

The geometric mean of transmissivity for permeable fractures is 0.084 m²/d, and the range from the mean minus one to the mean plus one standard deviation is 0.023–0.31 m²/d. The data below show that the transmissivity of the fractures is nearly the same at depths of 2.1–17 m; other studies have shown that fracture permeability decreases below a depth of 20–30 m (Moore 1988, pp. 53-55), for example.

Depth to fracture top (m)	Number of values	Geometric mean	Transmissivity (m^2/d)	
			Mean minus one standard deviation	Mean plus one standard deviation
2.1-6.1	22	0.096	0.022	0.43
6.1-12	16	0.072	0.027	0.19
12-17	11	0.079	0.021	0.30

About 65% of the piezometer wells have screens 3.0 m long; the other wells have a screen 1.5, 4.6, or 6.1 m long. The geometric mean of transmissivity for the screen intervals is $0.24 \text{ m}^2/\text{d}$, and the range from the mean minus one to the mean plus one standard deviation is $0.054\text{--}1.1 \text{ m}^2/\text{d}$ (Fig. 5). The average transmissivity of the screen interval is larger than that of the permeable fractures because some wells intercept more than one fracture.

ORNL DWG 91Z-16879

Figure 5. Cumulative probability graph of transmissivity data for piezometer wells in Melton Valley.

The geometric mean of hydraulic conductivity for the permeable fractures is 0.12 m/d, and the range from the mean minus one to the mean plus one standard deviation is 0.025–0.57 m/d (Fig. 6). The data below show that the hydraulic conductivity of the fractures is nearly the same at depths of 2.1–17 m. However, the average hydraulic conductivity of the fractures may be smaller at deeper levels.

Depth to fracture top (m)	Number of values	Geometric mean	Hydraulic conductivity (m/d)	
			Mean minus one standard deviation	Mean plus one standard deviation
2.1–6.1	22	0.099	0.018	0.55
6.1–12	16	0.14	0.052	0.37
12–17	11	0.14	0.037	0.53

Fig. 6. Cumulative probability graph of hydraulic conductivity data for permeable fractures in piezometer wells.

The data below show that the average hydraulic conductivity is nearly the same for fracture heights up to about 0.91 m, but average hydraulic conductivity decreases for higher fractures. Average transmissivity increases with fracture height up to a height of about 0.9 m but is nearly constant or decreases slightly for higher fractures. These results show that average aperture is smaller for fractures higher than about 0.9 m, and that, given the same hydraulic gradient, the average groundwater flow rate in fractures higher than about 0.9 m is nearly the same, regardless of fracture height. This conclusion, however, is based on few data and cannot be explained.

Fracture height (m)	Number of values	Geometric mean of hydraulic conductivity (m/d)	Geometric mean of transmissivity (m^2/d)
0.24-0.30	10	0.15	0.046
0.30-0.61	26	0.15	0.066
0.61-0.91	20	0.15	0.10
0.91-1.22	8	0.087	0.091
>1.22	8	0.038	0.086

Fracture aperture data (Table 2) are lognormally distributed (Fig. 7). The geometric mean is 9.5×10^{-5} m, and the range from the mean minus one to the mean plus one standard deviation is 5.7×10^{-5} to 1.6×10^{-4} m. The calculations for these data, however, assumed an orthogonal fracture spacing of 0.44 m, whereas the range was estimated to be 0.15-0.73 m. As noted previously, the range in hydraulic conductivity of permeable fractures, from the geometric mean minus one to the mean plus one standard deviation, is 0.025-0.58 m/d. Based on these data, the likely range in fracture aperture [Eq. (5)] is about 4.0×10^{-5} m to 1.9×10^{-4} m.

Fig. 7. Cumulative probability graph of fracture apertures.

If permeable fractures are the only part of the rock mass that drains by gravity, the specific yield, S_y , of a permeable interval can be calculated as

$$S_y = \frac{b}{s} \quad (6)$$

The data below show that the likely range in the specific yield of the permeable intervals is 9.2×10^{-5} to 7.5×10^{-4} .

Fracture spacing, s (m)	Hydraulic conductivity, K (m/d)	Aperture, b (m)	Specific yield, S_y
0.73	0.023	6.7×10^{-5}	9.2×10^{-5}
0.44	0.12	9.5×10^{-5}	2.1×10^{-4}
0.15	0.58	1.1×10^{-4}	7.5×10^{-4}

For comparison, Moore (1991, p. 9) used hydrograph analysis to calculate an average specific yield of 2.3×10^{-3} for a layer about 1.5 m thick at the water table. This comparison indicates that either (1) drainage from the regolith (including delayed drainage) contributes to the specific yield of the permeable layer near the water table or (2) fractured rock and regolith <1.5 m below the water table have a larger specific yield than do permeable intervals at deeper levels. A specific yield near the top of the calculated range is more likely than a lower value for the permeable layer near the water table because fractures with both northeast-southwest and north-south or northwest-southeast trends may produce a spatial fracture frequency about twice as large as in deeper permeable intervals. At deeper levels, as noted previously, some fractures are closely spaced, but average spacing may be larger, and the specific yield may be in the lower half of the calculated range.

CONCLUSIONS

The electromagnetic borehole flowmeter produces an absolute measurement of flow rate up or down a well at a selected depth position; the relative change in flow rate between two depth positions indicates whether or not a pervious fracture occurs in the interval. If a well has no natural flow, which is caused by a difference in the potentiometric heads of permeable intervals at different levels, flows are induced by water pumping or water injection. The latest model of the flowmeter can measure a water velocity as low as 0.05 cm/s, and many sequential flow rates within impermeable intervals differ by <0.02 L/min. Typical flowmeter surveys show a nearly constant flow rate in a matrix interval, a nearly constant first derivative of flow rate in a permeable interval, and abrupt changes in the first derivative of flow rate at the top and bottom of permeable intervals.

Results of flowmeter surveys conducted on ORR have been used to select screen lengths or monitoring depths in newly constructed wells, to check the accuracy of information on screen depths in well-construction archives, to evaluate the potential for cross-contamination in piezometer wells and long, open coreholes, and to characterize permeable intervals in the fractured rocks. The flowmeter surveys show a potential for cross-contamination in long, open coreholes, but also show that cross-contamination is not a concern for wells with screen lengths of 1.5–6.1 m if the borehole annulus of these wells is sealed from the surface to the water table.

Permeable intervals in the wells represent permeable fractures in the rocks. Groundwater flows in the direction of fracture length, hydraulic conductivity is determined by fracture aperture, and transmissivity is the product of hydraulic conductivity and fracture height. The nearly constant first derivative of flow rate within a permeable interval is interpreted to indicate that each permeable interval consists of a single fracture, that the vertical extent of a permeable interval in a well is approximately equal to fracture height, and that each permeable fracture has a uniform hydraulic conductivity. These interpretations, however, have not yet been confirmed by other data or by observations of rock cores.

The flowmeter surveys show that fractures are 0.24–3.5 m high; the geometric mean of fracture height is 0.67 m. Fractures >1.2 m high occur only within 6.1 m of the water table, whereas fractures <1.2 m high occur both near the water table and at deeper levels. The shorter fractures (65% of the total) have dips of 45° – 82° and probably transmit water chiefly toward cross-cutting tributary streams. The higher fractures (35% of the total) have dips of $>82^{\circ}$ and probably transmit groundwater downslope toward main-valley streams. The thicknesses of matrix intervals in the flowmeter surveys show that orthogonal fracture spacing is about 0.15–0.73 m; the steeply dipping fractures apparently have the closest spacings.

The effective porosity, specific yield, hydraulic conductivity, and transmissivity of the permeable fractures can be calculated from a combination of a borehole flowmeter survey and an injection test or a pumping test. The geometric mean of transmissivity for permeable fractures is 0.084 m/d, and the geometric mean of hydraulic conductivity is 0.12 m/d. Average hydraulic conductivity and transmissivity are nearly the same between depths of 2.1–17 m, but probably are smaller at deeper levels. Average hydraulic conductivity is nearly the same for fracture heights of <0.9 m, but decreases as fracture height increases beyond this point. Given the same hydraulic gradient, average groundwater flow rates in fractures higher than

0.9 m may be nearly the same regardless of fracture height.

The geometric mean of fracture aperture is 9.5×10^{-5} . For a fracture spacing of 0.15–0.73 m, the specific yield of a permeable interval is likely to be in the range 9.2×10^{-5} to 7.5×10^{-4} . Within 6 m of the water table, average specific yield is probably in the upper half of this range because more fractures occur at these levels. At deeper levels, some fractures are closely spaced, but the average specific yield may be in the lower half of the calculated range.

The data, analyses, and interpretations in this report should be useful for modeling of groundwater flow and contaminant transport. The flowmeter survey results also provide the first direct evidence for a difference in fracture characteristics (spacing, orientation, and height) of the permeable zone near the water table as compared with those at deeper levels.

REFERENCES

- Davis, E. C., W. J. Boegly, Jr., E. R. Rothschild, B. P. Spalding, N. D. Vaughan, C. S. Haase, D. D. Huff, S. Y. Lee, E. C. Walls, J. D. Newbold, and E. D. Smith. 1984. Site characterization techniques used at a low-level waste shallow land burial field demonstration facility. ORNL/TM-9146. Oak Ridge National Laboratory.
- Moore, G. K. 1988. Concepts of groundwater occurrence and flow near Oak Ridge National Laboratory, Tennessee. ORNL/TM-10969. Oak Ridge National Laboratory.
- Moore, G. K. 1991. Hydrograph analysis in a fractured rock terrane near Oak Ridge, Tennessee. ORNL/ER-45. Oak Ridge National Laboratory.
- Snow, D. T. 1968. Rock fracture spacings, openings, and porosities. J. Soil Mech. Found. Div., Proc. Am. Soc. Civ. Eng. vol. 94, pp. 73-91.
- Webster, D. A. 1976. A review of hydrologic and geologic conditions related to radioactive solid-waste burial grounds at Oak Ridge National Laboratory, Tennessee. U.S. Geol. Surv. Open-File Rep. 76-727, Nashville, Tennessee.
- Webster, D. A., and M. W. Bradley. 1988 burial grounds at Oak Ridge National Laboratory, Tennessee. U.S. Geol. Surv. Open-File Rep. 87-686, Nashville, Tennessee.

APPENDIX

RECORDS OF ELECTROMAGNETIC BOREHOLE FLOWMETER SURVEYS ON PIEZOMETER WELLS AND COREHOLES

The data in Tables A.1-A.3 were acquired in 1990-91 in cooperation with the Engineering Laboratory of Tennessee Valley Authority by the Oak Ridge Reservation Hydrology and Geology Study Project and the ORNL Environmental Restoration Program. The English units in the tables are those used for data collection. ORNL and Y-12 Plant coordinates are in feet. Flow rates are in gallons per minute; positive values indicate downward flows, and negative values are upward flows. The measure point for depth is the top of the inner casing; subtract the measure point correction for depth below land surface. Some records do not extend to the bottom of the well screen because of a restriction; some records start above the top of the well screen for quality assurance purposes.

Table A.1. Records of borehole flowmeter surveys on piezometer wells near ORNL; flows produced by water injection

	Depth (ft)	Flow (gpm)
Well No.: 531	59	0.05
Location: 21,967 N; 28,555 E	60	0.05
Screen interval: 60-75 ft	61	0.03
Measure point correction: 0.09 ft	62	0.03
	63	0.02
	64	0.02
	65	0.02
	66	0.02
	67	0.02
	68	0.02
	69	0.02
	70	0.02
	71	0.01
	72	0.01
	73	0.01
Well No.: 575	5	0.22
Location: 23,234 N; 31,699 E	6	0.22
Screen interval: 6-11 ft	7	0.07
Measure point correction: -0.12 ft	8	0.01
	9	0.01
	10	0.01
	11	0.01
Well No.: 636	39	0.104
Location: 17,668 N; 24,326 E	40	0.094
Screen interval: 40-55 ft	41	0.059
Measure point correction: 1.68 ft	42	0.025
	43	0.026
	45	0.023
	46	0.020
	47	0.015
	49	0.014
	51	0.012
	53	0.009
	55	0.007
Well No.: 637	46	0.076
Location: 17,715 N; 24,136 E	48	0.076
Screen interval: 51-68 ft	50	0.075
Measure point correction: 2.18 ft	52	0.074
	54	0.078
	56	0.057
	58	0.054
	60	0.058
	62	0.057

Table A.1 (continued)

	Depth (ft)	Flow (gpm)
	63	0.018
	64	0.000
	66	0.000
	68	0.000
Well No.: 638	54	0.071
Location: 17,495 N; 24,119 E	55	0.071
Screen interval: 57-72 ft	56	0.074
Measure point correction: 1.51 ft	57	0.068
	57.5	0.073
	58	0.019
	59	0.004
	60	0.000
	62	0.000
	64	0.000
	66	0.000
	68	0.000
	70	0.000
	72	0.002
Well No.: 639	50	0.240
Location: 17,395 N; 24,138 E	52	0.245
Screen Interval: 49-60 ft	54	0.248
Measure point correction: 1.59	56	0.248
	56.25	0.206
	56.5	0.158
	56.75	0.104
	57	0.046
	57.5	0.017
	58	0.014
	59	0.004
Well No.: 641	44	0.193
Location: 17,383 N; 23,985 E	45	0.196
Screen Interval: 45-60 ft	45.5	0.182
Measure point correction: 2.00 ft	46	0.171
	46.5	0.095
	47	0.004
	48	0.000
	50	0.000
	52	0.000
	54	0.000
	56	0.000
	58	0.000
	59	0.000

Table A.1 (continued)

	Depth (ft)	Flow (gpm)
Well No.: 668	9	0.037
Location: 17,417 N; 28,436 E	10	0.038
Screen Interval: 10-15 ft	11	0.037
Measure point correction: 1.41 ft	12	0.030
	13	0.010
	14	0.005
	15	0.003
Well No.: 669	5	0.032
Location: 17,389 N; 28,408 E	6	0.034
Screen Interval: 5-10 ft	7	0.033
Measure point correction: 1.87 ft	7.5	0.033
	8	0.026
	8.5	0.019
	9	0.018
	10	0.018
	11	0.018
Well No.: 703	56	0.83
Location: 22,376 N; 24,917 E	58	0.80
Screen Interval: 59-79 ft	60	0.86
Measure point correction: -0.16 ft	62	0.86
	64	0.92
	66	0.93
	68	0.90
	70	0.95
	71	0.96
	72	0.97
	73	0.98
	74	0.97
	75	0.89
	76	0.43
	77	0.07
	78	0.00
	79	0.00
Well No.: 705	17	0.06
Location: 21,837 N; 24,548 E	18	0.06
Screen interval: 18-28 ft	19	0.06
Measure point correction: -0.25 ft	20	0.05
	21	0.04
	22	0.04
	23	0.03
	24	0.02
	25	0.01
	26	0.01
	27	0.00

Table A.1 (continued)

	Depth (ft)	Flow (gpm)
	28	0.00
Well No.: 739	23	0.233
Location: 15,629 N; 23,604 E	24	0.237
Screen interval: 24-34 ft	24.5	0.234
Injection rate: 1.32 ft	25	0.228
	25.5	0.165
	26	0.146
	26.5	0.114
	27	0.055
	27.5	0.018
	28	0.014
	29	0.011
	30	0.010
	31	0.008
	32	0.006
	33	0.000
	34	0.000
Well No.: 740	15	0.214
Location: 15,779 N; 23,372 E	16	0.197
Screen interval: 15-25 ft	17	0.182
Measure point correction: 1.71 ft	18	0.173
	19	0.162
	20	0.137
	21	0.124
	22	0.099
	23	0.073
	24	0.040
	24.5	0.009
Well No.: 741	13	1.236
Location: 15,597 N; 23,353 E	14	1.229
Screen interval: 13-23 ft	15	1.268
Measure point correction: 1.10 ft	16	0.961
	17	0.871
	18	0.825
	19	0.458
	20	0.348
	21	0.056
	22	0.025
	23	0.000
Well No.: 743	13	0.36
Location: 15,098 N; 23,249 E	14	0.37
Screen interval: 17-27 ft	15	0.36

Table A.1 (continued)

	Depth (ft)	Flow (gpm)
Measure point correction: 1.71 ft	16	0.29
	17	0.28
	18	0.25
	19	0.19
	20	0.10
	21	0.07
	22	0.02
	23	0.00
	24	0.00
Well No.: 747	13	0.155
Location: 15,488 N; 25,065 E	14	0.152
Screen interval: 15-25 ft	15	0.155
Measure point correction: 1.92 ft	16	0.149
	17	0.139
	18	0.125
	19	0.122
	20	0.115
	21	0.095
	22	0.095
	22.5	0.082
	23	0.053
	24	0.032
Well No.: 748	13	0.223
Location: 15,891 N; 25,535 E	14	0.219
Screen interval: 14-24 ft	14.5	0.213
Measure point correction: 1.27 ft	15	0.172
	16	0.147
	17	0.147
	18	0.134
	19	0.105
	20	0.081
	21	0.071
	22	0.069
	23	0.037
	23.5	0.017
Well No.: 749	11	0.130
Location: 16,315 N; 26,039 E	12	0.131
Screen interval: 14-24 ft	13	0.132
Measure point correction: 1.45 ft	14	0.129
	15	0.119
	16	0.110
	17	0.108
	18	0.105
	18.5	0.056
	19	0.033

Table A.1 (continued)

	Depth (ft)	Flow (gpm)
	20	0.015
	21	0.002
	22	0.007
	23	0.000
Well No.: 756	13	0.214
Location: 16,661 N; 30,292 E	14	0.216
Screen interval: 13-23 ft	15	0.212
Measure point correction: 1.27 ft	16	0.205
	17	0.202
	18	0.196
	18.5	0.166
	19	0.139
	19.5	0.122
	20	0.052
	21	0.004
	22	0.003
	23	0.000
Well No.: 757	12	0.160
Location: 16,830 N; 31,230 E	13	0.153
Screen interval: 13-23 ft	14	0.142
Measure point correction: 1.85 ft	15	0.131
	16	0.126
	16.5	0.102
	17	0.096
	17.5	0.063
	18	0.046
	19	0.028
	20	0.013
	21	0.010
	22	0.000
Well No.: 758	11	0.050
Location: 16,686 N; 31,230 E	12	0.047
Screen interval: 13-23 ft	13	0.047
Measure point correction: 1.46 ft	14	0.047
	15	0.038
	16	0.028
	17	0.026
	18	0.018
	19	0.011
	20	0.005
	21	0.003
	22	0.001
	23	0.000
Well No.: 759	10	0.238

Table A.1 (continued)

	Depth (ft)	Flow (gpm)
Location: 16,559 N; 31,165 E	11	0.242
Screen interval: 13-23 ft	12	0.241
Measure point correction: 2.16 ft	13	0.243
	14	0.238
	14.5	0.161
	15	0.142
	15.5	0.113
	16	0.118
	17	0.115
	18	0.111
	19	0.107
	20	0.098
	21	0.064
	21.5	0.037
	22	0.022
	23	0.000
Well No.: 760	12	0.208
Location: 16,377 N; 31,073 E	13	0.204
Screen interval: 13-23 ft	14	0.202
Measure point correction: 1.08 ft	15	0.181
	15.5	0.164
	16	0.163
	17	0.121
	17.5	0.107
	18	0.100
	19	0.092
	19.5	0.088
	20	0.082
	21	0.050
	21.5	0.032
	22	0.019
	23	0.001
Well No.: 765	60	0.03
Location: 21,924 N; 37,043 E	62	0.04
Screen interval: 62-72 ft	64	0.04
Measure point correction: 1.94 ft	66	0.03
	68	0.04
	69	0.02
	70	0.02
	71	0.02
	72	0.00

Table A.1 (continued)

	Depth (ft)	Flow (gpm)
Well No.: 766	9	0.188
Location: 16,857 N; 29,429 E	10	0.191
Screen interval: 10-15 ft	10.5	0.175
Measure point correction: 1.57 ft	11	0.134
	11.5	0.107
	12	0.082
	12.5	0.042
	13	0.022
	14	0.000
	15	0.000
Well No.: 767	28	0.050
Location: 16,859 N; 29,444 E	30	0.048
Screen interval: 31-41 ft	32	0.049
Measure point correction: 1.81 ft	34	0.046
	36	0.047
	38	0.046
	39	0.009
	40	0.001
	41	0.002
Well No.: 768	5	0.034
Location: 16,646 N; 29,500 E	6	0.034
Screen interval: 6-16 ft	7	0.035
Measure point correction: 1.75 ft	8	0.030
	9	0.024
	10	0.018
	11	0.017
	12	0.009
	13	0.003
	14	0.001
	15	0.000
Well No.: 774	7	0.224
Location: 18,046 N; 28,685 E	8	0.223
Screen interval: 7-12 ft	8.5	0.175
Measure point correction: 1.31 ft	9	0.080
	9.5	0.020
	10	0.001
	11	0.000
Well No.: 775	35	0.118
Location: 18,026 N; 28,681 E	36	0.119
Screen interval: 37-47 ft	37	0.138
Measure point correction: 1.19 ft	38	0.108
	39	0.123
	40	0.045

Table A.1 (continued)

	Depth (ft)	Flow (gpm)
	41	0.017
	42	0.006
Well No.: 777	37	0.019
Location: 17,963 N; 28,879 E	38	0.011
Screen interval: 40-50 ft	39	0.021
Measure point correction: 1.65 ft	40	0.011
	41	0.011
	42	0.007
	43	0.008
Well No.: 779	35	0.039
Location: 16,957 N; 27,184 E	36	0.043
Screen interval: 38-48 ft	37	0.040
Measure point correction: 0.74 ft	38	0.034
	39	0.038
	40	0.028
	41	0.002
	42	0.000
	43	0.000
Well No.: 781	29	0.147
Location: 16,823 N; 27,295 E	30	0.142
Screen interval: 30-40 ft	31	0.127
Measure point correction: 2.00 ft	32	0.123
	33	0.114
	34	0.064
	35	0.005
	36	0.003
Well No.: 782	11	0.160
Location: 16,672 N; 27,367 E	12	0.167
Screen interval: 12-17 ft	13	0.079
Measure point correction: 1.98 ft	14	0.007
	15	0.004
	16	0.002
Well No.: 783	27	0.058
Location: 16,681 N; 27,388 E	28	0.067
Screen interval: 28-38 ft	29	0.013
Measure point correction: 1.94 ft	30	0.011
	31	0.009
Well No.: 790	37	0.69
Location: 21,462 N; 24,944 E	38	0.72
Screen interval: 39-49 ft	39	0.72
Measure point correction: 1.83 ft	40	0.33
	41	0.02
	42	0.02

Table A.1 (continued)

	Depth (ft)	Flow (gpm)
	43	0.00
	44	0.00
	45	0.00
	46	0.00
	47	0.00
	48	0.00
Well No.: 904	35	0.23
Location: 21,844 N; 37,305 E	36	0.23
Screen interval: 37-47 ft	37	0.24
Measure point correction: 1.86 ft	38	0.23
	39	0.24
	40	0.23
	41	0.24
	42	0.12
	43	0.06
	44	0.01
	45	0.01
	46	0.01
	47	0.01
Well No.: 905	32	0.22
Location: 21,607 N; 37,304 E	33	0.21
Screen interval: 34-44 ft	34	0.22
Measure point correction: 1.89 ft	35	0.21
	36	0.20
	37	0.03
	38	0.01
	39	0.01
	40	0.01
	41	0.01
	42	0.01
	43	0.01
	44	0.01
Well No.: 1053	22	0.245
Location: 15,045 N; 21,234 E	23	0.254
Screen interval: 25-35 ft	24	0.249
Measure point correction: 1.58 ft	25	0.260
	26	0.275
	27	0.219
	28	0.038
	29	0.036
	30	0.041
	31	0.040
	32	0.036
	33	0.041
	34	0.011

Table A.1 (continued)

	Depth (ft)	Flow (gpm)
	35	0.002
Well No.: 1055	13	0.204
Location: 15,693 N; 21,534 E	14	0.270
Screen interval: 14-24 ft	15	0.262
Measure point correction: 1.49 ft	16	0.270
	17	0.042
	18	0.031
	19	0.031
	20	0.011
	21	0.005
	22	0.008
	23	0.003
	24	0.000
Well No.: 1058	43	0.212
Location: 15,304 N; 21,543 E	44	0.210
Screen interval: 46-56 ft	45	0.209
Measure point correction: 2.11 ft	46	0.217
	47	0.175
	48	0.164
	49	0.163
	50	0.168
	51	0.168
	52	0.141
	53	0.150
	54	0.014
	55	0.017
Well No.: 1060	10	0.043
Location: 15,466 N; 21,782 E	11	0.045
Screen interval: 13-23 ft	12	0.045
Measure point correction: 2.03 ft	13	0.044
	14	0.041
	15	0.038
	16	0.038
	17	0.038
	18	0.037
	19	0.037
	20	0.035
	21	0.020
	22	0.009
Well No.: 1062	20	0.174
Location: 15,552 N; 22,372 E	21	0.175
Screen interval: 22-32 ft	22	0.173
Measure point correction: 2.11 ft	23	0.174
	23.5	0.135

Table A.1 (continued)

	Depth (ft)	Flow (gpm)
	24	0.122
	25	0.114
	26	0.086
	27	0.057
	28	0.049
	29	0.047
	30	0.037
	31	0.015
Well No.: 1118	5	0.147
Location: 15,839 N; 36,180 E	6	0.148
Screen interval: 6-11 ft	7	0.147
Measure point correction: 1.80 ft	8	0.143
	9	0.127
	10	0.103
	11	0.069
	12	0.011
Well No.: 1119	21	0.385
Location: 15,818 N; 36,175 E	22	0.386
Screen interval: 22-32 ft	23	0.387
Measure point correction: 2.15 ft	24	0.387
	25	0.342
	26	0.197
	27	0.170
	28	0.163
	29	0.161
	30	0.161
	30.5	0.160
	31	0.143
	31.5	0.113
	32	0.073
	33	0.036
Well No.: 1121	7	0.194
Location: 15,532 N; 35,919 E	8	0.204
Screen interval: 9-14 ft	9	0.160
Measure point correction: 1.80 ft	9.5	0.076
	10	0.059
	10.5	0.047
	11	0.019
	12	0.006
	12.5	0.002
	13	0.000
Well No.: 1122	34	0.090
Location: 15,527 N; 35,936 E	35	0.089
Screen interval: 36-46 ft	36	0.088

Table A.1 (continued)

	Depth (ft)	Flow (gpm)
Measure point correction: 2.16 ft	37	0.090
	38	0.088
	39	0.081
	40	0.080
	41	0.072
	41.5	0.043
	42	0.021
	43	0.015
	44	0.016
	45	0.007
	46	0.000
Well No.: 1126	45	0.225
Location: 15,230 N; 36,403 E	46	0.226
Screen interval: 47-57 ft	48	0.216
Measure point correction: 2.25 ft	48.5	0.107
	49	0.098
	49.5	0.054
	50	0.045
	51	0.046
	52	0.045
	53	0.045
	54	0.045
	55	0.044
	56	0.041
	57	0.003
Well No.: 1127	12	0.245
Location: 15,238 N; 36,599 E	13	0.237
Screen interval: 12-22 ft	14	0.234
Measure point correction: 2.11 ft	15	0.232
	16	0.230
	17	0.227
	18	0.194
	19	0.131
	20	0.109
	20.5	0.103
	21	0.066
Well No.: 1128	45	0.180
Location: 15,243 N; 36,619 E	46	0.176
Screen interval: 47-57 ft	48	0.152
Measure point correction: 1.98 ft	49	0.105
	50	0.103
	51	0.091
	51.5	0.068
	52	0.024
	53	0.017

Table A.1 (continued)

	Depth (ft)	Flow (gpm)
	54	0.018
	55	0.017
	56	0.016
	57	0.000
Well No.: 1129	30	0.232
Location: 15,189 N; 36,838 E	31	0.229
Screen interval: 29-39 ft	32	0.231
Measure point correction: 2.26 ft	32.5	0.215
	33	0.202
	34	0.197
	35	0.193
	35.5	0.186
	36	0.136
	36.5	0.033
	36.75	0.055
	37	0.031
	38	0.022
	39	0.013
	40	0.013

Table A.2. Records of borehole flowmeter surveys on piezometer wells near the Oak Ridge Y-12 Plant; flows produced by water injection

	Depth (ft)	Flow (gpm)
Well No.: GW 477A	54	0.046
Location: 29,920 N; 30,739 E	55	0.047
Screen interval: 55-65 ft	56	0.046
Measure point correction: 1.80 ft	57	0.042
	57.5	0.014
	58	0.005
	59	0.000
	60	0.000
	61	0.000
	62	0.000
	63	0.000
	64	0.000
	65	0.000
	66	0.000
Well No.: GW 477B	21	0.116
Location: 29,920 N; 30,739 E	22	0.121
Screen interval: 21.5-31.5 ft	23	0.117
Measure point correction: 2.42 ft	24	0.109
	24.5	0.082
	25	0.065
	26	0.055
	27	0.049
	28	0.043
	29	0.041
	30	0.032
	31	0.020
	32	0.005
	32.5	0.000
	33	0.000
Well No.: GW 477C	12	0.026
Location: 29,920 N; 30,739 E	13	0.031
Screen interval: 6-16 ft	14	0.027
Measure point correction: 3.06 ft	15	0.007
	16	0.000
	17	0.000
	18	0.000
	19	0.000

Table A.2 (continued)

	Depth (ft)	Flow (gpm)
Well No.: GW 484	13	0.111
Location: 29,912 N; 30,752 E	14	0.113
Screen interval: 12-22 ft	15	0.100
Measure point correction: 2.22 ft	15.5	0.115
	16	0.080
	17	0.061
	18	0.052
	19	0.048
	20	0.046
	21	0.052
	22	0.047
	23	0.034
	24	0.000
Well No.: GW 486	9	0.183
Location: 29,909 N; 30,714 E	10	0.185
Screen interval: 7-17 ft	11	0.162
Measure point correction: 3.31 ft	13	0.160
	14	0.159
	15	0.155
	16	0.142
	17	0.118
	18	0.080
	19	0.037
	20	0.000
Well No.: GW 487	9	0.242
Location: 29,914 N; 30,709 E	10	0.242
Screen interval: 8-18 ft	11	0.217
Measure point correction: 2.27 ft	12	0.211
	13	0.211
	14	0.192
	15	0.176
	16	0.172
	16.5	0.158
	17	0.128
	17.5	0.104
	18	0.048
	19	0.013
	20	0.000

Table A.2 (continued)

	Depth (ft)	Flow (gpm)
Well No.: GW 488	8	0.134
Location: 29,902 N; 30,711 E	10	0.136
Screen interval: 6.3-16.3	12	0.123
Measure point correction: 3.67 ft	14	0.123
	15	0.121
	16	0.107
	17	0.076
	18	0.031
	19	0.004
	20	0.000
Well No.: GW 491	9	0.151
Location: 29,915 N; 30,694 E	10	0.158
Screen interval: 6.5-16.5 ft	11	0.124
Measure point correction: 3.57 ft	12	0.123
	13	0.119
	14	0.114
	15	0.110
	16	0.080
	17	0.064
	18	0.036
	19	0.002
	20	0.000
Well No.: GW 496	5.0	0.017
Location: 29,918 N; 30,639 E	5.5	0.019
Screen length: 3 ft	6.0	0.021
Measure point correction: 2.65 ft	6.5	0.020
	7.0	0.020
	8.0	0.008
	8.5	0.004
	9.0	0.000
Well No.: GW 499C	9.0	0.313
Location: 29,890 N; 30,642 E	9.5	0.319
Screen length: 5 ft	10.0	0.323
Measure point correction: 2.95 ft	10.5	0.343
	11.0	0.311
	11.5	0.151
	12.0	0.071
	12.5	0.029
	13.0	0.015
	14.0	0.010
	15.0	0.001

Table A.2 (continued)

	Depth (ft)	Flow (gpm)
Well No.: GW 499D	8.0	0.186
Location: 29,883 N; 30,639 E	8.5	0.187
Screen length: 5 ft	9.0	0.179
Measure point correction: 3.37 ft	9.5	0.144
	10.0	0.110
	10.5	0.089
	11.0	0.068
	11.5	0.036
	12.0	0.001
	13.0	0.000
Well No.: GW 499E	9.0	0.159
Location: 29,875 N; 30,636 E	10.0	0.158
Screen length: 5 ft	11.0	0.164
Measure point correction: 3.14 ft	11.5	0.139
	12.0	0.129
	12.5	0.125
	13.0	0.107
	13.5	0.083
	14.0	0.054
	14.5	0.035
	15.0	0.021
Well No.: GW 499I	7	0.090
Location: 29,910 N; 30,666 E	8	0.067
Screen length: 5 ft	9	0.051
Measure point correction: 2.34 ft	10	0.042
	11	0.010
Well No.: GW 499N	9	0.125
Location: 29,913 N; 30,680 E	10	0.115
Screen length: 5 ft	11	0.122
Measure point correction: 2.95 ft	12	0.087
	13	0.080
	14	0.023
	15	0.000

Table A.3. Records of borehole flowmeter surveys on coreholes near ORNL and the Oak Ridge Y-12 Plant

	Depth (ft)	Flow (gpm)
Well No.: Corehole 2	20	0.049
Location: ORNL Main Plant	22	0.037
Screen interval:	24	0.029
Measure point correction:	26	0.018
Type: Natural flow in corehole	28	0.016
	29	0.012
	30	0.006
	32	0.009
	35	0.002
	40	0.014
	45	-0.017
	50	-0.030
	55	-0.026
	60	-0.027
	70	-0.015
	75	-0.037
	76	-0.025
	77	-0.091
	78	-0.091
	80	-0.088
	82	-0.089
	84	-0.089
	86	-0.089
	88	-0.086
	90	-0.087
	100	-0.089
	110	-0.088
	120	-0.088
Well No.: Corehole 2	40	0.103
Location: ORNL Main Plant	50	0.095
Screen interval:	51	0.110
Measure point correction:	52	0.046
Type: Water injection	60	0.048
	70	0.019

Table A.3 (continued)

	Depth (ft)	Flow (gpm)
Well No.: Corehole 3	7	0.000
Location: ORNL Main Plant	8	-0.089
Screen interval:	9	-0.366
Measure point correction:	10	-0.353
Type: Natural flow in corehole	11	-0.146
	12	-0.509
	13	-0.508
	14	-0.510
	15	-0.517
	30	-0.517
	100	-0.513
	140	-0.515
	180	-0.517
	240	-0.521
Well No.: Corehole 9	20	0.000
Location: ORNL Main Plant	30	0.000
Screen interval: 15-404 ft	40	-0.003
Measure point correction: 2.12 ft	50	0.000
Type: Natural flow in corehole 10/16/91	60	-0.005
	70	-0.007
	80	-0.004
	90	-0.006
	100	-0.005
	120	-0.004
	130	-0.006
	134	-0.007
	135	-0.118
	136	-0.120
	138	-0.119
	140	-0.127
	150	-0.135
	160	-0.123
	170	-0.117
	180	-0.150
	200	-0.153
	220	-0.154
	240	-0.159
	260	-0.160
	280	-0.161
	300	-0.159
	320	-0.159
	340	-0.008

Table A.3 (continued)

	Depth (ft)	Flow (gpm)
Well No.: Corehole 9	140	-0.041
Location: ORNL Main Plant	150	-0.046
Screen interval: 15-404 ft	170	-0.061
Measure point correction: 2.12 ft	180	-0.057
Type: Natural flow in corehole 11/15/91	190	-0.052
	220	-0.034
	221	-0.035
	223	-0.087
	225	-0.086
	240	-0.084
	260	-0.093
	280	-0.084
	300	-0.087
	320	-0.093
	325	-0.089
	330	-0.089
	335	-0.090
	338	-0.089
	339	-0.007
	340	-0.003
	345	-0.002
Well No.: Corehole 12	20	0.000
Location: ORNL Main Plant	25	-0.004
Open interval: 15-490 ft	30	-0.003
Measure point correction: 3.40 ft	31	-0.078
Type: Natural flow in corehole 11/6-7/91	32	-0.081
	40	-0.081
	60	-0.092
	80	-0.091
	100	-0.093
	120	-0.096
	140	-0.099
	160	-0.114
	180	-0.118
	200	-0.123
	220	-0.124
	240	-0.120
	260	-0.119
	280	-0.104
	300	-0.107
	302	-0.105
	304	-0.028
	306	-0.028

Table A.3 (continued)

	Depth (ft)	Flow (gpm)
Well No.: Corehole 12	308	-0.028
Location: ORNL Main Plant	310	-0.028
Open interval: 15-490 ft	315	-0.002
Measure point correction: 3.40 ft	320	-0.002
Type: Natural flow in corehole 11/6-7/91	330	-0.003
Well No.: Corehole WOL 2	54	0.013
Location: White Oak Dam	56	0.004
Open interval:	58	0.004
Measure point correction:	60	-0.012
Type: Natural flow in corehole 11/7/91	62	-0.031
	70	-0.027
	75	-0.031
	80	-0.032
	85	-0.032
	90	-0.032
	100	-0.034
	110	-0.035
	120	-0.034
	125	-0.035
	130	-0.031
	135	-0.033
	140	-0.029
	150	-0.021
	160	-0.14
	170	-0.016
	180	-0.015
	190	-0.012
	200	-0.013
	220	-0.011
	240	-0.007
	260	-0.005
Well No.: Corehole WOL 2	39	0.316
Location: White Oak Dam	40	0.380
Open interval:	41	0.314
Measure point correction:	43	0.301
Type: Water injection 5/17/91	45	0.359
	50	0.346
	55	0.360
	56	0.307
	57	0.315
	58	0.320
	59	0.241
	60	0.259
	61	0.149
	63	0.151
	65	0.154

Table A.3 (continued)

	Depth (ft)	Flow (gpm)
	70	0.149
	100	0.130
	130	0.096
	150	0.065
	170	0.052
	190	0.029
Well No.: GW 404	30	0.073
Location: 29,870 N; 30,636 E	40	0.071
Open interval:	50	0.071
Measure point correction:	60	0.072
Type: Water pumping	70	0.075
	80	0.072
	90	0.067
	100	0.074
	105	0.067
	110	0.062
	123	0.068
	124	0.074
	125	0.033
	135	0.035
	137	0.019
Well No.: GW 404	100	0.124
Location: 29,870 N; 30,636 E	110	0.095
Open interval:	123	0.095
Measure point correction:	130	0.034
Type: Water pumping	139	0.015
	150	0.012
	160	0.011
	170	0.000
	180	0.000

DISTRIBUTION

1. H. L. Adair
2. T. L. Ashwood
3. L. V. Asplund/N. W. Durfee
4. L. D. Bates
5. F. P. Baxter
6. H. L. Boston
7. T. W. Burwinkle
8. R. B. Clapp
9. K. W. Cook
10. J. H. Cushman
11. M. F. P. Delozier
12. R. B. Dreier
13. D. E. Fowler
14. C. W. Francis
15. B. J. Frederick
16. H. R. Gaddis
17. S. B. Garland II
18. C. W. Gehrs
19. C. D. Goins
20. D. F. Hall
21. S. G. Hildebrand
22. D. D. Huff
23. P. Kanciruk
24. P. M. Kearl
25. R. H. Ketelle
26. N. E. Korte
27. A. J. Kuhaida
28. V. Legg
29. P. J. Lemiszki
30. W. M. McMaster
- 31-35. G. K. Moore
36. J. B. Murphy
37. R. Nativ
38. C. E. Nix
- 39-40. P. T. Owen
41. D. E. Reichle
42. C. Rightmire
43. P. A. Rubin
44. G. E. Rymer
45. T. F. Scanlan
46. P. A. Schrandt
47. F. E. Sharples
48. L. A. Shevenell
49. D. S. Shriner
50. D. K. Solomon
51. B. P. Spalding
52. S. H. Stow
53. D. W. Swindle
54. L. E. Toran
55. J. R. Trabalka
56. S. D. Van Hoesen
57. R. I. Van Hook
58. L. D. Voorhees
59. D. R. Watkins
60. J. S. Watson
61. R. K. White
62. D. S. Wickliff
63. T. Zondlo
64. Central Research Library
- 65-69. ER Document Management Center
- 70-74. ESD Library
- 75-76. Laboratory Records Department
77. ORNL Patent Section
78. Office of Assistant Manager for Energy Research and Development, Oak Ridge Field Office, P.O. Box 2001, U.S. Department of Energy, Oak Ridge, TN 37831-8600
79. P. H. Edmonds, Radian Corporation, 120 S. Jefferson Circle, Oak Ridge, TN 37830
80. J. F. Franklin, Bloedel Professor of Ecosystem Analysis, College of Forest Resources, University of Washington, Anderson Hall (AR-10), Seattle, WA 98195
81. G. M. Hornberger, Professor, Department of Environmental Sciences, University of Virginia, Charlottesville, VA 22903
82. G. Y. Jordy, Director, Office of Program Analysis, Office of Energy Research, ER-30, G-226, U.S. Department of Energy, Washington, DC 20545
83. J. R. Kannard, Program Manager, Bechtel National, Inc., P.O. Box 350, Oak Ridge Corporate Center, 151 Lafayette Drive, Oak Ridge, TN 37830
- 84-87. W. E. Murphie, Department of Energy, Office of Environmental Restoration, Eastern Area D&D Branch, EM-423 (GTN), Washington, DC 20545
88. R. H. Olsen, Vice President for Research, University of Michigan, Medical Science Building II, #5605, 1301 East Catherine Street, Ann Arbor, MI 48109-0620

- 89. A. Patrinos, Acting Director, Environmental Sciences Division, Office of Health and Environmental Research, ER-74, U.S. Department of Energy, Washington, DC 20585
- 90-91. S. S. Perkins, DOE Oak Ridge Field Office, Information Resource Center, 105 Broadway, Oak Ridge, TN 37830
- 92-93. S. P. Riddle, DOE Oak Ridge Field Office, P.O. Box 2001, Oak Ridge, TN 37831-8541
- 94-95. R. C. Sleeman, DOE Oak Ridge Field Office, P.O. Box 2001, Oak Ridge, TN 37831-8541
- 96. W. Waldrop, TVA Engineering Laboratory, P.O. Drawer E, Norris, Tennessee 37828
- 97. F. J. Wobber, Environmental Sciences Division, Office of Health and Environmental Research, ER-74, U.S. Department of Energy, Washington, DC 20585
- 98-102. S. C. Young, TVA Engineering Laboratory, P.O. Drawer E, Norris, Tennessee 37828
- 103-104. Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831

END

**DATE
FILMED**

5 / 7 / 92