DOE/ER/40033--13

DE82 005518

Rockefeller University
Report No. DOE/ER/40033-13

(RU 81/A-12)

DEVELOPMENT AND PERFORMANCE OF A HIGH-PRESSURE
HYDROGEN TIME-PROJECTION CHAMBER

Thomas J. Chapin, Rodney L. Cool, Konstantin Goulianios,
Jerome P. Silverman, Gregory R. Snow, Harry Sticker,
and Sebastian N. White

The Rockefeller University, New York, NY 10021 USA

and

Yue-Hua Chou

Institute of High Energy Physics
Beijing, The People's Republic of China

Reported by: Thomas J. Chapin

MASTER

DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Presented at
The IEEE Nuclear Science Symposium
San Francisco, California
October 21-23, 1981

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

MGW

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

DEVELOPMENT AND PERFORMANCE OF A HIGH PRESSURE HYDROGEN TIME PROJECTION CHAMBER

Thomas J. Chapin, Rodney L. Cool, Konstantin Goulianos,
Jerome P. Silverman, Gregory R. Snow, Harry Sticker,
and Sebastian N. White

The Rockefeller University, New York, NY 10021 USA

and

Yue-Hua Chou

Institute of High Energy Physics
Beijing, The People's Republic of China

SUMMARY

We describe a high pressure hydrogen gas time projection chamber (TPC) which is presently operating at Fermilab both as target and as recoil detector in an experiment investigating the diffraction dissociation of photons on hydrogen, $\gamma p \rightarrow Xp$. The TPC, which consists of two cylindrical drift regions each 45 cm in diameter and 75 cm long, measures the polar angle and the energy loss dE/dx of the recoil protons. Typically, at 15 atm of H_2 with 2 kV/cm drift field and 7 kV on the 35 μ sense wires, the drift velocity is about 0.5 cm/ μ sec and the spatial resolution $\pm 200\mu$.

INTRODUCTION

We have been using a high pressure hydrogen filled time projection chamber (TPC) in a Fermilab experiment (E-612) which is investigating the diffraction dissociation of photons on hydrogen, $\gamma p \rightarrow Xp$. In this paper we present details on construction and performance of the chamber and describe briefly the experiment for which it was designed.

The chamber acts both as target and as track detector of recoil protons. It is used to measure the polar angle, θ , and dE/dx of protons with $10 < T < 50$ MeV and $45^\circ < \theta < 90^\circ$. The energy of protons is determined by stopping them in plastic scintillation counters located inside the high pressure vessel.

The experiment is operating in Fermilab's tagged photon beam ($20 \leq p_\gamma \leq 170$ GeV/c) which provides a flux of $1-2 \times 10^6$ tagged photons per pulse with a momentum resolution of $\pm 2\%$. The variables t and M_X^2 are determined from the measured quantities p_γ , T and θ as follows:

$$t = -2M_p T$$

$$M_X^2 = 2p_\gamma \sqrt{|t|} (\cos\theta - \sqrt{|t|}/2M_p)$$

Fig. 1 shows the mass spectrum expected from 50 GeV photons. A pressurized target and good detector coverage are needed to obtain a useful event rate. Good mass resolution is essential to the study of the resonances. A $\Delta M_X^2/M_X^2 = \pm 0.03$ may be obtained in the region $0.05 < M_X^2/s < 0.1$ with $\Delta t = 0.002$ (GeV/c) 2 and $\Delta\theta = 5$ mr. The latter is limited by multiple coulomb scattering in the target-detector combination. For this reason, a liquid target would be inadequate and a low Z drift chamber gas is desirable. The TPC that we have built is a target-detector combination that satisfies these requirements.

TREAD (The Recoil Energy and Angle Detector)

The recoil detector consists of two identical endcap assemblies mounted on a 26" I.D. x 84" long stainless steel tube. A schematic drawing is shown in Fig. 2. The vessel may be pressurized up to 20 atm

FIG. 1 - Missing mass spectrum expected from 50 GeV photons.

with hydrogen. The beam enters through a 2" dia. x 0.030" thick hemispherical beryllium window. Recoil protons from interactions of the beam with the hydrogen are stopped in 1 1/8" thick scintillation counters placed 9" away from the axis inside the high pressure vessel. The energy of the protons is determined from the counter pulse heights. Particles penetrating these counters register on anti-counters. The photon dissociation products exit through an 8" dia. x 0.080" thick aluminum window (not shown in the figure).

The ionization electrons generated along the path of the recoil proton drift along axial electric field lines towards a ground plate where they are detected by a set of concentric octagonal sense wires. Typically, at 15 atm of hydrogen with $E = 2$ kV/cm drift field the drift velocity is 0.5 cm/ μ sec. The sense wires and associated electronics record the time and measure the amount of the ionization as it arrives. Time differences between sense wires are then translated into polar angles and pulse heights into dE/dx . From dE/dx and T (recoil energy measured by pulse-height counters) the mass of the recoil may be calculated.

FIG. 2a - TREAD.

FIG. 2b - TPC sense wire arrangement.

Because the drift velocity of electrons in hydrogen is a function of the ratio of E to the gas density, angle measurements of the required accuracy demand tolerances on the electric field, temperature and pressure on the order of 0.1%. The temperature is maintained constant by an automatically controlled heating jacket surrounding the vessel. A pressure transducer controlled with preset limits activates input and exhaust solenoid valves to keep the pressure within tolerances. In practice, allowing the gas to leak at a constant rate maintains the pressure within 0.01 psi of the low set limit. Finally, the electric field is kept uniform by two "cages" of field-shaping concentric metal rings. The outer cage consists of 48 rings made of 1/8" copper wire and connected by a bleeder chain of 48 x 100 M Ω metal film resistors. These rings are insulated from the wall of the vessel by a 1/2" thick polyethylene tube. The thickness of the wire was chosen to prevent corona discharge. Since the inner cage is located in an already uniform electric field, thin (0.002" diameter) wires were used for its construction.

The sense wires which are stainless steel or nichrome (35 μ diameter) operate at 6.4 to 8 kV. They are located in the centers of 1/4" square grooves machined on the face of a 1/2" thick aluminum plate. With this arrangement, a track segment approximately equal to the width of the groove is focused onto each sense wire.

The drift time and gain stability of the TPC are monitored by ^{244}Cm α -sources positioned so as to leave ionization tracks directly over one wire of each sense wire plate. ZnS scintillation counters detect the α particles and provide a zero-time reference for drift velocity monitoring. Drift velocity measurements obtained in this manner are shown in Fig. 3 along with other measurements performed at lower pressures¹⁾. We find that drift velocities scale as E/p to $\pm 2\%$ over this pressure range.

FIG. 3 - Drift velocity vs. E/p .

SENSE WIRE GAIN

The sense wire gain in hydrogen was measured, prior to building TREAD, in a simple proportional counter consisting of an anode wire stretched along

the axis of an 0.5" I.D. aluminum cylinder. Measurements were carried out with 20 μ and 50 μ diameter sense wires at pressures from 5 to 15 atm. We have calculated the sense wire gain by integrating the first Townsend coefficient, α ,

$$\ln G = \int_{r_1}^{r_2} \alpha(r) dr$$

from the anode (r_1) to the cathode (r_2) using a simple approximation for α suggested by low pressure measurements²⁾:

$$\alpha/p = 5.1 \exp(-139 p/E(r)) \text{ cm}^{-1} \cdot \text{torr}^{-1}$$

where p/E is expressed in $\text{torr} \cdot \text{cm}^{-1}$. Our measurements agree well with the pressure and voltage dependence of the gain predicted in this manner. This is illustrated in Fig. 4 which shows a comparison with our measurements at a gain of 10^4 .

The maximum gain in the test counter and in TREAD was found to be in the range $2-5 \times 10^4$, essentially independent of sense wire diameter and gas pressure.

FIG. 4 - Voltage vs. pressure at a fixed gain of 10^4 .

ELECTRON ATTACHMENT

Our gas purification system (Fig. 5) was designed primarily to remove oxygen impurities, since O_2 is expected to be the main electro-negative contaminant in the chamber. The chamber gas is recirculated at a rate of 3 volumes/hr. It passes through a "Deoxo" palladium catalyst which combines H_2 and O_2 to form water molecules which are subsequently absorbed in a 4A $^\circ$ molecular sieve. Under steady state conditions, we find that the pulse height attenuation with drift time is characterized by a decay constant of 1.8 msec. Using available data on three-body attachment³⁾ to O_2 impurities in H_2 , this decay constant implies an

FIG. 5 - The hydrogen purification system.

oxygen level of < 1 part in 10^8 :

SPATIAL RESOLUTION

Fig. 6 shows the r.m.s. deviation of the drift time measured on a typical wire from fits to cosmic ray tracks passing through the axis of the chamber. Also shown is a fit of the form

$$\sigma^2 = \sigma_0^2 + \sigma_1^2 \cdot \left(\frac{Z}{1\text{cm}}\right)$$

where $\sigma_0 = 123 \pm 5 \mu\text{m}$ and $\sigma_1 = 22 \pm 1 \mu\text{m}$.

The value of σ_0 depends on the sense wire discriminator threshold. The second term is due to electron diffusion. The diffusion width along the drift direction, calculated from known transport coefficients⁴⁾ in H_2 , is $\sigma_D^2 = (68\mu\text{m})^2 \cdot Z/1\text{cm}$. Due to statistics, for the sense wire threshold used in the cosmic ray data, we would expect an "ideal" $\sigma_1 = 0.3 \times 68 = 21\mu\text{m}$.

PERFORMANCE IN THE BEAM

During the previous run of the experiment, the chamber was operated at a sense wire gain of 1.5×10^2 . At this gain, the total sense wire current was 2×10^{-8} Amps "on spill", caused primarily by low energy electrons produced in the beam halo. Under these conditions, we did not observe any deterioration of the chamber gain or spatial resolution due

FIG. 6 - Resolution vs. drift distance.

to space charge.

A scatter plot of sense wire pulse height vs. recoil kinetic energy obtained on-line is shown in Fig. 7. The recoil proton band is clearly visible.

FIG. 7 - dE/dx vs. recoil kinetic energy for raw events.

REFERENCES

- 1) J.J. Lowke, Aust. J. Phys. 16, 115 (1963).
- 2) D.J. Rose, Phys. Rev. 104, 273 (1956).
- 3) H. Shimamori and Y. Hatano, Chem. Phys. Lett. 38, 242 (1976).
- 4) L.G. Huxley and R.W. Crompton, *The Diffusion and Drift of Electrons in Gases* (Wiley, New York, 1974).