OAK RIDGE NATIONAL LABORATORY

OPERATED BY MARTIN MARIETTA ENERGY SYSTEMS INC.
POST OFFICE BOX X OAK RIDGE TENNESSEE 37831 -

2008

6036

ORNL/RAP/LTR--88/39

DE92 008391

DATE: August 26, 1988

SUBJECT: Dating Shallow Groundwater using ^3H - ^3He and ^{85}Kr

TO: L. D. Bates

FROM: D. K. Solomon

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

NTIS price codes—Printed Copy: A10 Microfiche A01

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Dating Shallow Groundwater using ^3H - ^3He and ^{85}Kr

D. K. Solomon
Environmental Sciences Division
Oak Ridge National Laboratory

ORNL/RAP/LTR-88/39

Determining the age of groundwater from monitoring wells can greatly aid in understanding a hydrologic system. Groundwater dating techniques have been used to estimate residence times ranging from about 1000 to 50,000 years. While such measurements have been very useful in hydrothermal and geochemical studies and in the development of groundwater supplies, they have been of limited use in contaminant studies associated with shallow groundwater systems since residence times are often much less than 1000 years.

The tritium (^3H) concentration of precipitation prior to 1952 was very low. As a result of aboveground nuclear testing, the ^3H tritium concentration of precipitation increased by as much as a factor of 10,000 in the mid-1960's. While ^3H has been used to place relative dates on groundwater (i.e. very low ^3H concentrations indicate the water is older than 1952), little use has been made of its daughter ^3He . Because ^3H undergoes radioactive decay to form ^3He , measurements of both ^3H and ^3He concentrations in groundwater will allow the determination of the age of the ^3H since the water was isolated from the atmosphere:

$$t = \lambda^{-1} \ln \left(\frac{^3\text{He}^*}{^3\text{H}} + 1 \right)$$

where $^3\text{He}^*$ is the radiogenic ^3He concentration (the radiogenic ^3H concentration is usually assumed to be equal to the total ^3He concentration since essentially the only other source of ^3He is from degassing of the mantle, which is thought to be very small), λ is the decay constant for ^3H , and t is time.

In 1986 a pilot study of ^3H and ^3He isotope concentrations in groundwaters from Solid Waste Storage Area Six (SWSA 6) was conducted (Poreda et al., 1987). The results of

this study indicate that ^3H ages in groundwaters range from about 1 month to over 6 years in SWSA 6. These ages correlate reasonably well with groundwater flow patterns estimated from hydraulic head data. These groundwater ages were coupled with a three-dimensional flow net and used to calculate hydraulic conductivities. For five wells, hydraulic conductivities of 3×10^{-6} m/s to 100×10^{-6} m/s were calculated. Moore et al. (1987) reported a geometric mean hydraulic conductivity of 3.6×10^{-7} m/s with a two standard deviation range of 8.1×10^{-8} - 1.6×10^{-6} m/s for wells located both in Melton and Bethel valleys; however, the range of all the data was from 2.9×10^{-8} to 2.1×10^{-5} . Thus the values determined from the ^3H - ^3He results are not unreasonable.

The samples collected in 1986 were processed using an extraction line designed for tracer work in oceanography which requires extremely low blanks. Since only samples with relatively low ^3H concentrations could be extracted without contaminating the low blank extraction line, only a limited number of samples were collected. These samples were thus intended only to verify the ^3H - ^3He dating technique. In order to use ^3H - ^3He measurements to define the movement of groundwater in SWSA 6 it is necessary to collect samples from various locations and depths throughout the site.

To process samples with a potentially high ^3He content, a subcontract to the University of Utah has been established. An extraction line made of special (1720) glass is being constructed at the University of Rochester, Department of Geological Sciences under subcontract to the University of Utah. The original subcontract from ORNL to the University of Utah was scheduled to be issued by February, 1988; however, delays in Purchasing, associated with permanent equipment required for the extraction line, resulted in the subcontract being issued in mid June. Since it was not possible to begin construction of the extraction line before June, 1988 the line is not yet complete. All

necessary parts have been purchased and it is estimated that the extraction line will be operational by November, 1988.

One potential problem with the ^3H - ^3He dating technique, discovered during the 1986 pilot study, is an apparent supersaturation of groundwater samples with respect to atmospheric ^4He . Concentrations of ^4He from 10 to 100% above atmospheric saturation were observed. This resulted in a difference of up to 40% in the calculated age for the sample with the highest ^4He concentration. While most waters had excess ^4He of only 10 to 20% it is important address this problem. The saturation state of other gases such as N_2 , O_2 , Ar, and Ne will be investigated using gas chromatography and mass spectrometry. Since this work is being conducted under the same University of Utah subcontract as the ^3H - ^3He dating, the analysis of samples has not yet begun.

Groundwater dating using the ^3H - ^3He technique will be done on approximately 40 samples collected primarily in and around SWSA 6. Deep groundwater samples from 9 of the hydraulic head monitoring station (HHMS) wells were collected in early August, 1988. Field analytical parameters including temperature, pH, dissolved oxygen (DO) and specific conductance were measured on each sample using a flow-through cell on a Hydrolab water quality meter. The results of the field measurements are shown in Table 1. Because of the long recovery period required for most of the HHMS wells, it was decided to collect the samples without significant purging of the well casings. A positive displacement piston pump (Bennett Pump) was used to collect the samples. The pump was positioned in or very near the open interval of each well. It was not possible to lower the pump into or near the open interval of wells 7A, 7B, and 6A, and thus samples were not collected from these wells. Approximately 5 gallons of water was removed prior to sample collection to purge the discharge lines of the pump. The pump and discharge lines were decontaminated between each well by pumping a 10% solution of

hydrochloric acid followed by a distilled water rinse through the pump and discharge lines.

Shallow and intermediate depth samples from SWSA 6 will be collected from the water quality monitoring wells. Arrangements were made with the Environmental Sampling Group of the Environmental and Health Protection Division to collect samples during the second-round sampling of the water quality wells which is scheduled for October, 1988. Sampling personnel were instructed in the collection of groundwater samples for dissolved gases during the August sampling.

Although the emphasis of the groundwater dating project is on the use of the ^3H - ^3He isotope pair, the feasibility of using krypton-85 (10.7 y half-life) to date shallow groundwaters has also been investigated. The atmospheric concentration of ^{85}Kr is believed to be much more stable at a given location than ^3H which is known to vary from storm to storm as well as seasonally (this is precisely the reason for measuring not only ^3H but its daughter ^3He thus circumventing the need to know the input concentration of ^3H in order to date the water). The concentration of ^{85}Kr in the atmosphere has been increasing throughout the nuclear era from near 0 in 1950 to about 45 dpm per cc of stable Kr, at standard temperature and pressure (STP), in 1984 for the northern hemisphere troposphere (Fig. 1). The data shown in Figure 1 were taken from the literature (Rozanki 1979, Weiss 1983) and were compiled by W. M. Smethie (personal communication). Since ^{85}Kr is a nuclear fission product, local atmospheric concentrations near reactors can be variable depending on the reactor output and atmospheric conditions. Although annual estimates are made of ^{85}Kr releases from reactors at ORNL, primarily the High Flux Isotope Reactor (HFIR), average atmospheric concentrations at ORNL are not known.

Three groundwater samples and one surface water sample were collected during the last week of May 1988 with the help of W. M. Smethie from the Lamont Doherty Geological Observatory, Columbia University. Due to the small dissolved quantity of ^{85}Kr in water, approximately 200 L of sample were collected. Groundwater samples were collected from well 741 near White Oak Dam, from well 458 in SWSA 5, and from a production well (ESD #2) operated by the Environmental Sciences Division located off of Bethel Valley Road near the Historic Graphite Reactor. The open or screened intervals for these wells is shown in Table 2. The selection of wells was severely limited by the required sample volume. An attempt was made to select wells having different open intervals (thus potentially having different ages) located spatially near one another; however, this was not possible due to the required volume of the sample. Hydraulic calculations indicated that a transmissivity of at least $0.15 \text{ m}^2/\text{day}$ was necessary to yield the required sample volume in a reasonable amount of time (about 3 hours). A surface water sample was collected from Melton Hill Lake near Melton Hill Dam. The surface sample was intended to act as a control for defining the present atmospheric concentration of ^{85}Kr in this area.

Samples from wells 741 and 458 were collected using a positive displacement piston pump (Bennett Pump). The discharge lines were connected directly to a field extraction system which degassed the samples. The ESD #2 well was sampled by connecting the extraction system to the discharge line of a dedicated submersible pump. The sample from Melton Hill Lake was collected using a centrifugal pump connected to the extraction system.

The extracted gas samples were collected in gas cylinders and shipped to Lamont Doherty Geological Observatory for analysis. The samples were cryogenically purified, and the ^{85}Kr activity was determined by proportional counting.

The results of the ^{85}Kr analyses are shown in Table 2. The ^{85}Kr concentration in the surface sample from Melton Hill Lake is about 5% lower than expected value based on the estimated atmospheric concentration for the northern hemisphere troposphere shown in Figure 1. Latitudinal variations in the atmospheric concentration of ^{85}Kr have been measured (Weiss, 1983) and may account for this small difference. The ^{85}Kr concentration measured in well 741 is less than the Melton Hill Lake sample, presumably a result of radioactive decay after the groundwater became isolated from the atmosphere below the water table. Figure 2 shows ^{85}Kr decay curves using an atmospheric source function similar to the one shown in Figure 1; the source function used in Figure 2 has been displaced by about 5% from the one shown in Figure 1 so that atmospheric ^{85}Kr concentration in 1988 agrees with the value measured in Melton Hill Lake. Since the sample from well 741 was collected in 1988 and has a ^{85}Kr concentration of about 32 (dpm/cc STP), Figure 2 indicates that this water was isolated from the atmosphere around 1986.5. Thus the apparent age of the sample is computed to be about 1.5 years. This age is reasonable in light of the ^3H - ^3He dates previously determined on nearby shallow groundwaters that ranged from 1 month to over 6 years.

Samples collected from both wells 458 and ESD #2 had ^{85}Kr concentration greater than the present atmospheric value. Since the same pump was used for both wells 741 and 458 it is unlikely that supersaturation of atmospheric ^{85}Kr occurred as a result of leakage from the compressed air used to drive the pump. Furthermore, an electric submersible pump was used in the ESD #2 well, and thus there is no reason to expect errors in the ^{85}Kr concentrations as a result of the sampling equipment. The only plausible explanation that can be offered at this point is that historically the atmospheric ^{85}Kr concentration was significantly elevated as a result of emissions from on-site reactors or processing of fission products. Since the HFIR has not been operating

recently, this effect would not be observed in the Melton Hill Lake surface sample or in the relatively young groundwater sample from well 741.

In addition to the ^{85}Kr analyses, samples for ^3H - ^3He analyses were also collected from wells 741, 458, and ESD #2. Since dating using the ^3H - ^3He is not dependent on source concentration, an evaluation of historic ^{85}Kr concentrations may be possible.

In Summary, precise dating using ^{85}Kr will require accurate estimates of the historic ^{85}Kr source term. The ^{85}Kr dating method appears to have possibilities especially for areas not effected by local sources. Although large sample volumes were necessary for measuring the ^{85}Kr by proportional counting, new laser enrichment techniques are being developed which could reduce the sample volume to several liters thus making this method attractive for use in lower permeability formations. The ^3H - ^3He dating requires only a small (several ml) of sample. Results from the previous study indicate that the ^3H - ^3He dating technique will greatly enhance our understanding of flow paths and residence times of groundwater on and near the Oak Ridge Reservation.

REFERENCES

Moore, G. K., D. D. Huff, and R. H. Ketelle. 1987. FY 1987 Piezometer Well Data Summary. ORNL/RAP/LTR-87/80.

Poreda, R. J., T. E. Cerling, and D. K. Solomon. 1987. Use of tritium and helium isotopes as hydrologic tracers in a shallow unconfined aquifer. J. Hydrology (In press).

Rozanski, K. 1979. Krypton-85 in the atmosphere 1950-1977: A data review. Environment International 2:139-143.

Weiss, W., A. Sittkus, H. Stockburger, and H. Sartorius. 1983. Large-scale atmospheric mixing derived from meridional profiles of krypton-85. J. Geophysical Res. 88:8574-8578.

Table 1. Field Parameters for Samples Collected from Hydraulic Head Monitoring Wells.
Samples Were Collected August 4-5, 1988.

Well #	Depth (m)	Temp. ¹ (°C)	pH ²	Dissolved Oxygen (mg/L)	Specific Conductance (uS/cm)
HHMS-7C	50	18.9	9.8	0.3	966
HHMS-8A	118	20.5	9.4	0.7	2100
HHMS-8B	56	NM	11.7	0.5	350
HHMS-8C	20	25.3	8.1	0.7	80.0
HHMS-5B	61	18.5	9.6	0.5	531
HHMS-5C	14.5	19.6	6.6	0.3	276
HHMS-5A	118	18.6	6.8	0.1	239
HHMS-6B	45	16.9	10.9	0.3	1836
HHMS-6C	14	18.7	8.6	0.4	451

¹Since solar heating occurs in the pump discharge lines, values should not be considered representative of in-situ conditions.

²High pH's may reflect the influence of drilling grout on unpurged samples.

Table 2. Results of ^{85}Kr Analyses

Sample ID	Screened Interval (m below land surface)	^{85}Kr (dpm/cc STP)	^3H pCi/L
ESD #2	9.1-91.4	100	433
458	57.9-61.6	71	590
741	3.7-6.7	32	1067
Melton Hill Lake	NA	40	- -

Krypton-85 in the northern hemisphere troposphere

Fig. 1 Estimated ^{85}Kr activity in the northern hemisphere troposphere.

Fig. 2. Decay curves for ^{85}Kr in water after isolation from the atmosphere. The atmospheric concentration of ^{85}Kr was assumed to increase linearly as indicated by the line labeled "Atmospheric". Contours represent the date when a sample (with a given ^{85}Kr activity) became isolated from the atmosphere.

INTERNAL DISTRIBUTION

1. J. S. Baldwin
2. L. D. Bates (2 copies)
3. W. J. Boegly
4. D. M. Borders
5. T. W. Burwinkle
6. R. B. Clapp
7. K. W. Cook
8. E. C. Davis
9. H. R. Gaddis
10. S. B. Garland
11. D. D. Huff
12. P. M. Kearl
13. I. L. Larsen
14. J. D. Marsh
15. L. E. McNeese
16. W. M. McMaster
17. T. E. Myrick
18. C. E. Nix
19. C. R. Olsen
20. P. T. Owen (5 copies)
21. R. K. Owenby
22. D. E. Reichle
23. T. H. Row
24. F. E. Sharples
25. D. K. Solomon (5 copies)
26. B. P. Spalding
27. L. E. Stratton
28. L. E. Toran
29. J. R. Trabalka
30. R. I. Van Hook
31. L. D. Voorhees
32. Laboratory Records
33. OFFICE OF ASSISTANT MANAGER, ENERGY RESEARCH AND DEVELOPMENT,
U.S. DEPARTMENT OF ENERGY, DOE FIELD OFFICE, OAK RIDGE
P.O. BOX 2001, OAK RIDGE, TN 37831-8600
- 34-35. OFFICE OF SCIENTIFIC AND TECHNICAL INFORMATION, P.O. BOX 62,
OAK RIDGE, TENNESSEE 37831

END

**DATE
FILMED
5/07/92**