12/4-29-92 JSD

PNL-8010
UC-704

Modeling the Behavior of a Light-Water Production Reactor Target Rod

D. J. Sherwood

March 1992

**Prepared for the U.S. Department Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute**

PNL-8010

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor Battelle Memorial Institute, nor any of their employees, makes **any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights.** Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or Battelle Memorial Institute. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

PACIFIC NORTHWEST LABORATORY
operated by
BATTELLE MEMORIAL INSTITUTE
for the
UNITED STATES DEPARTMENT OF ENERGY
under Contract DE-AC06-76RLO 1830

Printed in the United States of America

Available to DOE and DOE contractors from the
Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831;
prices available from (615) 576-8401. FTS 626-8401.

Available to the public from the National Technical Information Service,
U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

PNL--8010

DE92 012261

MODELING THE BEHAVIOR OF A LIGHT-WATER
PRODUCTION REACTOR TARGET ROD

[. J. Sherwood

March 1992

Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Richland, Washington 99352

REGISTER

EXECUTIVE SUMMARY

Pacific Northwest Laboratory has been conducting a series of in-reactor experiments in the Idaho National Engineering Laboratory (INEL) Advanced Test Reactor (ATR) to determine the amount of tritium released by permeation from a target rod under neutron irradiation. The model discussed in this report was developed from first principles to model the behavior of the first target rod irradiated in the ATR. The model can be used to determine predictive relationships for the amount of tritium that permeates through the target rod cladding during irradiation. The model consists of terms and equations for tritium production, gettering, partial pressure, and permeation, all of which are described in this report. The model addresses only the condition of steady state and features only a single adjustable parameter.

The target rod design for producing tritium in a light-water reactor was tested first in the WC-1 in-reactor experiment. During irradiation, tritium is generated in the target rod within the ceramic lithium target material. The target rod has been engineered to limit the release of tritium to the reactor coolant during normal operations. The engineered features are a nickel-plated Zircaloy-4 getter and a barrier coating on the cladding surfaces. The ceramic target is wrapped with the getter material and the resulting "pencils" are inserted into the barrier coated cladding. These features of the rod are described in the report, along with the release of tritium from the ceramic target. The steady-state model could be useful for the design procedure of target rod components.

ACKNOWLEDGMENTS

I would like to thank Max Freshley and Glenn Hollenberg for providing me the opportunity to work on this project. The support and encouragement provided by other members of the TTDP is also appreciated.

SYMBOLS AND DEFINITION USED IN EQUATIONS

<u>Symbol</u>	<u>Units</u>	<u>Meaning</u>
A_ℓ	cm^2/cm	Area per unit length
BU	--	Fractional burnup of initial ^6Li atoms.
GVR	--	Gas-volume ratio: the ratio of the STP volumes of gas (tritium plus helium) produced in the pellets to the pellet volume
GVR_f	--	Average GVR at end of irradiation
GVR_o	--	GVR at end of incubation period
J	$\text{moles } T_2/(\text{cm}^2 \cdot \text{s})$	Flux of tritium atoms through the cladding
K_a	$\text{atoms}/(\text{cm}^2 \cdot \text{s} \cdot \text{atm}^{1/2})$	Temperature and geometry dependent permeation rate constant
K_f	$\text{Pa}^{1/2} \cdot \text{m}/\text{s}$	Gettering rate constant
N_o	atoms per cm^3	Initial ^6Li atomic density in the lithium aluminate pellets.
p	Pascals	Tritium partial pressure
p_e	Pascals	Equilibrium partial pressure of tritium
P_{ss}	$\text{moles } T_2/(\text{m} \cdot \text{s} \cdot \text{Pa}^{1/2})$	Tritium permeability through stainless steel
PRF	(dimensionless)	Permeation reduction factor
Q	moles or curies	Quantity of tritium released from the entire rod in a given period
Rx	Reactions per cubic centimeter per second	^6Li volumetric reaction rate with neutrons producing tritium and helium, one atom each per reaction
t_f	--	Total irradiation period
V_ℓ	cm^3/cm	Pellet volume per unit length
ΔG_f°	kJ/mole	Standard free energy of formation of zirconium hydride

SYMBOLS AND DEFINITION USED IN EQUATIONS (contd)

<u>Symbol</u>	<u>Units</u>	<u>Meaning</u>
MRx_l	moles/m·s	Average molar production per unit length of $LiAlO_2$
ΔH_f°	kJ/mole	Standard Enthalpy of zirconium hydride formation
ΔS_f°	J/mole·k	Standard Entropy of zirconium hydride formation

Subscripts

l	per unit length
g	getter
p	pellet
c	cladding
o	during (or at) incubation period
s	post-incubation, or steady state
Σ	sum (used in L_Σ = sum of all pencil lengths)
f	"final" as in GVR_f or "formation" as in ΔG_f

CONTENTS

EXECUTIVE SUMMARY	iii
ACKNOWLEDGMENTS	v
SYMBOLS AND DEFINITIONS USED IN EQUATIONS	vii
1.0 INTRODUCTION	1.1
2.0 TRITIUM PRODUCTION AND TARGET ROD PERFORMANCE MODELING . . .	2.1
2.1 BACKGROUND ON TRITIUM PRODUCTION	2.1
2.2 DESCRIPTION OF THE LWR TARGET ROD	2.1
3.0 DESCRIPTION OF STEADY-STATE MODEL	3.1
3.1 TERMS AND EQUATIONS FOR TRITIUM PRODUCTION	3.1
3.2 TERMS AND EQUATIONS FOR TRITIUM GETTERING AND TRITIUM PARTIAL PRESSURE	3.4
3.3 TERMS AND EQUATIONS FOR TRITIUM PERMEATION	3.6
4.0 APPLICATION OF THE MODEL	4.1
4.1 RESULTS AND DISCUSSION	4.8
5.0 SUMMARY AND CONCLUSIONS	5.1
6.0 REFERENCES	6.1
APPENDIX A - DESCRIPTION OF THE WC-1 TEST IRRADIATION HISTORY . . .	A.1

FIGURES

2.1	The Getter-Barrier Target Rod Configuration	2.2
3.1	Microstructure of Typical Reference Product Barrier Coating	3.7
4.1	Comparison of Predicted Versus Measured Release of Tritium from the WC-1 Test, in mCi	4.9

TABLES

4.1	Material and Physical Properties for Modeling Permeation Release from Light-Water Reactor Target Rod	4.4
A.1	WC-1 Test Thermal Operating History	A.1
A.2	Average Component Temperature for WC-1 Test Target Rod with Coolant Temperature of 585°F	A.2
A.3	Cumulative Tritium Release (mCi) from WC-1 Test Target Rod	A.2

1.0 INTRODUCTION

This report presents a steady-state model, developed from first principles, for the behavior of a tritium target rod designed to produce tritium in a light-water new production reactor (NPR). The steady-state model is applicable to a target rod design concept being tested and qualified by Pacific Northwest Laboratory (PNL)^(a) through in-reactor experiments in the Idaho National Engineering Laboratory (INEL) Advanced Test Reactor (ATR). These experiments were conducted to determine the amount of tritium released by permeation from the target rod during neutron irradiation. A key requirement for qualifying the target rod design is to determine the level of tritium released from the rod to the reactor coolant in a production core ($\approx 15,000$ rods/core).

The parameters of the steady-state target rod model were adjusted to provide close agreement with the results obtained from the first of 11 rods irradiated in the ATR. This first irradiation was designated WC-1. The modeling procedure will be verified later against results from the remaining 10 rods. All of these tests utilize four-foot long target rods, which are compatible with the ATR core. A light-water production reactor, however, will require twelve-foot long target rods. Therefore, one of the purposes of performance modeling is to provide a basis for extrapolating data obtained from the four-foot long test target rods to twelve-foot long target rods.

The target rod tested in WC-1 contained all the components of the design concept. The target rod was designed to produce tritium and to limit its release to the reactor coolant under normal operating conditions. The ceramic lithium aluminate pellets within the rod are enriched in the lithium-6 (^6Li) isotope to provide target material. The release of tritium from these pellets generates a partial pressure of tritium within the target rod. The steady-state model described in this report permits, under certain assumptions, the calculation of the tritium partial pressure and the permeation of tritium through the target rod's barrier cladding.

(a) Pacific Northwest Laboratory is operated by Battelle Memorial Institute for the U.S. Department of Energy under contract DE-AC06-76RLO 1830.

The engineered features for limiting tritium permeation from the target rod are two-fold: 1) a distributed nickel-plated Zircaloy-4 getter material and 2) aluminized barrier layers on the inside and outside of the stainless steel cladding. Because this rod design is first-of-a-kind, adequate prediction of tritium release requires that the performance model predictions be referenced to experimental data, including the results of irradiation tests. Ideally, the model parameters would be selected on the basis of one set of in-reactor data and then verified against a separate set of such data. To date, the parameter selection process for the steady-state model has been completed, but the verification process has not.

Section 2.0 of this report describes the basic concepts of tritium production and target rod performance. Section 3.0 presents the terms and equations of this steady-state model. Section 4.0 describes the application of this model to physical properties of tritium release from the target rod and the parameter selection process. Section 5 summarizes the results and conclusions. Appendix A describes the irradiation history of the WC-1 experiment.

2.0 TRITIUM PRODUCTION AND TARGET ROD PERFORMANCE MODELING

2.1 BACKGROUND ON TRITIUM PRODUCTION

Tritium (^3H or T) is produced within target rods primarily by the absorption of thermal neutrons in ^6Li ; production from ^7Li is orders-of-magnitude lower. Target rods can release tritium to the reactor coolant via two mechanisms: permeation and leakage. Leakage is defined as release through a cladding breach. Leakage is an important release mechanism that has not yet been included in the model because it applies to a negligible number of rods in the production core. Thus, the steady-state model will address only permeation release from the target rod.

Tritium release from target rods to the reactor coolant is an important issue for plant safety and operation. High levels of tritium released in the reactor coolant would limit the access of maintenance personnel to plant components. Therefore, the target rod design must be shown to be capable of producing the required quantity of tritium while releasing acceptable levels to the reactor coolant. A steady-state model for the permeation release of tritium from a light-water reactor (LWR) target rod could provide useful information for the design procedure for rod components.

2.2 DESCRIPTION OF THE LWR TARGET ROD

The primary components of the target rod are the LiAlO_2 pellets, a Zr-metal liner that reduces any T_2O released from the pellets to T_2 (tritium), a getter that captures the tritium, and a barrier-coated stainless steel cladding that provides a boundary with the reactor coolant. The tritium stored in the getter plus the LiAlO_2 is available for extraction, a process which can be conducted in an operation following irradiation.

The configuration of the LWR target rod is shown in Figure 2.1. A one-foot long stack of annular LiAlO_2 pellets is inserted over the tubular Zr liner. The pellets/liner are wrapped in a nickel plated Zircaloy-4 (NPZ) getter tube. The resultant assembly is referred to as a "pencil". Twelve pencils, each approximately 12 inches long, are inserted into a stainless steel tube, which is then welded shut to form a hermetic seal. (Only four to

FIGURE 2.1. The Getter-Barrier Target Rod Configuration

five pencils were used in the test rods irradiated in the ATR.) The stainless steel cladding tube is 20% cold worked type 316; however, intermetallic aluminized barrier layers have been produced on the inner and outer surfaces.

3.0 DESCRIPTION OF STEADY-STATE MODEL

The LWR target rod is designed to produce in excess of 5000 Ci of tritium in the LiAlO_2 pellets during an approximately one-year lifetime in the NPR core. The rod is designed so that if all of this tritium is released from the pellets, the NPZ getter will contain it with a resulting $^3\text{H}/\text{Zr}$ atom fraction of less than 0.3. Tritium release from LiAlO_2 is controlled by transport through the porous crystalline microstructure, but for steady-state conditions, a simpler analysis, is appropriate.

3.1 TERMS AND EQUATIONS FOR TRITIUM PRODUCTION

The target rod produces tritium in LiAlO_2 pellets during irradiation according to the reaction:

The LiAlO_2 pellets are enriched in the isotope ^6Li , which reacts with a neutron ^1_0n to form the "heavy" proton (or "triton"), ^3_1H , and a helium atom ^4_2He . This reaction proceeds at a rate, R_x , in reactions per cubic centimeter per second, unique to each axial location along the rod's length, but we will only consider a volumetric average here. Pellets are loaded with an initial concentration of ^6Li , say N_0 atoms per cubic centimeter. Denoting the initial, average reaction rate by R_{x_0} , the fractional burnup of ^6Li is given by the following expression:

$$\text{BU}(t) = 1 - \exp \left[- \left(\frac{R_{x_0}}{N_0} \right) t \right] \quad (1a)$$

or, for small burnups (i.e., less than 30% of initial ^6Li atoms),

$$BU(t) \approx \left(\frac{Rx_o}{N_o} \right) t \quad (1b)$$

Burnup can also be expressed in gas-volume-ratio (GVR) units. The GVR is defined as the ratio of the STP volume of all gas produced to the target material (i.e., pellet) volume. This ratio is given by:

$$GVR = \frac{3}{2} \left[\frac{BU \cdot N_o}{6.023 \times 10^{23}} \right] \cdot 22414, \quad (2a)$$

where BU is fractional burnup of ${}^6\text{Li}$ given by equation (1); N_o is initial atomic density of ${}^6\text{Li}$ in the LiAlO_2 , in atoms/cm³. There are 6.023×10^{23} atoms/mole, and 22,414 cm³ per mole of gas at standard temperature and pressure; and for every ${}^6\text{Li}$ atom that fissions, one ${}^4\text{He}$ molecule and one-half ${}^3\text{H}_2$ molecule, or 3/2 total gas molecules are created. Using equation (1b) in equation (2a) gives

$$GVR(t) \approx \frac{3}{2} \left[\frac{Rx_o \cdot t}{6.023 \times 10^{23}} \right] \cdot 22414 \quad (2b)$$

A similar quantity is the average molar production rate per unit length of LiAlO_2 as defined by the following expression:

$$MRx_\ell \equiv \frac{Rx_o (V_\ell \cdot 100)}{6.023 \times 10^{23}} = 3.52 \times 10^{23} Rx_o, \text{ moles/m} \cdot \text{s} \quad (3)$$

where $V_\ell = 0.212 \text{ cm}^3/\text{cm}$ is the volume per unit length of LiAlO_2 .

Tritium is released from the LiAlO_2 because it has a limited solubility in the matrix. As the target is irradiated, tritium is generated, and the concentration of the isotope in the pellets increases with time. Eventually a "solubility limit" (that could be flux dependent) is reached, and steady-state release ensues. In-reactor testing (Boltax 1989) indicates that the "solubility" (in gas volume ratio units) of tritium in LiAlO_2 can be expressed as

$$\text{GVR}_0 = \exp(6.44 - 4.29 \times 10^{-3} T_p), \quad (4)$$

where T_p is the volumetric average temperature of LiAlO_2 in degrees Kelvin. When $\text{GVR} < \text{GVR}_0$, the LiAlO_2 is unsaturated and more tritium can be contained in the material; when $\text{GVR} > \text{GVR}_0$, the LiAlO_2 will not hold any more tritium. Thus, the average amount of tritium in the LiAlO_2 is given by equation (4). Before reaching the "solubility limit," tritium release is likely dominated by a mechanism known as recoil (Wise 1985; Lewis 1987), which is the physical ejection of newly produced tritium from the LiAlO_2 pellet surfaces as a result of their "fission" energy. This release rate was determined to be 3% of the production rate (Boltax 1989). After the "solubility limit" is attained, 100% of the additional gas produced in the LiAlO_2 matrix is released (Boltax 1989).

Thus, the ratio of tritium released to tritium produced in the pellets is given by

$$f_0 = 0.03 \text{ (due to recoil when } \text{GVR} < \text{GVR}_0),$$

$$f(t) = \left[\frac{\text{GVR} - \text{GVR}_0}{\text{GVR}} \right] \text{ (when } \text{GVR} > \text{GVR}_0).$$

If the production rate is constant (valid for small burnup and steady reactor power operation), then equation (2b) indicates that the incubation

period is defined as

$$t_i = (GVR_o/GVR_f)t_f, \quad (5)$$

where GVR_f is the average GVR at the conclusion of irradiation, and t_f is the total irradiation period. GVR_f is determined by a nuclear analysis of the target rod in the irradiation environment for a period of t_f .

3.2 TERMS AND EQUATIONS FOR TRITIUM GETTERING AND TRITIUM PARTIAL PRESSURE

Tritium is released at a high rate from $LiAlO_2$ pellets in the LWR target rod. The permeation rate of tritium through the cladding increases with the partial pressure of tritium inside it. Because hydrogen isotopes readily permeate metals and alloys, two features of the target rod were developed to reduce the amount of tritium released to the reactor coolant: 1) the $LiAlO_2$ pellets are wrapped in a nickel plated Zircaloy-4 getter and 2) a barrier coating is applied to the stainless steel cladding. This design has therefore been referred to as a getter-barrier. The functions of the getter and barrier coating are described below.

The affinity of zirconium for hydrogen isotopes is well known (Northwood and Kosasih 1983). Large amounts of hydrogen can be stored in zirconium because hydrogen precipitates into hydride compounds in this metal (Northwood and Kosasih 1983; Wenzl 1982); a H/Zr atom fraction of more than one-half is possible. This feature is being exploited with the nickel plated Zircaloy-4 (NPZ) getter for the LWR target rod. Nickel-plated zirconium promotes hydride formation, even under irradiation, since a hydrogen "window" is produced by the nickel overlay (Johnson 1975), thereby increasing the rate that hydrogen is taken up by the base metal (zirconium) (Kuus and Martens 1980). The coating prevents formation of a surface oxide film that restricts hydrogen uptake (Johnson 1975; Kuus and Martens 1980; Pick and Greene 1980), although even a clean metal surface may present an intrinsic barrier to uptake if there is a

strongly bound surface state for hydrogen (Pick and Greene 1980). A nickel film may diminish the energy difference between the surface and absorbed states (Pick and Greene 1980).

An effective getter reduces tritium permeation by absorbing the isotope rapidly, thereby lowering the partial pressure of tritium in the target rod. If the getter absorption rate is sufficiently high, then the tritium partial pressure would be maintained at the partial pressure for tritium in equilibrium with the Zircaloy-4 matrix and the gas phase, $p = p_e$. The partial pressure p_e is a thermodynamic property of the Zr-T₂ system; it is a function of the temperature and the amount of tritium stored in the Zr-matrix (Fromm and Horz 1980). If the getter does not absorb tritium at a sufficiently rapid rate, then the internal tritium pressure is determined by the getter absorption rate and the release rate of tritium from the LiAlO₂. In this case, the partial pressure of tritium in the target rod could be much higher than p_e . The getter absorption rate is not a thermodynamic property of the getter material; rather, it is highly sensitive to the metallurgical condition of the getter (e.g., Ni thickness, heat treatment, etc.).

The partial pressure of tritium in equilibrium with the Zr/Zr-hydride system is obtained as follows. For the equilibrium reaction

there is an equilibrium constant, K_f , given by

$$K_f = A/p_e^{\circ 1/2} = A \exp(-\Delta G_f^{\circ}/RT);$$

(assuming that the solid phases are in their standard states) thus, according to Fromm and Horz (1980),

$$p_e^{\circ} = A \exp(2\Delta G_f^{\circ}/RT);$$

where ΔG_f° is the standard free-energy change for hydride formation, and the

units of p_e° are atmospheres.

$$\Delta G_f^\circ = \Delta H_f^\circ - T\Delta S_f^\circ,$$

where $\Delta H_f^\circ = -95.3$ kJ/mole

$\Delta S_f^\circ = 76.6$ J/K·mole are the enthalpy and entropy of formation,
respectively (Fromm and Horz 1980).

Because the chemical species in a NPZ getter are not in their standard states, $p_e = \gamma p_e^\circ$ where γ is an activity coefficient. The quantity p_e is the minimum partial tritium pressure inside the target rod, assuming that the ratio of Zr to Zr-H is less than about one. Thus, a driving force for the release of tritium to the reactor coolant via permeation will always exist. If the NPZ getter has a low absorption rate constant, then the partial pressure could be much higher than p_e . A relationship for the case $p \gg p_e$ will be presented in Section 4.0.

3.3 TERMS AND EQUATIONS FOR TRITIUM PERMEATION

Storage of tritium in the getter results in a lower partial pressure of tritium inside the target rod. The lower partial pressure reduces the potential for permeation through the stainless steel cladding. Tritium permeation is further inhibited by applying a barrier coating on the cladding. The barrier coating is produced on the cladding surfaces by a pack-aluminization process, which has been exploited commercially to produce aluminide coatings on various steels (Heckel et al. 1977). When applied to the 316 stainless steel cladding, several distinct phases in the microstructure result, as shown on Figure 3.1. Other workers have also used aluminum coatings to reduce the permeability of steel to tritium (Van Deventer et al. 1980), and the subject of tritium permeation barrier development for various steels has recently been reviewed (Stover et al. 1984).

The complex microstructure formed on the cladding surface significantly complicates analysis of the permeation process. Even for the relatively simple case of a single oxide layer on a substrate the resultant permeation flux

3920304.1

FIGURE 3.1. Microstructure of Typical Reference Product Barrier Coating

can be very difficult to calculate (Buchkremer et al. 1984). However, a very simple approach is used for the steady-state model. Because an uncoated stainless steel tube allows a higher tritium current through it than a coated tube, the relative difference in permeability is quantified by the permeation reduction factor (PRF). If the permeation flux J across the rod's cladding is proportional to the square root of the tritium partial pressure p :

$$J = Kp^{1/2},$$

where K is a temperature and geometry dependent constant (Guthrie 1989), then the PRF is defined as

$$\text{PRF} = J_{\text{uncoated}}/J_{\text{coated}} = K_{\text{uncoated}}/K_{\text{coated}}$$

J_{uncoated} is the flux through an uncoated tube and J_{coated} is the flux through a barrier-coated tube, when the driving force for permeation, i.e., the pressure difference across the tube, is the same in both cases. It appears that order-of-magnitude effects in permeation resistance must be attributed to either chemical effects or a low-coating diffusivity (Guthrie 1989). A more rigorous treatment of permeation through a coated material can be found in Guthrie (1989) and Kunz et al. (1985).

4.0 APPLICATION OF THE MODEL

After the steady-state is attained, first-order effects dominate the permeation release of tritium from the target rod.^(a) Contributing to these effects are:

1. After a relatively brief incubation period, the LiAlO_2 pellets release tritium at the generation rate, as discussed earlier.
2. The getter absorbs tritium at some rate that establishes a partial pressure of tritium inside the target rod.
3. The tritium current through the barrier coated stainless steel cladding is (a) proportional to the square root of the partial pressure of tritium inside the target rod, and (b) proportional to the permeability of an uncoated stainless steel cladding, divided by the PRF to account for the influence of the barrier coating.

Relationships for these phenomenon are described here along with a transport equation applicable to the target rod. This equation gives an expression for the tritium partial pressure in the target rod. The partial pressure determines the permeation release rate of tritium from the target rod.

Based on the previous discussion of gas release from LiAlO_2 (Section 3.3), the tritium release rate per unit length of LiAlO_2 can be defined as

$$R_\ell = \frac{1}{2}(0.03) MRx_\ell, \quad t \leq t_i \quad (6a)$$

$$R_\ell = \frac{1}{2} MRx_\ell \quad t > t_i \quad (6b)$$

(a) Independently verified by E. P. Simonen. Private Communication (1991).

with t_i being given by equation (5). The factor of 1/2 arises because the reaction rate refers to atoms, whereas equation (6) accounts for molecules. Note that since the molar production rate is assumed to be constant that the gas release rate after the incubation period is 33 times greater than it is during the incubation period.

An empirical getter absorption rate, $[dN/dt]_g$ moles $T_2/m \cdot s$, can be defined as

$$\left[\frac{dN}{dt} \right]_g = K_a [p^n - (p_e)^n] \frac{A_g}{RT_g} \quad (7)$$

where K_a is the getter absorption rate constant,

$$K_a = B \exp \left(- \frac{Q}{RT_g} \right), \text{ Pa}^{(1-n)} \cdot \frac{m}{s} \quad (8)$$

B is an adjustable parameter, Q is an activation energy, $R = 8.314 \text{ J/K-mole}$ is the gas constant, and T_g is the getter temperature in degrees Kelvin; p denotes the partial pressure of tritium; p_e is the equilibrium partial tritium pressure, given by Grundy^(a),

$$p_e = 6.46 \times 10^{10} \exp \left[- \frac{(1.86 \times 10^4)}{T_g} \right], \text{ Pa} \quad (9)$$

and A_g is the area per unit length of getter, $A_g = 0.05 \text{ m}$. Note that equation (7) shows a rate as proportional to a mobility term (K_a/RT) multiplied by a driving force (the partial pressure) to the power n. It is also similar to relationships proposed for gas uptake via chemisorption (Low 1960).

(a) B. J. Grundy. 1990. Private Communication.

Ex-reactor testing of NPZ getters indicates that $n = 0.875$ and $Q = 34.1$ kJ/K-mole. Note that when $p = p_e$, the getter absorption rate is zero because equilibrium has been established. This equilibrium means that tritium is entering the getter at the same rate as it is leaving the getter: the net rate is zero.

The permeability of hydrogen through uncoated austenitic stainless steels appears to be relatively insensitive to composition, differing very little from that of "pure" γ -Fe (Le Claire 1984). The majority of the results show permeability constants within a factor of 1.5 from the mean value (LeClaire 1984):

$$P_{\gamma\text{-Fe}}[(\text{cm}^3 \text{ of } H_2 \text{ at STP})/(\text{cm} \cdot (\text{s})/(\text{atm})^{1/2})] = 2.33 \times 10^{-2} \exp(-7902/T),$$

where T is the temperature in degrees Kelvin. (Note that $K_{\text{uncoated}} = cP_{\gamma\text{-Fe}}$ where c is a geometric factor, and $J = K_{\text{uncoated}} p^{1/2}$.) The following was determined from this relationship for the permeability of 20% cold worked type 316 stainless steel, merely by changing the units:

$$P_{ss} = 3.27 \times 10^{-7} \exp(-7902/T_c) (\text{moles } T_2/\text{m} \cdot \text{s}/\text{Pa}^{1/2}),$$

where T_c denotes the average cladding temperature in degrees Kelvin. The permeability of the barrier coated cladding is assumed to be given by P_{ss}/PRF . Ex-reactor testing suggests that the $\text{PRF} = 200$ for the WC-1 test target rod.

The relationships required to model target rod behavior are summarized in Table 4.1. In this table, T_p is the average pellet temperature, T_g is the average getter temperature and T_c is the average cladding temperature, all in degrees Kelvin.

The principal assumption of gas transport behavior required to determine the partial pressure of tritium in the target rod is presented next.

If the tritium release rate from the LiAlO_2 pellets, R_ℓ , was initially greater than the getter absorption rate, $[dN/dt]_\ell$, then the partial pressure

TABLE 4.1. Material and Physical Properties for Modeling Permeation Release from Light-Water Reactor Target Rod

Property	Relationship
(Average, initial) production rate	$R_{X_0} = 1.2 \times 10^{14}$, atoms/cm ³ -s
(Average, initial) molar production rate per unit length	$MR_{X_0} = 4.2 \times 10^{-9}$, moles/m-s
Gas volume ratio	$GVR(t) = 5.58 \times 10^{-20} R_{X_0} \cdot t$
Solubility of tritium in LiAlO ₂	$GVR_0 = \exp(6.44 - 4.29 \times 10^{-3} T_p)$
Incubation period	$t_i = [G_0 / GVR(t_f)] t_f$
(Molar) tritium release rate from LiAlO ₂ pellets per unit length	$R_0 = \frac{1}{2} (0.03) MR_{X_0}, t \leq t_i$ $R_0 = \frac{1}{2} MR_{X_0}, t > t_i$ (moles T ₂ /m-s)
Partial tritium pressure in equilibrium with Zr in NPZ getter	$p_g = 6.46 \times 10^{10} \exp[-(1.86 \times 10^4) / T_g]$ (Pa)
NPZ getter absorption rate constant	$K_a = 0.245 \exp(-4100 / T_g)$ (Pa ^{0.125} m/s)
Permeability of 20% CW type 316 SS	$P_{ss} = 3.27 \times 10^{-7} \exp(-7902 / T_c)$ (moles T ₂ /m·s/Pa ^{1/2})
Permeation reduction factor	PRF = 200

of tritium would increase, which, in turn, would increase the getter absorption rate. Thus, since the permeation rate is assumed to be so small, when a steady-state is reached, we have

$$0 = R_\ell - [dN/dt]_\ell = R_\ell - K_a[p^n - (p_e)^n]A_\ell/RT; \quad (10)$$

or, solving for the partial pressure of tritium

$$p = \left[(p_e)^n + \frac{RT_g}{A_\ell K_a} R_\ell \right]^{\frac{1}{n}} \quad (11a)$$

It turns out that $RT_g R_\ell / A_\ell K_a \gg p_e$ when K_a is assumed to be given by equation (8); thus, only the second term in equation (11a) makes a significant contribution to the partial pressure of tritium in the target rod. Therefore,

$$p \approx \left[\frac{RT_g}{A_\ell K_a} R_\ell \right]^{\frac{1}{n}} \equiv \left[\frac{f R_\ell}{K_a} \right]^{\frac{1}{n}} \quad (11b)$$

where $f = 1.05 \times 10^5$ J/m-mole for $T_g = 362^\circ\text{C}$, but this constant is quite insensitive to variations in temperature; and finally

$$p = 5.48 \times 10^5 [R_\ell / K_a]^{1.14}, \text{ Pa.} \quad (11c)$$

On the other hand, when $K_a \gg RT_g R_\ell / A_\ell$, then $p \approx p_e$; and in this (the "fast getter") case, the partial pressure of tritium in the target rod will be very low. This case does not appear to be applicable to the target rods being irradiated in the ATR.

Since there are two tritium release rates given by equations (6), corresponding to $t < t_i$ and $t > t_i$, there will be two corresponding partial tritium pressures according to equations (11):

$$p = p_o, t \leq t_1, \quad (12a)$$

and

$$p = p_s, t > t_1; \quad (12b)$$

p_o denoting the average partial tritium pressure in the target rod during the incubation period, with the tritium release rate from the LiAlO_2 (R_ℓ) being given by equation (6a); and p_s denoting the same quantity for the post incubation period, where R_ℓ is given by equation (6b).

The permeation release rate (I) of tritium from a target rod will be assumed to be given empirically by the following modification to the standard relationship for a cylindrical membrane (Kishimoto et al. 1984) ($I = JA$ where $A = 2\pi r L_\Sigma$ is the cladding surface area, with r being the average cladding radius and L_Σ the sum of all the pencil lengths):

$$I = \frac{2\pi P_{ss} L_\Sigma}{PRF \ln(b/a)} p^{\frac{1}{2}}, \text{ moles } \frac{T_2}{s} \quad (13a)$$

$b/a = 1.138$ is the ratio of the outer and inner cladding radii. Substituting values for the constants, and equation (11c) for the partial tritium pressure in the target rod provides the following formula for I :

$$I = (1.43 \times 10^{-2} / PRF) \exp(-7900/T_c) [R_\ell / K_a]^{0.57}, \text{ moles } T_2/s. \quad (13b)$$

Because there are two periods with different partial tritium pressures ($p = p_o$ and $p = p_s$), there will be two different currents of tritium through the stainless steel cladding. These currents correspond to the substitution of equations (6) into equation (13b):

$$I = I_o, t \leq t_1, \quad (14a)$$

and

$$I = I_s, t > t_1. \quad (14b)$$

The amount of tritium released from a target rod by the process of permeation after irradiation for a period t is the following integral:

$$Q(t) = \int_0^t I dt, \text{ moles } T_2$$

Since I is a constant during two periods, the incubation period ($I=I_0$) and the post-incubation period ($I=I_s$), we have the following expressions for $Q(t)$. The total amount of permeation release from the target rod during irradiation in the incubation period is

$$Q(t) = I_0 t, \text{ moles } T_2, t \leq t_i; \quad (15a)$$

while for $t > t_i$ we have

$$Q(t) = I_0 t_i + I_s (t - t_i), \text{ moles } T_2, t > t_i. \quad (15b)$$

The units of curies (Ci) are generally preferred when dealing with a radioactive isotope. One Ci = 3.7000×10^{10} disintegrations/atom-s; the half-life for tritium is $t_{1/2} = 12.26$ years; therefore the decay constant λ ($\lambda \equiv \ln 2 / t_{1/2}$) is $\lambda = 1.79 \times 10^{-9} \text{ s}^{-1}$ (Lamarsh 1966). Thus, $(1.79 \times 10^{-9} \text{ disintegrations/s}) (1 \text{ Ci} / 3.7 \times 10^{10} \text{ disintegrations/atom-s}) (2.6.023 \times 10^{23} \text{ T atoms/mole } T_2) = 58300 \text{ Ci/mole}$; and

$$Q_{Ci}(t) = 58300 Q(t), \quad (16)$$

where $Q(t)$ is given by the previous two equations. Finally then,

$$Q_{Ci}(t) = \left(\frac{835}{\text{PRF}} \right) \exp \left(\frac{-7900}{T_c} \right) \left[\frac{R_\ell}{K_a} \right]^{0.57} t, \text{ Ci}, t \leq t_i \quad (17a)$$

$$Q_{Ci}(t) = Q_{Ci}(t_i) + \left(\frac{835}{PRF} \right) \exp \left(\frac{-7900}{T_c} \right) \left(\frac{R_\ell}{K_a} \right)^{0.57} (t-t_i), \quad Ci, \quad t \geq t_i \quad (17b)$$

4.1 RESULTS AND DISCUSSION

Equation (17) estimates the permeation release of tritium from a target rod as a function of irradiation time, average temperatures of the target rod components, cladding permeability, getter absorption rate constant and production rate. Figure 4.1 shows this relationship against the tritium release data from the WC-1 target rod irradiation in ATR. A description of this irradiation test and a tabulation of the tritium release results are given in Appendix A. Agreement is quite good; however, the getter absorption rate constant, K_a , given by equation (8), was adjusted to provide the fit.

Equation (17) varies inversely with the PRF, with the production rate to the 0.57 power, and with the getter absorption rate constant to the - 0.57 power. The estimate also varies exponentially with the cladding temperature. Additionally the getter absorption rate constant, K_a , is a function of temperature: K_a increases exponentially with the getter temperature. Consequently, the net activation energy for tritium permeation from this target rod design will be small; and as a result, temperature will not have as great an impact on permeation as one might expect.

Finally two closure welds are made in the target rod above and below the pencil stack. The top weld is uncoated (i.e., the local PRF, say PRF_w , is equal to one). Thus, the weld region has the (relatively very high) permeability of a stainless steel. Equation (17) neglects potential effects associated with the welds. This is acceptable for low cladding PRFs (very likely to be the case for test target rods irradiated in ATR), but for very high PRFs ($>> 1000$) permeation through weld regions will eventually dominate over that through the cladding.

FIGURE 4.1. Comparison of Predicted Versus Measured Release of Tritium from the WC-1 Test, in mCi

5.0 SUMMARY AND CONCLUSIONS

The function of the LWR target rod is to produce and retain tritium during irradiation so that the isotope can be easily extracted after irradiation. Achieving goal production levels of the isotope is a result of sufficient enrichment of LiAlO_2 with the ^6Li isotope. Retention of the isotope is dependent on the design and fabrication of the getter barrier system. Practically all of the tritium released from the LiAlO_2 pellets will be forced into the getter, if the getter is at all functional. A partial pressure of tritium will, however, still be maintained in the target rod. This partial pressure provides a driving force for the diffusion of tritium through the target cladding: a process known as permeation. Assuming that there are no cladding breaches, all of the target rods in the reactor will release tritium to the reactor coolant via permeation. The amount that each rod releases by this process is estimated by equation (17). A breached target rod will likely leak all tritium generated through the hole.

Permeation release predicted by equation (17) is inversely proportional to the PRF; and also proportional to the release rate from the LiAlO_2 pellets divided by the getter absorption rate constant, all to the 0.57 power. Thus, according to this means of estimating permeation, the release of tritium to the reactor coolant can be inhibited/reduced by manufacturing target rods with large PRFs and high getter absorption rate constants (K_a). The PRF is predicted to be more important than K_a in controlling the level of tritium permeation because permeation release varies as PRF^{-1} and only as $K_a^{-0.57}$.

Material properties for the target rod components are difficult to determine in the laboratory, and are almost impossible to determine in the irradiated condition, some of those listed in Table 4.1 must therefore be regarded as empirical. In particular, the getter absorption rate constant used here, equation (8), is not based on any ex-reactor experimentation. The functional relationship and the activation energy are supported by limited ex-reactor test results, and the preexponential value ($A = 0.245 \text{ Pa}^{0.125} \text{ m/s}$) was adjusted to fit data obtained from the WC-1 test. The PRF, on the other hand,

is based on ex-reactor measurements; and the gas release rate, equation (6), is based on analyses of the results of in-reactor tests. Basically then, the model presented here has one adjustable parameter.

6.0 REFERENCES

- Boltax, A. 1989. "Gas Release Equations for LiAlO_2 ." WSR-89-143, Westinghouse Advanced Energy Systems.
- Buchkremer, H. P., R. Hecker, H. Jonas, D. Stover, and U. Zink. 1984. "Advances in the Development and Description of Tritium Permeation Barriers in High-Temperature Alloys" Nuclear Technology 66:550-561.
- Fromm, E., and G. Horz. 1980. "Hydrogen, Nitrogen, Oxygen, and Carbon in Metals." Int. Met. Rev. 15:269-311.
- Guthrie, R.I.L. 1989. Engineering in Process Metallurgy, Clarendon Press, Oxford.
- Johnson, Jr., A. B. 1975. "A Review of Corrosion Phenomena on Zirconium Alloys, Niobium, Titanium, Inconel, Stainless Steel, and Nickel Plate Under Irradiation." Reviews on Coatings and Corrosion-Quarterly Review 1(4):299-365. Scientific Publications Division, Freund Pub. House, Ltd., Tel-Aviv, Israel.
- Kishimoto, N., T. Tanabe, H. Araki, H. Yoshida, and R. Watanabe. 1984. "Hydrogen Permeation in Metals During Exposure to a Process Gas Environment." Nuclear Technology 66:578-594.
- Kunz, W., H. Munzel, and U. Kunz, 1985. "Tritium Release from Zircaloy-2: Dependence on Temperature, Surface Conditions and Composition of Surrounding Medium." J. Nucl. Mater. 136:6-15.
- Kuus, G., and W. Martens. 1980. "Nickel as a Catalyst for the Reaction of Hydrogen with Zirconium." J. Less-Common Metals 75:111-118.
- Lamarsh, J. R. 1975. Introduction to Nuclear Engineering. Addison Wesley, Reading, Massachusetts.
- Le Claire, A. D. 1984. "Permeation of Hydrogen Isotopes in Structural Alloys." J. Nucl. Mater. 122 & 123:1558-1559.
- Lewis, B. J. 1987. "Fission Product Release from Nuclear Fuel by Recoil and Knockout." J. Nucl. Mater. 148:28-42.
- Low, M. D. 1960. "Kinetics of Chemisorption of Gases on Solids." Chem. Rev. 60(3):267-312.
- Northwood, D. O., and U. Kosasih. 1983. "Hydrides and Delayed Cracking in Zirconium and its Alloys." Int. Met. Rev. 28(2):92.
- Pick, M. A., and M. G. Greene. 1980. "Uptake Rates for Hydrogen by Niobium and Tantalum: Effect of Thin Metallic Overlayers." J. Less-Common Metals 73:89-95.

Stover, D., H. P. Buchkremer, R. Hecker, and H. J. Leyers. 1984. "Advances in The Development and Description of Tritium Permeation Barriers in High-Temperature Alloys." J. Nucl. Mater. 122 & 123:1541-1546.

Van Deventer, E. H., V. A. MacLaren, and V. A. Maroni. 1980. "Hydrogen Permeation Characteristics of Aluminum-Coated and Aluminum-Modified Steels." J. Nucl. Mater. 88:168-173.

Wenzl, H. 1982. "Properties and Applications of Metal Hydrides in Energy Conversion Systems." Int. Met. Rev. 27(3):140.

Wise, C. 1985. "Recoil Release of Fission Products from Nuclear Fuel." J. Nucl. Mater. 136:30-47.

APPENDIX A

DESCRIPTION OF THE WC-1 TEST IRRADIATION HISTORY

APPENDIX A

DESCRIPTION OF THE WC-1 TEST IRRADIATION HISTORY

EXPERIMENTAL PROCEDURE AND RESULTS

The target rod irradiated in the first water capsule (WC-1) experiment contains four pencils and each pencil is 30.5 cm in length. Test target rods thus have an active core length of 122 cm. Pellet inner and outer radii are 0.281 and 0.383 cm, respectively; getter inner and outer radii are 0.390 and 0.406 cm; and cladding inner and outer radii are 0.414 and 0.471 cm.

The WC-1 test was irradiated in the I-21 reflector position in the ATR at INEL. Nuclear analysis of the test in this location indicates that the average reaction rate in the LiAlO_2 pellets is

$$R_{X_0} \approx 1.2 \times 10^{14} \text{ atoms/cm}^3 \cdot \text{s}.$$

The temperature of the target rod was monitored by observing the maximum water temperature in the test capsule. Temperature control in the test capsule was achieved by controlling a blend of argon and helium gases. Design coolant temperature was 585°F, but the test was operated for significant periods at lower temperatures. The approximate thermal operating history of the WC-1 test is displayed in Table A.1.

The test was operated in the ATR for a total period of 284 days. Heat transfer analysis of the WC-1 test indicates average component temperatures

TABLE A.1. WC-1 Test Thermal Operating History

<u>Equivalent Full</u> <u>Power Days</u>	<u>Water Capsule Coolant</u> <u>Temperature, °F</u>
87	585
114	405
176	585
201	555
210	500
220	405
284	585

for operation at 585°F, as listed in Table A.2. The heat transfer analysis furnished an axial temperature profile (in °F) that assumed the maximum capsule temperature was 572°F. Here it was assumed that the component temperatures (in °F) changed linearly with the maximum capsule temperature.

Table A.3 presents the cumulative tritium released by the WC-1 target rod into the test capsule coolant system as a function of irradiation time. The units of tritium release displayed are millicuries (mCi).

TABLE A.2. Average Component Temperatures for WC-1 Test Target Rod with Coolant Temperature of 585°F

<u>Component</u>	<u>Temperature (°C)</u>
LiAlO ₂	T = 396
NPZ Getter	T ^p = 362
Stainless Steel Cladding	T ^g = 332

TABLE A.3. Cumulative Tritium Release (mCi) from WC-1 Test Target Rod

<u>mCi Released</u>	<u>Irradiation Time (days)</u>
1.9x10 ⁻⁶	13.8
3.2	52
21	85
25	117
27	124
39	138
48	152
73	190
87	220
117	257
132	275
140	284

DISTRIBUTION

No. of
Copies

No. of
Copies

OFFSITE

- 12 DOE Office of Scientific and
Technical Information
- 5 Office of Light Water Reactor
Designs
U.S. Department of Energy
1707 H Street NW
Washington, D.C. 20585
- W. F. Kelly, NP-12
D. Peko, NP-13
D. P. Beatty (3), NP-13
- D. J. Sherwood (10)
1008 Marshall Ave.
Richland, WA 99352

4 Westinghouse Hanford Company

H. W. Heacock
R. P. Omberg
B. J. Makenas
J. W. Weber

17 Pacific Northwest Laboratory

W. J. Apley
G. H. Beeman (5)
J. L. Ethridge
E. R. Gilbert
J. P. Pilger
E. P. Simonen
C. K. Thornhill
Publishing Coordination
Technical Report Files (5)

ONSITE

3 DOE Richland Field Office
(NP-90)

E. A. Erichsen
R. D. Filbert
A. S. Colburn

END

**DATE
FILMED**

6 / 11 / 92