01222

1 OF 1

4. DEMONSTRATION LOCATION SELECTION

4.1 SDA LOCATION VERSUS SELECTION CRITERIA

The matrix developed to assist in the selection of the demonstration location using the various selection criteria is presented in Table 1. This table presents the criteria met by each of the disposal areas under

2
EGG-WTD-9752
November 1991

APR 27 1992

**Idaho
National
Engineering
Laboratory**

*Managed
by the U.S.
Department
of Energy*

INFORMAL REPORT

**Buried Waste Integrated
Demonstration: Selection of Potential
Demonstration Locations**

**D. A. Arrenholz
J. L. Knight**

*Work performed under
DOE Contract
No. DE-AC07-76ID01570*

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This document contains new concepts or the author(s) interpretation of new calculations and/or measurements; accordingly, EG&G Idaho, Inc. is required by the United States Government to include the following disclaimer:

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

EGG-WID--9752

DE92 012224

**BURIED WASTE INTEGRATED DEMONSTRATION:
SELECTION OF POTENTIAL DEMONSTRATION LOCATIONS**

D. A. Arrenholz

J. L. Knight

Published November 1991

Idaho National Engineering Laboratory
EG&G Idaho, Inc.
Idaho Falls, Idaho 83415

Prepared for the
U.S. Department of Energy
Office of Environmental Restoration and Waste Management
Under DOE Field Office, Idaho
Contract DE-AC07-76ID01570

RECEIVED

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

BURIED WASTE INTEGRATED DEMONSTRATION:
SELECTION OF POTENTIAL DEMONSTRATION LOCATIONS

EGG-WTD-9752

Approved by:

S. K. Merrill

11/6/91
Date

W. H. Sullivan

11/1/91
Date

Prepared by:

D. A. Arrenholz

11-1-91
Date

J. L. Knight

11/4/91
Date

ABSTRACT

The first step towards identifying primary Buried Waste Integrated Demonstration locations is the selection of potential demonstration sites within the Subsurface Disposal Area. The sites selected are Pits 4, 5, 6, and 9, containing transuranic waste of Rocky Flats origin, the Acid Pit, and Pad A. The criteria and methodology for selection of these sites, as well as a description of the wastes present in each area, are included in this report. At a later date, technology-specific demonstration locations will be selected from these six potential sites. The selected locations will be used as necessary to demonstrate technologies whose potential abilities may be optimal on waste forms present at these identified locations.

CONTENTS

ABSTRACT	iii
1. INTRODUCTION	1
2. DESCRIPTION OF THE LOCATION SELECTION CRITERIA	2
3. DESCRIPTION OF THE LOCATIONS CONSIDERED	4
3.1 TRU Waste Pits and Trenches - Rocky Flats Origin	4
3.2 Acid Pit	5
3.3 Pad A	5
4. DEMONSTRATION LOCATION SELECTION	7
4.1 SDA Location Versus Selection Criteria	7
4.1.1 Space/Staging Areas	7
4.1.2 Utilities	11
4.1.3 Access	12
4.2 Location Selection and Methodology	12
4.3 Pit 4	13
4.4 Pit 5	13
4.5 Pit 6	17
4.6 Pit 9	24
4.7 Acid Pit	24
4.8 Pad A	29
5. CONCLUSION	34
6. REFERENCES	35

FIGURES

1. Map of the SDA and RWMC at INEL (EG&G 1982)	9
2. Pit 4 boundaries and dimensional information	14
3. Pit 5 boundaries and dimensional information	18
4. Pit 6 boundaries and dimensional information	21
5. Pit 9 boundaries and dimensional information	25
6. Acid Pit boundaries	30
7. Pad A waste limits	32

TABLES

1. Decision matrix for BWID site selection	8
2. Pit 4 waste disposal information.	15
3. Pit 5 waste disposal information.	19
4. Pit 6 waste disposal information.	22
5. Pit 9 waste disposal information.	26
6. Acid Pit waste disposal information.	31
7. Pad A waste disposal information	33

1. INTRODUCTION

The purpose of the waste characterization and demonstration location efforts under the Buried Waste Integrated Demonstration Program (BWID) at the Idaho National Engineering Laboratory (INEL) is two-fold. The first objective of this effort is to identify candidate locations for the demonstration of various site characterization (e.g., geophysical techniques) and remediation technologies. The waste locations selected should be representative of the buried waste conditions expected to be encountered during remediation at the various facilities making up the Department of Energy (DOE) complex.^a The second objective is to characterize these selected demonstration locations to a degree that will enable the planning and performing of these demonstrations in a safe and environmentally sound manner; the results of this effort will include both an analysis of the wastes and a description of the environs surrounding the waste site.

In order to achieve the first objective, identification of demonstration sites within the boundaries of the Subsurface Disposal Area (SDA) at the INEL, it is necessary to examine the disposal locations and conditions present at the SDA to narrow the list of potential BWID candidate sites. As part of an earlier effort, a summary report has been prepared based on historical information that describes the wastes, conditions, disposal locations within the SDA (Arrenholz and Knight 1991). The purpose of the current report is to present the list of potential BWID demonstration locations and to describe the process used for the selection of these locations. This document will be provided to DOE, BWID staff, and potential BWID technology sponsors to enable more efficient planning and scheduling of demonstrations and to assist in the selection of technologies for demonstration.

---

a. To ensure this representativeness, the conditions present in the DOE complex will be further defined through an ongoing complex-wide waste assessment begun during Fiscal Year 1991.

2. DESCRIPTION OF THE LOCATION SELECTION CRITERIA

To facilitate limiting the number of sites available for consideration as potential BWID demonstration locations, a list of four general selection criteria was developed by the Department of Energy (DOE) and the BWID program. These criteria were as follows:

- Transuranic (TRU) wastes
- Mixed TRU and low-level wastes (LLW)
- Hazardous organics
- Degraded waste containers.

No weighting factors were assigned to the criteria, thus, they were treated with equal priority when selecting the potential demonstration sites.

In addition to the general selection criteria, several additional factors, related primarily to operational aspects of the demonstrations, were taken into consideration by the authors when selecting the candidate sites. These factors were:

- The availability of open space for the staging of equipment, materials, and demonstration support facilities. In order to be considered as open space, highest priority was given to areas undisturbed by earlier disposal activities (i.e., not containing trenches, pits, or soil vault rows). While it is uncertain that the use of these earlier disposal areas for staging purposes would impact the wastes disposed or result in increased risks, it was felt that any such potential impacts were best avoided.
- The proximity of utilities to the demonstration site. Although the planning of the demonstrations are at an extremely early stage and

the support needs of the technologies are unclear, it is virtually certain that the demonstrations will require either electrical power, water, or both. The proximity of these utilities to the potential demonstration sites was, therefore, of concern.

- Access for the delivery of materials and equipment. In order to avoid potential impacts and minimize potential risks due to operating trucks or other equipment on areas previously used for the disposal of wastes at the SDA, the availability of roads to allow for such access was important. The impacts resulting from such operations are unclear but are easier to avoid during planning stages than to correct after the fact.
- Presence of atypical wastes. Atypical wastes are those wastes which were not typical of the usual waste shipments to the SDA. These are primarily items that were generated as a result of accident cleanup or decommissioning and decontamination activities, were prepared for ocean disposal, or are exceptionally large or dense. The presence of these wastes may present operational difficulties for certain technologies that will be demonstrated. An effort will, therefore, be made to select disposal areas not containing atypical wastes.

3. DESCRIPTION OF THE LOCATIONS CONSIDERED

Initially, the locations considered for the BWID Program were limited to the SDA pits and trenches containing transuranic (TRU) wastes of Rocky Flats Plant (RFP) origin. These are Pits 1 through 6 and 9 through 12, and Trenches 1 through 10. As a result of recent efforts to integrate the scope of the BWID program with the objectives of the Buried Waste Program (BWP), the Acid Pit and Pad A were selected as potential demonstration locations and are included in this discussion. These various areas are briefly discussed in the following sections.

3.1 TRU WASTE PITS AND TRENCHES - ROCKY FLATS ORIGIN

The pits and trenches containing RFP TRU wastes were opened from 1952 through 1970. The pits range in size from 342,416 ft³ to 1,052,941 ft³ (excavated volume) and are up to 12 ft deep. The trenches average 7 ft wide, up to 14.6 ft deep, and are up to 1,166 ft long. Trenches were excavated to basalt; however, the pits were generally backfilled with 2 to 5 ft of soil to provide a level floor (Arrenholz and Knight 1991).

Wastes received from RFP consisted of various items resulting from the production of nuclear weapons components. These wastes included a variety of sludges generated during the production process, machinery, piping, clothing, and miscellaneous other wastes, such as rags and tools. Wastes from RFP were most commonly shipped in steel drums (30, 40, and 55 gal) and wooden boxes (up to 105 x 105 x 214 in.) (Arrenholz and Knight 1991).

In addition, during 1960 through 1963, the INEL served as one of the two interim burial grounds in the United States for the disposal of low-level wastes. These wastes were generated by a variety of governmental and non-governmental institutions, including laboratories, universities, and

hospitals.^a Wastes from these sources, which included laboratory wastes, animal carcasses, radiation sources, and machinery, were buried at the SDA in some of the pits and trenches that also contained RFP wastes. These wastes were packaged in a variety of containers, including drums, wooden boxes, and concrete vaults.

Although detailed information has been lacking on the volumes of waste disposed of in the pits and trenches, efforts are currently underway to obtain additional information to permit a better estimation of these volumes.

3.2 ACID PIT

The SDA Acid Pit was open from approximately 1954 until 1961. This pit was an excavation used for the disposal of contaminated solutions of cleaning solvents and acids. Liquids were disposed of in this pit by gravity emptying the liquids down the sloped walls of the pit and using lime to neutralize the acidic solutions. Bottles of unusable or outdated chemicals, in some cases still in their bottled containers, were also dumped into the pit (Vigil 1989). Details on the exact chemicals dumped into the pit, as well as their volumes, are currently being developed.

3.3 PAD A

Pad A, also known as the Transuranic Disposal Area (TDA) is a ground-level asphalt pad, 320 x 240 ft, on which waste containers from RFP were stacked and then covered with soil. Only the eastern half (approximately) of the pad was used for waste disposal; the western half was not used. This pad was used from September 1972 until November 1978. Waste containers stacked on this pad consist mainly of 55 gal steel drums and

---

a. Unpublished results of T. L. Clements, *Buried Waste Characterization: Nonradioactive Hazards Study--Offsite Waste Generators*, October 1980.

4 x 4 x 7 ft wooden boxes.^a The majority of wastes on this pad are nitrate salts from RFP which are contaminated with low levels (less than 100 nCi/g) of transuranic nuclides.

---

a. Unpublished results of J. R. Bishoff, Transuranic Storage Area/Transuranic Disposal Area Penetration and Inspection, December 1979.

4. DEMONSTRATION LOCATION SELECTION

4.1 SDA LOCATION VERSUS SELECTION CRITERIA

The matrix developed to assist in the selection of the demonstration location using the various selection criteria is presented in Table 1. This table presents the criteria met by each of the disposal areas under consideration.

4.1.1 Space/Staging Areas

As seen in Figure 1,^a open space for staging of materials at the SDA is at a premium. The largest areas of open space are located as follows:

- between Pits 8 and 9 in the northeast portion of the SDA
- between Pits 5 and 8 in the northeastern area of the SDA
- between Pit 3 and Pad A in the north-central portion of the SDA
- west of Pit 3 and north of Trenches 24, 29, and 32 and east of Trenches 21 and 22
- south of Pit 12 and west of Pits 19 and 20 (this may not be available due to traffic to Pits 19 and 20, which are currently open and receiving waste).

In addition, there are several smaller areas that may also be available for the staging of materials and equipment. These are located at the western ends of Pits 4 and 10, south of the roadway along the northern boundary of Pit 6, between the roadway and Trench 32 west of Pit 3, south of the Acid Pit

---

a. EG&G Idaho, Inc., *Radioactive Waste Management Complex Schematic*, May 1982.

Table 1. Decision matrix for BWID site selection

Waste Location	TRU Contamination	Intermixed TRU & LLW	Hazardous Organics	Decomposed Containers	Staging Areas	Utilities	Access	Atypical
Trenches	Yes	Yes	No	Yes	No	P	Limited	No
Pit 1	Yes	Yes	No	Yes	No	P	No	Yes
Pit 2	Yes	Yes	Limited	Yes	No	P	Yes	Yes
Pit 3	Yes	Yes	V. Limited	Yes	Yes	P	Yes	Yes
Pit 4	Yes	Yes	Yes	Yes	Limited	W	Yes	Unknown
Pit 5	Yes	Yes	Yes	Yes	Yes	P/W	Yes	Unknown
Pit 6	Yes	Yes	Yes	Yes	Limited	W	Yes	No
Pit 9	Yes	Yes	Yes	Yes	Yes	P/W	Yes	No
Pit 10	Yes	Yes	Yes	Yes	Limited	No	Yes	Yes
Pit 11	Yes	Limited	No ^a	Yes	No	No	Yes	No
Pit 12	Yes	Limited	No ^a	Yes	Yes	No	Yes	No
Acid Pit	Unknown	Unknown	Yes ^b	No	Limited	No	Yes	No
Pad A	Yes	Yes	No	Yes	Yes	P/W	Yes	No

Utilities: P = electrical power
W = water

a. Although these pits did receive drummed wastes from Rocky Flats, potential, including organic wastes, these drums were removed during the Initial Drum Retrieval project in 1974 to 1978.

b. Hazardous organics are assumed to have been disposed of in this area, but current presence of these chemicals is unknown.

LEGEND

✕—✕	FENCE	◆	FIRE HYDRANT
==	ROAD	●	SUMP
++++	RAILROAD	●	SHALLOW SOIL <12'
- - - -	DIKE OR BERM	■	MASTODON/CAMEL BONE
●—●	POWER LINE	■	ENCOUNTERED DURING EXCAVATION
- - - -	DRAINAGE DITCH	◆	UNRECORDED WASTE
		◆	DISPOSAL BOUNDARY
		▲	MONUMENT
		●	MONITORING STATION
		⊕	CEMENTED WELL
		SV	SOIL VAULT ROW (SV)

Figure 1. Map of the S

- RADIOACTIVE (LLW & TRU)
- MIXED RADIOACTIVE & ORGANICS
- TRANSURANIC WASTE ONLY
- LOW LEVEL WASTE ONLY
- LOW LEVEL WASTE (HIGH RADIATION LEVELS)
- TRANSURANIC & ORGANICS
- AS YET UNDETERMINED
- TRANSURANIC CONTAMINATED LOW-LEVEL WASTE

DA and RWMC at INEL (EG&G 1982)

/u/gls/rwmc/rwmc-b3

near the ends of soil vault Rows 6, 8, and 11, and, potentially, on Pits 11 and 12, from which most of the wastes were removed during earlier retrieval efforts.^a

4.1.2 Utilities

Both water and electrical power are available at the SDA. Water is supplied through an 8 in. main which runs along the east-west roadway on the SDA. This water is mainly for fire fighting purposes. There are two hydrants located within the SDA fence just off the southeastern corner of Pit 8 and near the southeastern corner of Pad A, near the western boundary of Pit 5.^b

Electrical power within the SDA is supplied along both the northern and southern fencelines and along the eastern boundary. Along the northern fenceline are two overhead lines, one of 12.5 kV and one of 120/240 V; there is, however an interruption in the 12.5 kV line in the area of Pad A. Along the southern fenceline are three overhead lines, one each of 7.2 kV, 480 Y/277 V (commercial and standby power), and 120/240 V. Along the eastern fenceline north of the east-west roadway, in the area of Pit 9, are two overhead lines, 12.5 kV and 480 Y/277 V. South of the roadway along the eastern fenceline are three overhead lines, 7.2 kV, 480 Y/277 V, and 120/240 V. The 120/240 V line, however, ends at a point approximately two-thirds of the distance from the southeast corner of the SDA to the east-west roadway.

Although there appears to be ample provision for the distribution of electrical power at the SDA, as described above, the actual amount of power available for use to support the various technology demonstrations may be quite limited. This should be taken into consideration prior to planning or scheduling demonstrations at the SDA.

---

a. Unpublished results of K. B. McKinley and J. D. McKinney, *Initial Drum Retrieval, Final Report*, August 1978.

b. *FY-1991 Site Development Plan-Idaho National Engineering Laboratory*, EG&G Idaho, Inc.

4.1.3 Access

Access to the SDA is provided by a network of gravel roadways. The major artery is the east-west roadway that runs the length of the SDA and borders on Pits 2, 3, 4, 5, 6, 8, 9, 15, 16, and 17, as well as Pad A. A branch off of this roadway extends southward near the ends of Pits 4 and 10. Another southern branch crosses Pit 6, runs between Pits 10 and 11, the Acid Pit, and Pit 12 and provides access to the currently open Pits 19 and 20 (see Figure 1). The network of roadways thus available provide ample access to any of the waste areas being considered as BWID demonstration sites.

4.2 LOCATION SELECTION AND METHODOLOGY

Potential BWID demonstration locations were selected from the areas considered using the matrix presented in Table 1 and the methodology as follows:

- All entries shown as "Limited" or "Unknown" were treated as "No" responses.
- A "Yes" response in the "Atypical" column removed that site from consideration.
- "Utilities" responses of "P," "W," and "P/W" qualified the location for consideration, a "No" response eliminated the location.
- The presence of more than two "No" responses for a particular site resulted in its elimination from consideration as a potential demonstration location.

There were, however, two exceptions to this method. Due to the scope of the BWID program, and because they present unique opportunities for technology demonstration, the Acid Pit and Pad A were selected as potential demonstration locations.

After taking into consideration the criteria discussed earlier, and using the methodology described above, the locations identified as potential BWID demonstration sites are Pits 4, 5, 6, and 9, the Acid Pit, and Pad A. These areas are discussed individually in the following sections. Information on waste quantities is presented where this information is currently available.

4.3 PIT 4

Pit 4 meets all of the general selection criteria for the BWID demonstration site, with TRU wastes being found intermingled with the LLW, hazardous organics being disposed of in the pit, and degraded containers being present (Arrenholz and Knight 1991). A small area for staging purposes is located at the western end of the pit; another small area is also available for this purpose along the east-west roadway immediately south of Trench 32. Water is available to this site from a hydrant located across the east-west roadway north of the northeast corner of the pit (see Figure 1). Electrical power will need to be extended to the demonstration site from the powerlines located along either the north or south fencelines. Easy access to Pit 4 is afforded by the east-west roadway and by a roadway located just to the west of the pit. One drawback to the use of this site may be the lack of detailed information concerning the disposal of atypical wastes received from offsite sources during the interim burial ground period (Bishoff 1979).

Figure 2 presents a diagram of the boundaries of Pit 4; dimensional information is also presented in this figure. The wastes disposed of in Pit 4, as well as the waste generator and amounts of wastes, are given in Table 2.

4.4 PIT 5

As with Pit 4, Pit 5 also meets all of the general selection criteria. A moderately sized area that can be used for staging purposes is located just to the east of this pit and west of Pit 8 (see Figure 1). Utilities are available in immediate proximity to the site, with electrical power available along the northern fenceline of the SDA and water from the

Figure 2. Pit 4 approximate boundaries and dimensional information.

Table 2. Pit 4 waste disposal information

Location	Date Opened	Date Closed	Container Type	Conditions	Waste Source (amount)	Waste Category	Specific Wastes	Waste Amount ^a
P 4	1-3-63 ^b	9-26-67 ^b	Drums (31411 TRU) ^c	Stacked and Random	Rocky Flats ^c NRTS ^c	Metals		
			Boxes (2368 TRU) ^c Other (1493 MFP) ^c			Radionuclides	TRU Plutonium-238 ^d Plutonium-239 ^d Plutonium-240 ^d Plutonium-241 ^d Plutonium-242 ^d Americium-241 ^d LLW Uranium-235 ^d Uranium-238 ^d MFPE	
						Inorganics	Sodium nitrate ^f Potassium nitrate ^f Portland cement ^f Calcium silicate ^f Hydrated iron oxides ^f Hydrated magnesium oxides ^f Hydrated aluminum oxides ^f Hydrated silicon oxides ^f Hydrated plutonium oxides ^f Hydrated americium oxides ^f	
						Organics	1,1,1-trichloroethane ^f Trichloroethylene ^f Perchloroethylene ^f Carbon ^f tetrachloride ^f Texaco Regal oil ^f Organophosphates ^f Nitrobenzene ^f Versene (EDTA) ^f Alcohols ^f Miscellaneous ^f Hydraulic oil ^f Gearbox oil ^f Spindle oil ^f Freon ^f Varsof ^f	trace amounts ^f trace amounts ^f

Table 2. (continued)

Location	Date Opened	Date Closed	Container Type	Conditions	Waste Source (amount)	Waste Category	Specific Wastes	Waste Amount ^a
					General Atomics ^c Lawrence Radiation Lab. ^c U.S. Nuclear Corp. ^c Others ^c Rocky Flats ^f	Atypical	scrap lumber ^c concrete ^c miscellaneous equipment ^c scrap metal, valves, piping ^c Series 746 wastes ^f (empty oil drums) ^f Series 741 ^f Series 742 ^f Series 743 ^f Series 744 ^f Series 745 ^f	
						Sludges		

a. Waste quantities are presented where information is currently available.

b. EG&G Idaho, Inc., Radioactive Waste Management Complex Schematic, May 1982.

c. D. H. Card, History of Buried Transuranic Wastes at INEL, March 1977.

d. W. H. Lee, Letter to H. F. Soule, Rocky Flats Solid Waste Shipped to NRTS, December 1971.

e. T. L. Clements, Buried Waste Characterization: Nonradiological Hazards Study--Offsite Waste Generators, October 1980.

f. M. J. Vigil, Subsurface Disposal Area (SDA) Waste Identification (1952-1970 Emphasis), EGG-WM-8727, September 1989.

water main along the southern border to the pit.^a There is easy access to the site from the east-west roadway, which is adjacent to the southern pit boundary. As with Pit 4, a drawback may be the lack of detailed information regarding the presence of atypical wastes from offsite sources.

A diagram of the boundaries of Pit 5 is presented in Figure 3, along with dimensional information for the pit. Table 3 lists the wastes, waste generators, and amounts of wastes disposed of in Pit 5.

4.5 PIT 6

Pit 6 meets all of the general selection criteria. Open area for staging purposes in the immediate area of this pit is limited to an area along the northern boundary of the pit, along the east-west roadway (see Figure 1). This is offset, however, by the presence of nearby areas (west of Pit 9 and between Pits 5 and 8) that can also be used for this purpose. The area of Pit 11, from which most of the wastes were removed during the Initial Drum Retrieval project,^b may also be available for staging purposes. Although water is available from either of the hydrants, which are located across the roadway from the pit, electrical power will need to be extended to this site. Immediate access to this pit is afforded by the east-west roadway, which borders the northern boundary of the pit, and by a southern branch of this roadway, which crosses the pit.

A diagram showing the boundaries of Pit 6 is given in Figure 4 together with dimensional information for the pit. Wastes, waste generators, and amounts of wastes contained in Pit 6 are presented in Table 4.

---

a. *FY-1991 Site Development Plan-Idaho National Engineering Laboratory*, EG&G Idaho, Inc.

b. Unpublished results of K. B. McKinley and J. D. McKinney, *Initial Drum Retrieval, Final Report*, August 1978.

T91 0337

Figure 3. Pit 5 approximate boundaries and dimensional information.

Table 3. Pit 5 waste disposal information

Location	Date Opened	Date Closed	Container Type	Conditions	Waste Source (amount)	Waste Category	Specific Wastes	Waste Amounts ^a
P 5	6-18-63 ^b	12-22-66 ^b	Drums (18486) ^c Boxes (673) Cartons (677)	Random	Rocky Flats ^c NRTS ^c	Metals Radionuclides	TRU Plutonium-238 ^d Plutonium-239 ^d Plutonium-240 ^d Plutonium-241 ^d Plutonium-242 ^d Americium-241 ^d LLW Uranium-235 ^d Uranium-238 ^d Calcium silicate ^e Hydrated iron oxides ^e Hydrated magnesium oxides ^e Hydrated aluminum oxides ^e Hydrated silicon oxides ^e Hydrated plutonium oxides ^e Hydrated americium oxides ^e	
						Organics	1,1,1-trichloroethane ^e Trichloroethylene ^e Perchloroethylene ^e Carbon tetrachloride ^e Texaco Regal oil ^e Organophosphates ^e Nitrobenzene ^e Miscellaneous: Hydraulic oil ^e Gearbox oil ^e Spindle oil ^e Freon ^e Varsoil ^e	trace amounts ^e trace amounts ^e

Table 3. (continued)

Location	Date Opened	Date Closed	Container Type	Conditions	Waste Source (amount)	Waste Category	Specific Wastes	Waste ^a Amounts
						Atypical Sludges	Series 741 ^e Series 742 ^e Series 743 ^e	
a. Waste quantities are presented where information is currently available. b. EG&G Idaho, Inc., <u>Radioactive Waste Management Complex Schematic</u>, May 1982. c. D. H. Card, <u>History of Buried Transuranic Wastes at INEL</u>, March 1977. d. W. H. Lee, Letter to H. F. Soule, <u>Rocky Flats Solid Waste Shipped to NRTS</u>, December 1971. e. M. J. Vigil, <u>Subsurface Disposal Area (SDA) Waste Identification (1952-1970 Emphasis)</u>, EGG-WM-8727, September 1989.								

T91 0338

Figure 4. Pit 6 approximate boundaries and dimensional information.

Table 4. Pit 6 waste disposal information

Location	Date Opened	Date Closed	Container Type	Conditions	Waste Source (amount)	Waste Category	Specific Wastes	Waste Amounts
P 6	5-18-67 ^b	10-22-68 ^b	Drums (14396) ^c Boxes (3423) ^c	Random	Rocky Flats ^c NRTS ^c	Metals Radionuclides	TRU Plutonium-238 ^d Plutonium-239 ^d Plutonium-240 ^d Plutonium-241 ^d Plutonium-242 ^d Americium-241 ^d Sodium nitrate ^e Potassium nitrate ^e Calcium silicate ^e Portland cement ^e Hydrated iron oxides ^e Hydrated magnesium oxides ^e Hydrated aluminum oxides ^e Hydrated silicon oxides ^e Hydrated plutonium oxides ^e Hydrated americium oxides ^e 1,1,1-trichloroethane ^e Trichloroethylene ^e Perchloroethylene ^e Carbon tetrachloride ^e Texaco Regal oil ^e Polychlorinated biphenyls ^e Organophosphates ^e Nitrobenzene ^e Alcohols ^e VERSENE (EDTA) ^e Miscellaneous: Hydraulic oil ^e Gearbox oil ^e Spindle oil ^e Freon ^e Varso ^e	trace amounts ^e trace amounts ^e
					Rocky Flats	Atypical	Series 746 waste ^c (2451 boxes empty oil drums) ^e	

Table 4. (continued)

Location	Date Opened	Date Closed	Container Type	Conditions	Waste Source (amount)	Waste Category	Specific Wastes	Waste Amounts ^a
						Sludges	Series 741 ^e Series 742 ^e Series 743 ^e Series 744 ^e Series 745 ^e	

a. Waste quantities are presented where information is currently available.

b. EG&G Idaho, Inc., Radioactive Waste Management Complex Schematic, May 1982.

c. D. H. Card, History of Buried Transuranic Wastes at INEL, March 1977.

d. W. H. Lee, Letter to H. F. Soule, Rocky Flats Solid Waste Shipped to NRTS, December 1971.

e. M. J. Vigil, Subsurface Disposal Area (SDA) Waste Identification (1952-1970 Emphasis), EGG-WM-8727, September 1989.

4.6 PIT 9

Pit 9 also meets the four general selection criteria, and is attractive due to the large amount of work that has been done on the pit to identify the pit contents.^a There is a large area for staging materials and equipment immediately to the west of the pit (see Figure 1). Both electrical power and water are easily accessible, with both utilities running along the pit boundaries.^b The pit is also easily accessible, being located just inside the entrance to the SDA with the east-west roadway adjacent to the southern pit boundary. Atypical wastes are present in limited amounts and consist mainly of boxes of empty drums from Rocky Flats.^c A limited amount of waste generated as a result of a fire at RFP on May 11, 1969, may also be disposed of in this pit (Vigil 1989).

Boundaries of Pit 9, and dimensional information for this pit, are shown in Figure 5. Waste related information, including waste constituents, generators, and amounts, for Pit 9 are presented in Table 5.

4.7 ACID PIT

The Acid Pit, which is primarily a contaminated soil problem, was selected in order to provide an alternative waste environ for technology demonstrations under the BWID program. There is a significant lack of verifiable information regarding the types and amounts of wastes disposed of in the Acid Pit. Furthermore, no containers (other than bottles of unusable or outdated chemicals) were disposed of in this area. An advantage to this site is the planned sampling of soils within the perimeter of the Acid Pit, which is scheduled to be conducted during Fiscal Year 1992 (Lugar 1990).

---

a. Unpublished reports of E. C. Garcia and J. L. Knight, *EPA Toxic and Ordinary Metal Contents in Pit 9*, January 1989, *Hazardous Organic Content of Pit 9*, January 1989, *Hazardous Inorganic Content of Pit 9*, January 1989, *Detailed Estimate of Radioactive Material Contents for Pit 9*, February 1989, and T. E. Wierman, *ISV Field Test Siting and Source Terms*, May 1990.

b. *FY-1991 Site Development Plan-Idaho National Engineering Laboratory*, EG&G Idaho, Inc.

c. D. H. Card, *History of Buried Transuranic Wastes at INEL*, March 1977.

Excavated volume: 342,416 cubic feet
Surface area: 43,802 square feet
Depth: 8 feet
Overburden: 6 feet
Underburden: 3.5 feet
Estimates from Guay, 1989

T91 0339

Figure 5. Pit 9 approximate boundaries and dimensional information.

Table 5. Pit 9 waste disposal information

Location	Date Opened	Date Closed	Container Type	Conditions	Waste Source (amount)	Waste Category	Specific Wastes	Waste Amount ^a
P 9	11-8-67 ^b	6-9-69 ^b	Drums (3921) ^c Boxes (2029) ^c	Random	Rocky Flats ^c NRTS ^c	Metals	Beryllium ^d	41 gal ^{d*}
							Lithium ^d	238 gal ^{d*}
							Sodium (and compounds) ^d	3,469 gal ^{d*}
							Mercury ^d	
							Carbon steel ^e	326,501.8 kg ^{e*}
							Stainless steel ^e	309,693.8 kg ^{e*}
							Aluminum ^e	2,337.4 kg ^{e*}
							Iron ^e	2,668.8 kg ^{e*}
							Lead ^e	7,033.3 kg ^{e*}
							Zirconium ^e	17,420.0 kg ^{e*}
							TRU	
							Plutonium-238 ^f	0.0015 kg ^{g*}
							Plutonium-239 ^f	15.2 kg ^{g*}
							Plutonium-240 ^f	0.952 kg ^{g*}
							Plutonium-241 ^f	0.074 kg ^{g*}
							Plutonium-242 ^f	0.003 kg ^{g*}
							Americium-241 ^f	0.622 kg ^{g*}
							LLW	
							Uranium-234 ^g	0.0032 kg ^{g*}
							Uranium-235 ^g	
							Uranium-238 ^g	11,700.5 kg ^{g*}
							Cobalt-60 ^g	
							MAP ^g	
							MFp ^g	
							Unidentified beta/gamma ^g	
							Inorganics	
							Sodium nitrate ^h	20,099 gal ^{d*}
							Potassium nitrate ^h	10,050 gal ^{d*}
							Calcium silicate ^h	58,775 gal ^{d*}
							Portland cement ^h	4,182 gal ^{d*}
							Asbestos ^d	87,466.8 kg ^{d*}
							Thallium oxide ^d	3 gal ^{d*}
							Caustic compounds ^d	859 gal ^{d*}
							Sodium Hydroxide ^d	
							Acids	1,255 gal ^{d*}
							Hydrofluoric acid ^d	
							Hydrochloric acid ^d	

* estimated

Table 5. (continued)

Location	Date Opened	Date Closed	Container Type	Conditions	Waste Source (amount)	Waste Category	Specific Wastes	Waste Amount ^a
							Hydrated oxides ^h	16,075 gal ^{d*}
							Hydrated iron oxides ^h	
							Hydrated magnesium oxide ^h	
							Hydrated aluminum oxides ^h	
							Hydrated silicon oxides ^h	
							Hydrated plutonium oxide ^h	
							Hydrated americium oxide ^h	
						Organics	1,1,1-trichloroethane ^h	753 gal ^{i*}
							Trichloroethylene ^h	565 gal ^{i*}
							Perchloroethylene ^h	565 gal ^{i*}
							Carbon tetrachloride ^h	3,677 gal ^{i*}
							Texaco Regal oil ^h	5,875 gal ^{i*}
							Polychlorinated biphenyls ^h	0.10 gal ^h
							Organophosphates ^h	trace amounts ^h
							Nitrobenzene ^h	trace amounts ^h
							Alcohols ^h	1,287 ^{i*}
							VERSENE (EDTA) ^h	1,287 ^{i*}
							Ether ⁱ	838 gal ^{i*}
							Organic acids ⁱ	1,287 gal ^{i*}
							Gasoline ⁱ	163 gal ^{i*}
							Ethylene glycol ⁱ	49 gal ^{i*}
							Miscellaneous:	
							Used oils	2,378 gal ^{i*}
							Hydraulic oil ^h	
							Gearbox oil ^h	
							Spindle oil ^h	
							Freon ^h	
							Varsol ^h	
						Rocky Flats	RFP fire wastes ^c	
						Atypical	6 x 6 ft stainless steel vault ^j	
							Series 746 waste (1302 boxes empty oil drums) ^h	
							Series 741 ^h	17,579 gal ^{i*}
						Sludges	Series 742 ^h	23,798 gal ^{i*}
							Series 743 ^h	37,760 gal ^{i*}
							Series 744 ^h	8,043 gal ^{i*}
							Series 745 ^h	33,499 gal ^{i*}

* estimated

Table 5. (continued)

- a. Waste quantities are presented where information is currently available.
- b. EG&G Idaho, Inc., Radioactive Waste Management Complex Schematic, May 1982.
- c. D. H. Card, History of Buried Transuranic Wastes at INEL, March 1977.
- d. E. C. Garcia and J. L. Knight, Hazardous Inorganic Content of Pit 9, January 1989.
- e. E. C. Garcia and J. L. Knight, EPA Toxic and Ordinary Metal Content in Pit 9, January 1989.
- f. W. H. Lee, Letter to H. F. Soule, Rocky Flats Solid Waste Shipped to NRTS, December 1971.
- g. E. C. Garcia and J. L. Knight, Detailed Estimate of Radioactive Material Contents for Pit 9, February 1989.
- h. M. J. Vigil, Subsurface Disposal Area (SPA) Waste Identification (1952-1970 Emphasis), EGG-WM-8727, September 1989.
- i. E. C. Garcia and J. L. Knight, Hazardous Organic Content of Pit 9, January 1989.
- j. K. B. McKinley and J. D. McKinney, Initial Drum Retrieval Final Project, TRFF-1286, August 1978.

Utilities, both electrical power and water, to support demonstrations at the Acid Pit will need to be extended to the site as it is located near the center of the SDA. The need for an area for staging purposes may be satisfied by the small area located immediately south of the Acid Pit (see Figure 1). There is no evidence that atypical wastes are present in the Acid Pit.

Figure 6 shows the approximate outline of the boundaries of the Acid Pit. A list of the wastes presumed to have been disposed of in this area is presented in Table 6; actual wastes and amounts disposed of the Acid Pit are uncertain due to the lack of verifiable documentation.

4.8 PAD A

Like the Acid Pit, Pad A was chosen primarily in order to provide an alternative waste environment for technology demonstrations. In this case, the waste containers are located above grade and are covered with earth. The waste types and amounts present at Pad A are fairly well documented.^a Although there is no indication of hazardous organics being present, the other general selection criteria are met by the wastes located on the pad. In addition, open space for the staging of materials and equipment can be found in close proximity, utilities needed to support the demonstrations are located immediately adjacent to the pad, and there is easy access to the pad from the east-west roadway, which borders on the pad (see Figure 1). Atypical wastes are not present on the pad.

A drawing showing the outline of the Pad A boundaries, together with the approximate limits of the wastes disposed, is presented in Figure 7. A listing of the wastes, and amounts of wastes, disposed in this area is given in Table 7.

---

a. Unpublished report by J. J. King, *Pad A, Chemical and Radiological Inventory, and Limited Sampling Analysis: Preliminary Evaluation*, January 1991.

T91 0387

Figure 6. Acid Pit approximate boundaries.

Table 6. Acid Pit waste disposal information

Location	Date Opened	Date Closed	Container Type	Conditions	Waste Source (amount)	Waste Category	Specific Wastes	Waste Amount ^a
Acid Pit	1-1-54 ^b	1-1-61 ^b	None (uncontained liquids only)		NPTS	Inorganics	Nitric acid ^c Hydrochloric acid ^c Sulfuric acid ^c Sodium hydroxide ^c	
						Organics	Carbon tetrachloride ^c Machining oils ^c	

a. Waste quantities are presented where information is currently available.

b. EG&G Idaho, Inc., Radioactive Waste Management Complex Schematic, May 1982.

c. M. J. Vigil, Subsurface Disposal Area (SDA) Waste Identification (1952-1970 Emphasis), EGG-WM-8727, September 1989.

T91 0388

Figure 7. Pad A approximate waste limits.

Table 7. Pad A waste disposal information

Location	Date		Container type	Conditions	Waste Source (amount)	Waste Category	Specific Wastes	Waste Amounts ^a
	Opened	Closed						
Pad A	9-26-72 ^b	11-17-78 ^b	Drums (18739) ^c Boxes (2027) ^c	Stacked	Rocky Flats NRTS	Metals	Beryllium ^c	
						Radionuclides	TRU Plutonium-238 ^c Plutonium-239 ^c Plutonium-240 ^c Plutonium-241 ^c Thorium-232 ^c Americium-241 ^c	
							LLW Manganese-54 ^c Cobalt-60 ^c Ruthenium-106 ^c Cesium-134 ^c Cesium-137 ^c Cesium-141 ^c Europium-154 ^c Uranium-234 ^c Uranium-235 ^c Uranium-238 ^c	
						Salts	Potassium nitrate ^d Sodium nitrate ^d Miscellaneous ^d	approx. 30% of total approx. 60% of total approx. 10% of total

a. Waste quantities are presented where information is currently available.

b. EG&G Idaho, Inc., Radioactive Waste Management Complex Schematic, May 1982.

c. Unpublished report by J. J. King, Pad A Chemical and Radiological Inventory and Limited Sampling Analysis: Preliminary Evaluation, January 1991.

d. T. L. Clements, Content Code Assessments for INEL Contact-Handled Stored Transuranic Wastes, October 1982.

5. CONCLUSION

This report presents the results of the process used to identify potential BWID demonstration locations. Technology-specific demonstration areas will be chosen through consultation with DOE, representatives of the other DOE field offices, participants in the BWID program, members of the Buried Waste Program at EG&G Idaho, technology sponsors, and operations personnel at the Radioactive Waste Management Complex, who are responsible for the SDA. Upon selection of the BWID demonstration locations, a more detailed characterization of the area may be conducted by the INEL Environmental Restoration Program. This effort will further define the waste types and amounts, and disposal locations for the BWID locations. This characterization will rely not only on historical documentation, as used to prepare this report, but will also require the review of the available disposal records from the location selected.

6. REFERENCES

- Arrenholz, D. A., Knight, J. L., *A Brief Analysis and Description of Transuranic Wastes in the Subsurface Disposal Area of the Radioactive Waste Management Complex at INEL*, EGG-WTD-9438, Rev. 1, August 1991.
- Lugar, R. M., *Radioactive Waste Management Complex Subpit Sampling and Analysis Plan*, Rev. 1, EGG-WM-8934, September 1990.
- Vigil, M. J., *Subsurface Disposal Area (SDA) Waste Identification (1952-1970 Emphasis)*, EGG-WM-8727, September 1989.

END

DATE
FILMED

6/03/92