**DOE/MC/26044-3053
(DE92001135)**

**WEAR MECHANISM AND WEAR PREVENTION IN COAL-FUELED DIESEL
ENGINES**

Task VII: Extended Wear Testing

Topical Report

**By
J. F. Wakenell
S. G. Fritz
J. A. Schwalb**

July 1991

Work Performed Under Contract No. AC21-89MC26044

**For
U.S. Department of Energy
Morgantown Energy Technology Center
Morgantown, West Virginia**

**By
Southwest Research Institute
San Antonio, Texas**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

**Wear Mechanism and Wear Prevention in
Coal-Fueled Diesel Engines
Task VII: Extended Wear Testing**

Topical Report

**J.F.Wakenell
S.G.Fritz
J.A.Schwalb**

Work Performed Under Contract No.: DE-AC21-89MC26044

**For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
P.O. Box 880
Morgantown, West Virginia 26507-0880**

**By
Southwest Research Institute
Engine, Fuel, and Vehicle Research Division
6220 Culebra Road
San Antonio, Texas 78228-0510**

July 1991

TABLE OF CONTENTS

	<u>Page</u>
I. INTRODUCTION	1
II. EXPERIMENTAL APPARATUS AND PROCEDURE	1
A. Engine Description	1
B. Engine Test Cycle	2
C. Engine Instrumentation	3
D. Test Procedure	3
III. FUELS	4
IV. EXPERIMENTAL RESULTS	4
A. Performance Tests	4
B. Emissions Tests	10
1. <i>Gaseous Emission Measurement</i>	10
2. <i>Particulate Emission Measurement</i>	12
3. <i>Emission Test Results</i>	12
C. Wear Results	13
V. DISCUSSION	25
A. Performance Tests	25
B. Wear Tests	25
C. Emissions Tests	25
VI. CONCLUSIONS	26
APPENDIX A	A-1
APPENDIX B	B-1
APPENDIX C	C-1
APPENDIX D	D-1
APPENDIX E	E-1
APPENDIX F	F-1

LIST OF ILLUSTRATIONS

<u>Figure</u>	<u>Page</u>
1 BHP Versus Notch Position	6
2 BMEP Versus Notch Position	7
3 Fuel Rate Versus Notch Position	8
4 T.E. Versus Notch Position	9
5 BSFC Versus Notch Position	11
6 EMD 2-567 Engine Corrected NO _x Mass Emission Rate at Each Notch Position, Before and After a 500-Hour Durability Test, on Both Test Fuels	14
7 EMD 2-567 Engine Carbon Monoxide Mass Emission Rate at Each Notch Position, Before and After a 500-Hour Durability Test, on Both Test Fuels	15
8 EMD 2-567 Engine Hydrocarbon Mass Emission Rate at Each Notch Position, Before and After a 500-Hour Durability Test, on Both Test Fuels	16
9 EMD 2-567 Engine Average Particulate Mass Emission Rate at Each Notch Position, Before and After a 500-Hour Durability Test, on Both Fuels	17
10 SO ₂ EMD 2-567 Engine SO ₂ Emission Rate at Each Notch Position, Before and After a 500-Hour Durability Test, on Both Fuels	18
11 EMD Pistons	24

LIST OF TABLES

<u>Table</u>		<u>Page</u>
1	Engine Specifications	1
2	Engine Speed and Fuel Flowrate Combinations	2
3	Properties of the Engine Test Fuels	5
4	Summary of Emissions Data for the EMD 2-567 Locomotive Engine	19-22
5	Weighted Composite Brake Specific Emissions Summary for the EMD 2-567 Locomotive Engine	23

I. INTRODUCTION

Over the past several years, interest has arisen in the development of coal-fired diesel engines for the purpose of efficiently utilizing the extensive coal reserves in the United States, and therefore reducing dependence on foreign oil. One process which is being considered for use in producing clean coal fuel products involves mild gasification. This process produces by-products which can be further refined and, when blended with neat diesel fuel, used as an engine fuel. The purpose of this task was to test a blend of this coal liquid and diesel fuel (referred to as coal-lite) in an engine, and determine if any detrimental results were observed. This was done by performing a back-to-back performance and emission test of neat diesel fuel and the coal-lite fuel, followed by a 500-hour test of the coal-lite fuel, and completed by a back-to-back performance and emission test of the coal-lite fuel and neat diesel fuel.

II. EXPERIMENTAL APPARATUS AND PROCEDURE

A. Engine Description

The engine chosen as the test bed in this experiment was the two-cylinder version of the Electro-Motive Division of General Motors (EMD) 567 locomotive engine. This engine was chosen specifically because one of the markets for this fuel is the railroad industry. The two-cylinder engine was used, quite simply, because of the lower operating costs and fuel consumption and lower repair costs if detrimental results were observed. The EMD two-cylinder 567 engine was a limited production research engine built by EMD and designed specifically for research use. The engine is a two-stroke cycle, blower-scavenged unit with a displacement of 567 cubic inches per cylinder that produces 215 brake horsepower at 835 rpm. Details of the engine are presented in Table 1.

Table 1. Engine Specifications	
	EMD 2-567B
Number of Cylinders	2
Displacement (cu. in./cyl.)	567
Bore and Stroke (in.)	8.5 x 10
Rated Speed (rpm)	835
Rated Brake Horsepower	215
Compression Ratio	16.1
Cycle	2
Injection System	Unit Injector

The 567 series engines were produced and used by the railroad industry in 6, 8-, 12-, and 16-cylinder configurations. The engine is loaded by a DC generator and the power is absorbed by a resistive load grid, water cooled for heat dissipation.

B. Engine Test Cycle

The engine was operated at conditions that simulated the notch operation of a locomotive. Locomotive engines operate only at specified speed/power combinations defined by throttle positions or "notches." Since the power output and speed are constant at each notch position, the fuel consumption rate is also constant and can be defined for each position. EMD engines in locomotive service operate at eight power producing notches. There are also idle and, in some locomotives, low idle operating positions. To facilitate fuel testing, the positions were redefined in terms of speed and load combinations (see Table 2).

Table 2. Engine Speed and Fuel Flowrate Combinations			
Notch Position	Engine Speed (RPM)	Fuel Flowrate (kg/hr)	Typical BHP
8*	835	40.8	207
7	755	34.0	178
6	675	27.2	149
5	585	20.4	114
4	515	15.0	77
3	425	9.5	47
2	345	5.4	20
1	285	3.6	8
Idle	285	2.5	0
* Notch 8 of the schedule represents rated speed and load of the engine. All other positions represent part-load conditions.			

Fuel rate for the two-cylinder EMD 567 research engine was taken as 1/8 the typical values for the 16-cylinder 567 C with 16:1 compression ratio pistons. Unlike revenue service locomotive engines, the two-cylinder engine is equipped with a

pneumatic governor that permits infinite variations of both speed and load. However, during testing the engine was operated only at the speeds and fuel consumption rates corresponding to the notch schedule presented in Table 2:

Performance data was corrected to standard ambient conditions in all cases. Factors defined by EMD were applied to correct performance to 60° F and 29.9 in-Hg. Engine test data have shown the engine manufacturers recommended factors to provide the best correlation for correction.

C. Engine Instrumentation

The test engine was instrumented to monitor engine speed, power output and pressures and temperatures throughout the lubricating, cooling, intake and exhaust systems. Smoke density was measured using the Bosch method. A Micro-Motion mass flowmeter provided a continuous mass fuel flow rate measurement.

Engine instrumentation was connected to a low-speed data acquisition system. In addition to monitoring pressures and temperatures, the computer system also monitored alternator voltage and amperage output, the Micro-Motion voltage signal and engine speed. A computer averaging routine was employed for all performance measurements. During the performance tests, signals were recorded once every five seconds for approximately 20 minutes to provide a total of 250 data sampling readings. The 250 readings were averaged and the power output, thermal efficiency, mean effective pressure, and brake specific fuel consumption were calculated based on these averages. This procedure accounted for periodic oscillations in power output and fuel consumption rate and resulted in an accurate fuel consumption measurement.

D. Test Procedure

The study began with a tear-down and reassembly of the engine power packs (pistons, rings, and liners) for baseline measurement. Ring and liner measurements were performed using standard measurement instruments. Two new fuel injectors were "pop tested" for conformation of integrity and installed in the engine. Next, a nine hour baseline neat diesel fuel performance, economy, and emission test at all eight throttle notches (and idle) was performed.

Next, in order to evaluate the affects of the test (coal-lite) fuel, the engine was purged with the test fuel and a nine hour performance, economy, and emission test run using the test fuel. Data was recorded at each notch position. Upon completion of the performance test, the 500 hour durability test was performed. This test consists of 250 two-hour cycles at Notch 8, 5, and idle. During the durability test, performance data was recorded at Notch eight only. Emissions measurements were not taken during the durability test. Following the 500 hour test, another nine hour

performance, economy, and emission test using the test fuel was conducted in order to assess any performance loss as a result of engine wear. These results were compared to the pre-500 hour test fuel run.

The final engine test was performed using neat diesel fuel for a comparison to the baseline test.

Upon completion of the engine tests the engine power packs were removed and disassembled for inspection and measurement. Photographs were taken to visually record engine wear and carbon deposition. Engine wear was assessed based on a comparison to the initial measurement and visual inspection. The fuel injectors were again "pop tested" to check for injector dribbling. After which, the injectors were disassembled and inspected and measured.

III. FUELS

The fuels used for this evaluation were neat diesel fuel and the coal-lite liquid. The neat diesel fuel was a commercially available No. 2 diesel. Chemical analysis of the fuels are presented in Table 3.

IV. EXPERIMENTAL RESULTS

A. Performance Tests

The performance test results for all four performance tests are shown in Figures 1 through 5. Basically, there is very little difference between all the fuels. During the tests, horsepower was held constant as indicated in Figure 1. Therefore, there also should not be any differences in BMEP as shown in Figure 2. Because horsepower was held constant, any performance differences encountered as a result of the fuel differences would be detected in fuel consumption, BSFC, and possibly thermal efficiency.

Shown in Figure 3, is a plot of fuel consumption for each notch position. For the most part, fuel consumption was approximately the same for Notches 1 through 5. At the higher notches, fuel consumption varied. At Notch eight, the first coal-lite test fuel consumption was 4 percent greater than the first baseline. This increase in fuel consumption could be a function of two factors. Shown in Figure 4, thermal efficiency at Notch eight for the first coal-lite test was 3 percent less than the first baseline. This is a function of how efficiently the combusted fuel (heat) is converted into work, and partially accounts for the increase in fuel consumption. The other one percent difference is most likely a result of the 1 percent lower heating value of the fuel as shown in Table 3. The combined effect of a lower heat of combustion and reduced thermal efficiency will account for the increased fuel consumption. Notch eight was used as the example here, however the same conclusion can be drawn for the other notches where the difference was significant.

Table 3. Properties of the Engine Test Fuels

Property	Procedure ^a	Neat No. 2 Diesel Fuel	Coal-Lite Fuel
Gravity, ° APL, 60° F	D1298		29.8
Specific Gravity, 60° F			.8767
Distillation, ° F: IBP/5 ^b 10/20 30/40 50/60 70/80 90/95 EP ^c Recovery, % Residue, %	D86	344/394 425/461 490/508 525/540 560/578 611/636 660 99.5 0.5	354/392 425/456 480/499 518/534 555/578 609/633 653
Viscosity: cSt @ 104° F (40° C) SUS @ 104	D445		2.8
Flash Point, ° F	D93		154
Elemental Analysis, % Carbon Hydrogen Sulfur Nitrogen Oxygen (difference)	D3178 CEC 240 ^d XRF Chemilumi nescent	86.77 12.80 0.324 0.43	86.42 12.01 0.506 0.136 0.92
Hydrocarbon Type, (FIA) % Aromatics Olefins Saturates	D1319		45.5 1.2 53.3
Heat of Combustion Gross, Btu/lb Gross, MJ/kg Net, Btu/lb Net, MJ/kg	D240	19405 45.133 18187 42.300	19023 44.249 17928 41.702
Accelerated Stability, mg/100 ml	D2274		6.2
Carbon Residue, 10% Btms, wt%	D524		0.35
Particulates	D2276		12.6
Metals, ppm in fuel: Vanadium Potassium Nickel Iron	ICP ^d		<1 <25 <1 <1

a = Numbers preceded by a D are ASTM
d = Instrumental analysis

b = IBP is the initial boiling point
e = Inductively coupled plasma

c = EP is the end point

— Baseline # 1 - - - Coal-Lite # 1 . . . Coal-Lite # 2

Figure 1. BHP Versus Notch Position

— Baseline # 1 ····· Coal-Lite # 1 - - - - Baseline # 2 - ····· Coal-Lite # 2

Figure 2. BMEP Versus Notch Position

Figure 3. Fuel Rate Versus Notch Position

— Baseline # 1 ··· Coal-Lite # 1 - - - Baseline # 2 - · - Coal-Lite # 2

Figure 4. T.E. Versus Notch Position

Also shown at Notch eight (Figure 3), is a roughly 2 percent increase in fuel consumption for the post 500-hour coal-lite test. The immediate question asked is why this differs from the first coal-lite test (4 percent increase). The explanation here is not quite as clear however, it is suspected that throughout the 500-hour test, the engine was continuing to seat in the rings and liners and that motoring friction was higher for the pre 500-hour tests. This would result in greater fuel consumption at the start of test for both fuels when compared to the end of test (500 hours) results, and in fact, that is what was observed.

Finally, shown in Figure 5, is a plot of BSFC verses notch position. BSFC is determined by dividing fuel rate by horsepower. Specific fuel consumption is a comparative parameter that describes how efficiently the engine converts fuel into work. BSFC comparisons are preferred to thermal efficiency because all parameters are measured in standard and accepted units: time, horsepower, and mass. In any case, both thermal efficiency and BSFC indicate how efficiently the engine is working and the trends shown in Figure 5 (BSFC) are the same as those shown in Figure 4 (thermal efficiency).

B. Emissions Tests

The Department of Emissions Research of Southwest Research Institute (SwRI) performed steady-state gaseous and particulate emission tests on the engine using both fuels. The tests were performed before and after the 500-hour engine durability test of the coal-lite fuel. This report section summarizes the emissions test procedure and gives a detailed listing of the emission results as well as a composite emissions factor comparison of the baseline diesel fuel and the coal-lite fuel.

Gaseous Emission Measurement

Gaseous emission measurements during each steady-state test condition were obtained by sampling raw exhaust following procedures detailed in 40 CFR Part 86, Subpart D. Exhaust gases were analyzed for unburned hydrocarbons (HC), carbon monoxide (CO), oxides of nitrogen (NO_x), carbon dioxide (CO_2), and oxygen (O_2). Hydrocarbons were measured by a heated flame ionization detector (HFID) unit built to specifications given in SAE Recommended Practice J215. Carbon monoxide and carbon dioxide were measured by a non-dispersive infrared (NDIR) analyzer in a system that conforms to SAE Recommended Practice J177a. Oxides of nitrogen were measured using a chemiluminescent analyzer.

Sulfur dioxide (SO_2) mass emission rates were also determined for the EMD 2-567B engine. The exhaust of SO_2 in the diesel exhaust was measured as sulfate

Figure 5. BSFC Versus Notch Position

using an ion chromatograph following EPA procedures¹. SO₂ exhaust samples were collected in two glass bubblers, each containing 3 percent hydrogen peroxide. The temperature of the absorbing solution was kept at 0°C by means of an ice water bath. The bubbled samples were analyzed on an ion chromatograph and compared to standards of known sulfate concentrations. The measured SO₂ mass concentration in the exhaust were then compiled with the measured engine exhaust flow rates to compute the mass emission rate of SO₂.

Particulate Emission Measurement

Particulate measurements during each steady-state test condition were obtained using a "splitter" dilution system. The splitter system splits off a portion of the total raw exhaust flow and mixes it with dilution air. Mixing occurs in a dilution tunnel prior to sampling the mixture for particulate. The stainless steel dilution tunnel used for this work was 20 centimeters (8 inches) in diameter and approximately 5 meters (15 feet long). Particulate mass samples were collected on dual 47-mm Pallflex T60A20 fluorocarbon-coated glass fiber filters (primary and backup). Dilution air and the split-off portion of the total exhaust were regulated such that the maximum temperature at the filter sample zone was 52°C (125°F). All filters were weighed in a temperature and humidity controlled chamber to ensure consistency of results.

Emission Test Results

Mass emission rates of HC, CO, NO_x, particulates, and SO₂ were computed using the raw gaseous emissions measurements, the particulate tunnel flow data along with the particulate filter weight gain, and the engine air flow, fuel flow, and power output data. For the test performed in this program, the power output (bhp) at each notch position was held constant and observations of the mass flow rate of the fuel were made.

Individual emission test results for each test point are given in Appendices A-D. Included are the baseline pre 500-hour baseline test on diesel fuel (Appendix A), the pre 500-hour test on the coal-lite fuel (Appendix B), the post 500-hour test on the coal-lite fuel (Appendix C), and the final post 500-hour test on the baseline diesel (Appendix D).

A summary of the NO_x mass emission rates are shown in Figure 6. Note that ambient air temperature and humidity are known to affect internal combustion engine exhaust emissions. NO_x is especially sensitive to these factors, and as a result, NO_x correction factors are commonly used to adjust observed NO_x results to standard conditions. For this project, SwRI has reported NO_x values corrected to:

¹ "Analytical Procedures for Characterizing Unregulated Emissions from Vehicles Using Middle-Distillate Fuels" EPA Interim Report EPA-600/2-80-0068, 1980.

1. 85°F engine intake air temperature,
2. 75 grains of water per pound of dry air humidity.

The engine intake air temperature correction factor and humidity correction factor vary with measured fuel/air ratio (i.e. engine load). These correction factors are used for EPA 13-mode steady-state testing and are referenced in 40 CFR, Subpart D 86.345-79. The NO_x values shown in Figure 6 and Appendices A-D are the corrected values.

Figures 7, 8, 9, and 10 give summaries of the measured mass emission rates at each notch position for carbon monoxide, hydrocarbons, particulates, and sulfur dioxide, respectively.

A duty-cycle based weighting procedure was used in determining composite brake specific emissions. The weighting factors used in determining composite brake-specific emissions are typical of a locomotive line-haul duty cycle, and are fairly representative of locomotive operations through out the U.S.; with approximately 10 percent of the time spent at rated conditions (Notch 8) and a significant amount of time (55 percent) at idle. The remainder of the time is spent distributed over the other throttle notch positions. Table 4 shows the un-weighted and weighted emission results, as well as the composite weighted brake specific exhaust emissions expressed in g/bhp-hr.

The composite brake specific emissions for the EMD 2-567B operating on both baseline ASTM 2D diesel and the coal-lite fuel are summarized in Table 5.

C. Wear Results

Engine wear was assessed based on visual inspection and physical wear measurements. Wear measurements were taken according to the standard EMD dimension sheets. Sheets 1 through 26 are presented in Appendix C. Generally, in 500 hours of operation, wear in this class of engine should be at the lower limits of measurable range. Measurable range using classical measurement tools is typically 0.001" or greater. Therefore, wear reported less than 0.001" can be considered beyond the range of measurement accuracy. However, wear greater than 0.001" for this engine can be considered significant.

Of particular interest, when evaluating alternative fuels, is the ring and liner wear. These surfaces are normally the first to show signs of abnormal wear with undesirable fuels. As shown, on dimension sheets 13, 14, and 21, 22, the wear was

sgl/2681/summary.wq1/910430

SwRI

Figure 6. EMD 2-567 Engine Corrected NO_x Mass Emission Rate at Each Notch Position, Before and After a 500-Hour Durability Test, on Both Test Fuels.

SwRI

sgl/2681/summary.wq1/910430

Figure 7. EMD 2-567 Engine Carbon Monoxide Mass Emission Rate at Each Notch Position, Before and After a 500-Hour Durability Test, on Both Test Fuels.

sg/2681/summary.wq1/910430

SwRI

Figure 8. EMD 2-567 Engine Hydrocarbon Mass Emission Rate at Each Notch Position, Before and After a 500-Hour Durability Test, on Both Test Fuels.

SwRI

sgl/2681/summary.wq1/910430

Figure 9. EMD 2-567 Engine Average Particulate Mass Emission Rate at Each Notch Position, Before and After a 500-Hour Durability Test, on Both Fuels.

sgl/2681/summary.wq1/910515

SwRI

Figure 10. SO₂ EMD 2-567 Engine SO₂ Emission Rate at Each Notch Position, Before and After a 500-Hour Durability Test, on Both Fuels.

Table 4. Summary of Emissions Data for the EMD 2-567 Locomotive Engine

***** Weighted g/hr *****										
Test Summary 1/31/91					Baseline Diesel			BHP		
Notch	BHP	HC g/hr	CO g/hr	Corr. NO _x g/hr	Avg. Part. g/hr	Meas. SO ₂ g/hr	wf	BHP	HC g/hr	CO g/hr
8	207	157	531	2743	89	260	0.10	21	16	53
7	178	140	254	2360	91	183	0.05	9	7	13
6	149	126	127	2121	74	139	0.05	7	6	6
5	114	100	93	1462	67	99	0.05	6	5	5
4	77	77	62	893	51	77	0.05	4	4	3
3	47	57	59	520	55	50	0.05	2	3	3
2	20	53	58	257	120	25	0.05	1	3	3
1	8	40	45	138	nd	15	0.05	0	2	2
idle	0	37	35	100	53	15	0.55	0	20	19
Sum						1.00	50	66	107	717
Weighted Composite g/hp-hr =									1.3	2.1
									14.2	1.29
									26	64

Table 4. Summary of Emissions Data for the EMD 2-567 Locomotive Engine(Continued)

Test Summary 1/31/91					Baseline Diesel			***** Weighted g/hr *****					
Notch	BHP	HC g/hr	CO g/hr	Corr. NO _x g/hr	Avg. Part. g/hr	Meas. SO ₂ g/hr	wf	BHP	HC g/hr	CO g/hr	Corr. NO _x g/hr	Avg. Part. g/hr	Mea s. SO ₂ g/hr
8	206	263	906	2894	73	552	0.10	21	26	91	289	7	55
7	179	160	396	2585	68	424	0.05	9	8	20	129	3	21
6	149	121	210	2210	57	331	0.05	7	6	10	110	3	17
5	115	94	104	1584	52	253	0.05	6	5	5	79	3	13
4	78	73	65	984	38	174	0.05	4	4	3	49	2	9
3	47	58	56	568	41	107	0.05	2	3	3	28	2	5
2	19	53	64	309	77	63	0.05	1	3	3	15	4	3
1	8	43	54	192	nd	37	0.05	0	2	3	10	4	2
idle	0	44	49	107	64	25	0.55	0	24	27	59	35	14
Sum							1.00	50	81	165	770	63	138
Weighted Composite g/hp-hr =									1.6	3.3	15.3	1.26	2.75

Table 4. Summary of Emissions Data for the EMD 2-567 Locomotive Engine (Continued)

***** Weighted g/hr *****											
Test Summary 1/31/91				Baseline Diesel							
Notch	BHP	HC g/hr	CO g/hr	Corr. NO _x g/hr	Avg. Part. g/hr	Meas. SO ₂ g/hr	wf	BHP	HC g/hr	CO g/hr	Corr. NO _x g/hr
8	206	226	288	2643	86	627	0.10	21	23	29	264
7	179	193	234	2554	59	483	0.05	9	10	12	128
6	149	99	142	2313	48	343	0.05	7	5	7	116
5	113	101	76	1537	40	246	0.05	6	5	4	77
4	76	73	64	825	44	166	0.05	4	4	3	41
3	46	62	65	573	44	112	0.05	2	3	3	29
2	19	50	85	317	61	65	0.05	1	2	4	16
1	8	41	65	181	nd	42	0.05	0	2	3	9
idle	0	35	55	108	75	26	0.55	0	19	31	59
Sum						73	1.00	50	73	96	739
Weighted Composite g/hp-hr =									1.4	1.9	14.7
										69	150
										2.98	1.36

Table 4. Summary of Emissions Data for the EMD 2-567 Locomotive Engine(Continued)

***** Weighted g/hr *****											
Test Summary 1/31/91				Baseline Diesel							
Notch	BHP	HC g/hr	CO g/hr	Corr. NO _x g/hr	Avg. Part. g/hr	Meas. SO ₂ g/hr	wf	BHP	HC g/hr	CO g/hr	Corr. NO _x g/hr
8	206	140	668	2879	77	235	0.10	21	14	67	288
7	179	151	316	2405	59	459	0.05	9	8	16	120
6	148	99	179	2147	45	166	0.05	7	5	9	107
5	114	85	101	1567	41	114	0.05	6	4	5	78
4	78	68	64	1022	42	79	0.05	4	3	3	51
3	46	51	64	568	40	26	0.05	2	3	3	28
2	20	41	74	319	99	31	0.05	1	2	4	16
1	8	29	55	159	nd	19	0.05	0	1	3	8
idle	0	29	42	108	78	11	0.55	0	16	23	60
Sum								50	56	132	757
Weighted Composite g/hp-hr =									5.6	2.6	15.0
											71
											1.41
											1.48

**Table 5. Weighted Composite Brake Specific Emissions Summary
for the EMD 2-567 Locomotive Engine**

	PM	HC	CO	NO _x	SO ₂
	Composite (g/bhp-hr)				
Pre 500-Hour : Baseline 2D	1.29	1.3	2.1	14.2	1.3
Pre 500-Hour : Coal-Lite	1.26	1.6	3.3	15.3	2.8
Post 500-Hour : Coal-Lite	1.36	1.4	1.9	14.7	3.0
Post 500-Hour : Baseline 2D	1.41	1.1	2.6	15.0	1.5
EPA Heavy Duty Diesel Std. : 1994	0.1	1.3	15.5	5.0	NA
Proposed Off-Highway California 8 Mode : 1995 : 2000	0.4 0.16	1.0 1.0	N.A. N.A.	6.9 5.8	N.A. N.A.

significant on the piston and liner of the left cylinder. Wear on the piston of 0.002", and on the liner of 0.0057" is considerably greater than normal. Additionally, the wear area was visually detected, as shown in Figure 11.

Although the wear on the left piston and liner was significant, it does not mean that the wear was induced as a result of running the coal-lite fuel. In fact, other evidence indicates that the wear was not fuel related. This is substantiated by examining the right cylinder piston and liner. Wear here was below the measurable range as expected in 500 hours. Additionally, none of the other components measured indicated significant wear as shown on the dimension sheets (Appendix E).

Except for the left cylinder, visual inspection of all engine components did not indicate any abnormal wear condition. Photographs of the components inspected are presented in Appendix F. Visually, varnish deposits were observed on the injector needle assemblies (see photographs Appendix F). In fact, it was somewhat difficult to remove the needle from the bore due to the varnish deposits. The deposits did not inhibit engine operation but were unusual for 500 hours operation.

Figure 11. EMD Pistons

V. DISCUSSION

This test was performed in order to evaluate the performance and emissions of the coal-lite fuel as compared to neat diesel fuel and to determine if any detrimental wear would be observed after 500 hours of operation.

A. Performance Tests

The performance results indicated that, operationally in the medium-speed diesel engine, the fuel functioned well. No problems were encountered with starting, knock, or general engine operation. However, due to the lower heating value of the fuel and lower thermal efficiency observed, a fuel efficiency penalty of approximately 2 to 4 percent can be expected at the higher notch operation (Notches 5 to 8). The thermal efficiency penalty could be a result of a slower burn duration of the coal-lite fuel. Therefore, if this is the case, some of the penalty might be recovered by advancing the injection timing. This would have to be determined experimentally.

B. Wear Tests

In 500 hours of operation on medium-speed diesel engines, wear measurements can only determine if the fuel tested was catastrophic to the engine. Typically, the wear should be undetectable. Therefore, if wear is measured, then it can be assumed that the fuel is unsatisfactory and should not be consumed for fear of subsequent engine destruction. In this case, significant wear was detected in the left cylinder. The level of this wear, if fuel induced, would condemn the fuel for use in this engine. However, since this level of wear was not detected with any other components it can be assumed that the wear was a function of defective components or the rebuild and not a function of the fuel consumed.

Of some concern is the varnish deposits on the fuel injection components. After 500 hours, the injectors were still functioning properly however the needles were stuck in their bores. Some question exists if this would present a problem with unsatisfactory operation after additional hours of operation.

C. Emissions Tests

Based on the limited emissions tests performed on the EMD 2-567B engine, it appears that the coal-lite fuel blend tested did not significantly change the normally regulated exhaust emissions. The only significant difference detected in the measured exhaust emissions was SO_2 , where the weighted composite brake specific emissions of SO_2 were approximately two times higher on the coal-lite fuel as compared to the baseline diesel fuel. However, this result was not unexpected, as the fuel sulfur content of the coal-lite fuel blend was approximately twice that of the baseline diesel fuel. (It should be noted that SO_2 emissions are not regulated for

mobile sources.)

In general, locomotive engine emissions are not regulated in the U.S. The only possible exception to this are the various visible smoke standards in several areas. However, the California Air Resources Board has recently begun to study locomotive exhaust emissions, and regulations are anticipated within the next few years for engines built before 1990. At the national level, Congress, through the Clean Air Act Amendments of 1990, instructed the EPA to study locomotive exhaust emissions and to promulgate regulations by 1995. Those regulations would apply to new engines built since 1990.

Although the EMD 2-567B engine used in this study is representative of a large number of locomotive engines currently operating in the U.S., the 567 engine design is now two generations old. Significant improvements to the engine design have been incorporated to both significantly improve fuel economy and to reduce exhaust emission levels. Today's state-of-the-art locomotive engines have NO_x levels of approximately 8-10 g/hp-hr and particulate levels on the order of 0.15-0.25 g/hp-hr. Given the promising performance, wear and emission characteristics of the coal-lite in this limited testing on the EMD 2-567B engine, further evaluations may be warranted on full scale locomotive engines. This testing could involve performance and emissions testing on SwRI's 12-cylinder locomotive engines. These engines, an EMD 12-645E3B, and a GE 12-7FDL, are each rated at 2,500 bhp, and are representative of the majority of the existing locomotive fleet in North America. However, these engines are themselves one generation old, and do not incorporate all of the improvements of today's new locomotive engines. In addition to further 12-cylinder locomotive engine tests, a controlled long-term field study of the coal-lite fuel blend may be considered to evaluate the in-service characteristics of the fuel.

VI. CONCLUSIONS

After 500 hours of operation, performance and wear measurements made on the engine as a result of running on coal-lite fuel did not indicate that the fuel was catastrophic. However, varnish deposits on the fuel injectors should be monitored. If used in rail operation, the coal-lite fuel should be used in controlled field tests for one year until longer term results can be observed. The coal-lite fuel did not significantly change the normally regulated exhaust emissions, but did significantly increase SO_2 emissions because of its higher sulfur content.

APPENDIX A

GASEOUS and/or PARTICULATE EMISSIONS

IDLE

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 9
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 47666.
OBS. POWER, BHP .0

TEST DATE 1/31/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 59.
FUEL FLOW, LB/MIN .09

BAROMETER 29.55 IN.HG.
HUMIDITY 26.71 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47min 30.00 MIN.
MEAS. EXH. FLOW, LB/MIN 16.34
AIR FLOW, LB/MIN 16.25

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
68.	.53	4.600	11.00	15.00	96.
67.	.53	4.550	11.00	15.00	95.
67.	.53	4.600	11.00	15.00	94.
69.	.53	4.600	11.00	15.00	95.
69.	.53	4.600	11.00	15.00	95.
68.	.53	4.600	11.00	15.00	95.
66.	.53	4.500	11.00	15.00	93.
AVERAGE 68.	.53	4.579	11.00	15.00	95.

LFE VOL, SCF 7230.9 LFE MASS, LB. 543.3 BLOWER + 47min VOL, SCF 7497.0 BLOWER + 47min MASS, LB 563.3
LFE FLOW SCFM 241.02 LFE FLOW LB/MIN 18.11 BLOWER + 47min FLOW SCFM 249.88 BLOWER + 47min FLOW LB/MIN 18.78
F/A DRY, MEAS .0058 F/A CALC .0045 F/A PCT, MEAS -22.1

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-33&34	22.699	59.	3.334	.147
2	P47-35&36	22.719	59.	3.219	.142

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 95. DILUTION FACTOR 28.177
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 266.1 (7.54) , .67

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-33&34	4.139 (146.135)	1.2413	54.011	.000
P47-35&36	3.992 (140.970)	1.2402	52.102	.000

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	37.039	.000	137. PPMC
CO	34.829	.000	64. PPM
NOX	116.333	.000	131. PPM
NOX, CORR	99.721	.000	
CO2		0.	.93 PCT
O2			19.32 PCT
NOX CORRECTION FACTOR	.8572		WET CORRECTION FACTOR .9909

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 1

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 8
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 47682.
OBS. POWER,BHP 8.3

TEST DATE 1/31/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 61.
FUEL FLOW, LB/MIN .13

BAROMETER 29.55 IN.HG.
HUMIDITY 25.08 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 30.00 MIN.
MEAS. EXH. FLOW, LB/MIN 16.36
AIR FLOW, LB/MIN 16.23

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
69.	.55	4.850	11.00	15.00	101.
70.	.55	4.850	11.00	15.00	101.
69.	.55	4.830	11.00	15.00	101.
70.	.53	4.850	11.00	15.00	101.
71.	.55	4.850	11.00	15.00	102.
71.	.55	4.850	11.00	15.00	102.
71.	.55	4.830	11.00	15.00	101.
AVERAGE 70.	.55	4.844	11.00	15.00	101.

LFE VOL, SCF 7567.2	LFE MASS, LB. 568.6	BLOWER + 47mm VOL, SCF 7467.4	BLOWER + 47mm MASS, LB 561.1
LFE FLOW SCFM 252.23	LFE FLOW LB/MIN 18.95	BLOWER + 47mm FLOW SCFM 248.90	BLOWER + 47mm FLOW LB/MIN 18.70
F/A DRY, MEAS .0082	F/A CALC .0066	F/A PCT, MEAS -19.9	

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE TEMP DEG F	WEIGHT GAIN MILLIGRAMS	NG/SCF OF SAMPLE
1	P47-29&30	21.448	64.	6.477	.302
2	P47-31&32	21.478	64.	6.193	.288

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 101.
SPLIT EXHAUST VOL, SCF (SCH), LB/MIN

DILUTION FACTOR *****
***** (*****) , *****

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, NG/SCF (NG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-29&30	***** (*****)	*****	*****	*****
P47-31&32	***** (*****)	*****	*****	*****

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	40.034	4.853	152. PPMC
CO	45.421	5.506	86. PPM
NOX	174.091	21.102	202. PPM
NOX, CORR	148.042	17.944	
CO2		1065.	1.37 PCT
O2			18.44 PCT
NOX CORRECTION FACTOR	.8504		WET CORRECTION FACTOR .9871

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 2

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 7
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 47674.
OBS. POWER,BHP 20.0

TEST DATE 1/31/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 63.
FUEL FLOW, LB/MIN .20

BAROMETER 29.54 IN.HG.
HUMIDITY 25.56 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47min 30.00 MIN.
MEAS. EXH. FLOW, LB/MIN 21.53
AIR FLOW, LB/MIN 21.33

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
72.	.48	4.590	11.00	15.00	114.
72.	.48	4.590	11.00	15.00	114.
72.	.48	4.590	11.00	15.00	114.
72.	.48	4.590	11.00	15.00	114.
71.	.48	4.570	11.00	15.00	113.
71.	.50	4.550	11.00	15.00	113.
71.	.50	4.550	11.00	15.00	113.
AVERAGE 72.	.49	4.576	11.00	15.00	114.

LFE VOL, SCF 7132.6	LFE MASS, LB. 535.9	BLOWER + 47min VOL, SCF 7433.9	BLOWER + 47min MASS, LB 558.6
LFE FLOW SCFM 237.75	LFE FLOW LB/MIN 17.86	BLOWER + 47min FLOW SCFM 247.80	BLOWER + 47min FLOW LB/MIN 18.62
F/A DRY, MEAS .0094	F/A CALC .0080	F/A PCT, MEAS -14.6	

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-25&26	21.422	65.	6.160	.288
2	P47-27&28	21.412	65.	5.949	.278

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 114.
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 301.3 (8.53) , .75

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-25&26	7.095 (250.542)	1.1519	121.981	6.099
P47-27&28	6.856 (242.072)	1.1524	117.858	5.893

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	53.297	2.665	164. PPMC
CO	58.494	2.925	90. PPM
NOX	294.835	14.742	278. PPM
NOX, CORR	257.184	12.859	
CO2		659.	1.67 PCT
O2			18.07 PCT
NOX CORRECTION FACTOR	.8723		WET CORRECTION FACTOR .9845

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 3

PROJECT 03-2681-809

PROGRAM = END16B

TEST NO. RUN NO. 6
ENGINE MODEL EMD 2-567
TEST CELL LOCO LAB
RCR 1.758
BLOWER COUNTS 47656.
OBS. POWER,BHP 47.0

TEST DATE 1/31/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 66.
FUEL FLOW,LB/MIN .35

BAROMETER 29.54 IN.HG.
HUMIDITY 29.37 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47min 30.00 MIN.
MEAS. EXH. FLOW,LB/MIN 27.80
AIR FLOW,LB/MIN 27.45

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
72.	.45	4.300	11.00	15.00	122.
72.	.45	4.300	11.00	15.00	122.
71.	.44	4.300	11.00	15.00	122.
71.	.46	4.300	11.00	15.00	122.
71.	.47	4.300	11.00	15.00	122.
71.	.45	4.280	11.00	15.00	122.
AVERAGE 71.	.45	4.297	11.00	15.00	122.

LFE VOL, SCF 6723.0 LFE MASS, LB. 505.2 BLOWER + 47min VOL, SCF 7387.3 BLOWER + 47min MASS, LB 555.1
LFE FLOW SCFM 224.11 LFE FLOW LB/MIN 16.84 BLOWER + 47min FLOW SCFM 246.26 BLOWER + 47min FLOW LB/MIN 18.50
F/A DRY, MEAS .0127 F/A CALC .0104 F/A PCT, MEAS -17.9

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-21&22	21.533	63.	4.854	.225
2	P47-23&24	21.503	63.	4.697	.218

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 122. DILUTION FACTOR 11.120
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 664.4 (18.81) , 1.66

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-21&22	2.507 (88.507)	.5164	55.635	1.184
P47-23&24	2.429 (85.763)	.5171	53.911	1.147

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	57.498	1.223	132. PPHC
CO	58.966	1.255	68. PPM
NOX	597.133	12.705	422. PPM
NOX, CORR	520.189	11.068	
CO2		491.	2.19 PCT
O2			17.31 PCT
NOX CORRECTION FACTOR	.8711		WET CORRECTION FACTOR .9799

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 4

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 5
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 33964.
OBS. POWER, BHP 77.0

TEST DATE 1/31/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 67.
FUEL FLOW, LB/MIN .54

BAROMETER 29.55 IN. HG.
HUMIDITY 25.54 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 21.38 MIN.
MEAS. EXH. FLOW, LB/MIN 34.24
AIR FLOW, LB/MIN 33.70

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
73.	.52	4.080	11.00	15.00	123.
72.	.52	4.080	11.00	15.00	123.
72.	.49	4.130	11.00	15.00	123.
73.	.51	4.130	11.00	15.00	123.
73.	.52	4.150	11.00	15.00	124.
73.	.48	4.200	11.00	15.00	123.
AVERAGE 73.	.51	4.128	11.00	15.00	123.

LFE VOL, SCF 4591.9	LFE MASS, LB. 345.0	BLOWER + 47mm VOL, SCF 5256.2	BLOWER + 47mm MASS, LB 394.9
LFE FLOW SCFM 214.81	LFE FLOW LB/MIN 16.14	BLOWER + 47mm FLOW SCFM 245.88	BLOWER + 47mm FLOW LB/MIN 18.48
F/A DRY, MEAS .0161	F/A CALC .0136	F/A PCT, MEAS -15.6	

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-17418	15.154	61.	3.639	.240
2	P47-19420	15.169	61.	3.505	.231

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 123. DILUTION FACTOR 7.913
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 664.2 (18.81) , 2.33

PARTICULATE CONCENTRATION IN EXHAUST		CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
FILTER	CONCENTRATION, MG/SCF (MG/SCM)			
P47-17418	1.900 (67.099)	.5222	51.957	.675
P47-19420	1.828 (64.564)	.5217	49.994	.649

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	76.786	.997	147. PPM
CO	62.036	.806	60. PPM
NOX	1032.552	13.410	612. PPM
NOX, CORR	892.959	11.597	
CO2		468.	2.87 PCT
O2			16.31 PCT
NOX CORRECTION FACTOR	.8648		WET CORRECTION FACTOR .9744

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 5

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 4
ENGINE MODEL EMD 2-567
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 32889.
OBS. POWER,BHP 114.0

TEST DATE 1/31/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 67.
FUEL FLOW,LB/MIN .76

BAROMETER 29.60 IN.HG.
HUMIDITY 23.35 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 20.70 MIN.
MEAS. EXH. FLOW,LB/MIN 38.26
AIR FLOW,LB/MIN 37.50

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
72.	.55	4.080	11.00	15.00	123.
72.	.55	4.030	11.00	15.00	123.
72.	.50	4.100	11.00	15.00	122.
72.	.55	4.050	11.00	15.00	123.
72.	.55	4.050	11.00	15.00	123.
AVERAGE 72.	.54	4.062	11.00	15.00	123.

LFE VOL, SCF 4395.6	LFE MASS,LB. 330.3	BLOWER + 47mm VOL, SCF 5098.9	BLOWER + 47mm MASS,LB 383.1
LFE FLOW SCFM 212.32	LFE FLOW LB/MIN 15.95	BLOWER + 47mm FLOW SCFM 246.28	BLOWER + 47mm FLOW LB/MIN 18.51
F/A DRY, MEAS .0203	F/A CALC .0174	F/A PCT, MEAS -14.4	

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-13&14	14.616	73.	4.810	.329
2	P47-15&16	14.744	73.	4.028	.273

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 123.
SPLIT EXHAUST VOL,SCF (SCM), LB/MIN 703.2 (19.92) , 2.55

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, NG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-13&14	2.386 (84.251)	.4961	72.895	.639
P47-15&16	1.981 (69.944)	.4918	60.517	.531

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	100.087	.878	174. PPMC
CO	92.717	.813	82. PPM
NOX	1693.758	14.858	918. PPM
NOX,CORR	1461.542	12.821	
CO2		444.	3.69 PCT
O2			15.30 PCT
NOX CORRECTION FACTOR	.8629		WET CORRECTION FACTOR .9676

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 6

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 3
ENGINE MODEL EMD 2-567
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 47669.
OBS. POWER, BHP 149.0

TEST DATE 1/31/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 67.
FUEL FLOW, LB/MIN .99

BAROMETER 29.62 IN.HG.
HUMIDITY 23.31 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47min 30.01 MIN.
MEAS. EXH. FLOW, LB/MIN 43.69
AIR FLOW, LB/MIN 42.70

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
70.	.53	4.050	11.00	15.00	123.
71.	.53	4.020	11.00	15.00	123.
71.	.53	4.030	11.00	15.00	124.
71.	.55	4.030	11.00	15.00	124.
71.	.50	4.100	11.00	15.00	124.
71.	.50	4.100	11.00	15.00	124.
71.	.52	4.080	11.00	15.00	124.
AVERAGE 71.	.52	4.059	11.00	15.00	124.

LFE VOL, SCF 6394.1
LFE FLOW SCFM 213.10
F/A DRY, MEAS .0232

LFE MASS, LB. 480.5
LFE FLOW LB/MIN 16.01
F/A CALC .0195

BLOWER + 47min VOL, SCF 7394.5
BLOWER + 47min FLOW SCFM 246.44
F/A PCT, MEAS -15.9

BLOWER + 47min MASS, LB 555.6
BLOWER + 47min FLOW LB/MIN 18.52

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	NG/SCF OF SAMPLE
1	P47-9&10	20.770	71.	5.925	.285
2	P47-11&12	20.642	71.	5.921	.287

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 124.
SPLIT EXHAUST VOL, SCF (SCH), LB/MIN 1000.4 (28.33), 2.51

DILUTION FACTOR 7.392

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, NG/SCF (NG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-9&10	2.109 (74.455)	.3559	73.556	.494
P47-11&12	2.120 (74.866)	.3581	73.962	.496

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	126.259	.847	189. PPHC
CO	126.891	.852	97. PPM
NOX	2375.859	15.945	1113. PPM
NOX, CORR	2120.927	14.234	
CO2		441.	4.14 PCT
O2			14.55 PCT
NOX CORRECTION FACTOR		.8927	WET CORRECTION FACTOR .9639

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 7

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 2
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 47646.
OBS. POWER, BHP 178.0

TEST DATE 1/31/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 66.
FUEL FLOW, LB/MIN 1.21

BAROMETER 29.63 IN.HG.
HUMIDITY 24.93 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 30.00 MIN.
MEAS. EXH. FLOW, LB/MIN 49.79
AIR FLOW, LB/MIN 48.58

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
72.	.55	4.100	11.00	15.00	121.
72.	.55	4.100	11.00	15.00	122.
71.	.55	4.100	11.00	15.00	122.
71.	.55	4.050	11.00	15.00	121.
71.	.54	4.000	11.00	15.00	122.
71.	.55	4.100	11.00	15.00	122.
71.	.56	4.050	11.00	15.00	122.
AVERAGE 71.	.55	4.071	11.00	15.00	122.

LFE VOL, SCF 6404.7	LFE MASS, LB. 481.2	BLOWER + 47mm VOL, SCF 7408.1	BLOWER + 47mm MASS, LB 556.6
LFE FLOW SCFM 213.50	LFE FLOW LB/MIN 16.04	BLOWER + 47mm FLOW SCFM 246.95	BLOWER + 47mm FLOW LB/MIN 18.56
F/A DRY, MEAS .0250	F/A CALC .0230	F/A PCT, MEAS -7.8	

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-5&6	20.767	68.	6.432	.310
2	P47-7&8	20.757	68.	6.474	.312

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 122. DILUTION FACTOR 7.383
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 1003.4 (28.42), 2.51

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, NG/SCF (NG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-5&6	2.287 (80.747)	.3555	90.915	.511
P47-7&8	2.303 (81.313)	.3557	91.552	.514

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	140.413	.789	202. PPMC
CO	254.211	1.428	188. PPM
NOX	2753.695	15.470	1248. PPM
NOX, CORR	2360.537	13.261	
CO2		452.	4.90 PCT
O2			13.79 PCT
NOX CORRECTION FACTOR	.8572		WET CORRECTION FACTOR .9576

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 8

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 1
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
BCR 1.758
BLOWER COUNTS 47673.
OBS. POWER, BHP 206.8

TEST DATE 1/31/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 67.
FUEL FLOW, LB/MIN 1.45

BAROMETER 29.62 IN.HG.
HUMIDITY 29.21 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 30.00 MIN.
MEAS. EXH. FLOW, LB/MIN 55.92
AIR FLOW, LB/MIN 54.47

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
71.	.65	3.950	11.00	15.00	122.
72.	.65	3.980	11.00	15.00	124.
72.	.65	3.950	11.00	15.00	124.
72.	.65	3.950	11.00	15.00	124.
72.	.67	4.000	11.00	15.00	124.
73.	.66	4.000	11.00	15.00	123.
73.	.65	3.990	11.00	15.00	123.
AVERAGE 72.	.65	3.974	11.00	15.00	123.

LFE VOL, SCF 6237.2 LFE MASS, LB. 468.7
LFE FLOW SCFM 207.91 LFE FLOW LB/MIN 15.62
F/A DRY, MEAS .0267 F/A CALC .0266

BLOWER + 47mm VOL, SCF 7394.7
BLOWER + 47mm FLOW SCFM 246.49
F/A PCT, MEAS -.6

BLOWER + 47mm MASS, LB 555.6
BLOWER + 47mm FLOW LB/MIN 18.52

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-1&2	20.444	63.	6.306	.308
2	P47-3&4	20.424	63.	6.473	.317

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 123. DILUTION FACTOR 6.389
SPLIT EXHAUST VOL, SCF (SCH), LB/MIN 1157.5 (32.78), 2.90

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCH)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-1&2	1.971 (69.581)	.3125	87.991	.425
P47-3&4	2.025 (71.493)	.3128	90.410	.437

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	157.423	.761	217. PPMC
CO	531.231	2.569	379. PPM
NOX	3163.238	15.296	1383. PPM
NOX, CORR	2743.229	13.265	
CO2		466.	5.66 PCT
O2			12.79 PCT
NOX CORRECTION FACTOR	.8672		WET CORRECTION FACTOR .9511

APPENDIX B

B-1

GASEOUS and/or PARTICULATE EMISSIONS

IDLE

PROJECT 03-2681-809

PROGRAM = END16B

TEST NO. RUN NO. 9
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
ECR 1.656
BLOWER COUNTS 47620.
OBS. POWER,BHP .0

TEST DATE 2/ 4/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 73.
FUEL FLOW,LB/MIN .09

BAROMETER 29.26 IN.HG.
HUMIDITY 61.20 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 30.00 MIN.
MEAS. EXH. FLOW,LB/MIN 16.54
AIR FLOW,LB/MIN 16.45

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
81.	.60	4.600	10.00	14.00	106.
81.	.60	4.620	10.00	14.00	105.
80.	.60	4.600	10.00	14.00	105.
80.	.60	4.600	10.00	14.00	105.
80.	.60	4.600	10.00	14.00	104.
80.	.60	4.600	10.00	14.00	104.
80.	.60	4.600	10.00	14.00	104.
AVERAGE 80.	.60	4.603	10.00	14.00	105.

LFE VOL, SCF 6902.3	LFE MASS,LB. 518.6	BLOWER + 47mm VOL, SCF 7248.5	BLOWER + 47mm MASS,LB 544.6
LFE FLOW SCFM 230.08	LFE FLOW LB/MIN 17.29	BLOWER + 47mm FLOW SCFM 241.62	BLOWER + 47mm FLOW LB/MIN 18.15
F/A DRY, MEAS .0057	F/A CALC .0043	F/A PCT, MEAS -24.7	

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P90-69&70	22.559	68.	5.324	.236
2	P90-71&72	22.549	68.	5.169	.229

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 105. DILUTION FACTOR 20.937
SPLIT EXHAUST VOL,SCF (SCM), LB/MIN 346.2 (9.80) , .87

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P90-69&70	4.941 (174.477)	.9281	65.274	.000
P90-71&72	4.800 (169.471)	.9285	63.401	.000

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	43.968	.000	157. PPMC
CO	48.824	.000	86. PPM
NOX	112.095	.000	121. PPM
NOX,CORR	106.862	.000	
CO2		0.	.89 PCT
O2			19.20 PCT
NOX CORRECTION FACTOR	.9533		WET CORRECTION FACTOR .9904

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 1

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 8
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.656
BLOWER COUNTS 45450.
OBS. POWER,BHP 8.3

TEST DATE 2/ 4/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 75.
FUEL FLOW, LB/MIN .13

BAROMETER 29.25 IN.HG.
HUMIDITY 116.95 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 28.63 MIN.
MEAS. EXH. FLOW, LB/MIN 16.00
AIR FLOW, LB/MIN 15.87

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
82.	.60	4.800	10.00	14.00	112.
82.	.60	4.800	10.00	14.00	112.
83.	.60	4.800	10.00	14.00	111.
82.	.60	4.800	10.00	14.00	111.
82.	.60	4.800	10.00	14.00	111.
82.	.60	4.800	10.00	14.00	111.
82.	.60	4.800	10.00	14.00	111.
82.	.60	4.800	10.00	14.00	111.
AVERAGE	82.	.60	4.800	10.00	14.00
LFE VOL, SCF	6811.1	LFE MASS, LB.	511.8	BLOWER + 47mm VOL, SCF	6885.9
LFE FLOW SCFM	237.90	LFE FLOW LB/MIN	17.88	BLOWER + 47mm FLOW SCFM	240.51
F/A DRY, MEAS	.0086	F/A CALC	.0068	F/A PCT, MEAS	-21.2
				BLOWER + 47mm MASS, LB	517.4
				BLOWER + 47mm FLOW LB/MIN	18.07

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P90-65466	19.964	70.	8.271	.414
2	P90-67468	19.964	70.	7.930	.397

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 111.
SPLIT EXHAUST VOL, SCF (SCH), LB/MIN

DILUTION FACTOR *****
**** (****) , ***

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCH)
P90-65466	***** (*****)
P90-67468	***** (*****)

CONCENTRATION MULTIPLIER

G/HR

G/HP-HR

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	43.466	5.261	169. PPM
CO	54.393	6.583	105. PPM
NOX	164.835	19.951	195. PPM
NOX, CORR	191.510	23.180	
CO2		1074.	1.41 PCT
O2			18.57 PCT
NOX CORRECTION FACTOR	1.1618		WET CORRECTION FACTOR .9841

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 2

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 7
ENGINE MODEL EMD 2-567
TEST CELL LOCO LAB
HCR 1.656
BLOWER COUNTS 44781.
OBS. POWER,BHP 19.3

TEST DATE 2/ 4/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 78.
FUEL FLOW, LB/MIN .20

BAROMETER 29.24 IN.HG.
HUMIDITY 73.16 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 28.20 MIN.
MEAS. EXH. FLOW, LB/MIN 21.37
AIR FLOW, LB/MIN 21.17

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
84.	.55	4.480	10.00	14.00	123.
84.	.55	4.500	10.00	14.00	123.
84.	.55	4.470	10.00	14.00	123.
83.	.55	4.430	10.00	14.00	123.
83.	.55	4.430	10.00	14.00	123.
84.	.55	4.460	10.00	14.00	123.
83.	.55	4.480	10.00	14.00	123.
AVERAGE 84.	.55	4.464	10.00	14.00	123.

LFE VOL, SCF 6232.3	LFE MASS, LB. 468.3	BLOWER + 47mm VOL, SCF 6744.0	BLOWER + 47mm MASS, LB 506.7
LFE FLOW SCFM 220.98	LFE FLOW LB/MIN 16.60	BLOWER + 47mm FLOW SCFM 239.12	BLOWER + 47mm FLOW LB/MIN 17.97
F/A DRY, MEAS .0097	F/A CALC .0080	F/A PCT, MEAS -17.6	

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P90-61&62	20.084	70.	6.978	.347
2	P90-63&64	20.074	70.	6.768	.337

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 123. DILUTION FACTOR 13.181
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 511.7 (14.49) , 1.36

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P90-61&62	4.580 (161.704)	.6563	78.154	4.045
P90-63&64	4.444 (156.914)	.6566	75.839	3.925

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	52.801	2.733	160. PPMC
CO	64.435	3.335	97. PPM
NOX	312.182	16.158	288. PPM
NOX, CORR	308.971	15.991	
CO2		697.	1.67 PCT
O2			18.07 PCT
NOX CORRECTION FACTOR	.9897		WET CORRECTION FACTOR .9835

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 3

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 6
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.656
BLOWER COUNTS 47621.
OBS. POWER, BHP 46.6

TEST DATE 2/ 4/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 78.
FUEL FLOW, LB/MIN .35

BAROMETER 29.24 IN.HG.
HUMIDITY 82.18 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47min 30.00 MIN.
MEAS. EXH. FLOW, LB/MIN 27.83
AIR FLOW, LB/MIN 27.48

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
85.	.65	4.330	11.00	15.00	122.
84.	.65	4.330	11.00	15.00	122.
84.	.65	4.330	11.00	15.00	122.
84.	.65	4.310	11.00	15.00	122.
85.	.65	4.320	11.00	15.00	122.
85.	.65	4.330	11.00	15.00	122.
85.	.65	4.330	11.00	15.00	122.
AVERAGE 85.	.65	4.326	11.00	15.00	122.

LFE VOL, SCF 6410.6 LFE MASS, LB. 481.7 BLOWER + 47min VOL, SCF 7133.7 BLOWER + 47min MASS, LB 536.0
LFE FLOW SCFM 213.69 LFE FLOW LB/MIN 16.06 BLOWER + 47min FLOW SCFM 237.79 BLOWER + 47min FLOW LB/MIN 17.87
F/A DRY, MEAS .0130 F/A CALC .0113 F/A PCT, MEAS -13.6

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE TEMP DEG F	WEIGHT GAIN MILLIGRAMS	NG/SCF OF SAMPLE
1	P90-57&58	21.520	71.	4.065	.189
2	P90-59&60	21.550	71.	3.917	.182

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 122. DILUTION FACTOR 9.866
SPLIT EXHAUST VOL, SCF (SCH), LB/MIN 723.1 (20.48) , 1.81

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCH)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P90-57&58	1.864 (65.802)	.4584	41.419	.890
P90-59&60	1.793 (63.320)	.4578	39.857	.856

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	58.130	1.249	142. PPMC
CO	55.678	1.196	68. PPM
NOX	557.158	11.967	417. PPM
NOX, CORR	568.159	12.203	
CO2		510.	2.39 PCT
O2			17.19 PCT
NOX CORRECTION FACTOR	1.0197		WET CORRECTION FACTOR .9772

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 4

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 5
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
ECR 1.656
BLOWER COUNTS 25849.
OBS. POWER,BHP 77.9

TEST DATE 2/ 4/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 78.
FUEL FLOW, LB/MIN .55

BAROMETER 29.24 IN.HG.
HUMIDITY 78.45 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 16.29 MIN.
MEAS. EXH. FLOW, LB/MIN 34.42
AIR FLOW, LB/MIN 33.87

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
85.	.67	4.090	11.00	15.00	123.
85.	.67	4.090	11.00	15.00	124.
85.	.67	4.100	11.00	15.00	123.
85.	.67	4.100	11.00	15.00	123.
84.	.67	4.100	11.00	15.00	123.
AVERAGE 85.	.67	4.096	11.00	15.00	123.

LFE VOL, SCF 3300.8	LFE MASS, LB. 248.0	BLOWER + 47mm VOL, SCF 3872.7	BLOWER + 47mm MASS, LB 291.0
LFE FLOW SCFM 202.67	LFE FLOW LB/MIN 15.23	BLOWER + 47mm FLOW SCFM 237.79	BLOWER + 47mm FLOW LB/MIN 17.87
F/A DRY, MEAS .0165	F/A CALC .0142	F/A PCT, MEAS -13.7	

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P90-53&54	12.006	71.	2.491	.207
2	P90-55&66	11.958	71.	2.451	.205

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 123. DILUTION FACTOR 6.772
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 571.9 (16.20) , 2.64

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P90-53&54	1.405 (49.609)	.5640	38.617	.496
P90-55&66	1.388 (49.010)	.5663	38.151	.490

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	73.457	.943	145. PPMC
CO	64.526	.829	64. PPM
NOX	973.960	12.509	592. PPM
NOX, CORR	984.411	12.644	
CO2		476.	3.03 PCT
O2			16.18 PCT
NOX CORRECTION FACTOR	1.0107		WET CORRECTION FACTOR .9724

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 5

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 4
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
ECR 1.656
BLOWER COUNTS 39095.
OBS. POWER,BHP 114.7

TEST DATE 2/ 4/91
DIESEL COAL LIQU
TUNNEL NO. 25
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 78.
FUEL FLOW,LB/MIN .77

BAROMETER 29.26 IN.HG.
HUMIDITY 78.38 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 24.63 MIN.
MEAS. EXH. FLOW,LB/MIN 39.57
AIR FLOW,LB/MIN 38.80

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
84.	.70	4.110	11.00	15.00	122.
83.	.70	4.130	11.00	15.00	122.
81.	.70	4.100	11.00	15.00	121.
82.	.70	4.100	11.00	15.00	122.
84.	.70	4.130	11.00	15.00	123.
85.	.70	4.180	11.00	15.00	123.
AVERAGE 83.	.70	4.125	11.00	15.00	122.

LFE VOL, SCF 5055.7	LFE MASS,LB. 379.9	BLOWER + 47mm VOL, SCF 5862.2	BLOWER + 47mm MASS,LB 440.5
LFE FLOW SCFM 205.25	LFE FLOW LB/MIN 15.42	BLOWER + 47mm FLOW SCFM 238.00	BLOWER + 47mm FLOW LB/MIN 17.88
F/A DRY, MEAS .0201	F/A CALC .0182	F/A PCT, MEAS -9.8	

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P90-49&50	18.432	66.	4.235	.230
2	P90-51&52	18.471	66.	4.131	.224

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 122. DILUTION FACTOR 7.269
SPLIT EXHAUST VOL,SCF (SCM), LB/MIN 806.5 (22.84) , 2.46

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P90-49&50	1.670 (58.971)	.3944	52.773	.460
P90-51&52	1.626 (57.400)	.3935	51.367	.448

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	94.162	.821	169. PPMC
CO	103.507	.902	94. PPM
NOX	1563.241	13.630	870. PPM
NOX,CORR	1583.536	13.807	
CO2		452.	3.88 PCT
O2			15.05 PCT
NOX CORRECTION FACTOR	1.0130		WET CORRECTION FACTOR .9656

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 6

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 3
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.656
BLOWER COUNTS 47647.
OBS. POWER,BHP 148.6

TEST DATE 2/ 4/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 78.
FUEL FLOW,LB/MIN 1.01

BAROMETER 29.28 IN.HG.
HUMIDITY 82.46 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47min 30.00 MIN.
MEAS. EXH. FLOW,LB/MIN 47.21
AIR FLOW,LB/MIN 46.20

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIPP. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIPP. PRESS. IN. H2O	TUNNEL TEMP DEG. F
89.	.75	4.200	11.00	15.00	121.
90.	.75	4.200	11.00	15.00	122.
89.	.75	4.180	11.00	15.00	122.
89.	.75	4.180	11.00	15.00	122.
89.	.75	4.200	11.00	15.00	122.
89.	.75	4.190	11.00	15.00	122.
89.	.75	4.200	11.00	15.00	122.
AVERAGE 89.	.75	4.193	11.00	15.00	122.

LFE VOL, SCF 6138.2	LFE MASS,LB. 461.2	BLOWER + 47min VOL, SCF 7150.3	BLOWER + 47min MASS,LB 537.3
LFE FLOW SCFM 204.61	LFE FLOW LB/MIN 15.37	BLOWER + 47min FLOW SCFM 238.34	BLOWER + 47min FLOW LB/MIN 17.91
F/A DRY, MEAS .0221	F/A CALC .0219	F/A PCT, MEAS -1.0	

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P90-45&46	22.553	77.	4.878	.216
2	P90-47&48	22.611	77.	4.762	.211

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 122. DILUTION FACTOR 7.065
SPLIT EXHAUST VOL,SCF (SCM), LB/MIN 1012.1 (28.66) , 2.54

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P90-45&46	1.528 (53.955)	.3132	57.604	.388
P90-47&48	1.488 (52.537)	.3124	56.090	.377

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	120.731	.812	199. PPMC
CO	209.547	1.410	176. PPM
NOX	2139.056	14.390	1101. PPM
NOX,CORR	2209.823	14.866	
CO2		456.	4.69 PCT
O2			14.17 PCT
NOX CORRECTION FACTOR	1.0331		WET CORRECTION FACTOR .9588

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 7

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 2
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
BCR 1.656
BLOWER COUNTS 43728.
OBS. POWER,BHP 178.8

TEST DATE 2/ 4/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 78.
FUEL FLOW, LB/MIN 1.25

BAROMETER 29.30 IN.HG.
HUMIDITY 76.87 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 27.53 MIN.
MEAS. EXH. FLOW, LB/MIN 53.48
AIR FLOW, LB/MIN 52.23

LFE INFORMATION

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
89.	.75	4.150
89.	.75	4.180
89.	.75	4.200
89.	.75	4.200
89.	.75	4.200
89.	.75	4.200
89.	.75	4.200
89.	.75	4.200
AVERAGE 89.	.75	4.190

BLOWER INFORMATION

INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
11.00	15.00
11.00	15.00
11.00	15.00
11.00	15.00
11.00	15.00
11.00	15.00
11.00	15.00
11.00	15.00
11.00	15.00
AVERAGE 11.00	15.00

OTHER

TUNNEL TEMP DEG. F
123.
123.
123.
123.
123.
123.
123.
123.
123.
AVERAGE 123.

LFE VOL, SCF 5635.6
LFE FLOW SCFM 204.71
F/A DRY, MEAS .0242

LFE MASS, LB. 423.5
LFE FLOW LB/MIN 15.38
F/A CALC .0250

BLOWER + 47mm VOL, SCF 6566.3
BLOWER + 47mm FLOW SCFM 238.51
F/A PCT, MEAS 3.2

BLOWER + 47mm MASS, LB 493.4
BLOWER + 47mm FLOW LB/MIN 17.92

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P90-41&42	20.356	77.	4.662	.229
2	P90-43&44	20.385	77.	4.551	.223

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 123.
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 930.7 (26.36) , 2.54

DILUTION FACTOR 7.055

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)
P90-41&42	1.616 (57.053)
P90-43&44	1.575 (55.616)

CONCENTRATION MULTIPLIER

.3466
.3461

G/HR
69.002
67.263

G/HP-HR
.386
.376

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	159.730	.893	242. PPMC
CO	395.598	2.213	307. PPM
NOX	2546.390	14.243	1211. PPM
NOX, CORR	2585.356	14.461	
CO2		468.	5.35 PCT
O2			13.04 PCT
NOX CORRECTION FACTOR	1.0153		WET CORRECTION FACTOR .9539

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 8

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 1
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.656
BLOWER COUNTS 32104.
OBS. POWER, BHP 206.3

TEST DATE 2/ 4/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 78.
FUEL FLOW, LB/MIN 1.51

BAROMETER 29.29 IN.HG.
HUMIDITY 87.52 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 20.20 MIN.
MEAS. EXH. FLOW, LB/MIN 60.01
AIR FLOW, LB/MIN 58.50

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
88.	.75	4.210	11.00	15.00	123.
89.	.75	4.210	11.00	15.00	122.
89.	.75	4.210	11.00	15.00	122.
89.	.75	4.220	11.00	15.00	122.
89.	.75	4.220	11.00	15.00	122.
AVERAGE 89.	.75	4.214	11.00	15.00	122.

LFE VOL, SCF 4159.7 LFE MASS, LB. 312.6 BLOWER + 47mm VOL, SCF 4819.4 BLOWER + 47mm MASS, LB 362.1
LFE FLOW SCFM 205.89 LFE FLOW LB/MIN 15.47 BLOWER + 47mm FLOW SCFM 238.54 BLOWER + 47mm FLOW LB/MIN 17.92
F/A DRY, MEAS .0261 F/A CALC .0300 F/A PCT, MEAS 15.0

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P90-37438	15.007	74.	3.124	.208
2	P90-39440	15.027	74.	3.104	.207

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 122. DILUTION FACTOR 7.305
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 659.7 (18.68) , 2.45

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, NG/SCF (NG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P90-37438	1.521 (53.698)	.4868	72.871	.353
P90-39440	1.509 (53.285)	.4862	72.311	.351

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	262.600	1.273	394. PPMC
CO	906.040	4.393	703. PPM
NOX	2778.177	13.469	1321. PPM
NOX, CORR	2893.962	14.030	
CO2		486.	6.41 PCT
O2			11.78 PCT
NOX CORRECTION FACTOR	1.0417		WET CORRECTION FACTOR .9448

APPENDIX C

C-1

GASEOUS and/or PARTICULATE EMISSIONS

IDLE

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 9
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.656
BLOWER COUNTS 26124.
OBS. POWER,BHP .0

TEST DATE 2/26/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 63.
FUEL FLOW, LB/MIN .09

BAROMETER 29.41 IN.HG.
HUMIDITY 36.66 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 17.28 MIN.
MEAS. EXH. FLOW, LB/MIN 17.12
AIR FLOW, LB/MIN 17.03

LFE INFORMATION

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
77.	.55	4.470
77.	.55	4.470
76.	.55	4.470
76.	.55	4.470
76.	.55	4.470

AVERAGE 76.

.55

4.470

BLOWER INFORMATION

INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00

10.00

14.00

OTHER

TUNNEL TEMP DEG. F
101.
101.
101.
101.
101.

101.

LFE VOL, SCF 3937.2
LFE FLOW SCFM 227.81
F/A DRY, MEAS .0053

LFE MASS, LB. 295.8
LFE FLOW LB/MIN 17.12
F/A CALC .0045

BLOWER + 47mm VOL, SCF 4068.4
BLOWER + 47mm FLOW SCFM 235.39
F/A PCT, MEAS -16.0

BLOWER + 47mm MASS, LB 305.7
BLOWER + 47mm FLOW LB/MIN 17.69

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-105&10	15.725	57.	2.811	.179
2	P47-107&10	15.795	57.	2.766	.175

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 101.
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 131.2 (3.71) , .57

DILUTION FACTOR 31.019

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-105&10	5.545 (195.801)	1.9727	75.808	.000
P47-107&10	5.432 (191.810)	1.9639	74.263	.000

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	35.171	.000	135. PPMC
CO	55.477	.000	105. PPM
NOX	116.391	.000	135. PPM
NOX, CORR	107.717	.000	
CO2		0.	.93 PCT
O2			19.20 PCT
NOX CORRECTION FACTOR	.9255		WET CORRECTION FACTOR .9908

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 1

PROJECT 03-2681-809

PROGRAM = END16B

TEST NO. RUN NO. 8
ENGINE MODEL END 2-567B
TEST CELL LOCO LAB
HCR 1.656
BLOWER COUNTS 40797.
OBS. POWER, BHP 8.1

TEST DATE 2/26/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 65.
FUEL FLOW, LB/MIN .13

BAROMETER 29.40 IN.HG.
HUMIDITY 40.83 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 26.98 MIN.
MEAS. EXH. FLOW, LB/MIN 16.80
AIR FLOW, LB/MIN 16.67

LFE INFORMATION

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
80.	.60	4.650
79.	.60	4.650
79.	.60	4.650
78.	.60	4.650
78.	.60	4.650
78.	.60	4.650

BLOWER INFORMATION

INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00

OTHER

TUNNEL TEMP DEG. F
108.
108.
108.
108.
107.
107.

AVERAGE 79.

.60

4.650

10.00

14.00

108.

LFE VOL, SCF 6332.1
LFE FLOW SCFM 234.67
F/A DRY, MEAS .0079

LFE MASS, LB. 475.8
LFE FLOW LB/MIN 17.63
F/A CALC .0066

BLOWER + 47mm VOL, SCF 6322.6
BLOWER + 47mm FLOW SCFM 234.32
F/A PCT, MEAS -16.9

BLOWER + 47mm MASS, LB 475.1
BLOWER + 47mm FLOW LB/MIN 17.61

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-101&10	22.707	59.	6.676	.294
2	P47-103&10	22.747	59.	6.508	.286

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 108.
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN

DILUTION FACTOR *****
**** (****) , ****

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)
P47-101&10	***** (*****)
P47-103&10	***** (*****)

CONCENTRATION MULTIPLIER

G/HR

G/HP-HR

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	41.318	5.076	160. PPM
CO	64.696	7.948	124. PPM
NOX	194.113	23.847	228. PPM
NOX, CORR	181.456	22.292	
CO2		1066.	1.37 PCT
O2			18.07 PCT
NOX CORRECTION FACTOR		.9348	WET CORRECTION FACTOR .9871

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 2

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 7
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.656
BLOWER COUNTS 41690.
OBS. POWER,BHP 19.0

TEST DATE 2/26/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 68.
FUEL FLOW, LB/MIN .20

BAROMETER 29.40 IN.HG.
HUMIDITY 32.58 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 27.58 MIN.
MEAS. EXH. FLOW, LB/MIN 22.13
AIR FLOW, LB/MIN 21.93

LFE INFORMATION

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
82.	.50	4.250
82.	.51	4.270
81.	.51	4.270
81.	.52	4.270
81.	.52	4.270
81.	.55	4.270
81.	.55	4.270

AVERAGE 81. .52 4.267

LFE VOL, SCF 5914.5
LFE FLOW SCFM 214.42
F/A DRY, MEAS .0092
LFE MASS, LB. 444.4
LFE FLOW LB/MIN 16.11
F/A CALC .0080

BLOWER INFORMATION

INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00

BLOWER + 47mm VOL, SCF 6422.9
BLOWER + 47mm FLOW SCFM 232.85
F/A PCT, MEAS -13.6

OTHER

TUNNEL TEMP DEG. F
120.
121.
121.
122.
122.
122.
121.

BLOWER + 47mm MASS, LB 482.6
BLOWER + 47mm FLOW LB/MIN 17.50

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-97&98	23.124	61.	6.306	.273
2	P47-99&100	23.263	61.	2.611	.112

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 121.
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 508.4 (14.40) , 1.38
DILUTION FACTOR 12.635

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)
P47-97&98	3.446 (121.662)
P47-99&100	1.418 (50.072)

CONCENTRATION MULTIPLIER

.5464
.5431

G/HR
60.890
25.060

G/HP-HR
3.205
1.319

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	49.792	2.621	152. PPNC
CO	84.529	4.449	128. PPM
NOX	353.457	18.603	328. PPM
NOX, CORR	317.183	16.694	
CO2		705.	1.67 PCT
O2			17.82 PCT
NOX CORRECTION FACTOR		.8974	WET CORRECTION FACTOR .9850

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 3

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 6
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.656
BLOWER COUNTS 20970.
OBS. POWER,BHP 45.7

TEST DATE 2/26/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 68.
FUEL FLOW, LB/MIN .35

BAROMETER 29.40 IN.HG.
HUMIDITY 27.65 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 13.87 MIN.
MEAS. EXH. FLOW, LB/MIN 28.58
AIR FLOW, LB/MIN 28.23

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
80.	.55	4.050	10.00	14.00	124.
81.	.55	4.050	10.00	14.00	124.
81.	.55	4.050	10.00	14.00	124.
81.	.55	4.050	10.00	14.00	124.
AVERAGE 81.	.55	4.050	10.00	14.00	124.

LFE VOL, SCF 2834.0	LFE MASS, LB. 212.9	BLOWER + 47mm VOL, SCF 3231.1	BLOWER + 47mm MASS, LB 242.8
LFE FLOW SCFM 204.32	LFE FLOW LB/MIN 15.35	BLOWER + 47mm FLOW SCFM 232.96	BLOWER + 47mm FLOW LB/MIN 17.50
F/A DRY, MEAS .0125	F/A CALC .0111	F/A PCT, MEAS -11.7	

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-93&94	11.845	65.	2.879	.243
2	P47-95&96	11.815	65.	2.774	.235

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 124. DILUTION FACTOR 8.136
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 397.1 (11.25) , 2.15

PARTICULATE CONCENTRATION IN EXHAUST		CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
FILTER	CONCENTRATION, MG/SCF (MG/SCM)			
P47-93&94	1.978 (69.826)	.6869	45.133	.988
P47-95&96	1.910 (67.448)	.6886	43.596	.954

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	62.060	1.358	150. PPMC
CO	65.215	1.427	79. PPM
NOX	639.049	13.987	472. PPM
NOX, CORR	572.945	12.540	
CO2		516.	2.34 PCT
O2			17.06 PCT
NOX CORRECTION FACTOR	.8966		WET CORRECTION FACTOR .9798

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 4

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 5
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.656
BLOWER COUNTS 18634.
OBS. POWER,BHP 76.0

TEST DATE 2/26/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 68.
FUEL FLOW, LB/MIN .54

BAROMETER 29.39 IN.HG.
HUMIDITY 24.39 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 12.33 MIN.
MEAS. EXH. FLOW, LB/MIN 34.79
AIR FLOW, LB/MIN 34.25

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIPP. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIPP. PRESS. IN. H2O	TUNNEL TEMP DEG. F
81.	.59	3.900	10.00	14.00	123.
82.	.60	3.900	10.00	14.00	123.
82.	.60	4.000	10.00	14.00	123.
82.	.60	3.980	10.00	14.00	123.
AVERAGE 82.	.60	3.945	10.00	14.00	123.

LFE VOL, SCF 2447.9	LFE MASS, LB. 183.9	BLOWER + 47mm VOL, SCF 2869.9	BLOWER + 47mm MASS, LB 215.6
LFE FLOW SCFM 198.51	LFE FLOW LB/MIN 14.92	BLOWER + 47mm FLOW SCFM 232.73	BLOWER + 47mm FLOW LB/MIN 17.49
F/A DRY, MEAS .0158	F/A CALC .0140	F/A PCT, MEAS -11.3	

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-89&90	10.422	67.	2.446	.235
2	P47-91&92	10.540	67.	2.467	.234

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 123. DILUTION FACTOR 6.800
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 422.0 (11.95) , 2.57

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-89&90	1.596 (56.355)	.6525	44.336	.583
P47-91&92	1.592 (56.201)	.6452	44.215	.582

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	72.697	.957	145. PPMC
CO	64.024	.842	64. PPM
NOX	925.572	12.179	567. PPM
NOX, CORR	824.585	10.850	
CO2		476.	2.98 PCT
O2			16.18 PCT
NOX CORRECTION FACTOR		.8909	WET CORRECTION FACTOR .9749

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 5

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 4
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.656
BLOWER COUNTS 32237.
OBS. POWER,BHP 113.0

TEST DATE 2/26/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 68.
FUEL FLOW, LB/MIN .76

BAROMETER 29.39 IN.HG.
HUMIDITY 22.80 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 21.33 MIN.
MEAS. EXH. FLOW, LB/MIN 40.96
AIR FLOW, LB/MIN 40.20

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
84.	.63	3.900	10.00	14.00	123.
83.	.63	3.920	10.00	14.00	123.
83.	.63	3.900	10.00	14.00	122.
83.	.63	3.900	10.00	14.00	122.
83.	.63	3.900	10.00	14.00	123.
83.	.63	3.900	10.00	14.00	123.
AVERAGE 83.	.63	3.903	10.00	14.00	123.

LFE VOL, SCF 4172.3 LFE MASS, LB. 313.5 BLOWER + 47mm VOL, SCF 4964.3 BLOWER + 47mm MASS, LB 373.0
LFE FLOW SCFM 195.58 LFE FLOW LB/MIN 14.70 BLOWER + 47mm FLOW SCFM 232.70 BLOWER + 47mm FLOW LB/MIN 17.49
F/A DRY, MEAS .0190 F/A CALC .0182 F/A PCT, MEAS -4.3

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-85&86	17.715	67.	3.532	.199
2	P47-87&88	17.764	67.	3.436	.193

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 123. DILUTION FACTOR 6.269
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 791.9 (22.43) , 2.79

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-85&86	1.250 (44.132)	.3539	40.879	.362
P47-87&88	1.213 (42.814)	.3529	39.658	.351

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	100.717	.891	184. PPNC
CO	75.901	.672	70. PPH
NOX	1732.197	15.329	979. PPH
NOX, CORR	1537.138	13.603	
CO2		452.	3.88 PCT
O2			14.93 PCT
NOX CORRECTION FACTOR		.8874	WET CORRECTION FACTOR .9678

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 6

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 3
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.656
BLOWER COUNTS 45358.
OBS. POWER,BHP 149.0

TEST DATE 2/26/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 67.
FUEL FLOW, LB/MIN 1.00

BAROMETER 29.43 IN.HG.
HUMIDITY 25.10 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 30.00 MIN.
MEAS. EXH. FLOW, LB/MIN 48.47
AIR FLOW, LB/MIN 47.47

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
83.	.63	3.900	10.00	14.00	123.
83.	.65	3.930	10.00	14.00	123.
83.	.65	3.950	10.00	14.00	122.
83.	.65	3.950	10.00	14.00	122.
83.	.65	4.000	10.00	14.00	122.
83.	.65	4.000	10.00	14.00	122.
83.	.65	4.000	10.00	14.00	122.
AVERAGE 83.	.65	3.961	10.00	14.00	122.

LFE VOL, SCF 5961.8 LFE MASS, LB. 448.0 BLOWER + 47mm VOL, SCF 7009.2 BLOWER + 47mm MASS, LB 526.7
LFE FLOW SCFM 198.74 LFE FLOW LB/MIN 14.93 BLOWER + 47mm FLOW SCFM 233.65 BLOWER + 47mm FLOW LB/MIN 17.56
F/A DRY, MEAS .0212 F/A CALC .0212 F/A PCT, MEAS .0

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-81&82	25.102	66.	4.664	.186
2	P47-83&84	25.092	66.	4.569	.182

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 122. DILUTION FACTOR 6.692
SPLIT EXHAUST VOL, SCF (SCH), LB/MIN 1047.4 (29.66), 2.62

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCH)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-81&82	1.243 (43.904)	.2666	48.128	.323
P47-83&84	1.219 (43.027)	.2667	47.166	.317

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	98.581	.662	159. PPMC
CO	141.681	.951	116. PPM
NOX	2584.987	17.349	1297. PPM
NOX, CORR	2313.237	15.525	
CO2		453.	4.55 PCT
O2			13.92 PCT
NOX CORRECTION FACTOR		.8949	WET CORRECTION FACTOR .9625

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 7

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 2
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.656
BLOWER COUNTS 45271.
OBS. POWER,BHP 179.0

TEST DATE 2/26/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 70.
FUEL FLOW, LB/MIN 1.23

BAROMETER 29.47 IN.HG.
HUMIDITY 25.84 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 30.00 MIN.
MEAS. EXH. FLOW, LB/MIN 55.23
AIR FLOW, LB/MIN 54.00

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
85.	.65	4.030	10.00	14.50	123.
85.	.65	4.030	10.00	14.50	123.
85.	.65	4.030	10.00	14.50	123.
85.	.65	4.030	10.00	14.50	122.
85.	.65	4.030	10.00	14.50	121.
85.	.65	4.030	10.00	14.50	121.
85.	.65	4.040	10.00	14.50	121.
AVERAGE 85.	.65	4.031	10.00	14.50	122.

LFE VOL, SCF 6032.0	LFE MASS, LB. 453.2	BLOWER + 47mm VOL, SCF 6953.0	BLOWER + 47mm MASS, LB 522.4
LFE FLOW SCFM 201.07	LFE FLOW LB/MIN 15.11	BLOWER + 47mm FLOW SCFM 231.77	BLOWER + 47mm FLOW LB/MIN 17.41
F/A DRY, MEAS .0230	F/A CALC .0250	F/A PCT, MEAS 8.7	

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-77&78	24.548	69.	4.060	.165
2	P47-79&80	24.558	69.	4.636	.189

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 122. DILUTION FACTOR 7.549
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 921.1 (26.08) , 2.31

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-77&78	1.249 (44.085)	.3075	55.066	.308
P47-79&80	1.425 (50.319)	.3074	62.853	.351

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	193.318	1.080	297. PPMC
CO	234.398	1.309	184. PPM
NOX	2849.965	15.922	1371. PPM
NOX, CORR	2553.586	14.266	
CO2		462.	5.35 PCT
O2			12.66 PCT
NOX CORRECTION FACTOR	.8960		WET CORRECTION FACTOR .9562

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 8

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 1
ENGINE MODEL EMD 2-567
TEST CELL LOCO LAB
HCR 1.656
BLOWER COUNTS 45375.
OBS. POWER,BHP 206.0

TEST DATE 2/26/91
DIESEL COAL LIQU
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 66.
FUEL FLOW, LB/MIN 1.48

BAROMETER 29.49 IN.HG.
HUMIDITY 35.93 GRAINS H2O/LB. AIR
LPE NO. 15 ENG. LPE NO. 0
SAMPLE TIME 47mm 30.00 MIN.
MEAS. EXH. FLOW, LB/MIN 62.06
AIR FLOW, LB/MIN 60.58

LPE INFORMATION

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
83.	.65	4.100
83.	.65	4.100
83.	.65	4.100
83.	.65	4.100
83.	.65	4.100
83.	.65	4.100
83.	.65	4.100
83.	.65	4.100
AVERAGE 83.	.65	4.100

BLOWER INFORMATION

INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
10.00	14.50
10.00	14.50
10.00	14.50
10.00	14.50
10.00	14.50
10.00	14.50
10.00	14.50
10.00	14.50
AVERAGE 10.00	14.50

OTHER

TUNNEL TEMP DEG. F
120.
120.
120.
120.
120.
120.
120.
120.
AVERAGE 120.

LPE VOL, SCF 6173.8
LPE FLOW SCFM 205.81
F/A DRY, MEAS .0246

LPE MASS, LB. 463.9
LPE FLOW LB/MIN 15.46
F/A CALC .0294

BLOWER + 47mm VOL, SCF 7029.1
BLOWER + 47mm FLOW SCFM 234.32
F/A PCT, MEAS 19.3

BLOWER + 47mm MASS, LB 528.2
BLOWER + 47mm FLOW LB/MIN 17.61

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-73&74	24.048	65.	4.703	.196
2	P47-75&76	24.157	65.	5.429	.225

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 120.
SPLIT EXHAUST VOL, SCF (SCH), LB/MIN 855.3 (24.22) , 2.14

DILUTION FACTOR 8.218

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCH)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-73&74	1.607 (56.752)	.3418	79.653	.387
P47-75&76	1.847 (65.218)	.3402	91.535	.444

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	226.359	1.099	339. PPMC
CO	287.697	1.397	222. PPM
NOX	2871.758	13.941	1358. PPM
NOX, CORR	2642.882	12.830	
CO2		483.	6.32 PCT
O2			7.98 PCT
NOX CORRECTION FACTOR	.9203		WET CORRECTION FACTOR .9482

APPENDIX D

D-1

GASEOUS and/or PARTICULATE EMISSIONS

IDLE

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 9
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 45069.
OBS. POWER,BHP .0

TEST DATE 2/28/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 71.
FUEL FLOW, LB/MIN .09

BAROMETER 29.01 IN.HG.
HUMIDITY 83.92 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 30.00 MIN.
MEAS. EXH. FLOW, LB/MIN 16.94
AIR FLOW, LB/MIN 16.85

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
78.	.53	4.400	10.00	14.00	101.
78.	.53	4.400	10.00	14.00	101.
78.	.53	4.400	10.00	14.00	101.
77.	.53	4.400	10.00	14.00	101.
77.	.53	4.400	10.00	14.00	101.
77.	.53	4.400	10.00	14.00	101.
77.	.53	4.400	10.00	14.00	101.
AVERAGE 77.	.53	4.400	10.00	14.00	101.

LFE VOL, SCF 6618.4 LFE MASS, LB. 497.3 BLOWER + 47mm VOL, SCF 6796.7 BLOWER + 47mm MASS, LB 510.7
LFE FLOW SCFM 220.61 LFE FLOW LB/MIN 16.58 BLOWER + 47mm FLOW SCFM 226.56 BLOWER + 47mm FLOW LB/MIN 17.02
F/A DRY, MEAS .0054 F/A CALC .0046 F/A PCT, MEAS -14.1

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-142&14	22.090	65.	3.385	.153
2	P90-144&14	22.081	65.	3.330	.151

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 101. DILUTION FACTOR 38.118
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 178.3 (5.05) , .45

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, NG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-142&14	5.841 (206.245)	1.7255	79.009	.000
P90-144&14	5.749 (202.983)	1.7263	77.760	.000

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	29.001	.000	115. PPMC
CO	41.799	.000	82. PPM
NOX	96.748	.000	117. PPM
NOX, CORR	108.285	.000	
CO2		0.	.96 PCT
O2			18.95 PCT
NOX CORRECTION FACTOR	1.1193		WET CORRECTION FACTOR .9882

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 1

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 8
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 23590.
OBS. POWER, BHP 8.4

TEST DATE 2/28/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 72.
FUEL FLOW, LB/MIN .13

BAROMETER 28.91 IN. HG.
HUMIDITY 89.86 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 15.69 MIN.
MEAS. EXH. FLOW, LB/MIN 16.71
AIR FLOW, LB/MIN 16.58

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
82.	.55	4.700	10.00	14.00	111.
82.	.55	4.700	10.00	14.00	112.
82.	.55	4.700	10.00	14.00	111.
80.	.55	4.700	10.00	14.00	110.
AVERAGE 82.	.55	4.700	10.00	14.00	111.

LFE VOL, SCF 3624.2 LFE MASS, LB. 272.3 BLOWER + 47mm VOL, SCF 3538.2 BLOWER + 47mm MASS, LB 265.9
LFE FLOW SCFM 230.99 LFE FLOW LB/MIN 17.36 BLOWER + 47mm FLOW SCFM 225.51 BLOWER + 47mm FLOW LB/MIN 16.94
F/A DRY, MEAS .0078 F/A CALC .0070 F/A PCT, MEAS -10.0

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-138&13	11.740	68.	4.228	.360
2	P90-140&14	11.701	68.	4.166	.356

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 111. DILUTION FACTOR *****
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN ***** (*****) , ****

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-138&13	***** (*****)	*****	*****	*****
P90-140&14	***** (*****)	*****	*****	*****

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	28.571	3.405	120. PPMC
CO	55.374	6.600	116. PPM
NOX	149.600	17.831	193. PPM
NOX, CORR	159.175	18.972	
CO2		1005.	1.46 PCT
O2			18.69 PCT
NOX CORRECTION FACTOR		1.0640	WET CORRECTION FACTOR .9835

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 2

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 7
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 36081.
OBS. POWER, BHP 19.7

TEST DATE 2/28/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 74.
FUEL FLOW, LB/MIN .20

BAROMETER 29.07 IN.HG.
HUMIDITY 87.16 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47min 24.00 MIN.
MEAS. EXH. FLOW, LB/MIN 22.13
AIR FLOW, LB/MIN 21.93

LFE INFORMATION

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
79.	.50	4.290
79.	.50	4.290
79.	.50	4.280
79.	.50	4.290
79.	.50	4.300
79.	.50	4.290
AVERAGE 79.	.50	4.290

BLOWER INFORMATION

INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
AVERAGE 10.00	14.00

OTHER

TUNNEL TEMP DEG. F
120.
120.
120.
120.
120.
120.
120.
AVERAGE 120.

LFE VOL, SCF 5153.3
LFE FLOW SCFM 214.71
F/A DRY, MEAS .0092

LFE MASS, LB. 387.2
LFE FLOW LB/MIN 16.13
F/A CALC .0080

BLOWER + 47min VOL, SCF 5422.5
BLOWER + 47min FLOW SCFM 225.92
F/A PCT, MEAS -13.4

BLOWER + 47min MASS, LB 407.4
BLOWER + 47min FLOW LB/MIN 16.98

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-134&13	18.016	67.	5.051	.280
2	P90-136&13	18.045	67.	4.976	.276

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 120.
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 269.2 (7.63) , .84

DILUTION FACTOR 20.140

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)
P47-134&13	5.646 (199.377)
P90-136&13	5.554 (196.098)

CONCENTRATION MULTIPLIER
1.1179
1.1161

G/HR
99.780
98.139

G/HP-HR
5.065
4.982

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	40.811	2.072	125. PPMC
CO	73.537	3.733	113. PPM
NOX	285.514	14.493	268. PPM
NOX, CORR	318.895	16.188	
CO2		672.	1.67 PCT
O2			18.07 PCT
NOX CORRECTION FACTOR	1.1169		WET CORRECTION FACTOR .9819

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 3

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 6
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 45099.
OBS. POWER, BHP 46.0

TEST DATE 2/28/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 74.
FUEL FLOW, LB/MIN .35

BAROMETER 29.07 IN.HG.
HUMIDITY 82.07 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 30.00 MIN.
MEAS. EXH. FLOW, LB/MIN 28.22
AIR FLOW, LB/MIN 27.87

LFE INFORMATION

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
81.	.55	4.100
81.	.55	4.100
81.	.55	4.100
81.	.55	4.100
81.	.55	4.100
81.	.55	4.100
81.	.55	4.100
81.	.55	4.100

AVERAGE 81.

.55

4.100

BLOWER INFORMATION

INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00

10.00

14.00

OTHER

TUNNEL TEMP DEG. F
122.
122.
122.
122.
122.
122.
122.
122.

122.

LFE VOL, SCF 6128.1
LFE FLOW SCFM 204.25
F/A DRY, MEAS .0127

LFE MASS, LB. 460.5
LFE FLOW LB/MIN 15.35
F/A CALC .0116

BLOWER + 47mm VOL, SCF 6776.1
BLOWER + 47mm FLOW SCFM 225.84
F/A PCT, MEAS -8.4

BLOWER + 47mm MASS, LB 509.2
BLOWER + 47mm FLOW LB/MIN 16.97

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-129&13	21.678	68.	3.295	.152
2	P90-131&13	21.701	69.	4.027	.186

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 122.
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 648.0 (18.35) , 1.62

DILUTION FACTOR 10.457

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)
P47-129&13	1.589 (56.120)
P90-131&13	1.940 (68.514)

CONCENTRATION MULTIPLIER
.4824
.4818

G/HR
35.813
43.722

G/HP-HR
.779
.950

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	51.213	1.113	130. PPMC
CO	64.460	1.401	82. PPM
NOX	527.061	11.458	412. PPM
NOX, CORR	568.413	12.357	
CO2		504.	2.44 PCT
O2			17.19 PCT
NOX CORRECTION FACTOR		1.0785	WET CORRECTION FACTOR .9755

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 4

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 5
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 28131.
OBS. POWER, BHP 78.0

TEST DATE 2/28/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 75.
FUEL FLOW, LB/MIN .54

BAROMETER 29.08 IN.HG.
HUMIDITY 85.57 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 18.72 MIN.
MEAS. EXH. FLOW, LB/MIN 33.87
AIR FLOW, LB/MIN 33.33

LFE INFORMATION

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
83.	.59	3.920
83.	.59	3.920
83.	.59	3.920
83.	.59	3.920
83.	.59	3.930

AVERAGE 83. .59 3.922

BLOWER INFORMATION

INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00

OTHER

TUNNEL TEMP DEG. F
122.
124.
124.
124.
124.
124.

LFE VOL, SCF 3640.5
LFE FLOW SCFM 194.52
F/A DRY, MEAS .0165

LFE MASS, LB. 273.5
LFE FLOW LB/MIN 14.62
F/A CALC .0149

BLOWER + 47mm VOL, SCF 4220.2
BLOWER + 47mm FLOW SCFM 225.50
F/A PCT, MEAS -9.8

BLOWER + 47mm MASS, LB 317.1
BLOWER + 47mm FLOW LB/MIN 16.94

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-125&12	13.673	69.	2.529	.185
2	P90-127&12	13.605	69.	3.295	.242

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 124.
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 579.7 (16.42) , 2.33

DILUTION FACTOR 7.280

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)
P47-125&12	1.346 (47.544)
P90-127&12	1.763 (62.254)

CONCENTRATION MULTIPLIER

.5324
.5351

G/HR
36.420
47.687

G/HP-HR
.467
.611

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	68.298	.876	142. PPNC
CO	63.935	.820	68. PPM
NOX	950.598	12.187	615. PPM
NOX, CORR	1021.883	13.101	
CO2		464.	3.15 PCT
O2			15.93 PCT
NOX CORRECTION FACTOR		1.0750	WET CORRECTION FACTOR .9695

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 5

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 4
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 26164.
OBS. POWER,BHP 114.0

TEST DATE 2/28/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 72.
FUEL FLOW, LB/MIN .76

BAROMETER 29.10 IN.HG.
HUMIDITY 80.42 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47min 17.40 MIN.
MEAS. EXH. FLOW, LB/MIN 40.38
AIR FLOW, LB/MIN 39.62

LFE INFORMATION

BLOWER INFORMATION

OTHER

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O	TUNNEL TEMP DEG. F
84.	.60	3.950	10.00	14.00	122.
84.	.60	3.950	10.00	14.00	124.
84.	.60	3.950	10.00	14.00	124.
84.	.60	3.950	10.00	14.00	123.
84.	.62	3.950	10.00	14.00	123.
AVERAGE 84.	.60	3.950	10.00	14.00	123.

LFE VOL, SCF 3398.7	LFE MASS, LB. 255.4	BLOWER + 47min VOL, SCF 3951.1	BLOWER + 47min MASS, LB 296.9
LFE FLOW SCFM 195.35	LFE FLOW LB/MIN 14.68	BLOWER + 47min FLOW SCFM 227.10	BLOWER + 47min FLOW LB/MIN 17.06
F/A DRY, MEAS .0194	F/A CALC .0189	F/A PCT, MEAS -2.5	

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE SYS. TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-121&12	12.712	69.	2.269	.178
2	P90-123&12	12.693	69.	2.236	.176

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 123. DILUTION FACTOR 7.153
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 552.4 (15.64) , 2.39

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-121&12	1.277 (45.083)	.5627	41.166	.361
P90-123&12	1.260 (44.495)	.5636	40.629	.356

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	84.711	.743	160. PPM
CO	101.045	.886	97. PPM
NOX	1494.226	13.107	882. PPM
NOX, CORR	1567.139	13.747	
CO2		443.	4.01 PCT
O2			14.39 PCT
NOX CORRECTION FACTOR	1.0488		WET CORRECTION FACTOR .9623

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 6

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 3
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 45115.
OBS. POWER, BHP 148.0

TEST DATE 2/28/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 71.
FUEL FLOW, LB/MIN .98

BAROMETER 29.14 IN.HG.
HUMIDITY 75.20 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 30.00 MIN.
MEAS. EXH. FLOW, LB/MIN 47.63
AIR FLOW, LB/MIN 46.65

LFE INFORMATION

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
86.	.65	4.050
86.	.65	4.050
86.	.65	4.050
86.	.65	4.050
86.	.65	4.050
86.	.65	4.030
86.	.65	4.030

AVERAGE 86.

.65

4.044

BLOWER INFORMATION

INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00

10.00

14.00

OTHER

TUNNEL TEMP DEG. F
121.
121.
121.
122.
122.
122.
121.

121.

LFE VOL, SCF 5962.9
LFE FLOW SCFM 198.77
F/A DRY, MEAS .0213

LFE MASS, LB. 448.0
LFE FLOW LB/MIN 14.94
F/A CALC .0227

BLOWER + 47mm VOL, SCF 6837.2
BLOWER + 47mm FLOW SCFM 227.92
F/A PCT, MEAS 6.4

BLOWER + 47mm MASS, LB 513.7
BLOWER + 47mm FLOW LB/MIN 17.13

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-117411	22.388	68.	3.392	.152
2	P90-119412	22.388	68.	3.323	.148

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 121.
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 874.3 (24.76) , 2.19

DILUTION FACTOR 7.820

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)
P47-117411	1.185 (41.836)
P90-119412	1.161 (40.985)

CONCENTRATION MULTIPLIER

.3493
.3493

G/HR

45.065
44.149

G/HP-HR

.304
.298

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	99.012	.669	172. PPM
CO	178.535	1.206	160. PPM
NOX	2096.816	14.168	1150. PPM
NOX, CORR	2146.632	14.504	
CO2		443.	4.83 PCT
O2			14.42 PCT
NOX CORRECTION FACTOR		1.0238	WET CORRECTION FACTOR .9556

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 7

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 2
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 39775.
OBS. POWER, BHP 179.0

TEST DATE 2/28/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 71.
FUEL FLOW, LB/MIN 1.22

BAROMETER 29.18 IN.HG.
HUMIDITY 59.78 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 26.44 MIN.
MEAS. EXH. FLOW, LB/MIN 54.42
AIR FLOW, LB/MIN 53.20

LFE INFORMATION

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
88.	.65	4.100
88.	.65	4.100
88.	.65	4.100
88.	.65	4.100
88.	.65	4.100
88.	.65	4.100
88.	.65	4.100
88.	.65	4.100

AVERAGE 88. .65 4.100

LFE VOL, SCF 5297.2
LFE FLOW SCFM 200.37
F/A DRY, MEAS .0231
LFE MASS, LB. 398.0
LFE FLOW LB/MIN 15.06
F/A CALC .0255

BLOWER INFORMATION

INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00

10.00 14.00

BLOWER + 47mm VOL, SCF 6035.7
BLOWER + 47mm FLOW SCFM 228.31
F/A PCT, MEAS 10.1

OTHER

TUNNEL TEMP DEG. F
123.
123.
124.
124.
124.
124.
124.
124.

124.

BLOWER + 47mm MASS, LB 453.5
BLOWER + 47mm FLOW LB/MIN 17.16

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD. CU. FEET	AVG. SAMPLE TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-113&11	19.168	71.	3.121	.163
2	P90-115&11	19.197	71.	3.252	.169

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 124.
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 738.6 (20.92) , 2.10
DILUTION FACTOR 8.172

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)	CONCENTRATION MULTIPLIER	G/HR	G/HP-HR
P47-113&11	1.331 (46.986)	.4264	57.825	.323
P90-115&11	1.384 (48.884)	.4257	60.161	.336

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	150.811	.843	237. PPM
CO	316.210	1.767	257. PPM
NOX	2456.928	13.726	1223. PPM
NOX, CORR	2405.404	13.438	
CO2		453.	5.43 PCT
O2			13.16 PCT
NOX CORRECTION FACTOR	.9790		WET CORRECTION FACTOR .9514

GASEOUS and/or PARTICULATE EMISSIONS

NOTCH 8

PROJECT 03-2681-809

PROGRAM = EMD16B

TEST NO. RUN NO. 1
ENGINE MODEL EMD 2-567B
TEST CELL LOCO LAB
HCR 1.758
BLOWER COUNTS 30246.
OBS. POWER,BHP 206.0

TEST DATE 2/28/91
DIESEL DF-2
TUNNEL NO. 26
SAMPLE TIME 20x20 .00 MIN.
BLOWER TEMP. DEG. F 70.
FUEL FLOW, LB/MIN 1.47

BAROMETER 29.00 IN.HG.
HUMIDITY 68.95 GRAINS H2O/LB. AIR
LFE NO. 15 ENG. LFE NO. 0
SAMPLE TIME 47mm 20.10 MIN.
MEAS. EXH. FLOW, LB/MIN 60.20
AIR FLOW, LB/MIN 58.73

LFE INFORMATION

INLET TEMP DEG. F	INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
86.	.65	4.120
86.	.65	4.120
86.	.65	4.120
87.	.65	4.120
87.	.65	4.120

AVERAGE 86.

.65

4.120

BLOWER INFORMATION

INLET PRESS. IN. H2O	DIFF. PRESS. IN. H2O
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00
10.00	14.00

10.00

14.00

OTHER

TUNNEL TEMP DEG. F
122.
122.
122.
122.
122.

122.

LFE VOL, SCF 4042.1
LFE FLOW SCFM 201.10
F/A DRY, MEAS .0253

LFE MASS, LB. 303.7
LFE FLOW LB/MIN 15.11
F/A CALC .0296

BLOWER + 47mm VOL, SCF 4570.7
BLOWER + 47mm FLOW SCFM 227.40
F/A PCT, MEAS 17.2

BLOWER + 47mm MASS, LB 343.4
BLOWER + 47mm FLOW LB/MIN 17.09

FILTER DATA

POSITION	FILTER NUMBER	SAMPLE VOL. STD.CU.FEET	AVG. SAMPLE TEMP DEG F	WEIGHT GAIN MILLIGRAMS	MG/SCF OF SAMPLE
1	P47-109411	15.555	66.	2.889	.186
2	P90-111411	15.604	66.	2.853	.183

PARTICULATE RESULTS

AVG. SAMPLE ZONE TEMP, DEG F 122.
SPLIT EXHAUST VOL, SCF (SCM), LB/MIN 528.6 (14.97) , 1.98

DILUTION FACTOR 8.647

PARTICULATE CONCENTRATION IN EXHAUST

FILTER	CONCENTRATION, MG/SCF (MG/SCM)
P47-109411	1.606 (56.708)
P90-111411	1.581 (55.826)

CONCENTRATION MULTIPLIER

.5559
.5542

G/HR
77.199
76.000

G/HP-HR
.375
.369

EMISSION RESULTS

	G/HR	G/HP-HR	CONC.
HC	140.373	.681	212. PPMC
CO	668.319	3.244	526. PPM
NOX	2892.032	14.039	1395. PPM
NOX, CORR	2879.349	13.977	
CO2		473.	6.32 PCT
O2			11.90 PCT
NOX CORRECTION FACTOR		.9956	WET CORRECTION FACTOR .9435

APPENDIX E

DIMENSION SHEET

	DATE	BEGINNING or END OF TEST	RIGHT SIDE		LEFT SIDE	
			FRONT	REAR	FRONT	REAR
PISTON TO HEAD CLEARANCE Ref. PAGE 318 LIMIT <u>.068</u> <u>.026</u> NOTE RECORD BOTH BEFORE & AFTER TEST	11-15-90		.065	.057	.051	.056

PISTON PIN DIAMETER

**BORE OF
BLADE
ROD**

DATE _____

LEFT 88-G D0438

RIGHT 88-H 0060

[illegible]

DIMENSION SHEET

SERIAL NO.	DATE	RING THICKNESS			GAP IN 8.500 LINER	WIDTH	RING TO LAND CLEARANCE
		A	B	C			
<p>TOP RING LEFT SIDE</p> <p>Ref. Page 318 LIMIT GAP $\frac{.035}{.025}$ WIDTH $\frac{.247}{.246}$</p> <p>RING TO LAND CLEARANCE (ON ASSEMBLY) $\frac{.008}{.004}$</p> <p>Note: Record Both at Beginning and End of Test</p>	10-24-90	.3063	.3075	.3028	.035	.2470	
	10-29-90						.004
	3-22-91	.3055	.3065	.3025	.035	.2465	
	3-27-91						.005
	Discrepancy	0.0008	0.0001	0.0003	-0-	0.0005	0.001

[illegible]

DIMENSION SHEET

	DATE	RIGHT SIDE					LEFT SIDE				
		RING NO. 2	3	4	5		2	3	4	5	
PISTON RING WIDTH	10-24-90	.2430	.2425	.2485	.2485		.2425	.2428	.2485	.2485	
Record Both at Beginning & End Of Test	5-25-91	.2435	.2423	.2485	.2485		.2420	.2425	.2485	.2485	
LIMITS											
COMP. RINGS											
.247											
.246											
OIL RINGS											
.249											
.248											
REF. PAGE 318											

DIMENSION SHEET

	DATE	RIGHT SIDE					LEFT SIDE				
		RING NO. 2	3	4	5		2	3	4	5	
RING TO LAND CLEARANCE	10-29-90	.007	.007	.002	.002		.007	.007	.002	.002	
	3-27-91	.006	.008	.002	.002		.007	.007	.002	.002	
Record Both At Beginning and End of Test											
LIMITS COMP. RINGS											
OIL RINGS											
REF. PAGE 318											

[illegible]

[illegible]

Note: Record at beginning and end of each test.

See Page 318

Limits:

Top Land 8.447-8.452

8.488-8.490
Skirt

[illegible]

[illegible]

DIMENSION SHEET 14C

[illegible]

[illegible]

DIMENSION SHEET 15D

D Type Pin Bearing

The numbered end of the insert will go to the pee hole end of the carrier. The land labeled B at one end will become C at the other end.

F-16

DATE	RIGHT CARRIER PIN BEARING THICKNESS CARRIER NO. 87B-00373				OTHER END			
	PEE END			c	OTHER END			c
	a	b	c		a	b	c	
10-24-90	0.150	0.151	0.150		0.150	0.150	0.150	
3-20-91	0.150	0.151	0.150		0.150	0.150	0.150	
	LEFT CARRIER PIN BEARING THICKNESS CARRIER NO. 87B-00364				OTHER END			
	PEE END			c	OTHER END			c
	a	b	c		a	b	c	
10-24-90	0.150	0.150	0.150		0.150	0.150	0.150	
3-20-91	0.150	0.150	0.150		0.150	0.150	0.150	

DIMENSION SHEET 20

VALVE LEAKCHECK	DATE	CYL HEAD SH 21.3 4155				CYL HEAD SH 81J 4155			
		RIGHT SIDE				LEFT SIDE			
		1	2	3	4	1	2	3	4
<p>Test Cock</p> <p>CYLINDER HEAD (BOTTOM VIEW)</p> <p>Reference: MEASUREMENT PROCEDURE BULLETIN- TIME TO FILL RUBBER BULB (3" DIAMETER) COMPLETELY COLLAPSED</p> <p>^{1 1/2} LIMIT: 1 MINUTES MINIMUM RECORD ON ASSEMBLY ONLY</p>	10-9-90	2 MIN.	2 MIN.	2 MIN.	2 MIN.	2 MIN.	2 MIN.	2 MIN.	

[illegible]

SERIAL NO.	DATE	LETTER DIMENSIONS					LETTER DIMENSIONS				
		A	B	C	D	E	A'	B'	C'	D'	E'
		Depth	2"	6"	13"	16"	1"	2"	6"	13"	16"
90F 122D	10-30-90	8.5006	8.5000	8.4998	8.4975	8.4974	7.5008	7.5024	7.5025	7.4996	8.4984
LEFT HAND CYLINDER	5-28-91	8.5001	8.5002	8.4998	8.4994	8.4983	8.5014	8.5081	7.5078	8.4999	8.4984
	DIFFERENCE	-0.0005	0.0002	-0.0002	-0.0001	-0.0001	0.0026	0.0057	0.0053	0.0003	-0.0003

EMD TEST NO. _____

TEST PART WEIGHTS, GRAMSCamshaft Bearings

	Date	Right Front	Left Front	Right Rear	Left Rear
0 hours					
300 hours					

Pin Bearings

	Date	Right	Left
0 hours	11-14-90	508.40	509.65
300 hours	3-19-91	507.47	508.60

Thrust Washers

	Date	Right	Left
0 hours	11-14-90	715.62	715.33
300 hours	3-19-91	714.12	712.82

TEST PART DIMENSIONS, INCHESPiston Pin Diameter (Parallel to Threaded Holes)

		Date	Pee Hole End	Center	Opposite End
Right	0 hours	11-14-90	3.6845	3.6845	3.6845
	300 hours	3-19-91	3.6850	3.6849	3.6849
Left	0 hours	11-14-90	3.6840	3.6840	3.6839
	300 hours	3-19-91	3.6843	3.6843	3.6843

Pin Bearing Clearance in Carrier

		Date	Pee Hole End	Center	Opposite End
Right	0 hours	11-14-90	.010	.013	.016
	300 hours	3-19-91	.009	.013	.016
Left	0 hours	11-14-90	.009	.010	.013
	300 hours	3-19-91	.007	.009	.013

APPENDIX F

LEFT

RIGHT

LEFT

RIGHT

END

**DATE
FILMED**

4 / 29 / 92