10
3-25-92 JS①

LBL-29507 Rev.
UC-350

Lawrence Berkeley Laboratory

UNIVERSITY OF CALIFORNIA

APPLIED SCIENCE
DIVISION

**CO₂ Emissions from Developing Countries: Better
Understanding the Role of Energy in the Long Term**

Volume I: Summary

J. Sathaye and A. Ketoff

February 1991

APPLIED SCIENCE
DIVISION

DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. Neither the United States Government nor any agency thereof, nor The Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or The Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or The Regents of the University of California and shall not be used for advertising or product endorsement purposes.

This report has been reproduced directly
from the best available copy.

Available to DOE and DOE Contractors
from the Office of Scientific and Technical Information
P.O. Box 62, Oak Ridge, TN 37831
Prices available from (615) 576-8401, FTS 626-8401

Available to the public from the
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road, Springfield, VA 22161

Lawrence Berkeley Laboratory is an equal opportunity employer.

**CO₂ EMISSIONS FROM DEVELOPING COUNTRIES:
BETTER UNDERSTANDING THE ROLE OF ENERGY IN THE LONG TERM**

Volume I: Summary

Jayant Sathaye and Andrea Ketoff
International Energy Studies Group
Energy Analysis Program
Lawrence Berkeley Laboratory

July 1991

This work was supported by the U.S. Environmental Protection Agency, Office of Policy Analysis, Division of Global Climate Change through the US Department of Energy Contract No. DE-AC03-76SF00098.

MASTER *eb*

REPRODUCTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

This study examines energy use and carbon emissions in the developing world. Based on analyses of present energy-use patterns in 17 developing nations, this study presents high emissions and low emissions scenarios for these nations in the year 2025. These nations combined account for two thirds of the energy-related carbon emissions presently generated in the developing world. The analysis reveals that energy demand expands dramatically by 2025 and grows increasingly carbon intensive. In the high emissions scenario, carbon emissions from these countries increase four-fold. The greatest share of carbon stems from the industrial sector in 2025, followed by the transport and residential sectors. With the implementation of policies aimed at reducing CO₂ emissions, the low emissions scenario reduces the level of carbon in 2025 by 20 percent relative to the high emissions scenario figure. These nations achieve 80 percent of the carbon reductions by improving the efficiency of energy production and use and the remaining 20 percent by implementing fuel-switching measures. Of all the sectors examined, the industrial sector offers the greatest opportunity for absolute carbon savings (39 percent of the total).

Despite improvements in energy intensity, carbon emissions rise three-fold by 2025 in the low emissions scenario. These results indicate that rapidly increasing energy demands in the developing world, spurred by high rates of population growth and the desire for higher levels of material comfort, will continue to outpace the incorporation of energy-efficiency improvements into developing world economies. While opportunities exist to restrain the growth of energy use, the development paradigms currently being followed by developing nations -- based largely on industrialized world models -- will require substantially larger energy inputs in the future. As a result, emissions of carbon dioxide inevitably will rise. Despite these increases, according to both scenarios carbon emissions per capita in developing countries grow relatively slowly and remain only a fraction of per capita levels in industrialized nations in 2025.

PREFACE

Recent years have witnessed a growing recognition of the link between emissions of carbon dioxide (CO₂) and changes in the global climate. Of all anthropogenic activities, energy production and use generate the single largest portion of these greenhouse gases. Although developing countries currently account for a small share of global carbon emissions, their contribution is increasing rapidly. Due to the rapid expansion of energy demand in these nations, the developing world's share in global modern energy use rose from 16 to 27 percent between 1970 and 1990.¹ If the growth rates observed over the past 20 years persist, energy demand in developing nations will surpass that in the countries of the Organization for Economic Cooperation and Development (OECD) early in the 21st century.

Restraining the future growth of carbon dioxide emissions in the developing world entails a thorough understanding of present and future patterns of energy use in these regions. To address this need, the International Energy Studies Group at the Lawrence Berkeley Laboratory (LBL) initiated this study in collaboration with research groups in the developing world. The study seeks to examine the forces that galvanize the growth of energy use and carbon emissions, to assess the likely future levels of energy and CO₂ in selected developing nations and to identify opportunities for restraining this growth. The purpose of this report is to provide the quantitative information needed to develop effective policy options, not to identify the options themselves. The results are being used by the Intergovernmental Panel on Climate Change to determine the impact of changes in energy use and supply on carbon emissions and, ultimately, on the Earth's climate. The U.S. Environmental Protection Agency supported this work.

Individual studies were conducted for Argentina, Brazil, Mexico and Venezuela in Latin America; China, India, Indonesia and South Korea in Asia; and Nigeria, Sierra Leone and Ghana in Africa. A combined study was carried out for the countries of the Gulf Cooperation Council (Bahrain, Kuwait, Oman, Qatar, Saudi Arabia and the United Arab Emirates). For each nation, the participating regional experts derived a set of reasonable assumptions about future activity levels from a thorough analysis of energy use patterns in 1985.² Based on this information, the experts then developed high and low scenarios of energy use and carbon emissions for the year 2025. Although the same spread-sheet model was used for all of the country studies, the socio-economic and energy-related assumptions made in each case differ according to the unique conditions of each nation (See appendix A for a description of the methodology of the study).

The summary paper is being published in this volume (Volume I). The individual country studies for the Latin American, Asian and African and GCC countries are being published separately (Volumes II, III and IV respectively).

¹ These figures include the Middle East. British Petroleum Company, *BP Statistical Review of World Energy* (London: Corporate Communications Services, June 1991).

² Alternate base years were chosen in three cases due to the availability of better data (1987 for Mexico and Ghana and 1984 for Venezuela).

The scenarios and the initial report for each country were prepared by the following experts:

Argentina	---	Alfredo Behrens, Panama
Brazil	---	Gilena Graca, University of São Paulo
China	---	Wu Zongxin and Wei Zhihong, Tsing Hua University
Ghana/Sierra Leone	---	Ogunlade R. Davidson, University of Sierra Leone
GCC Countries	---	Abdul Majeed Al Shatti, Kuwait Institute for Scientific Research
India	---	R.K. Pachauri, Vivek Suri and Sujata Gupta, Tata Energy Research Institute
Indonesia	---	Saswinadi Sasmojo, Institut Teknologi Bandung
Korea	---	Ji-Chul Ryu and Seung-Jin Kang, Korea Energy Economics Institute
Mexico	---	Yolanda Mendoza, Ministry of Mines and Energy Gautam Dutt, National University of Mexico
Nigeria	---	A.O. Adegbulugbe, Obafemi Awolowo University
Venezuela	---	Nora Pereira, Ministry of Energy and Mines Ana Maria Segnini

In each case, the opinions expressed are those of the authors and do not necessarily reflect those of the affiliated institutions. The authors of this summary would like to thank Nina Goldman for editing this report.

Two workshops were held in conjunction with this project. We would like to thank the workshop participants, the individuals who contributed to the development of the scenarios and numerous colleagues in the United States and abroad who supported this project. We would specifically like to acknowledge the support of Hoe Sung Lee, Korea; A. Arismunandar, Indonesia; Zhou, Fengqi and Zhou, Dadi, China; Aaron Dychter and Marcelle Serrato, Mexico; Jose Goldemberg, Brazil; Alberto Larralde, Venezuela; Ibrahim Ibrahim, Qatar; and Irving Mintzer, United States.

**Participants in International Workshop on
Global Climate Change: Long-Term Energy Scenarios and
Policy Options for the Developing World, June 7-16, 1989**

Raul Aleman Petroleos de Venezuela S.A.	Seung-Jin Kang Ji-Chul Ryu Korea Energy Economics Institute	Peter Schwartz Global Business Network Emeryville, CA
Deborah Bleviss International Institute for Energy Conservation	Dan Lashof Natural Resources Defense Council	Al Sobey Bloomfield Hills, Michigan
Bill Chandler Batelle Pacific Northwest Lab	Yolanda Mendoza Ministry of Energy Mexico	Dan Sperling Mark DeLuchi University of California - Davis
Ogunlade Davidson University of Sierra Leone	Alan Miller Center for Global Change University of Maryland	Robert Williams Center for Energy and Environment Studies Princeton University
Qiu Daxiong Lu Ying-Zhong Wu Zongxin Tsinghua University China	Mohan Munasinghe World Bank	U.S. EPA Participants:
Joy Dunkerley Robin Roy Office of Technology Assessment U.S. Congress	Nora Periera Ministry of Energy and Mines Venezuela	Dilip Ahuja Dennis Tirpak
Gilena Graca University of São Paulo Brazil	Yogo Pratomo Office of Director-General for Power Indonesia	LBL Participants:
Sujata Gupta R.K. Pachauri Tata Energy Research Institute India	Amulya Reddy Indian Institute of Science	Charles Campbell Ashok Gadgil Charles Hitch Andrea Ketoff Florentin Krause Mark Levine Omar Masera Stephen Meyers Jayant Sathaye Lee Schipper Dave Shirley Isaac Turiel Rudy Verderber
Stein Hansen Norway	Marc Ross University of Michigan	
David Jhirad U.S. Agency for International Development	Saswinadi Sasmojo Institut Teknologi Bandung Indonesia	
	Stephen Schneider National Center for Atmospheric Research	

**Participants in International Workshop on
Reducing Carbon Dioxide Emissions from the Developing World:
Assessment of Benefits, Costs and Barriers, October 4-6, 1990**

A.O. Adegbulugbe
Obafemi Awolowo University
Nigeria

Abdul Majeed Al Shatti
Kuwait Institute for Scientific
Research

Ramesh Bhatia
University of Delhi

Jos J.C. Bruggink
ESC/CN
Netherlands

Richard Corrie
Ministry of Energy and Mines
Venezuela

Bill Chandler
Batelle Pacific Northwest Laboratory

Ogunlade Davidson
University of Sierra Leone

Christine Dawson
U.S. Department of State

Joy Dunkerley
Office of Technology Assessment
U.S. Congress

Luis Fernandez
National University of Mexico

Gilena Graca
University of São Paulo
Brazil

Namkoun Kyun
Moon Yoon Lee
Ministry of Energy
Korea

Yolanda Mendoza
Ministry of Energy
Mexico

Amulya Reddy
Indian Institute of Science

Saswinadi Sasmojo
Bandung Institute of Technology
Indonesia

Jerome Weingart
U.S. Agency for International
Development

John Weyant
Energy Modeling Forum
Stanford University

Wu Zongxin
Lu Ying-Zhong
Tsinghua University
China

U.S. EPA Participants:

Paul Schwengels
Dennis Tirpak

LBL Participants:

Charles Campbell
Maria Figueroa
Rafael Friedmann

Ashok Gadgil
Nina Goldman
Florentin Krause
Martha Krebbs
Lily Lee
Mark Levine
Willy Makundi
Omar Masera
Jayant Sathaye
Lee Schipper
Stephen Tyler

1 INTRODUCTION

In recent years, a number of studies have linked increases in the anthropogenic emissions of carbon dioxide¹ and other gases to global climate change. Of all human activities, energy production and use generate the single largest portion of these greenhouse gases.²

Developing countries currently account for a small share of global emissions of carbon dioxide (CO₂). Their contribution, however, is growing rapidly. Although tropical deforestation generates a sizable quantity of carbon emissions,³ energy consumption remains the largest single producer of greenhouse gases in developing nations. Energy use in these nations has increased at a faster rate than in the industrialized world over the past two decades (Figure 1); as a result, the developing world's share in the global consumption of modern energy rose from 16 to 24 percent between 1970 and 1989. If the average growth rates observed in the OECD and developing countries over the past 20 years persist, the level of energy demand in developing nations will approach that in the OECD countries by the year 2004.

Figure 1

WORLD PRIMARY ENERGY CONSUMPTION 1970-1989

¹ Throughout this paper the term carbon emissions only refers to those emissions generated from the production and use of commercial energy sources. Unless otherwise specified, emissions from the use of biomass fuels are excluded.

² Other significant sources include aerosols, refrigerants, rice cultivation, cement production and deforestation, which generate CFCs, methane and carbon dioxide.

³ Annual CO₂ emissions from tropical deforestation are estimated to be 700 million tons of carbon. This figure compares with approximately 1200 million tons a year from energy use in the same group of countries.

Restraining the future growth of carbon dioxide emissions in the developing world entails a thorough understanding of present and future patterns of energy use in these regions. To address this need, the International Energy Studies Group at the Lawrence Berkeley Laboratory has initiated a study in collaboration with research groups in a number of developing countries. The study seeks to examine the forces that galvanize the growth of energy use and carbon emissions, to assess the likely future levels of energy and CO₂ in selected developing nations and to identify opportunities for restraining this growth. The purpose of this report is to provide the quantitative information needed to develop effective policy options, not to identify the options themselves. An earlier report examined similar scenarios for five developing regions.⁴ Follow-up studies will examine the costs and benefits of reducing CO₂ emissions. The scenarios reported in this paper are being used by the Intergovernmental Panel on Climate Change to determine the impact of changes in energy use and supply on carbon emissions and, ultimately, on the Earth's climate.

This paper summarizes the results of long-term energy scenarios for China, India, Indonesia, Korea, Argentina, Brazil, Mexico, Venezuela, Nigeria, Ghana, Sierra Leone and the group of six member countries of the Gulf Cooperation Council (GCC).⁵ In 1985, these nations consumed 62 exajoules of energy. China and India together accounted for just under two thirds of this total (Figure 2). Hence, the aggregate figures for energy use and fuel shares presented throughout this paper are largely influenced by patterns of energy use in these two nations.

Figure 2

Country Shares in Primary Energy, 1985 (including biomass)

Total: 62 Exajoules

* 1987 data
** 1984 data

⁴ J. Sathaye, A. Ketoff, L. Schipper and S. Lele, *An End-Use Approach to Development of Long-Term Energy Demand Scenarios for Developing Countries*, Report No. LBL-25611 (Berkeley, California: Lawrence Berkeley Laboratory, 1989).

⁵ In this paper we refer to the study of GCC countries as one country study. The GCC countries include: Bahrain, Kuwait, Oman, Qatar, Saudi Arabia and the United Arab Emirates (UAE). The study presents the individual findings from the scenarios for the first 11 countries and an aggregate scenario for energy use in the GCC countries.

Primary energy per capita varies considerably among the 17 countries, ranging from a low of 12 gigajoules (GJ) per capita in India to a high of 208 GJ per capita in the GCC nations. Aside from in the Gulf region, levels of primary energy per capita in the study countries are far below per capita levels in industrialized countries (Figure 3).

Figure 3

**Primary Energy Per Capita, 1985
(including biomass)**

Based on a thorough analysis of energy-use patterns in 1985, regional experts from the participating developing countries derived a set of reasonable assumptions for the future. The experts then proceeded to create high and low estimates of energy use and carbon emissions for the year 2025. The low estimate for 2025 shows carbon emissions rising by almost 2 billion tons in the 12 study countries combined; the high estimate shows far greater CO₂ growth. These results indicate that even with substantial investment and technology transfer, population expansion and the growing demand for energy services in developing nations will lead to huge increases in carbon emissions by 2025. On a per capita basis, however, carbon emissions in the developing countries will remain far below average levels in industrialized nations in 2025.

The scenarios examine the implications of economic and population growth on changes in economic structure, ownership of consumer goods, production of industrial goods, unit-energy consumption and the mix of fuels. In addition, they help to identify the extent to which inadequate energy supply might constrain economic growth in some countries. This paper does not attempt to summarize the scenarios in a comprehensive manner, but rather to provide the reader with a sense of the set of transitions and issues that emerge as important to address in the debate on greenhouse gas emissions.

2 METHODOLOGY

The methodology used to construct the long-term energy scenarios combines elements of a detailed end-use analysis with judicious international comparisons to provide a guide to the likely level of activities in the future. The scenarios provide a self-consistent picture of the future from which energy demand and supply can be derived. The primary focus is on this picture of 2025; we do not explicitly analyze the path to the year 2025 quantitatively. Footnote 4 reports the detailed methodology.

Each country study examines the residential, transport, industrial, commercial and agricultural sectors and, for each of these sectors, estimates the demand for delivered energy, broken down into three major forms: fossil fuels, electricity and biomass.⁶ The studies further disaggregate the demand for fossil fuels into the use of coal, oil and natural gas. Based on the above analysis, the scenarios calculate the size of the fuel supply required to meet the energy demand. The scenarios rely on gross domestic product (GDP), in real terms, as the indicator of overall economic activity. The estimates of energy demand in the industrial, agriculture and service sectors and for freight transport take into account changes in the composition of GDP.

The approach used consists of three basic elements. First, the analysis separates energy demand according to its major end uses. Where information on future distribution of income is available, energy demand is further disaggregated by income class. The supply of primary energy is estimated on the basis of the demand for individual fuels and electricity for each major end use in each economic sector. Second, the study uses international comparisons to estimate future activity levels (e.g., the production of materials per capita and the saturation of consumer goods, such as appliances and cars). This method assumes that in the future developing countries will reach income levels similar to those enjoyed by more developed economies today and that purchases of consumer goods in developing countries will increase accordingly. In some countries changes in income distribution are analyzed explicitly for their impact on the saturation of consumer goods. Third, the scenarios balance levels of energy demand with energy supply in order to ascertain the availability of domestic and worldwide resources to meet 2025 demand levels. The use of the Atmospheric Stabilization Framework (ASF) checks the ability of the energy markets to meet the estimated demand at the assumed energy prices. The ASF has been applied extensively in the analysis of global energy scenarios.⁷ We report on the comparison of the 17 country studies and the ASF analysis at a later point in the paper.

Each sectoral discussion begins with a discussion of the particular end-use approach used. Each research group used the same spread sheet model (STAIR) to estimate the end-use and sectoral energy demand and the total primary energy supply (Figure 4). For each sector, the STAIR framework provides alternative ways of estimating energy demand. Different alternatives are chosen based on the availability of end-use data.

⁶ The terms "biomass" and "traditional energy sources" refer to agricultural residues, dung and fuelwood unless otherwise specified.

⁷ D. Lashof and D. Tirpak, *Policy Options for Stabilizing Global Climate -- Report to Congress*, (Washington, D.C.: U.S. Environmental Protection Agency, Office of Policy, Planning and Evaluation, February 1990).

Figure 4

INTERNATIONAL COMPARISONS

For each end-use, the estimate of energy demand depends on a series of driving forces. For example, factors such as distances traveled per car, fuel use per kilometer (fuel intensity) and levels of car ownership determine the energy demand for automobiles. The perceived availability of fuels and the relative prices as influenced by government policies determine the choice of fuels. Table 1 provides examples of the types of indicators used to estimate energy demand for 2025 for various end-uses.

Table 1
Structure and Indicators, Examples

Sector & End-Use	Indicators
General	Population (urban and rural), GDP and structure, fuel price, income distribution
Residential	Urban and rural population and number of households Level of electrification
Heating	Fuel use/household/degree-day
Cooking	Fuel use/capita per meal
Refrigerators	Unit electricity use per month
Transportation	Ton-kilometer by mode, distance traveled, number of vehicles/capita
Cars and Motorcycles	Fuel use/kilometer
Trucks and Buses	Fuel use/kilometer
Air and Water	Fuel use/value added
Industry	Physical output and value added
Energy-Intensive (Steel, Cement, etc.)	Fuel and electricity use/ton of output
Non-Energy-Intensive	Fuel and electricity use/value added
Mining	Fuel and electricity use/value added
Commercial	Fuel and electricity use and value added
Agriculture	Fuel and electricity use and value added

In most countries 1985 served as the base year for the scenarios. Different years were selected for Venezuela (1984), Ghana (1987) and Mexico (1987) due to the availability of better data. Estimates of changes in end-use efficiency and energy and fuel intensity are based on historical analyses of energy-consumption patterns. Researchers in individual countries relied primarily on literature available from sources within the countries. Comparative historical analyses have also been reported by Sathaye and Meyers, Sathaye, Ghirardi and Schipper, Goldemberg et al. among others.^{8,9,10}

⁸ J. Goldemberg, T. Johansson, A. Reddy and R. Williams, *Energy for a Sustainable World* (New Delhi: Wiley Eastern Limited, 1988).

⁹ J. Sathaye and S. Meyers, "Energy Use in the Cities of the Developing Countries," *Annual Review of Energy*, vol. 10, pp.109-33.

¹⁰ J. Sathaye, A. Ghirardi and L. Schipper, "Energy Demand in Developing Countries: A Sectoral Analysis of Recent Trends," *Annual Review of Energy*, vol. 12, 1987, pp.253-81

The use of **international comparisons** helps to determine the saturation of various energy-consuming goods in the residential and transportation sectors and to estimate the production levels of energy-intensive materials in the industrial sector. Basic elements of today's energy-use patterns (e.g., automobile and truck use, household appliance ownership, etc.) at different income levels are used to select future activity levels consistent with the income levels each developing country is projected to reach by 2025. Future activity levels are then modified to take into account the fact that changes in the ownership of energy-consuming goods depend not only on changes in income but also on changes in the prices of goods. In choosing comparison countries, researchers look for similarities in saturation levels across countries and/or regions. For example, automobile saturations in Latin America are several times those in Asia at relatively similar average income levels. Hence, Latin American countries may not serve as good guides to future levels of car saturation in Asia.

Figure 4 shows the concept used to project the 2025 activity levels for materials production and the saturation of consumer goods. Future activity levels are based on activity levels for countries at that income today. This assumption implies that the saturation of cars per household in country A will reach the same level in 2025 as that of country B today. Because the comparisons take into account the fact that the ownership of energy-consuming goods depends both on income and prices and that the prices of goods relative to income levels are likely to decline in the future, the future growth curve for the saturation of consumer goods will then be steeper as shown in Figure 4. Government policies can either delay or speed up the acquisition of consumer goods depending on the tariffs and licensing schemes that these policies promulgate.

3 SCENARIOS

The researchers developed two scenarios, a high emissions (HE) scenario and a low emissions (LE) scenario, to explore energy demand in a world where no exogenous constraints, such as the availability of capital, restrict the growth of the economy and energy demand. In the HE scenario, the governments of the developing countries promote policies between the base year and 2025 that do not explicitly address the need to limit the potential environmental damage associated with continued energy growth. In contrast, the LE scenario examines how far carbon emissions can be reasonably lowered in a world where the consequences of the increased atmospheric concentration of carbon dioxide are accepted as a major environmental concern.

The HE and LE scenarios incorporate the same economic and population growth rates, but different economic structures, energy intensities and fuel mixes. The reductions in carbon emissions achieved in the LE scenario occur largely as a result of efficiency improvements, fuel-switching efforts and small changes in economic structure. The scenarios assume a modest increase in energy prices over the observed time period. Consistent with earlier analyses of

global energy supply and demand, international oil prices increase to \$40/barrel (bbl) by the year 2025.¹¹

3.1 DEMOGRAPHIC AND ECONOMIC ASSUMPTIONS

The population growth rates for each country are based on projections by local demographic experts. Population growth rates vary from 0.5 percent per year in Korea to over 3 percent per year in Nigeria and the GCC (Table 2). The population growth rate remains low in China, where the birth rate is mandated to one child per family. Due to the inability of the government to control population growth in China's rural areas, however, the number of children averages two per family. India's population grows more rapidly than China's and, as a result, the size of India's total population exceeds that of China by 2025. The highly urbanized environments in most Latin American countries (Brazil, in particular) have led to substantial declines in overall population growth in recent years; this trend accounts for the low growth rates assumed in the scenarios for this region.

Table 2
Population (Millions)

Country	1985	2025	AAGR
China	1045	1420	0.8%
India	766	1692	2.0%
Indonesia	165	267	1.2%
Korea	41	50	0.5%
Argentina	31	47	1.1%
Brazil	132	214	1.2%
Mexico	77 ^a	143	1.7%
Venezuela	17 ^b	34	1.7%
Ghana	13 ^a	43	2.9%
GCC Countries	16	66	3.5%
Nigeria	96	317	3.0%
Sierra Leone	4	9	2.3%

AAGR = average annual growth rate

^a 1987 data; ^b 1984 data

Most African and GCC countries historically have experienced high population growth rates. In the recent past, however, these rates have increased in the African countries and declined in the GCC countries. Growth rates in Nigeria increased from 2.5 percent between 1965 and 1980 to 3.4 percent between 1980 and 1987. Over the same period rates declined in Saudi Arabia from 4.7 percent to 4.0 percent. The scenarios assume future growth rates will be commensurate with past trends for Nigeria, Ghana, Sierra Leone and the GCC countries.

¹¹ Lashof and Tirpak, *op cit*, Ref. 7.

The economic growth rates correspond with national projections or expert judgement. Since no long-term economic scenarios were available for 2025, the growth rates were based on each country's past economic history, weighed against current expectations of the effect of future internal and international economic conditions. The scenarios for some of the countries reflect optimistic visions, and incorporate economic growth rates that are relatively high, although still within the bounds of those experienced by these countries in the past.

The GDP growth rates shown in Table 3 reflect 40 year averages for each country. In the Asian countries, the economic growth rates remain high during the 1990s and then gradually decline. In contrast, the Latin American countries experience slower rates of economic growth in the early 1990s which then increase through 2010 before stabilizing. For Argentina, the outlook is more sober; the economy grows at a moderate pace over the four decades as the economy makes the transition towards agriculture-based industry. China's growth rates are based on the government's goal of achieving an average GDP per capita of \$2000 by 2025

Table 3
GDP (1985 Billion US\$)

Country	1985	2025	AAGR
China	324	2840	5.4%
India	191	1347	4.9%
Indonesia	84	280	3.0%
Korea	93	926	5.8%
Argentina	70	156	2.0%
Brazil	249	891	3.2%
Mexico	189 ^a	1000	4.4%
Venezuela	50 ^b	248	4.0%
Ghana	5 ^a	23	4.0%
GCC Countries	163	1084	4.7%
Nigeria	75	373	4.0%
Sierra Leone	1	3	3.0%

AAGR = average annual growth rate

^a 1987 data; ^b 1984 data

In Korea, high economic growth through 2025 causes income per capita to reach \$18,000, or roughly the 1985 U.S. level. The poor economic performance which has afflicted the Latin American countries over the past two decades continues to temper future economic growth; hence, these nations witness slower increases in GDP per capita (Table 4).

In Nigeria, the GCC countries and Venezuela, oil export revenues continue to color the national economic outlook. Because a substantial share of the world's oil exports originate from these countries, increases in the price of oil lead to substantial GDP growth. However, high population growth slows the increase in GDP per capita to more moderate levels in the GCC countries and Nigeria.

Some of the scenarios consider improvements in income distribution as an important element accompanying economic growth. Income distribution improves in Brazil and Venezuela, for example, increasing the number of middle-income families and implicitly spurring higher ownership levels of home appliances and cars.

Table 4
GDP/Capita (US\$ 1985)

Country	1985	2025	AAGR
China	310	2000	4.7%
India	250	796	2.9%
Indonesia	510	1050	1.8%
Korea	2276	18400	5.2%
Argentina	2296	3294	0.9%
Brazil	1879	4163	2.2%
Mexico	2470 ^a	6980	2.7%
Venezuela	2943 ^b	7318	2.3%
Ghana	343 ^a	533	1.2%
GCC Countries	10200	16400	1.2%
Nigeria	788	1176	1.0%
Sierra Leone	247	327	0.7%

AAGR = annual average growth rate

^a 1984 data; ^b 1987 data

4 SECTORAL ASSUMPTIONS AND RESULTS

In the following section, we describe the salient characteristics of the residential, industrial, transportation, agricultural and service sectors in the developing countries. The discussion focuses on the **transitions** in the structure, unit energy consumption and fuel mix that directly influence the level of carbon emissions and highlights the end-uses and fuels that offer the greatest potential for reducing carbon emissions.

4.1 DELIVERED ENERGY AND CARBON EMISSIONS

Table 5 shows the sectoral shares in 1985 for the 17 study countries combined. These shares are heavily influenced by energy use in China and India, which together account for over 60 percent of the total demand (Figure 2).

The residential sector consumes 37 percent of the delivered energy demand, including biomass, in the study countries (Table 5). In some countries, because of the large proportion of biomass used, the residential sector uses a far higher percentage of the delivered energy (e.g., 50 percent in India, 73 percent in Nigeria and 77 percent in Sierra Leone). In Venezuela, on the other hand, the household sector accounts for only 6 percent of total energy use, almost half

of which is in the form of electricity. Biomass use releases negligible net emissions of carbon, because crop residues and dung constitute the bulk of the biomass fuel supply. The residential sector, therefore, accounts for a much larger share of delivered energy demand than of total carbon emissions; 17 percent of the emissions produced in the study countries originate from the use of fuel and electricity in this sector.

Table 5
Delivered Energy and Carbon Dioxide Emissions, 1985

	Delivered Energy (Exajoules)		CO ₂ Emissions ^a (Million Tons)	
Residential	18.1	(37%)	155	(17%)
Transport	7.0	(14%)	135	(15%)
Industry	19.8	(40%)	470	(52%)
Services	2.6	(5%)	65	(7%)
Agricultural	1.6	(3%)	40	(4%)
Other	0.1	(1%)	40	(5%)
Total	49.3	(100%)	900	(100%)

^a Counted as carbon. Emissions associated with electricity generation are included, but those related to fuel supply loss are excluded.

MT = 10⁶ Tons; EJ = 10¹⁸ Joules

The use of diesel and gasoline dominates energy use for transportation. In the 12 study countries combined, transport activities consume 15 percent of the delivered energy. Once again, the share of transport energy in total demand varies considerably among countries, ranging from a low of 5 percent in China to a high of 38 percent in the GCC countries. Carbon emissions from the transport sector accounted for 135 million tons of the total in the base year.

Industry consumes the largest share of energy and generates the greatest portion of carbon; 40 percent of the total energy used in the study countries and over half of the total carbon emissions stem from the industrial sector. While industrial activities consume only 3 percent of Sierra Leone's total energy demand, they account for 58 percent of Venezuela's energy use. The composition of the industrial fuel mix varies across the countries.

The service sector accounts for only 5 percent of delivered energy use and a correspondingly small (7 percent) share of the total carbon emissions in the study countries.

While agriculture comprises a key component of most regions' economies, it accounts for only 3 percent of energy use in the developing world and 4 percent of carbon emissions.

4.2 RESIDENTIAL

A number of factors determine the level of energy demand in the residential sector: the extent of urbanization, the access to modern fuels (e.g., electrification), the size of households and the ownership of appliances. These factors are influenced by income levels, fuel prices, appliance costs and lifestyles.

Higher levels of **urbanization** correspond with higher average levels of monetary income. The level of urbanization differs across nations with similar income levels, however, and varies according to other factors, such as migration and settlement patterns. These factors particularly come into play in the four Latin American countries considered here and the GCC countries, where more than 70 percent of the population already resides in urban areas.

By 2025, the urban population share in the Latin countries and in Korea exceeds 80 percent but remains at around 50 percent in India and China. In the latter two countries, around 1.5 billion persons live in cities in 2025, compared to 400 million in 1985. The growth of the urban population increases the demand for modern fuels and electricity.

Consistent with past trends in today's more economically advanced developing countries, **household sizes** decline alongside rising incomes. The average household in India, for example, averages 5.5 members while that in higher income South Korea averages 4.7 at present. Within each country, the sizes of rural households exceed the sizes of urban ones. Therefore, the urbanization process serves to reduce average household sizes. Each country experiences a considerable drop in both urban and rural household sizes between 1985 and 2025, although the differences in average household sizes among the various countries remain large. While Argentina has 3.4 persons per rural household in 2025, Mexico has 5.0.

Most urban areas already have high **electrification** levels; by 2025, electricity reaches close to 100 percent of all urban households. A far smaller portion of rural homes has access to electricity. In Brazil, for example, a significant fraction of rural households (which account for 20 percent of Brazil's total population) remains without electricity in 2025, because the population migrates toward smaller villages and hamlets located in internal regions where the supply of electricity proves more difficult.

4.2.1 FUELS FOR COOKING, WATER AND SPACE HEATING

Households in developing countries channel the bulk of their residential energy supply towards **cooking and water-heating** activities. In nations that rely heavily upon biomass, kerosene and LPG to carry out these end uses it is not possible to distinguish between their application for cooking and water heating. Regions with available and affordable electricity supplies tend to use electricity for water heating.

With the exception of those households located in Indonesia, India and the African countries, most urban households do not use traditional fuels (i.e., fuelwood, charcoal and dung) for cooking and heating. In India, biomass serves as the primary fuel in 42 percent of all urban households. Biomass use in rural households, however, ranges from 90 percent in Brazil and 82 percent in India to 27 percent in Korea. LPG and kerosene constitute the two main commercial fuels used in this sector. Some nations with indigenous natural gas supplies (e.g., Argentina and Venezuela) have incorporated gas into their residential fuel mixes. Higher income households in certain nations use electricity for cooking (e.g., Venezuela).

In the scenarios, the use of biomass gives way to more convenient modern fuels by 2025 (Table 6). As modern fuels grow more available and as first costs grow less prohibitive, consumers switch from biomass fuels to kerosene and LPG and occasionally to electricity.

Table 6
Biomass Share of Residential Energy for
Selected Countries (%)

	1985	2025	
		High	Low
China	64	24	24
India	87	67	61
Indonesia	56	37	32
Nigeria	92	56	50

In countries such as India, where biomass use predominates, the substitution of more efficient modern fuels for traditional energy sources lowers the growth rate of residential energy demand in 2025. As a result, the share of energy used in India's residential sector declines from 49 percent in 1985 to 23 percent in 2025 in the HE scenario and to 20 percent in the LE scenario. This increased reliance on modern fuels adds to the residential sector's carbon emissions, however; as a result, the share of emissions produced by the residential sector rises from 10 percent in 1985 to 13 percent in 2025.

Space heating absorbs much of the residential energy demand in China and Korea. Households located throughout China and rural Korea use coal for this purpose. Over the long run, Korea, which has already begun phasing coal out of its residential fuel mix, eliminates its use of coal. In China, on the other hand, biomass use gives way to coal use as the number of urban households expands. China has no ready alternative to coal at present, despite government efforts to gasify coal and to promote the use of town gas. As Korea ends its reliance on coal, the contribution of space heating to carbon emissions per unit of delivered energy declines. Further, as electricity satisfies a growing share of the nation's space-heating needs, the share of space heating in total residential energy declines to 64 percent compared to 75 percent today. Argentina uses natural gas and electricity to satisfy its much smaller household space-heating requirements.

4.2.2 ELECTRICITY FOR LIGHTING, APPLIANCES AND WATER HEATING

Lighting is the first service for which electricity is used, followed by small appliances, radios and television sets. Refrigerators tend to be the first major electricity-intensive appliance purchased by developing world households, although in some of the more "appearance-conscious" countries the saturation of irons occurs equally as fast. Electric water heaters and clothes washers come next in regions where electricity is inexpensive, followed by air conditioners in nations with hot climates.

Levels of appliance ownership vary between the urban and rural areas within each country and across the study countries. In Mexico, for example, 80 percent of the urban households have refrigerators compared to only 45 percent of the rural ones; in contrast, in China only 10 percent of the urban and a negligible fraction of the rural households own refrigerators.

The ownership of appliances increases with rising incomes. Because of the falling prices of appliances relative to average income levels, however, consumers increasingly find themselves able to acquire appliances at lower income levels than consumers in the past. For example, a low-income consumer in Caracas in 2025 has all of the same appliances owned by an average-income household in today's industrialized countries. Because of the differences in household incomes and the relatively higher first cost and availability of appliances, households in rural areas have fewer appliances than their urban counterparts. The scenarios incorporate these differences when estimating the appliance ownership levels for 2025. With the exception of air conditioners, which have saturation levels that vary depending on local climate conditions, major appliances saturate almost 100 percent of the urban households in most countries by 2025.

Available data indicate that the unit electricity consumption of appliances has declined over the years. In Korea, for example, technical improvements have reduced electricity use in new refrigerators by 74 percent since 1973. Improvements have occurred in other appliances due to the use of advanced electronics and better compressors. In the future, increases in the average size of the appliances purchased by consumers demanding more or better service offset some of these gains. The scenarios show, for example, an increase in the unit electricity consumption of refrigerators in Korea; an increase in the average refrigerator size, from 240 to 400 liters, accounts for this rise. In Venezuela, on the other hand, where the present refrigerator stock already averages about 550 liters in size, economic growth allows for more efficient devices to saturate urban households lowering unit consumption by 2025.

Overall, electricity use for appliances per urban household (excluding electricity use for water heating and cooking) increases four-fold in China, over two-fold in Korea and 75 percent in Brazil in the HE scenario. In contrast, electricity use for appliances increases by 20-30 percent in Mexico and Venezuela (Figure 5). The figures expected for 2025 reflect current levels of electricity use for appliances in industrialized countries, particularly in Europe. In the LE scenario, Brazil, Mexico and Korea achieve particularly substantial reductions in unit consumption.

Figure 5

Appliance Electricity Demand In Urban Households

0018aplu.00.1/01

4.2.3 ENERGY TRANSITIONS AND CARBON EMISSIONS

In the residential sector, fuel transitions largely influence future levels of energy consumption and carbon emissions. Two major trends characterize the type of transitions occurring in this sector: the substitution of modern fuels for biomass and the rapid increase in electricity demand. Due to the general inefficiency of biomass fuel use, the replacement of modern fuels for biomass slows the increase in total residential fuel use. The spread of electric water heaters, refrigerators and other electricity-intensive appliances leads to a much larger share of electricity use in 2025 compared to 1985 (Table 7).

Table 7
Residential Fuel Shares and Carbon Emissions
17 Study Countries

	1985	2025	
		High	Low
Carbon Emissions (MT)	155	570	470
Delivered Energy (EJ)	18.1	30.8	25.6
Coal	22%	30%	32%
Oil	7%	13%	11%
Natural Gas	1%	6%	8%
Biomass	66%	34%	31%
Electricity	4%	18%	18%

The transition to modern fuels restrains the increase in energy use but accelerates that of carbon emissions.¹² For example, in India and China, the share of biomass in the residential fuel mix shifts from 87 percent and 67 percent respectively in 1985 to 67 percent and 24 percent respectively by 2025 (Table 6). CO₂ emissions from commercial fuel use increase 265 percent in China and 304 percent in India. The transition to electricity contributes to an increase in both energy use and CO₂ emissions.

Together, these two transitions serve to increase the quantity of **carbon emissions** associated with fuel and electricity use in this sector more than three-fold, from 155 million tons in 1985 to 570 million tons in 2025 in the HE scenario. Over this same time period, delivered energy increases by only 72 percent. The LE scenario restrains total carbon emissions to 470 million tons in 2025. The LE figure represents an 18 percent reduction with respect to the HE scenario figure. The difference between the two scenarios occurs primarily as a result of the use of more efficient lighting and appliances within households and the use of less carbon-intensive fuels to generate electricity in the LE scenario. Biomass maintains a similar share in the fuel mix in both scenarios in 2025.

4.3 TRANSPORTATION

The scenarios depend critically on assumptions about mobility, motorization, vehicle modes and efficiency levels (measured in vehicle-kilometers per unit of energy). This analysis distinguishes between the energy demand for road, air, rail and ship transport, and within the passenger transport sub-sector, between energy demand for different vehicles types (e.g., cars, motorcycles, taxis and buses).

The scenarios for China and Venezuela analyze the movement of freight and passengers using ton-kilometers (ton-km) and passenger-kilometers (pass-km). The analyses for the other countries rely on the number of vehicles, distance traveled and unit fuel consumption to estimate the energy use of passenger vehicles and trucks and on value added to calculate air, rail and ship transport energy demands.

4.3.1 FREIGHT TRANSPORT

Rail, trucks, water barges and ships constitute the principal modes for freight movement. The shares of these modes vary over time and across countries. In the industrialized countries, rail traffic predominated during the early part of this century. Trucks gradually replaced railways as the major carriers of freight partially because new rail infrastructure requires much higher capital investments and partially because obtaining new right of ways proves difficult.

¹² It is possible that biomass may release other greenhouse gases, such as N₂O and methane, in much higher proportions than fossil fuels. Thus, the transition from biomass to fossil fuels may actually raise the aggregate level of greenhouse gases released into the atmosphere.

A similar modal transition from rail to truck and air travel occurs in the 17 study countries and from rail to ship travel in Indonesia and China. With the exception of China and India, rail networks in the other countries remain relatively small and account for a negligible amount of traffic (railroads dedicated to carrying minerals are an exception). Venezuela's scenarios incorporate plans for developing a major national railroad system. In water-dominated countries like Indonesia barges and ships account for a larger proportion of traffic than elsewhere, and the shares of these modes increase.

The efficiency of trucks improves, although the improvement of diesel engines remains limited to around 30-40 percent of current levels, except in those countries where efficiencies are particularly low at present. China and India cease using coal to power their railways by 2025 and rely on more efficient diesel and electric traction instead. The other minor fuel transitions occurring lead to the increased use of natural gas and biomass alcohol.

4.3.2 PASSENGER TRANSPORT

Passenger travel is measured in passenger-kilometers to account for the distance traveled and the number of passengers serviced. When data on occupancy for personal vehicles are not available, the number of vehicles and distance traveled serve as the main indicators of passenger transport.

CARS, MOTORCYCLES AND BUSES

The scenarios assume that consumers continue to demand private cars to satisfy the desire for higher mobility and that while congestion and local pollution might limit car use and efficiency, these factors do not reduce levels of car ownership.

Even at similar income levels, levels of car and motorcycle ownership in Latin American and Asian countries vary widely. In the GCC countries, the types of cars owned resemble those in the United States and travel comparable distances. At present, car saturation ranges from a low of 0.6 cars per 1000 persons in China to 87 cars per 1000 persons in Venezuela and 145 cars per 1000 persons in the GCC countries (Table 8).

In China and India, the saturation of cars reaches about 20 and 16 cars per 1000 persons respectively by 2025. This growth implies that the two countries have about 28 and 27 million cars respectively. If 80 percent of these cars remain in urban areas, Chinese and Indian cities have about 35 cars per 1000 persons by 2025. This level may be compared to Bombay, which had about 21 cars per 1000 persons in 1980. On average, the congestion level in these two cities will exceed the current level in Bombay, unless infrastructure improves significantly. Car saturation in Korea increases more than fifteen-fold between 1985 and 2025. Despite this large increase, the country remains under-motorized in 2025 relative to the saturation of cars in industrialized countries at that income level today. By 2000, the cohort of adults reaching

driving age in Brazil are exposed to motorcycles and mopeds and, therefore, may acquire these vehicle types to increase their mobility in congested cities. By 2025, the saturation of motorcycles in Brazil far surpasses today's levels.

Table 8
Cars/'000 Persons

Country	1985	2025	
		High	Low
China	0.6	20	15
India	2.1	16	16
Indonesia	5.9	45	35
Korea	11.2	210	170
Argentina	126	200	200
Brazil	63	245	245
Mexico	64 ^a	250	200
Venezuela	87 ^b	320	320
Ghana	3.8 ^a	5	5
GCC Countries	145	232	232
Nigeria	11	14	14
Sierra Leone	7.1	10	10

^a 1987 data; ^b 1984 data

Historical evidence indicates that the average distance driven by cars declines dramatically as ownership passes from very low levels (i.e., under 25 cars per 1000 persons) to higher levels of 80 to 100 cars per 1000 persons.^{13,14} Beyond that level, far smaller drops in the distances traveled occur. Thus, distance traveled declines by 2025, particularly in Asia, where saturation levels increase dramatically. In all countries, however, vehicle-miles/capita increase, because the growth in car ownership offsets the decline in distance traveled per car.

Cars and motorcycles tend to be less energy intensive in Asian than in Latin American countries. China, India and Korea have smaller car and engine sizes compared to Mexico, Venezuela and the GCC countries. Because of the large car sizes and heavy congestion in Lagos, Nigeria, gasoline consumption per car surpasses that in Asian countries two-fold. Therefore, substantial potential for savings exists. The other two African countries also have low fuel efficiencies due to the use of older vintage cars and the tendency to hold onto vehicles for long periods of time.

Fuel efficiency, expressed in km/liter, improves as a consequence of technological improvements (Table 9). Efficiency increases more rapidly alongside higher economic growth as new vehicles penetrate the marketplace at a faster rate. Intensity does not decline as much in Korea as in the other countries, since the purchase of larger, more comfortable cars offsets

¹³ Reents, *Die Entwicklung des sektoralen End-und Nutzenergiebedarfs in der Bundesrepublik*, Juelich, 1977.

¹⁴ Deutsches Institut fuer Wirtschaft (DIW), *Verkehr in Zahlen 1987* (Berlin: DIW, 1987).

efficiency improvements. India and China have achieved significant efficiency improvements in recent years due to the implementation of a government policy which permits joint ventures with foreign manufacturers of smaller, more fuel-efficient vehicles.

Table 9
Fuel Efficiency (Km/Liter)

Country	1985	2025	
		High	Low
China	10	17	20
India	11	17	20
Indonesia	10	20	25
Korea	10	13	17
Argentina	8	12	16
Brazil	7.2	13.8	20
Mexico	5.4 ^a	15	19
Venezuela	4.4 ^b	8.3	14
Ghana	4.2 ^a	5.9	8.3
GCC Countries	10.0	16.6	25.0
Nigeria	5.3	11	15
Sierra Leone	5.0	6.3	7.1

^a 1987 data; ^b 1984 data

In some countries, the low emissions scenario assumes that the implementation of taxation measures and import restriction policies and the licensing of the manufacture of vehicles can restrain levels of car ownership. Many of the scenarios additionally assume that by simultaneously mandating higher standards and bolstering fuel prices through higher taxes fuel efficiency can be improved. Improvements in mass transport, which lead to higher bus saturations, complement these actions.

4.3.3 ENERGY USE

Fuel use for transport expands more than four-fold in the 17 study countries (Table 10).

Table 10
Transportation Fuel Shares and Carbon Emissions

	1985	2025	
		High	Low
Carbon Emissions (MT)	135	660	495
Delivered Energy (EJ)	7.0	33.6	25.7
Coal	9%	0%	0%
Oil	87%	93%	90%
Natural Gas	0%	1%	3%
Biomass	3%	3%	4%
Electricity	0%	3%	4%

Note: Percentages do not always add up to 100 percent due to rounding.

The increases range from seven- to ten-fold in the Asian countries, but remain smaller in the Latin American and African countries. Rapid increases in the ownership of cars and other personal vehicles, as well as an increase in freight transport, spur the bulk of the growth of transport energy demand in the Asian countries. The other countries, which already have witnessed high motorization levels and have greater potential for reducing fuel intensity, experience smaller percentage increases in fuel use.

Freight transport accounts for about half of the fuel used in the transport sector today. Ranging from 49 percent in Indonesia to 81 percent in China, the share of freight in transport energy in the Asian countries far surpasses freight's shares in other nations. In Latin America, freight's share ranges from 32 percent in Mexico to 48 percent in Brazil. By 2025, freight's share increases from 81 to 86 percent in China. This growth adds to the overall increase in freight's share for the 17 study countries combined from 52 percent in 1985 to 58 percent in 2025 in the HE scenario. Freight's share remains unchanged in the LE case.

Increases in overall GDP influence the growth of freight transport. In Nigeria and the GCC countries, for example, the rapid increase in GDP causes freight fuel use to rise very rapidly over the next four decades. In these two regions, GDP per capita increases much more slowly over the same period due to the high population growth rates; as a result, car saturations rise far more slowly. The share of freight in transport fuel use increases from 14 percent in 1985 to 26 percent in 2025 in Nigeria's HE scenario.

The types of fuels used for transport change most dramatically in India and China, where coal use for railways disappears by 2025. By 2025, oil and a small share of electricity satisfy the transportation needs of the 17 study countries combined. Natural gas plays a role in transport in both scenarios in Argentina, China and Indonesia and in the LE scenarios for India, Venezuela, Korea and Nigeria. Biomass, which provided significant quantities (15 percent) of transport fuel in Brazil in 1985, plays a larger role in both scenarios. Other countries also begin to integrate biomass into their transport fuel mixes.

4.3.4 CARBON EMISSIONS

Transport carbon emissions increase almost five-fold in the HE scenario, rising from 135 million tons in the base year to 665 million tons by 2025. This increase represents the largest growth in CO₂ emissions from any one sector. The LE scenario reduces emissions by 25 percent relative to the HE figure by improving fuel efficiency and increasing the use of mass transport.

Curtailling carbon emissions in the transport sector will require implementing efforts aimed at reducing unit fuel consumption in gasoline engines and air transport, where the potential for achieving reductions is larger than for diesel engines. Vehicle manufacturing processes have already been internationalized and the handful of large automobile manufacturers

already produce very similar engine and emissions-control systems. In a world where the reduction of carbon emissions becomes paramount, reducing unit fuel consumption in vehicles will prove easier than achieving reductions for goods produced by a large number of small manufacturers.

4.4 INDUSTRY

The industrial sector includes the mining, manufacturing and construction sub-sectors. Industrial structure depends on the type of final demand (including exports) that industries satisfy and the type of domestic resources that industry can readily exploit. Industry's share of GDP ranges from 42 to 50 percent, except in India, Ghana and Sierra Leone where industry plays a more minor role in the economy. Manufacturing constitutes a small component of GDP in India, Indonesia, Venezuela and the African and GCC countries. In India, Ghana and Sierra Leone agriculture still dominates the overall GDP, while in Venezuela and the GCC nations mining (mainly for oil and gas) accounts for a large share of the GDP.

Energy-intensive manufacturing accounts for a small fraction (16 percent) of industrial value added. However, energy-intensive activities consume a disproportionately larger fraction (60 percent or more) of the energy used in this sector. Energy-intensive activities include the production of steel, aluminum, cement, pulp and paper and petrochemicals. The larger countries -- Brazil, China and India -- produce virtually every type of energy-intensive product. The more resource-based economies -- which include Nigeria, the GCC countries, Mexico, Venezuela and Indonesia -- produce petrochemicals and one or two other energy-intensive products. The large-scale production of aluminum, which relies heavily on electricity, dominates industrial activity in Ghana.

Projecting changes within the industrial sector over a 40-year period proves difficult, but historical trends showing increases in materials consumption per capita provide a guide to the level of industrial production that might be expected in each country by 2025. Projected trends of future consumption can be translated into likely levels of physical output and then used to provide estimates of energy use for the energy-intensive industries.

The output of material per capita varies by an order of magnitude among the study countries. For example, steel output per capita in China surpasses that in India by a factor of three at present; by 2025, China's steel output per capita exceeds India's by a factor of seven (Figure 6). Korea, Venezuela and Brazil each have 1985 output levels substantially above those of the former two countries. But of the present output of steel, about 30 percent from Korea and 40 percent from Venezuela are exported.

Fertilizers constitute an important part of the Indian government's policy of food self-reliance. This policy has led to significant increases in their manufacture of fertilizer and further increases are planned. China has also increased its production of fertilizers in recent years. Venezuela produces large quantities of petrochemicals from indigenous oil and gas

resources and of aluminum from inexpensive hydroelectricity supplies. Petrochemicals form the backbone of future industrial development in Venezuela, the GCC countries and Nigeria; in these three nations, petrochemical output increases several-fold by 2025.

Figure 6

MATERIALS OUTPUT PER CAPITA

The share of energy-intensive industries as a proportion of value added in 2025 declines in Brazil, China, India, Korea, Argentina and Mexico. In contrast, in some of the energy-rich countries -- such as Indonesia, Nigeria and the GCC countries -- the share of energy-intensive industries increases in the future. The expansion of these industries adds significantly to the industry sector's energy consumption in these nations.

Comparing energy intensity across countries proves difficult, even when relating energy use to physical output. When comparing the energy intensity of steel production in different nations, for example, two characteristics must be considered: first, that the use of scrap reduces overall energy intensity and second, that the manufacture of more complex and higher value-added products increases overall energy intensity. Considering these factors, if the Chinese industry took on the characteristics of the U.S. industry in these two respects, the overall intensity would remain about 20 percent higher in China than in the U.S. (it is about 60 percent higher at present).¹⁵ In cement production, the use of dry versus wet cement plants influences the energy intensity. Additional modifications to each process also yield some improvement.

¹⁵ M. Ross and F. Liu, "The Energy Efficiency of the Steel Industry of China," *Energy*, vol.16, no. 5, 1991, pp.833-848.

Across countries, marked differences exist in energy use per unit of steel output (Figure 7).¹⁶ In Venezuela, steel production is far more electricity intensive than in the other countries. Brazil uses large amounts of charcoal to produce steel; hence, Brazil uses noticeably less coal than the other countries. In Japan, plants use about 18 GJ to produce one ton of steel while those in the other industrialized countries use up to 22 GJ/ton. In most scenarios reported here, the intensity of steel production today surpasses the figures assumed in the HE scenario. While the LE scenario assumes additional improvements, these remain small in most countries. India, for example, has experienced little or no improvement in unit energy consumption over the past 30 years and, therefore, witnesses minimal progress in the energy intensity of steel and cement production in the future. In China, even in the HE scenario, the levels of energy intensity assumed for steel production push the limit of what is assumed to be technologically feasible today.

Figure 7

FUEL INTENSITY, STEEL INDUSTRY

4.4.1 ENERGY USE

Industrial energy demand in the study countries increases from 20 EJ in 1985 to 70 EJ in 2025 in the HE case and to 60 EJ in the LE case (Table 11). Industry's share in total delivered energy increases from 40 percent in 1985 to 46 percent in 2025 in the HE scenario,

¹⁶ Due to the heavy use of biomass (charcoal) in Brazil's steel industry, figure 7 provides separate estimates for the fuel intensity of steel production in Brazil excluding biomass and for the biomass intensity of the Brazilian steel industry. In order to calculate the total fuel intensity of steel production in Brazil, the two figures must be added together. Hence, the total fuel intensity equals 26 GJ/ton in 1985, 24 GJ/ton in 2025 HE and 13 GJ/ton in 2025 LE.

but remains virtually unchanged in the LE scenario. Energy demand almost triples in China while increasing almost seven-fold in India despite similar growth in industrial output and in industrial value added. The substantial improvement in the efficiency of energy use in China's energy-intensive industries accounts for this disparity.

Table 11
Industrial Fuel Shares and Carbon Emissions

	1985	2025	
		High	Low
Carbon Emissions (MT)	470	1680	1385
Delivered Energy (EJ)	19.8	70.1	60.4
Coal	50%	40%	38%
Oil	22%	23%	21%
Natural Gas	12%	17%	21%
Biomass	5%	4%	3%
Electricity	12%	17%	18%

The industrial fuel mix grows less carbon intensive as the share of coal declines and that of natural gas increases. Industry presently depends heavily on coal in India, China and Korea, on oil and gas in Indonesia, Mexico, Venezuela, Argentina, Nigeria and the GCC countries, on hydroelectricity in Ghana and on biomass, oil and coal in Brazil. Electricity presently forms a significant share of the energy used by industry in each country. The share of electricity increases or remains stable as the emphasis of industrial activities shifts towards the production of higher value-added products.

In the HE case, the share of coal use declines by 2025, except in Indonesia and Nigeria, where the production of energy-intensive goods increases sharply. Coal use declines sharply in Korea's low emissions scenario, because Korea imports all of its the fuels and economic planners have tried to maintain a diversified mix of imported fuels. Indonesia limits the extent of its industrial coal use in the LE scenario by channeling a larger share of its abundant natural gas resources into the industrial fuel mix. In India and China, the fuel mix does not differ significantly in the HE and LE scenarios due to the limited potential for substituting less carbon-intensive fuels for coal. In both of these countries, the LE scenarios integrate larger quantities of natural gas into the industrial fuel mix in 2025 than do the HE scenarios.

4.4.2 CARBON EMISSIONS

By 2025, industry continues to make an overwhelming contribution to total carbon emissions. Carbon emissions increase three-fold between 1985 and 2025, rising from 470 to 1680 million tons in the HE scenario. The LE scenario reduces emissions by 296 million tons (or 18 percent) relative to the HE scenario.

Many opportunities exist for reducing carbon emissions in this sector, particularly in countries where fuels have been subsidized or where the optimal fuel choices have not been

incorporated into various industrial processes. For example, Venezuela heavily subsidizes the use of electricity in aluminum production at present and, in the mid-1980s, Brazil promoted the inefficient practice of using electricity in boilers. Countries can improve their unit energy consumption by implementing traditional energy-conservation measures and also by better utilizing their production capacity. For example, the Indian steel industry could decrease its unit energy consumption by 12 percent by increasing capacity utilization by 10 percent.¹⁷ Reducing emissions through fuel-switching measures proves difficult in countries which have limited energy sources, but should be easier to achieve in the energy-rich countries.

4.5 SERVICES

Little is known about the detailed structure of the service sector in developing nations. Offices, schools, hospitals, restaurants and hotels absorb most of this sector's energy.

Value added denotes activity levels in this sector. This figure is multiplied by the intensity of fuel use to obtain the fuel use for this sector.

Electricity and oil constitute the two major sources of energy in the service sector, except in China, where coal use dominates. Because of the high energy demand of China's service sector, mostly a result of its heavy space-heating requirements, coal supplied over half of the 1985 energy used in this sector for the 17 study countries combined (Table 12).

Table 12
Service Sector, Fuel Shares and Carbon Emissions

	1985	2025	
		High	Low
Carbon Emissions (MT)	65	285	240
Delivered Energy (EJ)	2.6	10.6	9.5
Coal	54%	44%	45%
Oil	23%	20%	19%
Natural Gas	4%	7%	9%
Biomass	1%	1%	1%
Electricity	18%	28%	26%

The service sector currently accounts for only 10 percent of the total electricity consumed in the study countries. Over the next four decades, however, as lighting and cooling levels increase and more stores, offices and other electricity-intensive buildings are erected, the use of electricity in the service sector increases faster than in any other sector. Oil consumption currently surpasses electricity use in the service sectors of Mexico and Argentina, where LPG fuels a large share of the cooking and water-heating activities in the nations' restaurants, hotels, hospitals, etc. The availability of piped natural gas in Argentina also influences its application

¹⁷ R.K. Pachauri, V. Suri and S. Gupta, *Long-Term Energy Scenarios for India Using the Stair Model*, (New Delhi, India: Tata Energy Research Institute, 1990).

in the service sector. In Korea, where the climate entails the heavy use of space heating, oil comprises almost 60 percent of the services' fuel mix. Electricity dominates the services' fuel mix in most of the other countries.

Between 1985 and 2025, services' energy use increases almost four-fold; the sector's share of total energy use increases from 5 percent in 1985 to 7 percent by 2025 in both scenarios (Table 13). Natural gas and electricity increasingly penetrate the services' fuel mix by 2025. Notably, electricity's share rises to 28 percent in the HE scenario and to 26 percent in the LE scenario. As a result, the fuel mix grows less coal intensive. This growth serves to increase services' **carbon emissions** four-fold (from 65 to 285 million tons) between 1985 and 2025 in the HE scenario. The LE scenario contains emissions to 240 million tons. The opportunities for improving the efficiency of lighting and space conditioning, the two major end-uses in the service sector, resemble those for the residential sector.

4.6 AGRICULTURE

Agriculture's share of GDP has decreased with industrialization and, except for in Argentina, this trend continues in each study country. Agriculture uses most of its energy to power irrigation pumping and on-farm equipment. Irrigation pumping accounts for most of the electricity used in this sector, while fossil fuel use is divided somewhat evenly between pumping and the operation of other machinery. In India and China, the use of irrigation has increased over the years due to the limited availability of land; in order to maintain high levels of food production, these two nations have been forced to use the available land more intensively.

Agriculture consumes 20 percent of the electricity used in India today. India highly subsidizes electricity prices for agriculture and, as a result, its use has increased more rapidly in the agriculture activities than in any other sector. In both scenarios, as the availability of irrigable land grows increasingly limited due to the scarcity of water, the growth rate of electricity declines.

Agricultural energy demand more than doubles by 2025; its 3 percent share of total energy use rises to 4 percent in both scenarios. The fuel mix grows less oil intensive and more natural gas and electricity intensive. The **carbon emissions** associated with agriculture rise from 40 million tons to 145 million tons in 2025 in the HE scenario. The LE scenario lowers the level of agricultural carbon emissions by 19 percent of the HE figure, to 120 million tons. Because most nations' agricultural sectors highly subsidize energy costs and use energy quite inefficiently, great potential exists for improving the energy efficiency of agricultural activities.

4.7 AGGREGATE DELIVERED ENERGY DEMAND

The total delivered energy demand for the 17 study countries increases from 49 to 152 EJ by 2025 in the HE scenario (Table 13). The LE scenario reduces this total to 127 EJ.

Table 13
Aggregate Fuel Shares and Carbon Emissions

	1985	2025	
		High	Low
Carbon Emissions (MT)	905	3635	2885
Residential	17%	16%	16%
Transport	15%	18%	17%
Industry	52%	46%	48%
Services	7%	8%	8%
Agriculture	4%	4%	4%
Other	5%	8%	7%
Delivered Energy (EJ)	49.2	151.5	126.5
Residential	37%	20%	20%
Industry	40%	46%	48%
Transport	14%	22%	20%
Services	5%	7%	8%
Agriculture	3%	4%	4%
Delivered Energy by Fuel Type			
Coal	33%	28%	29%
Oil	27%	38%	34%
Natural Gas	5%	10%	13%
Biomass	27%	10%	9%
Electricity	8%	15%	16%

Note: Carbon emissions include those from fuels used to generate electricity and from fuel supply losses.

On a per capita basis, the average delivered energy in 2025 equals only a fraction of that enjoyed in the United States today (333 GJ) (Table 14). Delivered energy/capita increases between 1985 and 2025 in both scenarios. In Sierra Leone and Nigeria, the only two exceptions, the massive substitution of modern fuels for biomass leads to a decline in energy use per capita, although carbon emissions per capita increase. Even in those nations where the economy grows most rapidly, energy consumption per capita remains at relatively low levels.

Electricity use increases almost six-fold, representing the largest increase for any type of energy aside from natural gas. Electricity's share in total energy demand increases from 8 to 15 percent in the HE scenario and to 16 percent in the LE scenario.

Electricity consumption per capita varies considerably among these countries (Table 14). Even at similar income levels, China's consumption per capita surpasses that of India. The four Latin American countries, Korea and the GCC nations historically have experienced higher levels of electricity consumption per capita than the other study countries. In the HE scenario, China's electricity consumption per capita reaches about the same level as Brazil's. By 2025, Korea's GDP per capita equals that in the United States today, but electricity consumption per capita remains 36 percent lower. On the other hand, at a lower GDP per capita, Venezuela's generation per capita in 2025 exceeds that of Korea in the LE scenario. In the GCC countries, due to the ubiquitous use of air conditioning and other household appliances, electricity consumption per capita in 2025 exceeds that of the United States today.

Table 14
Delivered Energy and Electricity Per Capita

	Energy/capita (GJ)			Electricity/capita (kWh)		
	1985	2025		1985	2025	
		High	Low		High	Low
China	23	42	37	370	1750	1620
India	9	18	15	160	610	550
Indonesia	10	27	23	150	420	390
Korea	48	153	120	1240	7555	6626
Argentina	36	47	39	1190	2090	1630
Brazil	32	50	31	1300	2780	1620
Mexico	47 ^a	68	54	1075 ^a	2325	2000
Venezuela	69 ^b	126	115	2570 ^b	7340	7310
Ghana	14 ^a	14	11	260 ^a	700	580
GCC Countries	136	233	196	7400	14400	12200
Nigeria	14	10	8	70	290	260
Sierra Leone	15	13	11	40	150	120
Average	20	35	29	440	1470	128

^a 1987 data; ^b 1984 data

5 ELECTRICITY GENERATION

We estimate the level of electricity generation in order to calculate the primary energy demand and carbon emissions for the two scenarios. We also calculate the shares of the various generating technologies in electricity production and, for selected countries, the capital requirements associated with these technologies.

Carbon emissions from the fuels used to generate electricity account for about 190 million tons, or 21 percent, of the total emissions in the 17 study countries.¹⁸ Only the carbon emissions generated by fuel use in the industrial sector surpass the magnitude of these emissions.

Compared to industrialized nations, developing nations generate and distribute electricity highly inefficiently. The thermal efficiency of electricity generation ranges from 24 percent in Venezuela to 29 percent in India to 34 percent in Korea. In each country, significant improvements in efficiency occur between 1985 and 2025, raising efficiency levels to those observed in the industrialized world today. The improvements occur with the introduction of more efficient power plants, improved institutional structures and better plant management.

Transmission and distribution losses, which reflect technical losses as well as theft and the electricity consumed during plant use, vary across the countries. Korea and Venezuela

¹⁸ We count all primary inputs to electricity (whether electricity is supplied by fossil fuel, nuclear power, hydro or some other form) at the same thermal efficiency (the inverse of the heat rate).

average relatively low losses, while those in Mexico, Brazil and India reach 15, 11 and 22 percent respectively. With the improved management of electric-utility systems and better technical control, both scenarios significantly reduce these losses by 2025.

The generation of electricity increases almost six-fold from 1200 TWh in 1985 to 7200 TWh in the HE scenario in 2025 and to 6240 TWh in the LE scenario. Electricity generation relies heavily on coal, particularly in the Asian study countries. This dependence increases by 2025 as nations try to phase oil out of the generation mix and exhaust other options (Table 15).

Table 15
Electricity Generation, Fuel Shares and Carbon Emissions

	1985	2025	
		High	Low
Carbon Emissions (MT)	190	1030	790
Electricity Generation (TWh)	1205	7240	6275
Fuel Use for Generation(EJ)	14.8	72.9	62.1
Coal	32%	43%	39%
Oil	21%	12%	11%
Natural Gas	8%	11%	8%
Biomass	0%	0%	1%
Nuclear and Geothermal	3%	7%	8%
Hydro & Other	36%	27%	33%

Note: Non-fossil electricity generation is counted in terms of fossil fuel equivalent.

China, exploits its nuclear, hydro and natural gas options to levels approaching their resource limits by 2025. As a result, electricity generation beyond 2025 may have to rely more heavily on coal, unless China discovers new resources and/or can find an economical way of using renewable resources. Hydro has great potential in the Latin American study countries, although these countries will have to develop more expensive sites. The LE scenario calls for a larger share of hydro generation by 2025. Mexico's scenarios consider the development of new medium-sized hydro projects, based on the recent trends in construction. In Brazil, on the other hand, the construction of large hydro plants slows down considerably (due to capital constraints and environmental concerns); natural gas serves as the principal supply source for the additional capacity required in the HE scenario.

Carbon emissions from the fuels used to generate electricity register the largest increase of all the sectors. Emissions increase more than five-fold, from 190 to 1030 million tons, in the HE scenario. The LE scenario reduces emissions by 24 percent, to 790 million tons. Much of the reduction occurs because of reduced demand for electricity in the LE scenario. Fuel switching plays a smaller role; efforts to change the electricity fuel mix are thwarted because of the lack of alternative energy sources in many of the study countries. Brazil achieves large reductions in the LE case, which help to restrict the role of non-hydro power generation to 10 percent of the nation's total electricity demand.

Capital costs for power plants vary considerably across the developing countries. Generally, China has much lower plant costs (56 percent of those in India for coal plants), largely because of the artificially low labor costs and the domestic manufacture of most components. Total capital costs as a fraction of GDP do not change significantly over the 40-year period, although they witness a large increase in absolute terms. These future estimates represent a reversal of present trends; in the recent past, capital costs have come to comprise an increasing share of GDP. In part, this difference results from the considerable improvement in plant efficiencies and the lower transmission and distribution losses achieved by 2025. In some nations, the construction of less capital-intensive fossil plants, with higher capacity factors compared to hydro plants, contributes to the drop in the capital cost/GDP ratio.

6 ENERGY INTENSITIES AND ENERGY SUPPLY

As described above in the sectoral discussion, the industrial structure, the efficiency of industrial fuel use, the level of household demand and the vehicles used for transport all influence the energy/GDP ratio. The future ratio depends on changes in these factors.

Energy consumption grows more slowly than GDP in each country between 1985 and 2025, except in Indonesia and the African and GCC countries; as a result, the primary energy/GDP ratio declines by 2025 (Figure 8).¹⁹ In China and Korea, this decline continues an earlier trend which began in the 1980s. For the other countries, the decline calls for a reversal of the trend of the last 10 years. Such a reversal has been observed historically in the industrialized countries.

Historically, in industrialized nations the primary energy/GDP ratio has risen over time and then eventually dropped. The energy/GDP ratio for the United States peaked in the 1920s; those for Italy and Japan peaked in the early 1970s; while West Germany's peaked in the early 1960s. Thus, it is not impossible to assume that the developing countries will experience a similar pattern and achieve lower energy-intensity values in the future.

The declining ratio in China and India results largely from the replacement of inefficient biomass with modern fuels. But even excluding biomass use, the energy/GDP ratio for China declines dramatically from 1.66 to 0.75 tons of oil equivalent/million dollars, or by about 45 percent of the 1985 figure. Although the decline appears large, the energy/GDP elasticity of 0.37 corresponds with the elasticity of 0.5 achieved in the 1980s. Further, the rapid growth of GDP leads to a substantial turnover in plants and equipment. Hence, China's 2025 industrial infrastructure will be of 2012 vintage and, therefore, highly efficient.

India experiences a rather modest improvement in efficiency and the nation's energy/GDP ratio (including biomass) declines to only 67 percent of the value in 1985 in the HE scenario.

¹⁹ Figure 8 provides the primary energy/GDP ratios as estimated in the HE scenario. Due to differing exchange rates, etc., energy/GDP ratios cannot be compared among the study countries; rather figure 8 shows how the ratio changes over time in each country.

In the LE scenario, the ratio declines to 53 percent. Without the inclusion of biomass, the ratio declines only slightly in the high emissions case to 94 percent of the 1985 figure (Figure 8).

Figure 8

In Indonesia both scenarios show energy-intensive industries accounting for a higher proportion of industrial value added in 2025. This transition differs from those observed in most of the other countries.

In all of the African countries, the expected development of more energy-intensive industries leads to an increase in this ratio. In Sierra Leone and Ghana, the historical trend of higher energy growth than GDP growth continues as previously high levels of suppressed demand, particularly in the household sector, begin to be met.

The primary energy supply in the 17 study countries combined increases almost four-fold in the HE scenario and three-fold in the LE scenario. The difference between the two totals indicates a significant potential for reducing energy use by 2025 (Table 16). In both scenarios, however, the share of coal increases relative to that in 1985 as China substitutes coal for biomass in its residential sector and as electricity generation relies more heavily on coal. The shares of other fuels increase by 2025 as well in order to compensate for the decreased reliance on biomass.

Despite the reductions in the energy/GDP ratio, China and India will find themselves hard-pressed for domestic resources of sufficient magnitude to satisfy their growing energy needs. In the HE scenario, China will have to mine as much as 3.1 billion tons of coal

compared to about 900 million tons in 1985. This amount of coal equals about the amount annually mined in the entire world in the late 1980s. India will have to produce about 850 million tons of coal compared to about 150 million tons in 1985. Judging from the current local environmental problems with coal mining and use, this increase will require substantial investments in coal clean-up technologies. For example, the concentration of suspended particulates in major Chinese cities already surpasses the guidelines set by the World Health Organization several-fold.²⁰ Further, given the deteriorating quality of coal in both countries, the amount of coal mined and transported may be even higher than these estimates suggest.

Table 16
Primary Energy and Fuel Shares

	1985	2025	
		High	Low
Primary Energy Supply (EJ)	62	217	177
Coal	34%	38%	36%
Oil	29%	33%	31%
Natural Gas	6%	11%	13%
Biomass	22%	7%	6%
Nuclear and Geothermal	1%	2%	3%
Hydro & Other	9%	9%	11%

Total oil demand in the 17 study countries increases from 8.3 million barrels per day (mbpd) in the base year to over 33 mbpd by 2025 in the HE scenario. Oil demand in 2025 ranges from between 6 and 8 mbpd in China, India and the GCC countries to about 4 mbpd in Mexico and around 2 mbpd in Indonesia, Korea and Brazil. This increase in total oil demand is large enough to exhaust the known OPEC excess production capacity, thereby placing an enormous pressure on the world oil supply. By 2025, China imports about 1.8 mbpd of oil and produces about 2.5 mbpd of synthetic oil from coal. Domestic production declines to 0.6 mbpd from around 2.0 mbpd today. Oil consumption in India reaches about 6.2 mbpd by 2025, up from about 0.8 mbpd in 1985. Domestic production amounts to about 0.6 mbpd today. In July 1990, with oil prices at only \$15/barrel, the Indian government had to adopt regulations to curb the use of oil, since insufficient foreign exchange existed to pay for oil imports. The estimated level of oil imports for 2025 would require \$82 billion (assuming that oil production in India stays at the 1985 level) compared to \$1.5 billion today, because the price of oil is assumed to be 2.5 times higher and the increased oil demand must be met by imports; this level would require far more foreign exchange than India currently generates. In most countries, the use of oil and coal increases in the HE scenarios, while that of natural gas and hydro increases in the LE scenarios in order to reduce carbon dioxide emissions.

The hydro capacity increases ten-fold in Venezuela and exhausts all the known hydro-reserves in the country today.²¹ In China, hydro-capacity approaches 225 GW by 2025,

²⁰ H. Wang and D. Zhau, *Air Pollution Control and Energy Use in China*, published in the Proceedings of the Chinese-American Symposium on Energy Markets and the Future of Energy Demand, Nanjing, China, November 1988.

²¹ Hydro capacity has already increased by a factor of four between 1985 and 1990.

which would exhaust the hydro-sites close to the population centers. Increases of such magnitude, although technically feasible, will create other concerns and may not be achievable given the current ecological dilemmas.

This paper only comments on the capital costs for electric power. A parallel analysis using the same methodology, equal population growth rates, but lower economic growth rates was conducted recently. This study estimated the capital costs for the energy sector for nine world regions. It concluded that there was a high probability that the expansion of the energy sector will be severely inhibited by capital scarcity, sharply slowing economic development.²² Given the higher economic and energy growth rates in the scenarios, the same conclusion applies.

7 CARBON DIOXIDE EMISSIONS

Total carbon emissions increase from 900 million tons in the base year to 3.6 billion tons in 2025 in the high emissions scenario for the 17 study countries (Tables 13 and 17). The low emissions scenario reduces emissions by 21 percent (to 2.9 billion tons). In effect, the increase in carbon emissions between 1985 and 2025 observed in the HE scenario equals about twice the amount produced by the United States in 1985. In the LE scenario, the growth in emissions between 1985 and 2025 equals slightly more than the amount produced in the United States in 1985.

Table 17
Carbon Emissions by Country
(Million Tons of Carbon)

	1985	2025	
		High	Low
China	480	1700	1365
India	115	700	615
Mexico	75 ^a	225	155
GCC Countries	60	400	330
Brazil	45	140	65
Korea	45	170	120
Indonesia	25	130	105
Venezuela	25 ^b	65	55
Argentina	20	45	30
Nigeria	10	55	40
Ghana	1 ^a	4	3
Sierra Leone	--	1	1
Total	900	3635	2880

^a 1987 data; ^b 1984 data

²² M. Levine, A. Gadgil, S. Meyers, J. Sathaye, J. Stafurik and T. Willbanks, *Energy Efficiency, Developing Nations, and Eastern Europe*, report to the U.S. Working Group on Global Energy Efficiency (Washington, D.C.: International Institute for Energy Conservation, June 1991).

The contribution of each end-use sector to carbon emissions changes little over this time period (Table 13). Carbon emissions from industry do not grow as fast as total emissions, which reduces industry's share of emissions. Despite the reduced share of biomass in the residential sector, its share of carbon emissions remains virtually unchanged. The opportunities for further reduction in carbon emissions from the HE to the LE scenario are more pronounced in the transport sector and less so in the industrial sector, which increases industry's share of carbon emissions in the LE scenario in 2025.

The aggregate fuel mix grows more carbon intensive between 1985 and 2025 as the share of biomass drops. Had the 1985 fuel mix prevailed in the HE scenario, the total carbon emissions generated by the 17 study countries combined in 2025 would equal 3.2 billion tons, 14 percent lower than the HE figure for 2025. In nine of the 17 study countries the fuel mix grows more carbon intensive. The exceptions, Korea, Venezuela and the GCC countries, occur primarily because of the reduced share of coal and the increased share of nuclear energy in Korea, the greater share of hydro in Venezuela and the larger share of natural gas in the GCC countries in 2025.

Most of the reductions in carbon emissions achieved in the LE scenario occur as a result of improvements in energy efficiency; fuel switching only plays a minor role. The LE scenario figure for carbon emissions in 2025 equals 78 percent of the HE scenario figure. Had the mix of fuels in the LE scenario remained the same as in the HE scenario in 2025, the LE carbon emissions would be 3 percent higher. In effect, more than 80 percent of the reductions in the LE scenario occur because of efficiency improvements and the rest result from fuel switching. In Venezuela, the sole exception, carbon reductions from fuel switching surpass those from efficiency improvements; 13 percent of the reductions in Venezuela result from fuel switching, while only 7 percent stem from efficiency improvements.

In absolute terms, China and India rank as the largest emitters of carbon dioxide. By 2025, while the emissions from China increase more than three-fold in the HE scenario, those from India increase six-fold because of fewer improvements in energy intensity. The significant use of biomass for industry and transport in Brazil contributes to the nation's relatively low emissions.²³ Because of efficiency improvements and because it has the option to rely almost completely on hydro-generation, Brazil's emissions decline by 50 percent of the HE figure in the LE scenario.

India, China and Korea, three countries which rely heavily on coal, also produce the most carbon dioxide per unit of energy supplied. Brazil, Venezuela and Mexico generate correspondingly less carbon dioxide. The amount of carbon emitted per unit of energy increases by 14 percent of the 1985 level in the HE scenario. In the LE scenario the CO₂/primary energy ratio drops slightly below the 1985 figure as a result of fuel switching.

²³ If the emissions from biomass use are counted, total Brazilian emissions almost double, from 45 to 80 million tons, in 1985. The same proportion prevails in 2025.

The rate of population growth largely determines increases in carbon emissions and, therefore, emissions per capita increase much more slowly in each country than total emissions (Table 18). However, given the substantial differences in population growth rates, the increase in emissions per capita can be misleading. For example, emissions per capita almost triple in both China and India, despite the fact that the increase in total emissions for India is double that of China.

Table 18
Carbon Emissions per Capita (Tons)

	1985	2025	
		High	Low
China	0.46	1.12	0.96
India	0.15	0.41	0.36
Indonesia	0.15	0.49	0.39
Korea	1.10	3.38	2.39
Argentina	0.65	0.95	0.63
Brazil	0.34	0.65	0.30
Mexico	0.98 ^a	1.57	1.08
Venezuela	1.47 ^b	1.91	1.62
Ghana	0.07 ^a	0.09	0.07
GCC Countries	3.68	6.05	4.99
Nigeria	0.10	0.17	0.13
Sierra Leone	---	0.11	0.11

^a 1987 data; ^b 1984 data

Table 19
CO₂ Emissions per Unit of GDP

	Using Exchange Rates			Using Purchasing Power Parities (PPP)		
	(Kgs/US\$ 1985)			(Kgs/US\$ 1985 PPP)		
	1985	2025		1985	2025	
		High	Low		High	Low
China	1.51	0.61	0.49	0.27	0.11	0.09
India	0.61	0.53	0.46	0.21	0.19	0.16
Indonesia	0.30	0.47	0.38	0.13	0.19	0.15
Korea	0.49	0.19	0.13	0.35	0.13	0.09
Argentina	0.29	0.29	0.20	0.17	0.17	0.12
Brazil	0.18	0.16	0.07	0.09	0.08	0.04
Mexico	0.40 ^a	0.23	0.16	0.27 ^a	0.16	0.11
Venezuela	0.51 ^b	0.27	0.23	0.44 ^b	0.23	0.20
Ghana	0.14	0.20	0.12	0.22	0.19	0.14
GCC Countries ^c	0.37	0.37	0.31	0.11	0.11	0.09
Nigeria	0.14	0.15	0.11	0.09	0.11	0.08
Sierra Leone	0.38	0.44	0.35	0.26	0.33	0.26

^a 1987 data; ^b 1984 data; ^c Estimates of purchasing power parities exclude Qatar for this region.

Note: 1985 ppp values were used for 2025 as well.

A comparison of carbon emissions per unit of GDP reveals that this ratio is highest for China (Table 19) than for any other study country. The sector-specific analysis of fuel use and efficiency described above explains the many reasons for the levels of carbon intensity displayed in Table 19. However, the use of PPP to estimate the carbon intensity reveals that China does not have the highest intensity, and that Venezuela and Korea have higher intensities than the other study countries. In effect, because of the structure of their economies, the types of fuels they use and the efficiency of their fuel use, the latter two countries emit more carbon to achieve the same level of purchasing power. These ratios and the corresponding rankings change in the future. By 2025 Venezuela and Sierra Leone display the highest intensities.

8 INTEGRATED ANALYSIS

This section compares the results of this study with those of an analysis using the Atmospheric Stabilization Framework model to check the accuracy of the fuel supply estimates for 2025. The ASF model incorporated the data on delivered energy demand from this study and data from similar studies on the industrialized and other countries to create an integrated picture of world energy demand in 2025.²⁴ The model then attempted to satisfy this estimated demand, taking into account the availability of energy supplies at stipulated energy prices. While the ASF model initially incorporated the same assumptions about fuel prices as did the individual country studies, it then adjusted prices according to its own supply curves. The ASF model then came up with new estimates for energy supply in 2025 as a result of placing the individual country studies in a global context.

Overall, the estimates of primary energy demand and supply for the 17 developing countries described here do not differ substantially between the country studies and the ASF runs, but the composition of the energy mix shifts. According to the ASF analysis, primary demand is 6 percent lower than the level indicated in the country studies. In terms of the fuel mix, coal production was higher and the conversion of coal to synthetic fuels played a much larger role in the ASF runs. The production of natural gas and the consumption of gaseous fuels fell below the levels estimated in the country studies, but energy from biofuels increased more rapidly in the ASF runs.

The differences in the mix of fuels stem from some simplifying assumptions about natural gas prices made by the ASF model and from the model's more optimistic assumptions about the availability and use of biomass. The ASF model assumes that natural gas prices track those of oil and that uniform changes in natural gas prices occur in each sector. In reality, neither holds true. The prices of natural gas and other fuels are administered by governments and selectively set for each end-use. The higher production levels of synthetic coal and biomass fuels (in liquid and gaseous forms) result from these higher gas prices as well as from differences in the underlying assumptions about the use of biomass.

²⁴ United States/Japan Expert Group, *Integrated Analysis of Country Case Studies*, report to the Energy and Industry Sub-group of the Intergovernmental Panel on Climate Change, September 1990.

Global carbon dioxide emissions, including those for the industrialized countries, amount to 12.4 billion tons in the country study base case. At 12.8 billion tons, this estimate is somewhat higher in the ASF scenarios due to the increased use of synthetic fuels.

9 CONCLUSIONS

The results of the scenario analyses indicate that the overall expansion of energy demand and the increasingly carbon-intensive composition of the energy mix (a result of resource constraints and the transition from biomass to modern fuels) will lead to a substantial growth in carbon emissions from developing countries between 1985 and 2025. Despite impressive declines in the intensity of energy use in most of the nations, carbon emissions in the study countries increase by 2.7 billion tons between 1985 and 2025 in the HE scenario. The LE scenario moderates this growth by improving the efficiency of energy use for most production processes and appliances in the developing world in 2025 to levels equivalent to those found in the industrialized world today. Nonetheless, carbon emissions still rise by 2 billion tons relative to the 1985 level.

Although overall emissions of CO₂ witness a dramatic increase, the growth of emissions on a per capita basis remains quite modest. Relative to industrialized countries, emissions per capita in the study countries remain at very low levels in 2025. For example, based on the growth rates of population and CO₂ assumed in these scenarios, carbon emissions per capita in India will not reach 1985 levels of emissions per capita in the United States until the year 2100. The high growth in total emissions coupled with the continuing low levels of emissions per capita in 2025 highlights a key controversy surrounding the role of developing countries in future efforts to arrest global climate change. On one hand, the growing contribution of developing countries to global emissions over the 40-year period suggests that developing countries must participate in international efforts to restrain emissions; curtailing the growth of emissions exclusively in industrialized countries will not be sufficient to avert the threats of global warming. On the other hand, any consideration of equity based on population sizes in the developing world implies that developing countries should be exempted from worldwide efforts to restrain the growth of energy and carbon emissions.

The analysis shows a wide variance in levels of emissions per capita and emissions per unit of GDP among the study countries. For example, carbon emissions per capita are significantly higher in the GCC countries than in any of the other study countries. Similar disparities prevail in emissions per unit of GDP (although the rankings change when GDP is estimated using purchasing power parity rates rather than exchange rates). These differences suggest that in order to assess the role of developing nations in future emissions-abatement activities, the developing world should not be lumped together as a single bloc of countries; rather each country must be evaluated according to its own unique circumstances.

Improvements in energy efficiency and fuel-switching measures serve as the two major avenues for controlling emissions of carbon dioxide in the country studies. Of the 23 percent

reduction in carbon emissions achieved in the LE scenario relative to the HE scenario, 19 percent results from efficiency improvements while only 4 percent results from fuel switching. Efficiency improvements prove the more effective of the two means, largely because by 2025 most of the study countries (except Venezuela and the GCC countries) have few indigenous fuel alternatives available and, therefore, have little flexibility in terms of changing the composition of their fuel mixes.

Hence, the scenarios indicate that the combination of higher energy efficiency and modest fuel switching can slow the growth of energy use and emissions in the developing world. However, achieving the potential gains associated with improved energy efficiency and fuel switching will entail a concerted effort on the part of consumers, manufacturers, energy-supply companies and governments. In addition, these improvements will not reverse the trend towards increased energy demand in these nations. Raising levels of economic growth will continue to entail increasingly higher levels of energy use across the developing world through 2025 and beyond.

Coal and oil shortages and constraints on the capital available for energy supply could lead to slower rates of economic growth than assumed in the scenarios. In China and India, where non-coal energy resources are limited, the scenarios show an unprecedented level of coal mining and oil imports. If these nations fail to raise energy efficiency to the targets set in the scenarios, even higher levels of coal production will be required. In both cases, socio-economic and local environmental constraints may block efforts to increase coal production.

In both scenarios, the industrial sector makes the largest contribution to total carbon emissions, followed by the transport and residential sectors. Emissions from the transport sector rise more rapidly than from any other sector. In absolute terms, the greatest opportunities for lowering emissions of carbon dioxide lie in the industrial sector; industry accounts for just under 40 percent of the reduction in emissions achieved in the LE scenario. The transport sector displays the largest relative potential for containing emissions (the aggregate LE scenario for the study countries reduces transport emissions by 25 percent relative to the HE scenario). However, the most promising sectors for reducing intensity and/or for switching fuels vary across the countries. In each country, the extent of the reductions possible within each sector is determined by the growth that the sector experiences and the potential for reducing fuel use in that sector, which in turn depends on the cost of supplying fuels to and the cost of conserving fuels in that end-use sector.

The shares of the industrial and transport sectors in total fuel use increase between 1985 and 2025. Simultaneously, the share of the residential sector declines. The drop in biomass consumption accounts for the falling share of the residential sector. As incomes increase, consumers shift to the use of more convenient and efficient fuels, such as kerosene and LPG, and eventually to electricity.

The trend towards increased use of coal and other fossil sources for generating electricity leads to higher carbon emissions per unit of electricity generated in both scenarios. The LE

scenario relies less heavily on coal and other fossil fuels than the HE scenario due to the greater exploitation of hydroelectric and nuclear sources. The use of biomass in electricity generation could offer an effective means for reducing carbon emissions from electricity generation in many developing nations; this potential strategy needs to be investigated more thoroughly.

Electricity takes on a far more important role in all of the countries studied over the next four decades. For this reason, the composition of the electricity fuel mix and the efficiency of electricity generation will have a major impact on future levels of energy-related carbon emissions. Most of the countries have plans to increase the use of carbon-based fuels for generation in the future; of particular concern, many of the countries hope to expand the production of coal-generated electricity. Both international lending institutions and electric power companies in developing countries have shown a growing interest in improving the efficiency of electricity generation and use in recent years. And in a number of countries, capital scarcity and growing concerns about local environmental issues have led to the re-evaluation of electricity-generation schemes. Efforts to better manage the growing demand for electricity through improving the efficiency of electricity supply and use can make a major contribution to restraining the growth of carbon emissions in the future.

The extent to which developing nations will be able to curtail the growth of energy demand and, correspondingly, emissions of carbon dioxide in the future will hinge on a number of crucial determinants ranging from the availability of natural resources and capital to the development and implementation of effective policy measures. Maximizing the potential for abating CO₂ emissions will entail a combination of both domestic efforts and international assistance. While this paper points out many common trends within this group of developing countries, it also highlights the wide variance in the economic, demographic and other energy-related factors among countries. The ability to optimize the opportunities for restraining the growth of CO₂ in these nations lies in recognizing and defining these differences. A thorough understanding of each nation's past, present and future patterns of energy use is the first step towards identifying the most effective path to a less carbon-intensive energy future.

END

**DATE
FILMED**

4 / 27 / 92