DR. 733

ENERGY

CONSERVATION

BNL 51067-

SURVEY OF AVAILABLE TECHNOLOGY FOR THE IMPROVEMENT OF GAS-FIRED RESIDENTIAL HEATING EQUIPMENT

MASTER

FINAL REPORT

August 1979

Prepared by
A. A. PUTNAM, S. G. TALBERT,
R. D. VERGARA, AND A. LEVY

of

BATTELLE, COLUMBUS LABORATORIES
505 KING AVENUE
COLUMBUS, OHIO 43201

and

D. W. DeWERTH AND T. R. NORRIS

of

AMERICAN GAS ASSOCIATION LABORATORIES
8501 EAST PLEASANT VALLEY ROAD
CLEVELAND, OHIO 44131

for

BROOKHAVEN NATIONAL LABORATORY
ASSOCIATED UNIVERSITIES, INC.
UPTON, NEW YORK 11973

UNDER CONTRACT NO. EY-76-C-02-0016 WITH THE

U. S. DEPARTMENT OF ENERGY

Division of Buildings and Community Systems

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

BNL 51067
UC-95d
(Energy Conservation-Buildings
and Community Systems - TID-4500)

SURVEY OF AVAILABLE TECHNOLOGY FOR THE IMPROVEMENT OF GAS-FIRED RESIDENTIAL HEATING EQUIPMENT

FINAL REPORT

**A. A. PUTNAM, S. G. TALBERT,
R. D. VERGARA, AND A. LEVY**

950 0081 —
**BATTELLE
COLUMBUS LABORATORIES
505 KING AVENUE
COLUMBUS, OHIO 43201**

DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

and

951 0394 —
**D. W. DeWERTH AND T. R. NORRIS
AMERICAN GAS ASSOCIATION LABORATORIES
8501 EAST PLEASANT VALLEY ROAD
CLEVELAND, OHIO 44131**

August 1979

Prepared for

**BROOKHAVEN NATIONAL LABORATORY
ASSOCIATED UNIVERSITIES, INC.**

UPTON, NEW YORK 11973

UNDER CONTRACT NO. EY-76-C-02-0016 WITH THE

**UNITED STATES DEPARTMENT OF ENERGY
DIVISION OF BUILDINGS AND COMMUNITY SYSTEMS**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED *leg*

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy (DOE), nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Printed in the United States of America
Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161
Price: Printed Copy \$9.00; Microfiche \$3.00
November 1979 525 copies

ABSTRACT

Available technology was surveyed as to possible application to more efficient gas-fired comfort heating and water heating in residences. Objectives were 1) to evaluate energy saving modifications and design approaches, including both retrofit and new systems, and 2) to identify RD&D required to bring to the marketplace those concepts that have a reasonable payback period.

Over 60 concepts, including both retrofit devices and new designs, were identified on the basis of the study of the technical literature and discussions with various segments of industry. After evaluating each concept on the basis of expected initial cost, energy consumption, and operating cost, those concepts with a reasonably short payback period were considered from the point of view of RD&D needs.

A principal recommendation covering several specific concepts was the study of condensing heat-exchanger systems. RD&D was recommended on both mechanical and aerodynamically valved pulse combustors, radiant burners, catalytic systems, heat pipe systems, self-powered heating units, and gas-fired heat pumps. Relative to retrofit concepts, recommendations covered the effects of derating on furnace corrosion and the methodology for predicting savings in individual homes. Need was also indicated for a methodology to optimize sizing of heating units and for data on energy demand requirements for integrated appliances. General recommendations related to systems control analysis, minimum venting requirements, and combustion air requirements in tight homes.

EXECUTIVE SUMMARY

The convenience, cleanliness, and low cost of natural gas has resulted in its dominance as an energy source for home heating in the U.S. Gas heating equipment is relatively simple, and its efficiency has been acceptable in the marketplace. Thus, equipment manufacturers have had little incentive in the past to invest in necessary R&D and tooling to introduce more efficient equipment. However, with energy supplies becoming tighter and costs becoming higher, there is growing demand for more efficient heating equipment.

Various equipment design approaches and modifications have been proposed that could lead to more efficient gas heating. Some of these concepts that may have failed to gain acceptance thus far because of economic reasons could be more viable with the expected trends in energy costs. A re-evaluation of these and newer approaches is appropriate, in terms of potential energy savings, safety and code requirements, environmental ramifications, and overall consumer acceptance.

This program had two objectives. The first objective was to identify and evaluate the energy saving modifications and design approaches suggested since 1945 that can be applied to gas-fired comfort heating and hot-water systems. The second objective was to identify the research, development, and demonstration (RD&D) that is required to bring to the marketplace those concepts that have a reasonable payoff period to the consumer.

Concepts were identified on the basis of (1) a study of the technical literature and (2) discussion with various segments of the industry. These concepts were then compared with current practice and safety codes. From this screening, 63 concepts emerged. Each concept was then evaluated on the basis of initial cost, energy consumption, and cost (both natural gas and electricity). Finally, the expected payback period to the consumer was determined.

As a basis for making a first cut relative to the potential of a concept in the marketplace, only concepts that showed a potential for a payback period of four years or less to the consumer were considered further. This left the 35 concepts which are presented in nine generic groups in Table ES-1.

Each of these concepts was considered from the viewpoint of needed RD&D to bring the concept to the marketplace or eliminate it from further consideration. This resulted in both recommendations relative to specific concepts and recommendations of a more general nature. These recommendations were grouped under three headings, namely, general concepts, retrofit concepts, and new concepts. Table ES-2 lists the suggested areas for RD&D.

A principal recommendation for RD&D is the study of condensing systems. This is because several concepts for significantly improved performance involve a condensing heat exchanger. A related RD&D need concerns the evaluation of the effects of corrosion when heating units are derated.

Several recommended studies relate the methodology involved and the backup data required in predicting heating unit demands and performance under various conditions. These items are not specific to particular concepts, but the information is needed to rapidly advance the penetration of energy-saving devices and new furnaces into the marketplace.

RD&D effort is recommended on four new types of heating units. Some mechanically valved pulse combustors are about to be marketed in the U.S.; aerodynamically valved pulsed combustors require a greater sophistication of design, and thus are farther from the marketplace. Heating units utilizing radiant burners for the high temperature end of heat exchangers appear to have a potential, especially in the area of overall compactness, plus high efficiency. The principal payoff in the area of catalytic systems would appear to be related to low emissions of NO_x . While the time to market obviously varies for each of these concepts, it is not clear as yet which ones may prove viable in the long run.

TABLE ES-1. CONCEPTS SELECTED FOR SHORT PAYBACK PERIODS *

<u>Combustion</u>	<u>Pilot</u>
Derating, with secondary air baffle	Reduced pilot input
Derating, with baffle and vent restrictor	
Power burner, noncondensing	<u>Controls</u>
Power burner, condensing	Thermostat setback
Pulse combustion burners	Fan control adjustment
Radiant burner, condensing	Fewer burner cycles
Catalytic burner, power, condensing	
Submerged combustion	<u>Heat Delivery System</u>
	Waste heat recovery
<u>Combustion Air</u>	Two-speed blower or pump
Sealed combustion	
Reduce excess air	<u>Field Modification</u>
Flue gas preheater of combustion air	Insulation jacket
Outside installation	
<u>Venting</u>	<u>Improved Equipment</u>
Vent damper	Design for less scaling and degradation
Double damper	Combination appliances
Vent restrictor	Field adjustable heat input
Increased flue baffling	Self-powered furnace (w/o electricity)
Power vent (forced draft)	Gas-fired heat pumps
	Natural convection systems
<u>Heat Exchanger</u>	
Heat-pipe heat exchanger	
Condensing flue products	

* A payback period of four years or less was used as the selection criterion.

TABLE ES-2. SUGGESTED AREAS FOR RESEARCH,
DEVELOPMENT, AND DEMONSTRATION

General Concepts

1. Condensing system study
2. System control analyses
3. Minimum venting requirements
4. Combustion air requirements in tighter homes

Retrofit Concepts

5. Corrosion effects of derating
6. Training manuals
7. Predictive savings methodology for individual homes

New Concepts

8. Proper sizing of heating units to match loads
 9. Mechanically valved pulse combustors
 10. Aerodynamically valved pulse combustors
 11. Radiant burner
 12. Catalytic systems
 13. Low cost heat pipe systems
 14. Self-powered heating units
 15. Gas-fired heat pumps
 16. Energy demand requirements for integrated appliances
-
-

Heat pipes are now being used in special industrial heat-exchanger applications; the development of a low cost heat exchanger based on heat pipes to be used in new heating units of an otherwise conventional design could increase seasonal efficiency greatly. In sections of the country where electrical blackouts are more frequent, self-powered heating units would have a great advantage; some effort should be made to incorporate this feature into new, more energy-efficient heating units.

Gas-fired heat pumps are some distance from the marketplace and may not have a short payback period when developed. However, they do incorporate an ability to handle both heating and cooling loads at a great economy in energy. For this reason, they are presently being investigated intensively, and support of this work should continue.

As a matter of perspective, it is not expected that all of the concepts evaluated will continue to show promise in the light of further study. These should be dropped. On the other hand, certain improvements in current designs and of various new concepts not covered above could prove worthy of at least development and demonstration support. In other words, a continual program reappraisal is needed as RD&D leads to new knowledge.

TABLE OF CONTENTS

	<u>Page</u>
BACKGROUND	1
OBJECTIVE.	2
SCOPE.	2
METHODOLOGY.	3
RD&D NEEDS	11
General RD&D.	12
Condensing Systems	12
Systems Control Analyses	12
Minimum Venting Requirements	13
Combustion Air Requirements.	13
Retrofit Developments	14
Combustion	14
Combustion Air	14
Venting.	15
Ignition	15
Controls	15
Heat Delivery Systems.	16
Field Modification	16
Summary for Retrofit Devices	17
New Equipment	17
Combustion	17
Combustion Air	20
Heat Exchanger	20
Controls	21
Heat Delivery System	21

TABLE OF CONTENTS
(continued)

	<u>Page</u>
Field Modification	21
Improved Equipment	22
Heating Demand Requirements for New Units.	23
CONCLUSIONS.	23
APPENDIX A. PROGRAM PLAN AND ORGANIZATION OF APPENDICES	
APPENDIX B. CHARACTERIZATION OF PRESENT GAS WARM-AIR FURNACES AND HOT WATER SYSTEMS	
APPENDIX C. LITERATURE SEARCH	
APPENDIX D. CONTACT SURVEY	
APPENDIX E. CONCEPT CHARACTERIZATION: TECHNICAL AND ECONOMIC EVALUATION	
APPENDIX F. INSTITUTIONAL BARRIERS RELATED TO SAFETY	
APPENDIX G. NON-SAFETY INSTITUTIONAL BARRIERS	

(Each Appendix has its own Table of Contents for your convenience)

LIST OF TABLES

Table 1. Payback Period for Efficiency Improvement Concepts	4
Table 2. Suggested Areas for Research, Development, and Demonstration.	25

FINAL REPORT
on
SURVEY OF AVAILABLE TECHNOLOGY FOR
THE IMPROVEMENT OF GAS-FIRED
RESIDENTIAL HEATING EQUIPMENT
to
BROOKHAVEN NATIONAL LABORATORY
by
A. A. Putnam, S. G. Talbert,
R. D. Vergara, and A. Levy
Battelle
Columbus Laboratories
and
D. W. DeWerth and T. R. Norris
American Gas Association Laboratories

August, 1979

BACKGROUND

The historic low price of natural gas and the relative low cost of residential gas-burning equipment has resulted in natural gas being used in over 50 percent of U.S. residences. However, these features of natural gas, along with various restraining codes and standards, have made it unattractive to invest in many modifications or new designs of gas heating equipment that would have resulted in significant energy savings.

Now that the energy situation is changing, the economics are changing also. The demand for such modifications and new types of heating units is increasing. However, there is a limited amount of information in a convenient form to serve as a guide as to which of the many concepts or modifications that have been proposed can be applied safely, economically, and effectively in residential space heating and water heating.

OBJECTIVE

The objective of this program was to identify and evaluate the energy-saving modifications and design approaches that can be applied to residential gas-fired comfort heating and water heating systems. Research, development and demonstration (RD&D) requirements were to be identified so that modifications with a potential for improving efficiency in an economical fashion might be more rapidly commercialized.

SCOPE

New concepts or modifications to burners, heat exchangers, venting arrangements, vents, pilots, controls, and distribution systems that have been suggested or developed since 1945 were considered. These modifications include replacement of the entire furnace, but do not include modifications necessitating structural changes in the residence. More specifically, the scope covered

- 1) Improvements in furnaces and boilers per se that will retrofit existing furnaces and boilers using existing ducts or hot water or steam piping (e.g., electronic ignition).
- 2) Improvements in the application of existing types of furnaces and boilers that can retrofit existing furnaces and boilers using existing ducting or hot water or steam piping (e.g., stack dampers).
- 3) Improvements in conventional furnace or boiler design that can be implemented by replacement of existing furnaces and boilers using existing ducting, or hot water or steam piping (e.g., greater heat-exchange surface).
- 4) Unconventional furnace or boiler design concepts that can be implemented by replacement of existing boilers and furnaces (e.g., catalytic combustion units or pulse combustion units).
- 5) Improvements in combustion air supply or venting for any of the above (e.g., sealed combustion systems).
- 6) Improvements in controls and modes of operation of the burner and blower or pumps (e.g., modulating controls).

METHODOLOGY

In order to accomplish the objectives of this program, seven primary tasks were delineated, namely:

- 1) Characterization of Present Gas-Fired Warm-Air and Hydronic Systems
- 2) Literature Search Pertaining to Gas Heating Technology
- 3) Survey of Manufacturers
- 4) Characterization of Concepts
- 5) Identification of Institutional Barriers Related to Safety
- 6) Identification of Institutional Barriers Related to Codes, Public Reaction, and Manufacturing
- 7) Recommendations for Research, Development, and Demonstration.

These tasks are described in detail in Appendix A.

As a result of the first three tasks, a list was compiled of pertinent energy-saving concepts that have appeared in the literature (Appendix C) or are presently being considered by the industry (Appendix D), and to compare them with the systems now on the market (Appendix B). These concepts were then grouped and characterized (Appendix E). Steady-state efficiencies, seasonal efficiencies, incremental first costs, and electric power input were assigned to each concept on the basis of available data, comparison with similar systems, and group-best judgments. This permitted, with assumed gas and electric costs, the identification of gas savings, electric savings, and total savings per year, and a range of payback periods to the consumer for each concept. Table 1 presents these data for the 63 concepts that were initially considered.

TABLE 1. PAYBACK PERIOD FOR EFFICIENCY IMPROVEMENT CONCEPTS

Concept	Type Furnace ¹	Steady- State	Seasonal	Incremental	Operating Power ⁴ Watts	Extra Power ⁵ Watts	Gas	Electricity	Total	Payback
		Efficiency ² %	Efficiency ² %	First Cost ³ \$			Saved 10 ⁶ Btu	Saved KWH	Savings \$/Yr	Period Years
0. Baseline Condition	AF	77	61	0	430	0	0	0	0	N.A.
	HB	77	65	0	100	0	0	0	0	N.A.
	WH	72	50	0	0	0	0	0	0	N.A.
A. Combustion										
1. Derating, 20% with reduced pressure or reduced orifices	AF	75	63	25-50	430	0	3.17	-125	1.54	16 - 32
	HB	75	65	25-50	100	0	2.98	-28.3	5.89	4.2-8.5
	WH	70	51	25-50	0	0	0.725	0.0	1.78	14 - 28
2. Derating, 20% with secondary air baffle ⁶	* AF	77	67	50-100	430	0	8.96	-81.9	17.85	2.8-5.6
	* HB	77	69	50-100	100	0	8.42	-18.9	19.69	2.5-5.1
	WH	72	55	50-100	0	0	3.36	0.0	8.24	6.1-12
3. Derating, 20% with baffle, plus vent restrictor	* AF	77	69	100-150	430	0	11.6	-62.4	25.30	4.0-5.9
	* HB	77	71	100-150	100	0	10.9	-14.6	26.01	3.8-5.8
	WH	72	57	75-125	0	0	4.54	0.0	11.14	6.7-11
4. Two-stage gas valve, high and low fire ⁷	AF	77	63	75-150	430	0	3.17	-173	-0.85	No
	HB	77	65	75-150	100	0	2.98	-39.1	5.35	14 - 28
5. Modulating gas valve ⁷	AF	77	65	100-200	430	0	6.15	-149	7.63	13 - 26
	HB	77	68	100-200	100	0	7.12	-31.5	15.88	6.3-12
6. Modulating gas and air valves ⁷	AF	77	70	150-250	430	0	12.9	-96.1	26.71	5.6-9.4
	HB	77	72	150-250	100	0	12.1	-22.3	28.55	5.3-8.8
7. Power burner ⁸ , non-condensing	* AF	80	75	100-150	545 ⁹	0	18.7	-159	37.82	2.6-4.0
	* HB	80	75	100-150	215 ⁹	0	15.5	-154	30.29	3.3-5.0
	WH	75	65	75-125	65 ⁹	0	8.54	-73.8	17.24	4.4-7.3
8. Power burner, ⁸ condensing	* AF	95	85	150-250	545 ⁹	0	28.2	-159	61.27	2.4-4.1
	* HB	90	85	150-250	215 ⁹	0	25.1	-154	53.74	2.8-4.7
	* WH	90	85	100-200	65 ⁹	0	15.2	-73.8	33.65	3.0-5.9
9. Pulse combustion burner ⁸ , condensing	* AF	95	95	300-600	455 ¹⁰	0	35.8	-34.5	85.99	3.5-7.0
	* HB	95	95	300-600	125	0	32.6	-33.4	78.27	3.8-7.7
	WH	95	95	250-500	25	0	17.5	-28.4	41.54	6.0-12.0
10. Radiant burner ⁸ , non-condensing	AF	79	64	100-200	430	0	4.69	-0.02	11.49	8.7-17
	HB	79	67	100-200	100	0	5.78	-0.03	14.17	7.1-14
	WH	74	55	75-150	0	0	3.36	0.00	8.24	9.1-18
11. Radiant burner ⁸ , power, condensing	* AF	90	85	150-250	545 ⁹	0	28.2	-159	61.27	2.4-4.7
	* HB	90	85	150-250	215	0	25.1	-163	53.27	2.8-4.7
	* WH	90	85	100-200	65	0	15.2	-73.8	33.65	3.0-5.9
12. Catalytic burner ⁸ , power, non-condensing	AF	85	70	100-200	630 ¹¹	0	12.9	-276	17.71	5.6-11
	HB	85	70	100-200	300	0	9.68	-267	10.37	9.6-19
	WH	85	65	75-150	100	0	8.54	-113	15.25	4.9-9.8

TABLE 1. (continued)

Concept	Type Furnace ¹	Steady- State Efficiency %	Seasonal Efficiency ² %	Incremental First Cost ³ \$	Operating Power ⁴ Watts	Extra Power ⁵ Watts	Gas Saved 10 ⁶ Btu	Electricity Saved KWH	Total Savings \$/Yr	Payback Period Years
<u>A. Combustion</u> (Continued)										
13. Catalytic burner, ⁸	* AF	90	85	150-250	630 ¹¹	0	28.2	-276	55.40	2.7-4.5
power, condensing	* HB	90	85	150-250	300	0	25.1	-280	47.40	3.2-5.3
	* WH	90	85	100-200	100	0	15.2	-113	31.67	3.2-6.3
14. Submerged combustion ^{8, 12}	* AF	90	85	150-300	630	0	28.2	-276	55.40	2.7-5.4
	* HB	90	85	150-300	300	0	25.1	-267	48.06	3.0-6.2
	WH	90	85	150-300	100	0	15.2	-113	31.67	4.8-9.4
15. Sequential firing of sections ⁷	AF	77	67	100-200	460 ¹³	0	8.96	-177	13.09	7.6-15.3
	HB	77	69	100-200	130	0	8.42	-77.9	16.74	6.0-12
<u>B. Combustion Air</u>										
16. Sealed combustion ⁽⁸⁾	* AF	77	73	100-250	430	0	16.4	-.02	40.29	2.5-6.2
	* HB	77	73	100-250	100	0	13.3	-.03	32.51	3.1-7.7
	WH	72	60	75-200	0	0	6.17	0.00	15.11	5.0-13
17. Reduce excess air	* AF	80	65	25-50	430	0	6.15	36.5	16.91	1.5-3.0
	* HB	80	67	25-50	100	0	5.78	7.95	14.57	1.7-3.4
	* WH	75	55	25-50	0	0	3.36	0.00	8.24	3.0-6.1
18. Preheater for combustion air	* AF	82	70	100-200	430	0	12.9	76.3	35.33	2.8-5.7
	HB	82	70	100-200	100	0	9.68	13.3	24.40	4.1-8.2
	WH	80	60	75-150	0	0	6.17	0.00	15.11	5.0-9.9
19. Outside installations ⁸	* AF	77	73	100-300	430	0	16.4	-0.02	40.29	2.5-7.4
	* WB	77	73	100-300	100	0	13.3	-0.03	32.51	3.1-9.2
<u>C. Venting Category</u>										
20. Vent damper, electrical	* AF	77	70	100-200	445	0	12.9	58.2	34.42	2.9-5.8
	HB	77	70	100-200	115	0	9.68	-4.7	23.50	4.3-8.5
	WH	72	57	75-150	15	0	4.54	-14.9	10.39	7.2-14
21. Vent damper, thermal	* AF	77	70	50-100	430	0	12.9	76.3	35.33	1.4-2.8
	* HB	77	70	50-100	100	0	9.68	13.3	24.40	2.0-4.1
	* WH	72	57	40-100	0	0	4.54	0.00	11.14	3.6-9.0
22. Vent damper, mechanical	* AF	77	70	100-200	430	0	12.9	76.3	35.33	2.8-5.7
	HB	77	70	100-200	100	0	9.68	13.3	24.40	4.1-8.2
	WH	72	57	75-150	0	0	4.54	0.00	11.14	6.7-13
23. Double damper, ¹⁴ electrical	* HB	77	73	100-200	115	0	13.3	0.98	32.56	3.1-6.1
	WH	72	60	100-200	15	0	6.17	-14.2	14.41	6.9-14
24. Double damper, ¹⁴ thermal and mechanical	* HB	77	73	100-200	100	0	13.3	18.3	33.42	3.0-6.0
	WH	72	60	100-200	0	0	6.17	0.00	15.11	6.6-13

TABLE 1. (continued)

Concept	Type Furnace ¹	Steady- State Efficiency %	Seasonal Efficiency ² %	Incremental First Cost ³ \$	Operating Power ⁴ Watts	Extra Power ⁵ Watts	Gas Saved 10 ⁶ Btu	Electricity Saved KWH	Total Savings \$/Yr	Payback Period Years
<u>C. Venting</u> (Continued)										
25. Vent damper, vent restrictor, derate (20% with baffle), and electric pilot	AF	77	73	200-300	460	0	16.4	-69.7	36.81	5.4-8.2
	HB	77	75	200-300	130	0	15.5	-48.8	35.53	5.6-8.4
26. Vent restrictor	* AF	77	67	75-100	430	0	8.96	53.1	24.61	3.0-4.1
	* HB	77	69	75-100	100	0	8.42	11.6	21.22	2.5-4.7
	WH	72	55	50-100	0	0	3.37	0.00	8.24	6.1-12
27. Draft hood replacement	AF	80	65	100-150	430	0	6.15	36.5	16.91	5.9-8.9
	HB	80	67	100-150	100	0	5.78	7.95	14.57	6.9-10
	WH	75	53	75-125	0	0	2.09	0.00	5.13	15 - 24
28. Increased flue baffling	* WH	75	53	10-20	0	0	2.09	0.00	5.13	1.9-3.9
29. Power vent ¹⁵ (forced draft)	* AF	80	70	50-150	530	0	12.9	-44.0	29.31	1.7-5.1
	* HB	80	70	50-150	200	0	9.68	-107	18.39	2.7-8.2
	* WH	75	60	50-150	50	0	6.17	-47.3	12.75	3.9-12
<u>D. Heat Exchanger</u>										
30. Heat pipe heat exchanger ⁸	* AF	82	75	100-200	430	0	18.7	-0.02	45.75	2.2-4.4
	* HB	82	75	100-200	100	0	15.5	-0.03	37.97	2.6-5.3
	* WH	82	70	50-150	0	0	10.6	0.00	25.91	1.9-5.8
31. Condensing flue products ⁸	* AF	95	75	100-250	430	0	18.7	-0.02	45.75	2.2-5.5
	* HB	90	75	100-250	100	0	15.5	-0.03	37.97	2.6-6.6
	* WH	90	70	75-200	0	0	10.6	0.00	25.91	2.9-7.7
32. Side-arm heater ³	WH	75	60	75-150	0	0	6.17	0.00	15.11	5.0-9.9
<u>E. Ignition</u>										
33. Reduced pilot input	* AF	77	62	10-25	430	0	1.61	9.56	4.43	2.3-5.6
	* HB	77	64	10-25	100	0	1.51	2.06	3.81	2.6-6.6
	WH	72	51	10-25	0	0	0.725	0.00	1.78	5.6-14
34. Electric pilot (IID)	AF	77	65	100-175	445	0	6.15	17.1	15.94	6.3-11
	HB	77	67	100-175	115	0	5.78	-10.9	13.62	7.3-13
35. Direct spark (DSI)	AF	77	65	75-150	445	0	6.15	17.1	15.94	4.7-9.4
	HB	77	67	75-150	115	0	5.78	-10.9	13.62	5.5-11
<u>F. Controls</u>										
36. Thermostat setback ¹⁶	* AF	77	65	0-100	430	2 ¹⁷	6.15	27.8	16.47	0.0-6.1
	* HB	77	67	0-100	100	2	5.78	-0.78	14.13	0.0-7.1
	* WH	74	55	0-25	0	0	3.36	0.00	8.24	0.0-3.0

TABLE 1. (continued)

Concept	Type Furnace ¹	Steady- State Efficiency %	Seasonal Efficiency ² %	Incremental First Cost ³ \$	Operating Power ⁴ Watts	Extra Power ⁵ Watts	Gas Saved 10 ⁶ Btu	Electricity Saved KWH	Total Savings \$/Yr	Payback Period Years
<u>F. Controls</u> (Continued)										
37. Time-of-day input	WH	72	55	100-200	0	3 ¹⁷	3.36	-26.3	6.93	14 - 29
38. Fan control adjustment	* AF	77	63	0-25	430	0	3.17	18.8	8.72	0.0-2.9
	* HB	77	65	0-25	100	0	2.98	4.09	7.51	0.0-3.3
39. Fewer burner cycles	* AF	77	63	25-50	430	0	3.17	18.8	8.72	2.9-5.7
	* HB	77	65	25-50	100	0	2.98	4.09	7.51	3.3-6.7
40. Humidity limit	AF	77	62	50-100	430	0	1.61	9.56	4.43	11 - 22
	HB	77	64	50-100	100	0	1.51	2.06	3.81	13 - 26
41. Temperature modulating aquastat	HB	77	65	50-150	100	0	2.98	4.09	7.51	6.7-20
42. Microprocessor control	AF	77	65	100-200	430	5	6.15	14.7	15.82	6.3-12.0
	HB	77	67	100-200	100	5	5.78	-13.9	13.47	7.4-15
	WH	72	53	50-150	15 ¹⁸	5	2.09	-59.9	2.14	23 - 70
43. Central control center	AF	77	64	150-250	430	5	4.69	5.96	11.79	13 - 21
	HB	77	66	150-250	100	5	4.40	-15.8	10.00	15 - 25
	WH	72	53	100-200	15	5	2.09	-59.9	2.14	47 - 93
<u>G. Heat Delivery System</u>										
44. Waste heat recovery	* AF	82	70	100-300	430	0	12.9	76.3	35.33	2.8-8.5
	HB	82	70	100-300	100	0	9.68	13.3	24.40	4.1-12
	WH	80	60	75-250	0	0	6.17	0.00	15.11	5.0-17
45. Two-speed blower or pump	* AF	77	62	20-100	322 ¹⁹	0	1.61	156	11.76	1.7-8.5
	* HB	77	64	20-100	75	0	1.51	34.9	5.46	3.7-18
46. Improved blower design ⁸	AF	77	61	20-50	387 ²⁰	0	0.00	59.3	2.97	6.7-17
47. More efficient motors	AF	77	61	20-100	387 ²⁰	0	0.00	59.3	2.97	6.7-34
	HB	77	63	20-100	90	0	0.00	13.3	0.67	30 - 150
48. Zone temperature control	AF	77	64	100-300	450	0	4.69	1.49	11.56	8.6-26
	HB	77	66	100-300	120	0	4.40	-19.5	9.81	10 - 31
49. Warm room	AF	77	67	100-300	450	0	8.96	28.0	23.35	4.3-13
	HB	77	69	100-300	120	0	8.42	-12.8	20.00	5.0-15
50. Storage of heat	AF	77	64	200-400	470	50 ²¹	4.69	-243	- 0.67	No
	HB	77	66	200-400	100	50	4.40	-212	+ 0.17	Very large

TABLE 1. (continued)

Concept	Type Furnace ¹	Steady- State Efficiency ² %	Seasonal Efficiency ² %	Incremental First Cost ³ \$	Operating Power ⁴ Watts	Extra Power ⁵ Watts	Gas Saved 10 ⁶ Btu	Electricity Saved KWH	Total Savings \$/Yr	Payback Period Years
<u>H. Field Adjustments Category</u>										
51. General tuneup and cleaning	AF	77	62	25-50	430	0	1.61	9.56	4.43	5.6-11
	HB	77	64	25-50	100	0	1.51	2.06	3.81	6.6-13
	WH	72	51	25-50	0	0	0.725	0.00	1.78	14 - 28
52. Insulation jacket	* WH	73	55	25-50	0	0	3.36	0.00	8.24	3.0-6.1
<u>I. Improved Equipment Category</u>										
53. Replace existing equipment ^{8, 22}	AF	85	75	500-1000	390	0	18.7	55.2	48.51	10 - 20
	HB	85	75	500-1000	90	0	15.5	13.3	38.64	13 - 26
	WH	80	65	200-300	0	0	8.54	0.00	20.93	9.6-14
54. Instantaneous water heater ²³	WH	80	70	200-400	0	0	10.6	0.00	25.91	7.7-15
55. Design for less scaling and degradation	* WH	72	60	25-100	0	0	6.17	0.00	15.11	1.7-6.6
56. Minimize heat leaks	WH	73	51	10-25	0	0	0.725	0.00	1.78	5.6-14
57. Heat traps for hot water pipe	WH	72	51	10-25	0	0	0.725	0.00	1.78	5.6-14
58. Combination appliances ^{8, 24}	* AF + WH	85	75	0-100	430	0	18.7	111	51.29	0.0-1.9
	* HB + WH	85	75	0-100	100	0	15.5	21.4	39.04	0.0-2.6
59. Field adjustable heat input ^{8, 25}	* AF	77	65	50-100	390	0	5.15	-38.0	13.18	3.8-7.6
	* HB	77	67	50-100	100	0	5.78	-23.5	13.00	3.8-7.7
60. Self-powered furnace ⁸	* AF	85	70	100-200	10 ²⁶	0	12.9	580	60.49	1.7-3.3
	* HB	85	70	100-200	10	0	9.68	120	29.74	3.4-6.7
61. Thermoelectric furnace ^{8, 27}	AF	80	66	400-800	10 ²⁶	0	7.58	580	47.55	8.4-17
	HB	80	68	200-400	10	0	7.12	120	23.46	8.5-17
62. Gas-fired heat pumps ^{8, 28}	* AF	140	120	300-500	930	0	49.2	-690	86.01	3.5-5.8
	HB	120	100	300-500	600	0	35.8	-668	54.40	5.5-9.2
	WH	130	110	200-400	250	0	20.2	-284	35.28	5.7-11
63. Natural convection systems ^{8, 29}	* AF	75	61	50-100	0	0	0.0	593	29.67	1.7-3.4
	HB	75	63	50-100	0	0	0.0	134	6.68	7.5-15

Footnotes:

1. AF = air furnace (100,000 Btu/hr); HB = hydronic boiler (100,000 Btu/hr); WH = water heater (45,000 Btu/hr).
2. Seasonal efficiency for furnaces based on 6-month heating season, Oct-Mar (4,368 hours), and for domestic water heaters on 12 months (8,760 hours).
3. Range of incremental first cost applies to both new and/or retrofit equipment.
4. Operating power is the rate of electric energy input while running.
5. Extra power is the constant electric input required above the baseline case.
6. Secondary air flow reduced to maintain the same steady-state efficiency after derating.
7. Average input for two-stage, modulating, or sequential valve operation assumed to be an average of the high and low fire inputs, or 75,000 Btu/hr.
8. This concept applies to new equipment only. Therefore, gas input was reduced by a ratio of the seasonal efficiencies to keep operating time constant ($q_2 = q_1 \times \eta_1/\eta_2$).
9. Power blower assumed to be 100 watts input with electric ignition of 15 watts for furnaces, and 50 and 15 watts for water heater.
10. Power input assumed to be a 100-watt blower operating 0.1 of the time (or 10 watts), and a 15-watt ignition input.
11. Combustion air blower assumed to be 200 watts for furnaces and 100 watts for water heater.
12. Submerged combustion systems would be separate from high line pressures in boilers or water heaters. Power blower of 200 watts assumed for furnaces and 100 watts for water heater.
13. Extra operating power needed for controls, etc.
14. Double damper assumed to be useful only on hydronic boilers and water heaters, as they maintain higher standby temperature levels.
15. With a power vent, it is assumed that a vent restriction of some type is included to minimize the escape of room air during the off cycle.
16. Setback assumed to nighttime for furnaces and a permanent 20 F for water heaters.
17. Extra continuous electric power needed for clock thermostat, controls, etc.
18. Extra electric power required for solenoid valve.
19. Assumed power reduction of one-half for low speed operation, and operating for one-half of the time at low speed.
20. Assumed 10 percent power reduction due to improved design.
21. Extra power for heat storage pump assumed to be 100 watts, but operating only one-half the time, and blower power increased 10 percent due to increased pressure drop of heat exchanger.
22. Replacement costs include removing old equipment, installing a properly sized furnace and allowing for the higher efficiency, and assuming power savings of 10 percent due to improved motors.
23. An instantaneous water heater would have an input rating of about 200,000 Btu/hr.
24. Combination appliances assumed to have the same total gas input rating as furnace only (i.e., 100,000 Btu/hr), and also the same electric input rating, as improved motor efficiencies would likely be offset by increased running time because functions are combined. However, overall lower operating time will result because of increased seasonal efficiency.

Footnotes: (Continued)

25. Average adjusted input assumed to be 80,000 Btu/hr, with lower blower speed also. (Pump speed not adjustable.)
 26. It was assumed that self-contained or thermoelectric furnaces will require about 10 watts for thermostat and gas valve during operation.
 27. The cost of a thermoelectric device to operate between the flue gas temperature and the incoming combustion air temperature was estimated on the basis of about \$1 - \$2 per watt. Presently the cost is about 10 times higher than this.
 28. A seasonal efficiency of 120 percent for a gas-fired heat pump represents a seasonal COP of 1.20. The efficiencies are slightly different for the three types of appliances because of their different temperature levels of operation. The outdoor fans were assumed to require 500 watts for the furnaces and 250 watts for the water heater.
 29. Natural convection (gravity) systems, using air, water, or steam, could be designed to have about the same overall seasonal efficiency as present forced circulation systems. Although first costs would increase, a net savings could be realized by eliminating the need for electrical operating power.
- * Selected items with payback period of 4 years or less.

It should be noted that this list is not all-inclusive. For instance, only more promising combinations of concepts are listed, e.g., radiant burners with condensing heat exchangers. Further, variations on a given concept are not listed; an example is the multiplicity of pulse combustor designs that are available. However, the list is felt to be sufficient for the objective of this study.

From considerations of the marketplace, it appeared that the payback period to the consumer on many concepts in the initial list was too long to be acceptable. Therefore, for screening purposes, an arbitrary limit of four years was set as a maximum payback period for a concept to be considered further. The resulting 35 concepts are shown with an asterisk in Table 1, presented earlier.

Each of these 35 concepts was considered from the point of view of what RD&D might be necessary to bring the concept to the marketplace. Potential safety problems (Appendix F) and institutional barriers (Appendix G) were part of the evaluation. The resulting recommendation and supporting discussion follow.

Detailed cost-benefit analysis of each concept was beyond the scope of this program. It would have required an in-depth evaluation of each technical problem involved in each concept, plus a judgment of the probability of technical success and consumer acceptance. On the other hand, estimates were made of potential savings to the consumer that would result from the development of even a limited number of the new concepts. These estimated savings can be used to justify a significant research effort. Appendix H describes this in more detail.

RD&D NEEDS

As indicated above, the information in the several Appendices of this report were combined to produce the listing of energy-saving concepts presented in Table 1. By using a four-year maximum payback period to the consumer, the concepts were reduced to those shown with an asterisk in Table 1. Consideration of the research needs of these concepts showed

that the needs could be grouped into three classes, namely, general RD&D needs, needs specific to retrofit development, and needs specific to new unit development. In the discussion of each of these need areas, reference is made to identification number of item in Table 1.

General RD&D

Condensing Systems

It is clear that for the largest improvement in energy performance of present heating and the highest performance of new designs, condensing systems must be used to recover heat from the products of combustion (8, 9, 11, 13, 14, 31)*. Thus, for several different designs of heating units, the problems in this portion of the unit are common. To produce a successful condensing system, methods will be needed to minimize or provide for acceptable levels of corrosion. Other problems affecting commercialization relate to condensate disposal and its possible effects on plumbing and sewage treatment, matching of the furnace to the structure, particularly regarding the reduced stack effect with cooled flue products, and various institutional factors relating to codes and safety.

The RD&D required involves selection and/or development of suitable heat-exchanger materials capable of providing adequate service in condensing units, assessment of condensate disposal, institutional problems, and, finally, a detailed economic analysis of the costs and benefits associated with condensing systems.

Systems Control Analyses

There are several suggestions for various combinations of manual and automatic control schemes to reduce the overall energy consumption for

* Numbers in parentheses refer to concept numbers in Table 1.

heating (36-43). Whether any of these suggestions are economically feasible depends on assumptions as to changes in fuel and electrical consumption, furnace lifetime, control system cost, and the value of any changes in comfort factors. Computer models are presently available to carry out evaluations (i.e. Figure B-11, Appendix B), but they need to be exercised more fully. Furthermore, some of the conclusions reached thus far relative to optimum size of heating unit and optimum firing time are open to question. Required are explanations of the reasons for the conclusions and independent checking of the results.

Minimum Venting Requirements

Several of the retrofit devices require a reduction of the venting air (3; 20-29). Because they are retrofit devices per se, some of these (3, 25-28) involve a risk that has to be examined. Further, some (20-24) involve a direct CO risk. For some (26-28) there are code barriers, and for others (23, 24), codes are in a process of revision. It appears that, in new furnaces of conventional design, attempts will also be made to minimize the venting air. RD&D required includes a study of the minimum venting air requirements for a wide range of characteristic homes and surrounding environments, to fix safe limits on the venting requirements under all weather conditions.

Combustion Air Requirements

As new homes are built more tightly, or old homes have various sources of air leakage from the outside sealed off, the point will be approached where there may be insufficient infiltration air for the furnace, boiler, or even water heater. It is also clear that wind direction can be involved, for a given home. Field measurements are needed comparing levels of CO, CO₂ and other combustion gases in new or modified structures with low infiltration relative to structures that have not been modified or designed for low infiltration. It would be worthwhile to evaluate present

codes and standards in this respect, to determine if they lead to consistent overdesign, are adequate in all cases, or are adequate only in certain cases. This evaluation should be made with the use of experimental data.

Retrofit Developments

Combustion

Derating a furnace or boiler, and including a secondary air baffle, and possibly a vent restrictor, has been shown to be effective in increasing the seasonal efficiency of conventional furnaces and boilers (2, 3). However, for some designs, experiments conducted by the A.C.A. Laboratories have shown that corrosion of the heat exchanger section has increased. Studies of life-cycle cost have indicated that in these instances, there may actually be an increase in cost with derating as a result of shorter furnace life. Studies are being carried out in the area, but further well-planned studies are required before a positive conclusion can be drawn on the long-term overall value of this approach. The relation of this program to that suggested above for condensation studies should be noted.

Combustion Air

A sealed combustion system (16) is ordinarily thought of as pertaining to a new installation. However, it can be, and has been, applied as a retrofit to furnace and boiler installations. The key to such a retrofit appears to be the adaptability of the home to some ducting changes, considering the possible pressure differentials between air inlet and stack exit, plus local code problems. A clear set of instructions for service personnel on how a home heating unit can be adapted to become a sealed combustion unit may be in order.

Reducing excess air (17) as a retrofit is an adjustment problem. The service personnel must be adequately trained and have adequate instrumentation so that the excess air is reduced by the maximum amount without incurring problems of CO or deposits. It is noted, since the minimum payoff

is more than one year, the adjustment must hold for at least two heating seasons even for a minimum adjustment cost.

Venting

As indicated in the discussion above on "minimum venting requirements", there are a multitude of approaches in the venting category, and a multitude of devices on the market. In many instances, the devices are such that homeowners might install them by themselves, with adequate instruction. However, service personnel with adequate instrumentation should be able to adjust the units more reliably to an optimum operation.

It would appear that the area needing research in this case is not the development of devices, but (a) the development of minimal requirements for vent flow based on experimental studies, and (b) the development of techniques for properly installing these devices in a specific home situation.

Ignition

The main reduction in pilot input can be made by a homeowner during the off-season by turning off the pilot. If a serviceman is needed to shut off and turn on the pilot, the procedure is not warranted.

The item (33) listed under this heading, however, refers to decreasing the firing rate of the pilot. It is seen that the payback period is very sensitive to service cost. No research is required, as manufacturers and servicemen should know the level of acceptable turndown of the pilot.

Controls

Thermal setback (36) can be accomplished simply by the homeowner, at no cost to himself. For the furnace or hydronic system, an automatic control might also be provided. Unless the new control were installed by the homeowner or was reasonably low in cost of installation, the monetary value of such an installation for the average homeowner would be questionable.

For the water heater, again the homeowner can make his own adjustment on modern units. In none of these cases does there appear need for research. Small demonstration projects to show savings might be helpful for educational purposes.

Adjustment of the temperature control on a fan (38) might be done by a reasonably adept homeowner, or a service technician might be required. Some experimentation would be required to maximize the savings. A documented procedural manual for this adjustment would be helpful. This could be based on results of a "systems control analysis" as discussed above.

In the case of setting a thermostat cycling rate so that fewer burner cycles are required (39), there is a question as to whether the present control system designs are sufficiently flexible. Computations to determine the optimum cycling rate can be readily carried out by now available mathematical programs (see discussion of "Systems Control Analyses"). Once this is done, modified and/or new control systems can be supplied to retrofit old heating systems and for use in new installations.

Heat Delivery Systems

A waste-heat recovery system (44) can be considered as a retrofit unit to recover stack heat, and heat either air for distribution to a room, or preheat combustion air. For the moderate recovery envisioned here, condensation should be avoidable. Thus, this device appears to fall, in essence, in the same group of devices as in the venting category, and requires the same type of research input.

A two-speed blower (45) may be installed in a furnace as a retrofit. If done by the homeowner, it would probably pay off. Otherwise, it would not.

Field Modification

A homeowner can install an insulating jacket on his water heater, or have it done. In the latter case, the cost effectiveness is questionable.

Summary for Retrofit Devices

Several conclusions can be drawn relative to the type of research indicated in respect to retrofit devices. First, there is a need for studies of condensing systems that could tie in with a more general condensing equipment development program. Second, there is an obvious need for competent servicemen to ensure safe and effective modifications of heating units. This leads to the suggestion that Training Manuals be prepared for such personnel. These should indicate the use and interpretation of the proper instrumentation in obtaining the optimum adjustment of currently available devices. Mathematical models of performance need to be exercised to provide the necessary direction for optimum usage of the various devices. The Manuals should be based on actual experience in installing such devices, possibly in demonstration programs.

As a third point, one finds that many homeowners are hesitant about retrofit devices, because they do not know the magnitude of the potential savings. From some of the results of the SHEIP program, this is a justifiable reluctance; in some instances retrofit devices saved very little energy. It is clear that improved methodology and correlation procedures are needed to predict the potential savings of any retrofit device in a specific home. Furthermore, small demonstration programs and educational efforts are needed to sell the homeowner.

New Equipment

Combustion

There appears to be no great problem in the technical area relative to the development of gas-fired power burners (7) for residential heating. Some gas-fired power burners are already on the market. Furthermore, the use of power burners is common for oil-fired residential heating equipment. Also, these systems are close to many presently available commercial and industrial systems. Finally, there appear to be no significant additional safety problems. Thus, it appears questionable whether any government-supported development or demonstration programs are necessary for the power burners per se.

Power burners combined with condensing systems (8) should achieve higher efficiencies. However, corrosion research, particularly in the materials area, directed toward lower cost, is required in this case. One must also consider, with such additional development time and change in some design factors, whether development of one or more of the systems discussed below might be a preferable direction.

Pulse combustors (9) can be divided into two classes, mechanically valved units (such as the World War II V-1 or buzz bomb) and those in which the mechanical inlet flapper valve is replaced by an aerodynamic valve (fluidic device).

The mechanically valved pulse combustor has been used over a period of years for home heating. A hydronic system developed by Lucas-Rotax was sold in both the U.S. and Canada over two decades ago. In the era of low price gas, however, the higher efficiency was apparently not worth the cost. In addition, the marketing effort was inadequate. This unit has been carried through to a high degree of development in subsequent research by the A.G.A. Laboratories. It, and similar units, are about to be reintroduced into the market for both warm-air and hydronic systems. These units are generally condensing; the little information available indicates the problems that result therefrom are minimal for the hydronic systems. Principal RD&D problems are related to increased life and decreased cost of the mechanical valve and starting system, and improving the fundamental understanding of the periodic combustion process and heat transfer process.

The aerodynamically valved pulse combustor system has not been carried to as high a degree of development as the mechanically valved units. However, this type of pulse combustor offers the potential of several distinct advantages for a gas-fired system, either warm air, hydronic, or domestic water heating. First, the necessity for a mechanical air flapper-valve is eliminated. Second, the pulse shape is not as sharp; as a result, cancellation of noise by using dual, coupled pulse combustors is a distinct possibility. Third, there is a possibility that the unit may be made self-starting and not require the starting and purging fan of the mechanically valved units. These advantages would lead to a less expensive, more compact system, with lesser maintenance requirements. On the other hand, there is a need for fundamental research in this area as well as the development and demonstration efforts that are in common for the two types of pulse combustors.

Radiant burners (11) are widely used in industry for a variety of applications, including comfort heating from a distance. In the case of a furnace, hydronic unit, or domestic hot water unit, however, direct radiant heating is not the aim.*

The aim of the radiant burner development for furnaces is to reduce the size of the furnace by combining an initial radiant heat exchange section with a subsequent hot-gas heat exchanger, while, at the same time, increasing the efficiency of heat utilization. Not only would comfort heating be handled by the heat exchanger, but some combustion air preheating could take place. The addition of a fan and a condensing system completes the small package. The main effort in developing this type of unit is in combining presently available techniques and components in a new package, the technological development of the system, and the demonstration of its feasibility. For a more long-range approach, one might consider the new developments in the area of compact oxygen enrichment membrane systems. The use of oxygen-enriched air could raise the radiant flux significantly.

Catalytic, power burner, condensing systems (13) appear even more exotic than pulse combustors or radiant units. However, such units have a potential advantage in their ability to produce relatively low emission levels of undesirable pollutants such as NO_x while maintaining good combustion efficiency. Such burners can also maintain combustion far beyond the conventional fuel/air flammability limits; this could help in providing a turn-down capability. Catalysts can be divided into three temperature regions--a central region between about 900 to 2000 F, a low temperature region with a characteristic absence of visible radiation, and a high-temperature region under study for aircraft engine reignition. The probable area of study for application to residential heating is the central region. Poisoning of the catalyst would be one problem area. A second is related to the fact that CH_4 is one of the less susceptible hydrocarbons to catalyst activity. Large amounts of excess air could be used to hold the temperature down; use of a

* Note that many room heaters do have a radiant section, with the hot gases then being passed into the room for direct air heating. Further, more acceptable units have a glass heat transmitting plate which directs the hot flue products through a heat exchanger where they exchange heat with room air before being vented to the atmosphere.

condensing system would minimize the thermal loss but the burner fan power might be excessive. An alternative would be to use a large recirculation of cooled products. The identification of suitable catalysts and the design of suitable systems would require considerable research effort. Consideration would also have to be given to safety aspects of the system.

Submerged combustion (14) is an alternative to a condensing system to achieve high thermal efficiency. In the case of a furnace (and for some possible variations of hydronic and hot water systems), a water-to-air heat exchanger would be required to extract heat from the water tank through which the flue products pass. The tank water would build up to an equilibrium composition with the product condensed; thus, the properties of the condensate would require investigation. In the case of hydronic systems, the products could be supplied directly to the system, with again a possible buildup problem and corrosion of distribution piping and radiators. In the case of direct heating of hot water, the products will be disposed of and any condensate problem minimized. It is clear that many of the problems in developing this system are related to the condensing system problems.

Combustion Air

Reducing excess air, using preheat, and using an outside installation are all items well within present art. There appears to be little need for research in these areas. However, demonstrations would be helpful.

Sealed combustion systems have seen little application in conventional housing with central heating units. There is a need for field evaluation of pressure differentials between the stack and combustion air inlet in sealed combustion units where the stack and air inlet are separated.

Heat Exchanger

Heat pipes (30) are a relatively recent technical innovation. As far as is known, they have only been applied to industrial heat exchangers and not to residential heating. Heat applied to one end of a closed system

vaporizes the enclosed liquid. The vapor moves rapidly to the opposite cooler end where it is condensed, giving up heat. The liquid moves back to the high-temperature end by capillary action. By incorporating gravity effects, the flow of heat can be made uni-directional. Thus, as an alternative to using a power-burner system to block off-cycle losses, heat-pipe heat exchangers could be used to minimize losses during the off period. The general field of heat-pipe technology is one of great current interest and rapid growth; in fact, special purpose industrial heat exchangers operating in the above outlined manner are now available. Research in this area would be directed toward the application of this rapidly growing technology to the specific design needs for furnaces, hydronic systems, and domestic hot water.

A condensing system(31) might be considered as a single improvement to present designs, as contrasted to a joint improvement with various combinations of other improvement elements. Research needs have already been discussed.

Controls

The various control adjustments that appeared profitable were discussed as retrofit devices. It would be expected that they also would be used on new units, with little or no increase in cost.

Heat Delivery System

Inclusion of two-speed pumps and blowers (45) offer no significant problem to manufacturers of conventional heating units as an improvement. It is merely a matter of whether the manufacturer feels the extra efficiency that might be attained is saleable at the increased unit cost.

Field Modification

An increase in the thickness of the insulating blanket (52) of a water heater can easily be made by a manufacturer. Again, the decision rests on his estimate of the saleability of the extra savings in fuel cost.

Improved Equipment

One of the greatest problems of a homeowner relative to the domestic water heater is remembering to flush the tank at proper periods. The manufacturer should therefore design to minimize scaling and degradation problems (55). As another approach to the problem, perhaps gas utilities could be induced to overstamp the monthly bill with various reminders to flush out the hot-water tank.

The combining of the furnace or boiler (58) with the domestic hot water system is not new. However, it has never been popular except in limited geographic areas for hydronic boilers with instantaneous hot-water coils. The gradual decrease in comfort heating load relative to hot water demands is bringing about a balance of loads. Combined with the possible savings in control cost, installation cost and energy savings, the option looks attractive. There appears to be no need for RD&D in this area, however, beyond determination of load demand characteristics of homes and demonstration of the market and practicality of the combined unit.

It is possible to design a heating unit that is more easily adjusted to meet the needs of a homeowner (59). However, the cost is such that the savings would be marginal. Furthermore, expected improvements in the proper sizing of furnaces to homes would make this less necessary. No RD&D is recommended.

The concept of a self-powered furnace to eliminate the need for an outside source of electricity is attractive to any homeowner. At one extreme, one can consider an improved furnace design which utilized only natural convection to circulate the heated air or water throughout the house (63). These types of systems were more common in the past; recently, wood stoves and air circulating fireplaces have gained acceptance. These "gravity distribution" systems, of course, have to be used in homes designed specifically for them. At the other extreme of self-powered furnaces (60), one can envision such systems as Rankine or Stirling-cycle-driven blowers or pumps, pulse combustors coupled with pulse motors or pumps, and thermoelectric powered motors and controls. The benefit of self-powered systems, immune to blackouts, would appear to justify the necessary RD&D.

While the payoff for gas-fired heat pumps is marginal, and the development is at least five years away from the marketplace, the considerable ongoing research efforts by GRI/DOE appear justified because of the combining of heating and cooling functions, and also because of the very high seasonal efficiencies that can be achieved during the heating season. Specifically, current work is being directed toward several types of systems, including absorption, Rankine, Stirling, and Brayton cycles. Some of these systems have the capability of achieving seasonal heating efficiencies greater than 100 percent, while maintaining seasonal cooling efficiencies similar to gas-fired absorption air conditioners.

Heating Demand Requirements for New Units

Regardless of the type of new furnace that may be available, it is considered that one aspect of the economic use of the heating unit is the proper sizing to match the heating load. It is well known that heating units are ordinarily oversized, and usually by a considerable amount, often 50 to 100 percent.* The principles that are involved in selecting a properly sized heating unit are also involved in two areas discussed above, namely, in predicting savings for retrofits in individual homes, and in predicting combustion air requirements to insure adequate venting. The scope of this suggestion should be directed, however, to the specific requirements of new heating unit installations in either new or old homes.

CONCLUSIONS

The concepts for increasing the efficiency of utilization of energy in gas-fired comfort heating and water heating units extracted from the three approaches of Appendices B, C, and D were presented in Table 1. On the basis of a payback period to the consumer of four years or less, these were reduced to the concepts shown with an asterisk in Table 1. The previous discussion was directed to the needs for RD&D for each of the four-year payback concepts.

* Some oversizing (e.g. 20 to 50 percent) is advantageous, however, as when night-time setback is practiced.

In some instances, there were no particular RD&D demands. In other cases, a particular RD&D demand showed up in relation to several concepts. In this section, only the recommended areas of RD&D are covered. The coverage is divided into three areas, general recommendations, retrofit study recommendations, and recommendations related to new equipment. The specific items and their RD&D requirements are listed in Table 2.

TABLE 2. SUGGESTED AREAS FOR RD&D

RD&D Area	Concept Applicability	RD&D Required
Condensing Systems	General	Development of materials and fabrication technology for corrosive environments. Evaluation of condensate disposal problems. Evaluation of compatibility of heating unit to structure. Evaluation of institutional and safety related problems.
Controls	General	Further application of existing computer programs to develop control design and operating data. Independent critical evaluation of computer program results to verify their validity.
Venting Requirements	General	Determination of minimum venting air requirements for wide range of home/topography/weather conditions to establish appropriate safety limits. An experimental program to acquire data on the adequacy of combustion air in tight houses and a determination of whether special provisions should be made to assure adequacy of combustion air.
Corrosion Effects of Derating	Retrofit	An experimental program to determine the amount of corrosion and reduced life of heating equipment under each derating scheme. This should be followed by a life-cycle cost analysis to determine the cost benefits of derating.
Training Manuals	Retrofit	Development of training manuals for service men to insure that safe and effective modifications to heating units are made.
Predictive Methodology for Savings in Individual Homes	Retrofit	Development of an improved methodology based on correlation of adequate data to allow prediction of potential savings of any retrofit device to the homeowner.
Proper Sizing of Heating Units to Match Loads	New Equipment	Development of an improved methodology for estimating the heating demand for new houses. This should be followed by experimental testing and checking of results.
Pulse Combustors	New Equipment	Development of mufflers, flapper valves, heat exchangers, and starting systems for mechanically valved pulse combustor units. This should be followed by demonstrations in connection with mechanically valved packages. For aerodynamically valved pulse combustors, experimental studies are required of the basic mechanism, the performance of fluid dynamic components, and the potential of coupling units for silencing. Development work on some of the simpler aerodynamic designs is also required.

TABLE 2. (continued)

RD&D Area	Concept Applicability	RD&D Required
Radiant Burners	New Equipment	A development program to experimentally and analytically evaluate the various design options using currently available radiant burner units. Research should be directed at establishing whether this type of system can be integrated into a package that is lighter and more compact than the alternative of a straight power burner and all-convective heat exchanger.
Catalytic Systems	New Equipment	Assessment and optimization of various possible arrangements of components, possible catalytic materials that can operate with natural gas in a home environment without being poisoned, package size and ancillary equipment requirements, and actual completeness of combustion and production of nitrogen oxides.
Low Cost Heat Pipe Systems	New Equipment	Development of several unit concepts based on heat pipes followed by the construction, laboratory, and field evaluation of any that appear to have economic potential when weighed against competing systems.
Self-Powered Heating Units	New Equipment	Evaluation, development, and demonstration of the various concepts that are possible and evaluation of how these concepts fulfill the requirements of modern houses.
Gas-Fired Heat Pumps	New Equipment	Continuation of current GRI/DOE-sponsored research on gas-fired heat pump development.
Design Requirements for Integrated Appliances	New Equipment	Development of appropriate design data for integrated appliances taking into account the time-varying energy demand requirements of various typical households.

APPENDIX A

PROGRAM PLAN AND ORGANIZATION OF APPENDICES

APPENDIX A

TABLE OF CONTENTS

	<u>Page</u>
PROGRAM PLAN AND ORGANIZATION OF APPENDICES.	29
Task 2. Characterization of Present Gas Warm-Air Furnaces, Hot Water and Steam Boilers, and Hot-Water Systems.	31
Task 3. Search and Analysis of Literature Since 1945	32
Task 4. Industrial Contact Survey for Current Plans and Ideas of Manufacturing, Utilities, and Trade Organizations.	33
Task 5. Concept Characterization and Generalization, Technical and Economic Evaluation.	34
Task 6. Recommendation for Research, Development, and Demonstration.	35
Task 7a. Institutional Barriers Related to Safety	35
Task 7b. Institutional Barriers Other Than Safety	35

LIST OF FIGURES

Figure A-1. Relationship of Tasks	30
---	----

APPENDIX A

PROGRAM PLAN AND ORGANIZATION OF APPENDICES

The objective of this program was to identify and evaluate the energy-saving modifications and design approaches that can be applied to residential gas-fired comfort heating and water heating systems. RD&D was identified so that any modification with a potential for improved efficiency at an economic cost could be brought rapidly to the marketplace.

The first task was to develop the details of the program. The next six tasks, as shown in Figure A-1 with the original task numbers from the proposal indicated, are discussed below.

Following the development of the program plan (Task 1), the information resulting from Tasks 2, 3, and 4 were developed as independent entities. Reports on these tasks are presented in Appendices B, C, and D. The results were then combined in Task 5 to produce a listing of concepts that could lead to improved efficiency of fuel utilization. Further concepts were added as a result of group review sessions. Finally, in Task 5, the concepts were evaluated from a savings, cost point of view. Concepts with a potential payback period of four years or less were delineated. These results are reported in Appendix E. Parallel to these tasks, two analyses were made of institutional barriers, considering non-safety (Appendix G) and safety (Appendix F) aspects separately. The safety considerations were applied to the specific energy saving concepts.

As a final step in the program, the concepts with a potential payback period of four years or less were considered from the point of view of the type of RD&D that would be required to bring them to market or eliminate them as contenders.

As an aid to estimating the level of research that might be justified, *in toto*, estimating procedures were worked out for total

Figure A-1. Relationship of tasks

potential energy and cost savings to homeowners by implementation of the contemplated improvements in efficiency. (Appendix H)

The individual task scopes and objectives are discussed below in more detail.

Task 2. Characterization of Present Gas
Warm-Air Furnaces, Hot Water and Steam Boilers,
and Hot-Water Systems

The objective was to report the present state of the art of furnaces, boilers, and water heaters through a review of about 30 different manufacturers' existing equipment; operating thermal efficiencies and projections of contemporary seasonal efficiencies were to be presented. The scope of this review included estimation/evaluation of present markets and projected markets for the future sale of this equipment by reviewing the statistical data of major concerned associations.

To achieve the objective of this task, the following steps were employed:

1. Review the design comments, pictures, and operating data of appliances used in the AGAL Research Project EP-1-23 (1978) wherein the following appliances were operated under well-adjusted and poorly adjusted conditions and their pollutant emissions measured:
 - a. Thirty-eight furnaces of 29 different manufacturers
 - b. Twenty hot water and steam boilers of 10 different manufacturers
 - c. Twenty-four water heaters of 12 different manufacturers
2. Obtain up-to-date information about appliance design and review the designs and operating data for typical representative furnaces, boilers and water heaters shown in the January, 1978, A.G.A. Directory of Certified Designs. Obtain data about steady-state thermal efficiency, burner design, heat exchanger design, pilots and controls. Review the following equipment:

- a. Twenty-one furnaces of 19 different manufacturers
 - b. Thirteen boilers of 12 different manufacturers
 - c. Thirteen water heaters of 7 different manufacturers
3. Obtain the steady-state thermal efficiency of installed furnaces from four different utilities and estimated seasonal efficiency of furnaces and boilers from a GAMA research project conducted at AGAL.
 4. Obtain market and market projection information from the Statistical Department of American Gas Association, Gas Appliance Manufacturers Association, and Appliance Manufacturer
 5. Obtain information from the gas industries Space Heating Efficiency Improvement Program (SHEIP)
 6. Obtain furnace venting information from a review of previous AGAL research, Gas Vent Institute, and acknowledged experts.

The results of this task are reported in Appendix B.

Task 3. Search and Analysis of Literature Since 1945

The objective of this task was to determine what new and reportedly more efficient concepts in burner design, heat exchanger design, and appliance design have appeared in the literature since 1945. Proceedings and minutes of specialized industry meetings and seminars were reviewed for information, in addition to the normal search of the periodical literature. Patents were reviewed, especially the specialized records of patents of some trade associations.

The following sources of information were to be searched for new and/or improved concepts in gas-fired appliances (furnaces, boilers, and water heaters):

1. AGAL files
2. A.G.A. Research and Utilization Conference Papers (1945-1955)
3. A.G.A. Research, Utilization and Marketing Conference Papers (1956-1968)
4. Conference on Natural Gas Research & Technology (1971-1974)
5. A.G.A. Operating Section Conference Papers
6. Appliance Manufacturer's "Appliance Conferences"
7. American Society of Gas Engineers (ASGE) Annual Meeting Technical Papers
8. ASHRAE Papers
9. Gas Abstracts
10. Periodical Literature
11. GAMA Patent Digest
12. Others.

The results of this task are reported in Appendix C.

Task 4. Industrial Contact Survey for Current Plans
and Ideas of Manufacturing, Utilities, and
Trade Organizations

The objective of this task was to obtain information not appearing in the technical literature about potential design and efficiency improvements in furnaces, boilers, and water heaters. This was accomplished by interviewing the technical directors of major concerned organizations, e.g., Gas Appliance Manufacturers Association, Association of Home Appliance Manufacturers, and American Society of Gas Engineers. Gas utilities which are known to conduct a separate research program were interviewed. Examples of the latter are Southern California Gas, Columbia Gas System Service Corporation, Consolidated Gas System Services Corporation, and Northern Illinois Gas. Selected manufacturers identified as candidates for information which might not appear in the technical literature were contacted and interviewed. These include the following manufacturers known to have conducted research or have a laboratory facility:

Warm Air Furnaces

1. York Corporation
2. Amana Refrigeration, Inc.
3. Rheem Manufacturing Co.
4. Carrier Corporation
5. Lennox Industries, Inc.
6. Luxaire, Inc.
7. Tappan Company

Hot Water and Steam Boilers

1. A. O. Smith Corporation
2. Burnham Corporation
3. Weil McLain

Hot Water Heaters

1. A. O. Smith Corporation
2. State Industries, Inc.
3. Rheem Manufacturing Company

The results of this task are reported in Appendix D.

Task 5. Concept Characterization and Generalization, Technical and Economic Evaluation

The purpose of this task was to consolidate and analyze the results of Tasks 2, 3, and 4. Specifically, meetings were held between the AGAL team and the BCL team to exchange information and formulate new concepts. As an aid in concept characterization, and to fill in possible gaps in concepts, several brainstorming sessions were held using BCL staff members.

The various concepts were considered from the standpoint of not only change in efficiency of operation, but first cost, reliability, and safety. Possible changes in pollution level and other possible benefits or disadvantages were also considered. A gross cost-benefit analysis was conducted for each significant design concept. Reasons for the failure of any particular design concept to reach the market and its potential were evaluated.

The results of this task are reported in Appendix E.

Task 6. Recommendation for Research, Development,
and Demonstration

The purpose of this task was to prepare an ordered list of research, development, and demonstration projects that could lead to commercialization of the energy effective modifications in a minimum of cost and time.

Each concept modification in its various forms was considered on the basis of cost, benefits, potential market, and time to market. The MOPPS scenario was used for the gas supply. To carry out this Task, estimates were made of the manufacturing cost, the installation cost, the maintenance cost, as well as the energy savings. Within the cost and time scope of the project, it is not possible to make detailed analyses. However, sufficient estimates were made to order the priorities of research, development, and demonstration on the various concepts and to eliminate those which would not be cost effective.

The results of the analyses for this task are reported in the main body of the report. The details of these cost estimates are reported as part of Task 5, Appendix E.

Task 7a. Institutional Barriers Related to Safety

The purpose of the task was to pinpoint the safety and environmental problems related to various concepts found to be energy and cost effective in Task 4. The results of the task are reported in Appendix F.

Task 7b. Institutional Barriers Other Than Safety

The purpose of this task was to anticipate the problems of commercialization (other than safety) of the various concepts shown to be energy and cost effective in Task 4. These problems include not only the various positive and negative incentives to manufacturers in the current economy, but other barriers which can be even more difficult to overcome. For example, there is often a public-reaction aspect to getting an acceptance

of any real or apparent change in energy-related areas. As a result, realistic estimates, considering public reaction, of the probability of obtaining necessary code changes were also made.

The results of this task are reported in Appendix G.

APPENDIX B

CHARACTERIZATION OF PRESENT GAS WARM-AIR
FURNACES AND HOT-WATER SYSTEMS

APPENDIX B

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	41
CONSTRUCTION DETAILS OF CURRENT EQUIPMENT.	41
Furnace Survey Results.	41
Burner Design.	43
Heat Exchanger Design.	47
Venting System Design.	49
Circulating-Air System Design.	51
Control System Application	55
Boiler Survey Results	57
Burner Design.	59
Heat Exchanger Design.	60
Venting System Design.	61
Control System	62
Domestic Water Heater Survey Results.	62
Burner Design.	63
Heat Exchanger Design.	65
Venting System Design.	67
Control System Design.	68
Performance of Current Equipment.	68
Efficiency	68
Emission Performance	75
REFERENCES	83

APPENDIX B

LIST OF TABLES

		<u>Page</u>
Table B-1.	Summary of Burner Types Used in the 21 Furnaces Studied.	46
Table B-2.	Summary of the Heat-Exchanger Designs Used in the 21 Furnaces Studied.	49
Table B-3.	Summary of Venting System Designs of 21 Furnaces Studied.	51
Table B-4.	Circulating Air System Design of the 21 Furnaces Studied.	54
Table B-5.	Summary of Burner Types Used in the 13 Boilers Studied	59
Table B-6.	Summary of Heat-Exchanger Designs Used in 13 Boiler Samples.	60
Table B-7.	Summary of Venting Systems for 13 Boiler Samples.	61
Table B-8.	Summary of Burner Types Used in the 13 Water Heaters Studied	65
Table B-9.	Summary of Tank Designs for 13 Water- Heater Samples.	67
Table B-10.	Summary of Venting Systems for 13 Water- Heater Samples.	67
Table B-11.	Forced-Air Furnace Emissions.	77
Table B-12.	Hot-Water Boiler Emission Results	79
Table B-13.	Steam Boiler Emission Results	80
Table B-14.	Hot-Water Heater Emissions.	81

APPENDIX B

LIST OF FIGURES

	<u>Page</u>
Figure B-1. Components of Typical Gas Forced-Air Furnace with Sectional Heat Exchanger.	42
Figure B-2. View of Typical Gas-Fired Burners.	44
Figure B-3. Identification of Primary and Secondary Combustion Air	44
Figure B-4. Pictures of the Two Major Types of Furnace Heat Exchangers,	48
Figure B-5. Cross Section of Different Types of Forced-Air Furnaces.	53
Figure B-6. Typical Components of a Gas Hot-Water Boiler	58
Figure B-7. Components of a Typical Gas Hot-Water Heater	64
Figure B-8. Control and Burner Components of a Gas Hot-Water Heater	70
Figure B-9. Energy Partitioning for Typical Gas-Fired Central Heating System (Including Burners and Boilers)	71
Figure B-10. Energy Partitioning for a Typical Gas-Fired Domestic Hot-Water Heater.	71
Figure B-11. Definition of Thermal Losses Associated With Combustion Heating Systems.	72

APPENDIX B

CHARACTERIZATION OF PRESENT GAS WARM-AIR FURNACES AND HOT-WATER SYSTEMS

INTRODUCTION

This appendix is divided into two parts, covering separately the construction details of currently available heating units and the performance of currently available heating units. In each part, furnaces, boilers, and hot-water heaters are considered separately.

CONSTRUCTION DETAILS OF CURRENT EQUIPMENT

Furnace Survey Results

Many types of central heating furnaces exist and are sold annually. This survey has been limited to those furnaces that share the larger portion of the market, being forced-air upflow, counterflow and basement-type central furnaces. The range of fuel gas input of the 21 furnaces representing 19 major furnace manufacturers ranged from a low of 80,000 Btu/hr to a high of 150,000 Btu/hr. The average input of the sample was about 105,000 Btu/hr. (This range was selected because it represents the majority of units currently being sold.)

The survey of these furnaces followed two related paths, the first being an analysis of the physical construction of the appliances. The second is a study of the operation and performance efficiency of the appliances, both actual and projected, as evaluated by the manufacturer, the utilities, and American Gas Association Laboratories (A.G.A.L.). A typical forced-air furnace is shown in Figure B-1.

Figure B-1. Components of typical gas forced-air furnace with sectional heat exchanger

Burner Design

Several types of burners are currently available for use in gas-fired central furnaces. The application of certain types of burners is generally dictated by the design of the heat exchanger being used. As an example, circular cast-iron drilled-port-type burners are most commonly found in furnaces employing a drum-type heat exchanger while stamped steel burners are used in furnaces designed with sectional-type heat exchangers. The following is a synopsis of the state-of-the-art burners available for domestic central-heating applications. Figure B-2 shows some typical burners. Atmospheric-type burners are used almost exclusively with primary and secondary air (see Figure B-3) naturally mixed with fuel. Most burners provide means for adjusting the amount of primary air.

Multiport Burners. As the name "multiport" implies, these burners have more than one opening through which the air/gas mixture passes into the combustion area. Multiport burners are generally either cast iron with drilled ports, or formed steel with stamped or ribbon ports, although other alloys, materials, and fabricating methods may be used. These burners are generally used as multiple units, each of a lower individual input (usually less than 40,000 Btu/hr-burner), manifolded together to achieve the desired appliance fuel-gas input rate.

Drilled-Port Burners. Drilled-port burners are almost exclusively made of cast iron. The burner is either circular or tubular in shape, both having numerous ports machined (drilled) through the surface. The circular-type burners are used in large single-chamber heat exchangers while the tubular burners are used with multi-sectioned heat exchangers.

Stamped Burners. Stamped burners may be fabricated from a variety of iron-metal alloys; however, the most common material is low-carbon steel. The burner ports are stamped in rows, either laterally or longitudinally across the top surface. The burner body is constructed from two stamped sections crimped or seam-welded together.

Drilled Multiport Burner

Stamped Steel Burner

Ribbon Burner

Single-Port Upshot Burner

Figure B-2. View of typical gas-fired burners

Figure B-3. Identification of primary and secondary combustion air

Ribbon-Port Burners. Ribbon-port burner bodies are similar to the cast iron and stamped-type burner bodies, depending upon the material used in fabrication. The difference between the types is the actual port structure. The ribbon-port burner has an opening (circular or rectangular depending upon burner geometry) in which a finely corrugated metal "ribbon" is inserted. This ribbon opening generally is the same length as the row of stamped or drilled ports of the burner's counterpart, and openings on the ribbon serve as burner ports.

Single-Port Burners. Single-port burners have a single opening through which the burning air/gas mixture enters the combustion area. This opening is generally large to accommodate the higher port loading required of the burner. Usually a single-port burner is used in conjunction with a flame spreader. The fuel gas input rate may vary from inputs of 40,000 Btu/hr per burner to higher than 150,000 Btu/hr per burner. Single-port burners may be cast iron, steel alloy, or a combination of both.

Single-port upshot burners are usually steel alloy fabricated tubes, directing the air/gas mixture vertically into the combustion area. The diameter of the tube is consistent with the fuel input rate and aeration requirement. A disc-type flame spreader is generally found several inches above the burner, offering flow restriction for the combustion products directing them toward the heat-exchanger surfaces, hence increasing the heat-exchanger efficiency. This type of burner design necessitates the use of a single-section or drum-type heat exchanger.

Single-port inshot burners are most often found in sectional-type heat-exchanger appliances. Their construction is basically similar to the upshot burner except that the tube is not oriented vertically, but at an angle above the horizontal. General application excludes the use of a flame spreader, allowing the reduced cross-sectional area of the heat-exchanger section to channel the flame for better heat-exchanger efficiency.

The single-port ring burner is a cast iron or combination cast iron-steel alloy ring burner which has a continuous vertical opening around the vertical periphery of the burner head. The air/gas mixture exits the burner at a horizontal angle, then spreads itself upwards. The disc part of the

burner acts as a built-in flame spreader, guiding the combustion products to the heat-exchanger walls. The single-port ring burner is designed for use in drum-type heat-exchanger appliances.

Power Burners. A power burner is a single-port or multiport burner through which the air/gas mixture is supplied to the combustion chamber at greater than atmospheric pressure. The construction of the burner is similar to those previously discussed, except primary aeration is supplied by an electrically powered mixing blower. Power burners are primarily designed for use with drum-type heat-exchanger appliances. One unique application of power burner design, however, involves a very compact combustion chamber through which a finned coil carries a heat-transfer fluid. None of the residential gas-fired central furnaces examined used power burners in their combustion systems. Power burners are most common in oil-fired equipment.

Multi-Rate Burners. Multiple-rate burners are those designed for use with a control system capable of delivering a variable input rate. The actual burner design spans the range of burners previously mentioned, with the ports and input being sized to accommodate the time variant fuel-gas input rate. Multiple-rate burners are used primarily in central furnaces designed for a higher than average maximum fuel-gas input rate, thus adding to the versatility of the appliance.

TABLE B-1. SUMMARY OF BURNER TYPES USED IN THE 21 FURNACES STUDIED

Burner Type				Single Input Rate	Multiple Rate*
Multiport		Single Port			
Steel Alloy	Cast Iron	Inshot	Upshot		
81%	9%	5%	5%	81%	19%
Average port loading for multiport:				232 Btu/hr-port	
Average port loading for single port:				67,500 Btu/hr-port	

* Percentage of burners designed for multiple rate input

Heat-Exchanger Design

There are currently two types of heat exchangers used in the construction of residential forced-air furnaces. The first is the sectional heat exchanger and the other is the drum-type heat exchanger (see Figure B-4).

Sectional Heat Exchanger. Also called a "clam shell", the sectional heat exchanger is fabricated from a steel alloy by joining two symmetrical halves. These halves are seam-welded together into a section, forming a leak-proof bond. The section can have a full bottom which encloses the burner, or may be open covering a separate burner tray. Near the top front of each section is an opening which allows the passage of flue gases into the draft hood. The individual sections are generally somewhat rectangular in cross section through the three planes and have a height-to-width ratio between 6 and 7. Heat transfer ribs, dimples and curves are stamped into the section halves before fabrication. Depending upon the designed fuel-gas input rate of the appliance, one or more sections may be joined together by a connection member.

The material used in the construction of sectional-type heat exchangers is usually a heavier thickness (.0625 to .050 in.) or a lighter thickness (.0500 to .0375 in.) aluminum or chromium alloy steel. The gage and type of material employed are consistent with the burner input rate per section, thus promoting the useful life of the appliance.

Drum-Type Heat Exchanger. The drum-type heat exchanger usually consists of two concentric sections. The outer section is a right regular cylinder with "doughnut" lateral cross section. The inner section is a complete right regular cylinder connected to the outer section by one or more open tubes. The outer section is the secondary heat exchanger, while the inner section, containing the single burner, is the primary heat exchanger. The typical arrangement of the two sections allows ample open space for circulating air wipe.

Drum Type

Sectional Type

Figure B-4. Pictures of the two major types of furnace heat exchangers

Internal flue gas retention is accomplished by the diameter of the connecting tubes between the primary and secondary heat exchangers. Due to the heavy gage material, surface ribbing is not generally employed as an aid for heat transfer to the circulating air.

The low carbon steel heat-exchanger sections and tubes are welded together forming a tightly sealed "drum". Openings for the burner, flue gas exhaust and usually a cleanout port are provided. This type of heat exchanger is of heavier thickness steel than the sectional type, and it is sometimes fabricated as a casting. The drum-type heat exchanger has a larger residual heat retention time than does other types, because of its higher mass.

Special-Type Heat Exchangers. One manufacturer makes a coffee-can size heat exchanger that utilizes an intermediate heat-transfer fluid. The heat exchanger consists of a packed bed of beads with small diameter tubes passing through the bed through which the intermediate fluid passes.

TABLE B-2. SUMMARY OF THE HEAT-EXCHANGER DESIGNS
USED IN THE 21 FURNACES STUDIED

Heat- Exchanger Type		Material		Thickness				Loading, Btu/hr-in ²		
Sect.	Drum	Low Carbon Steel	Alum. Steel	<.0625	.0625	.0500	.0375	<25	25-30	>30
90%	10%	90%	10%	5%	10%	75%	10%	5%	84%	11%

Venting System Design

The venting system is the part of the appliance which carries the combustion products from the furnace and discharges them outside of the home or heated area.

In addition to the two types of venting systems, the design of the venting system of the appliance may be enhanced to increase flue-gas residence time by the use of baffles. Baffles are generally strips of metal

usually flat or "V" shaped that are inserted into the flue outlet of the heat exchanger immediately before the draft hood entrance. In place of or in addition to baffles, a strip of metal partially blocking the heat exchanger flue outlet may be added. This piece is called a restrictor and, like the baffle, its function is to control the amount of excess-air flow through the heat exchanger to improve its seasonal efficiency.

Gravity Venting. Gravity venting systems (far and away the most prevalent) are those which rely solely on the buoyancy of the combustion products in the surrounding air for venting. The buoyant action caused by the higher flue gas temperatures causes the stream of gases to rise up the vent (chimney) system and exit the home. This effect also carries quantities of cooler room air into the flow. This process dilutes the flue gases with respect to both constituents and temperature; thus the limit of dilution has to be controlled in order to maintain effective venting. In order to establish and maintain adequate venting, certain amounts of the flue gas heat is used to create the buoyancy effect. Usually about 15 to 20 percent of the fuel energy is used to vent flue gases.

Dilution of the flue gases is accomplished by a part of the appliance known as the draft hood. Usually the draft hood is a rectangular box with three openings: one for the flue gas entrance, one for the room air entrance, and one for the diluted products to exit to the vent system. The discharge of the diluted products may be vertical or horizontal, so long as the connecting flue pipe maintains a vertical rise. The draft hood may be built into the appliance or it may be externally connected.

The draft hood dilution room air generally can amount to 1.4 times the total flue gas volume.

Power Venting. Power, or induced, exhaust employs a small electrical motor connected to a blower to vent the products from the combustion area. This construction warrants the necessity of much tighter construction tolerances due to the positive pressure (higher than surrounding environment) generated in the venting system. The design of the systems negates the usage of a draft hood; thus no room air dilution is employed. The draft air flow

is sized with respect to the fuel gas input rate since the major source of venting air is drawn from the burner secondary air paths. The blower sizing and speed of rotation are, thus, critical with regard to the desired fuel-gas burning rate. The use of induced-draft-type systems can improve both the steady state and seasonal efficiency of an appliance.

Power exhaust venting systems are primarily used on outdoor-type forced-air furnaces in combination with air conditioning. None of the appliances in this survey utilized a power exhaust venting system.

Direct Vent Systems (sealed combustion). Direct vent systems are designed for integral venting, and draw combustion air from an outside opening adjacent to the vent outlet. If the two openings are concentric, the vent system is referred to as balanced. If the two openings are located at different elevations, the system is referred to as unbalanced. Both systems have been successfully applied to furnaces, mobile home heaters, water heaters, and boilers.

TABLE B-3. SUMMARY OF VENTING SYSTEM DESIGNS OF 21 FURNACES STUDIED

Vent Type	Outlet Size			Outlet Size Diameter					Baffle Type			
	Diameter											
Built-In Vertical Discharge	4"	5"	6"	<4000	4-5000	5-6000	6-7000	>7000	Flat	"V"	Rest.	Both
100%	38%	48%	14%	5%	10%	18%	62%	5%	38%	38%	5%	19%

Circulating-Air System Design

The circulating-air system is the part of the appliance which moves the circulating air across the heat exchanger and supplies it to the room load. All forced-air circulating-air systems contain a blower assembly consisting of a blower wheel, a housing, and a motor drive for the wheel.

The drive may be coupled directly to the blower wheel by a common shaft, or it may be attached by means of a drive belt and pulley combination. The desired blower wheel velocity is achieved by adjusting the pulley ratio on the belt drive, or changing motor speed on the direct drive system. All of the appliance compartments containing the blower housings are sealed to minimize interference with the combustion air supplied to the burners. Duct work for cold-air return is connected to the inlet of the blower housing, thus isolating the circulating air supply from the immediate environment of the appliance installation.

The various sizes of blower wheels, motor power, and fuel-gas input has made a ready comparison of circulating-air systems difficult. An analysis of the data from the sample allowed the formulation of a circulation factor, defined as follows:

$$CF = \frac{E_m \times V}{E_G} \times 2545$$

where

CF = Circulation Factor

E_m = Horsepower of blower motor

V = Volume of blower wheel

E_G = Fuel-gas input rate in Btu/hr

2545 = A units conversion factor (1 HP = 2545 Btu/hr).

Application of this formula is found in Table B-4.

Four basic types of circulating-air systems are being used in residential forced-air furnaces. These are: upflow forced air, downflow forced air, horizontal-flow forced air, and basement-type forced air furnaces where the blower is located next to the heat exchanger and the air outlet is upflow (see Figure B-5).

Upflow Forced-Air Circulating System. The upflow-type forced-air system draws the circulating air in through the base of the appliance and forces it vertically upwards around the longitudinal surface of the heat exchanger. The warm air thus produced is supplied to the warm-air plenum mounted on top of the unit. The flow of the circulating air stream is parallel to the flow of the combustion gases.

DOWNFLOW OR COUNTER FLOW FORCED-AIR

HIGH-BOY OR UPFLOW FORCED-AIR FURNACE

HORIZONTAL FORCED-AIR FURNACE

LOW-BOY FORCED-AIR FURNACE

Figure B-5. Cross section of different types of forced-air furnaces

Downflow Forced-Air Circulating System. The downflow forced-air system draws the circulating air in through the top of the appliance where the blower compartment is located. The blower sits directly above the heat-exchanger sections, forcing the return air vertically downward. This arrangement results in circulating air movement in the opposite direction of the combustion product flow. The result is a preheating of the circulating air before it arrives at the hotter areas of the heat exchanger. The warm air is discharged through a plenum mounted on the base of the appliance. Downflow forced-air circulating systems have a slightly higher steady-state thermal efficiency than other conventional types of circulating systems and the upper areas of the heat exchanger tend to operate at cooler temperatures.

Horizontal Forced-Air Circulating System. The horizontal forced-air system is employed on appliances for installation in areas where vertical space is at a premium, such as attics and crawlspaces. As the title implies, the circulating air flow is in the horizontal plane. The blower compartment is to the rear of the heat exchanger sections while the warm air plenum is at the front. The circulating air flow is in a direction perpendicular to the path of the flue gases.

Basement-Type Forced-Air Circulating System. The basement-type forced-air system is similar to the upflow system. The primary differences are that (1) the blower is mounted in a compartment behind the heat exchanger, forcing the air into the heat exchanger area on a horizontal plane, and (2) the flue pipe is connected to a pipe which runs through the blower compartment preheating the circulating air. The plenum connection to the furnace is the same as an upflow furnace.

TABLE B-4. CIRCULATING AIR SYSTEM DESIGN OF THE 21 FURNACES STUDIED

Type of System			Circulation Factor (in ³)		
Upflow	Downflow	Basement	<3.5	3.5-4.5	>4.5
81%	14%	5%	10%	62%	28%
Average outlet plenum loading: 235 Btu/hr-in ²					

Control System Application

The control system is the part of the appliance that reacts to the environment in a pre-programmed manner. Their function includes not only igniting the main burner, but also monitoring circulating air temperature, starting and stopping the circulating air blower, monitoring the living quarter temperature, and even adjusting the fuel-gas input rate to be consistent with the outside temperature.

The control system of central furnaces can be grouped into two areas, the gas control system and the electrical control system.

Gas Control System. The gas control system for a central furnace consists of a main gas valve, a pressure regulator, and an automatic pilot valve or ignition device. The Automatic Main Control Valve is generally a combination of the three central components. By far the most widely used gas control system is the combination control with a continuous standing pilot. One hundred percent of the sample used the combination control and continuous standing pilot for gas control and ignition. Alternatives to this method are the electronic Intermittent Ignition Device (IID) and the Interrupted Ignition System (Direct Spark Ignition or DSI) which are becoming more popular with the increasing impetus placed on natural gas energy conservation.

The DSI system utilizes an electronic module to monitor and ignite the burner directly with a high voltage spark gap. The spark is de-energized once ignition has been verified by the control module. The IID uses an electronic module to ignite a standing pilot which in turn ignites the main burner. The pilot remains lighted and is extinguished only when the call for heat is satisfied. These systems have potential for significant energy savings, but can add a significant cost factor to the appliance.

The predominantly used standing gas pilot incorporates a pilot burner and a pilot generator (or thermocouple). The thermocouple is heated by the pilot burner and generates sufficient electrical power to maintain open the automatic pilot valve. If the pilot flame becomes extinguished,

gas cannot flow to the main burner. This safety feature insures that an ignition flame is present before gas can flow to the main burner.

Used in conjunction with the multiple rate burner is the modulating gas valve. This valve has the capability of supplying fuel gas to the burner manifold at varying input rates which are usually a function of outdoor temperature. The modulating valve is generally a two-stage valve with high and low fire input rates. The different rates are controlled by integral separate pressure regulators adjusted to supply different fuel gas rates. The low fire rate is usually employed at times when the outdoor conditions do not warrant a full heating supply input to compensate for building energy losses.

Electrical Control System. Forced-air furnaces generally use a combination fan/high temperature limit control. This is a bimetal strip wound in helical form which pivots about an axle when heated. The axle is connected to one or more adjustable micro-switches which control a gas valve to prevent overheating of the furnace in the case of an inoperative blower. Contemporary controls are set to shut off the gas if the outlet circulating air temperature reaches 200 F. The temperature at which the circulating blower energizes or de-energizes can also be controlled by the fan high limit control. The control is usually set to turn on the blower at a temperature of 120-130 F and turn it off at 90-100 F. The furnaces in the sample all used a combination fan/limit control.

Timer-operated fan controls are also available. These are bimetal switches which close upon heating. A heater element is energized when the main burners ignite, and after a pre-selected time interval, the blower is turned on.

Snap-disc-type limits are occasionally used for the fan and limit control function. Snap discs are bimetal switches exposed to the circulating air stream. When the air exceeds a pre-determined temperature, the disc opens or closes the switch.

Counter-flow and horizontal-flow forced-air furnaces use a snap disc limit as an auxiliary control in the blower compartment as a safety feature guarding against blower malfunction.

Vent Dampers. Another control device that is becoming more and more popular as an accessory to central heating appliances is the automatic vent damper. The automatic vent damper is an electrically, thermally, or mechanically operated apparatus that shuts off the flow of heated room air through the venting system during the off cycle. The electrically actuated version usually is a vane resembling a butterfly valve, which is pivoted through 90 degrees from the opened position to the closed position. The automatic vent damper is controlled by an electronic logic circuit which prohibits closure of the vane during the appliance on-cycle for safety purposes. This device interrupts the natural off-cycle stack action, thus saving the burden of reheating room air for venting purposes. Also somewhat significant is that the heat exchanger cool-down time is slightly increased, due to the reduced flow of cooler air through the off-cycle combustion systems. Most major manufacturers now have a model that includes an electrically actuated vent damper.

Boiler Survey Results

Central heating boilers are a viable alternative to residential central forced-air furnaces when central air conditioning is not readily desired as part of the installation. Two types of central heating boilers are sold for residential installation. The first is a low pressure hot water heating boiler and the other is a low pressure steam heating boiler. The basic construction of these units is similar; the differences are not noticeable to the consumer.

The fuel gas input range of the 13 central heating boiler designs of 12 major boiler manufacturers ranged from a low of 55,000 Btu/hr to a high of 420,000 Btu/hr, with the average being 142,000 Btu/hr. (The 420,000 Btu/hr input appliance was desired in order to examine a unique heat-exchanger design. The average input of the sample without inclusion of the 420,000 Btu/hr appliance was 120,000 Btu/hr.)

All of the boilers examined except the 420,000 Btu/hr appliance were convertible between hot water or steam depending upon the control train used. A typical central heating boiler is shown in Figure B-6.

Figure B-6. Typical components of a gas hot-water boiler

A hot water heating boiler is an appliance that heats water to about 180 F and circulates it through insulated pipes to the radiators located in the heated area. Water circulation is usually augmented by an electric pump.

The central steam heating boiler is identical in construction to its hot water heating boiler counterpart except for the control system. As the name implies, a central heating steam boiler generates steam for supply through the insulated heating pipes to the heated space radiators. The steam quality, that is, concentration of steam versus water, leaving the boiler must be in excess of 97 percent. The circulation of the steam through the piping is accomplished by the positive pressure (less than 15 psig) of the steam generated in the boiler. Residential steam boilers do not allow internal steam pressures in excess of 15 psig which corresponds to 250 F.

Burner Design

The burners for use in central heating steam and hot water boilers are essentially identical in design to those described in the Central Furnace section of this report. Three types of burners were used by the 12 manufacturers of the 13 boilers studied: multiport steel stamped, multiport cast iron drilled, and single port steel upshot with flame spreaders. A summary of these applications is found in Table B-5.

TABLE B-5. SUMMARY OF BURNER TYPES USED IN THE 13 BOILERS STUDIED

Burner Type			
Multiport		Single Port Upshot	
Steel Alloy	Cast Iron	Cast Iron	Multiple Rate
46%	38%	16%	0%
Average port loading for multiport*: 224.5 Btu/hr-port			
Average port loading for single port: 112,500 Btu/hr-port			

* Excluding 420,000 Btu/hr appliance with port loading, ~1500 Btu/hr-port

Heat Exchanger Design

The majority of hot water and steam heating boilers use a cast-iron sectional-type heat exchanger with multiport tubular burners. The sections are identical in design to each other and are ganged together in order to achieve the desired appliance fuel gas input rating. The sections are massive, accomplishing heat transfer by method of combustion gas impingement on the bottom of the section and flue gas contact with baffling pins cast into the heat exchanger walls. The cold water is fed into the bottom of the heat exchanger while the hot water leaves the top of the section.

Drum-type heat exchangers are also used, being basically a right regular cylinder combustion chamber with multiple flue passageways above the main chamber through which the flue gases pass. The design of drum-type heat exchangers precludes the use of cast iron; thus heavy gage welded steel alloy is most frequently used. Heat transfer is accomplished by combustion product impingement on the drum bottom and circulation of flue products through the flue passages. Spiral baffling is generally utilized to increase the heat transfer ability of the tubes.

A unique heating boiler design involves the use of coiled copper tubing and a finned-tube heat exchanger. The volume of water contained in the boiler is relatively small, but the high water throughput allows for extremely high input rates. The design is basically an instantaneous hot-water heating system that is not convertible to steam generation.

TABLE B-6. SUMMARY OF HEAT-EXCHANGER DESIGNS
USED IN 13 BOILER SAMPLES

<u>Heat Exchanger Type</u>			<u>Material</u>			<u>Flue Passage Loading (Btu/in²)</u>		
			Cast Iron	Steel	Copper	<2000	2-3000	>3000
Sect.	Drum	Coil						
69%	23%	8%	84%	8%	8%	31%	46%	23%

Venting System Design

The venting system for a central heating boiler is similar in principle to the venting system of a forced-air central furnace. The major exceptions are generally the type of draft hood employed and the presence of a flue collector above the heat exchanger.

The draft hood most commonly used is a cone type, externally mounted, vertical discharge draft hood. The main body of the draft hood is the same diameter as the flue collector outlet. Near the top of the body is a skirt of about twice the diameter of the body which allows the room air to enter and dilute the combustion products. The distance between the skirt and the flue collector is an important dimension of the appliance construction for safety.

Built-in vertical-discharge draft hoods are also used, but only to a limited extent. This type is exactly the same as the vertical-discharge draft hood found in the forced-air central furnaces.

The flue collector is a large, heavy gage alloy steel box fitted over the heat exchanger sections. The function of the flue collector is to contain all of the flue products leaving the sections and channel them into the draft hood body. The flue collector is usually bolted and cemented to the heat exchanger sections.

TABLE B-7. SUMMARY OF VENTING SYSTEMS FOR 13 BOILER SAMPLES

Vent Type									Baffling Type		
Ext. Vert. Dis- charge	Built- In	Outlet Size, inches				Flue Loading (Btu/in ²)			Pins Only	Spiral Only	Pins and Restr.
		4	5	6	7	<4000	4-6000	>6000			
92%	8%	8%	31%	38%	23%	23%	62%	15%	8%	8%	84%

Control System

The ignition controls for central heating hot-water boilers are identical to those previously discussed in the central heating forced-air furnace results.

In place of furnace warm-air limits and circulating boiler controls, hydronic counterparts are used with boilers. A hot-water boiler will use an immersion-type hot-water limit which monitors the internal water temperature. The adjustable limit is usually set to interrupt the gas flow when the water temperature exceeds 180 F. In addition, a combination limit/circulator control may be used to control an electrically powered circulating pump.

A steam boiler will use a steam limit control, generally set at 250 F in conjunction with a low-water cut-off switch which interrupts the gas flow when the internal water level falls below the designed level.

Both the hot-water and steam-heating boilers utilize a pressure-relief valve which opens upon pressures exceeding the limits recommended by the manufacturer.

Automatic vent dampers may be employed either as an accessory or as an integral part of the appliance. Four of the units in the sample supplied automatic vent dampers as integral parts of the appliance. The construction and operation of vent dampers is discussed in the Central Furnace section of this report.

Domestic Water Heater Survey Results

Currently two basic types of domestic hot-water heaters are sold in the United States. The most popular by far is the storage-type water heater while the other is the instantaneous-type water heater. This survey is limited to the investigation of storage-type water heaters as there are no domestic manufacturers of instantaneous-type hot-water heaters.

By definition, a storage-type water heater stores the heated water in an insulated storage vessel awaiting the demand of the user. While in this standby mode, some heat is lost, necessitating at some time

the reheating of the stored water back to the desired delivery temperature. Once the heated water in the storage tank is depleted, the draw must be stopped in order to allow the water to recover to the desired temperature. If draw continues, the water will be supplied at less than the desired temperature.

An instantaneous water heater has very little storage capacity, but a fairly high fuel-gas input rate, thus allowing the water to be heated from the cooler inlet temperature to the higher outlet temperature in the time it takes the water to flow through the appliance. An instantaneous water heater, therefore, can supply an indefinite supply of domestic hot water.

A typical storage-type water heater is shown in Figure B-7.

Consistent with consumer requirements, the fuel-gas input range for the 13 water heaters examined was from 28,000 to 70,000 Btu/hr (average about 50,000 Btu/hr) while the storage capacity averaged about 41 gallons. Although many water heaters with various trade names are sold, the basic water heater for several distributors may be built by one manufacturer. The individual distributors may then impose cosmetic changes on the appliances consistent with their trade line. The 13 water heaters examined represent the most popular models of seven major water-heater manufacturers and included some "high efficiency models".

Burner Designs

A single multiport burner is almost exclusively used in the domestic storage water heater. The burner body is circular, emitting the flame in a ring from the periphery of the burner head. The flame leaves the burner horizontally, being directed into the heat-exchange surface by the buoyance of the combustion process.

Three basic types of multiport ring burners are currently employed in the manufacture of domestic hot-water heaters. The first type is made of stamped steel, the second has a cast-iron body with a stamped-steel burner head, and the third is cast iron with drilled ports. These burners are similar in principle to the multiport stamped-steel burner discussed in the furnace section of this report.

Figure B-7. Components of a typical gas hot-water heater

The second type is the target burner. This burner is similar to the type mentioned above except that the air/gas mixture tube is eliminated. Gas through an orifice impinges on the underside of the burner head. The gas stream is aerated in its passage to the burner head. This abrupt velocity change of the new air/gas stream at the target increases turbulence of the air/gas mixture and forces the air mixture out formed ports or a slot where combustion occurs. The underside of the burner head, thus, is a "target" for the air/gas stream. This burner type appears to be the least expensive construction method for water-heater burners.

A special type of burner is a combination main burner and standing pilot. This design uses the main burner ports as the pilot ports by reducing the gas input to the burner during the pilot-only mode. The main burner, thus, is always ignited, having a much smaller flame emanating from the ports when full input to the appliance is not desired. This burner is usually constructed of stainless steel. None of the water heaters in the sample used this type of burner. It has been reported that this burner type is limited in its ability to use gases other than natural, and, therefore, this burner type is no longer being made.

TABLE B-8. SUMMARY OF BURNER TYPES USED IN
THE 13 WATER HEATERS STUDIED

Burner Type		
Multiport		
Steel Alloy	Cast Iron	Cast Iron/Steel Alloy
46%	23%	31%
Average port loading: 1393 Btu/hr-port		

Heat Exchanger Design

The domestic storage hot-water heater employs a large cylindrical tank which doubles as a heat exchanger and a storage tank. The tank is generally a glass-lined heavy-gage-steel cylinder with a center flue

passageway. The tank is designed to withstand a 300-psig internal static pressure, about five times the normal operating requirement. The bottom of the tank is convex towards the flue passage to promote the flow of combustion products to the flueway. About 50 percent of heat transfer occurs at the bottom surface, the remaining heat is transferred in the flue passage which is generally the same diameter or slightly larger than the draft hood connection. A spiral-wound flue baffle is generally used in this flue passageway to promote heat transfer.

The tank has a cold-water inlet dip tube which forces the cold water to the bottom section of the tank. This allows the colder water to settle at the bottom without severely mixing with the warmer water at the top. Also, this permits the colder water to be heated first when the main burner is ignited.

Connections for hot-water outlet and pressure relief are provided as well as an anode rod. The anode is a magnesium rod immersed into the tank. The function of the anode rod is to be the target for corrosion rather than part of the tank. Generally, the anode rod has sufficient sacrificial material to delay internal tank corrosion beyond the normal life of the tank from other mechanisms.

The instantaneous-type domestic hot-water heater consists usually of a compact copper-coil heat exchanger coupled with a high-input-rate burner. The volume and flow rate of water in the water heater is such that it can be completely heated to the delivery temperature during the passage from the cold inlet side to the hot outlet side.

The longitudinal cross section of the coil assembly may show the coil orientation to be cylindrical helix or a conical helix, both with a center flue passage.

The heat-exchanger design dictates that the instantaneous-type water heater is a more compact unit than the storage-type water heater. This factor makes the instantaneous-type water heater a more attractive appliance when space is at a premium such as under countertops or in recreational vehicles. A disadvantage of the instantaneous-type water heater is the necessity to modulate the burner input, hence heat-exchanger efficiency, during periods of very low draw and the fact that the rated inputs are very large.

TABLE B-9. SUMMARY OF TANK DESIGNS FOR 13 WATER-HEATER SAMPLES

Tank Type	Tank Capacity, gallons					Dip Tube Material	
	20	30	40	75	100	Polysulfane	Polypropylene
Glass Lined/Center Flue							
100%	16%	31%	37%	8%	8%	31%	69%
Average input rate to capacity ratio: 1340 Btu/hr-gallon							

TABLE B-10. SUMMARY OF VENTING SYSTEMS FOR 13 WATER-HEATER SAMPLES

Diverter Type	Outlet Diameter			Loading (Btu/in ²)			
	3"	4"	5"	<4000	4-6000	6-7000	>7000
External Vertical Discharge							
100%	61%	31%	8%	23%	31%	38%	8%
Average outlet diameter to skirt height ratio: 0.42 ±1							

Venting System Design

The principles of venting that have been previously discussed in this report hold true for the domestic water heater. The method of flue dilution is similar to that used in central heating boilers. The draft diverter is located directly over the outer flue passageway. Sufficient clearance is allowed for adequate air flow from the room to dilute the flue products to the desired constituent concentrations and temperature. The diverter usually has an integral flue restrictor fabricated across the outlet to retard the flow of flue gases. This, coupled with a single spiral or corrugated baffle, promotes better heat transfer to the upper section of the tank while adequately supporting the venting process.

Control System Design

All of the domestic hot-water heaters in the sample used standing pilots as the means of main burner ignition. The potential of alternate methods of ignition were presented earlier in this report. Electric or electronic ignition devices are not used because studies have shown there is no energy savings by using these devices on water heaters.

Most domestic storage-type hot-water heaters utilize a combination thermostat and gas valve to control the stored water temperature. This device has a plastic-coated copper immersion probe which screws directly into the side of the tank. Since the action of the thermostat is mechanically coupled to the valve, no electrical requirement is necessary. A typical control system for a storage-type hot water heater is shown in Figure B-8.

The control for an instantaneous-type domestic water heater requires, in addition, a flow switch to detect the movement of water through the appliance. Once flow is detected, the main burner is energized, thus supplying hot water at the desired rate. Systems of modulating the fuel-gas input rate in proportion to the water-flow rate have been implemented, but have not become popular at this time.

Automatic vent dampers, as discussed in the Central Furnace section of this report, are becoming available for application on domestic storage-type hot-water heaters.

Performance of Current Equipment

Efficiency

There are two measures of the efficiency performance of a central heating system. One is the steady-state, test-stand, thermal efficiency of output divided by input. The other is the seasonal efficiency of useful heat provided the home, divided by total heating system consumption measured over an entire heating season. These two values differ due to the off-cycle losses of the appliance-home system which must be made up by the heating

system. Figure B-9 is a simplified energy partition for a typical 1977-78 model forced-air furnace or central heating boiler without a vent damper or IID. Figure B-10 is an energy partition for a typical 1977-78 model domestic storage-type hot-water heater, also without a vent damper or IID. These figures also assume a reasonably good installation. Figure B-11, from Bonne⁽¹⁾, shows a breakdown of the various ON and OFF cycle losses that influence the thermal and seasonal efficiency.

Most gas appliances are designed to meet the minimum requirements of the applicable American National Standards Institute standard for gas-fired appliances. Each standard has its own requirement for efficiency; however, most central heating equipment is required to have a steady-state thermal efficiency of at least 75 percent. The specific requirements for particular appliances are discussed in the designated sections elsewhere in this report.

In response to a questionnaire prepared for this project, 76 percent of the manufacturers of gas-fired space and domestic water heating equipment reported that the steady-state thermal efficiency of their equipment was within 75-77 percent. Eighty-four percent of the same group predicted that the thermal efficiency of these appliances would increase at least two percent in the next five years (52 percent predicted an increase of over four percent). The majority of the respondents indicated that the impetus for these predicted increases was attributed to anticipated Federal mandates requiring some form of aggregate efficiency increase. Only 16 percent attributed the stimulus to consumer demands with the rest stating the projected increase in appliance efficiency was in line with their current corporate goals.

Central Furnace Efficiency Performance. Most gas-fired central furnaces are designed to meet the minimum requirements of the American National Standard for Gas-Fired Gravity and Forced Air Central Furnaces, Z21.47.⁽²⁾ The current version of this standard requires that the steady-state thermal efficiency of a gravity furnace be 70 percent and that of a forced-air furnace be 75 percent. A review of the performance of 21 1977-78 model forced-air furnaces showed that the average thermal efficiency was between 75 and 79 percent. For gravity furnaces, the thermal

Figure B-8. Control and burner components of a gas hot-water heater

Figure B-9. Energy partitioning for typical gas-fired central heating system (including burners and boilers)

Figure B-10. Energy partitioning for a typical gas-fired domestic hot-water heater

- L_C - heat of combustion of flue combustibles
 L_W - uncondensed water
 L_N - sensible heat of CO_2 , H_2O , N_2 between T_F and T_O
 L_E - sensible heat of excess air between T_F and T_O
- GROUP I.
On-cycle flue losses
- L_D - sensible heat of comb. d. air between T_F and T_O
 L_P - sensible heat of purge air between T_F and T_1
- GROUP II.
Off-cycle flue losses
- L_A - sensible heat of comb. air between T_O and T_1
 L_{DA} - sensible heat of comb. d. air between T_O and T_1
 L_H - sensible heat of hood d. air between T_O and T_1
 L_M - heat of vaporization of water to humidify furnace air
- Group III.
Contribution of total furnace air to building infiltration.
- L_L - wasted part of pilot flame heat during the summer
 η_s^* - steady state lab efficiency $= 1 - L_C + L_W + L_N + L_E$
 η_G - steady state efficiency--off cycle losses $= \eta_s^* - (L_A + L_H + L_M)\phi$
 η_T - seasonal efficiency referenced to outdoor temp $= \eta_s - L_D - L_P - L_{DA} \phi$

Figure B-11. Definition of thermal losses associated with combustion heating systems

efficiency was between 70 and 74 percent. In response to a questionnaire sent to furnace manufacturers, 68 percent felt that the steady-state thermal efficiency of their forced-air furnaces was between 75 and 77 percent. Thus, it appears that the steady-state thermal efficiency of a typical 1977-78 forced-air furnace is about 75 percent. This includes a jacket loss of about 0.5-1.0 percent that contributes to heating the dwelling in the case of installations in heated spaces.

After the furnace is installed in a home, its thermal efficiency can be expected to change somewhat because it will be attached to a chimney or flue which may be from 12 to 30 feet high (the steady-state efficiency conducted according to the ANSI Z21.47 is run with five feet of stack). This additional stack will increase the excess air flow through the furnace and lower the thermal efficiency. Data obtained from three utilities⁽³⁾ who measured the thermal efficiency of 139 forced-air furnace installations showed the average thermal efficiency to be 75.00 percent with a standard deviation of 3.77 percent. The median efficiency from this group was 74.45 percent. These data indicate that there is only a small reduction in thermal efficiency due to the installation (and if the draft hood is properly designed, this is the expected result).

The seasonal efficiency of a furnace (which includes the factors shown in Figure B-11 can be characterized by a mathematical model such as that developed by Honeywell, or by a controlled laboratory test such as the test NBS has developed for DOE to estimate the annual average energy utilization efficiency (EFFYA) of a furnace. These two approaches would show the seasonal efficiency of a 1977-78 forced-air furnace to be about 60-65 percent. Personal habits of the occupants of a home and the characteristics of the house, however, can have a significant effect on this average efficiency. Excessive door opening, a leaky home, no insulation or storm doors and windows could reduce the seasonal efficiency to as low as 50 percent.

After conducting the DOE efficiency rating procedure in about 50 separate tests using 12 different furnaces including two boilers, the following results were obtained:

The Average Annual Energy Usage Efficiency (which is essentially a seasonal efficiency) was about 61 percent for upflow forced-air furnaces, about 66 percent for counterflow forced-air furnaces, and about 63 percent for boilers.

Central Heating Boiler Efficiency Performance. Like central furnaces, most central heating boilers are designed within the requirements of an ANSI standard. ANSI Z21.13, American National Standard for Gas-Fired Low Pressure Steam and Hot Water Boilers⁽⁴⁾, specifies that the steady-state thermal efficiency for a central heating boiler must be at least 75 percent.* The efficiency performance of 13 central heating boilers was examined and found to be between 75 and 78 percent. The response to the questionnaire indicated that 80 percent of the respondents felt their appliance efficiency was in the range of 75 to 77 percent. The average jacket loss for a central heating boiler is estimated to be in the range of less than two percent. The overall aggregate thermal efficiency of currently available central heating boilers is slightly higher than forced-air furnaces, being between 76 and 77 percent.

The Z21.13 steady-state thermal efficiency test for boilers, like the Z31.47 test, is also conducted with only five feet of vertical stack as a venting system. This situation is analagous to the one previously discussed for the central furnaces being connected to a considerably higher venting system. Although no utility field test data are readily available for application to central heating boilers, the contingency of severe updraft reduction of efficiency is partially alleviated by the fact that an adequately designed draft hood should prevent significant reduction in thermal efficiency. This speculation is born out in part by the DOE EFFYA test previously cited. Although the boiler test results are not a truly valid statistical sample, they tend towards supporting the other evidence and common venting system engineering design criteria.

As previously indicated in the DOE EFFYA test conducted, the seasonal efficiency of a central heating boiler system under the same loading conditions is slightly higher than a central upflow furnace heating system. This average seasonal efficiency was found to be 63 percent, versus 60 percent for the furnace system.

* Output ratings and efficiencies for two residential heating boilers traditionally have been based on the thermal energy delivered to the piping system and do not take credit for the jacket heat loss as a contribution to heating the dwelling.

Domestic Water-Heater Efficiency Performance. The minimum thermal efficiency for a domestic hot-water heater is not overtly specified by the applicable ANSI standard, Z31.10.1, American National Standard for Gas Water Heaters⁽⁵⁾. The thermal efficiency, or recovery efficiency, is a part of a minimum daily heat quota test, consisting of the recovery efficiency and standby loss. The overall daily heat quota requirement necessitates that the recovery efficiency be at least 70 percent for state-of-the-art storage vessel design. Sixty percent of the water heater manufacturers responding to the questionnaire indicated that they felt their equipment was 75-77 percent efficient (assumed recovery efficiency). Eighty percent of the same group predicted that in five years there would be at least a two percent increase in the efficiency rating of their appliance.

A. D. Little⁽⁶⁾ found that to supply the average daily household usage of hot water of 71.4 gallons heated through 85 F, it would require a daily input of 55,000 Btu to an ideal storage water heater, i.e., a water heater with 100 percent recovery efficiency and a 4,000 Btu minimum standby loss. The same supply requirements, when applied to the gas water heater, were found to be 102,000 Btu. This study indicates an average "seasonal" efficiency of about 54 percent for the hot-water storage system.

This seasonal efficiency range is in agreement with data taken from experimental seasonal efficiency test houses and computer modeling of the storage hot-water heating system.

Emission Performance

Current ANSI standard requirements for gas-fired central heating appliances and domestic hot-water heaters specify an allowable pollutant emission level for only one flue gas constituent: carbon monoxide. The maximum emission level of carbon monoxide is 400 parts per million in an air-free sample of the flue gases. Although being considered by Federal and State authorities, no standards for the emission of other pollutants has yet been promulgated (except for the proposed California NO_x emission standards for central heating equipment and water heaters).

The following four tables (B-11, B-12, B-13, B-14) present data on gaseous emissions for relatively recent forced-air furnaces, hot water and steam boilers, and domestic water heaters. These data were determined in an A.G.A./GRI sponsored research program on the analysis of the flue products from gas appliances. The purpose of the project was to determine the composition of the effluents from all categories of gas-fired appliances and the contribution of such effluents to air pollution, as well as to determine appliance design factors which significantly influence emission levels of appliances so as to provide information for minimizing emissions.

These tables show that the emissions of significance from an air pollution standpoint, for gas-fired appliances, are NO_x ($\text{NO} + \text{NO}_2$) and CO . Also shown is that water backed systems emit higher levels of NO_x than air backed systems because of the different rate of cooling of flue gases; that burner type has an influence on the NO_x emission by affecting the mixing of fuel, air and combustion products; and that out-of-adjustment (yellow flame) operation generally lowers the NO_x emission and increases the NO_2/NO ratio of the appliance burner.

Yellow flames may result in the field due to long use with minimal housecleaning, resulting in lint and dust accumulations that obstruct air flow. Yellow flames are generally cooler than blue flames and this results in a lower NO_x emission. The cooler conditions favor the formation of NO_2 , thus the higher NO_2/NO ratio under yellow flame conditions.

The appliances shown in these tables represent a majority of the manufacturers of certified appliance designs in each category. All those manufacturers listed in the A.G.A. Directory of Certified Appliances and Accessories were invited to submit appliances for study.

TABLE B-11. FORCED-AIR FURNACE EMISSIONS (7)

FAF #	Input Rate, Btu./Hr	Blue Flame Adjustment								Yellow Flame Adjustment								Burner				Heat Exchanger				FAF #
		Sample, Percent CO ₂	Percent Primary Air	(1) Δt °F	Flue Gas Concentration PPM, Air Free (2)				NO _x ** Emission Factor, (E.F.) lbs/10 ⁶ Btu	Sample, Percent CO ₂	Percent Primary Air	(1) Δt °F	Flue Gas Concentration PPM, Air Free (2)				NO _x ** Emission Factor, (E.F.) lbs/10 ⁶ Btu	Multi-port	Single Port		Other	Sectional	Drum	Other		
					CO	NO	NO ₂	-CHO					CO	NO	NO ₂	-CHO			Up-shot	In-shot						
1	103,000	6.90	45	66	5.4	78.38	5.65	---	0.090	7.15	39	66	450	69.30	10.94	---	0.084			X		X				1
2	102,500	5.75	69	82	30	95.52	6.26	---	0.109	5.80	48	82	715	82.76	5.48	---	0.094	X				X				2
3	134,000	6.90	49	85	17	86.37	7.86	---	0.098	7.00	39	87	264	74.38	9.17	---	0.087	X	I			X				3
4	82,500	6.85	62	68	75	85.86	12.89	---	0.102	7.00	42	68	236	72.05	12.81	---	0.088	X				X				4
5	103,000	6.50	59	82	18	98.14	4.32	---	0.106	6.80	39	84	284	89.56	6.51	---	0.099	X				X				5
6	98,000	4.95	57	90	12	102.91	2.16	---	0.108	5.05	30	86	252	89.39	10.55	---	0.103	X				X				6
7	103,000	5.20	45	60	12	111.69	3.58	0.12	0.119	5.50	23	60	183	81.97	11.26	0.44	0.096	X				X				7
8	99,500	6.00	46	63	16	111.18	6.94	0.33	0.122	6.10	23	61	283	88.62	9.82	---	0.101	X				X				8
9	98,900	5.10	53	74	12	81.04	1.65	0.43	0.085	5.30	15	72	512	39.35	14.11	1.13	0.055		X				X			9
10	103,000	5.45	51	67	11	64.53	4.21	0.10	0.071	5.70	33	65	467	54.46	11.14	0.53	0.068			X		X				10
11	179,400	4.25	49	55	14	105.46	3.61	0.08	0.113	4.25	22	56	133	97.53	8.47	0.56	0.109	X				X				11
12	121,500	6.20	50	89	6	89.36	3.39	0.12	0.099	6.40	31	89	469	55.93	11.44	0.83	0.072		X	I			X			12
13	101,500	5.70	59	83	17	89.52	2.46	0.30	0.099	5.90	25	80	39	92.26	5.37	0.60	0.105	X				X				13
14	103,000	5.90	63	74	20	76.12	2.79	0.53	0.080	5.65	20	77	255	74.78	12.36	3.07	0.091	X	I			X				14
15	137,000	3.75	55	88	22	76.51	2.78	0.05	0.086	4.20	25	93	529	32.74	21.46	1.02	0.058			X	I		X	I		15
16	126,600	5.40	39	55	1.0	58.71	2.40	0.07	0.064	6.05	18	61	20	66.39	7.00	0.17	0.079				X	I(3)	X			16
17	104,600	5.45	51	63	2.8	107.63	4.34	0.13	0.118	5.45	14	67	315	82.92	5.49	1.06	0.098	X				X				17
18	102,000	8.40	50	85	31.7	72.17	1.77	0.29	0.078	8.50	42	85	613	64.33	2.85	0.39	0.071	X				X				18
19	96,900	5.05	62	67	5.5	96.81	3.80	0.21	0.105	5.10	29	71	379	74.75	10.64	1.40	0.091	X				X				19
20	85,300	6.80	64	93	6.4	90.60	4.02	0.19	0.101	6.85	43	97	1156	68.36	8.69	0.46	0.082	X				X				20
21	157,500	5.10	46	78	12.0	76.12	3.53	0.04	0.085	5.10	16	82	41.2	56.75	4.66	0.10	0.065		X	I			X			21
22	116,200	6.60	76	47	8.4	97.89	7.33	0.23	0.113	6.20	23	45	248	71.86	10.05	0.94	0.087	X				X				22
23	103,900	5.40	59	78	1.4	107.44	2.47	0.27	0.118	5.90	23	60	89	72.81	5.49	0.23	0.084	X				X				23
24	122,000	6.05	67	96	2.8	107.05	3.00	0.01	0.118	6.35	23	99	4.4	97.76	4.06	0.16	0.110	X				X				24
25	106,000	5.20	62	56	3.1	84.00	3.05	0.04	0.092	5.25	25	64	42	78.45	8.37	0.13	0.091	X				X				25
26	81,600	8.80	--	54	95	9.30	7.70	0.10	0.018												X (4)		X (5)			26
27	75,000	7.40	--	54	1.9	75.13	3.58	---	0.083	7.60	--	54	3.3	93.02	4.41	---	0.102		X				X			27
28	102,100	4.70	51	74	10.7	55.86	9.11	0.07	0.068	4.85	20	76	309	62.65	10.94	0.56	0.077				X					28
29	98,100	5.95	72	55	7.4	104.75	6.86	---	0.116	6.00	27	59	62	94.08	9.92	---	0.108	X				X				29
30	113,500	5.60	66	87	4.7	89.74	6.47	---	0.100	6.15	42	89	1046	75.00	10.93	---	0.089	X				X				30
31	98,400	5.70	74	74	3.8	84.86	5.92	---	0.095	5.80	54	77	215	73.88	10.47	---	0.088	X				X				31
32	96,000	6.90	56	40	3.3	77.06	4.66	---	0.086	7.05	21	38	213	78.71	8.92	---	0.092	X				X				32
33	104,200	8.70	--	79	5.1	97.39	2.59	---	0.107	11.80	--	86	75	82.29	4.16	---	0.093				X (6)		X (7)			33
34	95,000	5.10	65	76	127	80.56	5.93	---	0.093	5.10	43	72	668	79.41	9.79	---	0.096	X				X				34
35	98,500	5.10	58	50	4.5	77.95	5.46	---	0.090	5.20	34	55	1299	48.05	20.01	---	0.073			X		X				35
36	86,000	4.70	59	62	2.0	92.58	3.57	---	0.103	4.70	34	65	429	62.14	10.57	---	0.078	X				X				36
37	100,000	3.80	45	60	12.9	79.20	7.83	---	0.090	5.00	30	59	43	69.65	10.70	---	0.083			X		X				37
38	90,500	3.30	36	85	8.0	48.58	6.72	---	0.058	3.35	--	87	93	16.26	24.36	---	0.042				X (8)		X			38

TABLE B-11. (continued)

NOTES: Blue Flames - well adjusted conditions
Yellow Flames - out-of-adjustment conditions

* Actual input rate measured at time of sampling

** NO_x emission factor - lbs/10⁶ Btu, sum of NO and NO₂ calculated as NO₂

$$\text{NO}_x \text{ (lbs/10}^6 \text{ Btu)} = \frac{\text{NO}_x \text{ (ppm air free)} \times 10^6 \text{ Btu} \times P \times d(\text{NO}_2)}{10^6 \times \text{HV}}$$

where:

HV = heating value of gas in Btu/ft³

P = ft³ combustion products per ft³ gas burned (60 F, 30" Hg)

d = density of gas in lbs/ft³ (60 F, 30" Hg)

$$\text{NO}_2 (P \times d) = 1.061$$

*** Total aliphatic aldehydes expressed as formaldehyde

(1) Circulating air temperature rise

(2) (Air Free Concentration) = $\frac{\text{Ultimate CO}_2}{\text{Sample CO}_2} \times (\text{Sample Conc.})$

(3) Two rectangular ribbon blocks

(4)
& (5) Powered burner and unique heat exchanger

(6)
& (7) Powered burner with tubes in drum heat exchanger

(8) Multiport shaped to look like two logs

I Cast iron burner construction

TABLE B-12. HOT-WATER BOILER EMISSION RESULTS (8)

HWB	Input Rate, Btu/hr	Flame Condition	Sample CO ₂ Percent	Flue Gas Concentration, PPM, Air Free					NO _x Emission Factor,* lbs/10 ⁶ Btu	Burner
				CO	NO	NO ₂	CH ₄	Total Aldehydes		
4	134,900	Blue	3.95	6.3	92.5	5.4	6.7	0.40	0.102	Single-port**
4	132,000	Yellow	3.60	967	97.7	13.7	26.1	----	0.116	
5	94,200	Blue	5.15	7.9	148.0	11.4	1.1	0.18	0.165	Drilled MP**
5	95,500	Yellow	5.30	61	139.6	8.8	0.9	----	0.154	
6	139,100	Blue	5.30	4.3	142.9	13.3	0.9	0.18	0.162	Slotted MP**
6	140,400	Yellow	5.25	402	106.5	18.3	----	----	0.129	
7	87,300	Blue	4.65	5.4	165.5	10.2	1.7	----	0.182	Drilled MP**
7	87,300	Yellow	4.70	929	103.3	21.0	6.8	----	0.129	
8	106,300	Blue	5.30	7.0	157.2	12.5	----	0.13	0.176	Tubular slot- ted MP
8	109,200	Yellow	5.15	860	123.0	18.1	4.9	----	0.146	
9	60,700	Blue	4.25	20	158.8	10.1	2.7	0.26	0.175	Drilled MP**
9	60,700	Yellow	4.10	203	166.3	12.2	2.4	----	0.179	
10	123,500	Blue	3.20	308	228.0	14.9	10.9	0.38	0.252	Formed MP
10	123,500	Yellow	3.15	1855	227.6	8.8	14.5	----	0.245	
11***	162,700	Blue	3.20	9.3	86.4	8.7	4.5	0.24	0.099	Single-port**
11	164,100	Yellow	3.65	1075	63.5	7.1	11.5	----	0.073	
12	173,800	Blue	3.00	8.0	144.7	9.6	8.8	0.34	0.160	Tubular MP
12	175,000	Yellow	3.10	9.2	132.5	9.5	22.8	----	0.147	
13	293,000	Blue	3.90	89	85.3	4.9	11.8	0.43	0.094	Ribbon**
13	293,300	Yellow	3.90	237	57.3	8.6	4.8	----	0.068	
14a	392,000	Blue	4.95	51	157.7	17.2	2.4	0.18	0.181	Drilled MP**
14a	389,400	Yellow	5.10	355	137.6	10.4	2.7	----	0.153	
14b	392,800	Blue	4.80	90	124.3	5.3	2.5	0.16	0.134	Ribbon**
14b	393,400	Yellow	4.85	1277	63.2	11.5	28.2	----	0.077	
15a	584,300	Blue	4.60	175	148.5	11.9	3.3	0.25	0.166	Drilled MP**
15a	587,600	Yellow	4.65	281	116.5	12.3	48.0	----	0.133	
15b	582,500	Blue	4.70	919	86.1	9.9	7.4	0.26	0.100	Ribbon**
15b	584,400	Yellow	4.75	1801	125.5	15.3	19.4	----	0.146	
16	601,800	Blue*	2.65	27	159.0	24.7	31.5	0.67	0.190	Tubular MP
16	608,500	Yellow	2.80	39	140.8	12.9	19.3	----	0.159	
17	397,100	Blue	2.90	18.6	89.2	6.5	5.5	0.24	0.099	Single port
17	400,000	Yellow	3.98	29.4	94.3	7.5	11.0	----	0.106	
(MP = Multi Port)										
Average			Blue	4.16	55.1**	135.9	11.0	6.8	0.29	0.152
Std. Dev.			Blue	+0.91	+84.7	+39.6	+5.0	+7.7	+0.14	+0.044
Average			Yellow	4.25	572	118.5	12.3	14.9	----	0.135
Std. Dev.			Yellow	+0.83	+556	+42.4	+4.1	+12.8	----	+0.044

Notes: * Sum of NO + NO₂ calculated as NO₂
 ** Cast Iron
 *** Average of three separate measurements
 **** HWB 15 CO data omitted because of abnormally high value

TABLE B-13. STEAM BOILER EMISSION RESULTS⁽⁸⁾

HWP	Input Rate, Btu/hr	Flame **	Sample CO ₂ , %	Flue Gas Concentration, PPM, Air Free				NO _x * Emission Factor, lbs/10 ⁶ Btu	Burner Type
				CO	NO	NO ₂	CH ₄		
18	370,800	B	5.40	16.3	147.1	13.3	9.10	.166	MP Drilled (cast iron)
18	389,500	Y	5.40	356.3	151.9	13.4	3.95	.171	MP-Drilled (cast iron)
19	1,441,000	B	4.90	16.4	153.5	9.4	4.34	.169	MP-Slotted (steel tube)
19	1,441,000	Y	4.90	191.0	172.9	11.9	4.56	.192	MP-Slotted (steel tube)
20	405,000	B	4.15	236.5	147.0	9.0	----	.162	MP-Slotted (steel tube)
20	405,000	Y	3.90	681.0	147.5	7.0	----	.160	MP-Slotted (steel tube)
8	104,000	B	4.10	6.9	128.1	11.9	6.30	.145	MP-Slotted (steel tube)
8	104,000	Y	4.10	291.3	105.5	14.6	5.70	.124	MP-Slotted (steel tube)
<hr/>									
	Average	B	4.60	69.0	143.9	10.9	6.50	.161	
	Std. Dev.	B	+0.63	+111.7	+11.0	+2.1	+2.40	+0.011	
	Average	Y	4.60	380.0	144.5	11.7	4.70	.162	
	Std. Dev.	Y	+0.70	+212.0	+28.2	+3.3	+0.99	+0.028	

Notes: * Sum of NO and NO₂ calculated as NO₂
 ** B = Blue, Y = Yellow

TABLE B-14. HOT-WATER HEATER EMISSIONS⁽⁹⁾

WH #	Fuel Input ⁽¹⁾ Rate, Btu/hr	Blue Flame Adjustment								Yellow Flame Adjustment								Water Heater Type (5)	Burner Type (6)	Tank Size, Gallons	WH #
		(2) Δt, F	Primary Air, %	Sample CO ₂ , %	Flue Gas Concentration, ppm, Air Free ⁽³⁾				NO _x Emission Factor (EF), lbs/10 ⁶ Btu	(2) Δt, F	Primary Air, %	Sample CO ₂ , %	Flue Gas Concentration, ppm, Air Free ⁽³⁾				NO _x Emission Factor (EF), lbs/10 ⁶ Btu				
1	34,500	92	---	5.60	3.0	111.60	3.69	T	0.124	88	---	5.70	28.4	95.71	9.26	3.4	0.113	D	M	40	1
2	47,100	95	---	5.90	2.0	115.87	4.49	2.1	0.128	107	---	5.80	143	80.88	12.77	2.0	0.100	D	M	50	2
3A	27,500	129	---	4.35	6.3	119.31	5.77	5.2	0.130	102	---	4.65	30.5	121.91	10.32	8.3	0.137	D	M(7)	20	3A
3B	27,700	125	---	4.40	4.0	135.87	6.65	7.1	0.148	123	---	4.45	27.5	136.31	9.63	11.3	0.151	D	M(7)	20	3B
4	44,000	74	---	7.05	7.3	85.14	5.51	T	0.096									D	C	30	4
5	246,000	82	---	5.25	7.1	203.59	2.86	T	0.223	95	---	6.45	121	248.15	T	T	0.251	C	M	85	5
6	50,000	103	---	5.30	3.8	105.92	4.14	2.0	0.114									D	M	50	6
7	40,000	98	---	5.20	5.5	144.00	5.32	3.0	0.155	112	---	4.60	71	89.03	15.17	4.7	0.107	D	M	30	7
8	40,000	91	40	6.15	125	42.79	5.93	2.3	0.050	91	18	5.90	185	103.51	14.30	1.6	0.122	D	M	40	8
9	39,600	91	38	5.30	3.4	105.26	2.17	2.9	0.112	103	19	5.10	141	92.87	12.78	4.5	0.110	D	M	40	9
10	62,300	94	28	4.75	5.3	129.83	2.07	9.6	0.137	81	20	4.80	8.0	125.90	3.73	9.8	0.134	D	M	50	10
11	32,300	82	34	4.45	5.1	134.16	4.45	2.4	0.143	76	16	4.65	199	92.05	13.52	4.4	0.109	D	M	30	11
12	42,300	83	31	5.70	3.2	164.82	4.38	1.3	0.174	80	17	5.55	359	158.40	30.96	10.4	0.195	D	M	40	12
13	46,700	102	39	3.05	32.9	126.89	4.10	17.8	0.135	106	20	3.15	14.1	101.98	7.05	4.6	0.112	D	M	50	13
14	245,000	96	65	6.00	10.0	165.00	11.04	0.9	0.182	113	24	5.80	596	116.92	17.69	3.9	0.139	C	M	85	14
15	380,000	82	---	4.85	2.6	170.34	1.96	3.1	0.177									C	M	125	15
16	41,900	62	32	5.10	36.0	91.74	9.18	6.8	0.104	69	20	5.20	18.9	101.58	6.14	8.5	0.111	D	M	30	16
17	221,000	40	39	5.75	77.0	205.44	30.82	T	0.243	38	27	5.80	937	177.66	19.22	T	0.204	I	M	N/A	17
18	190,800	102	45	5.10	3.8	74.05	3.74	1.6	0.334	105	35	5.50	1645	77.50	6.37	26.0	0.090	C	S	100	18
19	224,700	53	37	6.70	30.1	284.58	15.37	T	0.313	53	20	6.25	895	174.11	18.76	T	0.201	I	M	N/A	19
20	37,200	74	---	6.10	41.0	55.06	7.32	T	0.067									D	C	30	20
21	36,200	83	---	6.20	2.1	106.18	3.60	T	0.119									D	C	30	21
22	47,000	104	---	6.50	2.7	98.00	4.55	T	0.110	110	---	6.15	197	81.33	22.42	T	0.111	D	M	30	22
23	31,200	86	31	7.40	3.2	106.90	4.70	T	0.116	79	14	7.60	246	64.50	19.50	T	0.087	D	M	40	23

TABLE B-14. (continued)

NOTES:

- (1) Actual fuel input rate measured at time of sampling, Btu/hr.
- (2) Outlet water temperature rise, F.
- (3) Air Free Concentration = $\frac{\text{Ultimate CO}_2}{\text{Sample CO}_2}$ (Sample Concentration)
(Note: Ultimate CO₂ = 12.0)
- (4) NO_x emission factor: lbs/10⁶ Btu, sum of NO and NO₂ calculated as NO₂.
Emission Factor = $\frac{\text{NO}_x (\text{ppm Air Free}) \times 10^6 \times P \times d (\text{NO}_2)}{10^6 \times H}$
where:
H = heating value, Btu/ft³
NO_x = air-free sum of NO and NO₂ concentrations, ppm by volume
P = (ft³ air-free products)/(ft³ gas burned) (60 F, 30" Hg.)
d = density of NO₂ lbs/ft³ (60 F, 30" Hg.)
(Note: P d = constant = 1.061)
- (5) Water heater type: D - Domestic
C - Commercial
I - Instantaneous
- (6) Burner type: C - Combination pilot-main burner
S - Single port
M - Multiport
- (7) Burner materials: 3A, stamped steel; 3B, stamped steel with cast iron formed ports.
- (8) Sealed combustion chamber design (experimental unit).

APPENDIX B REFERENCES

1. Bonne, U., Torborg, R. H., and Janssen, J. E., Digital Stimulation of the Performance of Combustion Heating Systems, AIChE Regional Symposium, Bloomington, Minnesota, February 21, 1975.
2. American National Standard Z21.47-1973, Gravity and Forced Air Central Furnaces, New York, New York.
3. Personal Communications from:
 - a. Paul Swenson, Consolidated Gas System Service Corporation
 - b. Jim Kennedy, Columbia Gas of Ohio
 - c. Dave Whitlock, Rochester Gas & Electric
4. American National Standard Z21.13-1974, Low Pressure Steam and Hot-Water Boilers, New York, New York.
5. American National Standard Z21.10.1-1975, Gas Water Heaters, New York, New York.
6. Arthur D. Little, Inc., Study of Energy-Saving Options for Refrigerators and Water Heaters: Volume 2: Water Heaters, Cambridge, Massachusetts, May 1977.
7. Thrasher, W. H. and DeWerth, D. W., Evaluation of the Pollutant Emissions from Gas-Fired Appliances, American Gas Association Research Report No. 1503, Cleveland, Ohio, May 1975.
8. DeWerth, D. W. and Sopko, V., Analysis of Flue Products from Gas-Fired Appliances, (unpublished status report for A.G.A.L. Research Project EP-1-23), Cleveland, Ohio, December 1975.
9. Thrasher, W. H. and DeWerth, D. W., Evaluation of the Pollutant Emissions from Gas-Fired Water Heaters, A.G.A.L. Research Report No. 1507, Cleveland, Ohio, April 1977.
10. Federal Register, May 10, 1978.

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

APPENDIX C

LITERATURE SEARCH

APPENDIX C

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION.	89
LITERATURE SOURCES REVIEWED	89
DESIGN FACTORS CULLED FOR IMPROVING GAS APPLIANCE EFFICIENCY.	90
Burners.	90
Heat Exchangers.	94
Venting.	95
Controls	97
SYSTEM CONCEPTS CULLED FOR IMPROVING GAS APPLIANCE EFFICIENCY	100
Jet Heet Furnace	100
Vacuum Gas Appliance Division, The Union Fork & Hoe Company.	100
Rankine Cycle Furnace.	101
Coppus Turbo-Boiler.	101
Thermocatalytic Reactor.	104
Household Heating with High Temperature Fluid.	104
High Temperature-High Velocity Forced Air Baseboard Heater	104
Submerged Combustion Water Heater.	108
REFERENCES.	110
BIBLIOGRAPHY.	112

LIST OF FIGURES

FIGURE C-1. Schematic Illustration of a Spiral Flame Burner	92
FIGURE C-2A. Schematic Illustration of an Experimental Rotating Arm Power Burner.	93
FIGURE C-2B. An Experimental Powered Gas Burner with Air Fan Blades and Gas Delivery Arms Mounted on a Common Hollow Shaft.	93
FIGURE C-3. An Experimental Traveling Flame Burner.	96

LIST OF FIGURES (Continued)

Page

FIGURE C-4.	A View of a Demonstration Furnace Using Four Compact Heating Modules in Parallel Next to a Contemporary 80,000 Btu/hr Input Furnace	96
FIGURE C-5.	Cross Section View of the Turbofan Self-Powered Furnace L Fan or "Therm".	102
FIGURE C-6.	Cutaway View of the Coppus Engineering Corp Turbo-Boiler.	103
FIGURE C-7.	Cross Section View of the Intertech Systems, Inc. Boiler-Water Heater Combination	105
FIGURE C-8.	Cross Section View of the American Thermocatalytic Corp Boiler Tube	106
FIGURE C-9.	Flow Diagram of Central Heat Source System Using Forced Circulation of Hot Fluid.	106
FIGURE C-10A.	The High-Velocity, High-Temperature, Forced-Air Base-board Heater System	107
FIGURE C-10B.	Section View of the Heat Exchanger and Air Flow	107
FIGURE C-11.	Typical Experimental Setup for a Submerged Combustion Burner Application.	109
FIGURE C-12.	Experimental Water Heater in Which Water Flowed Countercurrently Through the Combustion Products.	109

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

APPENDIX C

LITERATURE SEARCH

INTRODUCTION

The object of this task is to determine what new and reportedly more efficient concepts in burners, heat exchangers and appliance designs have appeared since 1945, which were not reduced to commercialization. This task was completed by reviewing all the pertinent literature available and a listing of pertinent patents and selecting those articles and patents which are germane to the aims of the above noted project.

LITERATURE SOURCES REVIEWED

The following sources of information were searched for new and/or improved concepts in gas-fired furnaces, boilers and hot water heaters:

1. American Gas Association Laboratories (AGAL) Files
2. Battelle Columbus Laboratories (BCL) Files
3. A.G.A. Research & Utilization Conference Papers (1945-1955)
4. A.G.A. Research, Utilization and Marketing Conference Papers (1956-1968)
5. Conference on Natural Gas Research & Technology (1971-1974)
6. A.G.A. Operating Section Conference Papers
7. Appliance Manufacturer's "Appliance Conferences"
8. American Society of Gas Engineers (ASGE) Annual Meeting Technical Papers
9. ASHRAE Papers
10. Gas Abstracts
11. Periodical Literature
12. GAMA Patent Digest.

DESIGN FACTORS CULLED FOR
IMPROVING GAS APPLIANCE EFFICIENCY

Burners

Pulse Combustion Burners have appeared several times in the literature^(1,2,3). This type of burner offers the potential of eliminating the need for conventional vent systems (large masonry chimneys) and off cycle flow losses through the appliance are essentially eliminated since the system operates like an off cycle vent damper. Further, extremely high heat release is attainable in relatively small volumes. Pulse combustion appears to offer an immediately useable technology and one boiler manufacturer recently has developed a commercially available boiler using a pulse combustion burner which operates at 90+ percent thermal efficiency.

Catalytic Burner Systems can offer some attractive advantages when used in the design of some types of gas-fired appliances^(1,4):

1. The burners generally operate with little or no visible flame,
2. Catalytic burners transfer heat mainly by radiation,
3. A wide span of operating temperatures is possible with catalytic burners,
4. The shapes of catalytic burner surfaces can be tailored to fit the need of the application, and
5. In some applications, the burner surface can be placed close to the heat exchanger or material being heated, thus, reducing heat-up time.

On the other hand, there appears to be a lack of technical information on this subject which may be the reason for its limited use by industry.

Infrared-Type Burners have been used to space heat industrial and commercial buildings for several years. Brief studies have been conducted to show that infrared burners can be used in the design of furnaces⁽⁵⁾, boilers⁽²⁾ and water heaters⁽⁶⁾. These studies have shown that while only small increases in operating efficiency were measured, the burners can have significant influence on the seasonal efficiency of appliances. The effect on the seasonal efficiency is noted because they operate with controlled

excess air and act to restrict flow through the appliance during the off cycle. Infrared burners do provide potential for high heat exchanger flux (smaller heat exchangers possible) and can be shaped to conform to the heat exchanger design. These studies have indicated that the higher cost of infrared burners have slowed commercialization.

Powered burners or eductor operated burner systems can improve the efficiency of appliances. This type of burner can provide a system which would operate with carefully controlled excess air flow and which appears to restrict most off-cycle flow through the heat exchanger. A powered system may operate without a normal vent system, such as a masonry chimney. The literature review has shown that around 1958 there was at least one appliance which operated with an eductor system, the Vacuum Gas Burner Division of Union Fork & Hoe Company⁽⁷⁾, but it never was very popular because of relatively high cost.

The venting arrangement for a powered burner appliance could use a chimney or could be ducted through the nearest outside wall using a suitable outdoor vent terminal. This latter arrangement would result in a vent terminal design similar to those used by existing direct vent systems. Since the present National Fuel Gas Code and American National Standard Z21.64-1978, "Direct Vent Furnaces" cover the design of and proper installation of direct vent systems, it would seem no new codes or standards will be needed for power vent system outdoor vent terminals.

A swirling flame burner⁽¹⁾ can be created by placing an atmospheric gas burner in a combustion chamber in which secondary air is introduced tangentially to the combustion chamber walls. Such an arrangement promoted a whirling, spiral-shaped flame pattern which hugged the combustion chamber walls. Because of the appearance of the flame, the burner is referred to as the "spiral flame burner". It was felt that the flame pattern produced might result in improved heat transfer characteristics. Figure C-1 shows a setup which produces a swirling flame.

An experimental burner was noted in the literature⁽¹⁾ that was intended to introduce primary air through the centrifugal force generated by rotating the burner. Figure C-2 schematically illustrates this experimental burner. Two hollow arms, each 7-in. long, were rotated by an electric motor. Gas and

Figure C-1. Schematic illustration of a spiral flame burner

Figure C-2A. Schematic illustration of an experimental rotating arm power burner

Figure C-2B. An experimental powered gas burner with air fan blades and gas delivery arms mounted on a common hollow shaft

centrifugally injected air were introduced at the junction of the arms, to produce flames at the open ends of the arms or at ports drilled along the arms. This type of burner could spread a flame over a large surface and improve the heat transfer capability of a heat transfer surface.

Figure C-3 illustrates an experimental device which probably can best be described as a "traveling flame" burner⁽¹⁾. The device consists simply of a length of pipe into which an air-gas mixture was injected at one end. The air-gas mixture was ignited by a pilot flame or electric spark at the other end and flashed back slowly into the pipe. In some instances, the flame front was observed to travel from 6 to 10 ft. in the pipe before it was extinguished. The entering air-gas mixture then forced the combustion products out of the pipe and the cycle was repeated. While this burner provided low heat release rate poor combustion resulted with CO emission higher than 400 ppm.

It was felt that such a device might be employed to heat rather evenly a long pipe heat exchanger in applications such as area-heating devices. Gas input rates used ranged from 10,000 to 30,000 Btu per hour with natural gas.

The Combex ANL burner⁽⁸⁾ which was studied early in the 1960's superimposed a high voltage a-c electrical current on the energy obtained from the combustion of gas. As a result, combustion gases were produced which were at a higher specific enthalpy and temperature than is obtainable from the fuel alone.

Heat Exchangers

The literature revealed very few heat exchangers, per se, which might be used in a gas appliance to improve efficiency.

In 1967, the Lau Blower Company developed an experimental rotating heat exchanger. This device utilized the hollow blades of a blower scroll as the heat transfer surface. Flue gases passed through the hollow section and, of course, circulating warm air flowed on the outside. The heat exchanger design provided a compact, higher-than-normal efficiency (85-87)

furnace. The eductor combustion system would also tend to seal the combustion system during the off cycle improving the seasonal efficiency. There were some problems associated with combustion efficiency, noise and costs which could be solved through additional study.

A compact heat exchanger was researched by Thermo Electron Engineering Corporation during the late 1960's which reportedly⁽⁹⁾ had heat transfer coefficients in the 40-80 Btu/hr ft² F range. The heat transfer modules at 20,000 Btu per hour input measured 9 x 9 x 2.5 in. The power burner operated at 15 percent excess air (Figure C-4). This heat exchanger was developed into a prototype furnace with the Rheem Manufacturing Company, however, no commercially available unit appeared. The reason why no commercial version appeared was not evident.

The General Electric Company developed a multiple tubular-shaped heat exchanger which was designed with metallic "hair" on the air side. This "hair" provided significant external surface on the air side of a furnace. When the tubes were internally baffled, the heat transfer efficiency of the exchanger was greater than the contemporary drum or sectional type heat exchanger. This heat exchanger is commercially available.

Finally, Amana Refrigeration, Incorporated built a furnace with a coffee-can sized heat exchanger which was more efficient than contemporary equipment. This exchanger consisted of a packed bed of small diameter solid spheres through which the flue gases were forced. This bed also accommodated small diameter tubes through which an intermediate heat transfer fluid was pumped. The intermediate heat transfer fluid released its heat to circulating air or water. The compact powered burner emitted a low level of NO_x because its flames impinged upon and were cooled by the heat exchanger. This heat exchanger is commercially available.

Venting

There appears to be two major areas of venting which can be modified to improve the seasonal efficiency of gas-fired appliances. One involves a reduction of the draft hood dilution air during the appliance on cycle and the second a reduction of the off cycle chimney losses.

Figure C-3. An experimental traveling flame burner

Figure C-4. A view of a demonstration furnace using four compact heating modules in parallel next to a contemporary 80,000 btu/hr input furnace

The first area involves a redesign of the gas appliance draft hood to minimize the relief opening dilution air flow. Current designs provide for about 1.4 volumes of dilution air per volume of flue gas flow. There is question about the need for this amount of excess dilution air flow. A study is needed to determine if the draft hood can be redesigned to hold energy losses into chimney and vent to an acceptable minimum.

The second area involves minimizing the off cycle chimney flow. This can be achieved by designing the vent system to operate as a direct vent system where no heated air is used for venting or for combustion air, or using vent dampers during the off cycle. The off cycle vent damper can be electrically, thermally or mechanically operated. All three types are available and savings have been reported which vary from 2 to 30 percent⁽¹⁰⁾ based on all sorts of variables like climate, appliance oversize, appliance location, etc.

Power venting is an approach which can be used to improve heat exchanger efficiency. If a blower is used to exhaust flue gases a higher pressure drop, more effective heat exchanger can be used. The Vacuum Gas Appliance furnace described in a following section of the report used this approach and operated under condensing flue gas conditions.

Controls

The literature has indicated that there are several control modifications which can improve the efficiency of furnaces, boilers or water heaters.

The use of an electric or electronic intermittent ignition device (IID) to replace standing pilots will improve the seasonal efficiency of warm air furnaces and boilers by from 2-5 percent⁽¹¹⁾. (There appears to be no significant savings by applying an IID to a water heater.)⁽¹²⁾ During the heating season, however, the IID saves very little energy. It is only after the potential summertime pilot gas is included in the calculation that the savings is realized. Thus, one of IID's important functions is to shut off the pilot during the summer. From this standpoint, it may be energy effective since there will be no need for a service call in the fall to re-light pilots which have been manually turned off.

An alternate 100 percent automatic ignition system is a direct spark ignition (DSI) system. This type of system provides electronic circuitry to supply a high voltage spark at the time gas flows to the main burners. The spark is established across electrodes just above the burner ports. Once the burners are lit, an electric circuit path is completed through the flame, permitting the gas valve to remain open as long as the flame is present. If the flame is extinguished or the spark is lost, the entire system goes into lockout requiring reset.

The fan control operation can be modified in two ways to improve the efficiency of a furnace. First, the fan-on temperature can be reduced from the manufacturer's recommended temperature setting of about 130 F on -- 105 F off to about 110 F on -- 85 F off. It has been reported that this modification can save about 2 percent of annual heating energy consumption. This modification causes the fan to begin taking heat from the heat exchanger sooner and allows it to run longer to extract more of the heat exchanger's retained heat. Continuous fan operation carries this approach to its limit and the same reference⁽¹³⁾ indicates that about a 5 percent savings will be achieved with continuous fan operation. Continuous fan operation does result in increased electrical costs and these additional costs must be subtracted from the cost of the gas savings.

Two-speed blowers have appeared several times on appliances over the years. The speed of the blower is regulated by the burner input if a multiple input or modulating input system, or by the furnace bonnet temperature. For example, the American Standard, Incorporated sold a furnace in the late 1960's which had a continuously operating blower which was controlled by the furnace's outlet warm air temperature. A solid state sensor in the warm air outlet varied the blower speed between 300 and 800 rpm. During the furnace off cycle, the blower operates continuously at 300 rpm. Again, the cost of continuous fan operation must offset any gas cost savings.

Controls which modulate the burner input in response to heating load have been available for many years. Early conversion burners used controls manufactured by the Detroit Lubricator Company. (Models 566, 565) which modulated both the gas supply and the combustion air supply. There are other controls which can achieve this result^(14,15). Reference 13 indicates that such a system can save as much as 10 percent of the yearly

heating energy. These controls generally have an outdoor temperature sensing system to indicate the extent of the needed energy in response to a call for heat from the thermostat.

Reverse acting aquastats on hot water boiler systems have been used to improve the efficiency of boilers⁽¹⁶⁾. This control operates to continue to pump water through the home, after the room thermostat is satisfied, until the return water temperature is about 100 F rather than the design return water temperature of 160-180 F. There have been no reports of the amount of energy savings possible. Reports of homeowners who have used this control system were that they were more comfortable and that the boiler cycled less frequently.

Room thermostats are equipped with a heat anticipator system which anticipates the room temperature reaching the set point and controls the heating system on cycles. A revision of existing systems to sense outdoor temperature and room temperature and cause the heating system to cycle 2-3 times per hour rather than 5-6 cycles per hour should not only save energy but improve comfort.

Programmed thermostats with integral nighttime setback could save energy by adjusting the thermostat set point during the day to conform to the home use. For example, during the day when the house is empty it could set back the thermostat, turn it up for the evening meal and after dinner-time, and turn it back again for the nighttime.

Microprocessor controls could be utilized to sense the outdoor temperature, the home use period and the indoor temperature, and adjust the thermostat set point and the furnace operation accordingly. Such a control could be used to control the appliance to maintain optimum comfort at minimum energy use. The blower speed, fuel input, humidifier electronic filter and thermostat set point could all be controlled by the micro-processor.

SYSTEM CONCEPTS CULLED FOR
IMPROVING GAS APPLIANCE EFFICIENCY

Jet Heet Furnace (17)

The Jet Heet Furnace of Englewood, New Jersey appeared on the market briefly during the early 1960's. It disappeared because of economics of the times. This appliance was a compact, power burner system which delivered high temperature (about 300 F) circulating air through small diameter flexible heat ducts. The ducts terminated in each room at a specially designed register which diluted the high temperature air with room air and delivered the resultant air at a reasonable temperature to the room. This system operated at about 80 percent steady state thermal efficiency and because of its power burner which restricted off cycle flow would probably operate at a seasonal efficiency somewhat higher than contemporary heating systems.

Vacuum Gas Appliance Division
The Union Fork & Hoe Company (18)

The Vacuum Gas Appliance Division of Rome, New York (in 1951) manufactured three cast iron heat exchanger furnaces of 65, 80 and 120,000 Btu per hour input. These units used an eductor to draw the flue gases through the cast iron heat exchanger counterflow to the circulating air flow. The water in the flue gases condensed and a special water trap was employed. In order to operate at these conditions, the steady state thermal efficiency must have been about 90 percent. Because an eductor was used which would act as an off-cycle vent damper, the seasonal efficiency of this unit also must have been about 85 percent. Again, it is our opinion that this unit disappeared due to the economics of the times and ready availability of fuel gas.

Rankine Cycle Furnace

The TRD Corporation of Mentor, Ohio has developed a gas-fired furnace based on the rankine cycle which incorporates modulating gas input, vent damper, flue damper, no need for electricity and high efficiency. The reported seasonal efficiency of this unit is about 85 percent⁽¹⁹⁾ and Figure C-5 is a cross section of the Turbotherm (patent applied for) furnace. This furnace will operate down to a minimum input of 20,000 Btu per hour with a modulating gas orifice and variable flame port. It also adjusts positions of the flue and vent dampers to aid in maintaining a high CO₂ throughout its firing range.

Coppus Turbo-Boiler

Figure C-6 is a view of a rotating heat exchanger boiler which produces hot water in 20 seconds from a cold start. The fast response is caused by a rotating heat transfer system which obtains heat transfer coefficients many times higher than conventional boilers. The unit described in the Coppus Engineering Corporation of Worcester, Massachusetts brochure takes only 2 sq ft of floor space and 2 cu ft of volume at an input of 330,000 Btu per hour and an efficiency of 85 percent. The high input is required because it is essentially an instantaneous boiler. An important feature of the system is its ability to match boiler performance with system needs. This is accomplished by varying the speed of rotation of the heat transfer system. This system, as presented, was suggested for commercial and industrial uses.

Intertech Systems, Inc.

The Intertech Systems, Inc. of Little Falls, New Jersey described a large heat pipe boiler system operated under a vacuum in which heat is transferred by the condensing water to heat exchangers for both a space water heating and domestic water heating system. The domestic water heat exchanger tank has a 17 gallon capacity. According to Intertech's brochure,

Figure C-5. Cross section view of the turbofan self-powered furnace L fan or "therm"

ROTARY HEAT EXCHANGER

COLOR CODE

WATER

COMBUSTION PRODUCTS

GAS-AIR MIXTURE

ROTARY HEAT EXCHANGER

ANNULAR BURNER

Figure C-6. Cutaway view of the Coppus Engineering Corp. turbo-boiler

the unit operates at a steady state efficiency of from 87 to 88 percent. Figure C-7 shows a cross section of the system and some notes about its operation.

Thermocatalytic Reactor⁽²⁰⁾

The American Thermocatalytic Corporation of Mineola, New York described a thermocatalytic reactor which could have use in furnaces and boilers. The reactor is a small diameter incandescent burner operating at a temperature of 1800-2000 F. This high heat transfer reactor can be used in either warm air or hot water systems. Figure C-8 shows a cross section of a boiler module where the reactor would be installed in the combustion chamber. Such a system could operate at thermal efficiencies as high as 95 percent. Since an eductor is required to move the flue products through the system and the eductor acts as a vent damper, a system of this design could have a seasonal efficiency as high as 85-90 percent.

Household Heating with High Temperature Fluid⁽²¹⁾

Reference 21 described the use of a centrally heated high temperature fluid to provide heat for household heating, water heating and cooking. The boiler or primary fluid heater for such a system would be of the liquid-tube, liquid-wall type with built-in economizer and air preheater. It was projected that the boiler could have an overall efficiency well above 80 percent. The boiler-heat transfer fluid system could operate by circulating the high temperature fluid or by circulating high temperature vapors. Figure C-9 is a flow diagram of a system which would circulate hot liquid.

High Temperature-High Velocity Forced Air Baseboard Heater⁽²²⁾

Reference 22 presents several ideas for heating an enclosed porch or add-on room. One of the ideas could be used in the design of a central warm air system. Figure C-10A is a view of the components of the high temperature-high velocity forced air baseboard unit and Figure C-10B is a view of the compact

DESCRIPTION OF THE SYSTEM:

In principle, the system operates as follows:

- The source of heat (1) heats the small quantity of liquid (2) in an evacuated hollow space (3).

- Saturated steam (4) is immediately generated and by means of condensation heat is transferred to the heating register or coil (5) and the domestic water tank (6).

- The whole process is operated in a pressure range of 0.1 - 1 at. abs. and is regulated by the controlling devices (7).

Figure C-7. Cross section view of the Intertech Systems, Inc. boiler-water heater combination

Figure C-8. Cross section view of the American Thermocatalytic Corp. boiler tube

Figure C-9. Flow diagram of the central heat source system using forced circulation of hot fluid

Figure C-10A. The high-velocity, high-temperature, forced-air baseboard heater system

Figure C-10B. Section view of the heat exchanger and air flow system for high-velocity, high-temperature, forced-air baseboard furnace

heat exchanger. The system uses an eductor that is driven by the circulating air blower. Its steady state thermal efficiency was about 85 percent and the eductor would cause its seasonal efficiency also to be higher than contemporary systems.

Submerged Combustion Water Heater⁽⁶⁾

Two approaches to a submerged combustion water heater were investigated in Reference 6. In one case, a special burner was constructed for direct submersion in water to be heated. Figure C-11 illustrates the design studied. Air and gas were premixed and introduced into the burner at 10 in. water pressure. The efficiency and speed of heating were improved compared to contemporary systems. A second type of submerged combustion studied involved spraying water into the flue passageway to be directly heated by hot flue gases. Figure C-12 illustrates this design. No extensive performance studies were conducted of this system.

Heat Pipe Furnaces

The use of heat pipes in the design of heating appliances has been considered several times in the past. Tappan and Thermacore currently are developing a heat pipe furnace for Brookhaven National Laboratory (BNL). A second development in this area is underway at the Thermoelectron Corp. who are developing a demonstration heat pipe furnace for the Gas Research Institute and BNL.

Figure C-11. Typical experimental setup for a submerged combustion burner application

Figure C-12. Experimental water heater in which water flowed countercurrently through the combustion products

REFERENCES

1. Griffiths, J.C., et al., New or Unusual Burners and Combustion Processes, American Gas Association Laboratories Research Bulletin 96, August 1963.
2. DeCaprio, J. F. and DeWerth, D. W., Study and Improvement of Gas Boilers Equipped for Both Hot Water and Space Heating Services, American Gas Association Laboratories Research Bulletin 106, June 1966.
3. Griffiths, J. C and Weber, E. J., The Design of Pulse Combustion Burners, American Gas Association Laboratories Research Bulletin 107, June 1969.
4. Kwellner, E. R., The Catalytic Heater, Appliance Engineer, Vol 6, No.5, 1972.
5. DeCaprio, J. F. and DeWerth, D. W., Effects of Flame or Burner Radiation on Overall Efficiency of Domestic Gas Heating Equipment, American Gas Association Laboratories Research Report 1431, September 1966.
6. Griffiths, J. C., Some New or Unusual Methods for Heating Water with Gas, American Gas Association Laboratories Research Bulletin 97, September 1963.
7. A.G.A. Directory of Approved Appliances and Listed Accessories, January 1954.
8. Arthur D. Little, Inc., Investigation of the Thermodynamic Properties of the Combex-ADL Natural Gas Burner, Report C-63206, June 15, 1961.
9. PAR Research & Development Report 1968, A.G.A., Washington, D.C., 1968.
10. Schwed, R. L., Fuel Savings Devices: A Status Report, Air Conditioning & Refrigeration Business, pp 38-39, August 1978.
11. Bonne, U. and DeWerth D. W., Improvements and Limitations Determined by Dynamic Computer and Laboratory Simulations of Gas-Fired Central Systems, Report Presented to A.G.A. Seasonal Heating Efficiency Program, November 3, 1977.
12. Hollowell, G. T., Comparison of Energy Consumption for Gas and Electric Water Heaters and Gas Pilots and Electric Ignition for Gas Water Heaters, A.G.A. Laboratories Report No. 1520, Cleveland, Ohio, December 1977.
13. Marcriss, R. A., Zawacki, T. S., et al., Energy Efficiency Program for Appliances: Home Heating Equipment, Furnaces, and Humidifier, Project 9511, Final Report, FEA Subcontract CR-04-60725-00-001, November 1, 1977.

14. Hill, H. Gordon, Modulated Gas Heat Supply for Homes, A.G.A. Research & Utilization Conference, April 4-6, 1961.
15. Personal Communication, Public Service Electric & Gas Co., October 19, 1978.
16. Ibid.
17. A.G.A. Directory of Approved Appliances and Listed Accessories, January 1960-1965.
18. A.G.A. Directory of Approved Appliances and Listed Accessories, January 1951.
19. Forker, J., New Furnace Has Seasonal Efficiency of 85%, Needs No Electricity, Air Conditioning & Refrigeration News, pp 49-51, August 1978.
20. Weiss, G., Gas-Fired Thermocatalytic^R Reactors - A Flameless Incandescent Source of Thermal Energy, 8th International Gas Conference, Stockholm, 1961.
21. Davis, E. G., et al., Engineering Paper Study of Supplying Household Heating Services by High Temperature Circulating Liquids and Vapors, and Comparison with Present Methods of Supplying Such Services with Gas, Report IGT No. 1, Project DGR-10-B, May 1947.
22. DeWerth, D. W., et al., New & Improved Methods of Heating Localized Areas In and Around the Home, American Gas Association Laboratories Research Bulletin 99, Cleveland, Ohio, February 1964.

BIBLIOGRAPHY

1. A.G.A. Laboratories, Cleveland, Ohio, Research Reports & Bulletin

<u>Title</u>	<u>Date</u>
a. Gas Summer Air Conditioning - Performance Characteristics of Air Duct Systems and Review of Methods for Design and Calculation of Pressure Losses in Three Systems (Bulletin 30)	1944
b. The Effects of Modulated Operation on Performance of Gas Warm Air Furnaces (Bulletin 51)	1948
c. The Effects of Confined Space Installation on Central Gas Space Heating Equipment Performance (Bulletin 53)	1949
d. Fundamentals of Heat Transfer in Domestic Gas Furnaces (Bulletin 63)	1951
e. Study of Performance Characteristics of Gas Boilers Equipped for Hot Water and Space Heating Services (Bulletin 1185)	1952
f. Combustion and Ventilation Air Supply to Gas Equipment in Small Rooms (Bulletin 67)	1954
g. Thermopile Forced Air Model Furnace (Report 1308 - unpublished)	1959
h. Design Factors of Gas Heating Appliances for More Effective Use of Heat Exchanger Surface (Bulletin 86)	1961
i. An Evaluation of Some New or Different Ways to Heat the Home (Bulletin 101)	1965
j. Development of a Compact Refrigerant Boiler for an Air Conditioning Application (Report 1447)	1967
k. Heat Transfer Characteristics of Helically Fluted Tubes in Single Water-Backed, Gas-Fired Heat Exchangers (Report 1460 - unpublished)	1968
l. Heating Appliances for Outdoor Installation (Report 1458)	1968
m. Gas-Fired Absorption Air Condition Systems for Outdoor Installation (Report 1465)	1960
n. Design of Central Heating Equipment to Use Gas at Moderately Elevated Pressure (Report 1475 - unpublished)	1970

- o. Evaluation of Available Information on Effects of Hydrocarbons on Gas Appliance Corrosion (Report 1494 - unpublished) 1973
- p. Development of a Central Heating Furnace with Ultra-High Efficiency (Report 1496 - unpublished) 1973
- q. Application of Heat to Domestic Gas Storage Water Heaters (Bulletin 71) 1956
- r. Principles of Design and Sizing of Automatic Gas Water Heaters for Maximum Service Efficiency (Bulletin 29) 1944
- s. A Study to Increase Gas Flame Radiation (Bulletin 104) 1965
- 2. Weiss, G., Thermocatalytic Reactors and Their Use in Gas Heating Appliances, A.G.A. Research & Utilization Conference Paper, May 1959.
- 3. Gergel, J. W., Future Trends in Water Heater Design, A.G.A. Research & Utilization Conference Paper, April 1963.
- 4. Elliott, C. L., Better Gas-Fired Heating Systems, A.G.A. Research & Utilization Conference Paper, April 1963.
- 5. Wormser, Alex, The New Wingarsheek Gas Burner, A.G.A. Research & Utilization Conference Paper, June 1966.
- 6. Reid, Jr., E. A., The Development and Application of an Advanced Gas-Fired Infrared Burner, Natural Gas Research & Technology Conference Paper, February 1971.
- 7. Lazaridis, L. J., Energy Saving Heat-Pipe Application for Residential and Commercial Appliances, Natural Gas Research & Technology Conference Paper, March 1974.
- 8. (?), An Energy Overview - Conservation Through New Energy Concepts, American Society of Gas Engineers Annual Meeting Paper, 1973.
- 9. Charron, J. C., A New Design for Wall-Mounted, Sealed Forced Draft Boilers Allows Significant Energy Conservation, 92nd Congress of the Association Technique de l'Industrie du Gaz en France Paper, Baule, France, September 1975.
- 10. U.S Patent No. 3,973,918, Method of Making a Gas-Fired Furnace, J. T. Tidwell (Assigned to Trane Co.), August 10, 1976.
- 11. Martin, J., The Double Flux Gas Space Heating System. A Study of a Heating Technique that Features Heat Recovery from Ventilation Air and Combustion, 93rd Congress of the Association Technique de Gaz en France Paper, Paris, France, September 1976.

12. Vrij, W. J., Economizers for Central Heating Appliances, Gas, 97 (Netherlands), pp 226-233, June 1977.
13. Buijserd, A. M., and Koelwijn, A. C., Optimal Utilization of Heat from Combustion Gases of Central Heating Boilers and Air Heaters, Gas, 97 (Netherlands), pp 218-225, June 1977.
14. Anon, Infra Red Space Heating and Process Heating: Efficient Utilization at its Best, Ind. Gas, Vol. 57, pp 18-21, July 1977.
15. U.S. Patent, 4,040,669, Burner Especially for Gaseous Fuels, Mendoza, F. C., June 21, 1977.
16. Sakhuja, R. K., Searight, E. F., et al., Improved Gas Fuel Appliances, Proceedings of 5th Energy Technology Conference, Washington, D.C., February 1978.
17. Clarke, F.J.P., Planning Energy Research Development in the United Kingdom, Gas (Dutch), 98, pp 188-195, May 1978 (in England).
18. Hirst, Eric, et al., Regional Analysis of Residential Water Heating: Energy Use and Economics, Oak Ridge National Laboratory Report ORNL/CON-31, October 1978.
19. Hirst, Eric, et al., An Engineering-Economic Model of Residential Energy Use, Oak Ridge National Laboratory Report ORNL/TM-5470, July 1976.
20. Dole, S. H., Energy Use and Conservation in the Residential Sector: A Regional Analysis, Rand Report R-1641-NSF, June 1975.
21. Macriss, R. A., and Belles, F. E., Evaluation of Alternatives for Conserving Fuel Resources, 13th World Gas Conference Paper, London, England, June 1976.
22. Patent No. 3,885,529, Heat Exchanger Structure for a Compact Boiler and the Like, May 1975.
23. Patent No. 3,833, 170, Single Unit Air-Water Heating Appliance, September 1974.
24. Patent No. 3,854, Heat Pipe Water Heater, December 1974.

APPENDIX D

CONTACT SURVEY

APPENDIX D

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	117
Utilities	117
Manufacturers	117
Discussion of Findings.	118
Combustion Air Category	119
Venting Category.	120
Heat Exchanger Surface Category	120
Ignition Category	120
Controls Category	121
Heat Delivery System Category	121
Field Adjustments Category.	122
Improved Equipment Category	122
Miscellaneous Category.	123
References.	123

APPENDIX D

CONTACT SURVEY

by

D. W. DeWerth

INTRODUCTION

The objective of this task is to obtain information not appearing in the open literature about potential design improvements for furnaces, boilers and/or water heaters. This was accomplished by interviewing utility, manufacturer and trade association technical staffs. The following contacts were made by either phone or visit.

Utilities

- Consolidated Natural Gas Service Company, Inc.
- Columbia Gas System Service Corporation
- Lone Star Gas Company
- Northern Illinois Gas Company
- Public Service Electric & Gas Company.

Manufacturers

Furnaces

- Amana Industries
- Ducane Industries
- Heil-Quaker Corporation
- Lennox Industries
- Rheem Manufacturing Company
- York Corporation

Boilers

- BDP (Bryant)
- Weil-McLain
- A. O. Smith Corporation

Water Heaters

- Rheem Manufacturing Company
- A. O. Smith Corporation
- State Industries, Inc.

Discussion of Findings

A brief description of these concepts or suggestions for research obtained through the contact survey are presented in one of the following categories:

- Combustion Category
- Combustion Air Category
- Venting Category
- Heat Exchanger Surface Category
- Ignition Category
- Controls Category
- Heat Delivery System Category
- Field Adjustments Category
- Improved Equipment Category
- Miscellaneous Category.

The items appearing in this list are those which appear to have merit and several may have appeared in the previously presented Appendix covering the Literature Search phase of this project.

Combustion Category

A manufacturer suggested that up-to-date burner design research is needed. Older studies on this subject do not cover modern burner designs.

The up-dated study should include a correlation of burner flexibility (needed because of the variety of pipeline quality fuels expected, LNG, SNG, etc.) against pollutant emission of the burner (because of the standards being promulgated by some states on NO_x emission).

Heat exchanger corrosion may become a serious problem in light of the all out effort to improve appliance efficiency. At higher efficiency levels, the flue gases are cooler and the possibility of condensing flue gases increases. Further, with different composition fuel gases there is a good possibility that the chemical composition of the condensate could change to a point where a more serious corrosion threat is created. A study of the effect of fuel gas composition on condensate composition could answer this question for designers who are considering high efficiency condensing systems.

Combustion Air Category

Modulating combustion air supply and modulating fuel input would maintain high efficiency at reduced rates. A modulating fuel input system designed to match the capacity of the heating system to outdoor temperature may provide a more efficient system. In order for the steady-state efficiency to be maintained at lowered inputs, the excess air supply also needs to be reduced. Some early conversion burner controls automatically modulated fuel gas and combustion air, and perhaps this technology could be revived and modified for today's appliances.

One way to closely control excess air is through the use of power burners. A power burner could be used to operate a furnace or water heater at a lower than normal excess air level, and thus improve its efficiency. Several of the contacts felt more design information was needed on power burners. The use of a power burner (or powered exhaust) system also would allow higher pressure drop and higher efficiency heat exchanger systems.

Combustion air preheat using flue gases - there was a patent issued several years ago covering an infrared burner design which used flue gases to preheat combustion air, resulting in an increase in the heat transfer efficiency

of the burner. A similar system may be applicable to other types of burners and other types of appliances. Too much preheat however, may increase the NO_x emission of the burner and this factor must be considered. A research program evaluating this potential for increasing the heat transfer efficiency of burners would be helpful to manufacturers.

Venting Category

It was pointed out several times that a basic venting study may be needed in light of the trend to cooler and cooler flue gases. The cooler flue gases are the result of efforts to improve efficiency. This trend may be causing condensation in masonry chimneys and may be causing intermittent spillage of flue gases under certain cycle schedules. A review of the assumptions used to develop presently used vent tables is needed to be sure the higher efficiency appliances are covered.

Appliance draft hood designs need to be reviewed with the thought in mind of minimizing the dilution air needed to make the draft hood operate satisfactorily. In indoor installation of appliances this dilution air is warmed room air. The loss of this warmed air is charged against the heating appliance and must be replaced. This reduces the seasonal efficiency of the appliance.

Draft hood designs also can be modified to act as a vent damper during the Off cycle according to one utility contact. Additionally, a manufacturer of water heaters reported that one draft hood design appeared to "hold back" the flue gases during the ON cycle and "hold back" OFF cycle flow. Thus, it appears there may be some possibility of designing a draft hood for an indoor appliance which would require less dilution air for satisfactory operation.

Heat Exchanger Surface Category

None beyond those mentioned in the Literature Search Task.

Ignition Category

None beyond those mentioned in the Literature Search Task.

Controls Category

Low cost solid state controls for appliances were mentioned by several contacts. A water heater manufacturer would like to have a control which would act as a thermostat, sense the time of day and act to reheat the water during off peak use periods. A furnace manufacturer suggested a solid state fan on controls to provide more efficient fan operation, or to modulate the fan speed. Solid state controls could also be used by boiler systems and a study of this entire area appears to be desirable.

Several comments were made about room thermostats. It was suggested that energy savings could be realized by having the thermostats anticipator provide 2-3 cycles per hour rather than the present 5-6 cycles per hour. Further comments suggested a study of the dead-band of present thermostats to see what effect this feature may have on energy consumption. Finally, it was suggested that the room thermostat sense outdoor temperatures and adjust its anticipation accordingly. It appears that a review of the performance and design of room thermostats may be in order.

Microprocessor controls were suggested for all categories of appliances. This solid-state system would control more than one appliance and sense the outdoor temperature and time of day.

Heat Delivery System Category

An overall review of air distribution system was suggested for warm air furnace systems. This review would look at new approaches to circulating warm air. More sophisticated blowers and high-speed turbine technology from NASA would be included, for example. In the literature search phase, a system was reported which delivered high temperature air through small diameter heating ducts, diluting the high temperature air with room air at the room register. Also to be considered in this program would be better zone balancing means and modulating volume systems.

Field Adjustments Category

All the field retrofits being studied in the gas industry's Space Heating Efficiency Improvement Program (SHEIP) were mentioned by contacts. This program does not include domestic water heaters. The major retrofit options being studied are:

1. Appliance derating (fuel and combustion air) and vent restriction,
2. Appliance derating (fuel and combustion air)
3. Vent damper and Intermittent Ignition Device (IID),
4. Appliance derating (fuel only),
5. Vent restriction (VR),
6. Vent dampers (VD), and
7. Appliance derating and IID, VD and VR.

Improved Equipment Category

In an effort to minimize flue losses Combined Appliances are recommended. This matter was looked at in detail in a A. D. Little report⁽¹⁾ For example, one contact suggested a combination hot water boiler and water heater combination.

A utility contact suggested work be conducted on a furnace requiring no electric energy. Work in the past has included studies of the use of thermopiles to generate electricity for a furnace blower; and work was conducted in past studies to generate electricity for appliances by thermoelectrics or fuel cells.

A water heater manufacturer suggested a tank within a tank construction for a water heater. The incoming water would be preheated in the outer shell by the heat loss from the main tank. The preheated water then would enter the inner tank at the top in a normal manner.

Gas-fired heat pumps - it was recommended that work continue on the development of gas actuated heat pumps.

Miscellaneous Category

On several occasions, it was suggested that the DOE furnace, boiler and water heater test methods be reviewed. These laboratory test methods which estimate the annual utilization efficiency were developed using basic assumptions about cycling, annual load, etc. It was felt that it would be desirable to verify these assumptions to insure that the test is valid.

Review proper furnace or boiler sizing techniques - in the past rules-of-thumb or ASHRAE heat loss calculations were used to size equipment. It has been shown that most of these techniques result in unacceptable oversizing. It is recommended that studies be conducted to determine the proper amount of oversize to use and a proper procedure for determining the heat loss of a home.

One of the factors needed to estimate the proper heat loss is the air infiltration rate. It was recommended that a simple technique be developed for estimating the air infiltration levels of homes.

References

1. Lee, W. D., Lawrence, W. T., and Wilson, R. P., "Design, Development, and Demonstration of a Promising Integrated Appliance, Phase I - Design, Final Report", A. D. Little, Inc. Report to ERDA. (Contract No. E-(04-3)-1209, September 1977.

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

APPENDIX E

CONCEPT CHARACTERIZATION: TECHNICAL AND ECONOMIC EVALUATION

APPENDIX E

TABLE OF CONTENTS

	<u>Page</u>
CONCEPT CHARACTERIZATION	127
Description of Energy Saving Concepts	141
Combustion Category.	142
Combustion Air Category.	144
Venting Category	144
Heat Exchange Surface Category	145
Ignition Category.	146
Controls Category.	146
Heat Delivery System Category.	148
Field Adjustments Category	149
Improved Equipment Category.	149
REFERENCES	152

LIST OF TABLES

Table E-1. Baseline Conditions for Gas-Fired Furnaces and Water Heaters.	130
Table E-2. Payback Period for Efficiency Improvement Concepts . . .	131

APPENDIX E
CONCEPT CHARACTERIZATION: TECHNICAL
AND ECONOMIC EVALUATION

The purpose of this task was to characterize the many energy saving concepts by consolidating and analyzing the results of the three previous tasks. The various modifications that were judged to be capable of saving energy in either existing or new equipment have been included. For purposes of organization, the concepts have been grouped into nine basic categories, which are:

- (1) Combustion
- (2) Combustion Air
- (3) Venting
- (4) Heat Exchanger
- (5) Ignition
- (6) Controls
- (7) Heat Delivery System
- (8) Field Adjustments
- (9) Improved Equipment.

The various concepts were considered on a conceptual basis from the standpoint of not only improved efficiency of operation, but also first cost, payback period, reliability, safety, and emissions. Although some future types of gas burners may have potential pollution problems, in general our experience indicates that emissions from residential gas devices is rather minimal--with the exception of carbon monoxide (CO) produced by poorly functioning units or blocked chimneys.

A simplified cost-benefit analysis was conducted for each design concept considered. Based on an estimated seasonal efficiency improvement and a range of probable first cost, a simple payback period was calculated. The estimated values of efficiencies and ranges of first costs for each concept were developed by collaboration between engineers from both Battelle and the A.G.A. Laboratories, and by consultation with various manufacturers and trade associations.

Table E-1 presents the baseline conditions that were used as a standard for comparison. These values represent the conditions that exist in the average or typical home today. Each concept was then compared to these

baseline values to calculate its energy savings and payback period. In order to calculate the annual savings in dollars for each concept evaluated, it was assumed that natural gas cost \$2.50/1000 cubic feet and that electricity cost 5¢/kWh.

Table E-2 presents the main results of this concept characterization study. For each concept it is indicated which type of furnace or water heater is affected, and what the estimated efficiencies, costs, power requirements, energy savings, and payback periods are expected to be. A description of each of these concepts is given in a subsequent section of this Appendix.

The estimates of the steady-state and seasonal efficiencies are intended to be realistic averages that would be realized across the entire spectrum of climatic conditions in the U.S. Studies have shown (e.g., the A.G.A.'s SHEIP study) that wide variations in efficiency improvements do occur from house to house and from region to region. However, only typical or average efficiency values were selected for this study to minimize the range of variables. In making these steady-state and seasonal efficiency estimates, particular advantage was taken of the wealth of data being gathered by the various gas utilities participating in the A.G.A.'s SHEIP study.* In addition, data were available from tests performed using the DOE procedures for estimating seasonal efficiencies for furnaces and boilers^(3,4). Also, efficiencies for specific concepts were discussed with manufacturers and utilities. Finally, the estimated efficiencies in Tables E-1 and E-2 were carefully examined so that the assumed value would be internally consistent with one another. As a point of perspective, the ability to estimate seasonal efficiency is not as sensitive in determining the payback period as our ability to estimate incremental first cost to the homeowner where a range of 2:1 can be expected.

The estimates of incremental first cost for each concept include a range of cost to generally cover the differences between retrofit and new equipment, and also the differences in various designs for the same type of device. In all cases, the cost estimates include only the differential cost.

* The Gas Industry's Space Heating System Efficiency Improvement Program (SHEIP): 1977-1978 Heating Season Status Report, American Gas Association Catalog No. S60078 (1979).

increase over the present equipment designs. For example, if a more efficient electric motor is substituted into new equipment, the differential cost is much less than if a new motor is purchased to replace an existing one. Since the estimated costs have a direct effect on the payback periods, they can also be used to indicate tradeoffs.

The power requirements are an estimate of the electrical power required by the modified furnace or water heater. The operating power refers to the electrical input only while the furnace is operating. The extra power refers to a continuous electrical input.

The payback period was calculated simply as,

$$\text{Payback Period, years} = \frac{\text{First Cost, \$}}{\text{Total Savings, \$/year}} \quad (1)$$

TABLE E-1. BASELINE CONDITIONS FOR GAS-FIRED
FURNACES AND WATER HEATERS

Type of Unit	Steady-State Efficiency, (1) Percent	Seasonal Efficiency, (1) Percent	Rated Input (2)		Seasonal Usage (3)	
			Gas (Btu/hr)	Electric (Watts)	Gas (10 ⁶ Btu)	Electric (kWh)
Air Furnace	77	61	100,000	430	100	590
Hydronic Boiler	77	63	100,000	100	97	130
Water Heater	72	50	45,000	0	37	0

(1) Efficiencies are based on data reported in various literature.

(2) Rated inputs are based on the average sizes of furnaces and water heaters reported in Appendix B and in reference 1.

(3) Seasonal usage of 100×10^6 Btu based on an average residential gas input for heating, and the 37×10^6 Btu is based on an average hot water use rate of 500 gal/wk(1) with a temperature rise of 85 F and a seasonal efficiency of 50 percent. The kWh for electric usage is based on 1380 hrs of blower or pump operation, as per DOE running time estimate of 1.38 times the burner-on time (1000 hrs). The operating time for a domestic water heater is about 820 hrs.

TABLE E-2. PAYBACK PERIOD FOR EFFICIENCY IMPROVEMENT CONCEPTS

Concept	Type Furnace ¹	Steady- State Efficiency %	Seasonal Efficiency ² %	Incremental First Cost ³ \$	Operating Power ⁴ Watts	Extra Power ⁵ Watts	Gas Saved 10 ⁶ Btu	Electricity Saved KWH	Total Savings \$/Yr	Payback Period Years
0. Baseline Condition	AF	77	61	0	430	0	0	0	0	N.A.
	HB	77	63	0	100	0	0	0	0	N.A.
	WH	72	50	0	0	0	0	0	0	N.A.
A. Combustion										
1. Derating, 20% with reduced pressure or reduced orifices	AF	75	63	25-50	430	0	3.17	-125	1.54	16 - 32
	HB	75	65	25-50	100	0	2.98	-28.3	5.89	4.2-8.5
	WH	70	51	25-50	0	0	0.725	0.0	1.78	14 - 28
2. Derating, 20% with secondary air baffle ⁶	* AF	77	67	50-100	430	0	8.96	-81.9	17.85	2.8-5.6
	* HB	77	69	50-100	100	0	8.42	-18.9	19.69	2.5-5.1
	WH	72	55	50-100	0	0	3.36	0.0	8.24	6.1-12
3. Derating, 20% with baffle, plus vent restrictor	* AF	77	69	100-150	430	0	11.6	-62.4	25.30	4.0-5.9
	* HB	77	71	100-150	100	0	10.9	-14.6	26.01	3.8-5.8
	WH	72	57	75-125	0	0	4.54	0.0	11.14	6.7-11
4. Two-stage gas valve, high and low fire ⁷	AF	77	63	75-150	430	0	3.17	-173	-0.85	No
	HB	77	65	75-150	100	0	2.98	-39.1	5.35	14 - 28
5. Modulating gas valve ⁷	AF	77	65	100-200	430	0	6.15	-149	7.63	13 - 26
	HB	77	68	100-200	100	0	7.12	-31.5	15.88	6.3-12
6. Modulating gas and air valves ⁷	AF	77	70	150-250	430	0	12.9	-96.1	26.71	5.6-9.4
	HB	77	72	150-250	100	0	12.1	-22.3	28.55	5.3-8.8
7. Power burner ⁸ non-condensing	* AF	80	75	100-150	545 ⁹	0	18.7	-159	37.82	2.6-4.0
	* HB	80	75	100-150	215 ⁹	0	15.5	-154	30.29	3.3-5.0
	WH	75	65	75-125	65 ⁹	0	8.54	-73.8	17.24	4.4-7.3
8. Power burner, ⁸ condensing	* AF	95	85	150-250	545 ⁹	0	28.2	-159	61.27	2.4-4.1
	* HB	90	85	150-250	215 ⁹	0	25.1	-154	53.74	2.8-4.7
	* WH	90	85	100-200	65 ⁹	0	15.2	-73.8	33.65	3.0-5.9
9. Pulse combustion burner ⁸ , condensing	* AF	95	95	300-600	455 ¹⁰	0	35.8	-34.5	85.99	3.5-7.0
	* HB	95	95	300-600	125	0	32.6	-33.4	78.27	3.8-7.7
	WH	95	95	250-500	25	0	17.5	-28.4	41.54	6.0-12.0
10. Radiant burner ⁸ , non-condensing	AF	79	64	100-200	430	0	4.69	-0.02	11.49	8.7-17
	HB	79	67	100-200	100	0	5.78	-0.03	14.17	7.1-14
	WH	74	55	75-150	0	0	3.36	0.00	8.24	9.1-18
11. Radiant burner ⁸ , power, condensing	* AF	90	85	150-250	545 ⁹	0	28.2	-159	61.27	2.4-4.7
	* HB	90	85	150-250	215	0	25.1	-163	53.27	2.8-4.7
	* WH	90	85	100-200	65	0	15.2	-73.8	33.65	3.0-5.9
12. Catalytic burner ⁸ , power, non-condensing	AF	85	70	100-200	630 ¹¹	0	12.9	-276	17.71	5.6-11
	HB	85	70	100-200	300	0	9.68	-267	10.37	9.6-19
	WH	85	65	75-150	100	0	8.54	-113	15.25	4.9-9.8

TABLE E-2. (continued)

Concept	Type Furnace ¹	Steady-State Efficiency %	Seasonal Efficiency ² %	Incremental First Cost ³ \$	Operating Power ⁴ Watts	Extra Power ⁵ Watts	Gas Saved 10 ⁶ Btu	Electricity Saved KWH	Total Savings \$/Yr	Payback Period Years
<u>A. Combustion</u> (Continued)										
13. Catalytic burner, ⁸ power, condensing	* AF	90	85	150-250	630 ¹¹	0	28.2	-276	55.40	2.7-4.5
	* HB	90	85	150-250	300	0	25.1	-280	47.40	3.2-5.3
	* WH	90	85	100-200	100	0	15.2	-113	31.67	3.2-6.3
14. Submerged combustion ^{8, 12}	* AF	90	85	150-300	630	0	28.2	-276	55.40	2.7-5.4
	* HB	90	85	150-300	300	0	25.1	-267	48.06	3.0-6.2
	WH	90	85	150-300	100	0	15.2	-113	31.67	4.8-9.4
15. Sequential firing of sections ⁷	AF	77	67	100-200	460 ¹³	0	8.96	-177	13.09	7.6-15.3
	HB	77	69	100-200	130	0	8.42	-77.9	16.74	6.0-12
<u>B. Combustion Air</u>										
16. Sealed combustion ⁽³⁾	* AF	77	73	100-250	430	0	16.4	-0.02	40.29	2.5-6.2
	* HB	77	73	100-250	100	0	13.3	-0.03	32.51	3.1-7.7
	WH	72	60	75-200	0	0	6.17	0.00	15.11	5.0-13
17. Reduce excess air	* AF	80	65	25-50	430	0	6.15	36.5	16.91	1.5-3.0
	* HB	80	67	25-50	100	0	5.78	7.95	14.57	1.7-3.4
	* WH	75	55	25-50	0	0	3.36	0.00	8.24	3.0-6.1
18. Preheater for combustion air	* AF	82	70	100-200	430	0	12.9	76.3	35.33	2.8-5.7
	HB	82	70	100-200	100	0	9.68	13.3	24.40	4.1-8.2
	WH	80	60	75-150	0	0	6.17	0.00	15.11	5.0-9.9
19. Outside installations ⁸	* AF	77	73	100-300	430	0	16.4	-0.02	40.29	2.5-7.4
	* WB	77	73	100-300	100	0	13.3	-0.03	32.51	3.1-9.2
<u>C. Venting Category</u>										
20. Vent damper, electrical	* AF	77	70	100-200	445	0	12.9	58.2	34.42	2.9-5.8
	HB	77	70	100-200	115	0	9.68	-4.7	23.50	4.3-8.5
	WH	72	57	75-150	15	0	4.54	-14.9	10.39	7.2-14
21. Vent damper, thermal	* AF	77	70	50-100	430	0	12.9	76.3	35.33	1.4-2.8
	* HB	77	70	50-100	100	0	9.68	13.3	24.40	2.0-4.1
	* WH	72	57	40-100	0	0	4.54	0.00	11.14	3.6-9.0
22. Vent damper, mechanical	* AF	77	70	100-200	430	0	12.9	76.3	35.33	2.8-5.7
	HB	77	70	100-200	100	0	9.68	13.3	24.40	4.1-8.2
	WH	72	57	75-150	0	0	4.54	0.00	11.14	6.7-13
23. Double damper, ¹⁴ electrical	* HB	77	73	100-200	115	0	13.3	0.98	32.56	3.1-6.1
	WH	72	60	100-200	15	0	6.17	-14.2	14.41	6.9-14
24. Double damper, ¹⁴ thermal and mechanical	* HB	77	73	100-200	100	0	13.3	18.3	33.42	3.0-6.0
	WH	72	60	100-200	0	0	6.17	0.00	15.11	6.6-13

TABLE E-2. (continued)

Concept	Type Furnace ¹	Steady- State Efficiency %	Seasonal Efficiency ² %	Incremental First Cost ³ \$	Operating Power ⁴ Watts	Extra Power ⁵ Watts	Gas Saved 10 ⁶ Btu	Electricity Saved KWH	Total Savings \$/Yr	Payback Period Years
<u>C. Venting</u> (Continued)										
25. Vent damper, vent restrictor, derate (20% with baffle), and electric pilot	AF	77	73	200-300	460	0	16.4	-69.7	36.81	5.4-8.2
	HB	77	75	200-300	130	0	15.5	-48.8	35.53	5.6-8.4
26. Vent restrictor	* AF	77	67	75-100	430	0	8.96	53.1	24.61	3.0-4.1
	* HB	77	69	75-100	100	0	8.42	11.6	21.22	2.5-4.7
	WH	72	55	50-100	0	0	3.37	0.00	8.24	6.1-12
27. Draft hood replacement	AF	80	65	100-150	430	0	6.15	36.5	16.91	5.9-8.9
	HB	80	67	100-150	100	0	5.78	7.95	14.57	6.9-10
	WH	75	53	75-125	0	0	2.09	0.00	5.13	15 - 24
28. Increased flue baffling	* WH	75	53	10-20	0	0	2.09	0.00	5.13	1.9-3.9
29. Power vent ¹⁵ (forced draft)	* AF	80	70	50-150	530	0	12.9	-44.0	29.31	1.7-5.1
	* HB	80	70	50-150	200	0	9.68	-107	18.39	2.7-8.2
	* WH	75	60	50-150	50	0	6.17	-47.3	12.75	3.9-12
<u>D. Heat Exchanger</u>										
30. Heat pipe heat exchanger ⁸	* AF	82	75	100-200	430	0	18.7	-0.02	45.75	2.2-4.4
	* HB	82	75	100-200	100	0	15.5	-0.03	37.97	2.6-5.3
	* WH	82	70	50-150	0	0	10.6	0.00	25.91	1.9-5.8
31. Condensing flue products ⁸	* AF	95	75	100-250	430	0	18.7	-0.02	45.75	2.2-5.5
	* HB	90	75	100-250	100	0	15.5	-0.03	37.97	2.6-6.6
	* WH	90	70	75-200	0	0	10.6	0.00	25.91	2.9-7.7
32. Side-arm heater ⁸	WH	75	60	75-150	0	0	6.17	0.00	15.11	5.0-9.9
<u>E. Ignition</u>										
33. Reduced pilot input	* AF	77	62	10-25	430	0	1.61	9.56	4.43	2.3-5.6
	* HB	77	64	10-25	100	0	1.51	2.06	3.81	2.6-6.6
	WH	72	51	10-25	0	0	0.725	0.00	1.78	5.6-14
34. Electric pilot (IID)	AF	77	65	100-175	445	0	6.15	17.1	15.94	6.3-11
	HB	77	67	100-175	115	0	5.78	-10.9	13.62	7.3-13
35. Direct spark (DSI)	AF	77	65	75-150	445	0	6.15	17.1	15.94	4.7-9.4
	HB	77	67	75-150	115	0	5.78	-10.9	13.62	5.5-11
<u>F. Controls</u>										
36. Thermostat setback ¹⁶	* AF	77	65	0-100	430	2 ¹⁷	6.15	27.8	16.47	0.0-6.1
	* HB	77	67	0-100	100	2	5.78	-0.78	14.13	0.0-7.1
	* WH	74	55	0-25	0	0	3.36	0.00	8.24	0.0-3.0

TABLE E-2. (continued)

Concept	Type Furnace ¹	Steady- State Efficiency %	Seasonal Efficiency ² %	Incremental First Cost ³ \$	Operating Power ⁴ Watts	Extra Power ⁵ Watts	Gas Saved 10 ⁶ Btu	Electricity Saved KWh	Total Savings \$/Yr	Payback Period Years
<u>F. Controls</u> (Continued)										
37. Time-of-day input	WH	72	55	100-200	0	3 ¹⁷	3.36	-26.3	6.93	14 - 29
38. Fan control adjustment	* AF	77	63	0-25	430	0	3.17	18.8	8.72	0.0-2.9
	* HB	77	65	0-25	100	0	2.98	4.09	7.51	0.0-3.3
39. Fewer burner cycles	* AF	77	63	25-50	430	0	3.17	18.8	8.72	2.9-5.7
	* HB	77	65	25-50	100	0	2.98	4.09	7.51	3.3-6.7
40. Humidity limit	AF	77	62	50-100	430	0	1.61	9.56	4.43	11 - 22
	HB	77	64	50-100	100	0	1.51	2.06	3.81	13 - 26
41. Temperature modulating aquastat	HB	77	65	50-150	100	0	2.98	4.09	7.51	6.7-20
42. Microprocessor control	AF	77	65	100-200	430	5	6.15	14.7	15.82	6.3-12.0
	HB	77	67	100-200	100	5	5.78	-13.9	13.47	7.4-15
	WH	72	53	50-150	15 ¹⁸	5	2.09	-59.9	2.14	23 - 70
43. Central control center	AF	77	64	150-250	430	5	4.69	5.96	11.79	13 - 21
	HB	77	66	150-250	100	5	4.40	-15.8	10.00	15 - 25
	WH	72	53	100-200	15	5	2.09	-59.9	2.14	47 - 93
<u>G. Heat Delivery System</u>										
44. Waste heat recovery	* AF	82	70	100-300	430	0	12.9	76.3	35.33	2.8-8.5
	HB	82	70	100-300	100	0	9.68	13.3	24.40	4.1-12
	WH	80	60	75-250	0	0	6.17	0.00	15.11	5.0-17
45. Two-speed blower or pump	* AF	77	62	20-100	322 ¹⁹	0	1.61	156	11.76	1.7-8.5
	* HB	77	64	20-100	75	0	1.51	34.9	5.46	3.7-18
46. Improved blower design ⁸	AF	77	61	20-50	387 ²⁰	0	0.00	59.3	2.97	6.7-17
47. More efficient motors	AF	77	61	20-100	387 ²⁰	0	0.00	59.3	2.97	6.7-34
	HB	77	53	20-100	90	0	0.00	13.3	0.67	30 - 150
48. Zone temperature control	AF	77	54	100-300	450	0	4.69	1.49	11.56	8.6-26
	HB	77	56	100-300	120	0	4.40	-19.5	9.81	10 - 31
49. Warm room	AF	77	67	100-300	450	0	8.96	28.0	23.35	4.3-13
	HB	77	69	100-300	120	0	8.42	-12.8	20.00	5.0-15
50. Storage of heat	AF	77	64	200-400	470	50 ²¹	4.69	-243	- 0.67	No
	HB	77	66	200-400	100	50	4.40	-212	+ 0.17	Very large

TABLE E-2. (continued)

Concept	Type Furnace ¹	Steady- State Efficiency ² %	Seasonal Efficiency ² %	Incremental First Cost ³ \$	Operating Power ⁴ Watts	Extra Power ⁵ Watts	Gas Saved 10 ⁶ Btu	Electricity Saved KWH	Total Savings \$/Yr	Payback Period Years
<u>H. Field Adjustments Category</u>										
51. General tuneup and cleaning	AF	77	62	25-50	430	0	1.61	9.56	4.43	5.6-11
	HB	77	64	25-50	100	0	1.51	2.06	3.81	6.6-13
	WH	72	51	25-50	0	0	0.725	0.00	1.78	14 - 28
52. Insulation jacket	* WH	73	55	25-50	0	0	3.36	0.00	8.24	3.0-6.1
<u>I. Improved Equipment Category</u>										
53. Replace existing equipment ^{8, 22}	AF	85	75	500-1000	390	0	18.7	55.2	48.51	10 - 20
	HB	85	75	500-1000	90	0	15.5	13.3	38.64	13 - 26
	WH	80	65	200-300	0	0	8.54	0.00	20.93	9.6-14
54. Instantaneous water heater ²³	WH	80	70	200-400	0	0	10.6	0.00	25.91	7.7-15
55. Design for less scaling and degradation	* WH	72	60	25-100	0	0	6.17	0.00	15.11	1.7-6.6
56. Minimize heat leaks	WH	73	51	10-25	0	0	0.725	0.00	1.78	5.6-14
57. Heat traps for hot water pipe	WH	72	51	10-25	0	0	0.725	0.00	1.78	5.6-14
58. Combination appliances ^{8, 24}	* AF + WH	85	75	0-100	430	0	18.7	111	51.29	0.0-1.9
	* HB + WH	85	75	0-100	100	0	15.5	21.4	39.04	0.0-2.6
59. Field adjustable heat input ^{8, 25}	* AF	77	65	50-100	390	0	6.15	-38.0	13.18	3.8-7.6
	* HB	77	67	50-100	100	0	5.78	-23.5	13.00	3.8-7.7
60. Self-powered furnace ⁸	* AF	85	70	100-200	10 ²⁶	0	12.9	580	60.49	1.7-3.3
	* HB	85	70	100-200	10	0	9.68	120	29.74	3.4-6.7
61. Thermoelectric furnace ^{6, 27}	AF	80	66	400-800	10 ²⁶	0	7.58	580	47.55	8.4-17
	HB	80	68	200-400	10	0	7.12	120	23.46	8.5-17
62. Gas-fired heat pumps ^{8, 28}	* AF	140	120	300-500	930	0	49.2	-690	86.01	3.5-5.8
	HB	120	100	300-500	600	0	35.8	-668	54.40	5.5-9.2
	WH	130	110	200-400	250	0	20.2	-284	35.28	5.7-11
63. Natural convection systems ^{3, 29}	* AF	75	61	50-100	0	0	0.0	593	29.67	1.7-3.4
	HB	75	63	50-100	0	0	0.0	134	6.68	7.5-15

Footnotes:

1. AF = air furnace (100,000 Btu/hr); HB = hydronic boiler (100,000 Btu/hr); WH = water heater (45,000 Btu/hr).
2. Seasonal efficiency for furnaces based on 6-month heating season, Oct-Mar (4,368 hours), and for domestic water heaters on 12 months (8,760 hours).
3. Range of incremental first cost applies to both new and/or retrofit equipment.
4. Operating power is the rate of electric energy input while running.
5. Extra power is the constant electric input required above the baseline case.
6. Secondary air flow reduced to maintain the same steady-state efficiency after derating.
7. Average input for two-stage, modulating, or sequential valve operation assumed to be an average of the high and low fire inputs, or 75,000 Btu/hr.
8. This concept applies to new equipment only. Therefore, gas input was reduced by a ratio of the seasonal efficiencies to keep operating time constant ($q_2 = q_1 \times \eta_1 / \eta_2$).
9. Power blower assumed to be 100 watts input with electric ignition of 15 watts for furnaces, and 50 and 15 watts for water heater.
10. Power input assumed to be a 100-watt blower operating 0.1 of the time (or 10 watts), and a 15-watt ignition input.
11. Combustion air blower assumed to be 200 watts for furnaces and 100 watts for water heater.
12. Submerged combustion systems would be separate from high line pressures in boilers or water heaters. Power blower of 200 watts assumed for furnaces and 100 watts for water heater.
13. Extra operating power needed for controls, etc.
14. Double damper assumed to be useful only on hydronic boilers and water heaters, as they maintain higher standby temperature levels.
15. With a power vent, it is assumed that a vent restriction of some type is included to minimize the escape of room air during the off cycle.
16. Setback assumed to nighttime for furnaces and a permanent 20 F for water heaters.
17. Extra continuous electric power needed for clock thermostat, controls, etc.
18. Extra electric power required for solenoid valve.
19. Assumed power reduction of one-half for low speed operation, and operating for one-half of the time at low speed.
20. Assumed 10 percent power reduction due to improved design.
21. Extra power for heat storage pump assumed to be 100 watts, but operating only one-half the time, and blower power increased 10 percent due to increased pressure drop of heat exchanger.
22. Replacement costs include removing old equipment, installing a properly sized furnace and allowing for the higher efficiency, and assuming power savings of 10 percent due to improved motors.
23. An instantaneous water heater would have an input rating of about 200,000 Btu/hr.
24. Combination appliances assumed to have the same total gas input rating as furnace only (i.e., 100,000 Btu/hr), and also the same electric input rating, as improved motor efficiencies would likely be offset by increased running time because functions are combined. However, overall lower operating time will result because of increased seasonal efficiency.

Footnotes: (Continued)

25. Average adjusted input assumed to be 80,000 Btu/hr, with lower blower speed also. (Pump speed not adjustable.)
 26. It was assumed that self-contained or thermoelectric furnaces will require about 10 watts for thermostat and gas valve during operation.
 27. The cost of a thermoelectric device to operate between the flue gas temperature and the incoming combustion air temperature was estimated on the basis of about \$1 - \$2 per watt. Presently the cost is about 10 times higher than this.
 28. A seasonal efficiency of 120 percent for a gas-fired heat pump represents a seasonal COP of 1.20. The efficiencies are slightly different for the three types of appliances because of their different temperature levels of operation. The outdoor fans were assumed to require 500 watts for the furnaces and 250 watts for the water heater.
 29. Natural convection (gravity) systems, using air, water, or steam, could be designed to have about the same overall seasonal efficiency as present forced circulation systems. Although first costs would increase, a net savings could be realized by eliminating the need for electrical operating power.
- * Selected items with payback period of 4 years or less.

where

$$\begin{aligned} \text{Total Savings, \$ / yr} = & (\text{Gas Saved, cu ft}) (\text{Gas Cost, \$ / cf}) \\ & + (\text{Electricity Saved, W-hr}) (\text{Electricity Cost, \$ / w-hr}) \\ & - (\text{Electricity Used, W-hr}) (\text{Electricity Cost, \$ / w-hr}). \end{aligned} \quad (2)$$

The gas saved was calculated from

$$\text{Gas Saved, cu ft / yr} = \frac{H}{1,020} \left(\frac{1}{\eta_1} - \frac{1}{\eta_2} \right) \quad (3)$$

where

H = Heating load, Btu/season

1,020 = Average energy content of natural gas⁽²⁾, Btu/ft³

η_1 = Seasonal efficiency of baseline condition, fraction

η_2 = Seasonal efficiency of improved system, fraction.

The heating load (H) for the furnaces was taken as 61×10^6 Btu/season (i.e., 100×10^6 Btu times 0.61), and the heating load for domestic hot water as 19×10^6 Btu/year (from Reference 1, for 500 gal/week at an 85 F temperature rise).

The electricity saved was calculated from the following equation, and represents the difference between the amount of electricity used in the conventional furnace and a modified furnace.

$$\text{Electricity Saved, W-hrs} = (H) (1.38) \left(\frac{W_1}{q_1 \eta_1} - \frac{W_2}{q_2 \eta_2} \right) \quad (4)$$

where

H = Heating load, Btu/season

1.38 = Multiplying factor representing the ratio of blower-on time to burner-on time⁽³⁾

W = Electrical power input during operation, watts

q = Furnace input rating, Btu/hr

η = Seasonal efficiency, fraction

1 = Baseline condition

2 = Improved condition.

Obviously, the amount of electricity save can be negative if, for example, the furnace has been derated so that $q_2\eta_2$ is less than $q_1\eta_1$.

The blower (or pump) operating time was obtained by multiplying the calculated burner operating time by a factor of 1.38, as given in the DOE guidelines for calculating seasonal efficiencies of furnaces⁽³⁾. The burner operating time was calculated simply as $H/q\eta$. Thus, the operating electric power required by the blower or pump is represented by the product of time and power input, or $(\frac{H \times 1.38}{q \eta})$ (W) watt-hours. For this study, it was assumed that a circulating pump on a hydronic boiler would operate similarly to an air blower (i.e., with a delayed shutoff time) for more efficient operation. Although the DOE guidelines suggest a factor of 1.0 for boilers instead of 1.38, some boiler manufacturers indicated to us that the actual factor is probably somewhere between 1.0 and 1.38. Therefore, the ratio factor of 1.38 was assumed for both the air furnaces and the hydronic boilers.

Another consideration was also given to blower operating time. Whenever new furnace equipment was being considered, rather than a modification of an existing furnace, then it was assumed that the new unit would have a lower input rating so that the total operating time would remain constant. In other words, $q_1\eta_1 = q_2\eta_2$ whenever new equipment was being considered. This was believed to be realistic from the standpoint of maintaining air circulation and comfort conditions in the home. Otherwise, a new unit having a seasonal efficiency of 90 percent, for example, would only run about two-thirds as much as the conventional furnace with a 61 percent seasonal efficiency, if their input ratings were kept the same.

The last term in Equation 2, electricity used, refers to any additional constant electrical input required by the efficiency improvement device. Such a device, for example, might be a clock thermostat or timer. The extra electrical power required by such a device is calculated by multiplying its constant power input by the number of hours in the heating season for a furnace, or in the year for a hot water heater (4,368 hours for an October-to-March season, or 8,760 hours in a year). This is expressed in equation form as

$$\text{Electricity Used, W-hrs} = (E)(N) \quad (5)$$

where

E = Electrical power required continuously, watts

N = Number of hours in season or year, hours.

The final expression for calculating the total savings is obtained by combining the above equations, and is

$$\begin{aligned} \text{Total Savings, \$ / yr} = & C_g \left(\frac{H}{1020} \right) \left(\frac{1}{\eta_1} - \frac{1}{\eta_2} \right) \\ & + C_e (H) (1.38) \left(\frac{W_1}{q_1 \eta_1} - \frac{W_2}{q_2 \eta_2} \right) \\ & - C_e (E)(N) \end{aligned} \quad (6)$$

where

C_g = Cost of gas, \$/cu ft

C_e = Cost of electricity, \$/w-hr.

As mentioned earlier, for this study the cost of natural gas and electricity was assumed to be \$2.50/1000 cu ft and 5¢/kWh, respectively.

As an example of the type of information contained in Table E-2, consider the second item under the Combustion Category, "Derating, 20 percent with secondary air baffle". For an air furnace, AF, the steady state efficiency would remain the same at 77 percent since the secondary air baffle would be adjusted to maintain the same flue loss. The seasonal efficiency was assumed to increase about 10 percent (from 61 percent to 67 percent) based on the recent A.G.A./SHEIP studies. The estimated incremental first cost of \$50-\$100 includes the cost of a service call, derating the furnace input 20 percent, installing and/or adjusting the secondary air baffle while measuring the flue gas temperature and CO_2 content to maintain a constant flue loss, and checking out the overall furnace control system operation. The range of cost allows for the labor variations that will exist when adjusting different types of furnaces in the field. The operating

power for the blower remains the same, 430 watts, and there is no extra power required for auxiliaries. Substituting these values into equation 3 reveals that 8.96 million Btu of gas will be saved. Equation 4 shows that 81.9 kWh more electricity will be consumed because of increased running time due to derating (actually, a negative savings). The total savings, from Equation 6, amounts to \$17.85 per season. Thus, the payback period based on Equation 1 ranges from 2.8 to 5.6 years. This concept, therefore, generally would be a worthwhile change to make to the average furnace.

If one wishes to calculate the primary energy savings realized by the example concept just discussed, the -81.9 kWh could be multiplied by the electric generating energy equivalent of 11,600 Btu input/kWh output. Thus, an additional 950,040 Btu per season of primary energy would be consumed for generating the extra electricity needed by such a furnace when derated 20 percent. Therefore, the net primary energy savings would be 8.01×10^6 Btu ($8.96 - 0.95 \times 10^6$) rather than the 8.96×10^6 Btu of natural gas energy saved.

For the purposes of this study, only the concepts showing a minimum payback period of 4.0 years or less were selected as being candidates for further consideration of research and development efforts. These selected concepts are shown with an asterisk in Table E-2, together with additional discussion and recommendations. Although some may argue for a longer or shorter payback period than the 4.0-year criterion, this was believed to be a reasonable time period. For example, the Air Force Logistics Command has been using a 6-year payback period to justify energy saving measures, and industrial firms often use a 2-year payback limit. Therefore, 4 years was believed to be a reasonable average time period for this study. A simple payback period of 4.0 years amounts to an 18 percent/year return on investment when using straight line depreciation and a 15-year equipment lifetime. Another economic measure shows that a 4.0 year payback period amounts to a 24 percent internal rate of return, again for a 15-year assumed lifetime.

Description of Energy Saving Concepts

Brief descriptions of the concepts listed in Table E-2 are given below so the reader can better understand the energy saving principles involved.

Combustion Category

1. Derating by Reduced Pressure or Reduced Orifice Only. The gas input rate to furnaces and water heaters can be reduced by either reducing the manifold pressure or by installing smaller orifices. This may save energy by allowing the furnace input to better match the heat load of the house, which reduces cycling losses. However, until more heat exchanger corrosion studies are conducted, the derating should be limited to no more than 20 percent, which would give 80 percent of the rated input.

2. Derating with Secondary Air Baffle. Besides reducing the gas input as described above, the flue gas outlet of the heat exchanger can be partially baffled to further increase the operating efficiency by reducing the amount of secondary air (see Figure 3, Appendix B). Recent corrosion studies by the AGAL have shown that baffling to obtain a constant flue loss of, say 20 percent, is better than adjusting for a constant CO₂ of, say 8.5 percent.

3. Derating, 20 Percent With Baffle, Plus Vent Restrictor. Similar to Item 2 above, except that a vent pipe restrictor is added downstream of the draft hood after the burner has been derated.

4. Two-Stage Gas Valve. This type of valve in the gas line will allow two firing rates for the burner, with the high firing rate being the normal rated input, and the low firing rate being about 50 percent. The low rate is accomplished by means of reduced manifold pressure, and is used during the milder winter months. The selection of firing rate can be either manual, or automatic by means of an outdoor thermostat.

5. Modulating Gas Valve. This type of control valve is similar to the two-stage valve, except that the firing rate is automatically modulated over some range of inputs. The firing rate is generally modulated to match the heating requirements, so the furnace may run continuously.

6. Modulating Gas and Air Valves. More efficient combustion can be achieved if the fuel/air ratio is kept constant by controlling both the gas and air flow rate during modulation.

7, 8. Power Burner. These burners are common on oil-fired equipment, and have three main advantages over naturally aspirated burners: (1) their fuel/air ratios can be set within tighter limits, (2) they minimize the escape of room air through the furnace during its off cycle, and (3) they can draw in outside air for combustion. These burners can be used on either condensing or non-condensing units.

9. Pulse Combustion Burners. The pressure oscillations in this type of burner are sufficient to be used to draw in outside combustion air and expel relatively low temperature flue products. It therefore is similar to having both a power burner and a power vent.

10, 11. Radiant Burner. These burners accomplish heat transfer by means of radiation from a high temperature surface on which the combustion takes place. They also can be used for directly heating objects. However, because of the high gas exit temperature required to maintain the glowing surface, means also must be used to recover heat from the flue products to achieve high overall efficiencies. The final heat exchanger section could be designed to be either condensing or non-condensing.

12, 13. Catalytic Burner. The use of some types of material, such as platinum, in contact with high temperature fuel and air, will promote better combustion reactions at generally lower temperatures. A catalyst is defined as a substance which alters the rate of a reaction, and is itself unchanged by the reaction. These systems can be either condensing or non-condensing.

14. Submerged Combustion. By pressurizing the combustion zone, it is possible to pass the combustion products directly through the liquid being heated. Higher efficiencies are achieved because the combustion products are cooled to the temperature of the liquid and because condensation of the water vapor is achieved.

15. Sequential Firing of Sections. By firing only the number of furnace section (or modules) required to meet the heating load, a step-wise modulation could be achieved. However, a limited number of experiments have shown that migration of flue products to the unfired cold sections can cause severe corrosion problems.

Combustion Air Category

16. Sealed Combustion. This refers to the use of all outside air for the entire combustion system, so that no room air escapes to the outside via the furnace or venting system. Care must be taken to avoid backdrafts created by wind pressure effects on the building. This concept is considered herein as applying to new equipment only. While it could be used in a retrofit mode, the cost of modification, and the necessity of checking the backdraft performance, would move it into an over 4-year payback case. Thus, it has not been considered herein as a retrofit device.

17. Reduce Excess Air. Present gas-fired furnace and heat systems use about 40 percent excess air for combustion. By careful design, this could probably be reduced to about 25 percent for natural draft units, and about 15 percent for forced draft equipment. (5.1)

18. Preheater for Combustion Air. The waste heat in the flue gases could be utilized to preheat the combustion air, thus improving the overall efficiency. Some type of heat exchanger would be required to prevent recirculation of the combustion products.

19. Outside Installations. When the heating equipment is installed outside of the residence, the situation is similar to having a sealed combustion system except for some additional heat losses from the jacket and duct connections. It was assumed that water heaters would not be installed outdoors because of the potential freeze-up problems in most areas of the U.S.

Venting Category

20, 21, 22. Vent Damper. A device that automatically closes off the vent pipe between the chimney and the draft hood to prevent the escape of room air up

the chimney while the burner is off. Damper systems are available which are activated either electrically (by solenoids), mechanically (by gas pressure), or thermally (by heat in the flue products) when the burner cycles on and off.

23, 24. Double Damper. A damper system which simultaneously closes off the vent pipe leading to the chimney and the flue pipe leading to the draft hood. This prevents room air from escaping up the chimney as well as from passing through the heat exchanger to cool the hot water reservoir, for example. This concept is adaptable primarily to hydronic boilers and water heaters because of their higher standby jacket temperatures.

25. Vent Damper, Vent Restrictor, Derate (20 Percent With Baffle), and Electric Pilot. This combination of four concepts represents about the highest amount of savings that could be achieved by retrofitting existing equipment. (Based on the A.G.A.'s SHEIP study.)

26. Vent Restrictor. A device which is permanently positioned in the vent pipe to reduce the flow of draft-hood dilution air to a minimum. In effect, this restricts the draft of a chimney to a point where no flue products will escape from the draft hood into the occupied space even during mild weather.

27. Draft Hood Replacement. This concept assumes that most present draft hoods allow too much dilution air to escape up the chimney, so that smaller flow areas or more restriction to flow could be used.

28. Increased Flue Baffling. Based again on the assumption that too much dilution air is allowed to flow into the draft hood, greater restriction to the flow of dilution air could be incorporated.

29. Power Vent. The use of a fan, ejector, etc. can assist in the flow of stack gases up the chimney. Such a forced-draft system also tends to minimize the escape of room air during the burner-off cycle.

Heat Exchange Surface Category

30. Heat Pipe Heat Exchanger. Heat pipes transfer heat mainly in one direction only, and thus could help prevent heat losses from a heated water tank or reservoir during the off cycle.

31. Condensing Flue Products. The water vapor generated by the combustion process contains a substantial amount of heat (about 10 percent of the total available), and this can be regained if the flue products are cooled to below the dew point temperature (about 130 F).

32. Side Arm Heater. The use of a separate "side-arm type" heater for a hot water storage tank would lessen the amount of standby losses from the primary heat transfer surface.

Ignition Category

33. Reduced Pilot Input. An operating pilot usually consumes about 1 cubic ft of gas per hour, so designs with reduced inputs might save about 2 percent of the total amount consumed, both in furnaces and water heaters.

34. Electric Pilots. An "Intermittent Ignition Device" (IID), as they are called, uses an electric spark to first ignite a gas pilot flame. When the pilot flame is proven to be lit, then the main gas valve opens. Thus, the continuous-burning pilot is eliminated.

35. Direct Spark Ignition (DSI). This device differs from the IID in that the electric spark is used to directly ignite the main burner flame rather than a pilot flame. Here again, the continuous-burning pilot is eliminated.

Controls Category

36. Thermostat Setback. This concept refers to the reduction of thermostat settings in the winter, and an increase of settings in the summer, for a given period of time each day. Clock thermostats are available to automatically accomplish this; it also can be done manually.

37. Time-of-Day Input. If and when time-of-day pricing affects gas rates, then devices which allow heating only during the lowest rate (off-peak) periods will save money. Such schemes already are in use for electrical water heaters in some areas. Some energy will be saved, also, because one long heat-up period will be substituted for several on/off cycles.

38. Fan Control Temperature Adjustment. Lower temperature settings (e.g., 130 F on/90 F off) and less temperature differential (e.g., 120 F/90 F) have been shown to save energy by allowing the furnace blower to come on sooner and operate longer. The breakover point is when the extra cost for blower electricity exceeds the reduced gas cost because of increased efficiency.

39. Fewer Burner Cycles. Current thermostats are designed to cycle the furnace burner about 5 to 6 times per hour over a wide range of heating loads, typically 20 to 80 percent. However, longer burner ON times and fewer burner cycles, say 2 to 3 times per hour, will improve the seasonal efficiency. This can somewhat be accomplished by adjusting the anticipator setting in the thermostat. Otherwise, new thermostat designs will be required.

40. Humidity Limit Control. It requires heat energy to evaporate water, so means of limiting the amount of water evaporated will save gas. For example, to operate a humidifier with a rated evaporation capacity of 15 gallons per day requires a heat input rate of about 5,200 Btu/hr. This represents about 5 percent of the furnace input rating (typically 100,000 Btu/hr), and therefore about 50 hours of burner operation out of about 1,000 hours per season.

41. Temperature Modulating Thermostat. In water boilers, it is advantageous to reduce the temperature to which the water must be heated in accordance to the heating load. These types of temperature modulating thermostats are termed "reverse acting aquastats", and generally adjust the setpoint temperature from, say 180 F down to 120 F, by sensing the outdoor air temperature. This feature also minimizes the jacket and pipe heat losses during the summer months if the system is not shut off.

42. Microprocessor Control. The use of pre-programmed micro-processor controls can optimize system performance for a wide range of operating conditions. For example, they could control on/off cycle times, temperature setbacks, firing rates, etc.

43. Central Control Center. The location of all of the heating appliance controls in one area would allow the occupants to control and observe the operation of the various systems. For example, the water heater's temperature could be increased just before peak demands were required, such as for washing clothes or bathing.

Heat Delivery System Category

44. Waste Heat Recovery. Since normally about 20 to 25 percent of the input energy is lost up the stack during steady-state operation, and even more during cyclic operation, it is possible to improve the overall efficiency by recovering some of the so-called "waste heat". This can be accomplished in several ways, including an additional heat exchanger installed in the vent pipe to heat room air or to preheat combustion air.

45. Two-Speed Blower. Having a lower speed setting controlled by the plenum air temperature would allow the blower to extract more residual heat from the heat exchanger while still maintaining a more comfortable air supply temperature.

46. Improved Blower Design. Increasing the blower efficiency by improving the blower wheel and scroll design would primarily save electrical energy.

47. More Efficient Electric Motors. The use of electric motors with higher efficiencies will lower the operating costs of blowers and pumps.

48. Zone Temperature Control. This concept involves controls which would allow different temperature levels to be maintained in separate zones or rooms of a residence. This might involve thermostatic controls of dampers in a forced-air system and of solenoids in a hydronic system.

49. Warm Room. The basic idea is to maintain one (or two) rooms at a comfortable temperature level while allowing the rest of the house to remain relatively cool. This might be accomplished by zone temperature controls discussed elsewhere, or by installing a separate space heater, etc. in the "warm room".

50. Storage of Heat. By incorporating means of storing heat produced by the furnace, the furnace could operate for longer periods of time at its steady-state efficiency level and then remain off for longer periods of time while heat is extracted from storage. Such energy storage could be accomplished by using rocks (in a forced-air system) or water (with forced-air or hydronic systems).

Field Adjustments Category

51. General Tuneup and Cleaning. In existing furnaces and hot water systems, a general tuneup of the controls and combustion characteristics, as well as cleaning of the heat exchangers, ducts, radiators, etc., will improve the overall performance.

52. Insulation Jacket. Increasing the thickness of the insulation on water heaters will lessen their heat loss to the surroundings.

Improved Equipment Category

53. Replace Existing Equipment. The newer, more-efficient appliances now appearing on the market could be used to replace some of the older less-efficient models in existence. Some of these newer appliances include electric pilots, automatic vent dampers, and more efficient motors. Further improvements are expected as manufacturers work toward increasing their seasonal operating efficiencies, and as new types of systems are introduced.

54. Instantaneous Water Heaters. Although considerably larger heat input rates are required for this type of water heater (e.g., 200,000 vs. 40,000 Btu/hr), they can achieve a higher overall operating efficiency because standby losses are minimized.

55. Design for Less Scaling. The heat transfer surface areas in a domestic water heater could be designed to be less susceptible to scaling and degradation. The bottom surfaces which are nearly horizontal are most affected.

56. Minimize Heat Leaks. Present domestic water heaters have heat conduction leaks via pipe connections, valves, legs, etc. which penetrate the insulation jacket. These could be minimized by more careful design.

57. Heat Traps for Hot Water Pipe. An inverted U-shaped outlet connection for the hot water pipe will lessen standby heat losses because natural circulation patterns are restricted. Studies at Purdue University show about 300 Btu/hr saved.

58. Combination Appliances. By combining the functions of space heating and water heating into one appliance, it should be possible to realize some overall energy savings. This approach is becoming more feasible since the design heating loads of new homes is approaching that of the domestic water heater, i.e., about 40,000 to 45,000 Btu/hr.

59. Field Adjustable Heat Input. This concept would allow the heat input to a furnace to be easily adjusted in the home to properly match the heating requirements. The adjustments should include fuel/air ratio and motor speed. However, as better prediction models are developed for the proper sizing of a heating system, this concept becomes less advisable.

60. Self-Powered Furnace. This concept would eliminate the need for electricity. Such designs include the gravity-type systems (air or steam), and the Rankine Cycle systems which drive their own blower.

61. Thermoelectric Furnace. These furnaces would generate both heat and electricity, and thus could be a self-powered system. Present thermoelectric cells have an efficiency of about 5 percent and could use a temperature differential of about 600 F.

62. Gas-Fired Heat Pumps. A heat pump is designed to supply either heating or cooling, and much work is presently being conducted by GRI and DOE on such gas-fired units. Current work is being directed toward the following types of heat pump systems; absorption, Rankine, Stirling, and Brayton cycles. The average heating COP is expected to be about 1.2, and the average cooling COP about 0.7. Commercialization will take at least until 1985.

63. Natural Convection Systems. Heating systems are in use that depend upon the natural circulation of heated air, water, or steam to transport heat throughout a house. Until recently, however, these types were considered "old fashioned" (e.g., the wood stove or steam radiators). Generally, larger ducts or pipes are required, but the need for electrically driven blowers or pumps is eliminated. It should be possible to design such "gravity" systems with seasonal efficiencies equal to present-day forced circulation units.

APPENDIX E REFERENCES

1. Arthur D. Little, Inc., "Study of Energy-Saving Options for Refrigerators and Water Heaters, Volume 2: Water Heaters", report to The Office of Transportation and Appliance Programs, Federal Energy Administration (May, 1977).
2. American Gas Association, "Gas Facts, 1977 Data", published by the A.G.A., Department of Statistics, 1515 Wilson Boulevard, Arlington, Virginia 22209.
3. Federal Register, "Part 430 - Energy Conservation Program for Appliances. Test Procedures for Furnaces and Vented Home Heating Equipment", V 43, No. 91, Part II, p 20164 (Wednesday, May 10, 1978).
4. American Gas Association Laboratories Research Report 1523, "Evaluation of Proposed DOE Efficiency Rating Procedure for Furnaces", to Gas Appliance Manufacturers Association (Jan, 1978).

APPENDIX F

INSTITUTIONAL BARRIERS RELATED TO SAFETY

APPENDIX F

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	155
DESIGN CERTIFICATION	155
SAFETY CONSIDERATIONS.	156
CODE BARRIERS.	156
CONCEPTS NOT COVERED BY CODES OR STANDARDS	158

APPENDIX F

INSTITUTIONAL BARRIERS RELATED TO SAFETY

INTRODUCTION

The purpose of this task is to review the safety related factors of the concepts identified in Appendix E, Table E-2, as having potential for improving the efficiency of furnaces, boilers and/or water heaters. The approach was to consider each concept in light of safety and applicable codes and standards. Inasmuch as the primary purpose of these codes and standards is to provide safety in the use of gas, any concept which was found to be not covered or in conflict with their provisions was noted and a judgement was made as to potential risk. No Risk denotes no additional risk over what currently exists.

The concepts considered in this analysis are numerically listed and described in Appendix E.

DESIGN CERTIFICATION

The display of the A.G.A. Laboratories' Certification Seal or Symbol on a gas appliance or accessory is a representation by its manufacturer that the unit, at the time it left the manufacturer's control, conformed with the design which was examined by A.G.A. Laboratories and found to comply with the appropriate American National Standard. These standards are promulgated by independent committees operating under and in accordance with the rules of the American National Standards Institute and other standards setting bodies. A.G.A. has no means of assessing the effect of field alteration on a design certified appliance, and accordingly such alterations must be the responsibility of the person making or authorizing them. This does not mean that the certification with respect to such an altered appliance is "withdrawn" or "void", it only means that A.G.A. cannot be responsible for the determination as to whether such appliances continue to comply with the standard.

SAFETY CONSIDERATIONS

Concepts which involve No Risk: 36-41, 43, 47-49; Concept 42 involves No Risk for all examples given with the exception of the control of firing rates which could result in safety problems unless the appliance designs were certified for use at the controlled firing rates.

The following concepts involve No Risk if the appliance has been design certified: 3-11, 16-19, 29-35, 45-46, 50, 52-62. There is a minor barrier to concept 32: The ANSI Standard for Side Arm-Type Water Heaters no longer exists. A new standard, if warranted, could be developed expeditiously.

Concepts which involve a risk even though an appliance may have been design certified incorporating the concept: 12, 13, 15, 20-24, 44; concept 12-13 due to the fact that too little is currently known about catalyst life and catalyst poisoning; concept 15 due to the reason included in the description of the concept; and concepts 20-24 due to the increased potential for CO, explosions, or fire hazards in the event of the control system or mechanical failure.

Concepts which involve risk inasmuch as they are retrofit concepts: 1 3, 25-27, 28; and concepts which involve risk if they are utilized as retrofit concepts are 4-6, 15, 20-24, 34, 35, 44, 52. A significant risk exists due to the fact that the safe operation of appliances using these concepts is dependent on the installer rather than the appliance designer. Modification of an appliance or system so it can operate outside its design parameters requires knowledge and engineering ability which is beyond the capability of most service people.

Concept 51 involves a "negative risk" in that it should eliminate some potentially hazardous existing installation.

CODE BARRIERS

There are no known code barriers on any concept for which the appliance has been design certified. Code barriers do exist, however, for

some concepts which require field modification of a design certified appliance or of an existing installation. These code barriers are safety related and exist due, in part, to past gas industry experience.

Specific barriers that appear in ANSI Z223.1-1974 National Fuel Gas Code (which is a basis for and typical of other model codes) are:

Concepts 1, 2:

- 1.4.1 - A listed appliance or accessory may be installed in accordance with its listing, or as elsewhere specified in 1.4.
- 1.6.1.1 - Each burner shall be adjusted to its proper input in accordance with the manufacturer's instructions. Over rating of burners is prohibited.

Concepts 2,23,24,28

- 1.3.1.10 - No device or attachment shall be installed on any appliance which may in any way impair the combustion of gas.

Concepts 26,44

- 1.5.8.6 - The vent connector shall be installed so as to avoid excessive turns or other construction features which create unnecessary resistance to flow or vent gases.

Concept 27

- 1.3.2.1 - (a) Every vented appliance, except incinerators, dual oven-type combination ranges, direct-vent appliances and units designed for power burners or for forced venting, shall be installed with a draft hood. The draft hood supplied with or forming a part of listed vented appliances shall be installed without alteration, exactly as furnished and specified by the appliance manufacturer. If a draft hood is not supplied by the appliance manufacturer

when one is required, it shall be supplied by the installing agency, be of a listed or approved type and, in the absence of other instructions, be the same size as the appliance flue collar. When a draft hood is required with a conversion burner, it shall be of a listed or approved type supplied by the installing agency or as recommended by the manufacturer.

(b) When the installer determines that a draft hood of special design is needed or preferable for a particular installation, advice of the manufacturer, the serving gas supplier or authority having jurisdiction shall be secured.

Proposals to modify the National Fuel Gas Code to permit Concepts 1 and 2 were proposed in 1977 and were deferred pending further information on safe appliance operation and heat exchanger corrosion. A proposal to permit Concept 26 was proposed in 1977 and rejected.

CONCEPTS NOT COVERED BY CODES OR STANDARDS

Although the standards used for design certification of gas appliances do not anticipate Concepts 9, 12-14, 31, 61 and 62, revisions could be made to standards when designs have progressed sufficiently to intelligently develop the needed coverage.

Work is currently in progress to develop coverage for Concept 23-24 with respect to Water Heaters.

APPENDIX G

NON-SAFETY INSTITUTIONAL BARRIERS

APPENDIX G

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	162
OBJECTIVE AND SCOPE.	163
METHOD OF APPROACH	163
RESULTS.	164
MECHANICS OF INTRODUCING NEW GAS-HEATING EQUIPMENT	165
Certification of New Equipment.	166
A.G.A. Laboratories Testing and Certification Procedure.	167
A.G.A. Processing of New or Revised Standards.	171
Installation of New Equipment	171
Model Codes.	171
Municipal Codes.	175
Legal Requirements as Potential Barriers to Commercialization of New Gas-Heating Appliance Technology	178
CONCLUSIONS AND RECOMMENDATIONS.	179
REFERENCES	180

LIST OF TABLES

Table G-1. ANS Standards Governing A.G.A. Testing/Certification of Residential Natural Gas-Fueled Heating Appliances and Accessories.	168
Table G-2. Model Codes Governing Installation of Residential Gas-Fueled Heating Appliances.	172
Table G-3. Residential Gas-Fueled Heating Appliance Installation Example Requirements Specified in Selected Codes	174
Table G-4. Survey of Municipal Codes Regulating Installation of Residential Gas Appliances	176

TABLE OF CONTENTS (Continued)

LIST OF FIGURES

	<u>Page</u>
Figure G-1. Topical Listing Extracted from the Table of Contents of Z21.47, Gas-Fired Gravity and Forced-Air Central Furnaces.	169
Figure G-2. Topical Listing Extracted from the Table of Contents of Z21.20, Automatic Gas Ignition Systems and Components.	170

APPENDIX G

NON-SAFETY INSTITUTIONAL BARRIERS

INTRODUCTION

In recent years the process of introducing technological change into the public domain has included recognition of the potential role that institutional factors can play. Environmental constraints and consumer protection have molded product liability concerns that manufacturers must consider. Thus, commercialization of advanced technology products necessarily includes interaction with the organization and formal procedures of American society.

For the rather specific technology of gas-fueled equipment designed for energy conservation in residential heating applications, the institutional factors can be grouped into (1) incorporation of the technology into the design repertory of the architectural and engineering professions, (2) assimilation of the technology by the construction, utility and appliance service industries, and (3) compliance of products with legal requirements. The first two, which involve problems of information dissemination and education, are not considered serious (referenced, for example, to the same considerations applied to solar energy technology). It is the third group that commands detailed attention in the present task.

OBJECTIVE AND SCOPE

The objective of this task is to characterize the problems of commercialization likely to confront the introduction of energy effective devices in natural gas-fueled residential heating systems (space and domestic water). In conjunction with that objective, the scope of the investigation has been confined to non-safety related institutional factors.* Furthermore, as discussed in the following subsection on Method of Approach, the scope is sharply focused upon potential barriers associated with product compliance to legal requirements.

METHOD OF APPROACH

The method of approach to the present study contains several distinct elements. One pertains to providing the study with a broad outlook on the problem of new concept commercialization. A useful expedient was taken by adapting the experience gained during the study documented in Reference 1. In that study, which dealt with solar heating and cooling systems, two of the principal topics addressed involved (1) institutional studies and (2) user acceptance and system/component exploitation factors. Several of the ideas contained in those topical discussions appeared to be relevant to the present study and have been adopted after judicious modification.

Among the more specific elements of the study was the collection (for comparison purposes) of standard codes governing the installation of natural gas-fueled appliances (in residential applications). These codes have been promulgated in the interest of regional, if not national, uniformity. More importantly, they constitute the technical bases for state and municipal legal sanctions.

A corollary specific study element was the survey of some two dozen cities to determine (1) the degree of adoption of standard codes, (2) the general nature of departures from standard codes, and (3) the procedures for effecting changes in municipal codes.

* Safety-related factors are addressed in a separate task report of the present study.

RESULTS

Unlike the emerging solar energy technology that is being introduced into the energy utilization market, natural gas appliance technology is mature and is being supported by a well entrenched infrastructure. The difference between the two technologies with respect to institutional and user acceptance factors is one of degree as can be surmised from the following list adapted from Reference 1.

- Incorporation of _____* into the design repertory of the architectural and engineering professions
- Assimilation of _____ by the construction, utility and support service industries
- Compliance of _____ with legal procedures
- Development of public policy encouraging _____ technology
- Formulation of standards and procedures for _____ design and implementation practice
- Assembly of materials responsive to _____ user educational and information needs
- Assessment of _____ reliability and safety
- Organization of _____ advertising and promotional campaigns
- Demonstration of _____ technical and economic feasibility.

At the present time, all but one of the above factors appear to be straightforward in their relevance and application to natural gas energy conservation equipment. The exception is "compliance to legal procedures", which is the focus of the remaining discussion.

* The blank may be filled either by "solar heating and cooling system" or by "natural gas energy effective equipment". Safety appears in the list only for the sake of completeness; it is addressed in a separate task of the present study.

MECHANICS OF INTRODUCING
NEW GAS-HEATING EQUIPMENT

In general, the legislative body of a municipality may pass an ordinance or statute that stipulates requirements for the installation and performance of equipment in buildings. The legislation may refer to or directly incorporate a codified set of recommendations from the municipality's Building Official, who heads another municipal agency that is responsible for assembly of the technical specifics for the code. Over the years the trend has been for the Building Official to recommend for adoption one of the model codes that have been developed by various industry associations. Modifications to satisfy local considerations are made by exercising the right of "home rule".

The model codes referenced in the previous paragraphs deal with the installation of equipment. These (installation) codes provide for the acceptability of equipment performance by two mechanisms: (1) approval by the municipality's Building Official and (2) and in some cases approval based on a listing published by a recognized testing agency. The requirement for Building Official approval not only preserves home rule powers but also provides for the review of "unlisted" equipment.* The two principal recognized listings for natural gas-fueled appliances are those of the American Gas Association (A.G.A.) Laboratories and the Underwriters Laboratories (UL).

It is evident that in regard to the commercialization of new residential gas-fueled heating equipment, two important steps should be included in product planning.

- Check the equipment certification procedures required to qualify for the published listing of a testing agency
- Check the requirements of the nationally recognized model codes governing equipment installation.

In the following subsections, these two considerations are addressed in detail.

* The mechanics for seeking approval of unlisted equipment generally requires a manufacturer to submit specifications to the Building Official or designated agency. This procedure may be a high risk expedient for advanced concepts.

Certification of New Equipment

At present there are no mandatory requirements for the certification of natural gas appliances. However, the acceptance of new equipment by municipal regulatory agencies is greatly enhanced by manufacturer participation in a voluntary certification program such as the one conducted by the A.G.A. Laboratories.

Satisfactory completion of testing and certification procedures entitles a manufacturer's product to bear an A.G.A. certification seal (the well known "Blue Star") and to be listed in A.G.A.'s "Directory of Certified Appliances and Accessories". The continuance of certification-in-good-standing is assured by three procedures: (1) a minimum of two annual inspections (one announced and another unannounced) of production facilities; (2) required conformance to revisions of standards by products manufactured subsequent to the effective date of a revision; and (3) possible verification of certification by retest (at the discretion of A.G.A.) after a five-year interval during which no changes in product design or applicable standard have occurred.

It is important to distinguish between the test/certification procedure and the standards that govern the procedure. The A.G.A. Laboratories serves as a test/certification agency. The A.G.A.'s Cleveland Laboratories also house the Standards Department, which functions independently as the secretariat for the American National Standards (ANS) Committees Z21, Z28, and Z223.* It is the Standards Department that processes the promulgation of new or revised standards developed by these independent committees. Thus, the commercialization of advanced residential heating equipment can benefit not only from placement on the A.G.A. listing through the test/certification procedure but also from early anticipation of needs for changes in the standards.

* Z21 is the ANS Committee on Performance and Installation of Gas Burning Appliances and Related Accessories

Z28 is the ANS Committee on Industrial Gas Equipment, Installation and Utilization.

Z223 is the ANS Committee on National Fuel Gas Code, which is of concern in the present study.

A.G.A. Laboratories Testing
and Certification Procedure

Arrangements for the voluntary test and certification of natural gas appliance and accessory designs to determine compliance with national recognized standards are made with the A.G.A. Laboratories' Testing Department. The test program is divided into three parts:

- Construction - Determination of manufacture in accordance with minimum construction specifications contained in an applicable standard and in accordance with reasonable concepts of safety, substantiality and durability.
- Performance - tests of equipment safety and performance (e.g., ignition system operation, combustion behavior, thermal efficiency, etc.).
- Description - compilation of descriptive record of the equipment tested for use in the follow-up inspection program.

After satisfactory completion of the test program, data are review and documented in a report to the manufacturer. Equipment compliance with provisions of applicable standards results in certificate issuance and equipment listing.

ANS standards that are relevant to the kinds of new equipment and installation procedures being considered for further development (i.e., furnaces, boilers, water heaters, combustion air supply, venting and controls) are correlated in Table G-1. Typical levels of detail are indicated by the topical listing extracted from the tables of contents for two examples (Z21.47 and Z21.20) and shown in Figures G-1 and G-2. Because specific procedures (e.g., test conditions and performance criteria) are involved in testing for equipment performance, the submission of new equipment featuring advanced technology should recognize possibilities of requiring new test equipment, test operational procedure and even performance criteria. Thus, subsequent to securing patent protection, plans to commercialize should include an early approach to the test agency to discuss potential requirements not covered by or in conflict with existing standards.

TABLE G-1. ANS STANDARDS GOVERNING A.G.A. TESTING/CERTIFICATION OF
RESIDENTIAL NATURAL GAS-FUELED HEATING APPLIANCES AND
ACCESSORIES

ANS Standard	Heating Appliance or Accessory		
	Appliance/ Performance	Combustion Air Supply/Venting	Controls
<u>Appliances (a)</u>			
Z21.10.1, Gas Water Heaters, Volume I Automatic Storage Type Water Heaters With Inputs of 75,000 Btu Per Hour or Less	X	X	X
Z21.47, Gas-Fired Gravity and Forced Air Central Furnaces	X	X	X
Z21.13, Gas Fired Low Pressure Steam and Hot Water Heating Boilers	X	X	X
<u>Accessories</u>			
Z21.21, Automatic Valves for Gas Appliances			X
Z21.18, Gas Appliance Pressure Regulators			X
Z21.23, Gas Appliance Thermostats			X
Z21.22, Relief Valves and Automatic Gas Shutoff Devices for Hot Water Supply Systems			X
Z21.20, Automatic Gas Ignition Systems and Components			X
Z21.12, Draft Hoods		X	

(a) Room heaters and floor and wall-type furnaces are beyond the scope of
interest of the present study.

PART I. CONSTRUCTION

1.1	Scope
1.2	General
1.3	Connections
1.4	Bolts, Nuts and Screws
1.5	Adjustments
1.6	Means for Ignition, Proof of Igniter, and Proof of Ignition
1.7	Electrical
1.8	Instructions
1.9	Marking

PART II. PERFORMANCE

2.1	General
2.2	Test Gases
2.3	Test Pressures and Pilot Burner Adjustments
2.4	Pilot Operating Characteristics
2.5	Timings
2.6	Continued Performance
2.7	Safety Circuit Analyses
2.8	Effects of Voltage Variation
2.9	Dielectric Strength
2.10	Accuracy and Stability of Flame Sensing Devices Responsive to Ambient Temperature
2.11	Substantiality of Sensing Elements
2.12	Marking Material Adhesion and Legibility

Figure G-1. Topical listing extracted from the table of contents of
Z21.47, gas-fired gravity and forced-air central furnaces

PART I. CONSTRUCTION

1.1	Scope
1.2	General Construction and Assembly
1.3	Materials
1.4	Combustion Air Supply
1.5	Water Heater Openings
1.6	Burners
1.7	Flame Spreaders
1.8	Primary Air Control
1.9	Main Burner Orifices and Orifice Fittings
1.10	Automatic Ignition Devices
1.11	Pilot Gas Filters
1.12	Gas and Water Connections
1.13	Opening for Relief Valve
1.14	Dip Tubes
1.15	Manually Operated Gas Valves
1.16	Gas Appliance Pressure Regulators
1.17	Adjustment of Minimum Input Rating
1.18	Thermostats
1.19	Automatic Valves
1.20	Bleeds and Vents
1.21	Temperature Limiting Devices
1.22	Flue Collars
1.23	Flue Pipe Extensions
1.24	Draft Hoods
1.25	Electrical Equipment and Wiring
1.26	Vent-Air Intake Pipes of Direct Vent Systems
1.27	Instructions
1.28	Marking

PART II. PERFORMANCE

2.1	General
2.2	Test Gases
2.3	Test Pressures and Burner Adjustments
2.4	Combustion
2.5	Burner and Pilot Operating Characteristics
2.6	Pilot Burners and Safety Shutoff Devices
2.7	Direct Ignition Systems
2.8	Heat Required to Supply Daily Quota of Hot Water
2.9	Manually Operated Gas Valves
2.10	Gas Appliance Pressure Regulators
2.11	Automatic Valves
2.12	Thermostatic Control
2.13	Storage Heater Temperature Limits
2.14	Quantity and Temperature of Hot Water
2.15	Temperature Limiting Devices
2.16	Pressure Relief Valves
2.17	Vacuum Relief Valves
2.18	Surface Temperatures
2.19	Wall, Floor and Ceiling Temperatures
2.20	Flue Gas Temperature
2.21	Temperature of Manually Operated Parts
2.22	Flame Spreader Temperatures
2.23	Flue Collars
2.24	Draft Hoods
2.25	Wind Test
2.26	Capacities of Storage Vessels
2.27	Storage Vessels
2.28	Nonmetallic Dip Tubes
2.29	Burner Durability
2.30	Tubing and Fittings
2.31	Rain Test
2.32	Direct Vent Systems
2.33	Marking Material Adhesion

Figure G-2. Topical listing extracted from the table of contents of
Z21.20, automatic gas ignition systems and components

A.G.A. Processing of New or Revised Standards

Suggestions for new or revised standards may be submitted by an organization or individual to the appropriate Standards Committee for which A.G.A. is secretariat (e.g., Z223). Such suggestions are incorporated into the agenda of a subcommittee meeting, which may be attended by the proposer of the suggestion. For changes of other than an editorial nature a review and commentary of the proposal is prepared and distributed for comment to interested parties (utilities, manufacturers, standards committees, and Federal agencies, including the Consumer Product Safety Commission). Some 300-650 copies are usually distributed by Z223 for this review. Based upon comments received, a consensus is revised at the subcommittee level and submitted to the main committee for approval and forwarding to ANS. Before adoption of new standards or substantial revisions, ANS requires a 60-day public review period.

The feature of standards promulgation and revision that deserves emphasis here is the time interval required for that activity--months to possibly in excess of a year.

Installation of New Equipment

As previously mentioned, the installation of new gas heating equipment in buildings is specified in the various nationally recognized model codes, all or parts of which may be incorporated into a municipal code. In the following discussion, an overview is given of the model codes and the results are summarized for a complementary survey of municipal practices.

Model Codes

The model codes that are most likely to be encountered in the commercialization of advanced technology gas heating devices are listed in Table G-2.

TABLE G-2. MODEL CODES GOVERNING INSTALLATION OF RESIDENTIAL
GAS-FUELED HEATING APPLIANCES

Code	Issuing Agency (a)	Comment
One and Two Family Dwelling Code	AIA BOCA ICBO SBCC	A composite of provisions drawn from other model codes and applied specifically to one and two family dwellings
Basic [Building, Mechanical, Plumbing] Code (b)	BOCA	
National [Building, Plumbing, Electrical] Code	AIA	
Code for the Installation of Heat Producing Appliances (c)	AIA	
Standard [Building, Gas, Plumbing] Code	SBCC	
Uniform [Building, Mechanical, Plumbing]	ICBO	
National Fuel Gas Code	ANS	Also known as ANS Z223.1 or as NFPA No. 54
NFPA Standards	NFPA	
No. 54 National Fuel Gas Code		Pocketbook editions
No. 70 National Electrical Code		
No. 70A Dwelling Electrical Code		
No. 85 Single Burner Boiler-Furnaces		
No. 89M Heat Producing Appliance Clearances		
No. 90B Warm Air Heating and Air Conditioning Systems		
No. 211 Chimneys, Fireplaces and Vents		

Footnotes for Table G-2

(a) Acronyms

A.G.A. American Gas Association
AIA American Insurance Association
ANS American National Standards
ASME American Society of Mechanical Engineers
BOCA Building Officials and Code Administrators International, Inc.

ICBO International Conference of Building Officials
NFPA National Fire Protection Association
SBCC Southern Building Code Congress International

(b) Separate codes are issued for each item in the brackets.

(c) This is the analog for a National Mechanical Code.

With regard to the relationship of existing codes to advanced technology equipment, the topics that are of direct concern are: *

- Appliance installation clearances (including accessibility)
- Combustion air supply
- Circulating air (for warm-air heating)
- Flue gas venting.

The One and Two Family Dwelling Code (which is representative of the AIA, BOCA, ICBO, and SBCC model codes**) and the National Fuel Gas Code (a combined ANS and NFPA code) are used in Table G-3 to illustrate the mix of qualitative and quantitative requirements of the above topics. Although both codes generally address the same topics, there are some interesting examples of requirements not specified in common. For example the Dwelling Code specifies an air pressure test as part of the installation inspection. In contrast, the National Fuel Gas Code specifies an appliance derating for installation altitudes higher than 2000 feet above sea level.

Both codes treat the acceptability of equipment design and performance by reference to approved jurisdictions and/or test agencies. Thus,

- Dwelling Code: Sec. M-1101, "Heat producing . . . appliances shall be approved by the Building Official for safe use or shall bear the label of an approved testing agency. Conformity with the applicable design and testing standards specified in Sec. S-26.1101 shall be evidence that the equipment is reasonably safe to persons and property".***

* It is assumed here that fuel supply requirements are satisfied.

** Acronyms are decoded in the footnotes to Table G-2.

*** The referenced Sec. S-26.1101 cites among the applicable standards NFPA No. 54, which is now the National Fuel Gas Code, and also NFPA No. 211 and 90B (see Table G-2).

TABLE G-3. RESIDENTIAL GAS FUELED HEATING APPLIANCE INSTALLATION
EXAMPLE REQUIREMENTS SPECIFIED IN SELECTED CODES

Topic/Requirement	Code	
	One and Two Family Dwelling Code (1975 Ed.)	National Fuel Gas Code
<u>Appliance Installation Clearance and Access</u>		
<ul style="list-style-type: none"> ● Clearance from combustible material 	18-in. to front, 6-in. to top, sides and back, 9-in. to vent connector; or, dimension necessary for servicing accessibility.	18-in. to front, 6-in. to top, sides and back, 6-in. to vent connector; sufficient clearance for servicing accessibility.
<ul style="list-style-type: none"> ● Clearance from protected combustible material 	Clearance reducible, depending upon type of protection.	Clearance reducible, depending upon type of protection.
<u>Combustion and Circulating Air Supply</u>	<p>If volume of an appliance room (in ft³) < 1/20 of maximum input Btu rating of all appliances therein, then provide combustion air opening of 2-in² per 1000 Btu input rating, but not less than 200-in². Half of the opening shall extend within the upper 12-in of the room, and the other half within the lower 12-in.</p> <p>Circulating air (from inside, outdoors, or both) must provide air change every 30 minutes for habitable rooms or every 12 minutes for bath and other similar rooms.</p>	<p>(a) If all air from inside building, provide opening of 1-in²/1000 Btu/hr input rating for all appliances within the enclosure (locations as in Dwelling Code)</p> <p>(b) If all air from outside of building, provide opening of 1-in.²/4000 Btu/hr input rating for all appliances within the enclosure (locations as in Dwelling Code)</p> <p>(c) If ventilation from inside building and combustion and draft hood air from outdoors, same as (a) and add an opening to outdoors of 1-in²/5000 Btu/hr input rating for all appliances in enclosure.</p>
<u>Venting</u>	Vent cross-sectional area not < 7-in ² unless vent is integral part of listed appliance	Engineering tables for sizing vents are provided. Alternate criteria also available. Interval vents of listed appliance is considered proper venting.

- National Fuel Gas Code: Par. 1.3.1.1, Appliances, Accessories and Equipment to be "Approved": "Gas appliances, accessories, and equipment shall be 'Approved'. 'Approved' shall mean 'acceptable to the authority having jurisdiction'".

"NOTE: In determining acceptability, the authority having jurisdiction may base acceptance on compliance with NFPA, American National or other appropriate standards. In the absence of such standards, said authority may require evidence of proper installation, procedure or use. The authority having jurisdiction may also refer to the listings or labeling practices (. . .) of nationally recognized testing laboratories,* i.e., laboratories qualified and equipped to conduct the necessary tests, in a position to determine compliance with appropriate standards for the current production of listed items, and the satisfactory performance of such equipment or materials in actual usage".

In view of the footnote to the previous quotation from the Dwelling Code, it appears that the source for code specifications governing gas appliances is the National Fuel Gas Code.

Municipal Codes

In recent years, municipalities that regulate the installation of gas appliances in residences have tended to adopt one of the model codes (see Table G-2) with or without modification. An indication of these choices for two dozen municipalities is shown in Table G-4. As footnoted in that table, the listed municipalities were chosen from Reference 2 to provide a background of potential replacement/retrofit market locations for advance technology equipment.

* The Code footnotes as among the recognized laboratories, UL, A.G.A. Laboratories and the Factory Mutual Research Corporation.

TABLE G-4. SURVEY OF MUNICIPAL CODES REGULATING INSTALLATION
OF RESIDENTIAL GAS APPLIANCES

State	Municipality ^(a)	Code ^(b)	Remarks
AL	Birmingham		
AZ	Phoenix	Uniform Mechanical Code (ICBO)	
AR	Little Rock		
CA	Los Angeles	Uniform Mechanical Code (ICBO)	
	San Diego	Uniform Mechanical Code (ICBO)	
	San Francisco		
	Santa Monica		
CO	Denver		
CT	Hartford	Basic Mechanical Code (BOCA)	
DE	Wilmington		
FL	Miami	National Fuel Gas Code (NFPA 54)	
GA	Atlanta	National Fuel Gas Code (NFPA 54)	
ID	Boise		
IL	Chicago	National Fuel Gas Code (NFPA 54)	
	Evanston		
IN	Hammond		
KS	Wichita		
KY	Louisville		
LA	New Orleans	National Fuel Gas Code (NFPA 54)	
ME	Portland		
MD	Baltimore		
MA	Boston	Massachusetts Fuel Gas Code	Adaptation of National Fuel Gas Code (NFPA 54)
MI	Detroit		
	Flint		
MN	Minneapolis	Minnesota Mechanical Code	
MS	Jackson		
MO	Kansas City	Uniform Mechanical Code (ICBO)	
	St. Louis	Basic Mechanical Code (BOCA)	
MT	Butte		
NE	Omaha		
NV	Las Vegas		

TABLE G-4. (CONTINUED)

State	Municipality ^(a)	Code	Remarks
NH	Nashua		
NJ	Newark		
NM	Albuquerque		
NY	Buffalo	National Fuel Gas Code (NFPA 54)	
	New York City	National Fuel Gas Code (NFPA 54)	
	Syracuse		
NC	Charlotte		
ND	Minot		
OH	Cincinnati	National Fuel Gas Code (NFPA 54)	
	Cleveland	Uniform Mechanical Code (ICBO)	
	Columbus		
OK	Oklahoma City		
OR	Portland	Uniform Mechanical Code (ICBO)	
PA	Philadelphia	National Fuel Gas Code (NFPA 54)	1969 version of NFPA 54 (i.e., ANSI Z21.30)
	Pittsburgh	National Fuel Gas Code (NFPA 54)	
RI	Providence		
SC	Columbia		
SD	Rapid City		
TN	Memphis	Basic Mechanical Code (BOCA)	
TX	Dallas	Uniform Mechanical Code (ICBO)	
	Houston	Uniform Mechanical Code (ICBO)	
UT	Salt Lake City	Uniform Mechanical Code (ICBO)	
VT	Burlington		
VA	Alexandria		
WA	Seattle	Uniform Mechanical Code (ICBO)	
WV	Charleston		
WI	Milwaukee		
WY	Casper		

- (a) For each state in the contiguous U.S. at least one municipality is listed having a high number of residential gas "househeating" customers⁽²⁾ (relative to other localities in the state) to indicate potential replacement/retrofit markets for advanced technology equipment.
- (b) Entries appear only for municipalities surveyed.

Table G-4 has several interesting features.

- For the municipalities surveyed, the ICBO, NFPA, and BOCA codes appear to have found acceptance.
- Two states have adopted codes for statewide use (Massachusetts and Minnesota).

Legal Requirements as Potential Barriers to
Commercialization of New Gas Heating
Appliance Technology

Most of the preceding discussion has dealt with characterizing the general nature of existing legal requirements and procedures for residential gas heating appliances. It appears that the various requirements, procedures and agencies interact in an institutional system that has a logically appropriate first point of encounter in the commercialization of new technology. This first point is either (1) contact with the A.G.A. Secretariat to ANSI regarding needed changes in the Z21 series standards used for certification/testing and ANSI Z223.1 (otherwise known as The National Fuel Gas Code, or NFPA No. 54), or (2) contact with A.G.A. Laboratories* for certification/testing if existing ANSI standards are adequate. It cannot be overemphasized that the Z21 series of standards governs product acceptance (because they lead to a certification seal and product listing) and the Z223.1 standard governs installation compatibility with the residence and other equipment. Attempts to enter the system farther downstream increase the risk of non acceptance of a product and/or delay in an already lengthy process.

The issue of retrofitting new equipment or modifying an existing installation is presently included in an amendment to ANSI Z223.1. One of the elements in the amendment is "1.7 Modifications to Existing Appliance Installations for the Purpose of Fuel Conservation", which would (1) amplify the methodology to be used for reduction of vent connector size and (2) allow retrofit installation of automatic vent damper devices. An important provision of 1.7 from a product liability standpoint, is the determination of a reference safe condition.

* UL is an appropriate alternate test agency.

"1.7.1 Prior to attempting any modification, a safety inspection of the existing appliance installation shall be performed . . .". [A recommended procedure is cited for conducting this inspection].

Because retrofitting is not directly addressed in present codes, there is considerable latitude for interpretation and application, at the municipality level, of either (1) wording that may be contained in the ordinance, or (2) general guidance such as found, for example, in the following excerpt from the Uniform Mechanical Code.

"Sec. 103. The provisions of this Code shall apply to the erection, installation, alteration, repair, relocation, replacement, addition to, use, or maintenance of any heating, ventilating, cooling, refrigeration systems, incinerators or other miscellaneous heat-producing appliances" [Emphasis added].

CONCLUSIONS AND RECOMMENDATIONS

Institutional factors that could become barriers to the commercialization of advanced concepts for residential gas-fueled heating applications have been identified. Among these factors, compliance with legal requirements was chosen for detailed examination. From this examination, the following conclusions have been reached.

- The major market locations in the contiguous United States do indeed have municipal codes governing residential gas-fueled heating applications.
- These municipal codes are generated by a complex process that (1) begins with the formulation of standards for product qualification and installation, (2) continues with the incorporation of these standards into nationally recognized model codes, (3) emerges with the selection of

a model code for adoption by a municipal building-related agency, and (4) finally is legalized by municipal legislation. Clearly, this process is lodged in a well entrenched infrastructure.

- In tracing the origins of information that is eventually incorporated into a municipal code, it has been concluded that the major sources of input are The American National Standards (ANS) Z21 series of standards governing equipment design and performance and Z223.1 National Fuel Gas Code (also known as NFPA No. 54) governing equipment installation.
- The commercialization of advanced concepts can be enhanced by careful examination of existing standards for potentially needed changes in product qualification and installation requirements/procedures. Such changes can then be proposed for consideration by an appropriate organization such as the A.C.A.

The principal recommendation resulting from this task study is to

- Suggest that the historical process associated with the recent modification, ANS Z223.1a, to the National Fuel Gas Code, can serve as an instructive example of the standards change procedure.

This modification contains provisions for "Modifications to Existing Appliance Installation for the Purpose of Fuel Conservation" (specifically including automatic vent damper devices).

REFERENCES

- (1) Frieling, D. H., Fischer, R. D., Yano, R. A., and Eibling, J. A., "A Critical Review and Analysis of the Advanced Research Implications of the Phase 0 Program Results on Solar Heating and Cooling of Buildings", National Science Foundation RANN Document No. NSF-RA-N-75-017 (March 1975). (Battelle Columbus Laboratories Report NSF/RANN/SE/AER 742436/FR/75/1).
- (2) Anon., "Gas House Heating Survey, 1977", American Gas Association (1978).

APPENDIX H

TOTAL ENERGY AND COST SAVINGS

APPENDIX H

TABLE OF CONTENTS

	<u>Page</u>
TOTAL ENERGY AND COST SAVINGS.	183

LIST OF TABLES

Table H-1. Number of Homes Heated and Supplied with Hot Water by Gas (1000's).	185
Table H-2. Cases for Gas-Fired Heating Equipment Population Projections	186
Table H-3. Number of Home Years (10^6)	187
Table H-4. Funding by 1990 in $\$10^6$, at Percent of Potential Savings	188
Table H-5. Funding by 2000 in $\$10^6$, at Percent of Potential Savings	188

APPENDIX H

TOTAL ENERGY AND COST SAVINGS

To establish a basis for estimating the amount of research investment that might be justified on a given energy savings device or approach, reference values were developed to be applied to each device. The basis for the developed values were tables on the "Residential Construction Industry Forecast", "Inventory of Units Using Gas for Space Heating", and "Forecast for Inventory in 1985" from an "in preparation" report to DOE from A. D. Little, Inc. on "Building Technologies", by M. Glask, et al. In addition, seasonal usage of natural gas for heating was assumed to be 10^8 Btu/unit, and for hot water, 37×10^6 Btu/unit. Only two of the four categories of homes were considered, single family and multiple housing containing up to four units. These categories cover over 80 percent of the housing units in these tables. Four other assumptions were made:

- 1) It was assumed that 50 percent of the present home heating systems in the northeast region are hydronic, and essentially no hydronic systems are used elsewhere. It was also assumed that essentially no new hydronically heated homes are being built because they are incompatible with central air conditioning and are inherently more costly than other types of heating.
- 2) In projecting change beyond 1985 in the percent of homes using gas heating, two alternatives were assumed:
 - a) that the percentage of homes heated with gas stayed constant after 1985, and
 - b) that the number of homes heated with gas after 1985 stayed constant.
- 3) It was assumed that the average furnace or water heater unit has a life of 15 years.
- 4) In evaluating the effect of each option on energy savings, it was assumed no other changes leading to conservation of energy take place.

Table H-1 shows the number of homes heated with gas-fired warm-air heating units, gas-fired hydronic heating units, and gas-fired domestic hot water units, based on the above assumptions.

Table H-2 lists a variety of scenarios possible for the application of new gas-saving devices.

Table H-3 shows the number of home-years involved in the use of an energy conservation device, under a variety of assumptions. The gas, electricity, or cost savings per home-year can be used with these values to estimate a maximum savings throughout the U.S.

This approach is believed to be sufficiently valid for the purpose of this study, namely, to indicate the proper directions for research programs on energy conservation by development of new or improved heating units and accessories.

As an example of the use of the table in considering retrofit devices, consider the second item in Table E-2 of Appendix E. The gas savings for derating 20 percent, with secondary baffle, for a hot air furnace is 8.96×10^6 Btu/yr. Consider that the full penetration of this change will take 10 years, starting in 1980 (Case D). Then from Table H-3a, Column D, $34.15 \times 10^6 \times 8.96 \times 10^6 = 306 \times 10^{12}$ Btu will be saved by 1985.

In a similar manner, for new furnaces, consider as an example the condensing pulse combustor, Item 9 of Table E-2 of Appendix E, for hot air heating. Assuming a five-year total penetration starting in 1985, this scenario is defined as Case S. Thus, the savings for 1990 is between $26.41 \times 10^6 \times 35.8 \times 10^6 = 945 \times 10^{12}$ and $22.27 \times 10^6 \times 35.8 \times 10^6 = 797 \times 10^{12}$ Btu. Similarly, the total use of electricity will be increased by 910×10^6 to 770×10^6 kWh. The total savings to consumers would be $\$2.27 \times 10^9$ to $\$1.92 \times 10^9$.

Tables H-4 and H-5 summarize several computations made in this manner, tabulating one percent of the cost savings. Specifically, for the devices with a payback period of four years or less, the devices with the maximum and minimum cost savings are considered (omitting Device 62). Identification numbers to Table 1 are also indicated. A five-year total penetration time starting in 1985 is assumed. As expected, in the early years, the savings from the retrofit devices are larger. However, over the long run, more savings result from the new designs. The penetration period of five years is an extremely optimistic value, even for simple retrofit

TABLE H-1. NUMBER OF HOMES HEATED AND SUPPLIED WITH HOT WATER BY GAS (10⁶)

(a) BUILT BY 1980 AND BUILT SINCE 1980

1985-2000 Constant	Type	Homes Exist- ing in 1980	1980 Homes		1980 Homes		1980 Homes		1980 Homes	
			Still Exist- ing in 1985	New Homes 1981- 1985	Still Exist- ing in 1990	New Homes 1981- 1990	Still Exist- ing in 1995	New Homes 1981- 1995	Still Exist- ing in 2000	New Homes 1981- 2000
Constant percent assumption	Warm Air	35.890	34.549	4.095	33.892	7.281	33.234	10.468	32.577	13.654
	Hydronic	2.331	2.391		2.251		2.210		2.170	
	Hot Water	38.221	36.840	4.095	36.143	7.281	35.444	10.468	34.747	13.654
Constant number assumption	Warm Air	35.890	34.549	4.095	33.892	4.793	33.234	5.490	32.577	6.188
	Hydronic	2.331	2.291		2.251		2.210		2.170	
	Hot Water	38.221	36.840	4.095	36.143	4.793	35.444	5.490	34.747	6.188

(b) BUILT BY 1985 AND BUILT AFTER 1985

1985-2000 Constant	Type	Homes Exist- ing in 1985	1985 Homes		1985 Homes		1985 Homes	
			Still Exist- ing in 1990	New Homes 1986- 1990	Still Exist- ing in 1995	New Homes 1986- 1995	Still Exist- ing in 2000	New Homes 1986- 2000
Constant percent assumption	Warm Air	38.644	37.987	3.186	37.329	6.373	36.672	9.559
	Hydronic	2.291	2.251		2.210		2.170	
	Hot Water	40.935	40.238	3.186	39.539	6.373	38.842	9.559
Constant number assumption	Warm Air	38.644	37.987	.698	37.379	1.395	36.672	2.093
	Hydronic	2.291	2.251		2.210		2.170	
	Hot Water	40.935	40.238	.698	39.539	1.395	38.842	2.093

TABLE H-2. CASES FOR GAS-FIRED HEATING EQUIPMENT PCFULATION PROJECTIONS

Case	Years Required For Total Penetration	Year Beginning Penetration	Type of Device	Type of System	Comment
A	5	1980	Add-on	Warm Air	Assumes all new units are at least equivalent
B	5	Ditto	Ditto	Hydronic	Ditto
C	5	"	"	Hot Water	"
D	10	"	"	Warm Air	"
E	10	"	"	Hydronic	"
F	10	"	"	Hot Water	"
G	5	1985	"	Warm Air	"
H	5	Ditto	"	Hydronic	"
I	5	"	"	Hot Water	"
J	5	"	"	Warm Air	Assumes new better units start in 1980
K	5	"	"	Hydronic	Ditto
L	5	"	"	Hot Water	"
M	5	1980	New	Warm Air	
N	5	Ditto	Ditto	Hydronic	
O	5	"	"	Hot Water	
P	10	"	"	Warm Air	
Q	10	"	"	Hydronic	
R	10	"	"	Hot Water	
S	5	1985	"	Warm Air	
T	5	Ditto	"	Hydronic	
U	5	"	"	Hot Water	

TABLE H-3. NUMBER OF HOME YEARS (10⁶)

(a) ADD-ON DEVICES

Year	Case from Table H-2											
	A	B	C	D	E	F	G	H	I	J	K	L
1985	68.3	4.5	72.8	34.1	2.3	36.4	0	0	0	0	0	0
1990	154.4	10.3	164.7	96.1	6.4	102.5	73.9	5.3	79.2	38.0	2.5	40.6
1995	182.6	12.2	194.8	124.3	8.3	132.6	168.3	10.9	179.2	66.3	4.4	70.7
2000	182.6	12.2	194.8	124.3	8.3	132.6	198.8	12.7	211.6	66.3	4.4	70.7

(b) NEW FURNACES

	Year	Case from Table H-2								
		M	N	O	P	Q	R	S	T	U
Constant percent assumption	1985	26.0	1.3	27.3	13.0	.6	13.7	0	0	0
	1990	139.7	7.0	146.7	101.3	5.1	106.3	26.4	1.3	27.7
	1995	323.7	16.3	339.9	285.2	14.3	299.6	144.2	6.8	151.0
	2000	548.5	27.2	575.7	510.0	25.3	535.3	337.9	15.9	353.8
Constant number	1985	26.0	1.3	27.3	13.0	.6	13.7	0	0	0
	1990	133.5	7.0	140.5	96.1	5.1	101.2	22.3	1.3	23.5
	1995	298.8	16.3	315.1	261.4	14.3	275.7	121.4	6.8	128.2
	2000	492.5	27.2	519.7	455.1	25.3	480.4	284.0	15.9	299.9

TABLE H-4. APPROPRIATE LEVEL OF RD&D FUNDING BY 1990 IN
\$10⁶, AT ONE PERCENT OF POTENTIAL SAVINGS

Numbers in () are Concept Numbers
of Table 1.

	Maximum		Minimum	
	Retrofit	New Design	Retrofit	New Design
Warm air	26.1 ⁽²¹⁾	19.2-22.7 ⁽⁹⁾	3.3 ⁽³³⁾	2.9-3.5 ⁽⁵⁹⁾
Hydronic	1.4 ⁽³⁾	1.0 ⁽⁹⁾	0.2 ⁽³³⁾	0.2 ⁽⁵⁹⁾
Hot water	12.0 ⁽⁵⁵⁾	7.9-9.3 ^(8,11)	6.5 ^(17,36)	6.1-7.2 ^(30,31)

TABLE H-5. APPROPRIATE LEVEL OF RD&D FUNDING BY 2000 IN
\$10⁶, AT ONE PERCENT OF POTENTIAL SAVINGS

Numbers in () are Concept Numbers
of Table 1.

	Maximum		Minimum	
	Retrofit	New Design	Retrofit	New Design
Warm air	70.2 ⁽²¹⁾	244.2-290.6 ⁽⁹⁾	8.8 ⁽³³⁾	37.4-44.5 ⁽⁵⁹⁾
Hydronic	3.3 ⁽³⁾	12.4 ⁽⁹⁾	0.5 ⁽³³⁾	2.1 ⁽⁵⁹⁾
Hot water	32.0 ⁽⁵⁵⁾	100.9-119.1 ^(8,11)	17.4 ^(17,36)	77.7-91.7 ^(30,31)

devices. However, a comparison of five year and ten-year penetration periods for new devices (Cases M, N, O compared with P, Q, R) shows only about a 28 percent less savings up to 1990, and 7 percent less savings up to 2000.

In considering Table H-5, one of the most striking results is the large RD&D funding that might be justified in an overall program to increase heating efficiency in residences. Under the most optimistic conditions on savings, which are thought to be reasonably realistic because of the multiple approaches that are available, and making allowances for a slower than five-year penetration, at a 1 percent level, the order of \$23 million a year for 20 years would be available for RD&D in this area; at a 10 percent level, the amount per year would be \$230 million.

It is not the prerogative of this study to suggest what percentage of the value of total potential energy savings to the consumer is justified to be spent on RD&D to ensure reasonable attainment of the potential. It must be noted, however, that 2 to 4 percent of total sales is a common allowance for RD&D for industry in this area of technology.