DOE/MC/27324--3055

DE92 001137

**Improved Pyrolysis Submodel for the
Wen Fixed-Bed Gasifier Program**

Final Report

**B.A. Adesanya
Y. Ruffin**

April 1991

Work Performed Under Contract No.: DE-FG21-90MC27324

For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
Morgantown, West Virginia

By
Hampton University
Department of Engineering
Hampton, Virginia

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

**Improved Pyrolysis Submodel for the
Wen Fixed-Bed Gasifier Program**

Final Report

**B.A. Adesanya
Y. Ruffin**

Work Performed Under Contract No.: DE-FG21-90MC27324

**For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
P.O. Box 880
Morgantown, West Virginia 26507-0880**

**By
Hampton University
Department of Engineering
Hampton, Virginia 23668**

April 1991

Contents

Summary	vii
1 Introduction	1
1.1 Devolatilization	2
2 The Model	5
2.1 Transport and Physical Properties	8
2.1.1 Density	8
2.1.2 Heat capacity	8
2.1.3 Thermal conductivity	8
2.1.4 Heat of reaction	9
2.1.5 Heat transfer coefficient	9
2.1.6 Diffusion coefficient	10
3 Experiment	11
3.1 Procedure	12
3.2 Results and discussions	13
4 Numerical computation	15
Conclusion	17
Recommendation for Future Work	18
Acknowledgement	19
Nomenclature	20
References	21
Appendix A - Program Listing	39
Appendix B - Experimental temperature profiles	55

List of Tables

1	Proximate Analysis of Coal Sample	24
2A	Experimental Run Conditions and Results	25
2B	Experimental Run Conditions and Results	26

List of Figures

1	High Temperature Fixed-Bed Reactor.	27
2	Typical Experimental Temperature Profile.	28
3	Comparison of Surface Temperature for Various Runs.	29
4	Comparison of Center Temperature for Various Runs.	30
5	Experimental Volatile Matter Profile.	31
6	Sample after Devolatilization.	32
7	Comparison of Model Prediction and Experimental Data for Center Temperature, $D_p = 16$ mm.	33
8	Comparison of Model Prediction and Experimental Data for Center Temperature, $D_p = 13.5$ mm, $E_o = 51765$ cal/mole, $\sigma = 11725$ cal/mole, Area Factor = 0.7.	34
9	Comparison of Model Prediction and Experimental Data for Center Temperature, $D_p = 10.2$ mm, $E_o = 51765$ cal/mole, $\sigma = 11725$ cal/mole, Area Factor = 0.7.	35
10	Comparison of Model Prediction and Experimental Data for Volatile Matter Loss, $D_p = 16$ mm.	36
11	Effect of rate of devolatilization pre-exponential constant, k_o , on volatile matter profile.	37
12	Effect of Particle Diameter on Centerline Temperature.	38
B1	Experimental temperature profile for Run :CD0608F.ARK.	56
B2	Experimental temperature profile for Run : CD06072A.ARK.	57
B3	Experimental temperature profile for Run : CD0608A.ARK.	58
B4	Experimental temperature profile for Run : CD0608B.ARK.	59
B5	Experimental temperature profile for Run : CD0608C.ARK.	60
B6	Experimental temperature profile for Run : CD0608D.ARK.	61

B7	Experimental temperature profile for Run : CD0608E.ARK.	62
B8	Experimental temperature profile for Run : CD0608H.ARK.	63
B9	Experimental temperature profile for Run : CD0608G.ARK.	64
B10	Experimental temperature profile for Run : CD0611A.ARK.	65
B11	Experimental temperature profile for Run : CD0611B.ARK.	66
B12	Experimental temperature profile for Run : CD0611C.ARK.	67
B13	Experimental temperature profile for Run : CD0619A.ARK.	68
B14	Experimental temperature profile for Run : CD0619B.ARK.	69
B15	Experimental temperature profile for Run : CD0619C.ARK.	70
B16	Experimental temperature profile for Run : CD0619D.ARK.	71

SUMMARY

A generalized model for devolatilization of large coal particles typically encountered in a fixed or moving bed gasifier has been developed. Two models were developed, one which does not consider diffusion of the volatile matter from the coal during devolatilization and the other which does consider diffusion of volatile species through the coal matrix. Both models predict a time-temperature history of the particle in a convective heat transfer environment. Thermal decomposition of volatile matter is treated as a series of independent chemical reactions in which the rate constants only differ in activation energy. The activation energy is expressed as a Gaussian distribution similar to those used by Anthony et al. (1975). Experimental data on devolatilization of coal samples with particle diameters ranging from 8 mm to 16 mm were obtained in a flow reactor and used for limited validation of kinetic and transport parameters of the model. This limited experimental data set is a major addition to the devolatilization data base, for it constitutes the only detailed and realistic data available on large coal particles. Devolatilization times predicted by the model (with updated parameters) are compared with data obtained from the METC 42-inch fixed-bed gasifier. The major problem encountered during the course of this work was the availability of transport data for coal. For example, the effective diffusion coefficient needed for the model which included diffusion was not available and thus realistic comparison or (parameter study) with the model was not possible. This is one area where additional experimentation is required. Future work will involve additional experimentation to measure interior particle temperature which can be used to obtain correlations for thermal conductivity, heat transfer coefficient and diffusion

coefficient. In addition, the resulting data can be used to correlate the extent of swelling during devolatilization.

1. INTRODUCTION

Various one- and two-dimensional, steady-state mathematical models have been developed to describe the chemical and physical processes taking place within a moving-bed gasifier (Yoon et al., 1978; Desai and Wen, 1978; Wen et al., 1982; TRW Systems and Energy Group, 1978; Cho and Joseph, 1981; Den et al., 1982). These models are useful in the conceptual design and scaleup of new gasifiers and provide a means of investigating various operating conditions in conjunction with minimum experimental data. For modeling purposes, the gasifier is usually assumed to consist of four zones: drying, devolatilization, gasification, and combustion. The drying and devolatilization processes are assumed to occur quickly at the top of the gasifier. The devolatilization sub-model, in particular, is usually ignored in gasifiers (Wen et al., 1982; TRW Systems and Energy Group, 1978; Cho and Joseph, 1981) or simplified to a non-rate process (Wen et al., 1982; Yoon et al., 1978). In a moving-bed gasifier, devolatilization products, resulting from volatile matter released in the upper section, constitute a substantial part of the coal gas product including pollutants such as COS and H₂S. Hence, for optimal design and development of pollution control strategies it is essential to understand the devolatilization process as well as to be able to predict devolatilization time and products in the gasifiers.

The majority of the experimental work reported for devolatilization of coals is most relevant on fluidized beds and entrained bed applications and is based on the pyrolysis of pulverized coal in inert atmospheres. Fixed- or moving-beds on the other hand use large uncrushed particles in the feed. Relatively little work has been reported on the devolatilization of large particles in fixed-beds in inert atmospheres.

1.1 DEVOLATILIZATION

In the upper part of a moving-bed gasifier, the coal is dried and devolatilized by a hot gas stream flowing upward from the gasification and combustion zones. As coal moves slowly downward through the bed, the temperature of the coal is increased and approaches that of the gas stream. As the coal is heated, volatile matter, at temperatures between 350° to 600°C, begins to decompose forming tars and gases as part of the product gas. During this period regardless of the rank of the coal almost 80% of the volatile matter is released (Mazumdar and Chatterjee, 1973). Much effort has focused on the kinetics, mechanisms, and product distribution in order to characterize the complex decomposition and transport phenomena involved in small coal particle devolatilization (<10 mm). However, relatively few studies on the devolatilization of large particles (> 10 mm) typically encountered in moving-bed gasifier have been reported (O'Conner, 1956; Fu et al., 1987).

Anthony and Howard (1976) provided a review of coal devolatilization, giving detailed results, correlations and postulated mechanisms. The complex processes occurring during devolatilization of coal have not yet been fully understood and hence, exact descriptions are not available. The rate of the devolatilization process has been approximated by a simple first-order decomposition occurring uniformly throughout the particle (Badzcoch and Hawksley, 1970; Rau and Robinson, 1966; Mentser et al., 1970). This model, however, is believed to be inadequate and a series of several first-order processes and variable order models (Shapatina et al., 1960; Pitt, 1962; Wiser et al., 1967; Skylar et al., 1969; Ubhayakar et al., 1976; Nsakala et al., 1977) have been developed to improve the prediction of the devolatilization rate. These models gave better fit to experimental data but still could not

account for the strong temperature-time dependency of the devolatilization rate. Anthony et al. (1975, 1976) proposed the model of an infinite number of independent first-order reactions whose activation energies can be represented by a continuous gaussian distribution. The generalized equation developed by Anthony et al. was successfully matched to experimental weight-loss results with Montana lignite and high volatile bituminous Pittsburgh coal. The data presented by Solomon et al. (1986) indicated that the distributed activation energy model was the better choice. It is worth noting however that most of the experimental studies on devolatilization of coal and subsequent characterization were performed with coal particle sizes from few millimeters to 50 μm or less, and with heating rates up to 10^4C/s . In addition, most of these researchers have assumed an isothermal particle.

In a moving-bed gasifier, the size of coal particle ranges from several millimeters to several centimeters with average heatup rates of over 100°C/min in the devolatilization zone. Due to the size of the particles, and the fact that coal is a poor conductive material, it takes some time before the interior temperature approaches the gas temperature. Using average thermophysical properties it can be shown that the heat transfer Biot number may vary in the range 1-20 for particles sizes ($> 1\text{ mm}$). Since the isothermal particles assumption requires $Bi < 0.02$, large temperature gradients may be expected within the particle during devolatilization.

Experimental data on volatile matter release and particle temperature profile for large coal particles do not exist in the literature. There is the single data point reported by O'Connor et al. (1958) for 1-in particle diameter. Even then, only the pyrolysis time was given. Fu et al. (1987) reported kinetic data on devolatilization of large coal particles, but the

largest coal particle used was 9 mm. In addition, the spherical coal particles used by Fu et al. were made from pulverized coal by pressing in a mold and interior temperatures profiles were not measured. This paper presents a devolatilization model which takes into account the non-isothermal particle behavior and its consequent impact on the volatile's evolution rate. Experimental data on volatile matter release and particle temperature profile of large coal particles were also reported and used to validate model parameters.

2 THE MODEL

Devolatilization of large coal particles in a moving- or fixed-bed gasifier is considered to involve the transfer of heat from the gas phase through the gas-solid interface to the particle surface. The heat is subsequently transferred by conduction to the interior of the particle. Evolution of volatile matter from the coal particle therefore depends on the relative rate of convective heat transfer to the surface to the conductive heat transfer from the surface. The loss of particle mass also creates a gaseous flux away from the particle which is detrimental to convective heat transfer. The swelling of the particle during devolatilization resulted in the particle shape changing from spherical at the beginning of the experiment to almost cylindrical under the action of gravity and drag as the experiment progresses. The model assumes a constant diameter. The energy balance on a single spherical coal particle is given by equation 1.

$$\rho C_p \frac{\partial T}{\partial t} = \frac{1}{r^2} \frac{\partial}{\partial r} (r^2 k_{eff} \frac{\partial T}{\partial r}) + q(T) \quad (1)$$

where q is the rate of energy consumed by pyrolysis of the coal during devolatilization per unit volume of coal and k_{eff} is the effective radial thermal conductivity of the coal particle.

The boundary and initial conditions associated with this equation are:

$$-k_{eff} \frac{\partial T}{\partial r} = h(T_g - T_s) \quad t > 0 \quad r = R \quad (2)$$

$$\frac{\partial T}{\partial r} = 0 \quad t > 0 \quad r = 0 \quad (3)$$

$$T = T_i; \quad q_i = 0 \quad t = 0 \quad 0 \leq r \leq R \quad (4)$$

The thermal decomposition of a coal particle is assumed to consist of a series of independent chemical reactions whose reaction constants, k_i , differ in activation energy (Pitts, 1962; Anthony et al., 1975, 1976). Furthermore, that the activation energy can be represented by a continuous distribution due to the large number of reactions. In this case, a gaussian distribution, $f(E)$, is assumed, such that

$$\int_0^{\infty} f(E) dE = 1 \quad (5)$$

and

$$f(E) = \frac{1}{\sigma (2\pi)^{1/2}} \exp\left[-\frac{(E-E_o)^2}{2\sigma^2}\right] \quad (6)$$

The amount of volatile matter left in the coal is therefore given by the expression

$$V^o - V = V^o \int_0^{\infty} \exp\left(-\int_0^t k dt\right) f(E) dE \quad (7)$$

$$k = k_o \exp\left[-\frac{E}{RT}\right] \quad (8)$$

E_o and σ are the mean and standard deviation of the activation energy distribution and k_o is assumed constant for all reactions. Thus the energy required for the pyrolysis is

$$Q(T) = \rho \Delta H (V^o - V) \quad (9)$$

Substituting for the amount of volatile matter left yields

$$Q(T) = \rho \Delta H V^o \int_0^{\infty} \exp\left(-\int_0^t k dt\right) f(E) dE \quad (10)$$

where ΔH is the heat of pyrolysis reaction, and V^o is the ultimate volatile yield. The average volatile matter loss, V_{av} is given by

$$V_{av} = \frac{3V^o}{r_o^3} \int_0^{r_o} \left[1 - \int_0^{\infty} \exp\left(-\int_0^t k dt\right) f(E) \right] r^2 dr \quad (11)$$

Similarly the weight loss is given by

$$W = 4\pi V^o \rho_c \int_0^{r_o} \left[1 - \int_0^{\infty} \exp\left(-k_o \int_0^t \exp\left(-\frac{E}{RT}\right) dt\right) f(E) dE \right] r^2 dr \quad (12)$$

The heat transfer calculations given by the above energy balance and accompanying boundary and initial conditions assumed heat transfer to be mainly due to convective heating by the gas, equation 2. Radiative effect can be included in this boundary condition. Internal conduction within the particle and some contribution from radiation through pores have been combined and expressed as effective thermal conductivity.

The material balance representing the diffusion of gaseous devolatilization product through the pores of a spherical particle is given by

$$\frac{\partial C}{\partial t} = D_{eff} \frac{1}{r^2} \frac{\partial}{\partial r} \left(r^2 \frac{\partial C}{\partial r} \right) + R_v \quad (13)$$

in which D_{eff} is the gaseous effective diffusivity and R_v is the rate of devolatilization within the particle. Because of the difficulty of obtaining the mass transfer coefficient of the devolatilization product from the surface of the particle to the gas stream, the boundary condition used with this equation, at the surface, assumes that there is negligible resistance to mass transfer. Therefore the concentration at the surface is equivalent to that in the bulk gas stream, i.e. $C(R,t) = C_{\infty}$. equation 13 was solved with equations 1-4 when product diffusion was included in the model.

2.1 Transport and Physical Properties

One of the primary objectives of this study was to utilize literature correlations and independent measurements to determine model parameters, thereby avoiding the practice of numerically determining values which provide the best "fit" to experimental data. However, because of the variations in coal types and composition, literature data needed to achieve this objective was lacking and hence this objective was partially met. Correlations from the literature were used for density, thermal conductivity, and heat capacity. Even then, there were substantial variation in the various correlations available in the literature for these properties. No heat transfer coefficient correlations were available for fixed- or moving-bed reactors, hence correlations for single particles in fluidized bed were used and a correction factor introduced into the model to account for this fact.

2.1.1 Density: The particle density was assumed to decrease in direct proportion to the mass loss, while the diameter was assumed to remain constant.

2.1.2 Heat capacity: The correlation proposed by Fritz and Moser, Equ. 14, which has been shown to hold reasonably well for all ranks of coal was used in this study.

$$C_p = 0.242 (1 + 0.008 VM) \quad (14)$$

2.1.3 Thermal Conductivity: Badzioch et al. (1976) measured the effective thermal conductivity and specific heat of coals up to 900°C. They found that the thermal conductivity was approximately constant up to $\approx 400^\circ\text{C}$ and increased rapidly at higher temperatures, predominantly as a result of radiant heat transfer across the pores and cracks in the carbonized coal; the volumetric specific heat (ρC_p) was approximately constant up to $\approx 350^\circ\text{C}$

and decreased at higher temperatures. The following expressions were fitted to their mean results and are used in the model.

$$k = \begin{cases} 0.23 & \text{for } T \leq 400^{\circ}\text{C} \\ 0.23 + 2.24 \times 10^{-5} (T - 400)^{1.8} & \text{for } T > 400^{\circ}\text{C} \end{cases} \quad (15)$$

$$\rho C_p = \begin{cases} 1.92 \times 10^6 & \text{for } T \leq 350^{\circ}\text{C} \\ 1.92 \times 10^6 - 2.92 \times 10^3 (T - 350) & \text{for } T > 350^{\circ}\text{C} \end{cases} \quad (16)$$

Both the thermal conductivity and the volumetric specific heat are in $\text{W m}^{-1} \text{K}^{-1}$ and $\text{J m}^{-3} \text{K}^{-1}$ respectively. This correlation was used in this model.

Other correlations which had been investigated include those that incorporate the effect of release of volatile matter and temperature on physical properties of the coal such as porosity, density, heat capacity and thermal conductivity.

2.1.4 Heat of Reaction: Quantitative estimate of the heats of reaction during thermal decomposition of coal have been published by Kasperczyk and Simonis, 1971, Agroskin et al., 1972, and Merrick, 1983. The first two investigators concluded that above 650°C the reactions are exothermic (266-441 kJ/kg), while Merrick studies predicted higher exothermic reactions (616 - 653 kJ/kg). Kasperczyk and Simonis studies also indicated that below 650°C , the reactions are endothermic. For this investigation an average heat of reaction of 300 kJ/kg was assumed.

2.1.5 Heat Transfer Coefficient: The major reasons given for the discrepancies in reported pyrolysis rates by many investigators have been attributed to inaccuracies in determining particle temperatures, which in turn results from the inability to predict the heat transfer

coefficient in gasifiers. Kunii and Levenspiel (1968) reported that Kothani (1967) has correlated existing gas-solid heat transfer data in fixed-bed:

$$Nu = 2.0 + 1.8 Re_p^{1/2} Pr^{1/3} \quad (17)$$

For $Re_p > 100$ and for single spheres

$$Nu = 2.0 + 0.6 Re_p^{1/2} Pr^{1/3} \quad (18)$$

The single particle expression is used to obtain the heat transfer coefficient used in this model. The effect of gaseous flux away from the surface of the particle will tend to decrease the heat transfer coefficient, while the change in particle shape due to swelling from our particular experiment tend to increase the surface area for heat transfer.

2.1.6 Diffusion coefficient: Correlations for diffusion of pyrolysis product gases are not available in the literature. Estimation from theory, such as from mixing rules and kinetic theory is not possible because the product gas distribution is unknown. Various investigators have used values which varied widely and which have been chosen arbitrarily. To properly include diffusion in the model, one must be able to estimate the effective diffusion coefficient independently, else, this will result in the introduction of another unknown parameter into a field already crowded with a lot of unknown parameters.

3 EXPERIMENT

A fixed-bed reactor system (Fig. 1) designed for sorbent regeneration studies was modified to run single particle devolatilization experiments under conditions similar to that found in moving-bed gasifiers. The fixed-bed reactor is composed of an Astro furnace equipped with graphite heating element and a reactor chamber enclosed by a 3 inch diameter alumina 998 muffle tube. The furnace vessel is cooled by water coolant. The graphite heating element is located in an inert (He) environment for protection from air oxidation. Preheating and heating of test gas are accomplished by passing the gas down and up through two annuli in the furnace hot zone. The temperature of the inlet gas to the bed is measured by a K-type thermocouple inserted from the top. The reactor was designed to operate at ambient pressure and high temperature up to 1650°C. A summary of the reactor design specification is shown in Fig. 1.

The modification to the reactor was aimed at obtaining conditions very similar to those found in the upper part of moving-bed gasifiers. Specifically, the sample is enclosed in an insulating tube to minimize if not completely eliminate radiation to and from the sample. Since the sample and the enclosing insulating tube is at the same temperature at the start of each run, the initial heat transfer is from the gas to the particle. It is anticipated that there will be some radiative heat transfer towards the later part of the run when the insulating tube is at the temperature of the gas.

3.1 PROCEDURE

Bituminous Arkwright coal is used in this study. Typical proximate analysis of the coal is shown in Table 1. Coal particles were picked by hand and edges were knocked off. Holes are drilled by a 3.2 mm drill bit in the spherical shaped particles with sizes ranging from 8 to 18 mm. The procedure consists of heating the reactor to the desired temperature. A coal particle with hole already drilled is weighted and an average diameter determined. A K-type thermocouple is then inserted into the hole and the particle is placed in an insulating tube to minimize if not completely eliminate heat radiation from the reactor wall. The sample, with the insulation tube in place, is then quickly raised into the desired location in the reactor. In order to obtain additional data to characterize the devolatilization process, a pre-weighed filter was placed at the exit gas line from the reactor to collect tar that was produced during devolatilization. After each run, the filter was weighed and the weight of tar collected obtain by subtraction. This data was gathered for the later half of the devolatilization runs.

A thermocouple monitored the center temperature as well as support the coal particle in the reactor. Three additional k-type thermocouples, as shown in Fig. 1, also monitored the temperature about an inch above the sample, the gas temperature at the surface of the particle, and the gas temperature below the sample. All four thermocouples were monitored and recorded every 15 seconds. Run conditions were at gas temperature of 650°C and 0.25 m/s gas linear velocity (based on empty tube diameter). The sample was allowed to remain in the reactor for the desired heating period, lowered to a cooling zone and purged with nitrogen to rapidly cool before removing from the reactor. The sample was delivered in a glass vial for proximate analysis.

3.2 Results and Discussions

The first series of runs (CD0607A.ARK - CD0611A.ARK) were carried out to develop the experimental procedure so as to be able to reproduce the temperature profiles. Fig. 2 shows a typical temperature profile. Fig. 3 and 4 compares the surface and center temperature for various runs at the same or very close particle diameter. Both figures showed the reproducibility of the procedure. The temperature variations can be accounted for by the response of the thermocouple used and the data acquisition procedure (one student keeping track of the time, another reading out the various temperatures, while a third student records the data). Table 2 gives the run conditions, average particle diameter, initial sample weight, and gas temperature for all runs. A total of 39 runs were made. Generation of a complete volatile matter versus time profile involved series of runs with the same particle diameter at discrete times. Thus these 39 runs resulted in one complete volatile matter versus time profile, (for the 16 mm diameter particle), given in Fig. 5. Each of the data points in Fig. 5 represents an average of several runs at the same devolatilization time. Detail temperature profiles are given in Appendix B.

Pictures of the sample were taken before and after devolatilization. These pictures indicated substantial swelling of the sample during devolatilization. Also, even though all samples were spherical at the beginning of the experiment, they were cylindrically shaped after the run. The extent of swelling depended on the duration of devolatilization. The cylindrical shape is attributed to drag along the surface of the sample as the gas flows along the length of the reactor tube. Fig. 6 shows a typical sample after devolatilization for five minutes. These pictures can be used to characterize swelling. From the pictures,

characteristic length and width can be measured and correlated with devolatilization time and process conditions.

4 NUMERICAL COMPUTATION

Equations 1-4 were solved using the modified Crank Nicholson finite difference method. Using the calculated temperature profile at each node point, the average volatile matter was obtained by integrating equation 11. All simulations were carried out using a heat of reaction of 300 KJ/kg. The gaussian distribution was represented by 21 sample points. Increasing the number of sample points beyond this point does not result in any improvement in the calculated profile.

Inability to accurately predict pyrolysis rates by many investigators have been attributed to inaccuracies in determining particle temperatures. In this model, the heat transfer coefficient was obtained from correlations for single particle spheres. The coal samples used for the devolatilization experiments were carefully shaped to spherical samples to yield experimental conditions similar to the model. A correction factor, f , was introduced into the model to account for the fact that the actual heat transfer coefficient in a fixed- or moving-bed gasifier will actually be less. Possible values of f will range from a little greater than zero to unity. In a typical bed, at any given cross-section, any particular particle will be surrounded by other particles such that only a fraction of the total surface area will be available for convective heat transfer. Fig. 7 shows the model prediction with f values of 0.7 and 1 compared to experimental data. In the case of an area factor of 0.7, the calculated results are in good agreement with experimental data. In this case, the use of an area factor will account for the fact that equation 17 is not completely applicable to this situation. The effect of gaseous flux away from the surface of the particle will tend to decrease the heat transfer coefficient. Figs. 8 and 9 compare model predictions with experimental data for

particle diameter of 10.2 and 16 mm respectively, using 0.7 area factor. Both figures show good agreement with experimental data.

Similarly, predicted pyrolysis rates depend on the values of the kinetic parameters, in this model, k_o , E_o , and σ . Kinetic data on devolatilization of large coal particles in fixed-beds do not exist. In addition, there is considerable disagreement on the kinetic data reported for devolatilization in fluidized beds. Rates reported in the literature vary from $<1 \text{ s}^{-1}$ to $\approx 100 \text{ s}^{-1}$. Most of these kinetic data have also been obtained at very high heating rates, 10^5 K s^{-1} . In a typical fixed- or moving-bed gasifier, the heating rate is in the order of 10 K s^{-1} . Fig. 10 compared the model prediction using kinetic data reported by Anthony et al. and with adjusted mean activation energy, E_o , and standard deviation of the activation energy distribution, σ , with experimental data. The model prediction using the adjusted energy parameters shows good agreement with experimental data. Each experimental point in Fig. 10 is an average of several runs at the specific time. The energy parameters do not have any significant effect on the temperature profile, hence, the model prediction in Figs. 8 and 9 were calculated using the adjusted parameters.

Using the adjusted energy parameter, the model prediction was compared with actual data from METC 42" gasifier. The model predicted 52 minutes to have 71% of the volatile matter released compared to measured time of 62 minutes. In this analysis, an area factor of 0.1 was used. This implies that the actual heat transfer coefficient in such fixed-bed gasifier is at least 10 times lower than that predicted from correlations for single particle spheres (Eqn. 17). This is comparable to the area factor of 0.05 reported by Smoot et al., 1989. Comparison of kinetic rate data by Solomon, et al. (1986) shows a wide variation in the

frequency factor, k_0 , by orders of magnitude. These differences have been attributed to the experimental methods used by various investigators, and the inability to accurately measure the particle temperature. Fig. 11 shows the effect of the frequency factor on volatile matter content. This figure definitely shows substantial impact of the frequency factor on volatile matter content. Future work in this area will involve combining this model with experimental data to correlate the three energy parameters used in this model.

Fig. 12 shows the effect of particle size on center temperature. The figure clearly indicates that substantial temperature gradient exist especially when one considers the agglomeration or clinking that occurs in actual gasifiers. In addition, our experimental work showed substantial swelling of the particle. If this swelling is accompanied by increase in porosity of the coal, then this will result in a much lower temperature profile resulting in lower rates of pyrolysis or yield of volatile matter.

CONCLUSION

A generalized model for devolatilization of large coal particles has been developed which is capable of predicting temperature and volatile matter profile in a convective environment. The ability of the model to accurately predict the temperature of the coal particles, means that, combined with experimental data, reliable correlation for large coal particle devolatilization can be developed.

An experimental procedure has also been developed to measure temperature profiles during devolatilization. This procedure can be used to obtain needed data on rates of pyrolysis, heat transfer coefficient, and physical properties such as thermal conductivity.

RECOMMENDATIONS FOR FUTURE WORK

Future efforts should involve a detailed experimental study using a fixed-bed reactor to carry out experimental runs at various temperatures such as at 1000, 1100, 1300, 1400, 1500°F; at different gas velocities and particle diameters; and using Bituminous Arkwright coal and other types of coal.

Such single particle experimental data can be used to develop correlations for the thermal conductivity under fixed-bed conditions and estimation of heat transfer coefficient. The experimental volatile matter profile can be combined with the model to obtain pyrolysis kinetic parameter: mean activation energy, E_o , and standard deviation of the activation energy distribution, σ , used in this model.

Experiments carried out with Bituminous Arkwright coal showed considerable swelling, future experimental work could be used to qualitatively characterize swelling during devolatilization. The objective being to characterize the extent of swelling as a function of time. In addition, the experimental effort and the mathematical model should be extended to multi-particle systems.

ACKNOWLEDGMENT

The author gratefully acknowledge the assistance of Dr. Hoan Pham of Air Products (formerly of Morgantown Energy Technology Center) for his contribution to the experiment work. The experimental part of this study would not have been possible without Dr. Pham's interest and commitment.

NOMENCLATURE

C_p	density, kg/m^3
E	activation energy, cal/mole
E_o	mean activation energy, cal/mole
h	heat transfer coefficient, $\text{J m}^2 \text{s}^{-1} \text{K}^{-1}$
Δh	heat of devolatilization, kJ/kg
k_{eff}	effective thermal conductivity, $\text{J m}^{-1} \text{s}^{-1} \text{K}^{-1}$
k	reaction constant, s^{-1}
Nu	Nusset Number, (hd/k)
Pr	Prandth Number
$q(T)$	energy released by devolatilization, J
R	gas constant
Re_p	Reynolds Number
r	radius, m
r_o	particle radius, m
t	time, s
T	temperature, K
T_g	gas temperature, K
V	volatile matter
V^o	ultimate volatile matter
ρ	density, kg m^{-3}
σ	standard deviation of activation energy distribution
subscript	
i	initial conditions
s	surface

REFERENCES

- Anthony, D. B. and J. B. Howard, "Coal Devolatilization and Hydrogasification," *AIChE Journal*, **22**, No. 4, p 625 (1976).
- Anthony, D. B., J. B. Howard, H. C. Hottel, and H. P. Meissner, "Rapid Devolatilization of Pulverized Coal," Fifteenth Symposium (International) on Combustion, p 1303, The Combustion Institute, Pittsburgh, Pa. (1975).
- Anthony, D. B., J. B. Howard, H. C. Hottel, and H. P. Meissner, "Rapid Devolatilization and Hydrogasification of Bituminous Coal," *Fuel*, **55**, p 121 (1976).
- Agroskin, A. A., Goucharov, E. I., and Gryanor, N.S., *Koksi Khimiya*, **9**, pp. 3 (1972).
- Badzioch, S. and P. G. W. Hawksley, *Ind. Eng. Chem. Process Des. Dev.*, **9**, p 521 (1976).
- Bissett, L. A., B. Morris, and L. E. Paulson, Final Report: Phase I - Research Gasification/Cleanup Test Facility Conceptual Design of 16-inch, Fixed-Bed Gasifier with Fixed-Bed Hot Gas Cleanup, February 1989.
- Cho, Y. S., B. Joseph, *Ind. Eng. Chem. Process Design Dev.*, **20**, p 314 (1981).
- Denn, M. M., J. Wei, W. C. Yu, and R. Cwiklinski, "Detail Simulation of a Moving-Bed Gasifier," Final Report prepared for Electric Power Research Institute (EPRI AP-2576), September 1982.
- Desai, P. R. and C. Y. Wen, "Computer Modeling of the METC Fixed-Bed Gasifier," Prepared for Morgantown Energy Research Center, West Virginia University, March 1978.
- Fu, M., Y. Zhang, H. Han, Y. Duan, "A Study on Devolatilization of Large Coal Particles," *Combustion and Flame*, **70**, p 253 (1987).
- Kasperczyk, J. and Simonis, W., 1971, *Glukauf-Forschungshefte*, **32**, pp. 23.
- Kothari, A.K., 1967, M.S. Thesis, Illinois Institute of Technology, Chicago.
- Kunii, D. and Levenspiel, O., 1968, **Fluidization Engineering**, Wiley, New York.
- Mazumdar, B. K. and N. N. Chatterjee, 1973, "Mechanism of Coal Pyrolysis in Relation to Industrial Practice," *Fuel*, **52**, p. 11.
- Mentser, M., H. J. O'Donnel, S. Ergun, R. A. Friedel, *Adv. Chem. Ser.*, **131**, p 1 (1974).

- Mentser, M., H. J. O'Donnel, S. Ergun, "Rapid Thermal Decomposition of Bituminous Coals," Am. Chem. Soc., Div. of Fuel Chem. Preprints, **14**, No. 5, p 94 (1970).
- Merrick, D., 1983, "Mathematical Models of the Thermal Decomposition of Coal 2. Specific Heats and Heats of Reaction," Fuel, Vol. 62, pp. 540-546.
- Nsakala, N. Y., R. H. Essenhigh, and R. L. Walker, Combustion Sci. Technol., **16**, p 153, (1977).
- O'Connor, J. G., M. W. Thring, C. Hulse, and M. G. Perry, "Partial Carbonization of High-Volatile Weakly Caking Lump Bituminous Coals," Proceedings of the Conference on Science in the Use of Coal; Institute of Fuel: London. paper no. 22, pc25-c33 (1958).
- Pham, H. N., R. J. Anderson, and P. S. Tam, "Methodology for Prediction of Sulfur Release and Capture in Moving-Bed Coal Gasifiers," Presented at AIChE Spring National Meeting, April 1989; Coal-Fired Power Generation and Cogeneration Session.
- Pitt, G. J, "The Kinetics of the Evolution of Volatile Products from Coal," Fuel, **41**, p 267 (1962).
- Rau, E. and J.A. Robertson, "The Use of the Microsample Strip Furnace in Coal Research", Fuel, **45**, p 73, (1966).
- Stubington, J. F. and Sumaryono, "Release of Volatiles from Large Coal Particles in a Hot Fluidized Bed," Fuel, **63**, p 1013 (1984).
- Solomon, P.R., Serio, M.A., Carangelo, R.M., and Markham, J.R., 1986, "Very Rapid Coal Pyrolysis," Fuel, **65**, February, pp. 182-194.
- Smoot, L.D. et al., 1989, Progress report on Measurement and Modeling of Advanced Coal Conversion Processes, METC, DE-AC21-86MC23075.
- TRW Systems and Energy Group, Morgantown Low-Btu Gasifier Simulation Program, Report prepared jointly with Morgantown Energy Technology Center, October 1978.
- Ubhayakar, S. K., D. B. Sticker, C. W. Von Rosenberg, Jr., and R. E. Gannon, paper presented at the Sixteenth Symposium (International) on Combustion. M.I.T., Cambridge, Mass., August 15-21, 1976.
- Wen, C. Y., H. Chen, and M. Onozaki, "User's Manual for Computer Simulation and Design of the Moving-Bed Coal Gasifier," Final Report prepared for Morgantown Energy Technology Center, Report No. DOE/MC/16474-1390, January 1982.

Wiser, W. H., G. R. Hill, and N. J. Kertamus, "Kinetic Study of the Pyrolysis of a High-Volatile Bituminous Coal," Ind. Eng. Chem. Process Design Develop., **6**, p 133 (1967).

Yoon, H., J. Wei, and M. M. Denn, "A Model for Moving-Bed Coal Gasification Reactors," AIChE Journal, **24**, p 885 (1978).

Table 1
Proximate Analysis

Volatile Matter	36.95
Ash	5.98
Moisture Content	1.33
Carbon	55.74

Table 2A
Summary of Experimental Run Conditions and Results

Run #	Particle Diameter (mm)	Gas Temperature (°F)	Sample Weight (gm)	Tar Collected (gm)
CD0607A.ARK	16	1206	-	-
CD0607B.ARK	16	1220	-	-
CD0608A.ARK	16	1200	-	-
CD0608B.ARK	16	1200	-	-
CD0608C.ARK	16	1200	-	-
CD0608D.ARK	16	1200	-	-
CD0608E.ARK	16	1195	-	-
CD0608F.ARK	16	1195	-	-
CD0608G.ARK	16	1195	-	-
CD0608H.ARK	16	1195	-	-
CD0611A.ARK	16	1200	-	-
CD0611B.ARK	16	1200	-	-
CD0611C.ARK	16	1200	-	-
CD0619A.ARK	17.433	1195	3.7280	0.0815
CD0619B.ARK	17.233	1194	3.7192	0.1147
CD0619C.ARK	16.00	1213	3.0742	0.1871
CD0619D.ARK	16.033	1213	3.1441	0.1758
CD0620A.ARK	14.433	1254	2.1718	0.0126
CD0620B.ARK	14.233	1252	2.0142	0.0374
CD0620C.ARK	14.90	1254	2.0897	0.1681
CD0622A.ARK	14.567	1215	2.3074	0.2144
CD0622B.ARK	14.433	1209	2.0255	0.1405

Table 2B
Summary of Experimental Run Conditions and Results

Run #	Particle Diameter (mm)	Gas Temperature (°F)	Sample Weight (gm)	Tar Collected (gm)
CD0622C.ARK	14.367	1210	2.3257	0.2036
CD0622D.ARK	13.167	1199	1.9028	0.1498
CD0622E.ARK	13.767	1200	1.9209	0.2030
CD0622F.ARK	13.467	1201	1.5960	0.1354
CD0622G.ARK	13.567	1200	1.8414	0.0055
CD0622H.ARK	13.567	1197	1.9116	-
CD0625A.ARK	10.067	1211	0.6703	0.0845
CD0625B.ARK	10.267	1201	0.7936	0.0442
CD0625C.ARK	9.533	1200	0.5997	0.0011
CD0625D.ARK	9.533	1205	0.6403	-
CD0625E.ARK	9.667	1206	0.6589	-
CD0626F.ARK	9.133	1201	0.7193	0.0194
CD0626G.ARK	9.267	1200	0.5552	0.0496
CD0626H.ARK	8.233	1201	0.9733	0.0423
CD0626I.ARK	10.033	1210	0.6962	-
CD0626J.ARK	11.167	1201	0.9240	0.0691
CD0626K.ARK	10.333	1203	0.7696	-

Graphite Felt Insulation
 Alumina Insulation
 Alumina 998
 Graphite Heating Element
 Insulation Tube

- Pressure, Pa 0-101325
- Maximum temperature, °K 1800 °K
- Space velocity, 1/hr 300-5000
- Maximum flowrate, SCFH 5 LPM
- Bed height, cm 0-10 cm
- Reactor ID, cm 2.75 cm
- Reactor materials alumina & zirconia
- Reacting environments oxidizing & reducing

Figure 1. High Temperature Fixed-Bed Reactor

Figure 2. Typical Experimental Temperature Profile.

Figure 3. Comparison of Surface Temperature for Various Runs.

Figure 4. Comparison of Center Temperature for Various Runs.

Figure 5. Experimental Volatile Matter Profile.

Figure 6. Sample before and after devolatilization

Figure 7. Comparison of Model Prediction and Experimental Data for Center Temperature, $D_p = 16$ mm.

Figure 8. Comparison of Model Prediction and Experimental Data for Center Temperature, $D_p = 13.5$ mm, $E_o = 51765$ cal/mole, $\sigma = 11725$ cal/mole, Area Factor = 0.7.

Figure 9. Comparison of Model Prediction and Experimental Data for Center Temperature, $D_p = 10.2$ mm, $E_0 = 51765$ cal/mole, $\sigma = 11725$ cal/mole, Area Factor = 0.7.

Figure 10. Comparison of Model Prediction and Experimental Data for Volatile Matter Loss, $D_p = 16 \text{ mm}$.

Figure 11. Effect of Rate of Devolatilization Pre-exponential Constant, K_0 , on Volatile Matter Profile.

Figure 12. Effect of Particle Diameter on Centerline Temperature.

APPENDIX A
Program Listing

```

C      PROGRAM PARTICLE
C
C      FILENAME  [ PART.FOR ]
C
C      TEMPERATURE AND VOLATILE CONTENT IN A SPHERICAL
C      COAL PARTICLE DURING DEVOLATILIZATION AND HEATING.
C
C      MAIN VARIABLES ARE DEFINED IN THE APPROPRIATE
C      SUBROUTINES.
C
C      THE DISTRIBUTION USED ARE THOSE USED BY ANTHONY ET AL.
C      FOR REACTION CONSTANT, MEAN ACTIVATION ENERGY, AND
C      STANDARD DEVIATION OF THE DISTRIBUTION.
C
C      THIS MAIN SUBPROGRAM ONLY CALL NECESSARY SUBROUTINES
C      IN THE APPROPRIATE SEQUENCE. ALL CALCULATIONS ARE
C      CARRIED OUT IN SUBROUTINES.
C
C      DIMENSION TOLD(50)
C      REAL KGI
C      COMMON / COAP /DENC,EFFK,DP,HTCP,HEPYR,CPCL,TCIN,GAST
C      COMMON / PRY / RKO, EO, SIGM, ULVO, XCR, DEFF, KGI
C      COMMON / CNS / ALPA,CONS1,CONS2,R,TGAS,ANU,CDMT,NP,F,GNU,
1 EFFG
C      COMMON / PROFL / TEMP(50), PYR(50), T, RX(50,21)
C      COMMON / RT / Y(2),COAL
C      DATA TPRNT,PI / 0.0,3.1416 /
C      DATA WLTAR, WLGAS,FTOWL/0.0,0.0,0.0/
C
C      OPEN DATA FILES (PC SPECIFIC)
C
C      *****
C      OPEN(UNIT=5,FILE='C:\WATFOR\WEN\PARTD.DAT',STATUS='OLD')
C      OPEN(UNIT=4,FILE='C:\WATFOR\WEN\PART.OUT',STATUS='UNKNOWN')
C      OPEN(UNIT=7,FILE='C:\WATFOR\WEN\PART.PLT',STATUS='UNKNOWN')
C      OPEN(UNIT=8,FILE='C:\WATFOR\WEN\PART.PRY',STATUS='UNKNOWN')
C      *****
C
C      READ THE PRINT INTERVAL AND DURATION OF SIMULATION
C      [ PRI, FNR ]
C
C      READ( 5,* ) PRI, FNR
C      NP = 30
C      DX = 1./FLOAT(NP)
C      DTIM = 0.1
C      T = 0.0
C      VAV = 0.0
C      WLOSS = 0.0
C      Y(1) = 0.0
C      Y(2) = 0.0
C      DO 2 I=1,NP
C          DO 3 J=1,21

```



```

      RX(I,J) = 0.0
3      CONTINUE
2      CONTINUE
C
C      CALL SUBROUTINE INPUT TO READ IN INPUT INFORMATION
C      AND CALCULATE DIMENSIONLESS PARAMETERS.
C
      CALL INPUT
      CALL OUTPUT
C      WRITE(*,*) ANU,GNU,ALPA
      DT = ALPA * DTIM * 4. / DP / DP
C      DTIM = DT * DP**2/4./ALPA
C
C      INITIALIZE PROFILE INCLUDING THE DISTRIBUTION TABLE
C
      DO 1 I = 1, NP
          TOLD(I) = CDMT
          TEMP(I) = CDMT
          PYR(I) = 1.0
1      CONTINUE
          TAVE = TCIN
          AVE = 0.0
          TIME = 0.0
          COAL = 1.0
          AVTEMP = TAVE*EO/1.986
C
          CALL GAUS( EO, SIGM )
C
          WRITE(4,18) DT,DTIM
18      FORMAT(10X,/10X,'DIMENSIONLESS TIME INCREAMENT = ',
1      E11.4,/10X,'REAL TIME INCREAMENT (SEC)      = ',E11.4,/)
          WRITE(7,15) T,TCIN,TCIN,VAV
          WRITE(4,16)
16      FORMAT(10X,'TIME (SEC)',5X,'CENTER (K)',5X,'SURFACE (K)',
1      5X,'VOL. MAT. LOSS',/)
          WRITE(8,12)
12      FORMAT(5X,'TIME (SEC)',3X,'W/L TAR',3X,'W/L GAS',3X,
1      'FR. TOTAL W/L',3X,'AV. SOLID TEMP (K)',/)
          WRITE(4,15) T, TCIN, TCIN, VAV
15      FORMAT(11X,F7.1,8X,F7.2,9X,F7.2,11X,F6.2)
10      CONTINUE
          TIME = T * DP**2 / 4. / ALPA
C          WRITE(*,*) 'TIME ---> ', TIME
          IF ( (TIME .GT. FNR) .OR. (VAV .GT. 0.94) ) GOTO 99
          T = T + DT
C
C      CALL SUBROUTINE PROFILE TO CALCULATE THE NEW
C      TEMPERATURE PROFILE.
C
      CALL PROFILE(DT, DX, TOLD, PYR, TEMP )
C
C      CALCULATE NEW ENERGY REQUIREMENT BY PYROLYSIS

```

```

C      CALL DEVE( DTIM, EO )
C
C      CALCULATE FRACTION OF VOLATILE MATTER LOSS
C
C      CALL AVERAGE( PYR, VAV )
C      AVE = 100.*VAV*ULVO
C      CEN = TEMP(1)*EO/1.986
C      SU   = F*ANU*DX/2.
C      SURD = ( ( 1.-SU/2.)*TEMP(NP) + SU*TGAS )/(1.+SU/2.)/2.
C      SURD = SURD + TEMP(NP)/2.
C      SUR  = SURD*EO/1.986
C
C      CALCULATE THE RATE OF TAR, CHAR, GAS RELEASE
C
C      CALL RATES(DT,DX,SUR,WLTAR,WLGAS,FTOWL)
C
C      CALCULATE AVERAGE PARTICLE TEMPERATURE
C
C      CALL AVTMP( SURD, NP, TAVE )
C      AVTEMP = TAVE*EO/1.986
C      WRITE(*,*) 'AVERAGE TEMPERATURE = ',AVTEMP
C
C      CHECK IF TIME TO PRINT RESULTS
C
C      IF ( TIME .GE. TPRNT-DTIM/2. ) THEN
C
C      IF PRINT TIME CALCULATE AVERAGE WEIGHT LOSS AND PRINT
C      PROFILES. IF NOT CONTINUE CALCULATION
C
C      TPRNT = TPRNT + PRI
C      WLOSS = DENC * PI * DP**3 * VAV / 6.
C      WRITE(7,15) TIME,CEN,SUR,AVE
C      WRITE(4,15) TIME,CEN,SUR,AVE
C      WRITE(8,11) TIME,WLTAR,WLGAS,FTOWL,AVTEMP
11      FORMAT(6X,F7.1,4X,F7.4,3X,F7.4,6X,F6.4,12X,F7.2)
C      ENDIF
C
C      UPDATE PROFILE AND CALCULATED PARAMETERS
C
C      CALL THERMAL( AVTEMP )
C      CALL HEATCAP( AVTEMP, VAV )
C      CALL PROPER( VAV )
C      DO 21 K = 1, NP
C          TOLD(K) = TEMP(K)
21      CONTINUE
C      GOTO 10
99      STOP
C      END
C-----
C      SUBROUTINE PROPER( A )
C

```

```

C      THIS SUBROUTINE CALCULATES PARAMETERS THAT HAVE CHANGED
C      DUE TO CHANGES IN PHYSICAL PROPERTIES SUCH AS THERMAL
C      CONDUCTIVITY, DENSITY, HEAT CAPACITY

```

```

C      VARIABLE:      A = AVERAGE VOLATILE MATTER LOSS
C

```

```

      REAL KGI
      COMMON / PRY / RKO, EO, SIGM, ULVO, XCR, DEFF, KGI
      COMMON / COAP /DENC,EFFK,DP,HTCP,HEPYR,CPCL,TCIN,GAST
      COMMON / CNS / ALPA,CONS1,CONS2,R,TGAS,ANU,CDMT,NP,F,GNU,
1 EFFG
      D      = DENC* (1. - A)
      ANU    = HTCP * DP / EFFK
      GNU    = HTCP * DP / EFFG
      CONS1 = D * HEPYR * ULVO * DP*DP * R / 4. / EO /EFFK
      ALPA  = EFFK / D / CPCL
      CONS2 = RKO * DP * DP / 4. / ALPA
C      WRITE(*,*) ANU,GNU,ALPA
      RETURN
      END

```

```

C-----
      SUBROUTINE HEATCAP( TAV, VAV )

```

```

C      THIS SUBROUTINE CALCULATES THE HEAT CAPACITY OF THE
C      COAL AS A FUNCTION OF TEMPERATURE USING THE CORRELATION
C      GIVEN BY BADZIOCH ET AL. (1976).
C

```

```

      COMMON / COAP /DENC,EFFK,DP,HTCP,HEPYR,CPCL,TCIN,GAST
      T = TAV - 273.15
      DEN = DENC * ( 1 - VAV )
      IF( T.LE. 350. ) THEN
         CPCL = 1.92E6/DEN/4.1868E6
      ELSE
         X = 1.92E6 - 2.92E3*(T-350.)
         CPCL = X/DEN/4.1868E6
      ENDIF
C      WRITE(*,*) 'CPCL=== ',CPCL
      RETURN
      END

```

```

C-----
      SUBROUTINE THERMAL( TAV )

```

```

C      THIS SUBROUTINE CALCULATES THE EFFECTIVE THERMAL
C      CONDUCTIVITY OF THE COAL USING CORRELATION GIVEN BY
C      BADZIOCH ET AL. (1976).
C

```

```

      COMMON / COAP /DENC,EFFK,DP,HTCP,HEPYR,CPCL,TCIN,GAST
      T = TAV - 273.15
      IF( T.LE.400.) THEN
         EFFK = 0.23/418.68
      ELSE
         X = 0.23 + 2.24E-5*(T-400.)**1.8

```

```

      EFFK = X/418.68
ENDIF
C      WRITE(*,*) 'EFFK --- ', EFFK
      RETURN
      END
C-----
-----
      SUBROUTINE GAUS( ACTE, STDEV )
C
C      THIS SUBROUTINE GENERATES THE GAUSSIAN DISTRIBUTION
C      FOR THE ACTIVATION ENERGY DURING PYROLYSIS. THIS
C      DISTRIBUTION HAS A MEAN, ACTE, AND A STANDARD
C      DEVIATION, STDEV.
C
C      THE DISTRIBUTION IS DEVIDED INTO 20 EQUALLY SPACED
C      INTERVAL FROM ( ACTE - 2*STDEV) TO ( ACTE + 2*STDEV )
C      INCLUDING 95% OF THE DISTRIBUTION.
C
C      THIS SUBROUTINE IS CALL DURING INITIALIZATION AND
C      GENERATES TWO ARRAYS, THE ACTIVATION ENERGY (AE(I))
C      AND ITS CORESPONDING FREQUENCY, ( FE(I) ).
C
      COMMON /DIS/ FE(21), AE(21), NDIS, EINC
      PI = 3.1416
      NDIS = 21
      EINC = 4.0*STDEV/FLOAT(NDIS-1)
      CP = STDEV*SQRT(2.*PI)
      ELW = ACTE - STDEV*2.
      AE(1) = ELW
      FE(1) = EXP( - ( AE(1) - ACTE )**2/2./STDEV**2 ) / CP
      WRITE(4,8)
8      FORMAT(16X,'ACTIVATION ENERGY          FREQUENCY ',/)
      WRITE(4,9) AE(1),FE(1)
9      FORMAT(16X,F11.2,13X,E12.5)
      DO 1 I = 2, NDIS
          AE(I) = ELW + FLOAT(I-1)*EINC
          FE(I) = EXP( -(AE(I)-ACTE)**2/2./STDEV**2 ) / CP
          WRITE(4,9) AE(I),FE(I)
1      CONTINUE
      RETURN
      END
C-----
-----
      SUBROUTINE INTG( X, DX, N, RES )
C
C      THIS SUBROUTINE USES SIMPSON METHOD TO INTEGRATE
C      X - ARRAY , FUNCTION TO BE INTEGRATED
C      DX - STEP SIZE
C      N - NUMBER OF DATA POINTS
C      RES - VALUE OF THE INTEGRAL
C
      DIMENSION X(1)

```

```

SUMO = 0.
NC = N - 1
DO 1 I = 2, NC
    SUMO = SUMO + X(I)
1 CONTINUE
RES = ( SUMO + X(1)/2. + X(N)/2. ) * DX
RETURN
END
C-----
C-----
SUBROUTINE DEVE( DT, ACTE )
C
C THIS SUBROUTINE OBTAINS THE INTEGRAL TERM FOR
C ENERGY REQUIRED FOR DEVOLATILIZATION. THE VALUE
C OF QP FROM THIS SUBROUTINE IS THE INCREMENTAL
C ENERGY REQUIRED FROM TIME ( T ) TO ( T + DT ).
C THE CALLING SUBROUTINE UPDATES FROM T=0 TO (T+DT).
C
C NP      NUMBER OF SPATIAL POINTS IN THE PARTICLE
C DT      DIMENSIONAL TIME STEP
C ACTE    MEAN ACTIVATION ENERGY
C UA      TEMPERATURE PROFILE ( ARRAY, DIMENSIONLESS )
C QP      INCREMENTAL DIMENSIONLESS ENERGY FOR PYROLYSIS
C
C DIMENSION FX(50), RP(50,21)
C COMMON / CNS / ALPA,CONS1,CONS2,R,TGAS,ANU,CDMT,NP,F,GNU,
1 EFFG
C COMMON / DIS / FE(21), AE(21), NDIS, EINC
C COMMON / PROFL / TEMP(50), PYR(50), T, RX(50,21)
C DATA RP / 1050*0.0 /
C DO 1 I = 1, NP
C     DO 5 J = 1, NDIS
C         A = CONS2*EXP( - AE(J)/ACTE/TEMP(I) ) * DT
C         RX(I,J) = RX(I,J) + A
C         FX(J) = EXP( - RX(I,J) ) * FE(J)
5     CONTINUE
C     CALL INTG( FX, EINC, NDIS, SUM )
C
C STORE THE CURRENT FRACTION VOLATILE MATTER LEFT
C
C     PYR(I) = SUM
1 CONTINUE
RETURN
END
C-----
C-----
SUBROUTINE INPUT
C
C THIS SUBROUTINE OBTAINS THE INPUT DATA
C
C CARD-1 DURATION OF SIMULATION
C - PRINT INTERVAL

```

```

C          - TOTAL SIMULATION TIME
C
C CARD-2    SIMULATION DESCRIPTION (60 CHARACTERS LONG )
C
C CARD-3    PROXIMATE ANALYSIS OF THE COAL (WT%)
C          - MOISTURE CONTENT ( WT% )
C          - VOLATILE MATTER CONTENT (WT%)
C          - FIXED CARBON CONTENT ( WT% )
C          - ASH CONTENT ( WT% )
C          * ALL FOUR ABOVE SHOULD SUM UP TO 100 PERCENT.
C
C CARD-4    ULTIMATE ANALYSIS ( BASED ON TOTAL WEIGHT OF COAL
C          INCLUDING MOISTURE AND ASH )
C          - CARBON CONTENT ( WT RATIO )
C          - HYDROGEN CONTENT ( WT RATIO )
C          - OXYGEN CONTENT ( WT RATIO )
C          - NITROGEN CONTENT ( WT RATIO )
C          - SULFUR CONTENT ( WT RATIO )
C
C CARD-5    INITIAL CONDITIONS ( PARTICLE )
C          - INITIAL TEMPERATURE (F)
C          - PARTICLE DIAMETER (IN)
C          - ULTIMATE VOLATILE MATTER YIELD (%)
C          - DENSITY OF PARTICLE (LBM/CU. FT )
C          - THERMAL CONDUCTIVITY OF COAL ( BTU/ HR-FT-F )
C          - THERMAL CONDUCTIVITY OF GAS ( BTU/HR-FT-F )
C
C CARD-6    OPERATING CONDITIONS (GAS)
C          - TEMPERATURE OF GAS (F)
C          - HEAT TRANSFER COEFFICIENT ( BTU/ SQ. FT -HR-F )
C          - VELOCITY OF GAS ( FT/SEC )
C          - FRACTION OF HEAT TRANSFER BY CONVECTION
C          - MASS TRANSFER COEFFICIENT ACROSS GAS FILM (CM/SEC)
C
C CARD-7    PYROLYSIS CONSTANT
C          - MEAN ACTIVATION ENERGY ( CAL/GMOLE )
C          - STANDARD DEVIATION OF DISTRIBUTION ( CAL/GMOLE )
C          - REACTION CONSTANT ( 1/SEC )
C          - HEAT OF PYROLYSIS ( CAL/GM )
C          - EFFECTIVE DIFFUSION COEFFICIENT (SQ. CM/SEC)
C
C CARD-8    PYROLYSIS RATE CONSTANTS AND ACTIVATION ENERGIES
C          - REACTION CONSTANT FOR COAL DEVOLATILIZATION (1/S)
C          - ACTIVATION ENERGY FOR COAL DEVOLATILIZATION
C            (CAL/G-MOLE)
C          - REACTION CONSTANT FOR TAR CRACKING (1/S)
C          - ACTIVATION ENERGY FOR TAR CRACKING (CAL/G-MOLE)
C          - REACTION CONSTANT FOR TAR DEPOSITION (1/S)
C          - ACTIVATION ENERGY FOR TAR DEPOSITION (CAL/G-MOLE)
C
C          CHARACTER*60 TITLE
C          REAL KGI

```



```

      RKO   = RCONS
      EO    = ACENM
      SIGM  = SDEV
      TAVE  = ( TCIN + GAST ) / 2.
      CPCL  = 0.25
      R     = 1.986
C      DEFF = 5.0E-3
      TGAS  = GAST * R / EO
      CDMT  = TCIN * R / EO
      ANU   = HTCP * DP / EFFK
      GNU   = HTCP * DP / EFFG
      CONS1 = DENC * HEPYR * ULVO * DP*DP * R / 4. / EO /EFFK
      ALPA  = EFFK / DENC / CPCL
      CONS2 = RKO * DP * DP / 4. / ALPA
C      FOR BITUMINOUS AND SUBBITUMINOUS COAL
      XCR = 1.30*VM + 0.025
      RETURN
      END

```

```

C-----
----

```

SUBROUTINE OUTPUT

```

C      THIS SUBROUTINE WRITES OUT INPUT AND CALCULATED
C      PARAMETERS.
C
      CHARACTER*60 TITLE
      REAL KGI
      COMMON / CD1 / TITLE
      COMMON / CD2 / RMOIST, VM, FIXC, ASH
      COMMON / CD3 / FC, FH, FO, FN, FS, FASH
      COMMON / CD4 / TCOAL, DIAP, VMD, DCOAL, THERK, THERG
      COMMON / CD5 / TPGAS, HTRC, GVEL
      COMMON / CD6 / ACENM, SDEV, RCONS
      COMMON / COAP / DENC, EFFK, DP, HTCP, HEPYR, CPCL, TCIN, GAST
      COMMON / PRY / RKO, EO, SIGM, ULVO, XCR, DEFF, KGI
      C O M M O N / C N S /
ALPA, CONS1, CONS2, R, TGAS, ANU, CDMT, NP, F, GNU,
1 EFFG
      COMMON / RT2 / CK10, CK20, CK30, E10, E20, E30
C
      WRITE(4,1) TITLE
1      FORMAT(5X,A60,/)
      WRITE(4,2) RMOIST, VM, FIXC, ASH
2      FORMAT(10X,'PROXIMATE ANALYSIS OF THE COAL (WT%)',/
115X,'MOISTURE CONTENT' = ',F6.2,/
215X,'VOLATILE MATTER CONTENT' = ',F6.2,/
315X,'FIXED CARBON CONTENT' = ',F6.2,/
415X,'ASH CONTENT' = ',F6.2,/)
      WRITE(4,3) FC, FH, FO, FN, FS
3      FORMAT(10X,'ULTIMATE ANALYSIS (BASED ON TOTAL WEIGHT)',/
1 15X,'CARBON CONTENT' = ',F6.4,/
2 15X,'HYDROGEN CONTENT' = ',F6.4,/

```



```

3 15X,'OXYGEN CONTENT           = ',F6.4,/
4 15X,'NITROGEN CONTENT         = ',F6.4,/
5 15X,'SULFUR CONTENT           = ',F6.4,/)
    WRITE(4,4) TCIN,DP,VMD,DENC,CPCL,EFFK,EFFG
4    FORMAT(10X,'              COAL PROPERTIES',//
1 12X,'INITIAL TEMPERATURE OF COAL [K]           = ',F6.1,/
2 12X,'PARTICLE DIAMETER [CM]                   = ',F6.3,/
3 12X,'ULTIMATE VOLATILE MATTER YIELD [%]          = ',F6.2,/
4 12X,'DENSITY OF PARTICLE [GM/CU. CM]           = ',F6.3,/
5 12X,'HEAT CAPACITY OF PARTICLE [CAL/G.K]        = ',F6.3,/
6 12X,'EFFECTIVE THERMAL CONDUCTIVITY [CAL/CM.S.K] = ',E10.3,/
7 12X,'THERMAL CONDUCTIVITY OF GAS [CAL/CM.S.K]   =
',E10.3,/)
    WRITE(4,5) GAST,HTCP,KGI,F
5    FORMAT(10X,/
1 12X,'GAS TEMPERATURE [K]                       = ',F7.1,/
2 12X,'HEAT TRANSFER COEFFICIENT [CAL/SQ. CM S. K] = ',E11.4,/
4 12X,'MASS TRANSFER COEFFICIENT ACROSS GAS [CM/S] = ',E11.4,/
3 12X,'FRACTION HEAT TRANSFER BY CONVECTION      =
',F4.1,/)
    WRITE(4,6) HEPYR,RKO,DEFF,EO,SIGM
6    FORMAT(10X,' DEVOLATILIZATION PARAMETERS',//
1 12X,'HEAT OF PYOLYSIS [CAL/GM]                 = ',E11.4,/
2 12X,'REACTION CONSTANT [1/S]                  = ',E11.4,/
3 12X,'EFFECTIVE DIFFUSION COEFFICIENT [SQ.CM/S] = ',E11.4,/
3 12X,'MEAN ACTIVATION ENERGY [CAL/MOLE]        = ',F11.2,/
4 12X,'STANDARD DEVIATION OF DISTRIBUTION [CAL/MOL]=
',F11.2,/)
    WRITE(4,8) CK10,E10,CK20,E20,CK30,E30
8    FORMAT(10X,'PYROLYSIS REACTION CONSTANTS',//
1 12X,'REACTION CONSTANT, COAL DEVO. [1/S;K10]    =
',E11.4,/
2 12X,'ACTIVATION ENERGY, COAL DEVO. [CAL/G-MOLE;E10] =
',E11.4,/
3 12X,'REACTION CONSTANT, TAR CRACKING [1/S;K20]  =
',E11.4,/
4 12X,'ACTIVATION ENERGY, TAR CRACKING [CAL/G-MOLE;E20]=
',E11.4,/
5 12X,'REACTION CONSTANT, TAR DEPOSITION [1/S;K30] =
',E11.4,/
6 12X,'ACTIVATION ENERGY, TAR DEPOS. [CAL/G-MOLE;E30] =
',E11.4,/
7 //)
    WRITE(4,7) ALPA,TGAS,ANU,GNU,CDMT,CONS1,CONS2
7    FORMAT(10X,'CALCULATED PARAMETERS.....',//
1 12X,'THERMAL DIFFUSIVITY [SQ. CM/S]             = ',E12.5,/
2 12X,'DIMENSIONLES TEMPERATURE OF GAS           = ',E12.5,/
3 12X,'NUSSELT NUMBER (PARTICLE)                 = ',E12.5,/
4 12X,'NUSSELT NUMBER (GAS)                     = ',E12.5,/
5 12X,'INITIAL TEMPERATURE OF PARTICLE [DIM]      = ',E12.5,/
6 12X,'CONSTANT 1 .... CONS1 .....              = ',E12.5,/
7 12X,'CONSTANT 2 .... CONS2 .....              =

```

',E12.5,//)

RETURN
END

C-----

SUBROUTINE AVERAGE(PY, AV)

C

C

C

C

THIS SUBROUTINE CALCULATES THE AVERAGE VOLATILE
MATTER LOSS

REAL KGI

COMMON / COAP / DENC, EFFK, DP, HTCP, HEPYR, CPCL, TCIN, GAST

COMMON / PRY / RKO, EO, SIGM, ULVO, XCR, DEFF, KGI

COMMON / CNS / ALPA, CONS1, CONS2, R, TGAS, ANU, CDMT, NP, F, GNU,

1 EFFG

DIMENSION PY(1), Y(50)

DX = 1./FLOAT(NP)

DO 1 I = 1, NP

Y(I) = (1. - PY(I)) * (DX * FLOAT(I-1))**2

1

CONTINUE

CALL INTG(Y, DX, NP, ANS)

AV = 3. * ANS

RETURN

END

C-----

SUBROUTINE PROFILE(DTT, DXX, UO, QP, UN)

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

C

THIS SUBROUTINE OBTAINS THE TEMPERATURE PROFILE
AT ANY TIME, T, IN THE PARTICLE.

DTT TIME STEP (DIMENSIONLESS)

DXX SPATIAL STEP (1/NC) (DIMENSIONLESS)

NC NUMBER OF SPATIAL POINTS

UO ARRAY, OLD TEMPERATURE PROFILE (T)

UN ARRAY, NEW TEMPERATURE PROFILE (T+DT)

DENS DENSITY OF COAL (SI UNITS)

EFFK EFFECTIVE THERMAL CONDUCTIVITY OF COAL

DP COAL PARTICLE DIAMETER

HTCP HEAT TRANSFER COEFFICIENT (SURFACE/GAS)

HEPYR HEAT OF PYROLYSIS

CPCL HEAT CAPACITY OF COAL

R GAS CONSTANT (= 1.986 CAL/MOL.K)

TGAS DIMENSIONLESS TEMPERATURE OF GAS

DEVOLATILIZATION PARAMETERS

RKO REACTION CONSTANT (1/S)

EO MEAN ACTIVATION ENERGY (CAL/MOL)

SIGM STANDARD DEVIATION OF THE ACTIVATION

ENERGY GAUSSIAN DISTRIBUTION (CAL/MOL)

ULVO ULTIMATE VOLATILE YIELD BASED ON DETAIL

ANALYSIS (FRACTION)

C

```

      REAL KGI
      COMMON / COAP / DENC, EFFK, DP, HTCP, HEPYR, CPCL, TCIN, GAST
      COMMON / PRY / RKO, EO, SIGM, ULVO, XCR, DEFF, KGI
      COMMON / CNS / ALPA, CONS1, CONS2, R, TGAS, ANU, CDMT, NP, F, GNU,
1  EFFG
      DIMENSION UO(1), UN(1), QP(1), TMOS(50,4)
      NC = NP
      DX2 = DX*DX
      AM = 1. + F*ANU*DX/4.
      DO 1 I = 1, NC
      AI = FLOAT(I)
      PYR = CONS1*QP(I)*RKO*EXP( -1./UO(I) )
      IF ( (I-NC).EQ. 0 ) THEN
        TMOS(I,1) = - .5/DX2 + .5/(AI-0.5)/DX2
        DA = ( 1. + 1./(AI-.5) )/DX2/2.
        DA = DA*( 1. - F*ANU*DX/4. )/AM
        TMOS(I,2) = 1./DTT + 1./DX2 - DA
        TMOS(I,3) = 0.0
        DA4 = ( 1. + 1./(AI-.5) )/DX2/2./AM
        DA1 = ( 1. - F*ANU*DX/4. )*UO(I)
        DA5 = ( F*ANU*DX/2. )*TGAS
        DA = ( DA1 + DA5)*DA4 - PYR
        DA2 = DA4 * DA5
        DA3 = (UO(I-1)-2.*UO(I))/DX2/2. + UO(I)/DTT
        TMOS(I,4) = DA3 - UO(I-1)/DX2/(AI-.5)/2.+ DA2 + DA
      ELSEIF ( (I-1).EQ.0 ) THEN
        TMOS(I,1) = 0.0
        TMOS(I,2) = 1./DTT + 0.5/DX2 + .5/(AI-.5)/DX2
        TMOS(I,3) = - ( 1. + 1./(AI-.5) )/2./DX2
        DA = ( 1. + 1./(AI-.5) )/2./DX2
        TMOS(I,4) = DA*(UO(I+1)-UO(I)) + UO(I)/DTT - PYR
      ELSE
        TMOS(I,1) = -0.5 * ( 1. - 1./(AI-0.5) ) /DX2
        TMOS(I,2) = 1./DTT + 1./DX2
        TMOS(I,3) = - (1. + 1./(AI-0.5) ) /DX2 /2.
        DA = .5*( UO(I+1) - 2.*UO(I) + UO(I-1) ) / DX2
        DA = DA + UO(I)/DTT - PYR
        TMOS(I,4) = DA + ( UO(I+1) - UO(I-1) )/2./(AI-.5)/DX2
      ENDIF
1    CONTINUE
C
C  CALL SUBROUTINE THOMAS TO CALCULATE THE NEW PROFILE
C
      CALL THOMAS( NC, TMOS, UN )
      DO 3 I = 1, NC
        IF( UN(I) .LT. 0.0 ) UN(I) = CDMT
3    CONTINUE
      RETURN
      END
C-----
C  THIS SUBROUTINE SOLVES TRIDIAGONAL SET OF LINEAR EQS.

```

```

C
      SUBROUTINE THOMAS(M,P,R)
      DIMENSION P(50,4),R(1),BETA(50),GAMMA(50)
      BETA(1) = P(1,2)
      GAMMA(1) = P(1,4)/P(1,2)
      DO 4 I = 2, M
          BETA(I) = P(I,2) - P(I,1)*P(I-1,3)/BETA(I-1)
          GAMMA(I) = ( P(I,4) - P(I,1)*GAMMA(I-1) )/ BETA(I)
4      CONTINUE
      R(M) = GAMMA(M)
      LM = M - 1
      DO 5 I = 1, LM
          J = M - I
          R(J) = GAMMA(J) - P(J,3)*R(J+1)/BETA(J)
5      CONTINUE
      RETURN
      END

C-----
      SUBROUTINE RATES( DXX, DTT, TMP, WLT, WLG, FTWL )

C
C      THIS SUBROUTINE CALCULATES THE RATE TAR, CHAR AND GAS
C      RELEASE BY DEVOLATILIZATION BASED ON THE RATE EQUATIONS
C      PROPOSED BY WEN IN HIS ORIGINAL PAPER.  THE CONSTANTS
C      IN THIS RATE EXPRESSION WILL HAVE TO BE FITTED TO
C      EXPERIMENTAL DATA.
C
      REAL KGI
      COMMON / COAP /DENC,EFFK,DP,HTCP,HEPYR,CPCL,TCIN,GAST
      COMMON / PRY / RKO, EO, SIGM, ULVO, XCR, DEFF, KGI
      COMMON / CNS / ALPA,CONS1,CONS2,R,TGAS,ANU,CDMT,NP,F,GNU,
1  EFFG
      COMMON / RT / Y(2),COAL
      COMMON / RT2 / CK10,CK20,CK30,E10,E20,E30
      AREA = 4.0*3.1416*(DP/2.)**2

C
C      CALCULATE ABSOLUTE TEMPERATURE FOR THE THREE POINTS FOR
C      BOTH GAS AND TAR.
C
      CK1 = CK10*EXP( - E10/1.986/TMP )
      CK2 = CK20*EXP( - E20/1.986/TMP )
      CK3 = CK30*EXP( - E30/1.986/TMP )

C
C      I=1,2,3 - TAR CONCENTRATION AT NP-1, NP, AND SURFACE
C      I=4,5,6 - GAS CONCENTRATION AT NP-1, NP, AND SURFACE
C
      A1 = XCR*CK1*COAL
      A2 = CK2 + CK3
C      WRITE(*,*) CK1,CK2,CK3,A2
C      TAR CONCENTRATION AT THE SURFACE
      CALL RUNK( A1,A2,DTT,Y(1) )
C      GAS CONCENTRATION AT THE SURFACE
C      Y(2) = Y(2) + CK2*Y(1)*DTT

```

```

      Y(2) = Y(2) + ((1.-XCR)*CK1*COAL+(CK2+CK3)*Y(1))*DTT
C
C   CALCULATE THE WEIGHT LOSS BY THE TAR AND THE GAS
C   USING THE MASS BALANCE AT THE PARTICLE SURFACE
C
      TARF = KGI*DENC*Y(1)
      GASF = KGI*DENC*Y(2)
      WLT  = WLT + TARF*DTT*AREA
      WLG  = WLG + GASF*DTT*AREA
      TWL  = WLT + WLG
      FTWL = TWL/( 4.*DENC*(DP/2.))**3/3.1416)
      IF (FTWL .GT. 1.00) FTWL = 1.000
      COAL = 1.0 - FTWL
C      WRITE(*,*) 'RATES-- ', Y
C      WRITE(*,*) 'RATES-- ', WLT,WLG,TWL,COAL,Y
      RETURN
      END
C-----
C
C   SUBROUTINE TO CALCULATE THE AVERAGE TEMPERATURE OF
C   THE PARTICLE.
C
      SUBROUTINE AVTMP( ST, NP, TAVE )
      COMMON / PROFL / TEMP(50), PYR(50), T, RP(50,21)
      DIMENSION AVT(50)
      DX = 1.0/FLOAT(NP)
      N = NP + 2
      AVT(1) = 0.0
      DO 1 I=1, NP
         XT = ( FLOAT(I) - 0.5 ) * DX
         AVT(I+1) = TEMP(I)*XT**2
1      CONTINUE
      AVT(N) = ST
      SUM = ( AVT(1)+AVT(2) + AVT(N-1)+AVT(N) )*(DX/2.)/2.
      SM = 0.
      NX = N-2
      DO 2 I = 3,NX
         SM = SM + AVT(I)
2      CONTINUE
      SM = DX*(.5*AVT(2) + SM + 0.5*AVT(N-1) )
      TAVE = 3.0*( SM + SUM )
      RETURN
      END
C-----
C   SUBROUTINE RUNK( AX, BX, DX, VAV )
      TK1 = ( AX - BX*VAV ) * DX
      Y1  = VAV + TK1*0.5
      TK2 = ( AX - BX*Y1 ) * DX
      Y1  = VAV + TK2*0.5
      TK3 = ( AX - BX*Y1 ) * DX
      Y1  = VAV + TK3
      TK4 = ( AX - BX*Y1 ) * DX

```

```
VAV = VAV + ( TK1 + 2.*(TK2+TK3) + TK4 )/6.0  
RETURN  
END
```

APPENDIX B
Experimental Temperature Profiles

Figure B1. Experimental Temperature Profile

Figure B2. Experimental temperature profile

Figure B3. Experimental temperature profile

Figure B4. Experimental temperature profile

Figure B5. Experimental temperature profile

Figure B6. Experimental temperature profile

Figure B7. Experimental temperature profile

Figure B8. Experimental temperature profile

Figure B9. Experimental temperature profile

Figure B10. Experimental temperature profile

Figure B11. Experimental temperature profile

Figure B12. Experimental temperature profile

Figure B13. Experimental temperature profile

Figure B14. Experimental temperature profile

Figure B15. Experimental temperature profile

Figure B16 Experimental temperature profile

END

**DATE
FILMED
4 128192**