DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

FINAL REPORT

**PROJECT TO DEMONSTRATE POTENTIAL ENERGY
SAVINGS FROM INDUSTRIAL CUSTOMERS**

Michigan Department of Commerce
PUBLIC SERVICE COMMISSION
6545 Mercantile Way
P.O. Box 30221
Lansing, Michigan 48909

and

THE DETROIT EDISON COMPANY
2000 Second Avenue
Detroit, Michigan 48226

In cooperation with:

DEPARTMENT OF ENERGY
Office of Utility Systems
Economic Regulatory Administration
Washington, D. C. 20461

This report was prepared under contract with the Department of Energy (FEA) and does not necessarily state or reflect the views, opinions, or policies of DOE or the Federal Government.

Reference to trade names or specific commercial products, commodities, or services in this report does not represent or constitute an endorsement, recommendation, or favoring by DOE of the specific commercial product, commodity, or service.

This report has been prepared pursuant to a cooperative agreement between the State of Michigan and the U.S. Department of Energy. Its issuance and content do not necessarily reflect the policies of the Michigan Department of Commerce, Public Service Commission, nor has it been adopted as policy by the Commission or the State of Michigan.

Page

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

PARTICIPATING AGENCIES

Michigan Department of Commerce
Public Service Commission
6545 Mercantile Way
P.O. Box 30221
Lansing, Michigan 48909

The Detroit Edison Company
2000 Second Avenue
Detroit, Michigan 48226

U.S. Department of Energy
Division of Regulatory Assistance
Office of Utility Systems
Economic Regulatory Administration
Twelfth & Pennsylvania Avenues, NW
Room 524 - Van Guard Building
Washington, D. C. 20461

REPORT PREPARED BY:

Robert P. Benko	- Supervisor, Special Studies Section, Technical Services and Issue Analysis Division of the Michigan Public Service Commission.
Gondy B. Rao	- Policy Analyst, Special Studies Section, Technical Services and Issue Analysis Division of the Michigan Public Service Commission. Principal Investigator and Writer.
Robert L. Veenstra	- Director of Customer and Marketing Services, Ann Arbor Division, Detroit Edison Company.
Robert S. Luke	- Energy Management Analyst, Commercial Market Planning, Detroit Edison Company.
Dr. Barbara Murray	- Consulting Economist
Joel Sharkey	- Editor, Supervisor, Issue Analysis Section, Technical Services and Issue Analysis Division of the Michigan Public Service Commission.
Dr. Harold Reinholds	- Economic Analyst, Special Studies Section, Technical Services and Issue Analysis Division of the Michigan Public Service Commission

Personnel of several departments of the Detroit Edison Company and the Michigan Public Service Commission assisted in conducting the technical surveys, analysis of the surveys, and the data processing of historical test data.

PROJECT TO DEMONSTRATE POTENTIAL ENERGY
SAVINGS FROM INDUSTRIAL CUSTOMERS

Project Organization Structure

Daniel J. Demlow, Chairman, Michigan Public Service Commission
Willa Mae King*, Commissioner, Michigan Public Service Commission
Lenton G. Sculthorp, Commissioner, Michigan Public Service Commission

Project Direction Group

William A. Babbitt, Industries' Consumer Representative
Roger Fischer, Chief of Staff, MPSC
Ernest Grove, Jr., Senior Executive Vice-President - Finance,
Detroit Edison Company
Tom Hancock**, Chief of Staff, Michigan Public Service Commission
James Hughes, Director of the Office of Management Planning and
Analysis, Michigan Department of Commerce
Eric Schneidewind, Director of the Office of Policy, MPSC
Dr. Harry Trebing, Professor of Economics, Michigan State University
Richard Viinikainen, Director - Rate Department, Detroit Edison Co.
Robert Wagner, Assistant Vice-President - Rates and Financial
Evaluation

Consultants

Dr. Barbara Murray, Economist
Randy Richardson, Engineer

Contact Persons Regarding Study

Robert Benko, MPSC, 517/373-8171 (Lansing, Michigan)
Robert Veenstra, Detroit Edison Co., 313/769-5888 (Ann Arbor, Michigan)

* Commissioner Willa Mae King replaced Commissioner William Ralls
on August 10, 1977.
** Mr. Hancock retired from the Commission in January, 1978.

PROJECT MANAGEMENT TEAM

John A. Abramson	- Director, Technical Services & Issue Analysis Division, Program Development, MPSC - FEA Project
Larry Bailey	- Governmental Auditor, Electric Division, MPSC, Surveys - FEA Project
Robert P. Benko	- Supervisor, Special Studies Section, MPSC, Project Manager, FEA Study
Samuel W. Byer	- Supervisor, Utility Systems Audit Section, MPSC, Data Processing - FEA Study
Jane Ann Charland	- Program Analyst, Special Studies Section, MPSC, Data Processing - FEA Study
Sharon Ehlke	- Program Analyst, Special Studies Section, MPSC, Data Processing - FEA Study
James F. Finn	- Industrial and Commercial Lighting Consultant, Commercial Market Planning, The Detroit Edison Company - FEA Project
Roger F. Fischer	- Director, Electric Division, MPSC
Alden Harrington	- Director of Business Services, Consumer Services Division, MPSC, Surveys - FEA Project
Thomas R. Lonergan	- Executive Secretary, MPSC, Project Planning and Control - FEA Study
Robert S. Luke	- Energy Management Analyst, Commercial Market Planning, The Detroit Edison Company, Surveys - FEA Project Coordinator
Wilbur F. McNinch	- Supervisor, Rate and Tariff Section, Gas Division, MPSC, Surveys - FEA Study
Ronald Radke	- Economic Analyst, Electric Division, MPSC, Data Processing - FEA Study
Gondy B. Rao	- Policy Analyst, Special Studies Section, Project Analysis, Evaluation, MPSC - FEA Project Coordinator
Dr. Harold Reinholds	- Economic Analyst, Special Studies Section, MPSC - FEA Study
Jane L. Rhoads	- Secretary, Special Studies Section, MPSC

Project Management Team - Cont'd

Dennis Schwartz*	- Economic Analyst, Special Studies Section, MPSC, Surveys - FEA Study
Joel A. Sharkey	- Supervisor, Issue Analysis Section, MPSC
Robert L. Veenstra	- Director of Customer and Marketing Services, Ann Arbor Division, The Detroit Edison Company, Project Manager - FEA Study
Edward C. Watt	- Comfort, Condition and Process Heating Engineer, Commercial Market Planning, The Detroit Edison Company, HVAC - FEA Project

FEA = Federal Energy Administration (DOE)
MPSC = Michigan Public Service Commission
HVAC = Heating, Ventilation, and Air Conditioning

* Mr. Schwartz left the Commission prior to the conclusion of the study.

TABLE OF CONTENTS

	<u>Page</u>
EXECUTIVE SUMMARY	ES-1
CHAPTER I - DETAILED SUMMARY OUTLINE	1
A. Introduction	2
B. Specific Project Goals	4
C. Project Methodology and Scope	4
D. Sample Selection Criteria	6
E. Relative Efficiency of the Sample Design	8
F. Surveys	9
G. Economic Analysis	11
H. Customer Acceptance of the Proposals	14
I. Implementation	15
J. Major Electrical Uses of the Test Companies by Specific Areas	16
K. Rationale for Using ANSI Lighting Standards	16
L. Customer Participation	17
M. Administration of the Test	17
N. Financial Assistance to the Test Customers	18
O. Control Customers	18
P. Additional Concerns of the Test	18
CHAPTER II - DETAILED METHODOLOGY	20
A. Sample Selection	21
B. Surveys	37
C. Economic Analysis	40
CHAPTER III - TECHNICAL SURVEY FINDINGS	43
A. Introduction	44
B. Summary Results and Findings	45
CHAPTER IV - PROGRAM IMPLEMENTATION	96
A. Introduction	97
B. A Summary of the Type and Category of Proposal Recommendations and Final Results of the Test	99
C. An Analysis of the Impact of New vs. Old Rates of the Test Customers	158

Continued....

	<u>Page</u>
CHAPTER V - SYSTEM-WIDE IMPLEMENTATION	169
A. Projected Savings on the Detroit Edison System	170
B. System-wide and Multi System-wide Implementation of the Demonstrated Activities	173
C. Conclusions	176
D. Recommendations	189
APPENDICES	192
Appendix A-I. Economic Feasibility of Load Management Investment: An Example	193
Appendix A-II. Load Management Survey Forms I, II & III . .	202
Appendix A-III. Historical Data Analysis and Demand Profiles	213
Appendix B. Evaluation of Demand Monitoring System, Test Customer SIC 33-B	222
Appendix C. System and Customer Load Curves Prior to Test and After Test	240
Appendix D. 1975, 1976, 1977 Rates and Conversion Factors	293
GLOSSARY	296
BIBLIOGRAPHY	305

TABLES

CHAPTER I

<u>Number</u>		<u>Page</u>
1	Allocation of Sample Test and Control Customers	8
2	Cost Effectiveness of Load Management Investments	13
3	Major Electrical Uses of the Test Companies by Specific Areas in 1975	16
4	Percent of the Proposal Recommendations Implemented	17

CHAPTER II

<u>Number</u>		
1	Classification of Detroit Edison's Primary Customers by Industry	23
2	Manufacturing SIC Groups Not Considered for Sample Selection	25
3	Classification of Primary Industrial Customers by Type	25
4	Monthly Primary Demand of Available Industrial Customers	26
5	Average Monthly Primary Demand Less than 6,000 kW	26
6	Average Monthly Primary Demand Greater than 6,000 kW	27
7	Allocation of 40 Companies to Different Strata - I	28
8	Allocation of 40 Companies to Different Strata - II	29
9	Relative Comparison of Sample Allocation to Strata	35

CHAPTER III

<u>Number</u>		
1	Annual Energy Consumption by 20 Test Companies and the Billing Cost of Energy in 1975	46
2	Annual Energy Consumption by Btu's of 19 Test Companies for 1975	47

TABLES (Cont'd)

Chapter III (Cont'd)

<u>Number</u>		<u>Page</u>
3	Distribution of Annual Billing Cost of Energy Paid by Test Companies in 1975	51
4	Distribution of Average Total Billing Cost of Energy Consumed by Test Companies in 1975 by Type of Energy	52
5	Summary of Monthly Peak Demand (kW) Changes, Test Companies - 1976	55
6	Estimated Monthly kW Changes by Specific Areas Due to Load Management (Test Companies)	57
7	Estimated Net Reduction in Peak Demand (kW) of the Test Companies Due to Electric Load Management	58
8	Summary of Monthly Kilowatt-hour Changes, Test Companies - 1976	61
9	Estimated Monthly Savings in Energy (kWh) Due to Load Management Compared to Actual Energy Consumption in 1975	63
10	Summary Areas for Monthly kWh Changes Due to Load Management Compared to 1975 kWh Consumption, Test Companies - 1976	64
11	Estimated Net kWh Reductions by Area Due to Load Management Compared to 1975 kWh Consumption Test Companies - 1976	65
12	Estimated Percentage Monthly Reduction in Demand and Energy Due to Load Management - 1976	67
13	Estimated Monthly Reduction in Electrical Energy Due to Load Management by Industry Groups	70
14	Estimated Annual Energy Cost for 1976 and Energy Cost with Load Management, Test Companies	72
15	Estimated Average Annual Energy Cost and Average Dollar Savings per Customer and Percent Savings with Load Management, Test Customer - 1976	74
16	Estimated Annual Dollar Savings Due to Load Management, Test Customers - 1976	75

TABLES (Cont'd)

Chapter III (Cont'd)

<u>Number</u>		<u>Page</u>
17	Estimated Annual Average Savings per Customer Due to Load Management	77
18	Summary of Estimated Percentage Savings of the Test Companies Due to Load Management	80
19	Financial Feasibility of Load Management Investments, Test Companies - 1976	82
20	Historical Average Load Factors of the Test Companies	87
21	Annual Percent of On-peak Kilowatt-hour Consumption of 20 Test Companies Between 9 am - 9 pm to the Total of 24-hour kWh Consumption (Monday-Friday)	89
22	Summary of Major Proposal Items	91

CHAPTER IV

<u>Number</u>		
A	Status of Major Proposal Recommendations	110
B	Continuation of the Status of Major Proposal Recommendations	116
1	Test Period Dates and Number of Months Customers were Tested	136
2	Summary of Monthly Peak Kilowatt Changes, Test Companies (1976-77)	138
3	Major Electrical Uses of the Test Companies by Specific Areas (1975)	139
4	Summary of Monthly kW Changes by Specific Areas During the Test Period, Test Companies (1976-77)	140
5	A Comparison Between Estimated and Actual Monthly Net Reductions in Peak Demand (kW) of the Test Companies Due to Load Management	141
6	Distribution of Estimated and Actual Net Percentage Reductions in Peak Demand by Specific Areas Due to Load Management Compared to 1975 Monthly Peak Demand Consumption	142

TABLES (Cont'd)

Chapter IV (Cont'd)

<u>Number</u>		<u>Page</u>
7	Summary of Monthly kWh Changes by Specific Areas During the Test Period, Test Companies (1976-77)	145
8	Summary of Estimated and Actual Net kWh Reduction by Area Due to Load Management	147
9	Estimated and Actual Percentage Monthly Reduction in Electrical Energy Due to Load Management Compared to 1976 (Before Proposal) Consumption	149
10	Distribution of Estimated and Actual Net Percentage kWh Reductions by Area Due to Load Management Compared to 1975 kWh Consumption	150
11	A Comparison Between Estimated and Actual Annual Dollar Savings (Electric), Test Companies, 1976-77	153
12	Average Percentage On-peak and Off-peak Monthly Consumption of Electrical Energy (kWh) by the Test and Control Companies Prior to Test Period and During the Test Period (Monday-Sunday)	156
13	Average Load and Power Factors of Test and Control Companies Prior to Test Period and During Test Period (Monday-Sunday)	157
14	Contract Capacity, Average Monthly Peak Demand and Energy On-off Peak Percentages of the Test Companies - 1976	160
15	An Analysis of the Impact of Old vs. New Rate Structure on the Annual Billing Cost of Test Companies	161
16	Annual Increase in Billing Costs by Components Due to New Rates	163
17	Percentage Increase in Annual Billing Costs by Components Due to New Rates and the Percentages of the Contract Capacity Utilized in 1976	164
18	Summary of the Percentage Increase in Annual Billing Costs of Demand and Energy (kWh) According to Percentage On-off Periods	165

TABLES (Cont'd)

Chapter IV (Cont'd)

<u>Number</u>		<u>Page</u>
19	Relationship Between the Percent of Contract Capacity Utilized and the Percent Increase in Annual Billing Cost Attributable to Demand (kW)	166
20	Analysis of Estimated and Actual Electric Dollar Savings and a Relative Comparison Between Old and New Rates	167
21	Demand Rates and Load Management Investments	168

CHAPTER V

<u>Number</u>		
1	Estimated Annual Megawatt Reduction on the Detroit Edison System Due to Energy Management	171
2	Relative Percentages of Energy Consumed by Industry in the Nation and in Michigan	175
3	Historical Annual Load Factors of the Detroit Edison System	183
4	Analysis of Customer Load Characteristics on System Peak Days - 1974	184
5	Average Inter-class Diversity Factors of Detroit Edison Customers, 1974 - On the Day of System Peak	186
6	Historical Percentage Contributions to the Peak and Load Factors of Industrial Class	187

CHARTS

Chapter III

<u>Number</u>		<u>Page</u>
I	Annual Energy Consumption by Btu's of 19 Test Companies for 1975	49
II	Percentage Distribution of Total Billing Cost of Energy Paid by Test Companies in 1975	53
III	Summary of Areas for Net Load Reduction	59
IV	Distribution of the Estimated Annual Percentage Dollar Savings Due to Load Management, Test Companies, 1976	78

Chapter IV

<u>Number</u>		
I	A Comparison Between the Estimated and Actual Net Percentage Reduction in Peak Demand of the Test Companies Due to Load Management and the Percentage Reduction Due to Specific Areas	143
II	Summary of Estimated and Actual Net kWh Reductions by Area Due to Load Management	151

THE DETROIT EDISON COMPANY
MANAGEMENT EFFICIENCY REVIEW

PHASE I REPORT

ERRATA

Page II-8 - The underlined sentence at the beginning of paragraph two now reads, in part: "These could be further opportunities...etc.". It should read: "There could be further opportunities...etc.".

Page II-10 - The third dash point on the page reads:

"There is a need to assess the effectiveness of key decision making particularly including processes and the interaction among them, the range of issues relating to...etc.".

This should read:

"There is a need to assess the effectiveness of key decision making processes and the interactions among them, particularly including the range of issues relating to...etc.".

EXECUTIVE SUMMARY

The study entitled, "Project to Demonstrate Potential Energy Savings From Industrial Customers", was conducted by the Michigan Public Service Commission (MPSC) in cooperation with The Detroit Edison Company under a cooperative agreement with the Federal Energy Administration (FEA).

PURPOSE

The purpose of the study was to determine the full potential for electric load management with respect to the industrial sector by adopting direct load management techniques; and to highlight certain options available to regulatory authorities and individual utilities to conserve energy. By conducting a demonstration project on a representative sample of primary industrial customers, information could be obtained on the potential impact of direct load management methods and other end-use conservation programs on a system-wide basis or multi system-wide basis.

The overall objective of the study was to explore the full potential for reducing on-peak demand, shifting the electrical usage patterns from on-peak to off-peak periods, and to develop methods to utilize electrical energy more efficiently for the industrial sector.

BACKGROUND

To a large extent, the demonstration project was an outgrowth of the 1974 oil embargo and other factors such as deteriorating energy supplies coupled with mounting demand for energy which contributed to what is generally referred to as our present energy crisis. The accelerating cost of fuel oil, rising interest rates and the worsening state of the economy made a profound impact on Michigan. The State's utilities were especially hard hit. In particular, because of the consequent capital shortage, a number of capacity expansion programs of the utility companies, which were designed to meet the peak demands as well as the growing demand for power, had to be curtailed, postponed, or cancelled altogether. Thus, the utilities and the regulatory authority were faced with the dilemma as how to utilize the existing generating facilities more efficiently without detrimental effects to the industrial economy of the State. The primary goal was to investigate the means and methods for reducing on-peak usage, shifting the on-peak demand to off-peak periods, and utilizing the electrical energy more efficiently in general, and in particular, within the industrial sector.

For the nation as a whole, in 1974, on the average, "less than one-half of installed electrical power generating capacity was utilized. To meet peak loads, more than twice the capacity necessary to meet average load had to be available to satisfy the peak demand requirements."¹ Thus,

¹Frank G. Zarb; Keynote address, proceedings of the Conference on the Challenge of Load Management - A Convergence of Diverse Interests, page 2.

it is the annual system peak load that has a greater impact on the installed generating capacity.

Another facet of the problem involves the historical pattern of load growth. Nationwide, during the period 1969-74, peak load grew at an average annual rate of seven percent while aggregate sales rose an average of five percent per year. The consequences of this kind of growth was a deterioration in the load factor which fell from 58 percent in 1969 to 54 percent in 1974. One important effect of this growth pattern has been to place increasing pressure on utilities for costly plant capacity expansion. Also, the decline in load factors has had a negative impact on the energy and capacity elements within the cost structure for electric generation.

RATIONALE FOR LOAD MANAGEMENT

Load management is defined as any deliberate reshaping of a utility's load curve that could be achieved through voluntary or involuntary actions by the affected customers. There are three alternative approaches to load management: (1) Direct Load Management Methods, (2) Indirect Load Management Methods, (3) Conservation Methods. These three methods are not necessarily mutually exclusive. The choice depends on the respective customer load profile and the extent to which the customers can profitably implement these methods.

Direct load management involves methods by which the utility obtains direct control over certain portions of customer loads. These methods include: time switches, load limiting devices, central demand control systems, etc. Successful implementation of direct load management methods by the utility customers implies that customers are prepared, either to shed certain portions of their peak loads or defer some of their loads to off-peak times, in order to utilize lower off-peak rates offered by the utility. In other words, once a customer has agreed to allow the service to certain loads to be interrupted, the utility gains control to manage those loads, either cycling these to diversify peak demand or deferring these to off-peak periods. This could lead to: (1) improved load factors for the utility and its customers, (2) reduced operating cost of peaking units and effective utilization of base units, (3) deferment of future capacity additions, and (4) monetary savings to the customers.

Indirect load management methods, on the other hand, would allow the customer, rather than the utility, to control loads. The indirect methods include: (1) rate mechanisms (e.g. time-of-day rates), (2) warning devices, (3) demand controllers that would allow the customers to alter their load patterns, (4) customer storage devices, etc. These methods are expected to induce the customers to reduce or shift demand away from system-peak, thus leaving to the individual customer, control over the extent to which any time the customer load at system-peak is reduced. However, the magnitude of customer response depends on the type of rate design in effect and the expected monetary savings. But, the utility cannot know in advance the aggregate amount of reduction in demand and hence, it would be difficult for the servicing utility to accurately predict the loads and to manage them more effectively.

The third approach, end-use conservation, offers a wide variety of methods for reducing peak period consumption of electricity. These include: efficient use of equipment (e.g. air conditioners), reduction of on-peak energy use through better insulation and better management of energy. The potential benefits of all these three methods would be: (1) improved system load factors, (2) monetary savings to customers, and (3) efficient use of resources.

Industrial demand for electricity fluctuates on an hourly and daily basis. Further, experience of the electric utilities indicates that industrial sector peak demands are coincident with the system peak loads. Current interest in load management stems from the fact that if the coincident peak demands of the customers can be deferred or shifted to off-peak periods of the system, the system's generating facilities can be utilized more efficiently or the same amount of energy could be supplied with fewer facilities. The resulting savings are of two types; namely, a saving of fixed costs associated with generating facilities which need not have to be installed, and a saving in operating costs (primarily fuel used in generation) which would result by using more efficient generation equipment. Of course, these potential savings must be balanced against any added capital investments necessary to purchase load management control systems, the cost of installing the equipment and the related costs of operation and maintenance.

METHODOLOGY

The methodology developed in the study relates only to two of the three alternative methods available for load management; namely, Direct Load Management and End-use Conservation.

Detailed methodologies with regard to: (1) Sample Selection, (2) Survey Procedures, and (3) Economic Feasibility of Load Management Investments, are presented in Chapter II of this report. A brief summary of these is provided below:

Sample Selection: Prior to Sample Selection, the population of primary manufacturing customers of Detroit Edison was subjected to a thorough analysis to identify the detailed characteristics in regard to the historical electricity consumption patterns - hourly, daily, and seasonal coincident peak demands, etc., of the customer classes. Based on the results of this analysis, a detailed sample selection criteria were developed. The entire population of industrial manufacturing customers was stratified according to the Standard Industrial Classification codes (SIC). It was decided that only those primary manufacturing industrial customers who have had primary monthly billing demands not exceeding 6,000 kW, and representing the several SIC codes, were to be considered for the purpose of Sample Selection. Further, the SIC groups having a total of 20 members or less were excluded for consideration.

The SIC codes finally selected for sample selection were: SIC 20 - Food Products, SIC 26 - Paper and Allied Products, SIC 27 - Printing and

Publishing, SIC 28 - Chemicals and Allied Products, SIC 30 - Rubber and Miscellaneous Plastic Products, SIC 32 - Machinery (except electrical), and SIC 37 - Transportation. A representative sample of 40 was selected from an effective population of 559 primary industrial customers, representing the aforementioned ten SIC groups using a stratified random sampling procedure, with the restriction that there must be at least two sample members representing each of the selected SIC groups (strata). The selected sample of 40 was further divided into two groups of equal size. One group of 20 sample customers was selected as the test group; and the remaining 20 sample members selected served as the control group. The test group of industrial customers was provided with technical and financial assistance. The test and control group customers, so selected, maintained homogeneous characteristics in regard to: (1) nature, type, and mode of manufacturing operations, (2) employment levels, (3) type of products produced, (4) coincident demand patterns, and (5) physical characteristics of the buildings, etc.

Survey Procedures: Several schedules and procedures were developed to conduct the in-depth, on-site, technical surveys of the test group customers, to identify the potential areas for load management, to study how efficiently the energy was being utilized, and to determine the potential savings by adopting load management techniques. The final results of these investigations were incorporated into the individual proposal recommendations of each of the test group customers. These individual proposal recommendations are available from the MPSC, Office of Special Studies, but are not presented in this report. The entire analysis of the proposals (analysis of technical surveys, economic analysis, historical data analysis and individual demand profiles) were reviewed, verified and documented by the technical staff of both the Michigan Public Service Commission and The Detroit Edison Company.

Economic Analysis: To determine the cost-effectiveness of load management investments, the following criteria were used: (1) a ten-year life for load management equipment, (2) a two-year cash-flow period, (3) 50 percent corporate tax rate, (4) ten percent investment tax credit, (5) eight percent discount rate to arrive at the present value, (6) ten percent return on investment, (7) a 24-month payback for 100 percent investment, and (8) first year write-off of the installation costs. The 24-month payback period was used as the test group customers expressed that they must get back this investment on or before 24 months. If the investment did not meet the 24-month payback criterion, the amount of investment subsidy needed to meet this criterion was determined. The investment subsidy is that amount of money necessary to bring a deficient cash-flow rate up to 100 percent over two years.

CUSTOMER PARTICIPATION

The test group customers were highly receptive to our proposal recommendations. Sixteen out of a total of 20 test customers actually participated in the experiment by implementing a major portion of all our proposal recommendations. Some of the test group customers (SIC 33 and 35) have implemented beyond our recommendations.

ADMINISTRATION OF THE TEST

It was pointed out above that 16 of the total 20 test customers have implemented the proposal recommendations in varying degrees. Some customers have carried out the recommendations earlier than others, as such, the test period varied between six to 11 months. The average test period of the customers was about eight months. The test period commenced in August, 1976, and ended on June 30, 1977. The project was partially funded by the Federal Energy Administration which provided \$200,000 augmented by Michigan's contribution of well over \$89,000 in staff time, and by The Detroit Edison Company which expended approximately \$40,000 in staff time, equipment and data collection. Direct supervision of the project was the responsibility of a project management team consisting of staff members of the MPSC and Detroit Edison. Two staff members, one from MPSC and one from Detroit Edison, were assigned full time to be project coordinators. The project coordinator representing The Detroit Edison Company was the main information source for the test customers. Overall, the policy direction was provided by a project direction group consisting of the heads of the state agencies, senior executives of Detroit Edison and an independent (not one of the test customers) industrial customer representative.

Financial Assistance to the Test Customers: Of \$200,000 FEA provided, \$100,000 was intended for test customers to purchase load management equipment. The financial assistance to each customer was limited to \$5,000 towards load management items only. However, a maximum of \$10,000 was allowed under special circumstances and if the monies were available. The load management equipment included timers, demand control systems, and other load limiting equipment. Proposal items such as lighting systems, insulation, ceiling fans, painting, etc., were not eligible for financial assistance. The estimated total amount eligible for load management was about \$50,000 out of a total \$100,000. Only two out of the 16 test customers who participated in the test initially requested reimbursement. FEA approved a sum of \$10,000 to a customer representing SIC 32 - Glass Products, to purchase and install a demand monitoring system, but subsequently, the customer declined to accept the offer due to excessive cost of installing the equipment. The second test customer, representing SIC 33 - Primary Metals, accepted the FEA offer of \$8,235 to purchase and install a demand monitoring system. The remaining test customers did not request monies.

Control Customers: The control group customers of the test who had similar and homogeneous characteristics as the test group customers were considered as standard for the purpose of the test. The control customers, by design, were not aware that they were selected for the study. Only the project staff knew about them. Energy audit survey was not conducted, nor was financial assistance provided. However, Survey Form 1 was mailed to these customers requesting them to complete the form and to mail it back to Detroit Edison. Detroit Edison provided historical electrical consumption data along with electrical consumption data during the test period. The response from the control customers in regard to the completion of Survey Form 1 was meagre. Six out of 20 control customers completed survey forms and mailed them to Detroit Edison project staff. Several request letters were sent but no answer was received from the remaining customers. Even those six customers who completed the Survey

Form 1 did not answer all the questions. The historical data submitted on Survey Form 1 were not even internally consistent and, as such, were not incorporated in the report.

Additional Concern of the Test: It was pointed out at the beginning, the objective of this study was to explore the potential possibilities for electric load management with reference to a sample of 20 test group customers in particular and the overall industrial sector in the short run. It was not the objective of the study to review the impact of the customer response with respect to any set of predesigned rates; on the other hand, the prime concern was to measure the impact and the feasibility of direct load management techniques and other end-use conservation measures.

LIMITATIONS OF THE STUDY

1. Direct load management (electric approach) was the prime concern of the study. The study did not attempt to measure the potential impact of alternative rate structures.
2. The study did not estimate the probable savings that could be attributable to other types of energy - natural gas, oils, etc. To the extent natural gas savings have been mentioned in the analysis, they refer to those savings directly associated with the changes in electric energy utilization, conservation or load management.
3. The SIC groups (strata) having less than 20 primary industrial customers were deleted, and the industrial customers (manufacturing) having monthly billing demands greater than 6,000 kW were not considered for inclusion in the sample, e.g. ordnance and accessories, textiles, lumber and wood products, furniture, petroleum refining, electrical machinery.
4. Financial assistance to the test group customers was limited only to those equipment items (e.g. timing devices, demand control systems, etc.) which would have a direct impact on load management; and those items which would have an indirect impact on load management were not eligible for financial assistance (e.g. lighting, insulation, painting).
5. The cost-effectiveness of load management capital investments was assessed using a 24-month payback criteria, instead of the productive lifetime of the equipment. This was due to the fact that the test group customers required investments to pay back on or before 24-month period.
6. Voluntary participation, as opposed to mandatory participation, affected the prompt implementation of a portion of the proposed recommendations and narrowed the overall scope of the project.

7. Labor strikes, unusual weather conditions that prevailed during the surveys, and coordination between customer managements, Detroit Edison staff and MPSC staff impeded the timely progress of the study.

MAJOR FINDINGS AND GENERAL CONCLUSIONS

Major Findings

1. Peak Demand Reduction (kW): On the average, the test customers reduced about six percent of their monthly peak demand by implementing load management techniques. This was in contrast to the estimated maximum reduction of 7.4 percent if all the recommendations had been implemented. Of the six percent actual peak demand reduction, about three percent reduction occurred in lighting, two percent reduction in the miscellaneous category (water heaters, battery chargers, electric forklifts, vent pumps, computers, pollution equipment, etc.), and about one percent reduction was attributable to processing. (See Table 5, page 56, Table 2, page 138; and Table 6, page 142.)
2. Energy Reduction (kWh): The test customers on the average were able to reduce their energy consumption by about four percent due to load management. This result was very close to the estimated energy reduction. Of the total 3.74 percent kWh reduction, about 3.16 (84 percent) occurred in the lighting area, about .43 (12 percent) reduction was in the miscellaneous category, approximately .17 (five percent) reduction was realized in processing, and an increase of .02 (less than one percent) occurred in the HVAC area.
3. Annual Dollar Savings of Test Customers (Electric): The average actual dollar savings of the 16 test customers who implemented load management techniques was approximately \$6,000 compared to the estimated average annual dollar savings of \$6,800 based on 18 customers. Of these savings, about 65 percent was due to peak demand (kW) reduction and the remaining 35 percent was due to energy (kWh) reduction. (See Table 16, page 75; and Table 11, page 153.)
4. Average Load and Power Factors of the Test and Control Companies: Five of the 16 participant test group customers who implemented 70-100 percent of the proposal recommendations have increased their average load factors by 2.2 percent during the test period as compared to their average load factors of the pre-test period. The average load factors of the corresponding control companies have declined approximately four percent compared to the pre-test period load factors. The same five test group customers reduced their peak demand by about 10 percent on the average during the test period. In fact, one test customer, who installed the demand monitor control system, improved his load factor by seven percent during the test period.

Further, the average load factors of seven out of 16 participated customers who implemented about 40-70 percent of the proposal recommendations have been improved by about 1.1 percent. The load factors of the corresponding control customers declined by about 1.4 percent on the average during the test period. The above-mentioned seven test group customers were able to reduce their peak demand by approximately 5.8 percent on the average. The average load factors of four of 16 participant customers who implemented about 10-40 percent of the recommendations, declined by about one percent; whereas, the average load factors of the corresponding control customers declined by 15.5 percent. The average percentage peak demand reduction of these customers was approximately 2.5 percent. The average load factors of four of the test group customers who did not implement any of the proposal recommendations declined by 4.6 percent compared to their pre-test period load factors. Thus, load management has had a significant impact on improving the load factors of the sample test group customers who implemented the recommendations. (See Table 9, page 149, and Table 13, page 157.)

5. The Annual Billing Cost of Energy as Percent of Sales Revenue: The average annual billing cost of energy was found to be a small percentage of the total sales revenues of the test group customers. The average billing cost was approximately 3.36 percent of the average total sales revenue for 15 of the 20 test companies for which data were available for 1975. However, the proportions of energy costs with respect to the individual sales revenues varied between a minimum of 1.5 percent to a maximum of eight percent. (See Table 1, page 46.)
6. Type and Mix of Energy Consumed by Test Companies in 1975: Of the total Btu's consumed by the test companies, on the average 20 percent was electric, 71 percent was natural gas, and nine percent was oils and miscellaneous forms of energy. It was found that the annual gas consumption was 3.5 times that of the annual Btu consumption of electric energy. (See Tables 1 and 2, pages 46 and 47.)
7. The Distribution of Annual Billing Cost by Type of Energy Consumed in 1975: The average percentage distribution of the annual billing costs of the companies surveyed showed that 51 percent of the cost was electric, 39 percent of the cost was natural gas, and 10 percent was oils and miscellaneous forms of energy.

A comparison with the previous finding reveals that these companies paid over 50 percent of the annual billing cost for using 20 percent of their energy in the form of electricity during 1975. (See Table 3, page 51.)
8. Possibility of Shifting from On-peak to Off-peak: Fifteen out of a total of 20 test customers were able to shift their energy (kWh) consumption from on-peak to off-peak period during the test period

as compared to the pre-test period. On the average, both test and control customers were able to shift their on-peak energy consumption to off-peak period by about one percent. But, the individual percentage peak reductions of a large majority of the test customers were higher, compared to the corresponding control customers. It is evident that there exists a possibility to shift (reduce) on-peak energy consumption to the off-peak period. However, the possibility for peak kWh or peak day shifts depends on the individual consumption patterns, mode of operation, process type, labor force, rate incentives, etc. The SIC groups which experienced the largest percentage shift from on-peak to off-peak were: Primary Metals (four percent) and Machinery (four percent). Food Products and Transportation shifted their on-peak energy to off-peak by about three percent on the average. These were followed by Transportation - two percent; Glass Products, Rubber Products, Printing & Publishing were able to shift by about one percent each. (See Table 12, page 156.)

9. Economic Feasibility of Load Management Investment: The economic feasibility of the capital investments needed for load management showed that seven of the 19 companies met the criterion of a 24-month payback and the remaining 12 companies required subsidies ranging from 13 percent to over 100 percent of capital investment to meet the 24-month criterion. If a 36-month payback criterion were selected, then 10 out of 19 companies would meet the 36-month standard. The above estimates were based on the assumption of the 1976 financial market standards (10 percent average rate of return on investment, 100 percent cash-flow rate - return on capital), and 1976 electric and gas rates applicable to primary industrial customers. It should be noted that the investments used to arrive at the payback periods did not include the cost of the technical services provided by MPSC and Detroit Edison staff. (See Table 19, page 82 .)
10. Systemwide (Detroit Edison) Savings: In the short run, by extrapolating the estimated savings of the sample test customers, it is expected that there could be about 31 MW savings on the Detroit Edison system annually due to load management. However, a part of these savings are of one-time nature (e.g. interlocking devices). (See Table 1 - page 171.)
11. Additional Findings:
 - a. Industry is very concerned about the costs of electric power along with the costs of other forms of energy. As these costs continue to increase, industrial customers will give an even greater emphasis to the development of methods to reduce these costs. However, the overriding concern of industry is a reliable and adequate source of power.

- b. Energy costs are too low compared to the cost of labor, raw material, and capital to motivate the industries to save energy or to manage industrial operations efficiently.
- c. Many small and medium size industries do not have sufficient resources of their own, capital and technical know-how, to implement a comprehensive energy management program.
- d. Companies have investment priorities other than investments in load management techniques.
- e. Industrial operations are not sensitive to temperature conditions.
- f. As customers become more aware of the potential energy savings available to them, their attitudes towards energy management were favorable in implementing the energy saving techniques.

GENERAL CONCLUSIONS

The findings of the study reveal that load management is a viable strategy. Further, adoption of load management techniques by the industrial sector would be expected to save about 31 MW on the Detroit Edison system alone. In other words, the installed capacity that can be deferred in the short run would be approximately \$22 million. The estimated savings would imply reduced consumption of high-cost or restricted fuels which would in turn lead to reduced average cost to the existing customers and improved load factors to the system.

Small and medium type of manufacturing industries do not have, at the present time, effective energy management programs although these industrial customers were aware of the energy shortages and have been attempting to reduce their energy consumption to the extent possible. As a result of this study, a significant number of the test customers have implemented the proposal recommendations and many of the sample customers developed their own ongoing energy management programs and have earmarked substantial amounts of money in their budgets for energy management. Overall, the response from the test customers was significant.

The analysis of load management investments of the study showed that the cost of labor was approximately 50 percent of the total investment. If the firm possesses in-house capabilities to install and to implement the day-to-day monitoring of the equipment, the load management investments would probably produce attractive payback periods.

The historical energy (electric, gas, oils) consumption profiles of the test customers revealed that natural gas Btu's represented about 70 percent of the total Btu consumptions. The plant in-depth technical surveys indicated that there exists a potential for natural gas savings and the possibilities for conversion from other types (gas, oils) of energy to electricity exists in all plants. A comprehensive energy conservation program for the industry should embrace all facets of energy

consumption. This unified approach will highlight the probable options available for the industry, utilities and the regulatory authorities. Industry needs adequate lead time (two-to-three years) for adopting the new techniques, conservation measures, and for implementing the load management techniques which are cost-effective. Proper signals should be provided to the customers by the utilities and the commissions in regard to the anticipated changes and with respect to supplies of energy and the rate mechanisms. A considerable number of educational campaigns and training programs should precede the introduction of innovative energy-efficient systems. Ultimate success of load management depends upon the type and characteristics of the industry and the mode of operation. The effectiveness of load management is contingent upon several factors such as (1) types of energy used, (2) the proportion of different kinds of energy used, (3) efficiency of equipment, (4) geographic location of the plant, (5) type and quality of buildings and work force, (6) percentage cost of energy in the operating budget compared to the costs of labor and material, the annual dollar savings expected by implementing the load management techniques and the attendant payback periods of load management capital investments, (7) the relative costs of electricity, natural gas and other kinds of energy, (8) availability of capital at low interest rates, (9) tax write-offs and subsidies, (10) readily available and suitable load management technology at reasonable cost, (11) day-to-day monitoring and periodic energy audits of the companies, and finally (12) the firm commitment of the top level management towards effective energy management.

CHAPTER I

DETAILED SUMMARY OUTLINE

- A. Introduction
- B. Specific Project Goals
- C. Project Methodology and Scope
- D. Sample Selection Criteria
- E. Relative Efficiency of Sample Design
- F. Surveys
- G. Economic Analysis
- H. Customer Acceptance
- I. Implementation
- J. Major Electrical Uses
- K. Rationale for Using ANSI Guidelines
- L. Customer Participation
- M. Administration of the Test
- N. Financial Assistance
- O. Control Customers
- P. Additional Concerns of the Test

DETAILED SUMMARY

A. Introduction

During 1974, electric utilities throughout the United States significantly reduced planned construction. Almost 50 percent of the proposed plants were either indefinitely delayed or permanently cancelled. Both the increasing scarcity of fossil fuels and deteriorating economic conditions contributed to these cutbacks. Users of electricity were encouraged to significantly reduce their consumption of electric energy in order to reduce consumption of fossil fuels. In addition, deteriorating economic conditions combined with high interest rates, high fuel prices, inflation and regulatory lag adversely affected the financial viability of electric utilities, thereby limiting their ability to attract necessary capital to finance the required construction programs.

Few states have experienced this problem as seriously as Michigan. The Detroit Edison Company and Consumers Power Company, which together supply over 90 percent of Michigan's generating capacity, drastically curtailed their construction programs in 1974. Detroit Edison, moreover, virtually stopped all ongoing construction programs during that critical year.

With long lead times needed to build electric generating plants (7-12 years, depending on the type of generating facility) and little or no major increases in utility construction programs pending, the ability of utilities to respond quickly to severe shortages in electric energy has been seriously impaired. It follows that any substantial shortages in electric power availability could create significant hardships for electric consumers in Michigan.

Another facet of the problem involves the particular pattern of load growth. Nationwide, during the period 1969-74, peak-load grew at an average annual rate of seven percent while aggregate sales rose an average of five percent per year. The consequence of this kind of growth was a deterioration in the net load factor, which fell from 58 percent in 1969 to 54 percent in 1974. Furthermore, though total electricity sold in 1974 declined slightly from the previous year, in contrast, peak load grew by almost five percent.

One important effect of this growth pattern has been to place increasing pressure on utilities for costly plant capacity expansion. Also, the decline in load factor has had a negative impact on the energy and capacity elements within the cost structure for electric generation.

The dramatic rise in peak load demand prompted two experts in the field to state that:

"To a considerable extent, the fundamental forces behind the rapid escalation in the costs of supplying electricity are beyond control. But judicious management of load growth offers an important opportunity to reduce some of the pressures on electric costs."¹

¹Joskow, Jules, and William B. Shaw, "Load Management Potential - An Overview" in Proceedings of the Conference on "The Challenge of Load Management: A Convergence of Diverse Interests", June 11-12, 1975, sponsored by Office of Utilities Programs, Federal Energy Administration, pp. 7-8.

Energy planners have suggested several alternative methods for addressing these problems. These alternatives fall into three broad categories:

- . Load Curtailment (reduction in the use of energy)
 - . Load Management (shifting of usage patterns)
 - . Price Signals (peak load pricing, time-of-day rates, etc.)
1. Load Curtailment - Load curtailment involves the actual reduction in the use of energy through several means including the reduction of lighting and temperature, controlling equipment usage and using more efficient electric appliances and equipment. These methods have the dual benefit of reducing generating requirements, and also decreasing the consumption of fossil fuels needed to generate electricity.
 2. Load Management - Load management is directed mainly at reducing peak generating capacity requirements. In essence, users of electricity are encouraged to shift the times they use electricity from peak usage periods to off-peak periods. If such shifting occurs, the generating capacity requirements may be reduced. Some fuel savings may also result since more efficient generating equipment is used to provide base load requirements. Incentives to encourage consumers to shift their usage of electricity to off-peak times usually include lower rates charged to consumers for usage during off-peak vs. on-peak periods.
 3. Price Signals - These approaches represent an attempt to reflect in rates the cost responsibility of customers who purchase electric power during peak periods. Such allocative rate mechanisms are used to support the view that the utilities' load factor can be improved by discouraging peak power purchases and encouraging off-peak consumption. This, it is argued, will result in less peak demands and hence less need for increased facilities and more efficient use of existing facilities.

Unfortunately, very little information was available to determine the potential of either load curtailment, load management, time-of-day, or peak-load pricing methods as a partial solution to the energy problem. Regulatory commissions, state energy offices, electric utilities, research institutions and federal agencies have begun major investigations into these methods to assist energy planners and policymakers in determining appropriate solutions to these problems.

With similar concerns in mind, the Federal Energy Administration's Office of Energy Conservation and Environment began, in 1975, to enter into "Cooperative Agreements" with agencies of state and/or local governments to support "demand management" projects for electric utilities. The basic purpose of these demonstration projects was to "highlight certain options available to regulatory authorities and individual utilities to conserve energy." By instituting such demonstration projects on a representative sample

of electric consumers, information could be obtained on the potential impact of such programs on a system-wide or multi system-wide basis.

The Michigan Public Service Commission (MPSC) has been active in exploring potential energy conservation programs. Detroit Edison also has been involved for some time in developing load curtailment and load management programs in order to increase the capability for providing adequate generating requirements in its service area. This report, which embodies the combined efforts of the MPSC and Detroit Edison, represents one of the few attempts made in the nation to determine the problems and potential of an energy management program for the industrial sector.

B. Specific Project Goals

For the most part, energy studies concerned with reducing or shifting consumer usage patterns have been primarily concerned with determining the kind and magnitude of incentives which would achieve those objectives. Very little else has been done to identify the specific areas and methods in which users may be encouraged to shift energy consumption patterns.

Most studies in this area have focused on residential consumers even though these consumers present a smaller potential for load management impact relative to industrial customers. For example, in 1974, in the Detroit Edison service area, residential consumption represented about 30 percent of the total electric energy consumption and about 24 percent of peak demand generating requirements. The industrial customers, however, accounted for 50 percent and 36 percent respectively, in these categories.

It was for this reason that the MPSC and Detroit Edison designed the demonstration project aimed at determining the potential for reducing peak usage and shifting usage patterns for the industrial sector. The objective was to be achieved by providing technical and engineering assistance and financing small capital investments for participating industrial customers. It is expected that this project would assist participating industrial customers in:

- . Determining potential areas for more efficiently utilizing electricity.
- . Determining potential changes in operations to enable some load shifting (shaping) to be accomplished.
- . Developing a program to implement the recommendations.
- . Monitoring and assisting in implementation of energy management programs and/or facilities and equipment improvements.
- . Measuring the results achieved.

C. Project Methodology and Scope

A summary outline of the basic steps that were followed in conducting the load management experiment is given below. The technical aspects of the methodology and scope of the study have been discussed in Chapter II.

To investigate the potential energy savings, a sample of 40 primary industrial customers of the Detroit Edison Company was selected using a stratified random sampling procedure. This sample was further divided into two groups of equal size. One group functioned as the test group customers* and the other as the control group customers. Prior to the selection of the sample primary industrial customers, a detailed sample selection criteria (presented in Chapter II) were developed. The sample primary industrial customers were derived from 10 Standard Industrial Classification codes (SIC).

Project Outline

- . Select two groups of 20 industrial customers to participate in the demonstration project.
 - ...Test Group - Provide additional energy management assistance.
 - ...Control Group - Unassisted above present level.
- . Document recent electric energy and demand usage patterns for both test and control groups.
- . Survey test group customers and develop specific energy management programs.
 - ...Analyze major system electrical usage patterns, and identify by other energy consumption patterns.
 - ...Identify areas of inefficient electrical consumption.
 - ...Determine production processes which could be shifted to off-peak utilization.
 - ...Determine environmental conditioning changes which may result in better electrical utilization (lighting, heating, cooling, ventilation, etc.).
 - ...Identify areas where small capital improvements could decrease energy consumption and/or shift peak usage.
- . Determine required equipment to achieve the objective of test group customers.
- . Assist test group companies in implementing recommended improvements in operations.
- . Perform data collection on both the test group and control group during the pilot measurement period and compare with present energy usage.
- . Analyze data from various programs relative to the plan.

* Each customer was given assurance that confidentiality would be maintained.

- . Evaluate results:
 - ...Pre and post energy management program for test group.
 - Overall consumption
 - Peak usage
 - ...Test Group vs. Control Group
 - Overall consumption
 - Peak usage
 - ...Sample and statistical considerations
 - ...Theoretical impact on utility load and capacity factors if the program were implemented on a system-wide basis.
- . Identify additional opportunities for long-term energy management improvements.
- . Prepare recommendations and disseminate reports.

D. Sample Selection Criteria

To investigate the potential for electric load management, a representative sample of 40 primary industrial customers of The Detroit Edison Company was selected using a stratified random sampling procedure. The sampled industrial customers were drawn from the following Standard Industrial Classification (SIC) codes:

. Food Products (SIC 20)	Glass Products (SIC 32)
. Paper Products (SIC 26)	Primary Metals (SIC 33)
. Printing & Publishing (SIC 27)	Fabricated Metals (SIC 34)
. Chemicals (SIC 28)	Machinery (SIC 35)
. Rubber Products (SIC 30)	Transportation (SIC 37)

Before selecting the sample, detailed sample selection criteria were developed and a detailed outline is presented in Chapter II of this report. A summary of the sample selection criteria is given below:

1. The total population of 672 primary industrial customers of Detroit Edison was stratified according to their respective industry groups (SIC codes).
2. The SIC groups having less than 20 industrial customers were not considered for the purpose of sample selection. These SIC codes include: Mining, Ordnance and Accessories, Textiles, Lumber and Wood Products, Furniture, Petroleum Refining, Electrical Machinery, Precision Instruments, and Miscellaneous Manufacturing. The total number of industrial customers representing the above SIC groups was 57 out of the possible 672 primary industrial customers. The basic reasons for not considering the above SIC codes were: some of these industrial customers were extremely large in size, e.g., Petroleum Refining, Mining, etc.; as such, it would have taken

considerable time and effort to conduct an energy audit. Further, these SIC codes did not have comparable members within the group for the purpose of selecting at least one test group customer and one control customer having similar physical and operating characteristics.

3. Only primary manufacturing industrial customers having a monthly billing demand not exceeding 6,000 kw were considered to be included in a sample of 40. The reasons for limiting the sample to 6,000 kw were that these customers generally were small and of medium size and represented approximately 90 percent of the total primary industrial (manufacturing) customers of The Detroit Edison Company. Further, the remaining 10 percent of the population of industrial customers were of considerably larger size and have had some kind of energy management program of their own. In addition, industries such as Cement, Steel, major Transportation, etc., have manpower as well as financial resources of their own. Further, the available project monies to finance the load management equipment was limited to a maximum of \$5,000 for each of the eligible test customers selected.
4. The selected sample of 40 was further divided into two groups of equal size. One group of 20 sample customers served as the control group. The remaining 20 sample customers served as the test group. The test group customers so selected would receive technical and financial assistance whereas the control group customers by design were treated as confidential and would not receive either technical or financial assistance. In other words, the control customers were not aware that they were considered as control customers. The control customers were considered as standard against which the test group customers were compared so far as the experimental results were concerned.
5. The sample of test and control companies that were selected maintained, as far as possible, homogeneous characteristics by size and mode of operations.
 - a. Had as far as possible the same number of work shifts
 - b. Had approximately similar technical processes, product lines, employment levels, and physical operating characteristics within the plant.
6. Prior to inclusion of the industrial customers into the sample, a thorough analysis of historical data relating to hourly billing demand covering a period of three years (1973, 1974, 1975) was conducted to discover the demand patterns, customer coincident peak-load characteristics with the system's peak and seasonal variations in demand.
7. Demand profiles of each of the selected test and control customers were drawn for 1973, 1974 and 1975, and comparisons with the system load curves were made to discover the coincidence peaks with the system.

E. Relative Efficiency of the Sample Design

Using the aforementioned sample selection criteria, it was found that the relative efficiency of the experimental test group customers was 232 percent more efficient compared to a proportional sample allocation method and to an optimum allocation method of sample selection. The experimental design required that there should be one-to-one correspondence between the sample test and control group customers. The selected total sample of 40 was approximately seven percent of a total of 559 available primary manufacturing industrial customers of Detroit Edison Company having monthly primary demand less than 6,000 kW.

The table below provides the allocation of 40 companies to different SIC codes or strata:

Table 1
Allocation of Sample Test and Control Customers

<u>SIC Strata</u>	<u>Stratum Size</u>	<u>Allocation of Sample Test & Control Companies</u>		<u>Sample Size</u>
		<u>Test</u>	<u>Control</u>	
20 Food Products	52	1	1	2
26 Paper & Allied Products	21	1	1	2
27 Printing & Publishing	21	1	1	2
28 Chemicals & Allied Products	26	1	1	2
30 Rubber & Misc. Plastic Products	52	1	1	2
32 Stone & Glass	21	1	1	2
33 Primary Metals	80	2	2	4
34 Fabricated Metals	104	4	4	8
35 Machinery (except electrical)	101	4	4	8
37 Transportation	<u>81</u>	<u>4</u>	<u>4</u>	<u>8</u>
Totals	559*	20	20	40

*Total primary industrial customers: 672

Less the industrial customers representing Mining, Ordnance and Accessories, Textiles, Lumber, etc.: 57

Less the industrial customers having the primary billing demand exceeding 6,000 kW: 56

Total available population of primary manufacturing industrial customers for sample selection: 559

F. Surveys

1. **Energy Survey of Test Customer Facilities:** There exists many more energy saving opportunities in a facility than might appear at first glance. A good way to identify them begins with an overall look at the entire process - manufacturing and non-manufacturing. A well-designed energy survey often reveals which areas offer the most attractive economic incentives for savings. Efforts must be directed first, toward high payoff non-capital requirement projects; second, toward limited capital requirement projects, and, third, toward capital-intensive projects. This requires a complete knowledge of gross energy consumption by (1) plant equipment utilized in the manufacturing of final products, and (2) the transmission systems that carry energy to the equipment. Thus, understanding relative energy consumption by equipment type is vital in any effort to focus on opportunities for end-use conservation.
2. **Electric Load Management Survey:** The basic purpose in conducting an in-depth on-site energy survey was to identify the potential areas for electric load management, the extent to which different types of energy were being utilized, and the areas of inefficient utilization of energy.

The major goal was not only to document major system processes which could be shifted to off-peak utilization periods, and to estimate the potential savings in energy that could be expected in the short run by adopting load management techniques and other conservation measures, but also to assess the cost-effectiveness of load management investments; and to understand the overall expectations and attitudes of the sample test customers in regard to the feasibility and applicability of direct load management techniques.

The areas of concern include: Cost, availability and adequacy of alternative energy sources, process limitations, off-peak utilization, labor union problems, financial resources needed to purchase capital intensive load management equipment and the relevant payback periods of capital investments, tax incentives, subsidies, governmental regulations such as OSHA, availability of energy utilization information systems, awareness of the industry towards limited energy supplies and other technological options. It should be noted that the primary objective was to investigate the potential savings attributable to electric load management. No attempt was made in the survey to investigate the potential savings due to natural gas or other forms of energy. The natural gas savings referred to in the analysis of the survey were the ones directly associated with changes in electric energy utilization. If the recommendations contained a heat recovery system, for example, the increased electric usage was followed by a decrease in gas consumption. In other words, the gas savings indicated were those directly related to electricity conservation and/or load management.

The primary objective was not only to analyze the existing energy consumption patterns but also to identify those test group customers who would have greatest potential savings and, in particular, the specific areas in which the maximum savings in peak demand (kW) and energy (kWh) would be attained; and to estimate the overall savings that would be expected by

implementing load management and other end-use conservation measures. A summary of these estimated savings is presented in Chapter III. It should be noted, however, that the estimated savings should be treated as theoretical maximums against which actual savings presented in Chapter IV, which could be achieved by monitoring of the experiment, would be compared.

3. Survey Methodology and Procedures: The most important steps were first to secure test customer acceptance to participate in the program, second to get management's commitment, third to conduct an in-depth on-site technical survey of customer facilities, fourth to submit the proposal recommendations to the customers for action, and fifth to implement the recommendations.

The basic methods and procedures involved in the survey were: Advance call or initial contact of the selected sample test customers, plant technical survey, data analysis, and proposal presentation. These methods and procedures are thoroughly explained in Chapter II of this report. A brief description of the rationale and criteria used is presented below:

Before conducting the survey, several schedules and forms were developed. Survey Form 1 was primarily intended to secure historical operating data of the customer. The items included were: products produced, operating characteristics -- number of work shifts, employment levels, product sales, gross energy consumption, energy costs by type, physical characteristics of the premises, utilization of connected loads by type of activity such as production and non-production. The Survey Form 1 was completed by the test customers. Survey Form 2 and Survey Form 3 were basically designed to record the technical survey data. These were completed by the project survey team with assistance from the appropriate plant personnel. Sample copies of these forms are presented in Appendix A of this report.

4. Advance Call: After the sample test group customers were selected, a meeting was arranged with top level management of each of the customers by the key personnel of the project staff to explain the objective of the project and to get management's approval and firm commitment to participate in the demonstration program. The customer response to the initial contact was overwhelming. One test customer declined to participate in the project due to specific reasons of his own. Another test customer, after having agreed to participate in the program, expressed his inability to participate as he was planning to move out of state. Suitable replacements of these customers were immediately secured.
5. On-site Survey: The survey team comprised of the following specialists: an assigned account representative of Detroit Edison; a lighting specialist; a specialist on space conditioning and processing systems (HVAC); two members of the MPSC staff, and a consulting engineer.

In the survey, major industrial processes were identified on a floor plan along with other peripheral equipment so the study would encompass the specific process as one entity. The following areas were the prime focus of the survey: (1) lighting systems, (2) areas for timing and control devices, (3) heat recovery application, (4) HVAC system improvements, (5) building insulation and structures, (6) off-hour audits and special testing meters, (7) potential for off-peak energy utilization, (8) recovery of process and boiler water, (9) demand control and/or monitoring systems, (10) general maintenance, (11) other uses of energy and the potential of transfer to electric energy.

The on-site technical surveys were conducted for only 19 out of a total of 20 test group customers. One test group customer representing SIC 27 - Printing and Publishing - had already implemented several energy conservation measures prior to being the test customer. The national association representing SIC 27 provides to all its members valid information regarding energy efficient technology and energy conservation methods. However, the survey team conducted a complete review of the operations including lighting, HVAC and process, and it was determined that there was very little scope for further improvement.

6. Analysis of Data: The recorded data were scrutinized and analyzed. The technical team and the independent engineering consultant evaluated the results for the potential for savings and possibilities for load management, the potential for shifting peak demand to off-peak periods, improvement in efficient use, costs of demand control equipment or other capital investment items and non-capital investment costs. Further, a summary of capital and non-capital investment costs with energy savings by cost per unit, time-of-day and energy shifted to off-peak loads was made available to the economic consultant. The economic consultant provided a complete analysis of the economic feasibility of load management investments of the individual companies which included the relevant pay-back periods, average rate of return on investment, and return on capital investments required to implement the recommendations contained in the proposal.
7. Proposal Presentation: A final summary of the survey recommendations (proposal) was presented to the managements of 19 of the 20 test customers. A special proposal was prepared in the case of a customer representing SIC 27 but was not formally presented due to the reasons mentioned in #5 above. After presenting the proposals, the customers were requested to respond to the proposal presentation at an early date.

G. Economic Analysis

1. Evaluation of Load Management Investments: The cost-effectiveness of load management investments was determined in terms of total investment rather than individual investments of the proposals. In other words, the project as a whole was evaluated and the relative merits of individual component investments were not investigated. Given this constraint, the next step was to evaluate the total project in terms of how much

the annual savings would be (both energy and in dollars) if the project were implemented. In the case of operating and maintenance savings of non-capital projects, it is a relatively simple matter. For a capital project, however, one needs to figure out not only the annual savings in both energy and money but also how much investment would be needed to carry it out and how long it would take for annual dollar savings to pay back the money invested in the project.

The basic data required to do the analysis were: (1) identification of load management equipment, (2) capital and installation cost of the equipment, (3) existing electric and gas energy use, (4) electric and gas energy use after load management, (5) 1976 electric and gas rates, (6) gas cost with load management, and (7) peak and off-peak kW and kWh percentages. Using this information, the dollar value of the energy savings associated with load management investment was calculated.

The criteria used to evaluate the load management investments were: (1) a ten-year life for equipment, (2) a two-year cash-flow period, (3) a 50 percent corporate tax rate, (4) a 10 percent investment tax credit, (5) eight percent discount rate to arrive at the present value, (6) a 10 percent return on investment, (7) a 24-month payback for a 100 percent cash-flow rate, and (8) a first-year write-off of the installation costs. The 24-month payback period was used as the test group customers expressed that they must get back their investment on or before 24 months. If the investment did not meet the 24-month payback criterion, the amount of investment subsidy needed to meet this criterion was determined. The investment subsidy is that amount of money necessary to bring a deficient cash-flow rate up to 100% over two years.

2. Summary of Estimated Savings, Total Investment, and Payback Period:
A summary of total investment required and the corresponding savings, and the payback periods of the test customers, assuming that all the proposal recommendations of the customers were carried out, are presented on the following page:

Table 2

COST EFFECTIVENESS OF LOAD MANAGEMENT INVESTMENTS

SIC Code	Business	Total Investment*	Annual Total Savings** (Gas & Elec.)	Payback Period (Mos.)	Subsidy Required to bring the Payback Period to 24 Mos.
20	Food Products	\$ 11,075	\$ 3,600	93.7	\$ 4,260
26	Paper Products	7,290	7,789	15.4	none
27	Printing & Publish.	-	-	-	-
28	Paints & Varnishes	5,425	17,816	6.9	none
30	Rubber Products	26,545	8,425	72.7	10,770
32	Glass Products	21,500	24,935	8.3	none
33	Primary Metals				
	Company A	9,270	5,126	31.5	1,300
	Company B	5,175	260	(147.0)	6,651
34	Fabricated Metals				
	Company A	500	1,512	4.7	none
	Company B	10,350	8,874	20.0	none
	Company C	4,000	600	(110.0)	6,550
	Company D	1,550	0	(26.9)	3,107
35	Machinery (except electrical)				
	Company A	11,050	7,244	27.9	1,400
	Company B	7,950	2,364	80.8	3,500
	Company C	11,800	9,499	20.7	none
	Company D	113,575	39,184	56.1	44,350
37	Transportation				
	Company A	11,150	(1,574)	(59.6)	14,187
	Company B	9,900	5,963	29.6	1,500
	Company C	4,375	3,446	21.8	none
	Company D	1,090	0	(115.0)	2,236

*Total Investment includes approximately 50% of labor cost of installing the recommended equipment.

**Using 1976 Electric and Gas rates.

Parenthesized figures indicate negative payback.

It should be noted that the total investment includes approximately 50 percent towards the labor cost of installing the load management equipment and implementing other conservation measures which did not carry capital expenditures. At the time of implementing the proposals, some of these investments either have increased or decreased due to the fact some customers did implement more or less than the proposal recommendations. The test group customers who implemented more than our proposal recommendations were: SIC 33-B, SIC 34-B, SIC 35-D, and SIC 37-A. However, the payback periods of these customers were not revised. In fact, the actual investments of the test customers slightly differed from the investments mentioned in Table 2.

H. Customer Acceptance of the Proposals

A total of 20 proposals were made including a special proposal to a test group customer representing SIC 27 - Printing and Publishing, since this customer had already implemented several energy conservation measures prior to being the test customer. However, the survey team conducted a complete review of the operations including lighting, HVAC, and process; and it was determined that there was very little scope for further improvement. A special proposal was made for this customer describing the unique characteristics of the mode of operations which are, in general, typical of this industry wherever they are located in the country; but no formal presentation of this special proposal was made to the customer.

Thus, formal proposal presentations were made only to the remaining 19 test group customers out of a total of 20 test group customers. Three of the 19 test group customers did not respond to our proposal recommendations despite our repeated efforts and did not implement any of the recommendations. Ten of the remaining 16 customers responded in writing to accept the proposals and to implement the recommendations, and the remaining six test groups customers agreed orally to implement the recommendations that were made in their respective proposals. Finally, 16 of the 20 test customers implemented either some or all the recommendations of the proposals.

The extent to which the proposal recommendations were implemented by the test group customers and the average length of time taken to implement the recommendations are as follows: Sixteen of the 19 test customers who responded to the proposals have implemented the recommendations in varying degrees of magnitude. These customers, in general, have not carried out the recommendations at one time. Instead, they have adopted them in a piecemeal fashion. Further, the test customers have taken an average period of four to five months to fulfill either some or all the proposal recommendations. However, some of the non-capital expenditure items, such as maintenance, lighting removal, relocations, etc., have been put into effect immediately. Some of the customers have implemented beyond our recommendations despite unattractive payback periods on their investments.

The three test group customers who did not respond and did not implement any of the recommendations were: (1) SIC 30, Rubber Products; (2) SIC 35-A, Machinery; and (3) SIC 37-D, Transportation.

I. Implementation

The details in regard to the type of recommendations implemented by the test group customers are itemized below. The following gives an overall summary of the percentage of the customers who implemented various recommendations by category.

1. **Timing and Control Devices:** Seventy-three percent of the customers have implemented most of the recommendations or have committed to implement in the near future. These include timing devices on:
 - a. water heaters
 - b. battery chargers
 - c. lighting systems
 - d. heat pumps
 - e. air conditioners, etc.
2. **Demand Control Systems:** Recommendations were made to three test customers, two of which have been implemented. One customer (SIC 32) did not implement the demand control system, despite an offer of \$10,000 to purchase the system, due to excessive labor cost involved in implementing all the recommended changes. A special analysis of the demand control system implemented by a customer representing SIC 33-B - Primary Metals - is presented in Appendix B of this report.
3. **Heat Recovery:** Sixty-seven percent of the customers in this category have implemented the heat recovery techniques and others have plans to implement heat recovery recommendations in the immediate future.
4. **HVAC System Improvements:** About 40 percent of the customers in this category have implemented the HVAC system improvements, and others have plans to implement them in the very near future.
5. **Recovery of Process and Boilers:** Approximately 63 percent of the customers have implemented recommended changes.
6. **Lighting:** About 58 percent of the customers in this category have implemented a large portion of our recommendations and others are seriously considering the installation of new lighting systems in the foreseeable future. However, items such as (a) relocation of lighting, (b) removal of excessive lighting, and (c) maintenance of existing lighting, have been accomplished by a large majority of the customers.
7. **General Maintenance:** Almost every customer in the test group has done something in this area.
8. **Insulation:** The response in this area was satisfactory. About 32 percent of the recommended customers have implemented the recommendations.
9. **Shift Changes:** There was a limited scope in this area so far as the sample test customers were concerned. But the overriding factors which were identified are additional cost of labor (shift premiums), labor union problems and process limitations.

10. Conversion: Capability exists in all plants. But this report did not focus on this issue.

J. Major Electrical Uses of the Test Companies by Specific Areas

During the survey, the test customers were requested to provide information regarding their major electrical uses by category. The table below provides a summary of major electrical use by specific area:

Table 3
Major Electrical Uses of the Test Companies
by Specific Areas in 1975

<u>Area</u>	<u>Estimated kWh</u>	<u>Estimated kW</u>
	<u>%</u>	<u>%</u>
Lighting	15	7
HVAC	6	6
Processing	73	84
Miscellaneous	<u>6</u>	<u>3</u>
Total	<u>100</u>	<u>100</u>

The major areas concentrated on in the survey were: lighting, HVAC, processing, and a miscellaneous category which includes a variety of items such as hot water heaters, air compressors, forklift chargers, pollution equipment, computers, vent pumps, etc. One of the major objectives of the study was not only to investigate the maximum potential to reduce the peak demand but also to identify the specific areas in which greater potential for peak demand reduction would exist. The above table points out that 84 percent of the peak demand (kW) was in the processing area, compared to 73 percent of energy (kWh). In fact, there exists a maximum potential for peak demand reduction in the production area but the technical survey was limited to those peak demand reductions which would not interfere with the production processes and equipment.

K. Rationale for Using ANSI (American National Standards Institute) Lighting Standards

The lighting recommendations incorporated in the proposals of the test customers were designed using ANSI standards. The basic objective was not only to eliminate unnecessary lighting, but also to maintain minimum industrial lighting standards as required by OSHA (Occupational Safety and Health Act of Federal Government) and other state and local requirements. During the review of lighting analysis, the areas were classified as hazardous and non-hazardous with consideration being given to worker safety and product quality. Consideration was also given to contribution of the lighting system to peak demand (kW) and energy (kWh). Further, the lighting analysis explored several alternatives to reduce peak demand and total energy consumption due to lighting and recommended the most efficient lighting systems. Worker safety, product quality, and efficient use of lighting were the hallmark of the industrial lighting recommendations. This was the corner stone of the recommendations.

L. Customer Participation

The test group customers were highly receptive to our proposal recommendation. Sixteen out of a total of 20 test customers actually participated in the experiment by implementing a major portion of all our proposal recommendations. Some of the test group customers (SIC 33 and 35) have implemented beyond our recommendations. In fact, a large majority of the customers have implemented non-capital items such as maintenance, removal of unnecessary equipment, etc., and items involving small and medium capital expenditures. A good portion of the customers have scheduled those items involving heavy capital expenditures into the immediate future for implementation. While the experiment was being conducted, some of the test customers informed the project staff that they had approved thousands of dollars in their 1978 budgets for energy management. A summary of the extent to which the test customers have implemented the suggested recommendations before the test period is given below:

Table 4
Percent of the Proposal Recommendations Implemented

<u>Test Customers</u>	<u>Percent of Recommendations Implemented</u>	<u>Test Customer SIC Codes</u>
4	-0-	27, 30, 35-A, 37-D
4	10 - 40	20, 32, 34-A, 37-C
7	40 - 70	26, 28, 33-A, 34-C, 34-D, 35-C, 37-B
5	70 - 100	33-B, 34-B, 35-B, 35-D, 37-A

It should be noted that the percentages of the recommendations implemented were based on the expected load reductions but not strictly comparable to the actual dollar amounts spent. Further, the details of the items implemented by the customers are presented in Chapter IV of this report.

M. Administration of the Test

It was pointed out earlier that 16 of the total 20 test customers have implemented the proposal recommendations in varying degrees. Some customers have implemented the proposal recommendations earlier than others, as such, the test period varied between six to 11 months. The average test period of the customers was about eight months. The test period commenced in August, 1976, and ended on June 30, 1977. The project was partially funded by the Federal Energy Administration which provided \$200,000 augmented by Michigan's contribution of well over \$89,000 in staff time and by The Detroit Edison Company which expended approximately \$40,000 in staff time, equipment and data collection. Direct supervision of the project was the responsibility of a project management team consisting of staff members of the MPSC and Detroit Edison Company. Two staff members, one from MPSC and one from Detroit Edison, were assigned full time to be project coordinators.

The project coordinator representing The Detroit Edison Company was the main information source for the test customers. Overall, the policy direction was provided by a project direction group consisting of the heads of the state agency, senior executives of Detroit Edison and an independent (not one of the test customers) industrial customer representative.

N. Financial Assistance to the Test Customers

Of \$200,000 FEA provided, \$100,000 was intended for test customers to purchase load management equipment. The financial assistance to each customer was limited to \$5,000 towards load management items only. However, a maximum of \$10,000 was allowed under special circumstances and if the monies were available. The load management equipment included timers, demand control systems, and other load limiting equipment. Proposal items such as lighting systems, insulation, ceiling fans, painting, etc., were not eligible for financial assistance. The estimated total amount eligible for load management was about \$50,000 out of a total \$100,000.

Only two out of the 16 test customers who participated in the test initially requested reimbursement. FEA approved a sum of \$10,000 to a customer representing SIC 32 - Glass Products, to purchase and install a demand monitoring system, but subsequently, the customer declined to accept the offer due the excessive cost of installing the equipment. The second test customer, representing SIC 33 - Primary Metals, accepted the FEA offer of \$8,235 to purchase and install a demand monitoring system. The remaining test customers did not request monies.

O. Control Customers

The control group customers of the test who had similar and homogeneous characteristics as the test group customers were considered as a standard for the purpose of the test. The control customers, by design, were not aware that they were selected for the study. Only the project staff knew about them. An energy audit survey was not conducted, nor even the financial assistance was provided. However, Survey Form 1 was mailed to these customers requesting them to complete the form and to mail it back to Detroit Edison. Detroit Edison provided historical electrical consumption data along with electrical consumption data during the test period. The response from the control customers in regard to the completion of Survey Form 1 was meagre. Six out of 20 control customers completed survey forms and mailed them to Detroit Edison project staff. Several request letters were sent but no answer was received from the remaining customers. Even those six customers who completed the Survey Form 1 did not answer all the questions. The historical data submitted on Survey Form 1 was not even internally consistent, and, as such, were not incorporated in the report.

P. Additional Concern of the Test

As was pointed out at the beginning, the objective of this study was to explore the potential possibilities for electric load management with reference to a sample of 20 test group customers in particular and the overall industrial sector in the short run. It was not the objective of the study to review the impact of the customer response with respect to any

set of predesigned rates; on the other hand, the prime concern was to measure the impact and the feasibility of direct load management techniques and other end-use conservation measures.

The estimated energy savings, annual dollar savings, load management investments of the study were derived using the old (1976) time-of-day rates. In May, 1977, while the experiment was being conducted, a revised rate structure applicable for the sample test and control customers went into effect. Additional analysis was carried out. The objective was first to measure the impact of the revised (new) rates in terms of the changes in annual dollar savings, payback periods of the test customers and to assess whether the new rates would promote the objective of load management; and second, to identify a set of demand rates that would provide a 24-month payback of those customers whose investments did not initially meet the criterion of 24 months and to gauge the additional costs involved in the short run. The analysis was intended to provide some clues to the policy makers (commissions and utilities) as to the nature and consequences in case such measures were implemented across the population of industrial customers having the same characteristics of the sample test and control customers. The details of the rate analysis are presented in Chapter IV of this report.

The second important concern of the study was to identify the type of feasible and operational policy instruments that would induce load management. These include tax incentives, subsidies, availability of capital at low interest rate, energy efficiency ratings, rate structures, energy management information systems, depreciation policies, etc.

The third concern was to know the characteristics of the industry environment in management decision-making, operational characteristics by SIC codes, energy use patterns, peak coincident load characteristics, possibilities for load shifting to off-peak intervals, and the attitudes of the industry towards energy shortages, availability and reliability of energy supplies and the future expectations of the industrial sector in general. The final concern was to measure the impact on the Detroit Edison system in the short run.

CHAPTER II

DETAILED METHODOLOGY

- A. Sample Selection
- B. Surveys
- C. Economic Analysis

A. METHODOLOGY FOR SELECTING A REPRESENTATIVE SAMPLE OF TEST AND CONTROL COMPANIES FROM THE POPULATION OF PRIMARY INDUSTRIAL CUSTOMERS OF THE DETROIT EDISON COMPANY GIVEN A SAMPLE SIZE OF 40.

1. PURPOSE:

The basic purpose of drawing a sample from any population or universe is to estimate the characteristics or the parameters of the population under investigation as accurately as possible with the knowledge of the sample members.

POPULATION:

The primary industrial customers of The Detroit Edison Company constituted the population for the purpose of selecting a sample.

SAMPLE SIZE:

The size of a sample of 40 primary industrial customers that were to be selected from the above population was fixed in advance and was approved by FEA.

METHOD OF SELECTING A SAMPLE OF 40 PRIMARY INDUSTRIAL CUSTOMERS:

The selection of the sample test and control companies was made by using a stratified random sampling with a purposive selection.

2. STRATIFIED RANDOM SAMPLING PROCEDURE:

If the population to be sampled is heterogeneous in nature, simple random sampling will give biased estimates of the population. In such a case, the population is divided into a number of homogeneous sub-populations or strata. A separate simple random sample is then drawn from each stratum at a rate giving the stratum its proper representation.

The effectiveness of such a procedure obviously depends upon the homogeneity of the strata. Some information about the universe must be available before suitable strata can be delineated. Such information may sometimes be extensive or quite limited.

PURPOSE OF ALLOCATION OF 40 SAMPLE CUSTOMERS TO INDIVIDUAL STRATA:

With reference to the load management project, the sample size was fixed at 40 prior to drawing an optimum size sample that the population at large would have warranted. The sample of 40 was fixed in advance and was agreed upon by FEA at the time the award was made. Given the sample size in advance, the problem was to allocate the total sample to different strata so that the corresponding sample estimates would have the desirable properties, such as minimum variance, and maximum precision of the estimates of the population as compared to other forms of allocation of the given sample 40 to the individual strata.

BASIC GOAL:

The basic goal of the load management project has been to identify those primary industrial customers within the service area of The Detroit Edison Company and which have the greatest potential for electric load management. To achieve this goal, detailed criteria for selecting a representative sample were developed.

3. SAMPLE SELECTION CRITERIA:

1. The total population of primary billing demand customers of Detroit Edison was stratified according to their respective industry groups (SIC codes) as shown in the table following:

TABLE I
CLASSIFICATION OF DETROIT EDISON'S PRIMARY CUSTOMERS BY INDUSTRY

	Type of Industry (By SIC Code)	Number of Customers 1975	% of Total
14	Mining	10*	0.52
	<u>Manufacturing Industries:</u>		
19	Ordnance and Accessories	2*	0.10
20	Food	53	2.77
22	Textiles	1*	0.05
23	Apparel and Fabrics	-	-
24	Lumber and Wood Products	1*	0.05
25	Furniture	6*	0.03
26	Paper and Allied Products	23	1.20
27	Printing and Publishing	21	1.10
28	Chemicals	27	1.41
29	Petroleum Refining	9*	0.47
30	Rubber and Plastics	53	2.77
32	Stone, Clay and Glass	25	1.31
33	Primary Metals	88	4.60
34	Fabricated Metals	104	5.43
35	Machinery	103	5.38
36	Electrical Machinery	13*	.68
37	Transportation Equipment	118	6.17
38	Precision Instruments	6*	.31
39	Miscellaneous Manufacturing	<u>9*</u>	<u>.47</u>
	TOTAL MANUFACTURING INDUSTRIES	672	35.11

* SIC Codes not used for selection of sample

TABLE I (Con't)

NON-MANUFACTURING INDUSTRIES*

<u>SIC Code</u>	<u>Type of Industry</u>	<u>Number of Industries 1975</u>	<u>% of Total</u>
40	Transportation, Communication and Other Public Utilities	149	7.78
50	Wholesale and Retail Trade	409	21.37
	Office Buildings	129	6.74
80	Hospitals	92	4.81
82	Schools	172	8.99
70	Apartments and Hotels	116	6.06
86	Government	70	3.66
89	Other Non-Manufacturing	<u>105</u>	<u>5.49</u>
	TOTAL NON-MANUFACTURING	1242	64.89
	TOTAL PRIMARY CUSTOMERS	1914	

* Non-Manufacturing primary customers not used for sample selection

Note: 35% of total primary customers of Detroit Edison constitutes the industrial (Manufacturing) customers and 65% represents the Non-Manufacturing sector.

It can be seen from Table I that there were a total of 1,914 primary demand customers during 1975 of which 35% were from the manufacturing sector and 65% were from the non-manufacturing sector.

2. The SIC groups having less than 20 industrial customers were not considered for the purpose of sample selection. These primary industrial groups are listed below:

TABLE 2

MANUFACTURING SIC GROUPS
NOT CONSIDERED FOR SAMPLE SELECTION OF CUSTOMERS

Mining	10
Ordinance and Accessories	2
Textiles	1
Lumber and Wood Products	1
Furniture	6
Petroleum Refining	9
Electrical Machinery	13
Precision Instruments	6
Miscellaneous Manufacturing	<u>9</u>
TOTAL	57

The total available primary industrial customers after deleting the 57 from 672 was 615. The table below shows the composition of the available 615 primary manufacturing companies classified as small, medium and large with respect to their primary demand for August, 1975.

TABLE 3

CLASSIFICATION OF PRIMARY INDUSTRIAL CUSTOMERS BY TYPE

MONTHLY PRIMARY DEMAND KW	TYPE	SIC GROUP										Total	% of Total
		20	26	27	28	30	32	33	34	35	37		
Less than 2,000	Small	51	18	19	25	52	16	70	99	88	59	497	81
2,000 - 10,000	Medium	2	4	2	2	-	7	11	5	14	27	74	12
10,000 & over	Large	-	1	-	-	1	2	7	-	1	32	44	7
TOTAL		53	23	21	27	53	25	88	104	103	118	615	100

Table 3 indicates that 81% of the total available primary industrial customers represents the small industries which had a primary demand of less than 2,000 kW per month, 12% represents the medium users and only 7% falls within the large group category - **Steel, Cement, Automobile companies** (Ford, General Motors, Chrysler, etc.). In fact, the larger group, consisting of only 7%, makes a significant impact on Detroit Edison system.

3. Only primary manufacturing industrial customers having the monthly billing demand not exceeding 6,000 kW were considered to be included into a sample of 40. The table below shows the classification of the available 615 primary industrial customers with respect to their monthly billing demands.

TABLE 4
MONTHLY PRIMARY DEMAND OF AVAILABLE INDUSTRIAL CUSTOMERS

MONTHLY PRIMARY DEMAND KW	SIC GROUPS										Total	% of Total
	20	26	27	28	30	32	33	34	35	37		
Less than 6,000	52	21	21	26	52	21	80	104	101	81	559	91
6,000 and over	1	2	-	1	1	4	8	0	2	37	56	9
TOTAL	53	23	21	27	53	25	88	104	103	118	615	100

It is to be noted that of the total 615 available customers, 91% had billing demands of less than 6,000 kW and only 9% had primary billing demands greater than or equal to 6,000 kW in August, 1975.

The tables below provide the levels of primary demand consumption for August, 1975.

TABLE 5.
AVERAGE MONTHLY PRIMARY DEMAND LESS THAN 6,000 KW

LEVELS	SIC									
	20	26	27	28	30	32	33	34	35	37
Mean	734	969	780	990	616	1124	913	667	931	1425
Median	615	472	444	729	499	430	501	486	532	774
Mode	571	450	385	720	341	400	397	381	392	500

TABLE 6
AVERAGE MONTHLY PRIMARY DEMAND GREATER THAN 6,000 KW

LEVELS	SIC									
	20	26	27	28	30	32	33	34	35	37
Mean	7040	9428	-	7680	16872	9213	48139	-	16021	24434
Median	7040	9428	-	7680	16872	9327	52515	-	16021	21216
Mode	7040	-	-	7680	16872	9327	82674	-	-	19846

The overall average demand for the first group was 909 kW for the month of August, 1975, and 25,152 kW average primary demand for the second group.

The principal reason for eliminating the primary demand customers having their primary demand greater than 6,000 kW was that these companies are considerably larger in size and it was felt that it would take a considerable amount of time to investigate the companies' facilities with regard to load management. Moreover, some of these larger companies have had energy management programs of their own. Therefore, it was decided to limit to those industrial customers having a primary demand of less than 6,000 kW and who would represent the population equitably. Further, a large percentage of these small and medium-size primary customers do not have any kind of energy management program, either due to a lack of technical know-how or financial capability.

By eliminating the 56 primary industrial customers who had a monthly primary demand exceeding 6,000 kW, we were left with (615-56) a truncated population of 559 primary industrial customers for the purpose of drawing a sample of 40.

4. Of the total available population of 559 primary manufacturing industrial customers, a sample of 40 was selected using a method of stratified random sampling with purposive selection. The following table indicates the sample so selected:

TABLE 7

ALLOCATION OF 40 COMPANIES TO DIFFERENT STRATA - I

SIC Strata	Stratum Size	ALLOCATION OF SAMPLE TEST & CONTROL COMPANIES			Sampling Fraction
		Test	Control	Sample Size	
20 Food & Kindred Products	52	1	1	2	.0385
26 Paper & Allied Products	21	1	1	2	.0952
27 Printing & Publishing	21	1	1	2	.0952
28 Chemicals & Allied Products	26	1	1	2	.0769
30 Rubber & Misc. Plastic Products	52	1	1	2	.0385
32 Stone & Glass	21	1	1	2	.0952
33 Primary Metals	80	2	2	4	.0500
34 Fabricated Metals Except Machinery	104	4	4	8	.0769
35 Machinery Except Electrical	101	4	4	8	.0792
37 Transportation	<u>81</u>	<u>4</u>	<u>4</u>	<u>8</u>	<u>.0583</u>
	559	20	20	40	.7444

5. A sub-sample of 20 was selected out of the sample of 40 to form the test group and the remaining 20 were taken to represent the control group with one-to-one correspondence to the test group companies that were chosen.
6. The sample of test and control companies that were selected maintained, as far as possible, homogeneous characteristics by size and mode of operations.
 - a) Had as far as possible the same number of workshifts.
 - b) Had approximately similar technological processes, product lines, employment levels, and physical operating characteristics within the plant.
7. Prior to inclusion of the industrial customers into the sample, a thorough analysis of historical data relating to hourly billing demand covering a period of three (3) years (1973, 1974 and 1975) was conducted to discover the demand patterns and the customer coincidence peak load characteristics, seasonal variations and the customer coincidence within the day with the system's peak.
8. Demand profiles of each of the selected test and control customers were drawn for 1973, 1974, and 1975 and comparisons with the system load curves were made to discover the coincidence peaks with the system.

4. Rationale for Sample Selection

The discussion that follows highlights the efficiency of the sample that was selected to represent the test and control companies as opposed to proportional allocation and optimal allocation of the total sample 40 to different strata.

TABLE 8

ALLOCATION OF 40 COMPANIES TO DIFFERENT STRATA - II

<u>SIC (Strata)</u>	<u>Stratum Size</u>	<u>Allocation of Sample Test & Control Co.</u>
20 Food & Kindred Products	52	2
26 Paper & Allied Products	21	2
27 Printing & Publishing	21	2
28 Chemicals & Allied Products	26	2
30 Rubber & Misc. Plastic Products	52	2
32 Stone & Glass	21	2
33 Primary Metals	80	4
34 Fabricated Metals Except Machinery	104	8
35 Machinery Except Electrical	101	8
37 Transportation	<u>81</u>	<u>8</u>
TOTAL	559	40

The above allocation was partly dictated by apriori knowledge and objective evaluation of the different strata.

Proportional Allocation of the Total Sample 40 to Different Strata

Notation: Let n denote the total sample to be allocated

Let N denote the total available population of industrial customers.

Let N_i denote the i -th stratum size.

Then the number of industrial customers to be allocated to each stratum is given by:

$$n_i = \frac{n \times N_i}{N}, \quad i = 1, 2, 3, 4, 5, 6, 7, 8, 9, 10$$

In our case: $n = 40$, $N = 559$

$N_1 = 52$, $N_2 = 21$, $N_3 = 21$, $N_4 = 26$, $N_5 = 52$, etc. $N_{10} = 81$

$$\begin{aligned} n_1 &= \frac{n \times N_1}{N} = \frac{40 \times 52}{559} \\ &= 3.7 \end{aligned}$$

$$\begin{aligned} n_2 &= \frac{n \times N_2}{N} = \frac{40 \times 21}{559} \\ &= 1.5 \text{ etc.} \end{aligned}$$

The proportional sample gives the following allocation:

Stratum	Stratum Size	Proportional Allocation	Adjusted
20 Food & Kindred Products	52	3.7209	3
26 Paper & Allied Products	21	1.5026	2
27 Printing & Publishing	21	1.5026	2
28 Chemicals & Allied Products	26	1.8604	2
30 Rubber & Misc. Plastic Products	52	3.7209	3
32 Stone & Glass	21	1.5026	2
33 Primary Metals	80	5.7245	6
34 Fabricated Metals Except Machinery	104	7.4418	7
35 Machinery Except Electrical	101	7.2272	7
37 Transportation	81	<u>5.7961</u>	<u>6</u>
TOTAL		39.9999	40

Since the experiment needs a minimum of two members in each group, one test and one control company, appropriate adjustment is made to arrive at a total of 40.

Comparison of Means and Variances Between the Sample Test and Control Companies and the Proportionally Allocated Sample

Notation:

Let $\bar{x}_1, \bar{x}_2, \text{etc. } \bar{x}_{10}$ be the individual sample means of the experiment.

Let $\frac{W_i}{N}$, $i = 1, 2, 3, \text{etc. } 10$, be the stratum weights; then the estimated average of the population of the industrial customers is:

$$\bar{x} = W_1 \bar{x}_1 + W_2 \bar{x}_2 + \text{etc.} + W_{10} \bar{x}_{10} \quad (1)$$

The variance of the weighted average is:

$$\sigma_{\bar{x}}^2 = W_1^2 \sigma_{\bar{x}_1}^2 + W_2^2 \sigma_{\bar{x}_2}^2 + \text{-----} + W_{10}^2 \sigma_{\bar{x}_{10}}^2 \quad (2)$$

where the individual $\sigma_{\bar{x}_i}^2$ refer to the accuracy with which the sample average for a stratum represent the true average for that stratum.

Further, if the variances of individual strata are $\sigma_1^2, \sigma_2^2, \text{-----} \sigma_{10}^2$ then:

$$\begin{aligned} \sigma_{\bar{x}_1}^2 &= \sigma_1^2 \left(\frac{1}{n_1} - \frac{1}{N_1} \right) \\ \sigma_{\bar{x}_2}^2 &= \sigma_2^2 \left(\frac{1}{n_2} - \frac{1}{N_2} \right) \\ \text{-----} &= \text{-----} \\ \sigma_{\bar{x}_{10}}^2 &= \sigma_{10}^2 \left(\frac{1}{n_{10}} - \frac{1}{N_{10}} \right) \end{aligned} \quad (3)$$

Since we do not know the stratum variances, the best estimates can be obtained by the corresponding sample variances:

$$s_1^2, s_2^2, \text{-----} s_{10}^2$$

Then equations (3) become:

$$\begin{aligned} \sigma_{\bar{x}_1}^2 &= s_1^2 \left(\frac{1}{n_1} - \frac{1}{N_1} \right) \\ \text{-----} &= \text{-----} \\ \sigma_{\bar{x}_{10}}^2 &= s_{10}^2 \left(\frac{1}{n_{10}} - \frac{1}{N_{10}} \right) \end{aligned} \quad (4)$$

Equation (2) reduces to:

$$\sigma_{\bar{x}}^2 = W_1^2 S_1^2 \left\{ \frac{1}{n_1} - \frac{1}{N_1} \right\} + \dots + W_{10}^2 S_{10}^2 \left\{ \frac{1}{n_{10}} - \frac{1}{N_{10}} \right\} \quad (5)$$

Using the above formulas, we get:

	Experimental Sample	Proportional Sample
Mean	950	1,158
Variance	10,211	23,732

It should be observed that the experimental sample mean (950 kW) primary demand is very close to the overall mean (909 kW) of the population of industrial companies having their demand less than 6,000 kW, than that of proportional allocation sample mean (1,158 kW); and the variance of the proportional sample is 2.32 times greater than that of the experimental sample variance.

5. Relative Efficiency of the Two Designs

Let σ_E^2 be the variance of the experimental sample allocation.

Let σ_P^2 be the variance of the proportional allocation of the sample.

The relative efficiency I is defined as the ratio of the two variances.

In our case:

$$\begin{aligned} \sigma_E^2 &= 10,211 \\ \sigma_P^2 &= 23,732 \\ I &= \frac{\sigma_P^2}{\sigma_E^2} = \frac{23,732}{10,211} = 2.32 \end{aligned}$$

This means that experimental sample allocation to the strata is 232% as efficient as the proportional allocation sample to the strata.

Optimal Allocation of the Sample

The precision of a stratified sample depends very much upon the way the sample is allocated to the strata. It is natural to ask if there is an optimum allocation which will make the sample error in $\bar{x}$ a minimum.

If $\bar{x} = W_1 \bar{x}_1 + \text{etc.} + W_{10} \bar{x}_{10}$, the variance of $\bar{x}$ is:

$$\sigma_{\bar{x}}^2 = W_1^2 \sigma_1^2 \left\{ \frac{1}{n_1} - \frac{1}{N_1} \right\} + \dots + W_{10}^2 \sigma_{10}^2 \left\{ \frac{1}{n_{10}} - \frac{1}{N_{10}} \right\} \quad (1)$$

For given total sample size n , it is possible to find values of n_1, n_2, n_3 , etc. n_{10} that make $\sigma_{\bar{x}}^2$ a minimum.

This is done by minimizing:

$$F = \sigma_{\bar{x}}^2 + K^2 (n_1 + n_2 + \text{etc.} + n_{10} - n) \quad (2)$$

where K^2 is a Lagrange multiplier.

Taking the partial derivatives of (2) with respect to n_1, n_2 , etc. n_{10} and K^2 , equating them to zero and simplifying the equations, we get:

$$n_1 = \frac{W_1 \sigma_1^2}{\sum W_j \sigma_j^2} \cdot n; \quad n_2 = \frac{W_2 \sigma_2^2}{\sum W_j \sigma_j^2} \cdot n, \text{ etc.} \quad (3)$$

$$n_{10} = \frac{W_{10} \sigma_{10}^2}{\sum W_j \sigma_j^2} \cdot n$$

The W_j are usually known before the sample is drawn. But the estimates of the σ_j^2 often can be computed only after the data from the sample become available. In that event, the analyst must make the best approximation possible at the time the sample is designed; when the data from that sample become available for analysis, a post-mortem can be conducted to see how well, or how badly, the allocation actually used conforms to the optimum. Such analysis is valuable for future surveys even though it is too late to correct deficiencies in the survey analysis already made.

Using S_1, S_2 , etc. S_{10} of the experiment as best estimates of σ_1^2, σ_2^2 , ---- σ_{10}^2 the optimum sample allocation should have been as follows:

Optimum Sample Allocation Using Standard Deviations of the Experimental Sample

<u>Stratum</u>	<u>Stratum Size</u>	<u>Optimum Sample Size</u>
20 Food & Kindred Products	52	.0487
26 Paper & Allied Products	21	.7181
27 Printing & Publishing	21	.0395
28 Chemicals & Allied Products	26	.5231
30 Rubber & Misc. Plastic Products	52	1.6058
32 Stone & Glass	21	2.9510
33 Primary Metals	80	16.7210
34 Fabricated Metals Except Machinery	104	7.7753
35 Machinery Except Electrical	101	8.5075
37 Transportation	<u>81</u>	<u>1.1100</u>
TOTAL	559	40.0000

6. Optimum Sample Allocation Using Standard Deviations of the Proportional Sample

<u>Stratum</u>	<u>Stratum Size</u>	<u>Optimum Sample Size</u>
20 Food & Kindred Products	52	1.9147
26 Paper & Allied Products	21	.5628
27 Printing & Publishing	21	.2573
28 Chemicals & Allied Products	26	1.5480
30 Rubber & Misc. Plastic Products	52	1.5057
32 Stone & Glass	21	1.0383
33 Primary Metals	80	3.9095
34 Fabricated Metals Except Machinery	104	10.5747
35 Machinery Except Electrical	101	6.5191
37 Transportation	<u>81</u>	<u>12.1699</u>
TOTAL	559	40.0000

TABLE 9
RELATIVE COMPARISON OF SAMPLE ALLOCATION TO STRATA

<u>SIC</u>	<u>Experiment</u>	<u>Proportional Allocation</u>	<u>Optimal Allocation</u>
20	2	3	2
26	2	2	1
27	2	2	-
28	2	2	2
30	2	3	2
32	2	2	1
33	4	6	4
34	8	7	10
35	8	7	6
37	<u>8</u>	<u>6</u>	<u>12</u>
TOTAL	40	40	40

Table 9 shows the ultimate distribution of the sample industrial customers (40), into various strata by using (1) sample selection criteria, (2) proportional allocation method, and (3) optimum allocation method. A relative comparison of the three methods from an efficiency standpoint revealed that the allocation of sample members using the sample selection criteria would give minimum variance. As was pointed out earlier, the experimental sample (Column 1 of Table 9) would be 232 times more efficient than the proportionally allocated sample presented in Column 2 of Table 9. We did not use the optimally allocated sample since some of the strata did not meet the design criteria of the experiment, namely that there should be at least two members in each stratum -- one test customer and one control customer.

The above analysis indicates that the practical worker need not be too disturbed about working with samples that are not allocated exactly in optimum fashion.

7. METHODOLOGY FOR HISTORICAL DATA ANALYSIS

To analyze the historical data relating to primary hourly billing demand of the test and control customers, the following methodology was developed. The basic purpose of the historical data analysis was to find, (1) significant customer demand patterns and trends and to identify the underlying factors responsible for the historical patterns; (2) to forecast the demand patterns in the immediate future; and (3) to explore the possibilities for shaping usage trends in the future by adopting certain feasible load management procedures.

The procedure that follows explains the basic steps to identify the customer coincidence period with the system, the potential demand peaks of the customers and the possibilities for load shaping:

- a. After a careful scrutiny of the primary billing demand data, it was decided to select one week in each month--the week in which maximum billing demand occurred for that month.
- b. Monday and weekends were not considered due to low level of demand as compared to the rest of the days in the week. In other words, the analysis focused on the patterns of billing demand for the week pertinent to Tuesday-Friday to represent the normal pattern of electric use.
- c. The average billing demand for the week selected (Tuesday-Friday) in each month was computed.
- d. The statistical measures computed were: average; standard deviation (measure of variation); and the coefficient of variation (measure of consistency). The larger the standard deviation, the greater will be the variation of the individual hourly demands around the mean. Similarly, the smaller the coefficient of variation, the greater the consistency in the hourly demands.
- e. Bartlett's Test was used to test for homogeneity of variances of hourly demands on the assumption that the distribution of the monthly means were approximately normally distributed (Central Limit Theorem).
- f. The same procedure was adopted to see whether there existed seasonal variations in the demand patterns.
- g. The average billing demands (average of all the weeks for 12 months of each year) along with the average loads of the system (Tuesday-Friday) were plotted on the charts for each year.

The dotted horizontal line on the charts represents a 95% confidence limit for each customer process and is called for simplicity the "Adjusted Average Billing Demand". This can also be called the process control line. All the hourly demands above the line indicate that excessive demands are occurring which can be investigated and can be leveled or can be shifted by adopting load management procedures. The sum total of the demands above the adjusted average line gives the magnitude of the customer load that can be shaped.

B. SURVEY METHODOLOGY AND PROCEDURES

1. Objectives

- A. Purpose -- The purpose of our on-site surveys was to accomplish tasks in the following sequence:
1. Document major system processes.
 2. Identify areas of inefficient electricity utilization.
 3. Determine aspects of system processes which could be shifted to off-peak utilization periods.
 4. Determine environmental conditioning changes which may result in better electricity utilization (lighting, heating, cooling, ventilation, etc.)
 5. Identify areas which would benefit from small capital improvements to decrease energy utilization or affect peak usage.
- B. Goal -- The goal was to present to the participating company an effective energy management program identifying the inefficient areas of energy utilization, if any, and developing an efficient and feasible program which would encourage them to participate and implement the recommendation.

2. Survey Procedures

To achieve the stated goals and objectives, four basic steps were followed:

- A. Advance Call
- B. Plant Survey
- C. Data Analysis
- D. Proposal Presentation.

A. Advance Contact of the Customers:

An advance call or initial contact with a prospective participant was conducted by a member of the MPSC Staff, a Detroit Edison Account Representative and a Detroit Edison Project Staff member. At this meeting an overview of the entire project was given to assure company management that all findings would be submitted to them regardless of the effects upon either their or Detroit Edison's system. After assuring confidentiality to the company management, a request was made to ensure the companies' full cooperation and arrangements were made to provide a floor plan with major processing systems superimposed on it, as well as personnel familiar with overall operations in order to complete a load management Survey Form 1.

The following is a list of the principal participants in our survey teams and their basic functions:

1. Assigned Account Representative -- This individual's basic function during all on-site surveys was to be the spokesman for the survey team and assist in the collection of relevant data. This data consisted of listing all electrical consuming devices above 5 horsepower that were associated with specific processing system and follow-up investigation for completion of load management Form 1.
2. Lighting Specialist -- This individual's function was to evaluate all lighting systems and to provide recommendations for more efficient utilization of electric energy for the existing equipment and to recommend the appropriate design, in some cases, to meet the ANSI standards, as compared to the existing system which would provide better utilization of space, better quality, etc.
3. Space Conditioning and Processing Specialist (HVAC) -- The identification of space conditioning and processing equipment was an essential part of all on-site surveys and provided the project staff with important information in the major energy-using segments of the participant's plant. Recommendations by this specialist included more efficient HVAC processes, up-dated technologies, heat loss and/or gain studies, heat recovery and transfer methods.
4. MPSC Staff - Two (2) -- The basic function of these team members was to oversee the methods used by the Edison specialists, to assure the validity of procedures and to make observations for the final report.
5. Consulting Engineer -- The independent consulting engineer was responsible for evaluation of the combined efforts of both Detroit Edison and MPSC personnel by review of the survey methods used and the proposal preparation. He provided on-site appraisal of work-in-progress to assure that major areas of energy utilization were considered and that the analysis was complete.

B. On-Site Survey

Major industrial processes were identified on the floor plan along with other peripheral equipment so the study would encompass the specific process as one entity. All survey data were recorded on a special form (Form 2) and inserted into the participant's file for analysis. Each member of the survey team was responsible for the study and documentation of a portion of the following items:

1. Lighting systems.
2. Areas for timing and/or control devices.
3. Heat recovery application.
4. HVAC systems improvements.
5. Building insulation and structure.
6. Off-hour audits and special testing meters.
7. Potential for off-peak energy utilization.
8. Recovery of process and boiler water.
9. Demand control and/or monitoring systems.
10. General maintenance.
11. Other uses of energy and the potential of transfer to electric.

C. Analysis of Data

The analysis group received all of the information and recommendations previously recorded by the advance and on-site survey teams and coordinated further studies or plant visitations, when necessary, to provide additional detail.

Consolidation of all feasible areas for study, recommendations for control and possible future areas for study were recorded on Summary Form 3. Analysts evaluated the potential and means for shifting energy demand to off-peak hour intervals, improvement in efficient use, costs of control equipment or other capital investment items and non-capital investment costs. This evaluation required close coordination and follow-up by the MPSC and the Detroit Edison Staff along with a review by the consulting engineer.

A summary of capital and non-capital investment costs with energy savings by cost per unit, time-of-day and energy shifted to off-peak loads, was made available to the economic consultant. The economic consultant provided a complete analysis of financial feasibility of load management investments of the individual companies which included the relevant payback periods, average rate of return, and return on capital investments required to implement the complete proposal.

The final responsibility of the survey analysis was to provide a well documented energy management proposal encompassing all areas of conservation for presentation to the management of the particular test customer. The analysis covered the following areas:

1. A cover letter that was personally presented to company management.

- 2.[†] A short synopsis of the overall project objectives.
- 3.[‡] The summary of all data received from the test customer and the recommendations concerning energy management in all areas of energy use, especially in the area of electricity.
- 4.[‡] The complete economic analysis as submitted by the project staff.
5. A three (3) year historical demand profile analysis.

D. Proposal Presentation

The formal proposal was presented to the test customer's top level management by representatives of the MPSC Project Staff, Detroit Edison Project Staff, as well as the account engineer. During this presentation all five areas of the proposal were reviewed and questions answered to encourage a management decision to accept the overall recommendations.

Once the basic concepts were accepted, it was the responsibility of the individuals at the presentation to encourage a written response from the customer to the staff detailing their ideas, proposed actions and overall general response to the project.

C. METHODOLOGY OF THE FINANCIAL ANALYSIS FOR THE LOAD MANAGEMENT PROJECT

The objective of the financial analysis was to provide a means and pro forma for the capital evaluation of the project team's recommended load management investment. The investment criteria used to determine if a subsidy would be required to have industry undertake the investment was the 24-month payback period proposed by representatives from industry. If the investment did not meet the 24-month payback criterion, the amount of investment subsidy required to meet that criterion was determined. The data required for the project team to implement this evaluation were:

- (1) Identification of the load management equipment.
- (2) Capital and installation cost of the equipment.
- (3) Existing electric and gas energy use.
- (4) Electric and gas energy use after load management.
- (5) 1976 electric rates.
- (6) 1976 gas costs.
- (7) Gas cost with load management.
- (8) Peak and off-peak kW and kWh percentages.

Using this information, the dollar value of the energy savings associated with the load management investment was calculated.

Based upon these energy savings, pre-tax profit projections were calculated. In calculating pre-tax profits, depreciation charges are based upon a ten year life of the equipment and all installation costs

are treated as a first year write-off. The adjusted monthly and annualized profits under these assumptions were calculated for two years.

The adjusted annualized pre-tax profits provide the basis of the capital investment evaluation. The capital investment evaluation was made based upon the following assumptions:

- (1) Adjusted annual profits are incremental pre-tax profits.
- (2) Corporate tax provisions are at a 50% rate.
- (3) The investment tax credit is 10%.
- (4) Excess investment tax credits and losses are carried forward to the second year of this project.
- (5) A discount rate of 8%.
- (6) A rate of return on investment standard of 10%.
- (7) A 24-month payback for a 100% cash flow rate.

Based upon these assumptions and the previously determined pre-tax profits, after-tax profits were determined for each of the two years along with the cash flow and discounted cash flow for each of the two years. Cash flow was determined by adding to after-tax profits depreciation charges. The cash flow was then discounted to determine its present value.

The performance measures used for the investment evaluation were the average annual rate of return on investment; the cash flow rate through two years, and the monthly payback period. In calculating the average rate of return on investment, the average after-tax profits over two years were divided by the capitalized project investment. The rate of return on capital, or cash flow rate, was determined by dividing the present value of two-year cash flow by the total project investment capitalized. The monthly payback was calculated by dividing the total capitalized investment by the average monthly present value of two-year cash flow.

Another performance measure that was calculated was the annual equivalent of revenues over costs. Essentially this measure determines the excess of the value of energy savings over the annual amount that would be required to pay back the investment in 10 years and provide an after-tax return on investment of 10%. In effect, this measures the difference in energy savings, or the extra revenues associated with the investment, over what would be considered annual installment payments on the load management investment.

If the investment did not meet the 24-month payback criterion, the amount of investment subsidy needed to meet this criterion was determined. The investment subsidy is that amount of money necessary to bring a deficient cash flow rate up to 100% over two years. The determination of the amount of subsidy was essentially an iterative process requiring adjustments in capitalized investment, depreciation charges, and the investment tax credit.

If installation cost exceeds energy savings in the first years, and after-tax profits are positive in the second year and over the two-

year period, the subsidy would impact the second year's profits and cash flow. An initial point of departure for the iterative process would be to take the difference between the average profits and net capitalized investment for the amount of subsidy. By stimulating various amounts of subsidy and the impact on pre-tax profits because of the changes in depreciation, after-tax profits because of the changes in the investment tax credit, net private capitalized investment, and the year in which the subsidy was received, the amount of subsidy was determined. Based upon the resulting net private capitalized investment, the rate of return on capital, monthly payback, and average rate of return on investment were calculated. The amount of subsidy and the value of the above performance measures with the subsidy are indicated in the cover letter.

The financial analysis is presented in seven schedules that were developed for this project. The schedules are:

- (1a) Financial Summary
- (1b) Annual Equivalent Revenues Less Costs
- (2) Capital Investment Evaluation
- (3) 1976 Energy Costs
- (4) Energy Cost with Load Management
- (5) Energy Savings
- (6) Projected Pre-tax Profits.

An example illustrating the capital evaluation of load management investment of a company is provided in Appendix A of this report. Appendix A is also provided with sample copies of Survey Forms 1, 2, and 3 along with the historical average annual load profiles and an example of historical data analysis of the same company.

CHAPTER III

TECHNICAL SURVEY FINDINGS

- A. Introduction
- B. Summary of Results
and Findings

A. Introduction

This chapter presents a brief summary of the major findings that were derived from the in-depth technical survey analyses of the selected sample of 20 test companies. The basic methodology of the technical surveys and the schedules that were designed to gather data were thoroughly discussed in the preceding chapter.

The basic purpose was to provide (1) the historical energy consumption patterns by type and mix of energy, annual billing costs, proportion of the annual billing costs of energy to annual product sales of each of the test group customers and the aggregate; (2) a summary of the average monthly peak demand (kW*) and energy (kWh*) consumption prior to survey, the estimated average monthly demand and energy consumption after the survey (by implementing load management and other conservation measures - proposal recommendations), assuming that all the proposal recommendations were implemented by the test group customers, the estimated net demand (kW) and energy (kWh) savings that could be attainable and the annual dollar savings that would be expected by implementing the recommended load management and other conservation measures; (3) the financial feasibility of load management investments; and (4) the identification of the initial reactions of the test and control group customers and the general observations about the industry's capabilities, attitudes and expectations about energy management.

It should be observed that the results presented in the ensuing tables and charts were the best estimates of the technical survey team. The results represent the maximum potential electric load reductions attainable if all the energy management recommendations incorporated in each test group customer's proposal were implemented.

The estimated results of this chapter are compared with the results of Chapter IV dealing with actual monitoring of the test. The estimated results are treated as optimums against which actual results are gauged.

*See the explanation of the terms demand (kW) and energy (kWh) in the "Glossary" of terms presented at the end of the report.

B. Summary Results and Findings

1. Annual Energy Consumption, Annual Billing Cost and the Percent of Annual Billing Cost to Total Sales Revenue of the Test Companies in 1975.

Table I presents (a) the individual amounts of different forms of energy consumed by the test companies in their respective units of measurement, (b) the total billing cost of energy in terms of dollars, and (c) the percent shares of the annual energy costs to the total sales revenues of the respective companies. This information was derived from customer survey Form 1 (a sample copy is presented in Appendix A). These survey forms were completed by the customer's management although some of the companies did not provide complete information due to confidentiality.

The basic purpose was to identify (1) an actual historical energy usage pattern by type of energy and the distribution of the different components of energy on the average by the test companies; and (2) to determine the actual percent of the energy billing costs to the respective sales revenues and to determine the aggregate average percent cost to aggregate average sales revenue per customer.

FINDING 1 "The average annual billing cost of energy was approximately 3% of the average total sales revenue for 15 of the 20 test companies for which data were available for 1975. However, the proportions of energy costs with respect to the individual sales revenues varied between a minimum of 1.5% to a maximum of 8%."

TABLE I

ANNUAL ENERGY CONSUMPTION BY 20 TEST COMPANIES AND THE BILLING COST OF ENERGY IN 1975*

SIC Code	Business	Electricity kWh	Natural Gas MCF's	Oil or Other Fuels Gals.	Average Monthly Electric kW	Total Billing Cost \$	Billing Cost % of Gross Sales Revenue
20	Food Products	7,587,600	125,000	20,000	1,457	355,000	2.80
26	Paper Products	4,640,100	13,528	668,593	213	323,600	5.20
27	Printing & Pub.	1,184,796	N.A.	N.A.	380	N.A.	N.A.
28	Chemicals	3,560,640	89,000	50,050	863	216,665	N.A.
30	Rubber Products	5,340,000	91,400	270,000	1,088	373,691	3.70
32	Glass Products	10,057,300	300,663	263,852	1,824	654,000	1.50
33	<u>PRIMARY METALS:</u>						
	Company A	7,507,596	94,545	-0-	2,207	312,000	N.A.
	Company B	2,546,640	56	-0-	390	125,400	2.80
34	<u>FABRICATED METALS:</u>						
	Company A	1,753,000	5,000	-0-	593	45,500	N.A.
	Company B	5,359,200	99,832	-0-	1,506	349,000	3.40
	Company C	2,400,000	35,484	-0-	650	63,000	7.80
	Company D	2,731,320	16,227	-0-	588	103,400	8.00
35	<u>MACHINERY:</u>						
	Company A	2,427,120	1,171	-0-	138	70,705	1.60
	Company B	1,974,276	38,280	-0-	387	87,000	1.50
	Company C	1,479,072	28,140	-0-	353	67,000	1.50
	Company D	6,634,560	119,398	30,000	1,791	369,960	2.10
37	<u>TRANSPORTATION:</u>						
	Company A	1,829,032	41,765	8,710	387	96,454	3.20
	Company B	1,700,000	16,500	-0-	361	124,000	1.80
	Company C	1,225,000	61,000	50,000	489	140,019	3.50
	Company D	<u>2,395,604</u>	<u>15,500</u>	<u>-0-</u>	<u>484</u>	<u>75,000</u>	<u>N.A.</u>
	TOTAL	74,132,856	1,192,489	1,361,205	16,749	3,954,394	50.40
	AVERAGE	3,706,643	62,763	71,642	838	208,126	3.36**

*The term energy is used in the general context to denote electricity, natural gas, oils and miscellaneous. The figures were derived from Customer Survey Form I.

**Based on 15 companies.

N.A. = Not Available

TABLE 2

ANNUAL ENERGY CONSUMPTION BY Btu's OF 19 TEST COMPANIES FOR 1975*

	<u>Billion Btu's</u>	<u>% of Total</u>
Electricity	219	20
Natural Gas	775	71
Oils & Miscellaneous	<u>99</u>	<u>9</u>
TOTAL	1,093	100

*Using an average seasonal efficiency factor of 65%.

Derived from Table 1 using the appropriate conversion factors which are given in the Technical Appendix - D.

2. Annual Energy Consumption by Btu's of 19 Test Companies for 1975.

In Table 1 of the preceding section, the total number of units of energy consumed by test companies by type of energy was presented. In Table 2, it is shown that the individual amounts of energy presented in Table 1 are expressed in terms of a common denominator called the Btu's for drawing valid comparisons. The British thermal unit (Btu) is defined as the quantity of heat required to raise the temperature of one pound of water to 1° Fahrenheit. Further, the actual Btu's of natural gas and oils are reduced by using an average seasonal efficiency factor of 65%. A seasonal efficiency factor is the ratio of usable Btu's delivered to the process as compared to the quantity of usable Btu's delivered to the manufacturing process equipment, such as boilers, furnaces, etc.

$$\text{Efficiency} = \frac{\text{Usable Btu's to Process}}{\text{Usable Btu's to the Equipment}}$$

FINDING 2 "Of the actual total Btu's consumed by the test companies in 1975, on the average....

20% was electric,
71% was natural gas, and
9% was oils and miscellaneous forms
of energy."

In other words, the companies derived approximately 80% of their total Btu consumption from energy sources other than electricity. Further, the annual natural gas Btu consumption was about four times that of the annual Btu consumption of electrical energy. Chart I shows the above observation more clearly.

Chart I

Annual Energy Consumption by Btu's of 19 Test Companies for 1975*

*Derived from Tables 1 and 2.

3. Distribution of Annual Billing Cost of Energy Paid by Test Companies in 1975.

In the preceding two sections, the analysis of the actual energy utilization of the test companies was presented. Table 3 shows the breakdown of the individual annual billing costs of these energies and the total annual billing costs paid by these companies.

The purpose was to identify the proportional distribution of these costs in the annual energy expenditures of these companies and to find the relative costs of these energies in terms of their Btu consumption. The following conclusions emerge from Table 3.

FINDING 3-A "The average percent distribution of the annual billing costs of the companies were:

51% of the cost was electric,
39% of the cost was natural gas, and
10% of the cost was oils and miscellaneous forms of energy."

FINDING 3-B "By comparing the results of Table 2 dealing with the percentage distribution of the total Btu consumption with the percentage distribution of the total costs, presented in Tables 3 and 4, it can be concluded that on the average, the companies paid over 50% of the annual billing cost for utilizing 20% of their energy in the form of electricity. The companies paid less than 50% of the total cost for consuming 80% of Btu's in the form of natural gas and oils. Comparing the cost of gas Btu consumption with the cost of electric Btu consumption, it is apparent that the relative cost of electricity in 1975 was 4.6 times* that of the cost of natural gas."

*The cost of 219 billion electric Btu's was \$2,028,753.
The cost of 874 billion gas and oil Btu's was \$1,925,641.
Therefore, the cost/billion electric Btu's was \$10,086.
The cost/billion gas and oil Btu's was \$2,203.
The relative cost of electricity = $\frac{9,306}{2,203} = 4.578$.

TABLE 3

DISTRIBUTION OF ANNUAL BILLING COST OF ENERGY PAID BY TEST COMPANIES IN 1975*

SIC Code	Business	ELECTRICITY		NATURAL GAS		OTHER FUELS		Annual Billing Cost
		Billings	% of Total	Billings	% of Total	Billings	% of Total	
20	Food Products	210,000	59	125,000	35	20,000	6	355,000
26	Paper Products	116,496	36	22,652	7	184,452	57	323,600
27	Printing & Pub.	N.A.	-	N.A.	-	N.A.	-	N.A.
28	Chemicals	103,999	48	93,166	43	19,500	9	216,665
30	Rubber Products	156,950	42	142,003	38	74,738	20	373,691
32	Glass Products	261,600	40	327,000	50	65,400	10	654,000
33	<u>PRIMARY METALS:</u>							
	Company A	209,040	67	102,860	33	-	-	312,000
	Company B	46,398	37	79,002	63	-	-	125,400
34	<u>FABRICATED METALS:</u>							
	Company A	41,000	90	4,500	10	-	-	45,500
	Company B	174,500	50	174,500	50	-	-	349,000
	Company C	44,730	71	18,270	29	-	-	63,000
	Company D	73,414	71	29,986	29	-	-	103,400
35	<u>MACHINERY:</u>							
	Company A	58,990	83	11,715	17	-	-	70,705
	Company B	48,720	56	38,280	44	-	-	87,000
	Company C	38,860	58	28,140	42	-	-	67,000
	Company D	199,778	54	151,584	41	18,498	5	369,960
37	<u>TRANSPORTATION:</u>							
	Company A	53,050	55	40,511	42	2,893	3	96,454
	Company B	79,360	64	44,640	36	-	-	124,000
	Company C	51,808	37	84,011	60	4,200	3	140,019
	Company D	<u>60,060</u>	77	<u>17,940</u>	23	<u>-</u>	-	<u>78,000</u>
Total Billing Cost		2,028,753		1,535,960		389,681		3,954,394
Average Billing Cost		106,776		80,840		20,509		208,125
Percent of Billing Cost		\$1		39		10		100

*Derived from Customer Survey Form L.

TABLE 4
DISTRIBUTION OF AVERAGE TOTAL BILLING COST
OF ENERGY CONSUMED BY TEST COMPANIES IN 1975 BY TYPE OF ENERGY

<u>TYPE OF ENERGY</u>	<u>AVERAGE BILLING COST</u>	<u>PERCENT OF TOTAL</u>
Electricity	\$106,776	51%
Natural Gas	80,840	39
Oils and Other Fuels	<u>20,509</u>	<u>10</u>
TOTAL	\$208,125*	100%

*Derived from Table 3

CHART II
PERCENTAGE DISTRIBUTION OF TOTAL BILLING COST
OF ENERGY PAID BY TEST COMPANIES IN 1975*

*Derived from Tables 3 and 4

4. Summary of Estimated Monthly Peak Demand (kW) Changes Due to Electric Load Management.

Table 5 was derived from the summary analyses of the final proposal recommendation made after the plants' on-site technical surveys were completed during 1976. The column representing "Before Proposal" monthly demand (kW) shows the average of the actual demand (kW) of the number of months prior to survey conducted during the earlier part of 1976. The column representing "After Proposal" shows the estimated monthly demand (kW) if all the recommendations of the proposals were implemented by the test group customers. Column 3 indicates the total change in demand (kW) due to load management and the last column of Table 5 shows the percent change as compared to the column representing "Before Proposal kW". It should be observed that in one case, SIC 37 - Company A, there occurred an increase in peak demand due to increase in the loads attributable to the HVAC system. The details of the load changes by areas are itemized in Table 6 which are highlighted in the next section. The basic purpose here is to focus on the maximum number of peak kW reduction and the overall aggregate maximum average percentage reduction in peak demand that could be expected due to load management.

FINDING 4 "The overall total net reduction per month in peak demand was estimated at 1,220 kilowatts which represented about 7%, on the average, of the total monthly peak demand. It should be noted, however, that 7% reduction in peak demand does not necessarily imply that there will be such a reduction on a total Detroit Edison system-wide basis. This aspect is discussed in Chapter V of the report."

TABLE 5.

SUMMARY OF MONTHLY PEAK DEMAND (kW) CHANGES

TEST COMPANIES - 1976*

STC Code	Business	Before Proposal** kW	After Proposal*** kW	Total Change kW	Change %
20	Food Products	1,480	1,430	(50)	(3.38)
26	Paper Products	800	693	(107)	(13.38)
27	Printing & Publishing	-	-	-	-
28	Chemicals	860	850	(10)	(1.16)
30	Rubber Products	1,100	1,036	(64)	(5.82)
32	Glass Products	1,950	1,750	(200)	(10.26)
33	<u>PRIMARY METALS:</u>				
	Company A	2,000	1,926	(74)	(3.70)
	Company B	360	340	(20)	(5.56)
34	<u>FABRICATED METALS:</u>				
	Company A	500	479	(21)	(4.20)
	Company B	1,450	1,337	(113)	(7.79)
	Company C	600	600	-	-
	Company D	600	600	-	-
35	<u>MACHINERY:</u>				
	Company A	500	430	(70)	(14.00)
	Company B	400	385	(15)	(3.75)
	Company C	380	270	(110)	(28.95)
	Company D	1,750	1,427	(323)	(18.46)
37	<u>TRANSPORTATION:</u>				
	Company A	380	387	7	1.84
	Company B	400	350	(50)	(12.50)
	Company C	550	550	-	-
	Company D	470	470	-	-
	TOTAL	16,530	15,310	(1,220)	
	AVERAGE	770	806	(64)	(7.38)

* Derived from Tables 3 and 4 of the economic analysis of the proposals of the individual test companies

** Based on the average monthly demand (kW) of each customer prior to survey in 1975

*** Refers to 1976 demand (kW) after survey was conducted

5. A Summary of Estimated Monthly kW Changes by Specific Areas Due to Load Management.

The estimated maximum net monthly change in kW (1220) due to load management, presented in Table 5, was the net result of the changes that occurred primarily in the following four major areas: (1) Lighting; (2) HVAC; (3) Processing; and (4) Miscellaneous Areas, which include (a) water heaters, (b) heat recovery systems, (c) air compressors, (d) electric forklift chargers, and (e) proposed demand control systems. The estimated maximum decreases in kW, the increase in kW, and the net change in each case are presented in Table 6. The objective here was to identify the areas in which there existed the maximum possibility for peak demand reduction.

From the analysis of the results presented in Tables 6 and 7, the following conclusions are evident.

FINDING 5 "The percentage net reductions in peak demand were in the following rank order:

<u>Area</u>	<u>Percent of Peak Demand Reduction</u>	<u>Distribution of 7.4% Reduction in Peak Demand</u>
Lighting	40	3.0
Processing	34	2.5
Miscellaneous	19	1.4
HVAC	<u>7</u>	<u>.5</u>
TOTAL	<u>100</u>	<u>7.4</u>

Comment: It was found from the summary analysis of the proposals that, of the total electric load consumption (actual percentage use of the connected load represents approximately 70-75%), the proportional use for each of the areas on the average was:

<u>Areas</u>	<u>Average Use Percent</u>	<u>Range</u>	
		<u>Minimum Percent</u>	<u>Maximum Percent</u>
Processing (Manufacturing)	70	63.0	89.0
Lighting	9	6.2	13.0
HVAC	13	9.0	16.0
Miscellaneous	<u>8</u>	4.0	11.0
TOTAL	<u>100</u>		

Table 6

ESTIMATED MONTHLY KWCHANGES BY SPECIFIC AREAS DUE TO LOAD MANAGEMENT*

Test Companies

SIC Code	Business	Load Reductions				Total Reductions kW	Load Increases				Total Increases kW	Net Change kW
		LTG.	KW HVAC	PROC.	MISC.		LTG.	KW HVAC	PROC.	MISC.		
20	Food Products	-	-	50	-	50	-	-	-	-	-	(50)
26	Paper Products			100	18 ¹	118	-	11	-	-	11	(107)
27	Printing & Pub- lishing	-	-	-	-	-	-	-	-	-	-	-
28	Chemicals	1	-	16	30	47	7	10	-	20	37	(10)
30	Rubber Products	40	-	-	24 ^{1,4}	64	-	-	-	-	-	(64)
32	Glass Products	56	50	40 ⁵	70	216	6	10	-	-	16	(200)
33	<u>Primary Metals</u>											
	Company A	11	-	60	4 ¹	75	1	-	-	-	1	(74)
	Company B	2	10	20	-	32	12	-	-	-	12	(20)
34	<u>Fabricated Metals</u>											
	Company A	-	-	-	21 ^{1,4}	21	-	-	-	-	-	(21)
	Company B	13	-	100	-	113	-	-	-	-	-	(113)
	Company C	0	0	0	0	0	0	0	0	0	0	0
	Company D	0	0	0	0	0	0	0	0	0	0	0
35	<u>Machinery</u>											
	Company A	17	25	20	18 ¹	80	-	10	-	-	10	(70)
	Company B	-	-	10	15 ¹	25	-	6	3	1	10	(15)
	Company C	46	70	-	30	126	8	8	-	-	16	(110)
	Company D	492	-	-	24 ¹	516	184	-	-	9	193	(323)
37	<u>Transportation</u>											
	Company A	-	-	-	3	3	1	9	-	-	10	7
	Company B	25	-	-	30 ³	55	-	5	-	-	5	(50)
	Company C	0	0	0	0	0	0	0	0	0	0	0
	Company D	0	0	0	0	0	0	0	0	0	0	0
	TOTAL	703	155	416	267	1,541	219	69	3	30	321	(1,220)

¹Water heaters; ²Heat recovery systems; ³Air compressor; ⁴Electric fork lift chargers; & ⁵Proposed Demand Control Systems

Bracketed figures indicate reductions.

*Proposal Recommendations.

TABLE 7

ESTIMATED NET REDUCTION IN PEAK DEMAND (kW) OF THE TEST COMPANIES
DUE TO ELECTRIC LOAD MANAGEMENT*

<u>AREAS</u>	<u>ESTIMATED NET PEAK DEMAND REDUCTION</u>	<u>% NET REDUCTION TO TOTAL kW</u>	<u>DISTRIBUTION OF 7.4% REDUCTION IN PEAK DEMAND</u>
Lighting	484	40%	3.0%
HVAC	86	7	.5
Processing	413	34	2.5
Miscellaneous	<u>237</u>	<u>19</u>	<u>1.4</u>
TOTAL	1220	100%	7.4%

*Derived from Table 6

CHART III

SUMMARY OF AREAS FOR NET LOAD REDUCTION*

*Derived from Table 6 and Table 7

6. Summary of the Estimated Monthly Kilowatt-hour Changes Due to Load Management.

It was shown in the previous section that the net reduction in peak demand (kW) was 7% per month. Table 8 shows the net absolute change in energy (kWh) that was expected if all the recommendations of the proposals were implemented. Further, Table 8 indicates the estimated net peak and off-peak kilowatt-hour reductions. One of the objectives of the study was to determine to what extent the on-peak loads of the test customers could be reduced/shifted to off-peak periods as a result of load management.

The following conclusions can be derived from Table 8.

FINDING 6-A "The overall average net reduction in kilowatt-hours/month/customer was estimated to be 11,478 which is about 4% of the total monthly kWh consumption of 19 test companies."

FINDING 6-B "Of the above total kWh reduction, approximately 56% was from on-peak and 44% was from off-peak."

TABLE B
SUMMARY OF MONTHLY KILOWATT-HOUR CHANGES

TEST COMPANIES - 1976*

SIC Code	Business	Before Proposal**			After Proposal***			Change			Percent Change		
		Total kWh	On Peak kWh	Off Peak kWh	Total kWh	On Peak kWh	Off Peak kWh	Total kWh	On Peak kWh	Off Peak kWh	Total	On Peak	Off Peak
20	Food Products	592,000	236,800	355,200	592,000	236,800	355,200	-0-	-0-	-0-	--	--	--
24	Paper Products	387,000	193,500	193,500	389,000	194,500	194,500	2,000	1,000	1,000	.52	.52	.52
27	Printing & Pub.	--	--	--	--	--	--	--	--	--	--	--	--
28	Chemicals	310,000	155,000	155,000	298,000	149,000	149,000	(12,000)	(16,000)	(16,000)	(23.23)	(23.23)	(23.23)
30	Rubber Products	400,000	240,000	160,000	377,500	226,500	151,000	(22,400)	(13,400)	(8,900)	(5.6)	(5.6)	(5.6)
32	Glass Products	754,000	542,800	211,200	693,200	499,104	194,096	(60,800)	(43,776)	(17,024)	(8.06)	(8.06)	(8.06)
33	PRIMARY METALS:												
	Company A	487,000	243,500	243,500	488,200	244,100	244,100	1,200	600	600	.25	.25	.25
	Company B	170,000	85,000	85,000	180,000	90,000	90,000	10,000	5,000	5,000	5.88	5.88	5.88
34	FABRICATED METALS:												
	Company A	149,000	96,850	52,150	149,000	96,850	52,150	-0-	-0-	-0-	--	--	--
	Company B	428,750	237,250	191,500	424,000	234,400	169,600	(4,750)	(2,850)	(1,900)	(1.11)	(1.11)	(1.11)
	Company C	163,000	97,800	65,200	163,000	97,800	65,200	-0-	-0-	-0-	--	--	--
	Company D	230,000	149,500	80,500	230,000	149,500	80,500	-0-	-0-	-0-	--	--	--
35	MACHINERY:												
	Company A	210,000	126,000	84,000	209,000	126,000	80,000	(10,000)	(6,000)	(4,000)	(4.76)	(4.76)	(4.76)
	Company B	160,000	100,000	60,000	170,000	110,500	59,500	10,000	6,500	3,500	6.25	6.25	6.25
	Company C	87,000	47,500	49,500	77,600	38,800	38,800	(9,400)	(6,700)	(4,700)	(10.80)	(10.80)	(10.80)
	Company D	570,000	316,000	254,000	440,000	264,000	176,000	(130,000)	(42,000)	(28,000)	(13.73)	(13.73)	(13.73)
40	TRANSPORTATION:												
	Company A	152,000	98,000	53,200	173,069	118,950	54,119	21,069	20,150	919	13.86	13.86	13.86
	Company B	130,000	78,000	52,000	122,000	73,200	48,800	(8,000)	(4,800)	(3,200)	(6.15)	(6.15)	(6.15)
	Company C	110,000	60,500	49,500	105,000	57,750	47,250	(5,000)	(2,750)	(2,250)	(4.55)	(4.55)	(4.55)
	Company D	145,000	101,500	43,500	148,000	101,500	43,500	-0-	-0-	-0-	--	--	--
	TOTAL	5,574,750	3,216,380	2,358,370	5,356,669	3,093,314	2,263,355	(218,081)	(123,066)	(95,015)	(3.91)	(3.93)	(4.03)
	AVERAGE	293,498	169,283	124,125	281,930	162,806	119,124	(11,478)	(6,477)	(5,001)			

*Derived from Tables 3 and 4 of the economic analysis of individual companies.

**Based on the average monthly kWh consumption of each test customer prior to survey in 1976.

***Monthly kWh consumption after survey was conducted.

-- Peak period is defined between 9 a.m. to 9 p.m. during Monday-Friday.

7. Estimated Monthly Reductions/Savings in Energy (kWh) Due to Load Management Compared to Actual Energy Consumption in 1975.

Table 9 indicates the actual consumption (kWh) in 1975 and the estimated total kWh consumption with load management.

FINDING 7 "The overall total monthly savings in energy would be about 208,050 kWh for the 20 test companies. This savings is about 4% of the total energy consumption in 1975."

Comment: It should be noted, however, that there would be no savings expected in 5 out of 20 test companies and an equal number of test customers would expect some increases as a result of (1) new and more efficient lighting system, and (2) new heat recovery systems.

TABLE 1

ESTIMATED MONTHLY SAVINGS IN ENERGY (KWH) DUE TO LOAD MANAGEMENT
 COMPARED TO ACTUAL ENERGY CONSUMPTION IN 1975

TEST COMPANIES					
SIC Code	Business	Energy Consumption (kWh) 1975	Energy Consumption with Load Mgmt. kWh	Savings kWh	% Savings
20	Food Products	632,300	630,300	2,000	0.32
26	Paper Products	386,675	388,675	(2,000)	(0.52)
27	Printing & Pub.	98,735	98,735	0	0
28	Chemicals	296,720	238,000	58,720	19.80*
30	Rubber Products	445,000	422,600	22,400	5.02
32	Glass Products	838,108	808,108	30,000	3.58
33	<u>PRIMARY METALS:</u>				
	Company A	625,633	626,833	(1,200)	(0.19)
	Company B	217,320	222,220	(4,900)	(2.25)
34	<u>FABRICATED METALS:</u>				
	Company A	146,083	146,083	0	0
	Company B	446,600	441,850	4,750	1.06
	Company C	200,000	200,000	0	0
	Company D	227,610	227,610	0	0
35	<u>MACHINERY:</u>				
	Company A	202,260	192,260	10,000	4.94
	Company B	164,523	174,523	(10,000)	(6.08)
	Company C	123,256	113,856	9,400	7.63
	Company D	552,880	445,000	107,880	19.51*
37	<u>TRANSPORTATION:</u>				
	Company A	152,419	184,419	(32,000)	(21.00)**
	Company B	141,666	133,666	8,000	5.65
	Company C	102,083	97,083	5,000	4.89
	Company D	<u>182,967</u>	<u>182,967</u>	<u>0</u>	<u>0</u>
	TOTAL	6,182,838	5,974,788	208,050***	3.36

*New and more efficient lighting system.

**Low heat recovery system.

***Estimated aggregate kilowatt hour by 20 test companies after implementation of proposed recommendations.

TABLE 1/1

PRIMARY AREAS FOR MONTHLY kWh CHANGES DUE TO LOAD MANAGEMENT (COMPARED TO 1977 kWh CONSUMPTION)

TEST COMPANIES - 1976

SET CODE	BUSINESS	REDUCTIONS (kwh)				TOTAL REDUCTION	INCREASES (kwh)				TOTAL INCREASE	NET CHANGE LPH
		EEG	U.F.	Proc	Misc		EEG	MISC	Proc	Misc		
20	Food Products	-	-	2,000	-	2,000	-	-	-	-	-	2,000
26	Paper Products	-	-	-0-	2,000	2,000	-	4,000	-	-	4,000	(2,000)
27	Printing & Pub	-0-	-0-	-0-	-0-	-0-	-0-	-0-	-0-	-0-	-0-	-0-
28	Chemicals	3,900	-	8,000	\$7,970*	69,870	2,450	3,500	-	5,200	11,150	\$8,720
30	Rubber Products	16,000	-	-	6,400	22,400	-	-	-	-	-	22,400
32	Glass Products	14,000	5,400	10,000	7,000	36,400	2,400	4,000	-	-	6,400	30,000
33	<u>ORGANIC METALS</u>											
	Company A	3,850	-	-0-	-0-	3,850	400	-	-	4,650	5,050	(13,200)
	Company B	300	800	-0-	-	1,100	6,000	-	-	-	6,000	(4,900)
34	<u>FABRICATED METALS</u>											
	Company A	-	-	-	-0-	-	-	-	-	-	-	-
	Company B	4,750	-	-0-	-	4,750	-	-	-	-	-	4,750
	Company C	-	-	-	-	-	-	-	-	-	-	-
	Company D	-	-	-	-	-	-	-	-	-	-	-
35	<u>NONFERROUS</u>											
	Company A	9,500	4,200	-0-	-0-	12,700	-	2,700	-	-	2,700	10,000
	Company B	-	-	5,000	6,600	11,600	-	3,000	2,000	16,600**	21,600	(10,000)
	Company C	14,500	200	-	-0-	14,800	3,000	2,400	-	-	5,400	9,400
	Company D	177,120	-	-	-0-	177,120	65,640	-	-	3,800	69,240	107,880
37	<u>TRANSPORTATION</u>											
	Company A	-	-	-	2,000	2,000	500	3,000	-	30,580**	34,000	(32,000)
	Company B	7,700	-	-	-	7,700	-	2,700	-	-	2,700	5,000
	Company C	10,000	-	-	-0-	10,000	-	2,000	-	-	2,000	8,000
	Company D	-0-	-0-	-0-	-0-	-0-	-0-	-0-	-0-	-0-	-0-	-0-
	TOTAL	260,720	10,600	25,000	81,970	378,290	80,190	27,300	2,000	60,550	170,240	208,050
	AVERAGE	13,722	530	1,316	4,314	19,910	4,231	1,437	105	3,187	8,960	10,950

*Increases are computed using 19 customers

**E (1) Bracketed figures indicate net increases

(2) Dash lines indicate the areas in which there were no recommendations for changes in demand/energy consumption

(3) Zero's indicate the areas where changes in demand resulted in no changes in kWh consumption

*Indicates kWh reduction due to removal of obsolete equipment

**Attributable to increased utilization of energy due to heat recovery systems and additional lighting during off-peak periods

TABLE 11

ESTIMATED NET kWh REDUCTIONS BY AREA DUE TO LOAD MANAGEMENT
COMPARED TO 1975 kWh CONSUMPTION

TEST COMPANIES - 1976

<u>Areas</u>	<u>Net kWh Reduction/Month</u>	<u>Average Net kWh Reduction/Month</u>	<u>% of Total</u>	<u>Distribution Of Total Savings %</u>
Lighting	180,330	9,491	87.0	2.91
HVAC	(16,700)	(879)	(8.0)	(.27)
Processing	23,000	1,211	11.0	.37
Miscellaneous	<u>21,420</u>	<u>1,127</u>	<u>10.3</u>	<u>.35</u>
TOTAL NET REDUCTION	208,050	10,950	100.0	3.36

Bracketed figures indicate increases.

Derived from Table 9 and Table 10.

8. Summary Areas for Monthly kWh Changes Due to Load Management Compared to 1975 kWh Consumption by the Test Companies.

Table 9 shows the total net kWh reduction that would be expected due to load management compared to 1975 kWh consumption by the test companies. Table 10 shows the areas in which these net reductions would occur. Table 11 presents a summary of the net reductions and percentage net reductions by specific areas within the plant.

Tables 10 and 11 suggest the following condition:

FINDING 8 "The maximum reduction (87%) in kWh would be expected in lighting, followed by processing (11%), miscellaneous (10%), and an increase in the order of 8% would be expected in HVAC."

The distribution of the total percentage savings (3.36%) would be:

<u>Area</u>	<u>Percent</u>
Lighting	2.91
Processing	.37
Miscellaneous	.35
HVAC	(.27)
TOTAL	3.36%

TABLE 12.

ESTIMATED PERCENTAGE MONTHLY REDUCTION IN DEMAND AND ENERGY
DUE TO LOAD MANAGEMENT - 1976

TEST COMPANIES			
SIC Code	Business	% Peak Demand (kW) Reduction	% Energy (kWh) Reduction
20	Food Products	3.38	--
26	Paper Products	13.38	(.52)*
27	Printing & Publishing	--	--
28	Chemicals	1.16	23.23
30	Rubber Products	5.82	5.60
32	Glass Products	10.26	8.06
33	<u>PRIMARY METALS:</u>		
	Company A	3.70	(.25)*
	Company B	5.56	(5.88)*
34	<u>FABRICATED METALS:</u>		
	Company A	4.20	--
	Company B	7.79	1.11
	Company C	--	--
	Company D	--	--
35	<u>MACHINERY:</u>		
	Company A	14.00	4.76
	Company B	3.75	(6.25)*
	Company C	28.95	10.80
	Company D	18.46	13.73
37	<u>TRANSPORTATION:</u>		
	Company A	(1.84)*	(13.86)*
	Company B	12.50	6.15
	Company C	--	4.55
	Company D	--	--
	Average Percent Reduction/ Customer	<u>6.34</u>	<u>2.70</u>
	Overall Percentage Reduction of 19 Test Customers together	7.34	3.91

*Increases in Energy Consumption

Derived from Tables 5 and 8.

9. Estimated Percentage Monthly Reductions in Demand (kW) and Energy (kWh) Due to Load Management.

In Tables 5 and 8 of this chapter, the potential electric savings in kilowatts (kW) and kilowatt-hours was shown. Table 12 provides a summary picture of these potential savings in percentages. It also provides an average percent savings per customer and the overall percent savings of the 19 test customers taken together. The results indicate the following conclusions:

FINDING 9-A "The overall monthly savings in peak demand (kW) would be about 7% for the 19 customers taken together compared to current consumption in 1976 due to load management; and the average reduction per customer/month in peak demand would be close to 6%. However, excluding those companies in which no reductions were expected and deleting the company which would experience higher use in demand, the expected peak demand reduction would be about 10%."

FINDING 9-B "The overall monthly savings in energy (kWh) for the 19 test companies would be approximately 4%; whereas the average savings in energy would be approximately 3%."

A close observation of Table 12 indicates that in 4 of the 18 cases the reductions in peak demand (kW) were followed by increases in energy (kWh) and in one case (SIC 37 - Company A) there was an increase in both demand and energy. The increases in use of electrical energy were primarily attributable to additional lighting, heating and processing changes, some of which were dictated by ANSI* standards, employee safety and comfort, and to minimize product rejections. Explanations for these increases were provided in their proposals.

* ANSI = American National Standards Institute

10. Estimated Monthly Reduction in Electrical Energy Due to Load Management by Industry Groups.

Table 13 details the average percent of monthly reductions in peak demand (kW) and energy (kWh) per SIC group, and the overall percent reduction in demand and energy of the total group. The purpose was to see the percentage reduction by SIC groups. Table 13 suggests the following conclusions:

FINDING 10-A "Although the average monthly reduction in peak demand per SIC group was about seven percent, the monthly reductions of the individual sic groups varied between a minimum of one percent to a maximum of 17 percent. Machinery, paper products, and glass products showed more than 10 percent reduction in peak demand usage, and the estimated reductions in other SIC groups were less than six percent."

FINDING 10-B "On the energy (kWh) side, the picture was different. Three of the SIC groups (paper products, primary metals, and transportation) showed increases in energy consumption compared to the reductions in peak demand. The average on/off-peak reduction per SIC group was about four percent each."

TABLE 13

ESTIMATED MONTHLY REDUCTION IN ELECTRICAL ENERGY DUE TO
LOAD MANAGEMENT BY INDUSTRY GROUPS

SIC GROUPS	Business	% Peak Demand (kW) Reduction	% Energy (kWh) Reduction		
			On Peak	Off Peak	Total
20	Food Products	3.38	--	--	--
26	Paper Products	13.38	(.52)*	(.52)*	(.52)*
28	Chemicals	1.16	23.23	23.23	23.23
30	Rubber Products	5.82	5.60	5.60	5.60
32	Glass Products	10.26	8.06	8.06	8.06
33	Primary Metals	4.63	(3.06)*	(3.06)*	(3.06)*
34	Fabricated Metals	3.00	0.37	0.37	0.37
35	Machinery	16.29	5.76	5.76	5.76
37	Transportation	<u>2.67</u>	<u>(0.79)</u>	<u>(0.79)</u>	<u>(0.79)</u>
Average Reduction per SIC Group		<u>6.73</u>	<u>4.29</u>	<u>4.29</u>	<u>4.29</u>
Overall Reduction (%) of the Total Group		7.38	3.83	4.03	3.91

* Increases in Energy Consumption.

The customer representing SIC 27 is not included since no formal proposal was made.

Derived from Tables 5 and 8.

11. Estimated Current Annual Energy Cost of the Test Companies and the Energy Cost with Load management and the Annual Dollar Savings.

In the earlier sections of this chapter, we presented the analysis of actual energy consumption in 1975 and the billing costs of the energy consumed, and the analysis of 1976 electric consumption, and the estimated reductions in electrical energy that were expected due to electric load management. In this section, and the following sections, the analysis of the 1976 energy costs (assuming 1976 rates), the expected dollar savings using 1976 rates, and the economic feasibility of the load management capital investments are presented.

Table 14 shows annual energy costs for 1976 (electricity and natural gas) of the test companies; and the estimated energy costs and the annual dollar savings that were expected with load management. The cost of oils and miscellaneous forms of energy were not available in detail. Approximately 10 percent of 1976 and estimated gas cost includes the cost of oils and miscellaneous forms of energy.

FINDING 11 "On the average, the companies would expect to save about \$7,974 if all the proposal recommendations were implemented and at 1976 rates. This average dollar amount represents approximately four percent savings annually, compared to 1976* average annual billing costs of energy."

*The new rates went into effect on May 28, 1977. The primary supply rates applicable to sample test and control customers are presented in Appendix D of this report.

TABLE 14.

ESTIMATED ANNUAL ENERGY COST FOR 1976 AND ENERGY COST WITH LOAD MANAGEMENT

TEST COMPANIES

Company Code	Business	1976				With Load Management				Total Annual Savings	
		Electricity Cost \$	%	Natural Gas Cost \$	Total Cost \$	Electricity Cost \$	%	Natural Gas Cost \$	Total Cost \$		
24	Food Products	204,595	62	125,000	329,595	200,995	62	125,000	325,995	3,600	1.10
26	Paper Products	122,616	56	97,000	219,616	115,236	54	96,600	211,836	7,780	3.54
27	Printing & Publishing	-	-	-	-	-	-	-	-	-	-
28	Chemicals	118,000	55	95,000	209,000	101,184	51	90,000	191,184	17,816	8.52
37	Textile Products*	147,360	39	226,337	373,697	138,935	27	226,337	365,272	8,425	2.25
32	Glass Products*	271,053	41	392,170	663,223	246,118	39	392,170	638,288	24,935	3.76
33	Primary Metals										
	Company A	225,816	68	168,990	394,806	220,690	68	166,080	386,770	8,136	2.06
	Company B	54,480	42	75,709	130,189	54,720	42	75,200	129,920	269	0.20
34	Secondary Metals										
	Company A	61,568	-	N/A	61,568	60,056	-	N/A	60,056	1,512	N/A
	Company B	177,459	49	188,224	365,683	168,585	47	188,224	356,809	8,874	2.43
	Company C	70,975	71	29,000	99,975	70,975	71	28,400	99,375	600	0.60
	Company D*	82,660	74	29,000	111,660	82,660	74	29,000	111,660	-0-	-0-
35	Highways										
	Company A	11,784	87	13,000	24,784	65,040	86	10,500	75,540	7,244	29.25
	Company B	56,256	62	34,800	91,056	56,892	64	31,800	88,692	2,364	2.60
	Company C*	41,976	67	20,140	62,116	32,477	54	23,140	55,617	9,499	15.35
	Company D	212,904	64	119,000	331,904	177,720	61	115,000	292,720	39,184	11.81
36	Transportation										
	Company A	53,443	55	42,954	96,397	57,717	59	40,254	97,971	(1,574)	(1.63)
	Company B	50,952	53	44,640	95,592	45,989	51	43,640	89,629	5,963	6.24
	Company C	58,212	41	84,000	142,212	57,366	41	83,400	138,766	1,446	2.42
	Company D*	58,896	77	17,937	76,833	59,896	77	17,937	77,833	-0-	-0-
TOTAL**		2,075,445		1,745,976	3,821,421	1,952,203		1,725,676	3,677,879	143,542	
AVERAGE***		115,302	59	96,899	212,201	108,456	58	96,871	204,327	7,974	3.76
OVERALL PERCENT			54				53				3.76

*Includes about 10 percent towards the cost of oils and other forms of energy.

**Totals are pertinent to 18 Test Customers. Company A at SIC 34 is deleted for computing the average.

***Average per Customer.

12. Estimated Annual Dollar Savings Due to Load Management.

Table 15 provides (1) the average annual cost by major types of energy consumed in 1976, (b) the estimated average annual cost with load management, (c) the average annual savings, and (d) the overall percent savings compared with 1976 cost.

FINDING 12-A "The average annual billing cost* of electricity in 1976 represented about 59% of the total cost which was 8% higher than 1975 average billing cost shown in Table 3 earlier. The 1976 annual average billing cost of fossil fuels (gas and oils, etc.) was 41% of the average annual cost of energy. The 1976 average billing cost of fossil fuels (41%) was 8% lower than 1975 figure presented in Table 3."

FINDING 12-B "Approximately 86% of annual dollar savings was due to electric savings alone and the remaining 14% was attributable to gas savings that was associated with increases in electric consumption."

FINDING 12-C "The overall savings in electric cost would be about 6% compared to 1976 cost and the savings in fossil fuels would be approximately 1%."

* Using the 1976 rates presented in Appendix D - Item 2.

TABLE 15

ESTIMATED AVERAGE ANNUAL ENERGY COST AND AVERAGE DOLLAR SAVINGS PER CUSTOMER
AND PERCENT SAVINGS WITH LOAD MANAGEMENT

TEST CUSTOMERS - 1976*

	<u>Average Cost (1976)</u>		<u>Average Cost with Load Mgmt.</u>		<u>Average Savings</u>	<u>% Savings Total Savings</u>	<u>Overall % Savings to Total 1976 Cost</u>
	<u>\$</u>	<u>%</u>	<u>\$</u>	<u>%</u>	<u>\$</u>		
Electricity	115,302	59	108,456	58	6,846	86	6.0
Natural Gas**	<u>96,999</u>	<u>41</u>	<u>95,871</u>	<u>42</u>	<u>1,128</u>	<u>14</u>	<u>1.0</u>
TOTAL	212,301	100	204,327	100	7,974	100	4.0

* Derived from Table 14

**Includes about 10% of the cost of oils and other fuels on the average.

TABLE 16.

ESTIMATED ANNUAL DOLLAR SAVINGS DUE TO LOAD MANAGEMENT*TEST CUSTOMERS - 1976

SIC Code	Business	Savings Due to kW Reduction On Peak \$	Savings Due to kW Reduction On Peak Off Peak \$ \$		Total Elec. Savings \$	Gas Savings \$	Total Annual Dollar Savings \$
20	Food Products	3,600	-0-	-0-	3,600	-0-	3,600
26	Paper Products	7,704	(180)	(156)	7,368	412	7,780
27	Printing & Pub.	--	--	--	--	--	--
28	Chemicals	720	6,480	5,616	12,816	5,000	17,816
30	Rubber Products	4,608	2,419	1,398	8,425	-0-	8,425
32	Glass Products	14,400	7,880	2,655	24,935	-0-	24,935
33	<u>PRIMARY METALS:</u>						
	Company A	5,328	(108)	(94)	5,126	-0-	5,126
	Company B	1,440	(900)	(780)	(240)	500	260
34	<u>FABRICATED METALS:</u>						
	Company A	1,512	-0-	-0-	1,512	N.A.	N.A.
	Company B	8,064	514	296	8,874	-0-	8,874
	Company C	-0-	-0-	-0-	-0-	600	600
	Company D	-0-	-0-	-0-	-0-	-0-	-0-
35	<u>MACHINERY:</u>						
	Company A	5,040	1,080	624	6,744	500	7,244
	Company B	1,080	(1,170)	(546)	(636)	3,000	2,364
	Company C	7,920	846	733	9,499	-0-	9,499
	Company D	23,256	7,560	4,368	35,184	4,000	39,184
37	<u>TRANSPORTATION:</u>						
	Company A	(504)	(3,627)	(143)	(4,274)	2,700	(1,574)
	Company B	3,600	864	499	4,963	1,000	5,963
	Company C	-0-	495	351	846	2,600	3,446
	Company D	-0-	-0-	-0-	-0-	-0-	-0-
	TOTAL	86,256	22,153	14,821	123,230	20,312	143,542
	Average Savings/ Customer**	4,792	1,231	823	6,846	1,128	7,974
	Percent Savings/ Customer	60	16	10	86	14	100

*Derived from Tables 5 and 8 and using industrial rate structure for 1976.

**Average for 18 customers. SIC 34, Company A, is deleted.

13. Estimated Annual Dollar Savings Attributable to On-peak Demand Reduction, On-peak and Off-peak Energy Reduction, and Gas Reductions Due to Load Management.

Table 16 shows the estimated annual dollar savings due to electric and gas reduction for each individual test customer. In Table 15, the average annual dollar savings per customer was shown to be \$7,974. Table 16 itemizes these savings by individual components of energy. The results indicate the following conclusions:

FINDING 13-A "Of the total average annual dollar savings (\$7,974), the maximum savings (\$4,792) occurred due to peak demand reduction which was 60% of the total savings. The estimated average annual percentages of savings were: Demand Reduction - 60%; Energy Reduction - 26%; and Gas Reduction - 14%."

FINDING 13-B "The total dollar savings attributable to on-peak demand and energy reduction was 76% and the dollar savings from off-peak energy reduction was about 10% of the total dollar savings."

Table 17 gives a summary picture of the average monthly peak demand and on/off-peak monthly energy reductions and the average annual dollar savings. Chart IV shows the estimated percentage distribution of the dollar savings.

CHART IV

DISTRIBUTION OF THE ESTIMATED ANNUAL PERCENTAGE DOLLAR SAVINGS DUE TO LOAD MANAGEMENT (Test Companies - 1976)

TABLE 17

ESTIMATED ANNUAL AVERAGE SAVINGS PER CUSTOMER DUE TO LOAD MANAGEMENTTEST CUSTOMERS - 1976

	<u>Average Monthly Reduction*</u> #	<u>1976 Rate</u> \$	<u>Average Annual Savings</u> \$	<u>% Savings</u>
Peak Demand (kW)	66.55	6.00	4,792	60
Energy (kWh)				
On Peak	6,837	0.015	1,231	16
Off Peak	5,279	0.013	823	10
Average Annual Gas Savings**			<u>1,128</u>	<u>14</u>
TOTAL			7,974	100

* Based on 18 customers.

** Attributable to changes in electric loads.

Derived from Table 16.

14. Detailed Summary of Estimated Percentage Savings of the Test Companies Due to Load Management.

Table 18 shows the percentage of (1) monthly peak demand reduction, (2) monthly energy reduction from on-peak and off-peak, (3) annual electric savings, (4) annual gas savings, and (5) total annual savings attributable to load management. Further, the table also indicates the average percentage savings of each SIC group.

The following conclusions are evident from Table 18.

FINDING 14-A "The overall annual dollar savings would be about 4% as compared to the 1976 annual billing costs of these test group customers. Of this 4% savings, electric savings would represent approximately 3% and the remaining 1% savings would result from the reduction in consumption of fossil fuels such as natural gas, oils, etc."

FINDING 14-B "On the average, the maximum electric savings in dollars occurred in Machinery (7.9%) and the minimum savings occurred in Transportation (0.34%)."

FINDING 14-C "On the average, the maximum percentage (9%) annual dollar savings was expected for SIC 35 - Machinery, and a minimum average savings of less than 1% for SIC 33 - Primary Metals."

TABLE 1B.

SUMMARY OF ESTIMATED PERCENTAGE SAVINGS OF THE TEST COMPANIES
DUE TO LOAD MANAGEMENT*

SIC Code	Business	Monthly Peak Demand Reduction (kW)	Monthly Energy (kWh) Reduction			Annual Electric Savings in Dollars	Annual Gas Savings in Dollars	Total Dollar Savings
		%	On Peak %	Off Peak %	Total %	%	%	%
20	Food Products	3.38	-	-	-	1.10	-	1.10
26	Paper Products	13.38	(.52)	(.52)	(.52)	3.35	.19	3.54
27	Printing & Pub.	---	---	---	---	---	---	---
28	Chemicals	1.16	23.23	23.23	23.23	6.13	2.39	8.52
30	Rubber Products	5.82	5.60	5.60	5.60	2.25	-	2.25
32	Glass Products	10.26	8.06	8.06	8.06	3.76	-	3.76
33	<u>PRIMARY METALS:</u>							
	Company A	3.70	(.25)	(.25)	(.25)	1.54	-	1.54
	Company B	5.56	(5.88)	(5.88)	(5.88)	(.18)	.38	0.20
	AVERAGE	4.63	(3.06)	(3.06)	(3.06)	0.68	.19	0.87
34	<u>FABRICATED METALS:</u>							
	Company A	4.20	-	-	-	N.A	N.A	N.A
	Company B	7.79	1.11	1.11	1.11	2.43	-	2.43
	Company C	-	-	-	-	-	0.60	0.60
	Company D	-	-	-	-	-	-	-
	AVERAGE	3.00	0.37	0.37	0.37	0.81	0.20	1.01
35	<u>MACHINERY:</u>							
	Company A	14.00	4.76	4.76	4.76	8.15	0.60	8.75
	Company B	3.75	(6.25)	(6.25)	(6.25)	(.70)	3.29	2.60
	Company C	28.95	10.80	10.80	10.80	13.55	-	13.55
	Company D	18.46	13.73	13.73	13.73	10.60	1.21	11.81
	AVERAGE	16.29	5.76	5.76	5.76	7.90	1.28	9.18
37	<u>TRANSPORTATION:</u>							
	Company A	(1.84)	(13.86)	(13.86)	(13.86)	(4.43)	2.80	(1.63)
	Company B	12.50	6.15	6.15	6.15	6.19	1.05	6.24
	Company C	-	4.55	4.55	4.55	.59	1.83	2.42
	Company D	-	-	-	-	-	-	-
	AVERAGE	2.67	(.79)	(.79)	(.79)	.34	1.42	1.76
	Average/Customer	6.34	2.70	2.70	2.70	2.96	.80	3.76
	Overall Average Reduction	7.38	3.83	4.03	3.91	3.22	0.54	3.76

*Derived from Tables 14 and 16

15. Financial Feasibility of Load Management Investments.

Table 19 shows (1) total annual dollar savings, (2) percentage annual dollar savings, (3) total investment cost of load management to attain these savings, (4) capital investment, (5) labor cost, (6) average annual rate of return over two-year period, (7) actual payback period given the savings and investment costs, and (8) subsidy amount required to meet the 24-month payback of load management given the 1976 savings derived by using the 1976 rates, total investment, and the constraint imposed with regard to payback period, and the prevailing financial market standards related to rate of return, and the return on capital.

The cost effectiveness of any load management system depends on the initial price, installation costs, and the system's reliability compared to savings which can be realized over a reasonable time period. In relation to this project, the reasonable time period was 24 months which was expected by the sample test group customers.

The major findings of this table are summarized below:

FINDING 15-A "The overall average annual dollar savings due to load management would be about \$7,974 which was about four percent compared to average billing cost of energy in 1976."

FINDING 15-B "To achieve about four percent average dollar savings in average energy billing costs, the average total investment cost of load management would be on the order of \$8,889 of which \$5,031 would be for load management equipment and about \$3,858 for installation of the equipment and required changes."

It should be noted that the aforementioned estimates did not include the cost of services rendered by the MPSC Staff and The Detroit Edison Company in conducting the surveys of plant facilities in order to make the proposals.

FINDING 15-C "If the costs of services rendered by Detroit Edison, MPSC Staff, and the independent consultants were included, the average estimated investment cost would have been between a minimum of \$12,000 and a maximum of \$14,000. (The imputed cost of MPSC and Detroit Edison services was estimated in the neighborhood of \$2,700 to \$4,700, and these amounts would have to be doubled if the companies were to contract with outside consulting firms.)"

TABLE 10

FINANCIAL FEASIBILITY OF "NOO" MAJOR ENERGY INVESTMENTS
TEST COMPANIES - 1976*

SIC Code	Business	Annual Savings Gas & Electric \$	Savings as Percent of Current Ex on Energy %	Total Investment \$	Required Capital Investment \$	Labor Expense \$	Average Annual Rate of Return Over 2-Year Period** %	Actual Payback Period (Months)	Subsidy Required To Meet 24-Month Payback \$
20	Food Products	3,600	1.10	11,075	5,725	5,350	6.2	93.7	4,260
26	Paper Products	7,780	3.54	7,290	4,215	3,075	77.7	75.4	None
27	Printing & Publishing**	--	--	--	--	--	--	--	--
28	Chemicals	17,816	8.52	5,425	4,775	850	184.0	6.0	None
30	Rubber Products	8,425	2.25	26,545	18,025	10,520	9.8	72.7	10,770
32	Glass Products	24,935	3.76	21,500	6,140	15,360	153.0	8.3	None
33	<u>PRIMARY METALS</u>								
	Company A	5,126	1.54	9,270	4,620	4,650	34.7	31.5	1,300
	Company B	260	0.20	5,175	3,975	1,200	(18.4)	(147.3)	4,661
34	<u>FABRICATED METALS</u>								
	Company A	5,512	2.50	500	250	250	282.0	4.7	None
	Company B	8,874	2.43	10,350	6,275	4,075	57.7	20.0	None
	Company C	640	0.80	4,000	2,300	1,700	(20.8)	(110.0)	6,550
	Company D	-0-	-0-	1,550	790	760	(58.1)	(26.9)	3,707
35	<u>MACHINERY</u>								
	Company A	7,244	8.75	11,050	7,500	3,550	38.2	27.9	1,400
	Company B	2,364	2.60	7,950	5,000	2,950	7.8	80.6	3,500
	Company C	9,499	13.55	11,800	6,875	4,925	54.8	20.7	None
	Company D	39,184	11.81	113,575	70,875	42,700	15.2	56.1	44,350
37	<u>TRANSPORTATION</u>								
	Company A	(1,574)	(1.63)	11,150	6,150	5,000	(30.7)	(59.6)	14,187
	Company B	5,963	6.24	9,900	6,400	3,500	16.0	29.6	1,500
	Company C	3,446	2.82	4,375	2,650	1,725	52.0	21.8	None
	Company D	-0-	-0-	1,090	890	200	(21.2)	(115.0)	2,236
	AVERAGE/CUSTOMER	7,974	3.76	8,889	5,031	3,858			3,081

(1) Standards: Return on Investment 10%; Cash Flow Rate (Return of Capital) 100%; Payback Period, 24 Months

(2) Annual Savings at Current Rates

(3) SIC 34, Company A, refers to electric savings and is not used for computing the average savings

(4) SIC 35, Company D, deleted for computing the average

* Derived from the summaries of the financial analysis of individual proposals of the Test Companies presented in the report

** Special proposal

*** The average annual rate of return is obtained by dividing the present value of the incremental cash flow by the total project investment capitalized. An example of the details is presented in Appendix A of this report. It is important to note that the incremental cash flows were calculated up to the end of the second year but not to the end of the 10-year life of the capital expenditure items.

FINDING 15-D "Given a 24-month payback criterion as the norm for the industry, the financial feasibility of the capital investments needed for load management showed that 7 of the 19 companies met the criterion of the 24-month payback, and the remaining 12 companies required subsidies ranging from 13% to over 100% of capital investment to meet the 24-month criterion. If a 36-month payback criterion was assumed, then 10 out of 19 companies would meet the 36-month criterion."

It is important to note that the above conclusions were the outcome of the analysis based on the 1976 rate structure which provided only a minimal 0.2¢/kWh differential between on-peak and off-peak. The existing demand and energy charges, therefore, were not sufficient enough to generate adequate annual dollar savings (24-month pay-back period) which would have been attractive by industry.

FINDING 15-E "The above conclusions were determined based on the following factors:

- a. Demand and energy rates
- b. Discounted cash flow
- c. Depreciation policies
- d. Tax policies
- e. Installation costs
- f. Consultants' charges."

These items are discussed at length in the next section.

16. Feasibility Criteria for Load Management Investment.

The financial feasibility of load management is a function of not only the reduction in the demand and energy use, but also:

- a. Demand and energy rates
- b. Discounted cash flow and annual equivalent revenues over costs
- c. Depreciation policies
- d. Tax policies
- e. Installation costs
- f. Consultants' fee (not included in the analysis)

The above factors were assessed in relation to Table 19 presented in Section 15.

- a. Demand and energy rates. The annual percentage energy savings using 1976 rates for the 19 of the 20 test companies presented in Table 19 ranged from 1.63% to 13.55%. In terms of kW and kWh, the largest percentage reductions were for demand (kW) rather than energy (kWh). Considering that the largest percentage impact was on demand, higher demand charges, rather than higher energy charges, would foster a more rapid return of capital and higher average rates of return on an investment. However, the study did not investigate the impact of alternative rates other than the rate structure prevailed in 1976, as it was not the purpose.
- b. Discounted cash flow and annual equivalent revenues over costs. An increase in discounted cash flow or annual equivalent revenues over costs would increase the number of investments that would meet the payback criterion used in the study.
- c. Depreciation policy. With respect to depreciation policies, accelerated depreciation would increase cash flow and, thereby, increase the average rate of return on investment and reduce the payback period necessary for investment.
- d. Tax policies. Larger investment tax credits would reduce the number of months required to obtain a 100% return of capital. Investment tax credits, which were used in the financial analysis, increased after-tax cash flow but were insufficient to eliminate the need for a subsidy for 12 of the 19 firms. Higher tax incentives would strengthen the financial feasibility for these companies.
- e. Installation costs. Another factor that affected the financial criterion was the installation costs (outside labor costs), which were a first year write-off, and were running 50%-100% of the capitalized investment. These costs substantially reduced the first year addition to pre-tax profits

due to load management equipment. If firms possessed the in-house capability for installation of the equipment, the costs of labor would be substantially reduced and in turn would increase the pre-tax profits.

- f. Consultants' fees. Several types of talents were used for this energy management project. Energy consultants included were (1) lighting specialist, (2) HVAC specialist, (3) gas specialist, (4) power systems analyst, (5) energy economist, (6) data systems analyst, and (7) process engineer. Normally, the companies involved in the study would have to pay the hourly charges ranging between \$25/hour to \$75/hour, if the companies were to hire them; however, the test companies got the services of MPSC and Detroit Edison Company staff at no cost. For the purpose of the study, we hired two consultants: (1) energy engineer, and (2) economic consultant, but the fees for these two consultants were not included in estimating the financial feasibility of the test companies.

17. Estimated Average Load Factors of 20 Test Group Companies

Table 20 shows the historical load factors for 1973, 1974 and 1975. The load factors were calculated using the following definition.

The load factor of a customer facility is defined as the ratio of total energy (kWh) used in a period to peak demand (kW) multiplied by the hours of operating time.

$$\text{Load Factor} = \left(\frac{\text{Total kWh used in a period}}{\text{Peak kW in a period} \times \text{hours of operating time}} \right) \times 100$$

The maximum load factor is 100 percent. The higher the load factor, the better the utilization of energy. For example, assume that plant load factor (efficiency) is 55 percent; in other words, if one extrapolates the demand peak over a billing period and compares with the energy usage over the billing period, there is a 45 percent energy peak that can be theoretically or ideally deferred during the low demand period.

FINDING 17 "Table 20 reveals that the historical average annual load factors (Monday-Friday) of the test customers. The average load factors deteriorated from 76 percent in 1973 to 70 percent in 1975. The year-to-year decline was about three percent on the average. The test customers experienced either greater or smaller percentage declines in their load factors compared to 1973, the year in which industrial activity, in general, was highest compared to the post war years. The average load factors of the Transportation sector slipped by about 13 percent followed by Primary Metals - 10 percent, Machinery - seven percent, and Fabricated Metals - four percent. The average load factors of Chemicals, Rubber Products, and Glass Products experienced a decline of nine percent, nine percent, and seven percent respectively. Printing and Publication showed an increase of three percent in the average load factors compared to 1973."

It should be noted that these load factors were computed using the information received (particularly operating time during 1973, 1974, and 1975) from the individual customers prior to implementation of time-of-day rates and should be treated as approximate. The general economic recession during 1974 and 1975, contributed to the decline in load factors.

Table 20

HISTORICAL AVERAGE LOAD FACTORS OF THE TEST COMPANIES

SIC Code	Business	Average Load Factors (Monday--Friday)			Average
		1973	1974	1975	
20	Food Group	80	80	80	80
26	Paper Products	92	92	92	92
27	Printing & Pub.	50	50	53	51
28	Chemicals	78	72	69	73
30	Rubber Products	-	86	77	82
32	Glass Products	77	70	70	72
33	<u>PRIMARY METALS:</u>				
	Company A	69	64	62	62
	Company B	<u>98</u>	<u>95</u>	<u>95</u>	<u>96</u>
	<u>Average</u>	<u>84</u>	<u>80</u>	<u>74</u>	<u>79</u>
34	<u>FABRICATED METALS:</u>				
	Company A	76	73	68	72
	Company B	69	66	66	67
	Company C	83	84	79	82
	Company D	<u>87</u>	<u>85</u>	<u>87</u>	<u>86</u>
	<u>Average</u>	<u>79</u>	<u>77</u>	<u>75</u>	<u>77</u>
35	<u>MACHINERY:</u>				
	Company A	76	75	72	74
	Company B	77	76	71	75
	Company C	61	50	48	53
	Company D	<u>71</u>	<u>73</u>	<u>66</u>	<u>70</u>
	<u>Average</u>	<u>71</u>	<u>69</u>	<u>64</u>	<u>68</u>
37	<u>TRANSPORTATION:</u>				
	Company A	83	-	76	80
	Company B	-	-	65	65
	Company C	60	58	42	53
	Company D	<u>81</u>	<u>73</u>	<u>63</u>	<u>72</u>
	<u>Average</u>	<u>75</u>	<u>66</u>	<u>62</u>	<u>68</u>
	GRAND AVERAGE	76	73	70	73

13. Historical Patterns of Energy Utilization.

Table 21 provides the average percent of energy (kWh) consumption by the test companies between the peak period (9:00 am - 9:00 pm) to the total energy (kWh) consumed within the 24-hour period Monday to Friday.

FINDING 18 "When analyzed for the historical patterns of energy (kWh) utilization by the 20 test companies between 9:00 am and 9:00 pm to the total (kWh) during a 24-hour period, Monday through Friday, it was found that 65% of the utilization occurred during 9:00 am to 9:00 pm for 1973, 65% for 1974, and 68% for 1975, on the average."

Table 21

ANNUAL PERCENT OF ON-PEAK KILOWATT HOUR CONSUMPTION OF 20 TEST COMPANIES*
BETWEEN 9 AM - 9 PM TO THE TOTAL OF 24-HOUR KWH CONSUMPTION - MONDAY-FRIDAY

<u>SIC Code</u>	<u>Business</u>	<u>1973</u>	<u>PERCENT</u> <u>1974</u>	<u>1975</u>
20	Food Products	61	61	62
26	Paper Products	56	56	56
27	Printing & Publishing	69	69	70
28	Chemicals	62	65	66
30	Rubber Products	N.A.	63	64
32	Glass Products	63	66	64
33	<u>PRIMARY METALS:</u>			
	Company A	71	73	80
	Company B	55	56	57
34	<u>FABRICATED METALS:</u>			
	Company A	68	70	72
	Company B	69	69	69
	Company C	59	59	75
	Company D	58	57	57
35	<u>MACHINERY:</u>			
	Company A	66	66	67
	Company B	64	64	68
	Company C	71	74	76
	Company D	68	68	69
37	<u>TRANSPORTATION:</u>			
	Company A	62	N.A.	66
	Company B	N.A.	N.A.	70
	Company C	75	70	72
	Company D	<u>65</u>	<u>68</u>	<u>72</u>
	Average	65	65	68

Derived from historical data provided by Detroit Edison Company.

*On-peak period 9 am - 9 pm.

19. Major Proposal Items Recommendation for Load Management of the Study.

Table 22 shows the major proposal items recommended to achieve the estimated savings that were presented in the preceding sections of this chapter.

These are:

- a. New lighting
- b. Timing and control devices
- c. Heat recovery
- d. HVAC system improvements
- e. Insulation
- f. Off-hours audits
- g. Shift changes
- h. Off-peak utilization
- i. Demand control systems
- j. Recovery of process and boiler water
- k. General maintenance
- l. Conversions

TABLE 22

SUMMARY OF MAJOR PROPOSAL ITEMS

<u>PROPOSED</u>	<u>NO. OF TEST CUSTOMERS</u>
1. New Lighting	19
a. Relocate (5)	
b. Remove (6)	
c. Maintain (19)	
2. Timing and Control Devices	17
a. Water Heaters	
b. Battery Chargers	
c. Lighting Systems	
d. Heat Lamps	
e. Air Conditioners	
3. Heat Recovery	9
a. Heat Pumps (3)	
b. Auxiliary Fans (7)	
c. Thermal Barriers (7)	
4. HVAC System Improvements	19
a. Vent Hoods (3)	
b. Solar Reflective Film (5)	
c. Maintenance (19)	
5. Insulation	19
a. Building	
b. Equipment (Piping)	
6. Off-Hour Audits	2
7. Shift Changes	2
8. Off-Peak Utilization	4
9. Demand Control Systems	3
10. Recovery of Process and Boiler Water	16
11. General Maintenance	19
12. Conversion	
a. From Gas	Capability exists in all plants.
b. From Oil	Capability exists in all plants

20. Customer Attitudes

During our initial discussions with the industrial test customer managements, pertinent to the overall energy management in their plants and in regard to the electric load management study, the company's top executives of the customers expressed the following general comments. It should be noted that these general comments, however, were not the result of a predesigned customer attitude survey. The customer attitude survey (prior to technical surveys or after the test) was not a part of the study. In general, the test customers were highly receptive to the very concept of energy management. Some of these test customers, however, have had general concerns regarding governmental projects and other regulations restricting their operations. It should be noted, also, that these attitudes and comments which were expressed at the initial meetings indicate the overall feelings of the test customers but not necessarily represent the entire spectrum of industrial class, even though, by design, the selected customers were supposed to be representative of the industry.

- a. "Most company managers were reluctant to agree to governmental involvement in their operation.
- b. I am not quite sure that it is necessary to do this type of study for our particular business since we are rather unique in operation.
- c. We already have an energy conservation program.
- d. Industry is generally concerned about the amount of energy it uses, however, we feel that we are conserving energy as best we can.
- e. I realize that certain portions of our process are inefficient, but with the economy as it is we cannot afford to invest money in anything except those relating to production.
- f. Where do you propose that we get the money for capital improvement? The banks are reluctant to provide funds for anything except production equipment.
- g. Detroit Edison has always been of help when we needed it and we feel it is important to have reliable utilities. We will be glad to participate.
- h. Because the government is financing this project, does this mean we will have them going through our plant snooping around?
- i. Who is going to know that we are participating? If we desire, can we use this project in our advertisement?"

Reactions of the test group customers and general findings of the technical survey:

The following general observations can be made as a result of our survey (prior to test) of sample test group customers:

FINDING 20-A "There has been adequate initial response from the test group customers. However, the discussions with plant management resulted in their request that the implementation of the energy management proposals would not:

- 'a. Interfere with or disrupt any production equipment.
- b. Violate the federal controls and regulations that they feel are currently restricting their economies for doing business.
- c. Require additional valley hour usage for production personnel because the anticipated labor costs associated with this change far exceed the possible energy savings."

It should be noted that items a through c were not the prerequisites established by MPSC or Detroit Edison Company. But they were the prerequisites of the companies. In regard to item c, the overall consensus of companies was that if the rate structure were attractive enough to offset labor costs, some of the energy intensive operations of these companies could be shifted to valley hours.

FINDING 20-B "The overall response from the test customers in regard to our proposals was very good despite the fact that the companies took considerable time, up to two to three months, in responding to our initial proposals."

FINDING 20-C "One test group customer declined to implement our recommendations even though the payback period of the investment showed 8.3 months, and rejected \$10,000 offered by FEA to purchase the load management equipment out of the total required investment of \$31,500. The management said 'Thanks for the offer. We cannot afford the labor cost of implementing all the recommendations which is approximately \$15,000 out of \$31,500 total investment.'"

FINDING 20-D "On the other hand, one test group customer representing SIC 35-D, implemented all of our recommendations, even though the initial payback period of investment was 56 months. The actual amount of investment was \$120,700 compared to an estimated amount of \$113,575. Of the actual expenditures, 60 percent was for capital investment and 40 percent was towards the cost of labor."

FINDING 20-E "One test group customer suggested that there should be sufficient tax incentive for efficient management of energy utilization and recommended classifying the industries on the basis of their energy use."

21. General Findings

- a. A large majority of the test companies did not have effective energy management programs.
- b. Many small and medium-size industrial customers did not have sufficient resources of their own (capital and technical know-how) to carry out an efficient energy management program.
- c. Many companies had other investments which take priority over the implementation of energy management programs.
- d. In comparison, energy costs were lower than labor, raw materials, capital, etc. and thus, does not encourage industrial customers to save energy or to manage industrial operations more efficiently than when energy management investments involved substantial expenditures.
- e. Industry is very concerned about the costs of electric power along with the costs of other forms of energy. As these costs continue to increase, industrial customers will give greater emphasis to the development of methods to reduce these costs. However, an overriding concern of the industry is reliable and adequate sources of power.
- f. The electrical consumption of the industrial customers was not temperature sensitive.
- g. Generally, small industries with limited capital were reluctant to undertake energy management steps until they are convinced it will result in increased profits.
- h. Industrial customers involved in this study initially had reservations about the feasibility of load management. After having associated with the surveys, the customers were positive in their attitudes.
- i. Some of the companies were subsidiaries of large corporations which required the approval of corporate headquarters to implement changes in local plant operations, which delayed the implementation of proposal recommendations.
- j. Some of these customers have developed partial energy management programs prior to being a test customer.

- k. Operating schedules of the plants may limit the implementation of recommended changes, such as removal of vintage or inefficient equipment, installation of new lighting systems, insulation of the buildings, painting, etc.
- l. Many companies had an investment criterion limiting action to those items which had no less than a 24-month payback period; and some of the sample test companies felt that the return on capital investment did not justify the expense.

CHAPTER IV

PROGRAM IMPLEMENTATION

- A. Introduction
- B. Summary of the Type and
Category of Proposal
Recommendations and
Final Results of the Test
- C. An Analysis of the Impact of
New vs. Old Rates

A. Introduction

In the preceeding chapter, the results of the analysis of the technical surveys and the estimated maximum savings that could be attainable on the premise that one hundred percent of the proposal recommendations would have been implemented by the test group customers, were presented.

The purpose of this chapter is to summarize the following:

1. The number of test customers initially responded to implement the proposal recommendations;
2. To what extent the proposal recommendations have been implemented;
3. The category of recommendations implemented;
4. Probable factors for the delays in implementation and the reasons for not implementing some or all of the recommendations;
5. Average length of test period;
6. The magnitude of demand (kW) and energy (kWh) savings;
7. Plant load and power factors before and after implementation of the test;
8. On-peak and off-peak percentage consumption of energy (kWh) of the test and control companies prior to implementation and after implementation of the test.

TEST & CONTROL GROUP CUSTOMER IDENTIFICATION CODE CHART

<u>SIC CODE</u>	<u>BUSINESS</u>	<u>TEST NO. CUSTOMERS</u>	<u>CONTROL NO. CUSTOMERS</u>
20	Food Group	1	1
26	Paper Products	1	1
27	Printing & Publishing	1	1
28	Chemicals	1	1
30	Rubber Products	1	1
32	Glass Products	1	1
33	<u>PRIMARY METALS</u>	2	2
	Company A		
	Company B		
34	<u>FABRICATED METALS</u>	4	4
	Company A		
	Company B		
	Company C		
	Company D		
35	<u>MACHINERY</u>	4	4
	Company A		
	Company B		
	Company C		
	Company D		
37	<u>TRANSPORTATION</u>	4	4
	Company A		
	Company B		
	Company C		
	Company D	—	—
	TOTAL	20	20

B. A Summary of the Type and Category of Proposal Recommendations.

A descriptive summary of the proposal recommendations of the test group customers is presented below. However, the detailed proposal recommendations of each individual customer can be found in the summary recommendations of the proposals.

Due to varying characteristics of the production processes, plant facilities, not every technique of energy management, can be implemented at each facility. Therefore, to assist in highlighting the specific areas of the recommendations, the reader can refer to the following:

<u>Energy Management Item</u>	<u>SIC Code</u>
Lighting	35 - Company D
Heat Recovery	37 - Company A
Demand Control	32/33 - Company B
Production	26/34 - Company B
Air Compressors	35 - Company C
Special Tests	20
Painting & Insulation	33 - Company B
Water Heaters & Battery Chargers	30/34 - Company A

SUMMARY RECOMMENDATIONS OF THE PROPOSALS

SIC CODE	BUSINESS	PROPOSAL RECOMMENDATIONS
20	Food Products	<ul style="list-style-type: none">a) Purchase and install 50-150 watt high-pressure sodium fixtures to replace incandescent ones in inactive and freezer storage areas.b) Replace unshielded fluorescent lamps with 800 MA high output fluorescent luminaires.c) Replace each compressor motor when it fails with size previously recommended as no savings are currently available.d) Analyze current motor substitution practices.
26	Paper Products	<ul style="list-style-type: none">a) Install color reflective film on glass in office area.b) Install storm windows on glass in the office area.c) Install supplemental or spot heating in basement area.d) Install low velocity ceiling fans (heating purpose).e) A timer device on the smaller pulper machine.
27	Printing & Publishing	<p>A complete review of the operations was made including the survey of lighting, HVAC, and process and it was determined that, because the customer had implemented several energy conservation measures prior to the survey, the scope for further energy management was limited.</p>
28	Chemicals	<ul style="list-style-type: none">a) The metal halide phosphor-coated lamps should be used in place of all mercury and incandescent light sources for both hazardous and non-hazardous areas. These lamps should especially be used for general lighting in work areas that require little or no color discrimination.b) Clean all luminaires and lamps annually since the greatest loss of light is due to the collection of dirt on both luminaires and lamps.

SIC CODE	BUSINESS	PROPOSAL RECOMMENDATIONS
28	Chemicals (Con't.)	<ul style="list-style-type: none"> c) Replace a total of eight two-lamp units which presently light the quality control room with 14 four-lamp, 40 watt deluxe cool white fluorescent lamps. This will result in an increased wattage of 1.1 kW. d) Remove 45 two-lamp, 40 watt lamps including ballasts in the lunchroom which will result in an every savings of 7.1 kW. e) All lighting luminaires should be relamped with new lamps on a four-year group lamp replacement plan. Approximately 20% of the best lamps should be saved to use for lamp burn-out replacement between group lamp replacement cycles.
30	Rubber Products	<ul style="list-style-type: none"> a) Install timer devices to operate the electric water heaters during off-peak periods. b) Scheduling of battery charger units to operate off-peak. c) Install remote control units to operate the overhead doors in shipping-receiving area. d) Replace incandescent lighting units with high pressure sodium fluorescent light sources.
32	Glass Products	<ul style="list-style-type: none"> a) Relocation of existing fluorescent fixtures in buildings 2, 3 and 4. b) Buy and install 125 new 400 watt mercury lamps in buildings. c) Design and install a hood to properly vent the fumes in building 4. d) Remove 123-455 watt mercury luminaires in building 5. e) Buy 8 low velocity fans to circulate the warm air trapped near the ceilings of buildings 2, 3, 4 and 8. f) Buy and install 55-2 - 75 watt T-1296 slim-line luminaires for buildings 2, 4, 5 and 8. g) Buy and install demand control system to control lighting and HVAC loads.

SIC CODE	BUSINESS	PROPOSAL RECOMMENDATIONS
33	PRIMARY METALS: Company A	<ul style="list-style-type: none"> a) Charge electric hi-lo units during off-peak billing hours. b) Use scrap chopper during off-peak hours. c) Remove 63 2-75 watt 96" slimline lighting in shipping storage area. d) Relocate lighting fixtures over bending fixtures. e) Install 3 recovered 2-75 watt 96" slimline fixtures in the slimline cut-off area and install 6 recovered 2-75 watt 96" slimline fixtures in the cutting press area. f) Purchase and install special metering equipment to provide a remote monitoring system for manual demand control. g) Purchase and install a timer device to operate the electric hot water heater off-peak.
33	PRIMARY METALS: Company B	<p><u>New Building:</u></p> <ul style="list-style-type: none"> a) Install special photocell to control lighting load during the lightest portion of the day. <p><u>New Offices:</u></p> <ul style="list-style-type: none"> a) Install new lighting system as designed by DeCo. b) Install special area switches to control lighting as needed by office personnel. c) Install special timing circuit for all air conditioning during peak periods. <p><u>Old Building</u></p> <ul style="list-style-type: none"> a) Install additional light fixtures as proposed by survey team. b) Reclamp and clean existing fixtures. c) Clean and paint with a light color all ceilings and walls. d) Install a special timer to allow for the treating of the oil for the compounding process during off-peak periods.

SIC CODE	BUSINESS	PROPOSAL RECOMMENDATIONS
34	FABRICATED METALS: Company A	<ul style="list-style-type: none"> a) Install a timer device on electric hot water to prevent operation during peak loads. b) Implement procedures to only recharge electric fork lift trucks during off-peak loads. c) Study feasibility of implementing heat recovery techniques for the oven used for material testing.
34	FABRICATED METALS: Company B	<ul style="list-style-type: none"> a) Shift the running of all buffing equipment by at least 1 hour during peak hours to reduce its effect on billing demands. b) Purchase and install a lighting system for each of the four priority areas. c) Investigate and determine a reason for the capacitor fuse problem...then repair or install necessary equipment.
34	FABRICATED METALS: Company C	<ul style="list-style-type: none"> a) Purchase and install 11-2 lamp 110 watts 800 MA fixtures. b) Remove 7 - 2 lamp 75 watts 435 MA unshielded ind. fixtures. c) Purchase and install additional auxiliary fans for use in selected areas.
34	FABRICATED METALS: Company D	<ul style="list-style-type: none"> a) Investigate feasibility of installing demand limiting devices for the two 32 kw stress relieving ovens and also in the building addition which is electrically heated. b) Replacement of existing lighting in the polish and inspection area with 5 - 4 foot four lamp, 40 watt fluorescent lamp fixtures. c) Replacement of five durotest fixtures with 2 - 2 lamp, 110 watt, 800 MA lighting fixtures. d) Purchase and install damper controls for the exhaust fans which currently run throughout the weekend.

SIC CODE	BUSINESS	PROPOSAL RECOMMENDATIONS
34	FABRICATED METALS: Company D (Con't.)	<ul style="list-style-type: none"> e) Replacement of defective thermostat in the inspection laboratory. f) The feasibility of shutting down the chromic acid tanks during the weekends.
35	MACHINERY: Company A	<ul style="list-style-type: none"> a) Purchase and install a timer device to control the heater elements of the electric water heaters. b) Purchase of ten propeller-type fans. c) Install equipment to operate air conditioning units for the computer room and other office areas off-peak. d) Install equipment to operate air compressor units used for sandblasting at off-peak times. e) Purchase of the proposed lighting system for the assembly areas.
35	MACHINERY: Company B	<ul style="list-style-type: none"> a) Purchase and install welding hoods and a make up air unit in the welding room. b) Purchase and install heat lamps and a time control unit for use in the toilet areas. c) Purchase and install infrared spot heating units for specified areas. d) Purchase and install a time control unit to operate 3 electric water heaters at off-peak times. e) Purchase and install 86 - 400 watt metal halide lamps to replace existing units. f) Purchase and install 10 kW electric oven and five microwave ovens. g) Conduct an off-hours audit of energy consumption and conservation measures.

SIC CODE	BUSINESS	PROPOSAL RECOMMENDATIONS
35	MACHINERY: Company C	<ul style="list-style-type: none"> a) Removal of 45,855 watts of lighting equipment as outlined in the recommendations. b) Install 32 - 96" fluorescent (2 - 110 watt 800 MA) and 22 - 400 watt high pressure sodium lamps. c) Install an interlocking control on the 70 kW oven heaters. d) Install timers on the electric hot water heaters in washrooms to control the 4.5 kw heating elements. e) Install controls for the motor generators set at crane locations to operate the M-G1 set when needed. f) Install a 25 h.p. air compressor as the main air system for the plant with the 75 h.p. unit as a backup.
35	MACHINERY: Company D	<ul style="list-style-type: none"> a) Investigation of the feasibility of installing timer devices on electric water heaters. b) Install solar reflective film on the office glass. c) Repair the steam leak at the acid tank junction. d) Replace the boiler steam pipe insulation. e) Install lighting equipment in plant locations as stated in Lighting Review Section.
37	TRANSPORTATION: Company A	<ul style="list-style-type: none"> a) Removal of some luminaires from over the top of presses and four rows alternating every other luminaire per row in the area over the steel stock and in the side aisles adjacent to the presses. b) Relocation of 14 - 2 lamp 75 watt 96" luminaires in shipping-receiving room area. c) Purchase and install pre-set, non-adjustable thermostats.

SIC CODE	BUSINESS	PROPOSAL RECOMMENDATIONS
37	TRANSPORTATION: Company A (Con't.)	d) Install a heat pump with an intermediate heat exchanger as a means of heat transfer from the heat treat area to shipping and receiving areas.
37	TRANSPORTATION Company B	a) Purchase and install a 30-horsepower compressor for the boring mill area. b) Buy and install 8 ceiling fans for use in the boring mill area. c) Install solar film on windows in the office area. d) Install pipe to connect the water-cooled air conditioner with the air compressor storage tank. e) Interlock the unit heaters with door operation and temperature. f) Replace existing lighting system in the boring mill area with high efficiency light source system.
37	TRANSPORTATION: Company C	a) Implement procedures for maintenance of office air conditioners. b) Closing duct opening in maintenance area. c) Charge electric fork lift units during off-peak hours. d) Buy and install 3 - 400 watt high pressure sodium ventilated luminaïres. e) Install equipment to implement heat recovery in the hammer area. f) Alter the operation of major furnaces to allow for partial usage during valley peak hour periods.
37	TRANSPORTATION: Company D	a) Purchase and install 37 - 400 ID x H 33 GC mercury lamps to replace lighting in the warehouse area. b) Purchase and install 3 - 2-110 watt 96" 800 MA lamps in the inspection area.

1. Customer Acceptance of the Proposal Recommendations

A total of 20 proposals were made including a special proposal to a test group customer representing SIC 27 - Printing and Publishing, since this customer had already implemented several energy conservation measures prior to being the test customer. In addition, the customer refused to provide the historical data on Survey Form I. However, the survey team conducted a complete review of the operations including lighting, HVAC and process, and it was determined that there was very little scope for further improvement. Due to the aforementioned reasons a special proposal was made for this customer describing the unique characteristics of the mode of operations which are, in general, typical of this industry wherever they are located in the country; but no formal presentation of this special proposal was made to the customer.

Thus, formal proposal presentations were made only to the remaining 19 test group customers out of a total of 20 test group customers. Three of the 19 test group customers did not respond to our proposal recommendations despite our repeated efforts and did not implement any of the recommendations. Ten of the remaining 16 customers responded in writing to accept the proposals and to implement the recommendations, and the remaining six test group customers agreed orally to implement the recommendations that were made in their respective proposals. Finally, 16 of the 20 test customers implemented either some or all the recommendations of the proposals.

2. The extent to which the proposal recommendations were implemented by the test group customers and the average length of time taken to implement the recommendations so far.

It was pointed out in the preceeding section that only 16 of the 19 test customers, who responded to the proposals, have implemented the recommendations in varying degrees of magnitude. These customers, in general, have not carried out the recommendations at one time. Instead, they have adopted them in a piecemeal fashion. Further, the test customers have taken approximately an average period of four to five months to fulfill either some or all the proposals. However, some of the non-capital expenditure items, such as maintenance, lighting removal, relocations, etc., have been put into effect immediately. Some of the customers have implemented beyond our recommendations despite unattractive payback periods of their investments. Other customers, even though the payback periods of their capital investments were less than 24 months, have not adopted all our proposals. These reasons are focused in item (4) under the heading, "Factors and Reasons for not Implementing the Recommendations."

The three test group customers who did not respond and did not implement any of the recommendations are (1) SIC 30 - Rubber Products; (2) SIC 35 A - Machinery; and (3) SIC 37 D - Transportation.

A summary picture of the proposal recommendations implemented by the 16 customers is given below:

<u>Number of Test Customers</u>	<u>Percent of Recommendations Implemented</u>
4	10 - 40
7	40 - 70
<u>5</u>	70 - 100
TOTAL <u>16</u>	

3-A. Type of Recommendations Implemented by the Test Customers.

The details in regard to the type of recommendations implemented by the test group customers are itemized in Table A. The following gives an overall summary of the percentage of the customers who implemented various recommendations by category.

- a. Timing and Control Devices: Seventy-three percent of the customers have implemented most of the recommendations or have committed to implement in the near future. These include: (1) timing and control devices on water heaters, (2) battery chargers, (3) lighting systems, (4) heat pumps, and (5) air conditioners, etc.
- b. Demand Control Systems: Recommendations were made to three test customers, two of which have implemented. One customer did not implement the demand control system, despite an offer of \$10,000 to purchase the system, due to excessive labor cost involved in implementing all the recommended changes. A special analysis of the demand control system implemented by a customer representing SIC 33 B - Fabricated Metals, is presented in Appendix B of this report.
- c. Heat Recovery: Sixty-seven percent of the customers in this category have implemented the heat recovery techniques and others have plans to implement heat recovery recommendations in the immediate future.
- d. HVAC System Improvements: About 40% of the customers in this category have implemented the HVAC system improvements, and others have plans to implement them in the very near future.

- e. Recovery of Process and Boilers: Approximately 63% of the customers have implemented recommended changes.
- f. Lighting: About 58% of the customers in this category have implemented a large portion of our recommendations and others are seriously considering the installation of new lighting systems in the foreseeable future. However, items such as (1) relocation of lighting, (2) removal of excessive lighting, and (3) maintenance of existing lighting, have been accomplished by a large majority of the customers.
- g. General Maintenance: Almost every customer in the test group has done something in this area. The general maintenance items include preventive maintenance on motors, lighting systems, broken windows, defective structures, replacement of filters, and establishing a preventive maintenance program, etc.
- h. Insulation: About 32% of the recommended customers have implemented. Others have scheduled to implement these recommendations in the near future.
- i. Off-hour Audits and Shift Changes: Off-hour audits were recommended for two test group customers representing SIC groups 34-B and 35-B. These customers have implemented our recommendations by allocating the duties to the appropriate personnel to conduct these audits on a regular basis.

Shift changes were recommended for two test group customers representing SIC groups 34-B and 37-C. These two customers did not implement the recommended changes. However, the SIC 37-C customer added an additional shift to utilize off-peak energy.

3-B. Control Customers

The methodology of sample selection as described in Chapter II indicated that the 20 control customers having homogeneous characteristics were considered as standard. No survey was conducted to the control customers. In fact they were not aware of their position as control customers by design of the study. Therefore, no pressure was applied to obtain the requested information on Survey Form 1, as it was strictly voluntary. Six out of 20 control customers completed the Survey Form 1 and the remaining control customers did not respond at all despite our repeated requests. However, Detroit Edison provided valid historical electric consumption data as well as the electric consumption data during the test period. Using the data, comparative analysis of the test and control customers was made in regard to on/off peak electric consumption and the load factors (see Tables 12 and 13 of this Chapter). The basis of these comparisons was that most of the control customers were aware of the energy situation and/or responding to their immediate needs without assistance from outside sources.

T A B L E A

STATUS OF MAJOR PROPOSAL RECOMMENDATIONS

STATUS OF MAJOR PROPOSAL RECOMMENDATIONS

TEST CUSTOMERS

	Proposed	No. of Customers	No. of Customers Implemented	SIC Codes
I.	Lighting	19	<u>11</u> 8	<u>20, 28, 32, 33-A, 33-B, 34-B, 34-C, 35-B, 35-D, 37-B, 37-C</u> 26, 30, 34-A, 34-D, 35-A, 35-C, 37-A, 37-D
	A - Relocation	5	<u>4</u> 1	<u>32, 33-A, 33-B, 37-A</u> 20
	B - Removal	6	<u>5</u> 1	<u>28, 32, 33-A, 34-C, 35-C</u> 37-A
	C - Maintenance	19	<u>9</u> 10	<u>28, 32, 33-A, 33-B, 34-B, 35-B, 35-C, 37-A, 37-B</u> 20, 26, 30, 34-A, 34-C, 34-D, 35-A, 35-D, 37-C, 37-D
II.	Timing and Control Devices	11	<u>8*</u> 3	<u>28, 33-A, 33-B, 33-B, 34-A, 34-A, 35-B, 35-B, 35-C, 37-C</u> 26, 35-A, 35-D
	A - Water Heaters	8	<u>3</u>	<u>34-A, 35-B, 35-C</u>
	B - Battery Chargers	4	<u>4</u>	<u>28, 33-A, 34-A, 37-C</u>
	C - Lighting System	1	<u>1</u>	<u>33-B</u>
	D - Heat Lamps	1	<u>1</u>	35-B
	E - Air Conditioners	1	<u>1</u>	33-B
The underlined figures denote the implementation.				

	Proposed	No. of Customers	No. of Customers Implemented	SIC Codes
III.	Heat Recovery	9	6	<u>26</u> , <u>33-B</u> , <u>35-B</u> , <u>37-A</u> , <u>37-B</u> , <u>37-C</u>
	A - Heat Pumps	3	<u>1</u>	<u>37-A</u>
			2	33-A, 34-C
	B - Auxiliary Fans	7	<u>3</u>	<u>26</u> , <u>35-B</u> , <u>37-B</u>
			4	28, 32, 33-C, 34-C
	C - Thermal Barriers	7	<u>2</u>	<u>33-B</u> , <u>37-B</u>
			5	26, 30, 32, 34-B, 35-C
IV.	HVAC System Improvements	19		
	A - Vent Hoods	3	<u>1</u>	<u>33</u>
			2	34-A, 34-B
	B - Solar Reflective Film	5	<u>2</u>	<u>26</u> , <u>37-D</u> (Testing Effects)
			3	35-C, 35-D, 37-A
	C - Maintenance	19	<u>14</u>	All doing something
V.	Insulation	19	<u>6</u>	<u>33-B</u> , <u>34-B</u> , <u>35-B</u> , <u>35-D</u> , <u>37-A</u> , <u>37-B</u>
	A - Building		<u>2</u>	<u>33-B</u> , <u>37-B</u>
	B - Equipment (Piping)		<u>4</u>	<u>34-B</u> , <u>35-B</u> , <u>35-D</u> , <u>37-A</u>
VI.	Off Hour Audits	2	<u>2</u>	<u>34-B</u> , <u>35-B</u>
VII.	Shift Changes	2	<u>1</u>	<u>37-C</u>
			1	<u>34-B</u>
II.	Off-Peak Utilization		<u>14</u>	See Table 12
			5	26, 30, 34-D, 35-D, 37-C

	Proposed	No. of Customers	No. of Customers Implemented	SIC Codes
X.	Demand Control Systems	3	<u>2</u> 1	<u>33-A, 33-B</u> 32
X.	Recovery of Process and Boiler Water	16	<u>10</u> 6	<u>26, 32, 33-A, 33-B, 34-C, 34-D</u> <u>35-B, 35-D, 37-A, 37-B</u> 20, 28, 30, 33-B, 34-A, 35-A
XI.	General Maintenance	19	<u>16</u> 3	Some completed and some limited 30, 34-A, 37-D
II.	Conversions A - From Gas B - From Oil			Capability exists in all plants Capability exists in all plants

NOTE: The underlined indicate those customers who implemented either fully or partially.

* The major portion of this control is being done manually - no capital equipment necessary.

4. Probable Factors Responsible for Delays in Implementation, Partial or No Implementation of the Proposal Recommendations by the Test Customers.

The following set of factors was primarily responsible for partial implementation of the proposal recommendations or non-implementation of any of the recommendations. Table B of this section provides details of the reasons for delays, etc. in each individual case.

Factors

- a. Budget constraints and limited financial resources.
- b. Proportion of energy cost in the operating budget.
- c. Expected net dollar savings.
- d. Payback of investment.
- e. Labor cost of implementation.
- f. Tax write-offs in the first and second years.
- g. Physical possibility and operating characteristics of production processes.
- h. Proportion and types of energy used and the energy vs. labor intensiveness of the firm.
- i. Location of the plant.
- j. Customer capability to use off-peak electric power.
- k. Number of shifts.
- l. Type and quality of existing equipment, buildings and the physical distribution of the buildings in the location.
- m. Availability of time.
- n. Environmental constraints, OSHA and other code regulations.
- o. Shift differential cost of labor to operate during the off-peak time; the willingness of labor to work during off-peak time, and the lack of an adequate rate incentive.
- p. Awareness of the management and the work force regarding the limited energy supplies.

- q. Type of management and form of organization.
- r. Demand for the product they produce.
- s. Energy conservation/load management measures already implemented prior to this project.

T A B L E B

CONTINUATION OF STATUS OF MAJOR
PROPOSAL RECOMMENDATIONS

SIC 20 FOOD PRODUCTS

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Lighting Changes	\$ 10,000	11-10-76	11-10-76	
2) Motor and Compressor Replacement	-	11-10-76	11-10-76	
3) Timers and Interlocks	<u>1,075</u>	11-10-76	11-10-76	
TOTAL	\$ 11,075			
II. <u>Items Implemented:</u>				
1) Will be done on random basis - currently not in progress.	-			Two year period.
2) Will be done when equipment fails	-			Uncertain
3) Compressor Control is being implemented on a manual basis	-			
III. <u>Items Rejected:</u>				
None				
IV. <u>Items Under Review/Undecided/Problem:</u>				
None				
V. <u>Other Conservation/Load Management Measures Implemented: (Non-Capital)</u>				
a) Rendering Process was Shut Down				
b) 100 kW/month and 30,000 kWh to HP of Load (Motor Compressor) has been transferred to the late afternoon shift and should be off from current peak (no kWh) savings				
Savings:	Estimated	Actual		
	50 kW	50 kW		

SIC 26 PAPER PRODUCTS

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Solar Film	\$ 400	6-16-76	9-14-76	
2) Storm Windows	2,300	6-16-76	9-14-76	
3) Supplemental Heat	1,700			
4) Ceiling Fans	2,400	6-16-76		
5) Timing System for Pulper	300	"		
6) Timer for Hot Water Heater	150	"	2/77	
TOTAL	\$ 7,250			
II. <u>Items Implemmented:</u>				
5) Timing System for the Pulper	\$ 300	-		
6) Timer for Hot Water Heater	150	2/77		
TOTAL	\$ 450			
III. <u>Items Rejected:</u>				
3) Infra-Red Spot Heaters	\$ 1,700	9-14-76		
IV. <u>Items Under Review/Undecided/Problem:</u>				
1) Solar Film	\$ 400			Budget problems - no implemented yet.
2) Storm Windows	2,300			Budget problems - no implemented yet.
4) Ceiling Fans	2,400			Undecided - possible fume problems.
TOTAL	\$ 5,100			
V. <u>Other Conservation/Load Management Measures Implemented:</u>				
a) Provided shelters on railroad dock doors.				
b) Painted skylight windows.				
c) Lowered Thermostats.				
d) Circulating flash-off steam into plant heating system - (Water Recovery)				
e) Reusing cooled water.				
f) Secured all exterior openings.				
VI. <u>Savings:</u>	Estimated	Actual		
	107 kW	18 kW		

SIC 28 PAINTS AND VARNISHES

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Install Timers and Interlocks	\$ 800	5-28-76	5-28-76	
2) Battery Charger Control	125		12-10-76	
3) Ceiling Fans	2,500			
4) Electric Heaters	2,000			
5) Removal of Lighting	-		12-10-76	
6) Install New Lighting System	1,500		12-10-76	
TOTAL	\$ 6,925			
II. <u>Items Implemented:</u>				
2) Battery Charger Control	\$ 125	1-10-77		
5) Removal of Lighting	-	1-3-77		
III. <u>Items Rejected:</u>				
3) Ceiling Fans	\$ 2,500	12-10-76		Would create fire hazard because of fumes.
4) Electric Heaters	2,000	9-27-76		Portable heaters are used in each location
TOTAL	\$ 4,500			
IV. <u>Items Under Review/Undecided/Problem:</u>				
1) Install Timers and Interlocks	\$ 800			Additional information is needed by management. No current plan for implementation.
6) Install New Lighting System	1,500			Considered but to-date not accepted by corporate management.
TOTAL	\$ 2,300			
V. <u>Other Conservation/Load Management Measures Implemented:</u>				
None				

Savings:

Estimated

Actual

10 kW

31 kW

SIC 30 RUBBER PRODUCTS

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Timers for Water Heaters	\$ 345	10-1-76	10-22-76	
2) Timers for Battery Chargers	360			
3) Remote Overhead Door Controls	840			
4) New Lighting System	<u>25,000</u>			
TOTAL	\$ 26,545			
II. <u>Items Implemented:</u>				
None				
III. <u>Items Rejected:</u>				
3) Remote Overhead Door Controls	\$ 840	10-22-76		
IV. <u>Items Under Review/Undecided/Problem:</u>				
1) Timers for Water Heaters	\$ 345			No decision taken to-date.
2) Timers for Battery Chargers	360			No decision taken to-date.
4) New Lighting System	25,000			Too much capital investment - probably will be done in 1978.
TOTAL	\$ 25,705			
V. <u>Other Conservation/Load Management Measures Implemented:</u>				
None				
VI. <u>Savings:</u>	Estimated	Actual		
	64 kW	- 0 -		

SIC 32 GLASS PRODUCTS

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Relocation of Lighting	\$ -	3-16-76	9-3-76	
2) Lighting Removal	-		"	
3) Vent Hood	2,000		"	
4) Low Velocity Fans	4,000			
5) Lighting Installation	7,500			
6) Demand Controller	18,000			
TOTAL	\$ 31,500			
II. <u>Items Implemented:</u>				
1) Relocation of Lighting	\$ 450	10/76		
2) Lighting Removal	600	"		
3) Vent Hood	1,300	11/76		
TOTAL	\$ 2,350			
I. <u>Items Rejected:</u>				
4) Low Velocity Fans	\$ 4,000	9-3-76		
6) Demand Controller	18,000	12-20-76		Due to excessive labor cost of installation - approximately \$15,000.
TOTAL	\$ 22,000			
IV. <u>Items Under Review/Undecided/Problem:</u>				
5) Lighting Installation	\$ 7,500			Still being considered
V. <u>Other Conservation/Load Management Measures Implemented:</u>				
a) Water Recovery has been implemented.				
b) Improved Maintenance.				
c) Monitoring efficiency of gas boilers and furnaces.				
I. <u>Savings:</u>	Estimated 200 kW	Actual 56 kW	and	a savings of \$5,000 due to water recovery.

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Battery Charger Control	\$ 300	6-16-76	8-23-76	
2) Scrap Chopper Control	300		"	
3) Lighting Removal	500		"	
4) Lighting Relocation	300		"	
5) Water Heater Control	145		"	
6) Demand Monitor	7,000		"	
7) Lighting Installations	470		"	
TOTAL	\$ 9,015			
II. <u>Items Implemented:</u>				
1) Battery Charger Control	\$ 300		8-23-76	
2) Chopper Control	300		8-23-76	
3) Lighting Removal	150		9-16-76	
4) Lighting Relocation	200		"	
5) Water Heater Control	145		"	
6) Demand Monitor	7,000			Installed
TOTAL	\$ 8,095			
III. <u>Items Rejected:</u>				
None				
IV. <u>Items Under Review/Undecided/Problem:</u>				
7) Lighting Installation	\$ 470			No action taken.
V. <u>Other Conservation/Load Management Measures Taken:</u>				
None				
VI. <u>Savings:</u>	Estimated	Actual		
	74 kW	69 kW		

SIC 33-B PRIMARY METALS

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Photo Cell to Control Lighting Load	\$ 300	6-23-76	6-30-76	
2) Special Area Switches	325		6-30-76	
3) A/C Timing Circuits in the new Office	350		6-30-76	
4) New (Office) Lighting	-		6-30-76	
5) New Lighting in the Old Productions Area	4,200			
6) Oil Compound Timer }	13,100		1-12-77	
7) Demand Monitor }				
8) Painting	-		6-30-76	
TOTAL	\$ 18,275			
II. <u>Items Implemented:</u>				
1) Photo Cell	\$ 300	8-30-76		
2) Switches	325	6-30-76		
4) New (Office) Lighting	-	6-30-76		
5) New Lighting in the Old Production Area	4,200	9-30-76		
7) Demand Monitor	13,100	4-1-77		
TOTAL	\$ 17,925			
III. <u>Items Rejected:</u>				
None				
IV. <u>Items Under Review/Undecided/Problem:</u>				
3) A/C Timing Circuits in the new Office	\$ 325			It will be done in the future.
6) Oil Compound Timer	-			No decision has been taken yet.
8) Painting	-	4-1-77		100% Completed
V. <u>Other Conservation/Load Management Measures Taken:</u>				
a) Insulation and Piping				100% complete.
b) Heat Recovery				100% for Process.
c) Thermal Barrier				Under Evaluation
d) Improved Control on Strip Dryers				Maintained
Savings:	Estimated 20 kW	Actual 67 kW		

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Timing Device for Heating Load	\$ 300	6-29-76	6-29-76	
2) Timing Device for Electric Forklift - off-peak	200		"	
3) Heat Recovery	-		"	
TOTAL	\$ 500			
II. <u>Items Implemented:</u>				
1) Timing Devices for Heating Load	\$ 300		11/76	
2) Timing Device for Electric Forklift	200		7/76	
TOTAL	\$ 500			
III. <u>Items Rejected:</u>				
None				
IV. <u>Items Under Review/Undecided/Problem:</u>				
3) Heat Recovery				Under investigation. Top management considers that own project with them is a waste of money. However, the individual at the plant is investigating our recommendations.
V. <u>Other Conservation/Load Management Measures Taken:</u>				
None				
VI. <u>Savings:</u>	Estimated	Actual		
	21 kW	21 kW		

SIC 34-B FABRICATED METALS

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Shifting of Buffing Machines	\$ -	6-10-76	8-20-76	
2) Installation of Lighting System	10,150		6-10-76	
3) Capacitor Fuses	200			
4) Heat Pump, Air Conditioning, and Heat Recovery	-			
TOTAL	\$ 10,350			
II. <u>Items Implemented:</u>				
2) Lighting System	\$ 10,150		10-21-76	
3) Capacitor Fuses	200		7-22-76	
4) Heat Pump, Air Conditioning, and Heat Recovery	3,000		4/77	Savings may not be indicated in the profit due to addition of more production equipment.
TOTAL	\$ 13,350			
III. <u>Items Rejected:</u>				
1) Shifting of Buffing Machine			3-77	
IV. <u>Items Under Review/Undecided/Problem:</u>				
None				
V. <u>Other Conservation/Load Management Measures Taken:</u>				
None				Installed second line - operating off-peak
VI. <u>Savings: (Monthly)</u>	Estimated	Actual		
	113 kW	48 kW	and	3200 kWh and 2% gas savings for 6 months.

SIC 34-C FABRICATED METALS

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Lighting Installation	\$ 1,000	6-29-76	9-14-76	
2) Lighting Removal	200			
3) Ceiling Fans	2,800			
4) Heat Pump				
5) Electric Furnace				
6) Heat Recovery				
7) Solid State Controls for Rectifiers	150,000			
8) Insulation of Process Tanks				
TOTAL	\$154,000			
II. <u>Items Implemented:</u>				
1) Lighting Installation	\$ 1,090		12-30-76	
2) Lighting Removal	75		11-19-76	
3) Ceiling Fans	3,100			
TOTAL	\$ 4,265			
III. <u>Items Rejected:</u>				
None				
IV. <u>Items Under Review/Undecided/Problem:</u>				
Items 4 through 8 are dependent upon decision concerning electric furnace.	\$150,000			Additional evaluation in progress
V. <u>Other Conservation/Load Management Measures Taken:</u>				
None				
VI. <u>Savings:</u>	Estimated	Actual		
	0 kW	\$22,000 gas savings/year followed by \$ 8,000 electric cost/year increase 50 kW Increase		

SIC 34-D FABRICATED METALS

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Control Stress Oven Heat	\$ -	7-27-76	7-27-76	
2) Change Lighting	440		"	
3) Damper Control	1,100		"	
4) Thermostat Replacement	10		"	
5) Shutting down Acid Tanks Over Weekend	-			
TOTAL	\$ 1,550			
II. <u>Items Implemented:</u>				
1) Control Stress Ovens	250			Special Manual Control is scheduled.
2) Change Lighting	470		9-22-76	
3) Damper Control	260		10-14-76	Manually controlled.
4) Thermostat Replacement	15			
TOTAL	\$ 995			
<u>Items Rejected:</u>				
5) Shutting Down Acid Tanks on the weekends	-		8-23-76	Cannot do due to long start-up on Monday.
V. <u>Items Under Review/Undecided/Problem:</u>				
None				
V. <u>Other Conservation/Load Management Measures Implemented:</u>				
All A/C in Offices is Received.				
VI. <u>Savings:</u>	Estimated	Actual		
	920 kWh/Mo.	50 kW -		
	6 months only			

SIC 35-A MACHINERY

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Timer for Hot Water Heater	\$ 150	7-7-76		
2) Fans	2,800			
3) Cycling Devices	400			
4) Interlocking Devices	700			
5) Lighting System	6,000			
6) Removal of Existing Lighting System	<u>1,000</u>			
TOTAL	\$ 11,050			
II. <u>Items Implemented:</u>				
None so far.				Possible rejections since there was no response from the customer.
III. <u>Saving:</u>	Estimated 70 kW	Actual 0		Did not implement anything.

SIC 35-B MACHINERY

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Make up Air Unit	\$ 3,000	6-23-76	6-23-76	
2) Time Control and Heat Lamps	450			
3) Infra-Red Spot Heaters	3,500			
4) Time Control on Water Heaters	300		6-23-76	
5) Lighting	-		6-23-76	
6) 10 kw Oven	700		6-23-76	
TOTAL	\$ 7,950			
I. <u>Items Implemented:</u>				
1) Make up Air Unit	\$ 5,240			Installation expected during Fall 1977
4) Time Control on Water Heaters	440		8-18-76	
5) Lighting	-		7-30-76	
6) 10 kw Oven	540		7-9-76	
TOTAL	\$ 6,220			
. <u>Items Rejected:</u>				
2) Time Control and Heat Lamps	450		6-23-76	
3) Infra-Red Spot Heaters	3,500		6-23-76	
TOTAL	\$ 3,950			
IV. <u>Items Under Review/Undecided/Problem:</u>				
None				
V. <u>Other Conservation/Load Management Measures Taken:</u>				
a) Maintenance and painting has been accomplished.				
b) Capacitors were installed to improve power factor.				
c) Welder Test conducted off-peak.				
I. <u>Savings:</u>	Estimated	Actual		
	15 kW	25 kW		

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Lighting Removal	\$ 4,000	5-23-76	6-23-76	
2) Lighting Installation	5,900			
3) Oven Control	-		6-23-76	
4) Water Heater Control	300		6-23-76	
5) M. G. Set Control	-		8-9-76	
6) Air Compressor - Damper	500		"	
7) Fans	<u>1,100</u>		-	
TOTAL	\$ 11,800			
II. <u>Items Implemented:</u>				
1) Lighting Removal	\$ 4,000		8-76	
2) Lighting Installation	-		-	Delayed until this space is needed
3) Oven Control	-		6-23-76	Disconnected
4) Water Heater Control	350		8-76	
5) M.G. Set Control	185		10-76	
6) Air Compressor Damper	90		-	Delayed due to space utilization changes.
7) Fans				
TOTAL	\$ 4,625			
III. <u>Items Rejected:</u>				
None				
IV. <u>Items Under Review/Undecided/Problem:</u>				
None				
V. <u>Other Conservation/Load Management Measures Implemented:</u>				
None				
VI. Savings:	Estimated	Actual		
	110 kW	118 kW		

SIC 35-D MACHINERY

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Water Heater Timers	\$ 575	8-11-76	10-21-76	
2) Solar Reflective Film	2,500		10-21-76	
3) Steam Leak Correction	-		8-11-76	
4) Pipe Insulation	-		"	
5) New Lighting System	109,000		"	
6) Removal of Old Lighting	<u>1,500</u>		"	
TOTAL	\$113,575			
II. <u>Items Implemented:</u>				
1) Timers Installed	700			Currently not operating Test area only Corrected
2) Solar Film	2,000			
3) Steam Leak	-			
4) Pipe Insulation	9,000			
5) New Lighting System	109,000	1-1-77		
6) Removal of Old Lighting	<u>-</u>	1-1-77		
TOTAL	\$120,700			
III. <u>Items Rejected:</u>				
None				
IV. <u>Items Under Review/Undecided/Problem:</u>				
None				
V. <u>Other Conservation/Load Management Measures Implemented:</u>				
a) Steam Leaks Corrected				No real Savings Expected
b) Pipe Insulation				
c) Cooling Tower Control				
d) Removal of Old Lighting				
VI. <u>Savings:</u>	Estimated	Actual		
	323 kW	332 kW	and	50 kw Off-Peak Only for Six Months

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Lighting Removal	\$ 500	7-13-76	9-14-76	
2) Lighting Relocation	300		"	
3) Non-Adjustable Thermostats	350		"	
4) Heat Pump for Recovery	10,000		"	
5) Water Loop Recovery	-		"	
6) Recuperations	-		"	
7) Insulation & Ceiling Fans	-		"	
TOTAL	\$ 11,150			
II. <u>Items Implemented:</u>				
1) Lighting Removal	\$ 300		12-10-76	
2) Lighting Relocation	190		"	
3) Non-Adjustable Thermostats	95		1-3-77	
4) Heat Pump & Recovery	130,000		Mid 77	
5) Water Loop Recovery	2,600		11-76	
7) Insulation & Ceiling Fans				On repair basis only Items 4 & 7 have been considered in a complete heat recovery system.
TOTAL	\$133,185			
III. <u>Items Rejected:</u>				
None				
IV. <u>Items Under Review/Undecided/Problem:</u>				
6) Recuperations				No decision has been taken.
V. <u>Other Conservation/Load Management Measures Implemented:</u>				
None				
VI. <u>Savings:</u>	Estimated	Actual		
	7 kW	10 kW		
	Increase			
	Gas savings of the order of \$27,000/year with an electric increase of 55 kW and 100,000kWh at a cost of \$5000/year.			

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) 30 HP Air Compressor	\$ 1,050	7-13-76	12-6-76	
2) Ceiling Fans	2,820		"	
3) Solar Film	200		"	
4) Water Pipe for A/C	100		"	
5) Unit Heaters	600		"	
6) Lighting System	<u>6,700</u>		"	
TOTAL	\$ 11,470			
II. <u>Items Implemented:</u>				
1) 30 HP Air Compressor	\$ 1,050		11-12-76	
2) Ceiling Fans	2,820		1-21-77	
3) Solar Film (Test Area)	200		Mid Summer	Under Investigation
4) Water Pipe for A/C	100		9-17-76	
5) Unit Heaters	600			Some removed & some Interlocked.
6) Lighting System	<u>6,700</u>		12-21-76	
TOTAL	\$ 11,470			
III. <u>Items Rejected:</u>				
None				
IV. <u>Items Under Review/Undecided/Problem:</u>				
None				
V. <u>Other Conservation/Load Management Measures Implemented:</u>				
a) They have three other buildings and are implementing similar measures in those buildings which we have not investigated.				
b) Employees are pointing out areas of savings to Management with financial reimbursement.				
VI. <u>Savings:</u>	Estimated	Actual		
	50 kW	-0-		

SIC 37-C TRANSPORTATION

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Lighting Installation	\$ 500	6-30-76	8-30-76	
2) Heat Recovery	3,500		"	
3) Close Duct Opening	300		"	
4) Fork Lift	75		"	
TOTAL	\$ 4,375			
II. <u>Items Implemented:</u>				
1) Lighting Installation	\$ 500		10-26-76	
3) Close Duct Opening	300		12-9-76	
4) Fork Lift (New installation)	75		8-30-76	
TOTAL	\$ 875			
III. <u>Items Rejected:</u>				
Valley hour operation			8-30-76	
IV. <u>Items Under Review/Undecided/Problem:</u>				
2) Heat Recovery				Still under consideration - not probable
V. <u>Other Conservation/Load Management Measures Implemented:</u>				
Air Conditioning Maintenance			7-30-76	
VI. <u>Savings:</u>	Estimated	Actual		
	- 0 -	- 0 -		

SIC 37-D TRANSPORTATION

TEST CUSTOMER

	Investment	Date Presented	Date Accepted	Comments
I. <u>Recommendations:</u>				
1) Warehouse Lighting	\$ 270	7-27-76	10-12-76	
2) Inspection Lighting	820		"	
TOTAL	\$ 1,090			
II. <u>Items Implemented:</u>				
None				No response from the customer ever since.
III. <u>Items Rejected:</u>				
None				
IV. <u>Items Under Review/Undecided/Problem:</u>				
None				
V. <u>Other Conservation/Load Management Measures Implemented:</u>				
None				
VI. <u>Savings:</u>	Estimated	Actual		Did not implement anything.
	- 0 -	- 0 -		

5. Average Length of the Test Period.

It was pointed out earlier that 16 of the total 20 test customers have implemented the proposal recommendations. Some customers have implemented the recommendations earlier than others; as such, the test period of each customer varied in months. Further, the savings to these customers would depend not only on the type of recommendations implemented, but the manner in which the day-to-day monitoring of the equipment installed was carried out during the experimental period. At no stage did we intervene during the course of the experiment, since we felt that our involvement during the experiment might bias the actual behavior of the management. However, we did assist in solving practical difficulties and problems faced by the customers at the time of installation of the equipment. The table below shows the test period dates and the approximate number of months each customer was tested.

Table 1 -- Test Period Dates and No. of Mos. Customer Tested

<u>SIC Code</u>	<u>Business</u>	<u>Test Period</u>	<u>No. of Months</u>
20	Food Products	11/76 - 6/77	8
26	Paper Products	2/77 - 6/77	5
27	Printing & Publishing	Special Case	-
28	Chemicals	1/77 - 6/77	6
30	Rubber Products	Not Implemented	-
32	Glass Products	11/76 - 6/77	8
33	<u>Primary Metals</u>		
	Company A	9/76 - 6/77	10
	Company B	11/76 - 6/77	8
34	<u>Fabricated Metals</u>		
	Company A	11/76 - 6/77	8
	Company B	10/76 - 6/77	9
	Company C	12/76 - 6/77	7
	Company D	9/76 - 6/77	10
35	<u>Machinery</u>		
	Company A	Not Implemented	-
	Company B	8/76 - 6/77	11
	Company C	10/76 - 6/77	9
	Company D	1/77 - 6/77	6
37	<u>Transportation</u>		
	Company A	1/77 - 6/77	6
	Company B	11/76 - 6/77	8
	Company C	11/76 - 6/77	6
	Company D	Not Implemented	-
Average Number of Months			<u>8</u>

6-A. Summary of Monthly Peak Demand (kW) Changes of the Test Customers During the Test Period.

Table 2 provides a relative comparison between the estimated peak demand changes and the actual peak demand changes of the 16 test customers who implemented the proposal recommendations. The first column of Table 2 shows the monthly peak demands of the 19 test group customers prior to the survey. The second column indicates the estimated monthly peak demands of the said 19 test customers that would have been expected if the customers had implemented 100% of the proposal recommendations (after the survey was conducted). The third and the fourth columns demonstrate the estimated and actual peak demand reductions. The fifth column gives the percentages of the estimated reductions compared to the actual peak demands of the customers that were presented in the first column. The sixth column presents the percentages of the actual reductions in peak demand achieved by the customers compared to the actual peak demands presented in the first column; and the last column provides the percentages of the actual peak demand savings presented in column four to the estimated savings in peak demand presented in the third column. The table also shows the total estimated and actual reductions in peak demand as well as the overall percentages of estimated and actual peak demand reductions. From the analysis of the results presented in Table 2, it follows:

FINDING 1 "The aggregate monthly peak demand savings of the 16 test customers was 845 kW which is about 70% of the estimated aggregate monthly peak demand savings of 1,220 kW."

FINDING 2 "The overall percentage saving in peak demand of the 16 test customers was about 6% compared to the estimated monthly peak demand savings of 7%."

6-B. Major Electrical Uses of the Test Companies by Specific Areas.

One of the major objectives of the study was not only to investigate for the maximum potential to reduce the peak demand but also to identify the specific areas in which greater potential for peak demand would exist. The major areas concentrated in the study were: lighting, HVAC, processing, and miscellaneous category which includes a variety of items such as hot water heaters, air compressors, forklift chargers, pollution equipment, computers, vent pumps, etc. The basic reason for selecting the above areas was that the test companies provided the information on Survey Form I regarding the major electrical uses within their plants, a summary analysis of which is presented in Table 3 that follows:

Table 2

SUMMARY OF MONTHLY PEAK KILOWATT CHANGES
Test Companies (1976-1977)

SIC Code	Business	Prior to Proposal kW (1)	After Proposal kW (2)	Estimated Change kW (3) = (1)-(2)	Actual Change kW (4)	Estimated Change % (5) = (3)÷(1)	Actual Change % (6) = (4)÷(1)	Actual Change % of Estimated Change (7) = (4)÷(3)
20	Food Products	1,480	1,430	(50)	(50)	(3.38)	(3.38)	100
26	Paper Products	800	693	(107)	(18)	(13.38)	(2.25)	17
27	Printing & Publishing	--	--	--	--	--	--	--
28	Chemicals	860	850	(10)	(31)	(1.16)	(3.60)	310
30	Rubber Products	1,100	1,036	(64)	0	(5.82)	0	0
32	Glass Products	1,950	1,750	(200)	(56)	(10.26)	(2.87)	28
33	<u>Primary Metals</u>							
	Company A	2,000	1,926	(74)	(69)	(3.70)	(3.45)	93
	Company B	360	340	(20)	(67)	(5.56)	(18.61)	335
34	<u>Fabricated Metals</u>							
	Company A	500	479	(21)	(21)	(4.20)	(4.20)	100
	Company B	1,450	1,337	(113)	(48)	(7.79)	(3.31)	42
	Company C	600	600	0	50	--	8.33	Increase
	Company D	600	600	0	(50)	--	(8.33)	Decrease
35	<u>Machinery (Except Elec.)</u>							
	Company A	500	430	(70)	0	(14.00)	0	0
	Company B	400	385	(15)	(25)	(3.75)	(6.25)	167
	Company C	380	270	(110)	(118)	(28.95)	(31.05)	107
	Company D	1,750	1,427	(323)	(332)	(18.46)	(18.97)	102
37	<u>Transportation</u>							
	Company A	380	387	7	(10)	1.84	(2.63)	Increase
	Company B	400	350	(50)	0	(12.50)	0	0
	Company C	550	550	0	0	--	0	0
	Company D	470	470	0	0	--	0	0
	TOTAL	16,530	15,310	(1,220)	(845)	(7.38)	(5.84)*	--
	AVERAGE	870	806	(64)	(44)	(7.36)	(5.06)**	(69)

NOTE: (a) Column (1) represents the average monthly kW consumptions of each customer prior to survey.
 (b) Column (2) represents the estimated average monthly kW consumption of the customers after survey was conducted.
 (c) Column (3) represents the difference of column (1) and column (2).
 (d) Column (4) represents actual savings realized after the implementation of proposal recommendations.
 (e) The customers representing SIC 3d, SIC 35-A and SIC 37-D, although accepted some of the proposal recommendations, did not implement any of the recommendations during the test period.

*Based on a total of 16 test companies that implemented the recommendations either partially or fully.

**Based on 19 test companies.

Table 3

Major Electrical Uses of the Test Companies by Specific Areas
(1975)

<u>Area</u>	<u>Estimated kWh</u>	<u>Estimated kW</u>
Lighting	15%	7%
HVAC	6	6
Processing	73	84
Miscellaneous	<u>6</u>	<u>3</u>
TOTAL	<u>100%</u>	<u>100%</u>

Table 3 points out that 84% of the peak demand was in the processing area, compared to 73% of energy use. In fact, there exists a maximum potential for peak demand reduction in the production area but the technical survey was limited to those peak demand reductions which would not interfere with the production processes and equipment.

Table 4
SUMMARY OF MONTHLY kW CHANGES BY SPECIFIC AREAS DURING THE TEST PERIOD
Test Companies 1976-77

SIC Code	Business	Reductions (kW)				Total Reduction	Increases (kW)				Total Increase	Net Change kW (Actual)	Estimated Net Change ***
		Lighting	HVAC	Processing	Miscellaneous		Lighting	HVAC	Processing	Miscellaneous			
20	Food Products	0	0	0	50	50	0	0	0	0	0	(50)	(50)
26	Paper Products	0	0	0	18 ¹	18	0	0	0	0	0	(18)	(107)
27	Printing & Publishing	0	0	0	0	0	0	0	0	0	0	0*	0
28	Chemicals	1	0	0	30	31	0	0	0	0	0	(31)	(10)
30	Rubber Products	0	0	0	0	0	0	0	0	0	0	0**	(64)
32	Glass Products	56	0	0	0	56	0	0	0	0	0	(56)	(200)
33	Primary Metals:												
	Company A	11	0	60 ⁵	4	75	5	0	0	0	5	(69)	(74)
	Company B	2	10	50 ⁵	17	79	12	0	0	0	12	(67)	(20)
34	Fabricated Metals:												
	Company A	0	0	0	21 ^{1,4}	21	0	0	0	0	0	(21)	(21)
	Company B	13	30	0	20	63	0	15	0	0	15	(40)	(113)
	Company C	0	0	0	0	0	0	50	0	0	50	50	0
	Company D	0	0	40	10	50	0	0	0	0	0	(50)	0
35	Machinery:												
	Company A	0	0	0	0	0	0	0	0	0	0	0**	(70)
	Company B	0	0	10	25	35	0	5	3	1	10	(25)	(15)
	Company C	46	70	0	18 ¹	134	8	8	0	0	16	(118)	(110)
	Company D	492	0	0	24 ¹	516	104	0	0	0	184	(332)	(323)
37	Transportation:												
	Company A	40	10	3	16	69	4	55	0	0	59	(10)	7
	Company B	0	0	0	0	0	0	0	0	0	0	0	(50)
	Company C	0	0	0	0	0	0	0	0	0	0	0	0
	Company D	0	0	0	0	0	0	0	0	0	0	0**	0
TOTAL:		661	120	163	253	1,197	214	134	3	1	352	(845)	(1,220)
AVERAGE:****		41	9	10	16	75	14	8	-	-	22	(53)	(64)

¹Water heaters; ²Heat recovery--considerable gas savings; ³Air compressor; ⁴Electric fork lift chargers; ⁵Demand control system

*Special proposal

**Company did not implement any of the proposed recommendations.

***Estimated on the assumption that all the proposed recommendations were implemented.

****Averages are computed using 16 companies.

6-C. Summary of Monthly kW Changes by Specific Areas.

In Table 2, the aggregate monthly peak demand savings (845 kW) was presented. Table 4 shows the distribution of the 845 kW reduction due to specific areas -- lighting, processing, HVAC, and miscellaneous items. The left-hand side of Table 4 shows the actual reductions attributable to the above mentioned areas, and the right-hand side of the table indicates the magnitude of the increases. The increases in peak demand were due to the implementation of specific recommendations of the proposal by the customer. For example, in the lighting area, the existing (prior to survey) substandard lighting was updated by using ANSI and OSHA minimum standards. This caused some peak demand increase. In other cases, the increases in the use of electricity were offset by dollar savings in natural gas. The details of the individual recommendations were documented in their respective proposals.¹ The last two columns of the table show a comparative picture of the actual net peak demand (kW) savings and the estimated net peak demand savings. A summary analysis of the actual and estimated peak demand reductions due to specific areas is presented in Table 5 below:

Table 5

A Comparison Between Estimated and Actual Monthly Net Reduction in Peak Demand (kW) of the Test Companies Due to Load Management*

<u>Areas</u>	<u>Estimated Peak Demand Reduction kW</u>	<u>% Net Reduction to Total kW</u>	<u>Actual Net Peak Demand Reduction kW</u>	<u>% Net Peak Demand Reduction to Total kW</u>
Lighting	484	39.7	447	52.9
HVAC	86	7.1	(14)	(1.6)**
Processing	413	33.8	160	18.9
Miscellaneous	<u>237</u>	<u>19.4</u>	<u>252</u>	<u>29.8</u>
TOTAL	<u>1,220</u>	<u>100.0</u>	<u>845</u>	<u>100.0</u>

*Derived from Table 4.

**Bracketed figures indicate increases.

The results presented in Table 5 suggest the following:

FINDING 3 "Of the total peak demand reduction of 845 kW, about 53% was in the lighting area, 30% was in the miscellaneous category, approximately 19% reduction was in the processing area, and a small increase of 2% was in the HVAC system. The above mentioned actual percentage reductions can be compared with the estimated percentage reductions: lighting - 40%, miscellaneous - 19%, processing - 34%, and HVAC - 7%."

¹The individual customer proposals (detailed) are not presented in this report; however, they are available with DOE.

Table 6

Distribution of Estimated and Actual Net Percentage Reductions
in Peak Demand by Specific Areas Due to Load Management
Compared to 1975 Monthly Peak Demand Consumption

<u>Areas</u>	<u>Test Companies</u>	
	<u>Estimated % Peak Demand Reduction/Month</u>	<u>Actual % Peak Demand Reduction/Month</u>
Lighting	2.93	3.09
HUAC	.52	(.10)
Processing	2.50	1.11
Miscellaneous	<u>1.43</u>	<u>1.74</u>
TOTAL	7.38	5.84*

*The total monthly peak demand (KW) of 19 test companies for 1975 (SIC 27 not included) was 16,530 kW, whereas the total monthly peak demand (kW) of 16 test companies for 1975 was 14,460 kW, excluding the three customers who did not implement anything.

The total monthly savings for 19 test companies compared to 1975 peak kW was estimated at 1,220 kW assuming that all the proposal recommendations were implemented.

The total monthly savings for 16 test companies during the test period was 845.

(1) Estimated monthly savings (%) in peak demand compared to 1975	=	$\frac{1,220}{16,530}$
	=	7.38%
(2) Actual monthly savings (%) in peak demand during the test period compared to 1975	=	$\frac{845}{14,460}$
	=	5.84%

Bracketed figures indicate an increase.

Derived from Table 5.

Chart I

A Comparison Between the Estimated and Actual Net Percentage Reduction in Peak Demand of the Test Companies Due to Load Management and the Percentage Reductions Due to Specific Areas

The results are not surprising since a large majority of the test customers have implemented lighting, HVAC, and miscellaneous recommendations. The actual peak demand reduction associated with processing is rather disappointing despite the fact that almost 70-80% of the loads are used for processing. The proposal recommendations in this area involved heavy capital expenditure items such as demand control systems, and other non-capital expenditure items such as shift changes and similar load management measures; and as such, the customers were reluctant to make any significant changes in the production processes, e.g. shift changes due to uncertainties of the risks involved. For example, the additional labor cost of shift premiums might far outweigh the savings associated with load management. In other words, under 1976 rates some of the proposal recommendations were not cost-justified.

6-D. Distribution of Estimated and Actual Net Percentage Reductions
in Peak Demand by Specific Areas.

It was pointed out in Table 2 that the overall percentage net reduction in peak demand was 6%. Table 6 shows the distribution of this overall percentage to specific areas: lighting, HVAC, processing, and miscellaneous items. The results presented in Table 6 indicate the following conclusion:

FINDING 4 "Of the overall 6% peak demand reduction, approximately 3% was in the lighting area, about 2% was in the miscellaneous category, 1% was in processing and an insignificant increase of .1% in the HVAC system."

Table 7
SUMMARY OF MONTHLY kWh CHANGES BY SPECIFIC AREAS DURING THE TEST PERIOD
Test Companies 1976-77

SIC Code	Business	Reductions (kWh)				Total Reduction	Increases (kWh)				Total Increase	Net Change kWh (Actual)	Estimated Net Change ***
		Lighting	HVAC	Processing	Miscellaneous		Lighting	HVAC	Processing	Miscellaneous			
20	Food Products	0	0	0	4,500	4,500	0	0	0	0	0	(4,500)	(2,000)
26	Paper Products	0	0	0	1,620 ¹	1,620	0	0	0	0	0	(1,620)	2,000
27	Printing & Publishing	0	0	0	0	0	0	0	0	0	0	0*	0
28	Chemicals	372	0	0	2,700	3,072	0	0	0	0	0	(3,072)	(58,720)
30	Rubber Products	0	0	0	0	0	0	0	0	0	0	0**	(22,400)
32	Glass Products	20,832	0	0	0	20,832	0	0	0	0	0	(20,832)	(30,000)
33	Primary Metals:												
	Company A	4,092	0	3,360 ⁵	360	7,812	2,232	0	0	0	2,232	(5,580)	1,200
	Company B	744	1,940	2,800 ⁵	1,530	7,014	4,464	0	0	0	4,464	(2,550)	4,900
34	Fabricated Metals:												
	Company A	0	0	0	1,890 ¹	1,890	0	0	0	0	0	(1,890)	0
	Company B	4,816	5,820	0	1,800	12,456	0	2,910	0	0	2,910	(9,546)	(4,750)
	Company C	0	0	0	0	0	0	9,700	0	0	9,700	9,700	0
	Company D	0	0	2,240	900	3,140	0	0	0	0	0	(3,140)	0
35	Machinery:												
	Company A	0	0	0	0	0	0	0	0	0	0	0**	(10,000)
	Company B	0	0	560	2,250	2,810	0	1,164	168	90	1,422	(1,388)	10,000
	Company C	17,112	14,744	0	1,620	33,476	2,976	1,552	0	0	4,528	(28,948)	(9,400)
	Company D	183,024	0	0	2,160 ¹	185,184	68,448	0	0	0	68,448	(116,736)	(107,850)
37	Transportation:												
	Company A	14,880	1,940	160	1,440	18,420	1,408	10,670	0	0	12,158	(6,270)	32,000
	Company B	0	0	0	0	0	0	0	0	0	0	0	(5,000)
	Company C	0	0	0	0	0	0	0	0	0	0	0	(8,000)
	Company D	0	0	0	0	0	0	0	0	0	0	0**	0
TOTAL:		245,092	24,444	9,128	22,770	302,234	79,608	25,996	168	90	105,862	(196,372)	(208,050)
AVERAGE:****		15,368	1,528	571	1,423	18,890	4,976	1,625	10	6	6,617	(12,273)	(10,950)

¹Water heaters; ²Heat recovery - considerable gas savings; ³Air compressor; ⁴Electric fork lift chargers; ⁵Demand control system

*Special proposal

**Company did not implement any of the proposed recommendations.

***Estimated on the assumption that all the proposed recommendations were implemented.

****Average is computed using 16 companies; bracket figures indicate net decreases.

6-E. Summary of Monthly kWh Changes by Specific Areas During the Test Period.

In the preceeding section, the analysis of net peak demand (kW) reductions of the test companies during the test period was presented.

This section deals with the analysis of net kilowatt-hour (kWh) reductions of the test companies during the test period. The analysis focuses not only on the total net kWh reductions, but also identifies the total kWh reductions due to major areas -- lighting, processing, heating ventilation and air conditioning (HVAC), and miscellaneous categories.

Table 7 presents in detail the individual test customer kWh changes and the corresponding net reductions or increases in some cases. The last column of the table indicates the estimated net kWh reductions on the assumption that 100% of the proposals were implemented by the test customers. Table 7 reveals the following finding:

FINDING 5 "The aggregate monthly total reduction of the 16 test customers who implemented the proposal recommendations was 196,372 kilowatt-hours; but about 60% of the above total was saved by one test customer alone, representing SIC 35 D - Machinery. The actual net kWh savings of seven of the 16 customers were higher than the estimated savings. The actual average kWh savings per customer (12,273 kWh) was about 12% higher than the estimated average kWh savings per customer (10,950 kWh). The overall percentage savings in kWh was about 4% -- see Table 9)."

Table 8 shows the distribution of the total net kWh reduction due to lighting, HVAC, processing, and miscellaneous items.

FINDING 6 "About 85% of the total kWh reduction occurred in the lighting area, about 12% reduction occurred in the miscellaneous category, approximately 5% in processing, and less than 1% increase occurred in HVAC."

Table 8

Summary of Estimated and Actual Net kWh Reductions by
Area Due to Load Management

Areas	<u>Test Companies</u>					
	Estimated net kWh Reduction/ Month	Average net kWh Reduction/ Month*	% of Total	Actual net kWh Reduction/ Month	Average net kWh Reduction/ Month**	% of Total
Lighting	180,330	9,491	86.7	166,284	10,392	84.7
HUAC	(16,700)	(879)	(8.0)	(1,552)	(97)	(0.8)
Processing	23,000	1,211	11.0	8,960	560	4.6
Misc.	21,420	1,127	10.3	22,680	1,418	11.5
TOTAL Net Reduction	208,050	10,950	100.0	196,372	12,273	100.0

Bracketed figures indicate increases.

* Averages are based on 20 test companies.

** Averages are based on 16 test companies as 4 out of 20 test companies did not implement any of the proposed recommendations.

Derived from Table 7.

6-F. A Summary of Estimated and Actual Percentage Savings in kW and kWh.

A relative comparison between the estimated and the actual net percentage savings in kW and kWh of the test customers is presented in Table 9. The table identifies the following finding which is a composite picture of Findings 2 and 6.

FINDING 7 "The test customers saved on the average about 6% in peak demand compared to the average estimated percentage savings of 7.4%. However, the actual average percentage savings in kWh was about 3.74 as compared to the average estimated percentage savings of 3.91. The customers saved fairly close to the estimated percentage in kWh but about 1% less on the peak demand side."

Table 9

ESTIMATED AND ACTUAL PERCENTAGE MONTHLY REDUCTION IN
ELECTRICAL ENERGY DUE TO LOAD MANAGEMENT COMPARED TO
1976 (BEFORE PROPOSAL), CONSUMPTION

Test Companies

SIC Code	Business	% Peak Demand (kW) Reduction		% Energy (kWh) Reduction	
		Estimated ¹	Actual ²	Estimated ¹	Actual ²
20	Food Products	3.38	3.38	--	.71
26	Paper Products	13.38	2.25	(.52)**	.42
27	Printing & Pub- lishing	--*	--	--	--
28	Chemicals	1.16	3.60	23.23	1.04
30	Rubber Products	5.82	-0-	5.60	-0-
32	Glass Products	10.26	2.87	8.06	2.49
33	<u>Primary Metals</u>				
	Company A	3.70	3.45	(.25)**	.89
	Company B	5.56	18.61	(5.88)**	1.04
34	<u>Fabricated Metals</u>				
	Company A	4.20	4.20	--	1.29
	Company B	7.79	3.31	1.11	2.14
	Company C	--	(8.33)	--	(4.85)
	Company D	--	8.33	--	1.38
35	<u>Machinery</u>				
	Company A	14.00	-0-	4.76	-0-
	Company B	3.75	6.25	(6.25)**	.84
	Company C	28.95	31.05	10.80	23.49
	Company D	18.46	18.97	13.73	21.11
37	<u>Transportation</u>				
	Company A	(1.84)**	2.63	(13.86)**	4.11
	Company B	12.50	--	6.15	--
	Company C	--	--	4.55	--
	Company D	--	-0-	--	-0-
AVERAGE		7.38	5.84 ³	3.91	3.74 ³

¹Estimated on the assumption that all the proposal recommendations were implemented.

²The results of actual experiment.

³Based on 16 companies that implemented the recommendations.

*No formal recommendations were made.

**Increases in energy consumption.

Derived from Tables 2 & 7

Zeros (-0-) indicate that these companies did not implement any of the recommendations.

Table 10

Distribution of Estimated and Actual Net Percentage kWh Reductions
By Area Due to Load Management Compared to 1975 kWh Consumption

<u>Areas</u>	<u>Test Companies</u>	
	<u>Estimated % Reduction/Month</u>	<u>Actual % Reduction/Month</u>
Lighting	2.91	3.16
HUAC	(.27)	(.02)
Processing	.37	.17
Miscellaneous	<u>.35</u>	<u>.43</u>
TOTAL	3.36	3.74*

*The total monthly energy consumption (kWh) of 20 test companies for 1975 was 6,182,838 kW hours. The total energy consumption (kWh) of 16 test companies for 1975 which implemented the proposal recommendations was 5,253,876 kW hours.

The total saving due to load management (estimated) was 208,050 kWh, and the actual total savings in kWh during the test period/month was 196,372.

$$\begin{aligned}
 (1) \text{ Estimated Savings} &= \frac{208,050}{6,182,838} \\
 &= 3.36\% \text{ (for 20 test companies)}
 \end{aligned}$$

$$\begin{aligned}
 (2) \text{ Actual Savings} &= \frac{196,372}{5,253,876} \\
 &= 3.74\% \text{ (for 16 test companies)}
 \end{aligned}$$

Bracketed figures indicate an increase.

Derived from Tables 7 and 8.

Chart II

SUMMARY OF ESTIMATED AND ACTUAL NET KWH
REDUCTIONS BY AREA DUE TO LOAD MANAGEMENT

Reference Table 9.

6-G. A Comparison between Estimated and Actual Dollar Savings Due to Load Management.

Table 11 gives a relative comparison between estimated and actual annual dollar savings due to load management by using the old rates * The table reveals the following findings:

FINDING 8 "About 65% of the actual total dollar savings was attributable to peak demand reduction compared to the estimated 70%. The remaining 35% of the actual total dollar reduction was due to energy (kWh) as compared to the estimated 30% of the \$94,243 actual savings of which one customer saved almost \$43,796 (46%). The average actual dollar savings per customer was approximately \$6,000 compared to the estimated annual dollar savings of \$6,500 per customer. Deleting customer SIC 35-D who saved almost 46% of the total savings, the actual average annual dollar savings would be approximately \$3,000."

* Detroit Edison

Primary rate (1976)

\$160 service charge/customer/month

Demand Charges

\$6.00/kW for first 1,000 kW
5.90/kW for next 9,000 kW
5.70/kW for the excess

1.5¢/kWh for all kWh consumed
during the on-peak period
(9 a.m. - 9 p.m.)
1.3¢/kWh for all kWh consumed
during the off-peak period

Plus fuel adjustment and purchased power clauses.

Table 11
A COMPARISON BETWEEN ESTIMATED AND ACTUAL ANNUAL DOLLAR SAVINGS (ELECTRIC)
Test Companies 1976-77

SIC Code	Business	Estimated Dollar Savings Due to Load Management					Actual Dollar Savings			
		kW	kWh	Elec. Total	Gas Savings*	Total Savings	kW	kWh	Elec. Total	
		\$	\$	\$	\$		\$	\$	\$	
20	Food Products	3,600	0	3,600	0	3,600	3,600	745	4,345	
26	Paper Products	7,704	(336)	7,368	412	7,780	1,296	272	1,568	
27	Printing & Publishing	--	--	--	--	--	--	--	--	
28	Chemicals	720	12,096	12,816	5,000	1,786	2,232	516	2,748	
30	Rubber Products	4,608	3,817	8,425	0	8,425	--	--	--	
32	Glass Products	14,400	10,535	24,935	0	24,935	4,032	3,600	7,632	
33	<u>Primary Metals</u>									
	Company A	5,328	(202)	5,126	0	5,126	4,968	937	5,905	
	Company B	1,440	(1,680)	(240)	500	260	4,824	428	5,252	
34	<u>Fabricated Metals</u>									
	Company A	1,512	0	1,512	--	--	1,512	324	1,836	
	Company B	8,064	810	8,874	0	8,874	3,456	1,627	5,083	
	Company C	0	0	0	600	600	(3,600)	(1,653)	(5,253)	
	Company D	0	0	0	0	0	3,600	538	4,138	
35	<u>Machinery</u>									
	Company A	5,040	1,704	6,744	500	7,244	--	--	--	
	Company B	1,080	(1,716)	(636)	3,000	2,364	1,800	238	2,038	
	Company C	7,920	1,579	9,499	0	9,499	8,496	4,863	13,359	
	Company D	23,256	11,928	35,184	4,000	39,184	23,904	19,892	43,796	
37	<u>Transportation</u>									
	Company A	(504)	(3,770)	(4,274)	2,700	(1,574)	720	1,076	1,796	
	Company B	3,600	1,363	4,963	1,000	5,963	--	--	--	
	Company C	0	846	846	2,600	3,446	--	--	--	
	Company D	0	0	0	0	0	--	--	--	
	TOTAL	87,768	36,974	124,742	20,312	145,054	60,840	33,403	94,243	
	PERCENT SAVINGS	70%	30%	86%	14%	100%	65%	35%	100%	

*We did not estimate all the gas savings. The estimated gas savings could be attributable to offsetting increases in electric consumption in many places. Further, the corresponding gas savings during the test period were not available.

7. Average On/Off Peak Percent Consumption of Electrical Energy (kWh) by the Test and Control Customers (Monday-Sunday).

Table 12 shows actual percentages of on-peak and off-peak consumption of energy by the test and control companies before and after the test period. It also shows the on-peak percentage change in consumption both by test and control companies. The following finding emerges from Table 12:

FINDING 9 "Fifteen (15) out of a total of 20 test customers were able to shift their energy (kWh) consumption from on-peak to off-peak period during the test period as compared to the pre-test period. On the average, both test and control customers were able to shift their on-peak energy consumption to off-peak period by about one percent; but, the individual percentage peak reductions of a large majority of the test customers were higher, compared to the corresponding control customers. It is evident that there exists a possibility to shift (reduce) on-peak energy consumption to off-peak period. However, the possibility for peak levels or peak day shifts depends on the individual consumption patterns, mode of operation, process type, labor force, rate incentives, etc. The SIC groups, which experienced the largest percentage shift from on-peak to off-peak were: Primary Metals (4%) and Machinery (4%). Food Products and Transportation shifted their on-peak energy to off-peak by about three percent on the average. These were followed by Transportation (2%), Glass Products, Rubber Products, Printing & Publishing were able to shift by about one percent each."

8. Average Load and Power Factors of Test and Control Companies.

Table 13 presents the average load and power factors of the test and control companies before and after the test period. The following findings are self-evident from the table.

FINDING 10 "The average load factors of five of the test group customers who implemented 70-100 percent of the proposal recommendations were improved by about 2.2 percent during the test period as compared to pre-test period average load factors. The average load factors of the corresponding control companies have declined approximately four percent compared to the pre-test period load factors. In fact, one test customer (SIC 33-B) who installed the demand monitor control system has improved his load factor by seven percent during the test period. The average load factors of seven test customers who implemented about 40-70 percent of the proposal recommendations have improved by about 1.1 percent. The average load factors of four test customers who carried out 10-40 percent of the recommendations have slipped by about one percent. Whereas, the average load factor

of the corresponding control customers declined by 15.5 percent. The average load factors of four of the test customers who did not implement any of the proposal recommendations declined by approximately 2.5 percent compared to their pre-test period load factors. Thus, load management has had a significant impact in improving the load factors of the sample test group customers who implemented the load management techniques."

FINDING 11 "There was no change in the overall average power factors of the test and control companies during the test period as compared to the pre-test period's power factors. However, the overall average power factor of the test companies was three percent lower than the overall average power factor of the control companies both in pre- and post-test periods. Also, the individual power factors of a large majority of the test customers were consistently lower than the power factors of the control companies."

Table 12

AVERAGE PERCENTAGE ON-PEAK AND OFF-PEAK MONTHLY CONSUMPTION OF ELECTRICAL ENERGY (KWH)
BY THE TEST AND CONTROL COMPANIES PRIOR TO TEST PERIOD AND DURING THE TEST PERIOD
(Monday - Sunday)

SIC Code	Business	Test Companies				On-peak % Change	Control Companies				On-peak % Change
		Prior to Test Period		Test Period			Prior to Control Period		Control Period		
		On-peak %	Off-peak %	On-peak %	Off-peak %		On-peak %	Off-peak %	On-peak %	Off-peak %	
20	Food Products	49	51	46	54	(3)	41	59	42	58	1
26	Paper Products	36	64	37	63	1	50	50	49	51	(1)
27	Printing & Publishing	54	46	53	47	(1)	42	58	41	59	(1)
28	Chemicals	49	51	52	48	3	50	50	45	55	-0-
30	Rubber Products	50	50	49	51	(1)	43	57	45	55	2
32	Glass Products	52	48	51	49	(1)	47	53	50	50	3
33	<u>Primary Metals</u>										
	Company A	56	44	54	46	(2)	42	58	40	60	(2)
	Company B	43	57	38	62	(5)	38	62	37	63	(1)
	Average	53	47	49	51	(4)	42	58	40	60	(2)
34	<u>Fabricated Metals</u>										
	Company A	62	38	60	40	(2)	59	41	58	42	(1)
	Company B	57	43	56	44	(1)	52	48	49	51	(3)
	Company C	51	49	48	52	(3)	56	44	54	46	(2)
	Company D	46	54	46	54	-0-	--	--	--	--	--
	Average	55	45	53	47	(2)	55	45	52	48	(3)
35	<u>Machinery</u>										
	Company A	50	50	48	52	(2)	52	48	48	52	(4)
	Company B	48	52	46	54	(2)	--	--	--	--	--
	Company C	71	29	55	45	(16)	62	38	56	44	(6)
	Company D	43	57	47	53	4	45	55	44	56	(1)
	Average	53	47	49	51	(4)	48	52	47	53	(1)
37	<u>Transportation</u>										
	Company A	47	53	45	55	(2)	46	54	47	53	1
	Company B	60	40	56	44	(4)	48	52	48	52	-0-
	Company C	44	56	59	41	3	50	50	61	39	1
	Company D	58	42	54	46	(4)	47	53	46	54	(1)
	Average	55	45	52	48	(3)	48	52	49	51	3
	OVERALL AVERAGE	50	50	49	51	(1)	46	54	45	55	(1)

Bracketed figures indicate reduction.

Table 13

AVERAGE LOAD AND POWER FACTORS OF TEST AND CONTROL COMPANIES
PRIOR TO TEST PERIOD AND DURING TEST PERIOD (MONDAY - SUNDAY)

SIC Code	SIC Description	Test Companies Average Load Factor			Control Companies Average Load Factor			Test Companies Average Power Factor			Control Companies Average Power Factor		
		Prior Period %	Test Period %	% Change	Prior Period %	Control Period %	% Change	Prior Period %	Test Period %	% Change	Prior Period %	Control Period %	% Change
20	Food Products	82	77	(5)	89	91	2	75	72	(3)P	87	87	--
26	Paper Products	97	90	(7)	81	90	9	85	85	--	85	83	(2)P
27	Printing & Publishing	60	49	(11)	72	86	14	81	60	(1)P	77	78	1P
28	Chemicals	86	87	1	89	88	(2)	87	88	1	89	94	5
30	Rubber Products	85	84	(1)	93	77	(16)	84	68	4	95	94	(1)
32	Glass Products	78	80	2	89	62	(27)	84	85	1	79	84	5P
33	Primary Metals												
	Company A	85	81	(4)	89	77	(12)	90	84	(4)	93	96	3
	Company B	65	72	7	71	73	2	35	74	(1)P	87	97	10
	Average	75	76	1	80	75	(5)	64	80	(8)	95	97	2
34	Fabricated Metals												
	Company A	71	74	3	61	52	(9)	80	83	3P	88	90	2
	Company B	74	75	1	54	57	3	89	90	1	88	84	(4)P
	Company C	64	48	(16)	34	38	4	84	87	3	94	93	(1)
	Company D	80	91	11	--	--	--	92	90	(2)	--	--	--
	Average	67	70	3	40	49	11	84	88	4	90	89	(1)
35	Machinery												
	Company A	69	71	2	71	63	(12)	31	81	50P	90	90	--
	Company B	96	88	(8)	--	--	--	75	75	--	--	--	--
	Company C	87	92	5	77	82	5	83	81	(2)P	87	87	--
	Company D	71	73	2	97	98	(1)	80	79	(1)P	86	85	(1)
	Average	83	86	3	82	84	2	80	79	(1)	89	87	(1)
37	Transportation												
	Company A	82	91	(9)	81	68	(13)	91	91	--	90	88	(2)
	Company B	79	87	8	73	76	3	87	92	5	83	83	--
	Company C	70	66	(4)	82	54	(28)	92	95	3	90	89	(1)
	Company D	75	65	(9)	93	88	(5)	77	72	(5)P	74	73	(1)
	Average	79	78	(1)	82	72	(10)	86	88	2	84	83	(1)
OVERALL AVERAGE		78	78	+0-	78	73	(5)	84	84	+0-	87	87	+0-

NOTE 1) Bracketed figures indicate decrease

2) P = Penalty - The term power factor generally means the relationship between the amount of energy utilized by a customer facility and the amount of energy supplied by the electric utility to the customer. A power power factor, which is expressed as percentage implies that the facility utilizes lower amount of energy compared to the amount supplied. The utility customer is required to maintain a power factor of 85 percent or greater. If the power factor falls below the required minimum of 85 percent, the utility informs the customer to correct the situation. If it is not corrected, the following schedule of penalty will be charged to the customer's monthly bill:

Power factor between	Percent	Penalty (Percent of total monthly bill)
85 - 90	1	
80 - 75	2	
75 - 70	3	
70 or less	3	percent penalty for the first two months, and if the situation is not corrected, the penalty in the third month and thereafter will be 25 percent of total monthly bill until the poor power factor situation is corrected

C. An Analysis of the Impact of New vs. Old Rates on the Test Customers

It was pointed out that the objective of this study was to explore the potential possibilities for electric load management in regard to the industrial sector. It was not the objective of the study to review the impact of the customer response with respect to any set of predesigned rates; on the other hand, the prime concern was to measure the impact and the feasibility of direct load management techniques.

The results presented in Chapter III relating to annual dollar savings, payback periods, etc., were derived using the old rates which were valid until May 27, 1977. On May 28, 1977, while the experiment was being conducted for the sample test group customers, a revised rate structure applicable to the primary industrial customers went into effect. The objective of the following analysis is first to measure the impact of the revised (new) rates in terms of the changes in annual dollar savings, payback periods of the test customers and to assess whether the new rates would promote the objective of load management, and second, to identify a set of demand rates that would provide a 24-month payback of these test customers whose investments did not meet the criterion of 24 months and to gauge the additional cost burden on these customers. This analysis is intended to provide some clues to the policymaker as to the nature and consequences in case such measures were implemented to the population of industrial customers having the same characteristics of the sample test and control customers. First, the impact of the new rates on the sample test customers is presented. The primary rates both old and revised are presented below:

Primary Rate (Old Rate until May 27, 1977) - Detroit Edison

\$160 Service Charge/Customer/Month

Demand Charges

\$6.00/kW for first 1,000 kW
5.90/kW for next 9,000 kW
5.75/kW for the excess.

Energy Charges

1.5¢/kWh for all kWh consumed
during on-peak period
(9 a.m. to 9 p.m.)
1.3¢/kWh for all kWh consumed
during off-peak period.

Plus fuel adjustment and purchased power clauses.

New Rate (Effective from May 28, 1977)

\$162 Service Charge/Customer/Month

Demand Charges

\$4.97/kW of on-peak billing demand
1.20/kW for first 1,000 kW of
contract capacity
.90/kW for next 9,000 kW of
contract capacity
.60/kW for excess kW of contract
capacity

Energy Charges

1.7¢/kWh for all kWh consumed
during on-peak period (9 a.m.
to 9 p.m.)
1.5¢/kWh for all kWh consumed
during off-peak period

It is to be noted that the concept of contract capacity was introduced in the new rate structure on the assumption that certain amount of capacity (transformers, etc.) would have to be installed at the customer premises by the utility and the customer has to pay the rental cost of this fixed equipment whether or not the customer uses the maximum capacity. If the customer exceeds the contract capacity, the new record would automatically be the maximum capacity; on the other hand, if the customer uses less than the contract capacity, he would have to pay the full cost of the contract capacity. As can be seen, there was no such provision for contract capacity in the old rate. Another feature of the new rate is that the demand charge was reduced from \$6.00/kW to \$4.97/kW. The basic objective of the new rate design has been (1) to meet the additional cost burden of the utility and to implement the cost of service methodology. That is, users of electric power would have to bear the cost burdens according to time patterns of use.

Table 14 shows (1) the contract capacity, (2) average monthly demands (kW) and average monthly energy use (kWh), and (3) the average percent of the time the customers were on-peak and off-peak during 1976. Table 15 details the annual billing costs of the sample test customers using the old rates as well as the new rates mentioned above. The table shows that on the average the annual billing costs of the customers were increased by about nine percent by using the new rates, compared to the annual billing costs of the customers derived by applying the old rates.

Table 14

CONTRACT CAPACITY, AVERAGE MONTHLY PEAK DEMAND, AND ENERGY.
ON-OFF PEAK PERCENTAGES OF THE TEST COMPANIES - 1976

SIC Code	Business	Contract Capacity kW	Peak Demand kW	Energy kWh	(Monday-Friday)	
					On-peak	Off-peak
20	Food Products	1,652	1,480	592,000	60	40
26	Paper Products	870	800	387,000	50	50
28	Chemicals	1,024	860	310,000	50	50
30	Rubber Products	1,230	1,100	400,000	60	40
32	Glass Products	2,208	1,950	754,000	72	28
33	<u>Primary Metals</u>					
	Company A	2,790	2,000	487,000	50	50
	Company B	422	360	170,000	50	50
34	<u>Fabricated Metals</u>					
	Company A	666	500	149,000	65	35
	Company B	1,578	1,450	428,750	60	40
	Company C	780	600	163,000	60	40
	Company D	676	600	230,000	65	35
35	<u>Machinery</u>					
	Company A	560	500	210,000	60	40
	Company B	460	400	160,000	65	35
	Company C	480	380	87,000	50	50
	Company D	2,175	1,750	510,000	60	40
37	<u>Transportation</u>					
	Company A	456	380	152,000	65	35
	Company B	454	400	130,000	60	40
	Company C	584	550	110,000	55	45
	Company D	624	470	145,000	70	30

Table 15

AN ANALYSIS OF THE IMPACT ON OLD VS. NEW RATE STRUCTURE
ON THE ANNUAL BILLING COST OF TEST COMPANIES*

Test Unit	Business	On-peak rate ¢/kWh	Off-peak rate ¢/kWh	Billing Costs (Old Rates)				Billing Costs (New Rates)				Increase for On-Peak Consumption \$	Increase for Off-peak Consumption \$	Total Increase in Billing \$
				On-peak (kWh)	Off-peak (kWh)	On-peak Total kWh	Total Billing \$	On-peak (kWh)	Off-peak (kWh)	On-peak Total kWh	Total Billing \$			
20	Food Products	50	40	105,984	64,392	170,376	207,621	109,711	72,461	182,172	224,796	11,796	7,379	17,175
26	Paper Products	50	50	57,600	35,079	92,679	123,113	60,240	30,474	90,714	134,544	7,035	4,396	11,431
27	Printing & Publishing	-	-	-	-	-	-	-	-	-	-	-	-	-
28	Chemicals	50	50	61,920	20,090	82,010	114,398	65,954	31,620	97,574	125,474	7,555	3,521	11,076
30	Hardware Products	60	40	79,000	41,508	120,508	147,754	82,468	40,960	123,428	160,248	8,660	3,634	12,294
32	Glass Products	72	28	139,260	98,413	237,673	270,079	143,742	110,740	254,482	292,402	16,817	4,796	21,613
33	Primary Metals Company A	50	50	142,000	44,143	186,143	225,241	153,012	40,674	193,686	246,516	15,743	5,532	21,275
	Company B	50	50	25,920	15,409	41,329	54,498	27,542	17,340	44,882	60,182	3,553	1,931	5,484
34	Fabricated Metals Company A	65	35	36,000	17,557	53,557	61,759	39,408	19,757	59,165	68,552	5,608	1,185	6,793
	Company B	60	40	101,860	46,636	148,496	177,470	109,206	52,479	161,685	192,555	11,189	3,896	15,085
	Company C	60	40	43,200	17,729	60,929	71,184	47,516	19,951	67,467	78,703	6,038	1,481	7,519
	Company D	65	35	43,200	27,102	70,302	82,963	45,516	30,498	76,014	90,504	5,712	1,829	7,541
35	Machinery Company A	60	40	36,000	22,812	58,812	72,054	37,884	25,708	63,592	78,708	4,746	1,908	6,654
	Company B	65	35	20,800	18,853	39,653	56,461	30,480	21,216	51,696	61,776	4,003	1,272	5,275
	Company C	50	50	27,360	7,806	35,166	42,068	29,575	8,874	38,449	46,279	3,203	988	4,191
	Company D	60	40	125,100	55,473	180,573	212,659	131,466	62,424	193,890	230,610	13,317	4,634	17,951
37	Transportation Company A	65	35	27,360	17,913	45,273	53,638	29,227	20,155	49,382	58,958	4,131	1,209	5,340
	Company B	60	40	20,800	14,140	34,940	51,119	30,396	15,912	46,308	55,668	3,368	1,141	4,509
	Company C	55	45	39,600	10,968	50,568	58,350	41,214	12,342	53,556	62,466	2,968	1,125	4,093
	Company D	70	30	33,840	18,400	52,240	59,082	37,019	20,706	57,725	65,555	5,485	988	6,473
Total				1,185,600	604,540	1,790,140	2,142,534	1,251,096	680,295	1,931,391	2,334,506	141,167	50,895	192,062

Data used is derived from Table 3 of the financial feasibility of load management investments.

Old Rate	Service Charge	\$160/month
	Demand Charge	\$6.00/kW for the first 1,000 kilowatts \$ 90/kW for the next 9,000 kilowatts \$ 75/kW for the excess
	Energy Charge	1.5¢/kWh for all kWh consumed during on-peak period (9 a.m. to 9 p.m.) 1.3¢/kWh for all kWh consumed during off-peak period Plus full adjustment charge 1.0¢/kWh for all kWh consumed

New Rate	Service Charge	\$162/month
5/77	Demand Charge	\$4.97/kW for on peak demand 1.20¢/kW for first 1,000 kW of contract capacity 90¢/kW for next 9,000 kW of contract capacity 60¢/kW for excess kW of contract capacity
	Energy Charge	1.7¢/kWh for all kWh consumed during on-peak period 1.5¢/kWh for all kWh consumed during off-peak period

*Applied to actual average monthly demand and energy (kWh) consumption of the companies
In other words, the kW's and kWh's were fixed, but the rates varied

Table 16 shows the annual billing cost increases attributable to demand and energy due to the implementation of the new rates. Table 17 provides the percentage increases of the billing costs presented in Table 16 and the percentage utilization of contract capacity. Table 18 summarizes the percentage annual billing cost increases classified according to time of use of energy and demand; and Table 19 presents the relationship between the utilization of contract capacity and the percentage billings increase related to demand. The results presented in Tables 18 and 19 suggest the following conclusions with respect to the impact of new rates applicable to the sample test group customers.

FINDING 12 "The higher the on-peak energy use, the higher the average increase in cost which is consistent with the cost of service theory as well as the objectives of load management. On the demand side, the higher the contract percentage utilization, the lower the increase in the demand billing cost on the average; or the lower the percentage utilization of contract capacity, the higher will be the percentage increase in billing demand cost. The contract capacity argument appears to be weaker in the context of load management. Overall, about 75% of the annual billing cost increase could be attributable to on-peak demand and on-peak energy consumption, and the remaining 25% was due to off-peak utilization of energy."

The above finding indicates that the new rates induce the industrial customers to adopt the load management techniques. However, a relative comparison of the annual dollar savings arrived by using the new and old rates, which are presented in Table 20, indicates that there has been a consistent decrease in savings of the sample test customers. The decrease in dollar savings will increase the payback periods of the customers which, in turn, discourages the customers to implement load management measures. This is due to the fact that the contract capacity theory concentrates more on the percentage utilization rather than reducing the peak demand.

To what extent the old demand rate (\$6/kW) should be increased so that some of the unattractive load management investments presented in Table 19 of Chapter III would meet 24 months payback criteria? Table 21 provides the extent to which the old demand rate should be increased in order to arrive at 24-month payback of the load management investments of the customers.

Table 16

ANNUAL INCREASE IN BILLING COSTS BY COMPONENTS DUE TO NEW RATES

SIC Code	Business	Increase Due to Demand \$	Increase Due to On-peak Energy \$	Increase Due to Off-peak Energy \$	Total Increase \$	Percent	
						On-peak %	Off-peak %
20	Food Products	3,727	8,069	5,379	17,175	60	40
26	Paper Products	2,640	4,395	4,396	11,431	50	50
28	Chemicals	4,034	3,521	3,521	11,076	50	50
30	Rubber Products	3,408	5,452	3,634	12,494	60	40
32	Glass Products	4,482	12,335	4,796	21,613	72	28
33	<u>Primary Metals</u>						
	Company A	10,212	5,531	5,532	21,275	50	50
	Company B	1,622	1,931	1,931	5,484	50	50
34	<u>Fabricated Metals</u>						
	Company A	3,408	2,200	1,185	6,793	65	35
	Company B	5,346	5,843	3,896	15,085	60	40
	Company C	3,816	2,222	1,481	7,519	60	40
	Company D	2,316	3,396	1,829	7,541	65	35
35	<u>Machinery</u>						
	Company A	1,884	2,862	1,908	6,654	60	40
	Company B	1,680	2,363	1,272	5,315	65	35
	Company C	2,215	988	988	4,191	50	50
	Company D	6,366	6,951	4,634	17,951	60	40
37	<u>Transportation</u>						
	Company A	1,867	2,244	1,209	5,320	65	35
	Company B	1,596	1,772	1,181	4,549	60	40
	Company C	1,614	1,374	1,125	4,113	55	45
	Company D	3,179	2,306	988	6,473	70	30

Derived from Table 15.

Table 17

PERCENTAGE INCREASE IN ANNUAL BILLING COSTS BY COMPONENTS DUE TO
NEW RATES AND THE PERCENTAGES OF THE CONTRACT CAPACITY UTILIZED IN 1976

SIC Code	Business	% of Contract Capacity Utilized	% Increase in Demand	% Increase in On-peak Energy	% Increase in Off-peak Energy	On-peak %	Off-peak %
20	Food Products	90	22	47	31	60	40
26	Paper Products	92	23	38	39	50	50
28	Chemicals	84	36	32	32	50	50
30	Rubber Products	89	27	44	29	60	40
32	Glass Products	88	21	57	22	72	28
33	<u>Primary Metals</u>						
	Company A	72	48	26	26	50	50
	Company B	85	30	35	35	50	50
34	<u>Fabricated Metals</u>						
	Company A	75	50	32	18	65	35
	Company B	92	35	39	26	60	40
	Company C	77	51	29	20	60	40
	Company D	89	31	45	24	65	35
35	<u>Machinery</u>						
	Company A	89	28	43	29	60	40
	Company B	87	32	44	24	65	35
	Company C	79	53	23	24	50	50
	Company D	80	35	39	26	60	40
37	<u>Transportation</u>						
	Company A	83	35	42	23	65	35
	Company B	88	35	39	26	60	40
	Company C	94	39	33	28	55	45
	Company D	75	49	36	15	70	30

Derived from Table 16.

Table 18

Summary of the Percentage Increases in Annual Billing Costs of
Demand and Energy (kWh) According to Percentage On-off Periods

	<u>Percent On- Off-peak</u>		<u>On-peak % Increase in Billing Cost</u>	<u>Off-peak % Increase in Billing Cost</u>	<u>Percent Increase in Demand</u>
	<u>On-</u>	<u>Off-</u>			
Group I	50	50	23	24	23
			26	26	30
			32	32	36
			33	28	39
			35	35	48
			38	39	53
		Average Increase	31	31	46
Group II	60	40	29	20	22
			39	26	27
			39	26	28
			39	26	35
			43	29	35
			44	29	35
		Average Increase	47	31	51
Group III	65	35	32	18	31
			42	23	32
			44	24	35
			45	24	50
		Average Increase	41	22	37
Group IV	70	30	36	15	21
			57	22	49
	72	28	Average Increase	19	35

Derived from Table 17.

TABLE 19

Relationship Between the Percent of Contract Capacity Utilized and the Percent Increase in Annual Billing Cost Attributable to Demand (kW)

	<u>On Peak</u> %	<u>Off Peak</u> %	<u>Percent of</u> <u>Contract</u> <u>Capacity</u> <u>Utilized</u>	<u>Percent Increase</u> <u>In Demand</u> <u>Billing Cost</u>
Group I	50	50	92	23
			85	30
			84	36
			<u>79</u>	<u>53</u>
		Average	<u>85</u>	<u>36</u>
Group II	55	45	94	39
Group III	60	40	92	35
			90	22
			89	27
			89	28
			88	35
			80	35
			<u>77</u>	<u>51</u>
		Average	<u>86</u>	<u>33</u>
Group IV	65	35	89	31
			87	32
			83	35
			<u>75</u>	<u>50</u>
		Average	<u>84</u>	<u>37</u>
Group	70	30	88	21
			<u>75</u>	<u>49</u>
		Average	<u>82</u>	<u>35</u>

Derived from Table 17.

Table 70

ANALYSIS OF ESTIMATED AND ACTUAL ELECTRIC DOLLAR SAVINGS
AND A RELATIVE COMPARISON BETWEEN OLD AND NEW RATES

SIC Code	Business	Estimated Total Savings Due to Load Management				Actual Total Savings Due to Load Management				On-peak (Monday-Friday) %	Off-Peak %
		Old Rates \$	New Rates \$	Difference \$	Percent Difference %	Old Rates \$	New Rates \$	Difference \$	Percent Difference %		
20	Food Products	3,600	2,982	(618)	(17)	4,345	3,835	(510)	(12)	60	40
26	Paper Products	7,368	6,765	(603)	(8)	1,568	1,385	(183)	(12)	50	50
27	Printing & Publishing	-	-	-	-	-	-	-	-	-	-
28	Chemicals	12,816	14,420	1,604	13	2,748	2,439	(309)	(11)	50	50
30	Rubber Products	8,425	8,172	(253)	(3)	0	0	0	0	60	40
32	Glass Products	24,935	23,922	(1,013)	(4)	7,632	7,450	(182)	(2)	70	30
33	Primary Metals										
	Company A	5,126	4,183	(943)	(18)	5,905	5,186	(719)	(12)	50	50
	Company B	(240)	(727)	487	203	5,252	4,486	(766)	(15)	50	50
34	Lubricated Metals										
	Company A	1,512	1,252	(260)	(17)	1,836	1,622	(214)	(12)	65	35
	Company B	8,874	7,662	(1,212)	(14)	5,083	4,719	(364)	(7)	60	40
	Company C	0	0	0	0	(5,253)	(4,868)	385	7	60	40
	Company D	0	0	0	0	4,138	3,596	(542)	(13)	65	35
35	Machinery										
	Company A	6,744	6,119	(625)	(9)	0	0	0	0	60	40
	Company B	(636)	(1,061)	425	67	2,038	1,763	(275)	(13)	65	35
	Company C	9,499	8,365	(1,134)	(12)	13,359	12,596	(763)	(6)	50	50
	Company D	35,184	32,872	(2,312)	(7)	43,796	42,494	(1,302)	(3)	60	40
37	Transportation										
	Company A	(4,274)	(4,693)	419	10	1,796	1,824	28	2	65	35
	Company B	4,963	4,537	(426)	(9)	0	0	0	0	60	40
	Company C	846	966	120	14	0	0	0	0	55	45
	Company D	0	0	0	0	0	0	0	0	70	30
	TOTAL	124,742	115,736	(9,006)	(7)	94,243	88,527	(5,716)	(6)	--	--
	AVERAGE	6,565*	6,091	(474)	(7)	5,890**	5,533	(357)	(6)	58	42

*Based on 19 customers

**Based on 16 customers

Bracketed Figures Indicate Decreases

Table 21

Estimated Demand Rates to Provide 24-Month Payback
of Load Management Investments

<u>SIC Code</u>	<u>Load Mgmt. Investment</u> \$	<u>Initial Payback Period Using Old Rates</u> (Months)	<u>Demand Rate Needed to Arrive at 4-month Payback</u> \$/kW	<u>Increase in Annual Billing Cost of the Customer</u> %
20	11,075	94	12.50	56
30	26,545	73	15.00	139
33-A	9,270	32	7.25	13
35-A	11,500	28	7.50	12
-B	7,950	81	26.00	162
-D	113,575	56	17.00	106
37-B	9,900	30	8.20	2-

The above table points out the fact that the annual billing cost of electricity would be substantially increased for the customers representing SIC's 20, 30, 35-B, and 35-D by adopting those demand rates which would produce a 24-month payback of their load management investments.

As was pointed out at the beginning of the impact analysis of new rates that increasing the demand charge was a hypothetical exercise, as such, modifications of the existing demand and energy charges and the peak period (9 a.m. to 9 p.m.) were not considered in the main text.

CHAPTER V

SYSTEM-WIDE IMPLEMENTATION

- A. Projected Savings on the Detroit Edison System
- B. System-wide and Multi System-wide Implementation of Demonstrated Activities
- C. Conclusions
- D. Recommendations

A. Projected Savings on the Detroit Edison System

In the preceding chapter, it was found that the sample test group customers, on the average, were able to save approximately six percent of their peak demand, and about four percent of energy consumption, by adopting energy management methods, which were recommended in their proposals. It is important to note that the above-mentioned savings were achieved through the voluntary cooperation of the sample industrial customers and under the prevailing time-of-day rates applicable to primary industrial customers.

It was pointed out in the sample selection criteria (Chapter II) that the test sample was derived from a population of small and medium category of manufacturing industrial customers having their monthly primary demands less than or equal to 6,000 kW. The potential savings that might be expected of large primary industrial customers and the corresponding impact on the Detroit Edison system was not a part of the projected savings and was not a part of the study by design. As can be expected, the estimated savings that are presented in this section could probably be much higher if one includes large industrial customers.

The primary focus here is to determine the potential savings that would be expected in the short run on the Detroit Edison system by extrapolating the results of the study to the population of small and medium type industrial customers, and under ceteris paribus assumptions - i.e., assuming the same rate structure, etc. In the short run, it is reasonable to assume that things will not change drastically. In the long run, it is possible that several or all of the variables may change. For example, if the demand and energy rates are increased, say, 25 percent, the impact on the system would, perhaps, be much higher compared to the impact derived under ceteris paribus conditions.

The ultimate objective was to identify and to quantify the potential reduction in peak loads on the system due to load management. Reduction of peak loads or shifting the loads from on-peak to off-peak would imply (1) improvement in average load factor of the system, (2) availability of additional base load kWh's to the existing customers/new customers or to spinning reserves, (3) reduction in the consumption of non-renewable fuels - natural gas and oils, (4) efficient allocation of resources, and (5) reduced average cost to the customers.

The short run annual savings that would be expected as a result of this study are summarized in the following table:

Table 1

Estimated Annual Megawatt Reduction on the
Detroit Edison System Due to Energy Management

SIC Code (1)	Business (2)	Annual Demand (MW) (3)	Max. Contribution to System Peak (MW) (4)	Reduction Due to Energy Mgmt. (MW) (5)
20	Food Products	45	31.5	1.0
26	Paper Products	39	27.3	3.0
27	Printing & Publ.	16	11.2	0
28	Chemicals	33	23.1	.3
30	Rubber Products	49	34.3	1.4
32	Glass Products	61	42.7	3.1
33	Primary Metals	458*	120.0**	4.0
34	Fabricated Metals	70	49.0	1.0
35	Machinery	126	88.2	10.0
37	Transportation	1,020*	372.0**	7.0
TOTAL		1,917	799.3	30.8

*Includes all Primary Metals and Major Automotives.

**Major Steel and Automotives are deleted.

Column (3) of the above table indicates the annual aggregates of individual industrial class demands and the total annual demand. The aggregate annual demand of the Primary Metal group is comprised of all Primary Metal industries including large industries such as steel. Similarly, the total demand of the transportation group is comprised of big auto industries. Column (4) of the table represents the individual class MW contribution to peak demand and the aggregate annual peak MW contribution. Column (5) represents the estimated MW reduction in peak demand by the industrial customers representing the SIC groups. These figures are arrived at by reducing the maximum contribution to system peak using an average coincidence factor of 70 percent and multiplying the resulting contributions to system peak by the individual estimated percentage reductions presented in Table 18 of Chapter III of this report.

The table shows that adoption of load management methods would be expected to reduce the need for new generating capacity by 31 MW. In the short run, what this implies is that the savings can be made available to new customers or can be supplied to meet the additional demands of the existing customers without any additional generating capacity requirements, or can be added to spinning reserves. For example, capacity purchases from other systems that are required to maintain adequate on-peak reserves may be reduced to the extent of 31 MW. A typical capacity charge for a six-month period is about \$13 per season. Another major benefit results from reducing the total requirement for installed capacity, which costs over \$700 per kW. In other words, the installed capacity that can be deferred, at least in the short term, would be \$22 million. Assuming status quo, the estimated savings would imply reduced consumption of high-cost or restricted fuels followed by reduced average cost to the existing customers and improved load factors to the system.

B. System-wide and Multi System-wide Implementation of Demonstrated Activities

Electric utility systems are not alike. They differ widely with respect to many factors such as: basic design; generation mix--percent of base load, intermediate load, peak load and purchased power; type of fuels used--hydro, nuclear, coal, oil, wood; capital structure; percent of the type of customers served--residential, commercial, industrial and their aggregate annual loads and by seasons; geographic location of the customers--urban, suburban, rural; usage patterns of the customers; appliance stock; existing production technologies; average daily, weekly, monthly and annual load factors of the customers and the servicing utility; the inter and intra class diversity factors of the customers; availability and substitutability of alternative forms of energy sources; relative prices of these alternative fuels; prevailing rate structure--promotional, traditional declining block type, flat and time-of-day rates; climatic conditions; economic growth, income levels and growth patterns in demand; and regulatory atmosphere. The operating structure of the utilities also varies. For instance, some utilities do not generate electricity but purchase from other utilities for the purpose of sale; some utilities partly generate their own and buy the rest from neighboring utilities through interconnected arrangements to meet either the emergencies or to supplement their required spinning reserves; and others generate their own power to meet the demands of their customers and to sell additional power to other utility systems. Despite these basic differences, it is not hard to find at least some utilities having approximately similar characteristics but which may still differ with respect to their load duration, load patterns summer vs. winter peaks, etc.

The industrial sector of the economy absorbs about 40 percent of all electric sales in the U.S. In Michigan, the industrial sector consumed about 46 percent of total electric sales during 1975. In particular, the industrial customers of Detroit Edison Company consume about 50 percent of total electricity generated and contribute approximately 40 percent of the peak demand.

The industrial demand for energy, in economic terms, is a derived demand. There are many factors contributing to this demand. One of these factors is the responsiveness of the industry towards price changes. For instance, the response of a manufacturer's demands depends on how responsive sales of his/her product are to price changes. The second factor is the technology associated with the production processes of the industry. The technological process and type of existing technology associated with the industry is a prime determinant of industry's ability to adjust its demand requirements and energy use. The third factor which largely determines energy use per unit of output within an industry or a firm, is the product mix. The fourth factor is the energy versus labor intensiveness of the industry. The fifth factor is the capacity utilization. For example, when capacity utilization is low, energy use per unit of output is high. Similarly, when capacity utilization is very high, energy use per unit of output is often high. There exists an optimum level where energy use per unit of output is

minimized. Sixth, substitutability of one type of energy to others capital for labor and vice-versa. Seventh, nature and type of pollution equipment that uses more energy for water and air pollution control; and systems that would enable the recovery of materials that are formerly discharged into the air or water--heat and water recovery systems. Eighth, energy efficient systems with multiple zonal controls which use considerably small amount of energy for producing the same or even larger quantity of products - high intensity lighting systems, heat pumps, water heaters, and other production equipment. And ninth, economic feasibility of shifting certain operations to use off-peak hours compared to shift premium differential to be paid to the labor force.

Efficiency in production and efficiency in energy use are two different things. Efficiency of production does not necessarily mean minimizing the energy output ratio. It is, in economic terms, efficient to produce at the lowest possible total cost per unit. This may well mean, in some cases, raising the energy output ratio. A firm may be efficient from a profit maximization point but may be inefficient from the standpoint of energy consumption.

The basic question remains. That is, to what extent can the experiences gained from the project be generalized? First, the methods and procedures that were developed in the study could be utilized with minor changes to identify the production systems - lighting, HVAC, processing and miscellaneous items which use electrical energy. These methods are simple and straightforward. By following the sequential steps developed in the technical survey procedures, economic analysis, and data analysis of the study, one can have careful track of all energy-bearing materials that enter a plant in order to determine where the energy is used and how efficiently it is used. This basic approach permits the detection of problem areas where energy savings can be realized in those industries having similar characteristics to that of the sample test group customers. There exists significant possibilities to save energy as the technical surveys of the study revealed that a large number of small and medium type of industries did not have energy management programs of their own. In larger manufacturing industries such as Transportation, that have instituted energy management procedures, information regarding the past savings in energy use are available; but there is little knowledge of the amount of savings with respect to a large number of small and medium type of industries. Systematic energy audits were very rare. One result of this is that individual plants or firms, prepare weak projections of their energy use because they do not know the past trends.

The past and present patterns of the industrial customers are essential to identify the probable nature and extent of savings. For instance, in 1975, the industrial sector of the State of Michigan consumed about 25.3 percent of total energy consumed in the state of which 10.9 percent was coal and oils, 10.3 percent was natural gas, and 4.1 percent was electric. A comparative picture of the relative percentages of energy consumed as measured in Btu's by industry in

Michigan, the nation, and the sample test group customers by type of fuels is given below:

Table 2

Relative Comparison of Energy Consumed in Michigan and the Nation - 1975

TYPE OF FUELS	Industrial Sector		Test Group
	Michigan 1975 %	U.S. 1974 %	Industrial Custo- mers 1975
Electric	16.0	13.4	20
Natural Gas	43.0	52.0	70
Oils, coal, etc.	41.0	34.6	10
TOTAL	100.0	100.0	100

SOURCE: Michigan Energy Administration and Bureau of Mines

The table shows that well over 80 percent of the total energy consumed by the industrial sector in Michigan was other than electric. Less than 20 percent of the Btu's consumed by the industrial sector in the nation and in Michigan was electric. The study identified that there exists possibilities for switching from other types of energy in the future. This process may accelerate much faster if the prices of oils, natural gas, and coal start escalating. Further, there may even exist critical shortages in the supply of natural gas and oils in the near future. Moreover, industries located in the urban areas may be restricted from using coal in many cases due to environmental hazards.

Future energy use by manufacturing sector depends on the speed at which substitutability takes place. In addition, the analysis of the technical surveys identified a greater potential for natural gas savings which may induce, perhaps, greater consumption of electric power. A scientifically conducted energy audit will provide clues to what and where to look for energy savings. Such methods can be replicated either on a system-wide or multi system-wide basis.

Utilities, regulatory commissions, federal and state energy agencies should develop and provide an operational mechanism to assist the industrial sector in conducting energy audits and provide the necessary impetus for an ongoing energy management program for the industry. The sample test customers are fully aware of the energy shortages and responded favorably by implementing the load management techniques. It is encouraging to note that many of these customers have allocated significant amounts for energy management in their operating budgets. The extent of savings that would be expected by the industrial sector across utilities in the nation depend primarily on the factors mentioned in the preceding sections - operating modes of industry, types of fuels used, cost of alternative fuels, the rate structure, etc.

C. Conclusions

This section outlines the following: (1) what were the significant accomplishments of the study, (2) what were the areas which were identified but were not addressed at length in this report, and (3) summary conclusions.

1. Major Accomplishments

- a. For the first time in this country, an attempt was made in demonstrating the fact that adoption of load management techniques by the industrial sector could influence the load and capacity factors of an electric generating system. It was shown that by altering the usage patterns of industrial customers through energy management, 31 MW of generating capacity could be reduced on the Detroit Edison system.
- b. Although fragmentary information was available in reducing or shifting consumer usage patterns through incentive mechanisms such as interruptible loads, off-peak utilization, etc., nothing was done to explore the specific areas and ways in which users may be encouraged to shift usage patterns. The study was able to identify, systematically, the areas in which greater potential for peak demand reduction would exist. The areas include: lighting, heating, ventilation, air conditioning (HVAC), processing and miscellaneous items such as water heaters, pollution equipment, dampers, battery chargers, fans, etc.
- c. The study was able to identify by areas other than electric consumption. For instance, potential exists for natural gas savings, and there exist possibilities for converting natural gas and oils to electric in many industrial plants surveyed. Opportunities for co-generation exist in larger plants compared to the small and medium type industries.
- d. The study was able to identify the areas which would benefit from small capital improvements to increase energy utilization during the off-peak period or affect peak usage. This category includes demand controllers and other controlling devices on water heaters, battery chargers, air conditioning, lighting systems, compressors, blowers, heat pumps, etc. Other items which indirectly affect the usage patterns are: thermal barriers, interlocks, storm windows, vent hoods, auxiliary fans, electric pumps and solar reflective films.
- e. Recommendations were made affecting those aspects of system processes which could be shifted to off-peak utilization. Examples of these are:

SIC 20 - Food Products: Defrosting the coolers during nighttime or using the compressors differently,

SIC 26 - Paper Products: Start the operation of the air conditioning system sooner in the morning in order to overcome the daytime solar heat gains,

SIC 34-D - Fabricated Metals: Install demand limiting devices for the stress relieving ovens and also in the building addition which is electrically heated,

SIC 37-C - Transportation: Charge the electric fork-lift units during off-peak periods.

Although recommendations were made to the above industries, significant number of test customers were able to utilize off-peak consumption during the test period as compared to the pre-test period.

- f. Detailed methods and procedures were developed for implementing the demonstrated activities on a system-wide or multi system-wide basis. The methods are well thought out and carefully designed. The model and the methods as outlined in Chapter II of this report could as well be applied directly to those industrial plants having characteristics similar to those of the test customers or any type of industrial plant with minor modifications.
- g. A total of 20 proposals were prepared, 19 of which were presented to the managements of the test customers for approval and implementation. Sixteen of a total of 19 test group customers participated in the test by implementing a majority of the proposal recommendations on a voluntary basis.
- h. A comprehensive and detailed analysis of the test was conducted for a test group customer representing SIC 33-B. The customer received a sum of \$8,235 from FEA towards the purchase of a demand control system as presented in Appendix B of this report. This customer was highly pleased with the savings achieved through demand management and has written a letter of appreciation to the project manager suggesting that other industrial plants should implement load management techniques to save energy and dollars.
- i. One of the encouraging highlights of the study was that during the surveys and monitoring of the test, numerous questions arose concerning additional energy saving technologies beyond the scope of the project. For example, in the heat recovery area, several test customers inquired into the types of equipment available to recover heated air from (90°F to 350°F) various production areas, the customers put aside, while implementing, due to the unattractive payback of estimated capital investments. The analysis of the technical surveys showed that approximately two percent of the total Btu's can

be recovered from areas such as transformer rooms, large enclosed motors, rectifiers, high bay ventilation fans and small furnaces and ovens, to maintain 65°F in production and non-critical areas. The dollar investments required to recover heat with respect to some of the test customers were: SIC 28 - \$4,000, SIC 34 - \$28,000, SIC 35 - \$7,000, and SIC 34 - \$18,000. These customers allocated the amounts to implement the remaining areas of suggested recommendations in due course.

In the area of controls, numerous electric temperature control systems are being installed within office spaces which previously had either a single master control or manual dampers with multiple control systems. An example of this involves a test customer who is planning to purchase several water source heat pumps with multiple control systems to replace the existing hot water boiler system and window air conditioners. The management expects the payback on the investment within two-to-three years. Other customers who have budgeted to implement the control devices are: SIC 33 - \$7,500, SIC 34 - \$3,500, and SIC 35 - \$9,000. Further, several customers who are using a large portion of their energy in the form of natural gas inquired about the methods and means of saving natural gas. In fact, they expressed that a survey of similar nature would help identify the areas of inefficient utilization and potential possibilities for additional savings.

- j. The study was able to identify the factors which would hasten or impede system-wide implementation. Factors that would hasten system-wide implementation are:
 - (1) Appropriate rate design that gives greater incentives for off-peak utilization.
 - (2) Tax incentives, subsidies and low interest loans for energy conservation and load management.
 - (3) Assist in conducting energy audits of the existing industrial users by the utilities.
 - (4) Develop an energy management program by the utility to assist the new industries or industrial parks developers in the initial designs of the new facilities and processes.
 - (5) Develop a training program to provide seminars on a regular basis for the management staff of the industry focusing on the latest developments regarding the energy saving/reducing technologies and load management methods.

Factors that would impede system-wide implementation are:

- (1) Unattractive payback periods of load management investments under free market rates.
 - (2) The rate design that does not encourage off-peak utilization.
 - (3) The characteristics of certain industrial processes, mode of operations, and the mix of industry. For instance, industries which are capital intensive and whose production technology mandate 24-hour or three-shift operations would have to focus primarily on increasing efficiency of usage rather than substantial shifts in usage.
 - (4) Labor cost associated with shift differential (shift premiums) and the willingness of the labor force or unions to work other than normal working hours.
 - (5) Marginal, and very low profitable firms and firms riddled with vintage technology and aged structures are not attracted very easily. Old and obsolete plants anticipating a move to another location with a new facility would probably not undertake the investment.
 - (6) The relative prices of substitute energies and the ability to utilize alternative energy sources. For instance, a firm that has a technology consisting of fixed input proportions, or where alternative energy sources cannot be used would probably be more willing to implement a load management program. On the other hand, the firms whose production technologies are of variable proportions would be responsive to relative price changes and would substitute lower priced energy sources.
- k. The study received excellent response from the contacted industrial customers in the initial phase of the survey. The initial response rate was 96 percent. The top level managements of the customers exhibited considerable interest and enthusiasm to participate in the project and provided valid historical data regarding their operations and plant physical characteristics. About 80 percent of the test customers not only implemented most of our recommendations but have decided to implement the remaining portions of the recommendations in the immediate future. It is significant to note that about 25 percent of the customers were convinced about the importance of load management and integrated energy management into their operations by funding this activity on a regular basis.

1. We were able to receive excellent cooperation and assistance from the project direction group, FEA, Detroit Edison Company, the industrial customer representative, and many individuals of the MPSC staff, in conducting and completing this complex task which required the knowledge and technical expertise of several disciplines.
- m. Energy Management Efforts by Detroit Edison Company: As a result of this study, Detroit Edison Company has developed a comprehensive and an effective energy management program addressing the specific needs of the different segments of its customers. Prior to this project, Detroit Edison has implemented several load management methods under the guidelines approved by the Michigan Public Service Commission. For example, in 1968, Detroit Edison installed over 200,000 radio switches to control water heaters. In the same year, Detroit Edison installed 800 radio switches on distribution substation voltage regulators to provide voltage management as an additional form of load management. The installation of these radio switches was part of a complete radio system to effect control of electrical loads totaling 360 megawatts on the Detroit Edison system. The radio-controlled load management system permits the temporary interruption of service to the water heaters of approximately 200,000 customers and thereby permits a deferment in the energy committed to these water heaters for about four hours. Detroit Edison had offered a controlled off-peak water heating rate for several years prior to the installation of the radio-controlled load management system.

Currently, the Detroit Edison Company is using the radio control system to improve system reliability, to improve water heater service, to reduce summer and winter peaks to system peak load and to extend the use of more efficient (base load) generating facilities. In addition to the present project, Detroit Edison is conducting several experiments in an effort to find additional ways to limit demands on the system and, thereby, minimize the need for additional capacity. These include time-of-day pricing, interruptible air conditioning rates for residential and commercial customers, solar homes, solar water heaters, heat pumps, heat and cold storage systems for the industrial customers, and a comprehensive distribution load circuit study. Besides, it has been conducting an extensive media campaign aimed at energy conservation and the promotion of better insulation. Detroit Edison has an extensive reference library dealing with energy management - educational materials for schools and colleges, engineers, architects, builders, developers, consultants, communities, etc. Moreover, Detroit Edison has been conducting energy management seminars for its employees, schools, builders, architects, consultants, and community groups frequently. In particular, as a result of

this load management study, Detroit Edison has developed a special energy audit team. The purpose of this team is to:

- (1) Develop procedures and techniques which identify and monitor the usage patterns and characteristics of energy-consuming equipment,
- (2) Identify the areas where energy management ideas would apply within operations of the customer, and
- (3) Provide a ready reference library to all its customers, vendors, architects, engineers, consultants, and research groups.

Prior to 1977, most small industrial customers only did maintenance where it was required to restore production. However, four 2-day maintenance seminars for industrial customers have been conducted during 1977, and all test customers have had at least one, and some three, employees in attendance.

Miscellaneous telephone calls have been received resulting from this project indicating interest in the following areas:

- (1) Demand control system,
- (2) Power factor equipment,
- (3) Protective lighting,
- (4) Fuel availability, and
- (5) Need for insulation and type of insulation.

2. Areas which were identified during the conduct of the study but were not investigated

While conducting the initial interviews, in-depth technical surveys, analysis of historical data, economic analysis of the load management investments and during the monitoring of the experiment, several areas, which could have had either direct or indirect affect on the final outcome of the results, were not investigated at length in the study due to the fact that most of the areas identified were considered beyond the scope of the project's request for proposal. The areas that were recognized in the study but were left out for further investigation and analysis are:

- a. Theoretical impact of the results on the utility load factor.
- b. Cost effectiveness of load management investments if the firms were to possess in-house capabilities to conduct the energy audits and to install the load management equipment -- or to hire an independent consultant to do the same.

- c. Cost effectiveness of load management investments resulting from alternative rate designs and other monetary and non-monetary incentives such as tax write-offs, subsidies, low interest rates or interest-free loans for energy management equipment.
- d. Economic impact of shift premiums in case some of the operations of the customers were to be shifted to utilize night-time off-peak hours.
- e. Cost effectiveness of load management investments when assessed in terms of total energy savings including natural gas, oils, coal, etc.
- f. Economic impact of capital intensive energy saving technologies such as heat recovery systems.
- g. Direct and indirect impact of conversions and economic implications of substituting other types of energy due to relative price changes.
- h. Impact and implications of co-generation -- generating steam for example, and other by-products of the industrial operations, to be used elsewhere in the plant or to be sold to other users.

Theoretical impact of the results on the utility load factor

The theoretical impact of the results on the utility's load factor was the only item of the Request For Proposal (RFP) which was not carried out. An attempt was made to estimate the impact but we were unable to derive any meaningful conclusions due to the complexity of the problem. The issues involved are summarized below:

It was pointed out earlier that if the experimental results of the study were extended to the industrial sector, there could be about 31 MW reduction on the Detroit Edison system. Does this reduction on the system have any bearing on the annual load factor of the system? Theoretically, any sizable amount of peak demand reduction on the system, resulting from load management, is bound to flatten the load curve of the system. There is bound to be an improvement in the load factor of the system. But, the extent to which this would occur, depends not only on the industrial sector but also on the other segments of the system as well--residential, commercial, and others. To highlight the case in point, we shall now define the basic concepts and discuss the interrelationships between them. One of these is the load factor of the system which is defined as the ratio of the average load to peak load or

$$\text{System Load Factor} = \frac{\text{Net energy for load (kW) hours}}{\text{Peak load (kW) x Hours in a month/year}} \times 100$$

The load factor is generally expressed as a percentage. The maximum load factor that can be achieved is 100 percent. One hundred percent load factor is possible only when the numerator and the denominator on the righthand side of the preceeding expression are equal in magnitude. In such a case the load curve looks like a horizontal line as shown in the figure.

In practice, the annual load factor of a system is usually less than 100 percent. For example, the historical annual load factors of the Detroit Edison system with which we are concerned are presented in the table below:

Table 3
Historical Annual Load Factors of Detroit Edison System

Year	1940	1950	1960	1965	1970	1971	1972	1973	1974	1975	1976
Load Factor	48.7	58.3	64.1	64.3	65.1	63.1	65.3	62.2	61.8	61.8	65.5

SOURCE: Workpapers for Company Exhibit A-5

The table indicates that the annual load factors of the system are less than 100 percent. A high load factor of a system, a customer, or a customer class, generally implies efficient utilization of the facilities. Efficient utilization of system's facilities not only depends upon the management of the system, but, by and large, on the usage patterns of the utility's customers. If the customer classes have poor load factors, this would be reflected on the system. The importance of load factors is usually indicated in cost terms. Generally, the higher the system's load factor the lower the average cost of service.

Electricity, as a finished product, cannot be stored. It has to be generated and supplied instantaneously as, and when, the customers need it at any time of the day--24-hours-a-day and 365-days-a-year. Moreover, the patterns of consumption of the customer demands vary at any point in time during the day, and during the seasons of the year. The times at which the peak demands and coincidence with system peak of the industrial, commercial and domestic customers of the Detroit Edison Company for 1974 are shown in the table on the following page.

Table 4

DETROIT EDISON COMPANY
Analysis of Customer Load Characteristics on System Peak Days - 1974
(Time at which Customer's Peak Occurred)

Hours Ending:	1 am	2 am	3 am	4 am	5 am	6 am	7 am	8 am	9 am	10 am	11 am	12 m	1 pm	2 pm	3 pm	4 pm	5 pm	6 pm	7 pm	8 pm	9 pm	10 pm	11 pm	12 m
Jan									TSP		TCP CP		IP									DP		
Feb											TSP TCP CP												DP	
Mar											CP		TSP	IP TCP									DP	
Apr											TSP TCP CP											DP		
May											TSP TCP CP											DP		
Jun														TSP IP TCP	CP								DP	
Jul													IP	CP	TSP							DP		
Aug													IP	CP	TSP TCP							DP		
Sep											IP			CP		TSP TCP						DP		
Oct											CP				IP			TCP DP TSP						
Nov											IP			CP					TCP DP TSP					
Dec										IP	CP							TCP TSP	DP					

TSP = Total System Peak Demand - Industrial, Domestic, Commercial, Others and losses and company use.

TCP = Total Customer Peak Demand - Industrial, Domestic, Commercial, Others.

IP = Industrial Peak Demand

DP = Domestic Peak Demand

CP = Commercial Peak Demand

SOURCE: Workpapers for Company Exhibit A-5

Some classes of customers demand more power at any point in time compared to others. Further, the peak demands of the different classes of customers may occur simultaneously or at different points in time. If all classes of customer peak occur at the same time, the load factor of the system would be lowest. There exists a natural diversity of the customers and customer classes as well. The natural diversity of different classes of Detroit Edison customers can also be seen from Table 4. The table shows that there exists diversity between domestic, commercial and industrial classes. The peak demands of these classes of customers occurred at different times of the day, the day in which system peak occurred. In particular, industrial customers' demands vary according to their size, mode of operations, technology, shift levels, etc. Due to the varying factors mentioned above, the peak demands of individual industrial customers would also vary. There may exist greater diversity in the case of some industrial customers and little diversity in the case of others. For example, an industrial customer having a three-shift operation might have a high load factor but low diversity factor, whereas a customer having a one-shift operation might have a low load factor and a high diversity factor.

Improvements in load factors for industrial customers must consider not only the load factor improvements due to peak reduction, but also the diversity factor for the system. The diversity factor is the ratio of the sum of non-coincident maximum demands of a system's customers to the sum of their maximum demand on the whole system.

$$\text{Diversity Factor} = \frac{\text{Sum of non-coincident maximum demands of customer classes at time of system peak}}{\text{Sum of maximum demands of customer classes at the time of system peak}}$$

If all customers register their maximum demands at exactly the same time, the diversity factor would be one. But, because of the difference in time of use, the sum of the non-coincident maximum demands is greater than the system's load at any moment of time as such, the diversity factor is greater than one. The attached charts explain the above definition more clearly.

There exists a relationship between the load factor and the diversity factor. A high diversity factor may compensate for low customer load factor. The higher the diversity factor of a customer class, the less the total plant capacity required to serve a particular market or service area. A customer class cannot have, at the same time, a high load factor and a high diversity factor. High load factor usage means a relatively continuous use of power. A high

load factor customer necessarily has a low diversity factor, whereas the lower the load factor, the higher the diversity factor. To summarize, a utility can have a desirable load factor for itself by having customers with high load factors, or by a high diversity factor, but either is achieved at the expense of the other. Improvements in load or diversity factors, that reduce idle capacity, would generally lower the average cost of service, and increase the utilization rate of the system capacity. The average inter-class diversity factors of Detroit Edison customers for the individual months in 1974 are presented in Table 5.

The table shows that the diversity factors are greater than one but very close to unity.

Table 5

Average Inter-class Diversity Factors of Detroit Edison
Customers, 1974 - On the Day of System Peak

Non-coincident Maximum Demands and System Maximum Demand								
(MW)								
Month	Indus- trial	Domestic	Com- mercial	Other	Losses & Comp-use	Total Non- coincident Demand	Total System Demand	Diversity Factor*
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
Jan	2427	1544	1001	251	460	5683	5247	1.08
Feb	2344	1437	1009	271	419	5480	5237	1.05
Mar	2389	1423	1025	256	416	5509	5237	1.05
Apr	2413	1330	958	159	407	5267	5030	1.04
May	2511	1250	929	232	410	4332	5079	1.05
Jun	2617	1437	1159	261	513	5987	5611	1.07
Jul	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Aug	2527	1934	1273	280	614	6628	6249	1.06
Sep	2648	1680	1176	264	527	6295	5702	1.10
Oct	2354	1325	948	277	415	5319	5177	1.03
Nov	2356	1612	1003	264	464	5699	5384	1.06
Dec	2156	1745	1038	278	473	5690	5405	1.05

SOURCE: Derived from workpapers for Company Exhibit A-5.

*Diversity factor is the reciprocal of the coincidence factor.

The theoretical impact of the results of the program if it were to be implemented on a system-wide basis depends upon how the program affects the diversity factors which in turn affect the industrial user load factor and the degree to which industrial users accounted for the peak demand upon the system. Further, the usage patterns of the industrial class also depends on the rate design in effect. The industrial segment (primary) of Detroit Edison consumes approximately 50 percent of the load. A bird's eye view of the historical percentage contribution to the peak, and the load factors of primary (industrial) class of Detroit Edison Company since 1940 are summarized in Table 6.

Table 6

Historical Percentage Contributions to the Peak & Load Factors of Industrial Class

Year	1940	1950	1960	1965	1970	1971	1972	1973	1974	1975	1976
Demand at Peak as % of Billing Demand	* --	85.0	85.2	86.6	84.2	82.2	87.1	89.1	82.3	80.0	82.5
	**69.1	72.7	64.8	82.7	75.9	82.6	84.2	78.4	76.6	76.0	79.4
Load Factor	--	62.5	62.9	71.3	74.1	71.4	75.8	75.9	73.0	71.2	75.5

*Summer

**Winter

System load and capacity factors are a function of the inter-class and intra-class load and diversity factors. Since this study did not deal with the impact of load management on the residential and commercial sectors, it is uncertain as to the extent of improvement on the system's load factor resulting from 31 MW reduction with respect to industrial class. There will be some improvement but we do not know exactly how much.

3. Summary Conclusion

The findings of the study suggest that electric load management is an effective and viable tool in reducing the peak demand (kW) as well as the overall energy (kWh) consumption. Adoption of load management methods would be expected to reduce approximately 31 MW generating capacity of the Detroit Edison system. In the short run, what this implies is that the capacity savings can be made available to new customers or can be supplied to meet the additional demands of the existing customers without that quantity (31 MW) of additional generating capacity requirements except for additional demands as warranted by economic growth. For example, capacity purchases from other systems that are required to maintain adequate on-peak reserves may be reduced to the extent of 31 MW. A typical capacity charge for a six-month period is about \$13 per kW. Lowering the peak load by 31 MW is thus equivalent to \$403,000 per season. An alternative way of evaluating the benefit is consideration of a reduction in the requirement for installed capacity which, in today's dollars, would cost over \$700 per kW. In other words, the installed capacity that can be deferred, at least in the short run, i.e. under existing conditions and with no growth, would be \$22 million. Assuming

status quo, the possible savings may also arise from reduced consumption of high-cost or restricted fuels which would reduce average cost to the existing customers.

The historical energy (electric, gas, oils) consumption profiles of the test customers revealed that natural gas Btu's represented about 70 percent of the total Btu consumption. The plant in-depth technical surveys indicated that there exists a potential for natural gas savings and the possibilities for conversion from other types (gas, oils) of energy to electric exists in all plants. However, the potential for cogeneration (steam) is meager in the case of small industrial customers. Possibilities exist generally in such large industries as paper, chemicals, petroleum, and cement which were not included in the sample. This is due to the fact that steam installations are large and involve huge capital investments. In view of dwindling supplies of natural gas and oils, and escalating costs of these fossil fuels, the industrial sector may, in the future, use greater amounts of base load electric power in its production operations. A comprehensive energy conservation plan for an industrial customer should embrace all facets of energy consumption. This unified approach will highlight the probable options available for the industry, utilities and the regulatory authorities. A piecemeal approach to the problem will often digress from the issue and may not provide a comprehensive set of alternative solutions and often lacks the touch of practical feasibility. Industry needs adequate lead time (two-to-three years) for adopting the new technologies, conservation measures, and for implementing the load management techniques which are cost-effective. Proper signals should be provided to the customers by the utilities and the commissions in regard to the anticipated changes and with respect to supplies of energy and the rate mechanisms. Sufficient educational campaigns and training programs must precede the introduction of innovative energy-efficient systems. The ultimate success of load management depends upon the type and characteristics of the industry and its mode of operation. The effectiveness of load management is contingent upon several factors such as (1) types of energy used, (2) the proportion of different kinds of energy used, (3) efficiency of equipment, (4) geographic location of the plant, (5) type and quality of buildings and work force, (6) percentage cost of energy in the operating budget compared to the costs of labor and material, the annual dollar savings expected by implementing the load management techniques, (7) the relative costs of electric, natural gas, and other kinds of energy, (8) availability of capital at low interest rates, (9) tax write-offs and subsidies, (10) readily available and suitable load management technology at reasonable cost, (11) day-to-day monitoring and periodic energy audits by the companies, and finally, (12) the firm commitment of top level management towards effective energy management.

Small and medium manufacturing industries do not have, at the present time, effective energy management programs although these

industrial customers were aware of the energy shortages and have been attempting to reduce their energy consumption to the extent possible. As a result of this study, a significant number of test customers have implemented the proposal recommendations and many of the sample customers developed their own ongoing energy efficient programs and have earmarked funds in their budgets for energy management.

One of the major cost items in the implementation of any load management program is that of cost of labor to install load management equipment and to implement other end-use conservation measures. The analysis of the load management investments of the study showed that the cost of labor was approximately 50 percent of the total investment. If the firm possesses in-house capabilities to install and to implement the day-to-day monitoring of the equipment, the load management investments would probably produce attractive payback periods. The load management investments of the study include about 50 percent towards the cost of installing the equipment, as such, one-third of the test customer payback periods exceeded the required 24-month payback period.

Another significant variable that affects the savings is the demand and energy rates prevailing during 1976. The demand and energy rates (demand charge \$6/kW and energy charge 1.5¢ on-peak and 1.3¢ off-peak) were not adequate to produce attractive savings which in turn would have met the desired norm of the industry (24-month payback).

Another variable which, to some extent, inhibits the savings is the existing time-of-day interval - 9 a.m. to 9 p.m. There is no flexibility built into this interval. Rate design strategy could consider multiple peak periods, e.g. 9 a.m. to 11 a.m., 1 p.m. to 3 p.m., shorter time interval, etc., which provide an option to the customer to reschedule some of his energy intensive operations to off-peak period. The charges during the peak period must be sufficient enough to induce the customer to save energy and monies. To adopt such rate designs, the utility and the commissions should thoroughly investigate the customer class usage, and peak coincident patterns. Direct and indirect load management strategies are not mutually exclusive. They can be combined in order to produce a significant impact.

D. Recommendations

- A proposal for developing a total load management program encompassing all energy usages. This program would assess the trade-off of benefits and costs associated with each energy use. This would include capital and labor costs, financial evaluations of each and the total package, as well as various direct and indirect subsidy programs, and consideration of developing of an overall rate structure encompassing all of the energy sources.

- A program to actively involve the utilities with the cooperation of commissions in the initial phase of the design of industrial parks and production processes of individual firms. This program would identify the equipment kilowatt demand and time-of-usage that would complement the objectives of load management, as well as output and cost objectives of the firms. This could involve the engineering staffs of utilities, commission, and other state energy agencies in the design of industrial parks and new plant facilities for the particular industry. Industry representatives, as well particular firm representatives, would also be included in determining the load and energy demand upon the single or multi-system utility. This would eventually encompass the incorporation into building codes of total energy load management objectives.
- A study to consider a program of increasing load diversity factors through various growth strategies. Developmental and incentive rate structures would be evaluated to implement overall load, diversity and growth objectives.
- In the area of education, both commissions and utilities should attempt to provide industry with information on anticipated rate structures, new technologies, etc., so that these can be factored into their forward investment planning. There should be increased emphasis upon energy audits by the firm's and the utility's energy personnel. The utility engineers should work closely with industry management, not only with respect to energy audits, but also in the determination of equipment kilowatt ratings in the production process. In addition to educational programs such as ongoing energy update seminars directed at existing customers, potential new customers should also be provided with energy audits and planning assistance in the location of their facilities.
- Before any load management method is implemented on a system-wide basis, it is important that the method must be technologically justified and the effects on the customer and generation and distribution facilities be considered. Thorough consideration of various socio-economic effects should be made by regulatory agencies as well as the utilities in order to evaluate:
 - a. Effect on the quality of service - response and acceptance by customers.
 - b. Price incentives.
 - c. Costs of special metering and control equipment and other capital intensive technologies must be measured against the potential reduction in peak load and resultant reduction in investment in new generating facility.
 - d. Effect of possible changes in load patterns on generation mix.
 - e. Effect of possible secondary peaks.

- Industrial customer load patterns are more a function of economic activity than of rate design. The effectiveness of rate increases and rate design to modify load patterns depends entirely on customer response, both immediate and long-range.

A P P E N D I X A

I '

ECONOMIC FEASIBILITY

OF

LOAD MANAGEMENT INVESTMENT

AN EXAMPLE

AN EXAMPLE TO ILLUSTRATE THE CAPITAL EVALUATION
OF LOAD MANAGEMENT INVESTMENT OF A COMPANY

The logical order for making an investment decision is to follow the analysis presented in the Tables 1 through 6:

- First: Table 1A Presents the financial summary.
- Second: Table 1B Presents the annual equivalent revenues less cost
 using the annual savings derived in Table 5.
- Third: Table 2 Presents the overall capital investment evaluation
 using the pre-tax profits of Table 6.
- Fourth: Table 3 which shows annual energy cost prior to survey.
- Fifth: Table 4 which provides an estimated annual energy cost
 with load management (after survey).
- Sixth: Table 5 Shows the estimated energy savings.
- Seventh: Table 6 Shows the pre-tax profit projections using
 depreciation of capital investment presented
 in Table 1.

To: The Management of the Company

Re: Load Management Investment, \$5,425

The load management equipment and associated expenses are indicated on Schedule 1A.

The projected reductions in energy costs, electric and gas, are \$17,816, which represents an 8.5 percent annual savings at 1976 rates.

The projected annual addition to pre-tax profits is \$11,688.50 in the first year and \$12,388.50 in the second year.

This performance will produce an average annual rate of return on investment of 346 percent over the two-year period, and a payback of investment in 6.9 months. Annual equivalent revenues associated with the investment exceed annual equivalent cost by \$16,704.57.

Will you please advise us as soon as your company has considered this proposal.

Schedule 1A

FINANCIAL SUMMARY -- 1976 RATES PLUS GAS

WITHOUT F.E.A. INVESTMENT

Line	Investment	Amount		
		Capital	Expense	Total
1	Interlocks 2 @ \$100	\$ 200.00	\$ 50.00	\$ 250.00
2	Timers 5 @ \$100	500.00	50.00	550.00
3	Timers for Battery Chargers 3 @ \$25	75.00	50.00	125.00
4	Fans 10 @ \$200	2,000.00	500.00	2,500.00
5	Electric Heaters	2,000.00	-	2,000.00
6	Total This Request	\$4,775.00	\$650.00	\$5,425.00
7				
8				
9				
10	Total Project			\$5,425.00
		Average Monthly		
		Energy	Pre-Tax	
		Cost	Profits	
11	<u>Current Year-to-Date</u>			
12	Sch. 3, Line 7	\$17,416.67		
13	<u>Project Projections</u>			
14	1st Year - Sch. 4 and 6	15,932.00	\$1,390.71	
15	2nd Year - Sch. 4 and 6	15,932.00	1,444.88	
		This		
		Request	Standard	
16	Return on Investment - Avg. Annual R.O.I. - Sch. 2	<u>184%</u>	<u>10%</u>	
17	Cash Flow Rate (Return of Capital) through 2 years - Sch. 2	<u>346%</u>	<u>100%</u>	
18	Cash Flow Rates -- Monthly Payback	6.9 months	24 months	

Schedule 1B

ANNUAL EQUIVALENT REVENUES LESS COSTS

WITH INVESTMENT TAX CREDIT

1976 RATES -- WITHOUT F.E.A. INVESTMENT

Annual Energy Savings	\$17,816.00
Less Before Tax Cash Flow Required (Annual Equivalent of Cost at 10%/10)	<u>11,111.43</u>
Annual Equivalent of Revenues Less Cost	\$16,704.57

Schedule 2

CAPITAL INVESTMENT EVALUATIONWITHOUT F.E.A. INVESTMENT1976 RATES PLUS GAS

Col.	1	2	3	4	5	6	7	8	9	10
inc	Year	Total Projected Annual Pre-Tax Profits			Tax Provision @ 50% Less I.T.C.	Total Annual Incremental			Present Value Factor @ 8%	Present Val. Of Incremental Cash Flow
		With Investment	Without Investment	Incremental		After-Tax Profits	Equipment Rent	Total Cash Flow		
1	1	\$16,688.50	-	\$16,688.50	\$7,801.75	\$8,886.75	\$477.50	\$9,364.25	.9259	\$ 8,670.36
2	2	17,338.50	-	17,338.50	8,669.25	8,669.25	477.50	9,146.75	.8573	7,841.51
3	2 Year Total, Cols. 6, 8, and 10 only					\$17,556		\$18,511		\$16,511.87
4	Average Annual Profit, Col. 6 only					\$ 8,778				

-193-

5 Total Project Investment Capitalized (Schedule 1)

6 Return on Investment -- Avg. Annual R.O.I.
(Line 4 + Line 5)

7 Present Value of 2-Year Cash Flow (Column 10, Line 3)

8 Cash Flow (Return of Capital) through 2 years
(Line 7 + Line 5)

9 Cash Flow Rate -- Monthly Payback

<u>This Request</u>	<u>Standard</u>
\$ <u>4.775.00</u>	
<u>184%</u>	<u>10%</u>
<u>\$16,511.87</u>	
<u>346%</u>	<u>100%</u>
6.9 months	24 months

Schedule 3

1976 ENERGY COST1976 RATES PLUS GAS

Line	Total	Amount	Offpeak	Rate	Subtotal	Onpeak			Cost
						Amount	Rate	Subtotal	
1	KW	860	430	\$6.00	\$2,580.00	430	\$6.00	\$2,580.00	\$ 5,160.00
2	KWHR	310,000	155,000	.013	2,015.00	155,000	.015	2,325.00	4,340.00
3	Monthly Electric Cost								9,500.00
4	Annual Electric Cost								114,000.00
5	Monthly Gas Cost								7,916.67
6	Annual Gas Cost								95,000.00
7	Monthly Energy Cost								17,416.67
8	Annual Energy Cost								209,000.00

Schedule 4

ENERGY COST WITH LOAD MANAGEMENT

1976 RATES PLUS GAS

Line	Total	Amount	Offpeak	Rate	Subtotal	Onpeak			Cost
						Amount	Rate	Subtotal	
1	KW	850	425	\$6.00	\$2,550.00	425	\$6.00	\$2,550.00	\$ 5,100.00
2	KWHR	238,000	119,000	.013	1,547.00	119,000	.015	1,785.00	3,332.00
3	Monthly Electric Cost								8,432.00
4	Annual Electric Cost								101,184.00
5	Monthly Gas Cost								7,500.00
6	Annual Gas Cost								90,000.00
7	Monthly Energy Cost								15,932.00
8	Annual Energy Cost								191,184.00

Schedule 5

ENERGY SAVINGS

1976 RATES PLUS GAS

Line		Monthly	Yearly
1	Current Energy Use -- New Rates Schedule 3, line 3, line 4	\$17,416.67	\$209,000.00
2	Energy Use After Investment Schedule 4, line 7, line 8	15,932.00	191,184.00
3	Energy Savings (line 1 minus line 2)	\$ 1,484.67	\$ 17,816.00

Schedule 6

PROJECT PRE-TAX PROFIT PROJECTIONS1976 RATES PLUS GASWITHOUT F.E.A. INVESTMENT

	<u>Year 1</u>	<u>Year 2</u>
Energy Savings		
Schedule 5, line 3	\$17,816.00	\$17,816.00
Less Expenses		
Depreciation	\$477.50	\$477.50
Total Expenses	477.50	477.50
Profit Monthly	1,444.88	1,444.88
Profit Annualized	17,338.50	17,338.50
Less Project Expense	650.00	0
Adjusted Monthly Profit	1,390.71	1,444.88
Adjusted Annualized	16,688.50	17,338.50

A P P E N D I X A

I I

SURVEY FORMS I, II & III

LOAD MANAGEMENT SURVEY

PRIMARY INDUSTRIAL CUSTOMER INTERVIEW FORM

Date of Interview _____

Customer Name _____ Division _____

Address _____

I. Type of Business:

SIC Code _____

II. Process Type:

Product Type:

a) Initial Process

a)

b) Intermediate

b)

c) Final

c)

III. Business Operating Characteristics:

a) Normal number of work shifts in a day: _____

b) Normal operating days per week: _____

c) Total man hours per work week: _____

d) Total number of employees: _____

e) Total number of production workers: _____

f) Shift	Hours/Day	No. Production Workers	Total Employees
1st			
2nd			
3rd			

g) Estimated seasonal, part time or overtime employment:

Employees	Seasonal	Part Time	Overtime	Total Man Hours Per Week
Production Workers				
Others				

IV. Vacation Policy:

Total Number of days/yr.

Period

Production Workers:

Others:

a) Number of annual
days

b) Vacation dates

V. Gross Area of Plant or Building (sq. ft.)

Office _____

Plant _____

Warehouse _____

Other (Recreation areas, conference rooms, cafeteria, etc.) _____

Total square feet: _____

VI. Major Electrical Uses:

Estimated kW (connected)

kWh

kW

Lighting _____

Air Conditioning _____

Motor Load _____

Space Heating _____

Processing _____

Pollution Equipment _____

Others (Specify) _____

Total _____

Expected additions (Jan-June, 1976): _____ % of the existing electrical use.

VII. Annual Operating Revenues and Expenses: 1973 1974 1975 (estimated)

Total sales revenue _____ \$ \$ \$

Total expenses _____

Total wages and salaries _____

Number of units produced:

Product A _____

Product B _____

Product C _____

VIII. Estimated plant capacity utilization (as percent of total plant capacity)

%

1973 _____

1974 _____

1975 _____

1976 _____

IX. Product Inventory Levels:

Average number of days inventory: _____

X. Plant Down Time:

Estimated man/hours week: _____

XI. Do you anticipate wage contract in 1976? Yes _____ No _____

XII. Total annual energy cost: 1973 \$ _____ 1974 \$ _____ 1975 \$ _____ (est.)

	<u>% of annual operating cost</u>	<u>Volume</u>
a) Electric energy		kWH
b) Natural Gas		MCF
c) Oil		Gallons
d) Others		

XIII. Does availability of alternative fuels affect your electric load:

Yes _____ No _____

If yes, to what extent (be specific): _____

XIV. Response to Economic Conditions:

How would you respond to the changes in economic conditions:

1. Labor force adjustment _____

2. Energy conservation _____

3. Inventory level adjustments _____

- h. Substitution of alternative forms of energy _____

5. Others (specify) _____

XV. Some electric utilities have an interruptible rate for large primary industrial (optional) customers. Service is subject to interruption by the power company when necessary.

Could you adjust your operation to an interruptible rate in exchange for lower cost power? Yes _____ No _____

XVI. Load Management:

Many proposals regarding the feasibility of load management have been advanced.

The following questions deal with some of the issues involved.

a) Do you have electric demand control equipment? (If the answer is yes, indicate the nature and type). Yes _____ No _____

b) How closely do you utilize the company valley hour provision? _____

c) How much have you been able to reduce peak demand with your equipment (or shift demand)? _____

d) If you do not have demand control equipment now, are you considering it?

XVII. Major Area of Investigation (briefly summarize) _____

Filled out by: _____

Phone _____

PLANT - AREA SKETCH

FEA 2 - A

	A	B	C	D	E
1					
2					
3					
4					
5					
6					
7					
8					

CUSTOMER ENERGY ACTIVITY

FIRM _____
ADDRESS _____
CITY _____

LIGHTING

HVAC

OTHER

SUR. EQ. NO.	LOCATION OF OPERATION	Opport. for Reduct.		Added Load Req.	Plan Mod		PROPOSED ACTION	Action			comments
		Yes	No		S	L		I M P L E	S T U D Y	A B O R T	
	Offices										
	Gen. Private										
	Con. Room										
	Drafting Rm.										
	Plant										
	Assembly										
	Manuf.										
	Heat Treat										
	Inspection										
	Machine Shop										
	Tool Room										
	Welding										
	Warehouse										
	Heating Plt.										
	Refrigeration										

Survey by: _____ Date: _____ Contact at Firm: _____

Follow Up
By Acct. Eng. _____ Date: -207- _____ Title: _____

CUSTOMER ENERGY ACTIVITY

FIRM _____
ADDRESS _____
CITY _____

LIGHTING

- HVAC

OTHER

[illegible]

Survey by: _____ Date _____ Contact at Firm: _____

Follow Up
By Acct. Eng. _____ Date: -208- Title: _____

FIRM: _____
ADDRESS: _____
CITY: _____

Area Survey:

[illegible]

Survey by Acct. Eng. _____ Date _____

Follow up by	Date
--------------	------

A P P E N D I X A

III

HISTORICAL DATA ANALYSIS

AND

DEMAND PROFILES

AN EXAMPLE

SIC 32 Test Company
PRIMARY MAILING DATES
1975
TUESDAY - FRIDAY

	12-1 AM	1-2 PM	2-3 PM	3-4 PM	4-5 PM	5-6 PM	6-7 PM	7-8 PM	8-9 PM	9-10 PM	10-11 PM	11-12 AM	MEAN	STD DEV	CV
JANUARY	502.	525.	528.	543.	614.	717.	1065.	1551.	1709.	1719.	1730.	1690.			
FEBRUARY	1653.	1647.	1665.	1224.	1131.	1071.	1171.	1044.	1044.	1023.	930.	819.	1141.	440.	38.5
MARCH	1954.	1915.	1876.	1434.	1356.	1270.	1155.	1251.	1105.	1287.	1116.	1095.	1311.	468.	35.7
APRIL	1641.	1641.	1655.	1374.	1150.	1102.	1201.	1143.	1137.	1125.	1077.	1023.	1251.	324.	25.9
MAY	1873.	1779.	1668.	1350.	1200.	1097.	1180.	1071.	1071.	1014.	996.	939.	1268.	380.	30.3
JUNE	2031.	2155.	1926.	1566.	1497.	1392.	1395.	1150.	1356.	1320.	1317.	1231.	1490.	396.	26.6
JULY	1062.	972.	972.	972.	946.	1062.	1256.	1915.	2055.	1965.	2070.	1941.			
AUGUST	1742.	2116.	1927.	1617.	1566.	1431.	1123.	1365.	1347.	1341.	1338.	1261.	1498.	399.	26.7
SEPTEMBER	1944.	2117.	1926.	1566.	1512.	1422.	1111.	1177.	1309.	1362.	1344.	1269.	1499.	304.	25.6
OCTOBER	1950.	1006.	1008.	993.	1044.	1170.	1303.	1903.	2100.	2049.	2148.	2043.			
NOVEMBER	2273.	2291.	2011.	1641.	1578.	1446.	1452.	1455.	1470.	1431.	1419.	1330.	1550.	400.	26.2
DECEMBER	906.	948.	949.	945.	947.	1053.	1117.	1051.	1978.	1917.	1954.	1930.			
	1953.	1462.	1465.	1515.	1455.	1356.	1155.	1198.	1350.	1315.	1314.	1269.	1457.	392.	26.2
	906.	951.	950.	930.	902.	1017.	1243.	1812.	1962.	1070.	1917.	1859.			
	1972.	1977.	1797.	1400.	1449.	1359.	1174.	1347.	1359.	1314.	1293.	1224.	1432.	370.	25.0
	912.	867.	876.	855.	879.	936.	1191.	1761.	1911.	1039.	1938.	1899.			
	1080.	1059.	1248.	1392.	1312.	1251.	1254.	1203.	1176.	1158.	1137.	1050.	1343.	394.	29.3
	1101.	1132.	1110.	952.	888.	990.	1245.	1034.	1923.	1854.	1917.	1687.			
	1928.	1929.	1876.	1400.	1359.	1302.	1293.	1251.	1219.	1194.	1176.	1161.	1405.	375.	26.7

CHI-SQUARE = 7.06

AVERAGE	933.	817.	866.	862.	440.	976.	1266.	1779.	1936.	1881.	1945.	1863.			
	1981.	1914.	1923.	1471.	1396.	1299.	1302.	1264.	1271.	1242.	1219.	1140.	1358.	392.	28.2
STD. DEV.	153.	157.	111.	191.	135.	135.	93.	139.	122.	110.	133.	122.			
	132.	152.	124.	127.	140.	128.	128.	128.	136.	136.	153.	157.	136.	16.	11.6
C.V.	16.	18.	18.	18.	15.	10.	7.	8.	6.	6.	7.	7.			
	7.	8.	7.	8.	10.	10.	11.	10.	11.	11.	13.	14.	11.	4.	36.9

[illegible]

SIC 32 Test Company
PRIMARY DRILLING DEMAND
1975

MONDAY - FRIDAY

12-1 AM 1-2 AM 2-3 AM 3-4 AM 4-5 AM 5-6 AM 6-7 AM 7-8 AM 8-9 AM 9-10 AM 10-11 AM 11-12 AM
 12-1 PM 1-2 PM 2-3 PM 3-4 PM 4-5 PM 5-6 PM 6-7 PM 7-8 PM 8-9 PM 9-10 PM 10-11 PM 11-12 PM MEAN STD DEV CV

JANUARY	554	556	546	526	602	715	1050	1577	1700	1711	1702	1726			
FEBRUARY	1650	1709	1602	1224	1128	1070	1075	1046	1050	1010	950	813	1143	449	39.3
MARCH	655	672	584	571	646	739	1128	1745	1917	1019	1951	1783			
APRIL	1912	1079	1760	1420	1350	1202	1306	1248	1290	1291	1183	1104	1297	472	36.4
MAY	778	761	754	786	782	840	1145	1550	1702	1670	1706	1649			
JUNE	1601	1663	1622	1305	1346	1202	1214	1159	1166	1152	1114	1046	1243	349	28.0
JULY	790	792	797	700	833	890	1101	1603	1819	1800	1074	1762			
AUGUST	1072	1798	1670	1339	1103	1090	1373	1060	1566	1013	996	943	1248	401	32.1
SEPTEMBER	974	800	800	886	917	1013	1250	1067	1900	2004	2015	1970			
OCTOBER	2571	2704	1915	1562	1406	1305	1365	1339	1142	1313	1376	1230	1455	420	29.4
NOVEMBER	929	871	870	841	907	991	1272	1082	2015	1946	2050	1951			
DECEMBER	1951	2172	1911	1610	1555	1430	1426	1360	1346	1351	1351	1274	1470	426	29.0
JANUARY	714	917	911	926	936	979	1291	1062	2020	1997	2014	1930			
FEBRUARY	1932	1915	1908	1560	1510	1414	1409	1360	1385	1354	1330	1262	1460	406	27.7
MARCH	431	410	436	922	974	1106	1361	1942	2969	2033	2126	2021			
APRIL	2083	2070	2082	1649	1548	1457	1459	1452	1476	1420	1421	1337	1534	429	28.0
MAY	495	905	936	912	948	1022	1290	1097	1947	1922	2014	1942			
JUNE	1950	1474	1449	1574	1466	1368	1366	1313	1361	1337	1313	1267	1449	400	27.6
JULY	976	462	878	854	866	950	1219	1770	1932	1655	1913	1804			
AUGUST	1874	1949	1872	1481	1440	1351	1371	1344	1356	1318	1296	1231	1404	392	27.9
SEPTEMBER	904	740	797	780	806	871	1169	1766	1913	1846	1934	1817			
OCTOBER	1971	1870	1793	1392	1300	1260	1270	1212	1200	1176	1152	1073	1329	421	31.7
NOVEMBER	496	400	450	814	852	958	1291	1010	1425	1058	1939	1072			
DECEMBER	1913	1227	1078	1488	1354	1298	1202	1236	1236	1193	1178	1154	1338	393	28.3

CHI-SQUARE = 2.6

PAGE	933	810	820	800	839	923	1223	1762	1922	1872	1942	1859			
STD. DEV.	1841	1916	1420	1470	1395	1301	1373	1262	1274	1246	1216	1147	1369	412	10.1
C.V.	126	135	141	132	116	116	88	129	119	113	123	112			
	130	140	122	122	140	127	128	125	111	133	146	152	127	13	10.5
	15	17	17	17	14	13	7	7	6	6	6	6			
	7	7	7	8	10	10	10	10	10	11	12	13	10	4	35.8

JAN-MAR	602	626	614	610	677	760	1110	1624	1791	1736	1803	1719			
APR-JUN	1710	1700	1600	1346	1201	1185	1199	1151	1173	1158	1082	994	1228	422	34.4
JUL-SEP	864	871	862	849	886	965	1277	1740	1945	1917	1908	1840			
OCT-DEC	1025	1009	1033	1504	1411	1302	1294	1253	1251	1226	1218	1151	1391	416	29.9
JAN-MAR	916	910	874	920	953	1036	1317	1885	2028	1984	2051	1964			
APR-JUN	1001	2012	1946	1578	1520	1413	1411	1378	1407	1373	1355	1289	1402	412	27.8
JUL-SEP	802	861	874	816	802	926	1226	1785	1923	1853	1929	1858			
OCT-DEC	1094	1016	1011	1454	1367	1303	1300	1264	1265	1229	1209	1153	1373	4	29.2

1475
SATURDAY

CHI-SQUARE = 121.02

SIC 32 Test Company
PRIMARY BILLING DEMAND
1975
SUNDAY

	12-1 PM	1-2 PM	2-3 PM	3-4 PM	4-5 PM	5-6 PM	6-7 PM	7-8 PM	8-9 PM	9-10 PM	10-11 PM	11-12 PM	MEAN	STD	DET	CV
JANUARY	362.	372.	372.	360.	372.	370.	372.	360.	336.	336.	336.	324.				
FEBRUARY	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	354.	23.		6.5
MARCH	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	354.	19.		5.0
APRIL	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	354.	33.		7.7
MAY	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	354.	48.		13.3
JUNE	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	354.	56.		13.0
JULY	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	354.	22.		5.1
AUGUST	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	354.	32.		6.9
SEPTEMBER	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	354.	23.		6.0
OCTOBER	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	354.	16.		4.5
NOVEMBER	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	354.	17.		4.7
DECEMBER	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	372.	354.	11.		1.9

CHI-SQUARE = 115.88

STAGE	461.	475.	429.	470.	426.	419.	407.	401.	397.	389.	389.	391.				
STC. DEV.	62.	67.	68.	64.	65.	65.	63.	60.	57.	61.	59.	63.	64.	7.		11.5
CV	16.	17.	18.	17.	17.	17.	16.	15.	14.	15.	14.	15.	16.	2.		10.2

JAN-MAR	424.	475.	472.	470.	408.	396.	396.	376.	360.	360.	360.	372.				
APR-JUN	472.	475.	470.	476.	424.	412.	410.	380.	364.	360.	372.	364.	391.	32.		8.3
JUL-SEP	472.	475.	470.	476.	424.	412.	410.	380.	364.	360.	372.	364.	391.	32.		8.3
OCT-DEC	472.	475.	470.	476.	424.	412.	410.	380.	364.	360.	372.	364.	391.	32.		8.3

SIC 32 - GLASS PRODUCTS - TEST COMPANY

AVG WEEK TUESDAY-FRIDAY - 1975

SIC 32 - GLASS PRODUCTS - TEST COMPANY

AVG WEEK TUESDAY-FRIDAY BY QUARTER 1975

SIC 32 - GLASS PRODUCTS - TEST COMPANY

AVG WEEK TUESDAY-FRIDAY WINTER 1975

SIC 32 - GLASS PRODUCTS - TEST COMPANY

AVG WEEK TUESDAY-FRIDAY SUMMER 1975

A P P E N D I X B

EVALUATION OF DEMAND MONITORING SYSTEM

Test Customer SIC 33-8

Purpose

To determine the effectiveness and operating characteristics of the new manual demand control system.

Description of the Equipment Operations

The operation of this monitoring system basically consists of the following steps:

1. A special relay senses the demand pulses transmitted to the utility recording meters and forwards this data to digital display at the control point.
2. The operator at this point continually verifies that the demand is within the present limits and records the reading each hour. If the demand is lower than the expected level, nothing is done; however, if the demand approaches the preset maximum, the plant engineer is notified and appropriate action is taken to reduce the load.
3. To determine which loads are sheddable, four recording tables and four three-dial meters are available for instantaneous review with all miscellaneous or non-essential loads subject to interruption. The decision is made as to which load is to be reduced until the emergency is over. At that time all load is returned to normal. The attached photographs describe the total demand control system.

Table 1 shows the distribution of the total load to various uses. Charts 1 through 8 show the plots of the loads at the various points and Tables 2 and 3 present the actual data recorded on the customer meter and on the utility system's meter.

Weaknesses

The only major weakness in this type of system is the response time of the operator and the plant engineer as the attached Chart 8 indicates that a minimum difference appears between the demand peaks recorded on the test and utility meter which is a result of the manual operation of the monitoring device. The utility metering is equipped with a synchronous time pulse which automatically resets the timer thus insuring accurate hourly readings. The test metering on the other hand, must be reset by a manual process. For example, if the operator of the equipment sets the meter one minute early or late, the recorded demand on the monitoring device would vary as much as eight kW which would be reflected not only in the specific demand in question, but the period immediately following as well. Therefore, it appears that some form of a synchronous time pulse is necessary to guarantee 100% accurate recordings; however, the current manual operation is functioning well within its desired range of accuracy.

Table 1

NORMAL PRODUCTION RUN

Distribution of the Total Load to
Total Load 400 kW Test Points

420				
390				
360				
330				
300	40%	TEST POINT* (Production)	#1	160 kW
270				
240				
	3.75%	TEST POINT*(Production)	#3	15 kW
210	6.25%	WAREHOUSE		25 kW
180	5%	OIL COMPOUNDER		20 kW
150				
120				
90	30%	TEST POINT* (Production)	#2	120 kW
60				
	10%	OFFICE		40 kW
30				
	5%	MISCELLANEOUS		20 kW

* Test points are production areas.

Chart 1

* Maximum Connected Load

Chart 2

-223-

* Maximum Connected Load for Test Points.

Chart 3

* Maximum Connected Load

Chart 4

-225-

* Maximum Connected Load

Chart 5

* Maximum Connected Load

Chart 6

Chart 8
TYPICAL DAY PLANT LOAD
UTILITY VS. TEST
METERING

Chart 7
TYPICAL DAY PLANT LOAD
RECORDED BY UTILITY METERING
(Three-shift Operation)
Primary Metals

Table 2
TEST METERING*
(August)

Recordings over 400:	2
over 390:	7
over 380:	15
Total Recordings:	288

<u>Hour</u>	<u>Wed.</u> <u>10</u>	<u>Thu.</u> <u>11</u>	<u>Fri.</u> <u>12</u>	<u>Sat.</u> <u>13</u>	<u>Sun.</u> <u>14</u>	<u>Mon.</u> <u>15</u>	<u>Tue.</u> <u>16</u>	<u>Wed.</u> <u>17</u>	<u>Thu.</u> <u>18</u>	<u>Fri.</u> <u>19</u>	<u>Sat.</u> <u>20</u>	<u>Sun.</u> <u>21</u>
1 am	330	334	376	351	341	354	344	355	345	333	308	319
2	303	362	266	352	357	357	348	354	329	348	332	317
3	312	<u>389</u>	307	338	360	354	352	359	323	349	343	322
4	311	353	366	336	367	352	363	375	327	327	343	311
5	318	328	351	359	351	338	336	345	333	354	322	315
6	336	345	343	332	330	327	346	368	351	377	312	313
7	336	354	344	358	365	344	328	363	321	356	318	317
8	317	370	350	328	340	345	357	362	359	328	317	315
9	344	372	286	322	352	349	376	369	<u>381</u>	341	336	322
10	<u>387</u>	<u>400</u>	352	342	345	<u>384</u>	<u>394</u>	<u>386</u>	<u>384</u>	315	332	307
11	362	<u>393</u>	355	374	345	365	<u>396</u>	<u>381</u>	365	332	334	306
Noon	330	353	346	336	352	361	370	376	375	326	330	297
1 pm	347	373	326	362	346	<u>381</u>	360	<u>386</u>	378	325	330	317
2	<u>384</u>	373	342	368	339	373	357	<u>380</u>	377	353	350	323
3	370	375	351	362	349	<u>411</u>	317	364	<u>396</u>	354	317	309
4	350	236	369	371	358	<u>384</u>	370	379	360	354	326	338
5	344	335	<u>386</u>	361	<u>384</u>	<u>394</u>	362	367	374	358	327	339
6	335	362	324	333	345	373	342	357	345	338	323	342
7	374	360	357	333	355	368	366	<u>380</u>	346	348	325	329
8	341	357	345	351	369	353	362	364	365	361	321	340
9	335	367	353	358	343	370	351	352	368	333	319	319
10	371	368	359	351	333	366	352	364	368	347	343	323
11	<u>396</u>	370	358	342	358	378	349	379	359	361	322	314
Mid.	345	365	363	350	<u>395</u>	344	361	350	330	314	307	286

* Hourly Billing Demands (kW)

Table 3
DETROIT Edison COMPANY
INDUSTRIAL INFORMATION SYSTEM
DEMAND CALCULATION REPORT

DATE 1995
PROCESSED DATE 06/24/77
SYSTEM UNIT 16

SCHEDULE NO 16
ROUTE NO 16 1W
IN CONSTANT 0.4400
ASSIGNED ACCT REP 02

RECORDED NO. 4442
RECORDED SET 01
TRK 4

DATE DAY 01/05/0207 03/05/0405 05/05/0605 07/05/0805 09/05/1005 11/05/1205 13/05/1405 15/05/1605 17/05/1805 19/05/2005 21/05/2205 23/05/2405

07/25 MON.	Y	X	X	X	26.8	367.3	375.4	381.3	379.1	363.7	358.6	359.5
	X	Y	X	X	379.6	368.7	382.2	354.4	353.6	370.4	370.4	345.2
07/26 TUE	346.9	346.0	340.2	324.2	363.7	364.5	329.7	378.0	392.2	364.5	350.2	359.5
	344.4	339.3	331.8	354.4	373.8	362.2	400.6	365.4	349.4	353.6	372.1	349.4
07/27 WED	364.5	352.6	345.2	340.2	372.9	371.6	386.4	403.2	338.9	373.1	376.3	422.3
	262.0	346.0	349.4	342.7	373.5	257.9	282.9	388.0	364.5	377.1	367.9	362.0
07/28 THUR	367.9	348.6	332.6	352.8	362.2	357.0	374.6	381.3	372.9	343.5	351.1	355.3
	362.0	337.6	364.5	357.0	363.7	359.5	371.2	357.0	341.8	357.8	346.0	368.7
07/29 FRI	341.0	361.2	352.8	355.3	358.6	373.8	351.3	373.8	384.7	383.0	346.0	341.8
	357.0	357.0	362.2	363.7	336.4	357.0	367.9	386.4	383.0	354.4	349.4	320.8
07/30 SAT	353.6	352.8	346.9	342.7	292.3	323.4	398.1	367.9	360.1	353.6	343.6	362.8
	346.6	343.5	346.0	362.8	289.8	357.8	354.4	372.9	355.3	332.6	362.0	338.5
07/31 SUN	334.3	342.7	347.7	356.1	350.2	61.2	332.6	342.7	345.2	368.0	342.4	349.0
	354.4	306.6	358.6	339.3	372.9	348.6	356.1	357.8	235.2	369.8	368.8	345.2
08/01 MON	336.8	319.2	333.4	317.5	354.4	358.6	374.6	368.7	372.9	285.6	353.6	354.4
	324.7	320.8	327.6	355.3	372.9	346.0	356.1	357.8	345.2	343.6	357.0	332.6
08/02 TUE	346.9	342.6	325.9	325.0	364.5	72.2	353.6	402.3	369.6	356.1	347.7	346.9
	329.2	346.9	341.8	346.0	341.4	372.1	383.8	347.7	352.8	342.7	366.2	370.4
08/03 WED	374.6	378.8	324.2	351.1	366.2	185.5	367.2	379.6	373.8	391.4	354.4	362.8
	383.0	350.2	338.5	341.8	378.0	383.8	370.4	391.4	355.3	365.4	355.3	372.9
08/04 THUR	347.7	304.0	341.8	299.8	349.4	372.9	346.0	364.5	383.0	372.1	351.1	346.9
	297.2	318.3	321.7	298.2	383.8	359.5	374.6	357.0	360.3	342.7	354.4	347.7
08/05 FRI	378.8	361.2	349.4	288.1	278.3	377.2	369.8	382.2	367.1	352.8	347.0	320.8
	368.7	357.0	365.4	320.0	383.8	383.9	391.5	376.4	349.5	344.4	339.4	312.5
08/06 SAT	308.3	306.6	306.6	308.8	97.4	99.9	397.5	374.1	366.6	377.4	377.4	329.1
	309.2	308.3	305.0	97.4	99.1	304.1	306.6	302.4	377.4	377.4	302.4	300.3
08/07 SUN	308.8	301.6	99.9	97.4	95.7	341.1	399.0	204.9	393.2	389.0	386.4	399.4
	99.1	99.1	301.6	95.7	94.9	386.1	399.0	195.7	391.5	387.3	391.0	224.4
08/08 MON	226.8	223.4	212.5	212.5	241.0	332.6	235.2	246.9	249.4	228.4	341.8	372.9
	218.4	216.7	210.6	236.8	236.8	325.9	245.2	249.4	278.0	269.6	358.6	336.8
08/09 TUE	347.7	357.0	295.6	336.0	383.8	379.6	356.1	335.1	376.3	354.4	362.8	335.1
	351.1	309.1	334.3	373.8	386.4	351.1	382.2	370.4	374.6	356.1	349.4	327.6
08/10 WED	373.4	334.1	322.4	332.6	346.0	360.3	356.3	367.0	335.1	385.5	341.0	389.7
	299.0	311.6	335.1	320.0	389.7	329.0	386.4	357.8	344.4	339.3	376.3	346.0
08/11 THUR	332.6	362.8	325.9	356.1	373.8	391.4	372.1	358.6	350.2	359.5	353.7	365.4
	369.6	362.7	345.2	372.1	404.0	356.1	378.8	235.2	360.3	362.0	372.1	372.1
08/12 FRI	347.9	324.2	355.3	273.8	343.0	346.0	325.9	359.5	381.3	357.0	347.7	357.0
	352.6	361.2	345.2	357.0	363.7	351.1	346.0	360.3	330.1	347.7	359.5	367.0
08/13 SAT	345.0	347.7	354.3	353.6	325.0	374.6	363.7	340.3	359.5	341.8	366.2	349.3
	337.9	328.4	344.4	317.5	353.6	325.7	368.7	372.1	327.6	341.0	351.1	355.3
08/14 SUN	336.0	359.5	346.0	359.5	358.6	352.8	351.9	378.8	383.0	361.2	341.0	357.8
	360.3	368.7	340.2	340.2	342.7	342.7	324.3	367.0	338.5	365.4	337.6	329.2
08/15 MON	351.9	355.3	337.6	345.2	359.5	351.1	337.2	375.6	359.0	369.6	369.6	366.2
	362.8	349.4	332.6	343.8	384.7	370.4	382.8	386.4	361.2	357.0	377.1	340.2
08/16 TUE	346.0	353.6	325.9	330.9	340.6	389.7	354.4	325.0	362.8	367.0	351.1	347.7
	361.1	345.4	345.5	364.5	387.2	366.2	357.1	371.2	343.8	379.7	369.7	344.4
08/17 WED	354.4	360.3	348.6	365.4	371.2	342.2	385.5	365.4	372.9	378.8	353.6	378.0
	353.8	373.8	365.4	360.3	367.2	377.1	379.6	377.1	364.4	363.7	366.2	350.2
	367.9	377.1	371.1	371.1	371.1	371.1	371.1	371.1	371.1	371.1	371.1	371.1

A P P E N D I X C

S Y S T E M A N D C U S T O M E R L O A D C U R V E S

Detroit Edison System Load Patterns

One of the most important characteristics of electric utility systems is that of their capital intensiveness relative to other utility systems. The second characteristic which primarily distinguishes from others is that electricity cannot be stored. It has to be produced and supplied to the customers instantaneously at any time of the day. Another factor is that of social obligation of the utility system which requires that facilities must be provided in order to serve the loads of its customers in all hours in a reliable and economic manner. As such adequate facilities should be provided to meet the high demand periods which usually occur in summer and winter months, as well as the fluctuating loads at other times of the year. In addition, the system should allow sufficient facilities to permit down time for periodic maintenance and inspections.

Not all the electric utility systems are alike. They differ in many ways in respect to design characteristics, mode of production, generation mix, transmission and distribution. In general, they are designed to produce electric power and to supply the loads to the customers in a most efficient and economic way. However, the load-carrying ability of some types of generation and several components in the transmission and distribution system varies according to temperature, type and nature of customer demands and other inherent characteristics of the system at any point in time. Further, the facilities have capacity ratings which are a direct function of the amount and duration of the load imposed on them. The greater the diversity of the customer demands, the greater will be the flexibility of the system to adjust to these demands without additional capacity requirements. Further, the greater the average load requirements of the customers, the better will be the system's load factor which, in turn, implies lower average cost to the customer.

The load characteristics (shape) of a system determine the amount and type of generation. The basic types of generation available today are:

- (a) Base Load - High capital cost, lowest operating cost, not designed to start and stop frequently.
- (b) Intermediate - Capital cost less than base load, operating cost higher than base load; designed for starts and stops once or twice a week.
- (c) Peakers - Lowest capital cost, highest operating cost, designed for daily starts and stops if necessary.

The optimum economic mix of Detroit Edison load is approximately:

- (a) Base Load - 50-70% Coal fired generation
- (b) Intermediate - 20-30% Hydro
- (c) Peakers - 5-10% gas, or oil fired combustion turbines

At the present time, the company has generating capacity of approximately 9,000 MW. About 67% is coal fired base load, 24% is intermediate and 9% is peaking.

The historical load patterns of the system are summarized below since effective load management relies on a thorough knowledge of system demands, hour-by-hour throughout the year. Chart 1 shows the system load growth between 1960-1975.

- (1) Output increased 6% per year.
- (2) Winter peaks grew at 5% per year.
- (3) Summer peaks, 6% per year.
- (4) Summer base, 5% per year.
- (5) Summer, temperature - response load per degree increase in mean temperature increased at a rate of 11%.
- (6) Since 1967, Detroit Edison has been a summer peaking utility.

Chart 2 shows summer and winter peak day load curves for 1975. The highlights are:

- (1) In 1975, the summer peak demand was 11% higher than the winter peak-
- (2) In 1973, the summer peak was 25% above the winter peak; the highest ratio to date.

Chart 3 shows the temperature effect on summer loads. The historical evidence indicates that:

- (1) Over 25% of the summer peak (1,700 MW) was temperature-responsive load, largely air conditioning.
- (2) This load was equivalent to 84 MW for each degree increase in mean temperature above 62°F.
- (3) Temperature-responsive loads are a composite of air conditioning, additional refrigeration and pumping loads and higher system losses.

- (4) Peak days usually occur between June and mid-September.

The characteristics of maximum system demands in 1975 by weeks are described in Chart 4.

- (1) System peaks exceeding 6,000 MW occurred in seven different weeks, and usually in only one day of that week.
- (2) Spring and fall peaks were under 5,000 MW for most weeks.
- (3) The winter peak occurred in December, just prior to Christmas.

The average daily loads by day, by week, for 1975 (August) are shown in Chart 5.

- (1) Average daily loads in the summer peak month were 600 to 900 MW below corresponding hourly demands on the peak day.
- (2) Average weekend loads were up to 1,400 MW below weekday demands.
- (3) Daily load factors were 83% on weekdays; 88% on weekends.
- (4) On peak days, when the impact of Ludington pumped storage is included, the effective daily load factor approaches 94%.

The primary rate customers were responsible for 46% of the 1975 sales and for 40% of the summer system peak. Seasonally and daily, primary rate demands tend to be more stable than the domestic or commercial customer.

- (1) The load factor of these customers equals or exceeds the system load factor on both daily (83-88%) and annual (68%) basis.
- (2) Experience to-date indicates that industrial and commercial load patterns are more a function of economic activity than of rate design or the conservation ethic.

Chart 1

SYSTEM LOAD GROWTH SINCE 1960

Chart 2

TOTAL SYSTEM

Chart 3

TOTAL SYSTEM-SUMMER

Chart 4

WEEKLY SYSTEM PEAKS - 1975

Chart 5

SYSTEM LOAD ON AVERAGE WEEKDAY, PEAK DAY AND WEEKEND

Chart 6

SYSTEM CUSTOMER LOADS BY MAJOR SECTORS

Chart 7

DETROIT EDISON COMPANY HOURLY LOADS (MEGAWATTS)
 REGULAR PRIMARY LOAD SUMMARY BY BUSINESS
 (EXCL. BULK, METAL, MELTING, IRON, EL. SCHOOLS)
 JULY 1974 (AVG. WEEKDAY TUESDAY-FRIDAY)

Chart 8

DETROIT EDISON SYSTEM
 HISTORICAL ANNUAL LOAD FACTORS

EXPERIMENTAL CHARTS OF THE TEST AND CONTROL COMPANIES

The attached charts relating to the test and control companies show the average weekday billing demands for the month of May, 1977 (test period) compared with the average weekday billing demands of the customers for the month of May, 1976 (prior period). It should be noted that the customer billing demands were not adjusted for production changes that might have taken place between the test year (1977) and the prior year (1976), since the actual production figures of the companies were not available. In some cases, the actual production increased in 1977 compared to 1976 production; in other cases actual production decreased. The extent to which the actual percentage change in production occurred in each case was not readily available. The customers refused to provide reliable production data. Further, due to averaging some of the charts do not clearly indicate the actual reductions. In addition, the magnitude of reductions in billing demand (kW), as pointed out in the text, were small compared to the actual billing demands. In order to have a noticeable affect, one should have actual production figures relating to test and prior years as well as separate meters for individual component demands attributable to operations of the companies.

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 20

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 20

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 26

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 26

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 27

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY DEMAND PER CUSTOMER (KILOWATTS)
AVERAGE MAY WEEKDAY (TUESDAY-FRIDAY)
AM013 SIC 27 CONTROL GROUP - PRIOR YEAR
AM023 SIC 27 CONTROL GROUP - TEST YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 28

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 28

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 30

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 30

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 32

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 32

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 33 A

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 33 A

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 33 B

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 33 B

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 34 A

TEST GROUP CUSTOMER TEST YEAR
TEST GROUP CUSTOMER PRIOR YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 34 A

CONTROL GROUP CUSTOMER TEST YEAR
CONTROL GROUP CUSTOMER PRIOR YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 34 B

TEST GROUP CUSTOMER TEST YEAR
TEST GROUP CUSTOMER PRIOR YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY DEMAND PER CUSTOMER (KILOWATTS)
AVERAGE MAY WEEKDAY (TUESDAY-FRIDAY)

AMW0110 SIC 34 B CONTROL GROUP - PRIOR YEAR
AMW0210 SIC 34 B CONTROL GROUP - TEST YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 34 C

TEST GROUP CUSTOMER TEST YEAR
TEST GROUP CUSTOMER PRIOR YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 34 C

CONTROL GROUP CUSTOMER TEST YEAR
CONTROL GROUP CUSTOMER PRIOR YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 34 D

TEST GROUP CUSTOMER TEST YEAR
TEST GROUP CUSTOMER PRIOR YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 34 D

CONTROL GROUP CUSTOMER TEST YEAR
CONTROL GROUP CUSTOMER PRIOR YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 35 A

TEST GROUP CUSTOMER TEST YEAR
TEST GROUP CUSTOMER PRIOR YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 35 A

CONTROL GROUP CUSTOMER TEST YEAR
CONTROL GROUP CUSTOMER PRIOR YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 35 B

TEST GROUP CUSTOMER TEST YEAR
TEST GROUP CUSTOMER PRIOR YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 35 B

CONTROL GROUP CUSTOMER TEST YEAR
CONTROL GROUP CUSTOMER PRIOR YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 35 C

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 35 C

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 35 D

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)
SIC 35 D

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 37 A

TEST GROUP CUSTOMER TEST YEAR
TEST GROUP CUSTOMER PRIOR YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 37 A

CONTROL GROUP CUSTOMER TEST YEAR
CONTROL GROUP CUSTOMER PRIOR YEAR

-248-

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 37 B

TEST GROUP CUSTOMER TEST YEAR
TEST GROUP CUSTOMER PRIOR YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
AVERAGE WEEK (TUESDAY-FRIDAY)

SIC 37 B

CONTROL GROUP CUSTOMER TEST YEAR
CONTROL GROUP CUSTOMER PRIOR YEAR

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
 AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
 AVERAGE WEEK (TUESDAY-FRIDAY)
 SIC 37 C

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
 AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
 AVERAGE WEEK (TUESDAY-FRIDAY)
 SIC 37 C

-249-

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
 AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
 AVERAGE WEEK (TUESDAY-FRIDAY)
 SIC 37 D

MICHIGAN ELECTRIC LOAD MANAGEMENT STUDY
 AVERAGE HOURLY PRIMARY BILLING DEMANDS (KILOWATTS)
 AVERAGE WEEK (TUESDAY-FRIDAY)
 SIC 37 D

A P P E N D I X D

Primary Supply Rate - 1975¹

Service Charge \$200 per customer per month.

A demand charge of:

\$5.10 per kilowatt of demand for the first 1,000 kilowatts,
\$5.00 per kilowatt of demand for the next 9,000 kilowatts,
\$4.84 per kilowatt of demand for the excess, plus an energy
charge per kilowatthour of 8.0 mills plus fuel adjustment.

Primary Supply Rate - 1976²

Service Charge \$160 per customer per month.

A demand charge of:

\$6.00 per kilowatt for the first 1,000 kilowatts,
\$5.90 per kilowatt for the next 9,000 kilowatts,
\$5.75 per kilowatt for the excess, plus energy charges
of 1.5¢ per kWh for all kWh consumed during the on-
peak period, and 1.3¢ per kWh for all kWh consumed
during the off-peak period.

Primary Supply Rate - 1977³

Service Charge \$162 per customer per month.

A demand charge of:

\$4.97 per kW of on-peak billing demand,
\$1.20 per kW for the first 1,000 kW of contract capacity,
\$.90 per kW for the next 9,000 kW of contract capacity,
\$.60 per kW for the excess kW of contract capacity, and
energy charges of 1.7¢ per kWh for all kWh consumed
during the on-peak period, and 1.5¢ per kWh for all
kWh consumed during the off-peak period.

¹Old Rate

²New Rate used to evaluate load management investments

³Present Rate not used to evaluate load management investments.

Conversion FactorsSource

Coal	1 pound	=	10,615 Btu	(1)
Natural Gas	1 cubic foot	=	1,000 Btu	(2)
Liquified Petroleum Gas	1 gallon	=	92,000 Btu	(3)
Gasoline	1 gallon	=	125,000 Btu	(4)
Distillate Oil	1 gallon	=	138,690 Btu	(4)
Kerosene	1 gallon	=	135,000 Btu	(4)
Residual Oil	1 gallon	=	149,690 Btu	(4)
Electricity				
Consumption	1 kWh	=	3,412 Btu	(5)
Production	1 kWh	=	10,500 Btu	(4)

- (1) U.S. Bureau of Mines, "Bituminous Coal and Lignite Distribution, 1973"
- (2) American Gas Association, Gas Facts, 1972 and 1973
- (3) Approximate value based on conversion factors used by Detroit City area propane dealers.
- (4) U.S. Bureau of Mines, "Crude Petroleum, Petroleum Products, and Natural Gas Liquids: 1972", (Average values for U.S.)
- (5) U.S. Congress, Subcommittee on Energy of the House Committee on Science and Astronautics, "Energy Facts", 1973.

GLOSSARY

Billing Demand

In many cases, actual and billed demand are different. Actual demand is a record of what your demand really was during the month. Billing demand is the actual demand adjusted by the various rate provisions and is the demand used for the computation of charges. The demand upon which billing to a customer is based, as specified in a rate schedule or contract. It may be based on the contract year, a contract minimum, or a previous maximum, and, therefore, does not necessarily coincide with the actual measured demand of the billing period. e.g.: The billing demand will not be less than 40% of the maximum demand specified in the contract during, say, eight months of October through May, nor less than 70% of the highest billing demand in the preceeding months of June through September.

Base Load

That part of the utility's load (kW) that is usually supplied by large, efficient power plants, e.g. coal or nuclear generating plants, or the minimum load over a given period of time.

Btu (British Thermal Unit)

The standard unit for measuring quantity of heat energy, such as the heat content of fuel. It is the amount of heat energy necessary to raise the temperature of one pound of water one degree Fahrenheit at sea level.

Capacity

The load for which a generating unit, generating station or other electrical apparatus is rated either by the user or by the manufacturer. The generally used measure of capacity is kW.

Capacity Factor

The ratio of total electric generation (in kWh) supplied by a unit, plant or system, divided by the product of number of hours in the period considered and the maximum dependable capacity (in kW).

Coincident Demand

The sum of two or more demands which occurs in the same demand interval.

Coincident with System Peak (Contribution to System Peak)

The demand developed at the time of the system peak by a group of customers with similar service characteristics, i.e. major class (domestic, commercial, primary, other), sub-class (bulk power, street lighting, municipal pumping).

Coincident Maximum Demand

The maximum sum of two or more individual demands occurring in the same demand interval for a given period of time.

Coincidence Factor (Reciprocal of Diversity Factor)

The ratio of the sum of the coincident demands of a group or class (primary) at the time of the system peak to the sum of the non-coincident maximum demands of that group or class in the month that the system peak occurs.

The coincidence factor can never be greater than unity. Its value lies between zero and unity. Since a large part of the facilities required to render electric service depends upon coincident or diversified maximum demands of groups of customers, it is evident that the higher the coincidence factor, the larger becomes the amount of facilities required per kilowatt of the non-coincident maximum demands of individual customers; and the lower the coincidence factor, the smaller it becomes.

Demand

The rate at which electric energy is delivered to or by a system, part of a system, or a piece of equipment expressed in kilowatts (kW), kilovolt ampere, or other suitable unit at a given instant or averaged over any designated period of time. The primary source of "demand" is the power-consuming equipment of the customers. At Detroit Edison, demand is defined as the energy output for an integrated hour.

Demand Charge

Those charges which reflect the costs associated with the use of production facilities needed to supply the customer with electricity. Demand or capacity costs vary with the amount of capacity (kW) required for the utility to meet its peak demand. The capital costs of generating stations and transmission lines constitute a major portion of these costs. Demand costs are applicable to primary class customers and are generally billed according to the maximum demand registered during a specified period; e.g. year, month, etc.

Demand Interval

The period of time during which the electric energy flow is averaged in determining demand, such as 60-minute, 30-minute, 15-minute, or instantaneous.

Diversity

That characteristic of a variety of electric loads whereby individual maximum demands usually occur at different times. Diversity among customers' loads results in diversity among the loads of distribution transformers, feeders, and substations, as well as between entire system (see Load Diversity).

Diversified Demand

The simultaneous demands of a group of customers, appliances taken as a whole.

Diversified Maximum Demand

The maximum demand of diversified nature, obtained either from direct measurement, by the addition, hour-by-hour, of the load curves of individual elements or by the mathematical application of probability factors (such as coincidence of diversity) to the non-coincident maximum demands of individual components comprising the whole.

Diversity Factor (Reciprocal of Coincidence Factor)

The diversity factor is a measure of diversity present between maximum loads of individual parts of a system. It is defined as the ratio of the sum of the non-coincident maximum demands of a group or class, to the sum of coincident or simultaneous power demands of that group or class at the time of the system peak.

While the coincidence factor can never be greater than unity, the diversity factor can never be lower than unity. The diversity factor varies between unity and infinity.

Energy Charge

Those charges reflecting costs that vary by level of electric energy (kWh) supplied, as contrasted with the demand charge. Fuel costs account for a principal part of energy charges. Energy costs can increase as less efficient generating capacity is brought into use.

Electrical Energy

The commonly used terminology in the electric utility industry is kilowatt-hours. Kilowatt-hours are obtained by multiplying kilowatts by hours, and kilowatts (kW) are obtained by dividing kilowatt-hours by the hours of use.

Energy Intensity

The amount of electrical energy in kWh required to manufacture one unit of production or the equivalent of one FRB index unit of production.

Energy Use

The amount of electrical energy, in kWh, used by a specified customer or class of customer in a specified period of time.

Hours Use of Billing Demand

Total annual primary energy use divided by the primary billing demand for the month in which the system peak occurs.

Inter-class Coincidence Factor

The ratio of the diversified maximum demand (coincident demand) of two or more classes, which may constitute the system or a major geographical division thereof, to the sum of the maximum demands of those classes.

Kilovolt Ampere (KVA)

It is defined as follows:

$$KVA = \sqrt{(kW)^2 + (KVAR)^2}$$

Where KVA = total current-carrying capability

kW = the active power-carrying capability

KVAR = the reactive power-carrying capability

The above two measures, KVA and KVAR, are peculiar to the alternating current commonly produced by utilities. They are the capability of the production system to meet the reactive requirements of the load, which is expressed as reactive kilovolt-ampere, and the total current-carrying capability of the electric portion of the production system expressed in kilovolt-ampere.

The ratio of kW to KVA is called the power factor.

Kilowatt (kW)

The kilowatt is a measure of capacity of electrical equipment and the load or demand, for power by a customer, customer class, or the system as a whole. It is equal to 1,000 watts (defined herein).

Kilowatt-hour (kWh)

It is the basic unit of electric energy, and, is equal to one kilowatt of power supplied to or taken from an electric circuit steadily for one hour. The kilowatt-hour is a measure of electrical energy, whereas the kilowatt is the electric power or the rate of energy usage. The relationship between power and energy is one of time. Power equals energy divided by time, and energy equals power multiplied by time. This distinction between power and energy has significance in terms of the nature and incurrence of costs. Kilowatts determine an electric utility's capacity requirements, whereas kilowatt-hours determine the amount of coal, gas, steam, or oil consumed.

Load

The amount of electric power (kW) delivered or required at any specified point(s) on a system. Load originates primarily at the power-consuming equipment of the customers.

Load Curve

A curve showing power (kW) supplied, plotted against time of occurrence, and illustrating the varying magnitude of the load during the period covered. This curve presents the load pattern of the utility's customers over the specified time period.

Load Curve Daily

Curves of 60-minute integrated demand (kW) for each clock-hour of a 24-hour day.

Load Diversity (Electric Power Utilization)

The difference between the sum of the maxima of two or more individual loads and the coincident or combined maximum load, usually measured in kilowatts over a specified period of time.

Load Duration Curve

A curve showing cumulative levels of kilowatt demand plotted against the cumulative number of hours (by day, by week, by month or by year).

Load Factor

The ratio of the average load in kilowatts supplied during a designated period to the peak or maximum load in kilowatts occurring in that period. The average load is equal to the total kilowatt-hours in the period divided by the corresponding number of hours.

$$L.F. (\%) = \frac{\text{kWh}}{(\text{Hr.}) (\text{kW})} \times 100$$

The load factor shows how steadily the maximum power requirement has been employed. The load factor cannot exceed 100 percent. It lies between zero and one hundred percent. The importance of the load factor is usually indicated in cost terms. Generally, the higher the system's load factor the lower the average cost of service. A higher load factor implies a relatively continuous use.

For example, if the August load factor for Customer A is 100 percent, A's average load equals its maximum load and A uses the same number of kilowatts at all times during the month of August.

Losses

System losses are accounted for in two ways: as energy losses, and as demand losses. Energy losses are the difference between total annual output and the total energy use billed to all customers for an entire year. Energy losses are expressed as a percent of output. Demand losses are the energy losses incurred during a given period of time, i.e. the hours of the system peak. They are not based on billing information, but rather on the loss characteristics of the equipment - transformers and conductors, etc. -- over and through which this energy is carried during the hour of the peak. Demand losses are expressed as a percentage of system peak.

Load Management

Load management is defined as a set of peak demand-limiting or load-shaping techniques by which the loads can be reduced or shifted from on-peak to off-peak periods. A typical industrial customer facility can be divided into two load groups:

- (a) Essential loads - are usually lighting, production equipment, small appliances, elevators, and other equipment which is critical to the operation of the building or industrial plant.
- (b) Non-essential loads - are those that can be reduced or deferred to avoid demand peaks. These frequently represent electric water heaters, electric systems, air conditioning, ventilation fans, battery chargers, continuous ovens, batch furnaces, lighting, heating and other loads employed in infrequently used rooms such as warehouses, recreation halls, etc.

It is rather difficult to reduce essential loads unless the operations are shifted to off-peak periods. Sometimes, shifting of the essential loads from on-peak to off-peak may be uneconomical. However, the non-essential loads can be curtailed or reduced or can be shifted from on-peak to off-peak periods thereby reducing the demand peaks.

Several methods and techniques are available to reduce the peak loads of the customer. These include demand control monitoring systems, ripple controls, timers, and off-peak utilization of power. Load management does not imply load curtailment. It means efficient utilization of electric power. Load management/energy management equates to load factor improvement by reducing the peak load or by increasing the average load. In cost terms, effective load management reduces the average cost to the customer.

Energy conservation, on the other hand, implies the reduction of the loads and overall consumption of electric energy. The conservation techniques or methods include automatic demand-limiting controls such as timers, ripple controls, limited use of air conditioning, eliminating permanently unnecessary lighting, etc.

The attached chart points out the basic difference between load management/energy management and energy conservation.

Manufacturing

Operating business establishments engaged in the production of goods.

Non-Coincident

The sum of two or more individual demands which do not occur in the same demand interval. Meaningful only when considering demands within a limited period of time, such as a day, week, month, a heating or cooling season, and usually for not more than one year.

Off-Peak

Energy supplied during periods of relatively low system demands, as specified by the supplier.

A GRAPHIC COMPARISON OF ENERGY MANAGEMENT vs. CONSERVATION

On-Peak

Energy supplied during periods of relatively high system demands, as specified by the supplier.

Peak Load

The maximum load consumed or produced by a unit or a group of units in a stated period of time. It may be the maximum instantaneous load or the maximum average load over a designated interval of time.

Peak Responsibility

The load of a customer, a group of customers, or a part of the system at the time of occurrence of the system peak load.

Power Factor

Power factor is the ratio of the "working power or active power" to the total capacity required to provide this power:

$$P.F. (\%) = \frac{\text{KW}}{\text{KVA}} \times 100$$

A low power factor implies inefficient use of the equipment. Because of the very substantial cost increases associated with service to low power factor loads - and because these costs do not reflect in metered use of "working power" - special provisions are made to compensate for the additional investment. Accordingly, some Detroit Edison rates call for penalties ranging from one percent to three percent where the power factor is below 85 percent but above 70 percent. Power factors below 70 percent are not permitted, and customers are required to invest in the corrective equipment necessary to improve power factors above 70 percent. Until such correction is made, there is a provision for a 25 percent penalty. Lightly loaded or oversized motors or transformers of the customers, most welding operations and certain fluorescent lamp ballasts are typical offenders.

The best way to improve power factor depends largely upon the particular operating considerations involved. In some cases, motors or transformers can be sized more closely to the actual work requirement, effectively improving the power factor. It may be that motor idling or "no load" running periods can be reduced, with a two-fold benefit - improved power factor, at the same time, more effective energy management.

Primary Class

A customer, sales and revenue classification pertaining to electrical energy supplied at primary or transmission voltages. Primary class customers provide their own transformers. These customers are relatively large, are usually industrial, and their electrical rates are based upon peak demands as well as total energy use.

Rate Design

Refers to the shape of the total rate schedule and is a function of the load characteristics of the customer classes and the utility's demand, energy and customer cost components. Examples of rate form include declining block, time-of-day and inverted.

SIC Code

The Standard Industrial Classification (SIC) is a system of classification of business establishments according to the type of activity in which they are engaged, for the purpose of facilitating the collection, tabulation and analysis of data relating to establishments. The SIC code is a numerical designation for each type or group of establishment. Major group codes have two-digit designations while some groups have three, and particular industries have four digits.

Watt

The electrical unit of power or rate of doing work. The rate of energy transfer equivalent to one ampere flowing under a pressure of one volt at unit power factor. It is analogous to horsepower or foot-pounds per minute of mechanical power. One horsepower is equivalent to approximately 746 watts. One kilowatt is equivalent to 1,000 watts.

BIBLIOGRAPHY

MAGAZINES AND JOURNALS

"A New Approach to Lighting Control Systems", Administrative Management, October, 1976.

"A Program for Energy Management", Plant Engineering, May, 1974.

"A Simplified Approach to Electrical Service", Refrigeration Service and Contracting, October, 1976.

"A Study of the Elasticity of Demand for Electricity by Residential Customers: Sample Markets in Nebraska", Land Economics, February, 1965.

"An Analysis of Power Generation Costs Safe", Electric Light and Power, September, 1976.

"Analysis of the Industrial Demand for Electricity", Economic Journal, June, 1968.

Atwater, Marshall A. and John T. Ball, "Heat Load Requirements in Multi-Unit Housing for Senior Citizens", Ashrae Journal, June, 1976.

"August Heat Boosts Summer Peak 7.9%", Electrical World, December 15, 1973.

"Automatic Controls Light the Way", Factory, May, 1976.

Ayers, D. L. and R. E. Strong, "Compressed Air Storage: Another Answer to the Peak Problem", Power Engineer, August, 1975.

Baxter, A. J., "Effect of Insulation on Winter Preheating", Ashrae Journal, June, 1976.

Beatson, C., "Creating a Uniform Energy Demand to Cut Electricity Costs", Engineer, January 23, 1975.

Beatson, C., "Keeping Peak Power Demand Under Control and Out of the Red", Engineer, May 13, 1976.

Bertolett, A. D., "Distribution Planning and All-Electric Load Building", IEEE Transactions on Power Apparatus and Systems, December, 1973.

Brown, H. H., "Utility Load Growth, The Environment and FPC Responsibility", Public Utilities Fortnightly, May 7, 1970.

"Buildings that Conserve Energy", Building Systems Design, Feb/Mar., 1974.

Castenschiold, Rene, "Obtaining Power Reliability with Multiple Utility Service and On-site Generation," Electrical Practice, May/June, 1976.

Chapman, D., "Electricity Demand Growth and the Energy Crisis," Science, November 17, 1972, Volume 178, Number 4062.

Chapman, Duane and Timothy Mount, "Electricity Demand and the Financial Problems of Electric Utilities," Cornell Agricultural Economics Staff Paper, No. 74-25, September, 1974.

Chapman, L. D., "Electricity Demand and Utility Capacity Planning: Testimony before the Atomic Safety and Licensing Board, U.S. Atomic Energy Commission," Cornell Agricultural Economics Staff Paper, No. 73-23, November, 1973.

Clayton, R. E., "Forecasting Load Model Sensitive to Weather Data," Electrical World, March 15, 1973.

Coggins, James L., "An Effective Energy Audit: The Flow Sheet Approach," Ashrae Journal, June, 1976.

"Coops to Start Peak Saving Installation," Electric World, January, 1974.

"Conserve Energy by Design," The Trane Company, 1974.

"Conserving Energy in Existing Buildings," Building Systems Design, 1974.

"Conserving Energy - Industrial Plants," Electrical Construction, Oct., 1976.

"Control Devices and Systems," Control Engineering, September, 1976.

de Mello, F. P., et. al., "Load Rejection Overvoltages as Affected by Excitation System Control," IEEE Transactions on Power Apparatus and Systems, March, 1975.

"Dialogue Explores FEA'S Lighting Role," Electric World, April 1, 1975.

"Efficiency: Lightings Response to Energy Demands," Electrical Contractor, May, 1974.

"Electric Lamps - Automatic Dimming Saves Energy Dollars," Electrical World, May 15, 1976.

"Electricity: A Year of Change and Crisis," Factory, May, 1974.

"Energy," Science, April, 1974.

"Energy - and How to Boost Efficiency in Electrical Systems and Loads," Electrical Construction and Maintenance, June, 1974.

"Energy - Conserving Luminaries," Transmission and Distribution, Oct., 1976.

"Energy - Heat Recovery and Energy Conservation," Electrical Review, August/September, 1976.

"Energy: How Critical is the Crisis," Consulting Engineer, March, 1973.

"Energy Management - A new Discipline," Consulting Engineering, Oct., 1976.

"Energy Marketing - Demand Controller Shows Winter Peak," Electrical World, October, 1976.

"Energy Report," Design News, September, 1976.

"Energy Saving Ideas to Eliminate Waste in Moving Materials or Production from Place to Place During Production," Electrified Industry, September, 1976.

"Energy - Saving Lighting," Modern Plant Operation and Maintenance, 1974.

"Energy Saving Project Helps 'Invent' the Future," Consulting Engineering, October, 1976.

"Energy Saving Warehouse, Office Design," Heating/Piping/Air Conditioning, September, 1976.

"Energy Systems Environment and Conservation Division," EPRI Journal, June, 1976.

"Energy Utilization Program Decreases the Use of Fuels and Electricity," District Heating, July/August/September, 1976.

"FEA Funds/Load Management Rate Reform," Electric Light and Power, September, 1976.

"FEA Starts Conservation Effort," Electric World, December 15, 1974.

Field, A. A., "Reducing Housing's Share of the Energy Budget," Heating/Piping/Air Conditioning, May, 1976.

"Fog-Like Mist Humidifies Furnace Air," Design News, September, 1976.

"Fossil Fuel and Advanced Systems Division," EPRI Journal, June, 1976.

Gujarati, D., "Demand for Electricity and Natural Gas," Public Utilities Fortnightly, January 30, 1969.

Guth, L., "How to Evaluate Elasticity Studies," Electrical World, January 15, 1974.

Hayes, R. H. and W. Crawford, "Automatic Controls Excel in Startups on Generating Unit with Once-Through Boiler," Power Engineer, June, 1975.

"Heat Recovery the Electrostatic Way," Electrified Industry, Sept., 1976.

Hegland, D. E., "Demand Control Trims Electric Bills, 21: 69/71," Diag. Automation, August, 1974.

Hill, John, "Nuclear Power: The Achievements, The Problems and The Myths," Combustion, June, 1976.

Holbay, Nick, "Energy Conservation Techniques for Centrifugal Chillers," Heating/Piping/Air Conditioning, May, 1976.

Hooke, R. G., "Forecasting the Demand for Electricity," AIEE Summer General Meeting, July, 1955.

Houthakker, H.S., "Dynamic Demand Analyses for Gasoline and Residential Electricity," American Journal of Agriculture Economics, May, 1974.

"How M/E Engineers Design Energy Conserving System," Actual Specifying Engineer, August, 1974.

"HVAC System Design Criteria for Energy Conservation," Ashrae Journal, August, 1974.

"Industry Fuel Savings Efforts Fall Short," Industry Week, June 2, 1975.

"Industry Holds Key to Energy Conservation," Consulting Engineering, October, 1976.

"Industry is Moving Beyond Obvious Energy - Saving More," Industry Week, June 24, 1974.

Jack, C. F., "Electric Water Heaters: Peak Shaving Slices High Demand," Electrical World, January 15, 1976.

Jewell, Perry R., "Rate Increases Growth Raise Profits," Electrical World, September 15, 1974.

Johnston, F. C., "Selecting Dry-type Transformers for Lowest Operating Costs," Electrical Construction and Maintenance, June, 1976.

Keller, William B., "Lighting Techniques That Make Sense and Save Energy," Electrical Construction and Maintenance, June, 1976.

Kind, C. G., "Probability Technique Adds New Meaning to Demand Forecasting," Electric Light & Power, January, 1969.

Kinney, W.F., "New Strategy for Alarm Information Display," Power Engineer, December, 1974.

Lambert, F. J., "Understanding Uninterrupted Power Systems," Instruction and Control Systems, October, 1974.

Landman, W. J., "HVAC Controls that Save Energy," DE Journal, November, 1974.

Lawrie, Robert J., "PF Capacitors Slash Costs and Save Plant Energy," Electrical Construction and Maintenance, June, 1976.

Lehman, D. Carl, "Evaluating Energy Savings Measures: Impact of Rising Energy Costs," Ashrae Journal, June, 1976.

"Light is Right But Save the Power," Administrative Management, October, 1976.

"Lighting and Energy Conservation," Environmental Design, 1974.

"Lighting the Way to More Efficient Heating," Administrative Management, October, 1976.

"Load-Forecasting Techniques Envelope to Meet Need," Electrical World, February 1, 1976.

"Load Growth is Poised in the Wings as Conservation Lower kWhr Use," Electrical World, June 1, 1974.

"L.P.S. Lighting Cuts Lighting Load 80% (Comparison of Two Similar Outdoor Lighting Installations, One Using Low Pressure Sodium Lamps, the Other Mercury Vapor)," Electrified Industry, September, 1976.

Macriss, A., and Robert H. Elkins, "Standing Pilot Gas Consumption," Ashrae Journal, June, 1976.

Main, Jeremy, "A Peak Load of Trouble for the Utilities," Fortune, November, 1969.

Mayer, J., "Saving Energy in an All Fuel Plant," Power, October, 1974.

McConnell, R. R. et. al., "Reducing Energy Consumption During the Cooling Season," Ashrae Journal, June, 1976.

"Modification of Existing System to Conserve Energy," Building Systems Design, 1974.

Moorthi, R. V. and R. P. Aggarwal, "Damping Effects of Excitation Control in Load-Frequency Control System," INST. EE PROC., November, 1974.

"National Bureau of Standards Electric Power Research 'Energy Measurement Technology'," Dimensions, January, 1976.

Nissel, Hans E., "Price Signals or Load Management," Public Utilities Fortnightly, January 1, 1976.

"Now Water Heated During Peak Demands for Power," Machine Design, February 20, 1975.

"Office Lighting and Energy Conservation," Administrative Management, October, 1976.

Olmsted, Leonard M., "Utilities Slash Spending Plans," Electrical World, September 15, 1974.

"Optimizing the Use of Energy for Lighting," Lighting Design and Application, 1973.

"Optimum Use of Energy - An Electric Industry Report," Ashrae Journal, February, 1973.

Owens, Ken, "Load Management: Utility Pain or Panacea?," Electric Light & Power, September 22, 1975.

"Plant Electric Systems," Power Magazine, October, 1976.

"Plant Expansions Goes High Pressure Sodium," Electrical Construction and Maintenance, May, 1976.

"Power Demand Control: Compelling But Proceed With Care," Electrified Industry, July, 1976.

"Power Systems - Planning and Operation," EPRI Journal, June, 1976.

"Practical Considerations for T & B," Building Systems Design, 1974.

"Price Elasticity Can Be Misleading," Electrical World, December 15, 1973.

"Public Policy for Solar Heating and Cooling," The Bulletin, October, 1976.

Quinn, G.C. and J. R. Knisley, "Controlling Electrical Demand," Electrified Practice, July/August, 1976.

"Radical Techniques of Energy Conservation," Ashrae Journal, March, 1974.

"Redesign Cuts Power Consumption of Recording Instrument," Product Engineering, September, 1976.

"Reducing Plant Power Costs," Automation, August, 1974.

"Roundtable on Energy Conservation," GSA/NBS, 1974.

"Save Low Resisting Grounds Save Operating Dollars," Electric Light & Power, September, 1976.

"Small Businesses can Cut Down on Electrical Usage," Electric Light & Power, September, 1976.

Southward, K., "Cutting Lighting Levels Uses More Oil, Gas",
Electric World, December 14, 1974.

Spethmann, D. H., "Importance of Control in Energy Conservation,"
Ashrae Journal, February, 1975.

Spielvogel, L. G., "Energy - Management: Technology--Engineering--People,"
Ashrae Journal, June, 1976.

Stanton, K. N., "Forecasting Annual or Seasonal Peak Demand in Electric
Utility Systems," IEEE Transactions on Power, Apparatus and Systems,
May/June, 1970.

Stanton, K. N., "Medium Range, Weekly and Seasonal Peak Demand Forecasting
by Probability Methods," IEEE Transactions on Power Apparatus and Systems,
1970.

"Streamlined Model Forecasts Accurately," Electrical World, November 1, 1974.

Stubblefield, Richard R., "Energy Conservation in Commercial Buildings,"
Heating/Piping/Air-Conditioning, June, 1974.

"Summer Peak Eases Up Only 1%," Electrical World, October 15, 1974.

Summerlad, R.E. and R. H. Pai, "Refuse: The World's Wasted Energy Source,"
District Heating, January/February/March, 1976.

"Supplementing Natural Gas," Compressed Air Magazine, June, 1976.

"TEM (Total Energy Management) Boosts Building's Energy Efficiency,"
Electrical World, September 15, 1975.

"The Economics of Conservation," Consulting Engineering, October, 1976.

"The FEA Tempest," Public Utilities Fortnightly, October, 1976.

"The New Light Source - Furniture," Administrative Management, October, 1976.

"The Search for a Superbattery Speeds Up," Business Week, July 19, 1976.

"Thirty-five Ways to Save Energy Right Now," American Air Filter, 1974.

Thompson, Grant P., "Energy Conservation and the Law," Ashrae Journal,
June, 1976.

"To Help Conserve Energy," Electrified Industry, June, 1976.

"Total Energy for Industrial Plants," Consulting Engineering, October, 1976.

Traudt, Verne, "Future Shock: Energy Cost Projections," Heating/Piping/
Air-Conditioning, May, 1976.

"Twenty-one Secrets of Lower Heating Costs By Helping to Cut Fuel Bills this Winter," Popular Mechanics, October, 1976.

"Two Ways to Cut Heat Losses/Gains (Minimize Energy Waste Through Windows - Cold Weather and Hot Weather)," Electrified Industry, September, 1976.

"Utilities See Power Conservation Limited to a 7.1% Drop," Electrical Week, October 14, 1974.

"Utility, Building Owners Unite in Peak-Shaving," Electrical World, August 15, 1975.

"Utility Develops Totally Submersible Bank as an Economic Alternative to Substation Capacitors, Shunt Capacitors for Totally Underground Systems," Transmission and Distribution, October, 1976.

VanNess, Rick, "From Sun to Satellite to Society," The Cornell Engineer, June, 1976.

Weckslar, A. M., "Price Elasticity: Will Increasing Power Costs Affect Demand?," Electric Light & Power, August, 1974.

Weivel, William A., "Work-station Lighting Designed to Save Energy," Electrical Construction and Maintenance, June, 1976.

Wells, N., "Save by Controlling Power Demand," AM Machine, February 1, 1975.

Whitmer, L. R., "Minimizing Space Energy Requirements Subject to Thermal Comfort Conditions," Ashrae Journal, June, 1976.

"Will Less Glass Save More Energy?," Heating/Piping/Air Conditioning, September, 1976.

Wilson, J. W., "Electricity Consumption: Supply Requirements, Demand Elasticity and Rate Design," American Journal of Agriculture Economics, May, 1974.

BIBLIOGRAPHY

BOOKS

Cornell, R. T., Prospects for Growth in Electricity Usage and the Requirements for Generating Facilities, Coleman and Co., July, 1974.

Federal Energy Administration, Proceedings of the Conference on the Challenge of Load Management, Conservation Paper No. 24, June 11-12, 1975.

The Conference Board, Energy Consumption in Manufacturing, Ballinger Publishing Co., Cambridge, Mass., 1974.