WSRC-TR--91-625

DE92 010635

SAVANNAH RIVER VM - INTELLECT APPLICATION SUPPORT DOCUMENTATION (U)

by

L. S. Carter

Westinghouse Savannah River Company
Savannah River Laboratory
Aiken, South Carolina 29808

This is a technical report

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report was prepared in connection with work done under Contract No. DE-AC09-89SR18035 with the U.S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U.S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

WSRC-TR-91-025

SAVANNAH RIVER VM

INTELLECT
APPLICATION SUPPORT DOCUMENTATION

(u)

by
L. S. Carter
Information Systems Engineering

B. F. Hayhoe
Authorized Derivative Classifier

Revision Date: 09/23/88

By: L.W. Price

INTELLECT APPLICATION SUPPORT DOCUMENT

CONTENTS

INTRODUCTION

Document Scope	1.0
Product Description	1.1
Operating Environment	1.1.1
Common Terms	1.2
Application Construction and Configuration	1.3
Generic Application Configuration	1.3.1
Defining a New Application	1.3.2
Security	1.4
Non-sensitive Applications	1.4.1
Sensitive Applications	1.4.2
Reporting and Auditing	1.4.3
Integrity	1.5

USER SERVICES

Interactive Front-end	2.0
Application Access - INTELLEC EXEC	2.1
INTELLPA XEDIT	2.1.1
RUNAPPL EXEC	2.1.2
Printing	2.1.2(A)
Batch Requests	2.1.2(B)
SUBMIT EXEC	2.2

ADMINISTRATIVE SERVICES

Application Database Refresh	3.0
Description	3.0.1
The Server Virtual Machine	3.1
Server Function Description	3.2
Command Transmission	3.2.1
Validation	3.2.2
Authorization Structure	3.2.3
Types	3.2.3(A)
Granting and Revoking	3.2.3(B)
Server Architecture	3.3
Description	3.3.1
Log File Management	3.3.2
Transcript (TSCRIPT) File Management	3.3.3
Authorization Management	3.3.4
Lexicon Management	3.3.5

SYSTEMS PROGRAMMING

Product Support	4.0
Installation	4.1
INTELLECT	4.1.1
KBMS	4.1.2

APPENDICES

APPENDIX A - APPLICATION MINIDISK ASSIGNMENTS
APPENDIX B - APPLICATION PROFILES
APPENDIX C - COMMANDS AND EXECs
APPENDIX D - SERVER COMMAND REFERENCE

FIGURES

FIGURE I GENERIC APPLICATION CONFIGURATION

FIGURE II INTELLECT APPLICATION LIST RECORD LAYOUT

FIGURE III USER FRONT-END ARCHITECTURE

FIGURE IV FILE PACKAGES FOR BATCH REQUESTS

FIGURE V APPLICATION REFRESH

INTRODUCTION

1.0 Document Scope

This document details the underlying support programming and structures that support the INTELLECT and KBMS products at the Savannah River Facility.

The target audience for this document includes INTELLECT System Administrators, INTELLECT programmers and developers, and VM Systems Programmers.

1.1 Product Description

INTELLECT

INTELLECT is an "online information retrieval system" that allows non-technical computer users to "retrieve required data using everyday conversational English".

KBMS

Knowledge Based Management System (KBMS) extends the capabilities of the INTELLECT product.

1.1.1 Operating Environment

INTELLECT and KBMS are installed on an IBM 3081 multi-processor controlled by the VM/SP HPO 4.2 operating system. Both products execute in CMS virtual machines.

1.2 Common Terms -

Listed below are some common terms used throughout this document and within the INTELLECT environment. Some of the terms may have dual meanings (a local meaning as well as a generic AICorp definition).

The local definition should be used in those contexts where both definitions may apply.

DB

Database. Also used as the CMS filetype of database files.

DFAM

Dynamic File Access Method. Also the filetype of database files used in DFAM applications.

INTELL

User ID of the INTELLECT application service virtual machine. This ID owns all application files (lexicons and database files).

LEXICON

Defines the terms, files, and file structures used in an application.

MASTER

An INTELLECT programmer/analyst authorized to make changes to the application's lexicon and database files.

MASTER LEXICON

The version of an application's lexicon currently under development. This lexicon is typically accessible only to application MASTERS.

PRIVATE LEXICON

A user's personal lexicon that, in conjunction with the public lexicon, defines their personal vocabulary to be used when using an application.

PUBLIC LEXICON

The production version of an application lexicon, generally accessible to all authorized users of the application.

1.2 Common Terms (continued)

ROLLIN

The act of replacing the PUBLIC LEXICON with the MASTER LEXICON. Usually performed after a MASTER has made changes to the MASTER LEXICON and wishes to make those changes available on the application's public disk.

RULES

System security rules which are used to control access to application files and to enforce exclusive WRITE access to application minidisks.

SX

Sequential application. The deprecated term used to describe any INTELLECT application that uses the sequential access method.

1.3 Application Construction and Configuration

Each application installed in the VM/INTELLECT environment has the same basic or generic configuration as detailed in section 1.3.1 (see also Figure I).

1.3.1 Generic Application Configuration

An application will possess, at a minimum, three minidisks which are typically owned by the INTELL service virtual machine. These disks are:

PUBLIC Minidisk - contains the public (production) lexicon and database files.

MASTER Minidisk - contains the development version of the lexicon. Also contains the pre-production DB files for SX applications.

FIGURE I: APPLICATION CONFIGURATION

1.3.1 Generic Application Configuration (continued)

LOG Minidisk - contains the applications master log to which all user logs are appended when they are received. Also contains the master TSCRIPT (transcription) file for the application.

Each application also has its own logical set of rules that define authorized program masters (those users eligible to request exclusive WRITE links) and defines users authorized to use the application if it is defined as SENSITIVE.

1.3.2 Defining a New Application

The following steps must be performed in order to define a new application in the VM/INTELLECT environment.

A. The INTELLECT Programmer/Analyst or System Administrator determines the -

- size of the database file(s)
- approximate size of the lexicon
- frequency of lexicon rollins
- logging and transcription requirements
- authorized masters.

B. The VM Systems Programmer defines the

- Public minidisk. The size of this disk is determined by database file size, lexicon size, frequency of lexicon rollins.

The frequency of rollins is important since the INTELL virtual machine performs the lexicon update. It guarantees the integrity of the existing lexicon by renaming it and COPYING the new version of the lexicon to the public minidisk. Therefore, rollin frequency defines in effect the number of lexicons that must be maintained on the public minidisk between disk cleanups.

1.3.2 Defining a New Application (continued)

- Master Minidisk

The size of this minidisk is determined by the size of the lexicon at production cutover, expected growth in the lexicon and the number of database files that must be maintained (for SX files only).

- LOG Minidisk

This minidisk is typically the smallest of the three; 3 cylinders of 3380 DASD is usually adequate (assuming TSCRIPT is OFF for the application). Take into consideration the number of users, how frequently the application will be used, and the typical size of user logs. Also allow some space for TSCRIPT files, should transcription be turned on for the application.

Note - refer to Appendix A for virtual addresses to be assigned. Addresses should be assigned consecutively in order to minimize system free storage requirements for the INTELL service machine.

C. INTELLECT System Administrator or VM Systems Programmer adds rules for the new minidisks.

Considerations:

- Public Minidisk
 - Add "ACCEPT W" rules for application MASTERS.
 - (for SENSITIVE applications only)
 - Add "REJECT *" (reject all links)
 - Add "ACCEPT RR" for each authorized user.

1.3.2 Defining a New Application (continued)

Master Minidisk - Add "REJECT *" (reject all links)
Add "ACCEPT W" for each application MASTER.

Log Minidisk - Add "ACCEPT W" for each application MASTER.

D. INTELLECT System Administrator authorizes (via the server AUTHORIZE command) each application master.

*suby intel authorize user's application @ name
Production*

E. VM Systems Programmer adds a record to the INTELL APPLS or INTELL TESTAPPL file (located on the AICIQ 192) for the application. Figure II details the record layout of these files.

F. VM Systems Programmer adds a record to the LOG ADDRESS file, located on INTELL's 191.

The record layout within this file is:

cc 1 - 8 Application Name
cc 9 Blank
cc 10 - 12 Log Disk Virtual Address

G. INTELLECT Programmer/Analyst sets up the lexicon and database files. He or she must ensure that the lexicon is replicated on both the public and master minidisks before releasing the application for general availability.

FIGURE II

APPLICATION LIST RECORD LAYOUT

The following record layout is used within INTELL APPLS and INTELL TESTAPPL.

INTELL APPLS lists all applications that are considered to be production.

INTELL TESTAPPL lists applications currently under development or undergoing test and evaluation.

Column(s)	Field	Field Description
1 8	Name	Application Name
9	<blank>	
10 17	Owner	Virtual Machine ID of Application owner (usu. INTELL)
18	<blank>	
19 21	Public_addr	Virtual address of the minidisk with public lexicon, database files, etc.
22	<blank>	
23 25	master_addr	Virtual address of the minidisk that holds the master lexicon.
26	<blank>	
27 34	appl_exec	EXEC/module used to invoke the proper INTELLECT application interface.
35 40	<blank>	
41 80	Description	Short description of the application.

1.4 Security

Security is implemented via system rules (VMSECURE Rules Facility). Only authorized INTELLECT System Administrators and VM Systems Programmers can change the rules.

1.4.1 Non-sensitive Applications

A. Public Minidisk

Access is granted to all users via an "ACCEPT LINK * RR" rule.

"ACCEPT LINK * W" rules are used to authorize application masters to update the application's database files.

B. Master Minidisk

"REJECT LINK *" prevents ALL links. Application masters are granted access via "ACCEPT W" link rules.

1.4.2 Sensitive Applications

A. Public Minidisk

"REJECT *" link rule is coded to prevent any links.

Access is then granted to each authorized user via an "ACCEPT LINK * RR" rule for each user.

"ACCEPT LINK * W" rules must also be coded for are used to authorize application masters to update the application's database files.

1.4.2 Sensitive Applications (continued)

B. Master Minidisk

"REJECT LINK *" prevents ALL links. Application masters are granted access via "ACCEPT W" link rules.

1.4.3 Reporting and Auditing

Unauthorized link attempts are reported to and monitored by the CTM Computer Security Officer.

1.5 Integrity

Data integrity is ensured via coding of the rules identified in section 1.4. "ACCEPT W" rules are used to serialize lexicon updates by the application masters, and to prevent database file refreshing while the application is being used.

The INTELL server virtual machine is the exception to the exclusive write rules. It "owns" all application minidisks and is thus able to rollin master lexicons when requested by application masters or INTELLECT System Administrators. Integrity of any file that may be currently in use is maintained by the server since it will rename a file to be replaced but not erase it.

System backups are performed nightly and can be used to restore a corrupted or inadvertently changed database file or lexicon. Application masters or INTELLECT System Administrators can also manually archive any application file they are authorized to link and access.

USER SERVICES

2.0 Interactive Front-End

The primary general user access to the INTELLECT environment is through the INTELLEC EXEC.

The front-end is constructed of three main components: INTELLEC EXEC, INTELLPA XEDIT, and RUNAPPL EXEC.

Figure III diagrams the logic and file and data inputs and outputs as the user moves throughout the INTELLECT session.

2.1 Application Access - INTELLEC EXEC

This EXEC obtains the link and access to AICIQ 192 (the INTELLECT code minidisk). It then configures the virtual machine (primarily changes message settings). Finally, it invokes the INTELLPA XEDIT macro.

2.1.1 INTELLPA XEDIT

This XEDIT macro is intended to be invoked as a profile macro while editing one of the local INTELLECT application lists, either INTELL APPLS or INTELL TESTAPPL.

It provides a full-screen panel that allows users to select or set any of the following options:

Application - the INTELLECT application to be used.

Lexicon - which lexicon the user wishes to use (public, private, or master).

FIGURE III: USER FRONT-END ARCHITECTURE

2.1.1 INTELLPA XEDIT (continued)

- PF keys - allows the user to select 12 or 24, the number of PF keys used inside INTELLECT.
- Printer - the user can select which printer output, if any, will be routed to. He can also print to a disk file.

Printer selection is also menu supported. The DEFAULT EXEC (the PROFS default printer selection EXEC) is used to support this.

User selections are saved across INTELLECT (and logon) sessions in a GLOBALV group called INTELL. These values are retrieved at entry to the macro and override the macro defaults for the above fields.

2.1.2 RUNAPPL EXEC

Perform required links and accesses to the application minidisks, and then invokes the INTELLECT access EXEC or module to start (finally!) the INTELLECT session.

After the user leaves INTELLECT itself, RUNAPPL checks for the following types of files whose filenames are the same as the application just exited:

- BATCH requests to be submitted for batch execution.
- LOG record of session dialogue (user and INTELLECT).
- TSCRIPT transcription record (used for diagnostic purposes).

How print and batch requests are handled by RUNAPPL EXEC are detailed below.

2.1.2 RUNAPPL EXEC (continued)

A. Printing

The printer ID selected by the user is passed to RUNAPPL and is used to tag the user's virtual printer, which is then spooled to RSCS.

The INTELLECT access EXEC is called with "PRINTER PRINTER"; any request to be routed to the printer is then spooled directly to the user's virtual printer.

Please note that ALL session print requests are routed to one spool or disk file. This file is NOT closed and transmitted to the printer until the user actually leaves INTELLECT.

B. Batch Requests

RUNAPPL tests for the existence of a file with a filename equal to the application name and a filetype of BATCH. If this file exists, it is packaged with any other file required for successful processing of the batch request(s). RUNAPPL builds the file list and then invokes the VMBATCH command.

INTELLECT batch requests are submitted as class I batch jobs.

Other VMBATCH parameters are set within RUNAPPL.

Figure IV details the files that may be packaged with the actual batch requests. Other files selected depend upon the type of application and which lexicon the user used when inside INTELLECT.

FIGURE IV
FILES PACKAGED WITH BATCH REQUESTS

File(s) to be Included	Lexicon Used		
	PUBLIC	PRIVATE	MASTER
<application> BATCH	Y	Y	Y
<application> LEXICONP	-	Y	-
<application> LEXICON (master)	-	-	Y
DB file(s) *SX appls. only (for masters)	-	-	Y

Y - indicates a file or group of files that would be packaged with the batch request file given the lexicon selected by the user.

2.2 SUBMIT EXEC

This EXEC is used to submit batch requests created by the user without entering INTELLECT. The edited request lives in a CMS file. Each request must be completed with a period.

Please see Appendix C for a detailed description of how this EXEC can be invoked.

ADMINISTRATIVE SERVICES

3.0 Application Database Refresh

An application database refresh typically involves updating the application's database files. Updated data from MVS databases is dumped to tape, which is then mounted for the VMHPO virtual machine.

3.01 Description

- A. Application data is extracted from the appropriate MVS database into flat tape files.
- B. The application master or INTELLECT System Administrator then executes the REFRESH EXEC (usually in batch mode). This EXEC:
 - 1) Requests a mount of the tape containing the updated database information.
 - 2) Invokes the application's load EXEC to move the data from tape into the individual sub-database DB files.
 - 3) Converts the DB files into a format acceptable to the application. For instance, each DFAM application requires that all DB files be converted to DFAM format by using the INTELLECT Loader utility. In this case, REFRESH executes the LDR EXEC for the application: this EXEC invokes the Loader utility as required.

Figure V diagrams the database refresh process and required files.

FIGURE V: APPLICATION REFRESH

3.1 The Server Virtual Machine

The INTELLECT server is a disconnected service machine intended to provide a rudimentary serialization and file handling facility for management of application LOG and TSCRIPT files, simple disk space and file management, and to handle roll in of master lexicons to the public minidisk when requested by an application master or INTELLECT System Administrator.

3.2 Function Description

3.2.1 Command Transmission

VMCF (Virtual Machine Communications Facility) services, specifically SMSG, are used to transmit commands to the server.

3.2.2 Validation

The server determines if the user is authorized to issue the command received. The command is not executed if the user is not authorized for the application.

3.2 Function Description (continued)

3.2.3 Authorization Structure

The actual number of users requiring server authorization is small. Therefore, for simplicity and efficiency sake, all authorization data are held in storage in GLOBALV groups (one for each application).

Please note that server authorization is a separate authorization level. Any user being granted master authority must still be added to the system rules file for the application.

A. Authorization Types

There are two levels of authorization that can be granted to a user:

System Administrator

This level of authorization allows the user to request any server function for any application managed by the server. A System Administrator can also issue server commands that control operation of the server itself.

Application Programmer/Administrator

This authorization level allows the user to control application logging and transcription file handling, and to request master lexicon rollins when necessary.

B. Granting and Revoking Authorization

Only System Administrators are authorized to grant and revoke authorizations. Please see section ???? for the server commands used to manipulate user authorizations.

3.3 Server Architecture

3.3.1 Description

The server virtual machine is driven by a single-threaded REXX exec that -

- receives user LOG files and appends them to the application's master log file, if logging is activated for the application.
- receives user TSCRIPT files and appends them to the application's master TSCRIPT file, if transcription is active for the application.
- processes authorization commands.
- manages the master lexicon rollin process.

3.3.2 Log File Management

A log file is created during each INTELLECT session. The user front-end exec RUNAPPL EXEC SENDFILES the log to the server, and then erases it from the user's A disk.

The server receives the file and appends it to the existing or master application LOG file on the application's LOG minidisk, if LOGGING is active for the application.

The user log is discarded if logging is not active for the application.

3.3.3 Transcript File Management

A Transcript file is a screen log of the user's INTELLECT session. It is created only if transcription is active for the application. The file is used locally for troubleshooting purposes.

3.3.3 Transcript File Management (continued)

Transcription is activated within INTELLECT by use of the "TRANSCRIPT" command. The user can activate transcription, or the application programmer can turn it on for anyone who uses the application.

When the user completes the INTELLECT session, the RUNAPPL EXEC tests for the existence of the application TSCRIPT file; if found it is SENDFILEd to the server. The server appends the user TSCRIPT file to the application master TSCRIPT file (located on the application LOG disk) if TSCRIPT is ON for the application. The user file is discarded otherwise.

3.3.4 Authorization Management

Authorized users can either be "System Administrators" or "Application Administrators" (otherwise known as MASTERS).

Authorization records are maintained in storage in GLOBALV groups. When a user is authorized, a GLOBALV group is created with a name the same as the user ID. The applications for which the user is authorized to administrator are maintained in the group's AUTH variable.

The user ID is also added to the application group's AUTH variable. Authorization can then be checked by referring to either the user ID group or the application group.

Cancelling authorization simply means dropping the user ID from the application group's AUTH variable, and removing the application from the user group's AUTH variable.

3.3.5 Lexicon Management

When the server receives a "ROLLIN" command from an authorized user, it will initiate a lexicon update.

A lexicon update or rollin involves copying a master lexicon from the application's master minidisk to the application's public minidisk:

- A. The server receives the ROLLIN command and ensures the requester is authorized to do so.
- B. The server re-links to the application public and master minidisks. It then determines the size of the master lexicon.
- C. If there is sufficient space on the public minidisk, the master lexicon is copied to the public minidisk with a filetype of NEWLEX.
- D. If the copy is successful, the current public lexicon is renamed to a mode 0 file and given a filetype that is a combination of the Julian date and the number of minutes since midnight. This guarantees the original public lexicon is not corrupted if any user is linked to the public minidisk. Finally, the NEWLEX file is renamed and is given a filetype of LEXICON.

SYSTEMS PROGRAMMING

4.0 Product Support

Vendor: AI Corporation

Phone: 617-890-8400

Ask for INTELLECT or KBMS support.

Cust #: None (identify as ~~E.I. DuPont at SRP~~)

Westinghouse, Savannah River Co.

4.1 Installation

4.1.1 INTELLECT

Version: ~~303B~~ 303G

Owner: AICIQ

Disk: 192

Shared System: AICIQ @ x'700000' (654 pages)
SQL/DS Interface code

AICIQQ @ x'CC0000' (596 pages)
SX Interface

AICIQD @ x'CC0000' (664 pages)
DFAM Interface

Co-existence Requirements: PROFS, ISPF, GDDM, SQL/DS, KBMS

4.1.2 KBMS

Version: KBMS 32

Owner: KBMS

Disk: 192

Shared System: KBMSB @ x'CC0000' (608 pages)

Note - A twin DCSS definition KBMSA, is also defined. This allows a new version of KBMS to be installed without corrupting the existing, production version. Refer to the VM SYSTEMS REFERENCE for details concerning KBMS installation.

Co-existence Requirements: PROFS, ISPF, GDDM, SQL/DS, all INTELLECT DCSS.

APPENDIX C

COMMANDS AND EXECs

Described in this appendix are the following commands and EXECs that have been developed locally to support INTELLECT in the VM environment:

AICBATCH EXEC

INTELLEC EXEC

INTELLMG EXEC

LDR.... EXEC

LOAD.... EXEC

PORTLEX EXEC

REFRESH EXEC

SUBMIT EXEC

AICBATCH EXEC

Purpose

Sets up a VMBATCH worker machine in order to execute a batch INTELLECT request.

This EXEC is not intended to be invoked directly by a user.

Invocation

AICBATCH application lexicon userid batch_parms

where: application = name of INTELLECT application

lexicon = lexicon to be used (PUBLIC, PRIVATE, or MASTER)

userid = logon ID of user

batch_parms = optional batch parameters. These can be:

FILE if FILE specified then it must be followed by the filename, filetype, and filemode of the batch request file actually submitted.

If file is not specified, the default batch request file name is the application and the filetype assumed to be BATCH.

NOLOG If specified suppresses transmission of the INTELLECT log created during batch execution to the INTELL server machine.

COMP If specified, spools job output to the 3800 laser printer as a Class 3 print job (compressed print).

Required Files

INTELL APPLS
INTELL TESTAPPL

AICBATCH EXEC (continued)

Residence

AICBATCH EXEC resides on AICIQ 192 .

Notes

1. This EXEC assumes it executes in a Class I virtual machine.
2. All files other than the application's public lexicon must have been packaged with the batch requests. This is done automatically by RUNAPPL EXEC. Please see Figure IV for a description of these files.

INTELLEC EXEC

Purpose

Invoke the primary user front-end.

Invocation

INTELLECT [(options[])]

where: options = TEST - select from the list of applications under development.

Required Files

INTELL APPLS
INTELL TESTAPPL
INTELLPA XEDIT
RUNAPPL EXEC

Residence

INTELLEC EXEC resides on SYSADMIN 399.

Notes

1. This EXEC can be invoked from CMS, PROFS command line, or from any PROFS menu.

INTELLMG EXEC

Purpose

INTELLECT Server virtual machine (INTELL) driver.

Invocation

INTELLMG

Required Files

INTELL APPLS
INTELL TESTAPPL
LASTING GLOBALV
LOG ADDRESS

Residence

INTELLMG lives on INTELL 191.

Notes

1. This EXEC is automatically invoked at INTELL autolog.
2. Valid server commands can be sent to the INTELL service machine via SMSG, or can be issued from a connected virtual machine console.

LOAD.... EXEC

Purpose

One defined for each application. Moves source DB files from tape to the application public minidisk.

The name of the EXEC is derived by "LOAD"+first four characters of the application name.

Invocation

LOAD....

Required Files

None

Residence

The LOAD.... EXEC resides on the application's public minidisk.

Notes

1. This EXEC is automatically executed by the REFRESH EXEC.
2. This EXEC assumes that the proper tape has been mounted at virtual address 181 (standard VMTAPE mount address).
3. Input tape file characteristics are coded in the LOAD.... EXECs. If they should change then the corresponding EXECs need changing as well.

PORTLEX EXEC -

Purpose

Designed to convert an exported lexicon (filetype LEXPORT) to correct lexicon format (filetype LEXICON). Intended to be executed in batch mode.

Invocation

PORTLEX application lexin master_vaddr type

where: application = name of INTELLECT application

lexin = filename of the exported LEXPORT file (<lexin> LEXPORT).

master_vaddr = address where the converted lexicon is to be written.

type = DEAM | SX

Required Files

None

Residence

AICIQ 192

PORTLEX EXEC (continued)

Notes

1. This EXEC renames the existing lexicon before invoking INTELLECT to import the new lexicon.

If the INTELLECT Interface EXEC returns a non-zero return code, then the existing lexicon is restored before PORTLEX finishes.

2. The virtual address specified is assumed to be owned by the INTELL server machine.
3. An authorized application master or INTELLECT System Administrator must rollin the newly imported lexicon.
4. Example Batch submission:

```
"VMBATCH SUBMIT [<lexin> LEXPORT] (CL I STOR 4M TIME 06:00:00  
USER191 NO) PORTLEX <application> <lexin> <master_vaddr> <type>"
```

The [<lexin> LEXPORT] parameter is optional and need not be specified if the LEXPORT file resides on the application master minidisk.

REFRESH EXEC -

Purpose

Perform database file refresh in a VMBATCH worker machine.

Invocation

REFRESH application ON volser EXEC load_exec

where: application = name of INTELLECT application being refreshed.

volser = volume serial of the tape containing the new DB files to be loaded.

load_exec = name of application EXEC to move the tape files to disk.

Required Files

INTELL APPLS
INTELL TESTAPPL

Residence

AICIQ 192

Notes

1. If the application is a DFAM application, REFRESH will attempt to invoke the application's LDR..... EXEC once the load exec has moved the tape files to disk.
2. The EXEC requires an exclusive WRITE link to the application public minidisk.

REFRESH EXEC (continued)

3. Example Batch Invocation:

```
"VMBATCH SUBMIT (CL I USER191 NO STOR 4M TIME 06:00:00 TAPE6250  
N) REFRESH application ON volser EXEC load_exec"
```


SUBMIT EXEC

Purpose

Provide users with the ability to submit INTELLECT batch requests for execution without having to enter INTELLECT.

Invocation

**SUBMIT batch_file [PRIVATE | PUBLIC [APPLication appl_name
[NOLOG [batch_parms]]]]**

where. batch_file = filename, filetype, filemode of the batch request file.

Only the filename is required. The filetype defaults to BATCH and the filemode defaults to A.

PRIVATE | PUBLIC

PUBLIC is the default. If PRIVATE is specified then the user's private lexicon for the file will be submitted as part of the file package.

APPLication appl_name

specifies the name of the application the batch requests run against. If not specified the application is assumed to be the same as the filename of the batch request file.

NOLOG

If specified suppresses transmission of the INTELLECT log to the server machine.

batch_parms

VM BATCH control parameters which the user can set.

These are: SPOOL | NOSPOOL
FILERETN | NOFILERETN

SUBMIT EXEC (continued)

Required Files

INTELL APPLS
INTELL TESTAPPL

Notes

1. INTELLECT batch jobs are intended to execute in Class I worker machines.

APPENDIX D

INTELLECT SERVER COMMAND REFERENCE

SYSTEM ADMINISTRATOR COMMANDS

These commands can be executed only by authorized system administrators.

Server commands are sent to the INTELLECT server machine INTELL via the SMSG command.

AUTHORIZE user_id appl1 [appl2]

Grant application or system administrator authorization to the specified user and for the designated applications.

"appl1" can be specified as * if user_id is being given System Administrator authority.

REVOKE user_id appl1 [appl2]

Revoke application or system administrator authorization from the specified user and from the designated applications.

If revoking System administrator authority for user_id then specify appl1 as *.

SHUTUP

Shuts down the server.

Note This DOES NOT prevent any user from using INTELLECT. No server functions will be available until the server is restarted. The server can only be restarted by a VM Systems Programmer.

APPLICATION ADMINISTRATOR COMMANDS

The following commands can be issued for an application by any authorized application or system administrator.

LOG ON | OFF application

Sets server handling of user logs. "ON" results in the server appending user logs to the application's master log. If LOG is set "OFF", then user logs are discarded upon receipt.

ROLLIN application

Replace the current public lexicon for "application" with the master lexicon.

TSCRIPT ON | OFF application

Sets server handling of user TSCRIPT files. "ON" results in the server appending any user TSCRIPT file received to the application's master TSCRIPT file, located on the application's log disk. TSCRIPT "OFF" results in any TSCRIPT file received being discarded.

WHOHAS application [MASTER | PUBLIC]

Determine who has a link to the indicated minidisk for "application". If neither MASTER or PUBLIC is specified then a list of users linked to both the application's public and master minidisks is returned.

END

**DATE
FILMED**

5 / 6 / 92