DOE

DOE/ER/13708--T3

REPORT OF TECHNICAL PROGRESS

DE92 010330

for

STATISTICAL FLUCTUATIONS IN LASERS

Rajarshi Roy
School of Physics
Georgia Institute of Technology
Atlanta GA 30332

FG05-87ER13708

We have made excellent progress on both theoretical and experimental fronts in the period June-December 1991, that our research has been supported by DOE, Office of Basic Energy Sciences, Chemical Sciences Division. The personnel involved in the research are John Thompson (now Assistant Professor of Physics at DePaul University in Chicago), Larry Fabiny, Darlene Hart and Dr. Pere Colet, a Fulbright postdoctoral fellow from Spain. The following is a summary of our research, part of which has been published or has been submitted for publication. These reprints and preprints are contained in the Appendix to this continuation application, and may be consulted for a detailed description of the research.

1) Energy exchange between multiple frequencies of light due to four-wave mixing in a nonlinear medium:

Light is often transported in optical fibers over distances ranging from a few meters to kilometers for purposes of communications, spectroscopic diagnostics of combustion, or simply to deliver laser light to remote locations. We have investigated the energy exchange processes that occur when intense light at multiple frequencies is transmitted through an optical fiber. These four-wave mixing processes occur when the light intensity is high enough to cause a nonlinear response of the fiber medium to the electric fields of the light waves, and may have a major impact on applications for which the light is required.

Our experiments and theoretical studies examined the situation where two input light beams (pump waves) at different wavelengths were launched at the fiber input. At the fiber output, we detected light not only at the original frequencies, but also at several sideband frequencies. The number and intensity of the sidebands depends on the intensity and wavelength separation of the input beams, and on the length of the fiber. A model of energy exchange due to four-wave mixing interactions of the pump waves and sidebands was formulated. We predicted and experimentally showed that the energy of the input waves is not monotonically depleted through distribution to the sidebands.^{1,2} Energy is instead exchanged between the sidebands and the pump waves in either a periodic or chaotic manner with propagation through the fiber, contrary to previous expectations.

At low power levels and large wavelength separations, the energy exchange process is periodic, and only a small fraction of the total input energy is distributed to the sidebands. At high intensities and small wavelength separations, we find that there could

MASTER

be a chaotic exchange of energy as the waves propagate down the fiber, resulting in random statistical fluctuations of the power in the pump waves and sidebands.

We have examined the statistical distributions of energy in the sidebands after propagation of two intense pump waves in the fiber.³ The fluctuations of the input pump waves have to be considered together with the four wave mixing interactions. A comprehensive numerical model including two pump waves and four sidebands shows excellent agreement with experiments for moderate power levels and large wavelength separations, but significant discrepancies between experiment and theory were noticed at high powers and small wavelength separations. We propose theoretical and experimental studies to investigate these discrepancies in the next section.

These investigations are of an extremely fundamental nature; they apply to interactions between multiple wavelengths of light in any nonlinear medium. Light propagation through atomic vapors and optical fibers doped with atomic species will display these phenomena. Four-wave mixing with time delayed correlated fields was studied theoretically in collaboration with Professor S. J. Smith's group in Boulder and Professor G.S. Agarwal in Hyderabad.⁴

2) Phase-locking of spatially coupled solid state lasers:

The concept of distributing pump power over an array of spatially coupled, phase-locked lasers instead of pumping a single laser at high power is attractive for several reasons. The spatially distributed pump power is less likely to cause damage in the active medium since the power density at any point in the medium is lower, and it is easier to deliver the power in a spatially distributed fashion with optical fibers from the diode lasers that are very often used to pump solid state lasers. This concept has been used with success for some time in semiconductor laser arrays, but there has been very little experimental work with solid state lasers so far. With the availability of diode pump lasers and new solid state materials, this concept may be very attractive in the near future for high power diode pumped solid state lasers.

We had proposed to study such coupled lasers, and have recently succeeded in building our first laser arrays and studying in depth the coherence properties of two coupled solid state lasers. We use an Argon ion laser (later to be replaced by multiple diode lasers) to pump two spatially separated spots in a Nd: YAG (neodymium doped yttrium aluminum garnet) laser rod. The superposed beams from the two lasers are incident on a video camera system that records the interference fringes. The contrast or visibility of the fringes is a direct measure of the mutual coherence of the two lasers. The video camera image is digitized and the contrast of the fringes is calculated for different separations of the pump spots. We find that even with an overlap of one part in 10^5 of the two laser beams in the YAG rod, the lasers are phase-locked and mutually coherent. A quantitative comparison of the experimental results is made with a theoretical model, and very good agreement is found. These results are at present being prepared for publication.

Our next goal is to fabricate laser arrays with more elements and a variety of two-dimensional geometric configurations. Further, if the lasers can be phase-locked and achieve a high degree of mutual coherence, the overlapped focused beams can generate a power density that is proportional to N^2 , where N is the number of lasers in the array. The proposed research is more fully outlined in the next section.

3) Amplification of weak laser signals:

In continuation of our work on the detection and amplification of weak laser signals, we have demonstrated a system whereby weak optical signals can be amplified with high frequency resolution to a macroscopically detectable level by regenerative amplification in a frequency shifted feedback cavity.⁵ The output of this amplifier has a logarithmic dependence on the intensity of the injected signal providing a dynamic range of five orders of magnitude. It is possible to detect injected signals as low as the spontaneous noise level in the amplifier with amplification factors of more than 10^4 being observed. This behavior is related to the introduction of a new experimentally controllable parameter, an acousto-optically induced frequency shift, which limits the growth time of light in the cavity.

This system, when more strongly pumped, but with only spontaneous emission as seed, produces laser like emission. The input-output characteristics, output spectrum and build up dynamics differ from a conventional laser oscillator. In particular, the output field spectrum has no mode structure and is continuous in nature. The system is thus a source of broadband tunable radiation. It has recently been used with great success by Professor Klaas Bergmann's group in Kaiserslautern to cool and velocity select atoms in an atomic beam⁶, without the need to rapidly chirp the laser field or use spatially varying magnetic fields to Zeeman tune the transition frequency.

References:

- 1) "Multiple Four-Wave Mixing Processes in an Optical Fiber", J. R. Thompson and R. Roy, Opt. Lett. **16**, 557 (1991).
- 2) "Nonlinear Dynamics of Multiple Four-Wave Mixing Processes in a Single Mode Fiber", J.R. Thompson and R. Roy, Phys. Rev. **A43**, 4987 (1991).
- 3) "Statistical Fluctuations in Multiple Four Wave Mixing in a Single Mode Optical Fiber", J.R. Thompson and R. Roy, Phys. Rev. **A44**, 7605 (1991).
- 4) "Four Wave Mixing with Time-Delayed Correlated Fields of Arbitrary Bandwidths and Pump Intensities", G. Vemuri, G.S. Agarwal, R. Roy, M.H. Anderson, J. Cooper and S.J. Smith, Phys. Rev. **A44**, 6009 (1991).
- 5) "Regenerative Amplification of a Weak Optical Signal in an Active Frequency Shifted Feedback Cavity, I. Littler, K. Bergmann and R. Roy, Opt. Comm., to be published.
- 6) "Velocity Control and Cooling of an Atomic Beam using a Modeless Laser", I. Littler, H-M. Keller, U. Gaubatz and K. Bergmann, Z. Physik **D18**, 307 (1991).

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**DATE
FILMED**
5/04/92