NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

PROGRESS REPORT for
U. S. D.O.E. Contract No. DEFG05-91ER40670
March 1, 1991 - February 29, 1992

entitled

The Solenoidal Detector Collaboration at the SSCL

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

APR 21 1992

UNIVERSITY OF MARYLAND
DEPARTMENT OF PHYSICS AND ASTRONOMY
COLLEGE PARK, MARYLAND

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

The Solenoidal Detector Collaboration at the SSCL (Task D of Grant Proposal)

In December of 1989 the University of Maryland HEP Group became one (of many) founding members of the Solenoidal Detector Collaboration. The collaboration is guided by an Executive Board, an Institutional Board, and a Technical Board (the names speak for themselves). Most of our faculty (A. Baden, A. Ball, C.Y. Chang, N.J. Hadley, A. Jawahery, S. Kunori, A. Skuja, and G.T. Zorn) are members of the collaboration as is Prof. Jordan Goodman of the Maryland Cosmic Ray Group.

Our primary interest is the detection and measurement of muons and the design of the muon detector and trigger for the SDC. We have been concentrating on the design of the forward muon system (in the approximate pseudo-rapidity region of $1.5 < |\eta| < 2.5$ corresponding to azimuthal angles of 9.4° to 26.0°) and at present are responsible for the engineering design of the detector and detector support system in this rapidity region. A. Skuja has been leading the detector layout and design work. A. Ball and G.T. Zorn has been developing a facility for testing various muon detector prototypes.

We are also participating in the development of a liquid argon (LAr) calorimeter adapted to the bunch structure of the SSC machine. At present a LAr calorimeter still remains an option for the choice of calorimetry for the SDC. Recent measurements at BNL in a 20 GeV pion beam confirm that many of the problems associated with long signal collection times of LAr can be solved. The Maryland group instrumented the beam line and provided the DAQ for the BNL tests. N.J. Hadley has led our LAr effort with able assistance from D. Fong and J. Goodman. Prof. Hadley is presenting the first results of the test beam work at the Vancouver DPF meeting.

We have received R & D grants through the SSCL, initially as a supplement to our existing contract (\$45,000), but this year as a separate (\$ 160,000) grant running concurrently with our contract. We have no Texas Commission money for SSC R & D.

D. Baden and S. Kunori have done extensive work on SDC computing. Prof. Baden serves on the SDC technical board as a member responsible for planning the online and offline computer architecture for the experiment. Prof. Baden is sharing a DOE grant awarded under the Presidential High performance Computing and Communications Initiative for his work. He has been awarded an SSC fellowship, as well. Dr. Kunori has been organizing the detector simulation environment (the so-called Monte Carlo SHELL) as well as overseeing the detailed muon detector simulation group.

The Design of the Forward Muon System for SDC and the R & D of High Resolution Muon Chambers

Investigators: A. Ball, N.J. Hadley, S. Kunori, A. Skuja, G.T. Zorn at the University of Maryland in collaboration with Arizona, Argonne, Brandeis, Colorado, Fermilab, Harvard, Illinois, KEK, Michigan, Minnesota, Osaka City, Rochester, Tsukuba, Tufts, Washington, Wisconsin.

The SDC Muon System

The basic layout of the SDC detector and muon subsystem is shown in Fig. 1. The central (barrel) and intermediate (transition) muon regions ($|\eta| < 1.5$), consists of three superlayers of muon chambers, one inside and two outside a 1.5 m thick octagonal magnetized iron toroid ($B \approx 1.8T$), all located outside of the central calorimeter. Within each superlayer, the majority of wire planes are arranged in such a manner that the wires form projective roads to facilitate the implementation of a simple wire trigger that makes a local measurement of the azimuthal angle (θ).

The forward muon detector consists of 2 superlayers of wire chambers, both upstream and downstream of a 4m octagonal magnetized iron toroid. The layers are placed 2m apart. The toroid itself is split into 2m sections with an additional superlayer of chambers placed between them. This layout of chambers allows the measurement of the muon trajectory both before and after the toroidal magnet, so that a stand alone measurement of the muon momentum is possible. The superlayer buried inside the toroid allows one to distinguish large angle scatters in the toroid from low energy muons. A set of gas Cherenkov counters is placed between the final two superlayers of the muon system to reject low energy backgrounds while forming the muon trigger.

Two planes of scintillator are placed behind each of the outer two superlayers of wire chambers, both in the barrel region as well as in the forward region.

The drift tubes that form the muon detector are approximately 8 cm. wide (4 cm maximum drift) in the barrel region, while they are only 4 cm wide to allow for higher occupancy in the forward region. Their maximum length is 8.3 m. The design of the tubes has not yet been decided, but they are likely to be similar to those now used by CDF or D0 (without the second coordinate readout). Several designs are under study.

In the central region, the width of the scintillation counters is $15 \text{ cm}/\sin^2 \theta$. In the endcap regions, the narrowest counters are 10 cm wide and the width scales as $\sin^{1.35} \theta$. These angular dependences are chosen to give a roughly uniform p_t resolution, taking account of both measurement and scattering errors. The counters have a maximum length of 3 m, and a photomultiplier views each end. Both scintillator layers are presently positioned outboard of the toroids. We are studying the possible advantages of moving one layer inside the toroids.

Figure 1: The SDC Detector (1991)

We are also considering the use of gas Cerenkov counters in the forward direction, where the environment is likely to be hostile. These counters are insensitive to muons that either have momenta less than 5 GeV/c or do not point to the interaction region within 50 mr. Beam tests of the effectiveness and efficiency of these counters will be conducted at Fermilab in late 1991.

The arrangement of muon detector superlayers tends to place muon detectors preferentially away from massive iron absorbers. This is beneficial because high-energy muons are often accompanied by soft electromagnetic debris at substantial angles to the muon trajectory. The additional lever arm allows the debris to separate transversely from the muon track so that it will be less often confused with the muon signals at either the trigger or pattern recognition stage.

The muon detection system has five distinct goals, each of which puts different requirements on the design of the system. These five goals are the following:

1. To provide a Level 1 trigger;
2. To provide information for the Level 2 and Level 3 triggers;
3. To identify muons;
4. To improve the momentum resolution at very high muon transverse momenta;
5. To provide the capability of operation at luminosities above the design level.

Level 1 trigger

The Level 1 trigger operates at the beam crossing rate of 60 MHz and must arrive at a decision in 2 μ s. Thus it must be simple and fast, and still have the ability to reduce the accepted rate to a few tens of kHz. It is possible to do this with the muon system by triggering on a coincidence between two scintillator layers and a wire chamber trigger that is derived locally within one of the superlayers beyond the toroids.

The two layers of scintillators are arranged to be projective in θ with the center of a counter in one layer lining up with the division between two counters in the other layer for an infinite momentum trajectory. A suitable coincidence between counters defines the time bucket of the event and discriminates against low energy muons.

The wire chamber trigger, which is in coincidence with the scintillator trigger, is similar to that used by CDF. The wires in every other plane are projective to the interaction point. The time difference Δt between pulse arrivals on paired wires is then inversely proportional to the transverse momentum of the trajectory. A trigger threshold can be set on Δt by a simple circuit, whose deadtime is matched to the pulse pair resolution of the chambers. To avoid inefficiencies due to soft particles accompanying a high-momentum muon, a logical

OR of triggers from the last two superlayers is employed. The wire chamber trigger has an adjustable threshold.

For transverse momentum trigger thresholds of interest at Level 1, namely 10–40 GeV/c, the resolution of the trigger is dominated by multiple Coulomb scattering in the calorimeter and toroids, and has an rms value of about 25%. Detailed calculations of the low-momentum rejection of this trigger for four and six θ layers within a superlayer are now being performed.

Level 2 and Level 3 triggers

The purpose of the Level 2 trigger is to reduce the trigger rate by sharpening the transverse momentum resolution. This is done by connecting a θ measurement in the muon system with a track-stub measurement in the inner tracker. In the absence of scattering, all valid trajectories beyond the flux return point to the interaction point in θ . By using projective θ wires, the simple circuit discussed above for the Level 1 trigger can be employed to find stiff tracks (i.e., those that have not scattered more than expected) and to record the θ information for transmittal to the second-level trigger processor, where a match is made to the inner tracker information. At Level 2, a coincidence of detector octants containing a Level 1 θ trigger and a Level 2 θ trigger should be sufficient.

At the highest values of $|\eta|$, the Level 2 θ trigger is replaced by an angle-angle measurement in θ across the 4 m thick iron toroids. For this reason, an additional superlayer of θ planes is employed in the forward angle region.

The function of the Level 3 trigger is to insure that the lower-level triggers were valid and that they match. Stereo information is used in this process. At forward angles, stereo information is generated by simply rotating planes of θ wires by 15 and 30 degrees.

Identification of muons and Momentum Measurement

The key to muon identification is the redundant momentum measurement based on the toroids. These measurements are multiple-scattering-limited at 18% in the central region and 10% in the forward region. They are accomplished by angle-angle measurements in θ across the toroids. For this reason, a set of six planes of θ wires, with a minimum of a 50 cm lever arm, have been added in the central region to the superlayer immediately in front of the toroids. No chambers beyond those required for the second-level trigger are required in the forward region.

In the central region, the highest precision measurement of muon momentum comes from a combination of θ measurements from the inner tracker and the muon system. This is because the effective sagitta measurement is made near the outer radius of the inner tracker, as illustrated in Fig. 12. The resolution for a 1 TeV/c muon at $\eta = 0$ is calculated to be 14%. Fig. 13 shows the expected muon resolution as a function of pseudorapidity for several muon transverse momenta.

We believe that the proposed muon detector has enough resolution and redundancy to be capable of operation well above the design value of $10^{33} \text{ cm}^{-2}\text{s}^{-1}$. At ten times design luminosity, we estimate that the rate of single hits per unit of pseudorapidity in the first layer of the muon system varies from about 1 MHz at $\eta = 0$ to 100 MHz at $\eta = 2.5$. This latter value corresponds to a 300 kHz rate in a 4 cm drift chamber cell, or an occupancy of 12% in the 400 ns time window set by the maximum drift time. The occupancies of cells at $\eta = 0$ will be about a factor of 50 less, indicating that the muon system will remain operational at very high luminosities.

Research and Development Work at Maryland on the Forward Muon System

The Maryland Group is working on the design of the muon detector in the forward region for the SDC. The muon detector at forward rapidities ($1.5 < |\eta| < 2.5$) has to provide an adequate measurement of the muon trajectories for both the muon trigger as well as a good momentum determination in a region where the central track no longer has adequate coverage. The muon detector consists of four measuring stations, two before a 4m iron toroid and two after it. To achieve the momentum precision desired in this region, each measuring station must measure the relevant coordinates to a 100 microns. This resolution is more than adequate for the trigger. The number of detector planes in each of the stations is just adequate to do the required measurement. A fifth station is placed in the middle of the magnetized toroids to identify large angle scatters of energetic muons. The required precision and lack of redundancy imply that the 100 micron resolution per station also translates to about 100 micron resolution per cell in the detector.

The muon detector must be designed and tested by October of 1991 so that the chosen design can be incorporated into the SDC proposal due in April of 1992. In addition a detailed engineering design incorporating all support structures necessary to maintain the 100 micron resolution locally, as well as from station to station, must be finished on the same time scale. We have started an extensive engineering study of the forward detector, and a stand alone version of the system is displayed in Fig. 2

The muon detectors will be of the tube type ("closed geometry") arranged in an octagonal geometry. Tube type chambers have been chosen to restrict cross-talk and to prevent broken wires from introducing large gaps in the acceptance. Because of the large muon rate in this region for the expected luminosities, as well as possible backgrounds from soft neutrons, the cell size of the tubes has been chosen to be $4\text{cm} \times 4\text{cm}$ in width, ranging in length from 2.5m to about 8m.

The Maryland group would like to construct chambers with similar characteristics to those of the DELPHI external muon tracker. This group is using 1.6 cm aluminum tubes running in the limited streamer mode, and has reported 100 micron resolution *in situ* even at angles approaching 45 degrees. The cost of the DELPHI detector fell well within the SDC guidelines for the muon detector.

However, we would like to use a different gas (e.g. the HRS gas) to severely limit the

Figure 2: A Stand Alone Forward Muon System

amount of hydrocarbons required, and operate the chambers in the proportional mode (to reduce the HV requirements as well as other difficulties associated with the limited streamer mode operation). The larger cell size (4cm vs 1.6cm) of the SDC experiment will require prototypes to be built to see if the reported resolution can be maintained with the larger cells. In addition, the desire of proportional mode operation may require that the muon cells be built with field shaping electrodes. This aspect of the chambers must also be investigated before a final choice of chamber design can be made.

This year the Maryland group will build several chamber types, made from aluminum. The chambers will have 4cm $\times$ 4cm cells, and will be constructed with 100 micron as well as 40 micron sense wires. Thin walled cells are preferred to reduce the number of locally produced delta rays or photons while the muons traverse the chamber walls. Two types of test chambers that will be constructed are:

- Aluminum tubes of 4cm square cells, 2.5m - 3m long with 10 cells for a prototype chamber. Two different chambers will be constructed, one with 100 micron wire (limited streamer mode) and one with 40 micron wire (proportional mode).
- I-beam type chambers for field shaping, also with 4cm cells. The I-beams will run at negative HV while the walls and sense wire will be at nominal ground. Preliminary field calculations for such a geometry, indicate that the field shaping will be more than adequate for 4cm cells with such a geometry. Again the chambers will have 10 cells per chamber. And we will again construct two types of chamber - one with 100 micron wire and one with 40 micron wire.

Larger cells and other (similar) cell geometries will also be investigated.

The Maryland group will do initial measurements of the chamber prototypes using a laser system, later augmented by test beam measurements either at FNAL or BNL. The chambers must be tested for the required precision as well as for two track resolution at normal incidence, as well as all angles up to 22 degree incidence (corresponding to the outer corners of the octagon arrangement). The laser system has been installed and initial measurements on a 5cm $\times$ 5cm cell have begun.

These prototype chambers must be built and tested on a time scale that allows the final chamber type to be chosen by end of the summer of 1991. The Maryland group will also interact with the mechanical engineering design group at Fermilab and Wisconsin to ensure that the support structure will provide the required local and global resolution.

Research and Development of A Liquid Argon Calorimeter for the SSC

A. Baden, R. Black, C.Y. Chang, H. Deng, D. Fong, N. Hadley, G. Long, and A. Skuja at the University of Maryland in collaboration with the Brookhaven National Lab, The University of Rochester, the Lawrence Berkeley Lab, the Superconducting Super Collider Lab, the Oak Ridge National Lab, the University of Tennessee, the University of Mississippi, the University of Washington, Florida State University, Michigan State University, and Adelphi University.

We are members of the Liquid Argon Calorimeter Collaboration (LACC) for SSC Research and Development. This proposal was first funded in FY 1990 with part of the funds coming from the DOE HEP and part from DOE SSC. The LACC has built a prototype lead liquid argon calorimeter. The calorimeter has lead plates since we believe that uranium, which has been successfully used by the DØ experiment at FNAL and by the Helios experiment at CERN, will be too expensive for use at the SSC. A unit cell of the calorimeter consists of one 12 mm lead plate followed by a 2mm argon gap, followed by a 1.6 mm G10 printed circuit board and then another 2 mm argon gap. The calorimeter is now being tested in a test beam at BNL. The purpose of these tests is to measure " e/π " as a function of momentum and to test response uniformity across the gaps between modules. Details of the physics goals and motivation for these tests as well as other aspects of the LACC research program are given in the Memorandum of Understanding. In what follows we will concentrate on the University of Maryland's role in this effort.

The Maryland members of the Liquid Argon Calorimeter Collaboration (LACC) include Professors Hadley, Skuja, Goodman, Chang, and Baden and Research Scientist Doug Fong plus three students. Maryland is responsible for providing instrumentation for the test beam. This instrumentation includes Cerenkov counters for particle identification as well as a scintillating fiber hodoscope for triggering and beam definition. We are also responsible for the data acquisition system.

We completed the revamping of two Cerenkov counters early this year and helped to install them in the beamline at BNL. We increased the length of the Cerenkov radiator to 3 meters and built new windows for both counters. These Cerenkov counters have now been successfully used to obtain well identified pion and electron beams at BNL at momenta from 500 MeV/c to 20 GeV/c. In addition, we built a 48 mm by 24 mm scintillating fiber hodoscope for the test beam out of 1 mm square scintillating fibers. This hodoscope, which is readout by 40 1/2" phototubes, enables us to measure the position of particles in the beam as well as to study the effects of high rate ($> 2 \times 10^7$ particles per second) data taking. The outputs of the 40 phototubes go to TDC's which record a time history for each event. The time resolution of the individual fibers was measured to be about 1.8 ns RMS, and their efficiency to be $92 \pm 2\%$.

We setup the data acquisition system for the testbeam using a VAXStation and CAMAC. We modified a Fermilab data acquisition program so that it was compatible with LACC

needs in the BNL testbeam. Both the hardware and software were ready in time for beam data taking at BNL which began in April.

The analysis of the testbeam data from the calorimeter is in progress. We have data at beam momenta ranging from 500 MeV/c to 20 GeV/c for both pions and electrons with various shaping times (50 ns, 100 ns and 200 ns) for the calorimeter electronics as well as different beam intensities. For use at the SSC, of course, we are particularly interested in the high rate, short shaping time data. Preliminary results from the data will be available by the end of the summer.

SDC Computing and Software Design

Work on SDC computing and software naturally falls into two time scales: near term and long term. Near term efforts are of order 1 year, and are geared to meet the needs of the collaboration for the submission of the technical proposal, due in April 1992. These efforts consist of developing an integrated Monte Carlo framework to assist in the design and evaluation of the detector as completely as possible. A group headed by Dr. Kunori has been meeting intensively since December 1990, and is charged with developing a software framework to run on the SSC Simulation Facility consisting of 800 MIPS processing farm running UNIX on a variety of RISC processors. This group has also been charged with collecting the appropriate geometries for the full detector simulation as well as developing appropriate algorithms to reconstruct and analyze the simulated events. Another near term effort consists of developing the computing section of the technical proposal. This plan will deal with the software architecture, data and code management, data distribution, and (distributed) nature of the collaboration as well as a costing for the entire scheme. The Monte Carlo group efforts will most likely continue into the years as the detector parameters are determined. The work for the proposal will naturally continue into longer term design and implementation of the SDC computing system.

Since the SDC detector will be very complex and many people are working on various subdetector systems, it was realized that we needed a well coordinated effort to establish a complete system of programs for Monte Carlo code, event reconstruction code and analysis code.

Based on his experience in software development for DØ and E665 at Fermilab, Dr. Kunori proposed a simple system of programs to the SDC collaboration during the summer of 1990. The proposal was accepted. The collaboration formed a programming group and asked him to lead the effort.

Requirements for the system are as follows:

- The program should be able to run on any computer commonly available in the high energy physics world, now and in the future.

Tracking Detectors		
- silicon	B.Hubbard	(UC Santa Cruz)
- scintillation fiber	D.Adams	(Rice)
- wire	A.Palounek	(LBL)
- wire-fiber hybrid	M.Corden	(Florida State/SCRI)
- pixel	D.Pellett	(UC Davis)
Calorimeter		
- scintillation tile	H.Trost	(ANL)
- liquid argon	M.Asai	(Hirosima Inst. Tech., Japan)
- forward calorimeter	A.White	(Florida)
Muon Detector		
- central/forward	V.Slonim/M.Daoudi	(Colorado)

Table 1: Authors of program packages: Detector simulation codes

- The framework program should have minimum functionality: basic i/o capability, data management, machine independent file access and error handling.
- Any program package should be written in modular style and be able to run under the common framework.
- The software system should be easily distributed to institutions in the collaboration.

After a few months of design work of the program system, actual coding started in November, 1990. Dr. Kunori was mainly responsible for the writing of the framework program, while Y.Takaiwa of KEK wrote an interface program to the event generators, ISAJET, HERWIG and PYTHIA. D.Coupal of SSC added a single particle generator to the interface program. For detector simulation, we have adopted GEANT. An interface program between GEANT and each subdetector code was written by D.Adams of Rice.

The GEANT geometries for each of the subdetectors were written by individuals from the subdetector groups. Major program packages for the subdetectors and their authors are listed in Table 1. Calorimeter simulation codes include parametrization for fast shower simulation. Most of the packages have already produced simulated data into well defined data structure.

The major effort of the group has shifted from developing GEANT simulation code to event reconstruction code and analysis code. Since track multiplicity in an SSC event is huge, estimating track reconstruction efficiency in tracking detectors is a very important but formidable job. The tracking group lead by W.Ford of Colorado has already made good progress toward track reconstruction code. They have already reconstructed track segments in some of the detectors and are working toward linking those segments in different detectors.

The program has been running on VAX-VMS and most UNIX machines including Apollo,

DEC stations, IBM RISC machines, Silicon Graphics and SUN. Also it has been running on the CPS system at SSCL, which is a UNIX farm for parallel processing. The code has been distributed to many institutions in the collaboration, including institutions in Japan. S. Frederiksen of SSCL has been working as a library manager and B. Traversat of SSCL adopted the program to the CPS. He now works as the manager of the framework program instead of Dr. Kunori.

Although the initial version of the program is functioning, we have to improve every part of the software system. The initial goal of this project was to produce information to assist with the detector design for the proposal (due April of 1992). However, the programs will continue to be used over many years in order to refine the detector design even after the proposal submission, as well as to analyze data from beam tests.

Interactions between protons in the counter-rotating beams at the SSC will occur at a rate of approximately 10^8 Hz. A detector *trigger* system will then select between 10-100 Hz of these collisions (or events) for writing to permanent storage for further analysis (compared with 1 Hz at the Fermi National Accelerator Laboratory (FNAL)), where on average an event will contain approximately 1000 kbyte of information (compared with approximately 150 kbytes at FNAL). This large quantity of data - up to 1000 Terabytes per year (an increase of between 100 and 1000 relative to FNAL) - along with an expected 1000 physicists highly distributed around the globe (an increase up to a factor of 10 relative to FNAL) requires a data access design that will be able to handle an increase of approximately 10^4 in total access. (Note a year of operation is taken to be 10^7 seconds of actual beam collisions.)

Total cpu required for offline (after initial storage) data analysis will be approximately 10^5 MIPS - an increase of a factor of a few hundred over present systems installed at various existing laboratories. This challenge is projected to almost be met by a simple extrapolation of the past decade's increase in processor power through the coming decade. However, the storage and access requirements will most likely not be met by similar extrapolations in storage densities and available bandwidth, as these advances do not come at the same rate as those for raw cpu power.

Most HEP computing schemes store data in sequential records using memory management software systems written at HEP laboratories. Data are analyzed via computer programs which are written mostly in FORTRAN, access events from storage as records, read it into common memory, and provide hooks for users to apply custom-written subprograms. Each of these programs is compiled and linked to a standard set of libraries. Once the analysis program is built, it is made to loop over a number of events. For each event the entire record is read from storage, and those parts of the event which are relevant to the particular analysis (and very few analyses use all of the data in a single event) are used by the user subprogram. Thus the computing environment consists of a complicated coupling between the data model and storage method.

Data from detectors at the SSC will strain existing approaches to data storage and access even more that it will the availability of computing power to process the data.

At least part of the required increase of about 10^4 in data handling must be provided by improved algorithms and not just by improvements in storage devices. A move to a database organization for data from an SSC detector would allow reading only those parts of events which are of interest for the particular analysis, effecting a substantial saving in data handling and I/O bandwidth requirements. As part of an early start funding from the DOE's HPC/CI efforts, Dr. Baden's group is working on an R&D proof-of-concept which would entail an evaluation of a database organization scheme in high energy physics (HEP). The goal is to understand if such a scheme is feasible in the existing HEP environment, and perform an evaluation of how such a scheme may scale to meet SSC requirements. A proposal to continue this R&D in order to fully develop an object oriented or relational database system for SSC data has been submitted to the DOE's Scientific Computing Staff.

END

**DATE
FILMED**

6 / 11 / 92