SEMI-ANNUAL PROGRESS REPORT

08/01/91 to 02/01/92

Project Title: Stochastic Modeling of Macrodispersion in Unsaturated Heterogeneous Porous Media.

Grant No.: DE-FG02-91ER61199

Funding Period: 08/01/91-07/31/92

Principal Investigator:

T.-C. Jim Yeh, Associate Professor
Department of Hydrology and Water Resources
The University of Arizona
Tucson, Arizona 85721
(602) 621-5943

OBJECTIVES OF THE PROPOSED STUDY:

The objectives of the proposed study are: 1) to investigate factors controlling the fate and transport of contaminants in heterogeneous unsaturated soils, and 2) to develop a computationally feasible methodology for predicting chemical movements in large-scale unsaturated zone.

The proposed study will provide ways to estimate uncertainties in chemical transport due to spatial variability of soil hydrologic parameters. The uncertainty analysis is essential to interpretation of any field experiment of transport of chemically reactive tracers. Without eliminating the uncertainty due to heterogeneity in hydrologic parameters, mechanisms and principles controlling chemical behaviors of contaminants in the field condition may be misinterpreted.

TASKS ACCOMPLISHED:

MASTER

To achieve the objectives of the proposed research, several tasks were specified: namely, model development and verification, field data analysis, and stochastic simulations. The following sections provide summaries of the tasks accomplished during the period from August 1, 1991 through February

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Model Development and Verification.

A highly efficient numerical model, VSFT3 (a three-dimensional model) for simulating water flow and fate and transport of reactive contaminants in porous media under variably saturated (i.e., saturated or unsaturated) conditions was developed.

This model solves the partial differential equations describing flow and the convection-dispersion processes in heterogeneous porous materials under variably saturated conditions. For slightly compressible fluid in porous media under variably saturated conditions, the governing partial differential equation is

$$\frac{\partial}{\partial x_i} \left[K_{ij} \frac{\partial(\psi + x_j)}{\partial x_j} \right] - (C(\psi) + \beta S_s) \frac{\partial \psi}{\partial t} = q_s \quad (1)$$

where x_i are the spatial coordinates ($i=1,2,3$ with x_3 being vertical); K_{ij} is the hydraulic conductivity tensor which is a function of moisture content or pressure under unsaturated conditions; ψ is the pressure head (negative for unsaturated conditions); C is the specific moisture capacity and is defined as $d\psi/d\theta$ where θ is the volumetric moisture content; β is the constant for saturation and is 0 in the unsaturated condition and 1 in saturated condition. S_s is the specific storage, t is time, and q_s is the source or sink term. If the porous medium is heterogeneous, hydraulic conductivity, specific storage, and specific moisture capacity terms are functions of the spatial coordinates.

The governing equation describing the transport of a chemically reactive solute can be expressed as:

$$\frac{\partial}{\partial x_i} \left[D_{ij} \frac{\partial c}{\partial x_j} \right] - q_i \frac{\partial c}{\partial x_i} - \theta \frac{\partial c}{\partial t} + \frac{\partial(\rho_b c^*)}{\partial t} + f k_2 \rho_b c^* = q_s (c - c_s) \quad (2)$$

with

$$\frac{\partial(\rho_b c^*)}{\partial t} = k_1 \theta c - k_2 \rho_b c^* + \frac{\partial(\rho_b c^*)}{\partial t} \quad (3)$$

where D_{ij} is the hydrodynamic dispersion tensor computed on the basis of the Darcy velocity; c is the solute concentration in the liquid; c^* is the adsorbed phase concentration; c_k^* is the kinetic fraction of the adsorbed chemical and c_e^* is the equilibrium fraction; k_1 is the forward (adsorption) rate constant, k_2 is the backward (desorption) rate constant and k_3 is the equilibrium constant; f is the loss coefficient for the selective first order removal; q_i are the specific discharge components; ρ_b is the bulk density of porous media; q_a is the injection/pumped fluid volume per unit aquifer volume; c_a is the solute concentration in q_a .

VSAFT3 uses a Galerkin finite element technique to approximate the solutions to the governing flow and transport equations. Triangular and rectangular prism elements are used in VSAFT3 to discretize the solution domain. In the cases where porous media are under unsaturated conditions, Picard iteration is employed to solve the non-linear unsaturated flow equation and an automatic time-stepping scheme is applied to ensure the convergence of the solution. Solution of Equation (1) gives the pressure values at nodal points in the solution domain, which are, then, used to obtain continuous velocity fields using a mixed finite element approach.

With the velocity field as input, the solute transport equations, Equations (2) and (3), are approximated by the Modified Method of Characteristics (MMOC) and finite element approaches. MMOC involves backward tracking of solute particles along the characteristics of the equations and solving dispersion and reaction terms on the fixed finite element grid. Generally speaking, MMOC reduces the numerical oscillation problems in solute transport simulations and allows the use of large time steps in the simulation.

The linear algebraic equations resulting from the finite element approximation of equations (1), (2), and (3) are solved by an highly efficient conjugate gradient method. To ensure faster convergence of the conjugate gradient method, the incomplete LU decomposition of the coefficient matrix is used to "precondition" the set of linear equations. The preconditioned conjugate gradient solver, thus, reduces computer memory requirements and CPU time.

The model has been successfully verified for a variety of flow conditions. For instance, Figure 1 illustrates an excellent agreement between the simulated and observed breakthrough data of atrazine in a Honeywood silt loam soil, collected by Elrick et al. (1966). The accuracy of a two-dimensional velocity field obtained by the numerical model is also tested by comparing with an analytical solution for an unsaturated flow situation as depicted in Figure 2. The result of the comparison is shown in Figure 3. Simulated contaminant plumes under the unsaturated condition are illustrated in Figures 4 and 5. Finally, Figures 7 through 12 show the comparison of the result from VSAFT3 with an analytical solution (Goltz and Robert, 1986) for transport of a reactive chemical

in three-dimensional saturated porous media (Figure 6).

Since VSATF3 is constructed with many highly efficient numerical features, it is capable of simulating flow and solute transport in large-scale geologic materials with a relatively small amount of CPU times. Thus, it is ideal for conducting the proposed stochastic simulations.

Analysis of Spatial Variability of Soil Hydrologic Properties

Hydrologic data of an infiltration experiment, conducted by Nash (1985) was analyzed to investigate the spatial variability of soil hydrologic parameters. These data will provide the information about the spatial variability of soil hydrologic parameters needed in our analysis of its effect on transport of contaminants in unsaturated soils. The attached paper, submitted to Water Resources Research, reports the details of the analysis.

PUBLICATIONS SUPPORTED BY THIS RESEARCH GRANT

Publications

1. Srivastava, R. and T.-C. J. Yeh, Finite element simulation of three-dimensional chemical transport through variably saturated porous media, in preparation, to be submitted to Water Resource Research, 1992.
2. Yeh, et al., Characterization and prediction of spatial variability of unsaturated hydraulic properties in a field soil: Las Cruces, New Mexico Tech., submitted to Water Resources Research, 1992. (see attached).

BUDGET JUSTIFICATION

The proposed research requires a large number of simulations of soil-water pressure head, soil moisture, and solute distributions in soil profiles. The distributions are generally very complex and require three-dimensional simulations with high resolution which demands large computer memory in our high speed IBM/RISC/6000 workstation. Without the increase in memory, the resolution of the simulation has to be reduced and would jeopardize the accuracy of the result. This additional cost is included in the proposed budget for the period of August 1, 1992 through July 31, 1993.

CASE 1

Comparison for One-dimensional Case

PARAMETERS:

$$L = 1.0 \text{ m}$$

$$\alpha_L = 0.025 \text{ m}$$

$$\alpha_T = 0 \text{ m}$$

$$q = 0.1 \text{ m/hr}$$

CASE 4

PARAMETERS:

$$L = 15 \text{ cm}$$

$$H = 10 \text{ cm}$$

$$a = 6 \text{ cm}$$

$$b = 9 \text{ cm}$$

$$q = 0.5 \text{ cm/hr}$$

$$K_s = 1.0 \text{ cm/hr}$$

$$\theta_s = 0.440$$

$$\theta_r = 0.067$$

$$\alpha = 0.01 \text{ /cm}$$

$$\alpha_L = 0.1 \text{ cm}$$

$$\alpha_T = 0.1 \text{ cm}$$

Comparison of Velocity with the Analytic Solution

(b)

(a)

WITH DISPERSION

Print || u2c10 || Unsaturated Flow and transport

Print || u2c10 || Unsaturated Flow and transport

Print || u2c20 || Unsaturated Flow and transport

Print || u2c40 || Unsaturated Flow and transport

NO DISPERSION

Print || utc5 || Unsaturated Flow and transport

Print || utc10 || Unsaturated Flow and transport

Print || utc20 || Unsaturated Flow and transport

Print || utc40 || Unsaturated Flow and transport

SOLUTE CONCENTRATION

CASE 2

PARAMETERS:

$$XL = 20 \text{ m}$$

$$YL = 2 \text{ m}$$

$$ZL = 2 \text{ m}$$

$$L = 1.1 \text{ m}$$

$$M = 0.375 \text{ m}$$

$$N = 0.375 \text{ m}$$

$$l = 3 \text{ m}$$

$$m = 0 \text{ m}$$

$$n = 0 \text{ m}$$

Reaction Constants:

$$k_1 = 0.0175 / d$$

$$k_2 = 0.0316 / d$$

$$k_3 = 1.78$$

XL

$$q = 0.031 \text{ m/d} \quad \alpha_L = 0.22 \text{ m} \quad \alpha_T = 0.018 \text{ m}$$

Breakthrough Curve at the Sampling Point

Time = 200

Level	Conc
6	0.12
5	0.10
4	0.08
3	0.06
2	0.04
1	0.02

Level	Canl
6	0.12
5	0.10
4	0.08
3	0.06
2	0.04
1	0.02

Breakthrough Curve at the sampling point

Breakthrough Curve at the Sampling point

DISPERSIVITY REDUCED TO ONE-TENTH

Time = 200

Level Cont
C 0.45
B 0.40
A 0.35
0 0.30
7 0.25
6 0.20
5 0.15
4 0.10
3 0.05
2 0.05
1 0.05

Level Cont
C 0.45
B 0.40
A 0.35
0 0.30
7 0.25
6 0.20
5 0.15
4 0.10
3 0.05
2 0.05
1 0.05

STOCHASTIC MODELING OF MACRODISPERSION IN THE UNSATURATED ZONE

Progress Report, Year 1 New Mexico Tech

The work reported here for year one was carried out by Dr. Allan Gutjahr and his graduate students at New Mexico Tech. Both completed work and ongoing work will be discussed.

The primary effort in this first year was concentrated on developing and testing the required computer programs and software. Considerable progress was made for both the two and three dimensional cases as discussed below. The tasks carried out in year one were the following:

- 1) Refinement and further testing of the Fast Fourier Transform technique for generating random fields in two dimensions.
- 2) Development of conditioning programs in two dimensions.
- 3) Applications of the conditioning procedure to some transport problems in the saturated case.
- 4) Extension of the two-dimensional results to three dimensions.

1) Fast Fourier Transform Random Field Generator

The algorithm previously developed (Gutjahr, 1989) was modified to save computer storage. In the original version the procedure required computer storage equal to four times the desired output field in two-dimensions and eight times the output field in the three dimensional case. By examining the Fast Fourier Transform procedure we were able to reprogram the method so that, independent of dimension, the storage requirements equal twice the field size. The idea behind the space saver version is the following. The usual FFT is

$$V(n_1, n_2) = \sum_{m_1=0}^{2M-1} \sum_{m_2=0}^{2M-1} W_{2M}^{n_1 m_1 + n_2 m_2} X(m_1, m_2)$$

where we consider the two-dimensional case, $W_{2M} = \exp(2\pi * i / 2M)$

and M is a power of 2. The exponent in the sum and the arguments of X are rewritten as $m_1 = 2j_1 + b_1$ and $m_2 = 2j_2 + b_2$. Then

$$V(n_1, n_2) = \sum_{(b_1, b_2) \neq (0,0)}^{(1,1)} W_{2M}^{n_1 b_1 + n_2 b_2} \sum_{j_1=0}^{M-1} \sum_{j_2=0}^{M-1} W_M^{j_1 n_1 + j_2 n_2} X(2j_1 + b_1, 2j_2 + b_2)$$

since $W_{2M}^2 = W_M$.

The inner sum is a Fast Fourier Transform for an M by M array. It can be calculated for each of the four values of (b_1, b_2) and a running sum updated.

For large fields (e.g. in three-dimensions fields of size 128 by 128 by 128) the space savings can be significant.

2) Conditioning development in two dimensions.

The procedures for carrying out joint conditioning have been developed and programmed. Options allowing measurement errors to be included have been built into the codes. This method uses conditioning in the spectral domain as discussed in the original proposal. The methods have been checked for linearized equations.

In several applications, a fine discretization is needed to get convergence to the desired measured properties. For the small variance case, eight to ten points per correlation length are usually sufficient. Current studies are examining large variance cases.

3) Applications of conditioning to transport.

The conditioning methods have been applied to two dimensional flow and transport problems. The effect of different types and amount of data on transport predictions were studied. The arrival time curves at boundaries were investigated. Information about both heads and transmissivities were used. If there is at least one observation per correlation length, the uncertainty in the arrival time predictions can be substantially reduced from the no-data case. In addition it appears this reduction does not depend substantially on the input variance of the transmissivity field if that variance is less than 1.

A second application involved testing the linearization used in the flow equations. Conditioned solutions were compared with exact solutions to flow equations that were obtained by using a multi-grid procedure. Again if there is at least one observation per correlation length the linearized solution compares well with the exact solution for the small variance (e.g. variance of $\log_e$ -transmissivity $< .5$) case.

4) Extension to three dimensions.

The transform method and the joint generation technique have been extended to three dimensions and current work involves extending the conditioning procedure to three dimensions.

Presentations

One presentation of this work was made at the AGU meeting in December and the support of the DOE subsurface program was acknowledged. Work on a manuscript for publication in either Water Resources Research or Mathematical Geology is currently proceeding. The paper is about 75% completed and we expect to submit it this semester.

END

**DATE
FILMED**

4 / 13 / 92