DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DOE/PC/89807--T7

DE92 012660

Rec 4-10-90

DOE/PC/89807--T7

**AN EVALUATION OF A PRE-CHARGING
PULSE-JET FILTER FOR SMALL COMBUSTOR
PARTICULATE CONTROL**

DOE CONTRACT NO. DE-AC22-89PC89807

PROJECT QUARTERLY REPORT

APRIL 1990

FOR THE PERIOD OF 12/1¹⁹⁸⁹₁ 2/28/90

PREPARED BY

J. M. QUIMBY

MAY 1 1992

**RESEARCH-COTTRELL ENVIRONMENTAL SERVICES AND TECHNOLOGIES
P.O. BOX 1500
SOMERVILLE, NEW JERSEY**

**PREPARED FOR THE
PITTSBURGH ENERGY TECHNOLOGY CENTER
U.S. DEPARTMENT OF ENERGY
P.O. Box 10940
PITTSBURGH, PENNSYLVANIA 15236**

DOE CONTRACT SPECIALIST: KEITH R. MILES

DOE PROJECT MANAGER: THOMAS D. BROWN

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

	<u>Page</u>
1.0 INTRODUCTION.....	1
2.0 OBJECTIVES.....	3
3.0 PROGRAM PLAN.....	3
4.0 WORK PERFORMED.....	4
5.0 WORK TO BE PERFORMED NEXT QUARTER.....	6
6.0 FORECAST.....	6

1.0 INTRODUCTION

A current national initiative is the replacement of natural gas and petroleum derived fuels with coal. In response to this initiative, the Department of Energy and private industry are developing a group of small to medium scale coal fired combustors over a size range from residential to light industrial. The success of this program depends on the availability of air pollution control systems suitable for use on the combustors and capable of satisfying control regulations anticipated for the 1990's.

Historically, combustors in this size range, even when coal fired, have had only rudimentary pollution controls, or none at all. On the other hand, particulate control by an electrostatic precipitator has been the norm for large coal fired utility boilers for many years. There are several reasons for this size dependent regulatory structure. The principal reason is that the large coal fired combustors generate the majority of particulate. Another reason is that the typical small combustor owner does not have the resources to operate and maintain a pollution control device such as an electrostatic precipitator.

If the use of coal in small scale combustors is successfully encouraged, then suitable pollution control devices must be an integral part of the combustor's system in order to prevent deterioration of air quality resulting from increased coal combustion. The operation and maintenance of these devices must be tolerated by the individuals and small companies which will utilize the combustors. Such control devices need to be developed in parallel with the development of the small-scale combustors.

Considering the array of commercially available particulate control devices, the pulse-jet fabric filter most closely meets these specifications. It is among the smallest of particulate control devices per unit gas flow, and it is one of the most commonly utilized particulate control device for small (less than 10,000 CFM) applications. The pulse-jet fabric filter has no moving parts and yields a dry ash product which can be disposed with combustor bottom ash. Pulse-jet filters are often applied to processes in which severe load swings are commonplace, with frequent stops and starts.

The desired emission level for particulate of $.02 \text{ lb}/10^6 \text{ Btu}$ represents a collection efficiency of approximately 98% when burning Beneficiated Illinois #6 Coal. Fabric filtration is generally recognized as being capable of achieving the highest collection efficiency of any particulate control technology. Overall collection efficiency of 99.9% is commonly guaranteed by vendors. Recently it has been found that the good collection efficiency of the fabric filter can be substantially improved by means of charging the particles prior to filtration. Typically, this technique has been shown to increase collection efficiency from 99.9% to 99.99%, or a ten-fold reduction in emissions. It has also been found that lower pressure drop across the filter results when charged particles are filtered. This additional performance enhancement can result in lowered operating costs or can allow the designer to reduce the size of the filter.

Based upon results such as these, it is clear that a pulse-jet fabric filter, equipped with a particle charger, can provide superior particulate control for the small combustor application, as well as meet all the requirements of simplicity, compactness, and reliability.

2.0 OBJECTIVE

The objective of this test program is the performance and economic evaluation of a pre charged-pulse jet filter as the principal particulate control device for a commercial or industrial scale coal fired combustor. Performance factors that will be considered are the effects of particle charge, air/cloth ratio, fabric types, percent humidity and inlet particulate loading on fine particle collection efficiency, and pressure drop. Economic factors that will be considered are capital costs, energy and other operating costs, and maintenance costs.

The program will result in a recommendation regarding the relative suitability of the pre charged pulse-jet filter for small combustor particulate control, as compared to other control devices. Fine particle control capability, ease of operation, and overall economics will be taken into consideration in making comparisons.

3.0 PROGRAM PLAN

This research project is divided into six distinct functional categories, or tasks, which must be completed in sequence. These tasks are categorized as follows:

TASK 1: Work Plan

TASK 2: Design, Procurement, and Installation

TASK 3: Shakedown

TASK 4: Test Program

TASK 5: Analysis and Economic Evaluation

TASK 6: Reporting

A schedule for the completion of Tasks 1 through 6 is provided in Table I, Milestone Schedule, where shaded portions of the graphic represent the monthly status of work performed. Table II, Cost Management Report, represents the status of accrued costs and Estimated Accrued Costs up to March 1, 1990. Table III includes a monthly status of Labor Hours, Costs expended, and Milestones.

4.0 WORK PERFORMED

- 4.1 The baghouse shell, property of Research-Cottrell, was retrofitted to accommodate two pulse jet assemblies. Prior to this contract the baghouse was a shaker-type fabric filter unit.
- 4.2 Two pulse jet cleaning units have been ordered from Flex-Kleen Inc., Chicago, Illinois at a unit cost of \$1,277 each. Two units were ordered as standard catalog items identified as: 36-BUBS-9 Arr. I. Each unit consists of a 3 x 3 tube sheet design, that accommodates 9 bags of 3 foot length.
- 4.3 Mr. E. R. Frederick was subcontracted to provide expert technical advice on the selection of fabric filters based on triboelectric considerations. A copy of Mr. Fredericks findings is attached in Appendix A. The fabrics chosen for use in this research investigation are Ryton™ from Phillips Fiber Inc. and Tefaire™ from DuPont Corp.
- 4.4 Nine fabric filters of Tefaire™ and nine filters of Ryton™ were ordered through Flex-Kleen, Inc. Tefaire™ fabric material was donated to the research investigation by DuPont Corp.
- 4.5 A literature investigation was conducted by Mr. Jay Quimby, to identify a suitable technique that would measure the charge of the dust after passing through the corona charger. A summary of the investigation is provided in Appendix B.
- 4.6 Nomex™ fabric filters were ordered through Flex-Kleen, Inc. to serve as a surrogate filter in erection, startup, and shakedown. Nomex™ filters were ordered so as to protect the Ryton™ and Tefaire™ products from unnecessary wear and because of a projected delay in the milestone schedule because of manufacturing delays by Phillips Fibers and DuPont.

- 4.7 Tests were conducted on pre-charger current density using different configurations of ground plates and by investigating the effect of altering the point to plane distance.
- 4.8 Specifications for construction of the pre-charger ground plates and corona discharge plate configuration were determined. Pre-charger designs were completed and the system components were ordered.
- 4.9 Specifications for the pulse energization system were determined and a pulser system was ordered from Ion Physics Corporation using non-Government funds.
- 4.10 Design of the layout of the experimental system was implemented. The laboratory was rearranged and cleaned to make room for the erection of the test system. Erection through February consisted of the following tasks:
- 1) The ductwork from the gas fired boiler was disassembled to allow accommodation of the baghouse shell.
 - 2) Stainless steel ductwork from the electric heater elements to the baghouse inlet was installed. The duct is round, 8-3/8" ED and 1/8" thick.
 - 3) Ductwork from the top hat assembly to the venturi meter was completed.
 - 4) Installation of the pulse-jet assembly in the baghouse was completed.
- 4.11 Heat loss calculations for the test system were made to determine the amount and type of insulation required to maintain 300° F inside the baghouse. Fiberglass insulation at 2 inch thickness from the boiler exit to the baghouse outlet was determined to be adequate.
- 4.12 A cyclone separator will be tested to inject fly ash into the heated flue gas, downstream of the electric heater elements. A cyclone is required because the fly ash that will be used for the project does not meet the project

requirement of 95% less than 20 μ m. A theoretical basis for application of the cyclone to yield an ash that is 95% less than 20 μ m is contained in Appendix C.

4.13 Mr. Jay Quimby was assigned Project Manager responsibilities and replaces Mr. Dennis Helfritch. Mr. Helfritch remains principal investigator.

5.0 WORK TO BE PERFORMED NEXT QUARTER

5.1 Completion of installation of test system which includes:

- 1) Manifold for pulse jet assembly.
- 2) Fabrication and installation of orifice plates.
- 3) Ordering and installation of insulation.
- 4) Fabrication, installation, and shakedown of corona pre-charger.
- 5) Completion of duct connections from boiler to baghouse, including installation of heater controllers and condenser (moisture control).
- 6) Installation and shakedown of pulser system.
- 7) Fabrication and installation of instrument control panel.
- 8) Fabrication and installation of sampling devices.
- 9) Compressed air hookups for pulse jet.
- 10) Installation of electronic timers for pulsed air.

6.0 FORECAST

No problems are anticipated the project remains on schedule and within budget.

Jay M. Quimby
Project Manager

Contract DE-AC22-89PC89807

Key Personnel Labor Report

For The Period 12/1/89 - 02/28/90

<u>Person</u>	Dec. (Hours)	Jan. (Hours)	Feb. (Hours)	Total (Hours)
D. J. Helfritch	39	4	16	59
J. M. Quimby	--	--	32	32

Hours are for Task 2.

APPENDIX A

RATIONALE for FIBER/FILAMENT SELECTION in FILTER MEDIA for COLLECTING COAL-FIRED BOILER EMISSIONS [PRECHARGED (NEGATIVE) PARTICULATE MATTER]

That electrical effects play a key if not controlling role in the fabric filtration process has been clearly indicated. Without an applied electric field at the filter surface, the inherent electrical or "triboelectric" properties of the media may be utilized to develop the charges required to control the filtration process as has been shown to be required from both experimental (1) and commercial experience.

One of the more clearly demonstrated applications of this phenomenon was made by Dr. G.W. Penney. He showed that corona (negative) charged red dye particles were deposited only on the triboelectro-positive wool fibers in a wool/acrylic respiratory filter. These deposits, furthermore, built-up as aggregates on the wool fibers. (It has been mentioned that Hansen (1940) produced a vastly improved wool fiber respiratory filter by adding rosin to the fibers). In both of these and other respiratory filter modifications as well as in numerous filter media tested by the writer, filtration performance for given types of particulate matter was found to depend upon the specific triboelectric features of the fibers/filaments that made-up the filter.

Based upon these data and overall commercial as well as experimental evidence, it seems apparent that optimum filtration performance for collecting a negatively charged fly ash in the absence of an imposed electric field can be realized with strongly triboelectropositive fibers/filaments in the medium. Since glass and Ryton are among the high temperature resistant materials suitable for the application under consideration, they deserve primary consideration as the media components. But the inherent TE(+) features of these fibers may be even further enhanced by including triboelectronegative elements in the same fabric. Accordingly, as shown in the Penney tests, it is suggested that in order to increase the field strength, some test candidates be included which contain a proportion of an electronegative fiber, (Teflon) which is also capable of withstanding the high temperature of collection.

Such other fiber/filament properties as diameter, with fineness to achieve high surface area and optimum efficiency, must also be considered together with the fabric qualities of weight, permeability and finish. Although napping, to increase triboelectric charge magnitude, should not be overlooked, this kind of modification is not recommended at this stage. A moderate permeability in the range of 35 to 60 cfm/sq.ft. at 0.5 w.g. and weight at 16 to 22 oz./sq. yd., depending on fiber/filament specific gravity and type of construction, is suggested. Although moisture, especially at start-up, is a problem that can be particularly serious and may be minimized by a water repellent treatment of the fabric, this issue may also be addressed later without interfering with this stage of the evaluation.

- (1) Frederick, E.R., An Annotated Bibliography On Electrical Effects in Particulate Matter Processes, 176pp, 1987.

E.R. Frederick

E.R. Frederick

---12/4/89---

Date

RESEARCH COTTRELL/DOE EVALUATION PROGRAM
MEDIA POSSIBILITIES

- *A. 100% Fiberglass, heavy (22oz.) woven
- #B. 100% 3d Ryton yarn (multifilament if available+) - BEANE
+currently only 1200/400 Ryton made - the 300/100
maximum size for BEANE construction expected in 1990.
- oC. 95% 3d Ryton yarn (multifil. ?)/5% s.s. - BEANE (see A)
- *D. 100% 3d Ryton staple - BEANE
[300d Ryton yarn (cotton system) expected very soon]
- (*)E. 100% 3d Ryton staple - needed
- oF. 95% 3d Ryton staple/5% s.s. - BEANE (see D)
- oG. 95% 3d Ryton staple/5% s.s. - needed (see D)
- *H. 55% 3d Ryton/45% 1.5d Teflon - BEANE (see D)
- *I. 55% 3d Ryton.45% 1.5d Teflon - needed
- oJ. 52% 3d staple Ryton/43% 1.5d staple Teflon/5% s.s. - BEANE
- oK. 52% 3d staple Ryton/43% 1.5d staple Teflon/5% s.s. - needed
- oL. 52% 3d Ryton (multifil. ?)/43% 1.5d Teflon /5% s.s. - BEANE
- oM. 95% 1.5d Teflon yarn (multifil. ?)/5% s.s. - BEANE
- #N. 100% 1.5d Teflon staple - needed
- oO. 95% 1.5d Teflon staple/5% s.s. - needed
- (*)P. 35% 1.5d Teflon staple/65% C fiberglass - TEFAIRE
- oQ. 33% 1.5d Teflon staple/62% C fiberglass/5% s.s. - mod. TEFAIRE ?
- *R. 45% 1.5d Teflon yarn/55% 3d Ryton BEANE
- oS. 43% 1.5d Teflon yarn/52% 3d Ryton/5% s.s. - BEANE
- oT. 43% 1.5d Teflon staple/52% 3d Ryton/5% s.s. - needed
- *U. SYSTAGLAS = SYSTAPOR (high temp. membrane) on fiberglass
- #V. SYSTAFELT PTFE 50 = SYSTAPOR (high temp. membrane) on TEFLON

Note:

- s.s. = stainless steel staple fiber or yarn as required.
- * = preferred - (Fabrics for primary consideration).
- # = not necessarily required, dependent upon early experience.
- o = of interest mostly for charge dissipation and cleanability.

E.R. Frederick

E.R. Frederick

12/4/89
Date

APPENDIX B

Particle Charge Measurement

A literature survey was conducted to investigate the suitability of our proposed measurement method for investigating the charge to mass (C/M) ratio of fly ash following a negative corona pre-charger. An annotated bibliography by Frederick² (1987) was used as a starting point as well as the R-C library. Hochrainer² (1985) provided a summary of different measurement techniques for electric charges on aerosols. Most techniques were costly and complex for the purposes of our experimental goal, however, the concept of a faraday cage using an electrometer for charge measurement was not unlike the concept Dr. Helfritch proposed.

The nature of the particle charge measurement device, for our purpose, needs to be simple, accurate, sensitive, and provide the charge of the bulk aerosol following the pre charger unit. Charge measurement techniques used by Penney³, Pontius⁴, and White⁵ utilized an electrometer to measure the electric charge given up by particles that were deposited on a conductive substrate. White⁵ described a measurement technique that could differentiate between positive and negative charged aerosols but the technique employed costly equipment that R-C does not have. Penney³ and Pontius⁴ used filters connected to an electrometer. Each investigator's measurement approach had similarities but used different materials of construction and different data reporting practices. These differences reflected the differences in the experimental goals by Penney and Pontius.

Penney³ used a HEPA filter to collect the entire mass of aerosol within a duct. The filter was shielded by a plexiglass frame and the plexiglass was shielded by a copper housing. No mention was made if different insulating or conducting materials could be used. The HEPA filter served as a gas cleaning device, and as a charge measurement device when connected to the

electrometer. Penney reported results as coulombs/m³.

Pontius⁴ used a silver membrane filter mounted in a plastic filter holder. The plastic holder was wrapped with aluminum foil and the foil was grounded so the plastic did not accumulate static charge. Aerosol was drawn out of a duct using an isokinetic probe through the filter. The silver membrane filter was connected to an electrometer for particle measurement reported as (coulombs/gram). Following sampling the filter was weighed on an analytical balance.

A drawback to measurement of accumulated charge by an electrometer is that the aerosol charge must be unipolar. Bipolar charges will counteract each other, therefore the electrometer measurement would be biased negative if bipolar charges existed. Both Penney and Pontius used the electrometer/filter technique to measure particle charge following negative corona discharge. In this project negatively charged particles will exist so charge measurement will be valid and not influenced by positive particle charge.

The authors mentioned above did not provide detail in the proper operation of the electrometer so Mr. John Yeager, Applications Engineer, of Keithley Instruments was contacted verbally to discuss R-C's sampling approach. Mr. Yeager described that the electrometer should be in the coulomb, fast, measurement mode. In this mode the charge is integrated over time to yield the total accumulated charge for a given sampling period. Mr. Yeager also recommended that the filter be insulated from stray fields by using a metal covering, such as a coffee can. An insulator connects the filter housing and coffee can internal surface, making the device an open ended faraday cage. Although Mr. Yeager was not familiar with filter sampling of aerosols he has had a great deal of experience in measuring powder charges by utilizing a faraday cage.

A trial experiment was performed in November 1989 to test the original design of our aerosol charge measurement device. The results of the experiment prompted this literature review to understand better the techniques for particle charge measurement. The experiment was conducted to determine if a glass fiber filter,

sandwiched between stainless steel mesh screens produced a readout on the electrometer. The experimental results were difficult to interpret because the polarity of the aerosol changed and the instrument readout was unstable. As a result of the literature review the following possible causes for failure are noted below:

1. Corona quenching by excessive dust concentration may have occurred (White⁵);
2. Charge reversal in insulting ducts has been demonstrated by Penney³. Our experimental setup may have had too many similarities as compared to Penney's experimental design;
3. The electrometer was measuring current (amps) and not charge. The instrument should have been in the coulomb mode (Yeager);
4. The filter assembly was not shielded from stray field currents. The power supply to the pre-charger and the pre-charger itself were close to the filter/electrometer setup.

It is suspected that items 3 and 4 were responsible for the failure of the experiment. The pre-charger used for this project will be in a steel baghouse and the dust concentrations will be on the order of 0.2 - 1.0 grains/ft³. The conducting duct and moderate concentration level will eliminate concerns for items one and two discussed above. The sampling probe used for conveying aerosol to the filter will be stainless steel. Liu⁶ et.al., compared different probe and transfer line materials (conductive and non-conductive) for sampling charged aerosols. No problems in the R-C experimental design are anticipated once the filter assembly is shielded and charge is measured in the coulomb mode.

References:

1. Frederick, E.R., Electrical Effects in Particulate Matter Processes, Filter Media Specification-Publisher, Pittsburgh, PA, (1987)
2. Hochrainer, D., Measurement Methods for Electric Charges on Aerosols, Ann Occup. Hyg., 29(2), 241-249, (1985)
3. Penney G., Electrostatic Effects in Fabric Filtration: Volume 1. Fields, Fabrics, and Particles, EPA 600/7-78-142a, Grant #R803020, (1978)
4. Pontius, D.H., A Novel Device for Charging High Resistivity Dust, JAPCA, 28(7), 698-700, (1978)
5. White, H.J., Industrial Electrostatic Precipitation, Addison-Wesley Publishing Co., Reading, Mass., (1963)
6. Liu, B.Y.H., Pui, D.Y.H., Rubow, K.L., and Szymanski, W.W., Electrostatic Effects In Aerosol Sampling and Filtration, Ann. Occup. Hyg., 29(2), 251-269, (1985)

APPENDIX C

Estimation of Cyclone Cut Diameter

Assumptions: Standard Temperature and Pressure = 293°K
 and 1 atmosphere Number of cyclone turns = 10
 Fly Ash density = 2g/cc

Equation(1) $Q(\text{ft}^3/\text{min}) = A(\text{ft}^2) V_i(\text{ft}/\text{min})$
 Where: Q = Gas flow through cyclone
 A = Inlet area of cyclone
 V_i = Velocity of gas and duct

$$\text{Equation(2)} \quad D_{p50} = \frac{9uW_i}{2P_i N_e V_i [D_p - D_g] 60} \quad 0.5$$

Where: d_{p50} = cut size (ft)
 u_{p50} = gas viscosity (lb/ft-hr)
 W_i = cyclone inlet diameter (ft)
 N_e = Number of gas turns in cyclone
 V_i = Velocity of gas at inlet of cyclone (ft/min)
 D_p = Density of Particle (lb/ft³)
 D_g = Density of gas (lb/ft³)
 P_i = 3.1416

Known variables in equations (1) and (2)

$$A = \pi D^2/4 = [3.14 \times (1"/12")^2]/4 = 5.45 \times 10^{-3} \text{ ft}^2$$

$$V_i = (\text{Variable}) \begin{array}{l} \text{at 2 cfm} = 367 \text{ ft/min} \\ \text{at 5 cfm} = 916 \text{ ft/min} \\ \text{at 10 cfm} = 1,833 \text{ ft/min} \end{array}$$

$$u = 4.38 \times 10^{-2} \text{ lb/ft hr}$$

$$W_i = 1 \text{ inch} = 8.33 \times 10^{-2} \text{ ft}$$

$$\begin{array}{l} D_p = 124.8 \text{ lb/ft}^3 \\ D_g = 0.075 \text{ lb/ft}^3 \end{array}$$

60 = conversion of minutes to hours

$$P_i = 3.1416$$

Substituting into equation (2)

$$\text{at 10 cfm } d_{p50} = 6.17 \times 10^{-6} \text{ ft} = 1.88 \text{ um}$$

$$\text{at 5 cfm } d_{p50} = 2.66 \text{ um}$$

$$\text{at 2 cfm } d_{p50} = 4.20 \text{ um}$$

Based on Lapples' work the collection efficiency can be predicted based on the particle size ratio d_p/p_{50}

Listed below in Table 1 are the collection efficiency predictions for particle diameter as the cyclone inlet velocity is varied:

Table 1. Estimates of Collection Efficiency as an Evaluation of Particle Size of Different Flow Rates.

2 cfm Particle Diameter (um)	5cfm Particle Diameter (um)	10 cfm Particle Diameter (um)	Collection Efficiency (Percent)
2.1	1.3	0.9	20
4.2	2.7	1.9	50 d_{p50}
8.4	5.3	3.8	80
12.6	8.0	5.6	90
16.8	10.6	7.5	95

References

Wark, K. Warner, C.F., "Air Pollution, Its Origin and Control", Dun-Donnelley Publishers, New York, page 185-193, 1975.

Lapple, C.E., "Process Use Many Collection Types," Chem. Engr., 58, 145, May 1951.

END

**DATE
FILMED**

6 / 11 / 92