ET&R

Engineering and Technology

August 1985

About the Cover

The CO₂ cycle, as it is now understood, cannot account for the total amount of carbon released over the earth. What is more, the portion unaccounted for appears to be growing as a result of man's industrial activities. The earth's deep oceans are believed to be the eventual long-term repository for this "missing" carbon, and precise measurements of the exchange of CO₂ gas between the ocean's surface and the atmosphere may lead to important revisions in the prevailing concept of the CO₂ cycle. Our cover design suggests the CO₂-bearing wind eddies that we have sampled over the arctic region and Caribbean Sea. For more information on these measurements, see p. 1.

Scientific Editor

Paul S. Brown

General Editors

Richard B. Crawford
Lauren de Vore
Mary Ann Esser
Robert D. Kirvel
Eleanor M. O'Neal
Palmer T. Van Dyke

About the Journal

The Lawrence Livermore National Laboratory, operated by the University of California for the United States Department of Energy, was established in 1952 to conduct nuclear weapons and controlled thermonuclear reaction research. Today, about 60% of our resources are devoted to defense programs, which include weapons and laser fusion research. Other major areas of focus are: magnetic fusion energy; laser isotope separation; chemistry and materials science; engineering; physics; biomedical and environmental sciences; computer science and technology; applied energy technology; and work for other Federal agencies. The *Energy and Technology Review* is published monthly to report on accomplishments in unclassified programs. A companion journal, the *Research Monthly*, reports on weapons research and other classified programs. Titles from recent issues of the *Energy and Technology Review* are listed opposite the inside back cover.

Graphics Designer
John Schuster

Production Staff
Louisa Cardoza
Dianne Carlson

E&TR

Energy and Technology Review

Lawrence Livermore National Laboratory

August 1983

UCRL--52000-83-8

DEGA 000988

Brief

Fusion Experiments Analysis Facility Completed

ii

Tracking the Global Carbon Cycle

We have developed a new sensor for rapid airborne measurements of carbon dioxide exchange rates in regions as diverse as the tropics and the arctic. These measurements are helping us unravel the details of the global carbon cycle.

1

Magnetic Compressors: High-Power Pulse Sources

Continuing developments are enabling us to design extremely reliable, high-current pulse compressors capable of generating continuous, 50-ns, 250-kV pulses at increasingly higher repetition rates exceeding 1 kHz.

11

Evolution of the Magnetic Configuration for the MFTF-B

Two recent developments in the tandem-mirror concept of magnetic confinement fusion—thermal barriers and axisymmetric mirror cells—have greatly improved the outlook for future tandem-mirror reactors. These advances will be realized in our Mirror Fusion Test Facility (MFTF-B), now under construction.

20

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

NOTICE

PORTIONS OF THIS REPORT ARE REPRODUCIBLE.

It has been reproduced from the best available copy to permit the broadest possible availability.

UCRL-52000-83-8
Distribution Category UC-2
August 1983

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Fusion Experiments Analysis Facility Completed

In the Laboratory's laser fusion program, intense laser beams are focused on a microscopic target filled with deuterium-tritium gas under high pressure. The incident laser radiation heats and implodes a target to compress and heat D-T fuel to conditions necessary for thermonuclear burn. The collection and timely analysis of experimental data are vital for evaluating the performance of individual targets and for designing future experiments. With the completion of our new \$1.5 million Fusion Experiments Analysis Facility (FEAF), we can examine data minutes after any target-irradiation experiment.

FEAF is an integrated computer system designed specifically to centralize the collection, analysis, and archiving of data obtained with the Laboratory's Novette and Nova laser facilities. The physical layout of FEAF is organized into three functional areas: a computer room, a user work area, and a document vault. The computer room houses the main computer hardware and all system storage devices. The work area is adjacent to the computer room and consists of a reception area, user work stations, and a hard-copy output area. A variety of devices, including computer terminals with screens, color monitors, an image

digitizer, and a digitizing tablet, are available in the work area.

With respect to computer hardware, the three major subsystems of FEAF (see Fig. 1) are the host computer, the image digitizer, and the one-way data communications link from Novette (and eventually from Nova). The facility is designed to allow work with both classified and unclassified information 24 hours a day. The host computer (VAX 11/780) supports time-shared, batch, and real-time operations; time-share users interact with the system from CRT terminals located at 10 work stations and in 22 staff offices.

It is essential that users who handle target-shot data be provided with high-resolution graphics. Therefore, we have installed computer terminals upgraded with 480- by 640-element hardware as our standard monochrome terminals. Color graphics are displayed on three 512- by 640-element color monitors that are attached to two display processors.

A variety of input/output devices facilitates transfer of information between FEAF and other computer systems. Our current input/output devices include an 8-in., double-density floppy-disk drive, a 10-Mbyte RL02 disk drive, and two 9-track magnetic tape drives. Devices for direct data transfer between FEAF and other machines include the Wang Office Information System and the one-way communications link from Novette. The latter link is needed because the FEAF VAX is a secure system containing classified information, while the Novette VAX contains only unclassified data. The one-way link enforces unidirectional data transfer regardless of the applications software that resides at either end of the system. For this purpose, the LSI-11 computer is housed in the FEAF computer vault and runs a program stored in read-only memory. The LSI-11 computer acts as a third-party message arbiter between the two VAX computers via optical-fiber cables and a communications protocol named NOVALINK. We developed file-transport software that can transfer sequential, direct-access, and indexed files across the one-way link.

Fig. 1

Basic architecture of the FEAF computer hardware. The heart of the system is a VAX 11/780 computer with 5.5 Mbyte of memory, 700 Mbyte of on-line storage, a variety of output devices, and over 30 remote user terminals. A one-way communication link enables direct data transfer from the unclassified Novette laser facility computer to the classified FEAF computer. Digitization of data by our image digitizer is controlled by a PDP 11/34 computer. After digitized data are collected, they are transferred to the VAX for final image analysis.

Additional security measures are based upon the Laboratory's security plan for automated data processing. After regular working hours, unattended terminals are disconnected from the computer by means of specially designed hardware disconnection units. A system operator can connect or disconnect all terminals by entering a preset number into a local keypad. Momentary contact switches permit individual users who access the computer vault after regular hours to connect and disconnect individual terminals. When a user requests output, a random number is returned to the terminal screen. The assigned number must then be entered into a keypad attached to a printer, thus ensuring that the user is present when output is generated.

Two recently published reference guides are available for Laboratory personnel who work on our system. The *FEAF User's Guide* provides an overview of the computer system; the *FEAF Operating Procedures* manual explains policies, procedures, and user responsibilities. A variety of on-line libraries and inventories provides more detailed documentation of available hardware and software.

Interaction between computer and user is controlled by an operating system called the Virtual Address Extension/Virtual Memory System, or simply VAX/VMS. The VAX/VMS supports batch and multiuser interactive operations, and it contains an excellent set of utility programs that facilitate program development and file management. We use a command line editor for editing the Digital Command Language and maintain several program development languages, including Fortran, Pascal, C, and Basic.

We have made available two software packages for doing graphics-related analysis of data. DISSPLA consists of graphics subroutines that can be called from Fortran, Pascal, or C and presents a high-level language interface to FEAF graphics hardware. TELLAGRAF is a conversational graphics system that understands English-like commands and features

automatic scaling, layout, and annotation.

For scientific programming, we maintain the RT-11 Scientific Subroutine package because it contains a cross section of commonly used mathematical and statistical routines. We use the International Mathematical and Statistical Library, written in Fortran, for both single- and double-precision arithmetic. Finally, our data management strategies are based on the powerful ORACLE data base management system. DISSPLA, TELLAGRAF, and ORACLE are commercially available.

Fig. 2

Computer-generated image of an imploding laser-fusion target, a 140- μ m-diam microsphere filled with deuterium-tritium. The original photograph, taken with an x-ray microscope, was scanned with an image digitizer and then processed with an applications code to yield a colored image (red indicates regions of maximum x-ray emission, and blue indicates the absence of x-ray emission). The three horizontal lines intersecting the target represent the limits and the centroid of the intensity lineout (the topmost curve) through the image. This top curve shows relative intensity of x-ray emission. Images like this one can be observed on-line and then permanently recorded on 35-mm film with our color hard-copy unit. With FEAF, we can digitize film in about ten minutes and then produce a colored image from the digitized data in only a few minutes. This process formerly took up to two weeks.

Raw data acquired during a typical target experiment usually include images recorded on film from instruments such as spectrographs, streak cameras, or x-ray microscopes. A typical FEAF analysis code must access the raw data and transform the information, by means of the appropriate algorithms, into meaningful results. The user interacts with an applications code to manipulate and display those results. Figure 2 shows a sample colored image after it has been processed with an applications code from the FEAF computer system.

For further information contact Richard A. Lerche (415) 422-5364. □

Key Words: computer facility; Fusion Experiments Analysis Facility (FEAF); inertial confinement fusion (ICF); Nova; Novette.

Tracking the Global

We have developed a new sensor for rapid airborne measurements of carbon dioxide exchange rates over large areas throughout the world. These measurements are providing new data on the sources and sinks in the global carbon cycle.

For further information contact
Gail E. Bingham or Joseph H. Shinn
(415) 422-6806.

Although the broad outlines of the carbon cycle are well known, there is still much to be learned about the process. The value of this knowledge becomes apparent when one considers that researchers have observed a rise, over the past century,¹ in atmospheric carbon dioxide (CO_2) that could in time lead to significant changes in climate.² Since chimneys and exhaust pipes continue to vent their wastes in ever larger volumes, understanding the details of the carbon cycle may be even more important in the future.

It would be useful to be able to make meaningful calculations of the global carbon cycle. To do this, we need to measure and understand the exchange of CO_2 between the atmosphere and the ocean, since the deep ocean is the only sink capable of continued assimilation of the large amount of carbon emitted into the air each year.³

To make such measurements, we have developed a fast-response CO_2 sensor designed for use on long-range weather research aircraft. Our sensor makes it possible to take direct measurements of CO_2 exchange over large areas in remote places such as the arctic and equatorial oceans, which are of particular importance in global CO_2 calculations.

Although much of the information we have so far obtained must be considered preliminary, the performance of the sensor to date is impressive. The data obtained clearly demonstrate the ability of the system to measure all of the aerial parameters related to CO_2 exchange and also indicate that, under certain conditions, the absorption of CO_2 by the ocean can be much more rapid than had been thought possible.

Until now, only indirect methods have been used to infer carbon exchange coefficients for the world's oceans. These methods include laboratory experiments,⁴ measurements of the static distribution of bomb-created carbon-14,⁵ analogies based on measurements of radon escape,^{6,7} and measurements of CO_2 transfer made in small chambers (usually of less than 1 m^2) floating on the surface of the ocean.⁸⁻⁹ With our new sensor, we can provide direct measurements, which we believe are much more reliable.

Most models of CO_2 absorption by the global ocean use an exchange coefficient E (expressed as grams of radon transferred per square metre per second) calculated from measurements of the rate at which radon gas escapes from the ocean's surface. (Radon is a convenient standard because it is

Carbon Cycle

always present and because, being radioactive, it is readily detectable.) The rate at which radon escapes is measured by determining the profile of dissolved radon gas in the upper few hundred meters of the ocean, a difficult and expensive procedure. The CO_2 fluxes estimated by this method tend to be small and have failed to show the correlation with environmental factors, such as wind speed, that theory predicts.

Since most calculations of the global carbon cycle depend on these estimates, it is important to validate them with direct measurements, especially for areas significant to global CO_2 calculations. One such region lies between Norway and Greenland, where the cold surface water can become dense enough to sink directly to the ocean bottom, carrying its burden of CO_2 with it and rapidly exposing fresh sea water capable of absorbing more CO_2 . Another is the equatorial belt where elimination by the tropical forests and upwelling in the equatorial oceans are believed to return a large amount of absorbed CO_2 to the atmosphere. Better understanding of the relationship between environmental parameters and CO_2 fluxes in these regions should make our predictions of future global CO_2 trends much more reliable.

Measuring CO_2 Exchange at a Remote Surface

The two ways of measuring the exchange of gases at a remote surface are called the aerodynamic (gradient) method and the eddy-covariance method. Aerodynamic methods (which are based on mean vertical concentration profiles) have been applied to measure fluxes in the ocean, but they are impractical for global estimates^{10,11} because they need a stable, fixed platform, and can sample only a limited area at a time.

The eddy-covariance method has several advantages and requires fewer assumptions. It has already been used very successfully for measuring fluxes of heat and water vapor. The open-cell sensors we have recently developed (for use on towers and long-range, high-performance aircraft) are sufficiently stable, reliable, fast, and accurate to allow regular, long-term eddy-covariance studies of CO_2 fluxes.

Basic Mechanisms of Turbulent Flux

The transfer of matter and energy between a surface and the atmosphere is driven by the temperature and concentration differences between them. For a thin layer at the surface (less than about 0.5 mm), transfer is by molecular diffusion. Above that, however, convection becomes the dominant transfer mechanism. In the boundary layer close to the earth's surface (typically from 10 to 150 m in depth), mixing and the exchange of gases is essentially by turbulent transfer. Since this layer normally contains no sources or sinks, fluxes through it are approximately constant with height.

The air in the boundary layer (which forms continually and which carries the signature of the surface below) flows in many coexisting eddies of various sizes. Figure 1a is a schematic drawing of how some of these eddies might look if they were visible (in reality, the eddy pattern would be much more complex than the drawing shows). The loops of circulating air that form the eddies "roll" along the surface of the land or water with a centroid velocity equivalent to the mean wind speed. The descending portion of the eddy brings with it air from above, and the ascending air, having interacted with the surface, brings up surface air.

This eddy pattern can be demonstrated by means of a sensor restricted to detect only vertical air motion. Such a sensor, moving horizontally through this system or stationed so the eddy system blows past it, will give readings alternately influenced by the surface and by the upper air. As Fig. 1b illustrates, the sensor will register the vertical component of air movement most fully if it passes through the eddy's center.

Figure 2, a one-minute section of actual data collected over the ocean, clearly shows these oscillations in readings for vertical wind velocity, water vapor density, and CO_2 density. By correlating fluctuations of the readings for CO_2 , water vapor, or temperature with the corresponding vertical wind velocity, we can determine the fluxes of CO_2 , water vapor, and heat through the horizontal plane of the sensor. The faster the instruments respond to the samples, the more completely we can describe the flow field.

The time average of all of the instantaneous products measured during the transect is the average flux for the region. Unlike the aerodynamic method of analysis, which requires accurate, absolute measurements to determine the difference in long-term average concentration with height above the surface, eddy-covariance analysis requires only relative measurements. It does, however, require a fast-response sensor that can accurately determine the relative differences between the ascending and descending flows.

The height at which we make our measurements determines the area included in the flux determination. The depth of a given boundary layer is determined by the size of the eddies that constitute it. Therefore, the higher we fly (so as to pass through the centers of the larger eddies), the deeper the boundary layer for which we obtain readings. A boundary layer is in equilibrium with an extent of upwind surface about 100 to 500 times the

Fig. 1

A simplified view of the turbulent exchange process in the mixing layer between the upper atmosphere and the earth's surface. (a) The boundary layer consists of numerous circular eddies of various sizes; small eddies may exist within larger ones. (b) As a sensor restricted to detect only the vertical component of air motion passes through an eddy, it will be affected alternately by descending upper air and ascending surface air. Simultaneous measurements of composition and physical properties, together with the vertical components of the wind, enable us to compare surface and upper-air conditions and to infer exchange rates.

Fig. 2

A short segment of sensor data (shown as deviations from the mean) for the vertical wind velocity (a), water vapor density (b), and CO_2 density (c) as detected by our airborne eddy-covariance sensor above the ocean. The cyclical nature of the boundary layer shows clearly. (The shaded vertical bands represent alternate upward and downward air movement.) Both water vapor and CO_2 density increase with each upward vertical wind gust (combined data in (d) and (e), respectively), indicating that the surface is a source for both.

layer's depth. As a result (within the turbulent boundary layer), increasing the sampling height increases the area averaged by the measurement.

This effect of sensor height on sampled region is explained in Fig. 3. The height at which aircraft measurements are taken, combined with the movement of the aircraft, allows an airborne system to survey a large area in a single sample run. For example, an 8-min record taken crosswind at an altitude of 33 m determines the flux of an area about 53 km long and 4 to 16 km wide, or about 500 km^2 .

Requirements for Eddy-Covariance Sensors

A sensor for measuring eddy covariance must be stable, sensitive, and (in comparison to previous sensors) fast-responding. These requirements are even more stringent when the sensor is

to be airborne instead of mounted on a tower. Sensitivity becomes crucial because, as the height above the surface increases, dilution makes the concentration differences between rising and falling air currents hard to detect. (The minimum safe operating height for an aircraft is about 30 m.) Also, the sensor's response time must be faster than that of a stationary sensor since an aircraft flies through the eddy system much more quickly than the wind would blow past a tower.

To meet these strict requirements, we built a radiometer that constantly compares infrared absorption at two wavebands, one (centered at 4.27 μm) straddling a strong CO_2 absorption band and one (at 3.85 μm) for reference. This choice of wavelengths almost perfectly balances the major atmospheric interferent normally encountered in CO_2 measurements, i.e.,

Fig. 3

The effect of height on sensor performance requirements and on the area that can be monitored from a single location. The higher the sensor (within the mixing layer), the larger the eddies measured and the wider the area of influence included in the data. An eddy is in equilibrium with an extent of upwind surface about 100 to 500 times the eddy's height. (The upwind direction is to the left in the illustration.) Larger eddies allow the sensor to be slower, but concentration differences decrease with height, requiring a more sensitive unit to achieve flux measurements of the same accuracy.

water vapor, because water vapor affects both bands equally.

Figure 4 is a diagram of our CO₂ sensor. A set of curved mirrors and lenses permits the diverging beam of infrared light from a constant-temperature heat source (800°C) to bounce back and forth as many as 12 times, providing up to 1.5 m of absorption path within the 12.5-cm-high cell,¹² although for CO₂ flux measurements we use only four traversals. After leaving the sample cell, the beam passes through a chopper/filter wheel and a lens that focuses it on the detector, which is chilled to -35°C.

The heat source is a miniature cavity resonator surrounded by a low-density ceramic insulator and further insulated by a quartz-glass, inverted Dewar flask. The detector is a photosensitive, lead selenide, 1-mm² resistor modified so its field of view is limited to that of the entrance lens. The source and the detector, even though they are less than 50 mm apart, must both be held at

rigidly controlled but very different temperatures. We provided a heat-exchange system that uses flowing water at ambient temperature to isolate one from the other and to prevent hot spots that could distort the internal optical bench, shift the filter transmission, and cause electronic drift.

CO₂ Sensor Calibration

One of the major problems in this development was the difficulty of controlling temperature, pressure, and CO₂ in a calibration chamber more accurately than the sensor could measure. We finally settled on two methods. The first, a type of calibration usually done in a laboratory, uses dry calibration gases of known CO₂ concentrations that can be applied under a wide range of static ambient conditions; it is useful for determining probable sensor response under most operational conditions. The second is an *in situ* calibration for use in flight.

For the first type of calibration, we slip a cylindrical hood over the sensor and fill it with dry air having a known CO₂ concentration. When conditions have stabilized, we measure the temperature and pressure in the

calibration hood so that we can calculate CO₂ density and determine its relationship to sensor output. (In calculating the CO₂ density, we correct for the effects of water vapor, whose density is measured independently.) Although the sensor could be pulled inside the aircraft for the first sort of calibration, at any time, this would use up valuable flight time and permit differences in temperature, pressure, and flow to change sensor response. The *in situ* calibration scheme avoids these complications.

For the *in situ* calibration, we carry a second infrared gas analyzer that can be calibrated by means of standard gases without interrupting the flux measurements. During the first portion of the flux measurement run, the internal analyzer determines the CO₂ concentration of air drawn from outside the aircraft. During the last portion of the run, the analyzer is switched from the external air sample to standard gases having known CO₂ concentration. This gives us a way to determine,

regularly and reliably to better than ± 0.1 ppm, the mean CO₂ concentration (typically 350 ppm) of the air through which we are flying. By simultaneously measuring the pressure, temperature, and water vapor of the air around the aircraft with other sensors, we can determine the mean CO₂ density at that altitude. Since changing pressure alters the *in situ* CO₂ density, a few minutes of level flight at two or three different altitudes provides an accurate determination of the sensor's *in situ* response.

The Aircraft and Its Research Instruments

Our CO₂ sensor has now flown in several missions as a component of the gust-probe system on two highly versatile and efficient, weather-research aircraft owned by the National Oceanic and Atmospheric Administration (NOAA). These planes are capable of

Fig. 4

The sensor for measuring CO₂ flux correlates the concentration of CO₂, temperature, pressure, and humidity with eddies moving upward and downward over a land or sea surface. The undisturbed airstream moves through the sensor's open, multipath absorption cell.

Fig. 5

Data-gathering instruments on the weather-research aircraft. (a) The gust probe, which extends in front of the plane to avoid artificial turbulence, measures air temperature, water vapor, and fine-scale turbulence. The small vane on the bottom of the probe senses ascending and descending air currents. (b) Our CO_2 sensor, mounted on its own pylon, allows air to flow through it. The signals from the gust probe and the CO_2 sensor are combined, along with data on water vapor and temperature, to calculate CO_2 flux. (c) View of the whole aircraft, showing location of the instruments.

meeting the most stringent experimental and operational requirements under severe storm and arctic weather conditions. The aircraft have a range of about 5600 km (3000 nautical miles) and can carry up to 18 crew members and scientists.

The research instruments on these aircraft include Doppler and imaging radars, automatic cameras, and radiation, aerosol, and cloud-physics probes. An inertial navigation system provides data on aircraft motion. Information from all aircraft sensors is collected at 40 samples per second by a redundant data-acquisition system.

During normal operations the backup data-acquisition computer provides real-time calculations and graphics information on dual TV screens at each crewman's station. Processed data are stored on a disk in a history file that can accommodate up to 18 hours of recording, allowing investigators to compare observations from previous flight patterns and even previous days with current information. Screen plots, meteorological data, and mean data are available, in printed form, at the end of the flight.

The gust sensors used in eddy-covariance measurements of flux are

located on a vibration-damped aluminum probe extending 3 m in front of the aircraft (Fig. 5a), which places them out of the turbulence caused by the plane itself. Strain gauges attached to small vanes near the tip of the probe measure vertical and horizontal turbulence. Dual, matched, fast-response thermistor bridges measure temperatures, and a microwave refractometer mounted just behind the vane system measures high-frequency humidity fluctuations. Gust-probe and inertial-platform data for flux calculations are digitized at 80 Hz and recorded on magnetic tape for post-flight analysis.

Because our CO₂ sensor is too heavy for the gust-probe boom, it has its own pylon near the front of the aircraft (Fig. 5b) that places it outside the aircraft boundary layer in essentially undisturbed air. In addition to the cavity that surrounds the CO₂ sensor, the pylon contains a fast-response temperature sensor and a high-frequency, static-pressure probe. This information, also recorded at 80 Hz, is used to correct for cavity-induced density variations.

At the end of the experiments, we analyze the recorded weather and mean CO₂ data to determine final CO₂ sensor calibrations and mean CO₂ concentration profiles. NOAA's Environmental Research Laboratory in Boulder, Colorado, analyzes the data collected by the high-frequency gust probe to develop the turbulence information. Both sets of data are then combined to determine the CO₂ flux and other atmospheric parameters. Over the arctic ice pack, the CO₂ flux-measuring system has demonstrated the capability of measuring CO₂ fluxes of less than 1.5×10^{-7} g/m²·s. A preliminary error analysis indicates that the system should be able to measure CO₂ fluxes as small as 5×10^{-8} g/m²·s.

Experimental Results

We have tested our CO₂-flux-measuring system during NOAA-sponsored weather-research missions over arctic and equatorial oceans. The

At the end of the experiments, we analyze the recorded weather and mean CO₂ data to determine final CO₂ sensor calibrations and mean CO₂ concentration profiles.

Fig. 6

The location and sea-surface state for each of a series of flux measurements made over a large area of open water (polynya) south of St. Lawrence Island in the Bering Sea, over the ice pack south of the polynya, and over the ice edge and open water of the Bering Sea, as well as several areas of intermediate ice cover. Mean air temperature for the day was -18°C , with a strong northerly wind varying between 15 and 20 m/s.

initial results, preliminary though they may be, were quite startling. The flux of CO_2 from equatorial waters was much larger than we expected, and the values for downward CO_2 flux observed over open arctic water near the ice edge were many times those predicted by the earlier, radon-based methods. If these data are confirmed by future studies, new mechanisms for gas exchange between the ocean and atmosphere must be developed to explain these high fluxes.

Arctic Measurements

Figure 6 shows the track of our measurement runs over the ice and

water in the vicinity of St. Lawrence Island in the Bering Sea. Strong winds from the north drag the ice pack away from the island shore, creating a large polynya (an area of open water). The temperature difference between the water in the polynya and the frigid air often exceeds 30°C .

Where the winter winds sweep over the polynya and the ice edge, the fluxes of water vapor and sensible heat are gigantic. The rapid cooling and freezing set up a natural convective flow in the water that mixes well below the surface and creates a slushy scum of "grease ice" on the surface.

This area is also of great interest for CO_2 exchange studies because of the wide variety of novel conditions it presents. Cold water absorbs much more CO_2 than warm water, and the rapid turnover brought about by the convective flow in the polynya should induce a localized high rate of CO_2 absorption. Furthermore, although the ice sheet greatly restricts the exchange of heat and water vapor from the ocean, the annual ice zone makes an imperfect barrier. Microchannels in the ice make it rather permeable to air exchange, and the sheet is filled with leads and fissures.

The region between St. Lawrence Island and the ice edge near St. Matthew Island presents a continually varying ice cover, ranging from solid ice to open water. The region is quite small, considering the range and speed of the aircraft, making it possible to collect data over the whole area in a short time. Consequently, we can compare gas-exchange rates among regions with different ice cover, but with the same atmospheric variables. Ice ridges make the surface aerodynamically rough, greatly increasing the wind-drag coefficient and turbulent heat and gas transfer from the surface.

Figure 7 shows the measured heat, water vapor, and CO_2 fluxes from regions of different ice cover. The fluxes are plotted against ΔT , the difference between the temperatures of the air and the sea surface. (The average sea surface temperature was

calculated from measurements made with a downward-looking infrared radiometer.) The winds during our measurements approached 18 m/s with an average temperature of -18°C , which is about the same as the maximum ΔT , since the open-water temperature is near 0°C . The solid ice sheet was considerably cooler, resulting in a ΔT near -8°C . Regions of mixed ice and water had intermediate mean ΔT values.

The measurements were remarkably consistent and had relatively small scatter for points taken over widely differing ice covers. Over open water, the sensible heat and water-vapor fluxes are large, but not unreasonable. The downward CO_2 flux, on the other hand, is enormous.

Equatorial Measurements

In an extension of this program, and in cooperation with researchers from NOAA, the Department of Energy, and the National Science Foundation, we made the first direct comparisons between the eddy-covariance flux measurements and the radon-based flux estimates. We compared data collected in the Caribbean and the equatorial Atlantic regions. At the same time we were making our data-gathering flights, researchers on an NSF-funded research ship measured radon profiles and differences in CO_2 concentrations across the interface of ocean and atmosphere. These simultaneous measurements provided data on all of the parameters needed for theoretical calculations of the CO_2 flux.

The data from this comparison are now being analyzed. A preliminary estimate has been made, from data collected on only one day of this experiment, of the vertical flux distributions for heat, water vapor, and CO_2 . These data, taken directly east of Barbados, show that the depth of the mixing layer (region of constant CO_2 flux) is more than 200 m.

The heat and water-vapor profiles show the same slope with height as other researchers have observed in tropical marine boundary layers. The

discrepancies between our eddy-covariance measurements and the radon-predicted values for CO_2 flux at the surface in the Atlantic are similar to those observed by previous investigators¹³ using tower-based systems but are not as large as those we observed in the arctic (cf. Fig. 7). Although these data suggest various interesting concepts, additional measurements and comparisons will be required to verify our initial observations.

Fig. 7

Flux data collected at 58 m during the arctic flight shown in Fig. 6, plotted against the mean temperature difference between the air and the surface, which provides a good indication of the amount of exposed water immediately below the aircraft. The data show remarkably small scatter about the mean. Large amounts of heat and water vapor were being transferred to the cold dry air from the water, and the average amount of CO_2 being absorbed over the polynya was many times that predicted by radon-based estimates and about what one would expect over a forest.

Conclusion

These early data form the basis of a continuing research effort to determine the adequacy of existing gas-exchange theory in describing that portion of the global carbon cycle associated with the oceans. The validation and explanation of these new results, along with the development of more accurate exchange coefficients, will greatly increase our ability to predict future changes in the mean global CO_2 concentration. The resulting confidence in our predictive capability should help in making the hard choices among competing energy sources that will face national leaders in the years to come.

Key Words: airborne atmospheric measurement; carbon cycle; carbon dioxide (CO_2); eddy covariance; infrared absorption; radon concentration profile.

Notes and References

1. R. B. Bacastow and C. D. Keeling, "Atmospheric Carbon Dioxide Concentration and the Observed Airborne Fraction," in *Carbon Cycle Modelling*, SCOPE 16, B. Bolin, Ed. (John Wiley and Sons, NY, 1981), pp. 103-112.
2. *Carbon Dioxide and Climate: A Scientific Assessment*, Climate Research Board, National Academy of Sciences, Washington, DC (1979). Also see *Carbon Dioxide and Climate: A Second Assessment*, Climate Research Board, NAS, Washington, DC (1982).
3. W. S. Broecker, T. Takahashi, H. J. Simpson, and T. H. Peng, "Fate of Fossil Fuel Carbon Dioxide and the Global Carbon Budget," *Science* **206** (4417), 409 (1979).
4. P. S. Liss, "Processes of Gas Exchange Across an Air-Water Interface," *Deep-Sea Res.* **20**, 221-238 (1973).
5. T. H. Peng, W. S. Broecker, G. G. Mathieu, Y. H. Li, and A. E. Bainbridge, "Radon Evasion Rates in the Atlantic and Pacific Oceans as Determined During the Geosecs Program," *J. Geophys. Res.* **84** (C5), 2471 (1979).
6. W. S. Broecker, and T. H. Peng, "Gas Exchange Rates between Air and Sea," *Tellus* **26**, 21 (1974).
7. T. H. Peng, T. Takahashi, and W. S. Broecker, "Surface Radon Measurements in the North Pacific Ocean Station Papa," *J. Geophys. Res.* **79** (12), 1772 (1974).
8. Y. Suglura, E. R. Ibert, and D. W. Hood, "Mass Transfer of Carbon Dioxide Across Sea Surfaces," *J. Mar. Res.* **21**, 11 (1963).
9. D. W. Hood and J. J. Kelley, "Evaluation of Mean Vertical Transports in an Upwelling System by CO_2 Measurements," *Mar. Sci. Comm.* **2**, 387 (1976).
10. S. Sethuraman, "Carbon Dioxide Fluxes over the Atlantic Ocean Estimated from Measurements at Tiana Beach, Long Island, New York," *Boundary-Layer Meteorol.* **20** (1), 19 (1981).
11. B. T. Hargrave and G. A. Phillips, "Annual *In Situ* Carbon-Dioxide and Oxygen Flux Across a Subtidal Marine Sediment," *Estuar. Coast. Shelf Sci.* **12** (6), 725 (1981).
12. G. E. Bingham, C. H. Gillespie, and J. H. McQuaid, "A Miniature, Battery-Powered, Pyroelectric Detector-Based Differential Infrared Absorption Sensor for Ambient Concentrations of Carbon Dioxide," *Ferroelectrics* **34**, 15 (1981).
13. M. L. Wesely, D. R. Cook, R. L. Hart, and R. M. Williams, "Air-Sea Exchange of CO_2 and Evidence for Enhanced Upward Fluxes," *J. Geophys. Res.* **87** (C11), 8827 (1982).

Magnetic Compressors: High-Power Pulse Sources

We are anticipating future needs beyond the capabilities of the spark-gap switches we developed for the Advanced Test Accelerator (ATA). We are continuing our efforts on magnetic pulse compressors that use nonlinear magnetic components and have designed reliable, high-current pulse compressors capable of generating continuous, 50-ns, 250-kV pulses at repetition rates exceeding 1 kHz. The use of new circuit designs and metallic glasses in these compressors will help us produce pulses with even higher repetition rates.

The Laboratory's Advanced Test Accelerator (ATA),¹ funded by the Defense Advanced Research Projects Agency, is a 50-MeV, 10-kA induction linear accelerator. The pulse of its output electron beam lasts up to 50 ns and can be repeated once a millisecond for up to ten pulses. This ten-pulse burst can be repeated every two seconds, giving the machine an average repetition rate of five pulses per second.

This performance, which makes the ATA unique among pulse power machines, came as the result of research on a novel, coaxial, gas-blown spark gap. The ATA contains modular, 250-kV induction-accelerator cells, each driven by a single pulse power unit. Each unit consists of a resonant transformer (1:10 step-up), a water-filled Blumlein pulse-forming line (PFL) for energy storage, and the

forementioned spark gap to discharge the PFL into the accelerator cell.

The initial commutation in the chain is performed by six fast-recovery, glass-envelope thyratrons, four operating in the forward and two in the reverse direction. These tubular thyratrons, specially made for high-peak-power, low-duty-factor applications, transfer energy held in intermediate storage through the 1:10 transformer and into the PFL. The transfer is completed in 20 μ s, and the tubes recover their ability to hold voltage in another 20 μ s.

A hiatus of 1 ms or more between pulses is necessary so the discharge products can be blown out of the spark gap. In theory, higher repetition rates could have been achieved by increasing the velocity of the gas that blows them out. Any significant increase is impractical, however, since the power required from the blower scales as the

For further information contact
Daniel L. Bix (415) 422-7091.

Fig. 1

A comparison of the pulse power requirements of various accelerators. Radio-frequency voltage and power at various locations in the pulse-forming network (a) in the Stanford Linear Accelerator, (b) in the ATA induction linear accelerator, and (c) in a comparable nonlinear magnetic drive.

cube of the repetition rate, and it is already at 11.2 kW per gap for 1-kHz operation.

Figure 1, which schematically compares the pulse power requirements for the ATA and the Stanford Linear Accelerator (SLAC), suggests part of the reason why we needed to use spark gaps in the ATA. Although the pulse

energy supplied to a SLAC radio-frequency accelerator section is essentially the same as that supplied to an ATA induction cell, the power level to the ATA is about a hundred times larger because the pulse is so much shorter.

The energy compression supplied by the spark gap (switch S_2 in Fig. 1b) supplies this power gain. A spark-gap switch consists of a coaxial anode and cathode with a trigger electrode between. The switch, which is filled with gas at high pressure, closes on command when the trigger electrode is pulsed, causing a breakdown arc within the gas, which then conducts current. The combination of a 250-kV operating voltage and a requirement for a current rise of 1 TA/ μ s (or 10^{18} A/s) forced us

to use the crude but effective high-pressure spark-gap technology. However, such technology is not adequate to achieve high repetition rates for future applications. It appears to be a rule of nature that the designed repetition rate will never be high enough; experimenters will always find reasons for wanting to go higher.

Research into alternative switching schemes began almost before the first spark gaps went into use. At first, we tried to develop a high-power version of the thyatron (switch S_1 in Fig. 1b). A thyatron is a triode (similar in design to a vacuum tube) filled with deuterium at low pressure. It operates as a closing switch, ionizing the deuterium, when the grid (one of the three electrodes) is pulsed. Such a

low-pressure gas switch certainly seemed to embody the technology most likely to meet our requirements.

This work provided us with invaluable insights into the physics of low-pressure gas switches. It also demonstrated that such a switch, while possible in concept, is impractical. Because of its size and expense, it would have been only a slight improvement over several hundred conventional thyatrons operating in a series-parallel configuration.

This realization would have come as a disappointment if we had not, on the way to developing the super thyatron, discovered something much better. We had been experimenting with saturable inductors to ease the rise-time requirements on our low-pressure switches (an idea gleaned from reports dating back to the 1950s), and they turned out to be far more effective than we had expected. We found that we could reduce the voltage and rise-time requirements enough to eliminate the need for a high-power switch. This idea, schematically depicted in Fig. 1c, made it possible to stay with conventional thyatrons.

Magnetic Pulse Compression

The basic circuit for magnetic pulse compression is essentially the same as originally conceived in the 1950s. The fundamental principle involved is to use the large changes in permeability exhibited by saturating ferri-(ferro-)magnetic materials to produce large changes in impedance. Figure 2a shows the permeability changes in a representative saturable magnetic material, and Fig. 2b illustrates the standard technique for capitalizing on this behavior. First, a repetitive power source (using existing technology) generates the initial pulse. As this pulse propagates through the network, it goes through several states of compression until it achieves the desired output shape.

By using multiple stages as shown, it is possible to achieve a much larger effective change in impedance than can be obtained from a single stage. In fact,

the effective change in impedance is limited only by the physical layout and materials properties. Figure 2c illustrates the results of the compression process.

The operation of this circuit can be described as follows. Capacitor C_1 charges through inductance L_0 until inductance L_1 saturates, becoming much less than L_0 . Once this happens, C_2 will begin to charge from C_1 through $L_{1\text{ sat}}$, but since $L_{1\text{ sat}}$ is much less than L_0 , C_2 charges more rapidly than C_1 did. This process continues through the successive stages until C_n discharges into the load through $L_{n\text{ sat}}$.

Fig. 2

Diagrams outlining the operation of magnetic pulse compression. (a) The hysteresis ($B-H$) loop of a typical saturable magnetic material. (b) Simplified schematic of a magnetic pulse compressor. The elements marked L_1 , L_2 , and L_n are nonlinear inductors. (c) Typical voltage waveforms associated with a magnetic pulse compressor.

To make this process efficient, we design each of these successive stages so that saturation occurs at the peak of the voltage waveform. Segment 1 to 2 in the hysteresis loop of Fig. 2a is the active or high-permeability region during which the inductor impedes current flow; the leveling off of the curve at point 2, reached at the peak of the voltage waveform, indicates core saturation when the inductor achieves a low impedance. During segment 2 to 4, the core is reset to its original state, ready for the next cycle.

The research and development effort that followed this discovery produced several primitive pulse power units based on magnetic compression. Even these early efforts proved to be such an improvement over the spark-gap switches that a few of them were installed in critical areas of the ETA and ATA, and all are still in operation.

Because pulse compressors are passive devices, their operation requires an initial pulse, which we usually obtain by discharging an intermediate storage capacitor through one or more thyratrons. Figure 3 outlines various methods of achieving high repetition rates with this general arrangement. Most of our pulsers operate in the simple command resonant charge mode, and the time required to recharge the intermediate storage capacitor combined with thyatron recovery times limits operation to about 15 kHz.

Aside from creating the ability to operate at increased repetition rates, the installation of magnetic pulse compressors appeared warranted on the basis of reliability and low maintenance. The benefits to the experimental program were also considerable.

The ATA Upgrade Prototype

Since October 1980, when we first began to work with magnetic switches, we have completed installation and final testing of a prototype magnetic switch package to replace the spark gaps in the ATA power units. The challenge was not to prove that a

magnetic switch would do the job but rather to produce a unit that would fit the existing space, use as much of the existing equipment as possible, and be as inexpensive and reliable as possible.

The problem was further complicated by a desire for a peak repetition rate exceeding several kilohertz and an average repetition rate of at least 100 Hz. We also wanted the ability to operate at 1 kHz for up to one minute in every ten to enable us to use the ATA for high-power, free-electron-laser experiments.

Figure 4 compares the two systems for driving ATA cells, the original one (containing a resonant transformer, a gas-blown spark gap, and a Blumlein line) and the new pulse compressor based on nonlinear magnetic elements. The latter is relatively inexpensive, and its performance surpasses that of any other system. Table 1 partially documents the capabilities demonstrated by this prototype.

Figure 5 compares the physical dimensions of the two systems. The existing pulse power unit is somewhat shorter than the new magnetic replacement, but it drives only one cell instead of two. The new unit consists of an input step-up transformer, one stage of compression to charge the transmission line, a second stage of compression, and the output coupling transformer. The output transformer can be housed as part of the magnetic pulse generator or as part of the load for best impedance matching.

Adding coupling transformers at both the input and the output of the magnetic pulse compressor improves the system's versatility by permitting it to achieve the desired output pulse while allowing the compression stages and the input switching device to operate at their most efficient values of voltage and current.

At this point in the evolution of the pulse-shaping hardware, we can design the transformer turns and the interstage capacitors as integral parts of the system. The resulting magnetic compressor is simple and extremely reliable, and it satisfies all the required performance specifications.

Fig. 3

Three kinds of magnetic compressor for use at high repetition rates. (a) The command resonant charge system, used up to 10 kHz. Both switches must recover before the unit can be pulsed again. (b) The Gatling-gun mode, used up to 30 kHz. Only one switch must recover before the unit is pulsed again, which increases the repetition rate. (c) Branched magnetics for producing a pulse with a high repetition rate (50 MHz). No switch recovery is required before the unit is pulsed again.

Fig. 4

Simplified schematics of pulse power chains for the ATA induction linear accelerator. (a) The present system, which uses a spark gap and Blumlein pulse formers. (b) The non-linear magnetic drive proposed for an upgrade of the ATA.

Fig. 5
 Geometric comparison between (a) the existing pulse power unit and (b) the prototype of the recently developed upgrade. The magnetic pulse compressor is longer and has about the same diameter as the existing pulse power unit, but it feeds two accelerator cells instead of one, making it possible to use only half as many units.

Table 1 Comparison of output pulse parameters of the current spark-gap driver of the Advanced Test Accelerator and the MAG-1 prototype of an upgraded magnetic compression system.

Parameter	Spark gap	Magnetic compression
Peak output power, GW	2.5	10
Pulse rise time (10%-90%) per cell, ns	18	15
Pulse length (FWHM), ns	70	80
Pulse energy, J	350	800
Efficiency (including resonant transformer), %	70	80
Voltage (2-cell driver) at 18 kA/cell, kV	100	300
Voltage (1-cell driver) at 25 kA/cell, kV	200	450
Pulse-to-pulse jitter at up to 1 kHz, ns	± 1	± 0.5
Peak burst rate (5 pulses), kHz	1	>10
Peak average repetition rate at 10% duty factor, kHz	0.1	1

A desire to double the individual accelerator-cell voltage, coupled with the difficulty of sending 500-kV pulses around the system, prompted us to adopt an alternate procedure. We send the output from the magnetic driver (about 170-kV peak) down to the accelerator cells via two 4- Ω , semirigid, water-filled transmission lines. There, a pulse transformer provides a 3:1 voltage step-up and a ferrite pulse sharpener steepens the rise time. Figure 6 shows the physical layout and the two voltage waveforms. Saturation of the ferrite in the cell core further shortens the waveform of the cell voltage. These cells are now operated at 250 kV for 50 ns and will probably need to be modified by having the ferrite core replaced with one wound from metallic glass, if operation at the full capability of the magnetic compressor (500 kV per cell) is desired.

Metallic Glasses

The most critical aspect of the magnetic pulse compression, in terms of achieving both high efficiency and fast rise times, is the material in its final stages. The only material that satisfies all of the requirements for these final stages is one or another of the new ferromagnetic metallic glasses.

In systems with low repetition rates, the overall power efficiency of the magnetic pulse compression stages is

Fig. 7

Simplified circuit diagram of the burst-mode pulse generator designed to provide any desired repetition rate for a fixed number of pulses (in this case, eight). The numbers indicate the order in which the capacitors are discharged. In this pulse generator, an example of the type illustrated in Fig. 3c, no switch recovery is required after pulsing before the unit is pulsed again.

not critical. Even our original, unoptimized pulse compressors, which were built from nickel-iron and ferrite left over from previous projects, achieved efficiencies of more than 50%. Our most recently constructed magnetic compressors, which have metallic glass cores, achieve efficiencies greater than 80%. In systems with high repetition rates, high efficiencies are necessary to reduce internal losses and heating, which affect the life of the components.

The rebirth of the pulse compression technique as a highly reliable source of pulses of very high power and high repetition rate is due in large part to this new amorphous material. Metallic glass offers all the necessary properties

of high saturation, high resistivity, and rapid transition from high to low permeability that make the magnetic compressor so attractive. Commercial availability of this material at about the time we needed it also made magnetic compression very practical.

Metallic glass is a generic term for metals that have been solidified rapidly (about a million degrees per second) that they have no time to form the usual crystal structure. The process is done commercially by directing a thin jet of the molten metal or alloy onto a chilled, rapidly rotating metal disk or cylinder. This automatically forms a ribbon of metallic glass about 25 μm thick, which spins off at a very high rate. Most of the material we use in our magnetic compressors is iron-based or an alloy of cobalt and iron that yields a higher saturation flux.

For short pulses, the dominant factor contributing to core losses is the presence of eddy currents. These losses scale as the square of the core material's thickness and inversely as its resistivity. Amorphous metals have resistivities about three times higher than the same material in crystalline form and can be mass produced in ribbon less than 28 μm thick, making them ideal for generating fast pulses with high efficiency.

Going to Higher Repetition Rates

The type of magnetic pulse generator discussed so far consisted of a repetitive pulse source and several serial stages of pulse compression. Such a system can supply a burst with any number of pulses or can operate continuously. The burst rate, as already mentioned, is established by thyatron recovery times. If the requirement is for a fixed number of pulses in a burst, however, then a new scheme of pulse generation becomes feasible.

This scheme involves a number of parallel storage capacitors and switches that are fired in sequence at practically any repetition rate. The circuit for such a magnetic burst generator, in which portions of the eight forward pulses are used to reset the saturable inductors in

Fig. 8

Output waveforms from a low-power test of the burst-mode pulse generator, operating at a repetition rate of 16 MHz (eight pulses in 500 ns).

the circuit between pulses, is shown in Fig. 7. This eight-pulse burst generator is essentially a two-stage magnetic compressor with eight first stages and four second stages all feeding into one output load.

The timing between the output pulses is simply determined by the time delay between triggering the successive SCRs (silicon controlled rectifiers, solid-state devices analogous to thyatrons). The output capacitors consist of varying lengths of RG58 coaxial cable. The timing delays between the triggering of the SCRs was determined by cable lengths. Figure 8 shows the summed output pulse from a 60-ns length of cable, which crams an eight-pulse burst into a 500-ns interval for an effective repetition rate of 16 MHz.

Although this initial proof-of-principle experiment was performed at low power, there is no apparent barrier to scaling it up indefinitely. Therefore, this technique of burst generation offers a way to build high-power pulse generators with essentially unlimited repetition rate.

Conclusion

An old technology (pulse compression) applied to a new magnetic material (metallic glass) is enabling us to develop a pulsed power system that is reliable and efficient

and that can be adapted to drive accelerators with a wide range of performance specifications. By adding a high-peak-power switch to initiate the compression chain, we reduced the total number of stages and produced a simpler, more efficient magnetic pulse generator. This higher efficiency makes it possible to operate an induction accelerator continuously with extremely high average power. The former repetition rate limitation was imposed by thyatron recovery time and not by magnetic properties. We have also developed a new magnetic pulse generator, operating in bursts, that magnetically isolates the recovery time of the switching device, allowing practically unlimited repetition rates. In short, magnetic pulse compressors are ideally suited for driving low-impedance induction accelerators with short pulses (70 ns), short rise time (15 ns), and high peak power (10 GW) at any desired repetition rate. ▮

Key Words: amorphous magnetic material; Advanced Test Accelerator; (ATA); Experimental Test Accelerator; (ETA); magnetic pulse compression; metallic glass.

Notes and References

1. For more information on the Advanced Test Accelerator, see the December 1981 *Energy and Technology Review* (UCRL-52000-82-12), p. 1.

Evolution of the Magnetic Configuration for the MFTF-B

The development of thermal barriers and axisymmetric mirror cells for tandem-mirror devices has markedly improved the expected performance and reduced the projected costs of proposed tandem-mirror reactors. These advances will be realized in our Mirror Fusion Test Facility (MFTF-B), now under construction.

For further information contact
Keith I. Thomassen (415) 422-1166.

If we are to produce energy by magnetically harnessing nuclear fusion, we must clear two major hurdles. First, we must control the fundamental processes of fusion, and second, we must simplify the various reactor designs. This is true of both the toroidal approach to magnetic fusion, in which the main concepts are the tokamak and stellarator, and the open-ended approach, pursued here at LLNL with the tandem-mirror design.

If we could generate fusion energy economically merely by containing the reacting plasma in a uniform magnetic field, we probably would have the ideal reactor. Such a device would embody the desirable features of simplicity, modest technology, and modular construction (for easy maintenance). Unfortunately, plasma cannot be contained in this simple magnetic geometry; it rapidly and freely streams out the ends.

In the early days of LLNL's magnetic fusion research program, we proposed to plug these leaks by squeezing the

flux lines together at each end with a high-field coil. The magnet geometry was still quite simple since all coils were circular. This magnetic "cork" was fairly effective on single particles because, as they approached the ends of the machine, their energy perpendicular to the magnetic field increased to conserve their magnetic moment. Hence, their parallel energy decreased, and they were reflected (or mirrored) by the strong field. However, with a mixture of particles, the axial leaks were only partially plugged, and the bulk of the plasma was driven by magnetohydrodynamic (MHD) fluctuations sideways to the walls of the chamber.

The MHD problems essentially were solved with the invention of the "minimum-B" geometries produced by baseball or yin-yang magnets. (In a minimum-B geometry, the magnitude of the magnetic field increases radially and axially from the center of the mirror.) During the 1960s and 1970s, we concentrated on reducing plasma losses

from the ends of these single-cell, minimum-B devices.

When it became clear that plasma containment in such cells would lead to only a marginal net energy gain in a reactor-sized mirror device, we turned our attention to the tandem mirror concept. This idea is something of a return to the early cylindrical plasma chambers but with the addition of minimum-B coils at each end to plug the leaks. However, unlike the earliest mirrors, the plugging action is electrostatic, not magnetic. In any mirror cell, minimum-B or axisymmetric, when the ions are magnetically trapped they leak out the ends less rapidly than do the electrons. So, a positive "ambipolar" potential develops that pulls the ions out and retards the electron flow until the two axial loss rates are equal. This ambipolar potential is the electrostatic plug for the ions in the central cell.

The first version of the tandem mirror was conceived in 1976.¹ In a reactor design based on this early concept, we found that the end regions would dominate the cost and complexity of the design, even though the end plugs are short compared to the size of the central cell. Ever since these early ideas were advanced, there has been a continuing effort to simplify the plugs.

Figure 1 traces the evolution of the mirror concept of magnetic confinement fusion, showing five stages in the configuration of the magnets used in various experiments. The simple, solenoidal set of magnets with high-field mirror coils at each end was used in our earliest experiments. The minimum-B single cells were used in the Baseball and 2XII-B experiments, and the Tandem Mirror Experiment (TMX) was the first simple tandem mirror. The first major improvement in

Fig. 1

Evolution of the magnetic configuration for confining plasmas in magnetic mirror devices. (a) The cylindrical configuration, plugged by magnetic mirrors. (b) The single-cell, minimum-B mirror produced by a coil shaped like the seams on a baseball. (c) The simple tandem mirror with baseball coils for MHD anchors and electrostatic plugs. (d) The auxiliary cell (A-cell) version of a tandem mirror with thermal barriers, using yin-yang anchors and the A-cell electrostatic plug. (e) The axi-cell, a tandem-mirror machine with thermal barriers, using yin-yang cells for the anchor and plugs and axicells to throttle the flow of central-cell plasma to the plugs.

the tandem was embodied in the MFTF-B when construction began in 1980 and is now being tested in the TMX Upgrade. That improvement, the use of "thermal barriers" to simplify the end plugs, was incorporated in the auxiliary magnetic mirror cells (A-cells) at each end of the magnet set. Finally, in 1982, a move toward greater axisymmetry in the magnets was made by changing the configuration (Fig. 2) to its current design, which uses axisymmetric mirror cells (axicells). The reasons for this change from the A-cell configuration and the benefits to be derived in the axicell configuration are described in the remainder of this article.

Evolution of the Tandem Mirror

The MFTF-B was reviewed and approved by the Department of Energy (DOE) in 1980. At that time, we were aware that the quadrupolar (non-axisymmetric) fields generated by the yin-yang and transition magnets (see Fig. 1) would adversely affect performance, largely because the radial plasma loss induced by the quadrupolar fields could be greater than the radial plasma loss due to collisional transport in a solenoidal field. However, the quadrupolar fields

were necessary, since they would be used (in a magnetic mirror) to provide the minimum-B property required to stabilize the plasma. Plasma confinement based on the MHD stability afforded by minimum-B fields was a major success in early magnetic mirror research.

A plasma can be stably confined even though regions of "good" and "bad" MHD stability exist in different parts of the machine. This variation in MHD stability is tolerable because tandem mirrors rely on the minimum-B character of portions of the magnetic configuration. For plasma to be contained, a plasma-pressure-weighted average of the field line curvature along the length of the machine must be favorable. "Goodness" is determined by the direction of field line curvature; if the lines are concave toward the machine axis, the curvature is good. An excellent illustration of this important technical point comes, by fortunate coincidence, from the fine arts: the creator of a sculpture in Atlanta's Peachtree Plaza has unwittingly nearly duplicated the ideal minimum-B field shape (Fig. 3). The inward bending of the rods in the sculpture, which are analogous to field lines, illustrates good inward curvature. We say the plasma in a tandem mirror is "anchored" by pressure in the good regions; hence, we

Fig. 2

The MFTF-B facility for our axicell, tandem-mirror machine with thermal barriers. The artist's drawing shows the magnet set inside the vessel and the numerous canister-shaped housings from which beams are directed into the plasma. These beam-line housings contain multimegawatt ion sources; the ions are neutralized by gas cells before they enter the magnetic fields in and around the plasma. Not visible are the megawatt-level microwave and rf sources for ion- and electron-cyclotron resonance heating. The machine is surrounded by a 2-m-thick concrete vault to reduce radiation outside the vault.

refer to the minimum-B cells as "anchors."

In contrast to the minimum-B mirrors, simple mirrors made from circular coils have field lines that bulge outward (bad curvature). Since at least some region of good curvature is necessary for MHD stability, it is hard to stabilize a plasma in a purely axisymmetric tandem mirror. There are, however, ways around this difficulty.² Cusp-shaped magnetic fields could be used, for instance, since cusp fields have good curvature and can be made from axisymmetric coils; however, they leak plasma too rapidly along open field lines. Some progress has been made to resolve the problems of purely axisymmetric tandems, but at this time we do not know how to achieve sufficient stability or reduce plasma leakage to acceptable levels.

To incorporate the desirable properties of axisymmetric fields (namely, engineering simplicity and reduced plasma losses) without losing the MHD stability properties of

minimum-B fields, we devised the axicell configuration to be used in the MFTF-B.³⁻⁵ This design, essentially an axisymmetric machine with a quadrupole, minimum-B magnet configuration at each end, is illustrated (along with an earlier A-cell version⁶) in Fig. 4. The axisymmetric portion has the usual solenoidal central cell with an axisymmetric mirror cell (axicell) added at each end. These axicells are used to reduce the axial flow of plasma to the end plugs; consequently, only a small fraction of the contained plasma even reaches the quadrupolar fields of the end plugs. The amount of plasma in this so-called passing fraction must not be too low (about 5%) or the entire plasma will be unstable—in this case, by trapped-particle instability modes, which would rapidly transport the bulk of the plasma to the walls of the machine.⁷

If we keep this passing plasma fraction low (but not so low as to provoke instabilities), a number of advantages accrue. Radial transport and

Fig. 3

Minimum-B magnetic configuration (a) illustrated by a sculpture located in Peachtree Plaza, Atlanta, Georgia, and (b) produced by a baseball coil. The rods in the sculpture are analogous to the magnetic field lines in a plasma flux surface. Note that all the rods curve inward and that the radius of curvature vector is essentially perpendicular to the surface created by the rods themselves.

(a)

(b)

loss are slowed because most of the plasma ions do not encounter the quadrupole fields at the ends. Also, the high density ratio between the central cell and end plugs is an especially advantageous feature (it will be explained in more detail below). This high density ratio is the reverse of that required in the standard tandem as it was first proposed and tested in the TMX.⁸ There, the end-plug density exceeded the central-cell density by nearly an order of magnitude, producing a confining potential equal to the electron temperature multiplied by the logarithm of that density ratio. Because of this density ratio requirement, the standard tandem idea did not extrapolate well to the reactor regime; to make the tandem mirror suitable for use in a future reactor, we devised the thermal barriers⁹ and incorporated them in both the A-cell and axicell versions of the MFTF-B.

Thermal barriers, located near each end of a tandem-mirror machine, are electrostatic barriers that separate the electrons in the center of the machine

from the electrons in the end plugs. In a thermal barrier machine, the confining potential can be created by heating electrons in the end plugs with microwaves at cyclotron resonance (electron cyclotron resonance heating, or ECRH). The temperature difference thus created between the electrons in the plugs and those in the central cell, rather than a density difference, generates a potential difference. Figure 5 shows the potential profile of a typical thermal barrier at one end of a tandem machine. We also show the negative of this profile to more easily visualize the electrostatic wells that confine the two populations of electrons.

The plasma density in the end region of a thermal barrier tandem is comparable to or a few times lower than the plasma density in the central

Fig. 4

Magnetic configuration of (a) the old A-cell version of the MFTF-B and (b) the new axicell version. End plugs are defined by the region where the electrostatic potential stops the ions from leaking out the ends of the machine. The anchors are yin-yang magnets that stabilize the plasma by virtue of their minimum-B fields. The primary new features are the axicells that reduce the end-plug plasma density to about 5% of the central-cell density, simplifying the end region design. Also, the new axicell version has only 12 central-cell coils (because there were space limitations), whereas the A-cell version had 14. The yin-yang mirror cells are used to plug the ends and provide MHD stability.

cell. This new density ratio afforded by the thermal barriers represents an important improvement in tandem machine design. Fusion power output is proportional to the square of the density in the central cell (times the central-cell volume), whereas the power required to sustain the plugs is roughly proportional to the square of the density in the plugs (times the plasma volume in the plugs). Therefore, we can improve the power gain in a reactor by reducing the plug density relative to the central-cell density. The attendant reduction of pressure in the plug (density times particle temperature) is also very important because that pressure is held by the magnetic field. If we can lower the plasma pressure, we can then reduce the magnetic field strength, leading in turn to much less stringent technology requirements.

This argument also implies that, if the magnetic field in the yin-yang end plugs is as high as technology will allow, we can increase the plasma density in the central cell and, consequently, the fusion power output. (In practice, a proper compromise would be made.) Tests of the thermal barrier—the technique that makes the increase in density ratio possible—are now in progress with the TMX Upgrade.¹⁰

In the axicell version of a tandem machine with thermal barriers, this density ratio is further increased over the value predicted for the former A-cell version of the MFTF-B, leading to yet another important feature (besides improved transport) of an axicell machine. Since fusion power density is greater if the plasma in the central cell is denser a tradeoff can be made between the plasma column diameter and the fusion power output. A smaller diameter permits the use of smaller magnets and points to a reactor that is economically more attractive. The size of the magnets is not critical in the central cell where the circular magnets are relatively inexpensive and simple to build, but size is very important in the end plugs where the yin-yang magnets are costly and complex. Recent designs of a tandem

reactor based on our axicell concepts call for yin-yang magnets only slightly larger than those in the MFTF-B and constructed with superconducting NbTi to meet the 8- to 9-T fields required at the conductor.¹¹ At field strengths greater than 9 T, we will have to use superconducting Nb₃Sn, a more expensive and brittle material that is particularly difficult to wind in the yin-yang geometry.

Details of the Axicell Concept

Figure 6 shows schematically the axicell magnet configuration for the MFTF-B, as well as profiles of (a) the magnetic field, (b) the potential, and (c) the plasma density along the axis of the machine. Concentrating first on the axicells and the central cell in Fig. 6, we can see that the density reaches a peak in the axicell and then drops rapidly in the transition and end regions to values well below the central cell density. This is the density drop at the ends

Fig. 5

Graphic representation of typical axial variation of electrostatic potential, ϕ , in a machine with thermal barriers (only one end is shown). (a) Graph of positive potential, $+\phi$, and (b) the negative of that potential, $-\phi$. In (a), the central-cell ions (temperature T_{ic}) are confined in the axial "well" of depth ϕ_c , whereas in (b) the central cell electrons (temperature T_{ec}) are confined in the "wells" of depth ϕ_b . The local bump in (b) is an electrostatic barrier that separates the ECRH-heated electrons (temperature T_{ep}) in the plug from those in the center; hence, it is called a thermal barrier. The barrier is created and maintained with local ECRH heating to trap electrons magnetically and with the neutral beams used for charge-exchange ion pumping to prevent ion charge from raising this potential (lowering the barrier).

mentioned earlier—one desirable property of the axicell design. There are two factors contributing to this density drop: the decrease in magnetic field from the 12-T peak to 0.3 T in the transition region, and the potential hump in the axicell that reflects some of the central-cell ions.

The fifteen-fold drop in magnetic field strength allows the magnetic field lines to expand as they emerge from the axicell. As a result, the plasma spreads out, and its density is reduced to approximately one fifteenth what it was. The potential hump is created in the axicell by injection of neutral beams to increase the density locally. As we noted earlier, when the electron temperature is constant, the potential

will vary logarithmically with density (the Boltzmann relation). Since there is no variation of electron temperature between the axicell region and the central cell, the density hump creates this potential hump.

To sustain the density drop at the end region, we must keep the transition region free of ions that would clog the potential "hole" between the central-cell potential and the peak confining potential. Most ions pass over the hole as they bounce from end to end, but some scatter locally and would eventually fill in this hole, raising the density, if they were not removed. To remove these trapped ions, we inject beams of neutral particles along the axis (or at a shallow angle) to provide

Fig. 6

Profiles of important parameters for the axicell thermal barrier machine with the new MFTF magnet set: (a) magnetic field, (b) potential, and (c) density, shown in relation to the coils that produce the field. The confining potential is erected on the "side slope" of the yin-yang mirror cell, and the thermal barrier is created at the bottom of this well. A density bump in the axicell gives rise to a potential bump in the axicell and, together with the expanding (falling) magnetic field, produces a large density drop between the central cell and the end regions. Beams and microwaves are shown on the left end only. An identical set, rotated 90° in most cases, feeds the corresponding regions on the right end.

the necessary pumping by charge exchange. (More efficient schemes using rf coils for pumping are being investigated; since the rf would enhance the radial drift of trapped ions from the region, this idea is called "drift pumping.")

In the yin-yang end plug, a thermal barrier and confining potential are constructed in the usual way, i.e., with sloshing-ion beams¹² and electron cyclotron resonance heating. The sloshing-ion distribution is set up by injecting ions into the mirror in such a way that they have velocity components that are both perpendicular and parallel (with respect to the magnetic field) at the midplane of the mirror cell. Thus, we achieve a double-peaked density distribution (axially) with a minimum at the midplane, instead of the single-peaked density in the mirror, as it occurs with only perpendicular beam injection at the midplane.

A double-peaked density distribution has a local minimum in potential at the midplane; this minimum is the beginning of a thermal barrier. Even without enhancing this dip in potential, low-energy ions are locally trapped, providing at least partial microstability to ion-cyclotron-frequency instabilities modes that have long plagued the mirror program. We achieved this important sloshing-ion distribution in recent experiments with the TMX Upgrade and observed a large improvement in microstability over that in the TMX.¹³

Completing the formation of the thermal barrier, we use ECRH to trap the electrons magnetically in the region around the mirror midplane, further lowering the potential and thereby creating a barrier. Since the potential forms in the first place because ions are magnetically trapped in the mirror and cannot escape as fast as electrons are lost axially, any process that prevents electrons from escaping locally will lower the potential locally and contribute to the thermal barrier.

We also apply ECRH to the plug electrons beyond the midplane to further build the confining potential

We achieved this important sloshing-ion distribution in recent experiments with the TMX Upgrade and observed a large improvement in microstability over that in the TMX.

peak. As Fig. 6c shows, the confining peak (actually, a potential well for electrons) is located on the side of a magnetic well, i.e., in a region with an axial gradient in the magnetic field. So, by giving perpendicular energy and magnetic moment to electrons by cyclotron resonance heating, we can produce an axial force equal to their magnetic moment (which is increasing) times the field gradient. When this axial force exceeds the electrostatic forces holding electrons in their local well, they are expelled from the well and become part of a sloshing-electron population contained in the entire mirror cell. As the local electron density tries to decrease, the local potential increases to maintain quasi-neutrality of charge.

The Crucial Transition Region

The transition region between the yin-yang end plugs and the axisymmetric part of the machine (starting at the axicell) is particularly critical. Its importance has only recently been appreciated, and we have produced significant new ideas and designs for it that are expected to improve the overall performance of the machine.¹⁴ In constructing the MFTF-B axicell, we were not able to take full advantage of all of these new concepts because new and prohibitively costly yin-yang plugs would have been required. We are considering new yin-yang magnets for future (1990s) upgrades of the MFTF-B,¹⁵ and our current tandem-mirror reactor designs do incorporate these new ideas.

To appreciate the problems encountered in this transition region, one must understand the concept of geodesic curvature of magnetic field lines and the importance of this component of field curvature to the equilibrium, stability, and transport in a tandem-mirror device. Geodesic curvature (curvature parallel to the surface) is best explained by analogy to lines on the surface of a sphere. Each line has a vector radius of curvature with two possible components, one

perpendicular or normal to the surface and the other parallel to the surface. A great circle (e.g., the equator) is a line of normal curvature on the surface of the earth; a line following, say, the 89° latitude circle near the north pole is a line with almost purely geodesic curvature.

Magnetic field lines also have curvature that can be broken down into components perpendicular to a flux surface and components on the flux surface. In an axisymmetric mirror machine, because there is no azimuthal variation in the magnetic field, there is only normal field line curvature. In a free-standing minimum-B mirror, there is little or no geodesic curvature, either. (In Fig. 3a, we see that all the steel rods curve inward, and the radius of curvature vectors for the rods is essentially perpendicular to the surface defined by the rods themselves.)

In the transition region, where the axisymmetric and quadrupole parts of the machine are joined together, the fan of plasma leaving the yin-yang magnets must be converted from an ellipse (in cross section) to a circle before it enters the throat of the axicell. In this elliptical plasma region, there is a great deal of geodesic curvature. There is also a lot of normal curvature, which is not surprising, since Maxwell's equations do not allow divergence in the magnetic field; therefore, variations in these curvature components are linked together.

In the former A-cell configuration of the MFTF-B, the field lines in the elliptical fan in the transition (see Fig. 1) have a lot of geodesic curvature, so ions passing through this transition region suffer a displacement off the flux surface. The magnitude of the displacement is given by an integral of the geodesic curvature through this region, and this step displacement determines the radial transport time in the experiment.¹⁶ This same integral is used to determine how badly the plasma column is distorted by axial quadrupole currents flowing from this region. If the equilibrium is distorted too badly, there are several deleterious effects on the plasma, so we have another reason to avoid the effects of curvature.

In the newer axicell design, however, we reduce the integral of the curvature to nearly zero by cancelling the contribution from one fan with one from a second fan (see Fig. 7). The second plasma fan, produced by a second transition coil, is turned 90° from the first. Therefore, as an ion follows a field line through the double fan, it is "bent" first one way and then the other to compensate for the curvature. Because the net displacement from the flux surface thus is essentially zero, the residual transport is determined by second-order effects. This new design for the transition region increases plasma containment in tandem-mirror devices by significantly reducing the radial transport, an objective we first sought by improving axisymmetry but finally achieved by combining the axicells with the double fan in the transition region.

MFTF-B As It Now Stands

Incorporating the axicell concept in the MFTF-B has required changes throughout the machine. These changes have involved about \$15 million in offsetting hardware and design costs and have not increased the overall cost of the facility and auxiliary equipment (currently about \$410 million).

We may summarize the changes from the magnet configuration first designed for the MFTF-B (the A-cell) to the succeeding configuration (the axicell):

- The A-cell magnet coils were eliminated from each end, and two of the fourteen central-cell coils were removed.
- The yin-yang mirror coils were separated axially, increasing the mirror ratio from 2:1 to 3:1 and decreasing the midplane field from 2 T to 1 T.
- Each transition coil was replaced with two smaller coils to produce the desired double-fan-shaped plasma in that region. Axicells were added at the ends of the central cell, each axicell consisting of 6-T and 12-T mirror coils with a midplane field of 4 T.
- Additionally, by reducing the spacing between the central cell coils from 2 m to 1.25 m, we were able to

increase the magnetic field there from 1 T to 1.6 T.

With the new magnetic configuration, there is a new set of operating conditions in the plasma that requires some changes in the neutral-beam and rf-heating systems. All 20 of the 20-kV, 100-A, 10-ms (pulse length) sources were eliminated because they give a fast, high-density start-up, which is not consistent with the slow, low-density start-up required in the low-density end plugs. We relocated sixteen of the 80-kV, 80-A, 500-ms sources, putting ten in the central cell, one in each axicell, and two in each yin-yang end plug; we also added an 80-kV, 50-A, 30-s source to each axicell (identical to the ones for generating the sloshing ions in each yin-yang magnet and the one for pumping the thermal barrier at each end). For pumping in the transition region, we added two 40-kV, 50-A, 30-s sources on each of the two end caps of the vacuum vessel.

The rf-heating systems were altered with the addition of 1 MW of power in the 12- to 20-MHz range, available from a half-loop antenna at one end of

Fig. 7

Flux surfaces and field lines on those surfaces for the new axicell magnet configuration for MFTF-B. A profound difference from the earlier A-cell design is the elimination of the single-fan transition in favor of the double-fan design for the axicell version. This produces a decrease of nearly an order of magnitude in the radial loss of plasma in the machine, directly increasing what would be an "energy gain" in a magnetic fusion reactor.

the central cell. About 400 kW should be absorbed in the plasma by ion cyclotron resonance heating (ICRH). Electron cyclotron resonance heating is still required at the thermal barriers and to create the confining potential; current plans call for eight 200-kW gyrotron tubes at frequencies of 28, 35, and 56 GHz.

These alterations necessitated numerous other changes in the MFTF-B vacuum vessel, support structures, vault, electrical systems, cryogenics, control system, and plasma diagnostics. Since approval was granted by the DOE late in the 1982 fiscal year, all of these modifications have been incorporated in the MFTF-B design and in existing contracts for the various subsystems.

The six months before and after the decision to incorporate the axicells in the MFTF-B was a turbulent period of very intense activity, but the project is once again running smoothly. We expect construction on the facility to be completed by September 1985 and all auxiliary heating and diagnostic systems to be operational by December 1986 for the initial plasma experiments.

Future Directions

The MFTF-B is the only tandem-mirror facility of its class in the world, and it will remain unique for some time

to come. Since we intend to use this investment to its fullest, we have explored various options for upgrading the facility to meet new goals in the 1990s. One idea, favored at the moment by LLNL and various DOE review committees, is to modify the end plugs once more to improve the physics performance and to insert a simple (axisymmetric) magnetic mirror cell in the center of the machine. In this high-field region, we can simulate plasma conditions in one of the modular cells of a tandem reactor.

In Fig. 8, the magnetic configurations of the MFTF-B and this proposed upgrade are shown. The insert in the central cell of the upgrade is a 4-m-long simple mirror with 12-T peak mirror fields and a 4.5-T midplane field. In the remainder of the central cell, the field is 1.6 T, so the inserted simple mirror cell can hold considerably more plasma pressure than can the central cell. We use this feature to create a hot, high-density plasma through beam injection into this mirror.

In one mode of operation with deuterium-tritium fuel, we would produce approximately 11 MW of fusion power in this section and could insert fusion blankets in this region (an additional 6 MW is produced in the remaining parts of the central cell). Tests of the blankets and auxiliary equipment would be part of a program to address issues of the power and fuel cycles to be used in fusion reactors.

In another mode of operation, we would run the beam and rf systems to maximize the containment time and power gain in the plasma. While operating with deuterium-tritium fuel, the upgraded machine is expected to have a power gain of approximately two, an order of magnitude better than that feasible with the MFTF-B.

This improved performance is the result of several features of the upgraded design. First, the magnetic field level in the end plugs would be about twice that of the MFTF-B magnets, permitting the adiabatic confinement of neutral beams of higher energy than the 80 kV used in MFTF-B.

Fig. 8

Comparison of the magnet configurations in (a) the MFTF-B as it is currently designed and (b) the potential upgrade to the MFTF-B. A 4-m-long simple mirror with 12-T peak mirror fields and a 4.5-T midplane field has been inserted into the central-cell coils. This mirror cell will be able to hold greater plasma pressure than the central cell could, allowing us to create a hot, high-density plasma by injecting a beam into this mirror. Using deuterium-tritium fuel, this cell will produce 11 MW of power.

(We propose to use 200-kV beams.) In turn, with higher energy beams, we can create higher electrostatic potentials to plug the ends of the machine. Another feature is the use of a yin-yang coil in the transition region. This yin-yang magnet has a dual purpose—it creates the double-fan transition and serves as an additional MHD anchor to stabilize the tandem configuration. (The yin-yang plug magnets in the MFTF-B are the sole MHD anchor.) With additional anchoring, the configuration should be stable up to a plasma pressure limit that is higher than we achieve with the MFTF-B.

Finally, in the upgraded design, the axicell is replaced by a single 18-T choke coil that reduces the passing ion fraction to the end plugs. Drift pumping replaces neutral-beam charge-exchange pumping, and collector plates on the end dome are electrically biased to control the plasma potential. All of these features contribute to improved performance in tandem-mirror machines and, therefore, are being incorporated in all of the advanced magnetic fusion reactors being designed by LLNL.

Whether this design or some other one prevails, we are searching for better ideas while validating the older ones. We believe this search eventually will lead to a workable, economical power reactor. □

Key Words: axicell; axisymmetric mirror cell; electron cyclotron resonance heating (ECRH); ion cyclotron resonance heating (ICRH); magnetic fusion; Mirror Fusion Test Facility (MFTF-B); Tandem Mirror Experiment (TMX); Tandem Mirror Experiment Upgrade (TMX-U); thermal barrier.

Notes and References

1. T. K. Fowler and B. G. Logan, "The Tandem Mirror Reactor," *Comments on Plasma Physics and Controlled Fusion* **11**, 167 (1977).
2. G. A. Carlson *et al.*, *Comparative End-Plug Study for Tandem Mirror Reactors*, Lawrence Livermore National Laboratory, Rept. UCID-19271 (1981).
3. K. I. Thomassen and V. N. Karpenko, *Axicell Design for the End Plugs of MFTF-B*, Lawrence Livermore National Laboratory, Rept. UCID-19318 (1982).
4. D. E. Baldwin and B. G. Logan, Eds., *Physics Basis for an Axicell Design for the End Plugs of MFTF-B*, Lawrence Livermore National Laboratory, Rept. UCID-19359 (1982).
5. J. Kesner, R. S. Post, B. D. McVey, and D. K. Smith, "A Tandem Mirror with Axisymmetric Central-Cell Ion Confinement," *Nuclear Fusion* **22**, 549 (1982).
6. K. I. Thomassen and V. N. Karpenko, *Tandem Mirror Fusion Test Facility MFTF-B*, Lawrence Livermore National Laboratory, Proposal LLL-Prop-163, Rev. 3 (1980).
7. H. L. Berk *et al.*, "Curvature-Driven Trapped-Particle Modes in Tandem Mirrors," *9th International Conference on Plasma Physics and Controlled Nuclear Fusion Research*, Paper IAEA CN-41/K-3, Baltimore, MD (September 1982).
8. F. H. Coensgen *et al.*, "Electrostatic Plasma-Confinement Experiments in a Tandem Mirror System," *Phys. Rev. Lett.* **44**, 1132 (1980); and T. C. Simonen *et al.*, "TMX Tandem Mirror Experiments and Thermal-Barrier Theoretical Studies," *9th International Conference on Plasma Physics and Controlled Nuclear Fusion Research*, Paper IAEA CN-41/G-1, Baltimore, MD (September 1982).
9. D. E. Baldwin and B. G. Logan, "Improved Tandem Mirror Fusion Reactor," *Phys. Rev. Lett.* **43**, 1318 (1979).
10. F. H. Coensgen *et al.*, *TMX Upgrade Major Project Proposal*, Lawrence Livermore National Laboratory, Proposal LLL-Prop-172 (1980). Results from experiments with the TMX Upgrade are discussed in the June 1983 *Energy and Technology Review* (UCRL-52000-83-6), p.
11. B. G. Logan, "Mirror Advanced Reactor Study (MARS)," *5th ANS Topical Meeting on the Technology of Fusion Energy*, Knoxville, TN (April 1983); and B. G. Logan *et al.*, *Mirror Advanced Reactor Study—Interim Report*, Lawrence Livermore National Laboratory, Rept. UCRL-53333 (1983).
12. For a discussion of sloshing ions, see the June 1983 *Energy and Technology Review* (UCRL-52000-83-6), p. 9.
13. T. C. Simonen *et al.*, *TMX-Upgrade (TMX-U) Operation in the Sloshing Ion Mode*, Lawrence Livermore National Laboratory, Rept. UCID-19568 (1982).
14. D. E. Baldwin and R. H. Bulmer, *A Physics Conceptual Design for the MFTF-B Transition Coil*, Lawrence Livermore National Laboratory, Rept. UCID-19562 (1982).
15. K. I. Thomassen and J. N. Doggett, Eds., *Options to Upgrade the Mirror Fusion Test Facility*, Lawrence Livermore National Laboratory, Rept. UCID-19743 (1983).
16. R. H. Cohen and J. H. Gilmore, Appendix H in *Physics Basis for an Axicell Design for the End Plugs of MFTF-B*, D. E. Baldwin and B. G. Logan, Eds., Lawrence Livermore National Laboratory, Rept. UCID-19359 (1982).

Past Titles

Articles published in recent issues of the *Energy and Technology Review* are grouped below mainly according to their chief sponsors, the Assistant Secretaries of the U.S. Department of Energy. Research funded by other Federal agencies is listed under Work for Others.

ENERGY RESEARCH

- Measuring Chromosome Changes in Exposed People: Cigarette Smokers (June 1983)
- Sloshing-Ion Experiments in the TMX-U (June 1983)
- The National Magnetic Fusion Energy Computer Center (April 1983)

DEFENSE PROGRAMS

International Security Affairs

- Ionospheric Detection of Explosions (May 1983)
- Negotiating With the Soviets (May 1983)
- Peaceful Nuclear Explosions in Soviet Gas Condensate Fields (May 1983)
- The Regional Seismic Test Network (May 1983)
- Seismic Verification of a Comprehensive Test Ban (May 1983)
- The Test Ban Treaties: Verifying Compliance (May 1983)
- The Supply Side of Nuclear Proliferation: A Look at West Germany (April 1983)

Military Application

- Gallium Arsenide Amplifier (Brief—June 1983)

CONSERVATION AND RENEWABLE ENERGY

- Aluminum-Air Battery Development: Toward an Electric Car (June 1983)

LABORATORY REVIEWS

- The State of the Laboratory (July 1983)
- National Defense (July 1983)
- Energy and the Environment (July 1983)
- Engineering and Science (July 1983)
- Offense and Defense (June 1983)

WILSON FESTSCHRIFT

- An Arbitrary-Mesh Computer Program With Applications to Astrophysics (March 1983)
- Black Hole Accretion: The Quasar Powerhouse (March 1983)
- Collisionless Matter and Galaxy Formation (March 1983)
- Does Stellar Collapse Produce Supernovae or Black Holes? (March 1983)
- Magnetorotational Collapse of an Iron Stellar Core (March 1983)
- Modeling Sources of Gravitational Radiation (March 1983)
- Pioneer of Numerical Astrophysics (March 1983)

WORK FOR OTHERS

National Science Foundation

- Modeling Urban Air Pollution (April 1983)

Waste Management Project Office—Nevada Operations Office

- A Nuclear Waste Package for Use in Tuff (Brief—April 1983)

Disclaimer

The document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial products, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government thereof, and shall not be used for advertising or product endorsement purposes.

Printed in the United States of America

Available from

National Technical Information Service

U.S. Department of Commerce

5285 Port Royal Road

Springfield, Virginia 22161

Price: Printed Copy \$4.50, Microfiche \$3.00