WSRC-TR--90-491

WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER LABORATORY DIVISION

DE92 009750

Keywords: Electrolysis,
Electrodialysis,
Saltstone,
Salt Solution,
Waste Management

Retention Time: Permanent

October 12, 1990

TO: D. L. Fish, 773-A

FROM: D. T. Hobbs, 773-A *DTH*

**Final Report - Electrochemical Processing of Nitrate Waste
Solutions (U)**

Attached is the final report prepared by the Electrosynthesis Company under contract #0892113 investigating the electrolysis and electrodialysis of alkaline salt solutions of the type which will be disposed of in saltstone.

cc: A. C. Almon, 773-A
L. E. McCurry, 773-A
SRL Records, 773-A

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

do!
MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Electrosynthesis
COMPANY INCORPORATED

Received by OSTI
MAR 19 1992

FINAL REPORT

ELECTROCHEMICAL PROCESSING OF NITRATE WASTE SOLUTIONS

**To: David Hobbs, Bldg. 773-A
Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29801-0001**

**From: The Electrosynthesis Company Inc.
East Amherst, New York 14051**

Date: May 31, 1990

Mailing Address:
P.O. Box 430
East Amherst, N.Y. 14051

Shipping Address:
3230 Union Rd.
Cheektowaga, N.Y. 14227

Tel: (716) 684-0513

TeleFAX: (716) 684-0511

EXECUTIVE SUMMARY

Research performed at The Electrosynthesis Company Inc. has successfully demonstrated that nitrate and nitrite can be efficiently removed from a synthetic effluent stream. The research reported here has studied two quite different approaches to the problem. The first approach is to remove the nitrate and nitrite ions through a membrane separation process, recovering nitric acid and sodium hydroxide solutions for reuse. The second approach is more conventional and studies the direct reduction of the nitrate and nitrite at a cathode. Both approaches have been shown to have merit but have their difficulties which will need further work to resolve.

Nitrate and nitrite have been almost completely removed from the synthetic effluent steam with good efficiency by affecting a separation across a pair of ion exchange membranes. In addition to recovering acid and base in this process, the volume of the remaining effluent is reduced considerably by transport of water across the membrane. One of the problems that remains with this process, however, is the stability of the membranes and particularly the stability of the anion exchange membrane. This membrane is exposed to both nitric acid and strongly alkaline solutions in the cell and to date long term stability has been a problem with the membranes tested. It is recommended that further work should evaluate other newly available membranes as well as study the effects of radiation on the performance of the membranes.

The direct reduction of nitrate and nitrite has been studied at several different electrode materials and it has been demonstrated that cathode material has a large effect on both the efficiency and the gas product distribution. Highest current efficiencies for the reduction process are seen at those electrode materials that are known to show high hydrogen overpotentials. Flow cell studies have demonstrated that temperature and current density are also important parameters in the system. The reduction process has been run efficiently at high current densities (600 mAcm^{-2}) at 80°C at a lead cathode. While this work has obtained the majority of the information needed for a preliminary engineering study, the long term stability of the electrochemical cell components remains a concern. Indeed, when a full synthetic mix was utilized, problems were experienced with solids precipitating out in the cell compartments. Further studies should identify the cause of these problems or find alternative electrode materials.

TABLE OF CONTENTS

	<u>Page</u>
Introduction-----	1-2
Experimental	
I. Makeup of Solutions-----	3-4
II. Analysis of $\text{NO}_2^-/\text{NO}_3^-$ -----	5
III. Analysis of Off Gases-----	6
IV. Membrane Separation Process-----	7-8
V. Direct Reduction in Glass Cell-----	8-9
VI. Direct Reduction in Flow Cell-----	9-10
Results and Discussion	
A. Membrane Separation Process-----	11-14
B. Direct Reduction in Glass Cell-----	15-17
C. Direct Reduction in Flow Cell-----	18-26
Recommendations and Conclusions-----	27-28

FIGURES

	<u>Figure</u>
Experimental	
Analysis of $\text{NO}_2^-/\text{NO}_3^-$ -----	1
Off Gas Analysis-----	2-3
Four Compartment Membrane Separation Cell-----	4
Glass Cell Direct Reduction Setup-----	5
ICI FM01 LC Flow Cell-----	6
Results and Discussions	
A. Membrane Separation Process	
Three Compartment Membrane Separation Cell-----	A.1
Experimental Results-----	A.2-A.13
Anion Exchange Membrane After Use-----	A.10
B. Direct Reduction in Glass Cell	
Identification of N_2O -----	B.1
Experimental Results-----	B.2-B.11

FIGURE

Figure

C. Direct Reduction in Flow Cell

Flow Cell Setup-----	C.1-C.2
Experimental Results-----	C.3-C.78
Cathode With Solids-----	C.79
Gas Flow Rate - Long Term Run-----	C.80
Cell Voltage at Lead and Nickel Cathode-----	C.81
Cell Voltage and Flow Rate-----	C.82
Instantaneous Current Efficiencies at Lead and Nickel--	C.83

TABLES

Table

A. Membrane Separation Process

Summary of Volume Changes-----	A.1
--------------------------------	-----

B. Direct Reduction in Glass Cell

Summary of Results at Various Electrodes-----	B.1
---	-----

C. Direct Reduction in Flow Cell

Summary of Nitrate and Nitrite Loss and Product Distribution-----	C.1
Summary of Current Efficiencies-----	C.2
Summary of Solution Analyses-----	C.3
Summary of Caustic Formation-----	C.4
Summary of Solids Analysis-----	C.5

Appendix 1: Equations for Calculation of Current Efficiencies

Appendix 2: Letter from Engineering Consultant, John Colman

INTRODUCTION

The Westinghouse Savannah River Company (WSRC) contracted The Electrosynthesis Co., Inc. to investigate electrochemical methods to remove nitrates and nitrites from waste solutions. These solutions contain high concentrations of nitrate, nitrite, sodium hydroxide and aluminate, as well as smaller amounts of several other contaminants. The goal of the R&D program was to provide enough information for an engineering study. This report summarizes the R&D efforts undertaken by ESC.

Two approaches to the removal of nitrate/nitrite have been studied; electrolytic reduction and electrochemical separation. The separation approach entails the recovery of nitric acid and sodium hydroxide from the waste using a three or four compartment electrochemical cell. This approach would also greatly reduce the remaining waste stream volume due to water transport across the ion exchange membranes. However, the stability of the anion exchange membranes in the strongly alkaline WSRC waste remains a concern. We have investigated the feasibility of the membrane separation process, paying particular attention to membrane stability, current efficiency, and membrane fouling.

The electrolytic reduction process involves the reduction of nitrate and nitrite at a cathode, producing ammonia and nitrogen gases. ESC has performed an extensive study of this process. Initial efforts focused on determining the best electrode material for the reduction. These studies were performed in a small divided glass cell using a simplified synthetic solution containing only nitrate, nitrite and sodium hydroxide. Current efficiencies for the reaction, and product composition were determined. Further parameters such as current density, the use of ion exchange membranes, temperature, and the buildup of metal precipitates on the cathode were investigated in a flow cell using the two more promising cathode materials identified in the glass cell

experiments. Again, current efficiency and product composition were measured in an attempt to determine optimal operation parameters.

EXPERIMENTAL

I. Make-up of solutions

A. Simplified mix - NaNO_3 , NaNO_2 , and NaOH only

<u>Reagent</u>	<u>Molarity</u>	<u>g/l</u>
NaNO_3 (99.8%)	1.95	166.04
NaNO_2	0.60	41.40
NaOH (98.7%)	1.33	54.37

The reagents were added, mixed, and diluted to 1L in a volumetric flask with deionized water. This mix was used in the electrochemical separation and glass H-cell reduction tests.

B. Complete Synthetic Mix

A non-radioactive synthetic mix was made up to simulate the complete waste stream.

	<u>Reagent</u>	<u>Concentration, g/l</u>	<u>Supplier</u>	<u>Grade</u>
(a)	NaNO_3	86.70	Baker	99.8%
	NaNO_2	41.40	EM	>99.0%
	Na_2SO_4	19.88	Baker	ACS
	$\text{Na}_3\text{PO}_4 \cdot 12\text{H}_2\text{O}$	3.23	Mallinckrodt	>98%
	NaCl	1.29	Morton	99.9%
	NaF	0.63	Fisher	95%
	Na_2SiO_3	0.81	MCB	
	$\text{Na}_2\text{CrO}_4 \cdot 4\text{H}_2\text{O}$	0.77	Baker	
	NaTPB (Sodium tetraphenylborate)	0.89	Aldrich	>99.5%
(b)	Na_2CO_3	16.96	Aldrich	>99%
	NaOH	102.80	Baker	98.7%

Parts (a) and (b) were mixed separately until dissolved and then combined. The NaTPB did not completely dissolve. Once mixed, the following reagents were added.

<u>Reagent</u>	<u>Concentration, g/l</u>	<u>Supplier</u>	<u>Grade</u>
$\text{Al}(\text{NO}_3)_3 \cdot 9\text{H}_2\text{O}$	116.29	Fisher	ACS
$\text{Na}_2 \{ \text{Ru}(\text{NO})(\text{NO}_2)_4 (\text{OH}) \}$	17.1 mg/l	WSRC	
HgCl_2	0.61 mg/l	Mallinckrodt	99.5%

The resultant synthetic mix has the following composition:

<u>Component</u>	<u>Concentration</u>
NaNO_3	1.95M
NaNO_2	0.60M
NaOH	1.33M
$\text{NaAl}(\text{OH})_4$	0.31M
Na_2SO_4	0.14M
Na_2CO_3	0.16M
NaCl	0.22M
NaF	0.015M
Na_2SiO_3	0.0038M
Na_3PO_4	0.0085M
Na_2CrO_4	0.0033M
NaTPB	0.0026M
$\text{Na}_2 \{ \text{Ru}(\text{NO})(\text{NO}_2)_4 (\text{OH}) \}$	$4.5 \times 10^{-5} \text{M} = 4.5 \text{mg/l Ru}$
HgCl_2	$2.2 \times 10^{-6} \text{M} = 0.45 \text{mg/l Hg}$

The synthetic mix, when diluted to volume, was filtered through Whatman #2 paper to remove undissolved NaTPB. The resultant filtrate was yellow and clear, with a specific gravity of 1.225g/ml. This mix was used for flow cell tests and a few of the membrane separation studies.

II. Analysis of NO_2^- and NO_3^-

Analyses of nitrate and nitrite were performed on a Waters 600 HPLC using a micro-Bondapak C18 column. The mobile phase was 0.05M KH_2PO_4 with 1 vial of PIC-A reagent (Waters) in 2L of buffer, running at a flow rate of 2.5ml/min. Detection of the species was by UV at 214 nm. This method gave excellent separation of the products with no interfering peaks. (see Fig. 1).

CHANNEL A INJECT 04/05/90 11:13:18

Figure 1

WSRC 04/05/90 11:13:18 CH= "A" PS= 1.
 FILE 7. METHOD 5. RUN 412 INDEX 1
 ANALYST: DH

NAME	MILLIMOLAR	RT	AREA	BC	RF
NITRITE	0.297	3.23	1671698	0156286	12.797
NITRATE	0.967	4.2	6993664	0172323	330.922
TOTALS	1.264		8665362		

III. Off Gas Analysis

Gas analyses were performed on a Perkin Elmer 8500 gas chromatograph using a thermal conductivity detector. Nitrogen and ammonia were separated and quantified on a Chromasorb 103 column modified with 10% Versamide 900/8% KOH (see Figure 2). Oxygen and nitrogen were separated and quantified on a molecular sieve 5A column (see Figure 3). Both columns used helium as the carrier gas at a flow rate of 60ml/minute. The injector temperature was 120°C, and 0.2mL of sample was injected. Hydrogen could be separated and quantified on the molecular sieve column if argon carrier gas at 60ml/min was used. However, oxygen and nitrogen could not be quantified on molecular sieves with argon carrier gas if a large amount of hydrogen was present since the hydrogen peak interfered with the oxygen and nitrogen peaks. The ratio of gases present was determined by using an external standard gas mixture containing known amounts of oxygen, nitrogen, ammonia and nitrous oxide. However, this standard mix was not available until the beginning of the flow cell studies. Earlier experiments in the glass cell assumed equal response factors for nitrogen, ammonia and nitrous oxide.

Figure 2

Figure 3

IV. Membrane Separation Process

Study of the membrane separation of nitrate and nitrite from WSRC waste solution was conducted in the MP flow cell (ElectroCell, Sweden). The flow cell was set up with 4 compartments, as shown in Figure 4.

FIGURE 4

FOUR COMPARTMENT ELECTRODIALYSIS

Exploded view of the EC Electro MP cell

Electrodes:

Anode: DSA-O₂
Cathode: 316 SS
Surface Area: 100cm²

Compartment Solutions:

Feed: Simplified mix or the complete synthetic mix
Membrane: 0.1M HNO₃
Anolyte: 18% H₂SO₄
Catholyte: 0.1M NaOH

Cell Separators:

Cation Exchange Membranes: Nafion 417 or 901

Anion Exchange Membranes: Various

Each compartment initially contained 450ml of solution. Samples taken from compartments were analyzed for (NO₂⁻) and (NO₃⁻) by HPLC and for (H⁺) and (OH⁻) by titration using a phenolphthalein indicator. The volumes for each compartment at time t were calculated by measuring the final volume, assuming a linear relationship between water transport and charge, and then subtracting the volumes taken for samples.

V. Direct Reduction in Glass H-cell

Constant current electrolyses were performed in a divided glass cell using various cathode materials. The cathode and anode chambers were separated by a Nafion 417 cation exchange membrane which isolated the reduction of nitrate/nitrite in the cathode chamber. 70ml of the WSRC simplified mix (1.95M NO₃⁻, 0.60M NO₂⁻, 1.33M NaOH) was added to the catholyte chamber and electrolyzed at 140mA/cm² (total cell current of 700mA). The catholyte chamber contained Teflon and epoxy spacers above the solution level which minimized the gas void volume. The chamber was sealed so as to be gas

Fig. 5

tight. Solution and gas samples were taken by a syringe introduced through septa such that the introduction of air into the chamber was avoided. The anolyte was 1.0M H_2SO_4 , and the anode was a 5cm^2 Pt flag. Figure 5 shows the glass cell setup.

Experiments typically ran for about 60,000 coulombs (24 hours). Nitrite and nitrate concentrations were measured by HPLC. Cathode off gases were analyzed by GC on the Chromasorb column. Nitrogen, nitrous oxide, and ammonia were assumed to be the only gases present, and any hydrogen present was ignored. Thus the glass cell off gas results only reflect the amounts of nitrite/nitrate reduction products relative to each other and not actual amounts of gases. Occasionally, an off gas sample was injected on the molecular sieve column to check for oxygen. Oxygen did not exceed 10% of the nitrogen peak area, indicating that little air contamination occurred. The volume of the catholyte was measured at the end of the run and a linear volume change throughout the run was assumed.

VI. Reduction In ICI Flow Cell

Flow cell studies were performed in the FM01-LC Electrolyzer, manufactured by ICI. (Figure 6). Either nickel or lead alloy cathodes were used, and the anode was nickel. The FM01-LC electrodes have a surface area of 64cm^2 per electrode face. The full synthetic solution was used in flow cell experiments. 700ml of solution was placed in a glass reservoir which was wrapped with heating tape. The solution was pumped from the reservoir through a flowmeter and into the FM01-LC through which a constant current was passed. The flowrate varied from 0.6 to 1.0 gallons per minute. The solution then returned to the reservoir. Temperature control was accomplished by an inline thermocouple probe connected to a temperature controller which controlled the heating tape. The temperature could readily be controlled within a $\pm 2^\circ\text{C}$ margin of the desired temperature. Off gases were disengaged from the

FIGURE 6

An exploded view of the FM01-LC Electrolyser assembly (Type 10).

solution in the reservoir and exited into a demister (column filled with glass beads) and a condenser to remove water mist and vapor. The off gas then escaped to the atmosphere through a bubbler. Gas and liquid samples were taken through septa to ensure the system remained gas tight.

Before an experiment started the cell was purged with helium to remove air. The current was then switched on and samples taken periodically to monitor the reaction. Gas samples were analyzed by GC. Relative amounts of oxygen, nitrogen, ammonia, and nitrous oxide were quantified by comparison to a standard gas used as an internal standard. Hydrogen was quantified by comparing the sample peak area to the peak area of a known volume of hydrogen.

At the end of the experiment the volume of solution remaining was measured and the volume at time t calculated by assuming a linear volume change throughout the run. The alkalinity of the solution at the beginning and end of the experiment was determined by titration against a standardized acid solution using a phenolphthalein indicator. At the end of the experiment the cell was disassembled and inspected for corrosion or build up of solids in the electrolyte compartments or on the electrodes. In all cases except where noted the cathode was cleaned with an etching solution (20% H_2O_2 /80% acetic acid for lead, 30% HNO_3 /10% H_2SO_4 /10% H_3PO_4 /50% acetic acid for nickel) to remove any solids deposited on it and to prepare for future use. The anode was rinsed off with water and was not etched unless solids had deposited on it as noted in the results section. For some runs, electrolyzed solution and solids deposited on the cathode or anode were sent to Westinghouse Savannah River Lab for analyses.

RESULTS AND DISCUSSION

A. Membrane Separation Process

Experiments were performed to determine the feasibility of recovering nitric acid and sodium hydroxide solutions from a nitrate/nitrite waste stream. The stability of ion exchange membranes, the current efficiency for the process, and effects of other components in the waste mixture were investigated.

An area of immediate concern for the membrane separation process is the stability of the ion exchange membranes. It is important that the membranes selected for the process are stable chemically to the nitric acid and sodium hydroxide formed, and also that they will not be damaged by the formation of heavy metal ion precipitation. The former is of particular concern for the anion exchange membrane. Indeed, until very recently anion exchange membranes that are stable to base were not available. One such stable membrane now available from Japan is Tosoflex. This is available in three different grades, of which the DF34 was thought most likely to be stable to both the acid and alkali environments it would encounter.

The first two experiments (Fig. A.2 - A.5) were designed to evaluate this membrane at a current density of $50\text{mA}/\text{cm}^2$ with the simplified WSRC mix. Initially a 3-compartment cell (Fig. A.1) was used rather than a 4-compartment cell. Current efficiencies greater than 100% for $\text{NO}_2^-/\text{NO}_3^-$ removal from the feed compartment resulted because the same charge used to affect the transport of NO_3^- through the membrane also may have directly reduced $\text{NO}_2^-/\text{NO}_3^-$ at the cathode. Hence a second experiment used a 4-compartment cell (Figure 4) where the additional membrane isolated the effects of the cathode. A third experiment at $100\text{mA}/\text{cm}^2$ was terminated early on because the cell failed due to a rapid increase in cell voltage thought to be caused by a membrane failure.

Tests in a glass cell confirmed that the Tosflex DF34 membrane had failed and was giving a higher cell voltage than a new membrane. The membrane had only lasted 12 hours at $50\text{mA}/\text{cm}^2$.

Subsequent experiments were conducted with a Neosepta AM-1 anion exchange membrane (a non-perfluorinated membrane). In a glass cell this membrane did not fail even with aluminate ion present. A concern here was that aluminate and silicate ions passing from an alkaline environment into the acid compartment through a pH gradient may precipitate out in the membrane. The next two experiments (Fig. A.6 - A.9) evaluated the Neosepta AM-1 membrane in the MP cell with the simplified mix at 50 and $100\text{mA}/\text{cm}^2$. Current efficiencies for the transport of nitrate and nitrite into the membrane compartment were slightly higher than those seen with the Tosflex membrane. Current efficiencies for hydroxide retention in the feed compartment are very high; however, the Nafion 417 cation exchange membrane was thought to be leaking some hydroxide ion from the catholyte compartment into the feed compartment. The cell was taken apart for inspection after the experiment at $50\text{mA}/\text{cm}^2$. The Neosepta membrane was discolored at the ports where caustic solutions (Feed, Catholyte) had gone through it. The membrane was also cracked in areas where it had dried out as a result of the gasketing being clamped down on the membrane. Figure A.10 shows a photograph of the Neosepta membrane after the experiment.

The final two electrodialysis experiments (Fig. A.11 - A.14) were conducted at $100\text{mA}/\text{cm}^2$ using the complete synthetic WSRC mix. The current efficiencies are very high at the beginning of the run but drop rapidly as the concentrations of NO_3^- and NO_2^- drop, giving rise to significant competition by OH^- for the charge transport. The current efficiencies reported at the beginning of Run 172-87 (Fig. A.10) for nitrate/nitrite removal from the feed compartment are above 100% and are probably due to experimental error. The

Neosepta membrane was not replaced after Run #172-77, so including Run #172-87 it lasted nearly 300,000 coulombs at 100mA/cm² without failing. After Run #172-87 the cell was disassembled. The Neosepta membrane was again cracked and discolored. For Run #172-95 a new Neosepta membrane was used. Also, a Nafion 901 cation exchange membrane was used in place of the 417 membrane between the feed and catholyte compartments to minimize the back migration of hydroxide into the feed. However, Figure A.13 shows that current efficiency for hydroxide retention was still much higher than for NO₂⁻/NO₃⁻ loss. Thus the 901 membrane appeared not to perform any better than the 417 at stopping hydroxide back migration.

In each of the experiments described above the HPLC analyses of the membrane compartment showed little or no nitrite present. This occurs because the nitrite ion is immediately converted to nitrous acid in the membrane compartment which then decomposes to form nitric oxide. The reactions for this are as follows:

Any nitric oxide present in the gaseous state will immediately react with oxygen and form nitrogen dioxide, a highly toxic brown gas. A brown gas was often seen when the membrane compartment was drained.

In conclusion the membrane separation process is promising and should be looked into further. Fairly high current efficiencies were obtained (>50%) for nitrate/nitrite removal even after 99% of the total quantity of NO₂⁻ and NO₃⁻ had been removed from the feed stream in Run 172-95. Table A.1 shows that the feed stream volume was reduced significantly during all experiments from the starting volume of 450ml. The long term stability and other problems

associated with ion exchange membranes is still questionable, however, and could not be resolved within the time frame of this project. Further R&D efforts under this contract focused on the direct reduction process because it was perceived as a simpler process which showed better promise of success in the time frame available. In addition there may be some deleterious effects to the perfluorinated cation exchange membranes from low levels of radioactivity present in the WSRC waste stream. The presence of NO_2 gas is a further concern. If these problems could be resolved and the process better characterized, it could prove to be an efficient means of removing nitrates from the waste stream.

B. Direct Reduction In Glass Cell

In the direct reduction of nitrites and nitrates, the following reactions take place:

During the glass cell studies, a third important reduction product was discovered and later identified by GC/MS to be N_2O (Figure B.1). The reaction for N_2O formation is thought to be as follows:

The formation of N_2 is obviously the preferred product because it requires less energy and the product does not require special treatment before exhausting. Any ammonia formed at the cathode may need to be separated from the oxygen formed at the anode to prevent the formation of a potentially explosive mixture. Moreover, ammonia may require further treatment before release to the atmosphere. As can be seen from the following table the formation of ammonia also requires more electrons per mole than nitrogen and therefore would increase the overall power requirements for the process.

<u># of Electrons Required to Form</u>			
<u>From</u>	<u>1/2N₂</u>	<u>1/2N₂O</u>	<u>NH₃</u>
NO ₃ ⁻	5	4	8
NO ₂ ⁻	3	2	6

Thus, the thrust of the glass cell studies was to find an electrode material that would minimize ammonia formation and maximize current efficiency for the reduction process. Current efficiencies reported for the glass cell studies were calculated based on the theoretical number of electrons required to form N_2 only. The theoretical amount of charge needed to reduce $\text{NO}_2^-/\text{NO}_3^-$ to the

actual levels obtained in the experiments was divided by the actual amount of charge used to obtain a current efficiency. Appendix 1 shows the equations used for the calculation for current efficiency.

The competing reaction at the cathode surface is the reduction of water to form hydrogen. If this reaction occurs, the current efficiency for the reduction of nitrite and nitrate will also be reduced. It is well known that metals vary widely in their hydrogen evolving characteristics. Hydrogen evolution occurs more readily at nickel than at most metals, and less readily at lead than at most other metals. Thus nickel and lead were tested first (Fig. B.2 - B.3) to determine the effect of hydrogen overpotential at a current density of 140mA/cm^2 . Figures B.2 - B.11 show the destruction of nitrate/nitrite and off gas composition for each cathode material, plotted against charge passed. Table B.1 summarizes the glass cell experiments. As can be seen the current efficiency for lead was much higher than for nickel. Also, nitrogen formation was favored with the lead cathode. In a further test (Fig. B.4), a high surface area form of nickel was used to see if a lower effective current density would improve the efficiency. Efficiency actually decreased, and a large amount of ammonia was formed, which is consistent with the lower hydrogen overpotential expected for porous nickel. Other cathode materials tested were cadmium, zinc, 316 stainless steel, ATJ graphite, and copper (Figs. B.5 - B.9). The hydrogen overpotential for these metals fall between nickel and lead with cadmium being the most similar to lead. As can be seen from Table B.1 cadmium performed slightly better than nickel in terms of current efficiency and ammonia production while graphite was worse. The zinc electrode tested dissolved during the electrolysis. The next material tried was lead alloy (Fig. B.10) manufactured by ICI containing tin and calcium to improve the mechanical strength of lead. Its performance was similar to, but not quite as good as, lead in terms of both current efficiency

and off gas composition. Finally, a low hydrogen overpotential electrode, also from ICI (containing ruthenium) was tested (Fig. B.11). This material should evolve hydrogen even more readily than nickel. In fact, the current efficiency was much worse than for nickel, and a large amount of ammonia was produced. This is of concern because ruthenium salts present at low levels in the WSRC waste could plate out onto a cathode eventually causing it to behave as this ruthenium electrode did.

It should be noted again that the offgas composition does not include hydrogen and therefore the percentages of the reduction products may be overstated.

In conclusion, it is interesting to note that the effect of changing the cathode material on the current efficiencies as well as the product distribution is surprisingly large. Table B.1 shows that lead and lead alloy were the best electrode materials for minimizing ammonia formation and maximizing current efficiency, in a divided glass cell with the simplified mix tested. The ruthenium electrode was by far the worst. The high surface area porous nickel and ruthenium electrodes were the only materials tested which did not give a significant amount of N_2O gas product, instead they gave a greater amount of ammonia. Both of these materials are expected to have lower overpotential for hydrogen evolution than does planar nickel.

C. Direct Reduction In Flow Cell

Based on the glass cell results, lead alloy and nickel were chosen as cathode materials for flow cell studies. Lead alloy was chosen because its mechanical strength makes it preferable to lead in a flow cell where large electrodes will be used. Moreover, if a metal flowcell is preferred, such as the ICI FM21 cell design, then the lead alloy may be the only form of lead available. Nickel was also studied further to see if its poor performance in glass cell studies was due to mass transport conditions which would be improved in the flow cell. Furthermore, if both the cathode and anode were nickel, it was suggested that the current could be periodically reversed to remove metal deposits on the cathode. In addition to electrode material, the effects of solution components, temperature, current density, and cell separators were evaluated.

Flow cell results were evaluated based on current efficiencies and the composition of off gases. A standard gas containing known amounts of N_2O , NH_3 , N_2 , and O_2 was obtained so that the ratios of these off gases could be measured accurately. Quantitative measurement of the gases was not possible because the gas volume could not be measured accurately. Current efficiencies reported were calculated based on N_2 as the only product as in the glass cell studies, or based on the ratios of N_2 , NH_3 and N_2O formed. Appendix 1 contains the equations used for the calculation of current efficiencies.

A decision to use the complete synthetic mix was taken at the beginning of the flow cell work since conditions that were as realistic as possible were desired. Moreover, it was important to be able to recognize any potential problems associated with using the synthetic mix as soon as possible. A temperature of $50^{\circ}C$ was initially chosen because an industrial cell would be expected to heat up during the process and run at close to this temperature. Figure C.1 shows the flow cell setup. Two flowmeters are shown because in

experiments 174-45 to 174-70 a microporous polypropylene membrane was used to separate the anode and cathode off gas streams, and thus the flows were split before the cell. Figure C.2 shows the division of flows within the cell.

The attached figures C.3-C.78 show the destruction of nitrite/nitrate, the off gas composition and current efficiencies plotted against charge for each set of conditions. Tables C.1. - C.5, summarize the flow cell experiments all at 1 million coulombs. All flow cell experiments were run for at least 1 million coulombs. In some experiments the passage of 1 million coulombs occurred while the experiment was running overnight so no actual intermediate data was available. In these cases, solution analyses, gas composition, and current efficiencies were extrapolated from the graphs to obtain results for the summary charts.

Experiments 174-9 and 174-16 studied the behavior of lead alloy and nickel cathodes. The same current density (140mA cm^{-2}) used in the glass cell studies was used. Notice that both materials showed markedly lower current efficiencies for the destruction process than was previously seen in the glass cell experiment.

Current efficiencies improve slightly when ammonia is included in the calculation because more of the charge used in the reaction is accounted for. N_2O is a very small contributor to the reduction products, so the addition of N_2O to the current efficiency calculation makes little difference. In general, the amount of $\text{NO}_2^-/\text{NO}_3^-$ reduction off gas products is much lower in these flow cell runs than in glass cell tests. Since the sum of reduction products plus anodically produced oxygen is much less than 100%, it can be assumed that some hydrogen is also evolved which would explain the depressed current efficiencies.

Lead alloy still showed a better current efficiency than nickel, but it produced more ammonia. This is quite different from the situation seen in the glass cells. The lead cathode has a powder layer of black solids deposited on it. The nickel cathode had a fine gray plate on it. This phenomena was not observed in any of the glass cell studies. It was hypothesized that the loss of current efficiency was due to heavy metals in the full synthetic mix (ruthenium, chromium) plating out or depositing on the cathode surface. Conditions to minimize the effects of these contaminants and to improve current efficiency were sought.

The next experiment, #174-24, looked at using a cation exchange membrane (Nafion 417) in the cell. The catholyte was the WSRC complete synthetic mix, and the anolyte was 1.0M H_2SO_4 . A lead anode was used because it was thought to be more stable than nickel which would be attacked by the acidic anolyte. Lead was also attacked. Analysis by SEM and XRD showed that insoluble lead salts (lead sulfate, lead oxide, lead nitrate) were formed in the anolyte. Chromium was removed from the catholyte (see Table C.3), probably as an insoluble lead chromate. The current efficiency for the reduction was improved slightly by the use of a membrane. Also, more N_2 and less NH_3 was produced than in the undivided cell experiment #174-9. The use of a divided cell was not investigated further, however, because of the uncertainty in the stability of perfluorinated ion exchange membranes to radiation fields. Moreover, the improved current efficiency may have resulted from the removal of chromium from solution rather than the use of a membrane.

Subsequent experiments (174-29 and 33) studied the effects of removing metal ions from the solution. The removal of either chromium or ruthenium from the starting mix resulted in a slight improvement in current efficiency, comparable to those seen when a membrane was used. At the end of the experiment without chromium, the solution had turned from colorless to yellow,

and a small amount of chromium was detected in the end solution (see Table C.3). This is thought to have come from the previous run, which may have had chromium trapped in the electrodes that was not removed by etching. The lead alloy cathode at the end of both runs had black powder deposited on it. A sample of this powder from run #174-33 was analyzed and determined by XRD to be mostly PbO (possibly Pb) (Table C.5). It was hypothesized that the lead cathode was dissolving in the highly alkaline solution and then replating based on solution analyses (Table C.3) showing soluble lead and tin present at the end of all runs where a lead alloy cathode was used. These analyses also show that little chromium or ruthenium was removed from solution in most tests.

Further experiments studied the effect of current density in an attempt to improve the current efficiency and to protect the cathode. During experiment #174-37 the cell heated up to 60°C due to the higher current density (300mA/cm²) being applied. The current efficiency was higher than in the case where a current density of 140mA/cm², and a temperature of 50°C were used. Also, more ammonia was produced. Whether the improvement was due to increased temperature or increased current density was not certain and in a further experiment (174-41) a lower current density (75mA/cm²) was tried. The current efficiency and gas composition were similar to experiment 174-9 where a current density of 140mA cm⁻² was used. A black powder coating was observed on the cathode in both experiments 174-37 and 174-41.

The gas composition results from experiments done thus far indicated that a potentially explosive mixture of ammonia and oxygen off gases could form. Obviously, this presents a major concern in an industrial scale cell. In order to avoid this explosion hazard two possible approaches were considered. The first would be to inject a large volume of air or nitrogen

into the off gas stream to bring the flammable gas content below the explosive limit. This approach would also necessitate sizing all subsequent gas handling equipment (scrubbers, HEPA filters, etc.) to handle the diluted stream. Because of the increased costs for an expanded ventilation system in radioactive service, an alternative approach was implemented. This required separating the anode and cathode gases inside the cell so that explosive mixtures are never formed. A microporous polypropylene separator (Celgard 3401) was placed between the anode and cathode. This separator was used in all subsequent experiments.

The effects of higher temperatures and current densities were investigated next. Experiment 174-45 duplicated experiment 174-37 except it ran at a higher temperature of 80°C. However, during the run, one of the anolyte compartments was at least partially blocked by green solids, and the anode was corroded and pitted. The solids are likely nickel sulfate which would form if the flow through the anode compartment was restricted causing the solution at the anode surface to turn acidic. Despite this, the current efficiency improved significantly as a result of the higher temperature, and in addition more ammonia was produced. This last experiment was repeated and the blockage problem seen previously was avoided by not tightening the cell frames down as much (174-48). As can be seen from Table C.2 the results were similar. In both experiments, the cathode had a black powder coating on it.

The next two experiments (174-51 and 174-54), were conducted at 600mA/cm² and 80°C to see if a higher current density would improve current efficiencies. A larger power supply was used to deliver the necessary current. During experiment 174-51, the power supply intermittently shut off the current. Once the power supply was repaired, the run was repeated. With the current on continuously, the solution heated up to 87°C. Despite this problem with the power supply, the current efficiencies are similar for both

runs. Differences in gas composition are likely due to the fact that air was sucked into the reservoir every time the current switched off during experiment 174-51. Overall, little difference in efficiency or product distribution was seen between 300 and 600mA/cm². The cathode still had a black powder coating on it.

Since increasing temperature and current density had improved current efficiency with a lead alloy cathode, a nickel cathode was also tried at 600mA/cm² and 80°C. Current efficiency was improved slightly, but was not as good as seen for the lead alloy cathode at 140mA/cm² and 50°C. Considerably less ammonia was produced than at a lead cathode. At 300mA/cm² similar results were obtained. In both experiments (174-57 and 174-62) an induction period at the beginning was observed where little destruction of nitrate/nitrite was occurring, and nitrate was actually being formed. As a result, current efficiencies were very low at the beginning of the experiments but improved and then leveled off at the end.

At the end of the nickel cathode experiments, the cathode had a very faint gray coating on it. It was hypothesized that the solids building up on the cathode may actually have helped the reduction. To test this, the cathode from experiment 174-62 was not cleaned off, and a duplicate experiment was run (#174-66). However, the induction period with nitrate formation and low current efficiencies was still seen. Overall, the current efficiency was worse than for the previous experiment. Hydrogen was measured for the first time at the beginning and end of this experiment and at the beginning of the run, 65% of the off gas was hydrogen. If only water were being electrolyzed, 67% of the off gas would be hydrogen according to the following equation:

This would indicate that early in the run very little reduction of

nitrite/nitrate is occurring at the nickel cathode, and that the electrode reaction is simply the reduction of water. At the anode, some oxidation of nitrite to nitrate also occurs causing the level of nitrate to increase. As a result of the reduction of water and oxidation of nitrite, current efficiencies for the reduction process are low or even negative during the early portion of all experiments using nickel cathodes. Negative current efficiencies were not shown on the current efficiency plots. By the end of the experiment, the level of hydrogen had dropped and the amount of reduction products had increased resulting in improved current efficiencies.

Because the performance of nickel in the flow cell could not be significantly improved by increasing temperature and current density, no further work was done with nickel cathodes. Results of experiments performed thus far indicated that a lead alloy cathode operating at 300 or 600mA/cm² and 80°C gave the best results. Since no reduction in current efficiency occurred at 600mA/cm², this set of conditions was chosen for further characterization in a long term run. For experiment #174-70, the same cell setup as used in other high current density lead cathode experiments was utilized, but total volume of the complete WSRC synthetic mix was increased to 10L, instead of 700ml used for all other experiments. Also, an estimate of gas flow rate was obtained by routing the off gas stream into a water displacement flask and measuring the amount of water displaced in one minute every time a solution sample was taken.

Over the first million coulombs, the current efficiency for experiment #174-70 was similar to other high temperature, high current density runs with lead cathodes with the exception that less ammonia was produced. The amount of hydrogen produced is much lower than that seen in the early stages of the nickel cathode experiment (174-66), indicating that more nitrate/nitrite was

being reduced. However, the current efficiency dropped off to 25% at 7 million coulombs and leveled off to about 20% thereafter. The experiment was terminated after about 15 million coulombs due to a flow blockage. This blockage did not develop until about 14 million coulombs. When the cell was dismantled and inspected, one of the anolyte compartments was completely blocked with green solids and the anode was badly corroded. The anode solids were composed mostly of nickel hydroxide (see Table C.5) which would form if conditions of localized acidity existed at the anode surface possibly causing corrosion of nickel into solution and subsequent precipitation as the hydroxide. The cathode had a thick layer of black powder deposited on it. This powder was mostly lead (Table C.5). The solution analysis (Table C.3) shows the same amount of lead present in solution before and after the run. Figure C.79 shows the cathode, anode, and anolyte compartment after the run.

Figure C.80 is a plot of the flowrate of off gases measured in experiment #174-70. The total volume of gas products was 1816L as determined by integrating the area under the curve. If the anode is assumed to only be producing oxygen, 840L would have been formed at STP. The volume of various off gas products theoretically formed at STP by the actual amount of charge passed is given below:

<u>Cathode Product</u>	<u>Volume</u>	<u>Anode Product</u>	<u>Volume</u>	<u>Total Volume</u>
Hydrogen only	1680L	Oxygen	840L	2520L
Nitrogen only	390L	Oxygen	840L	1230L
Ammonia only	454L	Oxygen	840L	1294L

The actual volume of gas formed falls between the values for hydrogen production and N_2/NH_3 production, indicating that a mixture of hydrogen and NO_2^-/NO_3^- reduction products were formed.

Figure C.81 is a plot of the cell voltage obtained when various current

densities were passed at a nickel cathode (Experiment #174-66) or lead alloy cathode (Experiment #174-70). The same nickel anodes and microporous separator were used in both experiments. More gas evolution was observed from the nickel cathode and as a result, the resistance between the anode and cathode was greater, and cell voltage was higher. Figure C.82 shows that cell voltage decreased as solution flow rate increases as would be expected. It is likely that a significant contribution to the cell voltage is from gas bubbles in the interelectrode gap and that higher flow rates will remove these bubbles more efficiently.

Table C.4 shows the amount of hydroxide formed in each flow cell run. The formation of hydroxide roughly follows the current efficiencies. This is expected because the reduction of nitrites/nitrates produces more hydroxide than does water electrolysis.

Figure C.83 shows the effect of the induction period on the nickel cathode. Instantaneous current efficiencies were calculated for a lead and nickel cathode under the same conditions based on the destruction of nitrite and nitrate during the period between samples rather than from the beginning of the run. Instantaneous current efficiencies for nickel are low during the induction period at the beginning of the run but closely follow those for lead throughout the remainder of the run. However, at the 1 million coulomb point, 60% of the nitrite and nitrate have been destroyed at the lead cathode whereas only 35% had been destroyed at nickel. At 60% destruction the current efficiency at nickel would be expected to be lower than that seen for lead. Nonetheless, if the induction period could be overcome, current efficiencies closer to those seen for lead could possibly be obtained at a nickel cathode.

CONCLUSIONS AND RECOMMENDATIONS

Electrochemical Separation Process

The electrochemical separation of nitrate and nitrite to give nitric acid and sodium hydroxide has been demonstrated. The process maintains good current efficiency to almost 100% removal of the nitrate and nitrite from the feed stream. The problems envisaged with the precipitation of aluminate and silicate, due to pH gradients in the membrane, did not occur to an appreciable extent in the time frame tested. However, failure of the anion exchange membrane did occur and is thought to be due to the harsh environments of acid and alkali on either side of the membrane.

The success of the process to date is encouraging and we would recommend that it be studied further. Any further work should include some long term tests to evaluate the stability of the membranes. Since this work was completed, we have been made aware of a new membrane (Neosepta AMH) that is reported to be stable to base. We recommend that this membrane be tested, and possibly one of the other Tosoflex membranes, under long term testing. It would also be important to study the effects of radiation on the membranes by measuring any changes in resistance and possibly looking for changes in performance.

Direct Reduction of Nitrates and Nitrites

The direct reduction of nitrate and nitrite has been demonstrated at several different electrode materials in both the glass cell and the ICI flow cell. Early work in the glass cell utilized a simplified synthetic mix and showed that the cathode material has a large effect on both the efficiency and the gas product distribution. However, these differences are less marked when the full synthetic mix is used. This is thought to be due to adsorption or

plating processes changing the surface properties of the electrode. Despite these factors, the lead cathode still appears to perform better than the nickel one giving better overall current efficiencies. The highest current efficiencies for the reduction process were seen at a lead cathode operating at a high current density (600 mAcm^{-2}) at 80°C . In a similar experiment a nickel cathode showed a long induction period before it began to operate efficiently. This induction process is not well understood at this time. Long term experiments showed that precipitation of solids, especially at the anode, is a problem still to be overcome in this process. The cause of the formation of the solids is not fully understood and it is recommended that this should be resolved in further work.

In view of the promising results obtained to date on this process, we would make the following recommendations for further studies: It is of utmost importance to solve the problem of solids formation in the cell, therefore the cause of this problem should be identified. This could be done by changing the electrode materials in the cell, particularly the anode material. Other anodes that could be tested might include DSA- O_2 or Pt clad materials. Other cathode materials that could be tested in the flow cell include amalgamated materials or carbon. There are also several electrode pretreatments that could be tried to improve performance. Once the optimum configuration has been found a long term stability test should be performed. It is recommended that this test should be for a minimum of 1000 hours during which the parameters of cell voltage, cell gas composition and current efficiency should remain constant.

Appendix 1

Current Efficiencies - WSRC

Equations:

Overall:

Calculations:

$$\% \text{CE for N}_2: [(\Delta \text{NO}_3)5 + (\Delta \text{NO}_2)3] \times 96487 / \text{actual C} \times 100$$

$$\text{For NH}_3: [(\Delta \text{NO}_3)5 + (\Delta \text{NO}_2)3] \times 96487 \times \frac{\text{N}_2}{\text{N}_2 + \text{NH}_3} / \text{actual C} \times 100$$

$$+ [(\Delta \text{NO}_3)8 + (\Delta \text{NO}_2)6] \times 96487 \times \frac{\text{NH}_3}{\text{N}_2 + \text{NH}_3} / \text{actual C} \times 100$$

$$\text{For N}_2\text{O}: [(\Delta \text{NO}_3)5 + (\Delta \text{NO}_2)3] \times 96487 \times \frac{\text{N}_2}{\text{N}_2 + \text{NH}_3 + \text{N}_2\text{O}} / \text{actual C} \times 100$$

$$+ [(\Delta \text{NO}_3)8 + (\Delta \text{NO}_2)6] \times 96487 \times \frac{\text{NH}_3}{\text{N}_2 + \text{NH}_3 + \text{N}_2\text{O}} / \text{actual C} \times 100$$

$$+ [(\Delta \text{NO}_3)4 + (\Delta \text{NO}_2)2] \times 96487 \times \frac{\text{N}_2\text{O}}{\text{N}_2 + \text{NH}_3 + \text{N}_2\text{O}} / \text{actual C} \times 100$$

Appendix 2

JOHN E. COLMAN & ASSOCIATES LTD.

1485 Shamrock Lane
Oakville, Ontario L6L 1R1
Telephone: (416) 827-0348

Dr. J. David Genders,
Project Leader,
Electrochemical Research & Development,
The Electrosynthesis Co. Inc.,
3230, Union Road,
Cheektowaga,
New York, 14227,
U.S.A.

May 3, 1990.

Dear David,

Re: Electrochemical Processing of Nitrate Waste Solutions.
Westinghouse Savannah River Company Project.

At our last project review meeting you requested that I comment on the applicability of the research results for engineering purposes.

The information presented is exactly what is necessary to commence preliminary engineering and complete a feasibility report on the cost of the electrochemical facilities necessary for the reduction of nitrate waste solutions. The type of data for cell current densities, voltages, current efficiencies, temperatures, electrodes, membranes, flow rates, material balances, gas compositions and effects of a variety of contaminants are satisfactory. However, it is essential to resolve the current problems of electrode materials and precipitates in the cells and to conduct long term tests. These long term tests should be run for several weeks to ensure that no further problems occur and that the chosen cell conditions remain relatively constant (e.g. cell voltage, current efficiency, cell gas composition).

A further problem that has not been addressed is that of cell liquor evaporation and solids removal. I am quite sure that this problem will only be resolved through testing by a suitable equipment manufacturer.

Based upon the results to date and provided that no further serious problems are revealed due to the complex nature of the nitrate waste solutions, then I am confident that a satisfactory process can be developed.

Yours Sincerely,

John E. Colman

Consulting Engineer

Figure A.1: Schematic of 3-Compartment Electrodialysis Cell

FIGURE A.2

Plot of Current Efficiency vs. Charge Feed Compartment #167-9

Tosflex DF34 50 mA/cm-2 3 Compartments

FIGURE A.3

Plot of Current Efficiency vs. Charge Membrane Compartment #167-9

—•— Based on NO₂+NO₃ —+— Based on H⁺ Gain

Tosflex DF34 50 mA/cm² 3 Compartments

FIGURE A.4

Plot of Current Efficiency vs. Charge Feed Compartment #167-30

—•— Based on NO₂+NO₃ —+— Based on OH-Retained

Tosflex DF34 50 mA cm⁻² 4 Compartments

FIGURE A.5

Plot of Current Efficiency vs. Charge Membrane Compartment #167-30

—•— Based on NO₂+NO₃ —+— Based on H⁺ Gain

Tosflex DF34 50 mA/cm² 4 Compartments

FIGURE A.6

Plot of Current Efficiency vs. Charge Feed Compartment #172-65

—•— Based on NO₂+NO₃ —+— Based on OH-Retained

Neosepta AM-1 50 mA/cm²

FIGURE A.7

Plot of Current Efficiency vs. Charge Membrane Compartment #172-65

—•— Based on NO₂+NO₃ —+— Based on H⁺ Gain

Neosepta AM-1 50mA/cm-2

FIGURE A.8

Plot of Current Efficiency vs. Charge Feed Compartment #172-77

—•— Based on NO₂+NO₃ —+— Based on OH-Retained

Neosepta AM-1 100 mA/cm²

FIGURE A.9

Plot of Current Efficiency vs. Charge Membrane Compartment #172-77

—•— Based on NO₂+NO₃ —+— Based on H⁺ Gain

Neosepta AM-1 100 mA/cm²

FIGURE A.11

Plot of Current Efficiency vs. Charge Feed Compartment #172-87

—•— Based on NO₂+NO₃ —+— Based on OH-Retained

Neosepta AM-1 100 mA/cm² Synthetic Feed

FIGURE A.12

Plot of Current Efficiency vs. Charge Membrane Compartment #172-87

—•— Based on NO₂+NO₃ —+— Based on H⁺ Gain

Neosepta AM-1 100 mA/cm² Synthetic Feed

FIGURE A.13

Plot of Current Efficiency vs. Charge Feed Compartment #172-95

—•— Based on NO₂+NO₃ —+— Based on OH-Retained

Neosepta AM-1, Nafion 901 Synthetic Feed

FIGURE A.14

Plot of Current Efficiency vs. Charge Membrane Compartment #172-95

—•— Based on NO₂+NO₃ —+— Based on H⁺ Gain

Neosepta AM-1, Nafion 901 Synthetic Feed

TABLE A.1

Summary of Solution Volume Data From Electrodialysis Runs

	Charge Passed (C)	Current Density (mAcm ⁻²)	Ion Exchange Membrane	End Volume		Water Transport (ml/1000 C)		Solution Not Accounted For
				Feed	Membrane	Feed	Membrane	
167-9	89,620	50	Tosflex	358	385	(1.0)	(0.7)	78
167-30	110,970	50	Tosflex	283	390	(1.5)	(0.5)	106
172-65	74,500	50	Neosepta	354	426	(1.3)	(0.3)	77
172-77	122,800	100	Neosepta	226	531	(1.8)	0.7	154
172-87	174,100	100	Neosepta	232	563	(1.3)	0.7	89
172-95	183,700	100	Neosepta	239	526	(1.2)	0.4	103

Numbers in Parentheses Indicate Solution Loss

TABLE B.1

Glass Cell Nitrate/Nitrite Reduction at Various Electrode Materials

	(Coulombs)	Solution Analysis - Loss in			% CE - N ₂ Only	Off Gas Analysis		
		Moles Nitrite	Moles Nitrate	Total Moles		% Nitrogen	% N ₂ O	% Ammonia
Nickel	62,059	(0.012)	0.112	0.100	81.4	42.6	54.0	3.5
Lead	60,376	0.003	0.124	0.127	97.4	75.4	24.2	0.4
Porous Nickel	60,500	0.032	0.079	0.111	78.3	68.6	3.4	27.7
Cadmium	52,840	(0.056)	0.143	0.087	84.4	63.2	34.7	2.1
316 Stainless	61,760	(0.005)	0.109	0.104	82.6	37.0	56.9	6.0
ATJ Graphite	60,390	0.024	0.081	0.105	76.5	45.3	37.6	17.0
Copper	60,870	0.018	0.089	0.107	79.1	55.3	32.2	12.4
Lead Alloy	60,630	(0.014)	0.124	0.111	92.8	66.6	31.5	1.9
Ruthenium on Ni	61,152	0.035	0.060	0.095	63.1	74.9	0.0	24.8

Results at approx. 60000 Coulombs

NITROGEN
N2.O.

Lib:NBS
61 M864 r920 RFN:10024-97-2
39 Bpk: 44 Mt: 44

#1 1.0
3378000

N₂O Actual mw
= 44.0001

1.00
55958000
4635000

FIGURE B.2

WSRC Reduction Run#172-7 Reduction at Ni

Off Gas Composition Reduction at Ni Cathode

FIGURE B.3

WSRC Reduction Run#172-13 Reduction at Pb

Off Gas Composition Reduction at Pb Cathode

FIGURE B.4

WSRC Reduction Run#172-19

Reduction at Porous Ni

Off Gas Composition

Reduction at Porous Ni Cathode

FIGURE B.5

WSRC Reduction Run#172-25

Reduction at Cd

Off Gas Composition

Reduction at Cd cathode

FIGURE B.6

WSRC Reduction Run#172-31 Reduction at Zn

Zn Cathode Dissolved

Off Gas Composition Reduction at Zn cathode

Zn Cathode Dissolved

FIGURE B.7

WSRC Reduction Run #172-48

Reduction at Type 316 SS

Off Gas Composition

Reduction at Type 316 SS Cathode

FIGURE B.8

WSRC Reduction Run #172-55

Reduction at Carbon

Off Gas Composition

Reduction at Carbon Cathode

FIGURE B.9

WSRC Reduction Run #172-60

Reduction at Copper

Off Gas Composition

Reduction at Copper Cathode

FIGURE B.10

WSRC Reduction Run #172-71

Reduction at Pb Alloy

Off Gas Composition

Reduction at Pb Alloy Cathode

FIGURE B.11

WSRC Reduction Run #174-2

Reduction at Ru/Ni

Off Gas Composition

Reduction at Ruthenium

TABLE C.1

Summary of Flow Cell Experiments

Experiment # 174- (Conditions)	Current Density (mA/sq. cm.)	Solution Analysis - Loss in			Off Gas Composition			
		Moles NO2	Moles NO3	Total moles	% N2O	% NH3	% N2	% O2
9 Pb/Ni 50 C	140	0.20	0.56	0.76	1.73	3.24	5.85	56.05
16 Ni/Ni 50 C	140	0.19	0.41	0.60	0.78	1.96	5.96	64.39
24 Pb/Pb 50 C	140	(0.01)	0.81	0.80	10.57	2.04	6.85	4.68
29 Pb/Ni 50 C, no Cr	140	(0.02)	0.89	0.87	2.93	3.95	6.58	58.24
33 Pb/Ni 50 C, no Ru	140	0.12	0.74	0.86	4.15	5.88	9.06	71.26
37 Pb/Ni 60 C	300	0.23	0.74	0.97	2.73	8.00	4.46	48.56
41 Pb/Ni 50 C	75	0.26	0.51	0.77	0.76	4.55	5.52	40.95
45 Pb/Ni 80 C	300	0.13	0.94	1.07	1.80	13.83	5.05	50.48
48 Pb/Ni 80 C	300	0.17	0.91	1.08	1.44	11.13	4.62	50.38
51 Pb/Ni 80 C	600	0.18	0.97	1.15	2.87	13.66	10.98	64.97
54 Pb/Ni 87 C	600	0.21	1.00	1.21	0.81	12.15	3.30	43.95
57 Ni/Ni 80 C	600	0.16	0.51	0.67	1.52	3.68	5.07	45.29
62 Ni/Ni 80 C	300	0.15	0.52	0.67	2.31	1.99	6.26	43.60
66 Ni/Ni 80 C	300	0.22	0.38	0.60	2.10	2.97	7.20	51.98

All flow cell results reported at 1.0MM Coulombs

#174-24 is a divided cell run.

#174-66 - Cathode not cleaned before run.

TABLE C.2

Current Efficiencies for Flow Cell Runs and Glass Cell Experiments

	Solution	Cathode/Anode	Temp C	Current Density (mA/sq. cm.)	% Current Efficiency for N2 only	% Current Efficiency for N2 + NH3	% Current Efficiency for N2 + NH3 + N2O	Water Loss (ml/mill C))
174-9	Complete mix	Lead Alloy/Nickel	50	140	34	42	40	81
174-16	Complete mix	Nickel/Nickel	50	140	19	31	30	57
174-24	Complete mix	Pb Alloy/Pb Alloy	50	140	51	50	47	
174-29	Complete, no Cr	Lead Alloy/Nickel	50	140	38	47	45	71
174-33	Complete, no Ru	Lead Alloy/Nickel	50	140	37	49	46	49
174-37	Complete mix	Lead Alloy/Nickel	60	300	41	61	58	77
174-41	Complete mix	Lead Alloy/Nickel	50	75	32	47	46	91
174-45	Complete mix	Lead Alloy/Nickel	80	300	52	79	77	103
174-48	Complete mix	Lead Alloy/Nickel	80	300	50	78	76	84
174-51	Complete mix	Lead Alloy/Nickel	80	600	54	79	77	72
174-54	Complete mix	Lead Alloy/Nickel	87	600	49	76	75	85
174-57	Complete mix	Nickel/Nickel	80	600	28	39	37	104
174-62	Complete mix	Nickel/Nickel	80	300	31	39	37	95
174-66	Complete mix	Nickel/Nickel	80	300	24	28	24	97
172-71	NO2, NO3, NaOH	Lead Alloy/Platinum	30-40	140	93			
174-2	NO2, NO3, NaOH	Ru on Ni/Platinum	30-40	140	63			

All flow cell results reported at 1.0MM Coulombs
#172-71, 174-2 are glass cell runs. #174-24 is
a divided cell run. #174-66-Cathode not cleaned.

TABLE C.3

WSRC Solution Analyses

	Cathode/Anode	Temp C	Current Density (mA/sq. cm.)	Pb mg/kg	Sn mg/kg	Ni mg/kg	Cr mg/kg	Ru mg/kg
174-16	Nickel/Nickel	50	140	106	4.91	1.51	150.0	29.2
174-24 Divided cell	Lead Alloy/Nickel	50	140	11.2	15.00		18.5	3.21
174-29 No Chrome	Lead Alloy/Nickel	50	140	66	13.50	0.07	9.6	0.46
174-33 No Ru	Lead Alloy/Nickel	50	140	56.4	12.90		124.0	.28
174-37	Lead Alloy/Nickel	60	300	233	12.00	1.71	156.0	4.43
174-41	Lead Alloy/Nickel	50	75	25.3	7.79	1.15	321.0	4.70
174-48	Lead Alloy/Nickel	80	300	95.7	8.12	0.47	143.0	5.19
174-54	Lead Alloy/Nickel	87	600	78.9	8.74	0.51	145.0	4.78
174-57	Nickel/Nickel	80	600	15.0	3.32	0.42	156.0	6.43
174-62	Nickel/Nickel	80	300	13.4		0.44	154.0	5.49
174-70(Long term)	Lead Alloy/Nickel	80	600	21.3	3.93	3.19	157.0	5.22
WSRC Feed(#16-62)				9.9	5.27	1.46	174.0	6.2
WSRC Feed(#174-70)				20.8	3.64		170.0	5.36
Simulant calculated				0	0.00	0.00	141.0	3.74

All solutions filtered before analysis.
Results corrected for volume changes during run.

TABLE C.4

Caustic Formation in Flow Cell Runs

	Solution	Cathode/Anode	Current Density (mA/sq. cm.)	% Current Efficiency for N2 only	% Current Efficiency for N2 + NH3 + N2O	Moles NO2/NO3 Destroyed	Moles OH- Formed
174-9	Complete mix	Lead Alloy/Nickel	140	34	40	0.76	0.63
174-16	Complete mix	Nickel/Nickel	140	19	30	0.60	0.65
174-24	Complete mix	Pb Alloy/Pb Alloy	140	51	47	0.80	1.20
174-29	Complete, no Cr	Lead Alloy/Nickel	140	38	45	0.87	0.54
174-33	Complete, no Ru	Lead Alloy/Nickel	140	37	46	0.86	0.93
174-37	Complete mix	Lead Alloy/Nickel	300	41	58	0.97	1.40
174-41	Complete mix	Lead Alloy/Nickel	75	32	46	0.77	0.72
174-45	Complete mix	Lead Alloy/Nickel	300	52	77	1.07	1.33
174-48	Complete mix	Lead Alloy/Nickel	300	50	76	1.08	1.09
174-51	Complete mix	Lead Alloy/Nickel	600	54	77	1.15	1.42
174-54	Complete mix	Lead Alloy/Nickel	600	49	75	1.21	1.13
174-57	Complete mix	Nickel/Nickel	600	28	37	0.67	0.80
174-62	Complete mix	Nickel/Nickel	300	31	37	0.67	0.87
174-66	Complete mix	Nickel/Nickel	300	24	24	0.60	0.67

All flow cell results reported at 1.0MM Coulombs

TABLE C.5**SEM and XRD Results of Solids Analysis**

Sample ID	Morphology and Particle Size	Elemental Composition	XRD Phases
174-14	Irregularly and flake shaped crystallites in loosely and densely packed aggregates; 0.1 - 500µm	Pb, Cr, Ni, Al, Sr, Na	PbO (massicot) NaPb ₂ (CO ₃) ₂ OH
174-24-C	Irregularly shaped crystallites in densely packed aggregates; 1-500 µm	Pb, Cr, Ni, Al, Sr, Ca, Na	Pb ₁₀ ((CO ₃) ₆ (OH) ₆ PbO (massicot) 3Pb(NO ₃) ₂ ·7PbO·1.5H ₂ O Sr ₄ (PO ₄) ₂ CrO ₄
174-24-A	Irregularly and cubic shaped crystallites in densely packed aggregates; crystallites 1 -15 µm aggregates 100 - 2000 µm	Pb, Si, Na, Mg, Ca, Ni	PbSO ₄ 3Pb(NO ₃) ₂ ·7PbO·1.5H ₂ O Pb ₁₀ ((CO ₃) ₆ (OH) ₆
174-33	Irregularly shaped crystallites in densely packed sponge-like aggregates; crystallites 1-15 µm	Pb, Al, Na, Ni, Cr, Ca, Si	PbO (litharge) PbO (massicot) PbMg(CO ₃) ₂
174-70 Anode "A"	Irregularly shaped crystallites in large aggregates; 5 to >5000 µm gray-black solids with small amount of green solids	Ni, Na, Al, Si, S, Cl	NaNO ₃ Na ₂ CO ₃ Na ₄ Ca ₈ Si ₅ O ₂₀ Ni
174-70 Anode "B"	Irregularly shaped crystallites in large aggregates; 5 to >1000 µm gray-green solids	Ni, Al, Na, S, Cl	Ni(OH) ₂ NaNO ₃ Na ₂ SO ₄ Na ₂ CO ₃ Ni ₆ Al ₁₂ (OH) ₁₆ (CO ₃ ,OH) ₄ ·4H ₂ O
177-70 Cathode	Irregularly shaped crystallites in large aggregates; 5 to >3000 µm dark gray-black finely divided solids	Pb, Ni, Na, Al, Cr, S, Si, Sn	Pb NaNO ₃ PbO

FIGURE C.1

Flow Cell Setup

FIGURE C.2

FM01 LC Cell

Flow Diagram

FIGURE C.3

**WSRC Flow Cell #174-9
Pb Cathode, Ni Anode**

FIGURE C.4

**WSRC Flow Cell #174-9
Pb Cathode, Ni Anode**

Charge Coulombs	Volume ml	Moles NO ₂	Moles NO ₃	Total NO ₂ +NO ₃	Moles OH-
0	700.0	0.389	1.251	1.640	1.29
57,100	695.4	0.429	1.146	1.575	
127,300	689.7	0.466	1.095	1.561	
186,000	685.0	0.437	1.045	1.482	
235,300	681.0	0.429	1.034	1.463	
280,500	677.3	0.406	0.994	1.400	
323,100	673.9	0.385	0.956	1.341	
1,382,700	588.3	0.121	0.564	0.685	
1,450,900	582.8	0.110	0.534	0.644	
1,543,000	575.3	0.096	0.507	0.603	
1,597,100	571.0	0.091	0.487	0.578	
1,648,700	566.8	0.087	0.475	0.562	
1,732,500	560.0	0.086	0.454	0.540	
1,807,000	554.0	0.082	0.437	0.519	2.43

CD = 140 mA/cm²
Flow Rate = 1.0 gpm
Temp. = 50C

FIGURE C.5

**WSRC Flow Cell #174-9
Pb Cathode, Ni Anode**

CD = 140 mA/cm²
Flow Rate = 1.0 gpm
Temp. = 50C

FIGURE C.6

**WSRC Flow Cell #174-9
Pb Cathode, Ni Anode**

Charge Coulombs	% N2O	% NH3	% O2	% N2
48,000	2.50	0.00	77.45	4.87
120,800	2.59	0.00	78.50	5.44
177,700	2.90	0.00	75.41	4.64
230,100	2.96	0.16	78.25	6.17
274,900	3.00	0.34	76.16	5.71
315,700	3.10	0.41	76.95	6.17
1,375,800	0.98	4.79	44.58	5.67
1,444,400	0.95	5.13	44.71	7.28
1,592,600	0.88	5.57	40.18	5.72
1,644,700	0.83	5.60	43.34	6.20
1,725,000	0.72	4.69	44.13	7.93
1,800,000	0.73	5.18	41.74	5.15

CD = 140 mA/cm²
Flow Rate = 1.0 gpm
Temp. = 50C

FIGURE C.7

**WSRC Flow Cell #174-9
Pb Cathode, Ni Anode**

CD = 140 mA/cm²
Flow Rate = 1.0 gpm
Temp. = 50C

FIGURE C.8

WSRC Flow Cell #174-16
Ni Cathode, Ni Anode

CD = 140 mA/cm²
Flow Rate = 0.5 gpm
Temp. = 50C

FIGURE C.9

WSRC Flow Cell #174-16 **Ni Cathode, Ni Anode**

Charge Coulombs	Volume ml	Moles NO ₂	Moles NO ₃	Total NO ₂ +NO ₃	Moles OH ⁻
0	700.0	0.396	1.289	1.685	1.20
34,400	698.0	0.371	1.284	1.655	
60,500	696.6	0.359	1.312	1.670	
85,000	695.2	0.349	1.349	1.698	
115,700	693.4	0.340	1.337	1.677	
156,000	691.1	0.323	1.335	1.658	
187,300	689.3	0.314	1.339	1.654	
213,400	687.8	0.300	1.301	1.601	
749,300	657.3	0.225	1.068	1.293	
795,000	654.7	0.222	1.066	1.288	
834,600	652.4	0.218	1.054	1.272	
888,600	649.3	0.216	1.040	1.256	
928,200	647.1	0.212	1.019	1.231	
982,500	644.0	0.196	0.912	1.108	
1,055,100	639.2	0.208	0.878	1.085	
1,032,200	641.2	0.191	0.850	1.041	
1,112,900	636.6	0.209	0.845	1.055	
1,149,800	634.5	0.211	0.844	1.055	
1,187,700	632.3	0.207	0.828	1.036	1.97

CD = 140 mA/cm²
Flow Rate = 0.5 gpm
Temp. = 50C

FIGURE C.10

WSRC Flow Cell #174-16
Ni Cathode, Ni Anode

CD = 140 mA/cm²
Flow Rate = 0.5 gpm
Temp. = 50C

FIGURE C.11

WSRC Flow Cell #174-16
Ni Cathode, Ni Anode

Charge Coulombs	% N2O	% NH3	% O2	% N2
31,600	0.61	0.00	62.81	5.21
57,700	0.95	0.00	60.55	7.05
82,200	0.90	0.10	64.94	4.30
113,500	1.09	0.18	62.91	6.03
150,700	1.28	0.20	64.07	5.46
184,700	1.42	0.33	62.26	7.00
207,100	1.48	0.35	65.10	4.85
740,000	2.17	1.92	67.03	4.00
792,200	1.79	2.39	62.45	7.84
832,300	1.65	2.51	65.74	4.84
885,800	1.74	2.84	64.06	6.29
924,800	1.70	3.01	65.24	5.43
964,500	0.78	1.96	64.39	5.96
1,068,300	1.04	1.06	62.29	6.16
1,109,800	1.09	1.82	65.25	4.42
1,147,300	1.00	1.81	63.04	5.78
1,180,200	0.99	2.02	63.67	3.54

CD = 140 mA/cm²
Flow Rate = 0.5 gpm
Temp. = 50C

FIGURE C.12

WSRC Flow Cell #174-16
Ni Cathode, Ni Anode

CD = 140 mA/cm²
Flow Rate = 0.5 gpm
Temp. = 50C

FIGURE C.13

**WSRC Divided Flow Cell #174-24
Pb Cathode, Pb Anode**

Catholyte = WSRC Complete Synthetic Feed
Anolyte = 1.035 M H₂SO₄
Membrane = Nafion 417 CD = 140 mA/sq. cm.

WSRC Divided Flow Cell #174-24
Pb Cathode, Pb Anode

Charge Coulombs	Volume ml	Moles NO ₂	Moles NO ₃	Total NO ₂ +NO ₃	Moles OH ⁻
0	700.0	0.363	1.166	1.529	1.04
89,800	742.2	0.375	1.027	1.402	
156,800	773.7	0.484	0.857	1.342	
229,700	808.0	0.564	0.713	1.277	
280,600	831.9	0.546	0.626	1.172	
1,304,000	1,312.9	0.299	0.259	0.558	
1,362,200	1,340.2	0.280	0.241	0.521	
1,406,600	1,361.1	0.278	0.244	0.521	
1,487,800	1,399.3	0.266	0.218	0.484	
1,563,800	1,435.0	0.260	0.208	0.468	2.92

Catholyte = WSRC Complete Synthetic Feed

Anolyte = 1.035 M H₂SO₄

Membrane = Nafion 417

FIGURE C.15

**WSRC Divided Flow Cell #174-24
Pb Cathode, Pb Anode**

Catholyte = WSRC Complete Synthetic Feed
Anolyte = 1.035 M H₂SO₄
Membrane = Nafion 417

FIGURE C.16

**WSRC Divided Flow Cell #174-24
Pb Cathode, Pb Anode**

Charge Coulombs	% N2O	% NH3	% O2	% N2
81,100	8.88	0.00	1.76	15.31
147,800	20.64	0.00	2.97	23.63
222,700	14.51	0.00	4.49	12.63
271,500	32.94	0.23	6.58	11.84
1,332,400	0.37	2.86	3.82	4.58
1,377,500	0.48	2.80	5.44	9.98
1,440,300	0.40	2.98	6.89	9.59
1,511,400	0.41	3.07	6.92	8.63
1,562,600	0.38	3.06	4.08	5.79

Catholyte = WSRC Complete Synthetic Feed

Anolyte = 1.035 M H₂SO₄

Membrane = Nafion 417

FIGURE C.17

WSRC Divided Flow Cell #174-24 **Pb Cathode, Pb Anode**

Catholyte = WSRC Complete Synthetic Feed

Anolyte = 1.035 M H₂SO₄

Membrane = Nafion 417

FIGURE C.18

WSRC Flow Cell #174-29
Pb Cathode, Ni Anode

Feed = WSRC Synthetic Feed without Chromium
Temp. = 50C CD = 140 mA/sq. cm.
Flow = 0.7 gpm

FIGURE C.19

WSRC Flow Cell #174-29
Pb Cathode, Ni Anode

Charge Coulombs	Volume ml	Moles NO ₂	Moles NO ₃	Total NO ₂ +NO ₃	Moles OH-
0	700.0	0.405	1.257	1.661	1.26
60,900	695.7	0.505	1.127	1.632	
114,900	691.9	0.567	1.058	1.625	
1,201,000	614.8	0.424	0.369	0.793	
1,267,100	610.2	0.380	0.342	0.722	
1,334,800	605.4	0.341	0.321	0.662	
1,392,300	601.3	0.330	0.323	0.653	
1,460,200	596.5	0.298	0.305	0.602	
1,523,000	592.0	0.272	0.289	0.561	2.08

Feed = WSRC Synthetic Feed without Chromium

Temp. = 50C

Flow = 0.7 gpm CD = 140 mA/sq. cm.

FIGURE C.20

**WSRC Flow Cell #174-29
Pb Cathode, Ni Anode**

Feed = WSRC Synthetic Feed without Chromium
Temp. = 50C
Flow = 0.7 gpm

FIGURE C.21

WSRC Flow Cell #174-29
Pb Cathode, Ni Anode

Charge Coulombs	% N2O	% NH3	% O2	% N2
54,400	3.44	0.16	74.64	6.23
108,500	3.98	0.16	67.03	8.51
1,181,800	2.93	3.95	58.24	6.58
1,259,500	2.79	3.77	56.19	8.33
1,330,700	2.56	4.75	50.52	4.87
1,388,600	2.42	4.82	53.75	7.28
1,453,000	2.17	5.63	53.78	7.59
1,518,100	2.04	5.80	54.20	4.61

Feed = WSRC Synthetic Feed without Chromium

Temp. = 50C

Flow = 0.7 gpm

FIGURE C.22

WSRC Flow Cell #174-29 Pb Cathode, Ni Anode

Feed = WSRC Synthetic Feed without Chromium
Temp. = 50C
Flow = 0.7 gpm

FIGURE C.23

**WSRC Flow Cell #174-33
Pb Cathode, Ni Anode**

Feed = WSRC Synthetic Feed without Ruthenium

Temp. = 50C

Flow = 0.8 gpm CD = 140 mA/sq. cm.

**WSRC Flow Cell #174-33
Pb Cathode, Ni Anode**

Charge Coulombs	Volume ml	Moles NO ₂	Moles NO ₃	Total NO ₂ + NO ₃	Moles OH ⁻
0	700.0	0.384	1.230	1.614	1.22
76,300	696.3	0.489	1.108	1.597	
132,700	693.5	0.481	1.058	1.538	
203,000	690.1	0.466	1.059	1.525	
267,600	686.9	0.426	1.006	1.432	
324,600	684.1	0.403	0.978	1.381	
1,398,900	631.5	0.179	0.210	0.389	
1,469,500	628.0	0.156	0.176	0.332	
1,527,200	625.2	0.138	0.149	0.288	
1,588,200	622.2	0.118	0.123	0.240	2.70

Feed = WSRC Synthetic Feed without Ruthenium

Temp. = 50C

Flow = 0.8 gpm CD = 140 mA/sq. cm.

FIGURE C.25

**WSRC Flow Cell #174-33
Pb Cathode, Ni Anode**

Feed = WSRC Synthetic Feed without Ruthenium
Temp. = 50C
Flow = 0.8 gpm CD = 140 mA/sq. cm.

FIGURE C.26

**WSRC Flow Cell #174-33
Pb Cathode, Ni Anode**

Charge Coulombs	% N2O	% NH3	% O2	% N2
69,400	3.75	0.00	95.06	7.72
132,700	5.47	0.13	93.95	8.67
198,100	5.28	0.38	95.17	7.65
262,500	5.03	0.73	97.19	8.88
318,300	4.99	1.17	99.54	8.56
1,367,000	3.70	8.42	56.04	9.33
1,398,900	3.43	8.32	52.55	5.55
1,523,300	3.29	8.04	50.70	7.17
1,582,100	2.87	8.50	47.04	5.50

Feed = WSRC Synthetic Feed without Ruthenium

Temp. = 50C

Flow = 0.8 gpm CD = 140 mA/sq. cm.

FIGURE C.27

**WSRC Flow Cell #174-33
Pb Cathode, Ni Anode**

FIGURE C.28

**WSRC Flow Cell #174-37
Pb Cathode, Ni Anode**

Feed = WSRC Synthetic Feed

Temp. = 60C

Current Density = 300 mA/sq. cm.

**WSRC Flow Cell #174-37
Pb Cathode, Ni Anode**

Charge Coulombs	Volume ml	Moles NO ₂	Moles NO ₃	Total NO ₂ + NO ₃	Moles OH ⁻
0	700.0	0.409	1.324	1.733	0.97
164,000	687.4	0.418	1.136	1.553	
307,500	676.3	0.366	0.987	1.353	
431,200	666.8	0.327	0.910	1.236	
599,200	653.9	0.273	0.802	1.074	
698,500	646.2	0.246	0.748	0.994	
832,400	635.9	0.218	0.680	0.899	
949,200	626.9	0.200	0.634	0.834	
1,047,500	619.3	0.181	0.587	0.768	2.44

Feed = WSRC Synthetic Feed

Temp. = 60C

Flow = 0.7 gpm CD = 300 mA/sq. cm.

FIGURE C.30

**WSRC Flow Cell #174-37
Pb Cathode, Ni Anode**

Feed = WSRC Synthetic Feed
Temp. = 60C
Current Density = 300 mA/sq. cm.

FIGURE C.31

**WSRC Flow Cell #174-37
Pb Cathode, Ni Anode**

Charge Coulombs	% N2O	% NH3	% O2	% N2
154,000	3.83	1.26	85.19	10.92
279,000	4.80	2.46	76.96	8.82
421,300	3.88	5.01	64.37	8.50
587,600	3.61	6.66	56.74	6.87
689,800	3.46	7.03	51.28	6.41
817,800	3.30	7.66	53.46	3.69
930,200	2.88	8.05	49.32	6.82
999,700	2.73	8.00	48.56	4.46

Feed = WSRC Synthetic Feed

Temp. = 60C

Current Density = 300 mA/sq. cm.

FIGURE C.32

**WSRC Flow Cell #174-37
Pb Cathode, Ni Anode**

Feed = WSRC Synthetic Feed
Temp. = 60C
Current Density = 300 mA/sq. cm.

FIGURE C.33

**WSRC Flow Cell #174-41
Pb Cathode, Ni Anode**

FIGURE C.34

**WSRC Flow Cell #174-41
Pb Cathode, Ni Anode**

Charge Coulombs	Volume ml	Moles NO ₂	Moles NO ₃	Total moles	Moles OH-
0	700.0	0.416	1.343	1.758	1.26
26,400	697.6	0.408	1.280	1.688	
619,000	643.7	0.213	0.967	1.180	
666,200	639.4	0.202	0.950	1.152	
713,700	635.1	0.192	0.932	1.124	
769,100	630.0	0.183	0.916	1.099	
818,600	625.5	0.175	0.893	1.068	
854,700	622.2	0.171	0.864	1.035	
1,458,900	567.2	0.122	0.693	0.815	
1,495,500	563.9	0.118	0.673	0.791	
1,543,200	559.6	0.115	0.650	0.765	2.42

Feed = WSRC Synthetic Feed

CD = 75 mA / sq. cm.

Flow = 0.5 gpm

FIGURE C.35

**WSRC Flow Cell #174-41
Pb Cathode, Ni Anode**

Feed = WSRC Synthetic Feed
Temp = 50°C
Flow = 0.6 gpm CD = 75 mA / sq. cm.

FIGURE C.36

WSRC Flow Cell #174-41
Pb Cathode, Ni Anode

Charge Coulombs	% N2O	% NH3	% O2	% N2
20,500	1.65	0.00	36.81	32.76
616,100	1.00	4.55	46.94	6.30
662,600	0.91	4.92	42.79	3.99
709,300	0.87	5.09	42.61	6.09
762,200	0.88	5.38	45.84	8.33
813,000	0.79	5.11	42.97	6.31
842,800	0.76	4.55	40.95	5.52
1,445,100	0.67	5.94	33.95	
1,492,400	0.64	5.42	34.02	8.34
1,539,800	0.57	5.32	34.79	5.18

Feed = WSRC Synthetic Feed

Temp = 50C

Flow = 0.6 gpm CD = 75 mA/sq. cm.

FIGURE C.37

**WSRC Flow Cell #174-41
Pb Cathode, Ni Anode**

Feed = WSRC Synthetic Feed
CD = 75 mA / sq. cm.
Flow = 0.5 gpm

FIGURE C.38

WSRC Flow Cell #174-45
Pb Cathode, Ni Anode
Temp = 80 C

Feed = WSRC Synthetic Feed
CD = 300 mA / sq. cm.
Flow = 0.5 gpm with polypropylene separator

FIGURE C.39

WSRC Flow Cell #174-45
Pb Cathode, Ni Anode
Temp = 80 C

Charge Coulombs	Volume ml	Moles NO ₂	Moles NO ₃	Total moles	Moles OH ⁻
0	700.0	0.395	1.276	1.671	0.92
165,600	683.0	0.462	0.964	1.426	
313,700	667.8	0.428	0.836	1.264	
411,200	657.7	0.393	0.726	1.119	
530,800	645.4	0.361	0.593	0.953	
656,000	632.6	0.340	0.526	0.866	
759,100	622.0	0.310	0.469	0.779	
813,600	616.4	0.286	0.425	0.711	
953,700	602.0	0.267	0.332	0.599	2.19

Feed = WSRC Synthetic Feed

CD = 300 mA / sq. cm.

Flow = 0.5 gpm with polypropylene separator

FIGURE C.40

WSRC Flow Cell #174-45
Pb Cathode, Ni Anode
Temp = 80 C

Feed = WSRC Synthetic Feed
CD = 300 mA / sq. cm.
Flow = 0.5 gpm with polypropylene separator

WSRC Flow Cell #174-45
Pb Cathode, Ni Anode
Temp = 80 C

Charge Coulombs	% N2O	% NH3	% C2	% N2
204,600	4.37	5.45	74.14	3.10
302,200	3.70	8.13	64.79	4.39
389,000	3.49	10.14	58.89	3.25
517,000	2.26	11.49	58.19	4.38
642,200	2.31	14.57	50.39	2.94
750,000	2.08	14.90	47.34	3.84
802,200	1.98	12.94	46.84	3.29
916,600	1.80	13.83	50.48	5.05

Feed = WSRC Synthetic Feed

CD = 300 mA / sq. cm.

Flow = 0.5 gpm with polypropylene separator

FIGURE C.42

WSRC Flow Cell #174-45
Pb Cathode, Ni Anode

Feed = WSRC Synthetic Feed
 CD = 300 mA / sq. cm.
 Flow = 0.5 gpm with polypropylene separator

FIGURE C.43

WSRC Flow Cell #174-48
Pb Cathode, Ni Anode
Temp = 80 C

Feed = WSRC Synthetic Feed
CD = 300 mA / sq. cm.
Flow = 0.6 gpm with polypropylene separator

FIGURE C.44

WSRC Flow Cell #174-48
Pb Cathode, Ni Anode
Temp = 80 C

Charge Coulombs	Volume ml	Moles NO ₂	Moles NO ₃	Total moles	Moles OH-
0	700.0	0.419	1.343	1.762	1.20
162,000	686.4	0.460	1.099	1.559	
386,200	667.6	0.450	0.875	1.325	
541,500	654.6	0.399	0.717	1.116	
644,000	646.0	0.374	0.635	1.009	
754,800	636.7	0.332	0.549	0.881	
850,000	628.7	0.302	0.505	0.807	
953,700	620.0	0.252	0.430	0.682	2.24

Feed = WSRC Synthetic Feed

CD = 300 mA / sq. cm.

Flow = 0.6 gpm with polypropylene separator

FIGURE C.45

WSRC Flow Cell #174-48
Pb Cathode, Ni Anode
Temp = 80 C

Feed = WSRC Synthetic Feed
CD = 300 mA / sq. cm.
Flow = 0.6 gpm with polypropylene separator

FIGURE C.46

WSRC Flow Cell #174-48
Pb Cathode, Ni Anode
Temp = 80 C

Charge Coulombs	% N2O	% NH3	% O2	% N2
367,500	2.49	6.12	63.47	4.95
529,400	1.83	6.46	58.53	6.43
628,600	2.26	11.25	58.76	5.71
745,000	1.83	12.66	57.78	5.78
838,300	1.44	11.13	50.38	4.62

Feed = WSRC Synthetic Feed
CD = 300 mA / sq. cm.
Flow = 0.6 gpm with polypropylene separator:

FIGURE C.47

WSRC Flow Cell #174-48
Pb Cathode, Ni Anode

Feed = WSRC Synthetic Feed
CD = 300 mA / sq. cm.
Flow = 0.6 gpm with polypropylene separator

FIGURE C.48

WSRC Flow Cell #174-51
Pb Cathode, Ni Anode
Temp = 80 C

Feed = WSRC Synthetic Feed
CD = 600 mA / sq. cm.
Flow = 0.6 gpm with polypropylene separator

FIGURE C.49

WSRC Flow Cell #174-51
Pb Cathode, Ni Anode
Temp = 80 C

Charge Coulombs	Volume ml	Moles NO ₂	Moles NO ₃	Total NO ₂ +NO ₃	Moles OH-
0	700.0	0.412	1.331	1.742	1.15
248,200	682.1	0.552	0.881	1.432	
372,800	673.0	0.518	0.775	1.293	
518,500	662.5	0.422	0.720	1.142	
675,400	651.2	0.316	0.603	0.919	
789,000	643.0	0.276	0.530	0.807	
954,500	631.0	0.230	0.363	0.593	2.51

Feed = WSRC Synthetic Feed

CD = 600 mA / sq. cm.

Flow = 0.6 gpm with polypropylene separator

FIGURE C.53

WSRC Flow Cell #174-51
Pb Cathode, Ni Anode
Temp = 80 C

Feed = WSRC Synthetic Feed
CD = 600 mA / sq. cm.
Flow = 0.6 gpm with polypropylene separator

FIGURE C.51

WSRC Flow Cell #174-51
Pb Cathode, Ni Anode
Temp = 80 C

Charge Coulombs	% N2O	% NH3	% O2	% N2
223,000	6.16	3.42	72.57	8.37
349,100	5.77	5.99	66.81	11.04
499,500	5.06	9.58	73.43	11.73
554,000	3.63	11.41	57.48	9.40
779,800	2.79	11.72	62.80	10.07
891,400	2.87	13.66	64.97	10.98

Feed = WSRC Synthetic Feed

CD = 600 mA / sq. cm.

Flow = 0.6 gpm with polypropylene separator

FIGURE C.52

WSRC Flow Cell #174-51
Pb Cathode, Ni Anode
Temp = 80 C

Feed = WSRC Synthetic Feed

CD = 600 mA / sq. cm.

Flow = 0.6 gpm with polypropylene separator

FIGURE C.53

WSRC Flow Cell #174-54

Pb Cathode, Ni Anode

Temp = 87 C

Feed = WSRC Synthetic Feed

CD = 600 mA / sq. cm.

Flow = 0.7 gpm with polypropylene separator

WSRC Flow Cell #174-54
Pb Cathode, Ni Anode
Temp = 87 C

Charge Coulombs	Volume ml	Moles NO ₂	Moles NO ₃	Total NO ₂ +NO ₃	Moles OH-
0	700.0	0.415	1.354	1.769	1.04
144,100	687.7	0.469	1.153	1.622	
342,600	670.8	0.513	0.836	1.349	
490,800	658.1	0.490	0.692	1.182	
718,200	638.7	0.395	0.557	0.952	
885,100	624.5	0.297	0.445	0.743	
992,000	615.4	0.279	0.434	0.713	
1,242,900	594.0	0.206	0.357	0.563	2.45

Feed = WSRC Synthetic Feed

CD = 600 mA / sq. cm.

Flow = 0.7 gpm with polypropylene separator

FIGURE C.55

WSRC Flow Cell #174-54
Pb Cathode, Ni Anode
Temp = 87 C

Feed = WSRC Synthetic Feed
CD = 600 mA / sq. cm.
Flow = 0.7 gpm with polypropylene separator

FIGURE C.56

WSRC Flow Cell #174-54
Pb Cathode, Ni Anode
Temp = 87 C

Charge Coulombs	% N2O	% NH3	% O2	% N2
125,400	3.88	2.98	71.66	5.34
320,000	3.52	8.15	72.20	8.72
464,000	2.70	11.98	65.11	8.34
696,800	1.48	13.57	49.93	5.44
861,800	1.01	12.85	45.90	4.01
973,400	0.81	12.15	43.95	3.30
1,213,900	0.59	9.39	42.99	3.63

Feed = WSRC Synthetic Feed

CD = 600 mA / sq. cm.

Flow = 0.7 gpm with polypropylene separator

FIGURE C.57

WSRC Flow Cell #174-54
Pb Cathode, Ni Anode
Temp = 87 C

Feed = WSRC Synthetic Feed

CD = 600 mA / sq. cm.

Flow = 0.7 gpm with polypropylene separator

FIGURE C.58

WSRC Flow Cell #174-57
Ni Cathode, Ni Anode
Temp = 80 C

Feed = WSRC Synthetic Feed
CD = 600 mA / sq. cm.
Flow = 0.5 gpm with polypropylene separator

FIGURE C.59

WSRC Flow Cell #174-57
Ni Cathode, Ni Anode
Temp = 80 C

Charge Coulombs	Volume ml	Moles NO ₂	Moles NO ₃	Total NO ₂ +NO ₃	Moles OH-
0	700.0	0.410	1.317	1.727	1.04
105,500	689.1	0.329	1.318	1.647	
257,500	673.3	0.243	1.313	1.556	
522,200	645.9	0.231	1.303	1.533	
686,700	628.9	0.266	1.099	1.365	
819,200	615.1	0.253	0.899	1.152	
937,500	602.9	0.258	0.848	1.106	
1,042,400	592.0	0.253	0.809	1.062	1.87

Feed = WSRC Synthetic Feed

CD = 600 mA / sq. cm.

Flow = 0.5 gpm with polypropylene separator

FIGURE C.60

WSRC Flow Cell #174-57
Ni Cathode, Ni Anode
Temp = 80 C

Feed = WSRC Synthetic Feed
CD = 600 mA / sq. cm.
Flow = 0.5 gpm with polypropylene separator

FIGURE C.61

WSRC Flow Cell #174-57
Ni Cathode, Ni Anode
Temp = 80 C

Charge Coulombs	% N2O	% NH3	% O2	% N2
236,500	0.32	0.75	33.05	4.70
512,300	1.91	1.21	45.95	5.21
675,300	2.96	1.80	49.70	6.98
806,600	2.65	2.36	47.93	6.65
928,700	2.03	2.97	46.54	4.82
1,027,000	1.52	3.68	45.29	5.07

Feed = WSRC Synthetic Feed

CD = 600 mA / sq. cm.

Flow = 0.5 gpm with polypropylene separator

FIGURE C.62

WSRC Flow Cell #174-57
Ni Cathode, Ni Anode
Temp = 80 C

Feed = WSRC Synthetic Feed
CD = 600 mA / sq. cm.
Flow = 0.5 gpm with polypropylene separator

FIGURE C.63

WSRC Flow Cell #174-62
Ni Cathode, Ni Anode
Temp = 80 C

Feed = WSRC Synthetic Feed
CD = 300 mA / sq. cm.
Flow = 0.8 gpm with polypropylene separator

WSRC Flow Cell #174-62
Ni Cathode, Ni Anode
Temp = 80 C

Charge Coulombs	Volume ml	Moles NO ₂	Moles NO ₃	Total NO ₂ +NO ₃	Moles OH ⁻
0	700.0	0.401	1.301	1.702	1.09
190,000	682.0	0.300	1.348	1.648	
281,100	673.3	0.300	1.342	1.641	
374,500	664.4	0.290	1.218	1.508	
511,900	651.4	0.313	1.140	1.453	
624,200	640.7	0.307	0.997	1.304	
753,700	628.4	0.293	0.890	1.184	
947,500	610.0	0.250	0.777	1.027	1.91

Feed = WSRC Synthetic Feed

CD = 300 mA / sq. cm.

Flow = 0.8 gpm with polypropylene separator

FIGURE C.65

WSRC Flow Cell #174-62
Ni Cathode, Ni Anode
Temp = 80 C

Feed = WSRC Synthetic Feed
 CD = 300 mA / sq. cm.
 Flow = 0.8 gpm with polypropylene separator

FIGURE C.66

WSRC Flow Cell #174-62
Ni Cathode, Ni Anode
Temp = 80 C

Charge Coulombs	% N2O	% NH3	% O2	% N2
170,600	0.39	0.78	32.78	1.43
270,000	1.51	0.94	40.83	4.72
365,200	2.09	0.97	44.86	5.17
500,000	3.01	1.31	49.14	8.32
613,700	3.36	1.50	50.13	8.02
742,000	3.38	1.70	48.21	8.22
915,600	2.31	1.99	43.60	6.26

Feed = WSRC Synthetic Feed

CD = 300 mA / sq. cm.

Flow = 0.8 gpm with polypropylene separator

FIGURE C.67

WSRC Flow Cell #174-62
Ni Cathode, Ni Anode
Temp = 80 C

Feed = WSRC Synthetic Feed

CD = 300 mA / sq. cm.

Flow = 0.8 gpm with polypropylene separator

FIGURE C.68

WSRC Flow Cell #174-66

Ni Cathode, Ni Anode

Temp = 80 C Cathode not cleaned before run.

Feed = WSRC Synthetic Feed

CD = 300 mA/sq. cm.

Flow = 0.7 gpm with polypropylene separator

WSRC Flow Cell #174-66

Ni Cathode, Ni Anode

Temp = 80 C Cathode not cleaned before run.

Charge Coulombs	Volume ml	Moles NO2	Moles NO3	Total NO2+NO3	Moles OH-
0	700.0	0.412	1.329	1.741	1.13
137,500	687.0	0.315	1.355	1.671	
311,100	670.6	0.269	1.461	1.730	
389,100	663.2	0.216	1.444	1.659	
485,900	654.0	0.178	1.475	1.653	
743,100	629.7	0.203	1.201	1.405	
873,000	617.4	0.209	1.068	1.276	
1,025,600	603.0	0.197	0.952	1.149	1.82

Feed = WSRC Synthetic Feed

CD = 300 mA/sq. cm.

Flow = 0.7 gpm with polypropylene separator

FIGURE C.70

WSRC Flow Cell #174-66

Ni Cathode, Ni Anode

Temp = 80 C Cathode not cleaned before run.

Feed = WSRC Synthetic Feed

CD = 300 mA/sq. cm.

Flow = 0.7 gpm with polypropylene separator

FIGURE C.71

WSRC Flow Cell #174-66

Ni Cathode, Ni Anode

Temp = 80 C Cathode not cleaned before run.

Charge Coulombs	% N2O	% NH3	% O2	% N2	% H2
117,900					65
266,900	0.88	0.58	36.41	4.21	
376,600	0.00	0.85	34.09	4.39	
476,900			35.60	1.41	
716,100	2.54	2.30	53.79	8.88	
862,700	2.10	2.97	51.98	7.20	
999,000					46

Feed = WSRC Synthetic Feed

CD = 300 mA/sq. cm.

Flow = 0.7 gpm with polypropylene separator

WSRC Flow Cell #174-66

Ni Cathode, Ni Anode

Temp = 80 C Cathode not cleaned before run.

Feed = WSRC Synthetic Feed

CD = 300 mA/sq. cm.

Flow = 0.7 gpm with polypropylene separator

FIGURE C.73

WSRC Flow Cell #174-70
Pb Cathode, Ni Anode
Temp = 80 C Long term run.

Feed = WSRC Synthetic Feed
CD = 600 mA/sq. cm.
Flow = 1.0 gpm with polypropylene separator

WSRC Flow Cell #174-70
Pb Cathode, Ni Anode
Temp = 80 C Long term run.

Charge Coulombs	Volume ml	Moles NO ₂	Moles NO ₃	Total NO ₂ +NO ₃	Moles OH-
0	9,870	5.596	18.052	23.649	18.20
426,400	9,822	5.451	17.856	23.307	
1,166,000	9,738	4.840	17.099	21.939	
6,388,200	9,144	2.972	16.240	19.212	
6,842,200	9,093	2.846	15.976	18.822	
7,422,500	9,027	2.771	15.896	18.667	
7,956,000	8,966	2.672	15.843	18.515	
12,598,200	8,439	2.127	14.819	16.945	
13,422,200	8,345	2.161	14.504	16.665	
14,470,600	8,226	2.098	14.083	16.181	24.28

Feed = WSRC Synthetic Feed

CD = 600 mA/sq. cm.

Flow = 1.0 gpm with polypropylene separator

FIGURE C.75

WSRC Flow Cell #174-70
Pb Cathode, Ni Anode
Temp = 80 C Long term run.

Feed = WSRC Synthetic Feed
 CD = 600 mA/sq. cm.
 Flow = 1.0 gpm with polypropylene separator

FIGURE C.76

**WSRC Flow Cell #174-70
Pb Cathode, Ni Anode
Temp = 80 C Long term run.**

Charge Coulombs	% N2O	% NH3	% O2	% N2	% H2
393,400					47.35
1,131,200	0.88	1.27	46.17	2.35	
6,360,100					57.73
6,907,700	0.56	4.75	40.25	1.08	
7,464,600	0.46	4.65	38.25	2.58	
7,984,100					60.24
12,696,800					55.87
13,445,600	0.89	7.91	40.49	2.50	
14,470,600					55.75

Feed = WSRC Synthetic Feed

CD = 600 mA/sq. cm.

Flow = 1.0 gpm with polypropylene separator

FIGURE C.77

WSRC Flow Cell #174-70
Pb Cathode, Ni Anode
Temp = 80 C Long term run.

Feed = WSRC Synthetic Feed
CD = 600 mA/sq. cm.
Flow = 1.0 gpm with polypropylene separator

FIGURE C. 78

WSRC Flow Cell #174-70
Pb Cathode, Ni Anode
Temp = 80 C Long term run.

Charge (coulombs)	% CE-N2	% CE-N2+NH3	% CE-N2+NH3+N2O
426,400	32.11		
1,166,000	58.22	80.27	74.75
6,388,200	25.58		
6,842,200	26.27		
7,422,500	25.03	40.24	39.43
7,956,000	24.03		
12,598,200	20.35		
13,422,200	20.16	33.17	32.33
14,470,600	20.23		

Feed = WSRC Synthetic Feed

CD = 600 mA/sq. cm.

Flow = 1.0 gpm with polypropylene separator

FIG C.79

FIGURE C.80

WSRC Flow Cell # 174-70 Gas Flow Rate Plot

Gas volume measured by water displacement.
CD = 600 mA/sq. cm.
Long Term run

FIGURE C.81

WSRC Voltage vs Current Plot Pb or Ni Cathode

ICI FM01 LC Cell with WSRC Synthetic mix
Celguard 3401 Polypropylene Separator

FIGURE C.82

**WSRC Voltage vs Flow Plot
Pb Cathode, Ni Anode**

ICI FM01 LC Cell with 10L WSRC Synthetic mix
Celguard 3401 Polypropylene Separator
CD = 600 mA/sq. cm. Temp = 80C

FIGURE C.83

Instantaneous Current Efficiencies

Runs 174-54 & 174-57

CD = 600 mA/sq. cm.
Polypropylene separator
Temp = 80C

The Westinghouse Savannah River Company (WSRC) contracted The Electrosynthesis Co., Inc. to investigate electrochemical methods to remove nitrates and nitrites from waste solutions. These solutions contain high concentrations of nitrate, nitrite, sodium hydroxide and aluminate, as well as smaller amounts of several other contaminants. The goal of the R&D program was to provide enough information for an engineering study. This report summarizes the R&D efforts undertaken by ESC.

Two approaches to the removal of nitrate/nitrite have been studied; electrolytic reduction and electrochemical separation. The separation approach entails the recovery of nitric acid and sodium hydroxide from the waste using a three or four compartment electrochemical cell. This approach would also greatly reduce the remaining waste stream volume due to water transport across the ion exchange membranes. However, the stability of the anion exchange membranes in the strongly alkaline WSRC waste remains a concern. We have investigated the feasibility of the membrane separation process, paying particular attention to membrane stability, current efficiency, and membrane fouling.

The electrolytic reduction process involves the reduction of nitrate and nitrite at a cathode, producing ammonia and nitrogen gases. ESC has performed an extensive study of this process. Initial efforts focused on determining the best electrode material for the reduction. These studies were performed in a small divided glass cell using a simplified synthetic solution containing only nitrate, nitrite and sodium hydroxide. Current efficiencies for the reaction, and product composition were determined. Further parameters such as current density, the use of ion exchange membranes, temperature, and the buildup of metal precipitates on the cathode were investigated in a flow cell using the two more promising cathode materials identified in the glass cell

END

**DATE
FILMED**

4 / 24 / 92