LA-UR- 92-693

Title:

The Effect of the Light Round-Trip Time
on the Performance of an Adaptive Optics
Turbulence Compensation System

LA-UR--92-693

DE92 011273

Author(s):

Phillip Stroud
Strategic Systems Engineering Group

Submitted to:

Final Report
February 24, 1992

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Los Alamos
NATIONAL LABORATORY

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the University of California for the U.S. Department of Energy under contract W-7405-ENG-36. By acceptance of this article, the publisher recognizes that the U.S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. The Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy.

Form No. 816-115
81-2629-110-01

The Effect of the Light Round-Trip Time on the Performance of an Adaptive Optics Turbulence Compensation System

Phillip Stroud

Los Alamos National Laboratory, Strategic Systems Engineering Group

February 24, 1992

1. Introduction. The propagation of a laser beam through atmospheric turbulence can, under many circumstances, be compensated to near diffraction limited levels, by use of an adaptive optics system. In the ideal case, a beacon light source is generated at the aimpoint. This light traverses through the turbulent path back to the aperture. The distribution of phase perturbations in the aperture plane is sensed, and the reverse of this phase is applied to the outgoing beam. When the turbulent path is long (e.g. a few hundred kilometers), and the effective wind speed is high (such as is the case when the laser is based on a plane, with airspeeds around 200 m/s), the performance of the adaptive optics system can be significantly degraded due to the time delay from when the beacon samples the turbulence, until the beam propagates through the turbulence. This effect has not been treated in the past, because for astronomical applications, the time delays due to the round trip time of light are too short (tens of microseconds) to cause problems.

This paper presents an analysis of the anisoplanatic effect of the round trip time of light. A formulation of the phase variance has been constructed for this effect. The time response of the adaptive optics system (i.e. servo bandwidth) is intimately related to the light round trip time effect, and is included in the analysis. Results are first obtained for the large aperture limit, and then the effects of finite aperture size are treated. A set of scaling relationships have been found that enable the formulation to be cast in a form that is insensitive to the turbulence strength profile along the propagation path.

2. Phase Variance Formulation. A formulation for the Strehl ratio for a focused compensated beam propagating through turbulence, was developed in a parent paper [LAUR 92-479]. That formulation can be applied to the anisoplanatic effect caused

by the finite speed of light. In the case that amplitude perturbations are negligible and the Strehls are greater than about 0.3 (the Marechal limit), the Strehl was given by

$$\mathcal{S} \equiv \frac{\langle I \rangle}{I_{DL}} = \exp(-\int_A \langle \phi_A^2 \rangle + \langle \int_A \int_B \phi_A \phi_B \rangle) \equiv \exp(-\sigma_\phi^2) \quad [1]$$

ϕ_A is the phase error at position $\vec{\rho}_A$ in the aperture plane. It is the phase perturbation due to turbulence for light propagating from $\vec{\rho}_A$ to the aimpoint, minus the phase correction applied at $\vec{\rho}_A$. The average over the aperture is designated by $\int_A$. The phase variance is the negative of the argument of the exponential, i.e. σ_ϕ^2 .

For a perfect sensor and deformable mirror, using a beacon source located at the aimpoint, the applied phase correction will be the phase increment sensed in the beacon light arriving at $\vec{\rho}_A$. The effect that will be treated here is the delay between the time the beacon samples a given turbule and the time the outgoing beam propagates through the turbule. During this delay, the turbule will move due to an effective perpendicular wind, $w(z)$. The outgoing beam will thus propagate through a different turbulence field than the beacon light. This delay will have two components. There is the round trip time of light, given by twice the distance from the aperture to the turbule divided by the speed of light. There will also be a delay due to the finite time between receipt of the beacon signal and emission of the compensated beam. This second delay represents the combined effects of a finite beacon sensor frame time, a finite processing time, and/or a finite bandwidth AO control loop for the deformable mirror.

In the notation of the previous paper, the phase perturbation received at time 0, at aperture position $\vec{\rho}_A$, is given by

$$\phi_A^{IN}(0) = k_0 \int_0^L dz \sqrt{0.066 C_n^2(z_0)} \int \frac{d\vec{k}}{k^{11/6}} \left[\cos(\vec{k}_\perp \cdot \vec{\rho}_A t/L + k_{||}(z-z_0) - \vec{k}_\perp \cdot \vec{w}z/c + \phi(\vec{k}, z_0)) \right] \quad [2]$$

while the phase perturbation on the outgoing light, emitted at time τ , is given by

$$\phi_A^{OUT}(\tau) = k_0 \int_0^L dz \sqrt{0.066 C_n^2(z_0)} \int \frac{d\vec{k}}{k^{11/6}} \left[\cos(\vec{k}_\perp \cdot \vec{\rho}_A t/L + k_{||}(z-z_0) + \vec{k}_\perp \cdot \vec{w}z/c + \vec{k}_\perp \cdot \vec{w}\tau + \phi(\vec{k}, z_0)) \right] \quad [3]$$

k_0 is the laser wavenumber in vacuum, $2\pi/\lambda$. z is the distance along the propagation path, where $z=0$ at the aperture, and $z=L$ at the aimpoint. z_0 is an arbitrary point in the vicinity of

z. C_n^2 is the index of refraction structure coefficient, which characterizes the strength of the turbulence. By definition, the expected value of the square of the difference of index of refraction at two points separated by a distance $\vec{r}$ is $\langle (n(\vec{r}+\vec{r}')-n(\vec{r}'))^2 \rangle = C_n^2 r^{2/3}$. $\vec{k}$ is the wavenumber of Fourier cosine expansion component of the turbulence. t is $L-z$. $\vec{w}$ is the effective wind speed as a function of z , with which the turbulence is blowing across the path. $\varphi(\vec{k}, z_0)$ is the phase of the turbulence component, which is a uniformly distributed random variable.

The compensated phase error, obtained by subtracting the phase perturbation received at time 0 from the phase perturbation of the outgoing beam emitted at time τ , is then

$$\phi_A(\tau) = k_0 \int_0^L dz \sqrt{0.066 C_n^2(z_0)} \int \frac{d\vec{k}}{k^{11/6}} \left\{ \left[\cos(\vec{k}_\perp \cdot \vec{\rho}_A/L + k_{||}(z-z_0) - \vec{k}_\perp \cdot \vec{w}z/c + \varphi(\vec{k}, z_0)) \right] - \left[\cos(\vec{k}_\perp \cdot \vec{\rho}_A/L + k_{||}(z-z_0) + \vec{k}_\perp \cdot \vec{w}z/c + \vec{k}_\perp \cdot \vec{w}\tau + \varphi(\vec{k}, z_0)) \right] \right\} \quad [4]$$

Following the development presented in the previous paper, the phase variance is found to be

$$\sigma_\phi^2 = 1.303 k_0^2 \int_0^L dz C_n^2(z) \int \frac{dk_\perp}{k_\perp^{8/3}} \left\{ 1 - \left[\frac{2 J_1(k_\perp R t/L)}{(k_\perp R t/L)} \right]^2 \right\} \left[2 - J_0(k_\perp w(\tau - 2z/c)) - J_0(k_\perp w(\tau + 2z/c)) \right] \quad [5]$$

In the limit of large aperture, the J_1 term of Eq[5] goes to zero. The phase variance is then

$$\begin{aligned} \lim_{R \rightarrow \infty} \sigma_\phi^2 &= 1.303 k_0^2 \int_0^L dz C_n^2(z) \int \frac{dk_\perp}{k_\perp^{8/3}} \left[2 - J_0(k_\perp w(\tau - 2z/c)) - J_0(k_\perp w(\tau + 2z/c)) \right] \\ &= 1.457 k_0^2 \int_0^L dz C_n^2(z) w^{5/3} \tau^{5/3} \left[\left| 1 - \frac{2z}{\tau c} \right|^{5/3} - \left(1 + \frac{2z}{\tau c} \right)^{5/3} \right] \quad [6] \end{aligned}$$

3. Large Aperture, Infinite Light Speed, Finite Bandwidth Case. In the limiting case where the speed of light goes to infinity, the phase variance is

$$\begin{aligned}\lim_{R; c \rightarrow \infty} \sigma_{\phi}^2 &= (20.13\tau)^{5/3} \left[0.01956 k_o^2 \int_0^L dz C_n^2(z) w^{5/3} \right] \\ &= (20.13\tau)^{5/3} f_o^{5/3}\end{aligned}\quad [7]$$

where f_o is Greenwood's frequency, given by

$$f_o = \left[0.01956 k_o^2 \int_0^L dz C_n^2(z) w^{5/3} \right]^{3/5} \quad [8]$$

The delay time, τ , can thus be interpreted in terms of the AO servo bandwidth. For an AO system which perfectly compensates all temporal fluctuations with frequencies below f_c , but doesn't respond to higher frequencies (i.e. a bandpass filter with a sharp cut-off at frequency f_c), the response is equivalent to using a delay time of $1/(20.13f_c)$. For a more realistic RC filter, with 3dB bandwidth of f_{3dB} (i.e. a bandpass filter $(f/f_{3dB})^2/[1+(f/f_{3dB})^2]$), the response is equivalent to using a delay time of $2.69/(20.13f_{3dB})$.

4. Large Aperture, Finite Light Speed, Infinite Bandwidth Case. In the limit of large aperture and zero delay time (i.e. infinite AO servo bandwidth), the phase variance including the finite speed of light is given by

$$\begin{aligned}\lim_{R \rightarrow \infty} \sigma_{\phi}^2 &= 2.91 k_o^2 \int_0^L dz C_n^2(z) w^{5/3} (2z/c)^{5/3} \\ &= (20.13 \ 2L/c)^{5/3} f_s^{5/3}\end{aligned}\quad [9]$$

where a new characteristic frequency, f_s , is defined by

$$f_s = \left[0.01956 k_o^2 \int_0^L dz C_n^2(z) (wz/L)^{5/3} \right]^{3/5} \quad [10]$$

As an example, for the Hufnagel-Valley 5/7 turbulence profile, using a light wavelength of $2.314 \mu\text{m}$, propagating from an altitude of 41kft to an aimpoint located at a cross-range of 400 km and an altitude of 25 km, with the effective wind speed given by $(200 \text{ m/s})(L-z)/L$, this frequency is found to be 17.96 Hz. This gives a phase variance (including piston) of

0.941 rad², corresponding to a Strehl of 0.39. This phase variance scales with wavelength to the minus six fifths power.

5. Large Aperture, Finite Light Speed, Finite Bandwidth Case. For the large aperture limit (or when the piston component is not removed) for a given turbulence profile, a normalized phase variance can be expressed as a function of a single parameter. The phase variance is normalized to the infinite bandwidth result

$$\lim_{R \rightarrow \infty} \frac{\sigma_\phi^2}{(20.13 f_s 2L/c)^{5/3}} = \frac{\int_0^L \frac{dz}{L} C_n^2(z) w^{5/3} [|\tau c/2L - z/L|^{5/3} - (\tau c/2L - z/L)^{5/3}]}{2 \int_0^L \frac{dz}{L} C_n^2(z) w^{5/3} (z/L)^{5/3}} \quad [11]$$

To proceed any further, the turbulence profile, $C_n^2(z)$, must be specified. Three cases have been treated: a uniform profile, a delta function at an arbitrary position along the path, and a fairly well behaved two parameter profile. The wind speed profile will be taken as $w=v(L-z)/L$. In addition, the following variables give a more compact notation:

$$y = \lim_{R \rightarrow \infty} \frac{\sigma_\phi^2}{(20.13 f_s 2L/c)^{5/3}} = \text{normalized phase variance} \quad [12]$$

$$x \equiv \frac{\tau f_o c}{2L f_s} = \text{normalized delay time} \quad [13]$$

With the uniform profile, $C_n^2(z)$ is constant along the path and can be taken outside the z integral. In this case, $f_o/f_s = 3.115$, and the normalized phase variance can be written

$$y = \frac{\int_0^L \frac{dz}{L} (1-z/L)^{5/3} [0.321 x - z/L]^{5/3} - (0.321 x + z/L)^{5/3}}{2 \int_0^L \frac{dz}{L} (1-z/L)^{5/3} (z/L)^{5/3}} \quad [14]$$

The normalized phase variance obtained by integration of Eq[14], is shown in Fig.1, expressed as a function of the single parameter, $x = \tau f_0 c / (2L f_s)$. The uniform profile gives the middle line in Fig.1.

Figure 1. The normalized phase variance (including piston) including the finite speed of light and the AO bandwidth. The phase variance is normalized to the infinite bandwidth phase variance. The three cases shown are in ascending order, the delta function turbulence profile, a uniform turbulence profile, and a turbulence profile localized near the aperture ($p=50$). The AO bandwidth is represented by a normalized delay time, depending on Greenwood's frequency, another characteristic frequency defined in the text, and the light round trip time.

Another profile which leads to simplifications in the integrals, is that of a delta function, i.e. $C_n^2(z) = \delta(z-z_0) C_n^2$. In this case, $(f_0/f_s) = L/z_0$, and the normalized phase variance is given by

$$y = \frac{1}{2} [|x - 1|^{5/3} - (x + 1)^{5/3}] \quad [15]$$

This normalized phase variance is shown as the lower line of Fig.1, again as a function of the parameter $x = \tau f_0 c / (2L f_s)$.

A third turbulence profile has been constructed which allows a large class of profiles to be simulated. The profile is given by

$$C_n^2(z) = (1-z/L)^p (z/L)^q C_n^2 / B(1+p, 1+q). \quad [16]$$

where p and q are adjustable parameters which determine the profile, and $B(m,n) = \Gamma(m)\Gamma(n)/\Gamma(m+n)$ is the Beta function. For $p=q=0$, this formulation gives a uniform profile. When p or q are large, this formulation gives a delta function located at $z = Lq/(p+q)$. When the turbulence is localized near the aperture, with something like an exponential fall-off with distance, the profile can be simulated by setting $q=0$, and $p=L/(\text{e-folding length of the actual profile})$. For zenith propagation from the ground, p will typically have values of 200 to 4000. For near horizontal propagation from an airplane to a target at 25 to 50 km altitude, p will have values of 2 to 50. For the case of $q=0$, $(f_s/f_0) = [(p+8/3)B(8/3, p+8/3)]^{3/5}$. The normalized phase variance is then

$$y = \frac{\int_0^L \frac{dz}{L} (1-z/L)^{p+5/3} [|[(p+\frac{8}{3})B(\frac{8}{3}, p+\frac{8}{3})]^{3/5} x - z/L|^{5/3} - ([(p+\frac{8}{3})B(\frac{8}{3}, p+\frac{8}{3})]^{3/5} x + z/L)^{5/3}]}{2 B(\frac{8}{3}, p+\frac{8}{3})} \quad [17]$$

The normalized phase variance obtained by numerical integration of Eq[17], is shown in Fig.1, again expressed as a function of the single parameter, $x = \tau f_0 c / (2L f_s)$, for the case of $p=50$. This profile gives the upper line in Fig.1. There is little difference between this case and the uniform profile case.

6. Finite Aperture. Finite Light Speed. Infinite Bandwidth Case.

When the aperture size is finite, the J_1 term of Eq[5] must be retained. The case of sufficiently large bandwidth will be treated, so that $\tau=0$. With a delta function turbulence profile, the normalized phase variance with piston removed will be

$$\begin{aligned} y &= 0.8942 \int \frac{d\mu}{\mu^{8/3}} \left\{ 1 - \left[\frac{2J_1(\mu\xi)}{\mu\xi} \right]^2 \right\} [1 - J_0(\mu)] \\ &= K(\xi) \end{aligned} \quad [18]$$

where $\xi \equiv \frac{1.59 D c}{20.13 f_s r_0 2L}$ is a normalized aperture, and r_0 is Fried's atmospheric coherence length for the path from 0 to L , defined by

$$r_0 \equiv \left[\frac{2.91}{6.88} k_0^2 \int_0^L dz C_n^2(z)(1-z/L)^{5/3} \right]^{-3/5} \quad [19]$$

The normalized phase variance obtained by numerical integration of Eq[18], is shown in Fig.2, expressed as a function of the normalized aperture.

In the limit of small normalized aperture, the phase variance approaches the asymptotic value of

$$\sigma_\phi^2 = 2.066 (D / r_0)^{5/3} \text{ for small } \frac{1.59 D c}{20.13 f_s r_0 2L} \quad [20]$$

This phase variance is exactly twice the phase variance of uncompensated turbulence. When the normalized aperture is sufficiently small, the phase error sensed by the beacon is uncorrelated to the required phase correction of the outgoing beam, because the turbulence changes too much during the light round trip time. The total variance is then the sum of the beacon and outgoing beam variances, i.e. twice the uncompensated result. When $\xi=0.316$, the compensated beam has the same phase variance as would be obtained with no compensation.

Figure 2. The normalized light round trip time phase variance (piston removed) as a function of a normalized aperture. The piston removed phase variance is normalized to the piston included phase variance, i.e. the large aperture phase variance. The aperture is normalized to the atmospheric coherence length times the characteristic frequency defined in the text times the light round trip time.

For the general profile of Eq[16], with $q=0$, the normalized phase variance is given by

$$y = \frac{1}{B(\frac{8}{3}, p + \frac{8}{3})} \int_0^L d\gamma (1-\gamma)^{p+5/3} \gamma^{5/3} K\left(\frac{\xi}{\gamma} [(p+\frac{8}{3})B(\frac{8}{3}, p+\frac{8}{3})]^{3/5}\right) \quad [21]$$

For $p=0$, this gives the uniform turbulence profile result. A numerical evaluation of the normalized phase variance is also shown in Fig.2 for this case. For values of p from zero to 50, representative of propagation from an airplane along near horizontal paths, the

resulting normalized phase variances differ from the uniform profile case by at most a few percent, and have the same asymptotes.

When D/r_0 is specified, the phase variance becomes a function of the single parameter $20.13 f_s 2L/c$. In the example given before (Hufnagel-Valley 5/7 turbulence profile, wavelength of $2.314 \mu\text{m}$, propagating from an altitude of 41kft to an aimpoint located at a cross-range of 400 km and an altitude of 25 km, plane speed of 200 m/s) the coherence length is 38.2 cm. For a 2 meter aperture, this gives $D/r_0 = 5.21$, and the normalized phase variance (for the $p=5$ profile) is 0.56. Since the large aperture limit phase variance was 0.941 rad^2 , the phase variance with piston removed is then 0.527 rad^2 . The Strehl is then 0.59 instead of 0.39. Fig.3 shows the Strehl as a function of $20.13 f_s 2L/c$, for several values of D/r_0 using a delta function profile formulation.

Figure 3. Light round trip Strehl as a function of a normalized light round trip time, for several ratios of aperture to atmospheric coherence length. The case shown is for the delta function class of turbulence profiles. The light round trip time is normalized with the characteristic frequency defined in the text.

7. Summary. The anisoplanatic effect due to the finite speed of light, has been analyzed. It has been found that when the light round trip time is significant relative to a characteristic time, i.e. $1/(20.13f_s)$, the intensity of the beam at the aimpoint will be degraded from diffraction limited values. The beam degradation due to finite light speed was obtained for three cases: infinite bandwidth and large aperture; finite bandwidth and large aperture; and infinite bandwidth and finite aperture. Several turbulence strength profiles were treated, and a formulation was developed which is relatively insensitive to the details of the profile. For an airborne laser propagating on near horizontal paths, the light round trip time anisoplanatic beam degradation becomes significant at 250 to 400 km range, depending on turbulence strength, wavelength, and plane speed.