Prepared for the U.S. Department of Energy
Assistant Secretary for Resource Applications
Grand Junction Office, Colorado

GJBX-140 '79

DPST-79-146-10

**ALBANY 1°×2° NTMS AREA
CONNECTICUT, MASSACHUSETTS,
NEW HAMPSHIRE, NEW YORK,
AND VERMONT**

DATA REPORT

MASTER

**NATIONAL URANIUM RESOURCE
EVALUATION PROGRAM**

**HYDROGEOCHEMICAL AND STREAM
SEDIMENT RECONNAISSANCE**

G. R. KOLLER

**SAVANNAH RIVER LABORATORY
AIKEN, SOUTH CAROLINA 29801**

PREPARED FOR THE U.S. DEPARTMENT OF ENERGY UNDER CONTRACT AT(07-2)-1

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

FOREWORD

This report is released without standard editorial and technical review in order to make the information available as soon as possible to interested organizations and to assist the search for uranium resources.

DISCLAIMER

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, mark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**ALBANY 1°x2° NTMS AREA
CONNECTICUT, MASSACHUSETTS,
NEW HAMPSHIRE, NEW YORK,
AND VERMONT:**

DATA REPORT

**NATIONAL URANIUM RESOURCE
EVALUATION PROGRAM**

**HYDROGEOCHEMICAL AND STREAM
SEDIMENT RECONNAISSANCE**

by

G. R. Koller

Approved by:

M. L. Hyder, Manager
Analytical Chemistry Division

NOTICE
This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Publication Date: August 1979

**ISSUED BY E. I. DU PONT DE NEMOURS AND COMPANY
SAVANNAH RIVER LABORATORY
AIKEN, SOUTH CAROLINA 29801**

PREPARED FOR THE U. S. DEPARTMENT OF ENERGY UNDER CONTRACT AT(07-2)-1

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

This data report presents preliminary results of ground water, stream sediment, and stream water reconnaissance in the National Topographic Map Series (NTMS) Albany 1° x 2° quadrangle. Stream sediment and stream water samples were collected from small streams at 1328 sites or at a nominal density of one site per 13 square kilometers (five square miles) in rural areas. Ground water samples were collected at 664 sites or at a nominal density of one site per 26 square kilometers (ten square miles). Neutron activation analysis (NAA) results are given for uranium and 16 other elements in sediments, and for uranium and 8 other elements in ground water and surface water. Field measurements and observations are reported for each site. Analytical data and field measurements are presented in tables and maps. Statistical summaries of data and a brief description of results are given. A generalized geologic map and a summary of the geology of the area are included.

Key data are presented in page-sized hard copy. Supplementary data are on microfiche.

Key data from ground water sites (Appendix A) include (1) water chemistry measurements (pH, conductivity, and alkalinity), (2) well depth, (3) elemental analyses (U, Br, Cl, F, Mn, Na, and V), and (4) graphical presentation only of Al and Dy analyses. Supplementary data include site descriptors (well age, frequency of use of well, etc.) and tabulated analytical data for Al and Dy.

Key data from stream sediment sites (Appendix B) include (1) water quality measurements (pH, conductivity, and alkalinity), and (2) important elemental analyses (U, Th, Hf, Al, Ce, Fe, Mn, Sc, Na, Ti, and V). Supplementary data from stream sediment sites include sample site descriptors (stream characteristics, vegetation, etc.) and additional elemental analyses (Dy, Eu, La, Lu, Sm, and Yb).

Key data from stream water sites (Appendix C) include (1) water chemistry measurements (pH, conductivity, and alkalinity) and (2) elemental analyses (U, Al, Br, Cl, Dy, F, Mn, Na, and V).

CONTENTS

Introduction	7
Geology, Tectonics, and Mineral Occurrences	11
Hydrology	27
Factors Affecting the Data	30
Quality Assurance	31
Results and Discussion of the Data	35
Acknowledgments	37
Cited References	46
Related Geologic Bibliography	57
Appendices	
A. Ground Water Reconnaissance Data	
B. Stream Sediment Reconnaissance Data	
C. Stream Water Reconnaissance Data	
D. User's Guide to SRL Data Reports	

LIST OF FIGURES

1. Location Map for the Albany $1^{\circ} \times 2^{\circ}$ NTMS Quadrangle Area 9
2. Location of the Albany $1^{\circ} \times 2^{\circ}$ NTMS Quadrangle on a
Physiographic Province Map 12
3. Areal Distribution of $\log (U/Hf)$ in Stream Sediment 41
4. Areal Distribution of $\log (U/Th)$ in Stream Sediment 42
5. Areal Distribution of $\log (Th/La)$ in Stream Sediment 43
6. Areal Distribution of U/Conductivity Values of Ground
Water 44
7. Areal Distribution of U/Conductivity Values of Stream
Water 45

LIST OF TABLES

1. State and County Abbreviations for SRL Site Codes 10
2. Geochronologic Data for the Albany Quadrangle 18
3. Precipitation Totals for 1977 at Selected Weather Stations 28
4. Precision of SRL 2.1 Analyses 32
5. Analyses for Uranium in DOE Sediment Standards 33
6. Analyses of Resin Standards and Blanks 33
7. Analyses of DOE Standard Uranium Solutions 34
8. Statistical Summary of Field Measurements and Elemental Analyses - Ground Water 38
9. Statistical Summary of Field Measurements and Elemental Analyses - Sediment 39
10. Statistical Summary of Field Measurements and Elemental Analyses - Stream Water 40

MAPS

(In Pocket)

- Plate 1A Geologic-Tectonic Map of the Albany Quadrangle
- Plate 1B Mineral Occurrences in the Albany Quadrangle
- Plate 2 Ground Water Sample Site Locations in the Albany Quadrangle
- Plate 3 Surface Sample Site Locations in the Albany Quadrangle
- Plate 4 Uranium Distribution in Ground Waters of the Albany Quadrangle
- Plate 5 Uranium Distribution in Stream Sediments of the Albany Quadrangle
- Plate 6 Thorium Distribution in Stream Sediments in the Albany Quadrangle
- Plate 7 Conductivity Distribution in Ground Waters of the Albany Quadrangle
- Plate 8 Uranium Distribution in Stream Waters of the Albany Quadrangle
- Plate 9 Conductivity Distribution in Stream Waters of the Albany Quadrangle

**DATA REPORT: ALBANY 1° x 2° NTMS QUADRANGLE: CONNECTICUT,
MASSACHUSETTS, NEW HAMPSHIRE, NEW YORK, AND VERMONT**

INTRODUCTION

The National Uranium Resource Evaluation (NURE) program was established to evaluate domestic uranium resources in the continental United States and to identify areas favorable for uranium exploration. The Grand Junction Office (GJO) of the Department of Energy (DOE) is responsible for administering and coordinating NURE program efforts. The Savannah River Laboratory (SRL) has responsibility for hydrogeochemical and stream sediment reconnaissance (HSSR) of 3.9 million square kilometers (1,500,000 square miles) in 37 eastern and western states. Other DOE laboratories are responsible for similar reconnaissance in the rest of the continental United States including Alaska. The significance of the distribution of uranium in natural waters and stream sediments will be assessed as an indicator of areas favorable for the location of uranium deposits.

The principal objectives of the NURE program are:

- Increase geologic knowledge of U.S. uranium resources in regions where uranium ore bodies are known to exist and are candidate supplies under present and near-term market conditions.
- Complete assessment of lower cost potential uranium resources in the conterminous U.S. and Alaska.
- Improve reliability and validate resource estimates and increase confidence levels.
- Expand scope of uranium assessment to include higher cost and relatively unknown domestic resources that may be feasible uranium supply alternatives.
- Apply advanced technologies for detection and assessment of uranium resources.

DOE-GJO is responsible for administering and coordinating efforts to meet these objectives including distribution of reports.

Inputs to the NURE program come from DOE prime contractors, DOE-sponsored research and development, the uranium industry, U.S. Geological Survey, U.S. Bureau of Mines, other federal and state government agencies, and independent sources.

The NURE program consists of six parts:

1. Hydrogeochemical and Stream Sediment Reconnaissance Survey
2. Aerial Radiometric Survey
3. Intermediate Grade Resource Studies
4. World Class Geologic Studies
5. Subsurface Geologic Investigation
6. Technology Application

The data presented here are reconnaissance data intended for use in identifying broad areas for further study. While care has been taken to provide reliable sampling and analyses, verification of individual analyses is beyond the scope of this report. The data should be viewed statistically because "one-point anomalies" may be misleading. Regional trends, however, should be reliable. With careful consideration of regional geology, these data should provide reliable guides to areas warranting further study.

This report is one of a series presenting basic data obtained by SRL reconnaissance. In the interest of disseminating available data as soon as possible, only neutron activation analyses are reported here. Supplementary reports will be issued later. All data will be available on magnetic tape from:

GJOIS Project
UCC-ND Computer Applications Department
4500 North Building
Oak Ridge National Laboratory
P.O. Box X
Oak Ridge, TN 37830

A brief description of sampling and analytical procedures and a detailed description of the maps, tables, and figures contained in this report are presented in the SRL document **User's Guide to SRL Data Reports** included as Appendix D in this report. A summary of the SRL development program in support of the reconnaissance is available in SRL-NURE progress reports (SRL-138). SRL data reports (SRL-146) have been open-filed for other quadrangles (Figure 1).

Table 1 summarizes the county abbreviations used in SRL sample identification numbers.

FIGURE 1. Location Map for the Albany 1° x 2° NTMS Quadrangle Area

TABLE 1

State and County Abbreviations for SRL Site Codes

Site Code	County	Site Code	County
Connecticut			
CTHA	Hartford	CTTO	Tolland
CTLI	Litchfield		
Massachusetts			
MABE	Berkshire	MAHM	Hampshire
MAFR	Franklin	MAWO	Worcester
MAHA	Hampden		
New Hampshire			
NHCH	Cheshire	NHHI	Hillsborough
New York			
NYAL	Albany	NYSR	Saratoga
NYCO	Columbia	NYSC	Schenectady
NYDU	Dutchess	NYUL	Ulster
NYGR	Greene	NYWS	Washington
NYRE	Rensselaer		
Vermont			
VTBE	Bennington	VTWI	Windham

GEOLOGY, TECTONICS, AND MINERAL OCCURRENCES

Introduction

This section summarizes the geology, tectonics, and mineral occurrences relevant to uranium geochemistry in the Albany 1° x 2° NTMS quadrangle.

Geology

The Albany quadrangle includes portions of Connecticut, Massachusetts, New Hampshire, New York, and Vermont (Figure 2). The geology is complex. Rocks are found which represent an almost complete sequence from middle Precambrian through Jurassic. Evidence for at least the Grenville, Avalonian, Taconic, Salinac, Acadian, Allegheny, and Palisadian orogenies is found in the quadrangle area. In the ensuing text, this quadrangle area will be considered in terms of various lithological, structural, and tectonic units. From west-to-east, these are:

- Catskill Escarpment and Helderberg Mountains
- Taconic Range and Appalachian Great Valley
- Precambrian Anticlinoria
- Connecticut Valley Synclinorium
- Bronson Hill Anticlinorium
- Merrimack Synclinorium

Catskill Escarpment - Helderberg Mountains

These topographic features will be considered together because they are closely related in time and space. They exist as topographic highs in the westernmost part of the Albany quadrangle. The Helderberg Mountains form a low ridge a few hundred feet high which extends parallel to the Mohawk and Hudson Rivers. West of the Albany quadrangle, the Escarpment and Catskill "Mountains" attain elevations of several thousand feet.

The Helderberg Mountains are primarily limestones/dolostones of Early Devonian Age (Laporte, 1967). They were deformed during the early stages of the Acadian event.

The Catskill Escarpment is composed of approximately 2700 m of Middle and Upper Devonian strata. The Hamilton Group begins with basal limestone (Onondaga) and rises through various marine

FIGURE 2. Location of the Albany 1° x 2° NTMS Quadrangle on a Physiographic Province Map

clastics to red beds and metabolized conglomerates at the top of the sequence (Fletcher, 1967). The sequence is believed to represent a deltaic clastic wedge formed from the erosion of uplands to the east and southeast (Lucier, 1966).

Taconic Range and Appalachian Great Valley

East of the Helderberg Mountains and southeast of the Adirondack Dome lies the northern extension of the Appalachian Great Valley (Rogers, 1970). To the east, the Valley changes into an upland surface known as the Taconic Range. The Range is bounded on the east by the Precambrian Berkshire Massif and southern Green Mountains.

Lengthy controversy has existed over the origin of the Taconic Range. The basic difference in the various hypotheses is whether the strata are allochthonous or autochthonous. The presently accepted model explains the origin of the Taconics in terms of early Paleozoic shelf and basin sedimentation followed by Taconic deformation and emplacement of transported basin strata.

From a eugeosyncline located east of the Precambrian anticlinoria, the Taconic sequence (about 1300 m of deep water strata) was thrust westward and emplaced on top of the miogeosynclinal synclinorium sequence (about 700 m of clastics and carbonates) and into contemporaneous shales several thousand meters thick.

Precambrian metamorphic and metaigneous rocks are covered by a basal clastic sequence (Cheshire-Potsdam) which thickens eastward. Source area was generally from the Adirondacks, but Zen (1968) indicates some transport from the east. The clastic sequence grades into a Lower Cambrian-Middle Ordovician sequence of carbonates (Wappinger Group and, where metamorphosed, Stockbridge Group). Rodgers (1968) compares the sequence to the carbonate platform of the Bahama Banks.

Precambrian Anticlinoria

A belt of Precambrian anticlinoria along the East Coast (Rodgers, 1970) is locally expressed as the Berkshire Massif and the southern portion of the Green Mountains. These features are related to the Reading Prong and the Adirondack Dome, respectively (Dallmeyer, 1975). The Green Mountain belt extends for a few km into the Albany quadrangle and then abruptly disappears, plunging beneath a Taconic synclinorium (The Greylock slice). Approximately 8 km to the south, there appears a comparable anticlinorium, the Berkshire Massif, which extends over 100 km southward into Connecticut.

The western front of the belt is a series of overlapping, low-angle, thrust faults. The faults juxtapose in a complex stratigraphic relationship of Precambrian igneous-metamorphic rocks and Cambro-Ordovician strata of the shelf and basin sequence (Zen, 1967; Norton, 1975; Ratcliffe and Harwood, 1975). The east side of the anticlinoria is fixed by a complex interwoven fault zone.

Lithologically, the Precambrian Mt. Holly complex of the Green Mountains (Skehan, 1971, 1972) is similar to gneisses of the Berkshire Massif (Ratcliffe and Zartman, 1976; Ratcliffe, 1975). The rocks have affinities with those of the Adirondack Dome and the Reading Prong. However, certain distinct lithologies of the Adirondacks (e.g., anorthosite) are lacking in the Massif. Further, while generally similar lithologies exist in each area, specific correlations have not yet been made (Drake, 1969; Young, 1971; Ratcliffe and Zartman, 1976).

The anticlinoria are composed of metasedimentary and metavolcanic rocks intruded by a syntectonic granodiorite suite. The igneous/metamorphic suite is overlain by a late Precambrian-Cambrian transgressive basal clastic sequence (the Cheshire-Dalton) which thickens eastward.

In addition to Precambrian dynamothermal metamorphism, the rocks were deformed and metamorphosed during the Taconic and Acadian events.

Connecticut Valley Synclinorium

This physiographic and structural unit lies within the broad area of the regional Connecticut Valley-Gaspé synclinorium. Locally of varied structural complexity, the downwarped area has a north-south linearity and a width from the east flank of the Precambrian Berkshire Massif to the Paleozoic Bronson Hill anticlinorium. It is composed of a eugeosynclinal sequence of rocks which range in age from Late Precambrian(?) to Early or Middle Devonian (Schnabel, 1976; Stanley and Hatch, 1976). Rodgers (1970) suggests that the upbuckling of basement in the anticlinoria to the west was accompanied by downbuckling of the adjoining sedimentary trough.

Subsequent metamorphic events have raised the rocks to kyanite grade just east of the synclinal axis (Hatch, 1975). Metamorphic grade rapidly decreases eastward, reaching chlorite grade at the synclinorium's margin. Across the eastern border of the province, defined locally by the Ammonoosuc Fault, the rocks of the Bronson Hill anticlinorium are of relatively high metamorphic grade.

Several intrusive series are located in this zone. Many small Middle Ordovician ultramafic bodies have been mapped extending through Vermont into northern Massachusetts (Chidester et al., 1967). Quartz monzonite and granodiorite outliers of the mainly syntectonic New Hampshire plutonic series also occur (Page, 1968). Smaller bodies of the Late Devonian series reported by Page (1968) and alkalic syenite, diorite, and gabbro of the White Mountain magma series occur to a limited extent. The youngest igneous suite includes the Triassic-Jurassic tholeiitic basalts which are intrusive and extrusive with respect to basement and Triassic-Jurassic rocks.

The west flank of the synclinorium is a relatively simple homoclinal structure (Hatch, 1976; Skehan and Hepburn, 1972). Conversely, structure in the central trough is much more complex (Rosenfeld, 1968; White and Jahns, 1950). A marked feature of this central belt is the existence of a series of domes. These antiforms are cored by Precambrian gneisses (exposed in southern portions of the Albany quadrangle) which upwelled into Paleozoic strata (Hepburn, 1972; Doll et al., 1961). The Paleozoic sequence has been isoclinally folded during two periods of deformation, the younger folds having an opposite sense of direction relative to the first (Rosenfeld, 1968).

The stratigraphic sequence is unclear (Stanley and Hatch, 1976; Hatch et al., 1968). Based upon the accepted stratigraphic sequence of the synclinorium, the eastern margin is either a series of faults or a rapid facies change into rocks of the Bronson Hill anticlinorium. Rodgers (1970) prefers the latter interpretation.

Contemporaneous with clastic and carbonate deposition on the shelf, a clastic and chert eugeosynclinal sequence was being deposited in deeper waters to the east. Subsequently, these eugeosynclinal strata and the slope and distal miogeosynclinal strata were transported into the Magog-Snake Hill-Martinsburg Trough. Slumping was accompanied by isoclinal and recumbent folding and sedimentary overlap. Slumping was also accompanied by the formation of sedimentary breccias, flysch, wildflysch, melanges, and/orolistostromes (Bird, 1963; Zen, 1967).

Subsequent deformation occurred in the Acadian orogeny. To the east of the Albany quadrangle, this event appears to have had more of a thermal character relative to the Taconic structural deformation. Overall, metamorphic grade increases eastward. While it is unclear which event produced the isograds in this area (Drobeck and Rutstein, 1978), current evidence favors the Taconide as being more thermally intense than the Acadian.

Bronson Hill Anticlinorium

This essentially linear structure extends from Maine to Connecticut, striking north-south in the Albany quadrangle. It has a gradational boundary to the east with the Merrimack synclinorium and has a fault-bounded (Ammonoosuc Fault) and gradational boundary to the west with the Connecticut Valley Synclinorium.

Although an anticlinorium in a regional sense, it differs from the Precambrian anticlinoria to the west (Rodgers, 1970). The latter are composed of a few anticlinal masses, whereas the Bronson Hill anticlinorium consists of numerous domes. These bodies are mantled by and separated by tightly pinched-to-isoclinal anticlines and synclines of metasediments and metavolcanics (Eskola, 1949; Thompson et al., 1968). The cores of these domes are composed mainly of unstratified gneisses of igneous origin (Oliverian plutonic series of Billings, 1956) and stratified gneisses. The Oliverian series ranges from quartz diorite (Kinsman) to granite (Bethlehem gneiss). Its presence is a major distinguishing characteristic for these domes (Billings, 1956; Page, 1968; Naylor, 1968).

The origin and geometry of the core rocks is critical to any interpretation of the anticlinorium. Thompson et al. (1968), believe the Oliverian series is igneous and intruded a basement sequence of protoliths which included carbonates, volcanics, and mixed clastics. The protolith for the Oliverian series may have been an ignimbrite suite. Naylor (1968) believes that the Oliverian and Highlandcroft series have the same parentage; however, subsequent deformations have produced differing appearances. The stratified core rocks consist chiefly of quartz, plagioclase, and hornblende or biotite.

Robinson (1978) has recently described the Bronson Hill anticlinorium as representing an Acadian convergence zone and Pennine zone (Thompson et al., 1968). Thus, the linear nature of the anticlinorium is inherited from a volcanic island arc (Berry, 1968). Continental collision produced an upbuckling of material which mushroomed upwards and flopped over in various directions. Thus, while the metamorphic grade generally rises to a maximum at the crest of the anticlinorium, this is not always the case because the deformation has produced extensive overturning of isograd surfaces (Thompson et al., 1968).

Merrimack Synclinorium

This synclinorium is a regional downwarped belt of highly metamorphosed deformed and intruded Silurio-Devonian(?) strata. It extends southeastward from central Maine to southern New Hampshire. Its strike becomes more north-south as it passes through Massachusetts and northern Connecticut (Rodgers, 1970).

The contact of the synclinorium and the Bronson Hill anticlinorium is the Monson Hill border fault (Peper and Pease, 1976). East of this major border fault is a highly disrupted zone in the synclinorium. Numerous, small, high-angle, cross faults and small, near-strike faults of varied attitude are present. Strata in the fault zone are westward-dipping, homoclinal Silurio-Devonian meta-sediments. Similarities exist with rocks mapped in New Hampshire (Billings, 1956) and tentative stratigraphic correlations have been suggested (Dixon, 1976; Skehan and Abu-Moustafa, 1976; Peper and Pease, 1976; Peck, 1976).

The homoclinal sequence is actually a fault wedge; its eastern contact is the Clinton-Newbury fault zone, which is a major westward-dipping thrust zone (Skehan, 1968; Skehan and Abu-Moustafa, 1976). The southwestward extension into the southeastern part of the Albany quadrangle is known as the Eastford Fault (Peper and Pease, 1976). Skehan (1968) considers that the fault marks a zone of long-term eastward tectonic transport. The surface expression of the fault is distinct because it separates rocks of markedly different metamorphic grade. To the east are high-grade (sillimanite-muscovite) metasedimentary and metavolcanic rocks considered to be pre-Silurian. To the west are low- and medium-grade (chlorite-andalusite) Silurio-Devonian strata of the synclinorium.

The age of the Merrimack Synclinorium is based upon the age of the carbon-bearing strata in the Worcester area located just east of the Albany quadrangle. Grew (1970) and Rodgers (1970) suggest a Carboniferous age for these strata and a resulting Siluro-Devonian age for the underlying metamorphics.

Summary of Geologic History

Summaries of data and alternative interpretations can be found in Lyons and Faul (1968) and Cady (1969). Representative data from these and other sources are presented in Table 2.

TABLE 2

Geochronologic Data

Age, m.y.	Method	$^{87}\text{Sr}/^{86}\text{Sr}$ Ratio	Reference	Remarks
1040 to 1080	U-Th-Pb		Ratcliffe and Zartman (1976)	Zircons from Tyringham and Washington basement gneisses of Berkshire Massif.
1000	Various		Lyons and Faul (1968), Gilluly (1966), Cady (1969)	Grenville basement.
605 $\pm$ 50	Rb/Sr		Brookins and Norton (1975)	Weakly foliated granite along east margin of Berkshire Massif.
485 $\pm$ 10	K-Ar		Leech et al. (1963) Lowden et al. (1963)	Quebec serpentinites; representative ages for ophiolites/ultramafics.
463 $\pm$ 62	Rb-Sr	0.7088 (001)	Ratcliffe and Mose (1978)	Intrusive granodiorite from thrust zone on east edge of Berkshire Massif.
460 to 485	K/Ar		Lyons and Faul (1968)	Metamorphism of Taconic Klippe slates.
450 $\pm$ 25	U-Pb		Naylor (1967)	Zircons from basement granite and gneiss units in core of Bronson Hill anticlinorium.
440 $\pm$ 40	Rb-Sr	0.706 (002)	Naylor (1967)	Granitic units of Bronson Hill anticlinorium.
411 $\pm$ 19	Rb/Sr	0.7107 (006)	Lyons and Livingston (1977)	New Hampshire Plutonic Series: Kinsman quartz monzonite Bethlehem gneiss Spaulding quartz diorite Concord granite—possibly 330 m.y.
405 $\pm$ 76	Rb/Sr	0.7065 (0022)		
402 $\pm$ 5	Rb/Sr	0.7143 (0003)		
359 $\pm$ 11	Rb/Sr	0.7144 (0004)		
385 $\pm$ 20	Rb/Sr		Lyons and Livingston (1977)	Post-acadian nappes.
340 to 390	K-Ar Rb/Sr		Lyons and Faul (1968)	Acadian-age granites and pegmatites.
235 to 300	K/Ar		Foland and Faul (1977)	Three igneous groups (230; 200 to 156; 125 to 100 m.y.) with maxima at 180 and 120 m.y.
204 to 280	K/Ar		Van Houten (1969) Dallmeyer (1975)	Correlative basaltic units to southwest.
183 to 110	Rb/Sr	0.7107 (0017)- 0.7183 (009) 0.766 (00*)- 0.830 (002)	Foland et al. (1971)	Four igneous series in White Mountain. Series representing two magma sources.
180	Pb/U K/Ar Rb/Sr		Lyons and Faul (1968)	Conway granite of White Mountain Series.
130	K/Ar		Faul et al. (1963) Lyons and Faul (1968)	Mt. Ascutney stock; Monteregean disturbance; small related bodies; scattered.

Precambrian History

A Pre-Neohelikean sequence of sediments was intruded by igneous rocks during the Grenville orogeny. Metamorphism to amphibolite facies and multiple deformation occurred during the time span of about 1200 to 850 million years (m.y.) before the present (BP). The peak of these events seems to have occurred around 1100 m.y. BP. Brookins and Norton (1975) have interpreted Rb/Sr data as indicating a period of volcanism around 1100 m.y. and intrusion of the Tyringham protolith during the Grenville orogeny at 900 m.y.

Uplift of these cratonic rocks was accompanied by an extensive period of erosion which resulted in a low rolling terrain in Late Precambrian time. To the north (northern New England) and south (Piedmont of Maryland), thick clastic wedges formed in association with the Avalonian disturbance (Lilly, 1966; Rast et al., 1978).

Early Paleozoic History

The Appalachian orthogeosyncline was established in latest Precambrian or earliest Paleozoic (Cady, 1969). Initially, the eugeosynclinal zone existed alone, the miogeosyncline being developed later. Sands derived mainly from erosion of the craton (remnants of the Avalon disturbance?) formed a basal clastic sequence which thickens northward and westward. The transgressive sequence was succeeded by carbonate deposition which continued into Middle Ordovician time.

The eastern boundary of the carbonates was probably a sharp declivity analogous to that of the modern day Bahama Banks (Rodgers, 1968), but with more marked tidal effects on sedimentation patterns (Mazzullo, 1978). The present location of the limit of carbonate deposition is slightly to the east of a belt of Precambrian gneisses (Dallmeyer, 1974). Rodgers (1970) further notes that by Early Cambrian, the usual northeast strike belts of Appalachian anticlinoria and synclinoria were well established.

Middle Ordovician time was punctuated by a sharp unconformity. Deep erosion and weathering and block faulting characterize the break-up of the Cambro-Ordovician shelf environment (Fisher and Warthin, 1977) which signaled the onset of the closing of the Iapetus Ocean (Bird and Dewey, 1970).

The shelf breakup can be considered as the onset of the Taconic Orogeny (500 to 450 m.y. BP). West of the Berkshire Massif, a rapidly deepening trough (Magog-Snake Hill-Martinsburg

Formation) received sediments from the craton and from the eastward and rapidly uprising Vermont-Quebec geanticline (Cady, 1969). Cambro-Ordovician shelf, slope, and distal deposits slumped, slid, or were pushed into this trough. The Taconic disturbance closed in Late Ordovician to Early Silurian with general uplift and erosion (Pavlides et al., 1968; Zen, 1967, 1972).

Devonian continental collision produced the events known as the Acadian orogeny (Bird and Dewey, 1970; Robinson, 1978). The orogeny was climaxed by the growth of major north-south trending arches and domes (Cady, 1969). Concomitantly, basement rocks were remobilized and intruded along with newly derived calc-alkalic plutons. Cady (1969) notes that these intrusions cratonized much of the orthogeosyncline.

Acadian events probably continued into Mississippian time (Hadley, 1964), because rocks in the Connecticut Valley synclinorium and Berkshire anticlinorium reflect 250 to 360 m.y. K-Ar ages. However, rocks of the Merrimack synclinorium were little affected by cooling until the Permian (Cady, 1969).

Post-orogenic sedimentation was characterized by extensive molasse deposits (Catskill stratigraphic section) and thick, poorly sorted sediments in central Massachusetts.

Late Paleozoic History

Late Paleozoic time was characterized by general uplift and erosion reflecting the Alleghenian event. This disturbance was not particularly strong in most of the Albany quadrangle.

Mesozoic History

Upper Triassic-Lower Jurassic was a time of crustal rifting associated with the opening of the modern Atlantic Ocean (Bird and Dewey, 1970). Associated high-angle faulting produced a taphrogeosyncline along the western margin of the Bronson Hill anticlinorium. Characteristic of this half-graben were concomitant terrestrial sedimentation, mafic hypabyssal intrusion, and mafic volcanism.

In Late Mesozoic time, the calc-alkaline White Mountain series was intruded. This occurred mainly in northern New England.

Cenozoic History

During Cenozoic time, the area was an upland subjected to erosion. In the Quaternary, glaciation extensively scoured the terrain, exposing bedrock. However, sedimentary deposits (formed during the glacial melt stage) have covered many of these exposures.

Igneous and Related Rocks

Precambrian

The anticlinal Berkshire Massif and the southern portion of the Green Mountains (Mt. Holly complex) are cored by rocks which date from around 1050 m.y. BP. The lithologies are possibly closely related in origin (e.g., Dallmeyer, 1974).

Gneiss Units -- Two major gneiss units exist--the Tyringham and the Washington (Emerson, 1917). In the Green Mountains, Skehan (1971) has named these the Stamford granite gneiss and the Wilington gneiss, respectively. The Tyringham gneiss is a coarsely blastoporphyritic, K-feldspar, biotite, ferrohastingsite granite gneiss (Ratcliffe and Zartman, 1976). Th-Pb dating indicates that the Washington gneiss, although reset by the Grenville and Paleozoic events, has an original age of about 1200 m.y. BP.

Avalonian -- Brookins and Norton (1975) have dated a biotite from the eastern edge of the Berkshire Massif at 605 ± 50 m.y.

Ordovician

Sills and dikes of foliated white to light-gray muscovite-biotite granodiorite and adamellite exist at the eastern edge of the Berkshire Massif. Rb/Sr whole rock isochrons give an age of 463 ± 62 m.y.

Ultramafic Complexes -- Ultrabasic rocks occur intermittently in a belt striking north-south through Vermont to the Massachusetts border, and thence, northeast-southwest through Drury, Massachusetts, to New York. Subsequently, these rocks were metamorphosed and deformed due to the plate interactions suggested by Bird and Dewey (1970). Radiometric studies suggest an age of 480 m.y. (Cady, 1969).

Oliverian Plutonic Series -- The rocks of this series form the core of the Bronson Hill anticlinorium located just to the east of the Connecticut River Valley. Radiometric data indicate a pre-Silurian age (Naylor, 1968; Lyons and Faul, 1968), yet Page (1968) prefers a post-Lower Devonian and pre-Acadian age because of stratigraphic considerations (Billings, 1937). Naylor (1968) relates this series to the Highlandcroft Series of Billings (1956) which occurs to the north. The major Oliverian plutons are composite bodies (Page, 1968). The oldest are dioritic which grade inward into granodiorite, monzonite, and granite.

Associated pegmatites are rare and small. Mineralogically, they are of granitic composition.

Some local sulfide veins and replacement deposits occur in intimate relationship to the Oliverian Series.

Devonian

The igneous and metamorphic events of this series are related in time and space, representing "discrete pulses" of the Acadian Orogeny. They seem also to be part of a continuum related to events of the Taconic and Alleghenian (Drobeck and Rutstein, 1978; Lyons and Livingston, 1977; Spooner and Fairbairn, 1970).

Page (1968) had divided Devonian igneous rocks into two series: the New Hampshire Plutonic Series and the Late Devonian Plutonic Series. Rocks of the New Hampshire Series are characterized by a black, gray, or white color with biotite as the main mafic mineral. Large crystals of K-feldspar are common. The major pegmatites of New England belong to this series.

The Late Devonian Plutonic Series forms a rather complete differentiation series from gabbros and norites through granites. They tend to be discordant plutons accompanied by metamorphic aureoles. Feldspars tend to be pink in contrast to those of the New Hampshire Series; also, the main mafic mineral is hornblende.

Mesozoic

This era was a time of crustal rifting (Bird and Dewey, 1970) characterized by tholeiitic volcanism (Connecticut River Valley) and alkaline intrusions (northern New England).

The Connecticut River is structurally controlled by a Mesozoic half graben into which were emplaced several km of sedimentary rocks and basaltic lavas and intrusives. Radiometric data suggest a Late Triassic age (Armstrong and Besancon, 1970),

whereas palynological analysis indicates an age of Early Jurassic (Cornet and Traverse, 1973).

Representatives of the White Mountain Magma Series are lacking in the Albany quadrangle. However, a few small bodies may exist at depth, so a few comments are in order. The discordant, epizonal, mildly alkaline series was emplaced throughout Middle to Late Mesozoic time (Lyons and Faul, 1968; Foland et al., 1971, 1977). This series exhibits a marked structural control (Chapman, 1968) which could be due to a migrating hot spot or a migrating transform fault.

Geologic Mapping

The state geologic maps of New York (Fisher et al., 1971), Vermont (Doll et al., 1961), New Hampshire (Billings, 1955), Connecticut (Rodgers et al., 1956), and Massachusetts (Emerson, 1917) have been used as major sources in the compilation of Plates 1A and 1B. A new geologic map of Massachusetts is to be published within the next few years. Plate 1A emphasizes lithologies and shows major faulting and folding.

Each of the above maps lists more detailed references to individual work used in compiling the larger maps. Emerson (1917) is a dated source for Massachusetts, but recent work will produce updated maps in the near future.

Where conflicts in mapping are noted at state boundaries, the more recent map of New York is used as a control. The maps of Vermont and New Hampshire are secondary controls.

The map of mineral occurrences (Plate 1B) represents an attempt to portray relevant data graphically on selected minerals and rock types.

The U.S. Geological Survey, New York State Geological Survey, and individuals from several universities are actively engaged in mapping projects in the Albany quadrangle. Robinson and students (University of Massachusetts, Amherst, Massachusetts) are continuing work in the Bronson Hill anticlinorium. Skehan and students (Boston College, Boston, Massachusetts) are working in the Merrimack synclinorium with Peck (U.S.G.S.). Skehan is also active in southern Vermont along with Thompson (Harvard University, Cambridge, Massachusetts). Norton (U.S.G.S.) is continuing his work in the Connecticut Valley synclinorium.

Ratcliffe and students (City College of New York, New York, New York) and Zartman (U.S.G.S.) continue their efforts in the Berkshire Massif as well as to the west in the Taconics. The

latter area is also being studied by Fisher (New York State Geological Survey). E-an Zen (U.S.G.S.) is also continuing his work in this area.

Uplift patterns in the Catskill Mountains and nearby Precambrian rocks are being studied by Rutstein (S.U.N.Y.-New Paltz, New York) and Isachsen (New York State Geological Survey).

Mineral Occurrences and Economic Geology

This section includes descriptions of notable occurrences of U, Nb, Ta, Sn, Be, Li, W, V, Th, rare earths, and Zr in the Albany 1° x 2° NTMS quadrangle. Also considered in this section are occurrences of pegmatites, massive sulphide deposits, and other notable mineralizations.

Overview

The regional igneous rock series are characterized by particular elemental associations (Page, 1968). Massive sulfides are commonly found with members of the Ordovician(?) Oliverian Plutonic Series. Ordovician ophiolite bodies are hosts for nickel and are mined for talc, serpentine, and asbestos (Chidester, 1968). Widespread pegmatites contain Be, U, Th, B, Li, and rare earths. These pegmatites appear to be genetically related to the Devonian New Hampshire Series plutons. Spatially related to the Late Devonian Plutonic Series are deposits of base metals, precious metals, tin, molybdenum, tungsten, nickel, and cobalt. Triassic-Jurassic volcanic and sedimentary rocks are potential hosts for copper, silver, uranium, barium, and base metals (Cox, 1970).

Adams et al. (1962) suggest that the Conway Granite of the White Mountain Series is a potential major low-grade source of thorium, because it averages 56 g of ThO₂ per ton. In fact, Billings and Keevil (1964) use this chemical difference to separate rocks of this series from those of the New Hampshire Plutonic Series. Cox (1970) notes the association of Ag, Zn, and Pb mineralization with the Mesozoic White Mountain Magma Series.

Pegmatites

At the northern edge of the Albany quadrangle, the Keene, New Hampshire, district is noted for the production of beryl, mica, and feldspar (Cameron et al., 1954; Page and Larrabee, 1962).

Billings (1941) notes some 20 pegmatite deposits in his Western Belt of Pegmatites which extends from Goshen to Blandford, Massachusetts. While generally small, these bodies locally contain abundant beryllium (beryl), boron (tourmaline), lithium (spodumene, lepidolite, and pollucite), and uranium, thorium, and rare earths (including cyrtolite, microlite, autunite, and torbernite).

Some particular pegmatite locations and associations are as follows: tin, in microlite (pyrochlore), was reported in the western belt (Emerson, 1917); cesium in pollucite, and lithium in spodumene were found at the Barrus Mine in Lithia, Massachusetts (MacFall, 1958); Baskerville (1908) reported columbite with rare earths from Chesterfield, Massachusetts; and Dana (1891) noted "tin ore" from Goshen, Massachusetts.

Uranium, Thorium, and Rare Earths

In Massachusetts, allanite is a common to abundant accessory in the Precambrian Tyringham gneiss in Becket, Dalton Hindsdale, Otis, Tyringham, Washington, and Sandisfield (Emerson, 1899). Hobbs (1893) notes abundant intergrowths of allanite and epidote at Sheffield, and at Buckland, allanite has decomposed to an abundant red mass locally (Emerson, 1895). Dale (1923) notes the presence of allanite in granite in the Monson granodiorite near Monson and in the vicinity of Pelham. Nearby, from a location now under the Quabbin Reservoir, Rodgers (1952) reports allanite with 0.905% U and 1.53% Th.

Other uranium-thorium occurrences include the following: Smith and Parsons (1938) note autunite from Chesterfield, Massachusetts; a hornblende gneiss at Mashapaug, Connecticut has 0.03% thorium; and Johnson (1951) estimates a deposit of 6500 lb of thorium; and McKeown (1951) reports 0.003 to 0.005% eU in phyllite in the vicinity of Brattleboro, Vermont.

Narten and McKeown (1952) measured 0.001% U from the Middle Devonian Esopus shale in Ravena, New York. To the south, they measured 0.001% U in Ordovician Hudson Valley shales. From schists in the vicinity of Berlin, New York, they report 0.003 to 0.004% eU.

Copper

MacFadyen (1956) reports isolated copper and quartz floats in streams on the south flank of Mt. Anthony, Vermont. Bedrock location is not known, but the local Mt. Anthony schist has abundant quartz veins which may have copper mineralization.

The potential for copper exists in the Triassic-Jurassic red beds of the Connecticut River Valley (Tourtelet and Vine, 1976).

Iron-Nickel-Chromium

Small pockets of limonite occur locally in the Albany quadrangle. MacFadyen (1956) notes a limonite deposit near Stamford, Vermont. Skehan (1971) reports a limonite locality near Wilmington, Vermont, and one for magnetite near West Dover, Vermont.

Near Catskill, New York, siderite, altered to limonite, constitutes the Burden iron ores (Ruedemann, 1931, 1942). The Copake iron ores located about ten miles to the east are probably related to this deposit.

Hanshaw and Barnett (1960) note 293 ppm Cr in the Talcott basalt in Connecticut; also reported are 74 ppm Ni and 86 ppm B. Huntington (1975) studied the metamorphosed iron-rich beds of the Littleton Formation in the vicinity of Orange, Massachusetts. Bray (1939) reports on the iron oxide intergrowths and textures of the emery ores from Chester, Massachusetts.

Titanium

Skehan (1971) reports abundant rutile in a marble unit in the vicinity of Whitingham, Vermont. He also notes abundant blue quartz in Precambrian gneisses of the Mt. Holly complex, suggesting the color may be due to titanium.

Manganese

In the vicinity of Commington, Massachusetts, the mica schist contains primary and secondary manganese minerals (Mosier and Thomas, 1949; MacFall, 1958). Frondel et al. (1960) studied the Mn-silicate weathering product, birnessite, and reports 0.005% lithia, some yttrium, ytterbium, and no barium. To the north, rhodonite is found in Plainfield, Massachusetts.

Asbestos

Emerson (1895) notes the occurrence of asbestos at the contact of an ultrabasic dike and silicate gneisses in Pelham, Massachusetts. Notable are the concentrations in the gneiss of allanite, rutile, and tourmaline.

Boron

A common secondary constituent of Triassic-Jurassic volcanics is datolite. Basalts from around Westfield, Massachusetts, often contain notable amounts of this mineral.

Sulfur

Several localities are especially rich in sulfate minerals. Local names such as "Alum Pond" abound.

Miscellaneous

Several occurrences of names suggesting mineralization were noted on various maps, but no further information was found. These occurrences are noted for reference:

Soapstone Hill - to the east of the northern portion of Quabbin Reservoir

Leadmine Pond - 10 km west of Southbridge, Massachusetts

Ore Hill - 19 km southwest of Westfield, Massachusetts

HYDROLOGY

Climate

There are considerable differences between the high and low temperatures and in the amount of precipitation in the Albany quadrangle, partly as a result of the difference in altitude between the mountains and the lowlands. The temperatures in the higher altitudes near Pittsfield, Massachusetts, average about -6°C in January and about 20°C in July. Rainfall and snowfall are heaviest through the higher elevations in the central portion of the quadrangle; the range is from about 1020 to 1220 mm per year (NOAA, 1977). The heaviest snowfall is about 1900 mm per year. Precipitation data for the 1977 calendar year are presented in Table 3.

Geography

A variety of topographic features occur in the Albany quadrangle. These features attest to differential erosion over long periods of time. In the west, the south-flowing Hudson River is bordered by a lowland cut in easily erodable shales and schists.

TABLE 3

Precipitation Totals for 1977 at Selected Weather Stations

Weather Station and Elevation, mm	Monthly Precipitation, mm												Annual Total, mm	Deviation from Normal, mm
	Jan	Feb	Mar	Apr	May	June	July	Aug	Sept	Oct	Nov	Dec		
Albany (83.8 mm)	38.4	66.8	150	86.6	58.2	72.9	58.7	93.0	169	102	123	1075	1125	+278
Heath (485 mm)	70.1	81.3	172	112	85.9	117	90.9	126	156	163	132	160	1470	+228
Springfield (57.9 mm)	67.8	66.3	167	107	104	112	104	51.6	166	141	111	125	1325	+244
Keene (146 mm)	58.4	40.1	126	95.0	92.2	93.7	51.3	91.2	137	158	57.7	117	1120	+123

West of the River are the lower slopes of the escarpment rising to the Catskill Mountains farther west. Elevations increase east of the Hudson River. The topography includes knobby slate hills and glacial lakes. The north-trending Taconic and Green Mountains occupy the center of the quadrangle. The mountains are composed chiefly of resistant metamorphic rocks (Fenneman, 1938).

East of the mountains is the New England Upland. The Upland consists of rolling hills, a network of surface streams, and monadnocks. The Upland altitude west of the Connecticut River is about 400 m, whereas altitudes on the Taconic Range and Green Mountains exceed 700 m in many places.

Glacial lakes and rocky gorges are common along tributary streams throughout the quadrangle. Flood plains are much less common on the tributaries than along the main rivers.

Dairy farming and poultry raising are the primary agricultural practices in the area. Much of the farm land is used for hay and grain crops. Cigar tobacco is raised in the Connecticut Valley Lowlands. Fruit growing and general farming are found throughout the area. Poultry and dairy farming as well as the application of fertilizer are the primary sources of pollution in the Albany quadrangle.

The population of the quadrangle is approximately one million people (U.S. Bureau of Census, 1970). The heaviest concentration of people is in the industrial area of Springfield on the Connecticut River and Albany on the Mohawk River.

Drainage and Hydrology

The Connecticut River passes from north to south and drains about half the quadrangle. The Chicopee River and tributaries drain Quabbin Reservoir, a large man-made lake near Springfield, Massachusetts. Larger tributaries to the Connecticut River are the Westfield, Deerfield, Miller, Ashuelot, West, and Farmington Rivers. The Housatonic River drains the south-central portion south of Pittsfield, Massachusetts. The Hudson River flows from north to south through Albany, New York. The two main tributaries in the area are the Mohawk and Hoosic Rivers, which enter north of Albany. Many smaller tributaries drain hundreds of lakes into the Hudson River.

Wells and springs supply adequate water for rural domestic use. Some of the bedrock is poorly fractured and is capable of yielding only a few liters per minute from drilled wells. Some bedrock wells are capable of yielding more than 200 liters per minute.

The principal aquifers are in stratified glacial drift. Most of the stratified drift deposits are thin and erratic in distribution. Perennial yields of several thousand liters per minute have been obtained from sand and gravel deposits at Schenectady, New York.

Recharge is local. The water from precipitation passes downward through upland glacial till and fractured rocks and then passes laterally to nearby lowland discharge areas. Small springs are abundant. Local water-table aquifers, or systems, prevail. Generally these are confined to the enclosing surface drainage basin. There are no major artesian aquifers.

Most of the ground water is of good quality. Ground water is soft and low in mineral matter. Some of it is slightly acid, and iron and manganese are common. The Triassic rocks in the Connecticut Valley yield hard water that is relatively high in dissolved-solids content. Ground water is contaminated locally in urban and suburban areas where septic tanks and other waste-disposal facilities are common.

The waters in the Connecticut River basin are of good quality. Polluted water occurs near Springfield, Massachusetts, because of sewage and industrial waste. Waters in the Hudson River Basin increase in dissolved solids below the Albany area. Sewage and industrial waste may contribute to the increase in dissolved solids.

FACTORS AFFECTING THE DATA

Stream sediment and stream water samples and associated site data were collected during the period July through October 1977. The vast majority of streams contained flowing water at the time of sampling. Ground water samples were collected primarily during November 1977 through March 1978. Many of the ground water samples from mountainous areas are from springs, and it is unlikely that these samples represent deeply circulating ground water. Data from springs and wells are plotted on the same areal distribution map. Separate areal distribution plots of these sample types would not provide additional geochemical information. Exact sampling dates for ground water and stream sediment are given in Tables A-2 and B-2, respectively.

QUALITY ASSURANCE

Sample Collection

At least five percent of the sampled sites were routinely checked by SRL personnel (or by a specified subcontractor) to assure that the reported field locations were accurate. Based on these quality assurance checks, more than 98% of the sampled sites were judged to be located as accurately as they could be plotted on county road maps. No evidence has been discovered of deliberate malfeasance by the sampling teams. Most sites that were mapped incorrectly were within 300 meters of their correct locations. Thus, the goals of a regional reconnaissance have not been compromised by mapping errors. Details of the quality assurance program are given elsewhere (SRL-138).

Analytical Standards

Sediment Standard SRL 2.1 was analysed along with NURE sediment samples primarily to provide precision data and routine systems checks for the analytical equipment and software. (Results for SRL 2.1 standard analyzed with sediment samples are presented in Table 4). The data reported in Table 4 give a good estimate of operating precision.

Three DOE intersite comparison standards containing nominal uranium concentrations of 5, 10, and 95 ppm were analyzed, one after each 230 sediment samples. Results are given in Table 5. An independent quality assurance program based on these standards is conducted for DOE by Ames (Iowa) Laboratory (D'Silva, et al.).

Every batch of twenty-five resin samples includes a blank resin sample. Resin blanks are not reacted with water samples. Every fifth batch includes a resin sample that was reacted with a standard solution containing nominally 0.278 ppb uranium. Analyses of standards and blanks are summarized in Table 6. Resins reacted with DOE standard solutions were analyzed along with samples. The uranium analyses of these standards are reported in Table 7. See D'Silva, et al. for Ames Laboratory summary.

TABLE 4

Precision of SRL 2.1 Analyses

<u>Element</u>	<u>Number*</u>	<u>Mean, ppm</u>	<u>Standard Deviation, $\pm 1 \sigma$</u>	<u>Coefficient of Variation, %</u>
U	269	7.80	0.27	3.4**
Th	259	25.8	4.8	18.7†
Hf	269	69.4	4.4	6.4**
Ce	256	130	31	23.7†
Dy	268	11.3	2.8	24.8**
Ti	256	8890	1580	17.8†
V	256	35.4	5.9	16.7†
Fe	221	5550	2030	36.6†
Mn	250	166	37	22.0†
Al	256	20200	2150	10.6**
Sc	269	3.50	0.88	25.2†
La	244	79.4	18.6	23.5†
Sm	234	10.5	3.7	34.9†
Eu	123	1.45	0.92	63.3†
Yb	242	10.0	3.6	35.5**
Lu	234	2.87	0.93	32.3†

* Number of determinations.

** Precision is probably about the same for samples as for SRL 2.1 standard.

† Precision is probably better for samples, because their concentrations are higher than those of SRL 2.1.

TABLE 5

Analyses for Uranium in DOE Sediment Standards

<u>Standard</u>	<u>No. of Samples</u>	<u>Uranium Concentration, ppm</u>		<u>Standard Deviation, $\pm 1\sigma$</u>
		<u>Recommended*</u>	<u>Found</u>	
A	10	5.2	5.25	0.16 (3.1%)
B	10	10.7	11.4	0.81 (7.4%)
C	8	93.7	96.4	6.41 (6.7%)

* Recommended values are averages of analyses of these standards by two laboratories.

TABLE 6

Analyses of Resin Standards and Blanks

A. Standards

<u>No. of Analyses</u>	<u>Uranium Concentration, ppb</u>			<u>Standard Deviation, $\pm 1\sigma$</u>
	<u>Minimum</u>	<u>Maximum</u>	<u>Mean</u>	
40	0.246	0.352	0.303*	0.026 (8.5%)

B. Blanks

<u>Element</u>	<u>Number of Analyses Above Detection Limit</u>	<u>Mean Concentration,** ppb</u>	<u>Standard Deviation, $\pm 1\sigma$</u>
U	36	0.024	0.013
Cl	36	3700	370
Al	35	20	6
Na	21	150	70

* The standard solution was prepared to be 0.278 ppb. The value 0.303 ppb is not corrected for 0.024 $\pm$ 0.013 ppb U in resin.

** These values can be considered background contribution in all analyzed water (resin) samples. Note that traces of chloride used in processing resin remain in the resin. The mean values listed here are expressed in ppb for one liter of ion-exchange water.

TABLE 7

Analyses of DOE Standard Uranium Solutions

<u>Standard</u>	<u>No. of Analyses</u>	<u>Uranium Concentration, ppb</u>		<u>Standard Deviation, $\pm 1 \sigma$</u>
		<u>Nominal</u>	<u>Mean</u>	
A-1	10	0.82	0.82	0.053 (6.4%)
B-1	5	7.77	7.58	*
C-1	4	100.2	94.8	*

* Too few analyses for standard deviations to be meaningful.

RESULTS AND DISCUSSION OF THE DATA

Stream Sediment Samples

SRL experience suggests that most uranium in stream sediment samples is present in resistate minerals. Interpretation of the areal distribution (Figure B-4) of uranium is best done by studying the areal distributions of the ratio of uranium to geochemically associated elements such as Th, Hf(Zr), Ce, etc. Elemental associations suggested here should be considered speculative pending detailed mineralogical investigations.

A scheme for deducing possible mineral hosts of uranium in stream sediment samples is discussed by Price and Ferguson (1977). Uranium can occur as a minor constituent of several heavy resistate minerals such as zircon or monazite. These minerals have little current commercial potential as uranium ore minerals. Failure to consider the mineral host could lead to an inaccurate assessment of targets for more detailed study.

A map showing the total amount of uranium in a given stream sediment sample may be more a function of stream gradient or sampling conditions than of any proximity to a commercial uranium deposit. For example, if uranium were uniformly present in the mineral zircon at a concentration of 5000 ppm, then a uranium distribution map for stream sediment samples of less than 149 micrometers would have highs and lows which were functions of many factors. These include: (1) the areal distribution of zircon, (2) the areal distribution of zircon grain size, (3) the effectiveness of sampled streams in sorting and concentrating zircon relative to diluent minerals such as quartz or micas, and (4) the effectiveness of the sampling method in obtaining "representative" samples.

On the other hand, comparison of a map showing the distribution of uranium with a map showing the distribution of the U/Zr (or U/Hf) ratio should reveal the actual uranium-in-zircon concentration or any aberrance therefrom. The areal distribution of this ratio is presented in Figure 3. The ratio of (U/Hf) should be low where zircon is the primary mineral host of uranium in sediment samples. High values of the ratio indicate areas where uranium is present in minerals other than zircon or where zircon is particularly enriched in uranium.

Using the same logic, areas where the areal distribution of the U/Th ratio (Figure 4) is high indicates where uranium is present in minerals other than resistates such as monazite or where these resistates are particularly enriched in uranium. Anomalous areas which persist on several ratio figures may be areas where uranium is present in some mineral other than common

resistate minerals. If these anomalous areas are supported by other considerations (such as radioactivity highs, geologic conditions, or high values of dissolved uranium in natural waters), then they may warrant a detailed field examination or detailed geochemical sampling.

The limited areal extent of most formations makes the correlation of anomalies with rock types in the Albany quadrangle difficult. Figures 3, 4, B-4, and B-5 are interpreted to suggest that the uranium and thorium anomalies associated with the Kinsman Quartz Monzonite (Kqm) and the Brimfield Schist (Cb) probably are attributable to the mineral monazite.

Neutron activation analysis (NAA) results above the analytical detection limit are summarized in Table 9. The tabulated values are for sediments of less than 149 micrometers (U.S. Std. 100-mesh) collected from small streams. Sieved fractions of other sizes, or rock or soil samples, even though collected in the same region, might yield entirely different values because of mineralogical variations.

Stream and Ground Water Samples

Concentrations of uranium in stream and ground water samples are dependent on several factors: (1) the concentration of uranium in the rocks (soils) through which the water passes, (2) the rate at which the uranium-bearing minerals in the rocks (soils) will release uranium, (3) the hydrologic character of the rocks (soils), and (4) the chemistry of the water (especially Eh, pH, and alkalinity).

The interpretation of analyses of uranium in natural waters is not straightforward. In active roll-front deposits, solubility of uranium may be low. Concentrations of uranium in natural waters may be very low near areas of active uranium deposition or very high in oxidizing zones near dissolving ore bodies.

To eliminate the effect of increasing uranium with increasing dissolved solids, it is advisable to use the areal distribution of uranium/conductivity ratio instead of total uranium in natural waters. Figures 6 and 7 show the areal distribution of uranium/conductivity for ground water and stream water, respectively. The ratio has been multiplied by 1000 for convenience. The ratio gives an approximation of the proportion of uranium in the dissolved minerals in natural waters.

Interpretation of Figures 7, B-2, and C-1 suggests that the conductivity anomalies along the western edge of the Albany quadrangle are not related to uranium. Figures C-4, C-7, and C-8 indicate that

the anomalous area (along the Hudson River) can likely be attributed to brackish water.

Figures 6 and A-4 indicate a belt of anomalous uranium values exists in the southwestern and west-central portion of the quadrangle. These anomalies probably are associated with the meta-sediments of the Stockbridge Formation (OCs) and the Waloomsac Formation (Owl).

NAA results above the detection limits are summarized in Tables 8 and 10 for ground water and stream water, respectively.

ACKNOWLEDGMENTS

The geologic and uranium occurrence information included in this report was compiled for SRL by Professor Martin S. Rutstein of SUCNY New Paltz, New Paltz, N.Y. The hydrology information was provided by Harry E. LeGrand, Raleigh, N.C. Most of the surface and ground water samples were collected by Biospheric Consultants International, Inc., for DOE and supplied to SRL. Final drafting of the geologic and mineral prospect maps was performed by Jack S. Whisnant of Carolina Geoscience, Inc., Irmo, S.C.

TABLE 8

Statistical Summary of Field Measurements and Elemental Analyses - Ground Water

Variable	n*	Measured Values			Log Mean [¶] ($\Sigma \log_{10} x$) n	Log Std. [¶] Deviation	Standard Deviation $\pm 1\sigma$
		Maximum**	Minimum [†]	Mean ^{††}			
pH	664	9.7	4.8	7.2			0.8
Conductivity	663	2900	10.0		2.1	0.4	
Alkalinity	664	8.4	0.01		-0.08	0.6	
U	601	21.8	0.001		-0.9	0.8	
Al	636	1814	2.7		1.5	0.4	
Br	320	3400	4.8		1.5	0.4	
Cl	646	268,799	1400		3.9	0.4	
Dy	57	2.9	0.02		-0.3	0.6	
F	361	1511	7.0		1.7	0.5	
Mn	471	2136	1.2		1.7	0.5	
Na	639	94,399	290		3.7	0.5	
V	101	3.2	0.1		-0.3	0.3	

* Number of observations. Some values are missing for reasons other than being below detection limit.

** Elemental concentrations in ppb; conductivity in $\mu\text{mhos/cm}$; alkalinity in meq/L .

[†] Minimum or detection limit.

^{††} Mean of values above detection limit.

[¶] Log units.

TABLE 9

Statistical Summary of Field Measurements and Elemental Analyses - Sediment

Element	n*	Measured Values		Log Mean†† ($\Sigma \text{Log}_{10} x$)	Log. Std. Deviation
		Maximum**	Minimum†	n	
U	1319	34.3	0.3	0.55	0.23
Th	1277	311.0	2.0	1.06	0.32
Hf	1175	286.0	1.0	1.25	0.39
Al	901	118,099	4100	4.71	0.16
Ce	1287	1458.0	9.0	2.01	0.27
Fe	1285	275,899	7499	4.51	0.20
Mn	1096	8899	30.0	3.03	0.27
Na	1208	85,899	1100	4.10	0.21
Sc	1290	64.0	0.2	0.96	0.30
Ti	886	37,999	400	3.84	0.23
V	1175	320.0	10.0	1.78	0.24
Dy	694	47.3	0.2	0.77	0.39
Eu	957	17.3	0.5	0.32	0.24
La	1287	771.0	6.0	1.66	0.28
Lu	1271	3.9	0.1	0.2	0.22
Sm	1282	101.0	1.0	0.88	0.26
Yb	1176	26.1	1.1	0.64	0.22

* Number of observations.

** Elemental concentrations in ppm.

† Minimum or detection limit.

†† Mean of values above detection limit.

TABLE 10

Statistical Summary of Field Measurements and Elemental Analyses - Stream Water

Variable	n*	Measured Values			Log Mean [¶] ($\Sigma \log_{10} x$) n	Log Std. [¶] Deviation	Standard Deviation $\pm 1\sigma$
		Maximum**	Minimum [†]	Mean ^{††}			
pH	1301	9.3	4.0	7.1			0.8
Conductivity	1302	2300	13.0		2.0	0.4	
Alkalinity	1292	11.6	0.01		-0.32	0.6	
U	873	18.4	0.001		-1.3	0.7	
Al	1277	2135	1.3		1.9	0.3	
Br	814	8513	0.8		1.5	0.5	
Cl	1283	162,199	3000		3.9	0.3	
Dy	80	7.1	0.02		-0.8	0.7	
F	617	447	7.0		1.5	0.3	
Mn	1092	5414	0.3		1.7	0.5	
Na	1282	169,549	200		3.6	0.4	
V	383	48.9	0.1		-0.4	0.3	

* Number of observations. Some values are missing for reasons other than being below detection limit.

** Elemental concentrations in ppb; conductivity in $\mu\text{mhos/cm}$; alkalinity in meq/L .

† Minimum or detection limit.

†† Mean of values above detection limit.

¶ Log units.

ALBANY
LOG U/HF
1172

1x2 Sheet
In Sediments
Values Above D.L.

LOG U/HF

FIGURE 3. Areal Distribution of log (U/Hf) in Stream Sediment

ALBANY
LOG U/TH
1274 Values Above D.L.

1x2" Sheet
In Sediments

LOG U/TH

• < -1.16	○ -0.82--0.75	○ -0.62--0.54	⊙ -0.41--0.33	● -0.17--0.05
• -1.16--0.94	○ -0.75--0.68	○ -0.54--0.48	⊙ -0.33--0.25	◆ -0.05--0.12
• -0.94--0.82	○ -0.68--0.61	○ -0.48--0.41	● -0.25--0.17	★ > 0.12

FIGURE 4. Areal Distribution of log (U/Th) in Stream Sediment

ALBANY
LOG TH/LA
1277

1x2 Sheet
In Sediments
Values Above D.L.

LOG TH/LI

FIGURE 5. Areal Distribution of log (Th/La) in Stream Sediment

ALBANY
Ux1000/Cond. In Ground Water
600
1x2" Sheet
Values Above D.L.

Ux1000/Cond.

+ < 0.313	o 0.070- 0.109	o 0.333- 0.582	o 1.929- 4.726	● 16.565- 37.764
x 0.013- 0.027	o 0.109- 0.180	o 0.582- 1.044	o 4.726- 8.518	◆ 37.764- 56.000
o 0.027- 0.070	o 0.180- 0.333	o 1.044- 1.929	o 8.518- 16.565	★ > 56.000

FIGURE 6. Areal Distribution of U/Conductivity Values of Ground Water

ALBANY 1x2" Sheet
 Ux1000/Cond. In Surface Water
 873 Values Above D.L.

FIGURE 7. Areal Distribution of U/Conductivity Values of Stream Water.

CITED REFERENCES

- Adams, J. A., Kline, M. C., Richardson, K. A., and Rogers, J. J. W. 1962, **The Conway Granite of New Hampshire as a Major Low-Grade Thorium Resource:** Proc. Natl. Acad. Sci., Vol. 48, pp. 1898-1905.
- Armstrong, R. L., and Besancon, J., 1970, **A Triassic Time Scale Dilemma: K-Ar Dating of Upper Triassic Mafic Igneous Rocks; Eastern U.S.A. and Canada and Post-Triassic Plutons, Western Idaho, U.S.A.:** Eclogae Geol. Helv., Vol. 63, pp. 15-28.
- Baskerville, C., 1908, **The Rare Metals, IV - Tantalum:** Eng. Mining Journal, Vol. 86, p. 1100.
- Berry, W. B., 1968, "Ordovician Paleogeography of New England and Adjacent Areas Based on Graptolites," in Zen, E-an et al., eds., **Studies of Appalachian Geology, Northern and Maritime:** John Wiley and Sons, N.Y.
- Billings, M. P., 1937, **Regional Metamorphism of the Littleton-Moosilauke Area, New Hampshire:** Geol. Soc. Amer. Bull. 48, pp. 463-566.
- Billings, M. P., 1941, **Pegmatites of Massachusetts:** Mass. Department Public Works Bull. 5, 22 pp.
- Billings, M.P., 1955, **Geologic Map of New Hampshire:** New Hampshire Planning and Development Commission, Division of Geological Sciences; Harvard University, Cambridge, Massachusetts; and U.S. Geol. Survey, Washington, D.C.; Scale: 1:250,000.
- Billings, M. P., 1956, **The Geology of New Hampshire, Part II - Bedrock Geology:** New Hampshire State Planning and Development Commission, Concord, N.H., 203 pp.
- Billings, M. P., and Keevil, N., 1964, **Petrography and Radioactivity in Four Paleozoic Magma Series in New Hampshire:** Geol. Soc. Amer. Bull. 57, pp. 797-828.
- Bird, J. M., 1963, "Sedimentary Structures in the Taconic and Adjacent Regions," pp. 5-21 in Bird, J. M., ed., **Stratigraphy, Structure, Sedimentation and Paleontology of the Southern Taconic Region, Eastern New York:** Guidebook, Geol. Soc. Amer., N.E. Mtg., Albany, N.Y.

- Bird, J. M., and Dewey, J. F., 1970, **Lithosphere Plate-Continental Margin Tectonics and the Evolution of the Appalachian Orogen:** Geol. Soc. Amer. Bull. 81, pp. 1031-1060.
- Bray, J., 1939, **Ilmenite-Nematite-Magnetite Relations in Some Emery Ores:** Amer. Mineral., Vol. 24, pp. 162-170.
- Brookins, D. G., and Norton, S., 1975, **Rb/Sr Whole Rock Ages Along the Precambrian-Cambrian Contact, East Side of the Berkshire Massif, Massachusetts:** Abs., Geol. Soc. Amer. N.E. Ann. Mtg., Syracuse, N.Y.
- Cady, W., 1969, **Regional Tectonic Synthesis of Northwestern New England and Adjacent Quebec:** Geol. Soc. Amer. Mem. 120, 181 pp.
- Cameron, E. et al., 1954, **Pegmatite Investigations, 1942-45, New England:** U.S. Geol. Surv. Prof. Pap. 255, 352 pp.
- Chapman, C. A., 1968, "A Comparison of the Main Coastal Plutons and the Magmatic Central Complexes of New Hampshire," pp. 385-396 in Zen, E-an et al., **Studies of Appalachian Geology; Northern and Maritime:** John Wiley, New York, N.Y.
- Chidester, A. H., 1968, "Evolution of the Ultramafic Complexes of Northwestern New England," pp. 343-354 in Zen, E-an et al., eds., **Studies of Appalachian Geology; Northern and Maritime:** John Wiley, New York, N.Y.
- Chidester, A. H., Hatch, N. L., Jr., Osberg, P., Norton, S., and Hartshon, J., 1967, **Geologic Map of the Rowe Quadrangle, Franklin and Berkshire Counties, Massachusetts, and Bennington and Windham Counties, Vermont:** U.S. Geol. Survey, Geol. Quad. Map GQ-642.
- Cornet, B., and Traverse, A., 1973, **Fossil Spores, Pollen, and Fishes from Connecticut Indicate Early Jurassic Age for Part of the Newark Group:** Science, Vol. 182, pp. 1243-47.
- Cox, D. P., 1970, **Lead-Zinc-Silver Deposits Related to the White Mountain Plutonic Series in New Hampshire and Maine:** U.S. Geol. Surv. Bull. 1312-D, pp. D1-D18.
- Dale, T., 1923, **The Commercial Granites of New England:** U.S. Geol. Surv. Bull. 738, 488 pp.
- Dallmeyer, R. D., 1974, **Tectonic Setting of the Northeastern Reading Prong:** Geol. Soc. Amer. Bull. 85, pp. 131-34.

- Dallmeyer, R. D., 1975, **The Palisades Sill; A Jurassic Intrusion?:** Geology, Vol. 3, pp. 243-245.
- Dana, E. S., 1891, **A Textbook of Mineralogy:** 16th ed., John Wiley, New York, N.Y., 536 pp.
- Dixon, H. R., 1976, "Summary Discussion of Stratigraphy of Eastern Massachusetts and Connecticut," pp. 277-284 in Page, L., ed., **Contributions to the Stratigraphy of New England:** Geol. Soc. Amer. Mem. 148.
- Doll, C. G., Cady, W., Thompson, J. B., Jr., and Billings, M. P., 1961, compilers and eds., **Centennial Geologic Map of Vermont:** Vt. Geol. Surv., Montpelier, Vt., Scale 1:250,000.
- Drake, A. A., Jr., 1969, "Precambrian and Lower Paleozoic Geology of the Delaware Valley, New Jersey-Pennsylvania," pp. 51-131 in Subitzky, S., ed., **Geology of Selected Areas in New Jersey and Eastern Pennsylvania and Guidebook of Excursions:** Geol. Soc. Amer. Ann. Mtg., Atlantic City, N.J., Rutgers University Press, New Brunswick, N.J.
- Drobeck, P., and Rutstein, M. S., 1978, **Paleozoic "Polymetamorphism" of the Upper Cambrian Briarcliff Dolostone of Dutchess County, New York:** Geol. Soc. Amer., N.E. Ann. Mtg., Boston, Mass.
- D'Silva, A. P., Floyd, M. A., and Hass, W. J., Jr., **Multilaboratory Analytical Quality Control for the Hydrogeochemical and Stream Sediment Reconnaissance:** Iowa State University, Ames Laboratory, Ames, IA. A series of monthly reports sponsored by USDOE. Available from NTIS, Springfield, Va.
- Emerson, B. K., 1895, **A Mineralogical Lexicon of Franklin, Hampshire, and Hampden Counties, Massachusetts:** U.S. Geol. Surv. Bull. 126, 180 pp.
- Emerson, B., 1899, **The Geology of Eastern Berkshire County:** U.S. Geol. Surv. Bull. 159, 139 pp.
- Emerson, B. K., 1917, **Geology of Massachusetts and Rhode Island:** U.S. Geol. Surv. Bull. 597, 289 pp.
- Eskola, P. E., 1949, **The Problem of Mantled Gneiss Domes:** Geol. Soc. London, Quart. Jour., Vol. 104, pp. 461-476.
- Faul, H., Stern, T., Thomas, H., and Elmore, P., 1963, **Ages of Intrusion and Metamorphism in the Northern Appalachians:** Amer. J. Sci., Vol. 261, pp. 1-19.

- Fenneman, N. M., 1938, **Physiography of Eastern United States:** McGraw-Hill Book Co., New York, N.Y., 714 pp.
- Fisher, D. W., Isachsen, Y., and Richard, L., 1971, **Geologic Map of New York, 1970:** New York State Mus. and Sci. Serv., Map and Chart Ser. 15, colored map (1:250,000).
- Fisher, D. W., and Warthin, A. S., Jr., 1977, "Stratigraphic and Structural Geology in Western Dutchess County, New York," pp. B6-1 to B6-36 in Johnsen, J., ed., **Guidebook 48th Ann. Mtg.:** N.Y. State Geol. Assoc., Poughkeepsie, N.Y.
- Fletcher, F., 1967, "Middle and Upper Devonian Clastics of the Catskill Front," in Waines, R., ed., **Guidebook 39th Ann. Mtg.:** N.Y. State Geol. Assoc., New Paltz, N.Y., pp. C1-C23.
- Foland, K., and Faul, H., 1977, **Ages of the White Mountain Intrusives--New Hampshire, Vermont, and Maine:** Amer. J. Sci., Vol. 277, pp. 888-904.
- Foland, K., Quinn, A. W., and Giletti, B., 1971, **K-Ar and Rb-Sr Jurassic and Cretaceous Ages for Intrusives of the White Mountain Magma Series, Northern New England:** Amer. J. Sci., Vol. 270, pp. 321-330.
- Fronдел, C., Marvin, U., and Ito, J., 1960, **New Data on Birnessite and Hollandite:** Amer. Mineral., Vol. 45, pp. 871-875.
- Grew, E. S., 1970, **Geology of the Pennsylvanian and Pre-Pennsylvanian Rocks of the Worcester Area of Massachusetts:** Ph.D. thesis, Harvard Univ., Cambridge, Mass., 263 pp.
- Gilluly, J., 1966, **Orogeny and Geochronology:** Amer. J. Sci., Vol. 264, pp. 97-111.
- Hadley, J. B., 1964, "Correlation of Isotopic Ages, Crustal Heating and Sedimentation in the Appalachian Region," pp. 33-34 in Lowry, W. P., ed., **Tectonics of the Southern Appalachians:** Virginia Polytech. Inst., Dept. of Geol. Sci., Mem. 1.
- Hanshaw, P. M., and Barnett, P., 1960, **Possible Use of Boron Chromium and Nickel Content in Correlating Triassic Igneous Rocks in Connecticut:** U.S. Geol. Surv. Prof. Pap. 400, pp. B170-B172.
- Hatch, N. L., Jr., 1975, "Tectonic, Metamorphic, and Intrusive History of Part of the East Side of the Berkshire Massif, Massachusetts," pp. 51-62 in **Tectonic Studies of the Berkshire Massif; Western Massachusetts, Connecticut, and Vermont:** U.S. Geol. Survey Prof. Pap. 888-D.

- Hatch, N. L., Jr., 1976, **Redefinition of the Hawley and Goshen Schists in Western Massachusetts**: U.S. Geol. Survey Bull. 1254-D, 16 pp.
- Hatch, N. L., Jr., Schnabel, R., and Norton, S., 1968, "Stratigraphy and Correlation of the Rocks on the East Limb of the Berkshire Anticlinorium in Western Massachusetts and North-central Connecticut," pp. 177-184 in Zen, E-an et al., eds., **Studies of Appalachian Geology; Northern and Maritime**: John Wiley, New York, N.Y.
- Hepburn, J. C., 1972, "Geology of the Guilford Dome Area, Southeastern Vermont," pp. 231-243 in Doolan, B., and Stanley, R., eds., **Guidebook for Field Trips in Vermont: New England Intercollegiate Geol. Conf., 64th Ann. Mtg., Burlington, Vt.**
- Hobbs, W., 1893, **New Occurrences of Parallel Intergrowths of the Minerals Allanite and Epidote**: Amer. Geologist, Vol. 12, pp. 218-219.
- Huntington, J., 1975, **Mineralogy and Petrology of Metaphosed Iron-Rich Beds in the Lower Devonian Littleton Formation, Orange Area, Massachusetts**: M.S. Thesis, University of Massachusetts, Amherst, Mass., 106 pp.
- Johnson, D., 1951, **Reconnaissance of Radioactive Rocks of Massachusetts**: U.S. Geol. Surv. TEI-69, 18 pp.
- Laporte, L. F., 1967, **Carbonate Disposition near Mean Sea-Level and Resultant Facies Mosaic; Manlius Formation (Lower Devonian) of New York State**: Amer. Assoc. Petroleum Geol. Bull. 51, pp. 73-101.
- Leech, G. B., Lowden, J., Stockwell, C., and Wanless, R. K., 1963, **Age Determinations and Geological Studies (Rpt. 4)**: Canada Geol. Surv. Pap. 63-17, 140 pp.
- Lilly, H. D., 1966, **Late Precambrian and Appalachian Tectonics in the Light of Submarine Exploration of the Great Bank of Newfoundland and in the Gulf of St. Lawrence; Preliminary Views**: Amer. J. Sci., Vol. 264, pp. 569-574.
- Lowden, J. A., Stockwell, C., Tipper, H., and Wanless, R. K., 1963, **Age Determinations and Geologic Studies (Rpt. 3)**: Canada Geol. Surv. Pap. 62-17, 140 pp.
- Lucier, W., 1966, **The Petrology of the Middle and Upper Devonian Kiskatom and Kaaterskill Sandstones; a Vertical Profile**: Ph.D. Thesis, University of Rochester, Rochester, N.Y., 92 pp.

- Lyons, J. B., and Faul H., 1968, "Isotope Geochronology of the Northern Appalachians," pp. 305-318 in Zen, E-an et al., eds., **Studies of Appalachian Geology, Northern and Maritime:** John Wiley, New York, N.Y.
- Lyons, J. B., and Livingston, D. E., 1977, **Rb-Sr Age of the New Hampshire Plutonic Series:** Geol. Soc. Amer. Bull. 88, pp. 1808-1812.
- Mazzullo, S. J., 1978, **Early Ordovician Tidal Flat Sedimentation, Western Margin of Proto-Atlantic Ocean:** J. Sed. Petrol., Vol. 48, pp. 49-62.
- MacFadyen, J. A., Jr., 1956, **The Geology of the Bennington Area, Vermont:** Vermont Geol. Surv. Bull. 7, 72 pp.
- MacFall, R., 1958, **Gem Hunter's Guide:** Science and Mechanics Publishing Co., Chicago, Ill., 188 pp.
- McKeown, F., 1951, **Reconnaissance of Radioactive Rocks of Vermont, New Hampshire, Connecticut, Rhode Island, and Southeastern New York:** U.S. Geol. Surv. TEI-67.
- Mosier, M., and Thomas, M., 1949, **Investigation of the Anson Betts Manganese Mine, Hampshire County, Mass.:** U.S. Bur. Mines Rpt. Investig. 4443, 8 pp.
- Narten, P., and McKeown, F., 1952, **Reconnaissance of Radioactive Rocks of the Hudson Valley and the Adirondack Mountains, New York:** U.S. Geol. Surv. TEI-70, 54 pp.
- Naylor, R. S., 1968, "Origin and Regional Relationships of the Core-Rocks of the Oliverian Domes," pp. 231-240 in Zen, E-an et al., eds., **Studies of Appalachian Geology; Northern and Maritime:** John Wiley, New York, N.Y.
- Naylor, R. S., 1967, **A Field and Coochronologic Study of Mantled Gneiss Domes in Central New England:** Ph.D. Thesis, California Instit. Tech., Pasadena, Calif., 123 pp.
- NOAA, 1977, U.S. Department of Commerce, National Climatic Center, Asheville, N.C.
- Norton, S. A., 1975, "Stratigraphic and Structural Relationships along the East Side of the Berkshire Massif, Massachusetts," pp. 166-178 in Ratcliffe, N., ed., **Guidebook for Field Trips in Western Massachusetts, Northern Connecticut and Adjacent Areas of New York:** New England Intercollegiate Geol. Conf., 67th Ann. Mtg.

- Page, L., 1968, "Devonian Plutonic Rocks in New England," pp. 371-373 in Zen, E-an et al., **Studies of Appalachian Geology; Northern and Maritime:** John Wiley, New York, N.Y.
- Page, J., and Larrabee, D., 1962, **Beryl Resources of New Hampshire:** U.S. Geol. Surv. Prof. Pap. 353, 49 pp.
- Pavlides, L., Boucot, A., and Skidmore, W., 1968, "Stratigraphic Evidence for the Taconic Orogeny in the Northern Appalachians," pp. 61-82 in Zen, E-an et al., eds., **Studies of Appalachian Geology; Northern and Maritime:** John Wiley and Sons, New York, N.Y.
- Peck, J., 1976, "Silurian and Devonian Stratigraphy in the Clinton Quadrangle, Central Massachusetts," pp. 241-251 in Page, L., ed., **Contributions to the Stratigraphy of New England:** Geol. Soc. Amer. Mem. 148.
- Peper, J., and Pease, M. H., Jr., 1976, "Summary of Stratigraphy in the Brimfield Area, Connecticut and Massachusetts," pp. 253-270 in Page, L., ed., **Contributions to the Stratigraphy of New England:** Geol. Soc. Amer. Mem. 148.
- Rast, N., Skehan, S. J., and Murray, D., 1978, **The Correlation of the Avalonian Precambrian and Lower Paleozoic Rocks of Eastern Maritimes (Canada) and Southeastern New York:** Abs., Geol. Soc. Amer., N.E. Mtg., Boston, Mass.
- Ratcliffe, N., 1975, "Cross-Section of the Berkshire Massif at 42°N; Profile of a Basement Reactivation Zone," pp. 186-219 in Ratcliffe, N., ed., **Guidebook for Field Trips in Western Massachusetts, Northern Connecticut, and Adjacent Areas of New York:** New England Intercollegiate Geol. Conf., 67th Ann. Mtg.
- Ratcliffe, N. M., and Harwood, D. S., 1975, "Blastomylonites Associated with Recumbent Folds and Overthrusts at the Western Edge of the Berkshire Massif, Connecticut and Massachusetts--A Preliminary Report," pp. 1-19 in **Tectonic Studies of the Berkshire Massif, Western Massachusetts, Connecticut, and Vermont:** U.S. Geol. Surv. Prof. Pap. 888-A.
- Ratcliffe, N., and Mose, D., 1978, **Probable Taconic Age of the Middlefield Thrust Zone, Eastern Margin of the Berkshire Massif, Massachusetts, on the Basis of Rb/Sr Geochronology of Intrusive Granitic Rock:** Abs., Geol. Soc. Amer., N.E. Ann. Mtg., Boston, Mass.

- Ratcliffe, N., and Zartman, R., 1976, "Stratigraphy, Isotopic Ages, and Deformational History of Basement and Cover Rocks of The Berkshire Massif, Southwestern Massachusetts," pp. 373-412 in Page, L., ed., **Contributions to the Stratigraphy of New England**: Geol. Soc. Amer. Mem. 148.
- Robinson, P., 1978, **The Bronson Hill Anticlinorium and Merrimack Synclinorium in Central Massachusetts--An Acadian "Pennine Zone"**: Abs., Geol. Soc. Amer., N.E. Ann. Mtg., Boston, Mass.
- Rodgers, J., 1952, **Absolute Ages of Radioactive Minerals from the Appalachian Region**: Amer. J. Sci., Vol. 250, pp. 411-427.
- Rodgers, J., 1968, "The Eastern Edge of the North American Continent During the Cambrian and Early Ordovician," pp. 141-149 in Zen, E-an et al., eds., **Studies of Appalachian Geology; Northern and Maritime**: John Wiley, New York, N.Y.
- Rodgers, J., 1970, **The Tectonics of the Appalachians**: John Wiley, New York, N.Y., 271 pp.
- Rodgers, J., Gates, R., Cameron, E., Ross, R., Jr., 1956, **Geologic Map of Connecticut (preliminary)**: Connecticut Geological and Natural History Survey, Scale 1:253:440.
- Rosenfeld, J., 1968, "Garnet Rotations Due to Major Peleozoic Deformations in Southeast Vermont," pp. 185-202 in Zen, E-an et al., eds., **Studies of Appalachian Geology; Northern and Maritime**: John Wiley, New York, N.Y.
- Ruedemann, R., 1931, **Age and Origin of the Siderite and Limonite of the Burden Iron Mines near Hudson, New York**: N.Y. State Mus. Bull. 286, pp. 135-152.
- Ruedemann, R., 1942, **Geology of the Catskill and Kaaterskill Quadrangles, Part I, Cambrian and Ordovician Geology of the Catskill Quadrangle**: N.Y. State Mus. Bull. 331, 188 pp.
- Schnabel, R., 1976, "Pre-Silurian Stratigraphy in South-Central Massachusetts and North-Central Connecticut," pp. 285-299 in Page, L., ed., **Contributions to the Stratigraphy of New England**: Geol. Soc. Amer. Mem.
- Skehan, J. W., 1968, "Fracture Tectonics of Southeastern New England, as Illustrated by the Wachusett-Marlborough Tunnel, East-Central Massachusetts," pp. 281-290 in Zen, E-an et al., eds., **Studies of Appalachian Geology; Northern and Maritime**: John Wiley, New York, N.Y.

Skehan, J. W., 1971, **The Green Mountain Anticlinorium in the Vicinity of Wilmington and Woodford, Vermont:** Vermont Geol. Surv. Bull. 17, 159 pp.

Skehan, J. W., 1972, "Stratigraphic and Structural Problems of the Southern Part of the Green Mountain Anticlinorium, Bennington-Wilmington, Vermont," pp. 245-267 in Drolan, B., and Stanley, R., eds., **Guidebook for Field Trips in Vermont:** New England Intercollegiate Geol. Conf., 64th Ann. Mtg., Burlington, Vt.

Skehan, J.W., and Abu-Moustafu, A. A., 1976, "Stratigraphic Analysis of Rocks Exposed in the Wachusett-Marlborough Tunnel, East-Central Massachusetts," in Page, L., ed., **Contributions to the Stratigraphy of New England:** Geol. Soc. Amer. Mem. 148.

Skehan, J. W., and Hepburn, J. C., 1972, "Stratigraphy of the East Flank of the Green Mountain Anticlinorium, Southern Vermont," pp. 3-26 in Doolan, B., and Stanley, R., eds., **Guidebook for Field Trips in Vermont:** New England Intercollegiate Geol. Conf., 64th Ann. Mtg., Burlington, Vt.

Smith, E., and Parsons, W., 1938, **Studies in Mineral Fluorescences:** Amer. Mineral., Vol. 23, pp. 513-521.

Spooner, C. M., and Fairbairn, H. W., 1970, **Relation of Radiometric Age of Granitic Rocks near Calais, Maine, to the Time of Acadian Orogeny:** Geol. Soc. Amer. Bull. 81, pp. 3663-3670.

SRL-138, **Savannah River Laboratory Quarterly and Semiannual Reports, Hydrogeochemical and Stream Sediment Reconnaissance, National Uranium Resource Evaluation Program:** E. I. du Pont de Nemours & Co., Savannah River Laboratory, Aiken, S.C.

No.	Period	SRL Doc. No.	DOE-GJ
			Doc. No.*
1	January-March 1975	DPST-75-138-1	GJBX-5(76)
2	April-June 1975	DPST-75-138-2	GJBX-6(76)
3	July-September 1975	DPST-75-138-3	GJBX-7(76)
4	October-December 1975	DPST-75-138-4	GJBX-8(76)
5	January-March 1976	DPST-76-138-1	GJBX-17(76)
6	April-June 1976	DPST-76-138-2	GJBX-27(76)
7	July-September 1976	DPST-76-138-3	GJBX-63(76)
8	October-December 1976	DPST-76-138-4	GJBX-6(77)
9	January-March 1977	DPST-77-138-1	GJBX-35(77)
10	April-June 1977	DPST-77-138-2	GJBX-55(77)
11	July-September 1977	DPST-77-138-3	GJBX-90(77)
12	October-December 1977	DPST-77-138-4	GJBX-37(78)
13	January-March 1978	DPST-78-138-1	GJBX-66(78)
14	April-September 1978	DPST-78-138-2	GJBX-13(79)
15	October-March 1979	DPST-79-138-1	GJBX-86(79)

SRL-146, **SRL-NURE Data Releases**, E. I. du Pont de Nemours & Co.
Savannah River Laboratory, Aiken, S.C.

No.	NTMS 1° x 2°	SRL Doc. No.	DOE-GJ
	Quadrangle		Doc. No.*
1	Winston-Salem†	DPST-77-146-1	GJBX-66(77)
2	Spartanburg	DPST-77-146-2	GJBX-09(78)
3	Charlotte	DPST-78-146-1	GJBX-40(78)
4	Greenville	DPST-78-146-2	GJBX-47(78)
5	Winston-Salem††	DPST-78-146-3	GJBX-58(78)
6	Greensboro	DPST-78-146-4	GJBX-74(78)
7	Knoxville	DPST-78-146-5	GJBX-75(79)
8	Scranton	DPST-78-146-6	GJBX-02(79)
9	Athens	DPST-78-146-7	GJBX-20(79)
10	Harrisburg	DPST-79-146-1	GJBX-31(79)
11	Portland	DPST-79-146-2	GJBX-28(79)
12	Glens Falls	DPST-79-146-3	GJBX-44(79)
13	Augusta	DPST-79-146-4	GJBX-45(79)
14	Dyersburg	DPST-79-146-5	GJBX-58(79)
15	Poplar Bluff	DPST-79-146-6	GJBX-63(79)
16	Hartford	DPST-79-146-7	(in process)
17	Williamsport	DPST-79-146-8	(in process)
18	Newark	DPST-79-146-9	(in process)
19	Albany	DPST-79-146-10	(this report)

† Sediment only. †† Ground water only.

Stanley, R., and Hatch, N. L., Jr., 1976, "Discussion: Early Paleozoic Stratigraphy of Western Massachusetts and Connecticut and Southeastern New York," pp. 351-356 in Page, L., ed., **Contributions to the Stratigraphy of New England: Geol. Soc. Amer. Mem.**, 148.

Thompson, J. B., Jr., Robinson, P., Clifford, T., and Trask, N., Jr., 1968, "Nappes and Gneiss Domes in West-Central New England," pp. 203-218 in Zen, E-an et al., eds., **Studies of Appalachian Geology; Northern and Maritime: John Wiley**, New York, N.Y.

Tourtelot, E., and Vine, V., 1976, **Copper Deposits in Sedimentary and Volcanogenic Rocks: U.S. Geol. Surv. Prof. Pap. 907-C**, pp. C1-C34.

* DOE-GJ reports are available on microfiche from the Grand Junction Office, DOE, for \$6.00. Prepaid orders should be sent to: Bendix Field Engineering Corporation, Technical Library, P.O. Box 1569, Grand Junction, CO 81501. Checks or money orders should be made out to Bendix Field Engineering Corporation, the operations contractor for DOE's Grand Junction Office.

U. S. Bureau of Census, **Census of Population, 1970, and Census of Agriculture, 1970**, Washington, D.C.

Van Houten, F. B., 1969, "Late Triassic Newark Group, North-Central New Jersey and Adjacent Pennsylvania and New York," pp. 314-347 in Subitzky, S., ed., **Geology of Selected Areas in New Jersey and Eastern Pennsylvania and Guidebook of Excursions**: Geol. Soc. Amer. Ann. Mtg., Atlantic City, N.J., Rutgers Univ. Press, New Brunswick, N.J.

White, W. S., and Jahns, R., 1950, **Structure of Central and East-Central Vermont**: J. Geology, Vol. 58, pp. 179-220.

Young, D., 1971, **Precambrian Rocks of the Late Hopatcong Area, New Jersey**: Geol. Soc. Amer. Bull. 82, pp. 143-158.

Zen, E-an, 1967, **Time and Space Relationships of the Taconic Allochthon**: Geol. Soc. Amer. Spec. Paper 97, 107 pp.

Zen, E-an, 1968, "Nature of the Ordovician Orogeny in the Taconic Area," pp. 129-139 in Zen, E-an et al., eds., **Studies of Appalachian Geology; Northern and Maritime**: John Wiley, New York, N.Y.

Zen, E-an, 1972, **The Taconized Zone and the Taconic Orogeny in the Western Part of the Northern Appalachian Orogen**: Geol. Soc. Amer. Spec. Pap. 135, 72 pp.

RELATED GEOLOGIC REFERENCES

- Bird, J. M., and Rasetti, F., 1968, **Lower, Middle, and Upper Cambrian Faunas in the Taconic Sequence of Eastern New York; Stratigraphic and Biostratigraphic Significance:** Geol. Soc. Amer. Spec. Pap. 113, 66 pp.
- Brophy, G. P., Foose, R., Shaw, F., and Szekely, T., 1967, "Triassic Geologic Features in the Connecticut Valley near Amherst, Massachusetts," pp. 61-72 in Robinson, P., ed., **Field Trips in The Connecticut Valley, Massachusetts:** New England Intercollegiate Geol. Conf., 59th Ann. Mtg.
- Cady, W., Albee, A., and Chidester, A. H., 1963, **Bedrock Geology and Asbestos Deposits of the Upper Missisquoi Valley and Vicinity, Vermont:** U.S. Geol. Surv. Bull. 1122B, 78 pp.
- Chidester, A. H., 1962, **Petrology and Geochemistry of Selected Talc-Bearing Ultramafic Rocks and Adjacent Country Rocks in North-Central Vermont:** U.S. Geol. Surv. Prof. Pap. 345, 207 pp.
- Chute, N. E., 1945, **The Talc, Soapstone, and Asbestos Deposits of Massachusetts:** U.S. Geol. Survey Open-File Rept., 42 pp.
- Dixon, H. R., and Lundgren, L., Jr., 1968, "Structure of Eastern Connecticut," pp. 219-229 in Zen, E-an et al., eds., **Studies of Appalachian Geology; Northern and Maritime:** John Wiley, New York, N.Y.
- Gates, R. M., and Christensen, N., 1965, **Bedrock Geology of the West Torrington Quadrangle:** Conn. State Geol. and Nat'l Hist. Surv., Quad. Rpt. 17, 38 pp.
- Grew, E. S., 1973, **Stratigraphy of the Pennsylvanian and Pre-Pennsylvanian Rocks of the Worcester Area:** Amer. J. Sci., Vol. 273, pp. 113-129.
- Hepburn, J. C., 1975, "Tectonic and Metamorphic Chronology of the Devonian and Silurian Rocks in the Guilford Dome Area, Southeastern Vermont," pp. 39-49 in **Tectonic Studies of the Berkshire Massif, Western Massachusetts, Connecticut, and Vermont:** U.S. Geol. Surv. Prof. Pap. 888-C.
- Herz, N. L., 1961, **Bedrock Geology of the North Adams Quadrangle, Massachusetts and Vermont:** U.S. Geol. Surv. Quad. Map, GQ 139.

- Lundgren, L. W., Jr., 1962, **Deep River Area, Connecticut - Stratigraphy and Structure:** Amer. J. Sci., Vol. 260, pp. 1-23.
- Narten, R. S., 1969, **Age and Origin of the Oliverian Domes, Central-Western New Hampshire:** Geol. Soc. Amer. Bull. 80, pp. 405-428.
- Norton, S. A., 1969, "Unconformities at the Northern End of the Berkshire Highlands," pp. 21-1 to 21-20 in Bird, J. M., ed., **Guidebook for Field Trips in New York, Massachusetts, and Vermont:** New England Intercollegiate Geol. Conf. 61st Ann. Mtg., Albany, N.Y.
- Norton, S., 1976, "Hoosac Formation (Early Cambrian or Older) on the East Limb of the Berkshire Massif, Western Massachusetts," pp. 357-371 in Page, L., ed., **Contributions to the Stratigraphy of New England:** Geol. Soc. Amer. Mem. 148.
- Palmer, A. R., 1971, "The Cambrian of the Appalachian and Eastern New England Regions, Eastern United States," pp. 170-214 in Holland, C., ed., **Cambrian of the New World:** Interscience, New York, N.Y.
- Ratcliffe, N., Bird, J., and Bahrami, B., 1975, "Structural and Stratigraphic Chronology of the Taconide and Acadian Polydeformational Belt of the Central Taconics of New York State and Massachusetts," pp. 55-86 in Ratcliffe, N., ed., **Guidebook for Field Trips in Western Massachusetts, Northern Connecticut and Adjacent Areas of New York:** 67th Ann. Mtg., New England Intercollegiate Geological Conference.
- Shaub, B., and Schenck, B., 1954, **Pollucite from Lithia, Massachusetts:** Amer. Mineral., Vol. 39, pp. 661-664.
- Skehan, J. W., and Hepburn, J. C., 1962, "Stratigraphy of the East Flank of the Green Mountain Anticlinorium, Southern Vermont," pp. 3-26 in Doolan, B., and Stanley, R., eds., **Guidebook for Field Trips in Vermont:** New England Intercollegiate Geol. Conf., 64th Ann. Mtg., Burlington, Vt.
- Thompson, J. B., 1956, **Skitchewaig Nappe, a Major Recumbent Fold in the Area near Claremont, New Hampshire:** Abs., Geol. Soc. Amer. Bull. 67, pp. 1826-1827.
- U.S. Geol. Survey (Trace Elements Staff), 1953, **Search for and Geology of Radioactive Deposits; Semiannual Progress Report, Dec. 1, 1952, to May 31, 1953:** U.S. Geol. Surv. TEI-330, 302 pp.

Wilson, J. L., 1957, **Geography of Olenid Trilobite Distribution and Its Influence on Cambro-Ordovician Correlation:** Amer. J. Sci., Vol. 255, pp. 321-340.

Wolfe, C. W., 1952, "Outstanding Pegmatites of Maine and New Hampshire," pp. 76-99 in Billings, M. et al., eds., **Geology of the Appalachian Highlands of East-Central New York, Southern Vermont, and Southern New Hampshire; Guidebook for Field Trips in New England:** Geol. Soc. Amer., 65th Ann. Mtg. Boston, Mass.

Zen, E-an, 1964, **Taconic Stratigraphic Names; Definitions and Synonyms:** U.S. Geol. Surv. Bull, 1174, 95 pp.

APPENDIX A: Ground Water Reconnaissance Data

Key data reported for ground water sites include:

- water chemistry measurements (pH, conductivity, and alkalinity)
- information on well water source
- elemental analyses (in order of appearance in figures) for U, Br, Cl, F, Mn, Na, V, and graphic presentation only of Al and Dy analyses

LIST OF FIGURES

- A-1 Areal Distribution of Ground Water pH Values
- A-2 Areal Distribution of Ground Water Conductivity
- A-3 Areal Distribution of Values of Ground Water Alkalinity
- A-4 Areal Distribution of Uranium Concentrations in Ground Water.
- A-5 Areal Distribution of Bromine Concentrations in Ground Water
- A-6 Areal Distribution of Chlorine Concentrations in Ground Water
- A-7 Areal Distribution of Fluorine Concentrations in Ground Water
- A-8 Areal Distribution of Manganese Concentrations in Ground Water
- A-9 Areal Distribution of Sodium Concentrations in Ground Water
- A-10 Areal Distribution of Vanadium Concentrations in Ground Water
- A-11 Areal Distribution of Aluminum Concentrations in Ground Water
- A-12 Areal Distribution of Dysprosium Concentrations in Ground Water

Figures on Microfiche:

Log Histograms and Cumulative Frequency Plots for pH, Conductivity, Alkalinity, U, Br, Cl, F, Mn, V, Al, and Dy; see microfiche labeled "Ground Water Plots."

LIST OF TABLES

- A-1 Key Field Measurements and Analytical Data - Ground Water
- A-2 Supplementary Field and Analytical Data - Ground Water
(See Microfiche Cards "Table A-2 Supp. Data" and "Ground Water Plots")

ALBANY
pH In Ground Water
664 Values Above D.L.

1'x2' Sheet

pH		pH units		
+ < 5.1	o 5.8- 6.1	○ 6.6- 6.9	⊙ 7.5- 7.8	● 8.3- 8.7
x 5.1- 5.5	o 6.1- 6.3	○ 6.9- 7.2	⊙ 7.8- 8.0	◆ 8.7- 9.2
• 5.5- 5.8	○ 6.3- 6.6	○ 7.2- 7.5	⊙ 8.0- 8.3	★ > 9.2

FIGURE A-1. Areal Distribution of Ground Water pH Values

ALBANY 1x2' Sheet
Conductivity In Ground Water
663 Values Above D.L.

Conductivity - micro-mhos per cm.

+ < 12.0	○ 25.0- 35.0	○ 78.0- 110.0	⊙ 220.0- 302.0	● 430.0- 600.0
x 12.0- 20.0	○ 35.0- 50.0	○ 110.0- 150.0	⊙ 302.0- 368.0	◆ 600.0- 1030.0
• 20.0- 25.0	○ 50.0- 78.0	○ 150.0- 220.0	⊙ 368.0- 430.0	★ > 1030.0

FIGURE A-2. Areal Distribution of Ground Water Conductivity

ALBANY *1x2' Sheet*
Alkalinity In Ground Water
664 Values Above D.L.

Alkalinity - milliequivalent/liter				
+ < 0.02	o 0.06- 0.14	○ 0.43- 0.83	⊙ 2.00- 3.00	● 4.50- 5.20
x 0.02- 0.02	o 0.14- 0.24	○ 0.80- 1.43	⊙ 3.00- 3.90	◆ 5.20- 7.20
• 0.02- 0.06	o 0.24- 0.40	○ 1.40- 2.03	⊙ 3.90- 4.50	★ > 7.20

FIGURE A-3. Areal Distribution of Values of Ground Water Alkalinity

ALBANY 1°x2° Sheet
 Uranium In Ground Water
 601 Values Above D.L.

Uranium concentration - p.p.b.					
+ < 0.001	○ 0.007- 0.011	○ 0.036- 0.067	⊙ 0.320- 0.677	● 2.632- 5.995	
* 0.001- 0.003	○ 0.011- 0.019	○ 0.067- 0.158	⊙ 0.677- 1.412	◆ 5.995- 9.635	
• 0.003- 0.007	○ 0.019- 0.036	○ 0.158- 0.320	⊙ 1.412- 2.632	★ > 9.635

FIGURE A-4. Areal Distribution of Uranium Concentrations in Ground Water

FIGURE A-5. Areal Distribution of Bromine Concentrations in Ground Water

ALBANY
Chlorine In Ground Water
646 Values Above D.L.

1x2' Sheet

Chlorine concentration - p.p.b.

+ < 2200.0	○ 3400.0- 3600.0	○ 4300.0- 5000.0	⊙ 10300.0- 16200.0	● 40700.0- 69200.0
* 2200.0- 3130.0	○ 3600.0- 3900.0	○ 5000.0- 6700.0	⊙ 16200.0- 26100.0	◆ 69200.0- 146500.0
• 3100.0- 3400.0	○ 3900.0- 4300.0	○ 6700.0- 10300.0	⊙ 26100.0- 40700.0	★ > 146500.0

FIGURE A-6. Areal Distribution of Chlorine Concentrations in Ground Water

A-10

ALBANY
Fluorine In Ground Water
361
1'x2' Sheet
Values Above D.L.

Fluorine concentration - p.p.b.

+ < 8.0	○ 11.0- 13.0	○ 23.0- 34.0	⊙ 81.0- 135.0	● 329.0- 550.0
× 8.0- 8.0	○ 13.0- 17.0	○ 34.0- 51.0	⊙ 135.0- 228.0	◆ 550.0- 824.0
· 8.0- 11.0	○ 17.0- 23.0	○ 51.0- 81.0	⊙ 228.0- 329.0	★ > 824.0

FIGURE A-7. Areal Distribution of Fluorine Concentrations in Ground Water

ALBANY *1x2' Sheet*
Manganese In Ground Water
471 Values Above D.L.

Manganese concentration - p.p.b.

+ < 3.6	○ 7.2- 9.6	○ 28.8- 48.2	⊙ 103.1- 134.5	● 209.0- 310.2
x 3.6- 4.9	○ 9.6- 17.3	○ 48.2- 76.2	⊙ 134.5- 167.1	◆ 310.2- 745.5
• 4.9- 7.2	○ 17.3- 28.8	⊙ 76.2- 103.1	⊙ 167.1- 209.0	★ > 745.5

FIGURE A-8. Areal Distribution of Manganese Concentrations in Ground Water

ALBANY
Sodium
639

1x2' Sheet
In Ground Water
Values Above D.L.

Sodium concentration - p.p.b.

• < 340.0	○ 770.0- 1070.0	○ 3320.0- 5200.0	⊙ 9230.0- 14350.0	● 36540.0- 52550.0
• 340.0- 530.0	○ 1070.0- 1670.0	○ 5200.0- 7130.0	⊙ 14350.0- 22290.0	◆ 52550.0- 80520.0
• 530.0- 770.0	○ 1670.0- 3320.0	○ 7130.0- 9230.0	⊙ 22290.0- 36540.0	★ > 80520.0

FIGURE A-9. Areal Distribution of Sodium Concentrations in Ground Water

FIGURE A-10. Areal Distribution of Vanadium Concentrations in Ground Water

ALBANY *1'x2' Sheet*
Aluminum In Ground Water
636 Values Above D.L.

Aluminum concentration - p.p.b.					
+ < 4.4	o 8.3- 10.0	○ 15.2- 29.9	⊙ 61.7- 81.2	● 139.9- 218.5	
x 4.4- 5.9	o 10.0- 12.0	○ 29.9- 51.7	⊙ 81.2- 99.6	◆ 218.5- 452.4	
• 6.9- 8.3	○ 12.0- 16.2	○ 51.7- 61.7	⊙ 99.6- 139.9	★ > 452.4

FIGURE A-11. Areal Distribution of Aluminum Concentrations in Ground Water

A-15

FIGURE A-12. Areal Distribution of Dysprosium Concentrations in Ground Water

TABLE A-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -GROUND WATER-- ALBANY SHEET

1

SRL I.D. *****	DOE I.D.		PH	COND. UM/CM	AKMXD MEQ/L	U PPB	DEPTH FEET	BR PPB	CL PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
CTHA511R	09-42.0120-	72.6730-4-52-000	8.2	218	2.70	1.803	U	34.3	4900	62	M	126.5	12070	0.7	8.27
CTHA512R	09-42.0164-	72.7113-4-52-000	7.8	315	2.50	1.587	190	24.4	3900	338	M	115.7	13450	0.2	5.04
CTHA550R	09-42.0058-	72.8442-4-52-000	7.0	68	0.70	0.722	200	38.9	5200	32	M	90.3	8330	0.8	10.62
CTHA551R	09-42.0101-	72.8869-4-52-000	6.0	94	0.50	0.028	35		6300	13	M	88.9	9190	-0.1	0.30
CTHA558R	09-42.0027-	72.5826-4-52-000	8.4	136	1.30	0.153	80	10.1	8900		M	95.3	9830	1.6	1.13
CTHA569R	09-42.0027-	73.0010-4-52-000	6.6	61	1.00	0.428	U	48.7	4000	29	M	84.9	7590	0.2	7.02
CTHA571R	09-42.0133-	72.9666-4-52-000	6.1	52	0.60	0.050	25	33.5	5100	14	M	114.7	8300	0.2	0.96
CTL1647R	09-42.0228-	73.4191-4-52-000	7.6	191	3.20	0.337	100		2800	8	M	39.6	1710	-0.1	1.76
CTL1648R	09-42.0329-	73.3880-4-52-000	7.3	600	8.40	0.310	80		19000		M		23040	-0.1	0.52
CTL1649R	09-42.0178-	73.3444-4-52-000	7.5	242	4.00	0.218	90		4300		M	24.8	4750	-0.1	0.90
CTL1659R	09-42.0233-	73.2919-4-53-000	7.2	382	7.20	0.572	0		11100	13	M		11540	-0.1	1.50
CTL1660R	09-42.0183-	73.2463-4-52-000	7.5	342	5.70	2.606	150	14.5	7800	33	M	167.1	8620	-0.1	7.62
CTL1661R	09-42.0013-	73.2162-4-52-000	7.3	273	4.00	0.292	30	19.4	16700	27	M	130.1	19180	-0.1	1.07
CTL1662R	09-42.0148-	73.1767-4-52-000	7.9	128	1.60	0.581	50	29.8	6400	47	M	105.3	8680	1.1	4.54
CTL1663R	09-42.0242-	73.1237-4-52-000	7.2	50	0.60	-0.002	80	18.8	3800	24	M	87.7	8860	-0.1	-0.03
CTL1664R	09-42.0127-	73.0868-4-52-000	7.2	35	0.34	0.007	U	12.8	4400	23	M	93.8	7940	0.4	0.20
CTL1665R	09-42.0116-	73.0598-4-52-000	7.0	138	1.60	0.260	U	28.8	11900		M	97.9	9850	-0.1	1.88
CTT0530R	09-42.0069-	72.3046-4-52-000	7.0	70	0.80	-0.002	180	15.8	4700	128	M	65.3	10000	-0.1	-0.02
MABE501R	25-42.6500-	72.9779-4-52-000	6.4	180	0.28	0.015	20		M		M		20190	-0.1	0.08
MABE502R	25-42.6867-	73.0030-4-53-000	6.8	20	0.12	0.001	0		5700		M		M	-0.1	0.05
MABE503R	25-42.6973-	73.0484-4-52-000	7.0	95	1.50	0.610	131	27.0	3700	49	M	30.4	3980	-0.1	6.42
MABE504R	25-42.7251-	73.0948-4-52-000	7.2	110	0.52	0.018	20		5800		M		3340	-0.1	0.16
MABE505R	25-42.6870-	73.1698-4-52-000	7.3	130	2.00	0.337	4		3500	8	M		1600	-0.1	2.59
MABE506R	25-42.6201-	73.0802-4-52-000	7.5	20	0.10	0.019	6	24.6	3300	11	M	22.7	2270	-0.1	0.95
MABE507R	25-42.6082-	73.0479-4-52-000	7.2	120	1.30	0.017	4	21.4	5600	22	M	20.2	3200	-0.1	0.14
MABE508R	25-42.6490-	73.0475-4-52-000	6.7	130	1.50	0.119	200	23.1	5000	20	M	62.9	2720	-0.1	0.92
MABE509R	25-42.6033-	72.9862-4-52-000	7.0	20	0.10	-0.002	U	12.1	3000	7	M	19.7	2300	-0.1	-0.09
MABE510R	25-42.5521-	72.9873-4-52-000	6.8	125	0.80	0.027	175		4100		M		M	-0.1	0.22
MABE511R	25-42.5646-	73.0291-4-52-000	6.8	140	1.80	0.170	150	34.1	6400	117	M	44.7	3310	-0.1	1.21
MABE512R	25-42.5836-	73.0895-4-52-000	7.2	110	1.20	0.003	8		4400		M		650	-0.1	0.03
MABE513R	25-42.5593-	73.1014-4-52-000	7.0	430	4.50	0.701	28	13.9	19700		M	169.6	730	-0.1	1.63
MABE514R	25-42.5578-	73.1290-4-53-000	7.6	50	0.32	0.065	0		4600		M	17.7	340	-0.1	1.30
MABE515R	25-42.5393-	73.1881-4-52-000	7.4	160	2.20	0.239	U		3500		M	20.5	540	-0.1	1.49
MABE516R	25-42.5213-	73.1918-4-52-000	7.4	130	1.50	0.042	U		3300		M	23.3	470	-0.1	0.32
MABE517R	25-42.4735-	73.1351-4-52-000	7.5	225	2.90	4.341	260		4700	24	M	53.2	1020	0.9	19.29
MABE518R	25-42.4613-	73.0951-4-52-000	7.7	145	1.70	0.310	U		3600	26	M	25.1	680	-0.1	2.14
MABE519R	25-42.5042-	73.0826-4-53-000	7.8	50	0.40	0.051	0		4300	12	M	10.2	800	-0.1	1.02
MABE520R	25-42.4958-	73.0331-4-53-000	7.7	35	0.18	0.017	0		3300	9	M		380	0.2	0.49
MABE521R	25-42.4791-	73.0186-4-53-000	7.0	40	0.28	-0.002	0		3600		M	7.1	410	-0.1	-0.04
MABE522R	25-42.4328-	73.0269-4-53-000	5.5	75	0.36	-0.002	0	31.4	8700		M		1310	-0.1	-0.02
MABE523R	25-42.4256-	73.0979-4-52-000	6.9	100	1.80	0.381	U		3900	45	M	18.8	1560	0.9	3.81
MABE524R	25-42.4237-	73.1654-4-53-000	7.1	60	0.60	0.038	0	21.9	3800	25	M		420	-0.1	0.63
MABE525R	25-42.3717-	73.1466-4-52-000	6.7	115	0.84	-0.002	160		4700		M	16.2	1820	-0.1	-0.01
MABE526R	25-42.3749-	73.1099-4-52-000	6.9	65	0.34	0.057	240	9.7	7400	14	M	4.9	2020	-0.1	0.88
MABE527R	25-42.3317-	73.0883-4-52-000	6.6	50	0.48	-0.002	90	19.5	4400	23	M	48.2	800	-0.1	-0.03
MABE528R	25-42.3516-	73.1268-4-52-000	6.7	320	3.90	0.349	18		17200	14	M		8240	0.2	1.09
MABE529R	25-42.2876-	73.0610-4-52-000	7.3	110	1.30	0.937	U		3000	128	M	15.3	1760	-0.1	8.52
MABE530R	25-42.3061-	73.0393-4-52-000	7.4	80	1.00	0.054	6	32.2	5200	17	M		660	-0.1	0.68
MABE531R	25-42.2650-	73.0398-4-52-000	7.8	85	1.20	0.816	U		3800	37	M	17.2	1350	0.5	9.60
MABE532R	25-42.2597-	73.0867-4-52-000	7.5	80	1.20	0.055	U	8.9	3200	129	M		2560	0.8	0.69
MABE533R	25-42.3118-	73.1259-4-52-000	6.2	115	1.60	0.136	12		3600	71	M	25.0	830	-0.1	1.18
MABE534R	25-42.2976-	73.1941-4-52-000	7.2	115	1.30	0.380	U	17.1	3700	78	M		700	-0.1	3.30
MABE535R	25-42.2377-	73.1168-4-52-000	6.7	35	0.20	0.028	5	44.6	3500	22	M		710	-0.1	0.80

TABLE A-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -GROUND WATER--

ALBANY

SHEET

2

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	DEPTH FEET	BR PPB	CL PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MABE536R	25-42.2249- 73.0984-4-52-000	6.9	145	2.20	0.079	U	.	5100	22	M	17.8	1800	0.4	0.54
MABE537R	25-42.1953- 73.0343-4-52-000	7.2	190	2.50	1.081	U	.	4100	197	M	69.5	7860	-0.1	5.69
MABE538R	25-42.1663- 73.0660-4-52-000	7.4	35	0.18	0.017	16	.	3900	19	M	8.1	990	-0.1	0.49
MABE539R	25-42.1083- 73.0748-4-52-000	6.2	25	0.14	0.025	U	23.3	3600	.	M	.	830	-0.1	1.00
MABE540R	25-42.0934- 73.0750-4-52-000	6.5	70	0.64	0.161	U	.	4800	.	M	7.2	1360	-0.1	2.30
MABE541R	25-42.1203- 73.1311-4-52-000	6.8	120	1.40	0.093	100	.	4400	109	M	.	2630	-0.1	0.78
MABE542R	25-42.0819- 73.1336-4-52-000	7.0	285	2.10	1.347	129	.	39700	70	M	210.8	4110	0.7	4.73
MABE543R	25-42.1062- 73.1955-4-53-000	6.5	50	0.28	0.027	0	.	6000	.	M	.	1280	-0.1	0.54
MABE544R	25-42.1489- 73.1387-4-52-000	7.2	140	1.90	0.211	225	16.2	3600	115	M	.	2600	-0.1	1.51
MABE545R	25-42.7322- 73.2283-4-52-000	7.4	205	2.50	1.290	200	.	4600	33	M	32.0	1660	-0.1	6.29
MABE546R	25-42.6973- 73.2250-4-52-000	7.7	125	1.90	0.247	U	.	4200	31	M	.	1270	-0.1	1.98
MABE547R	25-42.6655- 73.2651-4-53-000	7.5	40	0.30	0.024	0	.	3500	.	M	8.0	520	-0.1	0.60
MABE548R	25-42.6462- 73.2659-4-53-000	7.2	30	0.28	0.022	0	29.5	3300	17	M	.	290	-0.1	0.73
MABE549R	25-42.6035- 73.2911-4-52-000	7.4	110	1.60	0.025	250	.	4800	.	M	19.1	700	-0.1	0.23
MABE550R	25-42.5421- 73.3187-4-52-000	7.5	130	1.70	0.201	15	31.5	4200	.	M	.	1000	-0.1	1.55
MABE551R	25-42.5706- 73.2495-4-53-000	7.5	115	0.84	-0.002	0	.	4200	.	M	6.3	7050	-0.1	-0.01
MABE552R	25-42.6125- 73.2324-4-52-000	7.8	200	1.80	0.148	U	.	12400	.	M	49.9	3690	-0.1	0.74
MABE553R	25-42.6358- 73.2280-4-52-000	7.8	120	1.40	0.019	50	.	2000	.	M	12.2	520	-0.1	0.16
MABE554R	25-42.5866- 73.1604-4-52-000	7.6	80	1.20	0.021	50	.	2200	8	M	.	340	-0.1	0.26
MABE555R	25-42.5077- 73.2601-4-52-000	7.1	317	4.80	21.830	U	.	31400	.	M	34.1	14380	-0.1	68.86
MABE556R	25-42.4646- 73.3060-4-52-000	6.7	172	2.70	0.227	U	.	40300	.	M	42.9	5820	-0.1	1.32
MABE557R	25-42.4301- 73.3609-4-52-000	7.5	127	2.20	6.439	212	.	4100	31	M	27.2	1300	-0.1	50.70
MABE558R	25-42.3793- 73.3719-4-52-000	7.6	268	4.60	0.510	U	.	4500	.	M	51.2	770	-0.1	1.90
MABE559R	25-42.3807- 73.3317-4-52-000	7.2	121	1.90	0.250	250	.	4000	.	M	23.4	1130	-0.1	2.07
MABE560R	25-42.3373- 73.3904-4-52-000	7.6	311	4.50	2.252	U	21.3	6200	.	M	.	1670	-0.1	7.24
MABE561R	25-42.2961- 73.3872-4-52-000	6.9	235	3.40	0.177	U	.	6300	20	M	.	40680	-0.1	0.75
MABE562R	25-42.2455- 73.4246-4-53-000	7.2	65	0.90	0.080	0	36.1	3200	32	M	.	1470	-0.1	1.23
MABE563R	25-42.2094- 73.4218-4-52-000	7.1	340	5.20	2.231	165	.	9200	.	M	.	2160	-0.1	6.56
MABE564R	25-42.1484- 73.4350-4-52-000	7.4	310	4.90	1.460	150	.	12000	.	M	.	5670	-0.1	4.71
MABE565R	25-42.1241- 73.4114-4-53-000	8.3	50	0.50	0.023	0	.	3600	.	M	7.4	710	-0.1	0.46
MABE566R	25-42.0756- 73.4175-4-53-000	7.6	120	1.80	0.098	0	16.5	3800	23	M	.	1000	-0.1	0.82
MABE567R	25-42.0696- 73.3773-4-52-000	7.7	230	2.70	0.361	200	.	5500	.	M	.	1550	-0.1	1.57
MABE568R	25-42.1298- 73.3659-4-52-000	7.7	190	2.40	0.796	298	19.6	3400	29	M	.	3320	-0.1	4.19
MABE569R	25-42.1598- 73.3662-4-52-000	7.4	250	4.70	0.271	10	.	7100	.	M	.	4450	-0.1	1.08
MABE570R	25-42.2093- 73.3567-4-52-000	7.8	335	3.00	2.562	240	.	7200	.	M	175.6	1410	-0.1	7.65
MABE571R	25-42.2329- 73.3835-4-52-000	7.7	240	2.30	0.464	70	.	7100	.	M	.	670	-0.1	1.93
MABE572R	25-42.2348- 73.3260-4-52-000	8.0	170	2.20	0.046	U	.	8600	19	M	24.9	1940	-0.1	0.27
MABE573R	25-42.2094- 73.3256-4-52-000	7.9	60	0.70	0.392	38	.	4000	20	M	59.5	900	-0.1	6.53
MABE574R	25-42.1765- 73.3016-4-52-000	7.5	240	2.30	0.271	U	.	3800	21	M	.	700	-0.1	1.13
MABE575R	25-42.1549- 73.2780-4-52-000	7.7	260	3.90	0.148	U	.	4700	9	M	58.1	1320	-0.1	0.57
MABE576R	25-42.1064- 73.3047-4-52-000	7.9	200	2.60	0.995	250	.	5100	149	M	47.1	2820	-0.1	4.78
MABE577R	25-42.0763- 73.2861-4-52-000	7.9	250	3.70	1.949	U	.	5300	.	M	54.8	1050	-0.1	7.80
MABE578R	25-42.0874- 73.2562-4-52-000	8.1	150	1.90	2.990	U	30.3	3500	348	M	.	2960	-0.1	19.93
MABE579R	25-42.1238- 73.2638-4-52-000	7.9	145	2.50	0.211	9	.	4000	19	M	53.0	1070	-0.1	1.46
MABE580R	25-42.1914- 73.2620-4-53-000	8.0	70	0.70	0.122	0	.	3400	16	M	19.9	1190	0.4	1.74
MABE581R	25-42.1638- 73.2009-4-52-000	7.6	105	1.20	-0.002	20	.	3800	.	M	.	1050	-0.1	-0.01
MABE582R	25-42.2248- 73.1883-4-53-000	7.8	60	0.60	0.083	0	.	3600	16	M	18.2	1000	-0.1	1.38
MABE583R	25-42.2536- 73.1992-4-52-000	7.8	130	1.70	0.374	U	.	4000	21	M	.	6900	-0.1	2.88
MABE584R	25-42.2612- 73.2455-4-52-000	7.6	300	4.40	0.323	U	.	6000	.	M	133.9	7380	-0.1	1.08
MAFR501R	25-42.4500- 72.5340-4-53-000	6.3	90	1.20	0.098	0	20.3	4000	.	M	37.6	5400	-0.1	1.09
MAFR502R	25-42.4928- 72.5238-4-52-000	6.3	60	0.18	-0.002	21	.	13300	.	M	.	10420	-0.1	-0.02
MAFR503R	25-42.5342- 72.5238-4-52-000	6.6	105	1.40	1.721	40	.	3900	52	M	38.0	7200	0.3	16.39
MAFR504R	25-42.5873- 72.4940-4-52-000	6.6	20	0.16	0.103	5	.	3600	38	M	.	.	-0.1	5.15

A-17

TABLE A-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -GROUND WATER--

ALBANY

SHEET

3

SRL I.D. *****	DOE I.D.		PH	COND. UM/CM	AKMXD MEQ/L	U PPB	DEPTH FEET	BR PPB	CL PPB	F PPB	MG PPB	MN PPB	NNA PPB	V PPB	U/COND X 1000
MAFR505R	25-42.6115-	72.3329-4-52-000	6.5	20	0.14	0.002	8	.	3100	10	M	26.9	4680	-0.1	0.10
MAFR506R	25-42.6736-	72.3438-4-52-000	6.4	70	0.32	0.019	15	.	11800	.	M	25.1	9300	-0.1	0.27
MAFR507R	25-42.7047-	72.3525-4-52-000	6.4	35	0.28	0.011	12	14.5	4200	.	M	26.8	5250	-0.1	0.31
MAFR508R	25-42.6684-	72.2791-4-52-000	6.5	20	0.08	0.028	U	29.3	3900	.	M	32.0	4960	-0.1	1.40
MAFR509R	25-42.4572-	72.6005-4-52-000	5.4	60	0.24	0.013	U	.	10700	.	M	.	8250	-0.1	0.08
MAFR510R	25-42.4561-	72.6453-4-52-000	6.0	65	0.76	0.012	10	23.2	11900	.	M	.	7630	-0.1	0.07
MAFR511R	25-42.4676-	72.6912-4-52-000	6.4	50	0.26	0.007	12	26.8	4900	.	M	31.1	5850	-0.1	0.14
MAFR512R	25-42.5002-	72.7072-4-53-000	6.4	15	1.50	0.110	0	29.4	3500	.	M	34.5	5640	-0.1	0.96
MAFR513R	25-42.5040-	72.7518-4-52-000	6.6	100	1.30	0.344	U	15.9	3700	88	M	.	1830	0.7	3.44
MAFR514R	25-42.5043-	72.8155-4-52-000	6.0	290	0.08	0.005	110	.	61700	.	M	.	24990	-0.1	0.02
MAFR515R	25-42.5420-	72.7757-4-52-000	6.5	40	0.46	0.011	U	37.3	4800	.	M	9.4	1320	-0.1	0.28
MAFR516R	25-42.5504-	72.7166-4-52-000	6.8	55	0.44	0.006	10	.	4200	.	M	8.1	1560	-0.1	0.11
MAFR517R	25-42.5779-	72.6944-4-52-000	6.8	160	1.90	1.064	190	.	6200	32	M	13.8	2170	-0.1	6.65
MAFR518R	25-42.4480-	72.4703-4-52-000	6.6	70	0.80	0.290	200	4.8	4300	186	M	4.9	2650	0.4	4.14
MAFR519R	25-42.4519-	72.4144-4-52-000	6.4	215	1.10	1.055	300	14.5	19900	.	M	20.1	3630	-0.1	4.91
MAFR520R	25-42.6277-	72.2632-4-52-000	6.7	20	0.20	0.040	35	.	3900	52	M	.	1240	-0.1	2.00
MAFR521R	25-42.5488-	72.2963-4-52-000	6.7	30	0.12	0.007	13	20.6	4900	11	M	.	1060	-0.1	0.23
MAFR522R	25-42.5057-	72.3330-4-52-000	6.1	120	0.64	0.039	108	.	7200	.	M	26.5	2030	-0.1	0.33
MAFR523R	25-42.5037-	72.5729-4-52-000	6.0	60	0.42	0.093	3	.	3500	.	M	12.9	870	0.8	1.55
MAFR524R	25-42.5392-	72.5715-4-52-000	6.5	30	0.16	0.014	3	29.9	3500	13	M	8.7	860	-0.1	0.47
MAFR525R	25-42.5687-	72.5785-4-52-000	6.4	75	0.40	0.064	U	.	9000	53	M	20.0	3050	0.2	0.85
MAFR526R	25-42.5332-	72.6369-4-52-000	6.4	150	1.20	-0.002	22	.	6100	.	M	6.4	1980	-0.1	0.00
MAFR527R	25-42.5090-	72.6587-4-52-000	6.8	75	0.60	0.037	125	.	4200	.	M	8.7	790	-0.1	0.49
MAFR528R	25-42.5781-	72.7601-4-52-000	6.7	40	0.32	0.019	U	.	5000	.	M	6.1	1120	-0.1	0.48
MAFR529R	25-42.4933-	72.8669-4-53-000	7.0	85	1.20	0.457	0	.	3200	47	M	9.3	1650	0.2	5.38
MAFR530R	25-42.5381-	72.8242-4-52-000	7.0	45	0.42	0.017	6	.	3500	.	M	.	530	-0.1	0.38
MAFR531R	25-42.5390-	72.8744-4-52-000	6.4	140	0.40	0.063	120	49.2	10800	0	M	.	3070	-0.1	0.45
MAFR532R	25-42.5809-	72.8925-4-52-000	6.7	50	0.28	0.015	U	.	5800	.	M	8.9	1470	-0.1	0.30
MAFR533R	25-42.5819-	72.8433-4-52-000	6.8	35	0.34	0.034	U	25.0	3200	4	M	.	770	-0.1	0.97
MAFR534R	25-42.4911-	72.4713-4-52-000	4.8	100	0.12	-0.002	20	.	20000	.	M	7.2	7720	-0.1	-0.01
MAFR535R	25-42.5061-	72.4111-4-52-000	5.7	25	0.04	0.026	10	.	5900	67	M	24.2	1640	-0.1	1.04
MAFR536R	25-42.4633-	72.3453-4-52-000	6.1	65	0.40	0.027	U	31.6	7000	21	M	.	1880	-0.1	0.42
MAFR537R	25-42.5105-	72.2643-4-52-000	6.1	365	0.18	-0.002	30	908.3	M	.	M	.	M	-0.1	0.00
MAFR538R	25-42.5413-	72.3400-4-52-000	6.7	85	0.76	1.408	200	40.0	8800	60	M	.	4040	0.6	16.56
MAFR539R	25-42.6003-	72.2825-4-52-000	6.4	105	1.10	0.059	10	.	4400	.	M	15.8	2960	-0.1	0.56
MAFR540R	25-42.5937-	72.3428-4-52-000	7.0	70	0.80	0.164	165	.	4400	.	M	.	3850	-0.1	2.34
MAFR541R	25-42.5749-	72.3812-4-52-000	6.7	110	0.72	4.154	140	1884.0	8100	76	M	.	4220	0.4	37.76
MAFR542R	25-42.5443-	72.4029-4-52-000	6.8	290	0.36	0.215	30	.	M	.	M	.	44300	-0.1	0.74
MAFR543R	25-42.5564-	72.4697-4-52-000	6.8	15	0.06	0.045	15	27.6	5000	52	M	14.2	1320	-0.1	3.00
MAFR544R	25-42.6175-	72.4731-4-52-000	6.2	35	0.16	0.027	12	.	4100	.	M	.	600	-0.1	0.77
MAFR545R	25-42.6519-	72.4198-4-52-000	6.4	175	0.46	0.028	35	.	31300	.	M	.	14760	-0.1	0.16
MAFR546R	25-42.6292-	72.4106-4-52-000	6.6	30	0.14	0.018	12	.	7000	.	M	.	1960	-0.1	0.60
MAFR547R	25-42.6168-	72.6632-4-52-000	6.3	320	1.50	0.357	225	.	6100	31	M	14.7	4480	-0.1	1.12
MAFR548R	25-42.5875-	72.6717-4-52-000	7.0	160	1.60	0.155	18	.	6600	.	M	.	2070	-0.1	0.97
MAFR549R	25-42.6204-	72.6924-4-52-000	7.8	75	0.90	0.089	3	.	4800	8	M	5.4	1030	-0.1	1.19
MAFR550R	25-42.6644-	72.6954-4-52-000	7.0	285	3.10	0.422	8	.	11600	.	M	.	3850	-0.1	1.48
MAFR551R	25-42.6175-	72.7549-4-52-000	7.5	85	1.00	0.119	105	23.2	4100	59	M	38.0	1130	2.8	1.40
MAFR552R	25-42.6278-	72.8201-4-52-000	7.4	95	1.30	0.057	8	23.8	2800	52	M	69.9	2690	-0.1	0.60
MAFR553R	25-42.6685-	72.8265-4-52-000	7.5	35	0.36	0.015	4	14.3	3100	.	M	13.0	1450	-0.1	0.43
MAFR554R	25-42.6570-	72.8915-4-53-000	7.2	20	0.16	-0.002	0	24.1	2600	11	M	6.1	440	-0.1	-0.09
MAFR555R	25-42.6219-	72.8940-4-52-000	7.0	50	0.36	0.025	6	.	3700	.	M	11.1	520	-0.1	0.50
MAFR556R	25-42.5974-	72.9330-4-52-000	7.2	50	0.32	-0.002	U	.	4000	22	M	8.5	1840	0.1	-0.03
MAFR557R	25-42.6447-	72.9255-4-53-000	6.1	25	0.14	0.003	0	35.9	3400	16	M	4.5	640	-0.1	0.12

TABLE A-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -GROUND WATER--

ALBANY

SHEET

4

SRL I.D. *****	DOE I.D.		PH	COND. UM/CM	AKMXD MEQ/L	U PPB	DEPTH FEET	BF PPE	CL PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MAFR558R	25-42.6757-	72.9289-4-52-000	6.5	20	0.12	0.028	2		3700	19	M	1.2	520	-0.1	1.40
MAFR559R	25-42.7300-	72.9349-4-52-000	6.6	50	0.46	0.064	200	26.5	3700		M		680	-0.1	1.28
MAFR560R	25-42.7223-	72.9823-4-52-000	6.7	220	2.40	0.006	12		16400		M	44.6	3220	-0.1	0.03
MAFR561R	25-42.6019-	72.5083-4-52-000	6.0	310	1.40	0.099	435	767.6	M		M		M	-0.1	0.32
MAFR562R	25-42.6239-	72.5288-4-52-000	6.2	90	0.64	0.093	U		12500		M		8750	-0.1	1.03
MAFR563R	25-42.6602-	72.4815-4-52-000	6.5	150	0.64	0.019	150	17.4	7100	28	M	39.1	6020	-0.1	0.13
MAFR564R	25-42.7002-	72.4191-4-52-000	6.9	80	0.76	0.104	U	25.0	4400	161	M	55.9	6340	-0.1	1.30
MAFR565R	25-42.7100-	72.4758-4-52-000	6.7	70	0.28	-0.002	30	23.3	7600		M	38.5	5640	-0.1	-0.02
MAFR567R	25-42.7100-	72.5302-4-52-000	7.2	25	0.14	0.037	15		4200	24	M		6200	-0.1	1.48
MAFR568R	25-42.6565-	72.5932-4-52-000	7.0	20	0.28	-0.002	U		4300	11	M		5360	-0.1	-0.09
MAFR569R	25-42.7099-	72.6053-4-52-000	6.4	150	0.34	0.029	10		10800		M		7050	-0.1	0.19
MAFR570R	25-42.6844-	72.6355-4-52-000	6.9	295	3.50	0.759	U	18.0	10900		M	134.4	9950	-0.1	2.57
MAFR571R	25-42.7092-	72.6447-4-52-000	7.3	80	1.20	0.093	U	16.4	4600		M	41.0	5930	-0.1	1.16
MAFR572R	25-42.7072-	72.6776-4-53-000	7.2	115	1.30	0.190	0		4000		M	28.0	4970	-0.1	1.65
MAFR573R	25-42.6783-	72.7540-4-52-000	7.8	110	1.30	0.577	150	26.0	4700	337	M	26.8	8350	-0.1	5.25
MAFR574R	25-42.6941-	72.7743-4-52-000	7.7	45	0.56	0.017	10	18.0	4000		M	27.8	4770	-0.1	0.38
MAFR575R	25-42.7106-	72.8158-4-52-000	5.6	40	0.32	-0.002	3	29.3	5300		M	30.7	5610	-0.1	-0.04
MAFR576R	25-42.7075-	72.8933-4-52-000	6.7	155	0.88	0.304	170		22400		M		9960	-0.1	1.96
MAHA501R	25-42.1865-	72.2979-4-52-000	8.3	45	0.20	0.004	70	19.3	5300	13	M	53.0	6100	-0.1	0.09
MAHA502R	25-42.1520-	72.2776-4-52-000	8.0	M	0.70	0.011	210		4700	81	M		8730	-0.1	
MAHA503R	25-42.1415-	72.2092-4-52-000	7.8	70	0.40	0.009	15	27.1	8900		M	59.7	6760	-0.1	0.13
MAHA504R	25-42.1450-	72.1660-4-52-000	8.0	55	0.30	0.006	120	36.9	8200	38	M	105.1	6930	-0.1	0.11
MAHA505R	25-42.1101-	72.1652-4-52-000	7.7	210	0.90	0.038	1		30600		M	47.3	10830	-0.1	0.18
MAHA506R	25-42.0627-	72.1663-4-52-000	6.2	210	0.20	0.070	30		50300		M		24530	-0.1	0.33
MAHA507R	25-42.0483-	72.2122-4-52-000	7.4	30	0.20	0.007	14		4500		M		7130	-0.1	0.23
MAHA508R	25-42.1065-	72.2218-4-52-000	7.2	120	0.28	-0.002	1		10300		M	57.2	9440	-0.1	-0.01
MAHA509R	25-42.0960-	72.2864-4-52-000	7.2	360	0.60	0.025	350		24100		M	169.2	4780	-0.1	0.07
MAHA510R	25-42.0593-	72.2719-4-52-000	7.8	40	0.40	0.005	200		4500	124	M		1980	-0.1	0.13
MAHA511R	25-42.0839-	72.3317-4-52-000	7.0	55	0.24	0.006	25		6600		M	6.6	1880	-0.1	0.11
MAHA512R	25-42.0589-	72.3489-4-52-000	7.8	45	0.50	0.059	100		4800	63	M	12.5	1470	-0.1	1.31
MAHA513R	25-42.0552-	72.3940-4-52-000	7.3	90	0.32	0.067	100	9.5	11900		M		3710	-0.1	0.74
MAHA514R	25-42.0513-	72.4532-4-52-000	6.7	330	0.20	0.009	1		62100		M	17.1	30190	-0.1	0.03
MAHA515R	25-42.0906-	72.4614-4-52-000	7.9	250	1.10	0.829	120	3400.8	26100		M	24.5	11970	1.3	3.32
MAHA516R	25-42.0996-	72.3973-4-52-000	7.1	100	0.20	3.352	1	55.3	6400		M	63.5	2690	-0.1	33.52
MAHA517R	25-42.1292-	72.4012-4-52-000	7.7	65	0.40	0.380	1		4000	54	M	4.8	2300	2.4	5.85
MAHA518R	25-42.2538-	72.9492-4-52-000	6.0	60	0.26	0.020	480	40.8	5100	179	M		1910	-0.1	0.33
MAHA519R	25-42.3037-	72.9695-4-52-000	6.7	65	0.76	0.036	42		5300		M	25.2	1070	-0.1	0.55
MAHA520R	25-42.2757-	72.9073-4-52-000	6.1	120	1.00	0.298	70		2900	55	M	10.3	1830	-0.1	2.48
MAHA521R	25-42.2979-	72.9059-4-52-000	6.6	30	0.18	0.042	U		3700	12	M	4.9	600	-0.1	1.40
MAHA522R	25-42.1750-	72.9427-4-52-000	6.3	30	0.24	-0.002	3		10400	41	M	12.7	850	-0.1	-0.06
MAHA523R	25-42.2247-	72.3009-4-52-000	5.8	70	0.40	0.096	U		11000		M	7.9	2410	-0.1	1.37
MAHA524R	25-42.1741-	72.4017-4-52-000	6.0	25	0.26	0.025	6	36.1	4300	33	M		1370	0.5	1.00
MAHA525R	25-42.1852-	72.4767-4-52-000	6.1	120	0.90	0.118	U		6500		M	9.6	2650	1.1	0.98
MAHA526R	25-42.1971-	72.4986-4-52-000	6.3	120	2.20	3.617	500		5200	102	M		9040	1.1	30.14
MAHA527R	25-42.0361-	72.7031-4-52-000	6.5	350	2.40	0.677	100		3700	137	M	59.3	4170	1.5	1.93
MAHA528R	25-42.0906-	72.7659-4-52-000	6.5	65	0.36	0.123	25	11.3	5100	46	M		1130	-0.1	1.89
MAHA529R	25-42.1775-	72.7092-4-52-000	5.9	150	0.26	0.112	40	23.1	7100		M	112.3	6960	-0.1	0.75
MAHA530R	25-42.2232-	72.6521-4-52-000	6.3	500	3.50	0.305	150	25.7	48800		M		17690	-0.1	0.61
MAHA531R	25-42.1356-	72.8364-4-52-000	6.8	30	0.22	0.264	400		5100	20	M		1380	-0.1	8.80
MAHA532R	25-42.1382-	72.8565-4-52-000	6.8	110	1.30	1.414	245		5300	211	M	53.9	9220	-0.1	12.85
MAHA533R	25-42.1656-	72.8807-4-52-000	6.1	1300	0.40	0.158	38		186600		M		40820	-0.1	0.12
MAHA534R	25-42.1742-	73.0174-4-52-000	7.0	130	1.60	0.195	85	13.6	22100		M	55.8	11550	-0.1	1.50
MAHA535R	25-42.2154-	72.9583-4-52-000	6.7	100	0.88	0.033	200		7700	51	M	97.6	6450	-0.1	0.33

TABLE A-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -GROUND WATER--

ALBANY

SHEET

5

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	DEPTH FEET	BR PPB	CL PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MAHA536R	25-42.1833-72.7636-4-52-000	6.3	75	0.88	0.078	3	16.6	4400	11	M	53.6	5880	0.4	1.04
MAHA537R	25-42.1512-72.7631-4-52-000	6.9	105	1.40	2.454	130	.	8000	.	M	.	M	-0.1	23.37
MAHA538R	25-42.2191-72.8250-4-52-000	6.2	105	0.28	0.235	180	.	16300	.	M	57.9	9590	-0.1	2.24
MAHA539R	25-42.1933-72.8166-4-52-000	6.3	40	0.22	12.500	290	.	8000	.	M	.	7100	-0.1	312.50
MAHA540R	25-42.0411-72.7437-4-52-000	6.7	110	0.72	1.625	235	.	6500	.	M	.	M	0.3	14.77
MAHA541R	25-42.0364-72.8199-4-52-000	6.7	120	1.30	1.955	300	.	10400	.	M	39.0	8090	1.4	16.29
MAHA542R	25-42.0738-72.8153-4-52-000	7.0	95	0.80	0.879	250	.	11200	.	M	37.1	10760	2.8	9.25
MAHA543R	25-42.0355-72.8780-4-52-000	6.9	65	0.84	0.066	25	.	3300	15	M	46.1	6150	0.4	1.02
MAHA544R	25-42.1032-72.9025-4-52-000	7.0	35	0.36	0.045	U	.	3700	43	M	.	M	-0.1	1.29
MAHA545R	25-42.1162-72.9333-4-52-000	6.3	250	0.96	0.043	22	64.9	26700	.	M	.	12920	-0.1	0.17
MAHA546R	25-42.0722-72.9259-4-52-000	7.9	70	0.84	1.121	175	15.9	4600	41	M	44.1	7160	1.4	16.01
MAHA547R	25-42.0552-72.9404-4-52-000	6.6	75	0.88	0.243	350	.	4600	.	M	.	7350	-0.1	3.24
MAHA548R	25-42.0558-72.9887-4-52-000	6.7	75	0.80	0.039	45	.	4300	29	M	.	6310	-0.1	0.52
MAHA549R	25-42.1351-73.0214-4-52-000	6.2	200	1.40	0.414	200	.	39500	.	M	.	M	-0.1	2.07
MAHA550R	25-42.0842-73.0561-4-52-000	6.4	35	0.20	0.122	U	.	6900	.	M	.	7830	-0.1	3.49
MAHM501R	25-42.2500-72.3069-4-52-000	6.9	50	0.36	0.016	33	27.0	8300	.	M	13.1	3810	0.4	0.32
MAHM502R	25-42.2660-72.2628-4-52-000	7.1	95	0.30	0.022	18	.	14200	15	M	20.6	4900	-0.1	0.23
MAHM503R	25-42.2934-72.2537-4-52-000	7.3	95	0.60	0.029	125	52.9	10700	.	M	.	4560	1.6	0.31
MAHM504R	25-42.2923-72.2836-4-53-000	7.5	45	0.36	-0.002	0	.	6200	21	M	16.4	3350	0.3	-0.03
MAHM505R	25-42.2587-72.3715-4-52-000	7.5	50	0.28	0.023	35	36.7	6100	50	M	23.8	3590	-0.1	0.46
MAHM506R	25-42.2240-72.3627-4-52-000	6.5	45	0.24	0.012	15	43.8	7700	.	M	22.4	3300	-0.1	0.27
MAHM507R	25-42.2589-72.4213-4-52-000	7.3	09	0.60	1.302	100	.	23100	.	M	40.7	3950	-0.1	11.94
MAHM508R	25-42.2945-72.3864-4-52-000	8.5	60	0.70	3.609	U	39.4	4500	314	M	23.1	4120	1.0	45.11
MAHM509R	25-42.3006-72.4355-4-52-000	8.1	240	1.10	0.463	25	16.4	4700	52	M	126.1	6960	-0.1	1.93
MAHM510R	25-42.3471-72.4283-4-52-000	8.5	85	0.50	0.622	210	.	4200	.	M	.	2500	-0.1	7.32
MAHM511R	25-42.3843-72.4004-4-52-000	7.4	110	0.70	0.975	U	.	7700	.	M	10.0	2100	-0.1	8.86
MAHM512R	25-42.3757-72.4352-4-52-000	8.1	90	0.60	2.522	412	.	4200	.	M	.	4260	-0.1	28.02
MAHM513R	25-42.3018-72.4729-4-52-000	6.3	160	0.44	0.024	100	.	18700	.	M	.	5610	-0.1	0.15
MAHM514R	25-42.2664-72.4820-4-52-000	6.5	130	0.12	0.011	30	.	30400	.	M	.	11800	-0.1	0.08
MAHM515R	25-42.2617-72.5388-4-52-000	6.5	70	0.24	0.032	20	21.8	6200	.	M	17.6	2630	-0.1	0.46
MAHM516R	25-42.2980-72.5314-4-52-000	6.5	130	0.80	0.521	U	.	5600	.	M	.	M	-0.1	4.01
MAHM517R	25-42.4260-72.7842-4-52-000	6.2	55	0.40	0.046	30	30.8	4200	23	M	.	1260	-0.1	0.84
MAHM518R	25-42.4662-72.8382-4-52-000	7.0	50	0.16	-0.002	14	.	5000	.	M	7.4	1080	-0.1	-0.03
MAHM519R	25-42.4742-72.8995-4-52-000	7.2	140	0.92	0.737	210	36.0	6000	.	M	.	1320	0.1	5.26
MAHM520R	25-42.5123-72.9101-4-52-000	7.1	160	0.40	0.066	43	.	13500	.	M	14.1	1830	-0.1	0.41
MAHM521R	25-42.5071-72.9415-4-52-000	7.6	50	0.44	0.036	60	54.2	5000	36	M	17.3	1150	-0.1	0.72
MAHM522R	25-42.4637-72.9407-4-53-000	6.8	40	0.28	0.012	0	.	4800	34	M	7.5	1190	-0.1	0.30
MAHM523R	25-42.4263-72.9483-4-52-000	6.4	60	0.12	0.021	63	17.7	11000	.	M	23.6	5030	-0.1	0.35
MAHM524R	25-42.3756-73.0071-4-52-000	6.6	20	0.08	0.045	U	30.6	4000	.	M	32.5	600	-0.1	2.25
MAHM525R	25-42.3435-73.0044-4-52-000	7.0	150	0.40	0.104	100	.	4400	.	M	24.2	3190	0.6	0.69
MAHM526R	25-42.2667-72.8624-4-52-000	7.9	100	0.70	5.059	U	.	4000	136	M	6.8	2330	0.5	50.59
MAHM527R	25-42.2983-72.8456-4-52-000	6.6	85	0.28	0.063	50	.	5600	.	M	14.9	1810	-0.1	0.74
MAHM528R	25-42.2765-72.7906-4-52-000	7.8	105	0.90	2.235	210	.	3600	40	M	5.9	920	-0.1	21.29
MAHM529R	25-42.3020-72.7670-4-52-000	8.2	90	0.60	3.103	12	.	4700	41	M	.	1600	0.5	34.48
MAHM530R	25-42.2602-72.7280-4-52-000	7.7	85	0.50	0.263	240	32.0	15900	.	M	14.5	5010	-0.1	3.09
MAHM531R	25-42.4217-72.7133-4-52-000	7.3	105	0.52	0.056	27	.	5100	30	M	.	1520	-0.1	0.53
MAHM532R	25-42.3957-72.7282-4-52-000	7.7	105	0.80	0.938	150	.	10600	.	M	.	4910	-0.1	8.93
MAHM533R	25-42.3854-72.8022-4-52-000	6.8	65	0.24	0.466	20	53.3	8500	.	M	14.2	2610	-0.1	7.17
MAHM534R	25-42.3546-72.8281-4-52-000	7.2	75	0.48	1.102	270	.	3800	63	M	12.2	880	-0.1	14.69
MAHM535R	25-42.3790-72.8374-4-52-000	6.7	95	0.40	0.448	100	29.6	11600	.	M	.	2970	-0.1	4.72
MAHM536R	25-42.4200-72.8511-4-52-000	7.5	140	0.80	0.113	230	18.4	10900	86	M	102.1	2190	0.2	0.81
MAHM537R	25-42.4214-72.8885-4-52-000	6.9	40	0.24	0.034	150	.	4000	.	M	6.9	730	-0.1	0.85
MAHM538R	25-42.3815-72.9051-4-53-000	6.5	50	0.24	0.068	0	.	5100	.	M	.	1710	-0.1	1.36

A-20

TABLE A-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -GROUND WATER--

ALBANY SHEET

6

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	DEPTH FEET	BR PPB	CL PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MAHM539R	25-42.3779-72.9352-4-52-000	7.6	155	1.30	1.806	U	.	4200	.	M	.	7020	-0.1	11.65
MAHM540R	25-42.3478-72.8939-4-53-000	7.2	60	0.40	0.096	0	39.0	4500	26	M	.	1440	-0.1	1.60
MAHM541R	25-42.2954-72.7341-4-52-000	8.2	200	0.80	1.716	100	.	18100	.	M	.	4810	-0.1	8.58
MAHM542R	25-42.2365-72.7552-4-52-000	6.7	210	0.40	0.091	100	.	23500	22	M	12.4	8340	-0.1	0.43
MAHM543R	25-42.2205-72.7324-4-52-000	6.8	290	0.80	0.351	90	7.8	27900	.	M	3.6	10100	-0.1	1.21
MAHM544R	25-42.3419-72.7173-4-52-000	6.6	30	0.20	0.107	U	.	4100	.	M	4.0	850	-0.1	3.57
MAHM545R	25-42.3461-72.7620-4-53-000	7.8	20	0.20	0.059	0	28.5	3900	25	M	.	650	-0.1	2.95
MAHM546R	25-42.3807-72.6676-4-52-000	6.3	50	0.18	0.097	240	.	5400	15	M	6.0	1230	-0.1	1.94
MAHM547R	25-42.3025-72.6012-4-53-000	7.3	70	0.28	0.017	0	32.1	4700	10	M	.	1490	0.1	0.24
MAW0523R	25-42.4542-72.0200-4-52-000	6.8	128	1.20	0.100	450	.	6200	401	M	.	13580	-0.1	0.78
MAW0526R	25-42.5241-72.0296-4-52-000	6.2	33	0.22	0.023	15	45.2	4900	15	M	52.3	5700	-0.1	0.70
MAW0527R	25-42.4916-72.0139-4-52-000	6.8	108	1.30	-0.002	U	.	16600	.	M	.	M	-0.1	-0.01
MAW0528R	25-42.4878-72.0773-4-52-000	7.1	78	1.20	0.038	U	.	4600	116	M	.	14560	-0.1	0.49
MAW0529R	25-42.5329-72.0786-4-52-000	6.2	161	0.80	0.136	130	.	25900	.	M	145.5	14620	-0.1	0.84
MAW0530R	25-42.5710-72.0652-4-52-000	5.7	126	0.80	0.020	12	.	M	.	M	60.6	20190	-0.1	0.16
MAW0531R	25-42.6131-72.0106-4-52-000	5.6	297	0.30	0.010	110	52.0	M	.	M	.	M	0.8	0.03
MAW0536R	25-42.6521-72.0228-4-52-000	6.3	99	1.20	0.106	200	30.4	5300	249	M	139.8	13480	-0.1	1.07
MAW0537R	25-42.6513-72.0653-4-52-000	6.7	35	0.16	-0.002	110	12.6	4900	.	M	62.5	5920	-0.1	-0.05
MAW0538R	25-42.6153-72.0637-4-52-000	6.9	81	1.20	0.009	165	.	4600	208	M	.	17410	-0.1	0.11
MAW0541R	25-42.0744-72.0040-4-52-000	5.8	111	0.50	0.020	U	13.3	23100	.	M	31.7	13140	-0.1	0.18
MAW0542R	25-42.1092-72.0937-4-52-000	6.0	161	0.50	0.032	62	.	36400	.	M	.	16310	-0.1	0.20
MAW0543R	25-42.0728-72.0664-4-52-000	6.2	135	0.50	0.016	150	.	16300	.	M	91.7	9150	-0.1	0.12
MAW0544R	25-42.1547-72.0758-4-52-000	6.3	43	0.14	0.087	70	26.3	5000	8	M	.	M	-0.1	2.02
MAW0545R	25-42.1621-72.0186-4-52-000	6.8	153	0.90	0.128	U	14.2	4600	159	M	53.7	9040	0.2	0.84
MAW0548R	25-42.1187-72.0296-4-52-000	6.4	130	0.70	0.144	142	.	9600	.	M	.	7080	-0.1	1.11
MAW0561R	25-42.1691-72.1514-4-52-000	6.3	94	2.80	0.012	146	21.0	4800	97	M	117.0	6140	-0.1	0.13
MAW0562R	25-42.1711-72.2003-4-52-000	6.0	99	1.20	0.047	150	22.8	7400	104	M	.	7570	-0.1	0.47
MAW0563R	25-42.2002-72.2432-4-52-000	6.2	120	1.10	0.010	U	16.1	4000	8	M	52.1	4560	-0.1	0.08
MAW0564R	25-42.2035-72.2055-4-52-000	6.3	96	0.70	0.014	12	.	5500	.	M	.	4540	-0.1	0.15
MAW0565R	25-42.2392-72.2092-4-52-000	6.2	76	0.50	0.014	U	.	7100	.	M	.	4760	-0.1	0.18
MAW0566R	25-42.2068-72.1420-4-52-000	6.6	177	0.90	0.037	U	.	4400	181	M	.	5660	-0.1	0.21
MAW0567R	25-42.2534-72.1459-4-52-000	6.5	123	1.00	0.023	140	17.5	8700	68	M	99.3	5300	-0.1	0.19
MAW0568R	25-42.2802-72.1966-4-52-000	5.8	180	0.60	-0.002	12	42.2	16000	.	M	.	5710	-0.1	0.00
MAW0569R	25-42.2979-72.1476-4-52-000	6.0	181	0.40	-0.002	14	.	35500	.	M	.	19120	-0.1	0.00
MAW0570R	25-42.2926-72.0904-4-52-000	5.6	171	1.00	0.012	106	.	9600	.	M	.	5130	-0.1	0.07
MAW0571R	25-42.2494-72.0779-4-52-000	6.1	149	0.80	0.004	200	.	9500	.	M	.	5300	-0.1	0.03
MAW0572R	25-42.2106-72.0790-4-52-000	5.5	79	0.40	0.043	U	.	12500	.	M	28.9	5110	-0.1	0.54
MAW0578R	25-42.4577-72.0885-4-52-000	6.2	72	1.30	0.022	115	19.2	4700	81	M	35.3	2980	-0.1	0.31
MAW0579R	25-42.4307-72.0881-4-52-000	6.2	72	0.70	-0.002	165	.	M	.	M	.	M	-0.1	-0.02
MAW0580R	25-42.4353-72.1503-4-52-000	5.9	77	0.50	0.010	7	.	9000	.	M	5.1	3730	-0.1	0.13
MAW0581R	25-42.3729-72.2083-4-52-000	5.6	109	0.30	0.055	300	23.2	21100	.	M	10.0	8270	-0.1	0.50
MAW0582R	25-42.3234-72.2483-4-52-000	5.8	101	0.60	M	12	M	M	M	M	M	M	M	M
MAW0583R	25-42.3398-72.2043-4-52-000	5.6	342	0.50	0.040	U	.	44300	.	M	10.9	13580	-0.1	0.12
MAW0584R	25-42.3360-72.1548-4-52-000	6.1	239	1.50	1.955	U	.	7500	.	M	11.4	3320	-0.1	8.18
MAW0585R	25-42.3820-72.1533-4-52-000	6.5	212	1.00	0.169	200	.	15700	83	M	.	4910	-0.1	0.80
MAW0586R	25-42.3793-72.0767-4-52-000	6.8	121	0.60	0.004	180	35.0	7000	258	M	26.2	5410	-0.1	0.03
MAW0587R	25-42.3720-72.0465-4-52-000	6.7	167	0.70	0.101	120	5.5	14100	.	M	31.1	2730	-0.1	0.60
MAW0588R	25-42.3294-72.0793-4-52-000	7.0	141	0.90	0.058	190	9.9	5400	105	M	14.0	4760	-0.1	0.41
MAW0589R	25-42.3341-72.0286-4-52-000	6.2	121	0.60	0.010	U	33.1	10100	.	M	99.6	7170	-0.1	0.08
MAW0590R	25-42.4551-72.2082-4-52-000	6.2	108	0.60	-0.002	300	20.5	4600	48	M	74.8	6250	0.2	-0.01
MAW0591R	25-42.4839-72.2413-4-52-000	6.0	58	0.40	0.010	96	.	6200	.	M	55.5	5900	-0.1	0.17
MAW0592R	25-42.4884-72.1981-4-52-000	5.8	92	0.60	-0.002	100	.	14900	.	M	50.5	9230	-0.1	-0.01
MAW0593R	25-42.4897-72.1557-4-52-000	6.3	167	0.60	0.132	250	48.6	7600	185	M	54.6	8290	-0.1	0.79

A-21

TABLE A-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -GROUND WATER--

ALBANY

SHEET

7

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	DEPTH FEET	BR PPB	CL PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MAW0594R	25-42.5480-72.1475-4-52-000	6.2	49	0.40	-0.002	18	16.9	4900	.	M	51.1	5200	-0.1	-0.03
MAW0595R	25-42.5750-72.1426-4-52-000	6.8	115	0.90	0.661	U	.	5700	824	M	.	9350	-0.1	5.75
MAW0596R	25-42.5697-72.2057-4-52-000	6.8	70	0.70	0.025	85	16.6	4200	86	M	94.7	6710	-0.1	0.36
MAW0597R	25-42.5307-72.1939-4-52-000	5.2	192	0.50	0.192	U	33.8	M	.	M	.	24850	-0.1	1.00
MAW0598R	25-42.5782-72.2435-4-52-000	5.7	29	0.16	-0.002	U	.	5600	.	M	52.3	5260	-0.1	-0.06
MAW0599R	25-42.5713-72.2577-4-52-000	5.7	108	0.90	0.305	U	20.5	10800	.	M	62.5	6370	-0.1	2.82
MAW0600R	25-42.6339-72.2142-4-52-000	5.4	232	0.60	0.016	166	.	49300	.	M	.	15260	-0.1	0.07
MAW0601R	25-42.6832-72.2471-4-52-000	5.5	152	0.50	0.040	1	.	19700	.	M	.	10100	-0.1	0.26
MAW0602R	25-42.7102-72.2588-4-52-000	5.8	117	0.18	-0.002	25	24.2	6300	.	M	52.6	7100	-0.1	-0.01
MAW0603R	25-42.6987-72.2079-4-52-000	5.6	87	0.24	-0.002	20	18.6	8300	.	M	58.3	6100	-0.1	-0.01
MAW0604R	25-42.6690-72.2077-4-52-000	5.9	63	0.32	0.354	U	.	4100	22	M	.	M	-0.1	5.62
MAW0609R	25-42.6813-72.0334-4-52-000	6.0	130	0.32	0.055	U	.	8400	.	M	118.0	8240	-0.1	0.42
MAW0610R	25-42.6808-72.0858-4-52-000	6.1	173	0.60	0.005	U	36.4	18700	.	M	94.9	8890	-0.1	0.03
MAW0611R	25-42.6347-72.1550-4-52-000	6.5	83	0.50	1.309	165	.	4800	343	M	.	6840	-0.1	15.77
MAW0612R	25-42.6875-72.1646-4-52-000	6.4	255	0.90	6.036	U	.	16000	.	M	.	8920	-0.1	23.67
MAW0635R	25-42.2007-72.0143-4-52-000	7.0	111	0.90	0.167	U	8.5	2500	22	M	.	3530	-0.1	1.50
MAW0636R	25-42.2387-72.0303-4-52-000	6.7	110	0.80	0.056	250	.	5600	268	M	120.2	11860	-0.1	0.51
MAW0637R	25-42.2844-72.0090-4-52-000	6.4	35	0.18	0.010	8	.	5300	.	M	36.4	4410	-0.1	0.26
NHCH514R	33-42.9985-72.1490-4-52-000	6.6	40	0.01	0.008	16	.	6600	33	M	111.4	11620	-0.1	0.20
NHCH515R	33-42.9300-72.0997-4-53-000	7.1	10	0.02	0.068	0	.	5400	.	M	87.0	10360	3.2	6.80
NHCH516R	33-42.9402-72.0920-4-52-000	6.4	160	0.01	0.062	200	37.3	3900	392	M	127.3	20360	-0.1	0.39
NHCH517R	33-42.9091-72.0196-4-52-000	4.9	155	0.04	-0.002	U	35.6	12700	266	M	152.6	14470	-0.1	0.00
NHCH518R	33-42.9126-72.0866-4-52-000	6.2	150	0.14	0.016	190	.	13300	293	M	259.7	13080	-0.1	0.11
NHCH519R	33-42.9373-72.1445-4-52-000	5.6	170	0.02	-0.002	25	.	40700	.	M	88.5	23190	-0.1	0.00
NHCH520R	33-42.9367-72.1812-4-53-000	5.4	20	0.02	0.018	0	24.3	4800	15	M	99.0	9180	1.2	0.90
NHCH521R	33-42.9118-72.1924-4-53-000	5.7	40	0.02	-0.002	0	47.9	4900	15	M	89.6	10240	-0.1	-0.04
NHCH522R	33-42.8737-72.1813-4-52-000	5.3	130	0.08	0.027	28	21.8	21700	.	M	186.7	18980	-0.1	0.21
NHCH523R	33-42.8167-72.1742-4-52-000	5.1	48	0.02	0.278	125	27.7	3300	18	M	83.9	10580	-0.1	6.95
NHCH524R	33-42.8595-72.2485-4-53-000	5.3	28	0.02	0.002	0	13.5	4100	.	M	86.8	9820	-0.1	0.10
NHCH525R	33-42.8906-72.2458-4-53-000	6.0	600	0.02	0.008	0	.	108700	.	M	73.2	54590	-0.1	0.01
NHCH526R	33-42.8939-72.3001-4-52-000	6.3	120	0.06	0.041	310	.	13200	.	M	104.2	5440	-0.1	0.34
NHCH527R	33-42.9517-72.3334-4-52-000	7.7	160	0.04	0.076	10	9.3	35300	.	M	61.2	15330	-0.1	0.48
NHCH528R	33-42.9873-72.3469-4-52-000	7.9	40	0.04	0.002	12	19.0	5700	.	M	64.7	4170	-0.1	0.05
NHCH533R	33-42.9963-72.2253-4-52-000	5.9	240	0.04	-0.002	20	83.6	28400	.	M	110.0	8380	-0.1	0.00
NHCH535R	33-42.9142-72.1127-4-52-000	6.3	370	0.14	0.026	10	.	86100	.	M	106.0	28800	-0.1	0.07
NHCH536R	33-42.1900-72.1328-4-52-000	6.3	120	0.10	0.254	15	79.8	28000	.	M	97.1	7550	0.2	2.12
NHCH537R	33-42.7660-72.1704-4-52-000	5.7	63	0.02	0.005	12	20.9	18500	.	M	109.2	6210	-0.1	0.08
NHCH538R	33-42.7433-72.1764-4-52-000	6.0	73	0.12	3.612	165	46.1	7700	120	M	338.5	5870	-0.1	51.60
NHCH539R	33-42.7749-72.0517-4-52-000	6.2	83	0.34	-0.002	U	20.4	5800	115	M	205.4	6480	-0.1	-0.02
NHCH540R	33-42.7773-72.0982-4-52-000	6.3	40	0.06	1.204	100	51.1	5600	108	M	105.8	5570	-0.1	30.10
NHCH541R	33-42.7566-72.2542-4-52-000	6.0	40	0.06	0.017	355	27.9	4400	213	M	143.8	5100	-0.1	0.43
NHCH542R	33-42.7393-72.2680-4-52-000	5.5	300	0.02	0.017	11	.	94500	.	M	123.5	40210	-0.1	0.06
NHCH543R	33-42.8080-72.2657-4-52-000	5.9	80	0.10	0.025	18	13.3	5100	.	M	115.7	4850	0.3	0.31
NHCH544R	33-42.8370-72.2943-4-52-000	6.2	90	0.30	0.072	205	32.5	4000	134	M	134.5	6670	0.4	0.80
NHCH545R	33-42.8453-72.3332-4-52-000	6.2	20	0.02	0.010	12	38.4	4600	.	M	114.6	5040	-0.1	0.50
NHCH546R	33-42.8329-72.3606-4-52-000	6.1	340	0.10	0.473	222	.	65500	.	M	116.2	15360	0.8	1.39
NHCH547R	33-42.7610-72.3404-4-53-000	6.9	20	0.02	0.001	0	15.7	4800	.	M	109.1	4820	-0.1	0.05
NHCH548R	33-42.7566-72.3083-4-52-000	6.5	260	0.25	0.020	14	35.0	12300	.	M	162.3	10230	1.4	0.08
NHCH549R	33-42.8514-72.0204-4-52-000	6.2	380	0.38	0.054	250	.	89200	309	M	136.7	37410	-0.1	0.14
NHCH550R	33-42.8515-72.0718-4-53-000	5.3	20	0.02	0.019	0	.	5500	46	M	127.5	6370	-0.1	0.95
NHCH551R	33-42.8162-72.0594-4-52-000	6.1	70	0.16	0.054	20	.	4200	307	M	102.5	8410	-0.1	0.77
NHCH553R	33-42.7463-72.0159-4-52-000	5.9	100	0.02	-0.002	10	.	3300	.	M	107.3	7540	-0.1	-0.01
NHCH554R	33-42.7388-72.0007-4-52-000	6.8	60	0.12	0.314	180	40.8	4300	174	M	142.4	6990	-0.1	5.23

TABLE A-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -GROUND WATER-- ALBANY SHEET

8

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	DEPTH FEET	BR PPB	CL PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NHCH556R	33-42.7454-72.0931-4-52-000	6.2	210	0.38	0.098	10	13.8	24300	.	M	110.4	21730	-0.1	0.47
NHCH557R	33-42.7448-72.3953-4-52-000	7.4	70	0.04	0.205	10	18.7	12700	24	M	99.6	11620	0.4	2.93
NHCH558R	33-42.7934-72.4034-4-52-000	6.6	180	0.30	0.201	300	.	15800	744	M	116.5	12300	-0.1	1.12
NHCH559R	33-42.8174-72.4108-4-53-000	7.9	20	0.02	0.052	0	28.8	4900	69	M	102.4	6880	-0.1	2.60
NHCH560R	33-42.7807-72.5043-4-52-000	5.9	1300	0.30	0.027	12	.	89500	.	M	65.1	39070	-0.1	0.02
NHCH561R	33-42.8454-72.5486-4-52-000	6.7	50	0.04	0.021	200	22.2	5600	34	M	112.9	6240	-0.1	0.42
NHCH562R	33-42.8835-72.5427-4-52-000	6.4	110	0.14	0.045	150	.	13000	67	M	110.8	8580	-0.1	0.41
NHCH563R	33-42.8813-72.4988-4-52-000	6.8	50	0.08	0.018	18	31.2	6500	22	M	101.4	7600	0.3	0.36
NHCH564R	33-42.8485-72.4847-4-53-000	6.3	25	0.02	0.467	0	25.2	4400	35	M	92.5	6430	-0.1	18.68
NHCH565R	33-42.9016-72.4613-4-52-000	6.1	140	0.04	0.021	U	.	34600	.	M	43.3	13790	-0.1	0.15
NHCH566R	33-42.8926-72.4489-4-52-000	6.5	160	0.06	0.167	160	.	36500	.	M	103.0	18200	-0.1	1.04
NHCH567R	33-42.9103-72.4300-4-53-000	6.7	20	0.02	0.022	0	36.7	5000	34	M	101.9	6960	0.3	1.10
NHCH568R	33-42.9168-72.3849-4-52-000	6.4	50	0.06	0.056	150	15.2	3800	34	M	97.3	7210	-0.1	1.12
NHCH569R	33-42.9272-72.3482-4-52-000	6.9	70	0.30	3.069	180	37.5	8200	148	M	.	5290	0.4	43.84
NHCH570R	33-42.9600-72.4331-4-52-000	6.2	110	0.08	0.022	20	65.7	16400	.	M	36.6	9830	-0.1	0.20
NHCH571R	33-42.9557-72.4592-4-52-000	6.9	100	0.50	0.470	120	.	4200	299	M	21.7	5220	-0.1	4.70
NHCH572R	33-42.9878-72.4473-4-52-000	7.1	220	0.20	0.181	320	.	3800	707	M	67.6	16960	0.3	0.82
NHCH573R	33-42.9847-72.0031-4-52-000	7.1	85	0.40	0.027	297	1882.0	8700	204	M	100.6	12460	-0.1	0.32
NYAL510R	36-42.4541-73.9563-4-52-000	7.3	231	1.60	0.038	120	.	24300	42	M	76.5	18960	-0.1	0.16
NYAL511R	36-42.4615-73.9087-4-52-000	7.2	97	0.90	-0.002	10	.	5900	45	M	69.7	7030	-0.1	-0.01
NYAL512R	36-42.4919-73.9266-4-52-000	7.4	262	1.40	0.102	142	.	5100	86	M	153.9	11100	0.3	0.39
NYAL513R	36-42.4983-73.9828-4-52-000	7.0	230	2.00	0.009	140	15.5	14600	.	M	104.9	10710	-0.1	0.04
NYAL530R	36-42.6745-73.9216-4-52-000	7.1	234	1.70	0.149	U	.	12200	.	M	22.5	5370	-0.1	0.64
NYAL531R	36-42.6405-73.9025-4-52-000	6.9	2900	5.30	5.995	18	.	268800	.	M	745.5	9010	1.6	2.07
NYAL532R	36-42.6339-73.8233-4-52-000	9.2	530	3.90	0.033	U	.	48000	.	M	.	72300	-0.1	0.06
NYAL533R	36-42.6424-73.9699-4-52-000	7.6	344	3.10	0.152	120	.	5300	78	M	47.0	2830	-0.1	0.44
NYAL534R	36-42.6932-73.9814-4-52-000	6.7	134	0.50	-0.002	10	.	15100	.	M	.	9080	-0.1	0.00
NYAL535R	36-42.7224-73.9937-4-52-000	7.0	291	1.30	0.063	6	.	34200	.	M	29.6	19940	-0.1	0.22
NYAL536R	36-42.7200-73.9051-4-52-000	7.0	132	0.80	-0.002	20	12.9	14600	.	M	.	4310	-0.1	-0.01
NYAL537R	36-42.7744-73.7836-4-52-000	9.1	600	5.70	0.069	U	24.7	10100	1511	M	.	77880	-0.1	0.12
NYAL538R	36-42.5853-73.9848-4-52-000	7.5	470	2.80	0.884	90	.	46900	.	M	.	32590	-0.1	1.88
NYAL539R	36-42.5489-73.9747-4-52-000	3.5	270	2.40	0.034	85	16.9	9900	142	M	31.1	27620	-0.1	0.13
NYAL540R	36-42.5374-73.9088-4-52-000	8.6	402	3.70	0.021	80	.	M	.	M	.	60350	-0.1	0.05
NYAL541R	36-42.5802-73.8880-4-52-000	7.7	314	2.40	0.036	80	42.5	10300	74	M	147.3	15440	-0.1	0.11
NYAL542R	36-42.5368-73.8361-4-52-000	7.1	331	2.70	0.067	10	.	5900	.	M	.	2190	-0.1	0.20
NYAL543R	36-42.4991-73.8168-4-52-000	8.0	420	4.00	0.032	U	.	12100	314	M	.	46030	-0.1	0.08
NYAL544R	36-42.5055-73.7774-4-52-000	8.8	520	3.20	-0.002	U	.	12000	.	M	.	52240	-0.1	0.00
NYAL545R	36-42.5605-73.7819-4-52-000	9.1	297	2.00	0.003	U	154.4	20900	550	M	.	41090	-0.1	0.01
NYAL546R	36-42.5851-73.7969-4-52-000	8.6	381	2.30	-0.002	340	2961.0	27500	49	M	.	M	-0.1	0.00
NYAL547R	36-42.6043-73.8504-4-52-000	9.1	230	2.00	0.023	140	.	M	.	M	.	M	-0.1	0.10
NYCO501R	36-42.3358-73.7494-4-52-000	7.3	420	4.30	0.419	8	103.1	26800	57	M	.	8430	-0.1	1.00
NYCO502R	36-42.3826-73.7494-4-52-000	9.1	430	5.90	0.076	U	.	M	.	M	3.8	M	0.6	0.18
NYCO503R	36-42.4181-73.7301-4-52-000	8.6	410	5.20	0.137	175	783.3	15200	217	M	.	87200	-0.1	0.33
NYCO504R	36-42.4203-73.7035-4-52-000	7.5	400	3.30	0.233	90	.	25700	.	M	36.9	8790	-0.1	0.58
NYCO505R	36-42.4280-73.6467-4-52-000	6.5	380	1.60	0.078	125	306.6	43700	.	M	.	24460	-0.1	0.21
NYCO506R	36-42.3948-73.6248-4-52-000	7.5	310	3.90	0.443	U	22.0	9500	.	M	209.0	8250	-0.1	1.43
NYCO507R	36-42.3719-73.6641-4-52-000	7.4	450	4.20	0.129	U	.	92200	.	M	29.9	72350	-0.1	0.29
NYCO508R	36-42.3453-73.6786-4-52-000	7.1	115	1.40	0.022	80	29.9	5800	27	M	.	2890	-0.1	0.19
NYCO509R	36-42.3032-73.6776-4-53-000	6.9	200	1.40	0.039	0	.	18400	60	M	58.4	8350	0.3	0.20
NYCO510R	36-42.2555-73.7008-4-52-000	7.4	160	3.00	0.118	80	.	5300	38	M	35.1	3020	-0.1	0.74
NYCO511R	36-42.2878-73.6291-4-52-000	8.6	430	4.70	0.107	150	.	55700	571	M	134.5	62200	-0.1	0.25
NYCO512R	36-42.3254-73.6123-4-52-000	7.6	380	2.90	0.247	U	92.7	33000	.	M	106.0	3130	-0.1	0.65
NYCO513R	36-42.2471-73.6467-4-52-000	8.0	260	3.50	0.001	30	39.6	10600	347	M	.	40010	-0.1	0.00

TABLE A-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -GROUND WATER--

ALBANY

SHEET

9

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	DEPTH FEET	BR PPB	CL PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NYC0514R	36-42.3751- 73.4105-4-52-000	7.7	158	1.80	0.117	20	.	9100	.	M	41.2	4250	-0.1	0.74
NYC0515R	36-42.4278- 73.3935-4-52-000	7.5	249	2.90	8.289	160	25.4	6400	12	M	.	4560	0.2	33.29
NYC0516R	36-42.476- 73.3888-4-52-000	6.9	178	2.40	8.731	U	.	4100	48	M	43.7	5950	-0.1	49.05
NYC0517R	36-42.4683- 73.4614-4-52-000	7.3	250	2.80	7.600	U	.	7100	97	M	260.0	14170	0.4	30.40
NYC0518R	36-42.4755- 73.5052-4-52-000	7.4	185	1.80	10.360	100	22.9	3900	120	M	52.6	12840	-0.1	56.00
NYC0519R	36-42.4313- 73.5671-4-52-000	7.4	229	2.20	2.666	U	.	4500	62	M	117.1	5760	-0.1	11.64
NYC0520R	36-42.4187- 73.5169-4-52-000	7.1	140	1.90	0.320	U	24.5	7400	41	M	135.2	5440	-0.1	2.29
NYC0521R	36-42.4372- 73.4638-4-52-000	6.8	51	0.40	0.029	28	14.2	4300	40	M	18.8	4120	0.2	0.57
NYC0522R	36-42.3786- 73.4522-4-52-000	7.4	128	1.60	1.383	300	30.9	3900	34	M	15.7	13390	-0.1	10.80
NYC0523R	36-42.3796- 73.5179-4-52-000	7.2	352	4.50	0.183	132	.	6600	57	M	135.6	13010	-0.1	0.52
NYC0524R	36-42.1921- 73.6378-4-52-000	6.2	90	0.36	0.021	U	36.7	4400	16	M	19.3	5260	-0.1	0.23
NYC0525R	36-42.1934- 73.6708-4-52-000	7.2	280	3.70	0.272	5	.	4700	44	M	125.9	7220	-0.1	0.97
NYC0526R	36-42.1970- 73.7212-4-52-000	7.8	270	2.70	0.042	130	14.5	3800	70	M	87.9	9270	0.2	0.16
NYC0527R	36-42.1528- 73.7477-4-52-000	7.9	220	2.10	0.114	59	46.9	6400	54	M	85.2	5640	-0.1	0.52
NYC0528R	36-42.1230- 73.7511-4-52-000	9.1	220	3.00	0.049	200	.	5900	220	M	203.2	28320	-0.1	0.22
NYC0529R	36-42.1442- 73.8040-4-52-000	7.4	450	4.60	0.341	100	.	19000	35	M	69.1	15170	-0.1	0.76
NYC0530R	36-42.1035- 73.8468-4-52-000	7.3	250	2.90	0.258	U	16.3	7800	58	M	.	7220	-0.1	1.03
NYC0531R	36-42.0657- 73.8378-4-52-000	7.2	320	3.90	0.222	U	30.2	6800	13	M	.	7290	-0.1	0.69
NYC0532R	36-42.0676- 73.8032-4-52-000	7.0	230	1.90	0.124	138	.	10000	55	M	49.8	6510	-0.1	0.54
NYC0533R	36-42.0939- 73.7858-4-52-000	8.7	200	2.90	0.052	U	.	3800	311	M	20.9	26800	-0.1	0.26
NYC0534R	36-42.3400- 73.4741-4-52-000	6.8	112	1.20	0.405	U	28.6	4000	91	M	40.3	7160	-0.1	3.62
NYC0535R	36-42.3350- 73.5235-4-52-000	7.2	207	2.70	1.094	200	.	3100	46	M	64.9	11870	-0.1	5.29
NYC0536R	36-42.3321- 73.5779-4-52-000	7.1	272	3.70	2.923	170	.	4300	81	M	454.6	9620	-0.1	10.75
NYC0537R	36-42.3971- 73.5777-4-53-000	6.8	88	0.80	0.054	0	35.2	8500	.	M	25.7	8780	-0.1	0.61
NYC0538R	36-42.2861- 73.5827-4-52-000	7.2	262	3.00	0.402	U	38.8	3400	15	M	56.0	4540	0.3	1.53
NYC0539R	36-42.2978- 73.5194-4-52-000	7.3	257	2.10	1.128	150	24.2	4100	152	M	36.4	20600	-0.1	4.39
NYC0540R	36-42.2852- 73.4649-4-52-000	7.4	100	1.40	0.724	U	14.3	9400	85	M	49.2	28280	-0.1	7.24
NYC0541R	36-42.2412- 73.4640-4-52-000	7.2	62	0.50	0.020	38	36.7	6100	35	M	37.3	5350	-0.1	0.32
NYC0542R	36-42.2347- 73.5151-4-52-000	7.0	139	1.30	1.399	110	20.1	3900	54	M	44.3	5400	-0.1	10.06
NYC0543R	36-42.2460- 73.5684-4-52-000	6.8	108	1.00	0.161	160	.	5300	70	M	24.6	9230	-0.1	1.49
NYC0544R	36-42.1194- 73.6990-4-52-000	7.1	308	4.10	0.173	U	.	4300	32	M	174.4	18410	-0.1	0.58
NYC0545R	36-42.1533- 73.6911-4-52-000	7.3	238	2.90	0.050	130	21.5	7600	174	M	160.5	14470	-0.1	0.22
NYC0546R	36-42.1398- 73.6021-4-52-000	6.7	100	0.90	0.200	100	39.2	5300	30	M	41.9	6650	0.2	2.00
NYC0547R	36-42.1015- 73.6293-4-52-000	7.3	220	1.90	1.491	U	.	12400	29	M	104.6	7250	-0.1	6.78
NYC0548R	36-42.0573- 73.6538-4-52-000	7.8	200	2.70	0.665	355	22.7	6100	11	M	.	16900	-0.1	3.33
NYC0549R	36-42.0547- 73.6924-4-52-000	7.4	270	3.50	0.878	215	20.0	4400	58	M	56.5	21660	-0.1	3.25
NYC0550R	36-42.0655- 73.7361-4-52-000	7.6	213	2.90	0.200	1800	.	11200	58	M	897.2	9200	-0.1	0.95
NYC0551R	36-42.0271- 73.7579-4-52-000	6.4	113	0.50	0.016	150	17.2	11600	25	M	66.3	8750	-0.1	0.15
NYC0552R	36-42.0083- 73.6718-4-52-000	7.6	233	2.60	1.278	U	28.5	4000	95	M	103.1	13630	0.5	5.56
NYC0553R	36-42.0211- 73.6359-4-52-000	7.4	183	1.50	6.211	U	44.0	5100	43	M	41.7	5820	-0.1	34.51
NYC0554R	36-42.2031- 73.4810-4-52-000	7.2	345	4.50	6.699	50	.	4600	12	M	124.5	4850	-0.1	19.42
NYC0555R	36-42.1941- 73.5127-4-52-000	7.1	52	0.80	9.635	U	18.6	5000	39	M	41.2	4950	-0.1	185.29
NYC0556R	36-42.1911- 73.5735-4-52-000	7.2	141	1.70	7.601	34	18.2	4300	18	M	160.4	5540	-0.1	53.91
NYC0557R	36-42.1553- 73.5656-4-52-000	7.4	152	2.10	0.275	130	25.9	4600	85	M	108.4	8790	-0.1	1.81
NYC0558R	36-42.1531- 73.5098-4-52-000	6.5	68	0.40	0.024	U	21.6	6300	12	M	41.7	5740	-0.1	0.35
NYC0559R	36-42.0997- 73.5167-4-52-000	7.3	600	4.60	2.632	U	.	59700	.	M	159.3	36540	-0.1	4.39
NYC0560R	36-42.0924- 73.5650-4-53-000	7.4	165	1.90	0.300	0	.	7400	25	M	75.6	5170	-0.1	1.82
NYC0561R	36-42.0497- 73.5649-4-52-000	7.0	650	6.30	0.533	225	62.8	24400	.	M	268.2	13690	-0.1	0.82
NYC0562R	36-42.0645- 73.5240-4-52-000	7.3	330	5.00	0.182	U	18.2	4700	32	M	.	4220	-0.1	0.55
NYC0563R	36-42.0070- 73.5158-4-52-000	7.4	372	4.40	2.676	30	40.8	10400	.	M	.	9020	-0.1	7.19
NYC0564R	36-42.0089- 73.5801-4-52-000	7.2	212	2.30	1.115	100	.	3800	13	M	61.0	5210	-0.1	5.26
NYDU609R	36-42.0074- 73.7765-4-52-000	7.0	111	1.40	0.080	108	19.6	3300	13	M	94.9	9230	-0.1	0.72
NYDU639R	36-42.0122- 73.8662-4-52-000	7.1	450	4.00	0.169	U	.	43400	.	M	118.1	23550	-0.1	0.34

TABLE A-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -GROUND WATER--

ALBANY

SHEET

10

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	DEPTH FEET	BR PPB	CL PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NYDU640R	36-42.0051- 73.8316-4-53-000	7.6	139	2.00	0.020	0	.	3600	.	M	110.5	9020	-0.1	0.14
NYDU642R	36-42.0061- 73.9058-4-52-000	8.7	550	6.30	0.066	U	.	39100	74	M	190.2	94400	0.7	0.12
NYDU643R	36-42.0515- 73.9004-4-52-000	7.8	320	4.30	0.129	150	21.0	8900	25	M	153.6	12330	-0.1	0.40
NYDU644R	36-42.0760- 73.9037-4-52-000	7.6	304	3.30	0.159	80	.	11300	53	M	135.2	11580	0.5	0.52
NYDU645R	36-42.0538- 73.8638-4-52-000	7.6	251	3.20	0.132	U	18.6	6600	36	M	169.7	11530	-0.1	0.53
NYDU646R	36-42.0455- 73.8199-4-52-000	7.5	308	2.90	0.418	U	.	19000	.	M	143.4	11850	-0.1	1.36
NYGR501R	36-42.3995- 73.8174-4-53-000	7.7	334	3.20	0.136	0	.	12700	.	M	.	6570	-0.1	0.41
NYGR502R	36-42.4415- 73.8115-4-52-000	7.8	387	3.80	0.075	85	.	4500	25	M	99.2	9170	-0.1	0.19
NYGR503R	36-42.4327- 73.8686-4-52-000	7.9	195	2.00	0.069	145	24.1	4500	62	M	182.3	3640	-0.1	0.35
NYGR504R	36-42.3943- 73.8832-4-52-000	7.6	403	3.80	0.460	90	.	10000	.	M	232.6	5730	-0.1	1.14
NYGR505R	36-42.4034- 73.9313-4-52-000	7.3	128	1.20	0.047	60	38.4	4200	43	M	.	2550	-0.1	0.37
NYGR506R	36-42.3977- 73.9950-4-52-000	7.7	230	2.50	0.948	U	.	7700	.	M	.	23320	-0.1	4.12
NYGR509R	36-42.3603- 73.9907-4-52-000	7.5	303	3.10	0.805	U	16.3	12400	.	M	.	3460	-0.1	2.66
NYGR510R	36-42.3509- 73.9273-4-52-000	8.2	252	3.10	0.048	119	21.8	8000	54	M	.	43610	-0.1	0.19
NYGR511R	36-42.3550- 73.8722-4-52-000	7.7	270	2.50	0.041	150	12.7	4200	110	M	87.0	18420	-0.1	0.15
NYGR512R	36-42.3212- 73.8147-4-52-000	7.3	368	3.50	0.413	160	.	7100	.	M	.	M	-0.1	1.12
NYGR513R	36-42.3074- 73.8755-4-52-000	7.3	356	4.60	0.149	180	.	8200	135	M	10.6	27070	-0.1	0.42
NYGR514R	36-42.3115- 73.9271-4-52-000	7.3	173	1.80	0.503	60	.	6300	18	M	18.9	7320	-0.1	2.91
NYGR515R	36-42.3030- 73.9968-4-52-000	7.5	311	2.20	0.060	85	45.6	14200	.	M	144.2	13450	-0.1	0.19
NYGR552R	36-42.1794- 73.9962-4-52-000	6.3	135	0.60	-0.002	90	22.0	19200	.	M	.	9980	-0.1	0.00
NYGR553R	36-42.1771- 73.9292-4-52-000	7.0	313	2.40	0.337	150	.	13100	.	M	63.1	11180	-0.1	1.08
NYGR554R	36-42.2121- 73.9306-4-52-000	7.7	233	2.00	0.072	97	.	4600	38	M	.	14780	-0.1	0.31
NYGR555R	36-42.2165- 73.9968-4-52-000	7.2	134	1.00	0.122	125	.	5400	54	M	.	13560	-0.1	0.91
NYGR556R	36-42.2655- 73.9755-4-52-000	6.7	78	0.60	3.188	127	20.7	3900	18	M	24.4	2970	-0.1	40.87
NYGR557R	36-42.2602- 73.9373-4-52-000	6.6	212	0.50	-0.002	U	.	27400	.	M	.	11300	0.3	0.00
NYGR558R	36-42.2615- 73.8652-4-52-000	7.2	400	3.10	0.169	90	.	13000	.	M	62.6	38040	-0.1	0.42
NYRE501R	36-42.8399- 73.6476-4-52-000	8.3	560	8.40	0.218	350	.	7100	.	M	49.3	72980	-0.1	0.39
NYRE502R	36-42.7919- 73.6512-4-52-000	7.3	340	2.10	0.047	U	.	M	.	M	41.0	M	-0.1	0.14
NYRE503R	36-42.7164- 73.6496-4-52-000	7.8	250	3.90	0.547	135	10.1	5700	.	M	52.0	12500	-0.1	2.19
NYRE504R	36-42.6678- 73.6603-4-52-000	8.2	440	5.50	0.101	U	.	M	.	M	.	M	-0.1	0.23
NYRE505R	36-42.6696- 73.6903-4-52-000	7.1	370	1.60	0.013	22	.	M	.	M	.	M	-0.1	0.04
NYRE506R	36-42.6302- 73.5988-4-52-000	3.1	110	2.30	0.175	130	20.1	5600	.	M	42.9	8720	-0.1	1.59
NYRE507R	36-42.6301- 73.5330-4-52-000	7.9	130	2.20	0.202	U	.	3800	60	M	50.4	10920	-0.1	1.55
NYRE508R	36-42.6684- 73.5854-4-52-000	8.0	140	1.90	0.057	140	23.8	6500	32	M	45.6	12010	-0.1	0.41
NYRE509R	36-42.6683- 73.5246-4-52-000	8.5	120	2.40	0.527	340	38.9	3700	42	M	56.4	11270	-0.1	4.39
NYRE510R	36-42.7137- 73.5954-4-52-000	7.7	100	1.00	0.014	59	.	6800	.	M	.	7320	-0.1	0.14
NYRE511R	36-42.7589- 73.5895-4-52-000	7.0	410	3.70	0.637	U	.	M	.	M	.	31360	-0.1	1.55
NYRE512R	36-42.7614- 73.5397-4-52-000	7.6	320	3.80	0.232	182	.	15400	.	M	64.5	13630	-0.1	0.73
NYRE513R	36-42.7960- 73.5298-4-52-000	8.4	140	2.00	1.412	U	8.8	5000	10	M	47.1	26910	-0.1	10.09
NYRE514R	36-42.7973- 73.5923-4-52-000	7.6	140	2.00	0.134	86	.	3700	45	M	26.9	3110	-0.1	0.96
NYRE515R	36-42.8376- 73.5955-4-52-000	7.4	180	2.00	0.286	110	34.0	4800	71	M	110.4	7140	-0.1	1.59
NYRE516R	36-42.8440- 73.5245-4-53-000	7.0	120	1.60	0.058	0	.	6200	42	M	43.2	2610	-0.1	0.48
NYRE517R	36-42.8415- 73.4654-4-52-000	7.2	155	1.60	0.134	U	23.1	5600	11	M	.	2720	-0.1	0.86
NYRE518R	36-42.8430- 73.4089-4-53-000	7.5	40	0.28	0.008	0	33.0	3900	17	M	18.4	1040	-0.1	0.20
NYRE519R	36-42.8007- 73.3994-4-53-000	6.7	40	0.24	-0.002	0	.	4600	21	M	.	970	-0.1	-0.04
NYRE520R	36-42.7583- 73.4108-4-52-000	7.3	110	1.40	0.138	290	1723.0	4000	116	M	9.2	2320	-0.1	1.25
NYRE521R	36-42.7514- 73.4529-4-52-000	7.1	70	0.60	-0.002	U	.	6400	38	M	8.5	2260	-0.1	-0.02
NYRE522R	36-42.7858- 73.4608-4-52-000	6.8	140	1.70	0.039	U	.	9300	50	M	.	2480	-0.1	0.28
NYRE523R	36-42.7559- 73.3428-4-52-000	6.9	220	2.40	0.417	U	.	24500	.	M	.	8180	-0.1	1.90
NYRE524R	36-42.8029- 73.3386-4-53-000	7.0	130	2.00	0.208	0	27.1	5300	17	M	.	1940	-0.1	1.60
NYRE525R	36-42.8458- 73.3423-4-52-000	7.3	185	3.10	0.327	140	.	3300	29	M	48.5	4040	-0.1	1.77
NYRE526R	36-42.7246- 73.3069-4-52-000	7.6	195	2.30	4.242	75	.	3800	88	M	.	7730	-0.1	21.75
NYRE527R	36-42.7208- 73.3262-4-52-000	7.4	120	1.70	0.329	U	16.9	3700	21	M	104.7	1530	-0.1	2.74

TABLE A-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -GROUND WATER-- ALBANY SHEET

11

SRL I.D. *****	DOE I.D.		PH	COND. UM/CM	AKMXD MEQ/L	U PPB	DEPTH FEET	BR PPE	CL PPB	F PPB	MG FPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NYRE528R	36-42.6761-	73.3353-4-52-000	7.4	65	1.20	0.059	40	44.8	3700	44	M	.	1510	-0.1	0.91
NYRE529R	36-42.6261-	73.3440-4-52-000	9.1	170	2.90	3.438	200	.	3500	67	M	7.0	35880	-0.1	20.22
NYRE530R	36-42.5855-	73.3538-4-53-000	8.3	100	1.40	0.212	0	.	4000	41	M	.	1410	-0.1	2.12
NYRE531R	36-42.5447-	73.3538-4-52-000	8.0	170	2.00	0.303	70	.	7300	20	M	34.5	2840	-0.1	1.78
NYRE532R	36-42.6436-	73.4081-4-52-000	7.9	70	1.00	0.056	170	23.3	4000	54	M	.	3380	-0.1	0.80
NYRE533R	36-42.6655-	73.4171-4-52-000	7.7	80	1.00	0.352	300	.	3900	45	M	11.4	2310	-0.1	4.40
NYRE534R	36-42.7078-	73.4213-4-53-000	6.6	65	0.50	0.024	0	.	12300	.	M	5.7	4560	-0.1	0.37
NYRE535R	36-42.7134-	73.4722-4-52-000	7.4	145	2.40	1.063	U	.	4100	.	M	.	8370	-0.1	7.33
NYRE536R	36-42.6758-	73.4724-4-52-000	7.9	100	1.50	0.644	120	.	3800	.	M	28.4	5720	-0.1	6.44
NYRE537R	36-42.7147-	73.5091-4-52-000	8.2	130	1.90	0.951	500	.	4200	104	M	9.4	9600	-0.1	7.32
NYRE538R	36-42.6412-	73.4803-4-53-000	7.2	60	0.60	0.012	0	36.9	5300	.	M	28.8	1600	0.2	0.20
NYRE539R	36-42.6051-	73.6538-4-52-000	7.2	320	3.70	0.006	125	.	M	.	M	.	7340	-0.1	0.02
NYRE540R	36-42.5857-	73.7197-4-52-000	7.0	205	1.90	-0.002	20	66.7	8200	.	M	.	4070	-0.1	0.00
NYRE541R	36-42.5452-	73.7138-4-52-000	8.1	190	2.30	0.003	25	22.1	8100	.	M	46.7	3100	-0.1	0.02
NYRE542R	36-42.5139-	73.7065-4-52-000	8.0	400	3.70	0.170	250	1723.0	36300	.	M	41.3	44440	-0.1	0.43
NYRE543R	36-42.5074-	73.6596-4-52-000	8.7	370	2.90	0.028	210	20.6	6800	23	M	30.7	34690	-0.1	0.08
NYRE544R	36-42.5430-	73.6476-4-52-000	8.3	175	2.00	0.237	100	.	15700	.	M	.	5540	-0.1	1.35
NYRE545R	36-42.5078-	73.6100-4-52-000	8.0	160	1.80	0.565	U	26.2	8200	30	M	.	4790	-0.1	3.53
NYRE546R	36-42.5513-	73.5849-4-52-000	8.2	150	1.80	1.750	115	38.5	7300	26	M	63.3	6990	-0.1	11.67
NYRE547R	36-42.5977-	73.5927-4-53-000	7.6	50	0.80	0.004	0	25.6	3500	24	M	30.7	2910	-0.1	0.08
NYRE548R	36-42.5927-	73.5165-4-52-000	7.6	200	2.60	0.130	U	.	3400	109	M	137.0	8670	-0.1	0.65
NYRE549R	36-42.5479-	73.5273-4-52-000	8.5	200	2.70	2.059	U	15.5	3500	126	M	19.6	20220	-0.1	10.30
NYRE550R	36-42.5153-	73.5117-4-52-000	8.3	50	0.34	0.042	12	46.6	7800	.	M	20.5	3720	-0.1	0.84
NYRE551R	36-42.5425-	73.3933-4-52-000	8.4	140	2.40	0.301	300	27.3	3500	44	M	26.8	14350	-0.1	2.15
NYRE552R	36-42.5681-	73.4232-4-52-000	8.0	140	2.30	0.092	60	22.9	3200	196	M	140.9	8540	-0.1	0.66
NYRE553R	36-42.5453-	73.4679-4-53-000	7.9	30	0.70	-0.002	0	41.4	3700	43	M	22.6	2410	-0.1	-0.06
NYRE554R	36-42.5838-	73.4758-4-53-000	7.2	30	0.32	-0.002	0	18.5	3600	17	M	22.9	1700	-0.1	-0.06
NYRE555R	36-42.8770-	73.3360-4-52-000	6.8	230	2.80	1.911	U	.	10500	.	M	69.3	3430	-0.1	8.31
NYRE556R	36-42.9144-	73.3351-4-52-000	7.2	700	8.30	5.248	110	.	69200	.	M	.	20080	-0.1	7.50
NYRE557R	36-42.9319-	73.4000-4-53-000	7.2	140	1.60	0.118	0	.	5600	13	M	33.9	2840	-0.1	0.84
NYRE558R	36-42.8956-	73.4054-4-52-000	7.8	190	2.50	0.430	105	.	M	.	M	.	M	-0.1	2.26
NYRE559R	36-42.8881-	73.4601-4-52-000	7.7	170	2.00	0.123	105	.	4300	14	M	39.9	7080	-0.1	0.72
NYRE560R	36-42.9279-	73.4671-4-52-000	7.7	330	2.70	1.156	U	.	17100	.	M	232.0	5800	-0.1	3.50
NYRE561R	36-42.9217-	73.5328-4-52-000	7.2	260	2.80	0.258	U	13.5	7500	.	M	98.2	3430	-0.1	0.99
NYRE562R	36-42.8849-	73.5306-4-53-000	6.9	70	1.30	0.027	0	24.7	5500	23	M	.	2340	-0.1	0.39
NYRE563R	36-42.8837-	73.5985-4-52-000	7.6	215	3.30	0.419	115	.	12300	171	M	141.1	7820	-0.1	1.95
NYRE564R	36-42.9223-	73.5818-4-52-000	7.9	300	4.70	0.060	170	.	3400	66	M	32.8	21690	-0.1	0.20
NYRE565R	36-42.9247-	73.6402-4-52-000	9.2	420	5.20	0.093	300	52.3	7100	1317	M	19.8	80520	-0.1	0.22
NYSC504R	36-42.9169-	73.9982-4-52-000	9.7	483	4.90	0.039	186	.	1400	97	M	.	M	-0.1	0.08
NYSC505R	36-42.8990-	73.9297-4-52-000	7.7	141	0.80	-0.002	28	28.1	11400	.	M	20.5	17550	-0.1	0.00
NYSC506R	36-42.8993-	73.9515-4-52-000	7.8	389	3.20	0.827	U	23.5	4900	39	M	72.0	3640	0.4	2.13
NYSC507R	36-42.8637-	73.9875-4-52-000	7.4	740	3.10	0.042	U	.	146500	.	M	.	13750	-0.1	0.06
NYSC508R	36-42.8200-	73.8718-4-52-000	7.2	1030	4.10	0.356	22	.	203200	.	M	269.1	52550	-0.1	0.35
NYSC509R	36-42.7822-	73.8658-4-52-000	7.6	530	4.40	0.169	15	65.8	12500	.	M	579.8	6530	-0.1	0.32
NYSR543R	36-42.9886-	73.7135-4-52-000	6.6	232	1.60	0.058	U	48.0	6300	35	M	108.2	8270	-0.1	0.25
NYSR544R	36-42.9855-	73.6598-4-52-000	7.0	419	1.80	0.095	25	.	50000	.	M	343.6	26180	0.4	0.23
NYSR545R	36-42.9478-	73.6617-4-52-000	7.1	820	4.00	1.412	70	.	127300	.	M	459.4	10270	-0.1	1.72
NYSR546R	36-42.9469-	73.7132-4-53-000	7.9	243	1.70	0.131	0	.	10900	33	M	119.0	6410	0.6	0.54
NYSR547R	36-42.9478-	73.7737-4-52-000	8.3	147	1.10	0.022	23	37.8	5400	16	M	90.3	5290	-0.1	0.15
NYSR548R	36-42.9931-	73.7809-4-52-000	9.2	173	1.70	-0.002	95	32.2	4300	236	M	73.3	30410	-0.1	0.00
NYSR553R	36-42.9828-	73.9612-4-52-000	7.2	339	3.00	0.241	19	.	10200	23	M	95.7	10510	-0.1	0.71
NYSR557R	36-42.9481-	73.9674-4-52-000	7.6	620	3.80	0.523	25	.	21000	.	M	123.8	22640	-0.1	0.84
NYSR558R	36-42.9458-	73.9062-4-52-000	8.4	610	5.20	0.125	U	53.3	34600	329	M	117.2	84520	-0.1	0.20

TABLE A-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -GROUND WATER--

ALBANY

SHEET

12

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	DEPTH FEET	BR PPB	CL PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NYSR559R	36-42.9896- 73.9073-4-52-000	8.6	302	2.40	-0.002	125	.	18800	173	M	68.0	38430	-0.1	0.00
NYSR560R	36-42.9844- 73.8549-4-52-000	6.9	94	0.80	-0.002	28	41.2	5700	35	M	50.4	8390	-0.1	-0.01
NYSR561R	36-42.9394- 73.8404-4-52-000	8.2	399	4.20	0.019	95	.	8600	491	M	100.3	46350	-0.1	0.05
NYSR562R	36-42.9017- 73.7761-4-52-000	7.7	331	3.20	0.006	U	.	38500	.	M	128.9	33350	-0.1	0.02
NYSR563R	36-42.8982- 73.7148-4-52-000	7.7	362	3.40	0.342	20	.	7000	102	M	125.3	11510	0.3	0.94
NYSR564R	36-42.8552- 73.7049-4-53-000	8.0	383	3.40	0.541	0	.	8100	68	M	167.1	9680	-0.1	1.41
NYSR565R	36-42.8628- 73.7624-4-52-000	8.9	384	4.00	0.031	90	33.5	7500	746	M	41.0	77150	-0.1	0.08
NYSR566R	36-42.8072- 73.7801-4-52-000	6.6	990	3.40	0.413	12	.	122200	.	M	2136.0	45640	-0.1	0.42
NYSR567R	36-42.8137- 73.8477-4-52-000	7.2	550	3.20	0.076	U	30.7	57800	.	M	310.2	47500	-0.1	0.14
NYSR568R	36-42.8496- 73.8409-4-52-000	9.3	496	4.00	0.043	16	.	7700	483	M	40.4	78320	-0.1	0.09
NYSR569R	36-42.9094- 73.8364-4-52-000	7.9	264	2.40	0.070	12	.	6900	67	M	119.2	13720	-0.1	0.27
NYUL655R	36-42.0058- 73.9689-4-52-000	7.2	348	2.20	0.027	100	.	77500	.	M	.	15570	-0.1	0.08
NYUL656R	36-42.0379- 73.9698-4-52-000	7.1	239	2.00	0.032	50	35.7	21500	.	M	.	17930	-0.1	0.13
NYUL657R	36-42.0835- 73.9635-4-52-000	7.1	365	5.50	0.142	100	86.3	11400	124	M	.	3490	0.3	0.39
NYUL658R	36-42.1071- 73.9720-4-52-000	7.4	386	5.20	0.301	100	.	27800	.	M	43.9	12510	-0.1	0.78
NYWS524R	36-42.9701- 73.5701-4-52-000	7.7	360	4.80	0.351	70	43.0	7500	105	M	182.5	15040	0.5	0.98
NYWS525R	36-42.9694- 73.5073-4-52-000	8.0	210	4.10	0.163	150	32.8	5300	99	M	176.5	8350	0.2	0.78
NYWS530R	36-42.9711- 73.4524-4-52-000	7.8	340	4.40	0.745	100	36.3	6700	92	M	124.2	11740	-0.1	2.19
NYWS531R	36-42.9657- 73.3735-4-52-000	7.8	430	4.90	0.533	100	161.3	21100	84	M	145.8	21310	-0.1	1.24
NYWS532R	36-42.9766- 73.3311-4-52-000	7.6	150	2.10	0.046	U	19.8	4100	38	M	110.7	6650	0.2	0.31
VTBE519R	50-42.8902- 73.1411-4-53-000	6.3	132	1.00	0.036	0	.	23500	.	M	164.1	15150	-0.1	0.27
VTBE520R	50-42.8797- 73.0811-4-52-000	7.4	155	1.90	0.599	U	38.5	5400	42	M	156.5	9010	0.3	3.86
VTBE521R	50-42.8914- 73.0301-4-52-000	7.5	100	1.40	0.035	25	22.8	6500	.	M	166.1	8050	0.2	0.35
VTBE522R	50-42.8935- 72.9721-4-52-000	7.5	120	0.40	0.005	12	.	29900	.	M	141.8	20910	-0.1	0.04
VTBE523R	50-42.8297- 72.9934-4-52-000	7.1	65	0.70	-0.002	U	26.2	4300	43	M	173.7	10430	-0.1	-0.02
VTBE524R	50-42.7918- 73.0335-4-53-000	6.6	120	1.00	0.005	0	.	19800	.	M	150.4	11820	-0.1	0.04
VTBE525R	50-42.7646- 73.0564-4-53-000	6.3	22	0.16	-0.002	0	45.3	4500	.	M	132.2	8080	-0.1	-0.08
VTBE526R	50-42.8046- 72.9759-4-53-000	5.2	20	0.02	0.003	0	24.2	4600	39	M	141.3	7400	-0.1	0.15
VTBE527R	50-42.7792- 72.9451-4-53-000	6.9	40	0.36	-0.002	0	24.4	3800	19	M	141.0	7680	-0.1	-0.04
VTBE528R	50-42.7973- 73.2096-4-53-000	7.6	252	4.40	0.249	0	20.7	4600	13	M	203.0	7410	-0.1	0.99
VTBE529R	50-42.8451- 73.2008-4-52-000	7.4	460	4.40	0.209	160	.	64900	.	M	163.8	29530	-0.1	0.45
VTBE530R	50-42.8632- 73.2055-4-52-000	6.8	360	3.20	0.150	100	.	6100	19	M	231.9	8990	-0.1	0.42
VTBE543R	50-42.9928- 73.2054-4-52-000	8.1	250	3.60	0.343	200	18.4	3400	22	M	184.6	42680	0.4	1.37
VTBE544R	50-42.9839- 73.2215-4-52-000	8.3	100	1.50	0.065	125	15.8	3500	.	M	210.6	6440	-0.1	0.65
VTBE545R	50-42.9112- 73.2249-4-52-000	6.2	270	4.10	0.184	100	16.5	4200	24	M	283.8	5890	-0.1	0.68
VTBE546R	50-42.9529- 73.2467-4-53-000	6.5	115	2.30	0.010	0	24.8	4000	.	M	194.1	5760	-0.1	0.09
VTBE547R	50-42.9491- 73.1893-4-53-000	7.2	250	5.60	1.994	0	25.6	10600	.	M	347.3	8280	-0.1	7.98
VTBE548R	50-42.9223- 73.1798-4-52-000	7.5	85	1.40	0.144	12	26.8	4900	16	M	207.8	6310	0.4	1.69
VTBE549R	50-42.8291- 73.1676-4-52-000	7.1	145	1.90	0.053	15	.	6000	43	M	210.2	6970	-0.1	0.37
VTBE550R	50-42.8029- 73.1756-4-52-000	7.4	220	3.60	0.125	U	19.9	6800	.	M	254.5	6650	-0.1	0.57
VTBE551R	50-42.7479- 73.2359-4-52-000	7.7	260	3.90	1.029	85	39.3	9500	.	M	298.3	7160	-0.1	3.96
VTBE552R	50-42.8049- 73.2585-4-52-000	7.4	310	3.90	0.248	15	25.2	13900	.	M	236.5	9260	0.3	0.80
VTWI529R	50-42.9795- 72.6589-4-52-000	7.3	98	1.20	0.246	300	16.5	5400	142	M	76.2	7710	0.4	2.51
VTWI534R	50-42.9824- 72.5702-4-52-000	6.9	300	3.10	0.447	85	36.2	11600	.	M	84.5	7630	-0.1	1.49
VTWI535R	50-42.9751- 72.5929-4-52-000	6.9	165	1.40	0.330	143	36.9	11700	30	M	90.8	6870	-0.1	2.00
VTWI536R	50-42.9322- 72.7092-4-52-000	7.4	158	0.90	0.184	150	14.1	27500	30	M	128.5	15370	0.4	1.16
VTWI537R	50-42.9447- 72.6758-4-52-000	7.0	27	0.30	0.003	U	15.1	4200	.	M	47.7	4060	0.3	0.11
VTWI538R	50-42.9639- 72.7097-4-52-000	6.4	19	0.20	0.005	4	29.5	3900	10	M	49.5	3630	-0.1	0.26
VTWI542R	50-42.9607- 72.7925-4-53-000	6.4	47	0.50	0.013	0	16.9	3800	.	M	65.0	3530	-0.1	0.28
VTWI545R	50-42.9755- 72.8749-4-52-000	7.8	110	1.40	0.448	125	.	3400	64	M	95.9	5380	-0.1	4.07
VTWI546R	50-42.9313- 72.8533-4-52-000	6.8	58	0.60	0.136	U	.	3900	21	M	78.8	3990	0.4	2.34
VTWI547R	50-42.9565- 72.8146-4-52-000	7.1	200	1.80	0.475	230	22.9	8900	.	M	124.9	5460	-0.1	2.38
VTWI548R	50-42.9308- 72.7958-4-52-000	6.8	137	1.20	0.076	150	48.2	15000	.	M	78.6	5670	-0.1	0.55

TABLE A-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -GROUND WATER--

ALBANY

SHEET

13

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	DEPTH FEET	SR PPB	CL PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
VTW1549R	50-42.8903- 72.5625-4-52-000	7.2	263	3.40	0.194	U	23.0	10400	.	M	87.3	5050	-0.1	0.74
VTW1550R	50-42.9226- 72.5712-4-52-000	7.8	293	2.50	0.471	108	822.7	23600	.	M	85.9	7550	-0.1	1.61
VTW1551R	50-42.9402- 72.6126-4-52-000	7.1	72	0.80	0.019	U	40.5	5900	.	M	75.8	4090	-0.1	0.26
VTW1552R	50-42.8787- 72.5981-4-52-000	7.7	1.8	1.30	0.206	144	10.6	7200	285	M	88.3	7030	0.4	1.75
VTW1553R	50-42.8696- 72.6562-4-52-000	6.2	193	0.22	-0.002	4	.	43300	.	M	74.3	22290	-0.1	0.00
VTW1554R	50-42.8521- 72.6187-4-52-000	7.4	200	2.70	0.189	110	.	6300	.	M	78.1	4180	-0.1	0.95
VTW1555R	50-42.8345- 72.6501-4-53-000	7.9	102	1.40	0.069	0	14.6	4000	15	M	82.8	4070	-0.1	0.68
VTW1556R	50-42.7989- 72.6573-4-53-000	7.4	131	1.90	0.053	0	28.2	4800	15	M	87.3	4380	0.3	0.40
VTW1557R	50-42.7896- 72.6248-4-53-000	7.8	130	1.60	0.059	0	20.7	3400	22	M	94.5	5250	0.3	0.45
VTW1558R	50-42.7439- 72.6115-4-52-000	7.9	132	1.60	0.235	U	13.7	3800	53	M	120.7	5670	-0.1	1.78
VTW1559R	50-42.7520- 72.5728-4-52-000	7.0	60	0.50	0.142	110	24.1	3900	9	M	94.2	5010	-0.1	2.37
VTW1560R	50-42.8540- 72.8535-4-52-000	6.9	110	1.50	0.089	U	39.4	4800	1.0	M	114.1	5200	-0.1	0.81
VTW1561R	50-42.8113- 72.8491-4-52-000	6.5	54	0.60	0.007	8	26.8	5200	25	M	101.9	4680	-0.1	0.13
VTW1562R	50-42.7539- 72.9094-4-52-000	6.0	11	0.16	-0.002	6	14.0	4200	15	M	67.5	4560	-0.1	-0.17
VTW1563R	50-42.7549- 72.8601-4-52-000	6.2	30	0.26	0.010	U	21.7	3800	30	M	69.5	4240	-0.1	0.33
VTW1564R	50-42.7633- 72.7916-4-52-000	6.7	172	1.80	0.038	18	18.1	4400	26	M	89.4	4840	-0.1	0.22
VTW1565R	50-42.7663- 72.7430-4-52-000	6.5	110	1.40	0.089	U	17.5	5500	.	M	81.9	5350	-0.1	0.81
VTW1566R	50-42.8137- 72.7448-4-52-000	6.2	32	0.24	-0.002	7	28.4	5000	24	M	75.3	5280	-0.1	-0.05
VTW1567R	50-42.8152- 72.3033-4-52-000	6.8	110	1.50	0.256	100	32.1	4000	351	M	96.9	8010	-0.1	2.33
VTW1568R	50-42.8365- 72.3052-4-52-000	6.2	38	0.28	0.031	U	22.9	4400	19	M	76.7	4710	-0.1	0.82
VTW1569R	50-42.8395- 72.7234-4-52-000	6.9	79	0.90	0.062	50	42.4	4500	26	M	81.4	4990	2.4	0.78
VTW1570R	50-42.8862- 72.7433-4-52-000	6.8	41	0.48	0.335	275	15.3	3600	31	M	74.2	5620	-0.1	8.17
VTW1571R	50-42.8884- 72.7814-4-52-000	6.4	30	0.28	0.010	3	18.8	3500	.	M	78.7	4770	-0.1	0.33
VTW1572R	50-42.8945- 72.8565-4-52-000	7.0	91	0.94	0.121	U	41.3	4300	77	M	80.2	5550	0.6	1.33
VTW1573R	50-42.8778- 72.8969-4-52-000	6.7	110	1.60	0.051	15	41.5	4500	9	M	95.5	4590	-0.1	0.46
VTW1574R	50-42.8787- 72.6930-4-53-000	5.3	12	0.08	-0.002	0	11.4	3800	.	M	89.5	4700	-0.1	-0.16
VTW1575R	50-42.7862- 72.5507-4-52-000	5.8	25	0.18	0.008	3	26.6	3700	.	M	78.1	4920	-0.1	0.32
VTW1576R	50-42.7494- 72.4921-4-52-000	6.1	260	0.80	0.141	52	.	40900	.	M	79.3	18930	-0.1	0.54

APPENDIX B: Stream Sediment Reconnaissance Data

Key data reported for stream sediment sites include:

- water quality measurements (pH, conductivity, and alkalinity)
- elemental analyses (in order of appearance in figures) for U, Th, Hf, Al, Ce, Fe, Mn, Sc, Na, Ti, and V
- analyses for the supplemental elements Dy, Eu, La, Lu, Sm, and Yb
- sampling site descriptors (stream characteristics, vegetation, etc.)

LIST OF FIGURES

- B-1 Areal Distribution of Stream Water pH Values
- B-2 Areal Distribution of Stream Water Conductivity Values
- B-3 Areal Distribution of Stream Water Alkalinity Values
- B-4 Areal Distribution of Uranium Concentrations in Stream Sediment
- B-5 Areal Distribution of Thorium Concentrations in Stream Sediment
- B-6 Areal Distribution of Hafnium Concentrations in Stream Sediment
- B-7 Areal Distribution of Aluminum Concentrations in Stream Sediment
- B-8 Areal Distribution of Cerium Concentrations in Stream Sediment
- B-9 Areal Distribution of Iron Concentrations in Stream Sediment
- B-10 Areal Distribution of Manganese Concentrations in Stream Sediment
- B-11 Areal Distribution of Scandium Concentrations in Stream Sediment
- B-12 Areal Distribution of Sodium Concentrations in Stream Sediment
- B-13 Areal Distribution of Titanium Concentrations in Stream Sediment
- B-14 Areal Distribution of Vanadium Concentrations in Stream Sediment

Figures on Microfiche:

Log Histograms and Cumulative Frequency Plots for Stream Water pH, Conductivity, and Alkalinity as well as for U, Th, Hf, Al, Ce, Fe, Mn, Sc, Na, Ti, and V for Stream Sediments; see microfiche labeled "Sediment Plots."

LIST OF TABLES

- B-1 Key Field Measurements and Analytical Data - Sediment
- B-2 Supplementary Field and Analytical Data - Sediment (See Microfiche Cards "Sediment Plots" and "Table B-2 Supp. Data.")

ALBANY
pH In Surface Water
1301 Values Above D.L.

1x2° Sheet

pH		-pH units		
+ < 4.5	○ 5.5- 6.0	○ 6.7- 7.0	⊙ 7.7- 7.9	● 8.3- 8.6
+ 4.5- 4.9	○ 6.0- 6.4	○ 7.0- 7.4	⊙ 7.9- 8.1	◆ 8.6- 8.8
+ 4.9- 5.5	○ 6.4- 6.7	○ 7.4- 7.7	⊙ 8.1- 8.3	★ > 8.8

FIGURE B-1. Areal Distribution of Stream Water pH Values

ALBANY *1x2° Sheet*
Conductivity In Surface Water
1302 Values Above D.L.

Conductivity - micro-mhos per cm.					
+ < 18.0	○ 25.0- 30.0	○ 50.0- 71.0	⊙ 177.0- 270.0	● 450.0- 700.0	
x 18.0- 20.0	○ 30.0- 36.0	○ 71.0- 115.0	⊙ 270.0- 360.0	◆ 700.0- 1150.0	
• 20.0- 25.0	○ 36.0- 50.0	⊙ 115.0- 177.0	⊙ 360.0- 450.0	★ > 1150.0

FIGURE B-2. Areal Distribution of Stream Water Conductivity Values

ALBANY *1x2° Sheet*
Alkalinity In Surface Water
1292 Values Above D.L.

Alkalinity - milliequivalent/liter

+ < 0.01	o 0.06- 0.08	○ 0.20- 0.36	⊙ 1.30- 2.10	● 3.30- 4.40
x 0.01- 0.02	o 0.08- 0.12	○ 0.36- 0.70	⊙ 2.10- 2.90	◆ 4.40- 6.80
• 0.02- 0.06	o 0.12- 0.20	○ 0.70- 1.30	⊙ 2.90- 3.30	★ > 6.80

FIGURE B-3. Areal Distribution of Stream Water Alkalinity Values

ALBANY
Uranium
1319

1x2' Sheet
In Sediments
Values Above D.L.

Uranium concentration - p.p.m.

FIGURE B-4. Areal Distribution of Uranium Concentrations in Stream Sediment

ALBANY *1x2" Sheet*
Thorium *In Sediments*
1277 *Values Above D.L.*

Thorium concentration - p.p.m.

• < 2.0	• 4.0- 5.0	○ 7.0- 9.0	⊙ 15.0- 24.0	● 47.0- 75.0
• 2.0- 3.0	• 5.0- 6.0	○ 9.0- 12.0	⊙ 24.0- 36.0	◆ 75.0- 103.0
• 3.0- 4.0	○ 6.0- 7.0	○ 12.0- 15.0	⊙ 36.0- 47.0	★ > 103.0

FIGURE B-5. Areal Distribution of Thorium Concentrations in Stream Sediment

ALBANY
Hafnium
1175 Values Above D.L.

1x2 Sheet

In Sediments

Values Above D.L.

Hafnium concentration - p.p.m.

+ < 1.0	o 3.0- 6.0	○ 12.0- 16.0	⊙ 28.0- 40.0	● 67.0- 101.0
• 1.0- 1.0	o 6.0- 9.0	○ 16.0- 21.0	⊙ 40.0- 53.0	◆ 101.0- 204.0
• 1.0- 3.0	o 9.0- 12.0	○ 21.0- 28.0	⊙ 53.0- 67.0	★ > 204.0

FIGURE B-6. Areal Distribution of Hafnium Concentrations in Stream Sediment

ALBANY *1x2 Sheet*
Aluminum **In Sediments**
901 **Values Above D.L.**

Aluminum concentration - p.p.m.

- < 6600.0 • 31200.0- 35200.0 ○ 44700.0- 49500.0 ⊙ 62200.0- 69700.0 ● 83900.0- 93600.0
- 6600.0- 20000.0 ○ 35200.0- 40000.0 ⊙ 49500.0- 55100.0 ⊙ 69700.0- 79100.0 ● 93600.0- 103100.0
- 20000.0- 31200.0 ○ 40000.0- 44700.0 ⊙ 55100.0- 62200.0 ● 79100.0- 83900.0 ★ > 103100.0

FIGURE B-7. Areal Distribution of Aluminum Concentrations in Stream Sediment

ALBANY
Cerium
1278

1x2' Sheet
In Sediments
Values Above D.L.

Cerium concentration - p.p.m.

+ < 19.0	o 41.0- 51.0	○ 72.0- 86.0	⊙ 130.0- 179.0	● 310.0- 489.0
• 19.0- 30.0	o 51.0- 59.0	○ 86.0- 104.0	⊙ 179.0- 240.0	◆ 489.0- 632.0
• 30.0- 41.0	o 59.0- 72.0	○ 104.0- 130.0	● 240.0- 310.0	★ > 632.0

FIGURE B-8. Areal Distribution of Cerium Concentrations in Stream Sediment

ALBANY
Iron
1285 Values Above C.L.
1x2" Sheet
In Sediments

Iron concentration - p.p.m.

• < 8100.0	◊ 16400.0- 18900.0	○ 26600.0- 31000.0	⊙ 41000.0- 48400.0	● 63100.0- 73500.0
• 8100.0- 11800.0	◊ 18900.0- 22100.0	○ 31000.0- 36200.0	⊙ 48400.0- 54900.0	● 73500.0- 109400.0
• 11800.0- 16400.0	◊ 22100.0- 26600.0	○ 36200.0- 41000.0	⊙ 54900.0- 63100.0	★ > 109400.0

FIGURE E-9. Areal Distribution of Iron Concentrations in Stream Sediment

ALBANY 1x2" Sheet
Manganese In Sediments
1096 Values Above D.L.

Manganese concentration - p.p.m.

• < 110.0	○ 400.0- 490.0	○ 810.0- 980.0	⊙ 1480.0- 1900.0	● 2920.0- 3830.0
• 110.0- 250.0	○ 490.0- 620.0	○ 980.0- 1230.0	⊙ 1900.0- 2300.0	◆ 3830.0- 4940.0
• 250.0- 400.0	○ 620.0- 810.0	○ 1230.0- 1480.0	⊙ 2300.0- 2920.0	★ > 4940.0

FIGURE B-10. Areal Distribution of Manganese Concentrations in Stream Sediment

ALBANY *1x2" Sheet*
Scandium In Sediments
1290 Values Above D.L.

Scandium concentration - p.p.m.				
• < 0.3	◦ 2.3- 3.8	○ 7.3- 9.0	⊙ 13.1- 16.3	● 22.5- 27.8
• 0.3- 1.3	◦ 3.8- 5.4	○ 9.0- 11.1	⊙ 16.3- 19.4	◆ 27.8- 36.6
• 1.3- 2.3	◦ 5.4- 7.3	○ 11.1- 13.1	● 19.4- 22.5	★ > 36.6

FIGURE B-11. Areal Distribution of Scandium Concentrations in Stream Sediment

ALBANY *1x2 Sheet*
Sodium **In Sediments**
1208 **Values Above D.L.**

Sodium concentration - p.p.m.

- < 1700.0 ◊ 5700.0- 7000.0 ⊙ 10300.0- 12100.0 ⊙ 16900.0- 19500.0 ● 24300.0- 27200.0
- 1700.0- 4500.0 ◊ 7000.0- 8600.0 ⊙ 12100.0- 14300.0 ⊙ 19500.0- 22100.0 ◆ 27200.0- 32200.0
- 4500.0- 5700.0 ◊ 8600.0- 10300.0 ⊙ 14300.0- 16900.0 ⊙ 22100.0- 24300.0 ★ > 32200.0

FIGURE B-12. Areal Distribution of Sodium Concentrations in Stream Sediment

ALBANY 1x2' Sheet
Titanium In Sediments
886 Values Above D.L.

Titanium concentration - p.p.m.

• < 600.0	○ 3200.0- 3800.0	○ 5400.0- 6300.0	⊙ 9000.0- 11100.0	● 16800.0- 21600.0
• 600.0- 2000.0	○ 3800.0- 4600.0	○ 6300.0- 7500.0	⊙ 11100.0- 13600.0	◆ 21600.0- 30800.0
• 2000.0- 3200.0	○ 4600.0- 5400.0	⊙ 7500.0- 9000.0	⊙ 13600.0- 16800.0	★ > 30800.0

FIGURE B-13. Areal Distribution of Titanium Concentrations in Stream Sediment

ALBANY *1x2' Sheet*
Vanadium **In Sediments**
1775 **Values Above D.L.**

Vanadium concentration - p.p.m.				
• < 10.0	◦ 20.0- 30.0	○ 50.0- 60.0	⊙ 80.0- 100.0	● 140.0- 170.0
• 10.0- 10.0	◦ 30.0- 40.0	○ 50.0- 70.0	⊙ 100.0- 120.0	◆ 170.0- 190.0
• 10.0- 20.0	◦ 40.0- 50.0	○ 70.0- 80.0	● 120.0- 140.0	★ > 190.0

FIGURE B-14. Areal Distribution of Vanadium Concentrations in Stream Sediment

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS--

ALBANY

SHEET

1

SRL I.D. *****	DGE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
CTHA002S1	09-42.0202- 72.9496-4-50-000	6.2	300	0.16	5.9	14	35	83300	132	13600	1330	33700	8.4	5400	40
CTHA003S1	09-42.0358- 72.8950-4-50-000	4.9	30	0.00	18.3	112	32	65700	658	65200	2870	14800	19.9	7400	100
CTHA004S1	09-42.0263- 72.8376-4-50-000	6.6	32	0.10	M	M	M	M	M	M	M	M	M	M	M
CTHA005S1	09-42.0209- 72.7341-4-50-000	7.4	239	0.48	4.9	14	16	M	108	12600	M	12700	6.5		30
CTHA007S1	09-42.0241- 72.6783-4-50-000	7.6	238	0.90	4.1	14	16	M	76	22100	M	13400	8.9	M	30
CTHA008S1	09-42.0172- 72.6543-4-50-000	7.1	120	0.40	3.7	11	18	41300	95	26000	900	12900	6.4	5700	60
CTHA010S1	09-42.0160- 72.6049-4-50-000	8.0	300	1.30	5.6	19	47	M	128	42400	M	M	13.7	M	50
CTHA020S1	09-42.0002- 72.8972-4-50-000	6.9	72	0.10	6.4	M	M	55900	M	M	1410	14000	M	M	70
CTHA081S1	09-42.0186- 72.5476-4-50-000	6.6	180	0.90	4.7	20	18	53700	135	30200	950	17600	13.9	6000	60
CTHA082S1	09-42.0027- 72.5508-4-50-000	6.4	1000	0.44	7.4	40	36	46200	264	46200	1320	14500	21.7	M	80
CTL1153S1	09-42.0198- 73.3401-4-50-000	7.7	360	3.20	3.3	M	M	39400	M	M	560	7200	M	5000	40
CTL1154S1	09-42.0280- 73.2488-4-50-000	8.0	210	2.20	5.1	19	47	67000	195	42400	1360	12100	2.1	10200	80
CTL1155S1	09-42.0151- 73.4299-4-50-000	M	M	M	2.6	9	12	59000	87	60700	2360	7000	10.9	14800	70
CTL1156S1	09-42.0332- 73.3986-4-50-000	7.6	470	5.60	1.6	9	22	M	99	39000	3880	6800	8.1	8100	50
CTL1157S1	09-42.0329- 73.2947-4-50-000	7.3	300	3.70	4.5	13	24	45900	120	21400	390	6500	6.9	5900	40
CTL1161S1	09-42.0319- 73.2059-4-50-000	7.5	70	0.70	6.6	10	2	M	83	26600	M	M	10.1	M	M
CTL1162S1	09-42.0340- 73.1321-4-50-000	7.1	40	0.26	4.9	M	M	49300	M	M	1080	15900	M	6200	60
CTL1165S1	09-42.0133- 73.0959-4-50-000	7.3	40	0.26	2.5	7	20	M	63	37700	M	18400	16.1	M	110
CTL1166S1	09-42.0325- 73.0594-4-50-000	6.7	35	0.12	4.6	16	53	M	173	43100	2440	24200	16.5	9600	70
CTT0001S1	09-42.0061- 72.4982-4-50-000	7.0	600	0.70	2.4	7	11	32500		26500	710	13500	14.3	4600	40
CTT0002S1	09-42.0185- 72.4475-4-50-000	7.3	95	0.80	5.1	17	15	63500	99	19100	1120	29400	8.7	7600	70
CTT0011S1	09-42.0282- 72.3912-4-50-000	7.0	70	0.30	4.7	17		68700	100	64500	1670	20000	44.4	6400	160
CTT0012S1	09-42.0175- 72.3464-4-50-000	6.8	50	0.30	3.4	14	14	52700	102	50400	860	16300	25.8	5100	80
CTT0013S1	09-42.0207- 72.2798-4-50-000	6.8	40	0.18	8.9	65		64600	402	39100	1280	9600	12.4	8200	120
CTT0015S1	09-42.0127- 72.1455-4-50-000	6.3	140	0.16	12.4	96	32	M	485	62600	2870	7700	27.8	3500	110
CTT0018S1	09-42.0157- 72.1857-4-50-000	6.6	50	0.30	4.1	32	19	M	197	27200	590	6200	11.3	4300	70
CTT0019S1	09-42.0209- 72.2497-4-50-000	6.8	30	0.16	13.1	93		118100	489	35600	2160	12100	16.7	21700	180
MABE001S1	25-42.7325- 73.0676-4-50-000	6.1	50	0.20	1.7	7	27	21100	58	16600	550	12100	6.5	5500	40
MABE002S1	25-42.7085- 73.0714-4-50-000	6.5	180	0.85	2.2	9	18	38700	83	21300	440	5400	5.6	4600	30
MABE003S1	25-42.7093- 73.0358-4-50-000	6.3	45	0.14	1.9	6	12	34700	45	21100	700	7000	7.6	6500	30
MABE004S1	25-42.6697- 73.0095-4-50-000	6.5	190	0.14	2.7	9	44	29500	102	33700	820	6600	9.0	6700	40
MABE005S1	25-42.6616- 72.9713-4-50-000	5.7	35	0.12	4.6	5	7	44100	46	24400	910	12300	10.2	5900	70
MABE006S1	25-42.6876- 73.0010-4-50-000	6.3	20	0.08	1.7	6		51000	88	38600	1300	8600	11.4	5500	60
MABE007S1	25-42.6902- 73.0479-4-50-000	6.5	20	0.30	3.6	12	41	52800	69	47900	1120	9700	13.8	5300	50
MABE008S1	25-42.6608- 73.0411-4-50-000	6.5	40	0.12	1.6	5	12	33600	40	16800	390	6100	5.3	4300	30
MABE009S1	25-42.6714- 73.0871-4-50-000	8.0	260	3.60	2.0	9	21	41800	88	16300	410	6300	4.6	4700	40
MABE010S1	25-42.7135- 73.1086-4-50-000	7.3	120	0.85	1.7	3	17	39200	48	11800	390	9700	3.5	3200	30
MABE011S1	25-42.7408- 73.1178-4-50-000	6.2	50	0.16	2.0	3	23	20300	26	12700	280	6700	2.6	2700	10
MABE012S1	25-42.6727- 73.1346-4-50-000	6.8	225	2.20	1.7	4	7	33900	42	13800	560	4600	3.5	5400	40
MABE013S1	25-42.6863- 73.1613-4-50-000	7.1	285	3.90	1.5	4	4	20800	33	18500	780	2800	3.3	M	20
MABE014S1	25-42.7370- 73.1906-4-50-000	7.8	240	3.10	3.5	3	10	18500	30	7700	220	3100	1.4	1900	20
MABE015S1	25-42.5091- 73.2877-4-50-000	6.3	35	0.22	3.1	13		54900	139	31900	890	5900	8.3	M	50
MABE016S1	25-42.5144- 73.2494-4-50-000	7.3	190	2.20	1.6	2	7	45900	53	20700	950	4300	4.6	3800	40
MABE017S1	25-42.5471- 73.2502-4-50-000	6.9	30	1.50	1.4	4		40400	96	27500	570	6900	7.1	3800	40
MABE018S1	25-42.5790- 73.2512-4-50-000	7.0	60	0.55	1.8	13	5	39000	150	36400	1180	7300	2.7	M	40
MABE019S1	25-42.5421- 73.3177-4-50-000	6.8	100	0.85	2.2	11	6	59200	123	21900	1050	7900	6.1	4200	60
MABE020S1	25-42.5707- 73.3037-4-50-000	6.8	50	0.30	5.0	61		M	781	60200	2030	10900	13.7	6500	80
MABE021S1	25-42.5944- 73.2932-4-50-000	6.6	30	0.10	4.3	51		88900	523	56600	1400	8400	1.4	5700	70
MABE022S1	25-42.6240- 73.2807-4-50-000	6.6	50	0.28	4.1	24		88700	252	38500	1070	9200	10.0	5100	60
MABE023S1	25-42.6566- 73.2618-4-50-000	7.2	180	1.70	3.6	24	2	85300	292	35000	1260	8100	9.6	3600	50
MABE024S1	25-42.6804- 73.2549-4-50-000	6.5	120	1.10	6.0	52		107300	630	48000	1500	13100	12.1	6700	80
MABE025S1	25-42.7014- 73.2558-4-50-000	6.5	90	0.70	2.2	14		M	154	27700	980	4000	6.4	M	30
MABE026S1	25-42.7079- 73.2237-4-50-000	6.9	160	0.90	2.6	22		M	244	68100	120	6700	15.9		M

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

2

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
MABE027S1	25-42.7382-73.2426-4-50-000	6.6	70	0.54	1.6	10	1	M	139	42100	M	5900	8.8	5300	30
MABE028S1	25-42.6702-73.2121-4-50-000	8.4	280	4.20	2.5	10	16	M	111	29500	M	M	8.1	2500	M
MABE029S1	25-42.6442-73.2363-4-50-000	7.7	150	1.40	2.1	8	6	82100	23	33100	1600	14000	2.4	9400	80
MABE030S1	25-42.6274-73.2271-4-50-000	8.1	215	1.90	2.8	8	.	61800	86	36500	1310	12000	9.1	6800	70
MABE031S1	25-42.6033-73.2454-4-50-000	7.2	150	1.90	2.0	7	.	49000	75	21000	680	11600	5.4	6300	30
MABE032S1	25-42.5857-73.2282-4-50-000	7.6	195	2.50	1.3	.	.	41700	35	10200	550	9100	2.6	4700	40
MABE033S1	25-42.5500-73.2124-4-50-000	7.1	95	1.00	1.8	.	5	32400	.	21000	760	6800	5.5	5600	40
MABE034S1	25-42.5103-73.2117-4-50-000	7.7	430	4.20	1.5	7	7	M	48	23800	1070	7300	3.7	9300	20
MABE035S1	25-42.4883-73.3125-4-50-000	6.1	30	0.16	2.9	5	.	M	80	28600	M	7500	7.4	M	60
MABE036S1	25-42.4867-73.2905-4-50-000	6.6	120	1.35	3.2	16	9	M	249	47700	M	7800	11.8	M	M
MABE037S1	25-42.4697-73.2573-4-50-000	7.7	230	1.05	1.5	6	5	M	41	16200	650	5400	3.5	4600	30
MABE038S1	25-42.4610-73.2244-4-50-000	6.9	290	2.80	1.7	7	7	35500	62	26700	730	5300	6.6	5800	40
MABE039S1	25-42.5243-73.1926-4-50-000	7.1	115	1.40	2.2	7	18	46500	70	24900	810	8200	6.4	9300	50
MABE040S1	25-42.5649-73.1740-4-50-000	6.7	85	0.70	1.5	2	.	26000	37	13700	280	6500	3.3	M	20
MABE041S1	25-42.5956-73.1464-4-50-000	6.6	40	0.20	1.9	8	9	43400	83	30600	520	5300	6.9	8200	40
MABE042S1	25-42.6280-73.1463-4-50-000	7.4	175	2.10	3.3	11	12	M	107	32900	750	7400	9.4	8800	70
MABE043S1	25-42.6490-73.0963-4-50-000	6.9	335	3.80	1.1	5	8	8400	33	8000	.	2200	1.7	M	10
MABE044S1	25-42.6134-73.1017-4-50-000	8.0	140	1.40	3.4	22	36	M	163	27200	480	6600	7.1	M	30
MABE045S1	25-42.6164-73.0641-4-50-000	6.4	25	0.08	2.4	4	22	M	57	17600	M	14300	5.0	M	20
MABE046S1	25-42.6228-73.0368-4-50-000	6.6	30	0.16	3.2	4	41	M	90	19100	M	21200	6.2	M	40
MABE047S1	25-42.6198-73.0103-4-50-000	6.3	30	0.10	3.1	5	27	45400	90	24800	730	11600	9.4	M	40
MABE048S1	25-42.6280-72.9764-4-50-000	6.5	35	0.12	2.4	7	13	51300	65	37400	830	19100	13.9	8600	90
MABE049S1	25-42.5861-73.0042-4-50-000	6.3	25	0.08	2.8	7	13	M	81	34300	M	M	14.8	5000	30
MABE050S1	25-42.5519-73.0050-4-50-000	6.4	25	0.14	2.6	8	35	M	91	54400	M	M	20.1	M	M
MABE051S1	25-42.5877-73.0433-4-50-000	6.0	20	0.04	1.6	.	46	33900	51	12500	340	10700	5.6	3500	M
MABE052S1	25-42.5609-73.0502-4-50-000	6.3	40	0.18	3.3	8	18	50300	58	33000	1220	12300	8.9	M	40
MABE053S1	25-42.5828-73.0851-4-50-000	6.8	110	1.00	6.4	10	20	46800	89	19100	810	7800	5.2	5400	40
MABE054S1	25-42.5872-73.1251-4-50-000	7.3	270	3.30	2.9	14	28	37700	128	32500	690	5500	7.3	8400	40
MABE055S1	25-42.5570-73.1246-4-50-000	7.0	240	2.90	2.4	12	.	46800	59	29600	.	5600	6.7	M	50
MABE056S1	25-42.4867-73.1441-4-50-000	6.6	110	0.85	2.6	7	15	53400	62	26300	1030	8300	7.3	6100	50
MABE057S1	25-42.4961-73.1118-4-50-000	6.7	40	0.25	3.1	10	24	M	79	14500	M	4500	4.8	M	M
MABE058S1	25-42.5004-73.0835-4-50-000	6.5	35	0.10	3.2	10	24	46000	143	34000	1510	9500	10.1	7100	60
MABE059S1	25-42.4880-73.0466-4-50-000	6.4	35	0.08	2.4	6	1	M	81	32100	M	14500	10.5	M	M
MABE060S1	25-42.5109-73.0273-4-50-000	6.2	30	0.08	2.4	3	21	40700	83	16400	490	10700	5.8	3900	30
MABE061S1	25-42.5261-73.0610-4-50-000	6.7	30	0.08	2.7	12	21	62700	110	24000	870	14000	8.8	6800	60
MABE062S1	25-42.5510-73.0442-4-50-000	6.5	40	0.18	4.6	13	24	80300	114	24000	1460	19900	9.7	7300	70
MABE063S1	25-42.5386-73.0161-4-50-000	6.7	30	0.12	4.6	16	48	67300	117	30500	840	16000	12.2	7800	50
MABE064S1	25-42.5035-72.9920-4-50-000	6.7	30	0.08	3.4	9	27	45000	105	24900	700	12500	10.1	M	40
MABE065S1	25-42.4715-72.9986-4-50-000	6.7	40	0.20	4.2	9	53	42700	113	26100	880	10700	10.6	8800	40
MABE066S1	25-42.4616-73.0279-4-50-000	6.8	30	0.12	2.1	5	17	52800	54	17400	2230	14800	7.0	7300	40
MABE067S1	25-42.4336-73.0239-4-50-000	6.7	40	0.08	2.7	12	23	42400	86	26500	630	10200	9.6	6700	40
MABE068S1	25-42.4354-73.1190-4-50-000	6.9	85	0.65	2.2	7	22	37900	53	27300	530	8000	1.8	4500	40
MABE069S1	25-42.4611-73.1301-4-50-000	7.4	110	0.80	2.2	6	19	27700	81	18000	610	5500	5.5	6600	30
MABE070S1	25-42.4630-73.1718-4-50-000	7.4	115	0.80	2.1	7	15	33600	77	23500	690	5700	5.3	5800	30
MABE071S1	25-42.4580-73.3455-4-50-000	6.6	70	0.50	3.4	M	M	97800	M	M	1980	11000	M	7900	110
MABE072S1	25-42.4512-73.3140-4-50-000	6.9	120	1.00	1.4	7	8	M	74	23500	M	4400	4.1	M	M
MABE073S1	25-42.4233-73.3581-4-50-000	6.7	60	0.40	4.6	.	.	M	.	.	M	11000	1.1	M	60
MABE074S1	25-42.4183-73.3120-4-50-000	7.5	280	2.90	1.4	5	5	32600	72	19200	600	4000	4.3	3200	30
MABE075S1	25-42.4245-73.2879-4-50-000	7.2	220	2.30	1.3	4	9	31400	67	11800	680	4500	2.5	M	20
MABE076S1	25-42.4076-73.2429-4-50-000	6.9	70	0.70	1.8	5	13	36500	50	15500	470	5000	4.2	4800	30
MABE077S1	25-42.4283-73.1770-4-50-000	7.0	120	1.05	1.5	3	11	15300	30	8100	340	1900	2.3	M	20
MABE078S1	25-42.3989-73.1261-4-50-000	6.9	75	0.55	3.3	10	53	37400	142	34300	640	7400	9.6	6900	40
MABE079S1	25-42.3955-73.0918-4-50-000	6.8	70	0.50	4.2	11	43	59600	104	24700	1000	15100	9.0	10300	60

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

3

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
MABE080S1	25-42.4205-73.0720-4-50-000	7.0	40	0.24	2.6	5	18	39500	38	27100	850	12700	10.4	6900	60
MABE081S1	25-42.3987-73.0526-4-50-000	6.9	40	0.22	2.1	4	26	44900	85	25500	610	12800	10.5	6400	50
MABE082S1	25-42.3531-73.0910-4-50-000	6.7	75	0.42	3.0	7	49	46500	86	32200	810	15400	9.0	7400	30
MABE083S1	25-42.3803-73.0802-4-50-000	6.5	65	0.46	3.3	5	27	41200	104	27500	1050	11200	9.2	6200	50
MABE084S1	25-42.4086-73.1415-4-50-000	6.7	60	0.34	2.9	5	17	41100	53	19900	670	9600	8.2	5200	50
MABE085S1	25-42.3425-73.1361-4-50-000	6.8	25	0.10	3.6	4	60	73400	182	25800	1030	19800	15.3	10100	50
MABE086S1	25-42.3794-73.1408-4-50-000	6.5	35	0.10	3.6	6	53	61500	118	25500	930	16700	2.5	6800	40
MABE087S1	25-42.3789-73.1980-4-50-000	6.4	35	0.08	2.8	5	26	36500	62	10300	220	4800	2.2	3100	20
MABE088S1	25-42.3493-73.1741-4-50-000	4.0	30	0.00	2.0	2	31	45300	59	9000	200	10800	6.0	2800	20
MABE089S1	25-42.3463-73.1887-4-50-000	5.6	30	0.06	2.8	4	40	48400	94	20900	470	13500	9.1	6100	30
MABE090S1	25-42.3183-73.1051-4-50-000	6.6	45	0.22	2.4	6	25	52000	101	28500	960	13200	10.4	5800	50
MABE091S1	25-42.2972-73.1882-4-50-000	7.6	315	1.90	1.8	6	13	M	82	23900	560	7900	2.5	5500	30
MABE092S1	25-42.3062-73.2304-4-50-000	7.7	305	3.70	1.8	8	13	39400	59	15400	1030	6000	3.4	7100	40
MABE093S1	25-42.3050-73.2687-4-50-000	7.6	300	4.40	0.9	4	5	11300	30	11500	380	1700	2.3	3700	20
MABE094S1	25-42.2740-73.2725-4-50-000	7.1	80	0.80	3.4	11	1	48000	151	37800	710	10800	14.9	6200	40
MABE095S1	25-42.2562-73.1899-4-50-000	6.8	50	0.36	3.3	7	35	47300	114	34800	870	12100	12.8	7600	40
MABE096S1	25-42.2866-73.2166-4-50-000	7.2	50	0.36	1.9	11	19	53600	111	35400	860	10100	14.1	5900	60
MABE097S1	25-42.2724-73.1777-4-50-000	6.9	60	0.48	2.1	10	24	43200	140	35900	640	11100	12.9	M	40
MABE098S1	25-42.2613-73.1348-4-50-000	6.8	35	0.18	4.2	.	76	61800	73	29900	1190	19100	13.1	6700	50
MABE099S1	25-42.2829-73.1177-4-50-000	4.8	30	0.04	2.7	4	28	44000	93	22200	540	14200	9.3	4900	30
MABE100S1	25-42.3118-73.0640-4-50-000	6.7	80	0.24	3.3	4	38	71900	91	24400	1020	22600	12.5	8200	50
MABE101S1	25-42.3021-73.0402-4-50-000	6.6	80	0.54	4.0	3	.	51700	87	35800	1310	19000	16.9	6700	60
MABE102S1	25-42.2861-73.0716-4-50-000	6.4	70	0.40	1.7	.	31	58700	134	33500	590	18900	2.8	7200	40
MABE103S1	25-42.2643-73.0517-4-50-000	6.7	80	0.30	2.1	6	19	71900	110	26900	610	22900	1.2	8600	60
MABE104S1	25-42.2642-73.0169-4-50-000	6.9	115	0.20	3.5	6	.	53900	120	36800	970	18300	14.1	6800	40
MABE105S1	25-42.2213-73.0403-4-50-000	6.6	110	0.16	2.4	5	22	69600	84	20200	560	22700	10.0	8300	60
MABE106S1	25-42.2602-73.1047-4-50-000	6.8	80	0.60	4.7	7	69	61300	116	27400	2110	16900	9.7	M	60
MABE107S1	25-42.2168-73.1021-4-50-000	6.5	110	0.44	2.5	3	28	53000	96	33300	1470	20200	12.9	6700	50
MABE108S1	25-42.1960-73.0955-4-50-000	6.8	120	0.64	1.4	4	11	M	44	20900	560	5100	4.6	M	M
MABE109S1	25-42.1855-73.0541-4-50-000	6.7	80	0.28	2.8	6	1	M	89	25300	M	22700	11.4	M	50
MABE110S1	25-42.1579-73.0690-4-50-000	6.8	60	0.16	2.1	4	29	M	113	49200	M	18200	0.4	M	10
MABE111S1	25-42.2134-73.1257-4-50-000	6.5	35	0.14	2.2	4	27	M	74	27200	1090	7800	8.1	7100	40
MABE112S1	25-42.1944-73.1257-4-50-000	6.4	50	0.24	1.4	3	17	20200	31	15600	550	10800	3.9	4800	40
MABE113S1	25-42.2337-73.4331-4-50-000	6.7	110	1.35	3.1	8	.	45300	99	28800	570	10700	7.8	7300	40
MABE114S1	25-42.2628-73.4213-4-50-000	6.9	65	0.75	2.4	6	8	36800	77	24700	950	6800	6.2	6200	40
MABE115S1	25-42.2810-73.4246-4-50-000	6.8	40	0.30	4.2	12	9	M	104	44600	M	12400	12.8	M	80
MABE116S1	25-42.3087-73.4080-4-50-000	6.6	55	0.42	4.9	12	17	81700	117	48900	1930	14400	11.7	10000	100
MABE117S1	25-42.3423-73.3967-4-50-000	7.1	185	2.20	5.9	13	12	M	198	114500	M	6500	12.1	M	M
MABE118S1	25-42.3622-73.3790-4-50-000	7.3	130	1.50	3.2	11	15	M	132	32900	M	9700	7.5	M	10
MABE119S1	25-42.3496-73.3629-4-50-000	8.0	260	4.20	2.4	10	.	M	84	33000	1690	5800	5.0	M	20
MABE120S1	25-42.3753-73.3565-4-50-000	7.7	250	3.20	2.1	10	8	44500	94	38100	1550	3000	7.5	6600	60
MABE121S1	25-42.3968-73.3779-4-50-000	7.1	90	1.40	3.6	10	.	M	180	39800	1090	10200	1.3	6400	40
MABE122S1	25-42.3977-73.3616-4-50-000	7.0	430	5.60	2.7	12	8	61300	99	33700	1020	9200	9.0	M	60
MABE123S1	25-42.4008-73.3261-4-50-000	8.0	30	4.20	1.6	5	17	59400	113	23700	1110	6500	5.0	5700	50
MABE124S1	25-42.3802-73.3190-4-50-000	7.6	310	1.30	2.2	7	1	51200	129	47200	960	5100	11.2	8500	50
MABE125S1	25-42.3971-73.2674-4-50-000	7.5	190	2.30	1.8	9	10	47700	128	30800	1270	5400	6.6	10100	50
MABE126S1	25-42.3648-73.2621-4-50-000	8.4	430	4.30	2.5	13	19	38800	150	33800	1040	5300	7.1	8600	40
MABE127S1	25-42.3503-73.2998-4-50-000	8.0	210	2.80	2.2	9	14	M	101	33400	1000	5400	7.2	M	40
MABE128S1	25-42.3026-73.3351-4-50-000	8.0	250	2.40	2.1	10	8	M	100	39400	M	7200	8.3	.	80
MABE129S1	25-42.3186-73.3148-4-50-000	9.3	210	2.00	7.6	18	19	M	142	26400	M	6500	5.5	M	10
MABE130S1	25-42.2751-73.3205-4-50-000	7.6	230	2.30	2.7	6	12	36300	94	39200	1100	5200	8.1	6100	40
MABE131S1	25-42.2848-73.3605-4-50-000	8.1	260	3.10	1.8	7	12	60000	59	38500	1730	8700	7.8	9800	60
MABE132S1	25-42.2690-73.3803-4-50-000	7.1	260	1.25	4.0	6	.	54000	101	36200	1130	7300	8.0	10400	60

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

4

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
MABE133S1	25-42.2033- 73.3463-4-50-000	7.5	220	1.90	4.0	16	36	43500	149	23500	1310	5600	1.6	7900	40
MABE134S1	25-42.1697- 73.2556-4-50-000	7.1	130	1.40	3.3	5	.	43500	64	21500	690	13200	9.9	5100	30
MABE135S1	25-42.1710- 73.2169-4-50-000	7.2	200	2.70	2.5	5	23	M	82	30000	M	17000	12.1	M	M
MABE136S1	25-42.1546- 73.1930-4-50-000	6.2	50	0.28	2.2	4	21	M	64	19800	M	11400	8.5	M	M
MABE137S1	25-42.1876- 73.1995-4-50-000	5.8	35	0.12	2.9	4	21	M	67	20300	M	9500	7.4	M	M
MABE138S1	25-42.2201- 73.1831-4-50-000	7.1	125	1.35	2.9	8	29	M	89	25300	M	11100	8.9	M	50
MABE139S1	25-42.2409- 73.2211-4-50-000	6.2	60	0.44	2.7	11	.	43600	99	31900	410	8600	10.3	6500	40
MABE140S1	25-42.1956- 73.2288-4-50-000	6.6	50	0.36	3.7	11	48	81400	92	37700	1240	27700	16.0	12000	70
MABE141S1	25-42.1937- 73.2594-4-50-000	6.4	40	0.44	3.4	5	15	M	86	32300	M	M	13.6	M	20
MABE142S1	25-42.2301- 73.2819-4-50-000	6.6	40	0.20	3.4	6	34	55800	93	35400	880	14800	4.4	8200	60
MABE143S1	25-42.2087- 73.3196-4-50-000	7.7	240	2.60	3.2	13	23	M	109	26800	M	4200	7.4	M	M
MABE144S1	25-42.2427- 73.3229-4-50-000	7.6	210	2.50	3.7	8	36	43000	110	22200	460	11200	9.4	7200	40
MABE145S1	25-42.2272- 73.3634-4-50-000	8.1	290	2.10	2.0	8	.	55300	87	30900	1240	9000	7.2	5300	60
MABE146S1	25-42.2180- 73.3975-4-50-000	7.5	170	1.70	2.8	9	14	M	114	34200	M	M	8.3	M	20
MABE147S1	25-42.1909- 73.3999-4-50-000	7.4	160	1.40	3.9	15	1	M	223	40200	M	18300	7.9	M	70
MABE148S1	25-42.1700- 73.3522-4-50-000	6.1	110	0.95	4.2	17	23	M	183	28500	M	5100	6.8	M	M
MABE149S1	25-42.0791- 73.0751-4-50-000	6.2	38	0.10	4.0	12	65	64900	138	43200	2270	25400	17.8	10600	90
MABE161S1	25-42.0604- 73.0658-4-50-000	7.0	30	0.10	4.9	17	70	65400	235	52000	2070	27000	23.0	15000	110
MABE162S1	25-42.1500- 73.1069-4-50-000	7.1	44	0.20	4.3	14	37	M	150	48200	2920	21500	19.7	13000	110
MABE163S1	25-42.1693- 73.1479-4-50-000	7.1	48	0.22	11.3	9	97	M	123	42300	M	M	18.1	5700	M
MABE164S1	25-42.1289- 73.1292-4-50-000	7.2	56	0.32	4.8	19	42	63000	135	32600	1340	20400	11.6	11000	90
MABE165S1	25-42.0891- 73.1114-4-50-000	7.2	61	0.40	4.9	17	47	45200	128	32500	1090	16200	13.1	8600	50
MABE166S1	25-42.0440- 73.1400-4-50-000	7.2	50	0.26	4.5	17	59	M	149	60400	2020	24000	26.3	11300	140
MABE167S1	25-42.0541- 73.1589-4-50-000	6.9	45	0.22	7.6	10	80	44700	99	43000	810	17400	18.7	8300	60
MABE168S1	25-42.0934- 73.1666-4-50-000	6.9	52	0.42	5.1	13	89	53300	135	30600	880	19400	5.1	9600	60
MABE169S1	25-42.1206- 73.1617-4-50-000	7.3	92	0.74	3.6	8	23	43000	89	27600	780	16500	11.4	7200	50
MABE170S1	25-42.1180- 73.2193-4-50-000	7.3	90	0.56	1.4	.	.	33400	.	.	280	11100	1.8	3500	30
MABE171S1	25-42.1539- 73.2591-4-50-000	7.8	170	1.04	3.5	11	39	43300	91	28100	510	15100	11.2	6400	40
MABE172S1	25-42.1308- 73.2641-4-50-000	7.7	170	1.64	12.8	29	218	M	219	32300	M	5300	11.8	M	10
MABE173S1	25-42.1003- 73.2554-4-50-000	7.8	170	1.60	3.4	7	38	23100	90	17000	520	6900	6.1	5600	30
MABE174S1	25-42.0845- 73.2887-4-50-000	8.0	270	1.93	5.6	23	68	33400	126	39400	630	7100	12.6	7100	30
MABE175S1	25-42.0475- 73.3295-4-50-000	7.7	205	1.44	7.0	10	48	41800	113	19100	580	10300	8.2	5600	40
MABE176S1	25-42.0544- 73.3632-4-50-000	7.5	490	5.60	2.1	12	25	M	143	30400	M	M	6.0	M	M
MABE177S1	25-42.0670- 73.2858-4-50-000	7.9	190	1.85	3.6	10	43	35300	91	20300	630	8700	8.1	5800	30
MABE178S1	25-42.0502- 73.2543-4-50-000	7.1	270	2.33	4.6	11	43	M	63	18400	670	10300	8.4	6700	40
MABE179S1	25-42.0618- 73.2226-4-50-000	7.2	60	0.48	5.1	6	54	53300	67	22500	1170	19800	11.1	11200	70
MABE180S1	25-42.1044- 73.3306-4-50-000	6.9	120	1.16	4.3	14	2	M	121	23600	M	7400	7.2	M	M
MABE181S1	25-42.1244- 73.3324-4-50-000	7.1	112	1.12	5.5	20	39	M	169	35500	950	5500	6.6	M	40
MABE182S1	25-42.1057- 73.3704-4-50-000	7.1	238	2.00	19.0	66	111	M	832	55700	1420	7100	10.2	21200	40
MABE183S1	25-42.0815- 73.4150-4-50-000	7.2	110	0.76	1.8	8	12	51800	90	44700	1150	7900	10.5	6000	50
MABE184S1	25-42.0662- 73.4130-4-50-000	7.0	285	3.04	1.9	8	19	61400	111	53200	2020	9100	9.1	18600	60
MABE185S1	25-42.1382- 73.4114-4-50-000	6.8	1050	6.80	1.9	5	17	M	92	24300	M	5700	5.3	M	10
MABE186S1	25-42.1401- 73.3897-4-50-000	7.1	250	1.96	3.2	20	33	M	349	40500	M	9500	9.2	M	30
MABE187S1	25-42.1655- 73.4129-4-50-000	7.3	335	3.50	2.7	13	21	52500	179	24200	990	11500	5.4	9800	50
MABE188S1	25-42.1543- 73.4472-4-50-000	7.8	210	2.05	3.0	10	14	M	132	42700	1630	8100	8.2	M	60
MABE189S1	25-42.1180- 73.4583-4-50-000	6.3	20	0.10	3.4	14	26	51400	160	76500	1970	7100	13.4	22500	60
MABE190S1	25-42.0979- 73.4611-4-50-000	6.8	75	0.26	3.1	6	22	59500	98	38200	1820	12300	7.6	30800	70
MABE191S1	25-42.0785- 73.4651-4-50-000	6.7	52	0.30	3.3	7	12	42000	56	38600	850	9500	8.4	16700	60
MABE192S1	25-42.1062- 73.4857-4-50-000	6.9	79	0.56	2.9	10	.	M	105	74500	1080	8500	13.6	12500	50
MABE193S1	25-42.2036- 73.4393-4-50-000	M	M	M	2.7	13	12	M	122	31000	M	8600	7.5	1600	M
MAFR001S1	25-42.5143- 72.7189-4-50-000	8.4	130	0.70	3.3	10	13	61700	106	47900	800	12500	19.6	8200	90
MAFR002S1	25-42.4881- 72.7426-4-50-000	7.5	67	0.50	4.3	7	7	82700	54	35300	1490	17800	13.6	12300	120
MAFR003S1	25-42.4492- 72.7501-4-50-000	7.4	68	0.40	8.1	7	6	46600	50	33100	1160	10600	11.2	M	60

B-21

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

5

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
MAFR004S1	25-42.4171- 72.6410-4-50-000	6.8	112	0.60	1.5	3	6	M	62	31000	1980	13400	9.9	7300	80
MAFR005S1	25-42.4281- 72.6627-4-50-000	7.7	123	0.80	1.7	8	5	M	30	32600	1220	16600	11.9	7200	70
MAFR006S1	25-42.4356- 72.6881-4-50-000	7.5	54	0.36	1.6	2	3	25300	17	15600	900	6300	5.5	M	40
MAFR007S1	25-42.4787- 72.6945-4-50-000	7.8	75	0.80	2.8	2	10	49700	78	38400	1890	12700	14.9	9200	80
MAFR008S1	25-42.4715- 72.6716-4-50-000	7.6	77	0.70	2.5	6	6	86300	41	32900	1810	17900	12.6	10900	130
MAFR009S1	25-42.4688- 72.6413-4-50-000	7.6	193	1.20	1.8	4	17	40300	56	40000	1140	12900	19.1	10300	60
MAFR010S1	25-42.4888- 72.5979-4-50-000	7.2	176	0.80	2.6	2	18	48200	67	36300	1640	13900	13.5	11000	90
MAFR011S1	25-42.5481- 72.5808-4-50-000	7.3	87	0.80	6.0	6	51	44000	84	41000	1970	13500	17.3	M	90
MAFR012S1	25-42.5299- 72.6086-4-50-000	7.6	177	1.40	2.8	4	24	49300	86	42900	1150	14100	15.0	M	90
MAFR013S1	25-42.5576- 72.6220-4-50-000	7.1	111	0.70	2.9	10	23	43600	58	35100	1020	12100	5.1	8600	70
MAFR014S1	25-42.5399- 72.6466-4-50-000	7.0	97	0.70	1.8	6	15	51300	69	35900	1410	17400	12.1	12500	70
MAFR015S1	25-42.4383- 72.5909-4-50-000	7.1	145	0.30	3.4	10	33	M	91	39700	1470	17300	15.9	11800	90
MAFR016S1	25-42.4640- 72.5933-4-50-000	6.9	1310	0.50	8.7	22	97	M	171	97100	5420	15700	36.6	38000	190
MAFR017S1	25-42.5025- 72.6461-4-50-000	7.7	190	1.30	2.0	5	13	49300	45	30800	1320	13700	12.3	9900	70
MAFR018S1	25-42.5071- 72.6826-4-50-000	7.1	123	1.30	2.7	7	12	45800	41	34400	1120	12200	12.3	11800	70
MAFR019S1	25-42.5410- 72.6907-4-50-000	8.3	128	0.90	2.2	5	10	71700	62	53200	1760	18100	21.2	15800	110
MAFR020S1	25-42.5662- 72.7162-4-50-000	7.1	93	0.80	.	8	11	M	35	37400	1380	15800	18.4	M	100
MAFR021S1	25-42.5567- 72.7424-4-50-000	7.4	89	1.00	.	6	15	55800	44	50600	1770	13300	3.3	12800	80
MAFR022S1	25-42.4817- 72.7626-4-50-000	7.1	50	0.50	4.0	11	2	68100	102	54700	1880	14200	16.8	18500	100
MAFR023S1	25-42.5180- 72.7798-4-50-000	7.4	150	0.90	2.2	5	14	44900	57	53800	1210	12400	9.8	M	90
MAFR024S1	25-42.5305- 72.8072-4-50-000	7.0	117	1.20	1.9	9	8	58900	34	37500	1180	11700	6.6	18700	100
MAFR025S1	25-42.5577- 72.8062-4-50-000	7.5	115	1.10	2.1	8	13	M	62	62400	M	14900	20.0	5200	110
MAFR026S1	25-42.5933- 72.7892-4-50-000	8.0	132	1.50	2.1	6	9	44300	33	34700	880	11800	12.3	7900	80
MAFR027S1	25-42.6119- 72.7600-4-50-000	6.9	38	0.16	2.6	6	26	M	58	54300	1420	15500	22.1	14800	110
MAFR028S1	25-42.5893- 72.7663-4-50-000	7.1	83	0.90	2.4	7	.	79900	70	42200	.	24300	18.7	5400	140
MAFR029S1	25-42.6151- 72.8280-4-50-000	7.3	95	0.90	3.5	6	.	M	58	47400	1620	22900	16.5	17200	160
MAFR030S1	25-42.6273- 72.8774-4-50-000	7.2	66	0.70	1.7	6	14	50300	43	69200	1320	22300	27.2	3300	140
MAFR031S1	25-42.6079- 72.8857-4-50-000	7.3	70	0.80	1.6	8	12	58500	70	68000	1210	23600	29.0	9200	140
MAFR032S1	25-42.5777- 72.8516-4-50-000	7.3	52	0.50	1.9	9	7	45700	73	49200	880	13000	4.8	M	70
MAFR033S1	25-42.5659- 72.9075-4-50-000	7.4	53	0.60	1.0	2	7	M	42	46900	M	24000	19.7	M	150
MAFR034S1	25-42.6096- 72.9304-4-50-000	5.5	25	0.04	1.8	5	7	44800	65	53400	850	16900	13.8	8700	110
MAFR035S1	25-42.5773- 72.9487-4-50-000	6.7	39	0.18	2.1	6	16	49500	84	36300	670	18100	13.1	10300	60
MAFR036S1	25-42.5029- 72.8513-4-50-000	6.8	42	0.18	2.1	9	1	38400	161	49800	820	12500	23.6	11600	100
MAFR037S1	25-42.5371- 72.8553-4-50-000	6.5	35	0.16	2.5	10	7	44900	47	42200	970	10000	3.9	M	110
MAFR038S1	25-42.4858- 72.8099-4-50-000	6.9	38	0.30	2.2	9	.	M	63	28500	1740	6700	7.3	8100	50
MAFR039S1	25-42.4342- 72.5774-4-50-000	6.4	222	0.50	2.1	7	8	36400	65	19400	750	14600	9.1	7700	40
MAFR040S1	25-42.4598- 72.5642-4-50-000	7.5	101	0.90	3.4	12	16	M	57	33400	1710	15600	11.0	10800	70
MAFR041S1	25-42.4880- 72.5613-4-50-000	7.4	107	0.80	3.9	12	.	M	99	42100	1430	14100	15.1	11000	70
MAFR042S1	25-42.5048- 72.4476-4-50-000	5.1	22	0.02	4.0	3	47	62600	29	12600	920	26000	7.5	6000	30
MAFR043S1	25-42.5016- 72.4793-4-50-000	6.5	32	0.08	2.6	4	27	60400	59	20100	1080	22900	9.9	5600	30
MAFR044S1	25-42.4935- 72.5191-4-50-000	6.2	64	0.10	3.0	7	12	37600	60	19800	970	13900	9.5	7800	30
MAFR045S1	25-42.4490- 72.5347-4-50-000	7.4	106	0.60	4.6	11	14	58300	69	23800	1320	20400	10.2	11100	80
MAFR046S1	25-42.4512- 72.4942-4-50-000	7.2	75	0.26	2.5	6	10	66600	26	50700	2170	23500	21.3	10100	120
MAFR047S1	25-42.4385- 72.4828-4-50-000	6.8	37	0.06	4.6	2	46	55400	20	8600	590	20600	8.0	4400	20
MAFR048S1	25-42.4492- 72.4439-4-50-000	5.7	40	0.04	2.8	3	18	50700	22	9600	400	18800	6.4	M	20
MAFR049S1	25-42.4227- 72.4421-4-50-000	4.7	37	0.00	2.5	2	23	62700	19	7800	440	24800	6.7	4500	30
MAFR050S1	25-42.4294- 72.3996-4-50-000	6.1	28	0.06	3.6	9	21	M	42	19000	980	23300	10.6	7700	70
MAFR051S1	25-42.4575- 72.3878-4-50-000	6.4	30	0.06	2.9	3	12	55200	17	12800	750	21000	7.9	3800	40
MAFR052S1	25-42.4715- 72.3919-4-50-000	6.5	29	0.06	4.7	6	16	M	50	20600	M	22400	11.5	M	10
MAFR053S1	25-42.4638- 72.3746-4-50-000	7.0	92	0.18	3.1	5	12	47900	44	33100	1080	21100	24.2	5600	50
MAFR054S1	25-42.4899- 72.3420-4-50-000	6.9	33	0.14	2.2	4	.	M	24	21800	M	21500	9.7	M	70
MAFR055S1	25-42.5238- 72.3437-4-50-000	6.9	30	0.08	2.6	7	7	46300	41	20000	1170	15800	10.4	4700	40
MAFR056S1	25-42.5457- 72.3134-4-50-000	6.4	35	0.12	3.7	16	14	M	97	32700	M	2400	18.1	3300	M

B-22

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

6

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
MAFR057S1	25-42.5107-72.2591-4-50-000	6.2	70	0.08	4.6	14	17	54800	68	32300	910	19300	20.4	6100	80
MAFR058S1	25-42.5236-72.2880-4-50-000	5.7	26	0.06	9.3	39	33	M	219	50300	M	M	25.7	M	M
MAFR059S1	25-42.5548-72.2952-4-50-000	6.8	127	0.28	5.5	22	18	57900	150	24700	1160	19100	12.2	7500	60
MAFR060S1	25-42.5660-72.3295-4-50-000	7.0	32	0.14	5.0	20	2	50200	100	44500	2770	16400	24.3	8100	50
MAFR061S1	25-42.6015-72.3336-4-50-000	6.8	23	0.10	2.2	9	3	74400	58	27000	1300	29600	11.2	6300	80
MAFR062S1	25-42.6303-72.3358-4-50-000	6.4	32	0.12	2.7	11	2	67200	65	29700	2120	24000	21.3	5500	90
MAFR063S1	25-42.6328-72.3677-4-50-000	5.1	18	0.02	4.6	11	7	M	50	31300	M	M	19.2	M	M
MAFR064S1	25-42.6531-72.3491-4-50-000	6.2	22	0.06	3.0	6	9	71700	60	25400	1640	24500	19.4	4000	70
MAFR065S1	25-42.6982-72.3826-4-50-000	6.0	20	0.08	4.6	24	21	M	159	51100	M	M	32.7	M	M
MAFR066S1	25-42.7060-72.3498-4-50-000	6.9	47	0.16	5.0	27	15	M	179	32500	M	M	17.6	M	M
MAFR067S1	25-42.6491-72.3253-4-50-000	6.6	97	0.30	2.2	7	16	M	95	54100	2540	30500	28.8	M	140
MAFR068S1	25-42.6808-72.3113-4-50-000	6.5	23	0.10	7.2	28	.	44400	174	31800	940	9400	10.6	8000	50
MAFR069S1	25-42.6783-72.2808-4-50-000	6.9	27	0.12	5.7	20	9	76600	128	34300	3400	22500	18.2	10300	130
MAFR070S1	25-42.6595-72.2605-4-50-000	6.8	31	0.12	.	11	8	59300	84	42100	1280	20100	16.8	4800	80
MAFR071S1	25-42.6317-72.2451-4-50-000	6.5	35	0.10	5.8	26	22	69300	148	37000	2300	25200	20.6	10100	90
MAFR072S1	25-42.6483-72.2854-4-50-000	6.9	33	0.10	5.2	18	9	M	127	25900	2550	19500	12.6	8700	70
MAFR073S1	25-42.6223-72.2783-4-50-000	6.2	30	0.06	7.8	29	17	66500	187	36500	3620	19800	19.3	11200	120
MAFR074S1	25-42.5718-72.3879-4-50-000	5.4	23	0.04	2.8	5	9	52800	24	13400	720	23400	11.3	M	30
MAFR075S1	25-42.6138-72.3944-4-50-000	6.3	22	0.06	3.7	15	10	79300	64	51200	2280	26500	26.9	10400	170
MAFR076S1	25-42.7147-72.4433-4-50-000	6.5	77	0.18	3.0	10	13	51000	93	27500	.	18900	13.6	M	70
MAFR077S1	25-42.6801-72.4319-4-50-000	6.6	65	0.14	2.4	6	8	M	73	37500	1590	17800	15.2	7400	90
MAFR078S1	25-42.6484-72.3955-4-50-000	5.3	22	0.04	3.1	7	8	41800	66	30800	1460	18100	14.8	6500	50
MAFR079S1	25-42.6053-72.4111-4-50-000	5.9	43	0.06	4.5	8	21	M	69	23900	1720	22800	11.2	5600	60
MAFR080S1	25-42.5800-72.4375-4-50-000	6.2	29	0.06	4.1	6	32	45700	57	16500	800	16300	10.7	5100	20
MAFR081S1	25-42.5634-72.4171-4-50-000	4.8	21	0.00	4.4	10	26	M	75	48800	M	18100	21.4	.	50
MAFR082S1	25-42.5437-72.3737-4-50-000	5.4	19	0.04	2.4	5	.	M	35	26300	M	20200	15.1	.	70
MAFR083S1	25-42.5204-72.4241-4-50-000	5.7	25	0.04	5.2	5	30	M	48	17800	1240	27000	9.7	7900	70
MAFR084S1	25-42.5217-72.3931-4-50-000	4.7	20	0.00	4.3	10	7	M	58	21000	M	32200	12.8	M	80
MAFR085S1	25-42.5912-72.4911-4-50-000	M	M	M	7.5	30	24	40700	162	63100	3390	13100	21.6	M	100
MAFR086S1	25-42.6194-72.4698-4-50-000	6.6	36	0.14	3.3	10	14	M	68	24800	1110	17200	12.6	5600	60
MAFR087S1	25-42.6466-72.4414-4-50-000	6.4	45	0.14	4.8	14	1	85200	75	34200	1300	27600	22.1	8800	120
MAFR088S1	25-42.7153-72.4642-4-50-000	6.1	41	0.08	2.1	11	14	52200	69	43800	670	16200	17.7	7700	70
MAFR089S1	25-42.6745-72.4814-4-50-000	7.1	104	0.30	2.5	9	10	48700	67	36600	1420	14700	13.8	8800	70
MAFR090S1	25-42.6470-72.4881-4-50-000	6.9	60	0.28	2.5	9	10	76600	58	41100	1510	21000	14.3	10000	120
MAFR091S1	25-42.6460-72.5181-4-50-000	6.3	73	0.28	2.6	13	18	37500	125	24000	610	12500	12.2	7200	40
MAFR092S1	25-42.6092-72.5366-4-50-000	7.4	97	0.70	3.5	.	.	46100	.	.	860	15300	10.3	M	50
MAFR093S1	25-42.6144-72.5592-4-50-000	6.9	359	0.40	3.9	12	.	34800	94	25100	1250	11000	7.8	M	40
MAFR094S1	25-42.6250-72.5900-4-50-000	7.1	142	0.34	2.4	7	11	M	51	31400	990	17200	11.4	M	80
MAFR095S1	25-42.6773-72.5880-4-50-000	6.1	33	0.08	2.5	8	19	54600	32	43700	1610	12900	15.4	18500	90
MAFR096S1	25-42.6716-72.5108-4-50-000	6.9	38	0.12	3.9	15	13	41700	123	29400	910	10900	12.4	10400	60
MAFR097S1	25-42.7133-72.5262-4-50-000	6.8	36	0.10	3.4	23	21	56700	148	43100	1590	14200	16.3	19400	90
MAFR098S1	25-42.7055-72.5471-4-50-000	M	23	0.04	2.8	13	15	41300	126	42500	550	8300	1.4	M	70
MAFR099S1	25-42.7030-72.5652-4-50-000	7.4	62	0.34	1.9	6	9	53000	47	31200	1430	12600	10.3	15100	90
MAFR100S1	25-42.7205-72.5829-4-50-000	7.6	109	0.80	1.6	4	8	42600	.	31700	1680	10600	10.8	M	70
MAFR101S1	25-42.5733-72.5539-4-50-000	7.3	80	0.24	6.0	18	26	45200	114	33300	1730	15900	15.1	10200	70
MAFR102S1	25-42.5423-72.5486-4-50-000	7.2	58	0.16	3.3	9	15	58200	71	275900	1590	18400	64.0	7800	60
MAFR103S1	25-42.5445-72.5027-4-50-000	7.4	45	0.20	1.9	6	16	55100	69	25300	940	20100	13.2	4900	50
MAFR104S1	25-42.5603-72.5038-4-50-000	6.9	30	0.14	4.5	7	22	45700	48	22000	1220	15500	2.3	7200	50
MAFR105S1	25-42.5581-72.4640-4-50-000	6.6	22	0.08	2.7	6	12	56900	55	16300	700	18900	7.8	4300	40
MAFR106S1	25-42.5255-72.4728-4-50-000	6.9	26	0.08	2.1	6	9	40300	53	20000	800	16000	8.0	6500	40
MAFR107S1	25-42.5975-72.6202-4-50-000	6.5	158	0.90	3.7	11	34	71300	96	62500	2140	21600	22.0	21600	160
MAFR108S1	25-42.6200-72.6250-4-50-000	7.3	173	1.30	1.7	6	14	M	67	64200	1540	12200	0.5	11100	90
MAFR109S1	25-42.6325-72.6668-4-50-000	7.6	140	1.00	2.8	5	15	68500	83	54900	1850	18500	21.0	13700	130

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

7

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM	
MAFR110S1	25-42.6032-	72.6770-4-50-000	7.6	141	1.20	1.9	5	23	M	49	50700	2310	10800	18.3	11100	90
MAFR111S1	25-42.5734-	72.6783-4-50-000	7.8	165	1.20	1.3	4	15	61700	52	47300	2870	14600	17.3	20700	140
MAFR112S1	25-42.5841-	72.7014-4-50-000	7.2	101	0.40	2.0	3	11	48300	73	34700	1260	12200	12.6	9900	80
MAFR113S1	25-42.6277-	72.7350-4-50-000	7.5	72	0.60	3.0	11	25	68900	86	52800	1810	22000	21.3	14200	120
MAFR114S1	25-42.6469-	72.7219-4-50-000	7.4	78	0.60	1.9	4	13	43000	62	29700	750	10200	11.4	7400	70
MAFR115S1	25-42.6755-	72.7210-4-50-000	7.9	109	0.80	2.4	5	15	86300	76	39100	1490	21800	14.8	12700	140
MAFR116S1	25-42.6449-	72.6770-4-50-000	7.7	175	1.20	1.6	2	7	52300	30	31200	1100	13900	12.7	8300	90
MAFR117S1	25-42.6531-	72.6478-4-50-000	7.2	86	0.60	3.7	3	7	62400	42	37100	2350	18400	14.6	14800	100
MAFR118S1	25-42.6671-	72.6652-4-50-000	7.4	163	1.40	2.1	3	7	50500	43	36800	1280	12500	12.2	8500	90
MAFR119S1	25-42.7078-	72.6525-4-50-000	7.3	117	1.00	2.0	4	5	M	82	31200	M	14400	2.0	M	M
MAFR120S1	25-42.7094-	72.7055-4-50-000	7.8	160	1.30	2.6	6	17	78500	62	53500	1330	16000	18.8	11200	120
MAFR121S1	25-42.7211-	72.7003-4-50-000	7.6	129	1.00	1.9	5	12	83000	64	46900	1550	25100	18.4	12300	140
MAFR122S1	25-42.7224-	72.7319-4-50-000	7.5	80	0.60	3.2	4	37	51500	72	52700	1560	14900	15.6	17400	120
MAFR123S1	25-42.7019-	72.7753-4-50-000	7.6	56	0.50	2.5	9	3	67800	106	55200	1260	20900	2.0	15900	110
MAFR124S1	25-42.6770-	72.7517-4-50-000	7.7	62	0.50	2.4	11	20	79900	126	47500	1140	24100	20.1	12600	110
MAFR125S1	25-42.6745-	72.7877-4-50-000	7.4	41	0.22	2.4	6	14	M	81	39500	M	22100	14.8	M	110
MAFR126S1	25-42.6500-	72.8157-4-50-000	7.6	59	0.38	1.6	5	9	M	34	21400	540	8700	7.0	M	50
MAFR127S1	25-42.6277-	72.8143-4-50-000	7.5	60	0.40	1.4	.	6	M	28	13200	M	12500	5.4	M	50
MAFR128S1	25-42.6345-	72.8461-4-50-000	7.1	62	0.50	1.9	7	8	M	60	45000	M	20300	16.3	M	M
MAFR129S1	25-42.6524-	72.8623-4-50-000	7.2	55	0.18	1.6	5	12	M	54	59100	950	24600	27.2	8700	120
MAFR130S1	25-42.6828-	72.8453-4-50-000	7.0	43	0.26	2.2	4	23	79900	56	54300	1820	34300	19.7	16200	160
MAFR131S1	25-42.7054-	72.8350-4-50-000	7.1	30	0.12	2.8	3	25	71700	69	36500	950	24100	16.8	10000	100
MAFR132S1	25-42.7155-	72.8167-4-50-000	7.1	36	0.18	1.9	3	18	56700	55	38600	900	21500	16.8	M	90
MAFR133S1	25-42.7095-	72.8831-4-50-000	7.1	48	0.18	1.8	5	2	79100	57	29300	870	24000	13.0	7800	80
MAFR134S1	25-42.6917-	72.9036-4-50-000	7.0	39	0.10	3.1	6	22	M	52	48300	M	20900	18.2	.	M
MAFR135S1	25-42.7234-	72.9416-4-50-000	7.2	52	0.20	4.8	11	73	M	142	62400	M	12700	20.2	M	M
MAFR136S1	25-42.7256-	72.9953-4-50-000	7.0	25	0.06	3.3	12	39	M	109	60500	M	12000	20.3	.	30
MAFR137S1	25-42.7275-	72.9741-4-50-000	6.6	28	0.10	3.3	8	25	M	72	33700	M	17000	12.6	M	70
MAFR138S1	25-42.6933-	72.9313-4-50-000	6.9	39	0.12	3.0	7	22	64200	77	52100	1650	15300	19.4	12100	110
MAFR139S1	25-42.6517-	72.9293-4-50-000	7.0	22	0.08	2.7	11	9	65700	74	43900	1080	19400	15.5	M	100
MAFR140S1	25-42.6345-	72.8979-4-50-000	7.8	58	0.36	2.1	6	.	78100	57	51400	1690	31900	2.0	15000	170
MAFR141S1	25-42.6152-	72.7719-4-50-000	7.7	67	0.40	2.4	13	21	60000	57	55200	1100	20000	0.9	12300	100
MAHA001S1	25-42.1127-	72.1808-4-50-000	6.4	40	0.20	18.8	.73	1	M	948	92600	M	11300	0.3	M	180
MAHA002S1	25-42.1407-	72.1802-4-50-000	5.5	182	0.04	11.0	61	.	95900	338	34100	970	8500	1.4	M	100
MAHA003S1	25-42.1560-	72.2168-4-50-000	6.4	68	0.22	6.2	50	31	82700	325	41300	1210	12500	17.4	9200	80
MAHA004S1	25-42.1234-	72.2076-4-50-000	6.6	70	0.24	12.7	107	52	M	663	61800	2910	14100	24.3	22900	160
MAHA005S1	25-42.0786-	72.2081-4-50-000	6.8	140	0.24	13.1	102	40	71300	545	57100	1420	8200	21.2	M	120
MAHA006S1	25-42.0820-	72.1570-4-50-000	6.7	75	0.16	34.3	311	90	70600	1458	100300	3150	8400	40.2	23400	140
MAHA007S1	25-42.0647-	72.1643-4-50-000	7.1	47	0.16	12.8	103	31	73100	510	52500	1720	8800	19.8	12700	110
MAHA008S1	25-42.0465-	72.2062-4-50-000	7.2	60	0.24	10.2	71	28	101700	413	63400	1800	6800	25.2	M	170
MAHA009S1	25-42.0639-	72.2474-4-50-000	6.7	53	0.38	3.6	22	13	79300	171	39100	1130	11400	0.2	M	90
MAHA010S1	25-42.0765-	72.2674-4-50-000	5.8	44	0.16	5.0	31	14	79100	179	25700	940	15400	14.6	9600	100
MAHA011S1	25-42.1092-	72.2509-4-50-000	5.2	30	0.06	3.4	25	13	62700	146	38700	960	16200	17.6	7400	80
MAHA012S1	25-42.1127-	72.3157-4-50-000	6.9	105	0.24	4.0	22	24	51100	139	45100	1360	17500	22.0	6200	110
MAHA013S1	25-42.0889-	72.3131-4-50-000	6.9	60	0.18	5.4	43	24	54300	263	65900	1510	17100	29.5	6800	120
MAHA014S1	25-42.0903-	72.3405-4-50-000	5.0	35	0.02	3.2	12	14	51900	73	17400	590	25000	11.3	4500	40
MAHA015S1	25-42.0534-	72.3278-4-50-000	7.0	40	0.08	4.3	13	16	49700	111	38900	1410	19400	20.6	M	100
MAHA016S1	25-42.0484-	72.3039-4-50-000	6.8	61	0.14	3.9	23	21	69000	153	43000	1650	27100	26.3	8300	120
MAHA017S1	25-42.1344-	72.3122-4-50-000	6.5	103	0.30	5.4	31	3	51100	195	41300	1500	18200	24.3	M	100
MAHA018S1	25-42.1537-	72.2616-4-50-000	7.0	59	0.28	3.3	32	21	65500	192	44700	1060	18400	18.6	9000	90
MAHA019S1	25-42.1706-	72.2599-4-50-000	7.2	220	0.26	11.3	136	.	88100	729	105200	3530	17000	41.8	29800	200
MAHA020S1	25-42.1547-	72.2971-4-50-000	7.1	132	0.26	3.9	22	2	M	128	65400	M	M	4.1	11900	M
MAHA021S1	25-42.2280-	72.2909-4-50-000	6.8	45	0.22	10.6	42	27	49100	238	31600	1270	16200	15.8	9600	100

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS--

ALBANY

SHEET

8

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
MAHA022S1	25-42.2138-72.3168-4-50-000	7.0	59	0.24	11.7	M	M	45500	M	M	1260	16400	M	M	50
MAHA023S1	25-42.1905-72.2853-4-50-000	7.0	49	0.10	3.5	17	11	51900	117	30000	820	19600	12.3	5900	80
MAHA024S1	25-42.2020-72.3455-4-50-000	6.9	105	0.42	13.1	60	47	M	312	29500	1570	M	17.4	9300	70
MAHA025S1	25-42.1872-72.3673-4-50-000	6.3	76	0.32	7.6	45	2	M	219	33800	M	M	20.6	M	
MAHA026S1	25-42.1715-72.3449-4-50-000	7.0	448	0.24	5.2	17	19	62200	144	42000	2110	20700	19.6	7500	120
MAHA027S1	25-42.1571-72.3690-4-50-000	7.3	255	0.22	8.1	45	2	77900	246	31500	1600	26600	17.8	10300	130
MAHA028S1	25-42.1552-72.4108-4-50-000	7.2	105	0.20	7.4	38	41	58600	241	56500	2190	19500	25.0	12600	200
MAHA029S1	25-42.1819-72.4134-4-50-000	6.8	100	0.48	6.3	27	23	71900	179	25600	880	21100	12.4	6500	90
MAHA030S1	25-42.2218-72.4260-4-50-000	6.6	41	0.18	5.8	95	34	M	544	59100	1190	21000	26.4	M	170
MAHA031S1	25-42.2057-72.4714-4-50-000	7.2	75	0.24	5.5	25	25	M	166	28700	600	19700	12.3	M	30
MAHA032S1	25-42.2221-72.5013-4-50-000	7.2	120	0.52	5.9	27	25	33200	184	14800	990	13000	7.7	5600	30
MAHA033S1	25-42.1788-72.4749-4-50-000	6.7	128	0.48	13.2	87	55	43400	459	40000	1500	15600	17.4	M	60
MAHA034S1	25-42.1646-72.5357-4-50-000	6.6	180	0.92	10.0	41	.	43900	239	26900	1170	15900	4.4	9100	60
MAHA035S1	25-42.1265-72.4530-4-50-000	7.2	175	0.76	5.9	27	19	M	151	24800	850	17700	12.4	M	50
MAHA036S1	25-42.1288-72.4021-4-50-000	6.8	70	0.14	3.3	12	14	59600	102	35800	1250	22100	15.7	8400	120
MAHA037S1	25-42.1197-72.3581-4-50-000	6.2	55	0.14	19.7	152	206	64400	720	109400	4360	20200	44.1	27800	320
MAHA038S1	25-42.1463-72.3779-4-50-000	6.4	51	0.22	4.1	25	28	88300	152	38100	1060	33200	30.7	5300	120
MAHA039S1	25-42.0698-72.3959-4-50-000	6.6	55	0.10	5.1	16	31	66900	129	32200	1300	21700	24.7	5700	110
MAHA040S1	25-42.0593-72.3709-4-50-000	6.8	49	0.14	4.4	13	18	76000	68	24500	1450	27600	17.2	8900	130
MAHA041S1	25-42.0438-72.3834-4-50-000	6.8	45	0.16	6.2	12	13	58400	65	45100	1490	18000	27.8	M	110
MAHA042S1	25-42.0546-72.4391-4-50-000	7.1	60	0.22	5.1	20	24	51500	103	45900	1660	19100	1.0	M	120
MAHA043S1	25-42.0653-72.4491-4-50-000	7.2	92	0.40	5.0	20	22	M	104	35000	M	23400	21.8	M	30
MAHA044S1	25-42.0956-72.4646-4-50-000	7.3	160	0.72	6.5	39	22	M	216	46300	M	M	16.6	M	M
MAHA045S1	25-42.0755-72.4947-4-50-000	6.4	125	0.46	4.6	17	.	M	108	26600	M	18700	11.8	M	60
MAHA046S1	25-42.0447-72.4910-4-50-000	7.0	190	0.50	4.6	15	16	M	107	18100	750	25700	8.3	5300	60
MAHA047S1	25-42.0417-72.5191-4-50-000	7.2	151	0.54	2.9	7	6	47400	65	25100	680	18800	10.3	M	60
MAHA048S1	25-42.0517-72.5501-4-50-000	7.3	145	0.36	7.7	37	35	54200	218	37200	2060	19300	17.2	9700	90
MAHA049S1	25-42.1634-72.6323-4-50-000	7.4	278	1.52	3.5	20	.	58000	94	34500	2060	21100	13.0	9000	80
MAHA050S1	25-42.2370-72.6254-4-50-000	7.5	155	0.84	4.7	20	15	56100	92	28400	1150	20200	10.4	8100	90
MAHA051S1	25-42.2721-72.6181-4-50-000	7.5	105	0.48	6.1	39	33	49000	246	37800	.	16600	14.1	M	80
MAHA052S1	25-42.1954-72.6713-4-50-000	7.6	148	0.74	6.2	27	1	40400	136	16800	1110	16700	7.8	8300	40
MAHA053S1	25-42.1518-72.6725-4-50-000	7.3	122	0.54	6.5	19	15	M	103	33000	3160	17200	10.5	7400	70
MAHA054S1	25-42.1437-72.6363-4-50-000	7.3	180	0.64	3.1	16	15	37900	90	19900	780	13100	0.7	5000	40
MAHA055S1	25-42.1333-72.6611-4-50-000	7.4	210	0.66	4.9	23	.	40600	131	33000	810	15000	11.6	M	50
MAHA056S1	25-42.1066-72.6585-4-50-000	7.5	250	1.08	4.6	14	17	40000	96	19800	860	14100	8.6	M	50
MAHA057S1	25-42.1095-72.7763-4-50-000	6.3	69	0.26	4.9	22	38	M	127	44100	1100	12800	15.4	7600	50
MAHA058S1	25-42.1501-72.7935-4-50-000	6.7	95	0.18	7.9	24	19	M	176	31600	1140	13500	9.6	7300	50
MAHA059S1	25-42.1626-72.7642-4-50-000	7.3	80	0.28	6.1	33	17	54400	186	28400	870	15300	10.4	7200	60
MAHA060S1	25-42.1885-72.7591-4-50-000	7.2	125	0.30	6.7	28	23	60300	152	48400	1560	14100	15.6	14300	60
MAHA061S1	25-42.1754-72.7314-4-50-000	7.1	132	0.70	7.7	32	75	50600	253	61000	3040	11300	25.8	16700	70
MAHA062S1	25-42.1353-72.7127-4-50-000	7.4	110	0.64	3.3	12	14	33400	92	20500	890	12400	8.3	5700	50
MAHA063S1	25-42.0973-72.6832-4-50-000	7.7	230	1.16	4.3	10	21	M	61	25700	M	19200	8.7	M	70
MAHA064S1	25-42.0611-72.6707-4-50-000	7.4	260	0.84	3.4	14	22	49600	84	33100	1030	15700	12.8	7700	80
MAHA065S1	25-42.0423-72.6841-4-50-000	7.3	218	0.52	5.2	23	40	43900	181	47100	1390	14000	16.2	M	70
MAHA066S1	25-42.0424-72.6195-4-50-000	7.6	600	1.55	5.2	12	17	58800	89	35300	1210	17400	9.3	11300	90
MAHA067S1	25-42.0664-72.7347-4-50-000	7.8	165	0.64	4.3	22	23	38700	125	29100	1050	11600	10.7	7100	50
MAHA068S1	25-42.0821-72.7343-4-50-000	7.8	171	0.52	5.4	22	29	M	173	30600	960	12400	13.0	M	50
MAHA069S1	25-42.0868-72.7485-4-50-000	7.5	188	0.68	5.7	25	48	49900	184	35800	1300	13600	14.8	8900	60
MAHA070S1	25-42.0807-72.7680-4-50-000	7.2	305	1.44	4.8	15	22	46700	107	29500	1080	12200	11.1	M	50
MAHA071S1	25-42.0564-72.7687-4-50-000	7.7	211	0.88	7.5	19	44	M	133	34800	2050	17500	6.5	14300	90
MAHA072S1	25-42.0313-72.7840-4-50-000	7.5	145	0.40	5.8	23	.	43100	146	28800	1040	11300	10.9	M	50
MAHA073S1	25-42.0742-72.8134-4-50-000	7.1	100	0.36	12.8	29	38	43300	175	26000	1150	13700	11.6	7100	50
MAHA074S1	25-42.0921-72.8097-4-50-000	7.2	98	0.30	9.0	37	51	46000	227	45000	2170	14100	15.4	M	80

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY SHEET

9

SRL I.D. *****	DOE I.D.		PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM	
MAHA075S1	25-42.1216-	72.8213	-4-50-000	7.6	63	0.16	10.0	38	58	44100	253	50700	2870	14600	15.9	10400	90
MAHA076S1	25-42.1414-	72.8649	-4-50-000	6.7	30	0.06	8.3	43	40	47000	276	41000	1300	16200	17.7	M	80
MAHA077S1	25-42.1673-	72.8499	-4-50-000	7.0	406	0.32	8.5	39	81	49000	310	77100	2200	14100	24.7	13900	110
MAHA078S1	25-42.1905-	72.8583	-4-50-000	7.2	92	0.24	4.0	10	30	50700	112	45800	1310	15500	15.4	M	80
MAHA079S1	25-42.1763-	72.9531	-4-50-000	7.4	130	0.20	4.3	9	52	M	116	33900	130	M	7.1	5100	M
MAHA080S1	25-42.2075-	72.9830	-4-50-000	7.4	161	0.18	5.7	8	89	50800	86	36700	810	16300	14.0	6400	60
MAHA081S1	25-42.1998-	72.9549	-4-50-000	7.4	420	0.52	4.3	10	45	62400	87	44400	2820	19000	15.3	9800	120
MAHA082S1	25-42.1883-	72.9049	-4-50-000	7.6	148	0.24	3.5	10	32	47900	101	50700	2080	14200	17.7	M	100
MAHA083S1	25-42.2145-	72.9024	-4-50-000	7.6	35	0.14	3.0	12	7	58900	63	31000	940	15700	12.6	5200	80
MAHA084S1	25-42.2394-	72.8369	-4-50-000	7.5	80	0.16	4.7	20	19	61000	154	36800	1230	17000	11.6	10700	70
MAHA085S1	25-42.2076-	72.8103	-4-50-000	6.8	42	0.06	8.9	31	22	69700	217	28300	1480	18800	6.6	11900	70
MAHA086S1	25-42.2151-	72.8459	-4-50-000	7.4	34	0.18	4.4	21	24	M	127	40500	650	17600	13.3	M	70
MAHA087S1	25-42.2610-	72.9079	-4-50-000	7.6	60	0.30	4.0	12	32	M	98	33600	M	12600	4.8	6800	60
MAHA088S1	25-42.2775-	72.9254	-4-50-000	7.6	51	0.28	3.5	10	21	M	73	32800	920	13300	11.8	7900	70
MAHA089S1	25-42.2953-	72.9257	-4-50-000	7.4	76	0.50	4.1	9	4	M	122	50800	970	15000	1.8	8900	60
MAHA090S1	25-42.2983-	72.9030	-4-50-000	7.4	70	0.46	3.2	6	18	51500	66	33100	920	15700	11.4	M	70
MAHA091S1	25-42.3263-	72.9081	-4-50-000	7.6	61	0.42	2.8	10	16	65700	57	29600	1180	15300	9.6	11700	90
MAHA092S1	25-42.3357-	72.9451	-4-50-000	7.7	47	0.24	5.4	13	85	51800	141	70900	1230	16900	22.8	8600	90
MAHA093S1	25-42.3018-	72.9737	-4-50-000	7.4	56	0.38	2.7	11	18	86600	82	41300	1450	25400	14.3	10300	140
MAHA094S1	25-42.2621-	73.0022	-4-50-000	7.4	56	0.30	4.3	6	58	54300	100	35700	1050	16900	12.7	M	60
MAHA095S1	25-42.2667-	72.9784	-4-50-000	7.7	45	0.24	1.6	3	10	84100	75	42300	970	26100	16.6	7400	110
MAHA096S1	25-42.2468-	72.9549	-4-50-000	7.5	90	0.20	2.7	8	39	55800	83	76900	1870	16800	31.0	2700	150
MAHA097S1	25-42.1591-	73.0029	-4-50-000	5.0	40	0.00	5.5	5	87	65600	110	32200	1040	21900	12.7	8600	50
MAHA098S1	25-42.1898-	73.0157	-4-50-000	6.6	55	0.18	3.5	5	40	55300	80	28700	840	17600	11.5	6700	50
MAHA099S1	25-42.1265-	73.0631	-4-50-000	6.0	54	0.08	3.4	6	65	M	119	64700	1200	17800	25.9	M	90
MAHA100S1	25-42.0906-	73.0659	-4-50-000	6.2	40	0.12	4.8	2	85	49800	89	28100	790	20800	13.4	11000	30
MAHA101S1	25-42.1140-	72.9939	-4-50-000	5.6	20	0.02	3.9	7	52	M	98	36600	1090	21900	12.5	7600	70
MAHA102S1	25-42.0551-	73.0174	-4-50-000	7.3	50	0.14	3.7	3	54	M	88	37400	M	27300	13.6	.	M
MAHA103S1	25-42.0499-	73.0346	-4-50-000	6.5	51	0.26	3.5	7	35	M	109	29700	M	18800	13.3	M	M
MAHA104S1	25-42.0805-	72.9917	-4-50-000	6.9	45	0.14	4.1	7	52	M	90	34400	1030	28500	16.0	6700	50
MAHA105S1	25-42.0640-	72.9672	-4-50-000	7.1	30	0.10	3.2	5	33	M	71	37000	M	18700	14.1	M	10
MAHA106S1	25-42.0771-	72.9468	-4-50-000	6.9	35	0.16	8.7	15	125	M	140	67400	M	18200	16.5	M	40
MAHA107S1	25-42.1234-	72.9522	-4-50-000	6.4	30	0.08	6.4	12	124	M	122	45600	770	17600	15.3	.	.
MAHA108S1	25-42.1115-	72.8976	-4-50-000	6.8	33	0.10	11.9	38	110	M	240	40600	1580	20100	15.8	.	M
MAHA109S1	25-42.0798-	72.9100	-4-50-000	6.9	30	0.12	5.5	16	47	M	126	43900	1310	16600	15.7	.	M
MAHA110S1	25-42.0884-	72.8573	-4-50-000	7.1	34	0.14	4.7	19	32	M	163	44800	M	24100	17.0	.	90
MAHA111S1	25-42.1062-	72.8640	-4-50-000	6.9	30	0.10	13.5	46	3	70400	253	59400	3010	20900	16.1	16300	150
MAHA112S1	25-42.0629-	72.8620	-4-50-000	7.0	49	0.14	8.2	37	56	57100	246	52300	1440	18900	19.5	M	60
MAHMO01S1	25-42.2007-	72.7202	-4-50-000	7.5	180	0.88	4.8	20	21	36100	120	20600	740	10900	7.9	M	40
MAHMO02S1	25-42.2232-	72.7216	-4-50-000	7.1	90	0.48	6.0	30	35	44100	148	51800	1730	11100	18.4	M	50
MAHMO03S1	25-42.2333-	72.7494	-4-50-000	6.3	115	0.28	5.1	21	18	45200	145	21600	770	12000	7.7	M	40
MAHMO04S1	25-42.2591-	72.7118	-4-50-000	6.7	105	0.36	4.0	13	16	58700	86	27300	800	14200	2.4	8300	60
MAHMO05S1	25-42.2705-	72.7462	-4-50-000	7.5	77	0.36	3.2	13	10	M	62	22300	780	15500	4.1	5900	50
MAHMO06S1	25-42.2877-	72.7743	-4-50-000	7.7	65	0.44	5.2	16	13	47200	79	31000	960	13700	8.7	10200	50
MAHMO07S1	25-42.3217-	72.7800	-4-50-000	7.3	50	0.40	4.0	12	6	46700	64	32000	1070	14000	10.3	8100	40
MAHMO08S1	25-42.3453-	72.8058	-4-50-000	M	M	M	3.3	10	8	47600	51	37300	960	14100	13.8	2500	60
MAHMO09S1	25-42.3463-	72.7693	-4-50-000	7.8	50	0.36	5.0	17	.	49200	101	25000	770	13100	9.0	8300	40
MAHMO10S1	25-42.3213-	72.7525	-4-50-000	7.4	60	0.44	2.9	7	6	79300	45	22600	820	23400	2.0	7200	70
MAHMO11S1	25-42.3570-	72.7048	-4-50-000	7.4	72	0.58	3.7	11	7	43400	95	44700	1570	12200	15.6	11100	80
MAHMO12S1	25-42.3059-	72.6622	-4-50-000	7.8	90	0.60	3.7	18	13	38500	89	37700	1140	11000	14.7	11900	60
MAHMO13S1	25-42.2899-	72.6622	-4-50-000	8.2	165	1.04	3.9	11	14	M	94	34300	1380	13500	12.7	11100	80
MAHMO14S1	25-42.2417-	72.6601	-4-50-000	8.1	170	0.84	2.9	13	15	33200	79	32100	1000	11500	2.3	8000	60
MAHMO15S1	25-42.2698-	72.6952	-4-50-000	7.0	160	1.36	5.8	18	18	47500	112	36500	1840	12800	11.5	20300	80

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

10

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
MAHMO16S1	25-42.3099-72.7149-4-50-000	8.1	55	0.36	4.1	12	.	M	38	36200	M	13200	12.6	M	M
MAHMO17S1	25-42.3827-72.7094-4-50-000	7.7	80	0.60	6.5	26	19	52900	143	55200	2010	12100	15.2	23800	120
MAHMO18S1	25-42.4047-72.7074-4-50-000	M	M	M	3.6	11	2	M	60	40400	1160	14100	15.9	8900	60
MAHMO19S1	25-42.4017-72.6785-4-50-000	8.1	120	0.72	3.3	14	16	40200	96	33100	1100	12700	12.5	6600	60
MAHMO20S1	25-42.3522-72.6743-4-50-000	8.9	81	1.60	4.6	12	15	M	84	46200	1590	10700	16.2	14700	80
MAHMO21S1	25-42.3587-72.6104-4-50-000	7.9	165	0.96	2.7	9	16	M	78	33900	950	15000	14.6	M	70
MAHMO22S1	25-42.3372-72.5813-4-50-000	7.1	90	0.48	4.0	11	19	38400	89	21700	910	13700	10.4	6600	40
MAHMO23S1	25-42.3293-72.5641-4-50-000	7.6	98	0.68	5.2	19	22	38900	99	23600	1030	12400	10.2	8800	60
MAHMO24S1	25-42.2825-72.5878-4-50-000	7.7	120	0.92	11.7	66	61	48000	364	43300	2720	10400	20.1	14600	70
MAHMO25S1	25-42.3097-72.5849-4-50-000	M	M	M	4.7	15	19	M	112	18900	740	11700	7.1	5700	40
MAHMO26S1	25-42.2430-72.5827-4-50-000	7.1	120	0.88	10.6	41	35	M	214	37000	1900	15800	4.2	10800	100
MAHMO27S1	25-42.2497-72.5604-4-50-000	7.1	220	1.12	7.5	36	38	40000	219	29000	1220	11900	12.0	2600	40
MAHMO28S1	25-42.2196-72.5395-4-50-000	6.8	140	0.40	8.7	51	.	33400	276	25200	1460	10800	0.4	8800	40
MAHMO29S1	25-42.4081-72.7473-4-50-000	6.9	78	0.28	3.6	13	10	M	82	29500	810	12700	10.2	8600	60
MAHMO30S1	25-42.4344-72.7402-4-50-000	7.1	60	0.64	5.9	8	7	M	70	35000	M	12600	11.5	.	40
MAHMO31S1	25-42.4459-72.7781-4-50-000	6.3	30	0.12	3.9	13	7	M	83	34900	M	11900	6.9	M	50
MAHMO32S1	25-42.4258-72.7819-4-50-000	6.7	75	0.28	4.9	18	9	M	142	30900	M	12100	9.8	M	90
MAHMO33S1	25-42.4551-72.8401-4-50-000	6.8	90	0.28	3.1	13	8	M	79	39000	900	10000	12.2	M	50
MAHMO34S1	25-42.4476-72.8584-4-50-000	7.0	70	0.36	3.4	22	20	36800	115	63300	1240	10300	20.4	12500	80
MAHMO35S1	25-42.4785-72.8894-4-50-000	6.8	67	0.40	2.5	8	25	67200	45	33100	1480	22100	16.2	12700	110
MAHMO36S1	25-42.5136-72.8839-4-50-000	6.6	55	0.32	2.1	8	13	62700	52	58800	1480	17400	25.1	M	120
MAHMO37S1	25-42.5326-72.9264-4-50-000	M	M	M	3.1	12	40	41900	105	30200	760	12800	11.6	M	50
MAHMO38S1	25-42.5369-72.9624-4-50-000	M	M	M	4.5	10	8	44500	64	30900	980	12200	8.8	11200	50
MAHMO39S1	25-42.5029-72.9430-4-50-000	6.5	25	0.16	1.6	5	7	39500	43	27100	680	15000	11.4	M	50
MAHMO40S1	25-42.4857-72.9275-4-50-000	7.0	45	0.28	2.5	8	17	49800	46	38000	1090	14200	12.8	8500	80
MAHMO41S1	25-42.4484-72.9350-4-50-000	6.9	38	0.20	2.7	6	26	49700	84	39700	1180	16300	14.4	M	90
MAHMO42S1	25-42.4534-72.9608-4-50-000	6.7	20	0.08	2.5	7	26	46800	82	28000	710	13100	10.0	5900	40
MAHMO43S1	25-42.4217-72.9867-4-50-000	6.8	31	0.12	2.9	5	34	46900	120	25500	730	12400	13.4	4700	40
MAHMO44S1	25-42.3802-72.9780-4-50-000	6.7	30	0.24	1.8	4	10	84300	62	35000	910	24400	13.4	9000	110
MAHMO45S1	25-42.3644-73.0085-4-50-000	7.0	20	0.12	2.4	2	23	33200	34	23300	820	7100	5.2	6300	30
MAHMO46S1	25-42.3454-73.0353-4-50-000	7.1	50	0.36	3.6	8	46	68000	104	37600	1350	22100	16.8	13100	100
MAHMO47S1	25-42.3198-73.0288-4-50-000	7.2	55	0.24	1.9	4	16	62700	89	30200	580	21600	12.9	6400	60
MAHMO48S1	25-42.3223-72.9956-4-50-000	7.0	80	0.80	3.5	8	1	M	84	39300	1460	22200	14.3	11200	110
MAHMO49S1	25-42.3494-72.9679-4-50-000	7.3	43	0.32	2.7	4	33	63500	81	36400	990	21300	1.4	8500	80
MAHMO50S1	25-42.2874-72.8064-4-50-000	7.7	40	0.40	3.1	8	9	47300	86	22500	770	13800	8.4	5800	40
MAHMO51S1	25-42.2914-72.8395-4-50-000	7.2	28	0.16	3.9	12	10	68300	90	36800	1660	19600	12.9	11100	90
MAHMO52S1	25-42.2607-72.8609-4-50-000	7.3	75	0.48	3.3	16	9	47400	65	29400	1010	13000	10.2	M	70
MAHMO53S1	25-42.2497-72.8817-4-50-000	7.3	58	0.60	3.7	10	19	55300	68	32200	980	14100	11.2	M	60
MAHMO54S1	25-42.2949-72.8738-4-50-000	7.9	52	0.64	2.9	10	11	60500	66	30300	1080	15600	10.7	8000	60
MAHMO55S1	25-42.3230-72.8698-4-50-000	7.2	60	0.44	3.5	11	3	47300	101	45500	1510	10700	16.2	M	50
MAHMO56S1	25-42.3478-72.9016-4-50-000	6.7	65	0.56	2.8	10	23	58500	87	33200	1430	16600	12.3	12400	100
MAHMO57S1	25-42.3713-72.9296-4-50-000	7.2	42	0.20	3.4	7	27	M	93	34900	1980	16200	3.5	16900	90
MAHMO58S1	25-42.3950-72.9263-4-50-000	6.7	91	0.52	2.7	8	21	M	88	27800	M	10500	10.7	M	M
MAHMO59S1	25-42.4246-72.9203-4-50-000	6.4	40	0.24	4.0	12	23	M	108	51600	1670	11300	18.7	12400	50
MAHMO60S1	25-42.4207-72.8861-4-50-000	7.1	40	0.40	2.1	9	.	62200	.	34400	1170	22400	13.1	8600	90
MAHMO61S1	25-42.3985-72.8739-4-50-000	7.1	45	0.36	2.9	9	23	58600	78	35800	1260	13100	11.8	8700	90
MAHMO62S1	25-42.4029-72.8385-4-50-000	4.3	20	0.08	6.1	27	16	M	160	61200	M	14200	19.8	.	M
MAHMO63S1	25-42.4259-72.8347-4-50-000	4.8	20	0.10	4.4	11	6	52100	85	31000	750	12900	9.0	7400	80
MAHMO64S1	25-42.3906-72.8035-4-50-000	4.6	45	0.20	4.9	19	17	57100	94	34800	1140	13400	9.5	21500	80
MAHMO65S1	25-42.3464-72.8417-4-50-000	4.6	30	0.20	4.0	17	11	60000	100	31800	930	10100	10.1	10000	90
MAHMO66S1	25-42.3649-72.7915-4-50-000	5.4	27	0.24	5.0	18	12	78900	111	49800	2130	20500	14.8	18200	110
MAHMO67S1	25-42.3827-72.6495-4-50-000	5.4	65	0.44	3.4	13	15	52500	68	21100	1330	15600	9.7	13200	80
MAHMO68S1	25-42.3813-72.6269-4-50-000	6.2	120	0.36	7.9	30	131	M	223	100300	M	19200	33.6	.	160

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

11

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
MAHM069S1	25-42.4156-72.6307-4-50-000	5.7	100	0.40	1.7	4	1	M	37	35600	1050	14700	14.7	.	60
MAHM070S1	25-42.4129-72.5653-4-50-000	5.8	112	0.52	2.4	8	17	M	72	36000	1590	21200	18.2	14500	80
MAHM071S1	25-42.3855-72.5466-4-50-000	5.4	135	0.64	4.0	10	24	44000	67	22600	880	15500	12.0	7100	40
MAHM073S1	25-42.3200-72.4966-4-50-000	7.8	50	0.72	17.9	74	78	42200	463	43000	3000	11300	16.5	16400	100
MAHM074S1	25-42.3183-72.5261-4-50-000	7.9	80	0.52	6.7	31	35	40000	216	38700	1330	11600	16.0	M	90
MAHM075S1	25-42.2779-72.5238-4-50-000	7.7	125	0.64	2.0	6	5	32 00	37	13800	460	11300	3.2	M	30
MAHM076S1	25-42.2814-72.4856-4-50-000	8.2	105	1.00	3.3	7	2	42900	58	25400	840	15900	12.0	7000	20
MAHM077S1	25-42.2616-72.4633-4-50-000	8.1	70	0.64	5.1	20	18	49 00	122	29800	820	15900	11.7	M	70
MAHM078S1	25-42.2348-72.4649-4-50-000	8.1	50	0.36	6.1	13	14	63900	107	25000	870	27100	3.4	7200	80
MAHM079S1	25-42.2299-72.5177-4-50-000	M	M	M	2.0	6	15	55600	63	31300	1070	17200	13.9	7600	80
MAHM080S1	25-42.2510-72.5044-4-50-000	8.0	130	0.80	15.0	72	61	51300	466	55000	3530	14700	16.7	18500	130
MAHM081S1	25-42.2755-72.5555-4-50-000	8.3	92	0.64	7.2	38	32	38900	239	30700	1460	12600	11.6	8300	50
MAHM082S1	25-42.3495-72.5613-4-50-000	7.5	750	1.50	3.9	15	16	68500	67	32600	1730	19600	5.2	12100	120
MAHM083S1	25-42.3765-72.4971-4-50-000	7.4	56	0.24	4.6	7	50	54000	58	24000	1340	17200	13.8	8800	50
MAHM084S1	25-42.3399-72.5272-4-50-000	7.9	170	0.52	8.1	26	27	58300	170	33700	2230	18600	13.1	15700	120
MAHM085S1	25-42.4183-72.5257-4-50-000	7.8	50	0.32	3.5	5	20	M	39	15500	830	16800	9.7	M	40
MAHM086S1	25-42.4255-72.5004-4-50-000	7.8	50	0.40	6.1	7	69	45 00	50	15700	800	17100	10.9	5600	30
MAHM087S1	25-42.3309-72.4661-4-50-000	8.3	32	0.32	3.6	2	42	36300	36	16600	680	12800	10.1	M	40
MAHM088S1	25-42.3340-72.4285-4-50-000	4.5	20	0.10	3.2	4	25	41700	32	17200	560	16900	2.7	4700	30
MAHM089S1	25-42.4098-72.6009-4-50-000	M	M	M	3.3	15	55	M	112	40200	790	6500	9.2	M	30
MAHM090S1	25-42.3458-72.4633-4-50-000	7.6	49	0.28	10.7	36	49	37200	229	26300	1870	11500	11.5	8200	50
MAHM091S1	25-42.3295-72.4467-4-50-000	8.2	40	0.32	4.3	9	28	52300	85	20900	1010	17100	12.1	6400	60
MAHM092S1	25-42.3317-72.4269-4-50-000	8.5	62	0.20	4.1	13	13	42700	114	27200	780	15800	12.8	5600	60
MAHM093S1	25-42.2687-72.4313-4-50-000	8.2	35	0.32	6.8	14	.	60200	119	17900	770	22000	7.9	M	60
MAHM094S1	25-42.2377-72.4128-4-50-000	8.0	90	0.64	7.5	18	19	48200	220	33800	990	17000	3.4	M	100
MAHM095S1	25-42.2160-72.3669-4-50-000	8.2	70	0.40	5.0	15	23	63800	145	38400	1250	21200	17.3	6700	130
MAHM096S1	25-42.2377-72.3651-4-50-000	8.1	70	0.60	7.2	37	38	M	224	39300	1250	15800	19.4	8300	80
MAHM097S1	25-42.2641-72.3770-4-50-000	8.5	48	0.32	5.2	18	28	57500	153	42000	1350	19400	20.5	7800	90
MAHM098S1	25-42.2764-72.3671-4-50-000	8.3	25	0.16	4.4	12	15	M	65	32900	1140	18900	16.3	5500	70
MAHM099S1	25-42.2809-72.3112-4-50-000	7.9	52	0.24	3.7	8	12	M	65	27900	2100	26900	14.8	9300	110
MAHM100S1	25-42.2408-72.3087-4-50-000	7.9	160	0.24	11.0	85	63	61700	510	54900	1780	18600	23.8	11500	120
MAHM101S1	25-42.2760-72.2240-4-50-000	7.9	56	0.16	13.3	58	33	M	349	31900	1280	16600	12.2	10500	60
MAHM102S1	25-42.2798-72.2722-4-50-000	7.9	35	0.48	2.6	9	11	M	54	18500	M	32400	7.6	M	70
MAHM103S1	25-42.2431-72.2756-4-50-000	M	M	M	4.4	9	20	M	78	23200	770	17600	4.6	6600	50
MAHM104S1	25-42.2486-72.2452-4-50-000	7.4	30	0.24	3.4	.	25	46E00	53	20100	680	16100	15.5	4900	40
MAHM105S1	25-42.3026-72.4062-4-50-000	7.9	70	0.16	5.2	20	39	47E00	152	32200	860	15900	18.7	6500	50
MAHM106S1	25-42.3300-72.4016-4-50-000	7.4	60	0.16	3.4	7	2	M	53	13600	520	18800	10.6	M	40
MAHM107S1	25-42.3514-72.4107-4-50-000	6.2	30	0.12	2.5	7	12	47E00	51	20300	460	16100	8.9	3600	50
MAHO021S1	25-42.5326-72.0785-4-50-000	5.3	30	0.04	4.2	18	3	83300	101	27800	600	19000	6.9	5900	80
MAHO023S1	25-42.5803-72.0849-4-50-000	6.6	110	0.16	2.7	11	9	84100	45	22800	510	28000	5.2	4000	50
MAHO024S1	25-42.5670-72.0429-4-50-000	6.4	60	0.28	6.6	29	22	39E00	159	12900	690	11500	5.2	M	30
MAHO025S1	25-42.5455-72.0408-4-50-000	5.9	50	0.08	7.6	26	.	M	153	16500	660	16800	5.4	7400	40
MAHO026S1	25-42.5484-72.0002-4-50-000	6.5	80	0.12	3.2	11	8	M	62	21100	540	23600	7.6	6700	80
MAHO028S1	25-42.5837-72.0131-4-50-000	5.3	80	0.04	3.6	19	17	M	118	15500	420	13300	7.3	5200	20
MAHO031S1	25-42.6925-72.0186-4-50-000	6.2	50	0.12	3.7	7	.	33400	54	22100	340	5000	5.8	2300	60
MAHO032S1	25-42.7126-72.0608-4-50-000	4.9	30	0.02	7.6	37	29	55100	154	23500	780	15400	8.9	7400	40
MAHO033S1	25-42.6979-72.0867-4-50-000	6.0	50	0.08	9.1	49	26	M	232	23100	1960	13500	8.8	M	30
MAHO034S1	25-42.6639-72.0793-4-50-000	6.3	120	0.18	4.9	18	14	62100	149	18700	940	18500	1.5	6500	50
MAHO035S1	25-42.6337-72.0553-4-50-000	5.5	30	0.08	4.2	16	1	46E00	108	20100	380	11200	6.1	3900	40
MAHO036S1	25-42.5999-72.0457-4-50-000	4.5	25	0.00	4.7	20	14	69200	112	19700	960	20800	8.2	7300	50
MAHO037S1	25-42.6093-72.1053-4-50-000	6.3	70	0.32	6.3	24	25	49700	60	17100	1070	17700	6.1	M	30
MAHO038S1	25-42.6828-72.1160-4-50-000	6.2	40	0.08	3.6	12	9	76200	40	8000	1230	30100	4.4	5500	30
MAHO039S1	25-42.7026-72.1282-4-50-000	5.3	30	0.04	4.1	14	10	49900	.03	16300	660	19400	6.9	M	30

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

12

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
MAW0040S1	25-42.7143-72.1811-4-50-000	5.4	45	0.04	8.7	39	28	66700	256	19200	2170	23200	11.4	8700	40
MAW0041S1	25-42.6870-72.1782-4-50-000	5.5	40	0.04	5.7	16	13	71800	117	15000	1010	23200	7.7	8300	70
MAW0042S1	25-42.6973-72.2123-4-50-000	6.1	30	0.08	6.1	14	12	63100	91	17300	1150	17700	9.0	5100	60
MAW0043S1	25-42.6970-72.2622-4-50-000	5.4	30	0.08	3.4	11	9	71300	69	29400	1640	26200	12.8	8700	90
MAW0044S1	25-42.6844-72.2496-4-50-000	6.5	50	0.10	4.2	13	10	66500	81	30300	1860	22800	14.6	6300	90
MAW0045S1	25-42.6535-72.2193-4-50-000	6.6	40	0.12	3.3	15	19	M	65	30300	1500	20200	19.2	4800	30
MAW0046S1	25-42.6067-72.2217-4-50-000	7.0	45	0.16	3.5	9	12	79100	50	22200	1320	29500	7.7	5500	60
MAW0047S1	25-42.6581-72.1715-4-50-000	4.9	30	0.04	8.8	38	30	49100	260	24100	1320	17600	11.7	M	40
MAW0048S1	25-42.6348-72.1406-4-50-000	6.3	35	0.10	2.5	8	8	M	75	9700	M	M	1.9	2500	10
MAW0049S1	25-42.6088-72.1333-4-50-000	6.5	40	0.12	4.1	14	19	M	85	10300	M	27300	5.5	3000	40
MAW0050S1	25-42.6041-72.1644-4-50-000	5.7	60	0.06	4.6	25	28	M	144	15400	800	17800	8.5	8600	20
MAW0051S1	25-42.5836-72.1343-4-50-000	5.9	50	0.08	8.3	49	57	M	304	16600	M	M	8.7	M	M
MAW0052S1	25-42.5785-72.1716-4-50-000	6.2	30	0.04	4.7	18	37	70500	122	17200	1900	25400	7.2	11700	60
MAW0053S1	25-42.5671-72.2261-4-50-000	6.3	60	0.20	6.8	10	4	61800	57	20800	470	14300	12.3	4600	60
MAW0054S1	25-42.5833-72.2628-4-50-000	6.7	25	0.16	4.0	M	M	72500	M	M	1440	24900	M	6900	70
MAW0055S1	25-42.5509-72.1119-4-50-000	4.6	40	0.02	4.3	19	16	65900	147	26800	740	17200	0.2	8000	80
MAW0056S1	25-42.5474-72.1567-4-50-000	6.3	35	0.12	4.1	17	3	M	121	15200	M	26800	6.1	M	50
MAW0057S1	25-42.5096-72.1147-4-50-000	M	M	M	4.6	24	19	M	135	25300	M	19500	8.1	M	40
MAW0058S1	25-42.5466-72.1920-4-50-000	5.5	20	0.04	8.6	42	31	M	286	42400	2240	19900	13.3	14900	110
MAW0059S1	25-42.5410-72.2128-4-50-000	5.3	50	0.02	8.0	23	.	M	157	19200	870	18500	3.1	6600	60
MAW0060S1	25-42.5468-72.2393-4-50-000	6.5	35	0.16	11.4	37	18	71900	212	27600	2160	20900	11.5	10600	90
MAW0061S1	25-42.4899-72.1700-4-50-000	5.5	35	0.08	16.6	78	47	63300	388	36600	2170	18200	14.6	12600	80
MAW0062S1	25-42.4866-72.1295-4-50-000	5.4	30	0.04	7.7	43	118	72100	265	28900	2110	28000	11.9	21500	70
MAW0063S1	25-42.4716-72.1625-4-50-000	6.4	40	0.08	6.8	33	36	62500	226	23000	1260	20700	9.9	10000	60
MAW0064S1	25-42.4883-72.2160-4-50-000	5.6	50	0.06	7.3	33	17	M	214	23600	990	20600	12.8	7000	80
MAW0065S1	25-42.4887-72.2552-4-50-000	6.2	30	0.08	3.6	10	8	54300	48	26500	860	17900	12.4	3600	70
MAW0066S1	25-42.4564-72.2084-4-50-000	6.0	40	0.08	11.4	40	20	68000	213	22800	2080	20500	9.9	10100	80
MAW0067S1	25-42.4385-72.2052-4-50-000	6.5	50	0.08	10.2	33	21	M	176	24000	1200	17700	9.8	8400	50
MAW0068S1	25-42.4091-72.2106-4-50-000	5.8	100	0.20	2.1	7	4	44100	50	14400	230	6300	7.4	3600	60
MAW0069S1	25-42.3468-72.1849-4-50-000	6.6	70	0.34	4.9	17	28	M	153	30400	1320	16600	9.5	8700	80
MAW0070S1	25-42.4150-72.0961-4-50-000	6.8	60	0.20	10.9	52	48	57300	297	24100	1210	18000	8.5	10200	50
MAW0071S1	25-42.4359-72.0541-4-50-000	6.2	30	0.06	8.5	39	26	M	213	31500	940	14500	8.4	6600	50
MAW0072S1	25-42.4376-72.0834-4-50-000	6.6	50	0.29	12.0	56	48	M	337	21000	M	M	7.8	M	10
MAW0073S1	25-42.4606-72.0899-4-50-000	4.6	40	0.02	12.8	75	40	M	429	32900	1240	15900	12.7	11200	50
MAW0074S1	25-42.4718-72.1104-4-50-000	4.6	30	0.00	3.0	25	8	M	134	44100	730	17900	11.2	10300	130
MAW0075S1	25-42.4193-72.1203-4-50-000	6.4	100	0.18	3.7	18	18	61400	128	21700	690	18100	7.4	M	60
MAW0076S1	25-42.4344-72.1537-4-50-000	6.1	110	0.36	2.6	14	1	49900	85	24900	480	14500	7.8	5800	50
MAW0077S1	25-42.3765-72.1629-4-50-000	5.9	50	0.10	4.6	29	36	80800	286	40600	3140	24300	12.3	11500	90
MAW0078S1	25-42.3702-72.2222-4-50-000	6.6	50	0.20	7.9	51	30	M	373	53600	1990	16100	17.8	8400	80
MAW0079S1	25-42.3186-72.2509-4-50-000	7.1	45	0.20	2.6	8	9	80600	55	28700	1290	29900	15.3	7300	130
MAW0080S1	25-42.4075-72.0387-4-50-000	6.0	30	0.10	5.6	21	10	M	108	25700	4100	11900	7.2	4900	40
MAW0081S1	25-42.3917-72.0718-4-50-000	6.7	50	0.10	11.0	51	36	51700	291	31900	1120	13700	10.8	M	60
MAW0082S1	25-42.3725-72.1279-4-50-000	6.9	50	0.24	3.3	13	11	56400	98	22200	410	10700	7.4	5800	70
MAW0083S1	25-42.3476-72.1605-4-50-000	6.7	50	0.16	10.0	48	81	51400	363	30400	1470	19500	13.2	3200	70
MAW0084S1	25-42.3158-72.2082-4-50-000	7.2	120	0.40	7.3	39	49	67700	297	41600	1280	19900	15.5	10100	80
MAW0085S1	25-42.2547-72.1799-4-50-000	6.7	50	0.30	7.9	76	.	58500	405	43700	1220	13500	18.5	M	80
MAW0086S1	25-42.2648-72.1588-4-50-000	6.8	60	0.16	19.2	85	53	69500	487	43800	2410	12000	16.4	16800	100
MAW0087S1	25-42.2974-72.1422-4-50-000	7.2	80	0.20	17.5	59	33	M	364	28700	870	12100	10.3	M	60
MAW0088S1	25-42.3027-72.1828-4-50-000	7.2	70	0.24	8.7	46	33	M	286	31100	M	17300	11.6	M	10
MAW0089S1	25-42.2330-72.1356-4-50-000	6.7	90	0.52	8.1	36	17	M	214	20600	630	12400	8.7	M	50
MAW0090S1	25-42.1699-72.0638-4-50-000	7.0	50	0.22	18.5	86	29	M	474	27900	950	9500	10.6	M	40
MAW0091S1	25-42.1323-72.1020-4-50-000	7.1	270	0.64	5.2	32	14	M	209	66900	1130	7800	17.2	M	70
MAW0092S1	25-42.0530-72.0785-4-50-000	6.8	40	0.16	4.8	31	12	M	170	33900	1140	18900	13.6	8700	70

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

13

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
MAWO093S1	25-42.0553-72.0191-4-50-000	6.6	50	0.18	3.2	17	12	47000	119	36900	610	7600	9.5	M	60
MAWO094S1	25-42.0743-72.0050-4-50-000	6.8	100	0.32	6.5	31	16	M	159	24800	730	11300	5.0	3900	40
MAWO095S1	25-42.0923-72.0435-4-50-000	7.0	60	0.24	7.6	43	20	M	229	47900	1610	12000	19.5	7400	90
MAWO096S1	25-42.1200-72.0601-4-50-000	6.1	120	0.72	6.0	26	11	60100	180	26800	530	10100	10.2	M	70
MAWO097S1	25-42.1485-72.0587-4-50-000	6.8	30	0.14	3.7	22	10	M	160	39200	M	10000	12.5	M	60
MAWO098S1	25-42.2135-72.0285-4-50-000	6.4	160	0.36	13.9	77	31	41000	382	30400	740	8700	2.4	7000	40
MAWO099S1	25-42.1702-72.0884-4-50-000	6.5	50	0.14	3.5	12	6	M	77	70100	M	9100	6.3	M	70
MAWO100S1	25-42.1698-72.1338-4-50-000	6.7	30	0.12	3.5	13	8	39700	76	19100	530	7100	6.4	3700	50
MAWO101S1	25-42.2056-72.1227-4-50-000	6.7	45	0.24	5.2	22	12	42100	138	22600	620	8400	7.3	M	50
MAWO102S1	25-42.2002-72.1623-4-50-000	6.7	35	0.16	14.4	94	47	94500	620	42000	1110	11000	5.1	M	80
MAWO103S1	25-42.1678-72.1489-4-50-000	6.8	40	0.14	9.3	54	2	89700	331	35800	920	9500	11.9	8800	100
MAWO104S1	25-42.1745-72.1923-4-50-000	6.2	130	0.10	5.0	33		78900	178	27300	690	15300	10.3	6600	80
MAWO105S1	25-42.2004-72.1881-4-50-000	6.8	40	0.18	7.8	53	30	83100	297	40700	1290	12400	2.7	10800	110
MAWO106S1	25-42.2037-72.2271-4-50-000	7.1	85	0.38	4.7	34	26	58900	222	39500	910	15000	14.1	6000	70
MAWO107S1	25-42.2236-72.2247-4-50-000	7.1	50	0.24	9.0	82	53	81500	451	71800	2440	16400	30.8	M	100
MAWO108S1	25-42.2280-72.1813-4-50-000	6.2	40	0.30	8.9	54		M	308	30700	M	12900	0.2	M	60
MAWO109S1	25-42.2419-72.1150-4-50-000	7.0	90	0.34	4.5	16	9	M	99	16700	660	12700	6.5	3700	40
MAWO110S1	25-42.2594-72.1073-4-50-000	6.9	80	0.26	8.8	40	22	M	232	32800	940	13700	10.0	7800	90
MAWO111S1	25-42.2404-72.0561-4-50-000	6.6	60	0.26	4.1	15	7	57000	210	28400	520	10200	9.1	M	70
MAWO112S1	25-42.3028-72.0628-4-50-000	6.1	40	0.12	9.7	62	27	50700	326	19500	460	12300	8.8	5400	40
MAWO113S1	25-42.3153-72.0585-4-50-000	6.8	80	0.56	8.6	39	24	57400	240	28000	670	9700	8.9	7900	70
MAWO114S1	25-42.3243-72.1031-4-50-000	6.1	60	0.12	3.2	10	6	54000	55	19300	410	10000	5.6	5300	70
MAWO115S1	25-42.2971-72.1024-4-50-000	6.6	60	0.12	6.6	28	16	58900	205	31000	710	11500	8.2	5000	60
MAWO116S1	25-42.3204-72.1471-4-50-000	6.8	50	0.12	14.0	78	64	M	491	29900	M	15700	4.2	5900	10
MAWO117S1	25-42.3441-72.1147-4-50-000	5.3	40	0.06	10.0	51	31	53200	309	22100	490	12300	8.4	M	60
MAWO118S1	25-42.3750-72.0297-4-50-000	6.9	50	0.12	7.4	M	M	45800	M	M	790	12600	M	M	40
MAWO119S1	25-42.3597-72.0669-4-50-000	5.4	30	0.04	3.9	M	M	58800	M	M	350	14700	M	5200	50
MAWO120S1	25-42.3340-72.0522-4-50-000	4.8	30	0.00	7.6	34	20	47000	199	18500	750	13800	7.5	7500	50
MAWO121S1	25-42.3413-72.0037-4-50-000	M	M	M	3.5	10		81200	58	24400	530	18500	3.2	4600	90
MAWO122S1	25-42.3665-72.0091-4-50-000	6.1	30	0.30	9.0	37	24	66000	197	31000	950	14800	9.1	7500	70
MAWO131S1	25-42.4787-72.0301-4-50-000	6.3	55	0.16	6.5	28	16	69800	154	17000	960	21500	6.1	6400	60
MAWO132S1	25-42.4825-72.0764-4-50-000	5.9	30	0.06	4.2	16	8	56700	105	26700	430	9800	8.5	4800	60
MAWO133S1	25-42.4953-72.0228-4-50-000	6.0	30	0.08	1.6	6	2	21300	19	8200	170	4000	2.5	1900	30
MAWO134S1	25-42.5201-72.0290-4-50-000	4.3	30	0.00	2.0	4	7	28400	26	7500	210	8000	2.3	2800	30
MAWO180S1	25-42.1625-72.0051-4-50-000	6.7	70	0.28	9.1	34	17	43900	198	16400	850	10400	7.4	M	40
MAWO181S1	25-42.1260-72.0031-4-50-000	6.9	280	0.30	7.6	30	2	72500	188	27700	1300	16000	10.1	7700	80
MAWO182S1	25-42.1046-72.0098-4-50-000	6.6	60	0.28	7.4	39	27	41000	207	27000	930	10600	12.4	M	30
MAWO263S1	25-42.2280-72.0122-4-50-000	6.3	70	0.32	11.4	41	23	M	265	23400	M	10700	10.0	3900	30
MAWO264S1	25-42.3060-72.0358-4-50-000	5.4	65	0.16	7.7	25	17	M	171	28300	M	15500	7.9	M	M
MAWO265S1	25-42.2791-72.0252-4-50-000	6.6	160	0.85	6.2	M	M	59800	M	M	930	12700	M	5300	60
NHCH001S1	33-42.8919-72.1059-4-50-000	5.7	18	0.04	6.8	43		M	272	36000	M	M	13.3		10
NHCH002S1	33-42.9036-72.0916-4-50-000	6.5	81	0.06	5.9	21		M	155	28500		85900	11.3		M
NHCH003S1	33-42.9192-72.0465-4-50-000	6.8	89	0.14	6.3	33		M	192	29300	450	M	11.4		M
NHCH004S1	33-42.8815-72.0233-4-50-000	6.8	33	0.12	6.7	36	17	M	214	31200		M	12.4		M
NHCH005S1	33-42.8678-72.0613-4-50-000	6.0	27	0.04	9.2	46	5	M	269	38200		5300	3.7	13900	30
NHCH006S1	33-42.8325-72.0852-4-50-000	6.3	57	0.06	5.2	M	M	M	M	M		M	M		M
NHCH007S1	33-42.8195-72.0610-4-50-000	6.2	47	0.06	5.5	37		M	251	41300	660	M	14.4	6000	M
NHCH008S1	33-42.8024-72.0577-4-50-000	5.8	37	0.04	4.1	22	13	M	144	16400	490	M	7.3		10
NHCH009S1	33-42.8363-72.0277-4-50-000	6.5	76	0.22	6.6	39	24	M	233	30600	-80	M	11.6	6700	20
NHCH015S1	33-42.7717-72.0117-4-50-000	5.5	31	0.04	5.9	31	24	M	201	23000	480	6500	4.2	11400	M
NHCH016S1	33-42.7259-72.0354-4-50-000	5.0	26	0.02	2.8	18	15	M	115	19900	690	6400	7.3		20
NHCH017S1	33-42.7706-72.0713-4-50-000	5.3	105	0.04	4.8	28		M	145	9100	380	M	5.3		M
NHCH018S1	33-42.7425-72.0951-4-50-000	5.6	37	0.04	3.1	12	9	M	68	11500		M	4.7		-30

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

14

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL FPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
NHCH019S1	33-42.7349-72.1284-4-50-000	5.5	60	0.04	6.0	18	21	M	134	23200	.	M	8.8	M	M
NHCH020S1	33-42.7639-72.1339-4-50-000	5.7	145	0.10	4.3	15	13	M	94	14400	.	M	6.9	.	M
NHCH021S1	33-42.7593-72.1869-4-50-000	4.5	47	0.00	6.3	17	14	M	136	40800	.	M	17.4	9200	20
NHCH022S1	33-42.7751-72.1994-4-50-000	4.8	30	0.00	6.1	23	11	M	136	21100	.	M	9.1	M	M
NHCH023S1	33-42.7942-72.1268-4-50-000	5.3	27	0.02	6.7	36	17	M	244	28000	M	M	2.0	.	40
NHCH024S1	33-42.8120-72.1188-4-50-000	6.7	43	0.18	2.9	11	.	55700	85	18100	1150	17200	7.8	7600	40
NHCH025S1	33-42.9407-72.0319-4-50-000	6.2	36	0.06	10.6	84	41	M	506	53200	3100	13600	5.0	M	60
NHCH026S1	33-42.9418-72.0953-4-50-000	5.8	89	0.12	4.8	21	12	45300	128	25400	1420	15700	10.4	5700	40
NHCH027S1	33-42.9726-72.1068-4-50-000	6.6	27	0.08	7.2	34	12	M	209	37700	2510	M	13.7	M	M
NHCH028S1	33-42.9342-72.1565-4-50-000	6.2	44	0.06	8.3	49	17	M	293	47500	M	15100	20.0	4300	M
NHCH029S1	33-42.9341-72.1254-4-50-000	6.5	28	0.08	6.4	47	19	M	293	49500	2280	11200	19.4	M	M
NHCH043S1	33-42.9975-72.1961-4-50-000	6.3	48	0.08	3.5	12	9	M	84	39500	4440	18100	15.8	9500	60
NHCH050S1	33-42.9989-72.1855-4-50-000	6.7	66	0.08	9.2	40	.	51200	261	33300	2040	12900	4.1	9900	60
NHCH051S1	33-42.9897-72.2440-4-50-000	6.4	47	0.08	7.5	30	.	50500	175	28200	2730	16300	10.9	5200	50
NHCH064S1	33-42.9958-72.3234-4-50-000	6.9	42	0.16	3.7	9	6	M	54	29100	3140	15000	10.8	8600	60
NHCH077S1	33-42.9909-72.4432-4-50-000	7.5	117	0.32	2.7	10	4	45100	98	39700	4100	10700	1.8	7500	50
NHCH078S1	33-42.9923-72.3892-4-50-000	7.2	52	0.22	2.6	12	6	57000	78	33900	4110	16000	10.6	9600	90
NHCH079S1	33-42.7522-72.3123-4-50-000	6.9	40	0.18	2.5	9	9	62500	56	32800	1820	24200	17.9	5800	100
NHCH080S1	33-42.7600-72.3205-4-50-000	6.8	34	0.20	2.2	7	10	52800	57	30700	1390	21100	15.8	6300	70
NHCH081S1	33-42.7340-72.2293-4-50-000	5.7	33	0.06	6.3	24	14	71700	162	36200	1820	25700	18.5	5300	80
NHCH082S1	33-42.7522-72.2212-4-50-000	5.5	25	0.06	2.9	12	15	50100	99	37900	1710	18000	25.1	M	70
NHCH083S1	33-42.7724-72.2507-4-50-000	6.9	27	0.16	11.4	M	M	59600	M	M	1760	17500	M	6400	70
NHCH084S1	33-42.7913-72.2681-4-50-000	6.9	48	0.12	6.1	19	19	45800	115	31700	2850	15600	19.2	M	60
NHCH085S1	33-42.8217-72.2634-4-50-000	6.7	57	0.18	3.7	11	16	50400	75	22900	1720	18200	17.6	6500	50
NHCH086S1	33-42.8508-72.2531-4-50-000	6.8	82	0.12	6.0	33	.	M	180	31800	2340	18000	15.8	5000	30
NHCH087S1	33-42.8809-72.2327-4-50-000	7.1	39	0.18	5.7	26	13	M	181	48900	3120	17600	18.6	.	50
NHCH088S1	33-42.8685-72.2095-4-50-000	6.8	71	0.08	9.2	30	17	M	207	35800	4150	18200	7.7	M	50
NHCH089S1	33-42.7933-72.3022-4-50-000	6.1	28	0.10	2.8	10	15	M	51	38800	2980	16500	23.7	9200	70
NHCH090S1	33-42.8314-72.2880-4-50-000	6.6	48	0.26	4.4	14	14	78500	99	29100	2290	27200	15.2	6200	80
NHCH091S1	33-42.8459-72.3265-4-50-000	7.3	72	0.28	2.8	11	11	M	78	45100	4330	14500	29.1	8500	60
NHCH092S1	33-42.8718-72.3400-4-50-000	6.5	58	0.32	3.9	15	8	M	105	22900	M	23800	10.6	.	10
NHCH093S1	33-42.8754-72.2756-4-50-000	6.6	76	0.16	4.1	16	10	63300	107	23700	1710	21900	1.8	3700	50
NHCH094S1	33-42.9171-72.2957-4-50-000	7.1	224	0.50	3.3	9	10	47500	82	24900	1760	16200	11.3	M	50
NHCH095S1	33-42.9593-72.2657-4-50-000	6.9	122	0.14	4.8	16	7	46500	91	30800	3060	18100	13.1	M	50
NHCH096S1	33-42.9950-72.2579-4-50-000	5.9	100	0.06	4.2	22	13	50300	107	48100	3340	14300	19.9	5400	50
NHCH097S1	33-42.9757-72.2433-4-50-000	6.6	45	0.08	5.2	17	1	M	114	28000	M	23100	13.4	M	70
NHCH098S1	33-42.9757-72.2076-4-50-000	6.7	50	0.08	10.0	51	1	M	320	39900	M	11200	14.6	M	M
NHCH099S1	33-42.9379-72.2428-4-50-000	6.7	50	0.08	7.5	28	13	M	187	31100	M	17200	13.1	M	M
NHCH100S1	33-42.9572-72.2164-4-50-000	5.3	20	0.02	7.3	33	16	M	230	33500	2280	25700	13.9	7700	60
NHCH101S1	33-42.9151-72.1914-4-50-000	6.4	46	0.06	9.3	31	9	49000	215	35800	2190	12200	12.8	M	70
NHCH102S1	33-42.9113-72.1718-4-50-000	6.5	580	0.20	18.5	100	29	48500	576	47600	3590	12300	19.6	18300	50
NHCH103S1	33-42.8767-72.1795-4-50-000	6.5	30	0.08	3.0	14	6	63900	88	21900	1130	21900	10.1	3300	50
NHCH104S1	33-42.8710-72.1518-4-50-000	5.9	50	0.10	4.5	22	12	M	147	23300	950	19300	10.4	3300	40
NHCH105S1	33-42.8394-72.1381-4-50-000	5.5	55	0.04	2.2	9	.	72900	37	18100	1100	24800	8.0	5200	40
NHCH106S1	33-42.8234-72.1851-4-50-000	5.8	35	0.06	7.3	29	11	49700	135	26900	2690	16600	12.7	5600	50
NHCH107S1	33-42.8454-72.1811-4-50-000	5.7	48	0.06	8.2	32	13	46800	163	24300	2240	16700	10.3	6800	40
NHCH108S1	33-42.9793-72.3023-4-50-000	6.6	50	0.22	2.8	10	6	42400	75	30000	1450	15700	8.2	3600	40
NHCH109S1	33-42.9527-72.3239-4-50-000	7.0	205	1.00	5.5	24	26	61300	148	23400	1440	22200	12.2	7300	60
NHCH110S1	33-42.9374-72.3408-4-50-000	7.3	86	0.32	2.6	8	8	49100	39	21700	1910	19400	13.4	3700	40
NHCH111S1	33-42.9397-72.3924-4-50-000	7.4	61	0.36	3.1	9	2	65500	86	27100	2370	25800	11.2	7300	80
NHCH112S1	33-42.8957-72.4266-4-50-000	5.8	179	0.12	2.7	9	5	46400	60	24500	1520	16500	9.7	M	40
NHCH113S1	33-42.9197-72.4121-4-50-000	6.8	102	0.14	3.5	14	1	M	101	24700	2460	21800	12.0	8900	60
NHCH114S1	33-42.9452-72.4313-4-50-000	7.2	109	0.26	3.0	13	11	65100	75	39400	4660	21000	17.7	12100	80

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

15

SRL	I.D.	DOE	I.D.	PH	COND.	AKMXD	U	TH	HF	AL	CE	FE	MN	NA	SC	TI	V
*****					UM/CM	MEQ/L	PPM	PPM	PPM	PPM	PPM	PPM	PPM	PPM	PPM	PPM	PPM
NHCHI155S1	33-42.9718-	72.4647-4-50-000	7.5	118	0.32	3.4	15	13		M	98	51500	4540	10100	14.4	12000	60
NHCHI165S1	33-42.9551-	72.4859-4-50-000	7.2	58	0.20	2.1	11	8		57800	61	29500	1970	15800	1.9	9900	60
NHCHI175S1	33-42.9350-	72.4730-4-50-000	7.2	50	0.22	2.9	10			39200	94	43800	2010	10000	13.0	10200	40
NHCHI185S1	33-42.9046-	72.4782-4-50-000	6.8	203	0.22	3.5	18			44700	125	32500	1370	13700	11.0	1200	60
NHCHI195S1	33-42.8802-	72.4888-4-50-000	7.3	85	0.20	2.7	15			58500	99	22200	1360	20400	7.8	9600	60
NHCHI205S1	33-42.8650-	72.4917-4-50-000	7.1	68	0.16	4.6	18	11		42200	127	35400	2360	11600	12.0	9200	50
NHCHI215S1	33-42.8641-	72.5190-4-50-000	6.9	40	0.20	2.2	12	6		38300	90	37500	1620	9100	12.4	8800	50
NHCHI225S1	33-42.8783-	72.5385-4-50-000	7.3	68	0.30	2.1	9			40600	90	38500	1940	8600	13.1	10300	60
NHCHI235S1	33-42.9034-	72.5009-4-50-000	6.7	63	0.16	2.4	8	1		59200	66	24600	1510	20100	8.5	8500	60
NHCHI245S1	33-42.9260-	72.5130-4-50-000	6.6	41	0.14	3.4	14	10		44100	104	44700	1450	11700	12.6	M	60
NHCHI255S1	33-42.8193-	72.5253-4-50-000	6.7	72	0.22	2.5	13			50000	81	37400	1100	15900	14.9	7300	50
NHCHI265S1	33-42.7985-	72.5193-4-50-000	7.2	74	0.30	3.9	8	42		64100	96	50200	3260	20000	5.4	19200	110
NHCHI275S1	33-42.7316-	72.4505-4-50-000	7.0	90	0.14	6.5	26	49		46000	170	57200	3460	14100	9.5	M	80
NHCHI285S1	33-42.7225-	72.4370-4-50-000	7.0	118	0.20	2.1	6	6		49500	46	20400	1180	18300	10.5	3800	40
NHCHI295S1	33-42.8052-	72.4767-4-50-000	4.8	19	0.00	3.2	8	4		M		32400	2510	19000	10.9	7600	70
NHCHI305S1	33-42.7852-	72.4699-4-50-000	6.6	36	0.10	6.1	28			56200	162	24300	1290	14900	9.7	M	70
NHCHI315S1	33-42.7874-	72.4479-4-50-000	5.2	18	0.02	4.1	28			57700	139	17400	1110	18500	7.7	3900	40
NHCHI325S1	33-42.7869-	72.4297-4-50-000	6.6	30	0.14	5.1	41			68200	260	37900	3240	22900	14.5	6900	50
NHCHI335S1	33-42.7579-	72.3857-4-50-000	5.9	47	0.08	4.7	29			50700	185	31600	1690	17600	12.8	M	50
NHCHI345S1	33-42.7492-	72.3633-4-50-000	6.8	60	0.22	4.2	24	11		47600	126	18900	1360	19000	3.2	3800	40
NHCHI355S1	33-42.7285-	72.3480-4-50-000	6.7	36	0.16	3.2	12	12		54900	77	35500	1460	18600	4.6	M	80
NHCHI365S1	33-42.7896-	72.3570-4-50-000	6.9	32	0.18	4.4	19	22		72700	124	53200	4810	24100	0.6	14200	140
NHCHI375S1	33-42.7975-	72.3745-4-50-000	6.5	34	0.16	6.7	37			54900	224	43000	3580	16100	16.7	M	60
NHCHI385S1	33-42.8293-	72.3698-4-50-000	6.4	62	0.20	4.8	24			48700	163	26600	2290	15400	11.2	5500	40
NHCHI395S1	33-42.8247-	72.3712-4-50-000	6.1	32	0.10	4.2	21	5		M	110	29100	2270	14700	12.0	5500	60
NHHI0155S1	33-43.0000-	72.0327-4-50-000	6.1	60	0.12	7.4	54	31		50700	297	30500	1640	12500	12.8	11600	30
NHHI0635S1	33-42.9538-	72.0448-4-50-000	6.1	30	0.08	10.0	78			M	409	41400	1920	14200	17.5	13000	70
NYAL1015S1	36-42.4878-	73.9826-4-50-000	7.7	175	1.40	2.6	9	22		M	79	25600	M	M	6.4	M	M
NYAL1025S1	36-42.4803-	73.9235-4-50-000	7.6	145	1.30	3.1	11			M	63	36700	M	M	9.3	M	M
NYAL1035S1	36-42.4721-	73.8953-4-50-000	7.8	210	2.30	3.0	8	11		M	81	27200	M	M	8.8	1900	M
NYAL1045S1	36-42.4695-	73.8513-4-50-000	7.9	450	3.80	3.0	9	19		M	54	29000	900	8600	9.9	M	60
NYAL1055S1	36-42.4895-	73.7905-4-50-000	7.9	1150	7.40	2.5	8	5		M	83	36400	M	M	10.4	M	M
NYAL1215S1	36-42.6072-	73.7718-4-50-000	7.8	2000	4.10	3.6	7	46		50100	66	33600	1160	13600	5.1	12800	80
NYAL1225S1	36-42.6083-	73.7967-4-50-000	8.2	465	3.30	4.4	9	54		25200	52	28100	620	7400	4.4	10300	50
NYAL1235S1	36-42.5835-	73.7679-4-50-000	7.6	425	3.40	5.1	17	107		M	108	57100	M	M	11.1	M	20
NYAL1245S1	36-42.5677-	73.8154-4-50-000	7.6	660	3.20	1.5	3	12		21700	40	16900	380	5900	4.0	3700	20
NYAL1255S1	36-42.5414-	73.7932-4-50-000	7.3	600	1.30	2.0	5	31		M	37	22900	M	M	5.2	M	20
NYAL1265S1	36-42.5117-	73.8087-4-50-000	7.9	460	2.90	3.1	7	44		39900	107	59300	780	9100	12.3	8900	70
NYAL1275S1	36-42.5437-	73.8417-4-50-000	7.4	1000	6.70	2.7	7	19		46300	76	39900	830	8300	9.6	5500	80
NYAL1285S1	36-42.5271-	73.8467-4-50-000	7.3	900	3.20	1.9	3	5		32000	29	21800	350	6600	5.5	3600	40
NYAL1295S1	36-42.5263-	73.9120-4-50-000	7.6	201	1.60	3.1	12	11		82500	79	41100	1080	10300	12.8	8100	150
NYAL1305S1	36-42.5534-	73.8892-4-50-000	7.9	280	2.10	1.7	3	14		44400	87	19800	460	11400	5.9	5500	70
NYAL1315S1	36-42.5392-	73.9424-4-50-000	6.7	210	1.70	3.3	9	12		M	72	37500	M	M	13.1	M	
NYAL1325S1	36-42.5165-	73.9604-4-50-000	7.1	210	1.50	2.5	5	12		M	45	22500	M	11900	6.1	M	70
NYAL1335S1	36-42.5340-	73.9987-4-50-000	7.3	97	0.65	2.7	7	12		M	57	38300	M	M	9.7	2500	
NYAL1345S1	36-42.6003-	73.9913-4-50-000	7.9	590	2.80	4.1	11	12		M	83	57000	M	9300	18.0	M	180
NYAL1355S1	36-42.5737-	73.9608-4-50-000	7.8	530	2.80	3.4	8	18		M	77	37900	M	M	2.1	8200	20
NYAL1365S1	36-42.5891-	73.9158-4-50-000	7.5	400	2.80	3.5	9	2		54900	126	46800	1670	11300	12.6	6800	80
NYAL1375S1	36-42.5867-	73.8933-4-50-000	7.6	312	1.80	4.2	11	31		M	95	43100	M	M	9.4	M	M
NYAL1385S1	36-42.5886-	73.8555-4-50-000	7.9	395	2.70	3.5	9	45		M	96	37000	M	15800	6.8	M	80
NYAL1395S1	36-42.6124-	73.8621-4-50-000	7.8	700	4.80	2.9	8	15		M	77	37100	1320	9000	9.3	5700	70
NYAL1405S1	36-42.6071-	73.8989-4-50-000	7.7	410	2.90	2.9	12	18		M	71	47000	M	M	11.9	M	M
NYAL1415S1	36-42.6291-	73.9188-4-50-000	7.7	640	2.50	3.1	9	36		59400	124	52000	1260	15400	12.4	10100	90

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

16

SRL I.D. *****	DOE I.D.		PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
NYAL142S1	36-42.6297-	73.8848-4-50-000	7.5	920	5.50	2.8	5	11	45300	64	23800	1610	9100	6.6	4500	60
NYAL143S1	36-42.6403-	73.8442-4-50-000	M	M	M	2.4	7	6	M	37	18700	3350	11900	3.0	5400	70
NYAL144S1	36-42.6594-	73.8288-4-50-000	8.1	890	0.00	11.9	40	286	28800	225	120400	1850	7700	17.0	37700	180
NYAL145S1	36-42.6640-	73.8954-4-50-000	8.6	500	2.20	2.5	4	2	61800	68	31400	1980	10100	8.7	6100	110
NYAL146S1	36-42.7104-	73.8398-4-50-000	7.8	445	2.80	0.9	3	5	16800	9	10600	250	6700	2.8	1800	20
NYAL147S1	36-42.7344-	73.9096-4-50-000	8.1	460	1.90	6.4	12	108	34700	125	89700	1910	8700	12.1	34500	220
NYAL148S1	36-42.7134-	73.8991-4-50-000	7.9	311	1.80	15.6	21	210	28400	149	103900	1930	6600	17.9	33200	190
NYAL149S1	36-42.7315-	73.9600-4-50-000	7.8	425	1.90	4.1	7	51	31200	70	37500	1070	8700	8.0	10300	60
NYAL150S1	36-42.7491-	73.9841-4-50-000	8.1	1000	3.10	6.2	18	94	37500	117	47100	1640	10300	10.1	17300	80
NYAL151S1	36-42.7055-	73.9761-4-50-000	8.2	580	2.20	3.3	9	23	55400	83	34400	570	10500	9.5	M	90
NYAL152S1	36-42.6761-	73.9526-4-50-000	8.1	400	2.30	2.4	5	28	26200	58	25200	530	7800	6.0	8100	40
NYAL153S1	36-42.6464-	73.9579-4-50-000	7.8	440	2.40	2.7	6	30	50200	68	29500	640	12900	9.1	7100	80
NYAL154S1	36-42.6380-	73.9705-4-50-000	7.6	410	2.50	3.1	8	28	47600	76	40200	460	12000	10.3	6600	60
NYAL155S1	36-42.6624-	73.9858-4-50-000	7.4	360	3.40	3.2	13	16	53700	80	43300	570	8700	12.0	M	90
NYAL156S1	36-42.7559-	73.9050-4-50-000	7.7	335	3.50	4.1	11	38	49400	68	36600	3020	14100	7.1	11400	80
NYAL157S1	36-42.7439-	73.8436-4-50-000	7.7	460	2.90	7.3	14	101	32600	108	51000	1300	8700	10.2	18200	90
NYAL158S1	36-42.7369-	73.8097-4-50-000	7.8	590	3.40	3.2	6	36	41900	53	42900	2710	11600	6.6	8900	70
NYAL159S1	36-42.7374-	73.7754-4-50-000	8.0	510	3.20	4.2	13	58	28700	66	39000	.	8800	6.1	10200	70
NYAL160S1	36-42.7751-	73.7637-4-50-000	7.9	700	4.30	3.0	7	53	20000	70	41300	820	7000	6.7	M	80
NYAL161S1	36-42.7616-	73.8627-4-50-000	7.7	600	3.00	4.0	13	65	16400	83	33900	1150	7500	6.6	15400	70
NYAL162S1	36-42.7126-	73.7435-4-50-000	7.4	420	2.70	12.5	35	251	32700	210	112900	2360	7300	19.9	M	180
NYAL163S1	36-42.7474-	73.7207-4-50-000	7.5	570	3.20	3.9	10	15	66500	89	37300	950	8200	10.5	5800	100
NYAL164S1	36-42.7666-	73.7172-4-50-000	7.9	720	2.80	2.1	5	18	19900	76	27300	720	7500	5.9	M	50
NYC0001S1	36-42.1063-	73.5405-4-50-000	6.7	185	1.85	2.8	8	16	57700	108	63100	1160	8800	14.0	9300	70
NYC0002S1	36-42.1543-	73.5203-4-50-000	7.7	220	1.95	2.1	9	2	73100	81	23000	1230	13100	5.6	6900	70
NYC0003S1	36-42.1471-	73.5005-4-50-000	8.1	150	1.60	2.9	8	9	54400	88	34900	1110	7900	9.3	4800	60
NYC0004S1	36-42.1788-	73.4832-4-50-000	7.9	240	2.30	2.6	10	10	74000	103	31900	3210	11800	2.5	7000	80
NYC0005S1	36-42.1931-	73.5111-4-50-000	8.2	140	1.30	4.1	M	M	M	M	M	8900	5900	M	3400	70
NYC0006S1	36-42.2051-	73.4974-4-50-000	8.6	260	2.80	2.1	M	M	M	M	M	1580	6400	M	4500	40
NYC0007S1	36-42.2435-	73.4799-4-50-000	8.2	100	0.70	2.5	9	10	M	95	42000	790	14200	10.3	.	40
NYC0008S1	36-42.2377-	73.5117-4-50-000	8.1	100	0.80	6.4	17	12	85700	255	46700	2200	15000	12.0	M	30
NYC0009S1	36-42.2295-	73.5670-4-50-000	8.2	60	0.85	2.8	19	19	M	220	58600	640	12000	13.3	.	M
NYC0010S1	36-42.2137-	73.5596-4-50-000	8.1	70	0.50	3.4	13	10	79700	141	40800	2000	15000	10.2	M	M
NYC0011S1	36-42.2132-	73.5878-4-50-000	8.0	80	0.60	4.0	11	16	M	142	44200	M	11300	9.9	.	.
NYC0012S1	36-42.2373-	73.6243-4-50-000	7.9	95	0.50	3.2	16	14	M	244	45600	860	11700	11.5	.	M
NYC0013S1	36-42.2125-	73.6406-4-50-000	7.5	150	0.54	2.8	13	10	M	99	45300	400	14300	10.5	.	10
NYC0014S1	36-42.2333-	73.6329-4-50-000	7.7	150	1.14	2.6	13	16	M	112	34600	710	17200	7.8	2100	M
NYC0015S1	36-42.2331-	73.6738-4-50-000	8.0	245	0.80	2.4	6	12	64700	45	19100	1160	18800	1.2	5700	60
NYC0016S1	36-42.2234-	73.7330-4-50-000	7.9	275	2.10	2.0	5	11	44600	54	37500	1100	8700	7.2	5300	80
NYC0017S1	36-42.2044-	73.6982-4-50-000	8.5	230	1.80	2.6	7	17	47600	100	36600	1520	11200	9.0	M	60
NYC0018S1	36-42.1963-	73.7404-4-50-000	8.6	120	1.60	2.0	3	14	51600	64	18000	850	17100	4.9	5600	50
NYC0019S1	36-42.1652-	73.7363-4-50-000	8.0	215	1.55	2.4	9	19	M	76	44500	3930	11700	9.2	2600	60
NYC0020S1	36-42.1357-	73.7222-4-50-000	8.0	150	0.85	3.1	8	10	64800	83	32400	960	15200	3.7	5800	70
NYC0021S1	36-42.1624-	73.7067-4-50-000	7.9	140	0.90	3.0	8	10	79500	103	32200	1400	15200	9.2	6200	90
NYC0022S1	36-42.1395-	73.6719-4-50-000	8.0	140	0.75	3.7	9	19	80300	106	50600	1350	15700	11.1	6500	70
NYC0023S1	36-42.1421-	73.6503-4-50-000	7.9	135	0.75	3.9	9	.	62700	111	41900	1940	9700	8.9	5000	70
NYC0024S1	36-42.1738-	73.6446-4-50-000	7.8	95	0.55	5.2	15	18	75300	129	42500	1220	17000	3.8	6200	70
NYC0025S1	36-42.1551-	73.6124-4-50-000	7.8	100	0.55	3.1	10	16	74200	111	39100	1420	13900	1.9	6900	90
NYC0026S1	36-42.1553-	73.5698-4-50-000	7.9	150	0.90	4.0	9	8	M	91	33200	M	12600	2.6	M	80
NYC0027S1	36-42.1351-	73.5380-4-50-000	7.8	210	0.26	2.9	10	15	M	111	17700	M	11100	5.9	M	M
NYC0028S1	36-42.1133-	73.5684-4-50-000	6.1	170	1.60	2.6	15	14	M	92	39700	M	12400	8.7	M	70
NYC0029S1	36-42.1015-	73.5902-4-50-000	7.5	240	2.70	2.5	8	11	55400	96	31500	2080	9500	8.2	4100	60
NYC0030S1	36-42.1326-	73.6190-4-50-000	7.5	110	1.00	3.4	11	13	53400	152	39900	1990	9200	9.3	11800	70

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS---

ALBANY

SHEET

17

SRL I.D. *****	DOE I.O.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL FPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
NYC0031S1	36-42.1117- 73.6466-4-50-000	7.5	115	1.10	2.7	8	10	43500	71	53400	660	8300	3.9	4200	40
NYC0032S1	36-42.0902- 73.6760-4-50-000	7.7	135	1.05	2.5	6	9	63000	82	20300	1180	13100	4.7	5800	70
NYC0033S1	36-42.1083- 73.6961-4-50-000	7.7	160	1.35	2.7	11	15	44500	137	45600	940	9100	11.7	4700	60
NYC0034S1	36-42.1369- 73.7502-4-50-000	7.6	150	1.55	2.5	10	.	34900	26	34900	310	7700	7.7	3300	50
NYC0035S1	36-42.0753- 73.7276-4-50-000	7.8	185	1.05	2.7	8	11	M	81	34200	3240	8900	8.9	M	50
NYC0036S1	36-42.0511- 73.7328-4-50-000	7.9	95	0.60	3.6	14	22	87100	133	49000	420	14500	15.1	M	50
NYC0037S1	36-42.0292- 73.7331-4-50-000	7.8	85	0.40	2.8	9	11	M	80	31600	M	10700	7.4	M	M
NYC0038S1	36-42.0051- 73.6778-4-50-000	8.1	180	1.20	3.2	14	15	56200	156	36100	1020	10300	9.2	M	60
NYC0039S1	36-42.0209- 73.6399-4-50-000	8.0	110	0.65	4.0	9	12	60700	98	25700	570	13900	7.4	5600	70
NYC0040S1	36-42.0334- 73.6212-4-50-000	8.1	350	3.30	2.4	12	10	54200	89	25300	500	13600	6.3	4500	50
NYC0041S1	36-42.0074- 73.5945-4-50-000	8.4	320	3.10	2.4	12	14	65000	106	34200	1380	12700	8.9	6300	70
NYC0042S1	36-42.0119- 73.5689-4-50-000	8.3	370	4.40	2.5	10	12	66200	93	31900	1130	8400	3.2	6500	60
NYC0043S1	36-42.0311- 73.5778-4-50-000	8.9	320	3.20	1.8	6	7	46900	54	21900	2700	7100	5.5	3500	50
NYC0044S1	36-42.0677- 73.5323-4-50-000	8.2	310	3.00	2.6	9	.	M	106	39700	820	8300	4.5	9500	40
NYC0045S1	36-42.0655- 73.5686-4-50-000	8.3	440	3.10	2.9	10	22	M	118	57600	M	9000	10.9	1400	30
NYC0046S1	36-42.0635- 73.6069-4-50-000	8.4	320	3.80	2.6	15	22	52300	151	25500	880	13900	5.8	10200	60
NYC0047S1	36-42.0788- 73.6270-4-50-000	8.4	95	0.70	4.1	9	10	72000	95	32700	2670	10300	8.8	6500	90
NYC0048S1	36-42.0564- 73.6324-4-50-000	M	M	M	3.1	10	12	45300	112	30400	1350	9800	1.2	M	50
NYC0049S1	36-42.0537- 73.6925-4-50-000	7.7	160	1.45	3.2	10	9	M	98	73300	8330	8100	9.3	4500	50
NYC0050S1	36-42.1425- 73.7727-4-50-000	7.2	120	1.55	2.5	6	21	37500	60	22300	610	10500	4.4	4100	50
NYC0051S1	36-42.1606- 73.7692-4-50-000	7.7	210	1.70	1.1	2	9	21200	24	10500	230	8600	2.1	3200	30
NYC0052S1	36-42.1907- 73.7739-4-50-000	7.7	270	2.30	2.4	10	21	61700	93	43500	1320	14600	11.2	5800	80
NYC0053S1	36-42.2147- 73.7666-4-50-000	7.7	250	3.80	3.0	13	42	M	119	50100	M	13400	2.7	M	90
NYC0054S1	36-42.2168- 73.8009-4-50-000	8.3	370	3.10	2.6	6	24	M	80	31700	M	M	7.1	M	M
NYC0055S1	36-42.1998- 73.8229-4-50-000	7.8	380	3.90	2.8	7	16	M	66	24100	270	11700	1.8	M	50
NYC0056S1	36-42.1694- 73.8079-4-50-000	8.4	250	1.80	2.8	7	19	M	81	22300	410	13100	6.6	4200	40
NYC0057S1	36-42.1348- 73.8267-4-50-000	7.6	700	1.70	3.1	9	7	65100	88	38600	1710	10900	2.9	5400	90
NYC0058S1	36-42.1342- 73.8512-4-50-000	8.1	330	2.10	2.0	8	10	40100	19	22900	390	9600	4.6	M	40
NYC0059S1	36-42.1660- 73.8719-4-50-000	8.2	435	3.10	2.5	8	.	36500	64	28700	730	9400	7.6	6800	50
NYC0060S1	36-42.1507- 73.8757-4-50-000	8.1	390	3.10	2.7	6	20	M	61	26500	M	10200	6.8	3900	40
NYC0062S1	36-42.1.67- 73.8680-4-50-000	8.6	300	2.40	3.0	6	6	42700	64	19900	290	11400	6.1	3800	50
NYC0063S1	36-42.0827- 73.8544-4-50-000	7.9	310	2.40	3.3	9	2	67400	58	26200	500	13800	9.4	5200	80
NYC0064S1	36-42.0425- 73.7732-4-50-000	7.6	100	0.70	3.0	15	13	55500	96	44600	1460	11000	11.8	M	50
NYC0065S1	36-42.0731- 73.7988-4-50-000	7.6	110	0.75	2.8	8	14	64500	86	37000	4940	11900	2.2	M	80
NYC0066S1	36-42.1.12- 73.7942-4-50-000	9.1	240	1.60	2.4	10	3	46500	90	36800	970	9400	2.9	4600	50
NYC0067S1	36-42.1065- 73.7676-4-50-000	8.3	170	1.20	2.7	7	15	67500	76	25200	510	16000	4.7	6800	80
NYC0068S1	36-42.0897- 73.7729-4-50-000	8.2	165	1.15	3.0	9	10	51500	103	32800	1330	11300	4.1	M	70
NYC0069S1	36-42.2891- 73.7660-4-50-000	7.2	2300	7.20	3.0	10	12	84500	82	37400	3580	13400	9.0	7900	120
NYC0070S1	36-42.3.44- 73.7613-4-50-000	8.8	270	1.50	2.5	6	20	61400	84	23400	510	17900	6.5	5300	50
NYC0071S1	36-42.3483- 73.7774-4-50-000	8.8	255	1.60	2.6	12	10	M	71	46000	M	14400	5.9	M	90
NYC0072S1	36-42.3803- 73.7812-4-50-000	8.5	330	2.00	4.1	12	50	M	129	48700	M	15000	10.2	M	90
NYC0073S1	36-42.4.69- 73.7678-4-50-000	8.5	330	2.00	3.1	19	31	M	207	46000	M	11400	5.1	6400	50
NYC0074S1	36-42.4647- 73.7700-4-50-000	8.0	480	2.50	2.7	7	23	M	78	47900	M	9700	9.4	M	M
NYC0075S1	36-42.4758- 73.6488-4-50-000	7.6	350	1.70	3.0	7	16	49400	73	24400	1310	12400	6.9	4400	50
NYC0076S1	36-42.4684- 73.6763-4-50-000	7.3	240	2.00	2.7	4	15	48100	52	18800	640	13000	5.4	4900	50
NYC0077S1	36-42.4567- 73.7240-4-50-000	8.0	290	2.10	4.3	8	24	37700	83	39500	600	10400	8.2	6000	40
NYC0078S1	36-42.4325- 73.7321-4-50-000	7.5	275	2.40	3.2	9	13	63600	86	30900	820	14400	9.5	6900	90
NYC0079S1	36-42.4036- 73.7388-4-50-000	7.9	230	1.50	3.2	20	37	44400	244	46900	900	11000	11.4	M	50
NYC0080S1	36-42.4043- 73.6946-4-50-000	7.4	260	2.20	1.9	4	9	46900	80	20600	700	12800	4.9	4700	50
NYC0081S1	36-42.3640- 73.7100-4-50-000	7.5	355	1.60	2.9	12	2	42300	46	23000	730	12600	6.1	M	40
NYC0082S1	36-42.3166- 73.7365-4-50-000	7.8	1.00	1.70	2.5	10	2	78400	83	32000	1510	15100	9.3	6500	100
NYC0083S1	36-42.2973- 73.7136-4-50-000	7.5	470	2.10	2.4	8	12	46500	72	28300	1050	11100	7.7	M	60
NYC0084S1	36-42.2658- 73.7248-4-50-000	8.0	370	3.80	2.7	10	15	M	91	37800	M	M	8.4	M	M

B-34

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS--

ALBANY

SHEET

18

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
NYC0085S1	36-42.2631-73.7007-4-50-000	8.2	305	2.10	1.9	7	13	42000	34	26100	510	12900	6.8	3700	40
NYC0086S1	36-42.2917-73.6857-4-50-000	7.8	310	3.20	2.3	7	7	64100	46	29700	1080	14200	7.9	6300	80
NYC0087S1	36-42.2671-73.6454-4-50-000	8.0	230	1.80	2.4	6	11	63400	44	26200	1940	15700	6.7	6600	70
NYC0088S1	36-42.2836-73.6500-4-50-000	7.8	250	2.00	2.2	4	10	36100	59	21200	660	10600	6.4	5400	40
NYC0089S1	36-42.3184-73.6441-4-50-000	7.7	300	2.10	2.4	9	22	53200	79	26500	490	19800	6.3	4000	50
NYC0090S1	36-42.3345-73.6865-4-50-000	8.0	300	2.50	2.4	6	1	M	69	23300	1030	12500	5.0		30
NYC0091S1	36-42.3607-73.6718-4-50-000	7.9	140	1.30	3.0	13	18	M	92	48300	2420	10300	1.2	5000	40
NYC0092S1	36-42.3673-73.6381-4-50-000	7.9	210	1.00	2.7	5	7	M	48	27200	2760	11400	7.6	5600	80
NYC0093S1	36-42.3968-73.6401-4-50-000	7.3	220	1.50	M	M	M	M	M	M	M	M	M	M	M
NYC0094S1	36-42.4116-73.6582-4-50-000	7.5	180	1.60	2.7	12	21	M	143	26200	1650	18500	6.4	5400	M
NYC0095S1	36-42.4619-73.6452-4-50-000	7.6	210	1.10	2.7	8	14	M	84	48400	M	10500	8.2	M	10
NYC0096S1	36-42.4701-73.5285-4-50-000	6.1	100	0.70	4.4	10	22	M	119	41000	1670	11100	11.8		M
NYC0097S1	36-42.4772-73.5529-4-50-000	6.4	90	0.65	M	M	M	M	M	M	M	M	M	M	M
NYC0098S1	36-42.4658-73.5720-4-50-000	6.5	130	1.10	3.6	14	12	M	60	28300	4600	9700	7.8	M	20
NYC0099S1	36-42.4803-73.6012-4-50-000	6.9	110	0.70	3.1	6	12	M	67	32400	2940	11800	7.0	4900	50
NYC0100S1	36-42.4747-73.6170-4-50-000	7.0	360	2.20	2.4	11	13	62900	110	43400	6310	14800	10.8	5900	70
NYC0101S1	36-42.4261-73.6147-4-50-000	7.2	240	2.30	2.2	7	12	M	68	20300	2210	12300	4.2	2900	30
NYC0102S1	36-42.3830-73.6068-4-50-000	7.1	200	1.40	2.9	8	11	44200	57	29600	1940	9800	8.5	4300	60
NYC0103S1	36-42.3534-73.5977-4-50-000	7.1	200	1.20	2.9	9	10	M	89	36200	M	11700	8.7	M	M
NYC0104S1	36-42.3257-73.6089-4-50-000	8.5	220	2.10	2.9	8	14	69100	88	27900	1270	13000	8.0	5300	80
NYC0105S1	36-42.3010-73.6050-4-50-000	7.5	170	1.60	3.0	13	21	50300	97	40500	790	13000	10.4	M	50
NYC0106S1	36-42.3024-73.5762-4-50-000	7.3	110	0.75	3.5	12	14	57800	220	43800	1340	8800	10.9	4800	80
NYC0107S1	36-42.2551-73.6018-4-50-000	7.8	110	0.50	3.2	12	12	62800	141	52100	1060	10100	14.9	5100	70
NYC0108S1	36-42.2642-73.5761-4-50-000	8.5	105	1.10	4.1	11	13	65700	126	43800	480		10.0	M	10
NYC0109S1	36-42.2648-73.5042-4-50-000	7.3	105	0.60	3.0	12	12	50000	139	36200	1040	9400	5.1	4600	50
NYC0110S1	36-42.2662-73.4881-4-50-000	7.3	80	0.55	4.7	15	17	79300	206	43000	1330	10400	3.9	4800	60
NYC0111S1	36-42.2879-73.4713-4-50-000	7.1	95	0.30	3.7	17	17	M	246	54700	M	M	14.7	M	40
NYC0112S1	36-42.3329-73.4296-4-50-000	7.3	170	1.60	4.6	17	22	59800	260	48400	1900	9800	11.6	6300	70
NYC0113S1	36-42.3189-73.4898-4-50-000	6.9	80	0.60	5.9	18	12	162300	273	43300			11.7	3700	10
NYC0114S1	36-42.3003-73.5121-4-50-000	7.0	90	0.70	M	M	M	M	M	M	M	M	M	M	M
NYC0115S1	36-42.3144-73.5391-4-50-000	7.1	130	0.70	4.8	16	7	50000	92	39800			10.8	400	20
NYC0116S1	36-42.3350-73.5571-4-50-000	7.8	140	0.85	3.5	11	15	M	125	40600	M	M	11.5	M	M
NYC0117S1	36-42.3555-73.5554-4-50-000	8.4	135	0.65	3.6	10	11	52600	120	35700	1440	9900	9.9	M	70
NYC0118S1	36-42.3616-73.5216-4-50-000	8.4	80	0.42	4.3	13	16	M	149	43500	2320	13800	11.6	7400	120
NYC0119S1	36-42.3605-73.4898-4-50-000	8.4	85	0.44	5.5	18	15	57100	184	59700	1850	9600	18.4	5700	70
NYC0120S1	36-42.3819-73.4869-4-50-000	7.1	80	0.40	2.8	10	1	62400	103	36300	1100	11000	9.7	4600	80
NYC0121S1	36-42.3914-73.5606-4-50-000	7.5	235	1.07	3.0	13	23	47900	149	45100	1440	9600	11.5	4700	60
NYC0122S1	36-42.4383-73.5748-4-50-000	7.4	360	1.15	3.6	11	17	57100	64	31900	2020	12800	9.1	3100	50
NYC0123S1	36-42.4868-73.4819-4-50-000	5.9	60	0.32	4.1	8	22	M	104	23700	740	12000	7.2	5100	40
NYC0124S1	36-42.4890-73.4533-4-50-000	6.7	190	1.50	3.5	14	10	45500	181	36700	1000	10600	4.3	4400	40
NYC0125S1	36-42.4663-73.4225-4-50-000	6.9	115	0.70	3.6	12	15	M	123	32400	3120	15000	8.2	8500	80
NYC0126S1	36-42.4770-73.4081-4-50-000	6.8	70	0.28	3.7	13	14	M	123	32500	M	12000	9.6	M	70
NYC0127S1	36-42.4643-73.3905-4-50-000	6.9	195	1.70	4.6	55		53500	958	38300	790	11200	4.0	4400	50
NYC0128S1	36-42.4184-73.3994-4-50-000	7.3	150	1.50	M	M	M	M	M	M	M	M	M	M	M
NYC0129S1	36-42.4266-73.4324-4-50-000	6.1	170	2.00	M	M	M	M	M	M	M	M	M	M	M
NYC0130S1	36-42.4191-73.4734-4-50-000	7.4	210	1.80	3.5	10	20	62400	123	34500	1530	12500	9.2	5600	70
NYC0131S1	36-42.4658-73.4831-4-50-000	7.1	70	0.35	4.1	17	27	55900	203	51900	2000	10400	13.1	M	70
NYC0132S1	36-42.4559-73.5075-4-50-000	5.9	95	0.42	12.9	9	15	68900	94	34800	1370	11600	9.8	5600	80
NYC0133S1	36-42.4141-73.5169-4-50-000	7.3	150	0.85	3.5	20	30	52800	195	51200	1160	10400	12.4	8500	70
NYC0134S1	36-42.3995-73.5064-4-50-000	5.7	410	1.95	2.8	7	10	M	79	30000	3830	7800	7.7	1400	50
NYC0135S1	36-42.3785-73.4296-4-50-000	7.5	300	2.60	2.9	7	16	39900	101	23900	660	8500	6.9	M	50
NYC0136S1	36-42.3560-73.4285-4-50-000	8.2	110	0.90	3.5	16	13	63500	171	42300	1080	10600	10.2	M	70
NYDU001S1	36-42.0211-73.5111-4-50-000	8.4	210	2.60	0.4	M	M	5600	M	M	160	1100	M	1000	10

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

19

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
NYDU002S1	36-42.0453-73.5124-4-50-000	8.1	180	1.70	0.4	M	M	8200	M	M	250	1800	M	1700	10
NYDU003S1	36-42.0461-73.8686-4-50-000	8.0	290	1.70	0.3	M	M	6600	M	M	110	1400	M	M	10
NYDU004S1	36-42.0704-73.8939-4-50-000	8.5	255	2.00	0.5	M	M	6600	M	M	100	1300	M	500	10
NYDU005S1	36-42.0463-73.9111-4-50-000	8.2	315	2.20	0.4	M	M	8300	M	M	50	2100	M	700	10
NYDU006S1	36-42.0134-73.8958-4-50-000	8.7	285	2.20	0.3	M	M	4800	M	M	60	1600	M	M	M
NYDU007S1	36-42.0082-73.8575-4-50-000	8.7	240	2.40	0.3	M	M	6300	M	M	200	2000	M	600	10
NYDU008S1	36-42.0184-73.8208-4-50-000	8.5	175	2.00	0.4	M	M	4100	M	M	30	1300	M	500	10
NYDU009S1	36-42.0343-73.8078-4-50-000	8.1	200	1.80	3.0	12	20	69900	102	31900	1440	15700	9.0	6100	70
NYDU010S1	36-42.0247-73.7692-4-50-000	6.5	145	1.05	3.1	12	24	50200	166	46200	1180	9200	11.4	M	60
NYGR151S1	36-42.1531-73.9195-4-50-000	8.0	340	2.00	4.2	13	.	M	143	51800	520	5200	17.7	M	90
NYGR152S1	36-42.1809-73.9184-4-50-000	M	M	M	2.9	11	5	95100	82	42000	550	6300	15.8	6100	190
NYGR153S1	36-42.1783-73.8909-4-50-000	8.5	230	1.70	3.4	8	2	79900	71	35600	1290	10300	10.9	7000	110
NYGR154S1	36-42.2155-73.9123-4-50-000	8.0	1150	4.00	2.0	7	.	44400	58	27600	1370	3900	9.1	3200	80
NYGR155S1	36-42.1974-73.9505-4-50-000	7.9	260	3.00	3.0	9	7	41700	79	27700	610	5300	8.8	3900	70
NYGR156S1	36-42.1832-73.9758-4-50-000	7.3	150	0.70	2.5	7	13	30900	83	21300	290	4400	6.7	3900	50
NYGR157S1	36-42.2042-73.9748-4-50-000	7.6	130	0.95	2.5	7	16	36200	48	19200	350	7000	6.0	3900	50
NYGR158S1	36-42.2218-73.9890-4-50-000	7.3	160	1.15	3.0	9	8	47300	58	39300	480	4400	9.6	3500	80
NYGR159S1	36-42.2777-73.9800-4-50-000	5.8	100	0.62	2.7	4	10	39900	58	13400	330	5800	6.0	3400	50
NYGR160S1	36-42.3405-73.9932-4-50-000	7.5	150	1.50	2.9	12	13	M	57	38800	1830	6500	10.0	M	70
NYGR161S1	36-42.2755-73.9558-4-50-000	7.1	280	3.00	2.0	8	10	42400	53	21500	2830	8000	5.4	4200	60
NYGR162S1	36-42.3062-73.9506-4-50-000	7.5	110	0.80	3.7	6	12	M	66	26500	560	5400	10.0	3900	70
NYGR163S1	36-42.3113-73.9792-4-50-000	M	M	M	2.7	10	18	32300	80	32900	480	4900	10.3	3700	50
NYGR164S1	36-42.3667-73.9904-4-50-000	7.8	210	2.10	2.6	8	12	M	69	36700	1770	10600	9.7	6500	100
NYGR165S1	36-42.3613-73.9521-4-50-000	7.7	275	1.40	2.8	8	9	63800	68	37700	280	6600	11.8	4100	100
NYGR166S1	36-42.3944-73.9612-4-50-000	8.0	250	2.20	2.9	8	10	60100	52	41400	4470	7600	11.1	4400	100
NYGR167S1	36-42.4146-73.9846-4-50-000	7.6	325	3.10	1.9	6	15	38800	61	28400	1820	7100	7.0	5100	60
NYGR168S1	36-42.4392-73.9822-4-50-000	7.8	120	1.60	3.0	10	2	66800	87	36400	1060	7900	11.2	5900	110
NYGR169S1	36-42.4425-73.9054-4-50-000	8.0	125	1.45	3.0	7	16	66600	67	28400	1000	10000	8.7	7200	90
NYGR170S1	36-42.4391-73.9335-4-50-000	8.1	200	1.50	3.0	8	10	51300	49	29000	400	7100	9.8	5500	80
NYGR171S1	36-42.4118-73.9194-4-50-000	7.9	120	0.90	3.1	10	28	M	119	34700	240	6200	12.3	4400	50
NYGR172S1	36-42.3989-73.8830-4-50-000	7.8	220	2.40	2.6	7	18	M	67	27500	2670	8600	7.3	M	40
NYGR173S1	36-42.3838-73.8924-4-50-000	7.2	250	3.10	2.6	7	2	M	90	29100	M	M	7.0	M	10
NYGR174S1	36-42.3902-73.9306-4-50-000	8.1	170	1.30	3.5	8	2	M	74	38400	4120	5300	10.5	.	20
NYGR175S1	36-42.3386-73.9341-4-50-000	7.4	170	2.10	2.7	9	11	40200	81	24400	190	4900	2.9	4200	70
NYGR176S1	36-42.3478-73.9020-4-50-000	9.3	160	1.40	2.9	9	23	33500	75	22500	220	6900	7.2	4100	50
NYGR177S1	36-42.3239-73.9049-4-50-000	8.2	180	1.20	3.0	13	23	M	94	38000	1410	7400	11.0	5100	70
NYGR178S1	36-42.2670-73.8914-4-50-000	M	M	M	2.9	13	18	60600	110	38400	880	9600	11.5	6800	100
NYGR179S1	36-42.2664-73.9016-4-50-000	8.1	360	2.30	2.7	8	14	60000	67	32700	820	8600	9.4	5400	100
NYGR180S1	36-42.2325-73.9251-4-50-000	8.2	180	1.50	1.7	4	4	44300	29	20700	490	7600	4.9	3900	70
NYGR181S1	36-42.2609-73.8457-4-50-000	7.3	470	4.20	2.9	11	7	79500	90	41000	700	7300	13.1	4700	100
NYGR182S1	36-42.2875-73.8465-4-50-000	7.8	700	4.20	2.9	14	.	M	133	58800	M	M	15.6	M	M
NYGR183S1	36-42.3285-73.8501-4-50-000	7.7	1000	3.20	2.2	7	.	71600	55	37300	1440	5300	10.4	4600	100
NYGR184S1	36-42.3559-73.8385-4-50-000	7.9	500	3.10	2.6	9	14	45200	82	31200	560	8800	9.6	3800	60
NYGR185S1	36-42.3836-73.8400-4-50-000	7.2	320	3.00	1.8	4	11	27100	40	20300	470	5600	1.6	4900	50
NYGR186S1	36-42.4072-73.8601-4-50-000	7.9	215	2.00	3.1	10	17	65600	62	45600	1520	12400	11.5	7400	100
NYGR187S1	36-42.4179-73.8219-4-50-000	7.8	385	3.20	2.4	4	13	36800	60	24600	610	9000	5.5	4800	50
NYGR188S1	36-42.4562-73.8361-4-50-000	7.8	550	5.00	2.0	8	14	42300	.	29500	500	11000	7.9	5100	60
NYGR189S1	36-42.3937-73.8001-4-50-000	8.4	1400	4.80	4.1	7	56	63300	130	51500	1820	13100	11.8	17900	130
NYGR190S1	36-42.3660-73.8034-4-50-000	8.1	700	6.40	3.0	10	31	39200	105	51100	690	9400	11.8	7000	60
NYGR191S1	36-42.3279-73.8046-4-50-000	7.5	330	2.60	3.3	10	44	53600	104	43400	840	12800	10.6	10200	80
NYGR192S1	36-42.3099-73.8115-4-50-000	8.1	295	2.10	2.4	9	30	37500	96	42700	700	8500	10.0	5300	50
NYGR193S1	36-42.2742-73.8027-4-50-000	8.1	200	1.20	2.7	7	16	53900	51	35200	1150	10300	8.9	6600	80
NYGR194S1	36-42.2381-73.8568-4-50-000	7.7	380	3.30	3.0	8	12	84700	71	32700	640	18300	9.6	7100	100

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

20

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
NYRE001S1	36-42.4851- 73.6800-4-50-000	7.5	1000	1.50	2.8	9	3	76300	83	35100	1530	15800	8.9	7500	70
NYRE002S1	36-42.4786- 73.7153-4-50-000	7.2	400	2.90	3.5	9	44	42100	136	49000	1500	11100	10.6	8600	60
NYRE010S1	36-42.5174- 73.3606-4-50-000	7.1	125	1.12	4.3	84	.	89800	1315	64200	1310	14900	1.1	7700	80
NYRE011S1	36-42.5383- 73.3601-4-50-000	6.6	101	0.74	3.7	33	.	48000	380	32700	910	8000	7.7	4100	40
NYRE012S1	36-42.5656- 73.3630-4-50-000	7.3	106	0.88	3.0	36	16	76500	345	26200	1260	12300	6.6	5300	70
NYRE013S1	36-42.5970- 73.3581-4-50-000	7.4	62	0.48	3.6	50	.	93600	525	53500	1440	9300	12.6	5000	60
NYRE014S1	36-42.6130- 73.3824-4-50-000	7.5	92	0.60	4.1	11	31	34700	109	20900	890	10300	5.5	3700	30
NYRE015S1	36-42.5920- 73.4206-4-50-000	5.0	25	0.02	3.5	12	37	M	64	31700	1200	19000	7.4	M	30
NYRE016S1	36-42.5616- 73.3923-4-50-000	6.3	34	0.08	4.8	19	48	39000	167	17900	330	14300	6.2	3500	20
NYRE017S1	36-42.5399- 73.3945-4-50-000	7.4	115	0.88	4.5	60	.	78500	777	64200	1480	14000	15.5	5300	70
NYRE018S1	36-42.5337- 73.4142-4-50-000	7.4	60	0.20	3.5	11	28	46200	99	18800	1020	17300	2.0	M	30
NYRE019S1	36-42.5104- 73.4236-4-50-000	7.4	60	0.20	3.6	15	17	M	175	26200	790	13600	6.1	3800	50
NYRE020S1	36-42.5094- 73.4066-4-50-000	7.0	70	0.18	4.7	36	44	61300	408	37600	950	14100	9.2	M	50
NYRE021S1	36-42.7246- 73.3680-4-50-000	7.1	81	0.64	5.4	86	55	M	900	66000	1600	12300	16.6	6100	80
NYRE022S1	36-42.7135- 73.3805-4-50-000	7.7	40	0.16	3.4	19	32	52700	192	42300	640	13400	11.6	M	50
NYRE023S1	36-42.7039- 73.3695-4-50-000	7.9	63	0.38	4.1	15	27	70100	133	38800	1220	15800	10.5	6100	70
NYRE024S1	36-42.6774- 73.3315-4-50-000	7.6	39	0.20	3.7	24	.	99700	249	51900	1920	12600	13.7	M	80
NYRE025S1	36-42.6580- 73.3637-4-50-000	7.5	88	0.64	3.7	M	M	53000	M	M	900	13600	M	5400	50
NYRE026S1	36-42.6347- 73.3587-4-50-000	7.9	40	0.14	4.4	72	.	103100	795	59400	1860	11000	14.2	5800	90
NYRE027S1	36-42.6412- 73.3885-4-50-000	7.5	36	0.06	4.2	13	22	60500	93	33600	930	15800	9.6	5100	60
NYRE028S1	36-42.6532- 73.4160-4-50-000	4.6	31	0.00	4.3	10	25	37700	53	15800	480	21000	3.9	4600	30
NYRE029S1	36-42.6870- 73.4333-4-50-000	4.7	28	0.00	4.2	11	47	M	52	16800	240	21100	6.2	5100	30
NYRE030S1	36-42.6883- 73.4884-4-50-000	5.4	26	0.02	4.3	9	50	M	68	28200	M	22800	8.6	M	40
NYRE031S1	36-42.7155- 73.4656-4-50-000	4.3	30	0.00	4.1	M	M	M	M	M	300	21200	M	M	30
NYRE032S1	36-42.7175- 73.4290-4-50-000	5.3	22	0.04	4.7	8	9	56900	75	21900	720	20800	6.2	4000	40
NYRE033S1	36-42.6840- 73.3849-4-50-000	6.7	52	0.30	3.3	M	M	48700	M	M	640	16900	M	M	40
NYRE034S1	36-42.7075- 73.3304-4-50-000	6.8	49	0.22	3.3	48	.	110200	489	71900	2430	9900	16.3	5900	90
NYRE035S1	36-42.7413- 73.4024-4-50-000	6.5	25	0.22	3.5	11	2	M	46	24400	1440	26000	6.7	6700	60
NYRE036S1	36-42.6345- 73.4806-4-50-000	5.5	28	0.04	3.9	10	32	54200	73	18600	610	26900	5.3	6200	50
NYRE037S1	36-42.6124- 73.4798-4-50-000	5.7	27	0.04	4.8	10	60	M	59	27000	M	25200	6.1	M	50
NYRE038S1	36-42.5863- 73.4848-4-50-000	6.3	28	0.06	3.3	M	M	M	M	M	M	23600	M	M	40
NYRE039S1	36-42.6071- 73.5198-4-50-000	6.3	43	0.18	2.6	9	17	M	115	36300	M	13300	9.9	.	60
NYRE040S1	36-42.6143- 73.5737-4-50-000	6.9	103	0.88	2.9	7	19	M	83	32200	1300	11200	7.5	M	60
NYRE041S1	36-42.6131- 73.6020-4-50-000	7.0	177	0.96	2.6	8	19	M	82	28000	980	12800	5.4	M	40
NYRE042S1	36-42.5861- 73.6029-4-50-000	7.1	106	0.52	2.7	.	.	75200	.	.	1590	15700	0.9	8800	100
NYRE043S1	36-42.5836- 73.5564-4-50-000	6.9	100	0.72	3.1	7	28	44000	65	24400	510	13800	5.9	6400	30
NYRE044S1	36-42.5819- 73.5279-4-50-000	7.3	81	0.28	2.5	6	15	45700	40	13800	1350	15900	1.9	5700	40
NYRE045S1	36-42.5583- 73.5469-4-50-000	7.2	66	0.40	4.6	12	43	49800	69	27100	1060	18200	6.5	6100	40
NYRE046S1	36-42.5581- 73.5148-4-50-000	7.3	50	0.16	3.3	8	39	58100	30	29400	1020	22500	7.8	7900	50
NYRE047S1	36-42.5392- 73.4767-4-50-000	6.9	45	0.12	3.6	10	31	66800	54	28900	3090	23800	7.5	8000	50
NYRE048S1	36-42.5138- 73.4868-4-50-000	6.3	58	0.22	3.5	10	25	41700	61	17100	1140	19400	4.4	5600	30
NYRE049S1	36-42.5161- 73.5148-4-50-000	6.9	50	0.12	4.4	15	44	54100	115	47100	1870	14300	11.2	6100	60
NYRE050S1	36-42.5122- 73.5591-4-50-000	7.0	122	0.34	3.4	13	27	67900	100	38000	1230	13100	9.6	7000	60
NYRE051S1	36-42.5278- 73.6037-4-50-000	7.6	102	0.44	3.2	M	M	49800	M	M	1520	12000	M	M	60
NYRE052S1	36-42.5200- 73.6287-4-50-000	7.1	150	0.96	2.9	9	22	M	98	41900	4140	12100	8.6	6800	70
NYRE053S1	36-42.5558- 73.6774-4-50-000	7.6	275	1.70	1.9	M	M	38400	M	M	1270	8500	M	M	50
NYRE054S1	36-42.5607- 73.6432-4-50-000	7.6	145	0.76	2.6	M	M	54800	M	M	1320	12600	M	9500	70
NYRE055S1	36-42.5524- 73.5921-4-50-000	7.4	100	0.52	4.2	16	51	74500	94	43800	1500	21300	10.4	11200	70
NYRE056S1	36-42.5903- 73.6411-4-50-000	6.6	124	1.08	2.1	8	11	68900	77	46300	.	13300	9.1	M	60
NYRE057S1	36-42.7347- 73.2938-4-50-000	6.2	85	0.26	3.2	35	1	102300	391	73500	1630	7700	17.3	5200	70
NYRE058S1	36-42.7545- 73.3040-4-50-000	7.0	51	0.32	12.6	63	.	M	859	85600	M	M	19.8	M	M
NYRE059S1	36-42.7706- 73.3317-4-50-000	7.3	56	0.36	3.6	31	.	102200	430	66400	2670	8700	17.1	6300	100
NYRE060S1	36-42.7851- 73.3256-4-50-000	7.5	168	2.00	2.7	18	11	103800	211	65800	2180	8100	15.3	3800	70

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

21

SRL I.D. *****	DOE I.D.	PH.	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
NYRE061S1	36-42.7981- 73.3374-4-50-000	7.3	141	1.24	4.3	11	11	50500	89	24800	470	10400	7.7	3900	40
NYRE062S1	36-42.8199- 73.2892-4-50-000	7.8	138	1.20	2.5	24	.	98200	266	41100	1210	7500	10.4	M	70
NYRE063S1	36-42.8443- 73.3560-4-50-000	7.6	90	0.56	2.7	12	23	59900	136	49800	1100	11200	12.5	6800	70
NYRE064S1	36-42.8624- 73.3231-4-50-000	7.9	285	2.70	2.6	11	19	75100	138	34100	1410	10300	8.8	6900	100
NYRE065S1	36-42.8784- 73.3018-4-50-000	7.3	160	1.45	2.9	9	12	46400	131	36200	1050	6000	8.7	4100	60
NYRE066S1	36-42.8874- 73.3481-4-50-000	7.2	117	0.84	2.4	7	12	53700	66	20300	850	8700	5.0	4900	70
NYRE067S1	36-42.9213- 73.3125-4-50-000	7.1	128	0.74	4.3	12	18	67900	126	41800	940	6400	12.0	2000	100
NYRE068S1	36-42.9383- 73.3221-4-50-000	7.2	90	0.72	3.6	45	.	83500	438	42600	740	10100	10.7	5700	60
NYRE069S1	36-42.9307- 73.3494-4-50-000	7.2	92	0.72	2.4	14	.	M	156	32500	690	8800	7.9	5100	60
NYRE070S1	36-42.9315- 73.3873-4-50-000	7.2	270	2.40	2.5	15	24	M	134	30600	1010	9800	4.7	5900	70
NYRE071S1	36-42.9195- 73.4306-4-50-000	6.5	195	1.04	3.0	10	2	M	100	44400	1800	10100	2.9	6200	70
NYRE072S1	36-42.9300- 73.4656-4-50-000	7.2	163	1.28	2.9	9	16	48500	80	27800	1200	10000	7.9	M	40
NYRE073S1	36-42.8962- 73.4057-4-50-000	6.2	93	0.84	3.1	8	15	41900	78	26600	950	6900	7.7	4400	40
NYRE074S1	36-42.8928- 73.4201-4-50-000	6.9	140	1.13	3.0	11	18	59800	83	32400	990	9900	8.7	5400	70
NYRE075S1	36-42.8891- 73.4593-4-50-000	6.7	130	0.92	2.9	8	16	M	66	33100	2040	10000	6.8	5200	70
NYRE076S1	36-42.8704- 73.4594-4-50-000	6.4	110	0.76	2.7	12	33	M	102	27600	M	8500	8.0	4800	M
NYRE077S1	36-42.8601- 73.4102-4-50-000	6.9	100	0.88	3.4	10	21	M	100	31700	M	10500	9.2	1700	M
NYRE078S1	36-42.8483- 73.4151-4-50-000	6.7	89	0.60	3.2	12	15	78000	105	39700	.	12400	10.7	5200	70
NYRE079S1	36-42.8288- 73.3918-4-50-000	6.7	85	0.52	3.2	11	10	83500	88	39600	.	10100	8.5	.	M
NYRE080S1	36-42.8209- 73.3733-4-50-000	6.5	51	0.34	5.7	10	17	52300	86	37500	810	9900	9.9	6900	60
NYRE081S1	36-42.7764- 73.3832-4-50-000	6.2	38	0.18	4.7	15	51	56000	109	37700	1640	22200	10.8	6700	50
NYRE082S1	36-42.8080- 73.4016-4-50-000	6.2	55	0.24	4.9	13	55	65400	116	27000	1800	19800	8.1	7600	60
NYRE083S1	36-42.8192- 73.4312-4-50-000	6.5	55	0.28	3.6	11	28	67700	143	39700	1750	15400	1.6	6800	60
NYRE084S1	36-42.8407- 73.4853-4-50-000	6.8	83	0.56	3.1	11	22	81400	80	44200	1220	13200	11.2	7700	70
NYRE085S1	36-42.8178- 73.4736-4-50-000	7.4	55	0.32	3.4	9	20	M	93	26800	M	12700	8.1	M	M
NYRE086S1	36-42.8126- 73.5338-4-50-000	7.6	140	0.96	2.6	7	14	M	64	25300	470	M	7.3	.	M
NYRE087S1	36-42.8321- 73.5492-4-50-000	7.4	187	1.67	2.7	8	25	M	86	34200	890	9300	9.4	1600	30
NYRE088S1	36-42.8682- 73.5552-4-50-000	8.0	140	1.10	2.2	11	21	38700	96	29500	390	9500	8.0	M	40
NYRE089S1	36-42.8707- 73.5219-4-50-000	8.3	145	1.00	3.0	8	21	76700	101	53200	2740	15500	1.3	8100	100
NYRE090S1	36-42.8918- 73.5071-4-50-000	7.2	177	1.16	2.6	7	18	39400	66	17700	490	10100	5.0	M	40
NYRE091S1	36-42.9331- 73.5175-4-50-000	8.4	245	1.87	2.9	17	32	49500	131	25900	730	8000	3.0	6300	40
NYRE092S1	36-42.9195- 73.5381-4-50-000	7.3	260	2.20	4.8	11	20	43200	115	31600	710	9100	8.8	M	40
NYRE093S1	36-42.9175- 73.5791-4-50-000	7.7	203	1.55	2.6	6	17	M	80	22400	1390	M	5.8	4800	10
NYRE094S1	36-42.8986- 73.5404-4-50-000	8.9	211	1.53	2.0	9	17	55200	78	19500	710	10700	5.3	6600	50
NYRE095S1	36-42.8774- 73.5798-4-50-000	7.8	155	1.27	2.8	12	27	M	114	24000	1950	9600	6.1	6000	40
NYRE096S1	36-42.8604- 73.6079-4-50-000	7.2	340	4.40	2.4	6	15	35200	78	20100	450	7600	5.3	4500	30
NYRE097S1	36-42.8252- 73.6104-4-50-000	7.7	160	1.30	2.4	6	14	41000	72	19900	1000	8800	5.9	3800	50
NYRE098S1	36-42.8037- 73.6025-4-50-000	7.4	240	1.67	3.1	11	24	42800	67	37500	840	8800	9.8	5100	50
NYRE099S1	36-42.7931- 73.5715-4-50-000	7.7	352	3.00	2.8	11	25	M	121	44500	1720	10900	11.3	M	50
NYRE100S1	36-42.7892- 73.5326-4-50-000	7.4	121	0.80	3.5	13	13	89700	96	42000	3510	14700	11.5	10500	100
NYRE101S1	36-42.7690- 73.5194-4-50-000	7.2	52	0.32	3.5	10	25	M	98	34400	1350	17100	9.6	M	60
NYRE102S1	36-42.7570- 73.4225-4-50-000	5.4	24	0.02	4.5	9	54	44300	64	9600	220	28000	5.2	3200	30
NYRE103S1	36-42.7377- 73.4414-4-50-000	5.5	25	0.02	3.3	8	27	55100	53	17300	330	24900	4.6	4100	30
NYRE104S1	36-42.7345- 73.4733-4-50-000	5.6	30	0.02	3.4	11	34	44500	76	26100	570	19400	5.3	M	30
NYRE105S1	36-42.7561- 73.4886-4-50-000	6.9	48	0.14	2.9	6	26	46800	100	31000	830	19300	10.3	4800	30
NYRE106S1	36-42.7626- 73.5649-4-50-000	7.0	163	1.04	3.0	14	25	54600	110	51900	1740	10900	13.4	M	60
NYRE107S1	36-42.7756- 73.6139-4-50-000	7.8	225	1.73	2.6	8	27	M	71	30100	M	8900	8.3	M	M
NYRE108S1	36-42.7335- 73.6379-4-50-000	8.0	295	2.20	2.7	7	19	M	78	29200	M	10500	6.9	4900	60
NYRE109S1	36-42.6812- 73.6548-4-50-000	7.0	412	3.20	3.2	7	21	40400	81	30700	1480	10900	7.3	M	40
NYRE110S1	36-42.6851- 73.6884-4-50-000	7.4	360	1.93	3.0	9	27	40400	106	32200	660	9600	6.4	6400	60
NYRE111S1	36-42.6341- 73.7273-4-50-000	8.0	400	2.20	2.9	11	37	M	84	35200	M	M	7.8	5700	M
NYRE112S1	36-42.6625- 73.6793-4-50-000	7.8	209	1.10	2.5	6	26	M	98	24800	M	7400	5.3	M	40
NYRE113S1	36-42.6412- 73.6656-4-50-000	7.4	268	1.95	2.9	14	33	M	124	44600	1550	11900	9.5	M	30

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

22

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
NYRE114S1	36-42.6113- 73.6414-4-50-000	7.5	220	1.13	3.5	8	29	M	31	35400	4980	14300	7.7	11300	90
NYRE115S1	36-42.6127- 73.6957-4-50-000	7.7	248	1.33	3.3	12	38	45400	118	43200	1100	10800	9.3	M	80
NYRE116S1	36-42.6070- 73.7236-4-50-000	7.2	660	3.90	2.6	6	27	62900	75	36300	960	15500	8.7	10300	110
NYRE117S1	36-42.6385- 73.5382-4-50-000	7.4	82	0.44	3.6	13	21	64300	53	26300	1160	17100	5.4	6300	50
NYRE118S1	36-42.6458- 73.6040-4-50-000	7.7	170	1.00	3.3	11	1	55000	80	35100	1390	13900	7.7	9600	70
NYRE119S1	36-42.6702- 73.5713-4-50-000	7.1	135	1.00	2.6	6	19	M	54	27600	M	11800	5.1	3000	M
NYRE120S1	36-42.6742- 73.6036-4-50-000	7.3	181	1.60	2.8	9	26	49600	62	41100	2040	11800	10.9	6500	50
NYRE121S1	36-42.7015- 73.6065-4-50-000	8.5	325	2.00	3.0	9	29	43500	81	39500	450	10000	2.9	6300	50
NYRE122S1	36-42.7035- 73.5602-4-50-000	7.9	70	0.33	3.0	10	21	56000	84	32500	970	13200	9.4	3200	50
NYRE123S1	36-42.6852- 73.5257-4-50-000	7.3	42	0.20	4.2	8	39	41000	58	18000	700	18200	5.7	5300	30
NYRE124S1	36-42.7097- 73.5084-4-50-000	5.9	34	0.02	3.9	9	34	49500	133	24400	730	20400	7.2	M	40
NYRE125S1	36-42.7415- 73.5227-4-50-000	7.0	60	0.26	4.7	7	45	37800	73	20300	780	15500	6.8	5200	30
NYRE126S1	36-42.7369- 73.5661-4-50-000	7.4	125	0.72	3.0	9	16	43600	46	27400	1770	10700	6.6	3400	50
NYRE127S1	36-42.7375- 73.6094-4-50-000	7.3	370	2.10	3.1	9	24	45600	89	33300	840	10900	8.1	6500	40
NYRE128S1	36-42.7790- 73.6440-4-50-000	7.3	304	2.70	2.5	8	18	40500	76	25300	470	9400	6.9	M	50
NYRE129S1	36-42.8105- 73.6469-4-50-000	7.6	260	2.30	3.1	12	55	49300	178	60300	1760	9900	12.3	10100	90
NYRE130S1	36-42.8460- 73.6292-4-50-000	7.8	272	1.87	4.4	19	48	44300	209	32800	1190	8600	7.5	M	60
NYRE131S1	36-42.8649- 73.6709-4-50-000	8.0	270	2.20	5.7	31	85	49900	275	50400	1120	9100	8.4	16300	90
NYRE132S1	36-42.8931- 73.6294-4-50-000	8.0	455	4.00	3.0	16	27	34600	154	23100	990	6000	4.5	M	30
NYRE133S1	36-42.9175- 73.6462-4-50-000	8.7	232	1.60	3.6	23	55	52900	235	43900	1040	8600	9.7	7400	50
NYRE134S1	36-42.5229- 73.6821-4-50-000	7.1	145	0.96	2.4	7	13	46800	77	37700	1110	9800	9.6	M	60
NYRE135S1	36-42.5790- 73.6857-4-50-000	7.6	206	1.50	2.4	7	22	51200	70	28300	1130	13800	5.5	6400	50
NYRE136S1	36-42.5845- 73.7402-4-50-000	8.3	448	2.90	2.5	6	2	50300	78	34500	980	10500	8.0	M	70
NYRE137S1	36-42.5615- 73.7444-4-50-000	8.4	360	2.90	3.3	9	49	43800	164	60300	1190	10100	12.8	M	80
NYRE138S1	36-42.5153- 73.7266-4-50-000	8.4	320	1.90	2.1	7	21	M	154	27800	M	11900	7.2	M	M
NYRE139S1	36-42.5139- 73.7624-4-50-000	8.0	700	4.20	2.5	7	29	M	86	23900	430	9700	6.3	M	40
NYSC001S1	36-42.7744- 73.8299-4-50-000	7.6	402	3.10	4.7	10	72	29900	69	50500	950	7400	10.2	13900	80
NYSC002S1	36-42.7954- 73.8723-4-50-000	8.2	590	3.00	4.3	11	42	71400	101	51400	1930	12600	11.7	14700	140
NYSC003S1	36-42.8382- 73.8927-4-50-000	7.4	880	3.20	2.8	8	41	43800	112	55200	740	11200	12.1	M	70
NYSC004S1	36-42.8704- 73.9072-4-50-000	7.7	452	3.20	2.7	8	50	35500	79	39800	470	10600	6.2	6800	50
NYSC005S1	36-42.8496- 73.9481-4-50-000	7.8	250	1.80	2.5	5	28	51200	70	30600	1030	14400	8.1	8300	70
NYSC006S1	36-42.8606- 73.9828-4-50-000	7.4	380	2.90	3.3	12	26	55800	98	48700	1240	11800	13.0	7600	90
NYSC007S1	36-42.8077- 73.9932-4-50-000	7.7	229	0.90	2.1	5	18	40500	46	26400	480	12800	6.2	4200	50
NYSC008S1	36-42.9095- 73.9196-4-50-000	7.8	270	2.40	4.0	7	55	M	106	59400	1410	9800	14.1	16100	100
NYSC009S1	36-42.8816- 73.9474-4-50-000	7.6	351	2.10	2.5	7	1	51900	64	32900	650	13100	9.8	6200	60
NYSC010S1	36-42.9057- 73.9843-4-50-000	7.0	265	2.40	3.0	6	13	48500	95	38100	880	9000	10.5	5500	90
NYSR026S1	36-42.8493- 73.7537-4-50-000	7.8	320	2.20	3.7	9	67	32700	67	32300	670	9500	7.9	9800	60
NYSR027S1	36-42.8353- 73.7646-4-50-000	7.5	370	1.90	4.0	8	50	14500	73	41400	820	5200	6.7	13600	80
NYSR028S1	36-42.8026- 73.7713-4-50-000	8.0	465	2.20	3.7	9	50	34700	66	38700	880	9700	9.5	10500	60
NYSR029S1	36-42.8329- 73.8047-4-50-000	7.8	388	2.20	2.8	6	38	29300	49	20500	440	9700	5.6	6800	30
NYSR030S1	36-42.8663- 73.8217-4-50-000	7.4	475	3.50	3.9	10	55	36200	69	40100	840	9600	8.8	M	70
NYSR031S1	36-42.8036- 73.8259-4-50-000	7.7	295	1.70	3.5	7	60	34100	56	29700	610	10600	7.5	10400	40
NYSR032S1	36-42.8206- 73.8519-4-50-000	7.3	310	2.07	3.3	8	40	41600	104	42400	1090	11200	9.9	M	70
NYSR033S1	36-42.8273- 73.7405-4-50-000	7.7	380	2.20	2.2	7	28	32600	46	20500	500	10000	5.6	4700	40
NYSR034S1	36-42.8017- 73.6920-4-50-000	7.7	430	3.10	3.9	11	67	38700	83	54300	750	10200	0.8	M	70
NYSR035S1	36-42.8392- 73.6748-4-50-000	8.1	362	2.70	4.9	19	137	50800	181	110100	1700	11500	18.1	21800	160
NYSR036S1	36-42.8664- 73.7248-4-50-000	7.5	440	1.50	7.0	21	116	49200	139	54400	1600	12200	11.7	27600	140
NYSR037S1	36-42.8802- 73.7275-4-50-000	7.5	281	1.70	5.5	17	81	34700	115	41800	770	9300	10.4	13700	70
NYSR038S1	36-42.9132- 73.7380-4-50-000	7.8	260	1.70	2.5	7	22	41300	76	30900	950	10200	7.8	5900	50
NYSR039S1	36-42.9162- 73.7702-4-50-000	7.9	320	1.70	8.5	28	149	32500	153	82700	1620	7060	14.7	28400	150
NYSR040S1	36-42.8872- 73.7726-4-50-000	7.8	325	2.90	9.7	23	139	19200	150	74500	1790	4700	13.2	30300	150
NYSR041S1	36-42.8859- 73.7979-4-50-000	7.7	400	2.50	5.0	11	77	46500	92	60700	1820	11000	12.6	27700	150
NYSR042S1	36-42.8914- 73.8304-4-50-000	7.2	340	2.60	2.9	8	32	44500	74	27700	420	10500	8.3	6100	60

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

23

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
NYSR043S1	36-42.9053- 73.8390-4-50-000	7.0	485	3.80	3.5	9	54	33100	73	33200	590	9100	2.7	9000	50
NYSR044S1	36-42.9312- 73.8256-4-50-000	7.2	428	3.00	3.2	8	48	44700	71	25400	710	13700	6.7	10900	60
NYSR045S1	36-42.9393- 73.8517-4-50-000	7.4	418	4.40	2.4	4	20	20700	47	19900	430	5200	4.4	M	40
NYSR046S1	36-42.9486- 73.7810-4-50-000	7.6	258	2.40	12.0	40	269	29200	209	10900			16.1	M	M
NYSR047S1	36-42.9472- 73.7293-4-50-000	7.7	198	1.80	2.8	9	22	40400	70	32400	700	8600	8.2	6100	70
NYSR048S1	36-42.9541- 73.8046-4-50-000	7.7	330	1.90	3.9	12	10	69900	148	50300	510	9700	12.6	M	120
NYSR049S1	36-42.9695- 73.8320-4-50-000	7.3	234	1.60	3.4	11	8	M	99	54200	850	12600	14.9	6600	160
NYSR050S1	36-42.9754- 73.8492-4-50-000	8.1	306	3.10	2.9	8	29	50100	76	43000	790	11000	11.4	8700	80
NYSR051S1	36-42.8928- 73.8895-4-50-000	7.1	330	2.80	3.6	9	34	59600	115	43200	860	14100	11.8	M	100
NYSR052S1	36-42.9363- 73.9851-4-50-000	7.4	230	2.50	4.1	9	48	70300	107	63800	1930	16800	13.9	17200	140
NYSR053S1	36-42.9701- 73.9759-4-50-000	7.4	190	1.80	2.9	9	37	52400	91	50200	910	14500	16.4	7600	70
NYSR054S1	36-42.9945- 73.9851-4-50-000	7.2	170	1.50	3.5	14	36	55800	134	62800	1670	11200	16.0	9200	90
NYSR055S1	36-42.9654- 73.9181-4-50-000	7.2	217	1.40	3.9	8	36	82700	105	47900	1240	17700	13.2	14200	140
NYSR056S1	36-42.9884- 73.9234-4-50-000	8.3	350	1.60	3.5	8	35	53000	102	52700	870	11400	12.6	M	100
NYSR057S1	36-42.9906- 73.8840-4-50-000	7.7	1140	7.30	3.4	8	54	60300	133	55100	1170	15800	14.5	13500	90
NYSR058S1	36-42.9698- 73.8809-4-50-000	8.1	320	2.30	4.0	11	60	74500	121	61100	2010	18000	8.2	20600	150
NYSR059S1	36-42.9407- 73.8756-4-50-000	7.4	355	3.00	2.8	8	29	48700	95	38100	930	11700	2.9	M	80
NYSR060S1	36-42.9853- 73.7705-4-50-000	7.8	294	2.50	3.6	8	60	30100	66	36900	610	9300	9.0	9200	50
NYSR061S1	36-42.9418- 73.6875-4-50-000	8.0	660	7.00	2.5	9	36	53400	111	40300	880	10800	12.6	6400	80
NYSR062S1	36-42.9732- 73.7239-4-50-000	8.0	170	1.70	3.0	13	60	32300	88	40300	620	8800	10.0	8400	50
NYSR063S1	36-42.9666- 73.6867-4-50-000	7.9	240	2.50	4.4	11	6	40100	98	37600	1100	10400	9.3	11500	60
NYSR064S1	36-42.9880- 73.6892-4-50-000	8.3	1600	11.60	3.0	7	29	39900	73	29900	1740	9600	7.5	5900	60
NYSR065S1	36-42.9819- 73.6513-4-50-000	8.3	470	3.60	3.0	9	16	54700	109	34700	1020	9500	9.0	4900	80
NYSR066S1	36-42.9579- 73.6495-4-50-000	7.6	345	3.30	3.0	7	24	48400	82	34600	540	9100	6.4	M	70
NYUL101S1	36-42.0132- 73.9540-4-50-000	7.3	410	3.10	3.6	13	6	66900	89	38900	820	7600	5.4	5000	100
NYUL102S1	36-42.0293- 73.9566-4-50-000	7.2	275	2.60	3.1	11		64400	83	38600	1840	5700	11.5	M	100
NYUL103S1	36-42.0175- 73.9782-4-50-000	7.7	415	2.90	2.8	10	14	68000	102	36300	1160	8800	12.7	5700	120
NYUL104S1	36-42.0452- 73.9964-4-50-000	M	M	M	3.4	11	11	65200	85	36000	570	5900	13.3	4600	120
NYUL105S1	36-42.0886- 73.9770-4-50-000	7.6	480	1.50	3.2	9	13	49800	85	31400	460	6400	12.1	4300	70
NYUL106S1	36-42.0974- 73.9457-4-50-000	8.7	1300	0.62	2.4	7	16	43700	33	17500	290	9300	5.7	4800	60
NYUL107S1	36-42.1126- 73.9732-4-50-000	7.9	485	2.15	3.1	12	7	49600	99	30200	370	7600	12.0	5100	70
NYUL108S1	36-42.1405- 73.9861-4-50-000	8.0	100	1.00	3.2	9	12	42400	80	21800	550	4800	9.3	M	60
NYWS001S1	36-42.9774- 73.2880-4-50-000	7.2	102	0.92	3.6	49		97300	555	45900	960	11300	11.2	4300	70
NYWS002S1	36-42.9807- 73.3285-4-50-000	7.7	80	0.68	3.6	16	19	76200	140	37900	1150	13500	10.5	6000	70
NYWS003S1	36-42.9765- 73.3644-4-50-000	7.9	182	2.30	2.9	9	17	M	98	27000	660	9600	7.5	M	70
NYWS004S1	36-42.9852- 73.3818-4-50-000	7.8	176	1.70	3.4	23	22	91500	267	35300	950	15600	9.1	6500	100
NYWS005S1	36-42.9593- 73.3853-4-50-000	7.8	170	1.33	3.2	19	24	58700	215	32700	580	10500	8.5	M	60
NYWS006S1	36-42.9575- 73.3642-4-50-000	7.5	410	4.50	3.0	12	17	62700	116	37200	1440	12700	9.3	5500	70
NYWS007S1	36-42.9576- 73.4509-4-50-000	8.2	239	2.40	2.2	10	18	57400	76	33300	840	12500	9.0	4100	70
NYWS008S1	36-42.9820- 73.4269-4-50-000	8.0	150	1.70	3.5	14	31	47000	121	23800	850	9200	7.3	M	60
NYWS009S1	36-42.9841- 73.4807-4-50-000	7.7	196	1.73	2.5	10	28	41400	77	18900	410	10600	5.1	4100	40
NYWS010S1	36-42.9555- 73.4825-4-50-000	7.8	207	2.20	2.4	7	15	59100	68	21500	680	14100	6.5	4400	70
NYWS011S1	36-42.9605- 73.5200-4-50-000	7.8	140	1.40	3.1	9	35	48600	88	22300	950	10900	6.2	4900	50
NYWS012S1	36-42.9799- 73.5184-4-50-000	7.4	181	2.00	2.8	9	20	M	86	29200	1210	15400	8.7	5600	60
NYWS013S1	36-42.9871- 73.5513-4-50-000	7.1	208	1.80	3.0	8	24	64100	78	28600		13500	6.9	M	90
NYWS014S1	36-42.9580- 73.5563-4-50-000	7.1	180	1.60	2.5	5		55600	60	27900	1360	10800	7.2	3400	60
NYWS015S1	36-42.9542- 73.6031-4-50-000	7.4	900	7.50	2.7	11	18	43800	105	33000	790	7700	8.8	5900	60
NYWS016S1	36-42.9801- 73.6098-4-50-000	9.1	245	3.00	3.3	13	39	53300	147	48600	1460	10400	10.4	8900	80
VTBE001S1	50-42.7831- 72.9583-4-50-000	6.8	29	0.10	3.9	7	19	M	95	36800	1040	15400	10.3	9600	80
VTBE002S1	50-42.7506- 72.9490-4-50-000	6.9	24	0.14	3.2	5	22	33200	47	33100	710	8000	9.3	M	50
VTBE003S1	50-42.7556- 72.9783-4-50-000	6.6	21	0.12	3.6	9	2	M	77	50900	1270	15800	0.3	18200	100
VTBE004S1	50-42.7857- 72.9806-4-50-000	6.4	20	0.08	4.2	16	82	42900	135	69500	1310	9000	16.7	M	50
VTBE005S1	50-42.8134- 72.9710-4-50-000	6.3	18	0.06	4.1	M	M	79700	M	M	1050	19300	M	11800	90

B-40

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

24

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
VTBE006S1	50-42.8454-72.9916-4-50-000	6.7	132	0.12	3.7	9	32	44400	78	29100	630	13900	10.5	5600	50
VTBE007S1	50-42.8269-73.0020-4-50-000	6.3	19	0.06	4.1	8	37	66700	94	37300	1270	20900	15.0	8700	100
VTBE008S1	50-42.7922-73.0307-4-50-000	6.8	39	0.20	4.3	15	69	41700	98	40500	700	13600	16.2	6500	50
VTBE009S1	50-42.7623-73.0542-4-50-000	7.2	50	0.50	3.5	11	36	76300	98	33600	840	15000	8.2	10900	70
VTBE010S1	50-42.7623-73.0834-4-50-000	6.9	22	0.08	2.4	3	18	26300	45	12800	250	7800	5.5	2300	20
VTBE011S1	50-42.7760-73.0865-4-50-000	6.4	20	0.04	4.0	7	48	68200	105	42400	1230	20500	15.4	11300	90
VTBE012S1	50-42.7563-73.1322-4-50-000	6.5	20	0.08	2.8	4	49	38100	69	18500	860	10700	6.8	3600	20
VTBE013S1	50-42.7824-73.1503-4-50-000	6.2	20	0.04	3.4	13	39	M	84	27000	M	M	8.5	M	M
VTBE014S1	50-42.8277-73.1304-4-50-000	6.2	21	0.08	5.8	11	39	M	76	25000	M	M	11.4	M	M
VTBE015S1	50-42.8037-73.1376-4-50-000	5.9	20	0.06	4.4	5	43	M	59	14000	M	M	10.0	M	M
VTBE016S1	50-42.7472-73.1883-4-50-000	6.9	37	0.34	2.8	10	49	M	85	27900	M	M	5.9	M	M
VTBE017S1	50-42.7527-73.2229-4-50-000	7.8	190	0.60	4.0	26	45	M	183	29400	M	M	6.0	M	M
VTBE018S1	50-42.7646-73.2498-4-50-000	7.9	101	1.30	2.4	21	M	M	217	55100	M	M	13.0	M	M
VTBE019S1	50-42.7881-73.2542-4-50-000	8.2	259	3.60	2.6	38	M	M	479	45900	M	M	9.8	M	M
VTBE020S1	50-42.8184-73.2636-4-50-000	8.5	220	0.02	2.6	31	M	M	391	40900	M	M	3.6	M	M
VTBE021S1	50-42.8396-73.2583-4-50-000	8.3	168	2.60	3.0	23	25	M	392	37300	M	M	8.7	M	M
VTBE022S1	50-42.7773-73.2271-4-50-000	8.4	241	5.00	1.5	6	16	M	54	19600	M	M	1.0	M	M
VTBE023S1	50-42.7997-73.1837-4-50-000	8.2	110	1.90	3.5	7	52	M	78	11800	M	M	2.8	M	M
VTBE024S1	50-42.8188-73.1794-4-50-000	8.0	202	3.20	2.1	7	38	M	M	9700	M	M	2.7	M	M
VTBE025S1	50-42.8260-73.2071-4-50-000	8.5	365	6.00	6.6	28	204	M	248	17600	M	M	4.4	M	M
VTBE026S1	50-42.8660-73.2130-4-50-000	8.1	252	0.01	2.1	10	22	M	125	21700	M	M	4.8	M	M
VTBE027S1	50-42.8956-73.2583-4-50-000	8.0	39	4.80	5.6	11	72	M	96	29900	M	M	6.5	M	M
VTBE028S1	50-42.9123-73.2644-4-50-000	8.3	29	4.60	2.7	8	19	M	83	31000	M	M	1.9	M	M
VTBE029S1	50-42.9196-73.1862-4-50-000	8.1	78	1.10	3.7	10	56	M	87	9100	M	M	3.6	M	M
VTBE030S1	50-42.8580-73.1792-4-50-000	8.2	148	2.40	4.3	14	81	M	110	16500	M	M	4.0	M	M
VTBE031S1	50-42.8788-73.1615-4-50-000	7.7	111	1.20	3.1	9	54	M	109	17700	M	M	4.8	M	M
VTBE032S1	50-42.9079-73.1221-4-50-000	6.0	13	0.06	9.2	22	108	M	179	49900	M	M	8.7	M	M
VTBE033S1	50-42.8896-73.1231-4-50-000	7.1	50	0.30	3.3	8	26	M	61	24500	M	M	8.6	M	M
VTBE034S1	50-42.8741-73.0880-4-50-000	7.2	79	0.34	3.3	9	36	M	99	23000	M	M	6.1	M	M
VTBE035S1	50-42.8910-73.0238-4-50-000	6.1	50	0.10	4.7	5	52	M	92	23900	M	M	17.8	M	M
VTBE036S1	50-42.8881-73.0098-4-50-000	6.2	19	0.08	6.7	15	87	56100	111	38700	570	17700	4.5	6600	70
VTBE037S1	50-42.9393-73.0881-4-50-000	5.6	15	0.04	7.7	20	58	M	208	55600	M	M	11.3	M	M
VTBE038S1	50-42.8816-72.9497-4-50-000	6.9	26	0.10	5.7	10	58	M	103	32300	M	M	17.8	M	M
VTBE039S1	50-42.9084-72.9460-4-50-000	5.9	18	0.08	9.1	16	122	M	108	46100	M	M	19.7	M	M
VTBE040S1	50-42.9179-72.9712-4-50-000	6.4	43	0.12	4.0	6	45	M	108	28600	M	M	21.6	M	M
VTBE052S1	50-42.9866-73.1668-4-50-000	8.3	270	5.40	1.9	6	19	M	53	11200	M	M	3.1	M	M
VTBE053S1	50-42.9635-73.1603-4-50-000	8.0	130	2.40	1.6	M	M	M	M	M	M	M	M	M	M
VTBE054S1	50-42.9596-73.1983-4-50-000	8.4	335	5.20	3.0	10	60	M	109	19000	M	M	2.6	M	M
VTBE055S1	50-42.9452-73.2228-4-50-000	8.2	119	2.60	2.0	9	31	M	97	14000	M	M	2.9	M	M
VTBE056S1	50-42.9476-73.2505-4-50-000	7.8	252	3.80	2.4	21	28	M	274	26500	M	M	5.3	M	M
VTBE059S1	50-42.9622-73.2374-4-50-000	7.4	317	4.40	2.6	19	M	M	212	30900	M	M	4.0	M	M
VTBE060S1	50-42.9720-73.2101-4-50-000	7.7	129	1.60	2.8	19	34	M	207	20200	M	M	4.5	M	M
VTW1001S1	50-42.8701-72.6243-4-50-000	8.3	59	0.56	1.9	8	18	M	77	49100	1370	14500	19.2	M	110
VTW1002S1	50-42.8710-72.6437-4-50-000	8.4	65	0.40	1.6	5	5	M	52	41100	1030	19000	17.2	7100	90
VTW1003S1	50-42.8508-72.6387-4-50-000	8.3	122	1.00	1.6	8	8	44300	65	45400	1280	13900	9.0	M	100
VTW1004S1	50-42.8522-72.6028-4-50-000	8.2	130	1.08	2.7	4	19	49500	57	45400	2300	15400	17.4	M	100
VTW1005S1	50-42.8337-72.6501-4-50-000	8.3	92	0.92	1.5	5	M	54300	78	48600	920	14800	19.4	5700	100
VTW1006S1	50-42.8065-72.6656-4-50-000	8.6	55	0.60	1.7	6	7	M	51	40200	1220	16400	16.1	9800	120
VTW1007S1	50-42.7790-72.6727-4-50-000	8.6	48	0.32	1.5	6	7	M	54	53800	1660	18300	21.1	10500	120
VTW1008S1	50-42.7615-72.6612-4-50-000	8.5	50	0.56	1.6	5	7	85300	53	47200	2050	23300	0.5	13200	180
VTW1009S1	50-42.7704-72.6342-4-50-000	8.4	90	0.72	1.4	5	7	52300	43	41400	1350	13200	6.4	8800	110
VTW1010S1	50-42.8098-72.6112-4-50-000	8.4	140	1.40	1.7	3	9	M	51	40900	1410	14500	17.7	9900	100
VTW1011S1	50-42.7850-72.5992-4-50-000	8.8	191	1.20	1.9	4	M	M	59	50300	1710	13700	18.3	12200	120

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

25

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
VTW1012S1	50-42.8169-72.5749-4-50-000	8.7	135	1.30	1.6	5	7	702C0	38	36200	1640	18700	14.3	9700	140
VTW1013S1	50-42.7509-72.5703-4-50-000	8.6	52	0.40	1.7	5	5	427C0	41	27100	820	12400	0.3	4900	70
VTW1014S1	50-42.7752-72.5647-4-50-000	M	M	M	2.2	3	28	530C0	95	56500	1440	14900	23.0	11700	90
VTW1015S1	50-42.9358-72.5620-4-50-000	8.2	85	1.04	2.4	8	28	507C0	131	71000	1410	14900	28.1	M	110
VTW1016S1	50-42.9157-72.5531-4-50-000	8.3	167	1.90	1.5	4	13	453C0	61	37500	1320	11800	13.8	10000	70
VTW1017S1	50-42.8852-72.5644-4-50-000	8.6	210	2.00	1.9	M	M	571C0	M	M	1210	13300	M	6700	90
VTW1018S1	50-42.7592-72.5173-4-50-000	8.7	71	0.40	2.9	13	19	476C0	118	34900	1300	12800	14.4	11000	70
VTW1019S1	50-42.7353-72.4694-4-50-000	8.1	85	0.48	2.5	9	18	624C0	79	36500	2470	18800	16.0	16600	110
VTW1041S1	50-42.9845-72.5128-4-50-000	8.1	90	0.28	3.4	15	.	M	119	40800	M	M	4.1	M	M
VTW1042S1	50-42.9857-72.4644-4-50-000	8.2	107	0.92	2.8	18	8	M	116	38300	M	M	13.9	M	M
VTW1050S1	50-42.9847-72.5849-4-50-000	8.7	90	1.20	2.4	M	M	M	M	M	M	M	M	M	M
VTW1051S1	50-42.9891-72.6537-4-50-000	8.6	45	0.40	1.6	4	15	M	64	31700	M	M	16.1	M	M
VTW1061S1	50-42.9353-72.6104-4-50-000	8.0	130	0.92	2.2	6	13	M	35	41700	M	M	15.6	M	M
VTW1062S1	50-42.9154-72.6146-4-50-000	8.4	90	0.80	2.1	5	3	M	69	44000	M	M	18.8	M	M
VTW1063S1	50-42.9188-72.6756-4-50-000	8.1	60	0.64	2.6	7	26	M	79	47200	M	M	19.1	M	M
VTW1064S1	50-42.8779-72.6926-4-50-000	8.3	88	0.40	1.5	5	9	M	36	37900	M	M	15.8	M	M
VTW1065S1	50-42.8826-72.7444-4-50-000	8.3	70	0.40	1.8	8	14	M	37	71700	M	M	27.8	M	M
VTW1066S1	50-42.9028-72.7322-4-50-000	8.4	32	0.40	1.9	5	13	M	57	53900	M	M	19.1	M	M
VTW1067S1	50-42.9105-72.7137-4-50-000	8.2	45	0.48	1.8	5	17	M	65	53000	M	M	22.5	M	M
VTW1068S1	50-42.9391-72.7267-4-50-000	8.1	33	0.36	2.0	7	19	M	87	65100	M	M	25.3	M	M
VTW1069S1	50-42.9443-72.7448-4-50-000	8.2	80	0.80	1.9	6	15	M	52	62900	M	M	24.2	M	M
VTW1070S1	50-42.9799-72.7491-4-50-000	8.3	110	1.10	2.1	3	17	M	68	63900	M	M	23.5	M	M
VTW1071S1	50-42.9476-72.6747-4-50-000	8.6	60	0.60	2.1	3	11	M	65	58700	M	M	24.9	M	M
VTW1072S1	50-42.9588-72.6989-4-50-000	8.2	30	0.36	1.5	.	.	M	-22	.	M	M	1.0	M	M
VTW1075S1	50-42.9865-72.7786-4-50-000	7.9	39	0.52	2.5	7	29	M	116	52000	M	M	25.3	M	M
VTW1079S1	50-42.9650-72.8893-4-50-000	7.5	40	0.44	4.0	11	62	M	138	53600	M	M	19.8	M	M
VTW1080S1	50-42.9394-72.8547-4-50-000	7.4	90	0.44	4.2	7	80	M	135	71900	M	M	30.2	M	M
VTW1081S1	50-42.9643-72.8390-4-50-000	M	M	M	2.8	7	23	53700	104	55900	1510	16000	7.0	M	120
VTW1082S1	50-42.9267-72.8334-4-50-000	7.3	122	0.36	1.9	4	16	94700	94	66500	2940	22700	31.0	12600	220
VTW1083S1	50-42.9599-72.7918-4-50-000	7.5	108	0.32	1.6	3	11	66900	55	60500	2290	16900	28.1	9400	140
VTW1084S1	50-42.8646-72.8573-4-50-000	7.6	89	0.36	4.6	8	80	62200	157	70200	1560	19300	24.9	M	140
VTW1085S1	50-42.7575-72.7415-4-50-000	7.2	40	0.40	1.4	5	14	79000	65	73700	1970	24900	30.5	14000	220
VTW1086S1	50-42.7667-72.6965-4-50-000	7.9	49	0.56	2.7	7	10	52200	62	39300	1140	12100	15.0	10800	110
VTW1087S1	50-42.7928-72.7119-4-50-000	8.0	82	0.80	2.1	5	12	55800	75	51600	1450	13800	18.7	M	120
VTW1088S1	50-42.8051-72.6983-4-50-000	8.1	45	0.36	1.7	4	8	74100	49	53500	2210	25000	21.2	11900	180
VTW1089S1	50-42.8164-72.7393-4-50-000	7.9	30	0.36	2.1	3	33	58400	55	86300	2640	16900	28.2	3200	180
VTW1090S1	50-42.8385-72.7258-4-50-000	7.7	40	0.40	1.9	5	11	81900	61	64300	2900	26200	22.5	17900	190
VTW1091S1	50-42.8546-72.8382-4-50-000	7.7	90	0.28	3.0	5	42	59800	113	78000	1470	19900	28.7	M	140
VTW1092S1	50-42.8907-72.8218-4-50-000	7.7	60	0.32	5.7	11	108	63800	162	94700	2390	16800	38.9	13600	130
VTW1093S1	50-42.8969-72.8566-4-50-000	7.8	55	0.36	4.8	10	77	M	167	67100	1800	21400	23.8	18300	100
VTW1094S1	50-42.9153-72.8839-4-50-000	8.1	40	0.48	2.2	5	20	83900	90	50900	750	14100	15.2	M	70
VTW1095S1	50-42.8849-72.8962-4-50-000	7.6	45	0.40	2.6	5	23	67000	107	41200	680	16300	14.5	M	70
VTW1096S1	50-42.8211-72.8844-4-50-000	M	M	M	2.9	8	24	103500	95	53300	1160	20100	16.2	12300	100
VTW1097S1	50-42.7683-72.9242-4-50-000	7.7	120	0.60	3.1	5	33	54600	87	41400	1160	16400	16.3	M	70
VTW1098S1	50-42.7905-72.8726-4-50-000	7.8	32	0.28	2.8	6	27	58200	97	34800	670	18600	14.4	6200	50
VTW1099S1	50-42.7525-72.8499-4-50-000	7.7	30	0.32	1.7	3	13	65400	59	49700	1130	21100	21.2	8400	130
VTW1100S1	50-42.7508-72.8170-4-50-000	M	M	M	1.6	5	2	52900	34	50000	1330	17500	22.6	M	140
VTW1101S1	50-42.7836-72.8098-4-50-000	7.7	83	0.32	6.6	7	151	78000	208	93500	2380	23900	32.3	26100	180
VTW1102S1	50-42.8082-72.8199-4-50-000	7.7	40	0.40	2.6	5	51	69000	159	57100	1140	24900	22.2	9700	100
VTW1103S1	50-42.8313-72.7683-4-50-000	M	M	M	1.7	4	15	53700	60	50900	1510	19200	23.2	M	170
VTW1104S1	50-42.8158-72.8086-4-50-000	7.6	30	0.24	1.8	3	17	59200	60	57600	1680	20200	25.5	11300	190
VTW1105S1	50-42.7872-72.7721-4-50-000	7.7	40	0.32	1.8	5	19	57300	87	50700	470	18100	1.1	M	140
VTW1106S1	50-42.7602-72.7655-4-50-000	7.8	68	0.40	1.9	4	29	64900	122	52600	1380	32800	24.5	10100	150

B-42

TABLE B-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA - SEDIMENTS-- ALBANY

SHEET

26

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPM	TH PPM	HF PPM	AL PPM	CE PPM	FE PPM	MN PPM	NA PPM	SC PPM	TI PPM	V PPM
VTW1120S1	50-42.9406- 72.9919-4-5C-000	6.3	22	0.06	6.5	11	82	50800	137	31100	840	16900	20.8	8400	90
VTW1121S1	50-42.9733- 72.9766-4-5C-000	4.6	21	0.02	2.5	.	32	82400	68	31200	910	31200	20.1	7400	140
VTW1122S1	50-42.9657- 73.0043-4-5C-000	5.2	15	0.04	8.5	11	125	52300	118	30300	780	17300	18.9	8100	80

APPENDIX C: Stream Water Reconnaissance Data

Key data reported for stream water sites included:

- water chemistry measurements (pH, conductivity, and alkalinity)
- elemental analyses (in order of appearance in figures) for U, Al, Br, Cl, Dy, F, Mn, Na, and V

LIST OF FIGURES

- C-1 Areal Distribution of Uranium Concentrations in Stream Water
- C-2 Areal Distribution of Aluminum Concentrations in Stream Water
- C-3 Areal Distribution of Bromine Concentrations in Stream Water
- C-4 Areal Distribution of Chlorine Concentrations in Stream Water
- C-5 Areal Distribution of Dysprosium Concentrations in Stream Water
- C-6 Areal Distribution of Fluorine Concentrations in Stream Water
- C-7 Areal Distribution of Manganese Concentrations in Stream Water
- C-8 Areal Distribution of Sodium Concentrations in Stream Water
- C-9 Areal Distribution of Vanadium Concentrations in Stream Water

Figures on Microfiche:

Log Histograms and Cumulative Frequency Plots for U, Al, Br, Cl, Dy, Fl, Mn, Na, and V; see microfiche labeled "Surface Water Plots."

LIST OF TABLES

- C-1 Key Field Measurements and Analytical Data - Stream Water

FIGURE C-1. Areal Distribution of Uranium Concentrations in Stream Water

ALBANY 1x2' Sheet
Aluminum In Surface Water
1277 Values Above D.L.

Aluminum concentration - p.p.b.

+ < 7.2	o 21.9- 26.6	○ 46.5- 62.3	⊙ 109.5- 146.3	● 252.8- 448.8
x 7.2- 15.2	o 26.6- 33.9	○ 62.3- 84.1	⊙ 146.3- 194.1	◆ 448.8- 852.7
• 15.2- 21.9	o 33.9- 46.5	○ 84.1- 109.5	⊙ 194.1- 252.8	★ > 852.7

FIGURE C-2. Areal Distribution of Aluminum Concentrations in Stream Water

FIGURE C-3. Areal Distribution of Bromine Concentrations in Stream Water

ALBANY
Chlorine In Surface Water
1283 Values Above D.L.

Chlorine concentration - p.p.b.

+ < 3300.0	• 4000.0- 4300.0	○ 5300.0- 6300.0	⊙ 10800.0- 15400.0	● 33400.0- 49600.0
• 3300.0- 3700.0	○ 4300.0- 4600.0	○ 6300.0- 8100.0	⊙ 15400.0- 22200.0	◆ 49600.0- 109400.0
• 3700.0- 4000.0	○ 4600.0- 5300.0	○ 8100.0- 10800.0	● 22200.0- 33400.0	★ > 109400.0

FIGURE C-4. Areal Distribution of Chlorine Concentrations in Stream Water

ALBANY *1x2° Sheet*
Dysprosium In Surface Water
80 Values Above D.L.

Dysprosium concentration - p.p.b.

+ < 0.023	○ 0.026- 0.030	○ 0.049- 0.066	⊙ 0.761- 1.175	● 1.741- 1.968
× 0.023- 0.025	○ 0.030- 0.036	○ 0.066- 0.090	⊙ 1.175- 1.344	◆ 1.968- 7.063
• 0.025- 0.026	○ 0.036- 0.049	⊙ 0.090- 0.761	⊙ 1.344- 1.741	★ > 7.063

FIGURE C-5. Areal Distribution of Dysprosium Concentrations in Stream Water

ALBANY
Fluorine In Surface Water
617 Values Above D.L. *1x2' Sheet*

Fluorine concentration - p.p.b.

FIGURE C-6. Areal Distribution of Fluorine Concentrations in Stream Water

ALBANY *1x2" Sheet*
Manganese In Surface Water
1092 Values Above D.L.

Manganese concentration - p.p.b.					
+ < 1.8	o 9.4- 14.5	○ 30.6- 40.9	⊙ 101.8- 149.2	● 318.3- 584.5	
+ 1.8- 6.0	o 14.5- 21.1	○ 40.9- 63.3	⊙ 149.2- 198.3	◆ 584.5- 2392.0	
+ 6.0- 9.4	o 21.1- 30.6	○ 63.3- 101.8	⊙ 198.3- 318.3	★ > 2392.0

FIGURE C-7. Areal Distribution of Manganese Concentrations in Stream Water

ALBANY
Sodium
1282

1'x2' Sheet
In Surface Water
Values Above D.L.

Sodium concentration - p.p.b.

+ < 360.0	o 780.0- 1120.0	o 2070.0- 2980.0	o 6440.0- 8440.0	● 16040.0- 28940.0
x 380.0- 580.0	o 1120.0- 1540.0	o 2980.0- 4700.0	o 8440.0- 11100.0	◆ 28940.0- 49020.0
• 580.0- 780.0	o 1540.0- 2070.0	o 4700.0- 6440.0	o 11100.0- 16040.0	★ > 49020.0

FIGURE C-8. Areal Distribution of Sodium Concentrations in Stream Water

FIGURE C-9. Areal Distribution of Vanadium Concentrations in Stream Water

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER-- ALBANY SHEET

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
CTHA002R	09-42.0202-72.9496-4-51-000	6.2	300	0.16	-0.002	46	.	103000	0.818	.	M	.	34220	-0.1	0.00
CTHA003R	09-42.0358-72.8950-4-51-000	4.9	30	0.01	0.003	453	71.0	9900	-0.001	95	M	394.2	2280	-0.1	0.27
CTHA004R	09-42.0263-72.8376-4-51-000	6.6	32	0.10	0.028	67	45.0	9300	-0.001	15	M	38.3	2890	0.3	0.89
CTHA005R	09-42.0209-72.7341-4-51-000	7.4	239	0.48	0.422	80	55.2	16400	-0.001	46	M	97.6	6460	3.3	1.77
CTHA007R	09-42.0241-72.6783-4-51-000	7.6	238	0.90	0.168	50	.	28600	-0.001	85	M	127.5	9970	1.0	0.71
CTHA008R	09-42.0172-72.6543-4-51-000	7.1	120	0.40	0.042	100	61.0	11100	0.066	96	M	175.7	4830	1.6	0.35
CTHA010R	09-42.0160-72.6049-4-51-000	8.0	300	1.30	0.688	89	.	36700	-0.001	122	M	106.8	11790	1.6	2.29
CTHA020R	09-42.0002-72.8972-4-51-000	6.9	72	0.10	0.019	138	40.8	7500	-0.001	37	M	103.0	10190	-0.1	0.26
CTHA081R	09-42.0186-72.5476-4-51-000	6.6	180	0.90	0.030	55	60.5	14800	-0.001	24	M	194.9	13650	0.4	0.17
CTHA082R	09-42.0027-72.5508-4-51-000	6.4	1000	0.44	-0.002	119	.	147100	-0.001	.	M	299.4	77480	-0.1	0.00
CTL1153R	09-42.0198-73.3401-4-51-000	7.7	360	3.20	0.505	74	286.9	8500	-0.001	.	M	200.3	9700	0.4	1.40
CTL1154R	09-42.0280-73.2488-4-51-000	8.0	210	2.20	0.181	46	19.3	4400	-0.001	21	M	104.5	9100	0.2	0.86
CTL1156R	09-42.0332-73.3986-4-51-000	7.6	470	5.60	0.162	51	48.6	7200	-0.001	39	M	600.7	9350	-0.1	0.34
CTL1157R	09-42.0329-73.2947-4-51-000	7.3	300	3.70	0.048	43	15.2	5900	-0.001	.	M	273.2	8640	-0.1	0.16
CTL1161R	09-42.0319-73.2059-4-51-000	7.5	70	0.70	0.045	75	22.7	6200	-0.001	41	M	84.2	8910	0.5	0.64
CTL1162R	09-42.0340-73.1321-4-51-000	7.1	40	0.26	0.007	104	.	4500	-0.001	26	M	78.0	8740	0.6	0.18
CTL1165R	09-42.0133-73.0959-4-51-000	7.3	40	0.26	-0.002	65	8.1	4700	-0.001	62	M	74.9	8760	0.3	-0.04
CTL1166R	09-42.0325-73.0594-4-51-000	6.7	35	0.12	-0.002	76	32.7	4200	-0.001	30	M	76.7	8860	-0.1	-0.05
CTT0001R	09-42.0061-72.4982-4-51-000	7.0	600	0.70	0.057	188	.	47200	-0.001	397	M	221.0	60960	5.2	0.10
CTT0002R	09-42.0185-72.4475-4-51-000	7.3	95	0.80	0.017	72	.	7000	-0.001	17	M	118.8	10510	-0.1	0.18
CTT0011R	09-42.0282-72.3912-4-51-000	7.0	70	0.30	0.026	50	26.9	6000	-0.001	62	M	123.3	10530	0.2	0.37
CTT0012R	09-42.0175-72.3464-4-51-000	6.8	50	0.30	-0.002	51	34.8	5100	-0.001	29	M	118.3	9650	-0.1	-0.03
CTT0013R	09-42.0207-72.2798-4-51-000	6.8	40	0.18	0.003	86	29.8	4500	-0.001	34	M	111.8	9840	-0.1	0.08
CTT0015R	09-42.0127-72.1455-4-51-000	6.3	40	0.16	-0.002	47	17.0	23700	-0.001	20	M	136.7	15280	-0.1	0.00
CTT0018R	09-42.0157-72.1857-4-51-000	6.6	50	0.30	-0.002	63	26.2	5100	-0.001	57	M	142.5	9500	0.3	-0.03
CTT0019R	09-42.0209-72.2497-4-51-000	6.8	30	0.16	-0.002	67	56.5	4400	0.057	.	M	112.5	9210	-0.1	-0.06
MABE001R	25-42.7325-73.0676-4-51-000	6.1	50	0.20	-0.002	60	17.7	7600	-0.001	.	M	20.7	2340	-0.1	-0.03
MABE002R	25-42.7085-73.0714-4-51-000	6.5	80	0.85	0.022	271	35.8	24800	-0.001	.	M	49.9	8490	-0.1	0.12
MABE003R	25-42.7093-73.0358-4-51-000	6.3	45	0.14	-0.002	160	25.0	8000	-0.001	.	M	14.3	2150	-0.1	-0.03
MABE004R	25-42.6697-73.0095-4-51-000	6.5	90	0.14	-0.002	121	.	48400	-0.001	.	M	11.9	14940	-0.1	0.00
MABE005R	25-42.6616-72.9713-4-51-000	5.7	35	0.12	-0.002	96	18.9	4900	-0.001	20	M	13.4	1090	-0.1	-0.05
MABE006R	25-42.6876-73.0010-4-51-000	6.3	20	0.08	-0.002	92	30.1	4800	-0.001	14	M	13.9	800	0.2	-0.09
MABE007R	25-42.6902-73.0479-4-51-000	6.5	20	0.30	-0.002	131	30.8	11900	-0.001	.	M	18.7	4060	-0.1	-0.09
MABE008R	25-42.6608-73.0411-4-51-000	6.5	40	0.12	0.006	121	24.1	6300	-0.001	24	M	14.5	1290	-0.1	0.15
MABE009R	25-42.6714-73.0871-4-51-000	8.0	260	3.60	0.447	131	.	9800	-0.001	.	M	49.3	2670	-0.1	1.72
MABE010R	25-42.7135-73.1086-4-51-000	7.3	120	0.85	0.023	100	15.2	10300	-0.001	.	M	21.2	4100	-0.1	0.19
MABE011R	25-42.7408-73.1178-4-51-000	6.2	50	0.16	-0.002	214	17.8	5700	-0.001	21	M	100.8	1450	-0.1	-0.03
MABE012R	25-42.6727-73.1346-4-51-000	6.8	225	2.20	0.223	63	.	7800	-0.001	.	M	65.2	2540	-0.1	0.99
MABE013R	25-42.6863-73.1613-4-51-000	7.1	285	3.90	0.555	127	.	4900	-0.001	.	M	64.0	950	0.3	1.95
MABE014R	25-42.7370-73.1906-4-51-000	7.8	240	3.10	0.199	134	.	7800	-0.001	.	M	75.9	3140	-0.1	0.83
MABE015R	25-42.5091-73.2877-4-51-000	6.3	35	0.22	-0.002	252	17.9	4300	-0.001	16	M	19.8	470	-0.1	-0.05
MABE016R	25-42.5144-73.2494-4-51-000	7.3	190	2.20	0.132	99	.	4600	-0.001	.	M	.	410	0.3	0.69
MABE017R	25-42.5471-73.2502-4-51-000	6.9	130	1.50	0.154	227	.	5900	-0.001	.	M	34.3	1090	-0.1	1.18
MABE018R	25-42.5790-73.2512-4-51-000	7.0	60	0.55	0.006	381	41.9	4400	-0.001	19	M	24.6	590	-0.1	0.10
MABE019R	25-42.5421-73.3177-4-51-000	6.8	100	0.85	0.023	149	.	6800	-0.001	.	M	24.9	1810	0.2	0.23
MABE020R	25-42.5707-73.3037-4-51-000	6.8	50	0.30	-0.002	165	22.1	4400	-0.001	28	M	16.5	830	0.3	-0.03
MABE021R	25-42.5944-73.2932-4-51-000	6.6	30	0.10	-0.002	120	23.6	4500	-0.001	28	M	14.8	230	-0.1	-0.06
MABE022R	25-42.6240-73.2807-4-51-000	6.6	50	0.28	-0.002	114	25.3	4400	-0.001	22	M	15.8	490	-0.1	-0.03
MABE023R	25-42.6566-73.2618-4-51-000	7.2	180	1.70	0.234	83	25.0	6400	-0.001	.	M	68.0	1290	-0.1	1.30
MABE024R	25-42.6804-73.2549-4-51-000	6.5	120	1.10	0.058	404	.	5300	-0.001	.	M	27.9	930	-0.1	0.48
MABE025R	25-42.7014-73.2558-4-51-000	6.5	90	0.70	0.002	138	45.9	12700	-0.001	.	M	18.3	4190	-0.1	0.02
MABE026R	25-42.7079-73.2237-4-51-000	6.9	160	0.90	0.011	60	.	19900	-0.001	.	M	27.3	6430	0.3	0.07
MABE027R	25-42.7382-73.2426-4-51-000	6.6	70	0.54	-0.002	165	22.6	4700	-0.001	.	M	20.6	680	-0.1	-0.02

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY

SHEET

2

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MABE028R	25-42.6702- 73.2121-4-51-000	8.4	280	4.20	0.346	145	.	4500	-0.031	15	M	.	430	-0.1	1.24
MABE029R	25-42.6442- 73.2363-4-51-000	7.7	150	1.40	0.095	67	36.4	8100	-0.001	.	M	.	2850	-0.1	0.63
MABE030R	25-42.6274- 73.2271-4-51-000	8.1	215	1.90	0.229	107	31.8	12100	-0.001	.	M	23.1	4680	-0.1	1.07
MABE031R	25-42.6033- 73.2454-4-51-000	7.2	150	1.90	0.061	196	.	9000	-0.001	.	M	31.2	2220	-0.1	0.41
MABE032R	25-42.5857- 73.2282-4-51-000	7.6	195	2.50	0.167	244	20.5	4600	0.030	.	M	.	540	-0.1	0.86
MABE033R	25-42.5500- 73.2124-4-51-000	7.1	95	1.00	0.022	159	38.2	4700	-0.001	.	M	17.2	430	-0.1	0.23
MABE034R	25-42.5103- 73.2117-4-51-000	7.7	430	4.20	0.428	232	.	17500	-0.001	.	M	59.8	6740	-0.1	1.00
MABE035R	25-42.4883- 73.3125-4-51-000	6.1	30	0.16	-0.002	148	38.6	4500	-0.001	15	M	18.9	640	-0.1	-0.06
MABE036R	25-42.4867- 73.2905-4-51-000	6.6	120	1.35	0.088	130	.	5100	0.773	.	M	40.9	460	0.2	0.73
MABE037R	25-42.4697- 73.2573-4-51-000	7.7	230	1.05	0.227	416	.	11200	-0.001	.	M	52.0	3340	-0.1	0.99
MABE038R	25-42.4610- 73.2244-4-51-000	6.9	290	2.80	0.310	201	26.2	20000	-0.001	.	M	148.3	7130	-0.1	1.07
MABE039R	25-42.5243- 73.1926-4-51-000	7.1	115	1.40	0.012	125	.	4900	-0.001	16	M	39.1	1090	-0.1	0.10
MABE040R	25-42.5649- 73.1740-4-51-000	6.7	85	0.70	0.034	129	30.7	4400	-0.001	.	M	23.1	900	-0.1	0.40
MABE041R	25-42.5956- 73.1464-4-51-000	6.6	40	0.20	-0.002	225	28.0	4400	-0.001	.	M	20.0	350	-0.1	-0.04
MABE042R	25-42.6280- 73.1463-4-51-000	7.4	175	2.10	0.185	367	.	4700	-0.001	.	M	73.2	830	-0.1	1.06
MABE043R	25-42.6490- 73.0963-4-51-000	6.9	335	3.80	0.479	107	.	6100	-0.001	.	M	119.5	2130	0.4	1.43
MABE044R	25-42.6134- 73.1017-4-51-000	8.0	140	1.40	0.149	853	45.2	6500	-0.001	.	M	.	2120	0.8	1.06
MABE045R	25-42.6164- 73.0641-4-51-000	6.4	25	0.08	-0.002	399	32.3	4500	-0.001	.	M	50.9	1060	-0.1	-0.07
MABE046R	25-42.6228- 73.0368-4-51-000	6.6	30	0.16	-0.002	169	24.6	4500	0.041	27	M	43.5	1300	-0.1	-0.06
MABE047R	25-42.6198- 73.0103-4-51-000	6.3	30	0.10	-0.002	140	30.4	4400	-0.001	16	M	38.0	1290	0.2	-0.06
MABE048R	25-42.6280- 72.9764-4-51-000	6.5	35	0.12	-0.002	300	16.4	5000	-0.001	14	M	43.0	1400	-0.1	-0.05
MABE049R	25-42.5861- 73.0042-4-51-000	6.3	25	0.08	-0.002	148	195.4	4400	-0.001	14	M	36.0	1020	-0.1	-0.07
MABE050R	25-42.5519- 73.0050-4-51-000	6.4	25	0.14	-0.002	123	.	4700	-0.001	24	M	43.3	1340	-0.1	-0.07
MABE051R	25-42.5877- 73.0433-4-51-000	6.0	20	0.04	-0.002	349	16.8	4300	-0.001	.	M	53.4	900	0.3	-0.09
MABE052R	25-42.5609- 73.0502-4-51-000	6.3	40	0.18	0.020	114	18.0	4400	-0.001	18	M	60.1	1140	-0.1	0.50
MABE053R	25-42.5828- 73.0851-4-51-000	6.8	110	1.00	0.078	648	19.6	4800	-0.001	19	M	44.5	2160	0.5	0.71
MABE054R	25-42.5872- 73.1251-4-51-000	7.3	270	3.30	0.541	1123	.	6100	-0.001	.	M	122.8	860	0.9	2.00
MABE055R	25-42.5570- 73.1246-4-51-000	7.0	240	2.90	0.194	56	.	6000	0.032	.	M	76.1	2580	-0.1	0.81
MABE056R	25-42.4867- 73.1441-4-51-000	6.6	110	0.85	0.021	129	3089.0	6600	-0.001	12	M	.	3450	0.2	0.19
MABE057R	25-42.4961- 73.1118-4-51-000	6.7	40	0.25	0.031	242	.	5100	-0.001	19	M	13.5	640	-0.1	0.78
MABE058R	25-42.5004- 73.0835-4-51-000	6.5	35	0.10	12.160	296	.	3700	-0.001	.	M	.	1530	0.3	347.43
MABE059R	25-42.4880- 73.0466-4-51-000	6.4	35	0.08	0.010	269	4835.0	3700	-0.001	31	M	28.2	1610	-0.1	0.29
MABE060R	25-42.5109- 73.0273-4-51-000	6.2	30	0.08	0.013	207	.	3100	-0.001	18	M	.	1380	-0.1	0.43
MABE061R	25-42.5261- 73.0610-4-51-000	6.7	30	0.08	0.016	146	.	4800	-0.001	28	M	20.7	760	-0.1	0.53
MABE062R	25-42.5510- 73.0442-4-51-000	6.5	40	0.18	-0.002	154	.	3800	0.037	21	M	.	1820	0.3	-0.04
MABE063R	25-42.5386- 73.0161-4-51-000	6.7	30	0.12	-0.002	188	17.2	4700	-0.001	24	M	7.6	580	-0.1	-0.06
MABE064R	25-42.5035- 72.9920-4-51-000	6.7	30	0.08	-0.002	202	25.4	3900	-0.001	12	M	17.5	630	0.2	-0.06
MABE065R	25-42.4715- 72.9986-4-51-000	6.7	40	0.20	-0.002	200	10.9	4500	-0.001	16	M	14.6	890	0.3	-0.04
MABE066R	25-42.4616- 73.0279-4-51-000	6.8	30	0.12	-0.002	143	13.9	3800	-0.001	64	M	21.5	430	0.3	-0.06
MABE067R	25-42.4336- 73.0239-4-51-000	6.7	40	0.08	-0.002	323	40.8	5400	-0.001	24	M	26.3	1270	-0.1	-0.04
MABE068R	25-42.4354- 73.1190-4-51-000	6.9	85	0.65	0.004	93	.	5800	-0.001	16	M	22.7	1540	-0.1	0.05
MABE069R	25-42.4611- 73.1301-4-51-000	7.4	110	0.80	0.017	86	.	7300	-0.001	.	M	28.7	2090	0.2	0.15
MABE070R	25-42.4630- 73.1718-4-51-000	7.4	115	0.80	0.040	132	37.9	8900	-0.001	.	M	.	2200	-0.1	0.35
MABE071R	25-42.4580- 73.3455-4-51-000	6.6	70	0.50	-0.002	114	.	4700	-0.001	.	M	13.9	670	-0.1	-0.02
MABE072R	25-42.4512- 73.3140-4-51-000	6.9	120	1.00	0.058	60	39.4	6100	-0.001	12	M	.	1030	-0.1	0.48
MABE073R	25-42.4233- 73.3581-4-51-000	6.7	60	0.40	0.011	164	.	5000	0.036	.	M	7.5	350	-0.1	0.18
MABE074R	25-42.4183- 73.3120-4-51-000	7.5	280	2.90	0.104	61	.	11000	-0.001	.	M	58.5	3250	-0.1	0.37
MABE075R	25-42.4245- 73.2879-4-51-000	7.2	220	2.30	0.177	119	.	10900	-0.001	.	M	52.4	3580	0.5	0.80
MABE076R	25-42.4076- 73.2429-4-51-000	6.9	70	0.70	0.004	94	.	4300	-0.001	31	M	24.0	420	-0.1	0.06
MABE077R	25-42.4283- 73.1770-4-51-000	7.0	120	1.05	0.007	138	23.1	5900	-0.001	10	M	.	1440	-0.1	0.06
MABE078R	25-42.3989- 73.1261-4-51-000	6.9	75	0.55	-0.002	71	.	6300	-0.001	.	M	21.9	1540	-0.1	-0.02
MABE079R	25-42.3955- 73.0918-4-51-000	6.8	70	0.50	0.008	155	36.5	4500	-0.001	47	M	26.9	660	-0.1	0.11
MABE080R	25-42.4205- 73.0720-4-51-000	7.0	40	0.24	-0.002	93	30.6	4400	-0.001	26	M	.	630	0.3	-0.04

C-13

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER-- ALBANY SHEET

3

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MABE081R	25-42.3987-	73.0526-4-51-000	6.9	40	0.22	1.401	80	17.9	4500	-0.001	M	15.0	730	0.3	35.03
MABE082R	25-42.3531-	73.0910-4-51-000	6.7	75	0.42	-0.002	141	.	7600	-0.001	M	21.8	2150	-0.1	-0.02
MABE083R	25-42.3803-	73.0802-4-51-000	6.5	65	0.46	0.005	62	20.6	4200	-0.001	M	37.4	760	0.3	0.08
MABE084R	25-42.4086-	73.1415-4-51-000	6.7	60	0.34	-0.002	140	.	4300	-0.001	M	17.1	850	-0.1	-0.02
MABE085R	25-42.3425-	73.1361-4-51-000	6.8	25	0.10	-0.002	824	15.3	4400	-0.001	M	22.5	480	1.0	-0.07
MABE086R	25-42.3794-	73.1408-4-51-000	6.5	35	0.10	-0.002	162	.	4600	-0.001	M	29.3	580	-0.1	-0.05
MABE087R	25-42.3789-	73.1980-4-51-000	6.4	35	0.08	-0.002	330	15.9	3900	-0.001	M	35.2	320	-0.1	-0.05
MABE088R	25-42.3493-	73.1741-4-51-000	4.0	30	0.00	-0.002	290	19.6	4100	-0.001	M	18.4	480	0.5	-0.06
MABE089R	25-42.3463-	73.1887-4-51-000	5.6	30	0.06	-0.002	253	32.5	4400	-0.001	M	27.5	540	-0.1	-0.06
MABE090R	25-42.3183-	73.1051-4-51-000	6.6	45	0.22	-0.002	99	.	4300	-0.001	M	11.9	720	-0.1	-0.03
MABE091R	25-42.2972-	73.1882-4-51-000	7.6	315	1.90	0.059	70	.	49600	-0.001	M	.	18540	-0.1	0.19
MABE092R	25-42.3062-	73.2304-4-51-000	7.7	305	3.70	0.239	121	.	5500	-0.001	M	73.6	1390	-0.1	0.78
MABE093R	25-42.3050-	73.2687-4-51-000	7.6	300	4.40	0.323	68	30.9	8800	-0.001	M	139.2	2330	-0.1	1.08
MABE094R	25-42.2740-	73.2725-4-51-000	7.1	80	0.80	0.025	430	.	4100	-0.001	M	20.3	990	0.3	0.33
MABE095R	25-42.2562-	73.1899-4-51-000	6.8	50	0.36	0.002	156	.	4400	-0.001	M	17.1	700	-0.1	0.04
MABE096R	25-42.2866-	73.2166-4-51-000	7.2	50	0.36	-0.002	84	.	4800	-0.001	M	12.8	770	-0.1	-0.03
MABE097R	25-42.2724-	73.1777-4-51-000	6.9	60	0.48	0.031	194	12.1	5800	-0.001	M	46.1	430	0.1	0.52
MABE098R	25-42.2613-	73.1348-4-51-000	6.8	35	0.18	0.007	80	15.9	4100	-0.001	M	9.8	740	-0.1	0.20
MABE099R	25-42.2829-	73.1177-4-51-000	4.8	30	0.04	-0.002	195	22.0	5600	-0.001	M	25.0	1130	0.3	-0.06
MABE100R	25-42.3118-	73.0640-4-51-000	6.7	80	0.24	-0.002	542	14.0	12900	-0.001	M	8.0	3870	-0.1	-0.02
MABE101R	25-42.3021-	73.0402-4-51-000	6.6	80	0.54	0.015	51	14.0	8000	-0.001	M	41.3	2330	-0.1	0.19
MABE102R	25-42.2861-	73.0718-4-51-000	6.4	70	0.40	0.045	2135	.	7300	-0.001	M	6.7	2380	-0.1	0.64
MABE103R	25-42.2643-	73.0517-4-51-000	6.7	80	0.30	-0.002	605	.	14500	0.067	M	20.2	4240	-0.1	-0.02
MABE104R	25-42.2642-	73.0169-4-51-000	6.9	115	0.20	0.029	184	398.4	26200	-0.001	M	.	10070	-0.1	0.25
MABE105R	25-42.2213-	73.0403-4-51-000	6.6	110	0.16	-0.002	146	.	18500	-0.001	M	43.9	5490	-0.1	-0.01
MABE106R	25-42.2602-	73.1047-4-51-000	6.8	80	0.60	0.004	442	.	4800	-0.001	M	17.3	1380	-0.1	0.05
MABE107R	25-42.2168-	73.1021-4-51-000	6.5	110	0.44	-0.002	48	.	13900	-0.001	M	37.6	4520	-0.1	-0.01
MABE108R	25-42.1960-	73.0955-4-51-000	6.8	120	0.64	-0.002	67	12.5	16700	-0.001	M	.	6000	-0.1	-0.01
MABE109R	25-42.1855-	73.0541-4-51-000	6.7	80	0.28	-0.002	111	.	11000	-0.001	M	11.0	3760	-0.1	-0.02
MABE110R	25-42.1579-	73.0690-4-51-000	6.8	80	0.16	-0.002	55	28.2	10200	-0.001	M	.	3010	-0.1	-0.02
MABE111R	25-42.2134-	73.1257-4-51-000	6.5	35	0.14	-0.002	72	19.8	4000	-0.001	M	18.4	650	-0.1	-0.05
MABE112R	25-42.1944-	73.1257-4-51-000	6.4	50	0.24	-0.002	107	26.8	5400	-0.001	M	27.9	1140	0.3	-0.03
MABE113R	25-42.2337-	73.4331-4-51-000	6.7	110	1.35	0.069	270	.	4700	-0.001	M	96.1	1160	-0.1	0.63
MABE114R	25-42.2628-	73.4213-4-51-000	6.9	65	0.75	0.008	40	29.3	3800	-0.001	M	.	770	-0.1	0.12
MABE115R	25-42.2810-	73.4246-4-51-000	6.8	40	0.30	-0.002	46	17.0	4000	-0.001	M	12.0	420	-0.1	-0.04
MABE116R	25-42.3087-	73.4080-4-51-000	6.6	55	0.42	-0.002	121	25.8	3900	-0.001	M	18.6	550	0.3	-0.03
MABE117R	25-42.3423-	73.3967-4-51-000	7.1	185	2.20	0.157	88	10.1	7600	-0.001	M	100.9	3190	-0.1	0.85
MABE118R	25-42.3622-	73.3790-4-51-000	7.3	130	1.50	0.100	42	13.7	4200	-0.001	M	.	1020	-0.1	0.77
MABE119R	25-42.3496-	73.3629-4-51-000	8.0	260	4.20	0.188	30	.	6900	-0.001	M	50.3	2070	-0.1	0.72
MABE120R	25-42.3753-	73.3565-4-51-000	7.7	250	3.20	0.176	56	.	8800	0.090	M	76.6	2570	0.2	0.70
MABE121R	25-42.3968-	73.3779-4-51-000	7.1	90	1.40	0.006	67	22.4	3900	-0.001	M	52.7	800	-0.1	0.07
MABE122R	25-42.3977-	73.3616-4-51-000	7.0	430	5.60	0.211	42	29.0	18000	-0.001	M	.	10190	-0.1	0.49
MABE123R	25-42.4008-	73.3261-4-51-000	8.0	30	4.20	0.243	49	.	6800	-0.001	M	54.9	2050	-0.1	8.10
MABE124R	25-42.3802-	73.3190-4-51-000	7.6	310	1.30	0.021	116	21.2	4000	-0.001	M	45.6	630	0.4	0.07
MABE125R	25-42.3971-	73.2674-4-51-000	7.5	190	2.30	0.208	96	.	8000	-0.001	M	59.0	2440	0.4	1.09
MABE126R	25-42.3648-	73.2621-4-51-000	8.4	430	4.30	0.654	90	.	31000	-0.001	M	74.2	13170	-0.1	1.52
MABE127R	25-42.3503-	73.2998-4-51-000	8.0	210	2.80	0.144	81	.	7800	-0.001	M	49.8	2490	0.2	0.69
MABE128R	25-42.3026-	73.3351-4-51-000	8.0	250	2.40	0.306	103	.	12400	-0.001	M	.	4420	-0.1	1.22
MABE129R	25-42.3186-	73.3148-4-51-000	9.3	210	2.00	0.229	75	.	5300	-0.001	M	46.9	1740	-0.1	1.09
MABE130R	25-42.2751-	73.3205-4-51-000	7.6	230	2.30	0.400	62	13.5	7500	-0.001	M	91.3	1940	-0.1	1.74
MABE131R	25-42.2848-	73.3605-4-51-000	8.1	260	3.10	0.217	119	.	6700	-0.001	M	63.0	2360	-0.1	0.83
MABE132R	25-42.2690-	73.3803-4-51-000	7.1	260	1.25	0.011	176	31.5	4400	-0.001	M	54.7	1620	-0.1	0.04
MABE133R	25-42.2033-	73.3463-4-51-000	7.5	220	1.90	0.190	149	.	11200	-0.001	M	.	3890	-0.1	0.86

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER-- ALBANY SHEET

4

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MABE134R	25-42.1697-73.2556-4-51-000	7.1	130	1.40	0.100	66	.	7300	-0.031	.	M	29.7	2040	-0.1	0.77
MABE135R	25-42.1710-73.2169-4-51-000	7.2	200	2.70	0.155	78	.	8000	-0.001	16	M	.	1950	-0.1	0.78
MABE136R	25-42.1546-73.1930-4-51-000	6.2	50	0.28	0.006	187	13.4	7900	-0.001	.	M	.	1330	0.6	0.12
MABE137R	25-42.1876-73.1995-4-51-000	5.8	35	0.12	-0.002	73	19.5	4200	-0.001	.	M	11.9	1020	-0.1	-0.05
MABE138R	25-42.2201-73.1831-4-51-000	7.1	125	1.35	0.025	52	30.7	5000	-0.001	19	M	58.4	1030	-0.1	0.20
MABE139R	25-42.2409-73.2211-4-51-000	6.2	60	0.44	-0.002	80	14.5	4100	-0.001	12	M	.	750	-0.1	-0.02
MABE140R	25-42.1956-73.2288-4-51-000	6.6	50	0.36	-0.002	77	34.9	4600	-0.001	12	M	.	1130	0.3	-0.03
MABE141R	25-42.1937-73.2594-4-51-000	6.4	40	0.44	-0.002	127	27.4	4200	-0.001	25	M	38.8	890	-0.1	-0.04
MABE142R	25-42.2301-73.2819-4-51-000	6.6	40	0.20	-0.002	72	17.0	4300	-0.001	16	M	35.3	730	-0.1	-0.04
MABE143R	25-42.2087-73.3196-4-51-000	7.7	240	2.60	0.188	42	.	5100	-0.001	22	M	61.4	1050	-0.1	0.78
MABE144R	25-42.2427-73.3229-4-51-000	7.6	210	2.50	0.297	717	.	5500	-0.001	.	M	.	1510	-0.1	1.41
MABE145R	25-42.2272-73.3634-4-51-000	8.1	290	2.10	0.187	145	.	15800	-0.001	.	M	.	5830	-0.1	0.64
MABE146R	25-42.2180-73.3975-4-51-000	7.5	170	1.70	0.093	365	.	6400	-0.001	.	M	27.8	1640	-0.1	0.55
MABE147R	25-42.1909-73.3999-4-51-000	7.4	160	1.40	0.048	88	.	7400	-0.001	.	M	29.8	1800	-0.1	0.30
MABE148R	25-42.1700-73.3522-4-51-000	6.1	110	0.95	0.092	154	.	5300	0.079	23	M	41.1	1370	-0.1	0.84
MABE160R	25-42.0791-73.0751-4-51-000	6.2	38	0.10	-0.002	81	7.6	5200	-0.001	.	M	34.3	1230	-0.1	-0.04
MABE161R	25-42.0604-73.0658-4-51-000	7.0	30	0.10	-0.002	60	19.2	4100	-0.001	31	M	11.1	680	-0.1	-0.06
MABE162R	25-42.1500-73.1069-4-51-000	7.1	44	0.20	-0.002	37	22.7	4200	-0.001	16	M	68.0	780	-0.1	-0.04
MABE163R	25-42.1693-73.1479-4-51-000	7.1	48	0.22	-0.002	32	27.6	4200	0.025	16	M	20.9	660	0.1	-0.03
MABE164R	25-42.1289-73.1292-4-51-000	7.2	56	0.32	-0.002	39	.	4000	-0.001	11	M	13.6	900	0.2	-0.03
MABE165R	25-42.0891-73.1114-4-51-000	7.2	61	0.40	-0.002	33	39.1	4500	0.043	14	M	17.0	920	-0.1	-0.02
MABE166R	25-42.0440-73.1400-4-51-000	7.2	50	0.26	-0.002	39	.	4300	-0.001	10	M	.	840	0.1	-0.03
MABE167R	25-42.0541-73.1589-4-51-000	6.9	45	0.22	0.011	49	22.0	4400	-0.001	34	M	30.9	780	0.3	0.24
MABE168R	25-42.0934-73.1666-4-51-000	6.9	52	0.42	-0.002	45	30.9	3900	-0.001	19	M	119.8	740	-0.1	-0.03
MABE169R	25-42.1206-73.1617-4-51-000	7.3	92	0.74	0.042	53	23.0	4200	-0.001	.	M	.	1080	0.3	0.46
MABE170R	25-42.1180-73.2193-4-51-000	7.3	90	0.56	0.002	43	39.7	4700	-0.001	15	M	38.4	1040	-0.1	0.02
MABE171R	25-42.1539-73.2591-4-51-000	7.8	170	1.04	0.076	42	11.4	7000	-0.001	.	M	.	1880	-0.1	0.45
MABE172R	25-42.1308-73.2641-4-51-000	7.7	170	1.64	0.104	28	.	7100	-0.001	.	M	.	1660	-0.1	0.61
MABE173R	25-42.1003-73.2554-4-51-000	7.8	170	1.60	0.144	36	.	5600	-0.001	10	M	50.5	1770	-0.1	0.85
MABE174R	25-42.0845-73.2887-4-51-000	8.0	270	1.93	0.337	30	.	8300	-0.001	20	M	61.5	2390	-0.1	1.25
MABE175R	25-42.0475-73.3295-4-51-000	7.7	205	1.44	0.125	25	.	6800	-0.001	.	M	62.7	1810	-0.1	0.61
MABE176R	25-42.0544-73.3632-4-51-000	7.5	490	5.60	0.672	33	.	16500	-0.001	.	M	.	4310	-0.1	1.37
MABE177R	25-42.0670-73.2858-4-51-000	7.9	190	1.85	0.161	60	17.9	7600	-0.001	.	M	.	2020	0.2	0.85
MABE178R	25-42.0502-73.2543-4-51-000	7.1	270	2.33	0.489	33	.	5400	-0.001	.	M	95.0	1680	-0.1	1.81
MABE179R	25-42.0618-73.2226-4-51-000	7.2	60	0.48	0.004	44	31.8	4500	-0.001	18	M	37.8	720	0.2	0.07
MABE180R	25-42.1044-73.3306-4-51-000	6.9	120	1.16	0.038	34	29.8	4900	-0.001	16	M	54.8	1120	-0.1	0.32
MABE181R	25-42.1244-73.3324-4-51-000	7.1	112	1.12	0.034	37	.	5400	-0.001	22	M	51.3	1250	-0.1	0.30
MABE182R	25-42.1057-73.3704-4-51-000	7.1	238	2.00	0.378	30	.	7600	-0.001	.	M	113.1	2300	0.2	1.59
MABE183R	25-42.0816-73.4150-4-51-000	7.2	110	0.76	0.011	69	61.5	5700	-0.001	.	M	30.4	2670	0.2	0.10
MABE184R	25-42.0662-73.4130-4-51-000	7.0	285	3.04	0.430	35	.	9400	-0.001	.	M	105.5	3150	-0.1	1.51
MABE185R	25-42.1382-73.4114-4-51-000	6.8	1050	6.80	0.172	71	.	157100	-0.001	.	M	.	68960	-0.1	0.16
MABE186R	25-42.1401-73.3897-4-51-000	7.1	250	1.96	0.222	53	22.8	12500	-0.001	.	M	91.5	4560	-0.1	0.89
MABE187R	25-42.1655-73.4129-4-51-000	7.3	335	3.50	0.293	41	.	6500	-0.001	.	M	116.5	1910	-0.1	0.87
MABE188R	25-42.1543-73.4472-4-51-000	7.8	210	2.05	0.139	43	.	8400	-0.001	.	M	43.1	3510	-0.1	0.66
MABE189R	25-42.1180-73.4583-4-51-000	6.3	20	0.10	-0.002	53	23.5	4900	-0.001	.	M	17.0	780	-0.1	-0.09
MABE190R	25-42.0979-73.4611-4-51-000	6.8	75	0.26	0.002	55	36.0	10100	-0.001	.	M	49.3	2590	-0.1	0.03
MABE191R	25-42.0785-73.4651-4-51-000	6.7	52	0.30	-0.002	40	34.1	4600	-0.001	30	M	40.0	920	-0.1	-0.03
MABE192R	25-42.1062-73.4857-4-51-000	6.9	79	0.56	0.023	44	29.5	6000	-0.001	10	M	.	1650	-0.1	0.29
MAFR001R	25-42.5143-72.7189-4-51-000	8.4	130	0.70	0.056	40	11.9	9500	-0.001	.	M	29.8	3190	-0.1	0.43
MAFR002R	25-42.4881-72.7426-4-51-000	7.5	67	0.50	0.065	34	20.1	3700	-0.001	18	M	26.8	1360	-0.1	0.97
MAFR003R	25-42.4492-72.7501-4-51-000	7.4	68	0.40	0.377	57	19.7	4600	-0.001	.	M	32.4	1420	-0.1	5.54
MAFR004R	25-42.4171-72.6410-4-51-000	6.8	112	0.60	-0.002	23	20.8	6000	-0.001	.	M	83.2	1620	0.3	-0.01
MAFR005R	25-42.4281-72.6627-4-51-000	7.7	123	0.80	0.079	23	26.0	6300	-0.001	.	M	36.5	2190	-0.1	0.64

C-15

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER-- ALBANY SHEET

5

SRL I.D. *****	DOE I.D.		PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MAFR006R	25-42.4356-	72.6881-4-51-000	7.5	54	0.36	0.035	29	19.5	4300	-0.031	.	M	30.7	1660	-0.1	0.65
MAFR007R	25-42.4787-	72.6945-4-51-000	7.8	75	0.80	0.050	29	27.2	4700	-0.001	11	M	30.5	1390	-0.1	0.67
MAFR008R	25-42.4715-	72.6716-4-51-000	7.6	77	0.70	0.030	26	32.5	3900	-0.001	.	M	30.4	1430	0.2	0.39
MAFR009R	25-42.4688-	72.6413-4-51-000	7.6	193	1.20	0.070	40	11.6	14400	-0.001	.	M	51.2	5880	-0.1	0.36
MAFR010R	25-42.4888-	72.5979-4-51-000	7.2	176	0.80	-0.002	36	.	14000	-0.001	.	M	85.0	4890	-0.1	0.00
MAFR011R	25-42.5481-	72.5808-4-51-000	7.3	87	3.80	0.033	24	30.7	4800	-0.001	.	M	114.0	1770	-0.1	0.38
MAFR012R	25-42.5299-	72.6086-4-51-000	7.6	177	1.40	0.026	25	23.2	10100	-0.001	.	M	69.2	4230	0.3	0.15
MAFR013R	25-42.5576-	72.6220-4-51-000	7.1	111	0.70	0.016	27	21.2	7700	-0.001	.	M	141.3	2570	0.2	0.14
MAFR014R	25-42.5399-	72.6486-4-51-000	7.0	97	0.70	-0.002	18	14.1	4500	-0.001	.	M	100.5	1730	0.2	-0.01
MAFR015R	25-42.4383-	72.5909-4-51-000	7.1	145	0.30	-0.002	50	24.0	8900	-0.001	.	M	48.3	3110	0.2	0.00
MAFR016R	25-42.4640-	72.5933-4-51-000	6.9	310	0.50	-0.002	M	.	M	-0.001	.	M	.	169550	-0.1	0.00
MAFR017R	25-42.5025-	72.6461-4-51-000	7.7	190	1.30	0.081	42	.	20200	-0.001	.	M	42.3	10160	0.2	0.43
MAFR018R	25-42.5071-	72.6826-4-51-000	7.1	123	1.30	5.387	103	48.0	12700	-0.001	.	M	76.1	4850	0.3	43.80
MAFR019R	25-42.5410-	72.6907-4-51-000	8.3	128	0.90	-0.002	40	15.1	8500	-0.001	15	M	47.9	2330	-0.1	-0.01
MAFR020R	25-42.5662-	72.7162-4-51-000	7.1	93	0.80	0.053	55	.	10600	-0.001	.	M	43.3	3870	0.3	0.57
MAFR021R	25-42.5567-	72.7424-4-51-000	7.4	89	1.00	-0.002	40	12.7	4900	-0.001	.	M	42.4	1600	-0.1	-0.01
MAFR022R	25-42.4817-	72.7626-4-51-000	7.1	50	0.50	0.054	47	30.2	4900	-0.001	21	M	45.9	1580	0.2	1.08
MAFR023R	25-42.5180-	72.7798-4-51-000	7.4	150	0.90	-0.002	30	.	17600	-0.001	.	M	44.3	4840	-0.1	0.00
MAFR024R	25-42.5305-	72.8072-4-51-000	7.0	117	1.20	0.003	27	32.4	10300	-0.001	.	M	50.1	3410	-0.1	0.03
MAFR025R	25-42.5577-	72.8062-4-51-000	7.5	115	1.10	-0.002	42	23.3	8300	-0.001	.	M	35.6	2790	-0.1	-0.01
MAFR026R	25-42.5933-	72.7892-4-51-000	8.0	132	1.50	0.175	29	29.0	4600	-0.001	9	M	40.1	1690	0.2	1.33
MAFR027R	25-42.6119-	72.7600-4-51-000	6.9	38	0.16	-0.002	47	29.8	4600	-0.001	.	M	49.6	1940	-0.1	-0.04
MAFR028R	25-42.5893-	72.7663-4-51-000	7.1	83	0.90	-0.002	45	37.1	4800	-0.001	.	M	60.6	1830	0.2	-0.01
MAFR029R	25-42.6151-	72.8280-4-51-000	7.3	95	0.90	0.015	35	20.0	3900	-0.001	7	M	38.7	1180	-0.1	0.16
MAFR030R	25-42.6273-	72.8774-4-51-000	7.2	66	0.70	-0.002	33	22.8	3800	-0.001	.	M	43.7	1670	-0.1	-0.02
MAFR031R	25-42.6079-	72.8857-4-51-000	7.3	70	0.80	-0.002	36	.	4700	-0.001	.	M	39.8	1540	-0.1	-0.02
MAFR032R	25-42.5777-	72.8516-4-51-000	7.3	52	0.50	-0.002	39	25.2	5700	-0.001	23	M	40.9	1530	-0.1	-0.03
MAFR033R	25-42.5659-	72.9075-4-51-000	7.4	53	0.60	-0.002	30	27.3	4200	-0.001	11	M	43.0	1200	-0.1	-0.03
MAFR034R	25-42.6056-	72.9304-4-51-000	5.5	25	0.04	-0.002	71	26.2	3300	-0.001	15	M	17.5	860	-0.1	-0.07
MAFR035R	25-42.5773-	72.9487-4-51-000	6.7	39	0.18	-0.002	73	13.8	3900	-0.001	14	M	17.7	1040	-0.1	-0.04
MAFR036R	25-42.5029-	72.8513-4-51-000	6.8	42	0.18	-0.002	64	30.6	4600	-0.001	.	M	34.6	1080	-0.1	-0.04
MAFR037R	25-42.5371-	72.8553-4-51-000	6.5	35	0.16	-0.002	289	22.8	4400	-0.001	21	M	37.1	1020	0.3	-0.05
MAFR038R	25-42.4858-	72.8099-4-51-000	6.9	36	0.30	-0.002	50	20.4	4300	-0.001	24	M	19.8	810	-0.1	-0.04
MAFR039R	25-42.4342-	72.5774-4-51-000	6.4	222	0.50	-0.002	122	34.3	12500	-0.001	.	M	43.7	3650	-0.1	0.00
MAFR040R	25-42.4598-	72.5642-4-51-000	7.5	101	0.90	0.021	57	18.6	3900	-0.001	12	M	22.9	1770	0.3	0.21
MAFR041R	25-42.4880-	72.5613-4-51-000	7.4	107	0.80	0.046	52	23.0	5300	-0.001	16	M	38.2	1890	0.2	0.43
MAFR042R	25-42.5048-	72.4476-4-51-000	5.1	22	0.02	0.031	149	23.5	4400	-0.001	43	M	51.0	1270	0.3	1.41
MAFR043R	25-42.5016-	72.4793-4-51-000	6.5	32	0.08	0.091	109	.	4700	-0.001	39	M	17.9	1660	0.2	2.84
MAFR044R	25-42.4935-	72.5191-4-51-000	6.2	64	0.10	0.013	75	25.0	8100	-0.001	19	M	31.4	3070	-0.1	0.20
MAFR045R	25-42.4490-	72.5347-4-51-000	7.4	106	0.60	0.043	38	9.8	9300	-0.001	.	M	17.7	3080	-0.1	0.41
MAFR046R	25-42.4512-	72.4942-4-51-000	7.2	75	0.26	0.026	40	11.9	9200	-0.001	.	M	22.0	2880	-0.1	0.35
MAFR047R	25-42.4385-	72.4828-4-51-000	6.8	37	0.06	-0.002	176	24.2	6600	-0.001	12	M	23.3	2230	0.2	-0.04
MAFR048R	25-42.4492-	72.4439-4-51-000	5.7	40	0.04	-0.002	133	.	9000	-0.001	.	M	56.5	2540	-0.1	-0.04
MAFR049R	25-42.4227-	72.4421-4-51-000	4.7	37	0.00	0.012	210	18.9	6700	-0.001	.	M	66.7	1900	0.7	0.32
MAFR050R	25-42.4294-	72.3996-4-51-000	6.1	28	0.06	0.004	92	17.6	5400	-0.001	.	M	25.6	1690	-0.1	0.14
MAFR051R	25-42.4575-	72.3878-4-51-000	6.4	30	0.06	0.002	59	29.4	5800	-0.001	.	M	17.0	2020	-0.1	0.07
MAFR052R	25-42.4715-	72.3919-4-51-000	6.5	29	0.06	0.015	67	32.4	5400	-0.001	19	M	17.6	1570	-0.1	0.52
MAFR053R	25-42.4638-	72.3746-4-51-000	7.0	92	0.18	-0.002	68	28.1	15600	-0.001	.	M	20.6	5880	-0.1	-0.01
MAFR054R	25-42.4899-	72.3420-4-51-000	6.9	33	0.14	-0.002	104	10.4	5800	-0.001	12	M	29.9	1890	-0.1	-0.05
MAFR055R	25-42.5238-	72.3437-4-51-000	6.9	30	0.08	-0.002	171	14.3	5400	-0.001	10	M	11.3	1850	-0.1	-0.06
MAFR056R	25-42.5457-	72.3134-4-51-000	6.4	35	0.12	0.002	54	36.9	5000	-0.001	13	M	38.3	1680	-0.1	0.06
MAFR057R	25-42.5137-	72.2591-4-51-000	6.2	70	0.08	0.111	145	32.9	15700	-0.001	.	M	38.6	5350	0.4	1.59
MAFR058R	25-42.5236-	72.2880-4-51-000	5.7	26	0.06	-0.002	136	24.7	6100	-0.001	.	M	71.6	1870	0.4	-0.07

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY

SHEET

6

SRL I.D. *****	DOE I.D.		PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MAFR059R	25-42.5548-	72.2952-4-51-000	6.8	127	0.28	-0.002	28	22.1	20300	-0.031	.	M	50.2	7290	-0.1	-0.01
MAFR060R	25-42.5660-	72.3295-4-51-000	7.0	32	0.14	-0.002	34	.	5400	-0.001	.	M	32.4	1680	-0.1	-0.05
MAFR061R	25-42.6015-	72.3336-4-51-000	6.8	23	0.10	0.012	43	26.7	4200	-0.001	.	M	31.5	1210	0.1	0.52
MAFR062R	25-42.6303-	72.3358-4-51-000	6.4	32	0.12	0.056	1411	30.6	7000	-0.001	.	M	42.5	2230	-0.1	1.75
MAFR063R	25-42.6328-	72.3677-4-51-000	5.1	18	0.02	0.113	105	25.9	3600	-0.001	23	M	57.3	1110	0.3	6.28
MAFR064R	25-42.6531-	72.3491-4-51-000	6.2	22	0.06	-0.002	56	30.1	4000	-0.001	.	M	31.9	1380	-0.1	-0.08
MAFR065R	25-42.6982-	72.3826-4-51-000	6.0	20	0.08	0.007	122	16.4	4300	-0.001	18	M	39.5	1350	-0.1	0.35
MAFR066R	25-42.7060-	72.3498-4-51-000	6.9	47	0.16	-0.002	95	18.5	8200	-0.001	.	M	34.1	2900	-0.1	-0.03
MAFR067R	25-42.6491-	72.3253-4-51-000	6.6	97	0.30	-0.002	170	32.0	13200	-0.001	.	M	64.8	5290	-0.1	-0.01
MAFR068R	25-42.6808-	72.3113-4-51-000	6.5	23	0.10	-0.002	157	.	5300	-0.001	24	M	43.5	1580	-0.1	-0.08
MAFR069R	25-42.6783-	72.2808-4-51-000	6.9	27	0.12	-0.002	48	20.9	4400	-0.001	.	M	35.4	1280	0.2	-0.06
MAFR070R	25-42.6595-	72.2605-4-51-000	6.8	31	0.12	-0.002	114	24.3	5100	-0.001	21	M	33.3	1550	-0.1	-0.05
MAFR071R	25-42.6317-	72.2451-4-51-000	6.5	35	0.10	-0.002	146	33.9	5400	-0.001	17	M	44.5	1730	0.2	-0.05
MAFR072R	25-42.6483-	72.2854-4-51-000	6.9	33	0.10	-0.002	198	44.5	5900	-0.001	.	M	37.2	1620	0.2	-0.05
MAFR073R	25-42.6223-	72.2783-4-51-000	6.2	30	0.06	0.013	182	.	4600	-0.001	.	M	40.5	1590	0.5	0.43
MAFR074R	25-42.5718-	72.3879-4-51-000	5.4	23	0.04	-0.002	161	22.2	4500	-0.001	14	M	53.2	1230	0.4	-0.08
MAFR075R	25-42.6138-	72.3944-4-51-000	6.3	22	0.06	0.062	137	16.2	4800	-0.001	.	M	27.2	1410	0.2	2.82
MAFR076R	25-42.7147-	72.4433-4-51-000	6.5	77	0.18	-0.002	61	34.5	11100	-0.001	.	M	44.1	3690	-0.1	-0.02
MAFR077R	25-42.6801-	72.4319-4-51-000	6.6	65	0.14	-0.002	55	.	11100	-0.001	.	M	32.9	3560	-0.1	-0.02
MAFR078R	25-42.6484-	72.3955-4-51-000	5.3	22	0.04	0.126	115	24.1	5500	-0.001	.	M	54.9	1270	-0.1	5.73
MAFR079R	25-42.6053-	72.4111-4-51-000	5.9	43	0.06	-0.002	69	.	8500	-0.001	34	M	39.7	3090	-0.1	-0.04
MAFR080R	25-42.5800-	72.4375-4-51-000	6.2	29	0.06	0.033	108	31.5	5400	-0.001	29	M	32.2	1780	-0.1	1.14
MAFR081R	25-42.5634-	72.4171-4-51-000	4.8	21	0.01	0.051	195	15.7	4900	-0.001	40	M	88.2	1370	-0.1	2.43
MAFR082R	25-42.5437-	72.3737-4-51-000	5.4	19	0.04	0.039	116	25.4	6100	-0.001	.	M	67.7	1580	-0.1	2.05
MAFR083R	25-42.5204-	72.4241-4-51-000	5.7	25	0.04	0.003	71	26.9	5500	-0.001	.	M	50.4	2030	-0.1	0.12
MAFR084R	25-42.5217-	72.3931-4-51-000	4.7	20	0.00	0.054	227	24.3	5000	-0.001	.	M	120.2	1530	0.4	2.70
MAFR086R	25-42.6194-	72.4698-4-51-000	6.6	36	0.14	-0.002	58	27.9	5100	-0.001	34	M	35.7	2250	-0.1	-0.05
MAFR087R	25-42.6466-	72.4414-4-51-000	6.4	45	0.14	0.042	64	32.5	6500	0.071	.	M	54.7	2080	-0.1	0.93
MAFR088R	25-42.7153-	72.4642-4-51-000	6.1	41	0.08	-0.002	59	39.1	6500	-0.001	.	M	70.9	2220	0.3	-0.04
MAFR089R	25-42.6745-	72.4814-4-51-000	7.1	104	0.30	-0.002	42	34.4	16300	-0.001	.	M	47.7	6410	-0.1	-0.01
MAFR090R	25-42.6470-	72.4881-4-51-000	6.9	60	0.28	-0.002	69	25.8	6600	-0.001	22	M	74.0	2580	-0.1	-0.02
MAFR091R	25-42.6460-	72.5181-4-51-000	6.3	73	0.28	-0.002	54	26.2	10100	-0.001	.	M	65.1	3490	0.2	-0.02
MAFR092R	25-42.6092-	72.5366-4-51-000	7.4	97	0.70	-0.002	43	35.7	5000	-0.001	20	M	48.0	2380	-0.1	-0.01
MAFR093R	25-42.6144-	72.5592-4-51-000	6.9	359	0.40	-0.002	105	.	M	-0.001	.	M	78.1	38060	-0.1	0.00
MAFR094R	25-42.6250-	72.5900-4-51-000	7.1	142	0.34	-0.002	53	.	18900	-0.001	.	M	70.9	6700	0.4	0.00
MAFR095R	25-42.6773-	72.5880-4-51-000	6.1	33	0.08	-0.002	39	16.4	5000	-0.001	.	M	39.1	1730	0.3	-0.05
MAFR096R	25-42.6716-	72.5108-4-51-000	6.9	38	0.12	-0.002	57	27.0	5100	-0.001	.	M	38.4	1740	-0.1	-0.04
MAFR097R	25-42.7133-	72.5262-4-51-000	6.8	36	0.10	-0.002	46	27.1	5400	-0.001	19	M	60.8	1910	-0.1	-0.05
MAFR098R	25-42.7055-	72.5471-4-51-000	M	23	0.04	-0.002	147	21.7	4100	-0.001	49	M	63.7	1340	-0.1	-0.08
MAFR099R	25-42.7030-	72.5652-4-51-000	7.4	62	0.34	-0.002	41	22.2	4800	-0.001	14	M	38.6	2050	0.2	-0.02
MAFR100R	25-42.7205-	72.5829-4-51-000	7.6	109	0.80	12.940	45	31.9	4800	-0.001	.	M	39.9	2000	-0.1	118.72
MAFR101R	25-42.5733-	72.5539-4-51-000	7.3	80	0.24	-0.002	55	23.0	8700	-0.001	.	M	43.4	3070	-0.1	-0.02
MAFR102R	25-42.5423-	72.5486-4-51-000	7.2	58	0.16	-0.002	55	39.0	6900	-0.001	19	M	41.3	2750	-0.1	-0.02
MAFR103R	25-42.5445-	72.5027-4-51-000	7.4	45	0.20	0.001	53	32.0	5500	-0.001	23	M	38.6	2440	-0.1	0.02
MAFR104R	25-42.5603-	72.5038-4-51-000	6.9	30	0.14	0.019	42	31.4	4200	-0.001	27	M	39.0	1600	-0.1	0.63
MAFR105R	25-42.5581-	72.4640-4-51-000	6.6	22	0.08	0.005	69	28.1	4500	-0.001	16	M	35.9	1660	-0.1	0.23
MAFR106R	25-42.5255-	72.4728-4-51-000	6.9	26	0.08	0.018	62	18.3	4300	-0.001	29	M	35.8	1870	-0.1	0.69
MAFR107R	25-42.5975-	72.6202-4-51-000	6.5	158	0.90	-0.002	76	27.9	10100	0.068	.	M	169.7	3420	-0.1	0.00
MAFR108R	25-42.6200-	72.6250-4-51-000	7.3	173	1.30	0.160	55	25.8	7300	-0.001	.	M	45.3	2540	0.2	0.92
MAFR109R	25-42.6325-	72.6668-4-51-000	7.6	140	1.00	0.186	37	.	5900	-0.001	.	M	34.8	2170	0.2	1.33
MAFR110R	25-42.6032-	72.6770-4-51-000	7.6	141	1.20	0.044	40	18.1	4300	-0.001	.	M	46.6	1580	-0.1	0.31
MAFR111R	25-42.5734-	72.6783-4-51-000	7.8	165	1.20	0.131	63	16.6	7300	-0.001	.	M	49.0	2500	-0.1	0.79
MAFR112R	25-42.5841-	72.7014-4-51-000	7.2	101	0.40	-0.002	40	20.0	8200	-0.001	.	M	40.1	3190	-0.1	-0.01

C-17

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER-- ALBANY SHEET

7

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MAFR113R	25-42.6277-72.7350-4-51-000	7.5	72	0.60	0.014	36	21.7	3900	-0.001	.	M	37.6	1230	0.2	0.19
MAFR114R	25-42.6469-72.7219-4-51-000	7.4	78	0.60	0.001	61	25.6	4300	-0.001	10	M	33.8	1270	0.2	0.01
MAFR115R	25-42.6755-72.7210-4-51-000	7.9	109	0.80	0.070	105	31.4	4600	-0.001	14	M	38.8	1790	-0.1	0.64
MAFR116R	25-42.6449-72.6770-4-51-000	7.7	175	1.20	0.141	70	33.0	7400	-0.001	.	M	34.2	2560	-0.1	0.81
MAFR117R	25-42.6531-72.6478-4-51-000	7.2	86	0.60	-0.002	92	22.3	5500	0.052	.	M	176.1	1730	-0.1	-0.01
MAFR118R	25-42.6671-72.6652-4-51-000	7.4	163	1.40	0.216	53	34.1	7500	-0.001	.	M	143.4	2800	-0.1	1.33
MAFR119R	25-42.7078-72.6525-4-51-000	7.3	117	1.00	-0.002	50	28.4	5200	-0.001	.	M	70.5	1570	-0.1	-0.01
MAFR120R	25-42.7094-72.7055-4-51-000	7.8	160	1.30	0.076	36	17.9	4800	-0.001	.	M	33.7	1980	0.3	0.48
MAFR121R	25-42.7211-72.7000-4-51-000	7.6	129	1.00	0.067	47	25.7	4400	-0.001	.	M	48.2	2000	-0.1	0.52
MAFR122R	25-42.7224-72.7319-4-51-000	7.5	80	0.60	-0.002	60	19.6	5000	-0.001	.	M	39.4	1580	-0.1	-0.02
MAFR123R	25-42.7019-72.7753-4-51-000	7.6	56	0.50	0.019	1943	.	5900	-0.001	.	M	40.3	1940	-0.1	0.34
MAFR124R	25-42.6770-72.7517-4-51-000	7.7	62	0.50	-0.002	94	31.7	4700	-0.001	.	M	31.2	1480	0.3	-0.02
MAFR125R	25-42.6745-72.7877-4-51-000	7.4	41	0.22	-0.002	50	35.0	5700	-0.001	.	M	33.7	1290	-0.1	-0.04
MAFR126R	25-42.6500-72.3157-4-51-000	7.6	59	0.38	-0.002	77	24.9	5300	-0.001	22	M	29.2	1700	0.3	-0.02
MAFR127R	25-42.6277-72.8143-4-51-000	7.5	60	0.40	-0.002	82	37.2	5900	-0.001	.	M	35.1	1850	0.2	-0.02
MAFR128R	25-42.6345-72.8461-4-51-000	7.1	62	0.50	-0.002	23	30.7	5000	-0.001	.	M	36.1	1910	-0.1	-0.02
MAFR129R	25-42.6524-72.8623-4-51-000	7.2	55	0.18	-0.002	62	24.9	5100	-0.001	15	M	52.0	1940	-0.1	-0.03
MAFR130R	25-42.6828-72.8463-4-51-000	7.0	43	0.26	-0.002	110	42.6	10900	-0.001	35	M	298.4	10720	-0.1	-0.04
MAFR131R	25-42.7054-72.8360-4-51-000	7.1	30	0.12	0.027	151	.	10700	0.080	83	M	176.5	10110	0.3	0.90
MAFR132R	25-42.7155-72.8167-4-51-000	7.1	36	0.18	0.007	163	.	11700	-0.001	38	M	180.3	9640	-0.1	0.19
MAFR133R	25-42.7095-72.8831-4-51-000	7.1	48	0.18	0.024	140	.	14600	-0.001	66	M	164.7	11750	0.7	0.50
MAFR134R	25-42.6917-72.9036-4-51-000	7.0	39	0.10	-0.002	117	74.2	13400	-0.001	.	M	186.2	11510	-0.1	-0.04
MAFR135R	25-42.7234-72.9416-4-51-000	7.2	52	0.20	0.019	157	.	14300	-0.001	69	M	.	11100	-0.1	0.37
MAFR136R	25-42.7256-72.9953-4-51-000	7.0	25	0.06	-0.002	198	.	10100	-0.001	42	M	170.9	9700	0.7	-0.07
MAFR137R	25-42.7275-72.9741-4-51-000	6.6	28	0.10	-0.002	207	74.1	8700	-0.001	85	M	249.3	9210	-0.1	-0.06
MAFR138R	25-42.6933-72.9313-4-51-000	6.9	39	0.12	0.002	173	.	10300	-0.001	34	M	211.8	10310	-0.1	0.05
MAFR139R	25-42.6517-72.9298-4-51-000	7.0	22	0.08	0.001	163	.	8600	-0.001	68	M	188.9	10490	-0.1	0.05
MAFR140R	25-42.6345-72.8979-4-51-000	7.8	58	0.36	-0.002	130	84.8	10500	-0.001	76	M	204.4	11190	-0.1	-0.02
MAFR141R	25-42.6192-72.7719-4-51-000	7.7	67	0.40	0.008	173	36.9	11400	-0.001	62	M	189.9	11680	-0.1	0.12
MAHA001R	25-42.1127-72.1808-4-51-000	6.4	40	0.20	-0.002	98	46.5	7000	-0.001	23	M	53.4	8990	-0.1	-0.04
MAHA002R	25-42.1407-72.1802-4-51-000	5.5	182	0.04	0.001	139	.	37200	-0.001	.	M	134.4	20510	-0.1	0.01
MAHA003R	25-42.1560-72.2168-4-51-000	6.4	68	0.22	-0.002	109	34.0	8000	-0.001	.	M	87.3	9060	-0.1	-0.02
MAHA004R	25-42.1234-72.2076-4-51-000	6.6	70	0.24	-0.002	39	28.5	7300	-0.001	.	M	56.7	3040	-0.1	-0.02
MAHA005R	25-42.0786-72.2081-4-51-000	6.8	140	0.24	-0.002	31	.	26200	-0.001	.	M	32.2	9670	-0.1	0.00
MAHA006R	25-42.0820-72.1570-4-51-000	6.7	75	0.16	-0.002	24	10.4	10800	-0.001	.	M	35.7	4020	-0.1	-0.02
MAHA007R	25-42.0647-72.1643-4-51-000	7.1	47	0.16	-0.002	36	44.3	6000	-0.001	10	M	29.6	2510	-0.1	-0.03
MAHA008R	25-42.0465-72.2062-4-51-000	7.2	60	0.24	-0.002	45	41.5	6400	-0.001	15	M	40.3	2570	-0.1	-0.02
MAHA009R	25-42.0639-72.2474-4-51-000	6.7	53	0.38	-0.002	37	24.5	5500	-0.001	.	M	92.4	2280	-0.1	-0.03
MAHA010R	25-42.0765-72.2674-4-51-000	5.8	44	0.16	-0.002	101	28.5	5100	-0.001	15	M	37.2	2340	0.2	-0.04
MAHA011R	25-42.1092-72.2509-4-51-000	5.2	30	0.06	-0.002	112	36.1	4700	-0.001	.	M	47.7	1740	0.3	-0.06
MAHA012R	25-42.1127-72.3157-4-51-000	6.9	105	0.24	2.317	62	32.2	10800	-0.001	.	M	31.8	5360	0.4	22.07
MAHA013R	25-42.0889-72.3131-4-51-000	6.9	60	0.18	-0.002	61	29.1	6300	-0.001	.	M	29.5	2810	0.5	-0.02
MAHA014R	25-42.0903-72.3405-4-51-000	5.0	35	0.02	-0.002	139	22.8	5600	-0.001	.	M	29.1	2010	1.0	-0.05
MAHA015R	25-42.0534-72.3278-4-51-000	7.0	40	0.08	-0.002	75	23.2	4800	-0.001	19	M	24.3	2080	0.5	-0.04
MAHA016R	25-42.0484-72.3039-4-51-000	6.8	61	0.14	-0.002	64	19.9	6800	-0.001	.	M	35.1	3180	0.4	-0.02
MAHA017R	25-42.1344-72.3122-4-51-000	6.5	103	0.30	-0.002	66	34.7	11600	-0.001	.	M	38.8	5500	-0.1	-0.01
MAHA018R	25-42.1537-72.2616-4-51-000	7.0	59	0.28	-0.002	73	28.7	6300	-0.001	.	M	28.5	2900	0.4	-0.02
MAHA019R	25-42.1706-72.2599-4-51-000	7.2	220	0.26	-0.002	50	15.8	42800	-0.001	.	M	21.5	19090	-0.1	0.00
MAHA020R	25-42.1547-72.2971-4-51-000	7.1	132	0.26	-0.002	60	.	22200	-0.001	.	M	39.3	6390	-0.1	-0.01
MAHA021R	25-42.2280-72.2909-4-51-000	6.8	45	0.22	-0.002	57	33.9	4800	-0.001	14	M	27.8	2230	0.3	-0.03
MAHA022R	25-42.2138-72.3168-4-51-000	7.0	59	0.24	-0.002	69	28.5	6300	-0.001	.	M	27.3	2360	0.3	-0.02
MAHA023R	25-42.1905-72.2853-4-51-000	7.0	49	0.10	-0.002	69	24.8	5700	-0.001	.	M	46.6	2100	0.2	-0.03
MAHA024R	25-42.2020-72.3455-4-51-000	6.9	105	0.42	-0.002	61	67.5	9300	-0.001	.	M	39.9	4420	-0.1	-0.01

C-18

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY SHEET

8

SRL I.D. *****	DOE I.D.		PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MAHA025R	25-42.1872-	72.3673-4-51-000	6.3	76	0.32	-0.002	82	26.1	7700	-0.031	.	M	66.4	3180	0.7	-0.02
MAHA026R	25-42.1715-	72.3449-4-51-000	7.0	448	0.24	-0.002	40	.	M	-0.001	.	M	.	41080	-0.1	0.00
MAHA027R	25-42.1571-	72.3690-4-51-000	7.3	255	0.22	0.004	54	.	46900	-0.001	.	M	39.3	17280	-0.1	0.02
MAHA028R	25-42.1552-	72.4108-4-51-000	7.2	105	0.20	-0.002	51	.	14900	-0.001	.	M	31.7	5540	0.6	-0.01
MAHA029R	25-42.1819-	72.4134-4-51-000	6.8	100	0.48	0.023	43	28.8	8800	-0.001	.	M	49.3	3780	0.3	0.23
MAHA030R	25-42.2218-	72.4260-4-51-000	6.6	41	0.18	0.025	50	36.3	4500	-0.001	15	M	28.5	2000	0.3	0.61
MAHA031R	25-42.2057-	72.4714-4-51-000	7.2	75	0.24	0.025	34	29.2	4800	-0.001	24	M	45.8	2410	0.3	0.33
MAHA032R	25-42.2221-	72.5013-4-51-000	7.2	120	0.52	0.024	33	28.1	6800	-0.001	.	M	39.6	2930	0.4	0.20
MAHA033R	25-42.1788-	72.4749-4-51-000	6.7	128	0.48	0.006	36	71.4	13600	-0.001	.	M	62.8	4570	-0.1	0.05
MAHA034R	25-42.1646-	72.5357-4-51-000	6.6	180	0.92	0.028	24	37.8	17100	0.054	.	M	168.6	6530	-0.1	0.16
MAHA035R	25-42.1265-	72.4530-4-51-000	7.2	175	0.76	0.015	42	39.4	14700	0.083	.	M	40.5	5460	0.7	0.09
MAHA036R	25-42.1288-	72.4021-4-51-000	6.8	70	0.14	16.180	99	35.9	9200	-0.001	.	M	31.2	3690	0.4	231.14
MAHA037R	25-42.1197-	72.3581-4-51-000	6.2	55	0.14	-0.002	54	40.3	8700	-0.001	.	M	31.8	3600	0.4	-0.03
MAHA038R	25-42.1463-	72.3779-4-51-000	6.4	51	0.22	-0.002	81	35.0	4900	-0.001	25	M	36.9	2860	1.1	-0.03
MAHA039R	25-42.0698-	72.3959-4-51-000	6.6	55	0.10	0.004	57	34.7	8000	-0.001	.	M	28.8	3440	0.2	0.07
MAHA040R	25-42.0593-	72.3709-4-51-000	6.8	49	0.14	-0.002	40	4.8	5800	-0.001	.	M	24.1	2490	-0.1	-0.03
MAHA041R	25-42.0438-	72.3834-4-51-000	6.8	45	0.16	0.013	51	25.4	5300	-0.001	.	M	29.5	2250	-0.1	0.29
MAHA042R	25-42.0546-	72.4391-4-51-000	7.1	60	0.22	-0.002	52	28.6	7500	-0.001	.	M	28.7	3000	0.2	-0.02
MAHA043R	25-42.0653-	72.4491-4-51-000	7.2	92	0.40	0.041	39	30.9	7200	-0.001	.	M	95.0	3350	0.4	0.45
MAHA044R	25-42.0956-	72.4646-4-51-000	7.3	160	0.72	0.025	42	.	12100	-0.001	.	M	69.0	4940	1.2	0.16
MAHA045R	25-42.0755-	72.4947-4-51-000	5.4	125	0.46	-0.002	65	.	14100	-0.001	.	M	173.4	5600	-0.1	-0.01
MAHA046R	25-42.0447-	72.4910-4-51-000	7.0	190	0.50	0.014	42	.	16200	-0.001	.	M	.	7190	0.6	0.07
MAHA047R	25-42.0417-	72.5191-4-51-000	7.2	151	0.54	0.102	25	.	14100	-0.001	.	M	44.5	7090	1.8	0.68
MAHA048R	25-42.0517-	72.5501-4-51-000	7.3	145	0.36	-0.002	27	.	14000	-0.001	.	M	.	5410	-0.1	0.00
MAHA049R	25-42.1634-	72.6323-4-51-000	7.4	278	1.52	0.187	20	.	28700	-0.001	.	M	121.7	9790	0.4	0.67
MAHA050R	25-42.2370-	72.6254-4-51-000	7.5	155	0.84	-0.002	35	40.8	14800	-0.001	.	M	36.2	5130	-0.1	0.00
MAHA051R	25-42.2721-	72.6181-4-51-000	7.5	105	0.48	-0.002	28	40.0	9200	-0.001	.	M	34.3	3230	-0.1	-0.01
MAHA052R	25-42.1954-	72.6713-4-51-000	7.6	148	0.74	0.132	17	.	12500	-0.001	23	M	33.0	4610	1.0	0.89
MAHA053R	25-42.1518-	72.6725-4-51-000	7.3	122	0.54	0.050	15	.	14100	-0.001	.	M	16.8	4370	-0.1	0.41
MAHA054R	25-42.1437-	72.6363-4-51-000	7.3	180	0.64	0.041	20	40.7	18300	-0.001	.	M	85.8	5520	-0.1	0.23
MAHA055R	25-42.1333-	72.6611-4-51-000	7.4	210	0.66	0.196	22	.	14900	-0.001	.	M	.	4560	-0.1	0.93
MAHA056R	25-42.1066-	72.6585-4-51-000	7.5	250	1.08	0.348	33	.	21500	-0.001	30	M	59.4	8370	1.1	1.39
MAHA057R	25-42.1095-	72.7763-4-51-000	6.3	69	0.26	-0.002	22	.	6100	-0.001	.	M	10.5	2350	0.2	-0.02
MAHA058R	25-42.1501-	72.7935-4-51-000	6.7	95	0.18	0.007	35	28.2	12900	-0.001	15	M	25.9	5500	-0.1	0.07
MAHA059R	25-42.1626-	72.7642-4-51-000	7.3	80	0.28	-0.002	25	.	8900	0.709	.	M	.	4020	-0.1	-0.02
MAHA060R	25-42.1885-	72.7591-4-51-000	7.2	125	0.30	0.008	28	.	13000	-0.001	.	M	25.2	4930	-0.1	0.06
MAHA061R	25-42.1754-	72.7314-4-51-000	7.1	132	0.70	0.114	28	28.0	9900	-0.001	.	M	49.7	2630	-0.1	0.86
MAHA062R	25-42.1353-	72.7127-4-51-000	7.4	110	0.64	0.001	28	31.4	5900	-0.001	.	M	.	2550	-0.1	0.01
MAHA063R	25-42.0973-	72.6832-4-51-000	7.7	230	1.16	0.266	20	.	14300	-0.001	.	M	.	M	-0.1	1.16
MAHA064R	25-42.0611-	72.6707-4-51-000	7.4	260	0.84	0.077	30	49.1	22400	-0.001	.	M	116.3	8000	-0.1	0.30
MAHA065R	25-42.0423-	72.6841-4-51-000	7.3	218	0.52	-0.002	20	.	24500	-0.001	.	M	.	9110	-0.1	0.00
MAHA066R	25-42.0424-	72.6195-4-51-000	7.6	600	1.55	0.244	31	.	9500	-0.001	25	M	105.5	7980	-0.1	0.41
MAHA067R	25-42.0664-	72.7347-4-51-000	7.8	165	0.64	0.009	13	.	13600	1.175	.	M	.	6170	-0.1	0.05
MAHA068R	25-42.0821-	72.7343-4-51-000	7.8	171	0.52	0.096	43	.	13100	0.062	.	M	24.5	3850	-0.1	0.56
MAHA069R	25-42.0868-	72.7485-4-51-000	7.5	188	0.68	0.046	26	.	15100	1.342	.	M	15.7	3700	0.4	0.24
MAHA070R	25-42.0807-	72.7680-4-51-000	7.2	305	1.44	0.143	18	.	19100	-0.001	.	M	.	5980	0.8	0.47
MAHA071R	25-42.0564-	72.7687-4-51-000	7.7	211	0.88	0.164	24	52.7	15600	-0.001	.	M	25.0	4100	0.3	0.78
MAHA072R	25-42.0313-	72.7840-4-51-000	7.5	145	0.40	0.009	17	.	14000	-0.001	.	M	.	4980	0.2	0.06
MAHA073R	25-42.0742-	72.8134-4-51-000	7.1	100	0.36	18.370	24	38.9	11800	0.048	.	M	22.4	3690	0.3	183.70
MAHA074R	25-42.0921-	72.8097-4-51-000	7.2	98	0.30	0.001	24	27.4	11500	-0.001	22	M	.	4410	0.7	0.01
MAHA075R	25-42.1216-	72.8213-4-51-000	7.6	63	0.16	0.009	47	.	11700	-0.001	18	M	27.2	3710	-0.1	0.14
MAHA076R	25-42.1414-	72.8649-4-51-000	6.7	30	0.06	0.004	87	77.7	7600	-0.001	.	M	36.8	3040	-0.1	0.13
MAHA077R	25-42.1673-	72.8499-4-51-000	7.0	406	0.32	0.014	11	.	79900	-0.001	.	M	24.0	29040	-0.1	0.03

C-19

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY

SHEET

9

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PF2	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000	
MAHA078R	25-42.1905-	72.8583-4-51-000	7.2	92	0.24	-0.002	63	.	21000	0.061	.	M	9.4	6580	-0.1	-0.01
MAHA079R	25-42.1763-	72.9531-4-51-000	7.4	130	0.20	0.021	15	.	29500	-0.001	.	M	22.0	10230	-0.1	0.16
MAHA080R	25-42.2075-	72.9830-4-51-000	7.4	161	0.18	0.007	19	.	45500	-0.001	.	M	.	17410	-0.1	0.04
MAHA081R	25-42.1938-	72.9545-4-51-000	7.4	420	0.52	0.016	14	.	82800	7.063	.	M	.	36560	-0.1	0.04
MAHA082R	25-42.1883-	72.9045-4-51-000	7.6	148	0.24	-0.002	14	92.0	36200	-0.001	.	M	.	14000	-0.1	0.00
MAHA083R	25-42.2145-	72.9024-4-51-000	7.6	35	0.14	0.008	45	.	5900	-0.001	30	M	8.7	1310	-0.1	0.23
MAHA084R	25-42.2394-	72.8369-4-51-000	7.5	80	0.16	-0.002	21	10.3	18300	0.085	.	M	.	6680	-0.1	-0.02
MAHA085R	25-42.2076-	72.8103-4-51-000	6.8	42	0.06	0.015	126	42.4	10500	-0.001	31	M	13.1	3010	-0.1	0.36
MAHA086R	25-42.2151-	72.8455-4-51-000	7.4	34	0.18	-0.002	77	1829.0	8000	-0.001	.	M	5.3	2650	-0.1	-0.05
MAHA087R	25-42.2610-	72.9079-4-51-000	7.6	60	0.30	0.007	27	45.5	6100	-0.001	26	M	17.5	1500	-0.1	0.12
MAHA088R	25-42.2775-	72.9254-4-51-000	7.6	51	0.28	0.020	M	.	8000	0.761	.	M	.	1220	-0.1	0.39
MAHA089R	25-42.2953-	72.9257-4-51-000	7.4	76	0.50	0.001	27	.	6700	-0.001	38	M	.	1750	-0.1	0.01
MAHA090R	25-42.2983-	72.9030-4-51-000	7.4	70	0.46	-0.002	7	.	6700	-0.001	.	M	8.6	2570	0.2	-0.02
MAHA091R	25-42.3263-	72.9081-4-51-000	7.6	61	0.42	0.012	24	33.5	4900	-0.001	16	M	9.4	720	0.1	0.20
MAHA092R	25-42.3357-	72.9451-4-51-000	7.7	47	0.24	0.008	15	22.7	5700	-0.001	.	M	.	2460	0.2	0.17
MAHA093R	25-42.3018-	72.9737-4-51-000	7.4	56	0.38	0.004	25	7.9	4900	-0.001	43	M	.	1330	-0.1	0.07
MAHA094R	25-42.2621-	73.0022-4-51-000	7.4	56	0.30	-0.002	9	2679.0	7300	-0.001	.	M	10.6	2590	-0.1	-0.03
MAHA095R	25-42.2667-	72.9784-4-51-000	7.7	45	0.24	-0.002	24	18.7	5100	-0.001	.	M	.	2220	-0.1	-0.03
MAHA096R	25-42.2468-	72.9546-4-51-000	7.5	90	0.20	0.020	44	.	18000	-0.001	.	M	.	5740	-0.1	0.22
MAHA097R	25-42.1591-	73.0026-4-51-000	5.0	40	0.01	0.013	195	22.1	6400	-0.001	28	M	50.1	1570	-0.1	0.33
MAHA098R	25-42.1898-	73.0157-4-51-000	6.6	55	0.18	0.003	66	34.3	4500	-0.001	39	M	22.2	1660	1.5	0.05
MAHA099R	25-42.1265-	73.0631-4-51-000	6.0	54	0.08	0.013	47	.	10200	-0.001	.	M	7.1	3350	-0.1	0.24
MAHA100R	25-42.0906-	73.0658-4-51-000	6.2	40	0.12	0.026	276	.	10900	-0.001	22	M	63.8	2300	-0.1	0.65
MAHA101R	25-42.1140-	72.9939-4-51-000	5.6	20	0.02	0.019	249	42.5	4700	-0.001	33	M	370.4	1390	-0.1	0.95
MAHA102R	25-42.0551-	73.0174-4-51-000	7.3	50	0.14	0.006	70	44.2	9600	-0.001	39	M	49.2	3250	1.8	0.12
MAHA103R	25-42.0499-	73.0346-4-51-000	6.5	51	0.26	-0.002	M	.	11300	-0.001	.	M	333.6	3330	-0.1	-0.03
MAHA104R	25-42.0805-	72.9917-4-51-000	6.9	45	0.14	0.034	152	.	7400	-0.001	33	M	81.5	2730	1.0	0.76
MAHA105R	25-42.0640-	72.9672-4-51-000	7.1	30	0.10	0.011	124	41.5	5600	-0.001	15	M	55.2	2300	0.5	0.37
MAHA106R	25-42.0771-	72.9468-4-51-000	6.9	35	0.16	0.059	M	27.3	M	-0.001	.	M	57.7	2260	-0.1	1.69
MAHA107R	25-42.1234-	72.9522-4-51-000	6.4	30	0.08	0.042	M	68.0	M	-0.001	.	M	189.6	3400	-0.1	1.40
MAHA108R	25-42.1115-	72.8976-4-51-000	6.8	33	0.10	0.014	136	.	6600	-0.001	37	M	81.7	2890	-0.1	0.42
MAHA109R	25-42.0798-	72.9100-4-51-000	6.9	30	0.12	0.016	118	32.8	4900	-0.001	19	M	72.0	2900	-0.1	0.53
MAHA110R	25-42.0884-	72.8573-4-51-000	7.1	34	0.14	-0.002	103	.	6000	-0.001	43	M	75.8	2980	-0.1	-0.05
MAHA111R	25-42.1062-	72.8640-4-51-000	6.9	30	0.10	0.007	127	.	5200	-0.001	23	M	82.6	4870	-0.1	0.23
MAHA112R	25-42.0629-	72.8620-4-51-000	7.0	49	0.14	-0.002	87	40.2	8500	-0.001	48	M	88.5	7620	2.0	-0.03
MAHM001R	25-42.2007-	72.7202-4-51-000	7.5	180	0.88	0.067	106	40.5	12900	-0.001	.	M	110.3	7820	0.5	0.37
MAHM002R	25-42.2232-	72.7216-4-51-000	7.1	90	0.48	0.011	110	.	6600	-0.001	11	M	103.1	6720	-0.1	0.12
MAHM003R	25-42.2333-	72.7494-4-51-000	6.3	115	0.28	0.061	88	19.0	4000	-0.001	27	M	98.6	5850	0.3	0.53
MAHM004R	25-42.2591-	72.7118-4-51-000	6.7	105	0.36	0.003	70	11.8	7700	-0.001	10	M	103.1	7360	-0.1	0.03
MAHM005R	25-42.2705-	72.7462-4-51-000	7.5	77	0.36	0.020	85	36.8	3800	-0.001	17	M	96.6	5940	-0.1	0.26
MAHM006R	25-42.2877-	72.7743-4-51-000	7.7	65	0.44	0.004	109	13.8	5300	-0.001	.	M	98.3	6610	0.5	0.06
MAHM007R	25-42.3217-	72.7800-4-51-000	7.3	50	0.40	0.097	97	21.1	4400	0.055	22	M	103.7	6800	0.4	1.94
MAHM008R	25-42.3463-	72.7693-4-51-000	7.8	50	0.36	0.041	38	14.5	3500	-0.001	10	M	18.8	1700	-0.1	0.82
MAHM009R	25-42.3463-	72.7693-4-51-000	7.8	50	0.36	0.041	38	14.5	3500	-0.001	10	M	18.8	1700	-0.1	0.82
MAHM010R	25-42.3213-	72.7525-4-51-000	7.4	60	0.44	0.094	62	25.9	4800	-0.001	22	M	27.4	2230	-0.1	1.57
MAHM011R	25-42.3570-	72.7048-4-51-000	7.4	72	0.58	0.007	53	22.0	5400	-0.001	.	M	29.8	2200	0.2	0.10
MAHM012R	25-42.3059-	72.6622-4-51-000	7.8	90	0.60	-0.002	99	35.5	7300	-0.001	.	M	47.6	3240	-0.1	-0.01
MAHM013R	25-42.2899-	72.6622-4-51-000	8.2	165	1.04	0.015	37	49.7	14400	-0.001	.	M	93.4	5660	-0.1	0.09
MAHM014R	25-42.2417-	72.6601-4-51-000	8.1	170	0.84	0.065	71	.	12800	-0.001	.	M	31.0	4200	-0.1	0.38
MAHM015R	25-42.2698-	72.6952-4-51-000	7.0	160	1.36	0.119	47	45.6	9900	-0.001	.	M	39.4	3980	-0.1	0.74
MAHM016R	25-42.3099-	72.7149-4-51-000	8.1	55	0.36	0.016	33	8.4	4500	-0.001	21	M	39.1	2260	-0.1	0.29
MAHM017R	25-42.3827-	72.7094-4-51-000	7.7	80	0.60	0.026	53	27.1	7500	-0.001	12	M	25.1	3430	-0.1	0.33
MAHM019R	25-42.4017-	72.6785-4-51-000	8.1	120	0.72	0.041	44	34.5	4900	-0.001	.	M	45.1	2430	-0.1	0.34
MAHM020R	25-42.3522-	72.6743-4-51-000	8.9	81	1.60	0.103	42	20.1	8700	-0.001	.	M	43.4	3270	0.2	1.27

C-20

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY

SHEET

10

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MAHM021R	25-42.3587-72.6104-4-51-000	7.9	165	0.96	0.006	47		14700	-0.031		M	45.9	6440	-0.1	0.04
MAHM022R	25-42.3372-72.5813-4-51-000	7.1	90	0.48	0.027	55	20.7	8400	-0.001	23	M	43.5	3350	-0.1	0.30
MAHM023R	25-42.3293-72.5641-4-51-000	7.6	98	0.68	-0.002	81	9.8	6500	-0.001		M	48.1	2900	0.5	-0.01
MAHM024R	25-42.2825-72.5878-4-51-000	7.7	120	0.92	0.008	91	27.9	13800	-0.001		M	54.0	4750	0.7	0.07
MAHM026R	25-42.2430-72.5827-4-51-000	7.1	120	0.88	0.051	133	77.5	16800	-0.001		M	97.8	5740	-0.1	0.43
MAHM027R	25-42.2497-72.5604-4-51-000	7.1	220	1.12	0.127	227	70.7	32200	-0.001		M	68.8	10220	-0.1	0.58
MAHM028R	25-42.2196-72.5395-4-51-000	6.8	140	0.40	0.006	27	15.6	11100	-0.001		M	37.6	4460	0.2	0.04
MAHM029R	25-42.4081-72.7473-4-51-000	6.9	78	0.28	0.005	54	47.9	12400	-0.001		M	36.4	4700	-0.1	0.06
MAHM030R	25-42.4344-72.7402-4-51-000	7.1	60	0.64	8.346	53	44.9	8000	-0.001		M	46.8	2860	-0.1	139.10
MAHM031R	25-42.4459-72.7781-4-51-000	6.3	30	0.12	0.119	53	26.9	4100	-0.001	16	M	18.8	1700	-0.1	3.97
MAHM032R	25-42.4258-72.7819-4-51-000	6.7	75	0.28	-0.002	43		11700	-0.001		M	29.8	4650	-0.1	-0.02
MAHM033R	25-42.4551-72.8401-4-51-000	6.8	90	0.28	-0.002	53	15.7	25100	-0.001		M	25.6	9610	-0.1	-0.01
MAHM034R	25-42.4476-72.8584-4-51-000	7.0	70	0.36	-0.002	37	25.2	10300	-0.001		M	20.9	3710	-0.1	-0.02
MAHM035R	25-42.4785-72.8894-4-51-000	6.8	67	0.40	-0.002	54	19.3	7400	-0.001		M	72.5	2330	-0.1	-0.02
MAHM036R	25-42.5136-72.8839-4-51-000	6.6	55	0.32	-0.002	98	16.3	8000	-0.001		M	57.1	2680	0.3	-0.03
MAHM039R	25-42.5029-72.9430-4-51-000	6.5	25	0.16	-0.002	181	11.7	3800	-0.001		M	27.0	1350	-0.1	-0.07
MAHM040R	25-42.4857-72.9275-4-51-000	7.0	45	0.28	-0.002	78	17.7	4400	-0.001		M	18.1	1540	-0.1	-0.03
MAHM041R	25-42.4484-72.9350-4-51-000	6.9	38	0.20	-0.002	43	12.1	3000	-0.001		M	15.6	950	-0.1	-0.04
MAHM042R	25-42.4534-72.9608-4-51-000	6.7	20	0.08	-0.002	133	30.6	4000	-0.001		M	23.5	1160	-0.1	-0.09
MAHM043R	25-42.4217-72.9867-4-51-000	6.8	31	0.12	-0.002	129	24.4	4300	-0.001	22	M	30.3	1640	-0.1	-0.05
MAHM044R	25-42.3802-72.9780-4-51-000	6.7	30	0.24	-0.002	117	35.2	4800	-0.001		M	57.4	1460	-0.1	-0.06
MAHM045R	25-42.3644-73.0085-4-51-000	7.0	20	0.12	-0.002	193	11.1	3300	-0.001	17	M	21.3	470	-0.1	-0.09
MAHM046R	25-42.3454-73.0353-4-51-000	7.1	50	0.36	-0.002	114	38.2	4000	-0.001	19	M	26.3	810	0.3	-0.03
MAHM047R	25-42.3198-73.0288-4-51-000	7.2	55	0.24	0.018	203	20.3	4900	-0.001	30	M	24.6	1070	0.5	0.33
MAHM048R	25-42.3223-72.9956-4-51-000	7.0	80	0.80	0.006	110		6500	-0.001		M		2150	0.4	0.08
MAHM049R	25-42.3494-72.9679-4-51-000	7.3	43	0.32	0.014	115	24.1	4500	-0.001	25	M	33.4	1160	-0.1	0.33
MAHM050R	25-42.2874-72.8064-4-51-000	7.7	40	0.40	-0.002	47	22.2	3600	-0.001	13	M	14.5	790	0.3	-0.04
MAHM051R	25-42.2914-72.8395-4-51-000	7.2	28	0.16	-0.002	72	25.8	3500	-0.001	18	M	18.3	830	-0.1	-0.06
MAHM052R	25-42.2607-72.8609-4-51-000	7.3	75	0.48	0.007	57	31.6	9900	-0.001		M	35.6	3480	-0.1	0.09
MAHM053R	25-42.2497-72.8817-4-51-000	7.3	58	0.60	-0.002	46	34.1	6200	-0.001	31	M	23.9	1930	-0.1	-0.02
MAHM054R	25-42.2949-72.8738-4-51-000	7.9	52	0.64	0.015	68	20.3	4600	-0.001		M	23.2	1180	0.3	0.29
MAHM055R	25-42.3230-72.8698-4-51-000	7.2	60	0.44	0.014	122	38.1	8300	-0.001		M	36.4	2170	0.4	0.23
MAHM056R	25-42.3478-72.9016-4-51-000	6.7	65	0.56	0.027	76	23.2	6900	-0.001		M	26.4	1570	-0.1	0.42
MAHM057R	25-42.3713-72.9296-4-51-000	7.2	42	0.20	-0.002	98	23.0	6000	-0.001		M	20.7	1450	0.2	-0.04
MAHM058R	25-42.3950-72.9263-4-51-000	6.7	91	0.52	0.018	68	34.0	8900	-0.001		M	22.4	2160	-0.1	0.20
MAHM059R	25-42.4246-72.9203-4-51-000	6.4	40	0.24	0.031	1577		5000	-0.001	30	M	33.4	1940	1.2	0.78
MAHM060R	25-42.4207-72.8861-4-51-000	7.1	40	0.40	0.010	137	16.7	4400	-0.001		M	18.5	1060	-0.1	0.25
MAHM061R	25-42.3985-72.8739-4-51-000	7.1	45	0.36	-0.002	88	20.2	5000	-0.001		M	21.7	1470	-0.1	-0.03
MAHM062R	25-42.4029-72.8385-4-51-000	4.3	20	0.08	-0.002	82	415.4	4700	-0.001	16	M	35.2	1090	-0.1	-0.09
MAHM063R	25-42.4259-72.8347-4-51-000	4.8	20	0.10	5.018	168	42.4	6000	-0.001	17	M	40.2	920	-0.1	250.90
MAHM064R	25-42.3906-72.8035-4-51-000	4.6	45	0.20	-0.002	99	20.4	7300	-0.001		M	36.7	2160	0.2	-0.03
MAHM065R	25-42.3464-72.8417-4-51-000	4.6	30	0.20	-0.002	96	28.8	4600	-0.001		M	39.7	1410	-0.1	-0.06
MAHM066R	25-42.3649-72.7915-4-51-000	5.4	27	0.24	-0.002	93	20.8	4300	-0.001	32	M	17.7	1240	0.2	-0.06
MAHM067R	25-42.3827-72.6495-4-51-000	5.4	65	0.44	-0.002	94	24.7	8500	-0.001		M	41.1	3030	-0.1	-0.02
MAHM068R	25-42.3813-72.6269-4-51-000	6.2	120	0.36	0.003	93	28.6	5000	-0.001	37	M	26.1	1820	0.5	0.03
MAHM069R	25-42.4156-72.6307-4-51-000	5.7	100	0.40	0.041	197	38.4	6100	-0.001		M	17.0	2250	0.3	0.41
MAHM070R	25-42.4129-72.5653-4-51-000	5.8	112	0.52	-0.002	102		7500	-0.001		M	35.5	2360	0.2	-0.01
MAHM071R	25-42.3855-72.5466-4-51-000	5.4	135	0.64	0.012	147	35.7	17300	-0.001		M	78.0	5740	-0.1	0.09
MAHM073R	25-42.3200-72.4966-4-51-000	7.8	50	0.72	-0.002	68		5300	-0.001		M	19.7	1920	0.2	-0.03
MAHM074R	25-42.3183-72.5261-4-51-000	7.9	80	0.52	-0.002	115	51.6	20500	-0.001		M	121.0	6220	-0.1	-0.02
MAHM075R	25-42.2779-72.5238-4-51-000	7.7	125	0.64	0.043	65	27.4	15400	-0.001		M	54.3	5530	0.6	0.34
MAHM076R	25-42.2814-72.4856-4-51-000	8.2	105	1.00	0.017	156	22.0	6300	-0.001		M	24.2	2290	-0.1	0.16
MAHM077R	25-42.2616-72.4633-4-51-000	8.1	70	0.64	0.047	88	24.7	6000	-0.001		M	47.1	2440	-0.1	0.67

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY

SHEET

11

SRL I.D. *****	DOE I.C.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MAHM078R	25-42.2348-72.4649-4-51-000	8.1	50	0.36	0.154	143	33.7	7500	0.033	29	M	26.7	2580	0.3	3.08
MAHM080R	25-42.2610-72.5044-4-51-000	8.0	130	0.80	0.013	58		13200	-0.001		M	44.6	4650	0.8	0.10
MAHM081R	25-42.2755-72.5555-4-51-000	8.3	92	0.64	0.020	53	31.9	13400	-0.001		M	28.7	4990	0.5	0.22
MAHM082R	25-42.3495-72.5613-4-51-000	7.5	750	1.50	0.127	30		81900	-0.001		M		14150	-0.1	0.17
MAHM083R	25-42.3765-72.4971-4-51-000	7.4	56	0.24	-0.002	93	29.6	8900	-0.001		M	42.6	3130	-0.1	-0.03
MAHM084R	25-42.3999-72.5272-4-51-000	7.9	170	0.52	-0.002	146	81.5	30100	-0.001		M	106.4	9660	0.9	0.00
MAHM085R	25-42.4183-72.5257-4-51-000	7.8	50	0.32	-0.002	120	17.5	9600	-0.001		M	32.1	3180	0.5	-0.03
MAHM086R	25-42.4255-72.5004-4-51-000	7.8	50	0.40	0.040	138		17800	-0.001	40	M	26.8	6140	0.9	0.80
MAHM087R	25-42.3809-72.4661-4-51-000	8.3	32	0.32	0.006	77	36.8	6900	-0.001	20	M	1.8	2660	0.2	0.19
MAHM088R	25-42.3940-72.4285-4-51-000	4.5	20	0.10	0.037	457	64.4	11200	-0.001	47	M	50.5	3250	0.6	1.85
MAHM090R	25-42.3458-72.4633-4-51-000	7.6	49	0.28	0.016	40	36.0	7500	-0.001	36	M	13.6	2680	-0.1	0.33
MAHM091R	25-42.3295-72.4467-4-51-000	8.2	40	0.32	0.025	73	71.5	13400	-0.001	58	M		5630	0.6	0.63
MAHM092R	25-42.3017-72.4269-4-51-000	8.5	62	0.20	-0.002	52	35.4	14300	-0.001		M	26.0	4340	-0.1	-0.02
MAHM093R	25-42.2687-72.4313-4-51-000	8.2	35	0.32	0.053	157	108.3	19200	-0.001	78	M	67.5	5920	-0.1	1.51
MAHM094R	25-42.2377-72.4128-4-51-000	8.0	90	0.64	0.068	26		10800	-0.001	26	M		5480	-0.1	0.76
MAHM095R	25-42.2160-72.3669-4-51-000	8.2	70	0.40	-0.002	71	51.4	22000	-0.001	33	M	34.5	6540	-0.1	-0.02
MAHM096R	25-42.2377-72.3651-4-51-000	8.1	70	0.60	-0.002	31	35.8	8000	-0.001	5	M	27.1	2220	-0.1	-0.02
MAHM097R	25-42.2641-72.3770-4-51-000	8.5	48	0.32	0.026	107		14300	-0.001	69	M		4700	-0.1	0.54
MAHM098R	25-42.2764-72.3671-4-51-000	8.3	25	0.16	-0.002	36	37.2	6900	-0.001		M		2020	-0.1	-0.07
MAHM099R	25-42.2809-72.3112-4-51-000	7.9	52	0.24	-0.002	65	35.8	15400	-0.001		M	29.6	4700	-0.1	-0.03
MAHM100R	25-42.2408-72.3087-4-51-000	7.9	60	0.24	-0.002	212	76.2	29700	-0.001	94	M	34.8	8360	1.1	0.00
MAHM101R	25-42.2760-72.2240-4-51-000	7.9	56	0.16	-0.002	91	39.0	14600	-0.001	31	M	10.6	3910	-0.1	-0.03
MAHM102R	25-42.2798-72.2722-4-51-000	7.9	35	0.48	-0.002	232	82.7	19800	-0.001	99	M	68.3	7320	1.2	-0.05
MAHM104R	25-42.2486-72.2452-4-51-000	7.4	30	0.24	-0.002	83	43.0	7700	-0.001		M	8.2	1770	-0.1	-0.06
MAHM105R	25-42.3026-72.4062-4-51-000	7.9	70	0.16	0.016	156	25.0	30700	-0.001	43	M	25.0	11160	-0.1	0.23
MAHM106R	25-42.3300-72.4016-4-51-000	7.4	60	0.16	0.002	102	54.4	13800	-0.001		M	15.4	3280	-0.1	0.03
MAHM107R	25-42.3514-72.4107-4-51-000	6.2	30	0.12	-0.002	235	120.7	20400	0.082	41	M	74.2	5350	-0.1	-0.06
MAW0021F	25-42.5326-72.0785-4-51-000	5.3	30	0.04	0.002	161	23.6	5300	-0.001	47	M	57.4	2160	-0.1	0.07
MAW0023F	25-42.5803-72.0849-4-51-000	6.6	110	0.16	-0.002	194	25.6	20100	-0.001	41	M	184.6	7160	0.4	-0.01
MAW0024F	25-42.5670-72.0429-4-51-000	6.4	60	0.28	0.031	265	42.1	6700	-0.001	51	M	90.5	2970	0.7	0.52
MAW0025F	25-42.5455-72.0406-4-51-000	5.9	50	0.08	0.008	155	14.8	10000	-0.001	35	M	63.6	3630	-0.1	0.16
MAW0026F	25-42.5484-72.0002-4-51-000	6.5	80	0.12	0.048	286	30.8	13200	-0.001		M	63.9	5290	0.9	0.60
MAW0028R	25-42.5837-72.0131-4-51-000	5.3	80	0.04	0.001	176	13.0	14200	-0.001	30	M	69.1	6000	-0.1	0.01
MAW0031R	25-42.6925-72.0186-4-51-000	6.2	50	0.12	-0.002	76	13.9	10800	-0.001	46	M	44.7	4390	-0.1	-0.03
MAW0032R	25-42.712E-72.060E-4-51-000	4.9	30	0.02	-0.002	123	18.1	4800	-0.001	32	M	72.7	2110	0.2	-0.06
MAW0033R	25-42.6979-72.0867-4-51-000	6.0	50	0.08	0.025	114	20.1	9500	-0.001	47	M	54.7	3940	0.3	0.50
MAW0034R	25-42.6639-72.0793-4-51-000	6.3	120	0.18	0.015	77		21200	-0.001		M	139.6	8440	-0.1	0.13
MAW0035R	25-42.6337-72.0553-4-51-000	5.5	30	0.08	0.003	125	24.4	6100	-0.001	24	M	69.4	2440	0.5	0.10
MAW0036R	25-42.5999-72.0457-4-51-000	4.5	25	0.00	-0.002	133	15.3	5100	-0.001		M	55.1	2300	1.4	-0.07
MAW0037R	25-42.6093-72.1053-4-51-000	6.3	70	0.32	0.001	105	20.9	8200	-0.001	69	M	76.8	3370	0.4	0.01
MAW0038R	25-42.6828-72.1168-4-51-000	6.2	40	0.08	0.121	137	24.5	8500	-0.001	47	M	64.6	3770	-0.1	3.03
MAW0039R	25-42.7026-72.1282-4-51-000	5.3	30	0.04	0.120	213	23.4	4400	-0.001	84	M	102.4	2530	-0.1	4.00
MAW0040R	25-42.7143-72.1811-4-51-000	5.4	45	0.04	0.016	156	19.6	8500	-0.001	71	M	74.5	3690	-0.1	0.36
MAW0041R	25-42.6870-72.1782-4-51-000	5.5	40	0.04	0.009	181	16.1	10000	-0.001		M	58.5	8220	0.5	0.23
MAW0042R	25-42.6973-72.2123-4-51-000	6.1	30	0.08	-0.002	107	18.0	4000	-0.001	12	M	58.3	6010	-0.1	-0.06
MAW0043R	25-42.6970-72.2622-4-51-000	5.4	30	0.08	-0.002	236	29.1	5700	-0.001	25	M	57.9	6640	0.3	-0.06
MAW0044R	25-42.6844-72.2496-4-51-000	6.5	50	0.10	0.019	147	59.0	8300	0.100		M			-0.1	0.38
MAW0045R	25-42.6535-72.2193-4-51-000	6.6	40	0.12	-0.002	180	15.8	6600	-0.001		M	74.8	7190	0.3	-0.04
MAW0046R	25-42.6067-72.2217-4-51-000	7.0	45	0.16	0.004	148		5000	-0.001		M		7250	0.3	0.09
MAW0047R	25-42.6581-72.1715-4-51-000	4.9	30	0.04	-0.002	264		4700	-0.001	19	M	92.9	6600	0.8	-0.06
MAW0048R	25-42.6348-72.1406-4-51-000	6.3	35	0.10	0.035	191	33.1	5900	-0.001		M	65.8	6710	-0.1	1.00
MAW0049R	25-42.6088-72.1333-4-51-000	6.5	40	0.12	-0.002	129		6700	-0.001	26	M	57.8	6780	-0.1	-0.04
MAW0050R	25-42.6041-72.1644-4-51-000	5.7	60	0.06	-0.002	186	20.7	8800	-0.001	25	M	75.5	8520	-0.1	-0.02

C-22

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY SHEET

12

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
MAW0051R	25-42.5836-72.1343-4-51-000	5.9	50	0.08	-0.002	136	.	9100	0.043	.	M	.	M	-0.1	-0.03
MAW0052R	25-42.5785-72.1716-4-51-000	6.2	30	0.04	-0.002	132	19.4	4800	-0.001	15	M	63.2	5830	0.3	-0.06
MAW0053R	25-42.5671-72.2261-4-51-000	6.3	60	0.20	-0.002	110	36.7	5600	-0.001	.	M	62.8	6900	-0.1	-0.02
MAW0054R	25-42.5833-72.2628-4-51-000	6.7	25	0.16	0.010	127	.	5300	-0.001	.	M	.	7940	-0.1	0.40
MAW0055R	25-42.5509-72.1119-4-51-000	4.6	40	0.02	-0.002	262	19.4	5800	-0.001	.	M	80.3	6670	0.5	-0.04
MAW0056R	25-42.5474-72.1567-4-51-000	6.3	35	0.12	-0.002	97	12.8	4700	-0.001	54	M	51.9	6470	0.4	-0.05
MAW0058R	25-42.5466-72.1920-4-51-000	5.5	20	0.04	-0.002	154	30.0	5200	-0.001	52	M	88.0	4490	-0.1	-0.09
MAW0059R	25-42.5410-72.2128-4-51-000	5.3	50	0.02	0.011	98	47.4	9200	-0.001	13	M	104.5	6490	0.5	0.22
MAW0060R	25-42.5468-72.2393-4-51-000	6.5	35	0.16	0.004	69	33.5	5600	-0.001	45	M	100.2	5840	-0.1	0.11
MAW0061R	25-42.4899-72.1700-4-51-000	5.5	35	0.08	0.019	302	13.6	6000	-0.001	.	M	83.0	7150	0.6	0.54
MAW0062R	25-42.4866-72.1295-4-51-000	5.4	30	0.04	-0.002	232	.	4700	-0.001	25	M	.	6910	-0.1	-0.06
MAW0063R	25-42.4716-72.1625-4-51-000	6.4	40	0.08	-0.002	136	12.7	6900	-0.001	18	M	63.8	7140	0.4	-0.04
MAW0064R	25-42.4883-72.2160-4-51-000	5.6	50	0.06	-0.002	169	40.2	9900	-0.001	.	M	83.1	7590	-0.1	-0.03
MAW0065R	25-42.4887-72.2552-4-51-000	6.2	30	0.08	0.036	124	.	4500	0.026	.	M	56.2	6420	0.6	1.20
MAW0066R	25-42.4564-72.2084-4-51-000	6.0	40	0.08	-0.002	181	29.8	6500	-0.001	.	M	55.3	6700	-0.1	-0.04
MAW0067R	25-42.4385-72.2052-4-51-000	6.5	50	0.08	-0.002	102	13.7	8400	-0.001	.	M	52.5	7790	0.2	-0.03
MAW0068R	25-42.4091-72.2106-4-51-000	5.8	100	0.20	-0.002	186	.	21600	-0.001	.	M	.	16040	-0.1	-0.01
MAW0069R	25-42.3468-72.1849-4-51-000	6.6	70	0.34	-0.002	156	.	5900	-0.001	30	M	73.3	6330	0.2	-0.02
MAW0070R	25-42.4150-72.0961-4-51-000	6.8	60	0.20	-0.002	316	15.6	9300	-0.001	.	M	88.3	8220	-0.1	-0.02
MAW0071R	25-42.4359-72.0541-4-51-000	6.2	30	0.06	-0.002	178	.	5100	-0.001	.	M	.	6360	-0.1	-0.06
MAW0072R	25-42.4376-72.0834-4-51-000	6.6	50	0.20	0.003	452	38.2	9500	-0.001	.	M	52.2	8000	0.3	0.06
MAW0073R	25-42.4606-72.0899-4-51-000	4.6	40	0.02	-0.002	323	.	9400	-0.001	.	M	.	7370	0.5	-0.04
MAW0074R	25-42.4718-72.1104-4-51-000	4.6	30	0.00	0.006	252	.	3900	-0.001	22	M	.	M	-0.1	0.20
MAW0075R	25-42.4193-72.1203-4-51-000	6.4	100	0.18	-0.002	128	.	21100	-0.001	.	M	77.5	12410	-0.1	-0.01
MAW0076R	25-42.4344-72.1537-4-51-000	6.1	110	0.36	-0.002	133	7.6	14500	-0.001	.	M	274.3	11170	-0.1	-0.01
MAW0077R	25-42.3765-72.1629-4-51-000	5.9	50	0.10	-0.002	175	12.8	8200	1.258	46	M	.	8060	-0.1	-0.03
MAW0078R	25-42.3702-72.2222-4-51-000	6.6	50	0.20	-0.002	149	869.2	5600	-0.001	21	M	70.0	6420	0.3	-0.03
MAW0079R	25-42.3186-72.2509-4-51-000	7.1	45	0.20	-0.002	112	.	5300	-0.001	.	M	48.5	6920	0.2	-0.03
MAW0080R	25-42.4075-72.0387-4-51-000	6.0	30	0.10	-0.002	235	.	4600	-0.001	19	M	.	6320	0.3	-0.06
MAW0081R	25-42.3917-72.0718-4-51-000	6.7	50	0.10	-0.002	160	.	7300	0.067	19	M	.	8290	-0.1	-0.03
MAW0082R	25-42.3725-72.1279-4-51-000	6.9	50	0.24	-0.002	187	16.1	6400	-0.001	13	M	58.9	7330	0.3	-0.03
MAW0083R	25-42.3476-72.1605-4-51-000	6.7	50	0.16	-0.002	161	.	7300	1.741	20	M	.	8130	-0.1	-0.03
MAW0084R	25-42.3158-72.2082-4-51-000	7.2	120	0.40	-0.002	103	.	19700	-0.001	.	M	53.0	12180	-0.1	-0.01
MAW0085R	25-42.2547-72.1799-4-51-000	6.7	50	0.30	-0.002	116	51.7	7100	-0.001	.	M	151.4	6840	0.4	-0.03
MAW0086R	25-42.2648-72.1588-4-51-000	6.8	60	0.16	-0.002	80	.	8100	-0.001	.	M	.	8420	-0.1	-0.02
MAW0087R	25-42.2974-72.1422-4-51-000	7.2	80	0.20	-0.002	82	.	12300	-0.001	.	M	71.5	8830	-0.1	-0.02
MAW0088R	25-42.3027-72.1828-4-51-000	7.2	70	0.24	-0.002	85	.	8400	1.239	.	M	.	M	-0.1	-0.02
MAW0089R	25-42.2330-72.1356-4-51-000	6.7	90	0.52	-0.002	110	.	12900	-0.001	.	M	.	10420	-0.1	-0.01
MAW0090R	25-42.1699-72.0638-4-51-000	7.0	50	0.22	-0.002	147	14.4	4600	-0.001	72	M	55.6	6430	0.2	-0.03
MAW0091R	25-42.1323-72.1020-4-51-000	7.1	270	0.64	0.006	M	.	M	-0.001	.	M	.	26340	-0.1	0.02
MAW0092R	25-42.0530-72.0785-4-51-000	6.8	40	0.16	-0.002	123	27.1	5500	-0.001	25	M	65.3	6370	-0.1	-0.04
MAW0093R	25-42.0553-72.0191-4-51-000	6.6	50	0.18	0.006	182	21.2	7000	-0.001	.	M	81.9	7240	0.5	0.12
MAW0094R	25-42.0743-72.0050-4-51-000	6.8	100	0.32	-0.002	118	30.1	14300	-0.001	.	M	94.1	9940	-0.1	-0.01
MAW0095R	25-42.0923-72.0435-4-51-000	7.0	60	0.24	0.002	102	31.2	8300	0.058	.	M	109.9	8240	-0.1	0.03
MAW0096R	25-42.1200-72.0601-4-51-000	6.1	120	0.72	-0.002	122	.	8200	-0.001	.	M	.	M	-0.1	-0.01
MAW0097R	25-42.1485-72.0587-4-51-000	6.8	30	0.14	-0.002	249	24.9	4600	-0.001	28	M	114.0	6400	0.8	-0.06
MAW0098R	25-42.2135-72.0285-4-51-000	6.4	160	0.36	-0.002	110	34.7	36400	-0.001	.	M	472.2	15780	-0.1	0.00
MAW0099R	25-42.1702-72.0884-4-51-000	6.5	50	0.14	-0.002	106	.	10100	-0.001	.	M	92.8	7480	-0.1	-0.03
MAW0100R	25-42.1698-72.1338-4-51-000	6.7	30	0.12	-0.002	174	.	6000	1.444	.	M	.	6910	-0.1	-0.06
MAW0101R	25-42.2056-72.1227-4-51-000	6.7	45	0.24	-0.002	156	12.8	6000	-0.001	.	M	209.4	6690	-0.1	-0.03
MAW0102R	25-42.2002-72.1623-4-51-000	6.7	35	0.16	-0.002	107	21.4	5200	-0.001	26	M	60.3	7160	-0.1	-0.05
MAW0103R	25-42.1678-72.1489-4-51-000	6.8	40	0.14	0.010	179	.	5200	-0.001	.	M	58.0	6900	0.3	0.25
MAW0104R	25-42.1745-72.1923-4-51-000	6.2	130	0.10	-0.002	164	.	35200	-0.001	.	M	51.0	17690	-0.1	-0.01

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY

SHEET

13

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000	
MAW0105R	25-42.2004-	72.1881-4-51-000	6.8	40	0.18	-0.002	117	.	7200	-0.331	.	M	.	M	-0.1	-0.04
MAW0106R	25-42.2037-	72.2271-4-51-000	7.1	85	0.38	0.085	157	.	5600	-0.001	24	M	56.7	7200	0.3	1.01
MAW0107R	25-42.2236-	72.2247-4-51-000	7.1	50	0.24	-0.002	59	8.1	9700	1.344	.	M	.	M	-0.1	-0.03
MAW0108R	25-42.2280-	72.1813-4-51-000	6.2	40	0.30	0.004	110	.	4700	1.169	.	M	.	7700	-0.1	0.10
MAW0109R	25-42.2419-	72.1150-4-51-000	7.0	90	0.34	-0.002	70	.	12600	1.615	.	M	.	10210	-0.1	-0.01
MAW0110R	25-42.2594-	72.1073-4-51-000	6.9	80	0.26	-0.002	83	.	12200	-0.001	.	M	.	M	-0.1	-0.02
MAW0111R	25-42.2404-	72.0561-4-51-000	6.6	60	0.26	-0.002	133	28.8	8200	-0.001	.	M	49.6	7320	0.3	-0.02
MAW0112R	25-42.3028-	72.0628-4-51-000	6.1	40	0.12	-0.002	147	6.7	6600	-0.001	.	M	.	7310	-0.1	-0.04
MAW0113R	25-42.3153-	72.0585-4-51-000	6.8	80	0.56	-0.002	114	.	10500	-0.001	.	M	.	8340	-0.1	-0.02
MAW0114R	25-42.3243-	72.1031-4-51-000	6.1	60	0.12	0.038	141	.	3400	-0.001	.	M	.	8670	-0.1	0.63
MAW0115R	25-42.2971-	72.1024-4-51-000	6.6	60	0.12	-0.002	93	.	10300	0.043	.	M	.	7770	-0.1	-0.02
MAW0116R	25-42.3204-	72.1471-4-51-000	6.8	50	0.12	-0.002	73	26.9	7900	-0.001	10	M	46.8	6490	-0.1	-0.03
MAW0117R	25-42.3441-	72.1147-4-51-000	5.3	40	0.06	-0.002	204	26.3	6700	-0.001	.	M	.	6020	-0.1	-0.04
MAW0118R	25-42.3750-	72.0297-4-51-000	6.9	50	0.12	-0.002	174	32.5	11800	-0.001	.	M	65.8	8400	-0.1	-0.03
MAW0119R	25-42.3597-	72.0669-4-51-000	5.4	30	0.04	-0.002	148	.	5500	1.336	.	M	.	6510	-0.1	-0.06
MAW0120R	25-42.3340-	72.0522-4-51-000	4.8	30	0.01	-0.002	239	.	5700	-0.001	.	M	.	6180	0.4	-0.06
MAW0122R	25-42.3665-	72.0091-4-51-000	6.1	30	0.30	-0.002	44	21.4	5300	-0.001	20	M	26.2	6200	-0.1	-0.06
MAW0131R	25-42.4787-	72.0301-4-51-000	6.3	55	0.16	0.005	66	24.5	10300	-0.001	.	M	42.6	8710	-0.1	0.09
MAW0132R	25-42.4825-	72.0764-4-51-000	5.9	30	0.06	-0.002	96	29.1	5300	-0.001	19	M	33.9	5670	-0.1	-0.06
MAW0133R	25-42.4953-	72.0228-4-51-000	6.0	30	0.08	0.004	98	6.8	5800	-0.001	.	M	.	6250	-0.1	0.13
MAW0134R	25-42.5201-	72.0290-4-51-000	4.3	30	0.00	-0.002	305	19.3	4900	-0.001	.	M	36.6	5660	-0.1	-0.06
MAW0180R	25-42.1625-	72.0051-4-51-000	6.7	70	0.28	0.007	114	.	8100	0.026	.	M	.	8700	-0.1	0.10
MAW0181R	25-42.1260-	72.0031-4-51-000	6.9	280	0.30	-0.002	M	.	M	-0.001	.	M	.	32190	-0.1	0.00
MAW0182R	25-42.1046-	72.0098-4-51-000	6.6	60	0.28	-0.002	84	19.6	8100	-0.001	.	M	115.1	7520	-0.1	-0.02
MAW0263R	25-42.2280-	72.0122-4-51-000	6.3	70	0.32	0.013	128	.	6400	-0.001	.	M	.	7920	-0.1	0.19
MAW0264R	25-42.3060-	72.0358-4-51-000	5.4	65	0.16	0.017	199	15.0	11200	0.845	.	M	.	M	-0.1	0.26
MAW0265R	25-42.2791-	72.0252-4-51-000	6.6	160	0.85	0.010	83	.	12900	-0.001	.	M	91.2	8500	-0.1	0.06
NHCH001R	33-42.8919-	72.1059-4-51-000	5.7	18	0.04	-0.002	126	3797.0	7800	-0.001	.	M	7.4	1680	-0.1	-0.10
NHCH002R	33-42.9036-	72.0916-4-51-000	6.5	81	0.06	0.001	19	438.4	17700	-0.001	21	M	14.8	6350	-0.1	0.01
NHCH003R	33-42.9192-	72.0465-4-51-000	6.8	89	0.14	-0.002	16	.	19900	-0.001	.	M	.	4270	-0.1	-0.01
NHCH004R	33-42.8815-	72.0233-4-51-000	6.8	33	0.12	0.009	32	33.9	7100	-0.001	46	M	27.4	2590	-0.1	0.27
NHCH005R	33-42.8678-	72.0613-4-51-000	6.0	27	0.04	-0.002	42	.	8000	0.023	.	M	16.4	2490	0.4	-0.06
NHCH006R	33-42.8325-	72.0852-4-51-000	6.3	57	0.06	-0.002	71	.	11500	-0.001	46	M	17.3	4620	-0.1	-0.03
NHCH007R	33-42.8195-	72.0610-4-51-000	6.2	47	0.06	-0.002	51	.	11200	-0.001	.	M	52.0	3420	0.8	-0.03
NHCH008R	33-42.8024-	72.0577-4-51-000	5.8	37	0.04	-0.002	70	46.4	9100	-0.001	43	M	40.5	3150	-0.1	-0.04
NHCH009R	33-42.8363-	72.0277-4-51-000	6.5	76	0.22	-0.002	113	10.5	10600	-0.001	52	M	190.5	6370	-0.1	-0.02
NHCH015R	33-42.7717-	72.0117-4-51-000	5.5	31	0.04	-0.002	25	31.9	7400	-0.001	18	M	11.2	1830	0.2	-0.05
NHCH016R	33-42.7259-	72.0354-4-51-000	5.0	26	0.02	0.016	M	.	M	-0.001	.	M	31.8	1.	-0.1	0.62
NHCH017R	33-42.7706-	72.0713-4-51-000	5.3	105	0.04	0.030	78	.	21900	-0.001	.	M	62.4	7760	-0.1	0.29
NHCH018R	33-42.7425-	72.0951-4-51-000	5.6	37	0.04	0.020	M	95.2	M	-0.001	.	M	26.0	M	-0.1	0.54
NHCH019R	33-42.7349-	72.1284-4-51-000	5.5	60	0.04	0.113	130	20.8	12100	-0.001	53	M	19.0	4030	-0.1	1.88
NHCH020R	33-42.7639-	72.1339-4-51-000	5.7	145	0.10	0.157	169	.	32100	-0.001	.	M	102.8	9280	-0.1	1.08
NHCH021R	33-42.7593-	72.1869-4-51-000	4.5	47	0.00	0.015	184	18.4	8400	-0.001	36	M	34.4	2670	-0.1	0.32
NHCH022R	33-42.7751-	72.1994-4-51-000	4.8	30	0.01	0.009	249	.	4300	-0.001	27	M	.	2070	-0.1	0.30
NHCH023R	33-42.7942-	72.1268-4-51-000	5.3	27	0.02	0.123	M	1326.0	M	-0.001	.	M	42.2	M	0.2	4.56
NHCH024R	33-42.8120-	72.1188-4-51-000	6.7	43	0.18	0.031	44	34.3	5300	-0.001	64	M	23.4	1890	-0.1	0.72
NHCH025R	33-42.9407-	72.0319-4-51-000	6.2	36	0.06	0.009	31	28.9	6600	-0.001	31	M	20.7	1740	-0.1	0.25
NHCH026R	33-42.9418-	72.0953-4-51-000	5.8	89	0.12	-0.002	52	.	8700	-0.001	.	M	26.9	3730	-0.1	-0.01
NHCH027R	33-42.9726-	72.1068-4-51-000	6.6	27	0.08	0.005	27	35.3	5700	-0.001	48	M	13.0	1410	-0.1	0.19
NHCH028R	33-42.9342-	72.1565-4-51-000	6.2	44	0.06	-0.002	57	857.1	8400	-0.001	.	M	19.8	2170	-0.1	-0.04
NHCH029R	33-42.9341-	72.1254-4-51-000	6.5	28	0.08	-0.002	68	32.4	6000	-0.001	57	M	14.6	1570	-0.1	-0.06
NHCH043R	33-42.9975-	72.1961-4-51-000	6.3	48	0.08	0.007	55	.	9600	-0.001	34	M	21.7	2980	-0.1	0.15
NHCH050R	33-42.9989-	72.1855-4-51-000	6.7	66	0.08	0.017	47	39.5	13900	-0.001	49	M	16.8	5380	-0.1	0.26

C-24

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY

SHEET

14

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NHCH051R	33-42.9897-72.2440-4-51-000	6.4	47	0.08	0.026	90	4361.0	9700	-0.031	.	M	13.6	4150	-0.1	0.55
NHCH064R	33-42.9958-72.3234-4-51-000	6.9	42	0.16	0.085	53	47.4	5900	-0.001	57	M	26.1	1460	-0.1	2.02
NHCH077R	33-42.9909-72.4432-4-51-000	7.5	117	0.32	0.024	21	38.2	12900	-0.001	58	M	.	5980	-0.1	0.21
NHCH078R	33-42.9923-72.3892-4-51-000	7.2	52	0.22	-0.002	8	5663.0	6000	-0.001	.	M	.	2130	-0.1	-0.03
NHCH079R	33-42.7522-72.3123-4-51-000	6.9	40	0.18	0.016	108	35.0	7100	-0.001	15	M	7.1	1980	0.2	0.40
NHCH080R	33-42.7600-72.3205-4-51-000	6.8	34	0.20	0.018	15	4883.0	5000	-0.001	.	M	37.6	2070	-0.1	0.53
NHCH081R	33-42.7340-72.2293-4-51-000	5.7	33	0.06	0.011	129	39.7	8000	-0.001	22	M	19.2	2240	-0.1	0.33
NHCH082R	33-42.7522-72.2212-4-51-000	5.5	25	0.06	-0.002	189	.	11100	-0.001	.	M	59.3	2820	-0.1	-0.07
NHCH083R	33-42.7724-72.2507-4-51-000	6.9	27	0.16	-0.002	55	.	5000	-0.001	48	M	6.8	1690	0.3	-0.06
NHCH084R	33-42.7913-72.2681-4-51-000	6.9	48	0.12	-0.002	71	1119.0	9800	-0.001	.	M	13.4	3670	-0.1	-0.03
NHCH085R	33-42.8217-72.2634-4-51-000	6.7	57	0.18	0.017	38	.	10600	-0.001	24	M	43.2	3440	-0.1	0.30
NHCH086R	33-42.8508-72.2531-4-51-000	6.8	82	0.12	0.007	63	849.7	12100	-0.001	.	M	9.3	4650	-0.1	0.09
NHCH087R	33-42.8809-72.2327-4-51-000	7.1	39	0.18	0.012	43	28.1	5500	-0.001	43	M	12.8	1790	-0.1	0.31
NHCH088R	33-42.8685-72.2095-4-51-000	6.8	71	0.08	0.016	65	.	12200	-0.001	.	M	8.6	5010	0.2	0.23
NHCH089R	33-42.7933-72.3022-4-51-000	6.1	28	0.10	0.016	88	35.1	6100	-0.001	26	M	32.4	1640	-0.1	0.57
NHCH090R	33-42.8314-72.2880-4-51-000	6.6	48	0.26	-0.002	63	420.0	7300	-0.001	.	M	.	2030	-0.1	-0.03
NHCH091R	33-42.8459-72.3265-4-51-000	7.3	72	0.28	0.001	40	44.3	10400	-0.001	42	M	20.4	4510	-0.1	0.01
NHCH092R	33-42.8718-72.3400-4-51-000	6.5	58	0.32	0.108	68	.	10200	-0.001	.	M	612.2	3010	-0.1	1.86
NHCH093R	33-42.8754-72.2756-4-51-000	6.6	76	0.16	0.038	34	.	13600	-0.001	26	M	47.2	5280	-0.1	0.50
NHCH094R	33-42.9171-72.2957-4-51-000	7.1	224	0.50	0.026	3	.	36400	-0.001	.	M	66.3	12920	-0.1	0.12
NHCH095R	33-42.9593-72.2657-4-51-000	6.9	122	0.14	0.142	M	3442.0	30900	-0.001	.	M	.	7690	-0.1	1.16
NHCH096R	33-42.9950-72.2579-4-51-000	5.9	100	0.06	0.061	74	36.9	18000	-0.001	.	M	96.7	7350	-0.1	0.61
NHCH097R	33-42.9757-72.2433-4-51-000	6.6	45	0.08	0.011	20	.	8800	-0.001	.	M	26.6	3450	-0.1	0.24
NHCH098R	33-42.9757-72.2076-4-51-000	6.7	50	0.08	-0.002	63	47.3	9500	-0.001	25	M	11.5	3430	-0.1	-0.03
NHCH099R	33-42.9379-72.2428-4-51-000	6.7	30	0.08	0.008	55	5670.0	9800	-0.001	.	M	31.5	3380	-0.1	0.16
NHCH100R	33-42.9572-72.2164-4-51-000	5.3	20	0.02	0.200	234	17.5	5500	-0.001	45	M	39.0	1280	-0.1	10.00
NHCH101R	33-42.9151-72.1914-4-51-000	6.4	46	0.06	-0.002	50	.	10800	-0.001	.	M	.	3030	-0.1	-0.03
NHCH102R	33-42.9113-72.1718-4-51-000	6.5	580	0.20	0.011	95	.	109400	-0.001	.	M	239.4	45440	-0.1	0.02
NHCH103R	33-42.8767-72.1795-4-51-000	6.5	30	0.08	0.021	93	.	9700	-0.001	.	M	.	2990	-0.1	0.70
NHCH104R	33-42.8710-72.1518-4-51-000	5.9	50	0.10	0.049	114	.	10500	-0.001	69	M	38.8	3370	0.4	0.98
NHCH105R	33-42.8394-72.1381-4-51-000	5.5	55	0.04	-0.002	58	.	13100	-0.001	.	M	.	4090	-0.1	-0.03
NHCH106R	33-42.8234-72.1851-4-51-000	5.8	35	0.06	0.030	107	58.1	7600	-0.001	35	M	35.7	1950	0.3	0.86
NHCH107R	33-42.8454-72.1811-4-51-000	5.7	48	0.06	0.150	137	.	12800	-0.001	.	M	42.3	3720	0.3	3.13
NHCH108R	33-42.9793-72.3023-4-51-000	6.6	50	0.22	0.040	29	38.1	7400	-0.001	45	M	.	2550	0.2	0.80
NHCH109R	33-42.9527-72.3239-4-51-000	7.0	205	1.00	0.072	M	8513.0	22200	-0.001	.	M	180.9	6800	-0.1	0.35
NHCH110R	33-42.9374-72.3408-4-51-000	7.3	86	0.32	0.033	23	.	12000	-0.001	74	M	.	3700	-0.1	0.38
NHCH111R	33-42.9397-72.3924-4-51-000	7.4	61	0.36	0.005	41	6.1	7200	-0.001	.	M	.	3150	-0.1	0.08
NHCH112R	33-42.8957-72.4266-4-51-000	5.8	179	0.12	0.046	71	23.3	32500	-0.001	.	M	310.8	11660	-0.1	0.26
NHCH113R	33-42.9197-72.4121-4-51-000	6.8	102	0.14	-0.002	88	.	15900	-0.001	106	M	23.6	6190	-0.1	-0.01
NHCH114R	33-42.9452-72.4313-4-51-000	7.2	109	0.26	0.026	22	17.6	16500	-0.001	236	M	85.7	6120	-0.1	0.24
NHCH115R	33-42.9718-72.4647-4-51-000	7.5	118	0.32	0.021	20	.	11200	-0.001	57	M	.	6120	-0.1	0.18
NHCH116R	33-42.9591-72.4859-4-51-000	7.2	58	0.20	0.004	87	33.8	5800	-0.001	124	M	11.9	1970	-0.1	0.07
NHCH117R	33-42.9350-72.4730-4-51-000	7.2	50	0.22	0.049	67	.	3400	-0.001	248	M	27.8	1720	-0.1	0.98
NHCH118R	33-42.9046-72.4782-4-51-000	6.8	203	0.22	0.030	42	.	39100	-0.001	.	M	35.4	16370	-0.1	0.15
NHCH119R	33-42.8802-72.4888-4-51-000	7.3	85	0.20	-0.002	M	.	16500	-0.001	.	M	9.4	4660	-0.1	-0.01
NHCH120R	33-42.8690-72.4917-4-51-000	7.1	68	0.16	0.021	35	18.6	8800	-0.001	27	M	125.4	2930	-0.1	0.31
NHCH121R	33-42.8641-72.5190-4-51-000	6.9	40	0.20	-0.002	61	.	7000	-0.001	.	M	104.5	1680	-0.1	-0.04
NHCH122R	33-42.8783-72.5386-4-51-000	7.3	68	0.30	0.009	28	16.6	6000	-0.001	45	M	.	2030	-0.1	0.13
NHCH123R	33-42.9034-72.5009-4-51-000	6.7	63	0.16	-0.002	31	4106.0	7800	-0.001	18	M	104.3	3720	-0.1	-0.02
NHCH124R	33-42.9260-72.5130-4-51-000	6.6	41	0.14	0.011	24	.	5200	-0.001	33	M	8.2	1540	-0.1	0.27
NHCH125R	33-42.8193-72.5253-4-51-000	6.7	72	0.22	-0.002	12	5349.0	10500	-0.001	.	M	42.3	3330	-0.1	-0.02
NHCH126R	33-42.7985-72.5198-4-51-000	7.2	74	0.30	0.007	27	35.5	9400	-0.001	25	M	14.6	3190	0.2	0.09
NHCH127R	33-42.7316-72.4505-4-51-000	7.0	90	0.14	-0.002	3	.	11900	-0.001	12	M	24.6	4980	-0.1	-0.01

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER-- ALBANY SHEET 15

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NHCHI28R	33-42.7225-72.4370-4-51-000	7.0	118	0.20	0.016	22	.	20900	-0.001	.	M	38.2	8380	-0.1	0.14
NHCHI29R	33-42.8052-72.4767-4-51-000	4.8	19	0.01	0.311	178	.	3400	-0.001	37	M	251.1	1550	-0.1	16.37
NHCHI30R	33-42.7852-72.4699-4-51-000	6.6	36	0.10	0.026	16	.	3900	-0.001	67	M	.	2100	0.4	0.72
NHCHI31R	33-42.7874-72.4479-4-51-000	5.2	18	0.02	0.024	80	23.1	4700	-0.001	43	M	24.0	710	-0.1	1.33
NHCHI32R	33-42.7869-72.4297-4-51-000	6.6	30	0.14	0.006	30	5609.0	4100	-0.001	53	M	21.4	1970	-0.1	0.20
NHCHI33R	33-42.7579-72.3857-4-51-000	5.9	47	0.08	0.033	58	.	9800	-0.001	27	M	63.2	3320	0.3	0.70
NHCHI34R	33-42.7492-72.3633-4-51-000	6.8	60	0.22	0.022	49	28.3	9500	-0.001	29	M	20.0	2970	-0.1	0.37
NHCHI35R	33-42.7285-72.3480-4-51-000	6.7	36	0.16	0.026	27	.	5300	-0.001	36	M	.	1810	-0.1	0.72
NHCHI36R	33-42.7896-72.3570-4-51-000	6.9	32	0.18	0.012	M	.	M	-0.001	.	M	.	M	48.9	0.38
NHCHI37R	33-42.7975-72.3745-4-51-000	6.5	34	0.16	0.007	32	15.0	5200	-0.001	29	M	44.4	1550	-0.1	0.21
NHCHI38R	33-42.8293-72.3698-4-51-000	6.4	62	0.20	0.009	13	.	8000	-0.001	.	M	84.6	3720	-0.1	0.15
NHCHI39R	33-42.8247-72.3712-4-51-000	6.1	32	0.10	0.003	30	37.5	5200	-0.001	37	M	72.0	1230	-0.1	0.09
NHH1015R	33-43.0000-72.0327-4-51-000	6.1	60	0.12	-0.002	158	38.4	13600	-0.001	46	M	124.7	11880	-0.1	-0.02
NHH1063R	33-42.9538-72.0448-4-51-000	6.1	30	0.08	0.006	119	20.1	4600	-0.001	32	M	115.2	9300	0.3	0.20
NYAL101R	36-42.4878-73.9826-4-51-000	7.7	175	1.40	0.006	72	.	3600	-0.001	.	M	72.0	4010	-0.1	0.03
NYAL102R	36-42.4803-73.9235-4-51-000	7.6	145	1.30	-0.002	40	21.6	4000	-0.001	15	M	101.2	2260	-0.1	0.00
NYAL103R	36-42.4721-73.8953-4-51-000	7.8	310	2.30	0.060	120	15.0	16100	0.128	.	M	.	6780	-0.1	0.19
NYAL104R	36-42.4695-73.8513-4-51-000	7.9	450	3.80	0.405	488	.	37100	-0.001	.	M	307.8	15530	-0.1	0.90
NYAL105R	36-42.4895-73.7905-4-51-000	7.9	1150	7.40	0.602	M	597.8	M	-0.001	.	M	.	1930	-0.1	0.52
NYAL121R	36-42.6072-73.7718-4-51-000	7.8	2000	4.10	0.498	51	490.4	M	-0.001	.	M	.	M	5.3	0.25
NYAL122R	36-42.6083-73.7967-4-51-000	8.2	465	3.30	0.212	43	19.1	32400	-0.001	.	M	56.4	12600	0.4	0.46
NYAL123R	36-42.5835-73.7679-4-51-000	7.6	425	3.40	0.291	44	.	22700	-0.001	.	M	1115.0	9780	-0.1	0.68
NYAL124R	36-42.5677-73.8154-4-51-000	7.6	660	3.20	0.683	120	.	61900	0.432	.	M	338.6	24300	-0.1	1.03
NYAL125R	36-42.5414-73.7932-4-51-000	7.3	600	1.30	0.037	85	68.5	18400	-0.001	40	M	392.6	8390	-0.1	0.06
NYAL126R	36-42.5117-73.8087-4-51-000	7.9	460	2.90	0.234	50	.	28200	-0.001	.	M	58.5	11820	-0.1	0.51
NYAL127R	36-42.5437-73.8417-4-51-000	7.4	1000	6.70	0.471	79	58.8	70400	-0.001	.	M	172.9	49020	-0.1	0.47
NYAL128R	36-42.5271-73.8467-4-51-000	7.3	900	3.20	0.919	71	.	19100	-0.001	67	M	152.2	10900	-0.1	1.02
NYAL129R	36-42.5263-73.9120-4-51-000	7.6	201	1.60	0.015	37	.	6100	-0.001	35	M	80.5	4430	-0.1	0.07
NYAL130R	36-42.5534-73.8892-4-51-000	7.9	280	2.10	0.271	97	39.3	7100	-0.001	39	M	.	3490	-0.1	0.97
NYAL131R	36-42.5392-73.9424-4-51-000	6.7	310	1.70	0.002	37	.	38300	-0.001	.	M	1487.0	17070	-0.1	0.01
NYAL132R	36-42.5165-73.9604-4-51-000	7.1	210	1.50	0.062	60	.	15000	-0.001	.	M	383.9	6000	-0.1	0.30
NYAL133R	36-42.5340-73.9987-4-51-000	7.3	97	0.65	-0.002	56	23.8	4100	-0.001	23	M	288.7	1930	-0.1	-0.01
NYAL134R	36-42.6003-73.9913-4-51-000	7.9	590	2.80	0.845	74	73.0	20100	-0.001	.	M	84.5	8600	-0.1	1.43
NYAL135R	36-42.5737-73.9608-4-51-000	7.8	530	2.80	0.381	53	.	33600	-0.001	.	M	99.0	15360	-0.1	0.72
NYAL136R	36-42.5891-73.9158-4-51-000	7.5	400	2.80	0.299	57	.	37800	-0.001	.	M	317.2	20300	-0.1	0.75
NYAL137R	36-42.5867-73.8933-4-51-000	7.6	312	1.80	0.122	62	.	19100	-0.001	.	M	69.2	8760	0.5	0.39
NYAL138R	36-42.5888-73.8555-4-51-000	7.9	395	2.70	0.311	93	.	25300	0.121	.	M	83.4	9560	-0.1	0.79
NYAL139R	36-42.6124-73.8621-4-51-000	7.8	700	4.80	0.541	102	.	40000	-0.001	.	M	219.4	7450	0.6	0.77
NYAL140R	36-42.6071-73.8989-4-51-000	7.7	410	2.90	0.260	27	25.4	18900	-0.001	.	M	146.2	7650	-0.1	0.63
NYAL141R	36-42.6291-73.9188-4-51-000	7.7	640	2.50	0.372	6	.	M	-0.001	.	M	.	28390	-0.1	0.58
NYAL142R	36-42.6297-73.8848-4-51-000	7.5	920	5.50	0.722	26	.	67300	0.420	.	M	5414.0	M	-0.1	0.78
NYAL144R	36-42.6594-73.8288-4-51-000	8.1	890	0.01	11.906	87	.	124100	-0.001	.	M	196.2	48100	-0.1	13.38
NYAL145R	36-42.6640-73.8954-4-51-000	8.6	500	2.20	0.186	24	.	53500	1.968	.	M	.	17030	-0.1	0.37
NYAL146R	36-42.7104-73.8398-4-51-000	7.8	445	2.80	0.163	36	60.4	25000	-0.001	.	M	171.0	9770	-0.1	0.37
NYAL147R	36-42.7344-73.9096-4-51-000	8.1	460	1.90	0.101	35	.	55000	-0.001	.	M	.	19680	-0.1	0.22
NYAL148R	36-42.7134-73.8991-4-51-000	7.9	311	1.80	0.063	43	17.6	33400	-0.001	.	M	54.5	12860	0.4	0.20
NYAL149R	36-42.7315-73.9600-4-51-000	7.8	425	1.90	0.163	51	56.1	29600	-0.001	.	M	.	8230	-0.1	0.38
NYAL150R	36-42.7491-73.9841-4-51-000	8.1	1000	3.10	0.483	M	.	122300	-0.001	.	M	92.1	49860	-0.1	0.48
NYAL151R	36-42.7055-73.9761-4-51-000	8.2	580	2.20	0.283	56	24.6	40200	-0.001	.	M	126.3	16420	1.2	0.49
NYAL152R	36-42.6761-73.9526-4-51-000	8.1	400	2.30	0.441	23	.	21400	-0.001	.	M	104.1	6270	0.3	1.10
NYAL153R	36-42.6464-73.9579-4-51-000	7.8	440	2.40	0.143	33	41.3	16000	-0.001	.	M	75.0	5090	-0.1	0.33
NYAL154R	36-42.6380-73.9705-4-51-000	7.6	410	2.50	0.281	52	12.2	24100	-0.001	.	M	248.3	10870	-0.1	0.69
NYAL155R	36-42.6624-73.9858-4-51-000	7.4	360	3.40	0.196	41	.	13400	-0.001	25	M	231.1	9650	-0.1	0.54

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY SHEET

16

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NYAL156R	36-42.7559-73.9050-4-51-000	7.7	335	3.50	0.324	52	.	6700	-0.031	20	M	718.7	7820	-0.1	0.97
NYAL157R	36-42.7439-73.8436-4-51-000	7.7	460	2.90	0.212	56	.	30500	-0.001	35	M	446.8	19600	-0.1	0.40
NYAL158R	36-42.7369-73.8097-4-51-000	7.8	590	3.40	0.173	137	135.5	42100	-0.001	.	M	523.2	25580	-0.1	0.29
NYAL159R	36-42.7374-73.7754-4-51-000	8.0	510	3.20	0.267	109	.	33500	-0.001	.	M	486.4	23800	-0.1	0.52
NYAL160R	36-42.7751-73.7637-4-51-000	7.9	700	4.30	0.459	162	146.0	49300	-0.001	127	M	552.0	28940	-0.1	0.66
NYAL161R	36-42.7616-73.8627-4-51-000	7.7	600	3.00	0.197	139	.	37900	-0.001	49	M	461.8	28960	0.8	0.33
NYAL162R	36-42.7126-73.7435-4-51-000	7.4	420	2.70	0.264	88	14.4	30200	-0.001	.	M	225.2	17790	0.4	0.63
NYAL163R	36-42.7474-73.7207-4-51-000	7.5	570	3.20	0.940	250	92.7	37500	-0.001	103	M	524.4	29300	0.8	1.65
NYAL164R	36-42.7666-73.7172-4-51-000	7.9	720	2.80	0.604	212	.	77000	-0.001	.	M	444.6	30480	1.5	0.84
NYC0001R	36-42.1063-73.5405-4-51-000	6.7	185	1.85	0.230	225	.	8100	-0.001	16	M	150.8	6720	-0.1	1.24
NYC0002R	36-42.1543-73.5203-4-51-000	7.7	220	1.95	0.200	69	.	10800	-0.001	27	M	148.7	8070	0.6	0.91
NYC0003R	36-42.1471-73.5005-4-51-000	8.1	150	1.60	0.093	76	.	4900	-0.001	30	M	147.8	5470	0.7	0.62
NYC0004R	36-42.1788-73.4832-4-51-000	7.9	240	2.30	0.426	137	48.1	17300	-0.001	.	M	175.1	11070	-0.1	1.78
NYC0005R	36-42.1931-73.5111-4-51-000	8.2	140	1.30	0.113	86	19.8	7000	-0.001	.	M	153.8	6140	-0.1	0.81
NYC0006R	36-42.2051-73.4974-4-51-000	8.6	260	2.80	0.376	122	.	5400	-0.001	.	M	183.9	5980	-0.1	1.45
NYC0007R	36-42.2435-73.4799-4-51-000	8.2	100	0.70	0.044	99	8.6	7900	-0.001	.	M	112.6	6080	-0.1	0.44
NYC0008R	36-42.2377-73.5117-4-51-000	8.1	100	0.80	0.028	185	1171.0	5700	-0.001	21	M	120.9	6410	-0.1	0.28
NYC0009R	36-42.2295-73.5670-4-51-000	8.2	60	0.85	0.025	117	46.1	4600	-0.001	25	M	110.6	5150	0.6	0.42
NYC0010R	36-42.2137-73.5596-4-51-000	8.1	70	0.50	0.027	109	.	4700	-0.001	.	M	109.2	5610	0.3	0.39
NYC0011R	36-42.2132-73.5878-4-51-000	8.0	80	0.60	0.026	109	21.7	4500	-0.001	15	M	153.0	5980	-0.1	0.33
NYC0012R	36-42.2373-73.6243-4-51-000	7.9	95	0.50	0.002	99	20.7	6700	-0.001	.	M	116.9	6220	-0.1	0.02
NYC0013R	36-42.2125-73.6406-4-51-000	7.5	150	0.54	0.008	95	37.9	4700	-0.001	.	M	124.7	6750	-0.1	0.05
NYC0014R	36-42.2333-73.6329-4-51-000	7.7	150	1.14	0.071	213	22.2	5800	-0.001	33	M	134.9	6330	0.4	0.47
NYC0015R	36-42.2331-73.6738-4-51-000	8.0	245	0.80	0.153	128	.	14400	-0.001	56	M	166.8	7140	0.6	0.62
NYC0016R	36-42.2234-73.7330-4-51-000	7.9	275	2.10	0.041	98	24.6	11200	-0.001	25	M	401.7	7900	0.3	0.15
NYC0017R	36-42.2044-73.6982-4-51-000	8.5	230	1.80	0.103	75	.	19500	-0.001	20	M	111.7	10650	0.3	0.45
NYC0018R	36-42.1963-73.7404-4-51-000	8.6	120	1.60	0.078	88	31.4	8300	-0.001	34	M	121.9	6710	-0.1	0.65
NYC0019R	36-42.1652-73.7363-4-51-000	8.0	215	1.55	0.111	85	.	6000	-0.001	22	M	318.3	6730	-0.1	0.52
NYC0020R	36-42.1357-73.7222-4-51-000	8.0	150	0.85	0.018	93	18.6	5600	-0.001	44	M	120.7	7490	-0.1	0.12
NYC0021R	36-42.1624-73.7067-4-51-000	7.9	140	0.90	0.038	89	26.0	7000	-0.001	17	M	217.4	7110	-0.1	0.27
NYC0022R	36-42.1395-73.6719-4-51-000	8.0	140	0.75	0.037	73	37.3	11500	0.502	38	M	143.8	8160	-0.1	0.26
NYC0023R	36-42.1421-73.6503-4-51-000	7.9	135	0.75	0.039	84	.	5900	-0.001	47	M	460.8	6540	-0.1	0.29
NYC0024R	36-42.1738-73.6446-4-51-000	7.8	95	0.55	0.013	81	28.8	6100	-0.001	11	M	132.5	6910	-0.1	0.14
NYC0025R	36-42.1651-73.6124-4-51-000	7.8	100	0.55	0.017	68	41.8	5400	-0.001	.	M	118.4	6440	0.6	0.17
NYC0026R	36-42.1553-73.5698-4-51-000	7.9	150	0.90	0.242	69	17.8	7500	-0.001	55	M	146.0	6780	0.3	1.61
NYC0027R	36-42.1351-73.5380-4-51-000	7.8	210	0.26	0.178	72	22.4	4900	-0.001	18	M	165.0	5650	0.4	0.85
NYC0028R	36-42.1133-73.5684-4-51-000	6.1	170	1.60	0.194	80	15.9	7000	-0.001	38	M	163.7	6520	0.3	1.14
NYC0029R	36-42.1015-73.5902-4-51-000	7.5	240	2.70	0.225	86	14.9	7200	-0.001	9	M	144.1	7320	0.4	0.94
NYC0030R	36-42.1326-73.6190-4-51-000	7.5	110	1.00	0.090	66	15.9	5800	-0.001	25	M	315.5	6680	-0.1	0.82
NYC0031R	36-42.1117-73.6466-4-51-000	7.5	115	1.10	-0.002	62	36.2	5200	-0.001	61	M	184.2	6170	-0.1	-0.01
NYC0032R	36-42.0902-73.6760-4-51-000	7.7	135	1.05	0.094	74	14.7	10200	-0.001	.	M	118.9	7610	-0.1	0.70
NYC0033R	36-42.1083-73.6961-4-51-000	7.7	160	1.35	0.152	73	36.2	3600	-0.001	.	M	123.1	6110	-0.1	0.95
NYC0034R	36-42.1069-73.7502-4-51-000	7.6	150	1.55	0.065	55	.	4000	-0.001	39	M	172.2	6690	-0.1	0.43
NYC0035R	36-42.0753-73.7276-4-51-000	7.8	185	1.05	0.054	46	34.1	14700	-0.001	.	M	277.2	9820	-0.1	0.29
NYC0036R	36-42.0511-73.7328-4-51-000	7.9	95	0.60	0.032	76	12.8	5300	-0.001	.	M	107.1	6280	0.4	0.34
NYC0037R	36-42.0292-73.7331-4-51-000	7.8	85	0.40	-0.002	67	25.1	8100	-0.001	16	M	111.2	7200	-0.1	-0.01
NYC0038R	36-42.0051-73.6778-4-51-000	8.1	180	1.20	0.087	80	.	6600	-0.001	60	M	123.5	7290	-0.1	0.48
NYC0039R	36-42.0209-73.6399-4-51-000	8.0	110	0.65	0.091	83	14.1	4800	-0.001	53	M	145.5	6170	-0.1	0.83
NYC0040R	36-42.0334-73.6212-4-51-000	8.1	350	3.30	0.291	87	20.8	8800	-0.001	23	M	162.0	6980	-0.1	0.83
NYC0041R	36-42.0074-73.5945-4-51-000	8.4	320	3.10	0.311	109	19.0	7800	-0.001	19	M	186.3	7210	-0.1	0.97
NYC0042R	36-42.0119-73.5689-4-51-000	8.3	370	4.40	0.435	96	.	6900	-0.001	34	M	179.4	6600	-0.1	1.18
NYC0043R	36-42.0311-73.5778-4-51-000	8.9	320	3.20	0.421	84	.	9800	-0.001	40	M	181.3	7690	0.3	1.32
NYC0044R	36-42.0677-73.5323-4-51-000	8.2	310	3.00	0.509	94	2243.0	9000	-0.001	19	M	177.1	7550	-0.1	1.64

C-27

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER-- ALBANY SHEET 17

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NYC0045R	36-42.0655-73.5686-4-51-000	8.3	440	3.10	0.361	97	.	10200	2.488	32	M	236.0	7770	0.2	1.50
NYC0046R	36-42.0635-73.6069-4-51-000	8.4	320	3.80	0.293	90	.	7500	-0.001	.	M	149.2	5530	0.2	0.92
NYC0047R	36-42.0728-73.6270-4-51-000	8.4	95	0.70	0.002	81	25.8	4500	-0.001	12	M	103.1	5510	-0.1	0.02
NYC0049R	36-42.0537-73.6925-4-51-000	7.7	160	1.45	0.043	61	18.8	4800	-0.001	79	M	2530.0	5660	-0.1	0.27
NYC0050R	36-42.1425-73.7727-4-51-000	7.2	120	1.55	0.049	73	.	10200	-0.001	32	M	184.6	7350	-0.1	0.41
NYC0051R	36-42.1606-73.7692-4-51-000	7.7	210	1.70	0.074	85	26.4	8100	-0.001	34	M	127.5	6250	-0.1	0.35
NYC0052R	36-42.1907-73.7739-4-51-000	7.7	270	2.30	0.169	147	15.9	11000	-0.001	42	M	174.6	7390	-0.1	0.63
NYC0053R	36-42.2147-73.7666-4-51-000	7.7	250	3.80	0.184	104	23.0	6700	-0.001	73	M	215.7	6250	-0.1	0.74
NYC0054R	36-42.2168-73.8009-4-51-000	8.3	370	3.10	0.388	93	.	10500	-0.001	46	M	180.8	7500	0.3	1.05
NYC0055R	36-42.1998-73.8229-4-51-000	7.8	380	3.90	0.299	79	.	11000	-0.001	.	M	1000.0	8520	-0.1	0.79
NYC0056R	36-42.1694-73.8079-4-51-000	8.4	250	1.80	0.180	84	.	6600	-0.001	62	M	.	6820	0.2	0.72
NYC0057R	36-42.1348-73.8267-4-51-000	7.6	700	1.70	0.491	89	.	87100	-0.001	.	M	673.8	13410	0.7	0.70
NYC0058R	36-42.1342-73.8512-4-51-000	8.1	330	2.10	0.334	62	.	10700	-0.001	35	M	188.2	10430	-0.1	1.01
NYC0059R	36-42.1660-73.8719-4-51-000	8.2	435	3.10	0.243	82	.	23300	-0.001	77	M	219.1	17720	-0.1	0.56
NYC0060R	36-42.1507-73.8757-4-51-000	8.1	390	3.10	0.409	63	.	17100	-0.001	51	M	210.0	15460	0.5	1.05
NYC0062R	36-42.1167-73.8680-4-51-000	8.6	300	2.40	0.671	60	8.2	5600	-0.001	62	M	145.7	7170	0.5	2.24
NYC0063R	36-42.0827-73.8544-4-51-000	7.9	310	2.40	0.170	410	26.3	7900	-0.001	40	M	536.0	6190	1.4	0.55
NYC0064R	36-42.0425-73.7732-4-51-000	7.6	100	0.70	-0.002	86	21.5	5400	-0.001	25	M	106.8	5580	-0.1	-0.01
NYC0065R	36-42.0731-73.7988-4-51-000	7.6	110	0.75	-0.002	89	39.1	5200	-0.001	46	M	114.7	5800	-0.1	-0.01
NYC0066R	36-42.1112-73.7942-4-51-000	9.1	240	1.60	0.191	101	12.4	7700	-0.001	31	M	122.4	6070	0.7	0.80
NYC0067R	36-42.1065-73.7676-4-51-000	8.3	170	1.20	0.029	88	.	6200	-0.001	18	M	197.4	6210	-0.1	0.17
NYC0068R	36-42.0897-73.7729-4-51-000	8.2	165	1.15	0.081	97	28.5	8400	-0.001	37	M	119.2	6890	0.5	0.49
NYC0069R	36-42.2891-73.7660-4-51-000	7.2	2300	7.20	1.949	75	.	17500	-0.001	.	M	504.8	5130	-0.1	0.85
NYC0070R	36-42.3144-73.7613-4-51-000	8.8	270	1.50	0.150	87	54.4	12900	-0.001	13	M	146.4	9130	-0.1	0.56
NYC0071R	36-42.3483-73.7774-4-51-000	8.8	255	1.60	0.143	120	38.7	13500	-0.001	30	M	139.8	13130	0.3	0.56
NYC0073R	36-42.4169-73.7678-4-51-000	8.5	330	2.00	0.354	138	30.7	10800	-0.001	64	M	164.2	11630	1.1	1.07
NYC0074R	36-42.4647-73.7700-4-51-000	8.0	480	2.50	0.408	96	.	24300	-0.001	75	M	170.1	17670	0.3	0.85
NYC0075R	36-42.4758-73.6488-4-51-000	7.6	350	1.70	0.106	51	25.3	35400	-0.001	.	M	106.1	14320	0.5	0.30
NYC0076R	36-42.4684-73.6763-4-51-000	7.3	240	2.00	0.319	77	22.6	6100	-0.001	30	M	101.3	6030	0.3	1.33
NYC0077R	36-42.4567-73.7240-4-51-000	8.0	290	2.10	0.193	69	.	13200	-0.001	38	M	152.4	6400	0.7	0.67
NYC0078R	36-42.4325-73.7321-4-51-000	7.5	275	2.40	0.197	45	17.9	14300	-0.001	53	M	147.6	5860	0.4	0.72
NYC0079R	36-42.4036-73.7388-4-51-000	7.9	230	1.50	0.205	87	33.3	9300	-0.001	50	M	117.6	6810	-0.1	0.89
NYC0080R	36-42.4043-73.6946-4-51-000	7.4	260	2.20	0.094	61	72.1	12500	-0.001	93	M	1187.0	7240	-0.1	0.36
NYC0081R	36-42.3640-73.7100-4-51-000	7.5	355	1.60	0.036	100	.	34800	-0.001	.	M	157.8	22260	-0.1	0.10
NYC0082R	36-42.3166-73.7365-4-51-000	7.8	1100	1.70	1.066	73	.	3700	-0.001	.	M	320.2	4400	-0.1	0.97
NYC0083R	36-42.2973-73.7136-4-51-000	7.5	470	2.10	0.540	56	28.4	12100	-0.001	45	M	283.7	10390	-0.1	1.15
NYC0084R	36-42.2658-73.7248-4-51-000	8.0	370	3.80	0.447	95	11.8	12600	-0.001	61	M	147.0	7990	0.5	1.21
NYC0085R	36-42.2631-73.7007-4-51-000	8.2	305	2.10	0.271	79	20.8	8000	-0.001	51	M	118.9	6160	-0.1	0.89
NYC0086R	36-42.2917-73.6857-4-51-000	7.8	310	3.20	0.381	81	28.1	7500	-0.001	63	M	300.7	4860	0.5	1.23
NYC0087R	36-42.2671-73.6454-4-51-000	8.0	230	1.80	0.080	235	13.6	10100	-0.001	19	M	103.6	6220	0.6	0.35
NYC0088R	36-42.2836-73.6500-4-51-000	7.8	250	2.00	0.114	107	11.1	10100	-0.001	22	M	133.7	6240	-0.1	0.46
NYC0089R	36-42.3184-73.6441-4-51-000	7.7	300	2.10	0.296	85	43.0	8100	-0.001	61	M	194.4	6200	0.5	0.99
NYC0090R	36-42.3345-73.6865-4-51-000	8.0	300	2.50	0.234	99	.	7600	-0.001	48	M	116.0	5740	0.5	0.78
NYC0091R	36-42.3607-73.6718-4-51-000	7.9	140	1.30	0.010	65	50.7	4700	-0.001	53	M	1119.0	5070	-0.1	0.07
NYC0092R	36-42.3673-73.6381-4-51-000	7.9	210	1.00	0.049	78	31.5	6600	-0.001	44	M	174.3	5600	0.2	0.23
NYC0093R	36-42.3968-73.6401-4-51-000	7.3	220	1.50	0.023	99	.	6100	-0.001	39	M	.	5830	-0.1	0.10
NYC0094R	36-42.4116-73.6582-4-51-000	7.5	180	1.60	0.065	106	43.4	6900	-0.001	66	M	135.6	5100	-0.1	0.36
NYC0095R	36-42.4619-73.6452-4-51-000	7.6	210	1.10	0.046	79	.	13000	-0.001	.	M	92.1	6490	0.4	0.22
NYC0096R	36-42.4701-73.5285-4-51-000	6.1	100	0.70	0.029	70	22.6	4000	-0.001	23	M	71.9	4880	-0.1	0.29
NYC0097R	36-42.4772-73.5529-4-51-000	6.4	90	0.65	-0.002	82	17.4	5200	-0.001	51	M	80.6	5360	-0.1	-0.01
NYC0098R	36-42.4658-73.5720-4-51-000	6.5	130	1.10	0.030	112	43.9	5700	-0.001	46	M	96.8	6360	-0.1	0.23
NYC0099R	36-42.4803-73.6012-4-51-000	6.9	110	0.70	0.013	134	15.5	5900	-0.001	26	M	116.0	6020	-0.1	0.12
NYC0100R	36-42.4747-73.6170-4-51-000	7.0	360	2.20	0.126	72	.	40100	-0.001	.	M	231.3	16290	-0.1	0.35

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY

SHEET

18

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NYC0101R	36-42.4261-73.6147-4-51-000	7.2	240	2.30	0.055	80	23.6	8100	-0.001	32	M	114.8	6330	0.4	0.23
NYC0102R	36-42.3830-73.6068-4-51-000	7.1	200	1.40	0.074	280	395.3	6800	0.430	32	M	394.8	5880	0.5	0.37
NYC0103R	36-42.3534-73.5977-4-51-000	7.1	200	1.20	0.085	86	75.3	14700	-0.001	31	M	162.8	9620	-0.1	0.43
NYC0104R	36-42.3257-73.6089-4-51-000	8.5	220	2.10	0.208	65	19.2	7300	-0.001	45	M	107.1	7010	-0.1	0.95
NYC0105R	36-42.3010-73.6050-4-51-000	7.5	170	1.60	0.105	87	35.1	6700	-0.001	45	M	111.2	6480	-0.1	0.62
NYC0106R	36-42.3024-73.5762-4-51-000	7.3	110	0.75	0.021	95	53.8	6500	-0.001	.	M	97.7	5890	-0.1	0.19
NYC0107R	36-42.2551-73.6018-4-51-000	7.8	110	0.50	0.017	117	41.6	7300	-0.001	.	M	101.6	6020	0.3	0.15
NYC0108R	36-42.2642-73.5761-4-51-000	8.5	105	1.10	0.021	103	.	6800	-0.001	19	M	106.9	5910	0.4	0.20
NYC0109R	36-42.2648-73.5042-4-51-000	7.3	105	0.60	0.037	110	.	4500	-0.001	19	M	185.3	5310	0.3	0.35
NYC0110R	36-42.2662-73.4881-4-51-000	7.3	80	0.55	0.017	100	13.3	3300	-0.001	.	M	101.8	5140	0.6	0.21
NYC0111R	36-42.2879-73.4713-4-51-000	7.1	95	0.30	0.025	255	.	9800	-0.001	.	M	107.4	6930	0.8	0.26
NYC0112R	36-42.3329-73.4296-4-51-000	7.3	170	1.60	0.107	120	.	11500	-0.001	.	M	137.4	7990	0.3	0.63
NYC0113R	36-42.3189-73.4898-4-51-000	6.9	80	0.60	0.038	114	.	8100	-0.001	.	M	.	6410	-0.1	0.48
NYC0114R	36-42.3003-73.5121-4-51-000	7.0	90	0.70	0.013	90	12.3	4000	-0.001	26	M	137.3	4780	-0.1	0.14
NYC0115R	36-42.3144-73.5391-4-51-000	7.1	130	0.70	0.034	86	33.7	7700	-0.001	42	M	109.0	6600	-0.1	0.26
NYC0116R	36-42.3350-73.5571-4-51-000	7.8	140	0.85	0.068	103	6.2	6700	-0.001	17	M	102.3	6380	0.3	0.49
NYC0117R	36-42.3555-73.5554-4-51-000	8.4	135	0.65	0.085	103	29.2	4800	-0.001	25	M	102.2	5850	0.3	0.63
NYC0118R	36-42.3616-73.5216-4-51-000	8.4	80	0.42	0.034	93	.	4200	-0.001	13	M	92.9	4970	0.3	0.43
NYC0119R	36-42.3605-73.4898-4-51-000	8.4	85	0.44	0.014	99	38.6	5400	-0.001	44	M	100.5	5620	-0.1	0.16
NYC0120R	36-42.3819-73.4869-4-51-000	7.1	80	0.40	0.013	83	31.5	4200	-0.001	36	M	99.0	5220	0.3	0.16
NYC0121R	36-42.3914-73.5606-4-51-000	7.5	235	1.07	0.135	89	.	18200	-0.001	.	M	114.5	11330	0.2	0.57
NYC0122R	36-42.4383-73.5748-4-51-000	7.4	360	1.15	0.122	100	.	39100	-0.001	.	M	111.8	19480	0.5	0.34
NYC0123R	36-42.4868-73.4819-4-51-000	5.9	60	0.32	0.017	72	33.0	4300	-0.001	14	M	518.2	5810	-0.1	0.28
NYC0124R	36-42.4890-73.4533-4-51-000	6.7	190	1.50	0.250	84	.	8800	-0.001	.	M	193.2	8090	-0.1	1.32
NYC0125R	36-42.4663-73.4225-4-51-000	6.9	115	0.70	0.020	105	27.3	8100	-0.001	20	M	243.5	7810	0.4	0.17
NYC0126R	36-42.4770-73.4081-4-51-000	6.8	70	0.28	0.025	108	21.1	4600	-0.001	.	M	109.8	6280	0.3	0.36
NYC0127R	36-42.4643-73.3905-4-51-000	6.9	195	1.70	0.278	125	.	8200	-0.001	41	M	139.8	8490	-0.1	1.43
NYC0128R	36-42.4184-73.3994-4-51-000	7.3	150	1.50	0.094	308	8.8	3800	-0.001	23	M	123.1	5160	0.4	0.63
NYC0129R	36-42.4266-73.4324-4-51-000	6.1	170	2.00	0.158	75	48.0	3900	-0.001	36	M	123.6	5890	-0.1	0.93
NYC0130R	36-42.4191-73.4734-4-51-000	7.4	210	1.80	0.146	91	38.9	11200	-0.001	.	M	140.0	8550	-0.1	0.70
NYC0131R	36-42.4658-73.4831-4-51-000	7.1	70	0.35	0.012	93	17.8	4700	-0.001	19	M	110.7	6110	-0.1	0.17
NYC0132R	36-42.4559-73.5075-4-51-000	5.9	95	0.42	-0.002	97	41.4	5600	-0.001	34	M	104.7	7190	-0.1	-0.01
NYC0133R	36-42.4141-73.5169-4-51-000	7.3	150	0.85	0.122	710	.	8100	-0.001	49	M	127.4	7960	0.4	0.81
NYC0134R	36-42.3995-73.5064-4-51-000	5.7	410	1.95	0.080	122	.	43400	-0.001	.	M	368.1	24570	-0.1	0.20
NYC0135R	36-42.3785-73.4296-4-51-000	7.5	300	2.60	0.207	136	8.2	13500	-0.001	13	M	160.5	10210	-0.1	0.69
NYC0136R	36-42.3560-73.4285-4-51-000	8.2	110	0.90	0.092	106	13.7	3800	-0.001	17	M	95.5	5890	0.3	0.84
NYDU001R	36-42.0211-73.5111-4-51-000	8.4	210	2.60	0.142	75	24.8	3800	-0.001	30	M	119.7	6470	-0.1	0.68
NYDU002R	36-42.0453-73.5124-4-51-000	8.1	180	1.70	0.124	89	18.3	4300	-0.001	14	M	117.0	6770	-0.1	0.69
NYDU003R	36-42.0461-73.8686-4-51-000	8.0	290	1.70	0.321	69	.	11200	-0.001	30	M	186.2	8550	-0.1	1.11
NYDU004R	36-42.0704-73.8939-4-51-000	8.5	255	2.00	0.263	75	.	12300	-0.001	.	M	124.2	9510	0.4	1.03
NYDU005R	36-42.0463-73.9111-4-51-000	8.2	315	2.20	0.243	81	46.6	15300	-0.001	68	M	126.6	12590	-0.1	0.77
NYDU006R	36-42.0134-73.8958-4-51-000	8.7	285	2.20	0.128	80	.	11600	-0.001	.	M	108.4	10630	-0.1	0.45
NYDU007R	36-42.0082-73.8575-4-51-000	8.7	240	2.40	0.101	75	17.6	8000	-0.001	.	M	122.8	8490	-0.1	0.42
NYDU008R	36-42.0184-73.8208-4-51-000	8.5	175	2.00	0.028	80	20.7	7100	-0.001	.	M	102.8	8320	-0.1	0.16
NYDU009R	36-42.0343-73.8078-4-51-000	8.1	200	1.80	0.220	1621	.	4800	-0.001	22	M	160.6	7460	1.6	1.10
NYDU010R	36-42.0247-73.7692-4-51-000	6.5	145	1.05	0.013	111	13.7	6700	-0.001	33	M	198.3	8520	0.3	0.09
NYGR151R	36-42.1531-73.9195-4-51-000	8.0	340	2.00	0.179	62	.	23100	0.087	.	M	53.2	10710	-0.1	0.53
NYGR153R	36-42.1783-73.8909-4-51-000	8.5	230	1.70	0.134	138	.	16400	0.985	.	M	.	7190	0.5	0.58
NYGR154R	36-42.2155-73.9123-4-51-000	8.0	1150	4.00	0.305	29	.	85900	-0.001	.	M	25.4	24050	-0.1	0.27
NYGR155R	36-42.1974-73.9505-4-51-000	7.9	260	3.00	0.106	103	.	21500	-0.001	.	M	.	8900	-0.1	0.41
NYGR156R	36-42.1832-73.9758-4-51-000	7.3	150	0.70	0.092	838	.	5900	-0.001	47	M	243.4	2570	0.5	0.61
NYGR157R	36-42.2042-73.9748-4-51-000	7.6	130	0.95	0.067	87	.	6200	-0.001	.	M	86.6	2670	-0.1	0.52
NYGR158R	36-42.2218-73.9890-4-51-000	7.3	160	1.15	0.052	364	38.6	8300	-0.001	40	M	71.4	3240	0.3	0.33

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY

SHEET

19

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	ALOXO MG/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NYGR159R	36-42.2777-73.9800-4-51-000	5.8	100	0.62	0.325	46	4040.0	8100	-0.001	17	M	221.7	2700	0.3	0.25
NYGR160R	36-42.3405-73.9932-4-51-000	7.5	150	1.50	0.317	50	.	4800	-0.001	37	M	30.6	3020	-0.1	0.11
NYGR161R	36-42.2755-73.9558-4-51-000	7.1	280	3.00	0.346	50	.	10600	-0.301	24	M	1913.0	6150	0.8	0.15
NYGR162R	36-42.3062-73.9506-4-51-000	7.5	110	0.80	0.007	67	22.6	7900	-0.301	.	M	71.6	3570	-0.1	0.06
NYGR164R	36-42.3667-73.9904-4-51-000	7.8	210	2.10	0.085	49	30.1	6600	-0.301	35	M	65.6	4220	-0.1	0.40
NYGR165R	36-42.3613-73.9521-4-51-000	7.7	275	1.40	0.021	55	18.9	4100	-0.301	.	M	170.7	3140	-0.1	0.08
NYGR166R	36-42.3944-73.9612-4-51-000	8.0	250	2.20	0.144	41	.	12000	-0.301	.	M	47.4	4600	-0.1	0.58
NYGR167R	36-42.4146-73.9846-4-51-000	7.6	325	3.10	0.085	53	.	16600	-0.001	.	M	167.0	10510	-0.1	0.26
NYGR168R	36-42.4392-73.9822-4-51-000	7.8	120	1.60	0.008	31	42.3	5400	-0.001	48	M	83.7	3190	0.2	0.07
NYGR169R	36-42.4425-73.9054-4-51-000	8.0	125	1.45	0.011	88	45.6	5700	-0.001	31	M	58.1	3130	-0.1	0.09
NYGR170R	36-42.4391-73.3335-4-51-000	8.1	200	1.50	0.042	63	.	5700	-0.001	38	M	77.2	3680	-0.1	0.21
NYGR171R	36-42.4118-73.3194-4-51-000	7.9	120	0.90	0.020	59	32.0	5900	-0.001	66	M	63.3	3180	-0.1	0.17
NYGR172R	36-42.3989-73.3830-4-51-000	7.8	220	2.40	0.072	40	.	5700	-0.001	20	M	.	5320	-0.1	0.33
NYGR173R	36-42.3838-73.8924-4-51-000	7.2	250	3.10	0.118	36	40.3	4300	-0.001	37	M	2657.0	2430	-0.1	0.47
NYGR174R	36-42.3902-73.9306-4-51-000	8.1	170	1.30	0.090	45	35.7	5300	-0.001	62	M	94.6	4440	0.2	0.53
NYGR175R	36-42.3386-73.9341-4-51-000	7.4	170	2.10	0.007	415	.	7600	-0.001	.	M	.	5370	-0.1	0.04
NYGR176R	36-42.3478-73.9020-4-51-000	9.3	160	1.40	0.062	62	39.5	6600	-0.001	62	M	96.4	3500	0.4	0.39
NYGR177R	36-42.3239-73.9049-4-51-000	8.2	180	1.20	-0.002	80	.	8100	-0.001	.	M	.	3900	-0.1	0.00
NYGR179R	36-42.2664-73.9016-4-51-000	8.1	360	2.30	0.139	47	.	18900	-0.001	41	M	52.5	8960	0.3	0.39
NYGR180R	36-42.2325-73.9251-4-51-000	8.2	180	1.50	0.015	44	29.2	5300	-0.001	57	M	75.7	4590	0.4	0.08
NYGR181R	36-42.2609-73.8457-4-51-000	7.3	470	4.20	0.162	58	.	5400	-0.001	49	M	169.1	6010	0.2	0.34
NYGR182R	36-42.2875-73.8465-4-51-000	7.8	700	4.20	0.207	134	16.5	43400	-0.001	.	M	147.4	35140	1.6	0.30
NYGR183R	36-42.3285-73.8501-4-51-000	7.7	1000	3.20	0.289	M	.	M	-0.001	.	M	.	M	-0.1	0.29
NYGR184R	36-42.3559-73.8385-4-51-000	7.9	500	3.10	0.225	42	.	45400	-0.001	.	M	99.2	18190	-0.1	0.45
NYGR185R	36-42.3836-73.8400-4-51-000	7.2	320	3.00	0.115	52	.	8200	-0.001	.	M	22.7	4510	-0.1	0.36
NYGR186R	36-42.4072-73.8601-4-51-000	7.9	215	2.00	0.033	M	.	M	-0.001	.	M	.	M	-0.1	0.15
NYGR187R	36-42.4179-73.8219-4-51-000	7.8	385	3.20	0.108	59	.	8700	-0.001	.	M	.	5690	-0.1	0.28
NYGR188R	36-42.4562-73.8361-4-51-000	7.8	550	5.00	0.169	38	.	29200	-0.001	.	M	67.9	11780	-0.1	0.31
NYGR189R	36-42.3937-73.8001-4-51-000	8.4	1400	4.80	0.783	11	.	M	-0.001	.	M	.	M	0.5	0.56
NYGR190R	36-42.3660-73.8034-4-51-000	8.1	700	3.40	2.783	58	12.8	10800	0.056	447	M	584.5	11340	0.4	3.98
NYGR191R	36-42.3279-73.8046-4-51-000	7.5	330	2.60	0.422	380	.	20700	-0.001	275	M	456.8	7420	0.5	1.28
NYGR192R	36-42.3099-73.8115-4-51-000	8.1	295	2.10	0.214	154	.	9800	1.270	57	M	53.7	3570	0.4	0.73
NYGR193R	36-42.2742-73.8027-4-51-000	8.1	200	1.20	0.123	199	.	25500	-0.001	55	M	68.7	11010	0.6	0.62
NYGR194R	36-42.2381-73.8568-4-51-000	7.7	380	3.30	0.288	45	17.7	9000	-0.001	43	M	165.2	7650	0.3	0.76
NYRE001R	36-42.4851-73.6800-4-51-000	7.5	1000	1.50	-0.002	60	.	162200	-0.001	.	M	.	46160	-0.1	0.00
NYRE002R	36-42.4786-73.7153-4-51-000	7.2	400	2.90	0.186	27	.	35300	-0.001	.	M	61.2	9530	-0.1	0.47
NYRE010R	36-42.5174-73.3606-4-51-000	7.1	125	1.12	0.129	38	.	7200	-0.001	.	M	20.3	1980	-0.1	1.03
NYRE011R	36-42.5383-73.3601-4-51-000	6.6	101	0.74	0.052	15	.	6800	-0.001	.	M	.	1600	-0.1	0.51
NYRE012R	36-42.5656-73.3630-4-51-000	7.3	106	0.88	0.055	14	.	8300	0.605	.	M	12.9	1850	-0.1	0.52
NYRE013R	36-42.5970-73.3581-4-51-000	7.4	62	0.48	0.042	20	37.3	4700	-0.001	28	M	.	580	-0.1	0.68
NYRE014R	36-42.6130-73.3824-4-51-000	7.5	92	0.60	0.016	18	.	9900	-0.001	.	M	23.1	3000	-0.1	0.17
NYRE015R	36-42.5920-73.4206-4-51-000	5.0	25	0.02	2.286	148	.	3700	-0.001	45	M	86.8	1610	-0.1	91.44
NYRE016R	36-42.5616-73.3923-4-51-000	6.3	34	0.08	-0.002	72	12.0	4200	-0.001	23	M	34.2	1610	-0.1	-0.05
NYRE017R	36-42.5399-73.3945-4-51-000	7.4	115	0.88	0.022	20	29.9	6100	-0.001	.	M	36.9	2310	-0.1	0.19
NYRE018R	36-42.5337-73.4142-4-51-000	7.4	60	0.20	-0.002	51	35.8	3900	-0.001	33	M	33.7	2240	-0.1	-0.02
NYRE019R	36-42.5104-73.4236-4-51-000	7.4	60	0.20	-0.002	29	29.1	5200	-0.001	18	M	34.0	2260	-0.1	-0.02
NYRE020R	36-42.5094-73.4066-4-51-000	7.0	70	0.18	-0.002	31	15.0	5900	-0.001	.	M	31.2	2070	-0.1	-0.02
NYRE021R	36-42.7246-73.3680-4-51-000	7.1	81	0.64	-0.002	27	25.5	5600	-0.001	.	M	35.6	2280	-0.1	-0.01
NYRE022R	36-42.7135-73.3805-4-51-000	7.7	40	0.16	-0.002	22	18.4	4700	-0.001	16	M	27.0	1910	0.2	-0.04
NYRE023R	36-42.7039-73.3695-4-51-000	7.9	63	0.38	-0.002	96	13.1	4300	-0.001	19	M	33.7	2240	0.1	-0.02
NYRE024R	36-42.6774-73.3315-4-51-000	7.6	39	0.20	-0.002	23	25.6	4100	-0.001	16	M	28.8	1420	-0.1	-0.04
NYRE025R	36-42.6580-73.3637-4-51-000	7.5	88	0.64	0.006	24	32.1	5400	-0.001	.	M	31.3	2010	-0.1	0.07
NYRE026R	36-42.6347-73.3587-4-51-000	7.9	40	0.14	-0.002	21	18.9	4300	-0.001	.	M	29.9	1320	-0.1	-0.04

C-30-

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER-- ALBANY SHEET 20

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NYRE027R	36-42.6412- 73.3885-4-51-000	7.5	36	0.06	-0.002	42	19.7	4900	-0.001	22	M	27.7	1700	-0.1	-0.05
NYRE028R	36-42.6532- 73.4160-4-51-000	4.6	31	0.00	-0.002	160	23.3	5400	-0.001	15	M	67.3	1840	-0.1	-0.05
NYRE029R	36-42.6870- 73.4333-4-51-000	4.7	28	0.00	-0.002	131	18.0	4200	-0.001	43	M	61.6	1650	-0.1	-0.05
NYRE030R	36-42.6883- 73.4884-4-51-000	5.4	26	0.02	-0.002	142	16.6	4600	-0.001	30	M	51.8	1800	-0.1	-0.07
NYRE031R	36-42.7155- 73.4656-4-51-000	4.3	30	0.00	-0.002	123	23.7	4900	0.049	28	M	71.9	1660	-0.1	-0.06
NYRE032R	36-42.7175- 73.4290-4-51-000	5.3	22	0.04	-0.002	54	20.3	4100	-0.001	30	M	41.5	1280	-0.1	-0.08
NYRE033R	36-42.6840- 73.3849-4-51-000	6.7	52	0.30	-0.002	34	20.4	3500	0.031	25	M	26.3	1460	-0.1	-0.03
NYRE034R	36-42.7075- 73.3304-4-51-000	6.8	49	0.22	-0.002	20	18.9	4200	-0.001	8	M	32.0	1650	0.3	-0.03
NYRE035R	36-42.7413- 73.4024-4-51-000	6.5	25	0.22	-0.002	48	25.4	3600	-0.001	27	M	24.5	1640	-0.1	-0.07
NYRE036R	36-42.6345- 73.4806-4-51-000	5.5	28	0.04	-0.002	91	19.2	3900	0.033	32	M	36.6	1780	-0.1	-0.06
NYRE037R	36-42.6124- 73.4798-4-51-000	5.7	27	0.04	-0.002	111	31.2	4400	-0.001	49	M	33.0	1910	-0.1	-0.06
NYRE038R	36-42.5863- 73.4848-4-51-000	6.3	28	0.06	-0.002	98	29.4	4400	-0.001	46	M	21.7	1780	-0.1	-0.06
NYRE039R	36-42.6071- 73.5198-4-51-000	6.3	43	0.18	-0.002	29	22.0	3500	0.053	33	M	22.3	1680	-0.1	-0.04
NYRE040R	36-42.6143- 73.5737-4-51-000	6.9	103	0.88	0.006	41		3800	-0.001	11	M	75.8	2190	-0.1	0.06
NYRE041R	36-42.6131- 73.6020-4-51-000	7.0	177	0.96	-0.002	24	30.7	11500	-0.001		M	241.2	4740	-0.1	0.00
NYRE042R	36-42.5861- 73.6029-4-51-000	7.1	106	0.52	-0.002	25		6500	-0.001	21	M	51.8	3380	0.1	-0.01
NYRE043R	36-42.5836- 73.5564-4-51-000	6.9	100	0.72	-0.002	34	8.9	6000	-0.001		M	311.0	2650	-0.1	-0.01
NYRE044R	36-42.5819- 73.5279-4-51-000	7.3	81	0.28	-0.002	24	13.1	9700	-0.001		M	28.1	4030	-0.1	-0.01
NYRE045R	36-42.5583- 73.5469-4-51-000	7.2	66	0.40	-0.002	36	17.0	3700	-0.001		M	32.9	2040	-0.1	-0.02
NYRE046R	36-42.5581- 73.5148-4-51-000	7.3	50	0.16	-0.002	44	14.5	5300	-0.001	34	M	21.1	2550	-0.1	-0.03
NYRE047R	36-42.5392- 73.4767-4-51-000	6.9	45	0.12	-0.002	36	17.2	4300	0.050	30	M	36.1	2020	-0.1	-0.03
NYRE048R	36-42.5138- 73.4868-4-51-000	6.3	58	0.22	-0.002	31	23.8	3100	-0.001	30	M	46.2	2210	-0.1	-0.02
NYRE049R	36-42.5161- 73.5148-4-51-000	6.9	50	0.12	-0.002	35	24.6	5000	-0.001	26	M	26.7	2150	-0.1	-0.03
NYRE050R	36-42.5122- 73.5591-4-51-000	7.0	122	0.34	-0.002	28	21.1	3400	-0.001	19	M	34.8	2650	-0.1	-0.01
NYRE051R	36-42.5278- 73.6037-4-51-000	7.6	102	0.44	-0.002	33		6100	-0.001	17	M	29.4	3070	-0.1	-0.01
NYRE052R	36-42.5200- 73.6287-4-51-000	7.1	150	0.96	-0.002	38	25.3	7400	-0.001		M	73.4	3710	-0.1	0.00
NYRE053R	36-42.5558- 73.6774-4-51-000	7.6	275	1.70	0.066	24	13.8	16800	-0.001		M		5800	-0.1	0.24
NYRE054R	36-42.5607- 73.6432-4-51-000	7.6	145	0.76	-0.002	30		8600	-0.001		M	43.1	3950	-0.1	0.00
NYRE055R	36-42.5524- 73.5921-4-51-000	7.4	100	0.52	6.658	28	28.6	7500	-0.001		M	35.9	3310	-0.1	66.58
NYRE056R	36-42.5903- 73.6411-4-51-000	6.6	124	1.08	-0.002	26	20.7	4500	0.036		M	51.3	2950	-0.1	-0.01
NYRE057R	36-42.7347- 73.2938-4-51-000	6.2	85	0.26	0.004	64	11.7	11800	-0.001		M	102.5	3640	-0.1	0.05
NYRE058R	36-42.7545- 73.3040-4-51-000	7.0	51	0.32	-0.002	48	33.0	3800	-0.001	13	M	33.2	1290	-0.1	-0.03
NYRE059R	36-42.7706- 73.3317-4-51-000	7.3	56	0.36	-0.002	33	23.4	3900	-0.001		M	24.9	1590	-0.1	-0.03
NYRE060R	36-42.7851- 73.3256-4-51-000	7.5	168	2.00	0.510	28		3500	-0.001		M	39.9	1990	0.2	3.04
NYRE061R	36-42.7981- 73.3374-4-51-000	7.3	141	1.24	0.408	28		4300	-0.001	13	M	38.7	1700	0.4	2.89
NYRE062R	36-42.8199- 73.2892-4-51-000	7.8	138	1.20	0.279	62		3800	-0.001	11	M	38.7	1610	0.3	2.02
NYRE063R	36-42.8443- 73.3560-4-51-000	7.6	90	0.56	6.920	35	35.3	6200	-0.001	19	M	28.1	2800	0.2	76.89
NYRE064R	36-42.8624- 73.3231-4-51-000	7.9	285	2.70	0.358	26		9700	-0.001		M	70.5	4190	-0.1	1.26
NYRE065R	36-42.8784- 73.3018-4-51-000	7.3	160	1.45	0.175	36	9.9	5700	-0.001	11	M	49.4	3230	-0.1	1.09
NYRE066R	36-42.8874- 73.3481-4-51-000	7.2	117	0.84	0.025	18	18.4	3800	-0.001		M	32.3	2270	-0.1	0.21
NYRE067R	36-42.9213- 73.3125-4-51-000	7.1	128	0.74	0.024	26	14.6	4300	-0.001	21	M	36.2	2200	0.2	0.19
NYRE068R	36-42.9383- 73.3221-4-51-000	7.2	90	0.72	-0.002	29	19.4	4300	-0.001	7	M	32.5	1630	-0.1	-0.01
NYRE069R	36-42.9307- 73.3494-4-51-000	7.2	92	0.72	0.008	35	16.6	4000	-0.001		M	28.6	1850	-0.1	0.09
NYRE070R	36-42.9315- 73.3873-4-51-000	7.2	270	2.40	0.275	29		4500	-0.001		M	57.5	2940	-0.1	1.02
NYRE071R	36-42.9195- 73.4306-4-51-000	6.5	195	1.04	0.036	24	20.5	6000	-0.001	24	M	46.5	2570	-0.1	0.18
NYRE072R	36-42.9300- 73.4656-4-51-000	7.2	163	1.28	0.100	59		5700	-0.001		M	49.7	2870	0.2	0.61
NYRE073R	36-42.8962- 73.4057-4-51-000	6.2	93	0.84	-0.002	38	28.1	4500	-0.001		M	34.4	2260	-0.1	-0.01
NYRE074R	36-42.8928- 73.4201-4-51-000	6.9	140	1.13	0.017	32		4900	-0.001		M	32.8	2630	-0.1	0.12
NYRE075R	36-42.8891- 73.4593-4-51-000	6.7	130	0.92	0.003	28	27.5	6600	-0.001		M	91.5	2800	-0.1	0.02
NYRE076R	36-42.8704- 73.4594-4-51-000	6.4	110	0.76	0.019	30	19.9	4700	-0.001		M	65.3	2350	-0.1	0.17
NYRE077R	36-42.8601- 73.4102-4-51-000	6.9	100	0.88	0.012	28	20.5	3800	-0.001		M	28.7	2070	-0.1	0.12
NYRE078R	36-42.8483- 73.4151-4-51-000	6.7	89	0.60	0.006	25	21.8	3600	-0.001		M	62.8	2040	-0.1	0.07
NYRE079R	36-42.8288- 73.3918-4-51-000	6.7	85	0.52	-0.002	34	21.8	4700	-0.001	17	M	26.5	2290	-0.1	-0.01

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY SHEET

21

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MCQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NYRE080R	36-42.8209- 73.3733-4-51-000	6.5	51	0.34	-0.002	33	16.8	3900	-0.001	15	M	20.4	1710	-0.1	-0.03
NYRE081R	36-42.7764- 73.3832-4-51-000	6.2	38	0.18	-0.002	47	17.6	4000	-0.001	29	M	22.9	1600	-0.1	-0.04
NYRE082R	36-42.8080- 73.4016-4-51-000	6.2	55	0.24	-0.002	42	37.4	6500	-0.001	.	M	25.4	2160	-0.1	-0.03
NYRE083R	36-42.8192- 73.4312-4-51-000	6.5	55	0.28	-0.002	34	28.6	5300	-0.001	43	M	25.2	2160	0.2	-0.03
NYRE084R	36-42.8407- 73.4853-4-51-000	6.8	83	0.56	-0.002	50	33.6	6000	-0.001	26	M	49.5	2830	-0.1	-0.01
NYRE085R	36-42.8178- 73.4736-4-51-000	7.4	55	0.32	-0.002	41	21.6	3100	-0.001	.	M	23.7	1690	-0.1	-0.03
NYRE086R	36-42.8126- 73.5338-4-51-000	7.6	140	0.96	-0.002	32	.	5900	-0.001	.	M	36.1	2670	-0.1	0.00
NYRE087R	36-42.8321- 73.5492-4-51-000	7.4	187	1.67	0.034	13	.	5800	-0.001	18	M	19.4	2090	-0.1	0.18
NYRE088R	36-42.8682- 73.5552-4-51-000	8.0	140	1.10	0.023	23	29.0	6300	-0.001	14	M	52.0	2390	-0.1	0.16
NYRE089R	36-42.8707- 73.5219-4-51-000	8.3	145	1.00	0.052	24	.	6000	-0.001	14	M	25.6	2440	-0.1	0.36
NYRE090R	36-42.8918- 73.5071-4-51-000	7.2	177	1.16	0.040	14	8.6	6400	-0.001	42	M	69.3	2470	0.3	0.23
NYRE091R	36-42.9331- 73.5175-4-51-000	8.4	245	1.87	0.161	16	.	5600	-0.001	13	M	36.8	1640	-0.1	0.66
NYRE092R	36-42.9195- 73.5381-4-51-000	7.3	260	2.20	0.093	12	25.0	5500	-0.001	43	M	.	2500	-0.1	0.36
NYRE093R	36-42.9175- 73.5791-4-51-000	7.7	203	1.55	0.061	26	.	6100	-0.001	14	M	41.0	1910	-0.1	0.30
NYRE094R	36-42.8988- 73.5404-4-51-000	8.9	211	1.53	0.322	31	.	4700	0.035	36	M	.	2270	-0.1	1.53
NYRE095R	36-42.8774- 73.5798-4-51-000	7.8	155	1.27	0.025	13	.	4400	-0.001	.	M	.	1080	-0.1	0.16
NYRE096R	36-42.8604- 73.6079-4-51-000	7.2	340	4.40	0.276	25	.	7600	-0.001	78	M	391.7	3070	-0.1	0.81
NYRE097R	36-42.8252- 73.6104-4-51-000	7.7	160	1.30	0.023	18	18.8	5400	-0.001	35	M	.	1910	-0.1	0.14
NYRE098R	36-42.8037- 73.6025-4-51-000	7.4	240	1.67	0.073	15	18.5	9200	-0.001	.	M	108.3	3400	-0.1	0.30
NYRE099R	36-42.7931- 73.5715-4-51-000	7.7	352	3.00	0.400	11	.	12600	-0.001	69	M	.	5370	-0.1	1.14
NYRE100R	36-42.7892- 73.5326-4-51-000	7.4	121	0.80	0.019	22	.	6700	-0.001	.	M	14.4	2520	-0.1	0.16
NYRE101R	36-42.7690- 73.5194-4-51-000	7.2	52	0.32	0.077	34	32.8	5800	-0.001	47	M	.	1630	-0.1	1.48
NYRE102R	36-42.7570- 73.4225-4-51-000	5.4	24	0.02	-0.002	93	32.0	4100	-0.001	37	M	22.5	530	-0.1	-0.07
NYRE103R	36-42.7377- 73.4414-4-51-000	5.5	25	0.02	0.004	81	17.2	4200	-0.001	37	M	45.2	550	-0.1	0.16
NYRE104R	36-42.7345- 73.4733-4-51-000	5.6	30	0.02	0.002	127	21.5	4200	-0.001	55	M	40.5	960	-0.1	0.07
NYRE105R	36-42.7561- 73.4886-4-51-000	6.9	48	0.14	0.041	47	17.3	6300	-0.001	58	M	204.1	1820	-0.1	0.85
NYRE106R	36-42.7628- 73.5649-4-51-000	7.0	163	1.04	-0.002	17	.	7700	-0.001	.	M	.	M	-0.1	0.00
NYRE107R	36-42.7758- 73.6139-4-51-000	7.8	225	1.73	0.166	22	.	5500	1.124	30	M	31.5	2050	0.4	0.74
NYRE108R	36-42.7335- 73.6379-4-51-000	8.0	295	2.20	0.155	18	.	16300	-0.001	.	M	.	5930	0.2	0.53
NYRE109R	36-42.6812- 73.6548-4-51-000	7.0	412	3.20	0.578	70	43.9	16600	-0.001	71	M	319.5	8520	-0.1	1.40
NYRE110R	36-42.6851- 73.6884-4-51-000	7.4	360	1.93	0.140	20	.	23800	1.774	.	M	.	8050	-0.1	0.39
NYRE111R	36-42.6341- 73.7273-4-51-000	8.0	400	2.20	0.217	31	.	22100	-0.001	43	M	103.8	8580	-0.1	0.54
NYRE112R	36-42.6629- 73.6793-4-51-000	7.8	209	1.10	0.055	28	.	9600	-0.001	.	M	28.8	4270	-0.1	0.26
NYRE113R	36-42.6412- 73.6656-4-51-000	7.4	268	1.95	0.130	34	46.3	10500	-0.001	39	M	77.7	5320	0.1	0.49
NYRE114R	36-42.6113- 73.6414-4-51-000	7.5	220	1.13	-0.002	7	.	15400	-0.001	.	M	40.0	4550	-0.1	0.00
NYRE115R	36-42.6127- 73.6957-4-51-000	7.7	248	1.33	0.051	19	.	12300	-0.001	24	M	40.4	4230	-0.1	0.21
NYRE116R	36-42.6070- 73.7236-4-51-000	7.2	660	3.90	0.345	M	53.9	58900	-0.001	.	M	226.6	39800	-0.1	0.52
NYRE117R	36-42.6385- 73.5382-4-51-000	7.4	82	0.44	0.013	47	61.8	9300	-0.001	42	M	30.3	3190	-0.1	0.16
NYRE118R	36-42.6458- 73.6040-4-51-000	7.7	70	1.00	0.009	16	1543.0	9700	0.030	.	M	48.0	4240	-0.1	0.05
NYRE119R	36-42.6702- 73.5713-4-51-000	7.1	35	1.00	0.016	23	19.7	6300	-0.001	33	M	108.2	3060	-0.1	0.12
NYRE120R	36-42.6742- 73.6036-4-51-000	7.3	181	1.60	0.029	M	.	5200	-0.001	.	M	.	2400	-0.1	0.16
NYRE121R	36-42.7015- 73.6065-4-51-000	8.5	325	2.00	0.300	18	.	21900	-0.001	.	M	.	6940	-0.1	0.92
NYRE122R	36-42.7035- 73.5602-4-51-000	7.9	70	0.33	-0.002	30	3449.0	3300	-0.001	26	M	9.2	1860	-0.1	-0.02
NYRE123R	36-42.6852- 73.5257-4-51-000	7.3	42	0.20	0.003	59	38.2	5500	-0.001	70	M	56.5	1330	-0.1	0.07
NYRE124R	36-42.7097- 73.5084-4-51-000	5.9	34	0.02	0.003	65	.	3500	-0.001	36	M	18.1	1560	-0.1	0.09
NYRE125R	36-42.7415- 73.5227-4-51-000	7.0	60	0.28	0.012	34	29.0	6600	-0.001	47	M	18.0	1670	-0.1	0.20
NYRE126R	36-42.7369- 73.5661-4-51-000	7.4	25	0.72	0.008	M	.	6000	-0.001	.	M	12.3	2140	-0.1	0.06
NYRE127R	36-42.7375- 73.6094-4-51-000	7.3	370	2.10	0.291	544	15.5	15600	-0.001	54	M	769.8	5990	1.8	0.79
NYRE128R	36-42.7790- 73.6440-4-51-000	7.3	304	2.70	0.275	35	.	5800	-0.001	21	M	227.7	2830	0.5	0.90
NYRE129R	36-42.8105- 73.6469-4-51-000	7.6	260	2.30	0.041	34	.	14100	-0.001	.	M	.	4540	-0.1	0.16
NYRE130R	36-42.8460- 73.6292-4-51-000	7.8	272	1.87	0.171	29	52.5	13800	-0.001	61	M	86.2	6090	0.3	0.63
NYRE131R	36-42.8649- 73.6709-4-51-000	8.0	270	2.20	0.122	89	46.9	6500	-0.001	59	M	148.7	5720	-0.1	0.45
NYRE132R	36-42.8931- 73.6294-4-51-000	8.0	455	4.00	0.195	77	.	8300	-0.001	27	M	198.3	6520	0.4	0.43

C-32

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY SHEET

22

SRL I.D. *****	DOE I.D.		PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	OY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NYRE133R	36-42.9175-	73.6462-4-51-000	8.7	232	1.60	0.197	83	17.6	10500	-0.031	22	M	129.1	8750	-0.1	0.85
NYRE134R	36-42.5229-	73.6821-4-51-000	7.1	145	0.96	0.003	88	24.3	7000	-0.001	38	M	134.6	6730	-0.1	0.02
NYRE135R	36-42.5790-	73.6857-4-51-000	7.6	206	1.50	0.041	69	21.1	12500	-0.001	30	M	160.9	8500	0.3	0.20
NYRE136R	36-42.5845-	73.7402-4-51-000	8.3	448	2.90	0.588	59		25000	-0.001		M	175.4	9700	0.7	1.31
NYRE137R	36-42.5615-	73.7444-4-51-000	8.4	360	2.90	0.252	42	32.1	11800	-0.001	60	M	162.5	9050	0.5	0.70
NYRE138R	36-42.5153-	73.7266-4-51-000	8.4	320	1.90	0.186	34	20.2	12600	-0.001	42	M	164.9	8390	-0.1	0.58
NYRE139R	36-42.5139-	73.7624-4-51-000	8.0	700	4.20	0.962	81	36.8	22500	-0.001	45	M	338.8	21800	-0.1	1.37
NYSC001R	36-42.7744-	73.8299-4-51-000	7.6	402	3.10	0.197	66		21600	-0.001	44	M	217.3	16060	-0.1	0.49
NYSC002R	36-42.7954-	73.8723-4-51-000	8.2	590	3.00	0.343	101	23.9	46400	-0.001		M	284.8	33220	-0.1	0.58
NYSC003R	36-42.8382-	73.8927-4-51-000	7.4	880	3.20	1.434	703		92000	-0.001		M	834.0	46960	-0.1	1.63
NYSC004R	36-42.8704-	73.9072-4-51-000	7.7	452	3.20	0.227	328	21.6	29200	-0.001	80	M	187.7	23070	1.7	0.50
NYSC005R	36-42.8496-	73.9481-4-51-000	7.8	250	1.80	0.096	226	29.5	13900	-0.001	37	M	139.8	14690	1.1	0.38
NYSC006R	36-42.8606-	73.9828-4-51-000	7.4	380	2.90	0.195	104		15700	-0.001	36	M	150.1	18770	-0.1	0.51
NYSC007R	36-42.8077-	73.9932-4-51-000	7.7	229	0.90	0.032	95	12.7	21500	-0.001	44	M	152.7	15870	3.9	0.14
NYSC008R	36-42.9095-	73.9196-4-51-000	7.8	270	2.40	0.193	61		11900	-0.001	28	M	159.9	12170	-0.1	0.71
NYSC009R	36-42.8816-	73.9474-4-51-000	7.6	351	2.10	0.143	53		26800	-0.001		M	188.1	19480	0.4	0.41
NYSC010R	36-42.9057-	73.9843-4-51-000	7.0	265	2.40	0.053	57		10100	-0.001		M	159.4	16970	0.4	0.20
NYSR026R	36-42.8493-	73.7537-4-51-000	7.8	320	2.20	0.276	82		28000	-0.001		M		11890	-0.1	0.86
NYSR027R	36-42.8353-	73.7646-4-51-000	7.5	370	1.90	0.151	24		40000	-0.001		M	151.5	15550	-0.1	0.41
NYSR028R	36-42.8026-	73.7713-4-51-000	8.0	465	2.20	0.329	11		57300	-0.001		M	42.2	22870	-0.1	0.71
NYSR029R	36-42.8329-	73.8047-4-51-000	7.8	388	2.20	0.420	34		36700	-0.001		M		12600	-0.1	1.08
NYSR030R	36-42.8663-	73.8217-4-51-000	7.4	475	3.50	0.218	71	680.5	38700	-0.001		M	678.7	11040	-0.1	0.46
NYSR031R	36-42.8036-	73.8259-4-51-000	7.7	295	1.70	0.157	34		20400	-0.001	17	M	75.9	7650	-0.1	0.53
NYSR032R	36-42.8206-	73.8519-4-51-000	7.3	310	2.07	0.159	M	50.4	6900	-0.001		M		7430	-0.1	0.51
NYSR033R	36-42.8273-	73.7405-4-51-000	7.7	380	2.20	0.273	45		26100	-0.001		M	95.8	15170	0.6	0.72
NYSR034R	36-42.8017-	73.6920-4-51-000	7.7	430	3.10	0.416	66		23400	-0.001		M	108.3	13370	-0.1	0.97
NYSR035R	36-42.8392-	73.6748-4-51-000	8.1	362	2.70	0.400	38	39.9	10700	-0.001	34	M		3840	-0.1	1.10
NYSR036R	36-42.8664-	73.7248-4-51-000	7.5	440	1.50	0.094	M		M	-0.001		M		28500	-0.1	0.21
NYSR037R	36-42.8802-	73.7275-4-51-000	7.5	281	1.70	0.170	44	41.4	9900	-0.001	34	M	71.7	6040	-0.1	0.60
NYSR038R	36-42.9132-	73.7380-4-51-000	7.8	260	1.70	0.092	54		5400	-0.001		M	32.8	3770	0.3	0.35
NYSR039R	36-42.9162-	73.7702-4-51-000	7.9	320	1.70	0.121	67		20000	-0.001		M	62.7	8880	-0.1	0.38
NYSR040R	36-42.8872-	73.7726-4-51-000	7.8	325	2.90	0.215	64		12200	-0.001		M		380	-0.1	0.66
NYSR041R	36-42.8859-	73.7979-4-51-000	7.7	400	2.50	0.190	61		31700	-0.001	34	M	78.5	13020	-0.1	0.48
NYSR042R	36-42.8914-	73.8304-4-51-000	7.2	340	2.60	0.162	32		9100	-0.001		M	331.4	6210	-0.1	0.48
NYSR043R	36-42.9053-	73.8390-4-51-000	7.0	485	3.80	0.648	69	68.6	13200	-0.001	46	M	1122.0	8230	0.8	1.34
NYSR044R	36-42.9312-	73.8256-4-51-000	7.2	428	3.00	0.459	M	71.5	30700	-0.001		M	1355.0	15940	-0.1	1.07
NYSR045R	36-42.9393-	73.8517-4-51-000	7.4	418	4.40	0.210	55	44.2	12400	-0.001	169	M	107.0	20570	-0.1	0.50
NYSR046R	36-42.9486-	73.7810-4-51-000	7.6	258	2.40	0.052	101	675.5	9200	-0.001		M	41.5	3500	-0.1	0.20
NYSR047R	36-42.9472-	73.7293-4-51-000	7.7	198	1.80	0.061	64	30.0	3100	-0.001	32	M	86.2	1530	0.5	0.31
NYSR048R	36-42.9541-	73.8046-4-51-000	7.7	330	1.90	0.130	62	17.6	25300	-0.001		M	53.2	15500	-0.1	0.39
NYSR049R	36-42.9695-	73.8320-4-51-000	7.3	234	1.60	0.047	111	498.7	17500	-0.001	43	M	65.4	6930	-0.1	0.20
NYSR050R	36-42.9754-	73.8492-4-51-000	8.1	306	3.10	0.145	77		19400	0.327		M		6950	-0.1	0.47
NYSR051R	36-42.8928-	73.8895-4-51-000	7.1	330	2.80	1.185	47		23800	-0.001	15	M	119.6	9780	0.3	3.59
NYSR052R	36-42.9363-	73.9851-4-51-000	7.4	230	2.50	0.140	71		6800	-0.001		M		5210	-0.1	0.61
NYSR053R	36-42.9701-	73.9759-4-51-000	7.4	190	1.80	0.087	59		7900	-0.001		M	56.6	5170	0.2	0.46
NYSR054R	36-42.9945-	73.9851-4-51-000	7.2	170	1.50	0.041	26	25.4	7600	-0.001	35	M	160.8	2480	-0.1	0.24
NYSR055R	36-42.9654-	73.9181-4-51-000	7.2	217	1.40	0.054	81		9200	-0.001		M	61.0	4390	-0.1	0.25
NYSR056R	36-42.9884-	73.9234-4-51-000	8.3	350	1.60	0.116	28	13.0	38000	-0.001		M		12770	-0.1	0.33
NYSR057R	36-42.9906-	73.8840-4-51-000	7.7	1140	7.30	1.189	484		79500	-0.001		M	2392.0	12280	3.3	1.04
NYSR058R	36-42.9698-	73.8809-4-51-000	8.1	320	2.30	0.145	32		16000	-0.001		M	92.4	5450	-0.1	0.45
NYSR059R	36-42.9407-	73.8756-4-51-000	7.4	355	3.00	0.254	60		11700	-0.001	79	M	184.7	6870	0.3	0.72
NYSR060R	36-42.9853-	73.7705-4-51-000	7.8	294	2.50	0.120	47		17400	-0.001	68	M		6250	-0.1	0.41
NYSR061R	36-42.9418-	73.6875-4-51-000	8.0	660	7.00	2.238	139	2698.0	22300	-0.001		M	577.8	12580	-0.1	3.39

C-33

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER-- ALBANY SHEET 23

SRL I.D. *****	DOE I.D.	PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
NYSR062R	36-42.9732-73.7239-4-51-000	8.0	170	1.70	0.254	98	14.3	6500	-0.031	46	M	78.7	1860	-0.1	1.49
NYSR063R	36-42.9666-73.6867-4-51-000	7.9	240	2.50	0.285	80	19.0	12200	-0.001	.	M	158.1	6390	-0.1	1.19
NYSR064R	36-42.9880-73.6892-4-51-000	8.3	1600	11.60	0.655	542	.	148100	-0.001	.	M	2715.6	54000	-0.1	0.41
NYSR065R	36-42.9819-73.6513-4-51-000	8.3	470	3.60	0.612	140	31.0	29800	-0.001	.	M	160.7	12110	-0.1	1.30
NYSR066R	36-42.9579-73.6495-4-51-000	7.6	345	3.30	0.301	115	72.9	13600	-0.001	29	M	426.7	5440	-0.1	0.87
NYUL101R	36-42.0132-73.9540-4-51-000	7.3	410	3.10	0.608	61	.	10500	-0.001	48	M	55.5	13050	0.4	1.48
NYUL102R	36-42.0293-73.9566-4-51-000	7.2	275	2.60	0.248	449	94.6	13800	0.853	206	M	1066.0	9210	1.0	0.90
NYUL103R	36-42.0175-73.9782-4-51-000	7.7	415	2.90	0.231	72	.	40400	-0.001	67	M	.	19080	1.1	0.56
NYUL105R	36-42.0886-73.9770-4-51-000	7.6	480	1.50	0.065	82	251.6	77000	-0.001	.	M	.	40080	-0.1	0.14
NYUL106R	36-42.0974-73.9457-4-51-000	8.7	1300	0.62	0.160	M	.	M	-0.001	.	M	.	M	-0.1	0.12
NYUL107R	36-42.1126-73.9732-4-51-000	7.9	485	2.15	0.124	43	30.1	76100	-0.001	.	M	150.2	31780	1.0	0.26
NYUL108R	36-42.1405-73.9861-4-51-000	8.0	100	1.00	0.019	194	13.1	6800	-0.001	.	M	452.6	2570	0.3	0.19
NYWS001R	36-42.9774-73.2880-4-51-000	7.2	102	0.92	0.019	102	.	11800	-0.001	37	M	.	3780	-0.1	0.19
NYWS002R	36-42.9807-73.3285-4-51-000	7.7	80	0.68	0.011	52	24.0	4500	-0.001	27	M	.	1380	-0.1	0.14
NYWS003R	36-42.9765-73.3644-4-51-000	7.9	182	2.30	0.161	48	46.3	9500	-0.001	94	M	.	3550	-0.1	0.88
NYWS004R	36-42.9852-73.3818-4-51-000	7.8	176	1.70	0.116	97	19.9	9700	-0.001	.	M	35.0	4240	-0.1	0.66
NYWS005R	36-42.9693-73.3853-4-51-000	7.8	170	1.33	0.138	196	.	17700	-0.001	20	M	114.9	7310	-0.1	0.81
NYWS006R	36-42.9575-73.3642-4-51-000	7.5	410	4.50	1.112	308	1665.0	18800	-0.001	.	M	.	6240	-0.1	2.71
NYWS007R	36-42.9576-73.4509-4-51-000	8.2	239	2.40	0.251	148	.	25800	-0.001	98	M	234.5	10530	-0.1	1.05
NYWS008R	36-42.9820-73.4269-4-51-000	8.0	150	1.70	0.067	112	.	5600	-0.001	24	M	31.0	1930	-0.1	0.45
NYWS009R	36-42.9841-73.4807-4-51-000	7.7	196	1.73	0.133	324	.	14900	-0.001	45	M	317.8	5050	-0.1	0.68
NYWS010R	36-42.9555-73.4825-4-51-000	7.8	207	2.20	0.181	227	33.5	8100	-0.001	.	M	81.1	3430	-0.1	0.87
NYWS011R	36-42.9605-73.5200-4-51-000	7.8	140	1.40	0.117	73	.	5100	-0.001	45	M	391.0	4620	-0.1	0.84
NYWS012R	36-42.9799-73.5184-4-51-000	7.4	181	2.00	0.045	84	15.0	5300	-0.001	45	M	160.8	4860	-0.1	0.25
NYWS013R	36-42.9871-73.5513-4-51-000	7.1	208	1.80	0.041	76	36.5	6400	-0.001	32	M	101.2	5040	-0.1	0.20
NYWS014R	36-42.9580-73.5563-4-51-000	7.1	180	1.60	0.047	65	33.5	5900	-0.001	28	M	86.2	4580	-0.1	0.26
NYWS015R	36-42.9542-73.6031-4-51-000	7.4	900	7.50	1.215	544	.	74300	-0.001	.	M	2500.0	32680	-0.1	1.35
NYWS016R	36-42.9801-73.6098-4-51-000	9.1	245	3.00	0.452	97	.	7500	-0.001	22	M	358.6	6920	0.3	1.84
VTBE001R	50-42.7831-72.9583-4-51-000	6.8	29	0.10	-0.002	105	28.6	6400	-0.001	34	M	9.3	1830	0.3	-0.06
VTBE002R	50-42.7506-72.9490-4-51-000	6.9	24	0.14	0.004	49	.	3900	0.026	.	M	7.7	2110	-0.1	0.17
VTBE003R	50-42.7556-72.9783-4-51-000	6.6	21	0.12	0.014	83	21.0	4500	-0.001	16	M	13.9	750	-0.1	0.67
VTBE004R	50-42.7857-72.9806-4-51-000	6.4	20	0.08	-0.002	34	17.7	4000	-0.001	.	M	7.0	1300	0.1	-0.09
VTBE005R	50-42.8134-72.9710-4-51-000	6.3	18	0.06	0.003	76	.	3600	-0.001	19	M	3.4	710	-0.1	0.17
VTBE006R	50-42.8454-72.9916-4-51-000	6.7	132	0.12	0.011	88	7.8	14800	-0.001	.	M	1.3	5940	-0.1	0.08
VTBE007R	50-42.8269-73.0020-4-51-000	6.3	19	0.06	0.012	134	14.6	4800	-0.001	31	M	7.2	870	0.2	0.63
VTBE008R	50-42.7922-73.0307-4-51-000	6.8	39	0.20	-0.002	58	31.5	8000	-0.001	.	M	8.4	2500	-0.1	-0.04
VTBE009R	50-42.7623-73.0542-4-51-000	7.2	50	0.50	0.015	27	16.5	4200	-0.001	22	M	.	760	-0.1	0.30
VTBE010R	50-42.7623-73.0834-4-51-000	6.9	22	0.08	-0.002	108	17.2	4300	-0.001	.	M	.	1370	-0.1	-0.08
VTBE011R	50-42.7760-73.0865-4-51-000	6.4	20	0.04	-0.002	120	20.5	5500	0.041	.	M	8.8	1360	-0.1	-0.09
VTBE012R	50-42.7563-73.1322-4-51-000	6.5	20	0.08	-0.002	98	24.2	4500	-0.001	.	M	6.1	640	-0.1	-0.09
VTBE013R	50-42.7824-73.1503-4-51-000	6.2	20	0.04	-0.002	157	23.0	5600	-0.001	.	M	8.6	1320	-0.1	-0.09
VTBE014R	50-42.8277-73.1304-4-51-000	6.2	21	0.08	0.017	36	31.0	4200	-0.001	36	M	6.0	590	-0.1	0.81
VTBE015R	50-42.8037-73.1376-4-51-000	5.9	20	0.06	-0.002	124	11.8	4600	-0.001	.	M	5.7	1340	-0.1	-0.09
VTBE016R	50-42.7472-73.1883-4-51-000	6.9	37	0.34	0.021	60	36.4	4600	-0.001	33	M	.	630	0.2	0.57
VTBE017R	50-42.7527-73.2229-4-51-000	7.8	190	0.60	0.196	37	.	12800	-0.001	15	M	34.6	7180	-0.1	1.03
VTBE018R	50-42.7646-73.2498-4-51-000	7.9	101	1.30	0.082	26	.	5700	-0.001	23	M	.	1190	-0.1	0.81
VTBE019R	50-42.7881-73.2542-4-51-000	8.2	259	3.60	0.270	29	28.0	6000	-0.001	.	M	.	1300	-0.1	1.04
VTBE020R	50-42.8184-73.2636-4-51-000	8.5	220	0.02	0.397	28	22.9	4600	-0.001	11	M	.	1210	-0.1	1.80
VTBE021R	50-42.8396-73.2583-4-51-000	8.3	168	2.60	0.213	43	25.7	5700	-0.001	.	M	.	920	-0.1	1.27
VTBE022R	50-42.7773-73.2271-4-51-000	8.4	241	5.00	0.343	34	17.7	6400	-0.001	19	M	.	1240	-0.1	1.42
VTBE023R	50-42.7997-73.1837-4-51-000	8.2	110	1.90	0.118	63	28.4	5600	-0.001	.	M	.	760	-0.1	1.07
VTBE024R	50-42.8188-73.1794-4-51-000	8.0	202	3.20	0.093	32	.	8800	-0.001	22	M	.	2500	-0.1	0.46
VTBE025R	50-42.8260-73.2071-4-51-000	8.5	365	6.00	0.358	M	.	13100	-0.001	.	M	55.4	3370	-0.1	0.98

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY SHEET

24

SRL I.D. *****	DOE I.D.		PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
VTBE026R	50-42.1660-	73.2130-4-51-000	8.1	252	0.01	0.268	33	.	6500	-0.031	19	M	.	1290	-0.1	1.06
VTBE027R	50-42.8356-	73.2583-4-51-000	8.0	39	4.80	0.274	16	44.8	18800	-0.001	.	M	.	3840	-0.1	7.03
VTBE028R	50-42.9123-	73.2644-4-51-000	8.3	29	4.60	0.644	50	.	5200	-0.001	.	M	42.8	3570	-0.1	22.21
VTBE029R	50-42.9196-	73.1862-4-51-000	8.1	78	1.10	0.045	35	.	5200	-0.001	21	M	.	890	-0.1	0.58
VTBE030R	50-42.8580-	73.1792-4-51-000	8.2	148	2.40	0.104	44	13.2	7300	-0.001	10	M	.	1850	-0.1	0.70
VTBE031R	50-42.8788-	73.1615-4-51-000	7.7	111	1.20	0.021	46	.	7200	-0.001	155	M	29.1	4800	-0.1	0.19
VTBE032R	50-42.9079-	73.1221-4-51-000	6.0	13	0.06	0.006	121	35.6	5000	-0.001	50	M	10.1	800	-0.1	0.46
VTBE033P	50-42.8896-	73.1231-4-51-000	7.1	50	0.30	-0.002	63	.	9400	-0.001	.	M	6.1	4330	-0.1	-0.03
VTBE034R	50-42.8741-	73.0880-4-51-000	7.2	79	0.34	0.028	46	.	15500	-0.001	.	M	14.6	5150	-0.1	0.35
VTBE035R	50-42.8910-	73.0238-4-51-000	6.1	50	0.10	0.006	122	.	7900	-0.001	.	M	9.7	4510	-0.1	0.12
VTBE036R	50-42.8881-	73.0098-4-51-000	6.2	19	0.08	-0.002	120	22.8	4500	-0.001	37	M	9.3	950	-0.1	-0.10
VTBE037R	50-42.9393-	73.0881-4-51-000	5.6	15	0.04	-0.002	138	19.4	5300	-0.001	.	M	11.3	2170	-0.1	-0.12
VTBE038R	50-42.8816-	72.9497-4-51-000	6.9	26	0.10	0.006	63	29.2	6600	-0.001	23	M	4.5	1490	-0.1	0.23
VTBE039R	50-42.9084-	72.9460-4-51-000	5.9	18	0.08	-0.002	72	10.4	4900	-0.001	.	M	3.8	2490	-0.1	-0.10
VTBE040R	50-42.9179-	72.9712-4-51-000	6.4	43	0.12	-0.002	42	7.4	7100	-0.001	.	M	5.0	2370	-0.1	-0.04
VTBE052R	50-42.9866-	73.1668-4-51-000	8.3	270	5.40	0.137	27	.	7100	-0.001	.	M	.	1200	-0.1	0.51
VTBE053R	50-42.9635-	73.1603-4-51-000	8.0	130	2.40	0.093	41	22.4	4000	-0.001	40	M	.	500	-0.1	0.72
VTBE054R	50-42.9596-	73.1983-4-51-000	8.4	335	5.20	0.203	43	.	9600	-0.001	.	M	.	1900	-0.1	0.61
VTBE055R	50-42.9452-	73.2228-4-51-000	8.2	119	2.60	0.266	65	.	4700	-0.001	13	M	.	1410	-0.1	2.24
VTBE056R	50-42.9476-	73.2505-4-51-000	7.8	252	3.80	0.396	48	75.3	9000	-0.001	.	M	.	1680	-0.1	1.57
VTBE059R	50-42.9622-	73.2374-4-51-000	7.4	317	4.40	0.534	21	.	8700	-0.001	.	M	93.9	2090	-0.1	1.68
VTBE060R	50-42.9720-	73.2101-4-51-000	7.7	129	1.60	0.116	42	.	4600	-0.001	.	M	26.5	1220	-0.1	0.90
VTWI001R	50-42.8701-	72.6243-4-51-000	8.3	59	0.56	0.005	36	30.0	7100	-0.001	34	M	.	2890	-0.1	0.08
VTWI002R	50-42.8710-	72.6437-4-51-000	8.4	65	0.40	-0.002	63	36.3	11300	-0.001	.	M	.	6750	-0.1	-0.02
VTWI003R	50-42.8508-	72.6387-4-51-000	8.3	122	1.00	0.058	33	.	11900	-0.001	14	M	17.9	4650	0.2	0.48
VTWI004R	50-42.8522-	72.6028-4-51-000	8.2	130	1.08	0.118	57	.	15700	-0.001	.	M	21.9	6310	-0.1	0.91
VTWI005R	50-42.8337-	72.6501-4-51-000	8.3	92	0.92	0.046	76	.	8100	-0.001	18	M	16.5	2800	0.4	0.50
VTWI006R	50-42.8065-	72.6656-4-51-000	8.6	55	0.60	0.011	94	.	5700	-0.001	.	M	17.5	3710	-0.1	0.20
VTWI007R	50-42.7790-	72.6727-4-51-000	8.6	48	0.32	0.015	53	.	6500	-0.001	12	M	8.3	2680	-0.1	0.31
VTWI008R	50-42.7615-	72.6612-4-51-000	8.5	50	0.56	-0.002	62	22.5	6700	-0.001	.	M	.	3370	0.2	-0.03
VTWI009R	50-42.7704-	72.6342-4-51-000	8.4	90	0.72	0.035	68	36.6	5300	-0.001	.	M	12.9	2610	-0.1	0.39
VTWI010R	50-42.8098-	72.6112-4-51-000	8.4	140	1.40	0.096	62	2304.0	8100	-0.001	.	M	.	4240	-0.1	0.69
VTWI011R	50-42.7850-	72.5992-4-51-000	8.8	191	1.20	0.131	50	53.8	9800	-0.001	.	M	.	4030	-0.1	0.69
VTWI012R	50-42.8169-	72.5749-4-51-000	8.7	135	1.30	0.073	111	1312.0	7400	-0.001	.	M	.	4760	-0.1	0.54
VTWI013R	50-42.7509-	72.5703-4-51-000	8.6	52	0.40	0.016	38	43.5	6000	-0.001	23	M	.	2510	-0.1	0.31
VTWI015R	50-42.9358-	72.5620-4-51-000	8.2	85	1.04	0.039	63	31.0	5500	-0.001	27	M	.	3820	-0.1	0.46
VTWI016R	50-42.9157-	72.5531-4-51-000	8.3	167	1.90	0.189	69	25.1	9100	-0.001	10	M	.	3550	0.3	1.13
VTWI017R	50-42.8852-	72.5644-4-51-000	8.6	210	2.00	0.205	83	.	6500	-0.001	.	M	16.6	4120	-0.1	0.98
VTWI018R	50-42.7592-	72.5173-4-51-000	8.7	71	0.40	0.004	69	.	12300	-0.001	15	M	9.2	4420	-0.1	0.06
VTWI019R	50-42.7353-	72.4684-4-51-000	8.1	85	0.48	-0.002	133	.	7500	-0.001	.	M	39.1	6360	-0.1	-0.01
VTWI041R	50-42.9845-	72.5128-4-51-000	8.1	90	0.28	-0.002	70	22.0	18500	-0.001	.	M	.	8240	-0.1	-0.01
VTWI042R	50-42.9857-	72.4644-4-51-000	8.2	107	0.92	0.045	35	.	9000	-0.001	.	M	.	4440	-0.1	0.42
VTWI050R	50-42.9847-	72.5849-4-51-000	8.7	90	1.20	0.073	34	32.7	8000	-0.001	.	M	.	3190	-0.1	0.81
VTWI051R	50-42.9891-	72.6537-4-51-000	8.6	45	0.40	-0.002	121	.	11900	-0.001	.	M	24.1	5920	-0.1	-0.03
VTWI061R	50-42.9353-	72.6104-4-51-000	8.0	130	0.92	0.038	83	.	15400	-0.001	.	M	7.9	5880	-0.1	0.29
VTWI062R	50-42.9154-	72.6146-4-51-000	8.4	90	0.80	0.048	139	.	5300	-0.001	.	M	.	1850	-0.1	0.53
VTWI063R	50-42.9188-	72.6756-4-51-000	8.1	60	0.64	0.003	55	.	5300	-0.001	.	M	3.8	2270	-0.1	0.05
VTWI064R	50-42.8779-	72.6926-4-51-000	8.3	88	0.40	-0.002	75	1059.4	23500	-0.001	.	M	18.7	8330	-0.1	-0.01
VTWI065R	50-42.8826-	72.7444-4-51-000	8.3	70	0.40	-0.002	138	.	14400	-0.001	.	M	.	4610	-0.1	-0.02
VTWI066R	50-42.9028-	72.7322-4-51-000	8.4	32	0.40	-0.002	86	.	8700	-0.001	.	M	18.7	3720	-0.1	-0.05
VTWI067R	50-42.9105-	72.7137-4-51-000	8.2	45	0.48	-0.002	26	28.4	6900	-0.001	14	M	11.7	2460	-0.1	-0.03
VTWI068R	50-42.9391-	72.7267-4-51-000	8.1	33	0.36	-0.002	66	.	7100	-0.001	.	M	.	3230	-0.1	-0.05
VTWI069R	50-42.9443-	72.7448-4-51-000	8.2	80	0.80	0.018	26	.	6500	-0.001	.	M	.	2120	-0.1	0.23

C-35

TABLE C-1 TABULATION OF KEY FIELD MEASUREMENTS AND ANALYTICAL DATA -SURFACE WATER--

ALBANY

SHEET

25

SRL I.D. *****	DOE I.D.		PH	COND. UM/CM	AKMXD MEQ/L	U PPB	AL PPB	BR PPB	CL PPB	DY PPB	F PPB	MG PPB	MN PPB	NA PPB	V PPB	U/COND X 1000
VTW1070R	50-42.9799-	72.7491-4-51-000	8.3	110	1.10	-0.002	51	.	8900	-0.001	.	M	34.0	4160	-0.1	-0.01
VTW1071R	50-42.9476-	72.6747-4-51-000	8.6	60	0.60	-0.007	34	.	6600	-0.001	.	M	.	2300	-0.1	0.12
VTW1072R	50-42.9588-	72.6989-4-51-000	8.2	30	0.36	-0.002	79	.	9100	0.839	.	M	1.3	4100	-0.1	-0.05
VTW1075R	50-42.9865-	72.7786-4-51-000	7.9	39	0.52	0.007	90	60.4	9500	-0.001	.	M	33.6	5700	-0.1	0.18
VTW1079R	50-42.9650-	72.8893-4-51-000	7.5	40	0.44	0.023	239	31.8	6500	-0.001	15	M	27.3	3260	-0.1	0.58
VTW1080R	50-42.9394-	72.8547-4-51-000	7.4	90	0.44	-0.002	50	994.6	13800	0.058	.	M	14.6	7680	-0.1	-0.01
VTW1081R	50-42.9643-	72.8390-4-51-000	M	M	M	-0.002	1	0.8	M	-0.001	.	M	0.3	200	-0.1	.
VTW1082R	50-42.9267-	72.8334-4-51-000	7.3	122	0.36	0.006	78	.	24700	-0.001	.	M	23.2	8550	-0.1	0.05
VTW1083R	50-42.9599-	72.7918-4-51-000	7.5	108	0.32	0.004	562	.	9900	-0.001	.	M	18.8	4430	0.9	0.04
VTW1085R	50-42.7575-	72.7415-4-51-000	7.2	40	0.40	0.020	571	16.6	5100	-0.001	.	M	2.1	3810	0.4	0.50
VTW1086R	50-42.7667-	72.6965-4-51-000	7.9	49	0.56	0.002	24	.	4600	-0.001	20	M	6.2	2830	-0.1	0.04
VTW1087R	50-42.7928-	72.7119-4-51-000	8.0	82	0.80	-0.002	66	2733.3	11200	-0.001	.	M	5.6	6080	-0.1	-0.01
VTW1088R	50-42.8051-	72.6983-4-51-000	8.1	45	0.36	-0.002	41	.	6200	-0.001	28	M	4.5	3310	-0.1	-0.03
VTW1089R	50-42.8164-	72.7393-4-51-000	7.9	30	0.36	-0.002	116	1475.0	6300	-0.001	.	M	.	3910	-0.1	0.07
VTW1090R	50-42.8385-	72.7258-4-51-000	7.7	40	0.40	-0.002	81	40.2	5800	-0.001	18	M	11.7	3410	-0.1	-0.04
VTW1091R	50-42.8546-	72.8382-4-51-000	7.7	90	0.28	8.168	73	5.0	21200	-0.001	.	M	1.6	11560	-0.1	90.76
VTW1092R	50-42.8907-	72.8218-4-51-000	7.7	60	0.32	-0.002	91	34.1	9100	-0.001	.	M	6.8	4050	-0.1	-0.02
VTW1093R	50-42.8969-	72.8566-4-51-000	7.8	55	0.36	0.013	100	.	8700	-0.001	.	M	7.5	5500	-0.1	0.24
VTW1094R	50-42.9153-	72.8839-4-51-000	8.1	40	0.48	0.012	130	.	8200	-0.001	21	M	10.4	4620	-0.1	0.30
VTW1095R	50-42.8849-	72.8962-4-51-000	7.6	45	0.40	-0.002	48	36.9	7500	-0.001	.	M	10.9	4920	-0.1	-0.03
VTW1097R	50-42.7683-	72.9242-4-51-000	7.7	120	0.60	0.007	61	.	15400	-0.001	.	M	.	6640	-0.1	0.06
VTW1098R	50-42.7905-	72.8726-4-51-000	7.8	32	0.28	-0.002	707	.	10700	0.073	.	M	17.6	7860	0.4	-0.05
VTW1099R	50-42.7525-	72.8499-4-51-000	7.7	30	0.32	0.009	143	29.7	5600	-0.001	.	M	9.8	3200	-0.1	0.30
VTW1101R	50-42.7836-	72.8098-4-51-000	7.7	83	0.32	-0.002	51	39.2	11200	-0.001	.	M	5.6	5190	-0.1	-0.01
VTW1102R	50-42.8082-	72.8199-4-51-000	7.7	40	0.40	-0.002	93	.	6100	-0.001	.	M	4.8	3690	-0.1	-0.04
VTW1104R	50-42.8158-	72.8086-4-51-000	7.6	30	0.24	0.002	62	.	4500	-0.001	9	M	4.2	3030	-0.1	0.07
VTW1105R	50-42.7872-	72.7721-4-51-000	7.7	40	0.32	-0.002	46	27.5	6300	-0.001	.	M	4.3	3910	-0.1	-0.04
VTW1106R	50-42.7602-	72.7655-4-51-000	7.8	68	0.40	-0.002	56	16.2	8400	0.192	12	M	5.4	4170	-0.1	-0.02
VTW1120R	50-42.9406-	72.9919-4-51-000	6.3	22	0.06	-0.002	139	.	7200	-0.001	.	M	5.8	4760	-0.1	-0.08
VTW1121R	50-42.9733-	72.9766-4-51-000	4.6	21	0.02	0.003	188	22.0	5000	-0.001	.	M	27.5	2930	0.7	0.14
VTW1122R	50-42.9657-	73.0043-4-51-000	5.2	15	0.04	-0.002	195	37.7	4900	-0.001	23	M	32.6	3030	0.3	-0.12

APPENDIX D: User's Guide to SRL Data Reports

ABSTRACT

This document provides a detailed description of Data Reports prepared by Savannah River Laboratory (SRL) personnel for the National Uranium Resource Evaluation (NURE) program. The Guide includes descriptions of (1) sample collection and field measurements; (2) format, abbreviations, and codes used in data tables; (3) graphical presentation and maps; and (4) quality assurance programs for sample collection and analysis.

CONTENTS

Introduction D-3

Sample Collection and Field Measurements D-3

Data Presentation D-7

I. Columnar Entries for Ground Water Data D-9

II. Columnar Entries for Supplementary Ground Water Data D-13

III. Columnar Entries for Sediment Data D-17

IV. Columnar Entries for Supplementary Sediment Data D-18

V. Columnar Entries for Stream Water Data D-21

VI. Graphical Data and Maps D-22

Quality Assurance for Sample Collection D-22

References D-25

LIST OF FIGURES

- D-1 SRL Field Data Form for Ground Water Sites D-4
- D-2 SRL Field Data Form for Stream Water and Sediment Sites D-5
- D-3 SRL Field Data Form for Stream Sediment Sites D-6
- D-4 Print Modes for Ground Water Sampling Site Identifiers D-8
- D-5 Print Modes for Surface Sampling Site Identification D-8

LIST OF TABLES

- D-1 State Codes Used in DOE Identification Number D-10
- D-2 Type Codes Used in DOE Identification Number D-11
- D-3 Statistical Distribution Symbols for Areal Maps D-23

INTRODUCTION

This document provides a detailed description of Data Reports prepared by Savannah River Laboratory (SRL) personnel for the National Uranium Resource Evaluation (NURE) Program. The format described herein is that established for Data Reports in mid-1978. The descriptions of tables and figures are general enough to be applied to future Data Reports. However, some minor changes in format may be made as the program progresses.

SRL participation in the NURE Program is summarized in NURE-SRL progress reports (SRL-138).

SAMPLE COLLECTION AND FIELD MEASUREMENTS

Sampling personnel were trained by SRL staff members according to procedures in published SRL documents. In areas where both stream water and stream sediment were collected, the **Field Manual for Stream Water and Sediment Reconnaissance** (Ferguson and others, 1977) was used. Where only stream sediment was collected from surface sites, the **Field Manual for Stream Sediment Reconnaissance** (Ferguson and others, 1976a) was used. The **Field Manual for Ground Water Reconnaissance** (Ferguson and others, 1976b) was used in all areas.

A minimum of five sediment sub-samples was composited from each stream site. Approximately 400 g of sediment passing a 420-micrometer screen (U.S. Std. 40 mesh) were collected at each site. Dissolved ions in individual water samples were concentrated on portions of ion exchange resin [GJBX-77(77)], which were analyzed. Special procedures not included in the original field manuals were employed in certain areas. For example, ground water samples from Coastal Plain areas were collected for analysis of helium and neon.

Figures D-1 and D-2 illustrate the field forms completed at each ground water and stream sample collection site, respectively. Figure D-3 illustrates an alternate form that is used for surface sites from which only sediment is collected. Entries are self-explanatory. References 2 through 4 describe in detail the equipment and techniques (including criteria for site selection) for collecting samples and for making field measurements.

Nominal ground water and stream sampling density in rural areas varies from 13 to 25 square kilometers (5 to 10 sq mi) per site, depending upon the geology of the area. In areas of crystalline rock, surface sampling is generally denser than ground water sampling. In areas of sedimentary rock, the converse is true. Areas thought to have relatively high uranium potential

SRL GROUND WATER SITE FIELD DATA FORM

SITE CODE								DATE				TEAM NO.	GENERAL SITE DATA																										
State		Map Code		Site Number				Mo.	Day	Yr.	Hr.		Well or Spring	Depth of Well (feet)	Conf. of Depth	Age of Well (Yr)	Conf. of Age	Type of Well	Main Use	Freq. Use	Odor	Pipe Compos.	Where Samp. Taken	Classification	ml of Water Ion-exchanged														
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
Have a Good Day ☺																																							
41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80
pH		SPECIFIC CONDUCTANCE µmhos/cm		WATER TEMP (°C)		Drops H ₂ SO ₄		ml Water		INSTRUMENT I.D. - pH		pH PROBE I.D.		COND. INSTR. I.D.		COND. PROBE I.D.		SPARE (DO NOT USE)												Comments		Inform. Request		Do Not Use		CARD CODE			

State	Map Code	Site Number	ADDRESS (use / to separate lines)																																					
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	
41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	

IN THE CASE OF EACH CIRCLED ENTRY SPACE, ENTER MOST APPROPRIATE DESIGNATORS LISTED BELOW

20	W - Well
S - SPRING
Q - Others (use comments)	31	1 Human drinking
2 Animal drinking
3 Irrigation
4 Others (use comments)	33	1 None
2 Weak H ₂ S
3 Strong H ₂ S
4 Others (use comments)	35	1 Immediately after storage tank
2 From pipe before storage tank
3 Direct from pump
4 Direct from well or spring
5 From Municipal system
6 Unknown
7 Others (use comments)
25	1 Certain
and 2 Probable
29 3 Possible
4 Educated Guess
5 Unknown	32	1 Continuous (> once per day)
2 Once per day
3 Once per week
4 Once per month
5 Less than once per month
6 Not in use	34	1 Galvanized
2 Copper
3 Plastic
4 Steel
5 Lead
6 Unknown
7 Others (use comments)	36	1 Private (<2 families)
2 Semi-Private (used by 3 to 10 families)
3 Public (used by >10 families)
4 Industrial
5 Commercial (motel, etc.)
6 Recreational
7 Agricultural
Q Unknown
O Others (use comments)
30	1 Drilled
2 Dug
3 Driven
4 Unknown						
76	Enter "C" when comments are made						
76	Comments (Explain all "other" designators used above, plus describe all unusual or significant conditions such as proximity of contaminants, general rock type, formation when known, problems with instruments, etc. Use back of form for additional space)						

77 Enter "X" when analysis information is requested

I certify that the above sample was taken by SRL procedures at the indicated site and the information listed is correct at time of sampling.

Sampler(s) Signature(s)

I have checked this form and associated samples for accuracy, correct format, and legibility.

Field Supervisor (initials)

Standard Letters and Numbers

ABCDEFGHIJKLMNOPQRSTUVWXYZ

0123456789

FIGURE D-1. SRL Field Data Form for Ground Water Sites

IN THE CASE OF EACH CIRCLED ENTRY SPACE, ENTER MOST APPROPRIATE DESIGNATORS LISTED BELOW

- 09 Comments (Explain all "other" designators used above, plus describe all unusual or significant conditions such as proximity of contaminants, general rock type, formation when known, problems with instruments, etc. Use back of form for additional space).

Sampler(s) Signature(s)

Field Supervisor (initials) _____

0 1 2 3 4 5 6 7 8 9

D-5

SRL STREAM SITE FIELD DATA FORM

SITE CODE								DATE								TEAM NO.		GENERAL SITE DATA												ACTIVITIES/CONTAMINANTS (List up to Four)				COMMENTS		ROAD-STREAM SITE							
State		Map Code		Site Number				Mo.	Day	Yr.	Hr.																																
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40				
Have a Good Day ☺																																											
41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80				
pH		SPECIFIC CONDUCTANCE		WATER TEMP (°C)		ALKALINITY		Drops H ₂ SO ₄		ml Water		NO. OF SAMPLE COMPOSITES		SAMPLER TYPE		INSTRUMENT I.D. - pH		pH PROBE I.D.		COND. INSTR. I.D.		COND. PROBE I.D.		SPARE (DO NOT USE)																		CARD CODE	

IN THE CASE OF EACH CIRCLED ENTRY SPACE, ENTER MOST APPROPRIATE DESIGNATORS LISTED BELOW

20	1 Boulders
2 Cobble
3 Pebble
4 Sand
5 Silt
6 Clay
7 Organic Muck
8 Others (use comments)	22 & 23	1 < 1/2 ft
2 1/2 - 1 ft
3 1 - 2 ft
4 2 - 4 ft
5 4 - 8 ft
6 8 - 16 ft
7 16 - 32 ft
8 > 32 ft
9 Dry	26	1 Clear
2 Brown-Clear
3 Cloudy
4 Muddy
5 Algal
6 Others (use comments)	30	1 Flat
2 Low, 0-50'
3 Gentle, 50-200'
4 Moderate, 200-400'
5 High, >1000'
21	1 White/Buf
2 Yellow
3 Orange
4 Pink/Red
5 Green
6 Brown
7 Gray
8 Black
9 Others (use comments)	24	1 Stagnant
2 Slow
3 Moderate
4 Fast
5 Torrent
6 Dry	27	1 Depositing
2 Eroding
3 Unknown	31	1 Sunny/Clear
2 Overcast
3 Light Rain
4 Heavy Rain
5 Snowy
6 Other (use comments)
39	Enter "C" when comments are made	25	1 Dry
2 Low
3 Normal
4 High
5 Flood	28	1 Conifer
2 Deciduous
3 Brush
4 Grass/Pasture
5 Marsh/Swamp
6 Peat Bog
7 Other (use comments)	32 35	1 Chemical
2 Smelting
3 Mining
4 Sewage
5 Dumps
6 Farming
7 Power Generation
8 Urban
9 Other Industrial
40	Enter "R" when site is road stream site
"O" when site is off-road			29	1 Barron
2 Sparse
3 Moderate
4 Dense
5 Very Dense		A Recreational
B Residential
57	B - Bag S - Scoop						
40	Road-Stream Site Description
(Type, material, size, etc.)						

39 Comments (Explain all "other" designators used above, plus describe all unusual or significant conditions such as proximity to contaminants, general rock type, formation when known, problems with instruments, etc. Use back of form for additional space).

I certify that the above sample was taken by SRL procedures at the indicated site and the information listed is correct at time of sampling.

Sampler(s) Signature(s)

I have checked this form and associated samples for accuracy, correct format, and legibility.

Field Supervisor (initials)

Standard Letters and Numbers

ABCDEFGHIJKLMNOPQRSTUVWXYZ

0123456789

FIGURE D-3. SRL Field Data Form for Stream Sediment Sites

are sampled more densely than those thought to have lower potential. A discrepancy may be noted concerning the number of water quality measurements (pH, conductivity, alkalinity) as reported with stream sediment and stream water data. The inconsistency arises because some streams contain sufficient quantities of water to perform water quality measurements (as reported with sediment data) but insufficient quantities to collect a stream water sample.

Sampling site locations were marked precisely on compilation maps. The maps were returned to SRL for determination of geographic coordinates. An electronic digitizer (SRP-138) was used to measure, verify, and enter latitude and longitude data for each site into the SRL-NURE data base. These data were recorded to four decimal places, but are considered reliable to only three decimal places.

Plate 2 is a 1:250,000 scale overlay of the 1° x 2° quadrangle showing ground water sampling sites and SRL identification (ID) numbers. On Plate 2, well and spring sites are distinguished by the use of a "plus" (+) for wells and a circle (o) for springs. Print modes for Plate 2 are shown on Figure D-4. Plate 3 is a 1:250,000 scale overlay of the quadrangle showing surface sampling sites and SRL ID numbers. Print modes for Plate 3 are shown on Figure D-5.

DATA PRESENTATION

In each SRL Data Report, the reconnaissance data are presented in appendices. Coordinates and the most important analytical data and field measurements are listed in full-size tables. Statistical summaries and areal distributions of these measurements are also given in full-sized figures. Other field and analytical data are given in tables on microfiche only. Statistical summaries and areal distributions of these elements are also given in figures on microfiche only.

Detailed cumulative frequency plots are included in the margins of the 1:250,000 scale maps. Individual points are shown for the cumulative frequency plots and values are summed from highest to lowest for plots on the maps. These cumulative frequency plots also display the relationship between cumulative frequency and standard deviation and cover the complete range of samples.

The following section presents a brief explanation of the columnar entries for tables and descriptions of histograms, cumulative frequency, and areal symbol plots in the Appendices and on microfiche.

Print Modes for WELLS	Print Modes for SPRINGS
NCAS + 558 + NCAS 558 NCAS 558 + NCAS 558 + + NCAS 558 NCAS + 558	NCAS O 558 O NCAS 558 NCAS 558 O NCAS 558 O O NCAS 558 NCAS O 558
+(Site Location)	O(Site Location)

FIGURE D-4. Print Modes for Ground Water Sampling Site Identifiers

Print Modes for SURFACE SITES
NCAS + 058 + NCAS 058 NCAS 058 + NCAS 058 + + NCAS 058 NCAS + 058
+(Site Location)

FIGURE D-5. Print Modes for Surface Sampling Site Identification

I. Columnar Entries for Ground Water Data

The data for ground water will normally be presented in Table A-1 of Appendix A.

SRL Identification Number

Each SRL identification (ID) site code consists of seven characters. The first two characters give the state from which the sample was collected. Map name abbreviations are entered as Characters 3 and 4; normally these represent counties. State and county codes used are listed in Table 1 of each report. Sites are numbered sequentially within each map unit (Characters 5, 6, and 7). Numbers begin with 501 in each map unit for ground water sites and are generally consecutive. Columns 8 and 9 represent the sample analyzed. R means that ion exchange resin was analyzed for all elements reported except helium.

DOE Identification Number

Each sample is assigned a DOE ID number. The number consists of 28 characters as follows:

- 1-2 State (See Table D-1)
- 4-10 Latitude of site
- 12-19 Longitude of site
- 21 Laboratory code (4 = SRL)
- 23-24 Sample type (See Table D-2)
- 26-28 Replication code. Generally only original samples (-000) are reported in the Data Releases.

pH

Normally, pH will be in the range of 4.0 to 9.5. Values far outside this range may suggest instrument malfunction or pollution. Missing data are indicated by "M".

COND

Conductivity, measured in micromhos/cm.

TABLE D-1

State Codes Used in DOE Identification Number

<u>State</u>	<u>Code</u>	<u>State</u>	<u>Code</u>
Alabama	01	Nevada	32
Arizona	04	New Hampshire	33
Arkansas	05	New Jersey	34
California	06	New York	36
Connecticut	09	North Carolina	37
Delaware	10	Ohio	39
District of Columbia	11	Oklahoma	40
Florida	12	Oregon	41
Georgia	13	Pennsylvania	42
Idaho	16	Rhode Island	44
Illinois	17	South Carolina	45
Indiana	18	Tennessee	47
Kentucky	21	Texas	48
Louisiana	22	Utah	49
Maine	23	Vermont	50
Maryland	24	Virginia	51
Massachusetts	25	Washington	53
Michigan	26	West Virginia	54
Mississippi	28		
Missouri	29		

TABLE D-2

Type Codes Used in DOE Sample Identification Number^a

<u>Digit</u>	<u>Sample Type</u>
50	Stream sediment, sieved <149 μm and dried $\leq 110^\circ\text{C}$
51	Stream water, filtered through $\leq 0.8 \mu\text{m}$ filter at the site
52	Well water, filtered through $\leq 0.8 \mu\text{m}$ filter at the site
53	Spring water, filtered through $\leq 0.8 \mu\text{m}$ filter at the site
54	Lake water, filtered through $\leq 0.8 \mu\text{m}$ filter at the site
55	Lake sediment
56	Glacial till
57	Peat
58	Spare number ^b
59	Spare number ^b

a. The 28-character DOE-GJ identification number for NURE samples contains two digits to denote sample type. The digits 50 through 59 have been set aside for SRL use.

b. To be noted in individual reports as needed.

AKMXD

Alkalinity as milliequivalents of sulfuric acid required per liter of sample (meq/L) to titrate to a pH of approximately 4.5 (bromcresol-green/methyl-red end-point).

DPTH

Depth of the well in feet, if known. These data are generally provided by the householder. An estimate of the confidence in this number is given in the microfiche Table A-2. "U" indicates that the well depth is not known. Springs are coded as having a depth of 0 feet.

U

Uranium concentration is determined by delayed neutron counting of uranium from ground water concentrated on ion exchange resin. U is reported in parts per billion (ppb).

Values have been rounded to appropriate significant figures. Values for uranium are reported for all samples analyzed; however, analyses <0.040 ppb exhibit a high coefficient of variation. Missing data are indicated by "M". Where all analytical data for a sample are missing, samples will generally be analyzed and reported in a supplementary report.

U/COND

Uranium concentration in ppb multiplied by 1000 and divided by conductivity is listed in this column. This value gives an approximation of the ratio of uranium to total dissolved solids.

Helium

Helium (^4He) is determined for selected quadrangles using a specially developed mass spectrometric procedure (SRP-138b). When available, helium values are reported in standard cubic centimeters of helium per 1000 liters of air corrected to a constant ^{22}Ne content ($\text{cm}^3\text{He}/1000\text{L}$, i.e., ppm by volume). This method introduces a nearly constant 5.2 ppm helium background from air; thus, all samples analyzed are above detection limit.

Other Key Elemental Analyses

Other elements analyzed were determined by neutron activation analysis (unless otherwise noted) and are listed alphabetically.

Concentrations are reported in ppb. Values below detection limit are indicated by a minus (-). For example, -3 means that the sample contains less than 3 ppb of that element. If background is so high that an accurate estimate of the minimum detection limit is not available, a period (.) is used to indicate not only that the element was not detected, but that the detection limit is unusually high in that sample. Missing data are indicated by "M". Where all analytical data for a sample are missing, samples will generally be analyzed and reported in a supplementary report.

II. Columnar Entries for Supplementary Ground Water Data

These data are presented on microfiche only.

SRL Identification Number

Same as in Table A-1.

Supplementary Elemental Analyses

Same format as Table A-1.

SAMPDATE

The date of sampling (month/day/year). For example, 7/15/77. is July 15, 1977.

TEAM

This code identifies the personnel who performed the sampling and is used by SRL for quality assurance monitoring.

TEMP

The water temperature at the time of sampling is recorded in this column. The water temperature is recorded in degrees Celsius (°C) to the nearest whole degree.

WELSPR

A "W" in this column denotes a ground water sample taken from a well; and "S" denotes a sample taken from a flowing spring.

DEPTHCON

Confidence in the values of well depths is listed in this column. The possible entries are:

- 1 Certain
- 2 Probable
- 3 Possible
- 4 Educated Guess
- 5 Unknown

Any site with "U" listed in DPTH should have "5" listed for DEPTHCON.

AGE: AGECON

The ages of sampled wells are recorded to the nearest whole year. When only minimum ages are known, they are recorded. A "U" means the age of the well is unknown. Wells less than one year old are not sampled. The accuracy of the age determination is also entered. The possible entries are:

- 1 Certain
- 2 Probable
- 3 Possible
- 4 Educated Guess
- 5 Unknown

WELLTYPE

Sampled wells are classified by method of construction. The types listed are:

- 1 Drilled; denotes wells formed by rotary drills or augers.
- 2 Dug; denotes wells dug by manual or mechanical scooping equipment.
- 3 Driven; denotes wells formed by vertical pile drivers.
- 4 Unknown.

WELLUSE

This column describes the primary use of water from the wells.

- 1 Human drinking
- 2 Animal drinking
- 3 Irrigation
- 4 All other purposes

WELLFREQ

This column lists the frequency of use of sampled wells. The entries and their meaning are:

- 1 Continuous (more than once per day)
- 2 Once per day
- 3 Once per week
- 4 Once per month
- 5 Less than once per month
- 6 Not in use

Wells used less frequently than weekly are generally not sampled.

WELLODOR

Hydrogen sulfide odors in well water are noted. The entries in this column and their meanings are:

- 1 No odor
- 2 Weak H₂S odor
- 3 Strong H₂S odor
- 4 Others

PIPECOMP

The major materials used in pipes are listed in this column. The entries used and their meanings are:

- 1 Galvanized
- 2 Copper
- 3 Plastic
- 4 Steel
- 5 Lead
- 6 Unknown
- 7 Others

WELLOC

The positions at which samples are taken are listed in this column. The positions listed are relative positions in plumbing systems. The entries and their meanings are:

- 1 Immediately after storage tank
- 2 From pipe before storage tank
- 3 Direct from pump
- 4 Direct from well or spring
- 5 From municipal system
- 6 Unknown
- 7 Others

WELCLASS

Sampled wells are classified by use. The classes of wells recognized here are:

- 1 Private (less than 3 families)
- 2 Semiprivate (used by 3 to 10 families)
- 3 Public (used by more than 10 families)

- 4 Industrial
- 5 Commercial (motel, etc.)
- 6 Recreational
- 7 Agricultural
- 8 Unknown

III. Columnar Entries for Sediment Data

Sediment data (and accompanying water quality measurements) will normally be presented in Tables B-1 (full-sized tables) and B-2 (microfiche tables).

SRL Identification Number

Each SRL identification (ID) site code consists of seven characters. The first two characters give the state in which the sample was collected. Map name abbreviations are entered as Characters 3 and 4; normally these represent counties. State and county codes used are listed in Table 1 of each report. Sites are numbered sequentially within each map unit (Characters 5, 6, and 7). Numbers begin with 001 in each map unit for stream sites and are generally consecutive. Columns 8 and 9 represent the sample analyzed. In most reports, the S1 fraction [finer than 149 micrometers (U.S. Std. 100 mesh)] was analyzed. S0 and S2 mean that coarser or finer fractions, respectively, were analyzed. Specific fractions will be identified in individual reports as necessary.

DOE Identification Number

Each sample is assigned a 28-Character DOE ID number as described for Table A-1 on page D-9.

pH; COND, UM/CM; AKMXD, MEQ/L

Same format as Table A-1.

Key Elemental Analyses

The first three elements are listed in order of importance; other key elements are listed alphabetically.

Concentrations of each element (in ppm) are determined by neutron activation analysis (unless otherwise noted). Values have been rounded to appropriate significant figures. Note that the elemental (not oxide) concentration is quoted in this table. Values below detection limit are indicated by a minus (-). For example, -3 means that the sample contains less than 3 ppm of that element. If background limit is not available, a period (.) is used to indicate not only that the element was not detected, but that the detection limit is unusually high in that sample. Missing data are indicated by "M". Where all analytical data for a sample are missing, samples will generally be analyzed and reported in a supplementary report.

IV. Columnar Entries for Supplementary Sediment Data

These data are presented on microfiche only.

SRL Identification Number

Same as Table B-1.

Supplementary Elemental Analyses

Same format as Table B-1.

SAMPDATE

The date of sampling, month/day/year. For example, 7/15/77 is July 15, 1977.

TEAM

This code identifies the personnel who performed the sampling and is used by SRL for quality assurance monitoring.

SEDTYPE, etc.

This and following columns contain codes describing the stream characteristics. For example, 1 registered under SEDTYPE indicates that the stream bottom was composed primarily of boulders. Details of these descriptors are given below.

SEDTYPE**SEDCOLOR**

1	Boulder	1	White/Buff
2	Cobble	2	Yellow
3	Pebble	3	Orange
4	Sand	4	Pink/Red
5	Silt	5	Green
6	Clay	6	Brown
7	Organic Muck	7	Gray
8	Other	8	Black
		9	Other

The sediment entries reflect the nature of the loose sediment material at the sampled site.

STMWIDTH AND STMDEPTH

1	<1/2 ft	6	8-16 ft
2	1/2-1 ft	7	16-32 ft
3	1-2 ft	8	>32 ft
4	2-4 ft	9	Dry
5	4-8 ft		

An estimate of the AVERAGE width and depth of the stream over the 100 to 200 feet of stream length where the sample was taken.

STMFLOW**STMLEVEL****STMCOLOR**

1	Stagnant	1	Dry	1	Clear
2	Slow	2	Low	2	Brown Clear
3	Moderate	3	Normal	3	Cloudy
4	Fast	4	High	4	Muddy
5	Torrent	5	Flood	5	Algal
6	Dry			6	Other

The water description provides an indication of the general condition of the water at the time of sampling. STMFLOW indicates the rate of flow using the listed descriptors at the sampled location [i.e., if a stream is sampled in rapids, the 4 (Fast) or 5 (Torrent) may apply; but if the same stream were sampled above or below the rapids, the 2 (Slow) or 3 (Moderate) descriptors might be more accurate]. STMLEVEL describes the water level relative to its apparent normal level. STMCOLOR reflects the amount and type of dissolved or suspended load in the water on the basis of color. If a large amount of algae was suspended in the water, 5 (Algal) is entered. If the water was transparent, but had a definite brown or black color, then 2 (Brown-Clear) designator is entered.

STMCHANL

- 1 Depositing
- 2 Eroding
- 3 Unknown

The column labeled STMCHANL is coded with the appropriate descriptor listed above. A steeply inclined stream bed with fast-moving water can usually be considered as eroding; whereas a nearly-level, slow-moving stream may indicate a depositing channel (i.e., the stream is depositing its load of sand, silt, etc., in the calm water areas). The chosen descriptor applies to the general nature of the stream.

VEGTYPE

VEGDENS

1 Conifer	1 Barren
2 Deciduous	2 Sparse
3 Brush	3 Moderate
4 Grass/Pasture	4 Dense
5 Marsh/Swamp	5 Very Dense
6 Peat Bog	
7 Other	

These descriptions reflect the amount and type of plant growth in the immediate area of the sample location. The density is a subjective observation made in relation to visibility, ease of access, etc. The type of vegetation reflects the dominant plant type at or near the sample location. Conifers are broadly classed as evergreen trees and shrubs such as pine trees, etc. Deciduous plants are broadly classed as trees and shrubs that seasonally lose their leaves such as cottonwoods, maples, oaks, hickory, etc. Brush denotes relatively low-growing plants (which may or may not be deciduous) such as thorny bushes, etc. Grass denotes grasses of all types including natural and/or crops such as alfalfa, wheat, etc.

RELIEF

- 1 Flat
- 2 Low, 0-50'
- 3 Gentle, 50-200'
- 4 Moderate, 200-1000'
- 5 High, >1000'

Relief is an indicator of local surface expression. The area included around a sample location will usually not exceed a few hundred yards in mountainous terrains, but may exceed up to 1/2 mile in relatively flat areas.

WEATHER

- 1 Sunny/Clear
- 2 Overcast
- 3 Light Rain
- 4 Heavy Rain
- 5 Snowy
- 6 Other

The weather entry is a general indicator of the prevalent conditions at the time of sampling.

COMPOSIT

COMPOSIT refers to the number of subsamples taken at each site that are composited to give the sieved sample for that site.

CONTAMN

The activities/contaminants columns indicate those nearby activities which may influence the analytical results. It is a very important entry, chosen from the list of numerical designators shown. The major activity and/or contamination is always listed under CONTAMN4. A second activity, if considered important, is listed under CONTAMN3, etc.

CONTAMN1	1 Chemical	7 Power Generation
CONTAMN1	2 Smelting	8 Urban
CONTAMN3	3 Mining	9 Other Industrial
CONTAMN4	4 Sewage	A Recreational
	5 Dumps	B Residential
	6 Farming	

WATERTEM

The water temperature, taken at the time of sampling, is coded under WATERTEM. The water temperature is recorded in degrees Celsius (°C) to the nearest whole degree.

V. Columnar Entries for Stream Water Data

For areas in which stream water samples were collected for analysis, stream water data will be presented in Tables C-1 (full-sized tables). (Where only sediments are collected, stream water quality measurements are given in Table B-1).

SRL Identification Number

Each SRL identification (ID) site code consists of seven characters, as described for Table B-1. Columns 8 and 9 represent

the sample analyzed. For surface water, R means that ion exchange resin was analyzed.

DOE Identification Number

Same as Table A-1.

pH; COND, UM/CM; AKMXD, MEQ/L

Same format as Table A-1.

U, U/COND, Other Elemental Analyses

Same format as Table A-1.

VI. Graphical Data and Maps

Areal distributions ("symbol plots") of all measurements in Tables A-1, B-1, and C-1 are presented in hard copy. Graphical summaries of elemental data in Tables A-2 and B-2 are on microfiche only. Histograms and cumulative frequency plots are given on microfiche. The symbols for the areal distribution plots are derived from the statistical distribution of the measurements within the quadrangle being reported (Table D-3). Symbols are based upon statistical distribution rather than absolute values to permit convenient comparison of elements with widely differing concentration ranges.

QUALITY ASSURANCE FOR SAMPLE COLLECTION

Three to ten percent of the sampled sites were routinely checked by SRL personnel or by a separate subcontractor to assure that the reported field locations were accurate. Based on these quality assurance checks, the vast majority of sampled sites were judged to be located as accurately as they could be plotted on county road maps. Most sites that were mapped incorrectly were within 300 meters of their correct locations. Errors were generally more frequent for ground water than for surface sites. If more of the sites were judged to be significantly mismapped (based on the QA screening), all sites in the 80th percentile or above were remapped. Details of mapping errors are given in each Data Report in the section on **Factors Affecting the Data**. Thus, the goals of a regional reconnaissance have not been

TABLE D-3

Statistical Distribution Symbols for Areal Maps

TABLE D-3

Statistical Distribution Symbols for Areal Maps

<i>Symbol</i>	<i>Percentile Range</i>	<i>Standard Deviation Above Mean^a</i>
★	>99.5	>2.6
◆	98.6 to 99.5	2.2 to 2.6
●	96.4 to 98.6	1.8 to 2.2
⊙	91.9 to 96.4	1.4 to 1.8
⊙	84.1 to 91.9	1.0 to 1.4
⊙	72.6 to 84.1	0.6 to 1.0
⊙	57.9 to 72.6	0.2 to 0.6
⊙	42.1 to 57.9	-0.2 to 0.2
○	27.4 to 42.1	-0.6 to -0.2
○	15.9 to 27.4	-1.0 to -0.6
○	8.1 to 15.9	-1.4 to -1.0
◐	3.6 to 8.1	-1.8 to -1.4
◑	1.4 to 3.6	-2.2 to -1.8
×	<1.4	<-2.2
+	-	below detection limit

^a. Signs are reversed relative to cumulative frequency plots. In the cumulative frequency plots, values are accumulated from the largest to the smallest value to ensure that the largest value is plotted. "Percentile" assumes accumulation from the smallest to the largest value.

compromised by mapping errors. Details of the quality assurance program are given in NURE-SRL progress reports (SRL-138).

Field measurements were checked for approximately 2% of the sites. Where important variations occurred, the sampling subcontractor was required to repeat measurements for the area in question. Only the corrected values are reported. Questionable data that could not be corrected are discussed in individual reports or omitted, depending upon the severity of the potential error.

REFERENCES FOR APPENDIX D

Ferguson, R. B., Price, V., and Baucom, E. I., 1976a, **Field Manual for Stream Sediment Reconnaissance**: SRL Document DPST-76-358, E. I. du Pont de Nemours & Co., Savannah River Laboratory, Aiken, South Carolina. DOE-GJ Document No. GJBX-26(77).*

Ferguson, R. B., Price, V., and Baucom, E. I., 1976b, **Field Manual for Ground Water Reconnaissance**: SRL Document DPST-76-416, E. I. du Pont de Nemours & Co., Savannah River Laboratory, Aiken, South Carolina. DOE-GJ Document No. GJBX-30(77).*

Ferguson, R. B., Price, V., and Baucom, E. I., 1977, **Field Manual for Stream Water and Sediment Reconnaissance**: SRL Document DPST-77-363, E. I. du Pont de Nemours & Co., Savannah River Laboratory, Aiken, South Carolina. DOE-GJ Document No. GJBX-80(77).*

GJBX-77(77), **Proceedings of Symposium on Hydrogeochemical and Stream Sediment Reconnaissance for Uranium in the United States, Grand Junction, Colorado, March 16 and 17, 1977**: DOE-GJ Document No. GJBX-77(77).*

SRL-138, NURE-SRL progress reports:

1. **Savannah River Laboratory Quarterly Reports; Hydrogeochemical and Stream Sediment Reconnaissance - Eastern United States; National Uranium Resource Evaluation Program**: E. I. du Pont de Nemours & Co., Savannah River Laboratory, Aiken, South Carolina.

<u>No.</u>	<u>Quarter</u>	<u>SRL Document No.</u>	<u>DOE-GJ Document No.*</u>
a	January-March 1975	DPST-75-138-1	GJBX-5(76)
b	April-June 1975	DPST-75-138-2	GJBX-6(76)
c	July-September 1975	DPST-75-138-3	GJBX-7(76)
d	October-December 1975	DPST-75-138-4	GJBX-8(76)
e	January-March 1976	DPST-76-138-1	GJBX-17(76)
f	April-June 1976	DPST-76-138-2	GJBX-27(76)
g	July-September 1976	DPST-76-138-3	GJBX-63(76)
h	October-December 1976	DPST-76-138-4	GJBX-6(77)
i	January-March 1977	DPST-77-138-1	GJBX-35(77)

SRP-138 (Continued)

j	April-June 1977	DPST-77-138-2	GJBX-55(77)
k	July-September 1977	DPST-77-138-3	GJBX-90(77)
l	October-December 1977	DPST-77-138-4	GJBX-37(78)
m	January-March 1978	DPST-78-138-1	GJBX-66(78)

2. Savannah River Laboratory Semiannual Reports; Hydrogeochemical and Stream Sediment Reconnaissance - Eastern United States; National Uranium Resource Evaluation Program:

E. I. du Pont de Nemours & Co., Savannah River Laboratory, Aiken, South Carolina.

<u>No.</u>	<u>Period</u>	<u>SRL Document No.</u>	<u>DOE-GJ Document No.*</u>
a	April-September 1978	DPST-78-138-2	GJBX-13(79)
b	October-March 1979	DPST-79-138-1	GJBX-XX(79)

* DOE-GJ reports are available on microfiche from the Grand Junction Office, DOE, for \$6.00. Prepaid orders should be sent to: Bendix Field Engineering Corporation, Technical Library, P. O. Box 1569, Grand Junction, Colorado 81501. Checks or money orders should be made out to Bendix Field Engineering Corporation, the operating contractor for DOE's Grand Junction Office.

This is a detailed geological map of the Albanian region, showing topographic contours, elevation points, and various geological units labeled with codes like Oc, Cs, and C. The map includes a coordinate grid with latitude and longitude markings.

DISTRIBUTION

Copy No.

1-100 DOE-GJ (for open file)

101 Robert J. Wright, Jr.
Chief Geologist, URE
Federal Bldg., USDOE
12th and Pennsylvania Ave., N.W.
Washington, DC 20461

102 D. L. Everhart, Manager
Department of Energy
P. O. Box 2567
Grand Junction, CO 81501

103 David H. Dahlem, Project Officer
NURE Project Office
Department of Energy
P. O. Box 2567
Grand Junction, CO 81501

104-105 Donald E. Livingston
Manager, Geochemical Department, DADD
Bendix Field Engineering Corp.
P. O. Box 1569
Grand Junction, CO 81501

106-107 Terry W. Offield
Branch of Uranium & Thorium Resources
USGS
MS 964
P. O. Box 25046
Denver Federal Center
Denver, CO 80225

108 John W. Arendt
Union Carbide Corp.
Nuclear Division - MS 246
P. O. Box P
Oak Ridge, TN 37830

Legend
Major Stratigraphic Units
EASTERN NEW YORK, WESTERN MASS., CONN. AND VT.

Autochthonous	Eugeosynclinal Sequence
Hamilton Group	Allochthonous
Dhpl Plattekill Formation; equivalent to Ashokan Formation--shale, sandstone	On Normanskill Formation
Dhm Undifferentiated Lower Hamilton Group--shale, sandstone	Oa Austin Glen Formation--graywacke, shale
Middle Devonian Do Onondaga Limestone--cherty	Om Mt. Merino & Indian River Formations--shale, slate, chert
Dhg Helderberg Group--limestone, dolostone	Os Stuyvesant Falls Formation, south of Troy, equivalent to Poultney Formation "B"--shale, siltstone
DS Undifferentiated Lower Devonian and Upper Silurian rocks. Port Ewen thru Nemius Limestones, Rondout Dolostone	Ordovician OCe Elizaville Formation--shale, argillite, quartzite
Lower Devonian OSc Schenectady Formation; equivalent to Oag, autochthonous Austin Glen Formation (of Normanskill Group) or Bush Kill Formation (of Snake Hill Group)--graywacke, shale	OCu Undifferentiated Middle Ordovician through Lower Cambrian pelites and lesser conglomerate, quartzite and limestone
Middle Ordovician Owl Walloomsac Formation--slate, phyllite, schist, metagraywacke	Ep Poultney Formation--shale, limestone, conglomerate, equivalent to Gemantown Formation south of Troy, N.Y.
Oba Balzville Limestone	Cg Gemantown Formation--shale conglomerate, limestone
Ot Taconic Melange--chaotic mixture of Early Cambrian through Lower Ordovician clasts in pelitic matrix	Cn Nassau Formation--slate, shale, quartzite, North of 43°, Metawee slate
Lower Ordovician OCS Stockbridge Formation including Beekmantown Group and Wappinger Group--calcitic and dolomitic marble, limestone, dolomite.	Ca Austerlitz phyllite
Cambrian Cwm Winooski Dolostone, Monkton Quartzite and Rutland Dolostone	Cv Volcanics, greenstones, tuffs, basalts
Cc Cheshire Quartzite including Dalton Formation; equivalent to Poughquag Quartzite	Cr Rensselaer Graywacke
	Ce Everett Schist

Legend
Major Stratigraphic Units
of Vt., Central Mass., N.H. and N. Conn.

Q Quarternary glacial deposits--sand, clay, gravel	Cg Brimfield Schist (including Buylston Schist)
Tr Triassic and Jurassic red beds--arkose, shale, argillite, conglomerate, sandstone	Cam Amherst schist--migmatitic feldspar schist
Lower Devonian DL Littleton Formation--gray slate and phyllite	Cqu Quabbin quartzite
Dws Waits River Formation--limestone, volcanics, quartzite	Cor Erving Schist--quartz-hornblende schist
SF Fitch Formation--quartz-plagioclase-biotite granulite	
Middle & Upper Silurian DSN Northfield Formation--quartz-sericite slate or phyllite	
SS Shaw Mountain Formation--quartzite, conglomerate, schist	Sc Clough Formation--equivalent to Conway Schist, includes Goshen Schist, quartzite, quartz-mica schist
Unconformity	
Omm Missisquoi Formation--carbonaceous mica schist and phyllite	Opa Patridge Formation--carbonaceous mica schist
Middle Ordovician Omc Rusty weathering carbonaceous gneiss	Oam Ammonoosuc volcanic--andesite, rhyolite tuff, breccia, flows
Omb Barnard volcanic member--biotite and hornblende gneiss	Oh Hawley Schist; Equivalent to Omb in Mass.
OCst Stowe Formation--quartz-sericite-chlorite phyllite and schist, amphibolite	Og Berkshire schist--chlorite-sericite schist
Co Ottawaquchee Formation--carbonaceous phyllite	
OCup Undifferentiated Pinney Hollow, Ottawaquchee and Stowe Formations	
Middle Cambrian Camels Hump Group	
Ch Housac Formation including Pinney Hollow and Tyson Formations--schists, amphibolite, phyllite, dolomite	
Lower Cambrian Cca Cavendish Formation--schist, gneiss, carbonate, calc-silicate	
Eocambrian Precambrian (relative ages of units listed below are uncertain)	
mug interlayered metasedimentary rock and granitic or syenitic gneiss	Triassic Tb Thuleitic basalt intrusions & extrusions
am amphibolite	agd Agate granite
mu undivided metasedimentary rock and related migmatite	
bg biotite granitic gneiss	
bqp biotite-quartz-plagioclase gneiss	
qfg quartz-feldspar-gneiss	
m calcitic and dolomitic marble and calc-silicates	
q micaceous quartzite	
gn undivided gneisses of western Mass. Berkshire massif.	

IGNEOUS ROCKS*

Upper Devonian	agd Agate granite
Middle to Upper Devonian	big binary granite
	kum Kinsman quartz monzonite
	bgn Bethlehem gneiss
	qdz quartz diorite
	nng New Hampshire Series; undifferentiated in Vt. Devonian igneous rocks mapped by Emerson (1917); units not listed chronologically.
	hgr Hubbardston granite
	wg Williamsburg granite
	cg Coxs Hill granite
	mgd Monson granodiorite
	dd Dana diorite
	pg Pelham granite
	bt Belchertown intrusive
	hkg Hardwick granite
	peg pegmatite
Ordovician(?)	Oliverian Plutonic Series
	Ol granite, quartz monzonite, granodiorite
	U Ultramafic Rocks
	U serpentinite, carbonate rock
	Ud dunite, peridotite, serpentinite
Precambrian	see stratigraphic column

GEOLOGIC MAP ALBANY

GENERALIZED GEOLOGIC MAP OF THE ALBANY 15x20 QUADRANGLE, NEW YORK, VERMONT, NEW HAMPSHIRE, MASSACHUSETTS & CONNECTICUT

CREDITS

Compiler: Martin S. Rutstein

This map is a generalized and slightly modified version of the state maps of New York (Fisher et al., 1971), Vermont (Doll et al., 1961), New Hampshire (Billings, 1955), Connecticut (Rodgers et al., 1956) and Massachusetts (Emerson, 1917).

Drafting by J. S. Whisnant

MINERAL PROSPECTS

ALBANY 1°x2° QUADRANGLE
NEW YORK, VERMONT, NEW HAMPSHIRE,
MASSACHUSETTS & CONNECTICUT
SHOWING ANOMALOUSLY MINERALIZED ZONES

Compiler - Martin S. Rutstein
Sources of information
are cited in the text.

Print Modes for WELLS
NCAS + 558 + NCAS 558 NCAS 558 + NCAS 558 + + NCAS 558 NCAS + 558
+ (Site Location)

Print Modes for SPRINGS
NCAS ○ 558 ○ NCAS 558 NCAS 558 ○ NCAS 558 ○ ○ NCAS 558 NCAS ○ 558
○(Site Location)

GROUND WATER SAMPLE SITE LOCATIONS IN THE *ALBANY* QUADRANGLE

SURFACE SAMPLE SITE LOCATIONS
IN THE *ALBANY* QUADRANGLE

Uranium - parts per billion					
+ < D.L.	○ 0.005- 0.010	○ 0.036- 0.068	⊙ 0.329- 0.701	● 3.352- 6.699	
x < 0.003	○ 0.010- 0.019	○ 0.068- 0.155	⊙ 0.701- 1.625	◆ 6.699- 9.635	
○ 0.003- 0.005	○ 0.019- 0.036	⊙ 0.155- 0.329	⊙ 1.625- 3.352	★ > 9.635

URANIUM DISTRIBUTION IN THE GROUND WATERS OF THE ALBANY QUADRANGLE

Uranium - parts per million					
+ < D.L.	○ 1.600- 1.900	○ 2.700- 3.000	⊙ 4.400- 5.700	● 10.700- 13.200	
× < 1.400	○ 1.900- 2.200	○ 3.000- 3.600	⊙ 5.700- 7.700	◆ 13.200- 18.500	
○ 1.400- 1.600	○ 2.200- 2.700	⊙ 3.600- 4.400	⊙ 7.700- 10.700	★ > 18.500	

URANIUM DISTRIBUTION IN THE SEDIMENTS OF THE ALBANY QUADRANGLE

Thorium - parts per million				
+ < D.L.	○ 3.0- 5.0	○ 7.0- 9.0	● 16.0- 24.0	● 54.0- 84.0
x < 3.0	○ 5.0- 6.0	○ 9.0- 11.0	● 24.0- 38.0	◆ 84.0- 103.0
○ < 3.0	○ 6.0- 7.0	○ 11.0- 16.0	● 38.0- 54.0	★ > 103.0

THORIUM DISTRIBUTION IN THE SEDIMENTS
OF THE ALBANY QUADRANGLE

Conductivity - micro-mhos per cm.					
+ < D.L.	○ 20.0- 35.0	○ 75.0- 110.0	⊙ 220.0- 303.0	● 483.0- 620.0	
x < 20.0	○ 35.0- 50.0	○ 110.0- 150.0	⊙ 303.0- 380.0	◆ 620.0- 1030.0	
○ 20.0- 20.0	○ 50.0- 75.0	⊙ 150.0- 220.0	⊙ 380.0- 483.0	★ > 1030.0	

CONDUCTIVITY DISTRIBUTION IN THE GROUND WATERS OF THE ALBANY QUADRANGLE

Uranium - parts per billion				
+ < D.L.	○ 0.003- 0.005	○ 0.017- 0.037	⊙ 0.163- 0.267	● 0.672- 2.317
x < 0.002	○ 0.005- 0.009	○ 0.037- 0.090	⊙ 0.267- 0.420	◆ 2.317- 11.906
○ 0.002- 0.003	○ 0.009- 0.017	⊙ 0.090- 0.163	⊙ 0.420- 0.672	★ > 11.906

URANIUM DISTRIBUTION IN THE SURFACE WATERS OF THE ALBANY QUADRANGLE

Conductivity - micro-mhos per cm.				
+ < D.L.	○ 23.0- 30.0	○ 50.0- 71.0	⊙ 180.0- 270.0	● 500.0- 900.0
x < 20.0	○ 30.0- 36.0	○ 71.0- 115.0	⊙ 270.0- 370.0	◆ 900.0- 1150.0
○ 20.0- 23.0	○ 36.0- 50.0	⊙ 115.0- 180.0	⊙ 370.0- 500.0	★ > 1150.0

CONDUCTIVITY DISTRIBUTION IN THE SURFACE WATERS OF THE ALBANY QUADRANGLE