NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

12
3-3-92 JSD

PNL-7990

UC-311

Assessment of TEES® Applications for Wet Industrial Wastes: Energy Benefit and Economic Analysis Report

D. C. Elliott
T. H. Scheer

February 1992

Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute

PNL-7990

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor Battelle Memorial Institute, nor any of their employees, makes **any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights.** Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or Battelle Memorial Institute. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

PACIFIC NORTHWEST LABORATORY
operated by
BATTELLE MEMORIAL INSTITUTE
for the
UNITED STATES DEPARTMENT OF ENERGY
under Contract DE-AC06-76RLO 1830

Printed in the United States of America

Available to DOE and DOE contractors from the
Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831;
prices available from (615) 576-8401. FTS 626-8401.

Available to the public from the National Technical Information Service,
U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

PNL--7990

DE92 008203

ASSESSMENT OF TEES® APPLICATIONS
FOR WET INDUSTRIAL WASTES: ENERGY
BENEFIT AND ECONOMIC ANALYSIS REPORT

D. C. Elliott
T. H. Scheer

February 1992

Prepared for
the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830

Pacific Northwest Laboratory
Richland, Washington 99352

MASTER

SUMMARY

Fundamental work in catalyzed biomass pyrolysis/gasification led to the Thermochemical Environmental Energy System (TEES®) concept, a means of converting moist biomass feedstocks to high-value fuel gases such as methane. A low-temperature (350°C), pressurized (3100 psig) reaction environment and a nickel catalyst are used to reduce volumes of very high-moisture wastes such as food processing byproducts while producing useful quantities of energy. The energy input and output is illustrated below.

A study was conducted to assess the economic viability of a range of potential applications of the process. Cases examined included feedstocks of cheese whey, grape pomace, spent grain, and an organic chemical waste stream. The analysis indicated that only the organic chemical waste process is economically attractive in the existing energy/economic environment. However, food processing cases will become attractive as alternative disposal practices are curtailed and energy prices rise.

R9110141.1

FIGURE S.1. Energy Input and Output from TEES®

® TEES is a registered trademark of Onsite*Ofsite, Inc.

ACKNOWLEDGMENTS

The process design, costing, and economic analysis found in this report were performed under subcontract to Pacific Northwest Laboratory (PNL) by Onsite*Offsite, Inc. (O*O) under the supervision of Mr. Norman Banns, president. The project manager at O*O was Mr. Ted Scheer.

Funding for this research project, Low-Temperature Catalytic Gasification of Wet Industrial Wastes, was provided by the Office of Industrial Programs (now Office of Industrial Technology) of the U.S. Department of Energy's Office of Conservation and Renewable Energy. Both PNL and O*O acknowledge the support of Mr. Stuart Natof, the program manager for this project at DOE-Headquarters.

CONTENTS

SUMMARY	iii
ACKNOWLEDGMENTS	v
1.0 INTRODUCTION	1.1
1.1 THE TEES® PROCESS	1.1
1.2 LOW-TEMPERATURE CATALYTIC GASIFICATION OF WET INDUSTRIAL WASTES	1.3
2.0 CONCLUSIONS AND RECOMMENDATIONS	2.1
2.1 CONCLUSIONS	2.1
2.2 RECOMMENDATIONS	2.2
3.0 TEES® PROCESS DESCRIPTION	3.1
3.1 DESIGN BASIS	3.1
3.2 PROCESS DESCRIPTION	3.1
4.0 PROCESSING CASE ASSESSMENTS	4.1
4.1 FINANCIAL CRITERIA AND ASSUMPTIONS	4.1
4.2 ENERGY VARIABLES	4.2
4.3 CHEESE WHEY	4.2
4.3.1 Scope of Potential TEES® Users	4.2
4.3.2 Scope of Problems	4.4
4.3.3 Capital Costs	4.4
4.3.4 Operating Costs	4.4
4.3.5 Benefits	4.7
4.3.6 Economic Parameters	4.7
4.4 GRAPE POMACE	4.8
4.4.1 Scope of Potential TEES® Users	4.8
4.4.2 Scope of Problems	4.11

4.4.3	Capital Costs	4.11
4.4.4	Operating Costs	4.11
4.4.5	Benefits	4.11
4.4.6	Economic Parameters	4.13
4.5	SPENT GRAIN	4.14
4.5.1	Scope of Potential TEES® Users	4.14
4.5.2	Scope of Problems	4.15
4.5.3	Capital Costs	4.15
4.5.4	Operating Costs	4.16
4.5.5	Benefits	4.16
4.5.6	Economic Parameters	4.16
4.6	ORGANIC CHEMICAL WASTE	4.19
4.6.1	Scope of Potential TEES® Users	4.19
4.6.2	Scope of Problems	4.19
4.6.3	Capital Costs	4.19
4.6.4	Operating Costs	4.20
4.6.5	Benefits	4.20
4.6.6	Economic Parameters	4.20
5.0	REFERENCES	5.1
	APPENDIX - DETAILS OF CASH FLOW ANALYSIS	A.1

FIGURES

S.1	Energy Input and Output from TEES®	iii
3.1	Basic TEES® Unit Process Flow	3.3
4.1	Energy Input and Output from TEES®	4.3

TABLES

4.1	Estimated Whey in Top 10 Cottage Cheese Producing States, 1988	4.3
4.2	Capital Costs for Cheese Whey Feedstock Preparation and Handling	4.5
4.3	Capital Costs for Cheese Whey TEES® Process Section	4.6
4.4	Internal Rate of Return and Payout Sensitivity to Disposal Cost for Cheese Whey Integrated System	4.8
4.5	Statistics for Cheese Whey Processing (gas-fired heating)	4.9
4.6	Statistics for Cheese Whey Processing (electrical heating)	4.10
4.7	Capital Costs for Grape Pomace Feedstock Preparation and Handling	4.12
4.8	Internal Rate of Return and Payout Sensitivity to Disposal Cost for Grape Pomace Integrated System	4.13
4.9	Statistics for Grape Pomace Processing	4.14
4.10	1987 Year End Brewing Capacity	4.15
4.11	Capital Costs for Spent Grain Feedstock Preparation and Handling	4.17
4.12	Internal Rate of Return and Payout Sensitivity to Disposal Cost for Spent Grain Integrated System	4.17
4.13	Statistics for Spent Grain Processing	4.18
4.14	Statistics for Organic Chemical Base Case	4.21

4.15	Internal Rate of Return and Payout Sensitivity to Disposal Cost for Organic Chemical Integrated System	4.21
------	---	------

1.0 INTRODUCTION

This report presents the results of an economic assessment of the Thermochemical Environmental Energy System (TEES®) as it could be applied in four different industrial settings. The analysis includes capital and operating cost determination for the process and evaluation of the energy savings and economical benefit of incorporating the process into existing industrial processes.

This report consists of an introduction describing the TEES® process and the research project including this engineering analysis effort, conclusions and recommendations based on the results of the engineering analysis, technical description of the TEES® process, and a presentation of the economic assessments for the four process applications. The appendix contains details of the economic calculations.

1.1 THE TEES® PROCESS

The TEES® process is an outgrowth of fundamental work in catalyzed biomass pyrolysis/gasification that was initiated under Gas Research Institute funding in 1979 (Elliott and Sealock 1985). The TEES® concept, which was developed by Pacific Northwest Laboratory (PNL)^(a) from this work, has burgeoned as a means of converting moist biomass feedstocks (agricultural wastes, grasses and straws, and marine and aquatic plants) to high-value fuel gases such as methane (Sealock et al. 1988). The conversion system produces medium-to-high Btu gas while avoiding the inherent limitations associated with anaerobic digestion, including yield, rate, and flexibility. In addition, the ability of the catalytic system to work with dilute streams (1-20 wt%) gives the concept broad applicability to a number of non-biomass uses. Perhaps the most important use is the recovery of methane and CO₂ from low-solids content organic industrial and food processing waste streams.

(a) Operated for the U.S. Department of Energy (DOE) by Battelle Memorial Institute under contract DE-AC06-76RLO 1830.

The TEES® process is relatively simple. The organic-containing water slurry or solution is pumped to operating pressure (3000 psig), preheated to operating temperature (350°C), and exposed to a nickel catalyst. The pyrolytic mechanisms and nickel-catalyzed reactions result in the organic reacting with some water to produce a gas consisting primarily of methane and carbon dioxide. The clean water stream can be recycled within the industrial setting as needed. The product gas can be used as a medium-Btu fuel or separated by membranes into the component gases for chemical or other uses. A more detailed description of the process is provided in Section 3.0.

There are several unique features of the TEES® process which distinguish it from other thermochemical recovery technologies such as combustion and gasification. Three of the most important aspects of the technology that demonstrate its uniqueness are:

1. The use of the low-temperature (350°C), pressurized (3100 psig) reaction environment facilitates more efficient heat recovery from reaction products, which in turn allows the use of very high-moisture (around 95 wt% moisture) feedstocks. Heat transfer is improved under these conditions because the product stream has relatively high fluid density, which permits the use of compact, less costly heat recovery equipment. The reaction conditions serve to shift reaction equilibrium towards the production of methane, as opposed to lower valued fuel gases such as CO and hydrogen. Thus, the product from the TEES® process is more compatible with existing natural gas burners than the low-Btu gas available from conventional high-temperature gasifiers.
2. High reaction rates, even at the low temperatures employed in the process (350°C), are achieved by the use of commercial nickel catalysts. Residence time requirements for many feedstocks are estimated to be 10 to 20 minutes or less at temperature, which compares favorably with the requirements in conventional thermal systems operating at much higher temperatures (typically above 600°C).
3. The TEES® concept can be used to produce useful quantities of energy for many energy-intensive industries and at the same time solve byproduct disposal (both solid and liquid) and other environmental problems such as wastewater cleanup. The process can serve as a stand-alone gasification plant or can be integrated into existing industrial plants to accomplish specific energy, economic, and environmental goals.

In comparison with anaerobic digestion, which has shown potential as a means for simultaneously reducing the biochemical oxygen demand (BOD) and recovering energy from selected waste streams, the TEES® concept offers two major advantages:

1. In the TEES® process, reaction rates are at least two-to-three orders of magnitude greater than those attainable through anaerobic digestion. This increase in rate results in significant reductions in reactor volume and space requirements for the TEES® approach. The higher reaction rates also result in a process that is more responsive to rapid fluctuations in waste load or changes in waste composition.
2. The TEES® process has the ability to efficiently convert biochemically "inert" waste components such as lignins and lignin byproducts. For many waste streams, this improved conversion will result in increased resource recovery from the waste streams and greater reductions in discharge BOD and COD levels than can be obtained with bioconversion.

1.2 LOW-TEMPERATURE CATALYTIC GASIFICATION OF WET INDUSTRIAL WASTES

The purpose of this project is to facilitate the development of the TEES® concept to convert wet industrial wastes to significant quantities of methane in order to provide energy conservation and reduced disposal costs. Many specific industrial wastes (food processing, beverage production, pharmaceutical, petroleum refining, and chemical manufacturing) are in such a form that they cannot be economically incinerated or disposed of in a landfill or sewer. These waste streams consist of high-moisture solids, wet sludges, or highly-contaminated waste water that contain significant amounts of organic carbon which, if appropriate technology were available, could be converted to a useful fuel form.

TEES® is more than just a gasification system as it can be integrated into an existing plant to solve several energy and environmental needs. TEES® is a unique thermocatalytic gasification concept for converting wet industrial and food processing wastes to methane (for use in existing boilers) and carbon dioxide (for bottling, packaging, and other plant uses); at the same time, cogeneration, hot water for plant operation, wastewater treatment, and reduction in solid waste handling can also be achieved. The TEES® concept is

distinctive in its application to industry, and no biological or thermal processes exist that have the potential to provide the overall systems impact of TEES®.

Process research is being conducted in a 1-L bench-scale, continuous reactor system (CRS) to evaluate alternative catalysts, develop catalyst deactivation and lifetime data, and determine kinetic parameters for the conversion of a variety of food processing and organic wastewater feedstocks (Elliott et al. 1991).

To fully define and analyze the concept and evaluate its integration into specific industrial operations, O*O was subcontracted to perform engineering design and economic assessment of the TEES® process as it might be incorporated into existing industrial settings. This information is needed before the process can be advanced to commercial application. O*O was selected for the work because they hold the license to TEES® and had developed both designs for the process equipment and the industrial contacts necessary for obtaining the needed information. The system assessment thus performed provides DOE and industry with the information required to evaluate the fully integrated concept in various industrial applications.

In addition, O*O has prepared detailed designs and specifications for equipment used in a process development unit built to evaluate the effects of scaleup on the process.

2.0 CONCLUSIONS AND RECOMMENDATIONS

Based on the results of the energy benefit and economic assessment in Section 3.0 of this report, the following conclusions and recommendations are made.

2.1 CONCLUSIONS

The TEES® process can be incorporated into existing industrial settings and by so doing provide numerous cost savings such as energy return (as fuel gas or methane) to the plant, reduced waste transport and disposal costs, reduced water processing costs, internal production of a useful chemical (carbon dioxide), and conservation of important water resources.

A broad field of possible application for the TEES® process was identified, which suggests a large potential impact. Within the three food processing cases examined, the potential annual feedstock is 2 million tons cheese whey (the amount actually wasted, total amount of cheese whey is much larger), 0.4 million tons of grape pomace, and 9.4 million tons of spent grain (much of which is used as animal feed). Net gas production would be 1.2, 0.3, and 8.9 trillion Btu annually from the three feedstocks respectively. The organic chemical waste stream analyzed in this study was a relatively small operation, and it is expected that the scale of application of TEES® to organic chemical wastes is probably much larger than what was identified for food processing wastes.

In all cases there is a net energy production from the waste stream. The net amount of gas produced in the four cases varies from 18,481 SCF/day in organic chemical waste to 151,116 SCF/day for cheese whey to 1,939,797 SCF/day for grape pomace to 2,218,909 SCF/day for spent grain. In all cases the gas produced is a medium-Btu fuel gas that could be further upgraded by separation into high-Btu gas (90% methane) and carbon dioxide byproduct.

The analysis of the applications studied shows that only the organic chemical waste process is attractive in the existing energy/economic environment. However, the spent grain case would be attractive if byproduct credits

for sales of the spent grain as animal feed were not considered. The grape pomace and cheese whey cases will become attractive as alternative disposal practices are curtailed.

Adequate development time exists to prepare TEES® for commercialization as energy prices rise and environmental regulations become more stringent.

2.2 RECOMMENDATIONS

Since organic chemical waste processing appears to be economically viable now, further effort should be expended in this area of application of the TEES® process. The total amount of such waste is so large that it is likely to be the major application of TEES®. Obtaining sufficient information on organic chemical manufacturing wastewater streams for this type of detailed analysis was difficult. Stream-specific processing data is needed, so specific definition of the wastewater stream must be obtained. More cooperation from the organic chemical manufacturers should be elicited. Based on our limited success in our attempts thus far, it appears that a stronger effort will be required, including face-to-face meetings with manufacturers.

Wide application of the TEES® in the food processing industry should also be pursued. Several specific applications of the process can be useful to food processors in light of future curtailments of land disposal alternatives. The three cases analyzed in this research represent only a fraction of the potential applications of the process. A recent study of food processors states that over 200 million tons/yr of raw agricultural commodities are harvested annually in the USA, and less than 50% of these materials end up as useable products, which leaves the balance as potential feedstock for TEES®.

For processing of both organic chemical waste and food processing waste, the major effort needed is a combination of data acquisition and technology transfer. More tests need to be performed in the reactor system with specific feedstocks of interest to industry. In return, information on the feedstock composition, availability, and alternative uses must be obtained from industry. By this cooperative research, a sense of mutual interest and trust can be developed between PNL and industry to facilitate the technology transfer process.

Use of TEES® for the gasification of high-moisture (herbaceous, marine, and aquatic) biomass feedstocks and for treatment of wastewater streams from both thermochemical and biochemical conversion of biomass should be addressed as biomass research expands to meet future energy needs.

3.0 TEES® PROCESS DESCRIPTION

The basic TEES® process module does not change for any of the applications in this report; only the sizing of equipment and piping for different flow rates change. The slurry or suspension feed that is presented to the high-pressure feed pump from the feedstock preparation phase behaves the same in all cases, except for concentration and rate.

Similarly, a low-pressure effluent water and a medium-Btu gas at the pressure necessary to enter the plant fuel system have the same process characteristics for all cases.

3.1 DESIGN BASIS

The major design bases are a feed concentration of 20% by weight solids in water with eight minutes residence time over a supported, reduced nickel catalyst at 350°C and 3100 psig in the reactor.

3.2 PROCESS DESCRIPTION

The TEES® process is shown in Figure 3.1. The feed slurry is pumped at about 3150 psig into the tube side of the feed preheater where it picks up heat from the reactor effluent. Then it goes to the feed heater where it reaches the final temperature of 350°C before entering the reactor. Research indicates that biomass cells will break down in the presence of moisture when they reach about 250°C and will actually reach the catalyst bed in liquified form. This suggests that plugging by solids should not be a problem.

In the reactor, the feed makes contact with the a nickel catalyst. Complex, incompletely understood reactions between the water or steam and the organic molecules break the organics down almost completely, leaving the simple gases methane and carbon dioxide. Hydrogen gas and traces of other intermediates such as ethane and propane will also be present in most cases. Carbon monoxide is a probable intermediate reactant, and may be a trace component in the effluent gas.

The reactor effluent passes through a sintered metal filter to remove any catalyst or other solids, then through the shell side of the feed preheater.

After giving up as much heat as possible to the incoming feed, the reactor effluent (a mixture of most of the original water and the gaseous products) still has considerable temperature and most of its high pressure. A relatively new type of pressure reduction component, a biphasic turbine, is used to reduce the pressure of the two-phase mixture and turn a shaft to run an electric generator. The work expended creates power that can be put back into the power network and compensate for some of the power used, for instance, to run the pumps and motors. The biphasic turbine can also act as a gas-liquid separator.

If the biphasic turbine is out of commission, a bypass routes the effluent through an air-blown cooler to reduce the effluent temperature, if desirable for the final disposal of the effluent.

FIGURE 3.1. Basic TEES® Unit Process Flow

NOTE: THIS DRAWING TO BE WORKED WITH ALL PREPARATION & HANDLING AND PRODUCT TREATING DRAWINGS.

						<div>↔</div> <div>ONSITE</div> <div>OFFSITE</div>		PASADENA , CALIFORNIA	
REV.	DATE	DESCRIPTION		BY	CHK	APP'D			
ISSUED FOR CONSTRUCTION				CUSTOMER APPROVAL					
BY		DATE		BY		DATE			
DESIGNED		DRAWN		REVIEWED		APPROVAL		BASIC TEES UNIT	
BY TS		BY JCP		DATE		BY		DATE	
BY TS		BY JCP		DATE		BY		DATE	
FTIR						ACAD FILE NUMBER		SCALE	NONE
AT						2003PF01		JOB NO.	F-22003
								DRAWING NUMBER	F-1001
								REV.	0

4.0 PROCESSING CASE ASSESSMENTS

An economic assessment was made for each of four integrated systems using data representative of operating plants on the West Coast. These four cases include TEES® systems for cheese whey, grape pomace, spent grain, and an organic chemical wastewater. Most of the company representatives who supplied information did not want their company names exposed for competitive business reasons. Therefore, some of the data that might identify a particular source have been skewed. However, the values for utilities and other operating parameters are regionally representative, and data from any given situation can be used to assess the TEES® technology for that application.

Capital costs for the basic TEES® process equipment were based on vendor quotes and a standard 100,000 gallons per day process flowrate. Costs were extended to the application size by the "sixth-tenths" rule. Costs for feed-stock preparation and handling were based on vendor information for the exact application size.

4.1 FINANCIAL CRITERIA AND ASSUMPTIONS

The financial criteria of IRR (Investor's or Internal Rate of Return) and PAYOUT (Years to Payback Original Investment) were used to fashion each matrix for economic comparison. Since the cash flows and other data are given, the reader can calculate other criteria if desired.

Financial Assumptions are as follows:

- Base year is Year 0.
- Future dollar values are not discounted for inflation.
- Financing for capital investment is 100% external.
- Working capital is internal.
- Interest rate for borrowed funds is 10%.
- Financing is for 20 years.

- The accelerated depreciation period is 7 years
 - 3 years double declining balance
 - 4 years straight line
- The total state and federal corporate tax rate is 40%.

4.2 ENERGY VARIABLES

Energy products from the TEES® process are in the form of combustible gas, pressure letdown to drive electricity-generating turbines and a hot water stream for process heating. At the same time, energy is used by the process for feed heating and pump motors. These energy flows are depicted in Figure 4.1. Since this report covers more than one application and feedstock, the specifics are quite different. Gas production depends on the solids and carbon concentration in the feedstock. Cheese whey and spent grain wastewater are usually fairly dilute water solutions. Grape pomace starts from the solid state and is diluted to a pumpable state. Organic chemical wastewater streams are usually very dilute and their gas output is minimal. Each application will be treated separately.

4.3 CHEESE WHEY

4.3.1 Scope of Potential TEES® Users

Cheese whey is the watery residue drained and pressed from cottage cheese (and other cheese) production. It contains about 6% by weight of dissolved milk solids, mainly milk sugars and acids and fats. Depending upon the state of separation used at a specific facility, undissolved solids may be present. Total solids content may reach 25% in processed cheese wheys in which components have been extracted and the solution concentrated.

The potential whey available in this country is estimated to be more than 466 million gallons annually with 63% in the top ten states. The top two states, New York and California, account for 30% as shown in Table 4.1.

The total potential gas conversion is about 2.1 billion SCF with a fuel value of about 11 million therms assuming 6% solids. Of this quantity, 58% is calculated as available if feed heating is done with product gas.

R9110141.1

FIGURE 4.1. Energy Input and Output from TEES®

TABLE 4.1. Estimated Whey in Top 10 Cottage Cheese Producing States, 1988

Rank (MM)	State	Gallons	% of U.S.
1	New York	78.2	16.8
2	California	52.6	12.8
3	Pennsylvania	36.8	7.9
4	Wisconsin	24.7	5.3
5	Ohio	18.6	4.0
6	Washington	17.9	3.7
7	Indiana	17.0	3.5
8	Michigan	17.0	3.5
9	Illinois	15.5	3.2
10	Kentucky	13.1	2.7
Total Top 10			63+ %

Source: Dairy Products, 1988 Summary.

Production tends to be clustered around dairy centers. For example, 90% of production in California is said to exist within 30 miles of the town of Tulare. While the number and distribution is not known, the largest producer in California is said to represent over 26,000,000 gallons annually.

4.3.2 Scope of Problems

Cheese whey as a byproduct or waste is treated in many ways. It is fed to cattle, spread on the ground, and dumped to sewers of public owned treatment works (POTW). It is treated by filtration, reverse osmosis, fermentation to alcohol, and is a source of lactose and other chemicals.

If applied to the ground, the type and depth of soil, rainfall, depth of water table, etc., affect the loading that can be applied and whether odors occur. Cattle feeding and ground spreading are subject to transportation costs. Both may be affected by future research conclusions and governmental regulations.

In terms of dumping to sewer in Los Angeles County, the Sanitation District COD demand charge is \$43.20 per thousand pounds of COD, and the suspended solids charge is \$124.90 per thousand pounds of solids.

4.3.3 Capital Costs

Total estimated capital cost for this system is 5.1 million dollars (Tables 4.2 and 4.3):

• feedstock preparation and handling	\$ 0.1 million
• TEES® process	5.0
Total	\$ 5.1 million

The reactors and catalyst account for 47% of the equipment cost. The high pressure, high design temperature, and corrosion resistant metallurgy combine to make most of the reaction train design relatively expensive.

4.3.4 Operating Costs

Operating costs are a function of

- royalty
- local taxes and insurance

TABLE 4.2. Capital Costs for Cheese Whey Feedstock
Preparation and Handling

<u>Item</u>	<u>Description</u>	<u>Cost (1990 \$)</u>
1	Tank - 26 ft - 8 in. dia x 24 ft, carbon steel/epoxy lined, bolted construction, API w/6 in. crushed rock foundation. Two tanks = 2 x \$35,000 erected	70,000
2	Grading	5,000
3	Pump - 56 GPM x 30 psi head Goulds Model 3996 vertical inline, ductile iron, 3hp motor, 1 1/2 x 2. Two pumps = 2 x (2250 + 68 + 125)	4,900
4	Piping - 200 ft of 2 in. plastic = 200 ft @ 185.25/100 ft Fittings - tees = 6 x 33 - ells = 6 x 16 - cplg = 10 x 12 - union = 4 x 50 - nipples = 4 x 4 Valves - gate = 8 x 80 - check = 2 x 86	370 200 100 120 200 20 640 170
5	Instrumentation - Level indicator = 2 x 1500	3,000
6	Concrete	<u>2,000</u>
	Subtotal	86,720
7	Installation (Items 3 thru 6)	8,000
8	Engineering (Items 1 thru 6)	<u>13,000</u>
	Grand Total	107,720
	Rounded Total	108,000

**TABLE 4.3. Capital Costs for Cheese Whey TEES® Process Section
(70,000 GPD)**

<u>Item</u>	<u>Description</u>	<u>Cost (1990 \$)</u>
1	Reactors - 4 each 24 in. dia x 22 ft carbon steel/304 SS lined. ^(a)	400,000
	Other - including Biphase Turbine	497,000
	Installation	60,000
2	Catalyst - 144 ft ³	55,000
3	Civil - site prep 30 ft x 30 ft plot and	
4	Structural - include operating structure of 20 ft x 20 ft with 2 upper levels at 10 ft and 20 ft	350,000
5	Piping - materials (304 SS)	821,000
	- installation	90,000
6	Instrumentation - materials and installation	250,000
7	Electrical	72,000
8	Insulation	65,000
9	Painting	30,000
10	Building - control room	<u>150,000</u>
	Total equipment, installed	2,840,000
11	Engineering (20%)	568,000
12	Overhead, taxes, and insurance (10%)	<u>284,400</u>
	Subtotal	3,692,400
13	Contingency and cost recovery (35%)	<u>1,292,300</u>
	Grant Total	4,984,700
	Rounded Total	5,000,000

(a) Material cost based on 304 SS metallurgy (linings and pipe, valves, and fittings) for CO₂ wetted process sections.

- maintenance parts and supplies
- catalyst replacement
- power purchased
- operating and maintenance labor.

These are shown in Table 4.3 and the worksheet in the Appendix.

For the base case of gas used for feed heat, annual operating costs are \$301,000. If feed heat is by purchased electric power, operating costs are much higher, \$743,000. This could be mitigated by including an engine-driven generator set using produced gas, reducing the surplus gas, and increasing slightly the capital costs and operating costs. This option is not included in this study because of the added parts and extra operating and maintenance labor with an engine and generator set.

4.3.5 Benefits

- Water dumped to sewer has COD reduced by 98% or more, resulting in greatly lowered sewer charges
- Transport costs eliminated if whey was transported for disposal
- Water pure enough for recycle to plant for wash purposes or for agricultural irrigation.

4.3.6 Economic Parameters

For a 6% solids TEES® feedstock such as cheese whey, economic operation of TEES® would be strongly dependent on avoided cost of disposal or regulatory or other bars to disposal. Therefore, the financial results are shown as a function of disposal cost in Table 4.4. The base case is taken as the gas-fired feed heater case that minimizes operating costs but uses 58% of the gas produced.

A four-year payout and 22% internal rate of return would be achieved if disposal costs reached \$30 per ton or \$129 per 1000 gallons. \$30 per ton is not an unusual cost at this time for landfill disposal, but short distance tank-truck hauls are near \$2.20 per 1000 gallons or \$0.50/ton. If dumped to sewer in the Los Angeles Sanitation District, COD demand charge would be \$19.86/1000 gallons. If the product water could be recycled and used as wash

TABLE 4.4. Internal Rate of Return and Payout Sensitivity to Disposal Cost for Cheese Whey Integrated System

Disposal Cost		Base Case Gas Feed Heat		Sensitivity Case Electric Feed Heat	
<u>\$/Ton</u>	<u>\$/1000 Gal</u>	<u>IRR-%</u>	<u>Payout-yr</u>	<u>IRR-%</u>	<u>Payout-yr</u>
100	430	98.3	2	93.1	2
60	258	56.0	2	51.0	2
40	172	34.2	3	28.9	4
30	129	22.5	4	16.6	5 ^(a)
25	107.5	16.0	6	9.2	8
20	86	8.4	8	0	20+

(a) Details of \$30/ton calculations are in Tables 4.5 and 4.6.

water, then it would replace well water valued at \$0.50 per 1000 gallons. The value of recycle water for wash water is \$13,000 per year for 78,000 gallon/day. In a city environment, water could cost \$0.88 per 1000 gallons. In a drought year such as Southern California experienced in 1990, the limited availability and high cost of such water might well be disastrous to the cheese manufacturers without an alternate makeup source for water.

A sensitivity case using a COD demand disposal charge of \$19.86/1000 gallons and \$0.88/1000 gallons fresh water cost provides and 8.4% rate of return on investment as is seen in Table 4.4. Avoidance of higher disposal costs (as expected in the near future) results in higher return and faster payout.

4.4 GRAPE POMACE

4.4.1 Scope of Potential TEES® Users

Grape pomace is the residue of skins and pulp after the juice is extracted in the crushing operations during winemaking. One general treatment is to sun-dry the pomace in windrows on the ground. Moisture drops from 50% to 8%. The gasification potential is about 6 SCF of gas per pound of bone-dry

TABLE 4.5. Statistics for Cheese Whey Processing (gas-fired heating)

6% Whey

Total plant investment cost (\$)	- 5,100,000
Plant life (yr)	- 20
Annual taxes and insurance (% capital)	- 2
Annual supplies and maintenance (% capital)	- 1
Plant capacity (gal/d)	- 70,000
Plant capacity factor (%)	- 80
Plant water consumption (g/ton)	- 133
Plant electric consumption (kW/ton)	- 0.22
Biomass (waste) disposal cost (\$/ton)	- 129 for 4-yr payout
Plant steam value (\$/MMBtu)	- 3.5
Water cost (\$/1000 g)	- 0.50
Electricity cost (\$/kWh)	- 0.078
Number of operators per shift	- 1 (shared)
Shifts per day	- 3
Net salary per operator	- 62,400
Annual Catalyst Cost (\$)	55,747
Annual Water Cost (\$)	0
Annual Electric Cost (\$)	35,381
Annual Operator Cost (\$)	87,280
Annual Water Savings (\$)	12,250
Net Disposal Savings (\$)	<u>2,591,610</u> (Not actual)
Capital Cost (\$/1000 gpd)	72,860
Simple Payback (yr)	4
Return on Investment (%)	22.5

solid. Feeding a 10% by weight slurry leaves about 82% of the produced gas as surplus after subtracting plant fuel needs. For a 110 dry ton per day production rate the surplus gas would be 2,000,000 SCF/day of 454 Btu/SCF (HHV). This is 3.2 million therms of energy if the feed rate can be sustained for 350 days/year.

The problem is that the pomace is only made during a 90 day crush period once a year. The assumption is made in this study that other solids such as almond and walnut shells, peach, apricot and plum pits, apple and pear pomace and many other solid wastes are available in wine regions at various times and can supply 260 days feedstock. The gasification characteristics should be similar.

TABLE 4.6. Statistics for Cheese Whey Processing (electrical heating)

6% Whey

Total plant investment cost (\$)	- 5,100,000
Plant life (yr)	- 20
Annual taxes and insurance (% capital)	- 2
Annual supplies and maintenance (% capital)	- 1
Plant capacity (gal/d)	- 70,000
Plant capacity factor (%)	- 80
Plant water consumption (g/ton)	- 133
Plant electric consumption (kW/ton)	- 3.0
Biomass (waste) disposal cost (\$/ton)	- 129 for 5-yr payout
Plant steam value (\$/MMBtu)	- 3.5
Water cost (\$/1000 g)	- 0.50
Electricity cost (\$/kWh)	- 0.078
Number of operators per shift	- 1 (shared)
Shifts per day	- 3
Net salary per operator	- 62,400
Annual Catalyst Cost (\$)	55,747
Annual Water Cost (\$)	0
Annual Electric Cost (\$)	476,916
Annual Operator Cost (\$)	87,280
Annual Water Savings (\$)	13,000
Net Disposal Savings (\$)	<u>2,591,610</u> (Not actual)
Capital Cost (\$/1000 gpd)	72,860
Simple Payback (yr)	5
Return on Investment (%)	16.6

The other alternative is to provide a smaller TEES® unit, and feed 90/350ths of the season crush per day, or 28.5 tons/day. A plant of this size will not likely justify the labor crew necessary to manage the solid feed operation.

With approximately 935 wineries in the United States and 534 in California,^(a) the potential is on the order of 119,000 tons of dry pomace. While most of the wineries are of small-to-medium size, they are mainly clustered in concentrations that would favor a main disposal plant, in place of landfill

(a) According to 1989 Wine & Vines Buyers Guide.

that many use. California represents 96% of the USA production and most of California's is in the Napa Valley and the San Joaquin Valley. The largest producer is said to do 40% of California's bottling.

4.4.2 Scope of Problems

Grape pomace is currently disposed of by spreading in the vineyards as mulch, drying for animal feed and soil supplements, landfill and incineration. A large land area such as 2 to 3 acres is necessary to stockpile a crush's pomace until it sun-dries. If the weather turns humid, the stacks may mildew and be unpalatable as feed. Also, the stacks of pomace smell strongly while drying.

Spreading in the fields requires transport and labor and may exceed good land practice. Landfill is a resource rapidly becoming unavailable, and costs will escalate.

4.4.3 Capital Costs

Total estimated capital cost for this system is 11.0 million dollars as shown in Table 4.7.

• feedstock preparation and handling	\$ 0.5 million
• TEES® process	<u>10.5</u>
Total	\$11.0 million

4.4.4 Operating Costs

For the base case with gas feed heat, annual operating costs are \$1,149,000.00.

4.4.5 Benefits

- a non-polluting method of getting rid of grape pomace and other nut and fruit solid wastes
- reduced transportation costs
- less fuel gas to be purchased
- possible reduction of BOD by 90% or more if other water is added.

TABLE 4.7. Capital Costs for Grape Pomace Feedstock Preparation and Handling

<u>Item</u>	<u>Equipment</u>	<u>Cost (1990 \$)</u>
1	Truck unloading system including subterranean feedstock holding basin, basin hopper, hopper btm conveyor belt, bucket elevator feeder, and bucket elevator	100,000
2	Concrete for basin	30,000
3	Main storage/feed hopper, 24 ft dia x 11 ft straight side x 57.7 degree bottom cone overall height = 30 ft	50,000
4	Installation (items 1 thru 3)	50,000
5	Engineering (items 1 thru 3)	25,000
6	Rotary feeder valve (hopper btm outlet)	1,000
7	Moyno pump, flowrate = 36 gpm, head = 20 psi 2G065G1 cast iron buna N stator 50 rpm, approximately 15 HP, fixed speed:	
	two pumps (one spare) 2 x \$15,000	30,000
8	Mill:	
	two macerators (one spare) 2 x \$6,000	12,000
9	Weigh feeder-belt, weight measure basis	17,830
10	Piping	1,000
11	Structural support for weigh feeder	1,000
12	Concrete foundations (etc. for items 7 and 9)	500
13	Installation (items 6 thru 12)	15,000
14	Engineering (items 6 thru 12)	<u>10,000</u>
	Belt weigh basis---approximately	343,330
	35% contingency	<u>120,000</u>
	Total	464,000

4.4.6 Economic Parameters

The economics show that a net disposal cost of \$135/ton would give a 4-year payout and 23% internal rate of return (see Table 4.8).

With 8% moisture in the raw feedstock, 19 gallons of water are brought in with each ton. Since 133 gallons per bone dry ton are needed in the chemical reaction, then makeup water of $133 - 19 = 114$ gallons/ton is required at small annual cost (\$2,600).

Some pomace is presently sold for about \$38 per ton as animal food additive. This generally requires grinding facilities and intermediate storage. If pomace is groundspread or landfilled, haulage costs on the order of \$3 to \$4 per ton are incurred using large (50 yd³) trailers.

This application is penalized by the need for feed preparation and handling facilities. Conveying and weigh-control equipment and a pit are capital costs, and they also require manpower and attention.

TABLE 4.8. Internal Rate of Return and Payout Sensitivity to Disposal Cost for Grape Pomace Integrated System

<u>Disposal Cost \$/1000 Gal</u>	<u>IRR - %</u>	<u>Payout - yr</u>
170	31.7	3
135 ^(a)	23.1	4
115	17.8	5
100	13.5	6
90	10.3	7
85	8.5	8
80	6.7	9

(a) Details of \$125/ton calculations are in Table 4.9.

TABLE 4.9. Statistics for Grape Pomace Processing

Total plant investment cost (\$)	- 11,000,000
Plant life (yr)	- 20
Annual taxes and insurance (% capital)	- 2
Annual supplies and maintenance (% capital)	- 1
Plant capacity (gal/d)	- 300,000
Plant capacity factor (%)	- 80
Plant water consumption (g/ton)	- 133
Plant electric consumption (kW/ton)	- 2.0
Biomass (waste) disposal cost (\$/ton)	- 135 for 4-yr payout
Plant steam value (\$/MMBtu)	- 3.5
Water cost (\$/1000 g)	- 0.50
Electricity cost (\$/kWh)	- 0.078
Number of operators per shift	- 1
Shifts per day	- 3
Net salary per operator	- 62,400
Annual Catalyst Cost (\$)	181,300
Annual Water Cost (\$)	2,584
Annual Electric Cost (\$)	144,144
Annual Operator Cost (\$)	374,400
Annual Water Savings (\$)	93,800
Net Disposal Savings (\$)	5,244,750 (Not actual)
Capital Cost (\$/ton/h)	4,130
Simple Payback (yr)	5
Return on Investment (%)	23.1

4.5 SPENT GRAIN

4.5.1 Scope of Potential TEES® Users

Spent grain in the beer brewing industry is the solids separated from the beer after fermentation. Different manufacturers use combinations of barley, rice, and other grains plus hops and yeasts. The moist spent grain comes out of the kettles saturated with liquid and is pressed or centrifuged. The wastewater usually goes to sewer and is subject to COD demand charge and suspended solids charge.

The U.S. brewing industry went into 1988 with a capacity of 221.0 million barrels. This indicates the following annual nationwide potential:

Spent grain - dry tons	850,000
Wastewater - gallons	460 million
TEES® gas (total) - SCF	2.0×10^{10}
TEES® gas (net) - SCF	1.6×10^{10}
(HHV) - therms	89 million
Net therms per dry ton	100 million

This potential is divided by companies as shown in the following Table 4.10.

TABLE 4.10. 1987 Year End Brewing Capacity
(millions of Bbls)

Anheuser-Busch	78.0
Miller	44.0
Heileman	26.0
Stroh	24.5
Coors	16.0
Pabst	11.0
Schmidt	4.3
Genesse	3.3
Pittsburgh	1.2
All others	<u>12.7</u>
	221.0

Source: Beverage Industry, Annual
Manual 1988/89

Some of these companies have multiple plants around the country, usually near population centers.

4.5.2 Scope of Problems

Spent grain is sold for animal feed in both the "as is" form (moist) and dried. Excesses are land-filled, groundspread, and dumped to sewer. Sanitation district landfill tipping fees are about \$20 per ton plus transportation charges of \$3 to \$4 per ton. However, the scenario of vanishing landfills continues.

4.5.3 Capital Costs

Total estimated capital cost for this system is 12.6 million dollars for a 200,000 wet ton (79% H₂O) per year system spent grain. This includes a

feedstock handling installation (Table 4.11) to divert "as is" spent grain from the storage bins to a booster pump and macerator before going to the TEES® module. Also the TEES® gas is dried and the methane and carbon dioxide separated so each can be used in the plant.

• feedstock preparation and handling	\$ 0.12 million
• TEES® process	12.0
• gas drying and separation	<u>0.49</u>
Total	\$12.6 million

The reactors and catalyst account for 48% of the equipment cost.

4.5.4 Operating Costs

For the base case with gas used for feed heat, operating costs are \$1,220,000 per year. Of this, \$250,000 is for operating labor and might be eliminated if the existing operators can absorb the added responsibilities.

4.5.5 Benefits

- avoided cost of purchased carbon dioxide (\$40-\$50/ton)
- avoided cost of part of purchased fuel gas
- avoided sewer charges if spent grain sales fail.

4.5.6 Economic Parameters

This 9% spent grain integrated system would require a net disposal cost of \$110 per dry ton to give a 4-year payout and IRR of 22.5%.

Since landfill and transport would be about \$ (23 + 3) = \$26 per wet ton (79% moisture), this would actually be $\$26 \div .21 = \$124/\text{dry ton}$ for 120 dry tons per day.

Adding in wastewater disposal at \$2,300 per day for 45 gpm (\$19 per dry ton) gives a total of $\$124 + \$19 = \$143$ per dry ton, or about a 3-1/2 year payout (Table 4.12).

The annual disposal cost for 350 days is

$$350 \times 120 \text{ d ton/day} \times \$143/\text{d ton} = \$6,000,000.$$

TABLE 4.11. Capital Costs for Spent Grain Feedstock Preparation and Handling

<u>Item</u>	<u>Equipment</u>	<u>Cost (1990 \$)</u>
1	Process unit storage bin disch line modifications, bin bypass line	4,000
2	Rotary feeder valve (hopper-bottom outlet)	1,000
3	Divertier valve, hopper disch line	500
4	Moyno pump, (primary and spare) flowrate = 86 gpm; head = 20 psi; cast iron, buna-n stator, 50 rpm, 15 hp (2 ea. 15,000)	30,000
5	Weigh feeder (weight measure basis)	17,830
6	Piping	5,000
7	Electrical, Instruments	3,500
8	Structural support for weigh feeder	1,000
9	Concrete foundations (etc. for items 9 and 11)	1,000
10	Installation (items 1 thru 9 @ 25%)	16,000
11	Engineering (items 1 thru 9 @ 10%)	<u>6,400</u>
	Subtotal	86,230
12	Contingency (35%)	<u>30,180</u>
	Total	116,410

TABLE 4.12. Internal Rate of Return and Payout Sensitivity to Disposal Cost for Spent Grain Integrated System

<u>Disposal Cost \$/1000 Gal</u>	<u>IRR - %</u>	<u>Payout - yr</u>
150	31.7	3
110 ^(a)	22.5	4
90	17.5	5
75	13.4	6
65	10.4	7

(a) Details of \$110/ton calculations are in Table 4.13.

TABLE 4.13. Statistics for Spent Grain Processing

9.2% Spent Grain

Total plant investment cost (\$)	- 12,700,000
Plant life (yr)	- 20
Annual taxes and insurance (% capital)	- 2
Annual supplies and maintenance (% capital)	- 1
Plant capacity (gal/d)	- 350,000
Plant capacity factor (%)	- 80
Plant water consumption (g/ton)	- 133
Plant electric consumption (kW/ton)	- 1.5
Biomass (waste) disposal cost (\$/ton)	- 135 for 4-yr payout
Plant steam value (\$/MMBtu)	- 3.5
Water cost (\$/1000 g)	- 1.00
Electricity cost (\$/kWh)	- 0.080
Number of operators per shift	- 1 (shared)
Shifts per day	- 3
Net salary per operator	- 62,400
Annual Catalyst Cost (\$)	254,067
Annual Water Cost (\$)	0
Annual Electric Cost (\$)	121,632
Annual Operator Cost (\$)	312,000
Annual Water Savings (\$)	93,800
Net Disposal Savings (\$)	<u>399,456</u> (Not actual)
Capital Cost (\$/ton/h)	4,410
Simple Payback (yr)	4
Return on Investment (%)	28.3

This would be ample incentive to decrease amount of disposal. Actually, "as is" grain can frequently be sold for animal feed at current prices of \$16 to \$18 per ton, or about \$81 per dry ton.

An income that has not been applied elsewhere is the separated carbon dioxide. This is equivalent to about \$17 per dry ton if displacing purchased CO₂ or half that if sold to a vendor. The street value amounts to \$700,000 per year or \$350,000 if sold to a distributor.

Excess gas costs \$0.65/therm to produce (operating costs + capital cost).

4.6 ORGANIC CHEMICAL WASTE

4.6.1 Scope of Potential TEES® Users

The application chosen for this category is the wastewater for a soap making company in the Caribbean area. The 40,000 COD wastewater has been groundspread in the past, but current regulations mandate that this is stopped soon. COD demand charges escalate at COD levels above 300 mg/L in proportion to the excess.

Although there are numerous chemical producers, blenders, and packagers, a number were contacted without being able to isolate a suitable stream. Most seemed to be variable mixtures with multiple sources. In general, streams were quite dilute with CODs being in the 500 to 5,000 range. This would seem to be a candidate for TEES® only if a plant were facing a severe penalty for disposal or facing shutdown. Therefore no attempt has been made to quantify this source from an energy viewpoint.

4.6.2 Scope of Problems

Most of the streams described above end up being dumped to sewers despite the ever increasing costs. Chemicals defined as "hazardous" are not included in this discussion.

In the past, some have been discharged to streams, the ocean, and to percolation ponds and fields; these sinks are now unpopular and being legislated against in many, if not most, communities.

The cheapest thing for companies to do, in many cases, is to look internally and modify their facilities or practices to recycle, minimize, or eliminate their carryover.

4.6.3 Capital Costs

Total estimated capital cost for this system is 2.5 million dollars. The only extra cost beyond the basic TEES® module is for tankage for two days storage of feedstock and a transfer pump.

The reactor output gas is 50,000 SCF per day of which 62% is used for TEES® fuel. The excess is available for burning with the parent plant's fuel.

- feedstock preparation and handling \$0.5 million
- TEES® process 2.0
- Total \$2.5 million

The reactors and catalyst account for 41% of the total equipment cost.

Capital costs payments over 20 years are \$299,000 annually.

4.6.4 Operating Costs

For the base case with gas used for feed heat, annual operating costs are \$232,000. This case benefits from no labor costs because it is staffed on all three shifts. The addition of the TEES® process with no feedstock handling equipment poses no significant increase in duties.

4.6.5 Benefits

- A wastestream that is no longer permitted to be groundspread can be purified without atmospheric pollution and without increasing the sanitation district load and future taxes.
- Purified wastewater can be 98% recycled into the plant and decrease expenditure for city water.

4.6.6 Economic Parameters

This case comes closer, on its own merits, to showing a normal commercial payout. A positive return is shown in the base case. The IRR is 3.3% and the payout 13 years (Table 4.14).

Intangibles include possible future escalation of sewer charges and possible lower capital costs if feedstock testing justifies less expensive metallurgy. Therefore, the possibility of a 3 or 4 year payout is not impractical (Table 4.15), but finer tuning is not possible without tests in the TEES® evaluation reactors.

TABLE 4.14. Statistics for Organic Chemical Base Case

Organic Chemical

Total plant investment cost (\$)	- 2,520,000
Plant life (yr)	- 20
Annual taxes and insurance (% capital)	- 3
Annual supplies and maintenance (% capital)	- 1
Plant capacity (gal/d)	- 20,000
Plant capacity factor (%)	- 80
Plant water consumption (g/ton)	- 133
Plant electric consumption (kW/1000 gpd)	- 145
Biomass (waste) disposal cost (\$/ton)	- 132
Plant steam value (\$/MMBtu)	- 3.5
Water cost (\$/1000 g)	- 1.00
Electricity cost (\$/kWh)	- 0.125
Number of operators per shift	- 0
Shifts per day	- 3
Net salary per operator	- 62,400
Annual Catalyst Cost (\$)	35,520
Annual Water Cost (\$)	0
Annual Electric Cost (\$)	16,800
Annual Operator Cost (\$)	0
Annual Water Savings (\$)	6,055
Net Disposal Savings (\$)	<u>799,260</u>
Capital Cost (\$/gpd)	145.66
Simple Payback (yr)	13
Return on Investment (%)	3.3

TABLE 4.15. Internal Rate of Return and Payout Sensitivity to Disposal Cost for Organic Chemical Integrated System

<u>Disposal Cost \$/1000 Gal</u>	<u>IRR - %</u>	<u>Payout - yr</u>
275	31.6	3
225	23.2	4
190	16.9	5
170	12.9	6
160	10.7	7
150	8.3	8
145	7.1	9

5.0 REFERENCES

Elliott, D. C., and L. J. Sealock, Jr. 1985. "Low Temperature Gasification of Biomass Under Pressure." In Fundamentals of Thermochemical Biomass Conversion, eds. R. P. Overend, T. A. Milne, and L. K. Mudge, pp. 937-950. Elsevier Applied Science, London.

Elliott, D. C., G. G. Neuenschwander, E. G. Baker, L. J. Sealock, and R. S. Butner. 1991. Low-Temperature Catalytic Gasification of Wet Industrial Wastes FY 1989-1990 Interim Report. PNL-7671, Pacific Northwest Laboratory, Richland, Washington.

Sealock, L. J., Jr., D. C. Elliott, R. S. Butner, and G. G. Neuenschwander. 1988. Low-Temperature Conversion of High-Moisture Biomass: Topical Report January 1984-January 1988. PNL-6726, Pacific Northwest Laboratory, Richland, Washington.

APPENDIX

DETAILS OF CASH FLOW ANALYSIS

CONTENTS

Cheese Whey, 6 wt% Dry Solids, Product Gas Used to Heat Feed	A.1
Estimated Cash Flow Analysis	A.1
Cash Flow Analysis Worksheet Notes	A.2
Calculation of Estimated Cash Flow	A.3
IRR and Payout Calculations	A.5
 Cheese Whey, 6 wt% Dry Solids, Electricity Used to Heat Feed	 A.6
Estimated Cash Flow Analysis	A.6
Cash Flow Analysis Worksheet Notes	A.7
Calculation of Estimated Cash Flow	A.9
IRR and Payout Calculations	A.11
 Grape Pomace, Product Gas Used to Heat Feed	 A.12
Estimated Cash Flow Analysis	A.12
Cash Flow Analysis Worksheet Notes	A.13
Calculation of Estimated Cash Flow	A.15
IRR and Payout Calculations	A.17
 Spent Grain, 9 wt% Dry Solids, Product Gas Used to Heat Feed	 A.18
Estimated Cash Flow Analysis	A.18
Cash Flow Analysis Worksheet Notes	A.19
Calculation of Estimated Cash Flow	A.21
IRR and Payout Calculations	A.23
 Organic Chemical, 4 wt% in Water, Product Gas Used to Heat Feed	 A.24
Estimated Cash Flow Analysis	A.24
Calculation of Estimated Cash Flow	A.25
IRR and Payout Calculations	A.27

TEES PROCESS ESTIMATED CASH FLOW ANALYSIS

WORKSHEET				
APPLICATION 6% Cheese Whey (PRODUCT GAS IS USED TO HEAT THE FEED)				
LOCATION West Coast			\$/GPD	
CAPITAL INVESTMENT (Note 1)		5,100,000	88.85	
(Includes front end preparation but no downstream usage.)				
* License fee (example)		25,000	0.44	
			\$/Yr	\$ per
ANNUAL COSTS:				1000 gal
** Royalty (example) - \$		25,700	(25,700)	(1.23)
				0.00
Supplies, operating - pct of CapInv		1.0	(51,000)	(2.54)
Taxes and insurance - pct of CapInv		2.0	(102,000)	(5.08)
Application Parameters:				
Test gas conversion - SCF/gal		4.5		
Feed volume - gal/day		57,400		
Waste sales value - \$/1000 gal		0.000	0	0.00
Waste disposal cost - \$/1000 gal		129.000	2591610	129.00
Operating days per year		350		
Purchased gas price - \$/therm(Calif)		0.280		
Purchased power price - \$/kw-hr(Calif)		0.079		
Makeup water value - \$/1000 gal		0.300	12,250	0.12
Process Operation:				
Standard volume - gal/day		70,000		
Number of reactors		4		
Catalyst - \$/lb		5.00		
Catalyst life - months assumed		18		
Catalyst bulk density - lb/cuft		74		
Catalyst volume - cuft (all reactors)		226	(55,747)	(2.77)
Gross heat required:				
Feed heater - MMBTU/hr (Note 2,3)		2.1		
Heat loss - MMBTU/hr		0.2		
Produced gas HHV - BTU/SCF		515		
Total gas produced - SCF/day		258,300		
Gas used for heat - SCF/day		107,184		
Excess gas produced - SCF/day		151,116	76,268	3.80
Total power required - kw		88		
Internal pwr recovered - kw		34		
Purchased power - kw		54	(35,361)	(1.75)
Hot water produced - gal/min		0	0	0.00
Steam produced - lb/hr		0	0	0.00
Labor, wkend oprating crew - 1 man/shft/day		3	(74,880)	(3.73)
Labor, maintenance - men/day, 5 day/wk		1	(62,400)	(3.11)
** License value for this example only.				
***Royalty formula may include gpm, total gas produced, separated methane or carbon dioxide, in any combination.				

Onsite*Offsite, Inc.

06/22/90

TEES PROCESS ESTIMATED CASH FLOW ANALYSIS
WORKSHEET
NOTES

.....

1. Capital investment based on 304SS lined reactors and downstream vessels and 304SS downstream piping. Prices as of Jan. 1990.
2. Gas furnishes plant heat.
3. Heat exchange approach is 20 degF.

Onsite RUParts, Inc.

TEES PROCESS 1
CALCULATION
RPM

Plant Life - yrs: 20 Amount Borrowed:
Cost: 5,100,000 Life of Loan
Salvage Value (assumed): 100,000 Simple Interest Rate - 2
Deprec. Life: yrs Payment starts - yr
Deprec. Method: DDB Incl Incl
Incl Line 4 yrs
Incl Line 40 N Fed 1 State

1 Year	2 Book Value	3 Deprec	4 Capital Investment	5 Savings	6 Lost Income	7 Operating Costs
0	5,100,000	729,571	5,125,000	0	0	0
1	4,371,429	1,040,816	0	2,667,878	0	402,107
2	3,530,612	743,440	0	2,667,878	0	402,107
3	2,587,172	621,793	0	2,667,878	0	402,107
4	1,903,329	621,793	0	2,667,878	0	402,107
5	1,343,586	621,793	0	2,667,878	0	402,107
6	771,793	621,793	0	2,667,878	0	402,107
7	100,000	0	0	2,667,878	0	402,107
8	100,000	0	0	2,667,878	0	402,107
9	100,000	0	0	2,667,878	0	402,107
10	100,000	0	0	2,667,878	0	402,107
11				2,667,878	0	402,107
12				2,667,878	0	402,107
13				2,667,878	0	402,107
14				2,667,878	0	402,107
15				2,667,878	0	402,107
16				2,667,878	0	402,107
17				2,667,878	0	402,107
18				2,667,878	0	402,107
19				2,667,878	0	402,107

1. BL end of year

Col 2 = 2 - 3.

Col 3 = Depreciation calculated for Col 2.

Col 5 = Disposal cost + Makeup cost + Excess gas value + Hot water value

Col 6 = Waste sales value.

Col 7 = Energy + Supplies + Local taxes & insurance + Catalyst makeup + Pur

Col 12 = Savings - Lost income - Operating cost - Depreciation.

Col 13 = 12 x 100 / (100 - 2).

Col 14 = Savings - Lost income - Operating cost - Loan payment.

00000000

BANK OF AMERICA
CREDIT CARD FEED BACK

10
11
12
13

0	5	10	15	17	19	19
Reg. Loan End	Simple Interest	Principals Repaid	Total Repaid	Variable Income	Total Income	Cash Flow
2,500,000	250,000	44,140	3,000,000	3,004,000	3,004,000	50,000
3,000,000	300,000	50,190	3,500,000	3,514,000	3,514,000	1,375,000
4,000,000	400,000	65,811	4,065,811	4,021,000	4,021,000	1,250,000
5,000,000	500,000	81,392	4,581,392	4,155,000	4,155,000	1,190,000
6,000,000	600,000	97,950	5,097,950	4,305,000	4,305,000	1,130,000
7,000,000	700,000	115,484	5,615,484	4,475,000	4,475,000	1,070,000
8,000,000	800,000	134,000	6,134,000	4,655,000	4,655,000	1,010,000
9,000,000	900,000	153,500	6,653,500	4,845,000	4,845,000	950,000
10,000,000	1,000,000	174,000	7,174,000	5,045,000	5,045,000	890,000
11,000,000	1,100,000	195,500	7,695,500	5,255,000	5,255,000	830,000
12,000,000	1,200,000	218,000	8,218,000	5,475,000	5,475,000	770,000
13,000,000	1,300,000	241,500	8,741,500	5,705,000	5,705,000	710,000
14,000,000	1,400,000	266,000	9,266,000	5,945,000	5,945,000	650,000
15,000,000	1,500,000	291,500	9,791,500	6,195,000	6,195,000	590,000
16,000,000	1,600,000	318,000	10,318,000	6,455,000	6,455,000	530,000
17,000,000	1,700,000	345,500	10,845,500	6,725,000	6,725,000	470,000
18,000,000	1,800,000	374,000	11,374,000	7,005,000	7,005,000	410,000
19,000,000	1,900,000	403,500	11,903,500	7,295,000	7,295,000	350,000
20,000,000	2,000,000	434,000	12,434,000	7,595,000	7,595,000	290,000
21,000,000	2,100,000	465,500	12,965,500	7,905,000	7,905,000	230,000
22,000,000	2,200,000	498,000	13,498,000	8,225,000	8,225,000	170,000
23,000,000	2,300,000	531,500	14,031,500	8,555,000	8,555,000	110,000
24,000,000	2,400,000	566,000	14,566,000	8,895,000	8,895,000	50,000
25,000,000	2,500,000	601,500	15,101,500	9,245,000	9,245,000	0
26,000,000	2,600,000	638,000	15,638,000	9,605,000	9,605,000	0
27,000,000	2,700,000	675,500	16,175,500	9,975,000	9,975,000	0
28,000,000	2,800,000	714,000	16,714,000	10,355,000	10,355,000	0
29,000,000	2,900,000	753,500	17,253,500	10,745,000	10,745,000	0
30,000,000	3,000,000	794,000	17,794,000	11,145,000	11,145,000	0
31,000,000	3,100,000	835,500	18,335,500	11,555,000	11,555,000	0
32,000,000	3,200,000	878,000	18,878,000	11,975,000	11,975,000	0
33,000,000	3,300,000	921,500	19,421,500	12,405,000	12,405,000	0
34,000,000	3,400,000	966,000	19,966,000	12,845,000	12,845,000	0
35,000,000	3,500,000	1,011,500	20,511,500	13,295,000	13,295,000	0
36,000,000	3,600,000	1,058,000	21,058,000	13,755,000	13,755,000	0
37,000,000	3,700,000	1,105,500	21,605,500	14,225,000	14,225,000	0
38,000,000	3,800,000	1,154,000	22,154,000	14,705,000	14,705,000	0
39,000,000	3,900,000	1,203,500	22,703,500	15,195,000	15,195,000	0
40,000,000	4,000,000	1,254,000	23,254,000	15,695,000	15,695,000	0
41,000,000	4,100,000	1,305,500	23,805,500	16,205,000	16,205,000	0
42,						

bioRxiv preprint doi: <https://doi.org/10.1101/2019.09.04.288000>; this version posted September 4, 2019. The copyright holder for this preprint (which was not certified by peer review) is the author/funder, who has granted bioRxiv a license to display the preprint in perpetuity. It is made available under aCC-BY-NC-ND 4.0 International license.

1. The first group of people who are interested in the study of the history of the United States are the people who are interested in the history of the United States.

TABLE
IRR AND PAYOUT CALCULATIONS

APPLICATION: 6% Cheese Whey
 BASE CASE: Gas used for feed heat
 DISPOSAL COST: 129 \$/1000 GAL
 30 \$/TON

	CASHFLOW FOR IRR	TRIAL IRR	CUMLTVE CASHFLOW	YEAR
1	(5,007,062)	1000	(5,007,062)	1
2	1,373,124		(3,633,938)	2
3	1,250,326		(2,383,612)	3
4	1,197,434		(1,186,178)	4
5	1,192,779		6,601	5
6	1,187,658		1,194,259	6
7	1,182,024		2,376,283	7
8	927,110		3,303,393	8
9	920,294		4,223,687	9
10	912,796		5,136,483	10
11	904,548		6,041,031	11
12	895,475		6,936,506	12
13	885,496		7,822,002	13
14	874,518		8,696,520	14
15	862,442		9,558,962	15
16	849,159		10,408,121	16
17	834,547		11,242,668	17
18	818,475		12,061,143	18
19	800,795		12,861,938	19
20	781,347		13,643,285	20
	"IRR-%"			"PAYOUT- YRS"
	22.5			4
	22.5			

FEED PROCESS ESTIMATED CASH FLOW ANALYSIS

WORKSHEET				
APPLICATION 8% Cheese Whey (ELECTRICITY IS USED TO HEAT THE FEED)				
LOCATION	West Coast		\$/GPD	
CAPITAL INVESTMENT (Note 1)		\$,100,000	\$2.25	
(Includes front end preparation but no downstream usage.)				
* License fee (example)		25,000	0.24	
			\$/Yr	\$ per 1000 gal
ANNUAL COSTS:				
** Royalty (example)	- \$	25,700	(25,700)	(1.23)
				0.00
Supplies, operating	- pct of Capinv	1.0	(\$1,000)	(2.54)
Taxes and insurance	- pct of Capinv	2.0	(102,000)	(5.08)
Application Parameters:				
Test gas conversion	- SCF/gal (note 5)	4.5		
Feed volume	- gal/day	57,400		
Waste sales value	- \$/1000 gal	0.000	0	0.00
Waste disposal cost	- \$/1000 gal	129,000	2591610	129.00
Operating days per year		350		
Purchased gas price	- \$/therm (Calif)	0.280		
Purchased power price	- \$/kw-hr (Calif)	0.073		
Makeup water value	- \$/1000 gal	0.500	12,025	0.61
Process Operation:				
Standard volume	- gal/day	70,000		
Number of reactors		4		
Catalyst	- \$/lb	5.00		
Catalyst life	- months assumed	18		
Catalyst bulk density	- lb/cuft	74		
Catalyst volume	- cuft (all reactors)	226	(55,747)	(2.77)
Gross heat required:				
Feed heater	- MBTU/hr (Note 2,3)	2.1		
Heat loss	- MBTU/hr	0.2		
Produced gas heat	- BTU/SCF	512		
Total gas produced	- SCF/day	258,300		
Gas used for heat	- SCF/day	0		
Excess gas produced	- SCF/day	258,300	130,364	6.49
Total power required				
	- kw	752		
Internal gas recovery	- kw	54		
Purchased power	- kw	723	475,915	23.74
Hot water produced	- gal/min	0	0	0.00
Steam produced	- lb/hr	0	0	0.00
Labor, weekend operating crew	- 1 man/shift/day	3	(74,880)	(3.73)
Labor, maintenance	- men/day, 5 day/wk	1	(52,400)	(2.61)

** License value for this example only.

***Royalty formula may include gpm, total gas produced, separated methane or carbon dioxide, in any combination.

TEES PROCESS ESTIMATED CASH FLOW ANALYSIS
WORKSHEET
NOTES

.....

1. Capital investment based on 304SS lined reactors and downstream vessels and 304SS downstream piping. Prices as of Jan. 1990.
2. Electricity furnishes plant heat.
3. Heat exchange approach is 20 degF.

Onsite*Offsite, Inc.

DISPOSAL COST
TEES PROCESSING
CALCULATION
HP

Plant Life - yrs: 20
Cost: 5,100,000
Salvage Value(assumed?): 100,000
Deprec Life: 7 yrs
Deprec Mode: (dbl) (dbl) (dbl) 3 yrs
Tax rate assumed: 40 % Fed + State
Amount Borrowed:
Life of Loan:
Simple Interest Rate - %
Payment Starts - yr

1 Year	2 Book Value	3 Deprec	4 Capital Investment	5 Savings	6 Lost Income	7 Operating Costs
0	5,100,000	728,571	5,125,000	0	0	0
1	4,371,429	1,040,816	0	2,721,974	0	848,643
2	3,639,612	743,440	0	2,721,974	0	848,643
3	2,907,795	621,793	0	2,721,974	0	848,643
4	2,175,978	621,793	0	2,721,974	0	848,643
5	1,444,161	621,793	0	2,721,974	0	848,643
6	712,344	621,793	0	2,721,974	0	848,643
7	100,000	0	0	2,721,974	0	848,643
8	100,000	0	0	2,721,974	0	848,643
9	100,000	0	0	2,721,974	0	848,643
10	100,000	0	0	2,721,974	0	848,643
11				2,721,974	0	848,643
12				2,721,974	0	848,643
13				2,721,974	0	848,643
14				2,721,974	0	848,643
15				2,721,974	0	848,643
16				2,721,974	0	848,643
17				2,721,974	0	848,643
18				2,721,974	0	848,643
19				2,721,974	0	848,643

* At end of year

Col 2 = 2 - 5.

Col 3 = Depreciation calculated for Col 2.

Col 5 = Disposal cost + Makeup cost + Excess gas value + Hot water value

Col 6 = Waste sales value.

Col 7 = Royalty + Supplies + Local taxes & insur + Catalyst makeup + Pur

Col 12 = Savings - Lost income - Operating cost - Depreciation.

Col 13 = Taxable income * taxrate/100.

Col 14 = Savings - Lost income - Operating cost - Loan payment.

TABLE

129 4/1000 GRL =

50 (\$/TON)

06/28/90

ESTIMATED CASH FLOW ANALYSIS
 OF AN ESTIMATED CASH FLOW
 PROJECTION FOR Cheese Whey

 DATA USED FOR TLED HCHT

5,251,000 (including license \$2
 20
 12
 0

LOAN REPAYMENT SCHEDULE

8	9	10	11	12	13	14
Loan	Simple	Principal	Total Loan	Taxable	Fed + State	Cash
Sal	Interest	Repaid	Payment	Income	Inc Tax	Flow
3,500,500	256,250	44,740	300,990	(984,821)	(393,929)	52,938
3,051,890	505,789	96,192	601,981	326,736	130,690	1,149,660
4,061,698	496,170	105,811	601,981	655,721	253,488	1,017,863
4,055,887	495,589	116,392	601,981	765,950	306,380	964,971
4,050,495	473,950	128,031	601,981	777,589	311,035	950,315
4,045,464	461,146	140,834	601,981	777,589	316,157	955,194
4,040,630	447,063	154,518	601,981	790,392	321,790	949,561
4,036,015	431,571	170,409	601,981	804,475	326,704	944,647
4,031,603	414,530	187,450	601,981	1,441,760	576,704	867,830
4,027,397	395,785	206,195	601,981	1,458,801	583,520	860,332
4,023,397	375,166	226,815	601,981	1,477,546	591,018	852,084
4,019,493	352,484	249,496	601,981	1,498,165	599,266	843,012
4,015,747	327,535	274,446	601,981	1,520,847	608,359	833,032
4,012,101	300,090	301,291	601,981	1,545,797	618,319	822,054
4,008,512	269,901	33,080	601,981	1,573,241	629,296	810,279
4,005,011	239,693	36,308	601,981	1,603,450	641,372	797,609
4,001,645	209,164	40,816	601,981	1,636,638	654,655	784,084
4,000,027	189,985	44,998	601,981	1,673,167	669,267	769,011
4,000,029	169,783	48,198	601,981	1,713,549	685,559	753,541
4,000,031	147,165	53,817	601,981	1,757,548	703,019	737,882
4,000,031	121,681	58,799	601,981	1,806,168	722,467	722,467
4,000,031	10,681	588,799	601,981	1,859,650	743,860	577,491
	6786487	5554115	12340662			

Cost of goods value.

Fixed power & labor.

TABLE
SENSITIVITY CASE: ELECTRICITY USED FOR FEED HEAT

APPLICATION: 6% Cheese Whey
DISPOSAL COST =

129 \$/1000 GAL
30 \$/TON

	CASHFLOW FOR IRR	TRIAL IRR	CUMULATIVE CASHFLOW	YEAR
1	(5,032,062)	10	(5,032,062)	1
2	1,140,660		(3,891,401)	2
3	1,017,862		(2,873,539)	3
4	964,971		(1,908,568)	4
5	960,315		(948,253)	5
6	955,194		6,941	6
7	949,561		956,501	7
8	694,647		1,651,148	8
9	687,830		2,338,978	9
10	680,332		3,019,311	10
11	672,084		3,691,395	11
12	663,012		4,354,407	12
13	653,032		5,007,439	13
14	642,054		5,649,493	14
15	629,979		6,279,472	15
16	616,695		6,896,167	16
17	602,084		7,498,251	17
18	586,011		8,084,262	18
19	568,331		8,652,594	19
20	548,883		9,201,477	20
	"IRR-%"		"PAYOUT- YRS"	
	16.6		5	

TEES PROCESS ESTIMATED CASH FLOW ANALYSIS

WORKSHEET				
APPLICATION	Grape Pomace	(PRODUCT GAS IS USED TO HEAT THE FEED)		
LOCATION	West Coast	\$ / TON / DAY		
CAPITAL INVESTMENT	(Note 1)	11,000,000	99099.10	
(Includes front end preparation but no downstream usage.)				
License fee (example)		25,000	0.10	
			\$ / Yr	\$ per Ton
ANNUAL COSTS:				
* Royalty (example)	- \$	116,550	(116,550)	(3.00)
Supplies, operating	- pct of CapInv	1.0	(110,000)	(2.83)
Taxes and insurance	- pct of CapInv	2.0	(220,000)	(5.66)
Application Parameters:				
Test gas conversion	- SCF/dry lb	11.0		
Feed volume	- gal/day	240,000		
Waste sales value	- \$/dry ton	0.000	0	0.00
Waste disposal cost	- \$/dry ton	135.000	5244750	135.00
Operating days per year		350		
Purchased gas price	- \$/therm(Calif)	0.280		
Purchased power price	- \$/kw-hr(Calif)	0.078		
Makeup water value	- \$/1000 gal	0.500	(2,584)	(0.07)
Process Operation:				
Standard volume	- gal/day	300,000		
Number of reactors		5		
Catalyst	- \$/lb	5.00		
Catalyst life	- months assumed	18		
Catalyst bulk density	- lb/cuft	74		
Catalyst volume	- cuft (all reactors)	735	(181,300)	(4.67)
Gross heat required:				
Feed heater	- MMBTU/hr (Note 2,3)	8.6		
Heat loss	- MMBTU/hr	0.9		
Produced gas HHV	- BTU/SCF	454		
Total gas produced	- SCF/day	2,442,000		
Gas used for heat	- SCF/day	502,203		
Excess gas produced	- SCF/day	1,939,797	863,055	22.22
Total power required	- kw	360		
Internal pwr recoverd	- kw	140		
Purchased power	- kw	220	(144,144)	(1.72)
Hot water produced	- gal/min	0	0	0.00
Steam produced	- lb/hr	0	0	0.00
Labor, oper - 2 shifts/1 man - 1 shift/2 men		5	(312,000)	(3.71)
Labor, maintenance - men/day, 5 day/wk		1	(62,400)	(0.74)

* Royalty formula may include gpm, total gas produced, separated methane or carbon dioxide, in any combination.

TEES PROCESS ESTIMATED CASH FLOW ANALYSIS
WORKSHEET
NOTES

-
1. Capital investment based on 304SS lined reactors and downstream vessels and 304SS downstream piping. Prices as of Jan. 1990.
 2. Gas furnishes plant heat.
 3. Heat exchange approach is 20 degF.

Onsite*Offsite, Inc.

TEES PROCESS &
CALCULATION
APP

Plant Life - yrs: 20 Amount Borrowed: 1
Cost: 11,000,000 Life of Loan
Salvage Value (assumed): 100,000 Simple Interest Rate - %
Deprec. Life: 7 yrs Payment Starts - yr
Deprec. Method: DBI Dbl Bal 3 yrs
Str. Line 4 yrs
Tax rate assumed: 40 % Fed + State

1 Year	2* Book Value	3 Deprec	4 Capital Investment	5 Savings	6 Lost Income	7 Operating Costs	8
0	11,000,000	1,571,429	11,025,000	0	0	0	0
1	9,428,571	2,244,898	0	6,107,805	0	1,148,978	10
2	7,183,673	1,603,499	0	6,107,805	0	1,148,978	10
3	5,580,175	1,370,044	0	6,107,805	0	1,148,978	10
4	4,310,131	1,370,044	0	6,107,805	0	1,148,978	10
5	2,840,087	1,370,044	0	6,107,805	0	1,148,978	10
6	1,470,044	1,370,044	0	6,107,805	0	1,148,978	10
7	100,000	0	0	6,107,805	0	1,148,978	10
8	100,000	0	0	6,107,805	0	1,148,978	10
9	100,000	0	0	6,107,805	0	1,148,978	10
10	100,000	0	0	6,107,805	0	1,148,978	10
11				6,107,805	0	1,148,978	10
12				6,107,805	0	1,148,978	10
13				6,107,805	0	1,148,978	10
14				6,107,805	0	1,148,978	10
15				6,107,805	0	1,148,978	10
16				6,107,805	0	1,148,978	10
17				6,107,805	0	1,148,978	10
18				6,107,805	0	1,148,978	10
19				6,107,805	0	1,148,978	10

* At end of year

Col 2 = 2 - 3.

Col 3 = Depreciation calculated for Col 2.

Col 5 = Disposal cost + Makeup cost + Excess gas value + Hot water value

Col 6 = Waste sales value.

Col 7 = Royalty + Supplies + Local taxes & insur + Catalyst makeup + Purch

Col 12 = Savings - Lost income - Operating cost - Depreciation.

Col 13 = Taxable income * Taxrate/100.

Col 14 = Savings - Lost income - Operating cost - Loan payment.

TABLE

06/22/90

ESTIMATED CASH FLOW ANALYSIS
N OF ESTIMATED CASH FLOW
LOCATION: Grape Pomace

=====

USED FOR FEED MEAT

=====

,005,000 (including License 4)

20

12

0

CASH FLOW ANALYSIS

8	9	10	11	12	13	14
Eq Loan	Simple Interest	Principal Repaid	Total Loan Payment	Tangible Income	Fed + State Inc Tax	Cash Flow
512,500	551,350	96,246	547,496	2,122,679	849,071	201,575
889,631	1,089,063	206,829	1,294,992	1,625,866	650,346	3,013,480
673,701	1,061,570	227,622	1,289,992	2,287,958	915,183	2,748,651
446,029	1,044,608	250,304	1,294,992	3,544,175	1,017,670	2,646,165
195,699	1,019,569	275,425	1,294,992	2,569,214	1,027,686	2,636,149
920,272	992,027	302,965	1,294,992	2,596,756	1,038,702	2,625,132
617,307	961,731	338,062	1,294,992	2,627,053	1,050,821	2,613,014
284,045	928,405	366,588	1,294,992	4,050,423	1,612,169	2,051,666
912,457	891,746	405,247	1,294,992	4,062,081	1,626,033	2,037,003
514,211	851,721	443,521	1,294,992	4,107,406	1,642,962	2,020,822
070,659	807,664	482,828	1,294,992	4,151,763	1,660,705	2,003,129
582,711	758,221	520,221	1,294,992	4,200,556	1,680,222	1,983,612
045,989	704,599	560,393	1,294,992	4,254,226	1,701,631	1,962,143
455,896	645,560	600,453	1,294,992	4,313,268	1,725,307	1,938,528
306,163	589,616	714,576	1,294,992	4,378,211	1,751,384	1,912,550
091,267	529,179	795,813	1,294,992	4,449,648	1,779,059	1,883,975
305,724	459,597	914,595	1,294,992	4,528,250	1,811,292	1,852,543
441,579	384,158	996,852	1,294,992	4,614,609	1,845,868	1,817,967
490,244	309,074	1,049,918	1,294,992	4,709,753	1,883,901	1,779,934
444,026	146,485	1,150,510	1,294,992	4,814,544	1,925,738	1,738,092
294,316	29,452	1,265,561	1,294,992	4,929,595	1,971,758	1,692,077

14549732.26 11948121.18 26547543.44						

Steam value,

used power + labor.

TABLE
IRR AND PAYOUT CALCULATIONS

APPLICATION: Grape Pomace
 BASE CASE: Gas used for feed heat
 DISPOSAL COST = 135 \$ per ton

	CASHFLOW FOR IRR	TRIAL IRR	CUMLTVE CASHFLOW	YEAR
1	(10,798,425)	1000	(10,798,425)	1
2	3,013,488		(7,784,936)	2
3	2,748,651		(5,036,285)	3
4	2,646,165		(2,390,120)	4
5	2,636,149		246,029	5
6	2,625,132		2,871,161	6
7	2,613,014		5,484,175	7
8	2,051,666		7,535,840	8
9	2,037,002		9,572,843	9
10	2,020,872		11,593,715	10
11	2,003,129		13,596,844	11
12	1,983,612		15,580,457	12
13	1,962,143		17,542,600	13
14	1,938,528		19,481,128	14
15	1,912,550		21,393,678	15
16	1,883,975		23,277,654	16
17	1,852,543		25,130,197	17
18	1,817,967		26,948,164	18
19	1,779,934		28,728,097	19
20	1,738,097		30,466,194	20
	"IRR-%"			"PAYOUT- YRS
	23.1			4
	23.1			

TEES PROCESS ESTIMATED CASH FLOW ANALYSIS

WORKSHEET

APPLICATION	9.2% SpentGrain (PRODUCT GAS IS USED TO HEAT THE FEED)			
LOCATION	West Coast			\$/TON/DAY
CAPITAL INVESTMENT	(Note 1)	12,700,000	105833.33	
(Including front end preparation, membrane separator, and product methane filter/coalescer.)				
License fee (example)		25,000	0.09	\$ per
			\$/Yr	Ton
ANNUAL COSTS:				
* Royalty (example)	- \$	150,000	(150,000)	(3.57)
Supplies, operating	- pct of CapInv	1.0	(127,000)	(3.02)
Taxes and insurance	- pct of CapInv	2.0	(254,000)	(6.05)
Application Parameters:				
Test gas conversion	- SCF/dry lb	11.7		
Feed volume	- gal/day	284,000		
Waste sales value	- \$/dry ton	81.000	-3402000	(81.00)
Waste disposal cost	- \$/dry ton	135.000	5670000	135.00
Operating days per year		350		
Purchased gas price	- \$/therm(Calif)	0.350		
Purchased power price	- \$/kw-hr(Calif)	0.080		
Makeup water value	- \$/1000 gal	1.000	0	0.00
Process Operation:				
Standard volume	- gal/day	350,000		
Number of reactors		7		
Catalyst	- \$/lb	5.00		
Catalyst life	- months assumed	18		
Catalyst bulk density	- lb/cuft	74		
Catalyst volume	- cuft (all reactors)	1030	(254,067)	(6.05)
Gross heat required:				
Feed heater	- MMBTU/hr (Note 2,3)	12.3		
Heat loss	- MMBTU/hr	1.2		
Produced gas HHV	- BTU/SCF	550		
Total gas produced	- SCF/day	2,808,000		
Gas used for heat	- SCF/day	589,091		
Excess gas produced	- SCF/day	2,218,909	1,494,990	35.59
Total power required	- kw	370		
Internal pwr recoverd	- kw	189		
Purchased power	- kw	181	(121,632)	(1.22)
Hot water produced	- gal/min	0	0	0.00
Steam produced	- lb/hr	0	0	0.00
Labor, oper - 1 extra man each shift		4	(249,600)	(2.51)
Labor, maintenance - man years/year		1	(62,400)	(0.63)

Royalty formula may depend on gpm, total gas produced,
separated methane, carbon dioxide, or capacity.

Onsite*Ofsite, Inc.

06/28/90

TEES PROCESS ESTIMATED CASH FLOW ANALYSIS
WORKSHEET
NOTES

-
1. Capital investment based on 304SS lined reactors and downstream vessels and 304SS downstream piping. Prices as of Jan. 1990.
 2. Gas furnishes plant heat.
 3. Heat exchange approach is 20 degF.

Onsite Offsite, Inc.

TEES PROCESSES
CIRCUIT
HP
22
GH
17

Plant life - yrs: 20 Amount Borrowed: 1
Cost: 12,700,000 Life of loan
Salvage Value (assumed): 100,000 Simple Interest Rate: 2
Depreciated: 0 pp Payment 5.00%
Depreciated: 0 pp
Depreciated: 4 pp
Depreciated: 40 pp

1 Year	2 Foot Value	3 Deprec	4 Capital Investment	5 Savings	6 Lost Income	7 Operating Costs
0	12,700,000	1,814,286	12,725,000	0	0	0
1	10,885,714	2,591,937	0	164,990	(214,000)	1,218,699
2	8,293,878	1,891,312	0	164,990	(214,000)	1,218,699
3	6,442,566	1,585,641	0	164,990	(214,000)	1,218,699
4	4,856,924	1,585,641	0	164,990	(214,000)	1,218,699
5	3,271,283	1,585,641	0	164,990	(214,000)	1,218,699
6	1,685,641	1,585,641	0	164,990	(214,000)	1,218,699
7	100,000	0	0	164,990	(214,000)	1,218,699
8	100,000	0	0	164,990	(214,000)	1,218,699
9	100,000	0	0	164,990	(214,000)	1,218,699
10	100,000	0	0	164,990	(214,000)	1,218,699
11				164,990	(214,000)	1,218,699
12				164,990	(214,000)	1,218,699
13				164,990	(214,000)	1,218,699
14				164,990	(214,000)	1,218,699
15				164,990	(214,000)	1,218,699
16				164,990	(214,000)	1,218,699
17				164,990	(214,000)	1,218,699
18				164,990	(214,000)	1,218,699
19				164,990	(214,000)	1,218,699

* At end of year

Col 2 = 2 - 3.

Col 3 = Depreciation calculated for book.

Col 5 = Disposal cost + Makeup cost + Salvage value + Hot water value.

Col 6 = Waste sales value.

Col 7 = Royalty + Supplies + Local taxes + minor + Capitalized makeup + Purchase.

Col 12 = Savings + Lost income + Operating cost + Depreciation.

Col 13 = Savings + Lost income * 100/100.

Col 14 = Savings + Lost income + Operating cost + Loan payment.

TABLE
IRR AND PAYOUT CALCULATIONS

APPLICATION: 9.2% Spent Grain
 BASE CASE: Gas used for feed heat
 DISPOSAL COST = 135 \$ per ton

	CASHFLOW FOR IRR	TRIAL IRR	CUMLTVE CASHFLOW	YEAR
1	(12,467,123)	1000	(12,467,123)	1
2	4,040,571		(8,426,552)	2
3	3,734,807		(4,691,745)	3
4	3,618,030		(1,073,715)	4
5	3,606,470		2,532,756	5
6	3,593,755		6,126,510	6
7	3,579,768		9,706,278	7
8	2,930,125		12,636,403	8
9	2,913,200		15,549,603	9
10	2,894,583		18,444,187	10
11	2,874,105		21,318,292	11
12	2,851,578		24,169,870	12
13	2,826,799		26,996,669	13
14	2,799,542		29,796,210	14
15	2,769,559		32,565,769	15
16	2,736,578		35,302,347	16
17	2,700,298		38,002,645	17
18	2,660,391		40,663,037	18
19	2,616,493		43,279,530	19
20	2,568,206		45,847,735	20
	"IRR-%"			"PAYOUT- YRS
	28.3			4
	28.3			

TEES PROCESS ESTIMATED CASH FLOW ANALYSIS

WORKSHEET				
APPLICATION	4% Organic Chem	(PRODUCT GAS IS USED TO HEAT THE FEED)		
LOCATION	Caribbean area		\$/GPD	
CAPITAL INVESTMENT (Note 1)		2,520,000	145.66	
(Includes front end preparation but no downstream usage.)				
License fee (example)		25,000	1.45	
			\$/Yr	\$ per
ANNUAL COSTS:				1000 gal
* Royalty (example)	- \$	80,000	(80,000)	(13.21)
				0.00
Supplies, operating	- pct of CapInv	1.0	(25,200)	(4.16)
Taxes and insurance	- pct of CapInv	3.0	(75,600)	(12.49)
Application Parameters:				
** Gas conversion	- SCF/gal	7.9		
Feed volume	- gal/day	17,300		
Waste sales value	- \$/1000 gal	0.000	0	0.00
Waste disposal cost	- \$/1000 gal	132.000	799,260	132.00
Operating days per year		350		
Purchased gas price	- \$/therm	0.350		
Purchased power price	- \$/kw-hr	0.125		
Makeup water value	- \$/1000 gal	1.000	6,055	1.00
Process Operation:				
Standard volume	- gal/day	20,000		
Number of reactors		2		
Catalyst	- \$/lb	10.00		
Catalyst life	- months assumed	18		
Catalyst bulk density	- lb/cuft	74		
Catalyst volume	- cuft (all reactors)	72	(35,520)	(5.87)
Gross heat required:				
Feed heater	- MMBTU/hr	0.62		
Heat loss	- MMBTU/hr	0.06		
Produced gas HHV	- BTU/SCF	515		
Total gas produced	- SCF/day	50,170		
Gas used for heat	- SCF/day	31,689		
Excess gas produced	- SCF/day	18,481	11,659	1.93
Total power required	- kw	26		
Internal pwr recoverd	- kw	10		
Purchased power	- kw	16	(16,800)	(2.77)
Hot water produced	- gal/min	0	0	0.00
Steam produced	- lb/hr	0	0	0.00
Labor, operating (existing personnel)		0	0	0.00
Labor, maintenance (existing personnel)		0	0	0.00
* Royalty formula may depend on gpm, total gas produced, separated methane and/or carbon dioxide, or installed capacity, depending on application.				

TAB

Onsite*Offsite, Inc.

TEES PROCESS ESTIMATE
CALCULATION OF L
APPLICATION*****
GAS USED

Plant Life - yrs: 20 Amount Borrowed: 2,545,000
 Cost: 2,520,000 Life of Loan
 Salvage Value (assumed): 100,000 Simple Interest Rate = 2
 Deprec. Life: 7 yrs Payment Starts - yr
 Deprec. Mode: Old Del Bal 3 yrs
 Str Line 4 yrs
 Rate assumed: 40 % Fed + State

1 Year	2* Book Value	3 Deprec	4 Capital Investment	5 Savings	6 Lost Income	7 Operating Costs	8 Avg Loan Bal
0	2,520,000	360,000	2,545,000	0	0	0	1,272,500
1	2,160,000	514,286	0	816,974	0	233,120	2,511,250
2	1,845,714	367,347	0	816,974	0	233,120	2,463,250
3	1,528,567	294,592	0	816,974	0	233,120	2,411,250
4	983,776	294,592	0	816,974	0	233,120	2,353,250
5	689,184	294,592	0	816,974	0	233,120	2,289,250
6	394,592	294,592	0	816,974	0	233,120	2,220,250
7	100,000	0	0	816,974	0	233,120	2,143,250
8	100,000	0	0	816,974	0	233,120	2,058,250
9	100,000	0	0	816,974	0	233,120	1,965,250
10	100,000	0	0	816,974	0	233,120	1,863,250
11				816,974	0	233,120	1,750,250
12				816,974	0	233,120	1,626,250
13				816,974	0	233,120	1,490,250
14				816,974	0	233,120	1,340,250
15				816,974	0	233,120	1,175,250
16				816,974	0	233,120	993,250
17				816,974	0	233,120	794,250
18				816,974	0	233,120	574,250
19				816,974	0	233,120	333,250
				816,974	0	233,120	67,250

* At end of year

Col 2 = 2 - 3.

Col 3 = Depreciation calculated for Col 2.

Col 5 = Disposal cost + Makeup cost + Excess gas value + Hot water value + Steam

Col 6 = Waste sales value.

Col 7 = Royalty + Supplies + Local taxes & insur + Catalyst makeup + Purchased

Col 12 = Savings - Lost income - Operating cost - Depreciation.

Col 13 = Taxable income * Tax rate/100.

Col 14 = Savings - Lost income - Operating cost - Loan payment.

06/27/00

POLYMER LETTERS

00 C++ Language 36
20
10
0

n	9 Simple Interest	10 Principal Repaid	11 Total Loan Payment	12 Taxable Income	13 Fed + State Inc Tax	14 Cash Flow
00	127,150	22,217	149,467	(482,350)	(194,900)	45,433
04	254,167	42,787	296,935	(481,999)	(72,640)	357,559
07	346,591	52,544	298,935	(29,884)	(11,953)	296,873
08	341,136	53,790	298,935	48,126	19,350	265,669
09	239,356	63,578	298,935	53,506	21,582	263,352
10	236,999	69,936	298,935	60,364	24,105	260,814
11	232,005	76,930	298,935	67,257	26,903	258,016
12	213,517	84,623	298,935	369,142	147,817	137,103
13	209,850	93,085	298,935	378,904	151,202	133,718
14	199,541	102,594	298,935	382,513	154,925	129,499
15	186,702	112,633	298,935	392,542	159,021	125,899
16	175,939	123,396	298,935	408,345	163,526	121,399
17	167,649	136,296	298,935	421,105	168,482	116,437
18	149,620	149,913	298,935	434,334	173,933	110,996
19	154,620	164,906	298,935	449,335	179,930	104,989
20	117,530	181,396	298,935	466,16	186,526	90,393
21	99,399	199,536	298,935	484,155	193,782	91,157
22	79,445	219,490	298,935	504,109	201,764	85,156
23	57,496	241,439	298,935	526,558	210,543	74,379
24	33,452	265,583	298,935	550,502	220,201	64,719
25	6,294	292,141	298,935	577,560	230,824	54,095
<hr/>						
	33,00669,201	2358092,373	6129163,213			

summary + literature

TABLE
IRR AND PAYOUT CALCULATIONS

APPLICATION: 4% Organic Chemical
 BASE CASE: Gas used for feed heat
 DISPOSAL COST: 132 \$/1000 GAL

	CASHFLOW FOR IRR	TRIAL IRR	CUMLTVE CASHFLOW	YEAR
1	(2,474,567)	10	(2,474,567)	1
2	357,559		(2,117,008)	2
3	296,873		(1,820,136)	3
4	265,669		(1,554,467)	4
5	263,357		(1,291,110)	5
6	260,814		(1,030,296)	6
7	258,016		(772,280)	7
8	137,102		(635,177)	8
9	133,718		(501,460)	9
10	129,994		(371,466)	10
11	125,898		(245,567)	11
12	121,393		(124,174)	12
13	116,437		(7,737)	13
14	110,986		103,249	14
15	104,989		208,238	15
16	98,393		306,631	16
17	91,137		397,768	17
18	83,156		480,924	18
19	74,376		555,300	19
20	64,719		620,018	20
	"IRR-%"			"PAYOUT- YRS
	3.3			13
	3.3			

DISTRIBUTION

No. of
Copies

No. of
Copies

OFFSITE

R. Moorer
Biofuels Systems Division
U.S. Department of Energy
Forrestal Building (CE-341)
1000 Independence Avenue
Washington, DC 20585

S. L. Natof
Waste Material Management
Division
Forrestal Building (CE-222)
1000 Independence Avenue
Washington, DC 20585

12 DOE/Office of Scientific and
Technical Information

M. J. Antal
Department of Mechanical
Engineering
University of Hawaii
2540 Dole Street
Honolulu, HI 96822

R. E. Bailey
Kraft Food
2211 Sanders Road
Northbrook, IL 60062

N. G. Banns
Onsite*Offsite, Inc.
2500 E. Foothills Boulevard
Suite 201
Pasadena, CA 91107

S. P. Barone
Gas Research Institute
8600 West Bryn Mawr Avenue
Chicago, IL 60631

R. Beale
Vice President, Operations
Lamb-Weston
P.O. Box C 1900
Tri-Cities, WA 99302

H. W. Ewart
Tree Top, Inc.
Technical Center
111 S. Railroad Avenue
P.O. Box 248
Selah, WA 98942

I. Feins
Engelhard Corporation
101 Wood Avenue
Iselin, NJ 08830

B. Goodman
National Renewable Energy
Laboratory
1617 Cole Boulevard
Golden, CO 80401

B. Haley
Miller Brewing Company
651 N. 39th Street
Milwaukee, WI 53233

W. M. McKinney
United Catalysts, Inc.
P.O. Box 32370
Louisville, KY 40302

H. Meyer
Gas Research Institute
8600 West Bryn Mawr Avenue
Chicago, IL 60631

No. of
Copies

C. R. Nelson
Gas Research Institute
8600 West Bryn Mawr Avenue
Chicago, IL 60631

R. Overend
National Renewable Energy
Laboratory
1617 Cole Boulevard
Golden, CO 80401

M. A. Paisley
Battelle-Columbus Division
505 King Avenue
Columbus, OH 43201

J. Pereira
Process Development and
Optimization Center
Corporate Research and
Development
Anheuser-Busch Companies, Inc.
Executive Offices
One Busch Place
St. Louis, MO 63118

R. Radford
Ocean Spray Cranberries, Inc.
P.O. Box 195
Markham Star Route
Aberdeen, WA 98520

10 T. H. Scheer
Onsite*Offsite, Inc.
2500 E. Foothills Boulevard
Suite 201
Pasadena, CA 91107

G. Simons
California Energy Commission
1516 - 9th Street, MS-43
Sacramento, CA 95801

D. J. Stevens
Cascade Research, Inc.
2952 George Washington Way
Richland, WA 99352

No. of
Copies

R. J. Weisskirchen
The Blitz-Weinhard Brewing
Company
1133 West Burnside Street
Portland, OR 97209

FOREIGN

A. Bridgwater
Energy Research Group
Aston University
Birmingham B4 7ET
UNITED KINGDOM

E. Hogan
Bioenergy Division
Energy, Mines and Resources
580 Booth Street
Ottawa, Ontario K1A 0E4
CANADA

K. Mackie
Forest Research Institute
Private Bag 3020
Rotorua
NEW ZEALAND

D. San Filippo
Research Division
Shamprogetti
20097 S. Donato Milanese
Milan
ITALY

K. Sipilä
Technical Research Centre
of Finland
Laboratory of Fuel and
Process Technology
P.O. Box 205
SF-02151 Espoo
FINLAND

No. of
Copies

DOE Richland Field Office

D. R. Segna, A5-90

24 Pacific Northwest Laboratory

E. G. Baker, K2-12

R. S. Butner, K2-12

D. C. Elliott, K2-12 (10)

No. of
Copies

E. A. Eschbach, K1-24

S. R. Gano, K2-12

D. K. Hilliard, K2-12

G. G. Neuenschwander, K2-12

L. J. Sealock, Jr., K2-10

L. D. Williams, K1-41

Publishing Coordination

Technical Report Files (5)

END

**DATE
FILMED**

3 / 25 / 92