285②

PREPARED FOR THE U.S. DEPARTMENT OF ENERGY,
UNDER CONTRACT DE-AC02-76-CHO-3073

PL-2813
-426

PPPL-2813

FAST-ION RADIAL DIFFUSIVITY EVALUATED FROM VERTICAL NEUTRAL
RTICLE MEASUREMENTS FOLLOWING SHORT PULSE BEAM INJECTION INTO
A TFTR OHMIC PLASMA

BY

Y. KUSAMA, ET AL.

January 1992

PPPL
PRINCETON
PLASMA PHYSICS
LABORATORY

NOTICE

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial produce, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

NOTICE

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the:

Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831;
Prices available from (615) 576-8401.

Available to the public from the:

National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, Virginia 22161
703-487-4650

Fast-Ion Radial Diffusivity Evaluated from Vertical Neutral Particle Measurements following Short Pulse Beam Injection into a TFTR Ohmic Plasma

Y. Kusama¹, W. W. Heidbrink², Cris W. Barnes³, M. Beer, G. W. Hammett, D. C. McCune, S. S. Medley, S. D. Scott, and M. C. Zarnstorff

Plasma Physics Laboratory
Princeton University
Princeton, NJ 08543

PPPL--2813

DE92 006645

Abstract

The radial diffusivity of fast ions was evaluated from vertical neutral particle measurements in experiments where a short pulse of neutral deuterium beams was injected into a TFTR ohmic deuterium plasma. A comparison between the temporal evolution of the measured neutral particle flux and theoretical calculations showed that the spatially-averaged diffusion coefficient of fast ions is $\leq 0.1 \text{ m}^2/\text{sec}$. This value is approximately an order of magnitude less than the diffusion coefficient for thermal ions and is consistent with results obtained previously on TFTR from other diagnostics.

Permanent Address:

- ¹ Naka Fusion Research Establishment, Japan Atomic Energy Research Institute, Naka-machi, Naka-gun, Ibaraki-ken, 311-01 Japan.
- ² University of California, Irvine, CA 92717, USA.
- ³ Los Alamos National Laboratory, Los Alamos, NM 87545, USA.

MASTER

EP

1. Introduction

In heat transport studies, it has been assumed that the fast ions behave classically and have zero radial diffusion. It is important, however, to obtain detailed measurements of radial transport of fast ions in order to characterize the heat transport more accurately. Moreover, radial transport of the fast ions is one of the key issues in the transition from L-mode to an improved confinement regime. For example, the high-performance supershot plasmas in TFTR require a high density concentration of beam-produced fast ions in order to be sustained. Whether alpha particles behave classically or anomalously is one of the important issues for achieving ignition in a magnetic fusion device, because the concept relies on substantial heating of the plasma by fusion-product alpha particles as they slow down classically. Therefore, studying the slowing-down and transport properties of energetic ions, including fusion-produced ions, is important in contemporary large tokamaks.

The radial diffusion of energetic ions has been studied using several methods of diagnostic measurement in tokamaks. Tangential charge-exchange measurements during low-power tangential neutral beam injection in TFTR showed that the inward radial diffusivity of passing ions was $\leq 0.10 \pm 0.05 \text{ m}^2/\text{sec}$ [1, 2]. Triton burnup measurements in TFTR supershots showed that the triton radial diffusivity was $\leq 0.05 \text{ m}^2/\text{sec}$ [3]. A triton diffusivity of $0.10 \pm 0.05 \text{ m}^2/\text{sec}$ has been suggested also in JET by comparing the measured 14 MeV neutron emission rate with calculations including the triton diffusion [4].

Short neutral beam pulse experiments were carried out on DIII-D [5, 6] to investigate the slowing-down properties of beam ions. Similar experiments were done on TFTR to study the fast-ion radial diffusivity and the results have been reported by Heidbrink et al. [7]. This report presents additional information on the neutral flux measurements from the vertically viewing charge-exchange neutral particle analyzers and on the results obtained by comparing the data with a theoretical calculation in which an empirical, spatially constant, diffusion coefficient for the energetic beam ions can be included.

2. Neutral Particle Measurements and other Diagnostics

Two vertically-viewing, mass-resolved, charge-exchange neutral particle analyzers [8, 9] were used to measure the charge-exchange flux produced by tangentially injected beam ions. The sightlines correspond to a major radius of $R = 2.44$ m for one analyzer (EV4) and $R = 2.97$ m for the other analyzer (EV6) as shown in Fig. 1. Due to the geometry, these analyzers only observe banana-trapped ions. Figure 2 shows the relation between the analyzer sightlines and the beam injection lines as a function of major radius. The pitch angle on a magnetic surface of the particles detected by the analyzers was calculated analytically from conservation of energy and magnetic momentum. The pitch angles of fast ions produced by neutral beam injection were calculated from the tangency radii of the beam lines and mapped onto the horizontal plane of the same magnetic surface. The pitch angle which is detectable by each of the EV4 and EV6 charge-exchange analyzers at the respective minor radius, r , is mapped at $R = R_0 + r$. It has been assumed in this calculation that the magnetic axis is located at $R = 2.44$ m and the

magnetic surfaces are coaxial and circular. The horizontal direction in the figure corresponds to radial diffusion of ions while the vertical direction corresponds to pitch angle scattering. This figure indicates that ions must undergo some pitch-angle scattering from the orbit they were initially deposited on before they can be detected by the charge-exchange analyzers. Analyzer EV6, in particular, is sensitive only to deeply-trapped banana particles outside of $r/a \geq 0.8$.

For the calculation of the expected behavior of the charge-exchange signal, the temporal evolution of the electron density profile was obtained from Abel inversion of the line densities measured by a 10-channel vertical interferometer. The electron temperature profile was measured by electron cyclotron emission using the Michelson interferometer (with values generally in agreement with the radiometer measurements). H_{α} line intensities were monitored by a poloidal array of absolutely calibrated detectors with filters. The neutral density was calculated assuming a wall source proportional to the poloidal average of the H_{α} light.

3. Experimental Results

Figure 3 shows typical waveforms (#49113) for neutral beam power, central electron density, central electron temperature and total stored energy. The plasma current was $I_p = 0.8$ MA and the toroidal field was $B_T = 4$ T. Deuterium neutral beams ($P_b \sim 20$ MW, $E_b \sim 90$ keV) of 20 ms pulse length were injected into an ohmic deuterium plasma at 3.004 sec. The tangency radii of the beams were 1.73 m, 1.99 m, and 2.05 m parallel to the plasma current, and -1.99 m and -2.32 m anti-parallel to the plasma current. Except for the region $r/a \geq 0.8$, the beam ions are born on passing orbits. Since the

line-averaged electron density of the target plasma was $\sim 0.7 \times 10^{19} \text{ m}^{-3}$, the beam ions are deposited with a centrally peaked profile. As shown in Fig. 3, the central electron density and temperature were perturbed by 20% and 8%, respectively, due to the beam injection. Z_{eff} was 4.1 ± 0.2 in this series of discharges. For these plasma parameters, the Spitzer slowing-down time for the deuterium beam ions in the plasma core is $\tau_s \sim 1.5 \text{ sec}$, and the central pitch-angle scattering time is $\tau_d \sim 0.55 \text{ sec}$. For the same discharge as shown in Fig. 3, the time evolution of the neutral flux at 30 keV and 50 keV which was measured by the two analyzers are shown in Fig. 4. Analyzers EV4 and EV6 correspond to $r/a \sim 0.05$ and 0.60 , respectively, where $a = 0.8 \text{ m}$. The raw data which are shown by the dotted curves include the background noise from neutrons and plasma light. A maximum neutron emission rate of $7.5 \times 10^{13} \text{ n/sec}$ was observed just after the beam blip which exhibited an e-folding decay time of $\sim 0.15 \text{ sec}$. The neutron emission rate was so low that the neutron noise on analyzers was negligible. Background noise due to plasma light was corrected by the following procedure. The light noise, $F_n(t)$, was obtained by averaging the measurements from three anodes (# 67, 69, and 71) of the microchannel plate detector above the injection energy where no significant particle signal was observed. Prior to neutral beam injection, the time-averaged noise ratios, $S_n(E)$, were determined by $S_n(E) = \overline{F(E,t)} / \overline{F_n(t)}$, where $F(E,t)$ was the count rate including noise. During this period, no significant neutral particle flux was detected in the detector channels for energies above 25 keV. Under the assumption that $S_n(E)$ is constant throughout a discharge, the noise-corrected neutral flux during beam injection was evaluated by $F_{nc}(E,t) = F(E,t) - S_n(E)F_n(t)$ and the error was defined as $S_n(E)F_n(t) / |F_{nc}(E,t)|$. In Fig. 4, the noise-corrected signals are shown by a solid line with error bars.

The uncertainties are small in the initial phase, but increase with time due to the decay of fast ion signal.

4. Data Analysis and Discussion

The measured temporal behavior of the charge-exchange fluxes was analyzed with the time dependent transport analysis and diagnostics simulation code, TRANSP [10] using the measured temperature and density profiles. For calculation of the fast ion distribution in velocity space from which the charge-exchange neutral flux was obtained, a Fokker-Planck model [11] was used instead of the usual Monte Carlo model in order to reduce statistical noise in the results. The edge hydrogenic neutral influx was inferred from the poloidal average of the H_α line intensities (as opposed to the common assumption of a constant particle confinement). Z_{eff} was assumed to be radially uniform.

The radial diffusion of the fast ions is evaluated by

$$\frac{\partial}{\partial t} f(E, \mu, r, t) = \frac{1}{r \tau_B(E, \mu, r)} \frac{\partial}{\partial r} [r \tau_B D_{\text{fast}} \frac{\partial f}{\partial r}] + C(f) + S \quad (1)$$

where D_{fast} is the fast ion diffusivity. $f(E, \mu, r, t)$ is the bounce-averaged fast ion distribution function as a function of Energy E , magnetic moment μ , radius r , and time t . τ_B is the bounce time, and the factor of $r\tau_B$ results from conservation of particles. C is the velocity-space diffusion collision operator, and S represents sources (neutral beam injection) and sinks (thermalization and CX losses). Passing and banana-trapped particles were assumed to diffuse

with the same D_{fast} , which is assumed to be independent of energy and radius also.

Figure 5 compares the temporal evolution of measured charge-exchange fluxes with the TRANSP code calculations for $D_{\text{fast}} = 0, 0.1$ and $1.0 \text{ m}^2/\text{sec}$. The neutral flux measured by the EV4 analyzer is consistent with the $D_{\text{fast}} = 0 \text{ m}^2/\text{sec}$ prediction for both the 30 keV and 50 keV energies except for $\sim 0.1 \text{ sec}$ immediately after beam injection. Comparison of the total neutron emission, most of which originated from the passing ions in the core region, with the TRANSP simulation showed that the decay of the measured neutron flux was in good agreement with the $D = 0 \text{ m}^2/\text{sec}$ prediction [7] as well. On the other hand, the 30 keV neutral flux measured by the EV6 analyzer persists longer than the $D_{\text{fast}} = 0 \text{ m}^2/\text{sec}$ prediction. Explaining the time evolution requires $D \sim 0.1 \text{ m}^2/\text{sec}$ for the radial diffusivity of fast ions, while $D = 1.0 \text{ m}^2/\text{sec}$ makes the decay of charge-exchange flux faster than the measurement. Even for the 50 keV flux measured by EV6, a non-zero diffusivity is necessary to explain the time evolution. In the $D_{\text{fast}} = 0$ simulations, the fast ions remain at the radius where they were initially deposited, and the decay of the signal is due to collisional slowing down of the beam. The (outer) EV6 signal is predicted to fall much more quickly than the (central) EV4 signal, because the slowing down time is significantly shorter in the colder outer region of the plasma. This can only be explained by a small amount of radial diffusion which replenishes the fast ions in the outer part of the plasma with fast ions from the core. However, if there is too much radial difference, then all of the ions are lost too quickly.

The discrepancy between the (outer) EV6 signal which suggests $D = 0.1$, and the (core) EV4 signal which suggests a smaller D , might be explainable by allowing D to be larger for deeply trapped particles and/or by assuming D

increases with r . Our present simulations assumed D was a constant, independent of pitch angle and radius. This would be consistent with the neutron measurements of this experiment [7], which are sensitive primarily to the majority of fast ions which are near the plasma core and have passing pitch angles, and which indicated $D \ll 0.1 \text{ m}^2/\text{sec}$. Thus these results indicate that D_{fast} is larger for deeply trapped ions and/or increases with r .

5. Summary

The radial diffusivity of fast ions was evaluated in a short pulse deuterium beam injection into the ohmic deuterium plasma. The comparison between the measured neutral particle flux and theoretical calculations showed that a fast-ion diffusivity of $\sim 0.1 \text{ m}^2/\text{sec}$ is required in order to explain the temporal evolution of charge-exchange flux measured at an off-axis position.

Acknowledgments

The authors would like to thank all of the staff who have supported the TFTR program. In addition, we would like to express special thanks to Dr. D.M. Meade and Dr. K.M. Young for their continuous support and encouragement.

References

- [1] R. H. Radeztsky, S. D. Scott, R. Kaita, R. J. Goldston, G. W. Hammett, et al., in Proc. of 15th Eur. Conf. on Controlled Fusion and Plasma Heating, Dubrovnik(1988), Vol. 12B, Part I, p. 79, European Physical Society, 1988.
- [2] P. C. Efthimion, M. Bitter, E. D. Fredrickson, R. J. Goldston, G. W. Hammett, et al., in Proc. of the 12th International Conference on Plasma Physics and Controlled Nuclear Fusion Research (Nice, 1988), Vol. 1, p. 307, IAEA, Vienna, 1989.
- [3] S. D. Scott, C. W. Barnes, L. R. Grisham, G. W. Hammett, D. W. Johnson, et al., in Proc. of the 13th International Conference on Plasma Physics and Controlled Nuclear Fusion Research (Washington, DC, October 1990), IAEA, Vienna, Austria, Paper IAEA-CN-53/A-3-6.
- [4] S. Conroy, O. N. Jarvis, M. Pillon, and G. Sadler, in Proc. of 17th Eur. Conf. on Controlled Fusion and Plasma Heating, Amsterdam (1990), Vol. 14B, Part I, p. 98, European Physical Society, 1990.
- [5] W. W. Heidbrink, J. Kim, and R. Groebner, Nucl. Fusion, **28** (1988) 1897.
- [6] W. W. Heidbrink, Phys. Fluids, **B2** (1990) 4.
- [7] W. W. Heidbrink, C. W. Barnes, G. W. Hammett, Y. Kusama, S. D. Scott, M. C. Zarnstorff, L. C. Johnson, D. McCune, S. S. Medley, H. K Park, A. L. Roquemore, J. D. Strachan, and G. Taylor, Phys. Fluids **B3** (1991) 3167.
- [8] A. L. Roquemore, G. Gammel, G. W. Hammett, R. Kaita, and S. S. Medley, Rev. Sci. Instrum, **56** (1985) 1120.
- [9] C. L. Fiore, S. S. Medley, G. W. Hammett, R. Kaita, and S. D. Scott, Princeton Plasma Physics Laboratory Report, PPPL-2490, 1987.

- [10] R. J. Hawryluk, in B. Coppi et al. , editors, Physics of Plasmas Close to Thermonuclear Conditions, volume 1, p. 19, CEC, Brussels, 1980.
- [11] G. W. Hammett, Ph. D. Dissertation, Princeton University, 1986.

Figure Captions

- Fig. 1 Sightlines of the vertically viewing charge-exchange neutral particle analyzers. EV4 and EV6 are located at $R = 2.44$ m and 2.97 m, respectively.
- Fig. 2 The relation between the sightlines of EV4 and EV6 and the beam lines. The beam lines are identified by their tangency radius, R_{tan} .
- Fig. 3 Wave forms for selected plasma parameters (#49113). From the top, neutral beam power, central electron density, central electron temperature and total stored energy are shown.
- Fig. 4 Time evolutions of the 30 keV and 50 keV charge-exchange flux measured by EV4 [(a), (b)] and EV6 [(c), (d)]. The raw signals are shown by a dotted line and the noise-corrected ones are shown by a solid line with error bars.
- Fig. 5 Comparison between the time evolution of the measured neutral fluxes and TRANSP calculations with $D = 0$, 0.1, and 1.0 m^2/sec [(a) and (b) are for EV4, (b) and (c) are for EV6].

Fig. 1.

Fig. 2.

Fig. 3.

Fig. 4.

Fig. 5.

EXTERNAL DISTRIBUTION IN ADDITION TO UC-420

Dr. F. Paoloni, Univ. of Wollongong, AUSTRALIA	Prof. I. Kawakami, Hiroshima Univ., JAPAN
Prof. M.H. Brennan, Univ. of Sydney, AUSTRALIA	Prof. K. Nishikawa, Hiroshima Univ., JAPAN
Plasma Research Lab., Australian Nat. Univ., AUSTRALIA	Director, Japan Atomic Energy Research Inst., JAPAN
Prof. I.R. Jones, Flinders Univ, AUSTRALIA	Prof. S. Itoh, Kyushu Univ., JAPAN
Prof. F. Cap, Inst. for Theoretical Physics, AUSTRIA	Research Info. Ctr., National Instit. for Fusion Science, JAPAN
Prof. M. Heindler, Institut für Theoretische Physik, AUSTRIA	Prof. S. Tanaka, Kyoto Univ., JAPAN
Prof. M. Goossens, Astronomisch Instituut, BELGIUM	Library, Kyoto Univ., JAPAN
Ecole Royale Militaire, Lab. de Phy. Plasmas, BELGIUM	Prof. N. Inoue, Univ. of Tokyo, JAPAN
Commission-Europeen, DG. XII-Fusion Prog., BELGIUM	Secretary, Plasma Section, Electrotechnical Lab., JAPAN
Prof. R. Bouciqué, Rijksuniversiteit Gent, BELGIUM	S. Mori, Technical Advisor, JAERI, JAPAN
Dr. P.H. Sakanaka, Instituto Fisica, BRAZIL	Dr. O. Mitarai, Kumamoto Inst. of Technology, JAPAN
Instituto Nacional De Pesquisas Especiais-INPE, BRAZIL	J. Hyeon-Sook, Korea Atomic Energy Research Inst., KOREA
Documents Office, Atomic Energy of Canada Ltd., CANADA	D.I. Choi, The Korea Adv. Inst. of Sci. & Tech., KOREA
Dr. M.P. Bachynski, MPB Technologies, Inc., CANADA	Prof. B.S. Liley, Univ. of Waikato, NEW ZEALAND
Dr. H.M. Skarsgard, Univ. of Saskatchewan, CANADA	Inst of Physics, Chinese Acad Sci PEOPLE'S REP. OF CHINA
Prof. J. Teichmann, Univ. of Montreal, CANADA	Library, Inst. of Plasma Physics, PEOPLE'S REP. OF CHINA
Prof. S.R. Sreenivasan, Univ. of Calgary, CANADA	Tsinghua Univ. Library, PEOPLE'S REPUBLIC OF CHINA
Prof. T.W. Johnston, INRS-Energie, CANADA	Z. Li, S.W. Inst Physics, PEOPLE'S REPUBLIC OF CHINA
Dr. R. Bolton, Centre canadien de fusion magnétique, CANADA	Prof. J.A.C. Cabral, Instituto Superior Tecnico, PORTUGAL
Dr. C.R. James,, Univ. of Alberta, CANADA	Dr. O. Petrus, AL I CUZA Univ., ROMANIA
Dr. P. Lukáč, Komenského Univerzita, CZECHO-SLOVAKIA	Dr. J. de Villiers, Fusion Studies, AEC, S. AFRICA
The Librarian, Culham Laboratory, ENGLAND	Prof. M.A. Hellberg, Univ. of Natal, S. AFRICA
Library, R61, Rutherford Appleton Laboratory, ENGLAND	Prof. D.E. Kim, Pohang Inst. of Sci. & Tech., SO. KOREA
Mrs. S.A. Hutchinson, JET Library, ENGLAND	Prof. C.I.E.M.A.T, Fusion Division Library, SPAIN
Dr. S.C. Sharma, Univ. of South Pacific, FIJI ISLANDS	Dr. L. Stanflo, Univ. of UMEA, SWEDEN
P. Mähönen, Univ. of Helsinki, FINLAND	Library, Royal Inst. of Technology, SWEDEN
Prof. M.N. Bussac, Ecole Polytechnique,, FRANCE	Prof. H. Wilhelmson, Chalmers Univ. of Tech., SWEDEN
C. Mouttet, Lab. de Physique des Milieux Ionisés, FRANCE	Centre Phys. Des Plasmas, Ecole Polytech, SWITZERLAND
J. Radet, CEN/CADARACHE - Bat 506, FRANCE	Bibliotheek, Inst. Voor Plasma-Fysica, THE NETHERLANDS
Prof. E. Economou, Univ. of Crete, GREECE	Asst. Prof. Dr. S. Cakir, Middle East Tech. Univ., TURKEY
Ms. C. Rinni, Univ. of Ioannina, GREECE	Dr. V.A. Glukhikh, Sci. Res. Inst. Electrophys. Apparatus, USSR
Dr. T. Mui, Academy Bibliographic Ser., HONG KONG	Dr. D.D. Ryutov, Siberian Branch of Academy of Sci., USSR
Preprint Library, Hungarian Academy of Sci., HUNGARY	Dr. G.A. Eliseev, I.V. Kurchatov Inst., USSR
Dr. B. DasGupta, Saha Inst. of Nuclear Physics, INDIA	Librarian, The Ukr.SSR Academy of Sciences, USSR
Dr. P. Kaw, Inst. for Plasma Research, INDIA	Dr. L.M. Kovrizhnykh, Inst. of General Physics, USSR
Dr. P. Rosenau, Israel Inst. of Technology, ISRAEL	Kernforschungsanlage GmbH, Zentralbibliothek, W. GERMANY
Librarian, International Center for Theo Physics, ITALY	Bibliothek, Inst. Für Plasmaforschung, W. GERMANY
Miss C. De Palo, Associazione EURATOM-ENEA, ITALY	Prof. K. Schindler, Ruhr-Universität Bochum, W. GERMANY
Dr. G. Grosso, Istituto di Fisica del Plasma, ITALY	Dr. F. Wagner, (ASDEX), Max-Planck-Institut, W. GERMANY
Prof. G. Rostangni, Istituto Gas Ionizzati Del Cnr, ITALY	Librarian, Max-Planck-Institut, W. GERMANY
Dr. H. Yamato, Toshiba Res & Devel Center, JAPAN	Prof. R.K. Janev, Inst. of Physics, YUGOSLAVIA

END

**DATE
FILMED
3 / 3 / 92**