LEGIBILITY NOTICE

A major purpose of the Technical Information Center is to provide the broadest dissemination possible of information contained in DOE's Research and Development Reports to business, industry, the academic community, and federal, state and local governments.

Although a small portion of this report is not reproducible, it is being made available to expedite the availability of information on the research discussed herein.

Technology Applications Bulletins

ON THE COVER: Color composite digital X-ray image of the elemental distributions in a malachite ore. Red represents the manganese distribution, green represents the iron distribution, and blue represents the copper distribution. Data for constructing the image, which spans a 1-mm² area of the specimen, were taken with the HXRP-5, a high-resolution X-ray microprobe. The color composite is useful in determining the extent of association of the elements. (Cover image by Donald A. Carpenter, Y-12 Plant Development Division.)

Office of Technology Applications

Vice President

W. W. Carpenter

Information Services

Manager of Technology Transfer

Donald W. Jarec

Secretary

Pauline Hughes

Publication Division

Editor

Walter Koncinski, Jr.

Typography

Sandi Lyttle

Makeup

Larry Davis

Bob Eldridge

Graphics Division

Leon Smith

Larry Bohannon

Cover Design

Vickie L. Conner

Martin Marietta Energy Systems, Inc. (Energy Systems), operates five facilities for the U.S. Department of Energy (DOE):

- the Oak Ridge National Laboratory (ORNL), which is a large, multidisciplinary research and development (R&D) center whose primary mission is energy research;
- the Oak Ridge Y-12 Plant, which engages in defense research, development, and production; and
- the uranium-enrichment plants at Oak Ridge; Paducah, Kentucky; and Portsmouth, Ohio.

Much of the research carried out at these facilities is of interest to industry and to state or local governments. To make information about this research available, the Energy Systems Office of Technology Applications publishes brief descriptions of selected technologies and reports. These technology applications bulletins describe the new technology and inform the reader about how to obtain further information, gain access to technical resources, and initiate direct contact with Energy Systems researchers.

Office of Technology Applications

Information Services

Martin Marietta Energy Systems, Inc.

P.O. Box 2008

Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

MASTER

8

CONTENTS

	Page
TECHNOLOGY APPLICATIONS NEWS	1
TECHNOLOGIES AVAILABLE FOR LICENSING	19
ARTIFICIAL INTELLIGENCE, ROBOTICS, AND MANUFACTURING PROCESSES	
Algorithms for Efficient Use of Multiprocessor Hardware	21
MEASUREMENTS AND CONTROLS	
HRXRP-5 High-Resolution X-ray Microprobe	23
Fracture-Mechanics Analysis on a Distributed-Memory Parallel Processor	25
Linear Harmonic Analysis of Free-Piston Stirling Engines	27
Single-Board Microcontroller Suitable for Rapid Prototyping	29
Demodulation Circuit for ac Motor Current Signature Analysis	31
Test System For Erosion-Corrosion Studies	33
An Automated Hot-Cell Titration System	35
New Applications of Silicon Micromachining	37
Instrumentation System for Precision Measurements of Flow Vectors	39
MEDICAL AND BIOMEDICAL TECHNOLOGY	
Radiolabeling Technique for Early Cancer Detection	41
ENERGY CONSERVATION	
Triple-Effect Absorption Chiller Using Two Refrigeration Circuits	43
Seven-Effect Absorption Chiller Using Three Refrigeration Circuits	45
Building Foundations Research Agenda	47
An Enhanced Computer Program for Modeling Absorption Heat Pump Systems	49
Infiltration Reduction for Single-Family Houses	51
Occupant Evaluation of Commercial Office Lighting	53
Documentation for Residential Reference House Energy Demand Model	55
The Princeton Scorekeeping Method Compared with Energy End-Use Load Data	57
TRANSPORTATION	
Review of Nonresidential Transportation Energy Use Data	59
Technology Transfer for DOE's Office of Transportation Systems	61
ENERGY PRODUCTION	
Wood-Burning Retrofit Saves Fuel at an Oil-Fired Steam Plant	63
Reliability Studies for Compressed-Gas-Insulated Apparatus	65
Assessment of Material Requirements for Advanced Steam Cycle Systems	67
Study of Solar Power Supply System at Mississippi County Community College	69
An All-Metal Reentrant Vacuum Feedthrough	71
CUMULATIVE INDEX FOR FY 1988	73

TECHNOLOGY APPLICATIONS NEWS

Alvin W. Trivelpiece Named ORNL Director

Energy Systems has announced the appointment of Alvin W. Trivelpiece as director of ORNL. He also serves as a vice president of Energy Systems, which manages four other energy-related facilities in addition to ORNL. Dr. Trivelpiece assumed full responsibility for his new appointments on January 1.

In announcing the appointment, Energy Systems President Clyde C. Hopkins said, "We are extremely fortunate to have Dr. Trivelpiece lead our team at ORNL. His experience in academics, industry, and government will enable him to provide strong guidance in both strategic planning and the implementation of science and technology programs. His strong scientific and engineering credentials will ensure the commitment to high standards within the Laboratory, and his personal character and leadership will provide new direction for ORNL."

Before joining ORNL, Dr. Trivelpiece was executive officer of the American Association for the Advancement of Science. He has also been the director of DOE's Office of Energy Research; corporate vice president for Science Applications, Inc.; vice president for engineering and research at Maxwell Laboratories, Inc.; professor of physics at the University of Maryland; and assistant director for research in the U.S. Atomic Energy Commission's Division of Controlled Thermonuclear Research.

Dr. Trivelpiece said that he accepted the position with Energy Systems because "it's an opportunity to be closer to hardware and science, which is really where my background is." An advocate of the Superconducting Super Collider, Dr. Trivelpiece has stressed the importance of basic research and technology transfer to the well-being of the U.S. economy. (Quoted with permission from *Energy Daily*, October 6, 1988.)

R&D 100 Awards

Each fall, *Research & Development* magazine recognizes the top 100 technical innovations of the year with its R&D 100 awards (formerly the R 100 awards). The winners are selected from thousands of scientific and technical achievements worldwide. They are chosen because of their importance, uniqueness, and usefulness to mankind. This year, the OPSNET computer architecture, developed at ORNL, and the HRXRP-5 high-resolution X-ray microprobe, developed at the Oak Ridge Y-12 Plant, both won R&D 100 awards. Their developers were honored on September 22 in ceremonies at Chicago's Museum of Science and Industry.

The OPSNET Parallel Computer

Available for Licensing

The OPSNET parallel computer was developed by John D. Allen, Jr., and Philip L. Butler of ORNL's Instrumentation and Controls Division. It executes the OPS5 expert system language, which is used to emulate the decision-making processes of experts in fields such as medical diagnosis, organic chemical synthesis, and intelligent robot control. Previously, uses of expert systems for real-time process control have been limited by slow execution speeds, even with powerful mainframe computers. OPSNET outperforms conventional computer architectures and does so at a fraction of the cost of other parallel machines.

Ask for bulletin Number 650.

Philip L. Butler (left) and John H. Allen, Jr., of ORNL's Instrumentation and Controls Division, with the OPSNET machine.

The HRXRP-5 High-Resolution X-ray Microprobe

The HRXRP-5 was developed by Donald A. Carpenter, Roger L. Lawson, Mark A. Taylor, Gary M. Haney, and Karl Z. Morgan of the Y-12 Plant Development Division. It is an analytical device that produces color images of chemical-element distributions in metal, ceramic, composite, biological, and geological specimens. Typically, analyses with the HRXRP-5 are carried out in air with little or no sample preparation. Analysis time is fast enough to maintain a high sample throughput, and relatively large specimens can be analyzed because no vacuum chamber is required.

See Bulletin Number 674 in this issue.

The developers of the HRXRP-5 X-ray microprobe (left to right): Karl Morgan, Don Carpenter, Gary Harvey, Mark Taylor (seated), and Roger Lawson.

Lecture Series Focuses on U.S. Global Competitiveness

ORNL's Program Planning and Analysis Office has continued to sponsor speakers in its "U.S. Global Competitiveness and the National Laboratories" lecture series. Four speakers have appeared since Senator Jim Sasser began the program with a keynote address in February 1988. These speakers offered their observations about the relationship between scientific research and industrial applications. They presented specific examples of how private industries can reap the benefits of basic research.

Dr. Richard N. Foster, director of the McKinsey & Company management consulting firm, gave a presentation based on his widely acclaimed book, *Innovation: The Attacker's Advantage*. According to Foster, the lifetime of a developing technology is finite and limited by the amount of R&D needed to fully realize that technology's potential. The national laboratories can help industrial managers estimate the value of a technology during its maturation.

Dr. Siegfried S. Hecker, director of the Los Alamos National Laboratory, sought to clarify the identities of national laboratories and to define their role in the U.S. bid for global competitiveness. He described a new, precompetitive way for DOE laboratories to work with private industry, using the new superconductivity pilot center program as an example.

Dr. Fumio Kodama, professor of innovation policy at Saitama University and director of Japan's National Institute of Science and Technology Policy, spoke about technological diversification in Japan. He explained how Japan's "research association scheme" has enabled competing private industries to collaborate successfully on R&D projects.

The fourth speaker was Dr. Ralph E. Gomory, senior vice president for science and technology for IBM and *Research & Development* magazine's choice for "Scientist of the Year" in 1987. Speaking from the corporate point of view, Dr. Gomory described the relationship between scientific research and the manufacturing and development of commercial products.

Innovation: The Attacker's Advantage

Foster addressed technological innovation from the standpoint of a corporate executive officer whose task it is to maximize the return from product R&D. According to Foster, every technological innovation has its limits, and the cost of improved performance increases as that limit is approached. The size of the gap between the current state of the art and what is unknown about the new technology determines both the "level" and the useful lifetime of that technology. A large gap indicates a high technology, and its useful lifetime lies within the time it takes to close that gap.

A student of the science historian Thomas Kuhn, Foster has observed that technological innovation proceeds in a discontinuous, "revolutionary" manner although it may be perceived as a smooth, "evolutionary" process. For example, the replacement of the vacuum tube by the

Dr. Richard W. Foster, director of McKinsey & Company: "I think the national labs have a unique role to play in the economic landscape by telling our people what these limits of performance are and why. It's a basic science question."

transistor could be interpreted as an evolutionary step for the electronics industry generally. However, for the companies involved, it was a revolution in which the dominant companies lost to newcomers who were trained and tooled up for the new technology. Based on many examples like this one, Foster has concluded that, "Unlike in conventional military warfare, the attacker has the advantage in the marketplace. . . . The technological productivity of the new technology is so many times superior to that of the older technology that you start with an inbred economic advantage."

The lifetime of a technology follows an arc that climbs slowly at first, then steadily and quickly as increasingly difficult problems affecting its performance are solved. This progression will continue until the problems become so difficult that the gains in performance are no longer worth the effort that they require. At this point, it is an opportune time for an innovative technology (such as transistors) to replace the mature technology (vacuum tubes).

According to Foster, corporate executive officers need to recognize and gauge the upper limit of a developing technology so they can manage its useful lifetime responsibly. However, scientists close to the basic research are better able to assess a new technology's limitations and can serve as useful advisors to decision-makers in industry: "I think the national labs have a unique role to play in the economic landscape by telling our people what these limits of performance are and why. It's a basic science question."

Superconductivity Pilot Centers

Hecker stated his perception of the current and future role of national laboratories in the technology transfer process. Technology transfer from the national laboratories to private industries has been strongly encouraged by the federal government. However, according to Hecker, the current method of technology transfer has frustrated both the laboratories and industry because it is being handled like a sales transaction and because it is governed by a daunting amount of bureaucracy.

Hecker said that "technology has been treated too much as a commodity that can be bought or sold or passed around when, in fact, it has to be woven into the fabric of commercial innovation." According to him, the relationship between the laboratories and industries ought to be a partnership in which the three principal partners in the technology transfer process have definite obligations. The laboratories must recognize that technology development should be guided by market pull. Industry, in turn, must recognize the benefits of collaborative technology development in the precommercial, precompetitive stages that will benefit U.S. industry as a whole; the laboratories are not now and should not become "job shops" for individual companies. Federal agencies need to minimize bureaucracy and nurture these partnerships.

Most of the federally funded laboratories were started in response to war or crisis and continue to be well suited for high-risk, goal-oriented projects. As Hecker put it, "We are often

Dr. Siegfried S. Hecker, director, Los Alamos National Laboratory: "Technology has been treated too much as a commodity that can be bought or sold or passed around, when in fact it has to be woven into the fabric of commercial innovation."

assigned responsibilities beyond any person's known competence." One major responsibility currently assigned to the national laboratories is to identify and pursue strategic technologies suitable for collaborative R&D.

Hecker described the new superconductivity pilot centers as a project that will demonstrate a precompetitive collaboration on a strategic technology. Applied high-temperature superconductivity is a new, high-risk and potentially highly lucrative field. The new pilot centers at ORNL, Los Alamos, and Argonne will focus on generic technology development and collaboration with industry.

An agreement that will expedite this experimental program is being finalized by DOE. The agreement will provide the criteria for joint R&D projects between industry and the national laboratories. These criteria include collaborative and cost-shared research, protection for proprietary information, exclusive patent and use rights, and licensing provisions for laboratory-owned intellectual property.

Japanese Technological Diversification

Kodama described his research into the technological diversification that has taken place recently in Japanese industry. By analyzing an extensive data base maintained by the Japanese government, he has devised methods to quantify the influence of R&D investments on economic restructuring in Japan. [Details of this analysis can be found in Dr. Kodama's article, "Technological Diversification of Japanese Industry," *Science* 233(4761), 291-96 (July 18, 1986).]

Dr. Kodama has observed among Japanese corporations a "paradigm change," which has taken place since 1985. Although once primarily oriented toward production, Japanese companies now spend much more money on R&D than on capital investment. He redefined "corporation" to suit what he has observed happening in Japan: "The corporation could be said to be shifting from being a place for production to being a place for thinking: thinking for survival, thinking for the future." The Japanese government has taken steps to exploit this paradigm change by encouraging and directing these large private investments in technological R&D.

The Japanese government has instituted a "research association scheme," which can cause the creation of new companies and which improves existing ones. In this R&D program, the government works with competing companies to develop concerted research efforts. The government also provides funds and tax benefits. The competing companies share costs and researchers; they avoid conflicts of interest by solving problems that they share but are not

Dr. Fumio Kodama, professor of innovation policy at Saitama University and director of Japan's National Institute of Science and Technology Policy: "The corporation could be said to be shifting from being a place for production to being a place for thinking: thinking for survival, thinking for the future."

directly related to their product line. Existing vendors and support companies benefit from this research, and new companies may be formed to satisfy the new materials needs brought about by this research. Participating companies commonly form parallel, in-house research teams that work concurrently with this research effort. Investment in a parallel team is considered venture capital for the individual companies.

Kodama used the Very Large Scale Integration Project to illustrate a successful example of this scheme. With government support, competing producers of computer chips collaborated to improve the production of silicon crystals. The companies avoided conflicts of interest by solving problems that concentrated on making silicon rather than making chips. In this way, they created new opportunities for vendors of silicon crystals, optical fiber, and manufacturing support equipment without jeopardizing their own product line.

The Role of Science in Manufacturing

Speaking from the point of view of American industry, Gomory discussed the role of science in product development. He offered specific reasons for close collaboration between private industry and the national laboratories. He defined two distinct methods of product development, which he demonstrated with two models: the ladder and the cycle.

The ladder model of product development describes the comparatively rare occasion when novel scientific discoveries make possible novel technical applications. Gomory offered the examples of the new developments in nuclear physics that led to the building of the atomic bomb and the new developments in solid-state physics that enabled the development of the transistor. These new discoveries descended the ladder from the realm of science into the realm of manufacturing and development. Prevalent in universities and government research laboratories, this ladder mechanism is dominated by scientists, whose expertise governs the work of the engineers.

Much more common is the product-development cycle, which takes place within individual private companies. Once a product is established, it undergoes recurrent refinement: design change to prototype to manufacture. This cyclic process is dominated by engineers within the company. It is a closed system, constrained by manufacturing deadlines and by the tooling capabilities of the manufacturer. This cycle is also fueled by the market; a company with a faster cycle time has the appearance of being an industry leader.

Dr. Ralph E. Gomory, senior vice president for science and technology, IBM Corporation: "It is extremely important that . . . the engineers in the manufacturing and development cycle, go out and look for new ideas and pull in those that fit."

Because this refinement cycle is a closed system, scientists conducting basic research without knowledge of the constraints involved have little chance of having their new ideas applied to conventional manufactured goods. An engineer with hands-on experience with a product can apply a novel idea at an opportune moment during the cycle; however, it is nearly impossible for someone on the outside to impose a new idea, no matter how good that idea appears to be. For that reason, Gomory said that "it is extremely important that . . . the engineers in the manufacturing and development cycle go out and look for new ideas and pull in those that fit."

Energy Systems has granted a license to Wyle Laboratories of El Segundo, California, to market a device that diagnoses motor-driven systems by analyzing current flow through the system's electric motor. The motor current signature analysis (MCSA) device was developed by David M. Eissenberg and Howard D. Haynes of ORNL's Engineering Technology Division. The work was part of the Nuclear Regulatory Commission Plant Aging Research Program to assess the aging of motor-operated valves used in nuclear power plant safety systems.

This new diagnostic tool is suitable for widespread application as a means for cost-effective condition monitoring of many types of electric-motor-driven mechanical equipment. Advantages of MCSA include the use of noninvasive clamp-on current probes as sensors, which can be located anywhere along the power line to the motor, including at remote motor-control centers. In addition, unlike accelerometers, which can sense in one plane only, the MCSA can detect and monitor all mechanical loads.

Ask for Bulletin Number 608.

MCSA applied to a centrifugal pump. The output signals obtained in A and B are analyzed to determine load changes within the pump and motor that correspond to degradation and service wear and thus provide evidence of incipient failure.

Roof Research Center Dedicated

The Roof Research Center, operated by ORNL's Energy Division, was officially dedicated during a public ceremony on September 14. Designated as a national user facility, this \$2.8-million experimental station is used for research to improve the thermal efficiency of all types of roof systems while maintaining durability and long service, all at competitive prices. The centerpiece of the Roof Research Center is the Large-Scale Climate Simulator, which consists of two chambers. One chamber simulates outdoor weather conditions; the other, indoor conditions. A second facility, the Roof Thermal Research apparatus, is used primarily to monitor the long-term field thermal performance of different types of roof systems.

John Berg, DOE principal deputy assistant secretary for Conservation and Renewable Energy, cuts the ribbon (made of roofing felt) at the dedication of the ORNL Roof Research Center. Also pictured are (left to right) George Courville, program manager, Building Thermal Envelope Systems and Materials; Murray Rosenthal, ORNL associate director for Advanced Energy Systems; Roger Bengston, vice president and general manager of Menville Corporation's Roofing Division; and Marlin Pottleiger, president, National Roofing Contractors Association.

Specific projects for the center can be suggested by DOE and ORNL staff and by the roofing industry. Provisions are also available for a limited amount of proprietary research for specific companies. A users' manual, *A National User Facility for Thermal Performance and Durability of Roofing Systems* is available to those interested in research at the Roof Research Center.

Ask for Bulletin Number 633.

Imaging Agent Licensed to Du Pont for Research Applications

Energy Systems has granted a license to E. I. du Pont de Nemours and Company for an ORNL nuclear medicine technology that can be used to manufacture a chemical compound that may help doctors detect cancer in its early stages. "This is the first royalty-bearing license for a nuclear medicine technology developed at ORNL," said Bill Carpenter, Energy Systems vice president for technology applications. "The agreement enables Du Pont to supply the compound to research institutions across the country." Du Pont will sell the new compound through its Medical Products Department in Boston.

A group of ORNL researchers, led by Prem C. Srivastava of the Nuclear Medicine Group in the Health and Safety Research Division, designed and synthesized the new chemical agent known as iodophenylmaleimide. This agent is labeled with radioactive iodine and can be attached to antibodies specific to proteins produced by cancer cells. When linked to the antibody, the ORNL compound will be attracted to tumors where specialized cameras can detect the radiation, thus helping doctors locate the tumors at an early stage in their development.

P. C. Srivastava (right) led the team that developed the newly licensed iodophenylmaleimide imaging agent. He is shown being assisted by team member John Allred.

Studies at ORNL and the University of Michigan show that the ORNL agent enables antibodies to retain the iodine much better than agents now being used. This capability would greatly decrease the patient's exposure to radiation from released iodine. In addition, iodine retention increases the half-life of the radiolabeled antibody, which ensures optimum therapeutic effect.

See Bulletin Number 683 in this issue.

TECHNOLOGIES AVAILABLE FOR LICENSING

The following technologies are currently available for licensing from Energy Systems:

- ZZX-4200 High-Temperature Thermal Insulation Structures
(Bulletin Number 600)
- Nickel Aluminides
(Bulletin Number 599)
- Whisker-Reinforced Ceramic Matrix Composites
(Bulletin Number 568)
- Automatic Coordinate Measuring System
(Bulletin Number 612)
- Lead-Indium Phosphate and Lead-Scandium Phosphate Glasses for Optical Components
(Bulletin Number 622)
- Ultrasonic Ranging and Data System
(Bulletin Number 579)
- Triple-Effect Absorption Chiller Using Two Refrigeration Circuits
(Bulletin Number 684)
- Seven-Effect Absorption Chiller Using Three Refrigeration Circuits
(Bulletin Number 685)
- Motor Current Signature Analysis Process
(Bulletin Number 608)
- Demodulation Circuit for ac Motor Current Signature Analysis
(Bulletin Number 678)
- OPSNET Parallel Computer
(Bulletin Number 650)

Technology Applications Bulletins

Bulletin Number 673

Oak Ridge National Laboratory

ARTIFICIAL INTELLIGENCE, ROBOTICS, AND MANUFACTURING PROCESSES

ALGORITHMS FOR EFFICIENT USE OF MULTIPROCESSOR HARDWARE

Key words: Shared-memory multiprocessor; distributed-memory multiprocessor; hypercube; computational algorithm; linear systems

Because of recent developments in computer hardware, large and powerful parallel computer architectures have become commercially available. Distributed-memory multiprocessors (such as the Intel and Ncube hypercubes) and shared-memory multiprocessors (such as a Sequent Balance 8000) are potentially much faster than similar single processors and cheaper than serial processors of similar aggregate power. The challenge for computer programmers lies in developing algorithms that maximize the efficiency of these new machines. Researchers in ORNL's Mathematical Sciences Section are developing and refining a variety of algorithms for efficient parallel processing.

For example, algorithms and software for serial computers have already reached a high state of development for performing matrix factorizations and using the resulting factors in the solution of systems of linear equations, such as a system derived from the discretization of a partial differential equation. The six ORNL reports described in this bulletin present and analyze algorithms for such matrix computations on shared- and distributed-memory parallel computers. Algorithms have been developed for the *LU* factorization, where the matrix factors are a lower triangular matrix *L* and an upper

triangular matrix *U*, and for the *QR* factorization, where the factors are orthogonal *Q* and upper triangular *R*.

In the ORNL report, *Solution of Sparse Positive Definite Systems on a Shared-Memory Multiprocessor*, algorithms are presented for performing the Cholesky factorization (which is an *LU* factorization with *U* equal to the transpose of *L*) of a sparse matrix and for solving the resulting sparse triangular systems on a shared-memory parallel computer. Numerical experiments demonstrating the performance of these algorithms on a Sequent Balance 8000 system are documented.

QR Factorization of a Dense Matrix on a Shared-Memory Multiprocessor contains a new algorithm for computing an orthogonal decomposition of a rectangular matrix on a shared-memory computer. This algorithm, which uses Givens rotations, features a low synchronization cost. Analyses and experiments performed on an eight-processor Sequent Balance 8000 show that the algorithm is effective in balancing the load and producing high efficiency (speed-up).

Three reports containing tested factorization algorithms are also available for distributed-memory multiprocessors. *Parallel Solution of Triangular Systems on Distributed-Memory Multiprocessors* presents several algorithms for solving triangular systems of linear equations. New wavefront algorithms have been developed for both row-oriented and column-oriented matrix

storage. The performance of new and previously proposed algorithms is analyzed theoretically and illustrated empirically using implementations on Amtek, Intel, and Ncube hypercubes.

LU Factorization Algorithms on Distributed-Memory Multiprocessor Architectures describes four approaches for implementing the LU factorization on a hypercube. Four algorithms were analyzed to determine whether the choice of storage scheme for the coefficient matrix a pivoting strategy affects the efficiency of parallel factorization; the algorithms preferred for given sets of conditions were identified. Empirical results were obtained by implementing the algorithms on an Intel iPSC hypercube.

QR Factorization of a Dense Matrix on a Hypercube Multiprocessor describes a scheme that involves embedding a two-dimensional grid in a hypercube network. An algorithm for reducing a rectangular matrix to upper triangular form using orthogonal transformations on a hypercube multiprocessor is described. Numerical experiments were performed on a 64-processor Intel iPSC hypercube to verify the theoretical results.

The problem of load balancing on a hypercube has also been addressed. A row-oriented implementation of Gaussian elimination with partial pivoting on a local-memory multiprocessor is described in *Gaussian Elimination with Partial Pivoting and Load Balancing on a Multiprocessor*. The simple, inexpensive load-balancing scheme described in this report maintains computational balance in the presence of pivoting. An analysis of the communication costs of the algorithm is developed, along with an analysis of the computation performed in each node processor. Experiments using an Intel iPSC hypercube are described to demonstrate the extent to which the analytical model predicts performance.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

E. Chu and A. George, *QR Factorization of a Dense Matrix on a Shared-Memory Multiprocessor*, ORNL/TM-10581, Oak Ridge National Laboratory (October 1987).

E. Chu and A. George, *QR Factorization of a Dense Matrix on a Hypercube Multiprocessor*, ORNL/TM-10691, Oak Ridge National Laboratory (February 10, 1988).

G. A. Geist and C. H. Romine, *LU Factorization Algorithms on Distributed-Memory Multiprocessor Architectures*, ORNL/TM-10383, Oak Ridge National Laboratory (March 1987).

A. George and E. Chu, *Gaussian Elimination with Partial Pivoting and Load Balancing on a Multiprocessor*, ORNL/TM-10323, Oak Ridge National Laboratory (March 1987).

A. George et al., *Solution of Sparse Positive Definite Systems on a Shared-Memory Multiprocessor*, ORNL/TM-10260, Oak Ridge National Laboratory (January 1987).

M. T. Heath and C. H. Romine, *Parallel Solution of Triangular Systems on Distributed-Memory Multiprocessors*, ORNL/TM-10384, Oak Ridge National Laboratory (March 1987).

MEASUREMENTS AND CONTROLS

HRXRP-5 HIGH-RESOLUTION X-RAY MICROPROBE

Key words: X-ray microprobe; elemental fluorescence; nondestructive testing

A new high-resolution X-ray microprobe, the HRXRP-5, has been developed at the Oak Ridge Y-12 Plant. The HRXRP-5 produces high-resolution color images of the distributions of chemical elements in metals, ceramics, and composites, as well as in biological and geological materials (Fig. 1). It uses a highly collimated, intense X-ray beam as a fluorescence probe. A

Fig. 1. Elemental distribution in a malachite ore. These grey scale images show separate element distributions in a higher-contrast format than the color composite (see cover). Comparisons between the two formats facilitate feature location and characterization.

typical analysis with HRXRP-5 is carried out in air with little or no sample preparation and is fast enough to maintain a high sample throughput.

During an analysis, a highly collimated X-ray beam impinges upon the sample surface, causing specific elemental fluorescence. The fluorescent X rays are captured with a solid-state detector and then separated by energy to identify each element present in the analysis volume. This analysis is repeated up to 40,000 times per sample by translating the sample in a grid pattern normal to the incident X-ray beam. Elemental spatial distributions are displayed on a graphics workstation as color, grey-scale, or color topographic images.

The HRXRP-5 fills a technological gap between high-resolution electron-beam microprobes and low-resolution X-ray beam devices. With the X-ray microprobe, analyses are carried out in air, whereas electron-beam microprobes require a high vacuum. Unlike electron beams, which are limited to the near surface, X-ray beams can penetrate up to 40 μm beneath the surface, depending on the material analyzed. In addition, the low peak-to-background ratio inherent in X-ray beam instruments results in greater sensitivity than electron-beam instruments. Because electrical conductivity is not required, the specimens do not need to be coated with a thin film of conducting substance. Thus, nondestructive tests can be carried out on ceramics and biological materials in addition to metals and alloys.

The HRXRP-5 occupies a unique position in the field of X-ray beam-induced X-ray fluorescence instrumentation because of its high resolution and speed. The unique features of the HRXRP-5 are its high-brilliance, laboratory-based X-ray source combined with a tightly coupled collimation system consisting of extremely fine-bore glass capillary tubing. The source is a microfocus X-ray tube with a 10- μm focal spot operated at 22 W power.

The end of the capillary tube is placed only a few millimeters from the focal spot of the X-ray tube by means of a unique coupling system that uses an O-ring fitting to maintain the vacuum inside the X-ray tube. X rays emanating from the focal spot are transmitted down the glass capillary tubing by total external reflection from the smooth capillary walls with an intensity loss proportional to length of the tubing rather than to the square of the distance, as in conventional X-ray collimation using metal pinholes. A spatial resolution of nearly 5 μm is obtained routinely with the HRXRP-5. Typical scans resulting in 5 μm spatial resolution require from a few minutes to about 1 h (compared to the many hours to several days required for other instruments using laboratory sources of X rays).

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

D. A. Carpenter et al., "A Scanning X-Ray Microprobe with Glass Capillary Collimation, pp. 391-93 in *Microbeam Analysis—88*, ed. D. E. Newbury, San Francisco Press, 1988.

MEASUREMENTS AND CONTROLS

FRACTURE-MECHANICS ANALYSIS ON A DISTRIBUTED-MEMORY
PARALLEL PROCESSOR

Key words: Fracture mechanics; nuclear power reactors; computer modeling; parallel processing

For more than a decade, ORNL has conducted research in fracture mechanics as part of the Heavy Section Steel Technology (HSST) program sponsored by the Nuclear Regulatory Commission. The HSST program is devoted to assessing and extending the margin of safety against fracture of the thick-walled steel pressure vessels used in light-water-cooled nuclear power reactors. This program couples material and structural testing with analytical studies using finite-element fracture mechanics to determine the behavior and structural integrity of steel pressure vessels containing crack-like flaws.

The fracture-mechanics approach accepts that some flaws will be present in a structure, but assumes that conditions can be established to ensure that the flaws do not grow to an unacceptable size during the lifetime of the structure. Life prediction in fracture mechanics requires calculation of crack-tip stress intensity parameters to quantify both stable crack growth and the conditions for unstable fracture in complex geometries under complex loads.

Over the last decade, numerical techniques such as the finite-element method have been established as powerful aids to fracture analysis. However, these numerical solutions are often executed at a considerable computing cost,

especially for nuclear and aerospace applications in which a high degree of accuracy is necessary. Computation research being done for the HSST program has several goals. Two goals in the area of parallel computing are mapping key finite-element algorithms to a parallel processor and demonstrating the possible savings in execution time when parallel processing replaces serial processing.

A parallel-processing code was developed based on a fracture-analysis system originally designed to accommodate the limitations of microcomputers. The parallel code was designed to use a large number of processors if the problem size warrants it. This program contains a virtual crack extension technique for evaluation of the crack-tip stress-intensity parameters and deals with 2-dimensional geometries, linear elastic material behavior, and static loadings.

A parallel multifrontal solution technique, which assigns one front to each processor, was developed and tested using a hypercube parallel-processing computer. For the test, a small example problem lending information to crack extension in plates (such as neutron-hardened boiler plates) exposed to thermal shocks (Fig. 1) was run. This example was implemented on five processors (four hypercube processors and one host).

The problem was partitioned into four subproblems, each of which was assigned to its own processor. Additional "super boundary

Fig. 1. (a) Icon for the simple fracture problem of a plate with a center crack of length $2a$ loaded mechanically to the stress level σ . (b) Finite-element mesh of problem in (a) containing 28 elements and 101 nodes. The roller boundaries on the left and bottom sides provide symmetry. Stress is applied as loads on top nodes. The crack is contained in the bottom-center two elements.

Fig. 2. Partitioning of sample into four blocks/subproblems, with two super boundary elements (SBEs) delineated by dashed lines. The dots are the nodes on the block boundaries belonging to the SBEs. Each block (P1-P4) is assigned to its own hypercube processor.

Additional information:

Office of Technology Applications
 Martin Marietta Energy Systems, Inc.
 P.O. Box 2008
 Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

J. A. Ciarard and G. A. Geist, *Implementing Fracture Analysis on a Distributed-Memory Parallel Processor*, ORNL/TM-10367, Oak Ridge National Laboratory (March 1987).

elements," around which communication and redundant calculations revolve, were also defined (Fig. 2). Each processor operated on the assumption that it was solving an entire problem although only the host processor knew the complete structure of the test problem. Overall execution time for the the test problem was decreased by more than 58% in comparison with serial processing. Even larger savings are possible when problem size and/or complexity increase. More complex problems, such as some nonlinear fracture problems, could greatly benefit from employing ideas from this method of finite-element fracture analysis.

MEASUREMENTS AND CONTROLS

LINEAR HARMONIC ANALYSIS OF FREE-PISTON STIRLING ENGINES

Key words: Free-piston Stirling engines; modeling theory; thermodynamics; dynamics

Researchers in ORNL's Engineering Technology Division have developed the linear harmonic analysis (LHA) method, which provides insights into both the thermodynamics and dynamics of free-piston Stirling engines (FPSEs). Unlike a numerical approach, LHA provides a semiclosed-form solution that offers additional insights into the underlying physical processes of FPSEs and provides a solid basis for further theoretical development.

This research was based on the Sunpower RE-1000, a well-tested, well-documented commercial reference engine (Fig. 1). The RE-1000 engine contains a single power piston and a displacer sprung to the engine housing. For the current version of LHA, the working space of the engine is divided into three control volumes, and motion of the engine housing is neglected. However, LHA is not limited to such a simple representation; more control volumes or dynamic equations could be added if necessary.

Cylinder heat transfer, pressure drop, and seal leakage losses are all included in the current version of LHA. These variables are included simultaneously as part of the thermodynamic/dynamic calculations so that all of the interactions between the losses, thermal performance, and dynamic behavior are accounted for. Traditional solution methods have time-stepping integrations

Fig. 1. Simplified schematic of a free-piston Stirling engine.

that can be plagued by numerical instabilities and can use large amounts of computer time. The LHA solution method accounts for the important thermodynamic losses that are coupled together in FPSEs, yet it is efficient enough for optimization studies.

Execution time for LHA is about 100 times less than the time required for an equivalent numerical integration method. Even with its speed, LHA has sufficient mathematical accuracy for most practical Stirling engine applications. The mathematical accuracy of the LHA assumptions was verified by independently solving the same

nonlinear equations using a numerical integration method and comparing the results. The differences between the LHA and numerical predictions were less than 5% for all important parameters, which is about equal to or less than the uncertainty associated with typical Stirling engine experimental measurements. This combination of computational speed and mathematical accuracy makes LHA ideal for FPSE optimization programs.

LHA also has advantages over other linear closed-form solution methods that have been developed for FPSE dynamic problems. All previously published closed-form solutions are second-order analyses in which the losses are treated separately. LHA method is a third-order analysis where the losses, as well as their interactions, are included intrinsically in the FPSE dynamic solution.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

N. C. J. Chen, F. P. Griffin, and C. D. West., *Linear Harmonic Analysis of Stirling Engine Thermodynamics*, ORNL/CON-155, Oak Ridge National Laboratory (August 1984).

N. C. J. Chen and F. P. Griffin, *Linear Harmonic Analysis of Free-Piston Stirling Engine Thermodynamics*, ORNL/CON-172, Oak Ridge National Laboratory (June 1986).

N. C. J. Chen, F. P. Griffin, and C. D. West, "Linear Harmonic Analysis for Stirling Machines and Second Law Analysis of Four Important Losses," pp. 1973-81 in *19th Intersociety Energy Conversion Engineering Conference*, Vol. 3, American Nuclear Society, San Francisco, Aug. 19-24, 1984.

Technology Applications Bulletins

Bulletin Number 677

Oak Ridge National Laboratory

MEASUREMENTS AND CONTROLS

SINGLE-BOARD MICROCONTROLLER SUITABLE FOR RAPID PROTOTYPING

Key words: Microcontroller; computerized housing design; rapid prototyping

The National Association of Home Builders (NAHB) Smart House Project is a cooperative research and development effort involving American home builders and a number of major corporations. The purpose of the project is to incorporate current technology in the distribution and use of energy and communication services in the home. ORNL is contributing to the Smart House Project by providing technical advice and consulting services to NAHB in the areas of overall evaluation and design, project management, and development of facilities for use in design evaluation and system integration.

Certain parts of the designs now used for home electrical and gas-distribution systems are as much as 100 years old. In spite of the radical change in energy-use patterns (from primarily lighting to primarily heating and cooling use), the basic energy-distribution and control systems used in homes have not changed in several decades. As a result, the needs of modern homes are not being met. The Smart House Project will provide designs for intelligent control and coordination services among appliances and the devices used to control their operation.

The Smart House design must meet rigid requirements for reliability, installability, and maintainability. This design will also establish a new standard of safety for power distribution in

the home, primarily by incorporating closed-loop control of electrical appliances. With this feature, branch circuits are de-energized except when power is necessary to operate appliances. To initiate the flow of power, the device controlling an appliance (such as the switch on a vacuum cleaner) must send an electronic message to the control for the circuit leading to the appliance. After the circuit is powered, the control for the circuit requires a continuing "nominal operation" signal from the appliance to maintain the supply of power.

Researchers in ORNL's Energy Division evaluated a commercially available, single-board microcontroller for use in developing and testing Smart House products (Fig. 1). Two ORNL reports, *Evaluation of a Single-Board Microcontroller Suitable for Rapid Prototyping*, and *Optimizing the Zilog Z8 FORTH Microcontroller for Rapid Prototyping*, concern criteria ORNL has developed for evaluating microcontrollers intended for use in rapid prototyping, the adaptation of a commercially available microcontroller to meet these requirements, and a summary evaluation of both the prototyping requirements and the performance of the candidate microcontroller.

Based on experience in laboratory development and testing for DOE conservation programs, ORNL presented requirements that should be met by a microcontroller suitable for rapid prototyping. A commercially available, FORTH-based microcontroller then was evaluated against

Fig. 1. Single-board microcontroller for use in developing and testing Smart House products.

these requirements. The study showed that a full-screen editor can be developed for the tested single-board microcontroller in about 40 h. Execution speed of a FORTH control program can range from 12 times slower to 3 times faster than IBM AT FORTH, depending on the degree of optimization of the microcontroller FORTH program. The report shows how Z8 FORTH-provided system primitives can be redefined to achieve fast execution speed. Also, ORNL devised a simple modification of Z8 FORTH to support multitasking. The microcontroller that was evaluated generally met rapid-prototyping requirements. The test resulted in concern about the readability of FORTH control programs, the execution speed of nonoptimized FORTH, and the

need to augment the basic complement of FORTH words provided with the microcomputer.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

R. Edwards, *Evaluation of a Single-Board Microcontroller Suitable for Rapid Prototyping*, ORNL/TM-10361, Oak Ridge National Laboratory (February 1987).

R. Edwards, *Optimizing the Zilog Z8 FORTH Microcontroller for Rapid Prototyping*, ORNL/TM-10463, Oak Ridge National Laboratory (September 1987).

MEASUREMENTS AND CONTROLS

Available for Licensing

DEMODULATION CIRCUIT FOR AC MOTOR CURRENT SIGNATURE ANALYSIS

Key words: Nondestructive testing; ac electric motors; electrically driven equipment; spectral analysis

Motor current signature analysis (MCSA) diagnoses mechanical problems in equipment driven by electric motors by capturing, processing, and analyzing the electrical signals generated by the motor. This technology, developed at ORNL, is currently available for licensing from Energy Systems. In applying MCSA to ac-motor-driven equipment, one of the issues faced was how to deal with the 60-Hz line frequency and its harmonics.

Because of their magnitudes, the 60-Hz frequency and its harmonics dominate the frequency spectrum of any signal detected in the

power line feeding the electric motor. In the original development of MCSA, this problem was solved by effectively demodulating the desired signal from the 60-Hz carrier by means of an rms-to-dc converter. However, because of the characteristics of this detection device, it also acted as a low-pass filter, partially suppressing the desired frequencies near and above 60 Hz.

An improvement to the existing demodulation technique, which provides a higher measurement resolution and sensitivity, has been developed for application to MCSA. This technique uses two well-known detection methods: amplitude and phase demodulation. The application of these methods to MCSA is shown in Fig. 1.

It has been found that periodic, load-induced variations in motor current signals simultaneously

Fig. 1. Block diagram of the demodulation circuit for ac motor current signature analysis.

produce amplitude-modulation (AM) and phase-modulation (PM) effects. However, certain types of frequency sources tend to produce proportionately more of one type of modulation than the other. For that reason, both AM and PM detectors are provided in this design for analysis and comparison. The AM demodulator can be provided in the form of integrated electronic chips or discrete element circuits. It may be one of several types, but preferably it should be a synchronous or "product" detector. The PM demodulator can be a quadrature, discriminator, FM feedback, phase-locked loop, or pulse-counting/pulse-width type. In addition, the use of phase demodulation can provide an instantaneous power-factor measurement for the motor if the PM detector is referenced to the applied ac line voltage rather than to the current.

This demodulation system can be implemented with standard electronic components and added

onto the other spectral analysis equipment needed to implement MCSA. Although the circuit and MCSA were developed initially for monitoring motor-operated valves and compressors in gaseous diffusion uranium-enrichment plants, the techniques may be applied as well in industry for monitoring, diagnostics, trend analysis, and preventive maintenance programs for a wide variety of electrically powered devices.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

"Motor Current Signature Analysis Process," Bulletin No. 608, *Technology Applications Bulletins*, Oak Ridge National Laboratory (Winter 1988).

MEASUREMENTS AND CONTROLS

TEST SYSTEM FOR EROSION-CORROSION STUDIES

Key words: Coal conversion systems; erosion; erosion-corrosion testing; material degradation; scanning electron microscope

The combination of erosion and corrosion can cause considerable material degradation in systems such as gas turbines and coal conversion systems. For that reason, many researchers have studied these problems. Conventionally, this research has been carried out in two ways.

One test is performed with a gas gun, which directs a gas stream loaded with solids onto a target. The test particles are about the size of the erosive particles in systems of interest. However, because many grams and even hundreds of grams of particles strike the surface, only cumulative effects are measured; little or nothing is learned about the response of the target material to individual impacts. Another technique, in which single particles are used to investigate the basic deformation response of the target, employs particles considerably larger than those found in the systems of interest. Consequently, it is not clear that the material behavior observed in the experiments is characteristic of that under impacts by much smaller particles.

Researchers in ORNL's Metals and Ceramics Division have constructed a system that permits studies of the impact effects of single particles of the size found in coal conversion systems. Furthermore, the test samples can be examined

at temperature and under corrosive conditions with a scanning electron microscope. Erosion and corrosion studies have been performed separately with this device, and eventually these tests will be performed simultaneously.

The experimental system combines a commercially available scanning electron microscope (SEM) with a gas-operated gun (Fig. 1) that shoots single particles at a specimen at high velocity and a hot stage that heats both the specimen and the corrosive test gas and directs the gas onto the specimen. The specimen holder and hot stage can be rotated about the stationary gun so that the angle of impact can be varied from 10 to 90° (perpendicular to the flight path of the projectile). To rapidly remove both the propellant gas and the corrosive test gas, a turbomolecular pump supplements the SEM's standard pumping system. A custom-designed photoelectric velocity measurement system, built into the barrel of the gun, measures the velocity of the projectile. The velocity measurements can be used to relate momentum or kinetic energy values to the damage caused by the projectile striking its target.

Two commercially available measuring devices, separate from the test assembly, are used to evaluate test samples. A profilometer is used to make two-dimensional scans of the surfaces resulting from impacts or corrosion (Fig. 2). An ultralow-load microindentation apparatus measures the hardness in and around the impact craters. For example, indentation tests of craters

Fig. 1. Schematic drawing of the currently used erosive-particle gun (not to scale). The gun is fed by a gear-driven, 20-shot rotary magazine. Each chamber containing a projectile ball is accompanied by an alignment hole; light passing through the alignment hole from a light-emitting diode to a detector indicates that a projectile is correctly positioned to fire.

(a)

in a nickel-based alloy showed that the bottom of a crater was generally harder than the surrounding unaffected surface. In addition, an image-enhancement system was added to the imaging electronics; this addition enables creation of a permanent digital record of images and produces images with greatly reduced noise levels.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

J. R. Keiser, *Design, Construction, and Initial Results for an Erosion-Corrosion Test System*, ORNL/TM-10049, Oak Ridge National Laboratory (May 1986).

(b)

Fig. 2. (a) SEM image of an erosion crater formed by the impact of a tungsten carbide ball into a target sample and (b) a two-dimensional profilometer trace of the same crater.

MEASUREMENTS AND CONTROLS

AN AUTOMATED HOT-CELL TITRATION SYSTEM

Key words: Titration system; hot cell; nuclear fuel reprocessing

Operation of a nuclear-fuel-reprocessing plant requires an analytical support laboratory capable of meeting process-control, product-quality, and nuclear-safeguard requirements. Because of the radioactivity accompanying many of the samples, the analytical instruments must be selected, modified, or specifically developed for use in hot cells. Titrimetric procedures have been used successfully in hot cells and are generally immune to radiation-induced bias. The principal disadvantage of titration, which has led to the development of automated titration systems, is that it is generally a time- and manpower-intensive procedure.

An automated titration system has been developed in ORNL's Analytical Chemistry Division specifically for operation in a hot-cell environment (Fig. 1). This system is composed of an in-cell titrant delivery unit, in-cell electronics systems, computer interfaces, a microcomputer, and software. The titrant delivery unit inside the hot cell is linked to the microcomputer in the operator area of the laboratory by means of a signal-distribution box.

The operating principle of the titrant delivery unit is the piston displacement of liquid. The delivery drive consists of a stepping motor that turns a precision-ground lead screw. Attached to the motion-conversion nut is a permanent magnet

Fig. 1. In-cell system of the ORNL remote titrator.

that actuates Hall-effect proximity switches to stop the stepping motor at the full and empty positions of the buret. The end of the piston push rod connects to the piston with the coupling system shown in Fig. 2. The orientation of the piston push rod is fixed; the piston is free to rotate. When the push rod is positioned at the buret change position, this coupling system allows the buret to be removed and attached by sliding it horizontally. The buret is positioned on the delivery unit housing by a spring-loaded locating pin with a hemispherical head and is clamped securely to the delivery unit housing. A

Fig. 2. Push rod-to-piston coupling for titrant delivery unit.

three-way solenoid valve mounted on the buret housing is used to control the direction of fluid flow during all movements of the buret piston.

Interchangeable burets having barrels fabricated from precision-bore Pyrex tubing are available with capacities of 5, 10, and 25 mL. The means of the absolute error in delivered volume for these burets are 0.9, 1.1, and 1.8 μL , respectively.

An elevator module is used to position the titration vessel under the electrodes and titrant delivery tubes. It is powered by a reversible ac motor; limit-of-travel signals are generated by Hall-effect proximity sensors, which are actuated by a permanent magnet attached to the rear of the elevator table.

Data indicate that the titrant delivery unit performs its task with high accuracy and precision. The titration system has been used successfully for potentiometric titrations for several years in support of nuclear-fuel-reprocessing R&D activities. Evaluation studies have shown that this system's accuracy and precision are not limited by titrator performance factors but by sample preparation procedures, the equilibrium constant of the titration reaction, and statistical uncertainties associated with the standard titrant.

This system is also capable of performing amperometric titrations. Changing between the potentiometric and amperometric modes of operation involves changing the in-cell transducers, the in-cell electronics, and the titrator control program.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

L. N. Klett, *A Hot-Cell Titration System*, ORNL/TM-10780, Oak Ridge National Laboratory (July 1988).

MEASUREMENTS AND CONTROLS

NEW APPLICATIONS OF SILICON MICROMACHINING

Key words: Miniature sensing devices; alpha detector; small-angle X-ray scattering

The use of photolithography and anisotropic etching of silicon wafers to make strong, thin membranes has created a large family of miniature sensing devices such as pressure transducers and accelerometers. Engineers at ORNL have fabricated thin windows by anisotropic chemical etching of single-crystal silicon. These windows are mechanically strong and yet transparent to many kinds of radiation. Two applications of these windows have been developed: a rugged alpha detector and a fluid sample cell for small-angle X-ray scattering.

In conventional alpha-radiation detectors, the photomultiplier tube is shielded by a window that blocks ambient light but allows alpha particles to pass through. Aluminized Mylar, the most commonly used window material, is easily damaged by particles such as dirt and sand. Therefore, it is expensive to use alpha detectors in the field because they have very short life expectancies. Experiments have shown that etched silicon is an acceptable replacement for aluminized Mylar.

The new design (Fig. 1) is substantially more resistant to environmental contamination and mechanical damage than the conventional design. This rugged alpha detector is physically compatible with existing instruments, so it can be easily retrofitted to replace the more fragile Mylar-window design. Its detection efficiency is

Fig. 1. Design for a rugged alpha detector using a chemically micromachined silicon wafer. Thicknesses are not to scale.

comparable to the older detector, yet it is highly resistant to thermal shock, abrasion, and moisture.

The second application of etched silicon wafers that was studied was their use as containers for liquid samples to be studied by the ORNL 10-m small-angle X-ray scattering (SAXS) camera (Fig. 2). It is difficult to examine liquid samples in the SAXS because the X-ray beam line is evacuated, and the liquid must therefore be contained in a sealed capsule with thin windows. Two common window materials are beryllium and Mylar; both materials present difficulties. Beryllium windows have unacceptably high scattering, and Mylar windows tend to balloon outward, changing the effective sample thickness. Experiments have shown that etched silicon wafers would not have either of these drawbacks; they would also be able to form strong, airtight joints by soldering to low-expansion alloys.

Fig. 2. Fluid sample holder for small-angle X-ray scattering. Note that a hole could also be drilled from the bottom to facilitate filling, draining, and cleaning.

Additional information:

Office of Technology Applications
 Martin Marietta Energy Systems, Inc.
 P.O. Box 2008
 Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

R. J. Lauf et al., *New Applications of Silicon Micromachining*, ORNL/TM-10590, Oak Ridge National Laboratory (June 1988).

MEASUREMENTS AND CONTROLS

INSTRUMENTATION SYSTEM FOR PRECISION MEASUREMENTS
OF FLOW VECTORS

Key words: Three-dimensional fluid-flow vector;
Pitot tubes; data acquisition

A new instrumentation system developed at ORNL can be used to make precision measurements of the three-dimensional fluid-flow vector in open channels, tunnels, and tubes. This system was designed originally to measure flowing water at 0 to 80°C, but it could be adapted to measure other liquids or gases. Probes fabricated to date have a Monel tube sheath with nickel capillary-tube Pitots set in a silver solder matrix, but other construction materials could be used if required. In some applications, measurements can be made at static pressures up to several hundred pounds per square inch. The system is composed of three major components: a fixed flow probe, a sensor/electronics module (Fig. 1), and a computer-based data acquisition and analysis system.

The 0.250-in.-diam flow probe has a 40° (half angle) conical tip with seven 0.062-in. Pitot tubes in a close-packed hexagonal array. The probe has a cone of acceptance of $\pm 30^\circ$ in both pitch and yaw. The seven Pitot tubes extend to a seven-channel sensor/electronics module several feet away. For water speeds of 20 to 60 ft/s, differences in velocity magnitude can be resolved to $\pm 0.1\%$ and angular differences to 0.1° . Accuracy is estimated at 1% for magnitude and 1° for vector angles.

The sensor/electronics module (1.75 in. diam and 6 in. long) is sealed and filled with oil. It contains seven solid-state pressure transducers, seven constant-current sources and analog signal-conditioning channels, and an eight-channel multiplexer that scans the transducer array and transmits data to the data acquisition and analysis system. The eighth channel of the multiplexer transmits a signal proportional to the temperature of the pressure transducer microchip in a typical measuring channel. The frequency response of the module is restricted by a 100-Hz low-pass filter in each analog channel to avoid signal errors caused by aliasing.

The sensor/electronics module includes a special diaphragm valve for liquid-flow applications. This valve permits the flushing of the fluid-sensing tubes, a process which can be followed by sealing to isolate the individual sensing channels. A sealed bladder inside the module equilibrates the pressure inside the module with the static pressure of the fluid without allowing the fluid to contaminate the electronics. The computer-based data acquisition and analysis system, which was designed to acquire data from 30 probes and is remote from the sensor/electronics module, updates the pressure measurements from each probe at a 2-kHz rate.

The flow-measurement system requires empirical calibration in a tow tank, water tunnel, or wind tunnel to develop a calibration matrix

Fig. 1. Components of flow vector instrumentation system. The sensing/electronics module (top) is connected to the fixed probe (bottom), which contains seven Pitot tubes in a hexagonal array.

covering the speed, yaw, and pitch ranges of expected use. Calibration coefficients developed from these measurements allow the data acquisition and analysis system to calculate flow vectors from the relationships among the Pitot pressure measurements independently of any static or reference pressure measurement. However, the local pressure inside the sensor/electronics module cannot differ from the total fluid pressure at the Pitot port by more than 25 psi without potential damage to the solid-state pressure transducers.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

"A New Instrumentation System for Precision Measurements of Flow Vectors, *I&C Signals*, Development Bulletin No. 7, Oak Ridge National Laboratory (January 12, 1988).

Technology Applications Bulletins

Bulletin Number 683

Oak Ridge National Laboratory

MEDICAL AND BIOMEDICAL TECHNOLOGY

RADIOLABELING TECHNIQUE FOR EARLY CANCER DETECTION

Key words: Radiolabeling; maleimides; radioimmunodetection; radioimmunotherapy

Researchers in the Nuclear Medicine Group of ORNL's Health and Safety Research Division have developed a new radiolabeling technique that may provide a safe and an effective method for the early diagnosis and treatment of cancer. This technique exploits the immune system's ability to produce antibodies that target specific proteins produced by cancer cells. It is an improvement over previous techniques for radiolabeling antibodies because the radiolabel (radioactive iodine) remains firmly bound to the antibody.

By chemically binding a radioactive isotope to these special antibodies, the ORNL team has produced new compounds that can carry radioactive isotopes through the bloodstream to a malignant tumor (Fig. 1). In this way, researchers can locate a tumor by using special imaging devices (radioimmunodetection) or, by using a different isotope, destroy cancerous cells (radioimmunotherapy). These compounds can locate a primary tumor early, before it has had time to spread the seeds of cancer throughout the rest of the body.

In the conventional procedure, radioactive iodine (^{123}I or ^{131}I) is attached to the amino acid tyrosine, which is a part of the antibody. However, using conventionally radioiodinated antibodies for cancer diagnosis or treatment has the drawback of in vivo deiodination (the release of iodine from the labeled antibodies injected into

Fig. 1. Steps involved in the preparation of radiolabeled antibody for immunodetection and therapy of cancer. (a) Tumor cells from a cancer patient are injected into a mouse; the mouse produces antibodies specific to antigens produced by the cancer cells. (b) The antibody-producing cells are cloned and produce more antibodies. (c) Antibodies from the cloned cells can be labeled with radioactive iodine by means of the ORNL technique. (d) The labeled antibodies carry the isotope to the cancer site, initially in test animals and then, if successful, in human cancer patients.

the body). Two problems are caused by in vivo deiodination: the therapeutic in vivo half-life for the radiolabeled antibody is reduced, and unwanted, potentially cancer-causing radioactive iodine becomes trapped in the thyroid or stomach, resulting in an increased exposure to radiation.

The technique developed at ORNL minimizes deiodination. The researchers designed and synthesized a new radiolabeled maleimide agent (an organic compound containing nitrogen, hydrogen, and oxygen), which can be covalently attached to a benzene ring (phenyl) that includes a stably bound ^{125}I atom. The new imaging agent, called iodophenylmaleimide, can be prepared using an iodine-reactive mercury acetate maleimide kit developed at ORNL. This imaging agent has a strong affinity for the sulfhydryl (thiol) group that is naturally or artificially attached to an antibody.

Although ^{125}I was selected for experimental reasons, the new agent could also be labeled with ^{123}I for diagnosis or with ^{131}I for therapy. Other radioisotopes that could be used with modifications of functional groups on the maleimide agent are indium-111 (^{111}In), yttrium-90 (^{90}Y), and rhenium-188 (^{188}Re).

A preliminary study carried out at the University of Michigan, using nude mice implanted with melanoma and colon tumors, showed that the ORNL maleimide agent can label antibodies that seek out these types of cancer cells and that in vivo deiodination of the labeled antibody is insignificant (Fig. 2). Studies done with rats at ORNL compared the performance of the ^{125}I -maleimide-labeled antibody with the performance of conventionally prepared (^{131}I -tyrosine-linked) antibody and confirmed that using the ORNL agent results in less release and therefore less thyroid uptake of the radioactive iodine.

Fig. 2. In studies at the University of Michigan using nude mice, the maleimide-labeled antibody resulted in dramatically lower iodine uptake in thyroid gland tissue compared with iodine uptake from use of the same amount of antibody labeled by the conventional technique using tyrosine linkage. The low thyroid uptake indicates a relatively high in vivo stability of the ORNL-developed agent, iodophenylmaleimide.

U.S. Patent Number 4,735,792, "Radioiodinated Maleimides and Use as Agents for Radiolabeling Antibodies," has been granted for this technology.

Additional information:

Office of Technology Applications
 Martin Marietta Energy Systems, Inc.
 P.O. Box 2008
 Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

P. C. Srivastava, "New Radiolabeling Technique May Aid Early Cancer Detection," *Oak Ridge National Laboratory Review* 21(1), 34-5 (1988).

P. C. Srivastava, "Radioiodinated Maleimides and Use as Agents for Radiolabeling Antibodies," U.S. Patent 4,735,792 (1988).

P. C. Srivastava et al., "Evaluation of N-(p-[^{125}I]iodophenyl)maleimide for Labeling Monoclonal Antibodies," pp. 296-97 in *Seventh International Symposium on Radiopharmaceutical Chemistry Abstracts*, University of Groningen, the Netherlands, 1988.

ENERGY CONSERVATION

Available for Licensing

TRIPLE-EFFECT ABSORPTION CHILLER USING TWO REFRIGERATION CIRCUITS

Key words: Absorption chiller; absorption refrigeration; refrigeration; air-conditioning

In the United States, most large buildings are air-conditioned using electrically driven chillers. Absorption chillers, which are driven by natural gas, provide an alternative to electric chillers. However, currently available absorption chillers that use conventional single-effect and double-effect cycles are relatively inefficient compared with good electric chillers. A new, triple-effect absorption circuit using two refrigeration circuits (Fig. 1), which greatly improves cooling efficiency

of absorption systems, has been designed and demonstrated with computer simulations at ORNL.

Conventional absorption chillers are not economical in most parts of the United States, but because of high foreign fuel costs and scarce electricity, single-effect and double-effect chillers are widely used and are growing in use annually elsewhere in the world. In the late 1960s, U.S. manufacturers were virtually without foreign competition for the sales of absorption chillers worldwide. However, since the early 1970s, the Japanese have been steadily improving the conventional double-effect chillers. Japanese

Fig. 1. Diagram of the new triple-effect absorption chiller using two refrigeration circuits.

manufacturers now dominate world manufacturing and sales of absorption chillers.

The new triple-effect absorption chiller concept developed at ORNL is calculated to be 30 to 60% more efficient than the best equivalent double-effect chiller now manufactured by the Japanese. In addition, because the triple-effect cycle uses heat more efficiently than double-effect cycles, the total heat-exchange requirements for the triple-effect cycle are less than they are for double-effect cycles, making the triple-effect chiller potentially less expensive to build. Figure 2 shows the energy efficiencies of all existing technology compared with the triple-effect efficiency levels.

In an absorption refrigeration circuit, a primary fluid (refrigerant) in a gaseous state is absorbed by a secondary fluid (the absorbent). This absorbent/refrigerant combination is known as a solution pair. Heat absorbed by the refrigerant vapor is transferred to the absorbent and rejected by the absorbent to a heat sink. Heat from an external source is supplied to maintain the continuity of the cycle. Currently, absorption chiller designs include single-effect, double-effect, and dual-loop systems.

The cooling efficiency, or coefficient of performance (COP), of a cooling system is determined by the ratio of cooling effect to heat

input. The COP of single-effect chillers is typically between 0.5 and 0.7. Performance can be improved to COPs between 0.7 and 1.25 by using the double-effect evaporation principle and a double-effect system, in which external fuel energy can be effectively used twice in the high- and low-temperature generators. The efficiency of dual-loop cycles is about the same as that for double-effect cycles in air-conditioning and refrigeration applications.

The new triple-effect absorption chiller design yields a cooling COP of about 1.7 to 1.9. Two distinct single-effect refrigeration circuits, operating at high and low temperatures, are combined to effectively use the external heat input three times. A modification to a typical refrigerant/absorbent solution pair allows the high-temperature circuit to operate at a higher temperature than can be obtained compared with conventional double-effect solutions. The reject heat of both the condenser and the the absorber of the high-temperature circuit is directed to the generator of the low-temperature circuit, thereby producing about 50% more refrigerant vapor than double-effect chillers can.

U.S. Patent Number 4,732,008 has been granted for the triple-effect absorption chiller.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge TN 37831-6257

Telephone (615) 574-4192, FTS 624-4192

R. C. DeVault, "Triple Effect Absorption Chiller Utilizing Two Refrigeration Circuits," U.S. Patent No. 4,732,008 (March 22, 1988)

R. C. DeVault, "DOE Absorption Program Overview," pp. 105-109 in *Proceedings of the 2nd DOE/ORNL Heat Pump Conference: Research and Development on Heat Pumps for Space Conditioning Applications*, Crystal Gateway Marriott, Washington, D.C., April 17-20, 1988, Oak Ridge National Laboratory, August 1988

Fig. 2. Absorption cycles have been identified with performance potential well beyond current technology.

ENERGY CONSERVATION

Available for licensing

SEVEN-EFFECT ABSORPTION CHILLER USING THREE REFRIGERATION CIRCUITS

Key words: Absorption chiller; absorption refrigeration; refrigeration; air-conditioning; heating

The seven-effect absorption chiller is a concept currently being studied at ORNL. This new absorption chiller design, which uses three

refrigerant circuits (Fig. 1), can be used as an absorption cycle for air-conditioning. Various configurations of this cycle are also possible that would provide heat during the winter.

Absorption refrigeration cycles are heat-operated cycles in which a primary fluid (refrigerant) in a gaseous state is absorbed by a secondary fluid (the absorbent). This

Fig. 1. The seven-effect absorption cycle. A heat exchanger transfers reject heat from the condenser and absorber from circuit 1 to circuit 2 and from circuit 2 to circuit 3. This concept produces 1 unit of refrigeration effect in the high-temperature evaporator (circuit 1), 2 units in the medium evaporator (circuit 2), and 4 units in the lower evaporator (circuit 3), yielding a total of 7 units of refrigeration effect for 1 unit of external thermal energy.

absorbent/refrigerant combination is known as a solution pair. The unique feature of the seven-effect chiller is that three thermally coupled single-effect absorption cycles operate to effectively use heat input seven times, thereby increasing efficiency substantially. It is not possible to use the same solution pair for all three single-effect cycles; different solution pairs can be selected to maximize efficiency.

Because of its higher efficiency, the seven-effect system would use less than 50% of the primary energy needed to drive the best air-conditioning systems now available. This new concept offers the potential of an improved coefficient of performance (COP), the measure of efficiency given by the ratio of heat energy extracted for cooling (or heat added for heating) to the work needed to operate the cycle. The

COP for the seven-effect absorption chiller is in the range 2.19 to 3.12. By comparison, the COP of a single-effect absorption cycle is typically 0.5 to 0.7. More-efficient double-effect and dual-loop cycles both have about the same COP (1.0 to 1.2).

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-E 37
Telephone: (615) 574-4192; FTS 624-4192

No further documentation is available for this technology.

Technology Applications Bulletins

Bulletin Number 686

Oak Ridge National Laboratory

ENERGY CONSERVATION

BUILDING FOUNDATIONS RESEARCH AGENDA

Key words: Building foundations; thermal efficiency; research program

A significant amount of heat is lost each year in the United States from houses with poorly insulated foundations. Most of these foundations have substantial surface area and less resistance to heat loss than a double-pane window. Little had been done to reduce this waste of energy until ORNL conducted a study for DOE and

recommended that a research program be undertaken to provide data for energy-efficient foundation design. As a result of this recommendation, the DOE Building Foundations Research Review Panel, composed of buildings specialists from both the public and private sectors, convened to set the agenda for a cooperative research program (Fig. 1).

Members of this panel produced the Building Foundations Research Agenda by selecting and

Fig. 1. Flow chart of Building Foundations Research Program.

ranking specific issues concerning the optimization of foundation construction. This agenda addresses the interactions of a variety of factors, including thermal performance, structural integrity, indoor air quality, radon mitigation, waterproofing, drainage, and moisture migration. The research described in this agenda is applicable primarily to new residential construction with masonry foundations, including slab-on-grade, crawl-space, and basement systems. To a lesser extent, pressure-treated wood systems, foundations for small commercial buildings, and retrofits of existing buildings are also considered.

The major objectives of this ongoing research are to improve the technical information about building foundations and to disseminate that information effectively to the buildings community. Improvements to the technical base include accurate soil characterization for calculating foundation heat loss, a validated foundation heat- and mass-transfer algorithm that can be coupled to whole-building simulation models, critical experimental results from one or more well-characterized test sites, and detailed field measurements and design tools that enable builders to estimate the thermal performance of whole buildings. This information will be disseminated principally through publication of

research results and handbooks for designers and builders.

The ORNL report, *Building Foundations Research Agenda*, contains the agenda, the details of how it came into existence, and a list of the review panel members. The *Building Foundation Design Handbook*, proposed and outlined in this report, has since been written and is currently available. This handbook serves as a companion to the new ASHRAE Standard 90.2, *New Residential Construction*.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

DOE/ORNL Building Foundations Research Review Panel
and J. Christian, *Building Foundations Research Agenda*,
ORNL/CON-222, Oak Ridge National Laboratory
(December 1986).

Kenneth Labs et al., *Building Foundation Design Handbook*,
ORNL/Sub-72143/1 (May 1988).

"Assessment of the Energy Savings Potential of Building
Foundations Research," Bulletin No. 634, *Technology
Applications Bulletins*, Oak Ridge National Laboratory.

ENERGY CONSERVATION

AN ENHANCED COMPUTER PROGRAM FOR MODELING ABSORPTION
HEAT PUMP SYSTEMS

Key words: Absorption systems; chemical heat pumps; computer simulation

The need for reliable and effective system-modeling programs for absorption systems has grown with the development of working chemical heat pumps. Several computer models have been developed, but these models can only simulate a single system having a particular design, flow arrangement, and working material. Researchers at Technion (the Israel Institute of Technology), under subcontract to ORNL, have developed a modular, user-oriented simulation program that can be used to model a variety of absorption-system configurations. This program, called ABSORB, has been enhanced by further research in ORNL's Energy Division.

The main ABSORB program contains unit subroutines and property-data subroutines. The unit subroutines contain all the fundamental equations applicable to the physics of standard absorption system components (such as absorbers, desorbers, evaporators, and condensers). The user can specify individual unit subroutines, which are then called up by the main ABSORB program. The connection between different units is made automatically by the main program, which specifies the output of one to be the input of another. The unit subroutines call on the property-data subroutines for the

thermodynamic properties of the working materials. This separation between the unit subroutines and property-data subroutines provides the flexibility for each unit to operate with different working materials.

The original code for ABSORB has been modified in a continuing effort to improve its robustness, flexibility, and applicability. Modifications include (1) a revised strategy for solving the system equations, (2) increased modularization of the program, and (3) efforts to employ the code to determine an optimum economic design of a heat pump system.

The solution routine originally selected was written specifically for the simultaneous solution of a system of nonlinear algebraic equations. The revised approach uses a nonlinear optimization program, which permits the user to specify bounds on the variables and inequality relationships among the variables as a part of the problem statement, thus simplifying the treatment of these constraints.

The program was modified to increase its modularity and thereby its readability and its adaptability in regard to future enhancements. This modification was achieved principally by employing separate routines to generate the constraint equations and their first derivatives. Thus, calculations of overall material balance, component material balance, enthalpy balance, heat-exchanger energy balance, and equilibria are

performed in separate subroutines called by the unit subroutines instead of being calculated in line in each unit subroutine.

The ABSORB code was validated for three systems that use a nonvolatile, lithium bromide (LiBr)-water working material. Computer simulations of single-stage and double-stage heat transformers and a single-stage chiller (Fig. 1) were validated against experimental data. Given the constraints of the testing, a close correlation was found between the predictions and the measurements.

Additional information:

Office of Technology Applications
 Martin Marietta Energy Systems, Inc.
 P.O. Box 2008
 Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

Gershon Groseman and Elizabeth Michelson, *Absorption Heat Pump Simulation and Studies: A Modular Computer Simulation of Absorption Systems, Final Report*, ORNL/Sub/83-43337/2, Oak Ridge National Laboratory (April 1986).

Richard L. Cox, *Improvements and Enhancements of the ABSORB Computer Program for Modeling Chemical Absorption Heat Pump Systems*, ORNL/TM-9957 (July 1986).

Fig. 1. Results for the single-stage chiller with a LiBr-water working material.

Technology Applications Bulletins

Bulletin Number 688

Oak Ridge National Laboratory

ENERGY CONSERVATION

INFILTRATION REDUCTION FOR SINGLE-FAMILY HOUSES

Key words: Conservation retrofits; low-income housing; infiltration reduction

Standard infiltration retrofit procedures to improve a house's thermal efficiency often include routine caulking or weather-stripping of doors and windows. However, these areas may not be the major contributors to a home's infiltration problems; walls, ceilings, attic accesses, fireplaces, electrical outlets, or other areas may also need attention. A house having too little infiltration or ventilation can also have problems. Standards must be met to protect the integrity of the structure and the health and comfort of its occupants.

The DOE Office of Buildings and Community Systems' Building Energy Retrofit Research Program commissioned ORNL to develop a procedure by which retrofits could be made more efficiently. A joint project was carried out, during which ORNL's retrofit audit program was field-tested and an infiltration retrofit procedure developed by the Wisconsin Energy Conservation Corporation was evaluated.

The Wisconsin retrofit procedure employs a blower door, which is a device that either pressurizes or depressurizes a house to aid in locating leaks and to allow a measure of a house's leakiness. Proper use of the blower door can be a great help in identifying and repairing significant infiltration leaks within a house. A fan is mounted into the envelope of a structure, normally a door (Fig. 1). Varying the speed of the

(a)

(b)

Fig. 1. (a) Blower door installed. (b) Diagram showing the components of the blower door assembly.

fan varies the indoor-outdoor pressure differential. Once this system is operating, leaks can be pinpointed by feeling for drafts or by observing the movement of smoke produced by smoke sticks.

To measure the effects of infiltration retrofits, both the pressure differential and the rate of air flow through the fan are measured. The flow rate through the fan must equal the air-leakage rate from the house at the measured pressure differential. Division of this volumetric flow rate by the house volume gives the number of air changes per unit of time at the pressure differential. For example, the number of air changes per hour at 50-Pa (n -ACH50) depressurization were used in the ORNL study to compare leakage rates before and after retrofits.

The retrofits in this study produced an average 16% reduction in air-leakage rate. For the seven houses recommended for retrofit, 89% of the targeted reductions were accomplished with 76% of the recommended expenditures. The average cost of retrofits per house was reduced by a factor of four compared with previous programs. The average payback period for recommended retrofits was 4.4 years (based on predicted energy savings computed from achieved air-leakage reductions). Although exceptions occurred, the procedure's 8-ACH50 minimum initial leakage rate for advising retrofits to be performed appeared a good choice, based on cost-effective air-leakage reduction. Houses with initial 7-ACH50 leakage rates or below consistently required substantially higher costs to achieve significant air-leakage reductions.

No statistically significant average annual energy savings were detected as a result of the

study's retrofits. Measured savings for individual houses varied widely in both positive and negative directions, indicating that the results were affected by factors not considered in the study. Recommendations to improve the retrofit procedure include more extensive training of retrofit crews, checks for minimum air-exchange rates to ensure air quality, and addition of the basic cost of determining the initial leakage rate to the recommended expenditure level. Recommendations for the field test of the procedure include increasing the number of houses in the sample, timely examination of metered data to detect anomalies, and monitoring indoor temperatures. Although inappropriate in a field-test procedure, an investigation into the effects of air-leakage rate reductions on heating loads needs to be performed.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

M. B. Gettings, L. N. McCold, and J. A. Schlegel, *Field Test Evaluation of Conservation Retrofits of Low-Income, Single-Family Buildings in Wisconsin: Blower-Door-Directed Infiltration Procedure, Field Test Implementation and Results*, ORNL/CON-228/P5, Oak Ridge National Laboratory (June 1988).

"Energy-Conserving Retrofit Audit for Single-Family Buildings," Bulletin No. 665, *Technology Applications Bulletins*, Oak Ridge National Laboratory.

ENERGY CONSERVATION

OCCUPANT EVALUATION OF COMMERCIAL OFFICE LIGHTING

Key words: Commercial lighting; energy standards; design guidelines

Electric lighting accounts for an estimated one-third of the energy used in commercial buildings. Lighting energy standards and design guidelines are important determinants of energy use in buildings, but because of inadequate empirical data and analysis, these standards and guidelines have been based primarily upon professional judgment. Thus, there is little assurance that recommended lighting values requiring the lowest possible energy use provide optimal user satisfaction and comfort.

A research effort was undertaken to begin developing an archival data base to aid in better understanding the relationship between measures of lighting power density and the quality of the lighting environment. Initiated by the American Institute of Architects Foundation, this research has received extensive review by members of the professional, industrial, and research communities. The results are summarized in a three-volume report published by ORNL:

- Volume 1, a description of the research methodology and a bibliography;
- Volume 2, a preliminary analysis of the data; and
- Volume 3, a data archive and a data-base management system.

The research procedure included soliciting information from occupants via questionnaires and obtaining expert judgments (for the initial

buildings) from a team of four experts who walked through the buildings and evaluated the sampled work stations. These subjective responses were complemented by a series of field measurements of photometric, acoustic, and thermal conditions. Conceptually, the process was to treat the subjective responses as the qualitative measures and to compare the unit-power-density and the photometric data against these measures.

This study is considered to be preliminary in nature; with further research, it may provide informed guidance for establishing lighting standards and other policy issues. Many tentative findings emerged from the analysis. For example, one surprising finding was that lighting satisfaction tends to decrease as lighting power density increases (Fig. 1). Occupants who

Fig. 1. Work station lighting satisfaction compared with lighting power density. (Numbers in parentheses refer to the numbers of work stations for which both lighting-power-density values and occupant responses have been recorded.)

described their work station spaces as "dim" also tended to be dissatisfied with the lighting at their work stations. Occupants who were most bothered by bright lights and glare were most likely to express dissatisfaction with the lighting at their work stations (Fig. 2). No relationship

was found between work-related activities of employees and indicators of lighting quality.

Additional information:

National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161

Telephone: (703) 487-4650; FTS 737-4650

G. Gillette and M. A. Brown (ed.), *Occupant Evaluation of Commercial Office Lighting, Volume 1: Methodology and Bibliography*, ORNL/TM-10264/V1, Oak Ridge National Laboratory (November 1986).

R. W. Marans and M. A. Brown (ed.), *Occupant Evaluation of Commercial Office Lighting, Volume II: Preliminary Data Analysis*, ORNL/TM-10264/V2, Oak Ridge National Laboratory (November 1987).

G. Gillette and M. A. Brown (ed.), *Occupant Evaluation of Commercial Office Lighting, Volume III: Data Archive and Database Management System*, ORNL/TM-10264/V3, Oak Ridge National Laboratory (August 1987).

Fig. 2. Perceived discomfort from reflected glare compared with mean illuminance. (Numbers in parentheses refer to the numbers of work stations for which both lighting-power-density values and occupant responses have been recorded.)

ENERGY CONSERVATION

DOCUMENTATION FOR RESIDENTIAL REFERENCE HOUSE ENERGY DEMAND MODEL

Key words: Computer model; forecasting; energy demand; energy consumption; housing; heating; air-conditioning

The ORNL Residential Reference House Energy Demand Model (RRHED) is a computer-based end-use simulator that forecasts energy demand based on a detailed evaluation of how households use energy for particular appliances. RRHED is a

mid- to long-term theory-based engineering and economic stock-adjustment model that simulates energy use and the impact of policies over a 20- to 30-year period. Energy consumption and policy impacts are forecast by fuel type and category of equipment (Fig. 1).

The four-volume report, *The ORNL Residential Reference House Energy Demand Model (ORNL-RRHED)*, documents the RRHED model. It contains an overview and summary, a user

Fig. 1. Interaction of model components in the ORNL Residential Reference House Energy Demand Model. The energy use for each reference house is defined in terms of four major components: building stock, use, technology choice, and fuel and equipment choice.

reference guide, a technical description of the RRHED model, and a collection of case studies. This report has two main objectives. First, it introduces RRHED to researchers with little background in end-use modeling. Second, it provides the details that a user needs to understand both the theory behind the model specification and the structure of the code. This information will allow the user to modify subroutines for particular applications.

RRHED is currently being used by a number of analysts throughout the United States. This report provides them with a benchmark for consistent analysis. Also, the user reference guide is necessary because the model is relatively complex and the FORTRAN code used to run it is extensive. Some innovative approaches are applied to general economic problems, which involve the use of sophisticated modeling techniques and novel interactions between engineering and economic data bases. This documentation introduces these approaches to the research community.

The case studies provide examples of how the RRHED model can be used. For example, RRHED was used to predict the influence of proposed building-envelope standards on conservation and fuel choice. These standards were developed by the Northwest Power Planning Council in response to the Pacific Northwest Power Planning and Conservation Act of 1980 (P.L. 96-501). State or local governments within the region were originally required to implement these standards during or before 1986. The focus of the policy analysis study was

whether the council standards were as cost-effective as alternative supply options.

This analysis raised significant and unresolved issues about social policy and social versus private cost-effectiveness of policy. It is argued that as proposed, the standard policy is neither privately nor socially cost-effective. However, the social and private cost-effectiveness of this policy could be optimal if the standards were implemented in the presence of a market-clearing mechanism that would share benefits among builder, homeowner, and utility.

Additional information:

National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161

Telephone: (703) 487-4850; FTS 737-4850

D. M. Hamblin et al., *The ORNL Residential Reference House Energy Demand Model (ORNL-RRHED) Volume 1. Overview and Report Summary*, ORNL/CON-177/V1, Oak Ridge National Laboratory (February 1986).

D. M. Hamblin et al., *The ORNL Residential Reference House Energy Demand Model (ORNL-RRHED) Volume 2. User Reference Guide*, ORNL/CON-177/V2, Oak Ridge National Laboratory (February 1986).

D. M. Hamblin et al., *The ORNL Residential Reference House Energy Demand Model (ORNL-RRHED) Volume 3. Technical Description*, ORNL/CON-177/V3, Oak Ridge National Laboratory (February 1986).

D. M. Hamblin et al., *The ORNL Residential Reference House Energy Demand Model (ORNL-RRHED) Volume 4. Case Studies*, ORNL/CON-177/V4, Oak Ridge National Laboratory (February 1986).

ENERGY CONSERVATION

THE PRINCETON SCOREKEEPING METHOD COMPARED WITH ENERGY END-USE LOAD DATA

Key words: Space heating; residential electricity use; electricity consumption; Princeton Scorekeeping Method; submetered end-use load data

The Princeton Scorekeeping Method (PRISM) is perhaps the best known and most widely used method to adjust residential energy-use data for differences in winter severity. Research was conducted to determine the accuracy of PRISM results, especially the accuracy of its ability to break down total residential energy use into space-heating and non-space-heating components. PRISM results were compared with submetered data that were gathered as part of the Hood River Conservation Project (HRCP).

The submetered data include whole-house and space-heating electricity uses (recorded at 15-min intervals), weather data recorded at the Hood River Experiment Station (also at 15-min intervals), and information obtained from detailed on-site home interviews. HRCP's collection of these comprehensive data provided a rare opportunity to examine the performance of PRISM and identify reasons for differences between PRISM estimates and submetered electric load data.

PRISM estimates were compared with monthly load data and actual monthly utility bills. In addition, data for 12 weeks (instead of the usual 1 year) were used to drive the PRISM model to

determine if 3 months of data could provide accurate estimates.

The results of this study confirmed that PRISM estimates are in almost perfect agreement with whole-house, end-use load data, but that, on average, it overestimates space-heating electricity use (Table 1). The study also revealed that errors in billing data affect the accuracy of PRISM estimates. The accuracy of PRISM estimates based on only 12 weeks of data depends strongly on the season chosen. In general, PRISM

Table 1. Comparison of PRISM estimates with load data for 71 homes that use more than 4000 kWh/year for space heating

	Median	Mean	Standard deviation
<i>Electricity use (kWh/year)</i>			
Total			
Load data	22,500	23,300	6,900
PRISM estimate	22,500	23,300	6,900
Ratio, PRISM/load	1.00	1.00	1.00
Space heating			
Load data	11,600	12,000	5,100
PRISM estimate	10,900	12,500	5,600
Difference, PRISM-load	600	500	2,500
Ratio, PRISM/load	1.05	1.06	0.22
<i>Reference temperature (°F)</i>			
Load data	62.1	61.9	4.0
PRISM estimate	56.0	57.0	6.1
Difference, PRISM-load	-4.4	-5.0	4.5
<i>Model Performance (R²)</i>			
Load data	0.75	0.74	0.09
PRISM	0.97	0.96	0.04

estimates of electricity use for space heating are more accurate for homes that rely primarily on electricity for space heating but do not use much electricity for air-conditioning.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

E. Hirst and R. Goeltz, *Electricity Use for Residential Space Heating: Comparison of the Princeton Scorekeeping Method with End-Use Load Data*, ORNL/CON-203, Oak Ridge National Laboratory (April 1986).

H. Hwang, *Assessment of Princeton Scorekeeping Method Space-Heating Estimates Using End-Use Data from the Hood River Conservation Project*, ORNL/CON-270, Oak Ridge National Laboratory (January 1989).

TRANSPORTATION

REVIEW OF NONRESIDENTIAL TRANSPORTATION ENERGY USE DATA

Key words: Nonresidential transportation; energy use; data source

Because of the Residential Transportation Energy Consumption Survey and other surveys, good data are available describing residential transportation energy use. Data about nonresidential transportation energy use, however, range from very good to virtually nonexistent. An ORNL report written for the Energy Information Administration surveys and evaluates the available data.

Data Source Compendium of Non-Residential Transportation Energy Use lists data sources, levels of detail, frequency of publication, time between data occurrence and data availability, and the probability of continued publication. To the extent possible, the quality of the data is assessed. Data for all modes of nonresidential transportation—highway, air, rail, marine, pipeline, and military—are reviewed. Exhibits of

tables from the various data sources, showing energy-consumption estimates or other data from which measures of energy use may be derived, are included.

For modes of transportation that are the most regulated, a significant amount of data is available. Conversely, for those areas or modes where there is no regulation and the industry itself is rather disjointed, little information is available.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

R. N. McGill and M. C. Holcomb, *Data Source Compendium of Non-Residential Transportation Energy Use*, ORNL/TM-9329, Oak Ridge National Laboratory (November 1985).

TRANSPORTATION

TECHNOLOGY TRANSFER FOR DOE'S OFFICE OF TRANSPORTATION SYSTEMS

Key words: Technology transfer; transportation; case studies; ceramics; reinforced ceramics

Successful transfer of automotive R&D can have wide-ranging applications throughout the industrial community (Fig. 1). The ORNL report, *Technology Transfer for DOE's Office of Transportation Systems: Assessment and Strategies*, contains a review and assessment of technology transfer efforts by the U.S. DOE Office of Transportation Systems (OTS). Barriers to technology transfer are discussed, and

recommendations to improve efficiency are made in this report. An inventory of recent OTS technology transfer efforts is supplemented by nine detailed case studies that demonstrate five distinct approaches to industry:

- contracting to industry,
- licensing,
- demonstration projects,
- user facilities, and
- financial incentives.

One example of how the technology transfer process operates is given in the case study involving whisker-reinforced ceramic composites. In an OTS heat-engine program, a major effort was directed at developing tougher and stronger ceramic materials to meet demanding gas-turbine performance criteria. Because the ceramics industry is typically made up of small concerns having limited R&D budgets and research facilities, improvements necessary for the OTS heat-engine program needed to come from outside the private sector.

Development of whisker-reinforced ceramic composites began at ORNL with funding from DOE's Energy Conversion and Utilization Technologies program. OTS subsequently funded ORNL scientists for further work. The resulting composite consisted of an alumina matrix reinforced with microscopic "whiskers" of silicon

Fig. 1. The primary, secondary, and spin-off audiences for technology transfer efforts by the U.S. DOE Office of Transportation Systems.

carbide, which double the toughness of the normally brittle alumina. The new material is 40% tougher and 25% stronger than nonreinforced ceramics.

Energy Systems obtained a patent waiver from DOE in 1986. In June 1986, Energy Systems granted a license for the composite to Atlantic Richfield's ARCO chemical subsidiary in exchange for a licensing fee, advanced royalties, and future royalties based on product sales. The royalties are shared with the ORNL inventors as part of an incentives program. Remaining monies are placed in a technology transfer fund to support future development of products and processes.

Additional licenses have subsequently been signed with Energy Systems for this technology, primarily for manufacturing fast, long-lasting cutting tools and other wear parts. At least one

of these companies may use the new ceramic in the production of next-generation auto parts. Potential audiences for spin-off development of this technology include manufacturers of silicon-chip packaging, radioactive-waste containment, and spacecraft external heat protection.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

S. A. Snell, M. A. Brown, and A. Zerega, *Technology Transfer for DOE's Office of Transportation Systems: Assessment and Strategies*, ORNL/CON-244, Oak Ridge National Laboratory (April 1988).

ENERGY PRODUCTION

WOOD-BURNING RETROFIT SAVES FUEL AT AN OIL-FIRED STEAM PLANT

Key words: Renewable resource; wood-burning boiler; waste wood; cost analysis

The military services are participating in the Department of Defense Energy Conservation Investment Program (ECIP), in which promising conservation retrofit projects are identified, justified, and implemented. One such project was

undertaken by the U.S. Army at Fort Stewart, Georgia, where a new wood-burning boiler and a wood-conveying system were added to the three oil-fired boilers of the central energy plant (Fig. 1). This retrofit was undertaken to exploit the abundant waste wood available at Fort Stewart. Its success was validated by a team of researchers from ORNL's Energy and Instrumentation and Controls divisions.

Fig. 1. System diagram for Fort Stewart central energy plant, including the added wood-burning system.

During the 1-year postretrofit validation study, the ORNL team gathered data about steam production; wood, fuel oil, and electrical energy consumption; other necessary plant operations; and ambient temperature. Preretrofit operations were simulated by treating actual postretrofit study data as if the new boiler were not in operation. Preretrofit and postretrofit data were compared to determine cost and energy savings.

During the postretrofit study period, the wood-burning boiler produced about 90% of the steam required by the central energy plant to meet seasonal heating and cooling demands. Consequently, over 2.88×10^6 gal of fuel oil were conserved. It was estimated that about 4×10^5 Btu of nonrenewable energy can be saved annually by burning waste wood. A life-cycle cost analysis has projected first-year savings of more than \$1.2 million. The discounted savings ratio is 3.36, and the estimated simple payback period for the ECIP project is 6.7 years.

In addition to the valuable experience gained that can be applied in designing, building, and evaluating wood-burning boiler plants in the future, the study also shows that a postretrofit data can be used to develop preretrofit simulation data, which can then be used for energy and cost comparisons.

Additional information:

National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161

Telephone: (703) 487-4650; FTS 737-4650

M. A. Broders and D. R. Miller, *ECIP Project Validation Plan: Wood Burning Boiler Plant, Project No. 193, Fort Stewart Georgia, ORNL/TM-8933/P1, Oak Ridge National Laboratory (May 1984).*

M. A. Broders and D. R. Miller, *Phase II—Design: ECIP Project Validation Plan: Wood Burning Boiler Plant, Project No. 193, Fort Stewart Georgia, ORNL/TM-8933/P2, Oak Ridge National Laboratory (September 1984).*

M. A. Broders and D. R. Miller, *Phases I and II—Design: ECIP Project Validation Plan: Wood Burning Boiler Plant, Project No. 193, Fort Stewart Georgia, ORNL/TM-8933/P2/R1, Oak Ridge National Laboratory (August 1985).*

M. A. Broders and D. R. Miller, *Energy and Cost Savings Analysis of Wood Burning Boiler Plant, Fort Stewart Georgia, ORNL/CON-219, Oak Ridge National Laboratory (August 1987).*

Technology Applications Bulletins

Bulletin Number 695

Oak Ridge National Laboratory

ENERGY PRODUCTION

RELIABILITY STUDIES FOR COMPRESSED-GAS-INSULATED APPARATUS

Key words: Gas insulators; SF₆; reliability; high voltage; failure

Compressed sulfur hexafluoride gas (SF₆) is currently being used by the utilities industry as electrical insulation in high-voltage electrical apparatus. Compressed-gas insulated equipment is relatively new in electric-power technology. Consequently, long-term performance data and discriminating test procedures for these devices are somewhat lacking. Bases for comparison among manufacturers are sometimes difficult, and better information about the mechanisms, processes, and rates for low-voltage failures is needed. The uncertain reliability of compressed-gas-insulated apparatus has been cause for concern to the utilities industry.

Reliability studies and experiments were carried out for DOE's Office of Energy Storage and Distribution at the Massachusetts Institute of Technology's High-Voltage Research Laboratory, partially with the support of ORNL's Energy Division staff. This project had four broad goals: identify processes important to insulator reliability, model these processes, verify model concepts, and establish criteria for equipment design and specification.

These studies have provided basic information about low-probability insulation failures and have quantified the failures sufficiently to form the basis for improving insulator designs. They have also provided utilities with a means to better

assess the expected performance of specific equipment. For example, factors important to reliability in compressed-gas-insulated apparatus can now be better modeled. Low-probability failures are better understood and more predictable as a result of this research, and recommendations have been made that can be used for improving and monitoring insulator reliability.

Results of the investigations are summarized in the ORNL report, *Research Factors That Affect the Reliability of Compressed Gas Insulated Apparatus*. This report contains a description of a reliability model, descriptions of the experimental apparatus, procedures and results for high-voltage tests of gas gaps and insulator surfaces, and the results of a full-scale application that combined the concepts developed during the gas-gap breakdown and surface flashover studies. In addition, a collection of journal articles that were generated by this research are reprinted as appendixes to this report.

Additional information:

National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161

Telephone: (703) 487-4850; FTS 737-4850

C. M. Cooke et al., *Research on Factors That Affect the Reliability of Compressed Gas Insulated Apparatus*, ORNL/Sub/80-7979, Oak Ridge National Laboratory (July 1988).

ENERGY PRODUCTION

ASSESSMENT OF MATERIAL REQUIREMENTS FOR ADVANCED STEAM CYCLE SYSTEMS

Key words: Coal-fired generation; advanced steam cycle; fuel efficiency; computer modeling; materials requirements

To offset rising fuel costs and potential greenhouse effects, utility companies may be led to invest in higher-efficiency coal-fired power plants to meet future demands for electricity. Use of advanced steam cycles will increase the operating efficiency of commercial power plants, but cost-effective application of these cycles will require improvements in both designs and materials. Recent Electric Power Research Institute (EPRI) studies have recommended using a supercritical steam cycle (4500 psi, 1100°F) based on incremental improvements to current plant designs and materials. To this end, EPRI has initiated a 5-year R&D program with tasks aimed at providing the necessary technology for these plants to meet utility operating requirements. The Japanese have under way a similar program that includes verification of the reliability of structural materials for advanced steam-cycle applications.

A study was performed at ORNL to identify areas in which DOE could carry out appropriate R&D that would contribute to the required technological advancements, especially in developing materials for advanced steam-cycle coal-fired electric power plants. In general, advanced plant concepts used as a basis for the

ORNL study were derived from the EPRI studies because they considered the most recent industry requirements, including availability, on- and off-cycling capability, low-load operation, and fuel flexibility. The Tennessee Valley Authority's Bull Run Steam Plant was used as a reference for selecting steam-cycle design parameters. Results of the ORNL study, including a discussion of steam-cycle modeling and criteria for advanced materials, are found in the ORNL report, *Assessment of Material Requirements for Advanced Steam Cycle Systems (> 1100°F)*.

The thermodynamic performance of the turbine cycle was modeled using PRESTO, a computer code developed at ORNL to model conventional high-pressure and superheated steam turbine cycles (Fig. 1). This model was used to estimate improvements in thermal efficiency stemming from higher temperatures and pressures. From this study, several conclusions emerged about conventional coal-fired plants. For example, fixing main steam conditions at 4500 ps., improved overall efficiencies, and lower fuel costs are achievable as temperature is increased from 1100 to 1400°F. However, increases in steam temperature above 1100°F produce less significant increases in efficiency without attendant increases in steam throttle pressure. The model also showed that fuel savings over 30 years can offset higher capital costs, providing that the improved materials have better reliability and strength at higher temperatures

Fig. 1. Advanced steam plant, based on the ORNL PRESTO modeling computer code (steam conditions: 4500 psi, 1100°F).

than currently used materials. Specification of plant designs required for operation above 1200°F await the development of specific flow charts and further modeling of advanced plant parameters.

The ORNL study concludes that materials developments for applications above 1400 to 1500°F could be logically incorporated into current materials programs. Because of cost and corrosion considerations, development of improved boiler materials has greater pay-off than development of improved turbine materials. Allowable materials costs are closely related to allowable design stress; consequently, the attainment of higher efficiency through the

development of advanced systems depends on the development of cost-effective higher-strength materials.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

J. R. DiStefano, J. H. DeVan, and L. C. Fuller, *Assessment of Material Requirements for Advanced Steam Cycle Systems (> 1100°F)*, ORNL/TM-10489, Oak Ridge National Laboratory (February 1988).

ENERGY PRODUCTION

STUDY OF SOLAR POWER SUPPLY SYSTEM AT MISSISSIPPI
COUNTY COMMUNITY COLLEGE

Key words: Solar power; photovoltaic/thermal array

The installation of a solar-powered photovoltaic/thermal system at Mississippi County Community College in Blytheville, Arkansas, was completed in 1981. Originally, this system was built to supply the college with heat,

hot water, and electricity (Fig. 1). Installing this system was one of the early major solar power projects funded by DOE.

In 1984 this system was converted for all-thermal output. It operated during the winter of 1984-85 until it was damaged by a severe winter storm. A study published by ORNL, *Mississippi County Community College Solar Power Supply System: Final Summary Report*,

Fig. 1. Flowchart of Mississippi County Community College solar energy system.

summarizes what was learned during photovoltaic/thermal (PV/T) operation. The less extensive information available for the all-thermal system is also reviewed in this report.

The PV/T array consisted of 45 rows of linear parabolic reflectors with their axes oriented north-south. Each row contained six reflectors (Fig. 2) mounted end to end on a common shaft that could be rotated through an arc of 270° . The system was operated and monitored by a Hewlett-Packard 9845 computer. In the conversion to all-thermal operation, the array was reduced from 45 to 33 rows of reflectors.

The PV/T system was never able to exceed 55% of rated electrical output. The performance inadequacies are thought to have been caused by inherent problems in the concentrating PV design rather than by operating or maintenance

shortcomings. Preliminary estimates suggest that the all-thermal system was more successful; its thermal energy output exceeded that of the older PV/T system in spite of the fact that its collector area was 27% smaller.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

S. I. Kaplan, *Mississippi County Community College Solar Power Supply System: Final Summary Report*, ORNL/TM-9859, Oak Ridge National Laboratory (February 1986).

Fig. 2. Mississippi County Community College solar collector row.

ENERGY PRODUCTION

AN ALL-METAL REENTRANT VACUUM FEEDTHROUGH

Key words: Vacuum seal; reentrant seal; all-metal

Researchers in ORNL's Fusion Energy Division have designed, built, and tested a demountable, all-metal reentrant vacuum feedthrough for use with the Advanced Toroidal Facility (ATF) diagnostics. This type of feedthrough is required for diagnostics containing electrical coils that must permanently remain in place in the vacuum chamber. The new design is different from commercially available all-metal feedthroughs in that it allows the vacuum vessel port cover to be removed while leaving the internal diagnostics in situ. This new feedthrough has been proven to remain leaktight at temperatures above the bakeout temperature of the ATF vacuum chamber (150°C).

A cross-sectional view of the seal is given in Fig. 1. The seal is composed of two flanges whose mating surfaces are machined to accept a standard Conflat copper gasket (b). One flange (a) is welded to (or machined into) the vacuum chamber's port cover, around the penetration that it will seal. The second flange (c) is attached to the base of an extension that passes through the penetration. The tube passing through the vacuum chamber port cover is welded to the external end of the extension. A jacking ring (e), which is drilled and tapped to accept a circle of jackscrews (d), attaches to the extension by either a threaded connection or a

Fig. 1. Cross section of the assembled seal, (a) seal flange welded to the inside of vacuum chamber; (b) standard Conflat copper gasket; (c) seal flange with extension welded to fluid line or tube; (d) jackscrew; (e) jacking ring; (f) chrome-plated thrust washer.

circ-clip fitted into a machined groove. Tightening the jackscrews forces the two mating surfaces together, thus forming a seal. A chrome-plated thrust washer (f) between the outer surface and jacking ring prevents the bolts from galling the chamber's outer surface.

A minimum assembly diameter is maintained because the jackscrews are on the same radius as the sealing ring, which permits close spacing of the feedthroughs. In addition, no rotational torques are applied to the overall seal assembly during the sealing process, and no special keying or alignment is required for the reentrant seal or the overall assembly. The seal has a narrow sleeve section, which maintains some elasticity in the assembly and maximizes the clear aperture.

The prototype design criterion for use on the ATF was to generate a sealing force in excess of 2000 lb/in. for the sealing surface. The properties of type 304 stainless steel, considerations for a margin of safety, and the need to retain minimal spacing dictated the remaining dimensions. The feedthrough was tested with unlubricated, high-strength screws and with lubricated, series 300 stainless-steel screws. Both types of bolts produced leaktight

seals when torqued to 20 and 40 in.-lb, indicating a wide margin of sealing force. The assembly retained its seal (to 1×10^6 atm cc/s He) after 2 h in an oven at 250° C. In addition, the seal can be broken and reassembled using the same gasket. Criteria can be established for any feedthrough diameter and suited to standard Conflat flange sizes.

Additional information:

Office of Technology Applications
Martin Marietta Energy Systems, Inc.
P.O. Box 2008
Oak Ridge, TN 37831-6257

Telephone: (615) 574-4192; FTS 624-4192

P. H. Edmonds and W. D. Shipley, "A Reentrant Bakeable All-Metal Feedthrough Vacuum Seal," *J. Vac. Sci. Technol. A* 6(1) (1988), 165-67.

CUMULATIVE INDEX FOR FY 1988

	Bulletin Number
Artificial Intelligence, Robotics, and Manufacturing Processes	
ROBOTICON: Real-Time Control for an Autonomous Mobile Robot	601
OPSNET: Parallel Architecture for Expert Systems	650
Soft-Thresholding Image Analysis	651
OPSMOP: Parallel Symbol-Matching Coprocessor for Rule-Processing Systems	652
Measurements and Controls	
Crystal Laser Monitor	602
Remote Sensor and Cable Identifier	603
Portable, Surface-Enhanced Raman Spectroscopy System	604
REAL-OPS: Real-Time Expert System Control	605
Explosives Sensor	606
Sigmajig: A Weldability Test Device	607
Motor Current Signature Analysis Process	608
Super Grip	609
Differential Mechanical Properties Microprobe	610
Ultrasonic Techniques for the Evaluation of Ceramic Joints	611
Advanced Software for the Efficient Manufacture of Complex Industrial Castings	612
Atmospheric-Sampling Glow Discharge Ionization Source	625
APIS: An Acoustical System for Identification of Subspecies of Honeybees	626
An Accurate Laboratory Test System Using Commercial Equipment for Eddy-Current Measurements	627
Californium-Source-Driven Subcriticality Monitor	628
Solar-Powered, Infrared Bee Transmitter	653
Nondestructive Testing with Pulsed Eddy Currents	654
High-Efficiency Scintillation Detector for Thermal and High-Energy Neutrons	655
Cut-Off Tool Adapter	656
Pulsed-Aerosol Analyzer	657
Strain-Gaged Bolt Process for the Direct Measurement of Valve-Stem Thrust	658
Axial-Gap Permanent Magnet Motor	659
Evaporator Control System	660
Medical and Biomedical Technology	
Fiber-Optics Fluoroimmuno-Sensor	613
Information Science	
Implementing and Managing Change: A Guide for Assessing Information Technology	629
Energy Conservation	
Snail Cryopump	614
High-Temperature Corrosion of Silicon Carbide by Alkali Halides	615
Driver Energy Conservation Awareness Training	616
Horizontal Ground-Coil Heat Exchangers	617
Energy and Economic Efficiency Alternatives for Electric Lighting in Commercial Buildings	618
Monitoring of Residential Groundwater-Source Heat Pumps the Northeast	619
Single-Family Building Retrofit Research	630

Energy Measurements Of Single-Family Houses	631
Passive Solar Structures Enhanced with Phase-Change Materials	632
Roof Research Center	633
Assessment of the Energy-Savings Potential of Building Foundations Research	634
Weatherization Assistance for Low-Income Households	635
Improved Planning Methods for Electric Utilities	661
Residential Energy Conservation Shared-Savings Program	662
Flow Regimes of Refrigerant Mixtures Condensing Inside Tubes	663
Use of Evaluation Results in Bonneville Power Administration's Planning Models	664
Energy-Conserving Retrofit Audit for Single-Family Buildings	665
Environmental Technology	
Oak Ridge National Environmental Research Park	636
Technical Guidance for Groundwater Monitoring	637
Ecological Research Needs at Hazardous Waste Disposal Sites	638
Treatment of Low-Level Radioactive Waste from Commercial Nuclear Reactors	639
A Three-Dimensional Finite-Element Model of Water Flow Through Saturated-Unsaturated Media	666
Chemical and Waste Management	
Two-Pot: A Simplified Process for the Extractive Distillation of Nitric Acid	640
Update of Acute and Chronic Aquatic Toxicity Data for Heavy Metals and Organic Chemicals Found at Hazardous Waste Sites	641
Treatment of Solvent Extraction Solvents with Activated Alumina	642
Chemical Hazard Information Profile of Triphenyl Phosphite	643
Emulsion-Phase Contactor	667
Grout Fixation of Variable Phosphate/Sulfate Waste	668
Energy Production	
Determination of Effects of Atmospheric Contamination on Photovoltaic Cells in Concentrating Systems	620
Study to Assess the Effects of High-Altitude Electromagnetic Pulse on Electric Power Systems	621
Basic Studies of Gases for Fast Switches	644
Elastomer Pump Seals for Coal Liquefaction Applications	645
A Process-Inherent, Ultimate Safety Boiling-Water Reactor	669
Advanced Materials	
Lead-Indium Phosphate and Lead-Scandium Phosphate Glasses for Optical Applications	622
Active-Substrate Brazing Process	623
Molybdenum Resistance Heater	624
High Temperature Materials Laboratory	646
Advanced Process for Fabricating Optical Devices and Waveguides, Especially Lithium Niobate (LiNbO ₃ :Ti)	647
Beam-Processed, High-Efficiency Solar Cells	648
Process for Wear Inhibition of Artificial Hips and Knees by Ion Implantation	649
Nickel-Iron Aluminides for Advanced Coal Conversion Systems	670
X-Ray Methods for Analyzing Rough Wear Surfaces	671
Platinized Chloroplast: A New Bioelectronic Material	672

The Martin Marietta Energy Systems, Inc., Office of Technology Applications publishes *Technology Applications Bulletins* three times a year. If you would like to be put on the mailing list, fill out and return one of the attached cards. A spare card is provided in case you know of a colleague who would also like to receive the bulletins.

Yes, place my name on the mailing list to receive *Technology Applications Bulletins*. (Please type or print the following information.)

Name _____ Title _____

Company _____

Address _____

City _____ State and Zip _____

My interest areas are

☐ Artificial Intelligence, Robotics, and Manufacturing Processes;	☐ Transportation;
☐ Measurements and Controls;	☐ Radioactive Materials;
☐ Medical and Biomedical Technology;	☐ Chemical and Waste Management;
☐ Information Science;	☐ Energy Production; and
☐ Energy Conservation;	☐ Advanced Materials.
☐ Environmental Technology;	☐ I am interested in licensing new technologies.

2/89

Yes, place my name on the mailing list to receive *Technology Applications Bulletins*. (Please type or print the following information.)

Name _____ Title _____

Company _____

Address _____

City _____ State and Zip _____

My interest areas are

☐ Artificial Intelligence, Robotics, and Manufacturing Processes;	☐ Transportation;
☐ Measurements and Controls;	☐ Radioactive Materials;
☐ Medical and Biomedical Technology;	☐ Chemical and Waste Management;
☐ Information Science;	☐ Energy Production; and
☐ Energy Conservation;	☐ Advanced Materials.
☐ Environmental Technology;	☐ I am interested in licensing new technologies.

2/89

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This document was prepared under the sponsorship of the U.S. government by Martin Marietta Energy Systems, Inc., under contract No. DE-AC05-84OR21400. Neither the government nor any person acting on its behalf assumes any liability from the use of this information or warrants that this use will be free from privately owned rights.