DOE/ER/13035--T2

PERFORMANCE REPORT

ACCELERATOR BASED EPITHERMAL NEUTRON SOURCE

FOR NEUTRON CAPTURE THERAPY

Principal Investigators

DOE/ER/13035--T2

Robert Brugger and Jay Kunze

DE92 005544

May 1991

The following is a performance report covering the period from October 1990 through April 1991. A presentation was given by Robert Brugger at the DOE-OER University Nuclear Engineering Research Program Annual Review at Savannah River Lab on April 23, 1991.

Table 1 lists epithermal neutron beams that are now operating or have been designed for Neutron Capture Therapy (NCT). Several investigators [1,2] have suggested that a charged particle accelerator with light element reactions might be able to produce enough epithermal neutrons to be useful in NCT. The reaction of choice so far has been the $\text{Li}(p,n)$ reaction with protons up to 2.5 MeV. A moderator around the target would reduce the faster neutrons down to the epithermal energy region. The goals of the present research are:

1. Identify better reactions
2. Improve the moderators
3. Find better combinations of 1 and 2

The target is to achieve, at the patient location, an epithermal neutron current of greater than $10^9 \text{ n/cm}^2 \text{ sec}$, with a dose to tissue from the neutrons alone of less than 10^{-10} rads/n and a dose from the gamma rays in the beam of less than 10^{-10} rads/n.

This research and development program is related to several efforts of the DOE. First and foremost, the program is part of the DOE effort to develop NCT. DOE is the lead agency of the federal government for developing NCT. Finding epithermal neutron sources that will be accepted in a clinical environment is a key to the success

MASTER

1

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

of NCT. Secondly, the DOE may have need of an intense source of low energy neutrons for detecting small quantities of transuranic elements in barrels of the low level radioactive waste. Third, the DOE might use an intense source of low energy neutrons for detecting explosives.

The schedule for this research program is:

- October 1990: Start
- April 1991: Have working codes that calculate the neutron yields from the reactions, and have working the Monte Carlo Code to calculate the neutron transport through the moderator.
- October 1991: Have calculated all the neutron yields for the reactions.
- December 1991: Have picked several promising reactions and have moderators designed for these reactions.
- October 1992: Optimize the reactions and the moderators and reach conclusions about this type of epithermal neutron source.

Table 2 shows a set of neutron yielding reactions that have light element targets and light element particles. The last two columns show yields that have been calculated for several of these reactions. The forward yield may be more indicative of the effectiveness of the reaction than the total yield because it is in the forward direction that the patient will be located. It may be difficult to redirect neutrons that start in the backward direction so that some will reach the patient location. The yield of the $\text{Li}(p,n)$ reaction is relatively high, but the $\text{T}(p,n)$ reaction and its inverse show promise.

Table 3 shows another set of neutron yielding reactions that are being studied. Only a few yields have been calculated so far. For a number of these, complete cross sections have not been measured and published, and assumptions are having to be made to calculate yields. While the yields for this set of reactions is an order of magnitude lower than the first set, the target materials are more convenient. Ways are being explored to increase the yields from these sources.

Figures 1, 2, and 3 show plots of the yields from several of the reactions of the first set of reactions. Data in this form is needed as the input to the Monte Carlo Code for the calculation of the effectiveness of the moderator. Figure 4 shows the geometry of the first moderator for the $\text{Li}(p,n)$ reaction. Fluxes and doses in the phantom have

been calculated. Calculations with a modified moderator have started.

In conclusion, the research and development of the program are on schedule. By the end of the first year, the codes will be working and yields from the reactions will have been calculated. Evaluation of moderators will have started. By the end of the second year, the promising reactions will have been selected and moderators will have been designed for these.

One presentation has been made related to this program [3].

- [1] Wang, C.K., T.E. Blue, and J.W. Blue, "An Experimental Study of the Moderator Assembly for a Low-Energy Proton Accelerator Neutron Irradiation Facility for BNCT", Neutron Beam Design, Development, and Performance for Neutron Capture Therapy, pp. 271, edited by Otto K. Harling, John A. Bernard, and Robert G. Zamenhof, Plenum Press, New York, NY, 1990
- [2] Shefer, R.E., R.E. Klinkowstein, J.C. Yanch, and G.L. Brownell, "A Versatile, New Accelerator Design for Boron Neutron Capture Therapy: Accelerator Design and Neutron Energy Considerations", Neutron Beam Design, Development, and Performance for Neutron Capture Therapy, pp. 259, edited by Otto K. Harling, John A. Bernard, and Robert G. Zamenhof, Plenum Press, New York, NY, 1990
- [3] Wu, H., R.M. Brugger, and J.F. Kunze, "Low Energy Accelerator Sources for Boron Neutron Cancer Therapy", paper presented at the Missouri Academy of Science 1991 Annual April Meeting at Westminster College in Fulton, Missouri, April 20, 1991

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

TABLE I
EPITHERMAL BEAMS FOR NCT

REACTOR	POWER	EPITHERMAL NEUTRON FLUX	NEUTRON DOSE* PER NEUTRON	GAMMA DOSE PER NEUTRON	CURRENT/ FLUX
	MW	$n/cm^2sec \times 10^{-9}$	$RADS/n/cm^2 \times 10^{11}$	$RADS/n/cm^2 \times 10^{11}$	
MURR [1]	10	9.5 ± 0.3	3 ± 0.3	0.3 ± 0.1	0.81
BMRR [2]	3	1.8	4.87	0.3	closer to 0.5
MITR [2]	5	0.25	20.1	3.3	closer to 0.5
PETTEN [2]	45	1.1	7.8	0.5	closer to 1.0
GTRR [3]	5	>10.0	3.4	0.1	closer to 1.0
PBF [2]	25	14	1.9	0.18	closer to 1.0

*Flux > 10 keV and dose from > 10 keV neutrons

- [1] Brugger, R.M., J.A. Shih, and H.B. Liu, "An Epithermal Neutron Beam for Neutron Capture Therapy at the Missouri University Research Reactor", Nuclear Technology, to be published
- [2] Newsletter of the European Collaboration on Boron Neutron Capture Therapy, 8, D. Gabel editor, 1991
- [3] Less, T.J., "Reactor Moderated Intermediate Energy Neutron Beams for Neutron Capture Therapy", PhD Dissertation, Nuclear Engineering, University of Missouri-Columbia, 1987

TABLE II

April 15, 1991

Possible Reactions for Producing Neutrons for BNCT Using a Low Energy Accelerator

Reactions	Q-valve (MeV)	Eth (MeV)	Neutron Energy at Eth (MeV)	Maximum Incident Particle Energy (MeV)	Neutron Energy Range (MeV)	Total Neutron Yields (0-180deg) (n/P)*1E5	Forward Neutron Yields (0-30deg) (n/P)*1E5
Li-7(p,n)Be-7	-1.645	1.881	0.029	2.5	0.0-0.78	14.80	1.92
H-1(Li-7,n)Be-7	-1.645	13.097	1.441	13.3	1.0-1.9	1.04	1.04
T-3(p,n)He-3	-0.764	1.019	0.064	1.67	0.0-0.858	20.20	3.64
H-1(t,n)He-3	-0.764	3.051	0.573	3.19	0.4-0.869	1.80	1.80
C-12(d,n)N-13	-0.281	0.328	0.003	1.23	0.0-0.911	0.74	0.06
Be-9(p,n)B-9	-1.852	2.058	0.021				
B-11(,n)N-14	0.158	0.000	0.147				
D-2(p,n)2(H-1)	-2.227	3.341	0.371				
H-1(d,n)2(H-1)	-2.227	6.681	1.485				
B-11(p,n)C-11	-2.765	3.018	0.025	3.77	0.0-0.915	3.75	0.41
N-15(p,n)O-15	-3.537	3.770	0.030	4.45	0.0-0.814	13.50	2.16

* * * * *

TABLE III

April 15, 1991

Possible Reactions for Producing Neutrons for BNCT Using a Low Energy Accelerator

Reactions	Q-value (MeV)	Epth (MeV)	Neutron Energy at Epth (keV)	Maximum Proton Energy (MeV)	Neutron Energy Range (keV)	Total Neutron Yield (0-180deg (n/p*1E6)	Forward Neutron Yield (0-30deg) (n/p*1E6)
Ca-48(p,n)Sc-48	-0.5095	0.5202	0.246	1.311	0-800		
Mn-55(p,n)Fe-55	-1.0141	1.0373	0.36	1.818	0-800		
Cr-53(p,n)Mn-54	-1.3798	1.4061	0.538	2.187	0-800		
Ti-49(p,n)V-49	-1.3836	1.4121	0.616	2.1915	0-800		
V-51(p,n)Cr-51	-1.5338	1.5642	0.786	2.342	0-800		
Co-59(p,n)Ni-59	-1.8556	1.8874	0.588	2.665	0-800		
Cu-65(p,n)Zn-65	-2.1320	2.169	0.563	2.944	0-800	3.06	0.254
Cr-54(p,n)Mn-54	-2.1571	2.1974	0.82	2.97	0-800		
Ni-64(p,n)Cu-64	-2.4599	2.4987	0.672	3.274	0-800		
Sc-45(p,n)Ti-45	-2.8440	2.908	1.55	3.669	0-800	2.61	0.247
Cu-63(p,n)Zn-63	-4.1480	4.2146	1.19	4.977	0-800	0.276	0.223
Ni-62(p,n)Cu-62	-4.7296	4.8066	1.416	5.565	0-800		
Ni-60(p,n)Cu-60	-6.9094	7.0256	2.263	7.77	0-800		
Ti-46(p,n)V-46	-7.8368	8.0087	4.387	8.73	0-800		

Li-7(p,n)Be-7 Reaction Normalized Neutron Yield

FIGURE 1

H-3(p,n)He-3 Reaction Normalized Neutron Yield

FIGURE 2

H-1(t,n)He-3 Reaction Normalized Neutron Yield

FIGURE 3

FIGURE 4

END

DATE
FILMED
3/2/92

I