MEDIUM ENERGY MEASUREMENTS OF N-N PARAMETERS

A Progress Report

DOE/ER/40446--4

For

DE92 005464

the one year period

January 1, 1991 - December 31, 1991

PRINCIPAL INVESTIGATOR

Peter J. Riley,
Department of Physics,
University of Texas at Austin,
Austin, Texas, 78712-1081

November 30, 1991

Submitted to the United States Department of Energy

Under Grant No. DE-FG05-88ER40446

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Administrative Information

This progress report has not been submitted to any other agency of the United States Federal Government.

Further information relating to the technical portions of this proposal may be obtained from Dr. Peter J. Riley, Department of Physics, RLM 5.208, the University of Texas at Austin, Austin, Texas, 78712. Telephone numbers: (512) 471-5957 or (512) 471-1153.

Contractual matters should be referred to the University's Office of Sponsored Projects, P.O. Box 7726, Austin, Texas 78712. Telephone Number: (512) 471-1352 or 471-5071.

Written by:

Peter J. Riley, Professor of physics

Approved by:

Wayne K. Kuenstler, Director, Office of Sponsored
Projects

Stephen A. Monti, Vice Provost

TABLE OF CONTENTS

I. Overview.....	1
II. Progress on Research Projects	3
A. LAMPF E876, Spin Transfer Measurements in np Elastic Scattering.....	3
B. LAMPF E1234, KLL and P for np Elastic Scattering.....	8
C. TRIUMF E372, Single Pion Production in np Scattering	9
D. LAMPF E1097, Single Pion Production in np Scattering	18
E. BNL E871, A New Search for Very Rare K_L^0 Decays	39
III. Status of Experiments	45
IV. Personnel Working on Projects	47
V. Publications and Abstracts.....	48
VI. Title Pages of Publications.....	49

MEDIUM ENERGY MEASUREMENTS OF N-N PARAMETERS

I. Overview

This progress report requests continued support for the Medium-Energy nucleon-nucleon (N-N) physics program of the University of Texas at Austin, the major part of which involves research done at the Nucleon Physics Laboratory (NPL) at the Los Alamos Meson Physics Facility (LAMPF). Other research has been and will be continued to be carried out at BNL. We are also analyzing data from a TRIUMF experiment in which we participated, but we have no further plans for experimental work at TRIUMF. Our **Progress Report** will describe work done during 1991, and will focus on problems that we face with existing experiments, or on experiments in which we hope to participate in the coming year.

Broadly speaking, the aim of the N-N experimental program is the determination of the nucleon-nucleon amplitudes at medium energies. The required data include both elastic and inelastic experiments, and in addition the measurement of polarization and polarization transfer parameters. The experiments at BNL are not nucleon-nucleon experiments, and we will discuss them later.

Our LAMPF nucleon-nucleon measurements have consisted of the following measurements:

(1) p-p elastic absolute cross section measurements (E1072), with the goal of measuring the p-p differential cross section at LAMPF energies to an absolute accuracy of 1%. The experimental measurements were carried out during the summer of 1988. Analysis has required careful evaluation of detector efficiencies, backgrounds, and a thorough study of beam attenuation in the target and surrounding materials. Data analyses are now nearly complete.

(2) Spin transfer measurements in np elastic scattering (E876). This experiment is being carried out in two phases. Phase 1 consists of the measurement of the four spin-transfer observables K_{LL} , K_{SS} , K_{SL} and K_{LS} at 500, 650, and 800 MeV. In Phase 2 the observable K_{NN} will be measured at the three energies. At the present time we have completed Phase 1. The 800 MeV data, and their analyses, are described in a paper accepted for publication in Physical Review C, December, 1991. The 500 and 650 MeV data have been analyzed, and will be submitted for publication in a later manuscript. The data are proving invaluable in fixing the isospin 0 phase shifts and amplitudes.

In addition, our measurements of the neutron beam polarization for E876 uncovered a significant disagreement with our previous measurements of $K_{LL}(d)$ at 800 MeV, suggesting that our previous LAMPF np elastic analyzing power data should be renormalized. Consequently, we wrote and submitted a new proposal, (E1234), " K_{LL} and P for np Elastic Scattering." These measurements were also carried out during the summer of 1991, and the data have been analyzed.

(3) n-p inelastic polarization measurements (E1097), "Single Pion Production in np Scattering," designed to measure the cross section and analyzing powers for the reaction $np \rightarrow pp\pi^-$. Crucial to this experiment is a cylindrical drift chamber which will surround the target, and much of our present efforts are involved with the testing and development of this chamber. We carried out preliminary testing of our chamber and its associated electronics at LAMPF during the summer of 1991, and expect to complete this work during 1992. Phase I running, which will employ an unpolarized liquid hydrogen target, will be

carried out during the summer of 1993, and phase II running, using a polarized (frozen spin) target, in 1994.

During the past three years we have been involved in a neutron-proton inelastic scattering experiment at TRIUMF (E372) "Single Pion Production in np Scattering," designed, as LAMPF experiment 1097, to measure the cross section and analyzing powers for the reaction $np \rightarrow pp\pi^-$. This experiment measures the same quantities as will E1097, Phase I, at the higher LAMPF energies. Our data taking runs for E372 were carried out during September, 1990, and February, 1991. The data are now being analyzed here at the University of Texas by Mark Bachman, whose Ph. D. dissertation will be based on the data and its analyses.

We are also participating in an experiment at Brookhaven National Laboratory, "Study of Very Rare K_L^0 Decays," (BNL 791). Data taking for this experiment is now completed, and analysis is underway. In addition, a proposal for a new generation rare-decay measurement has been approved (BNL 871), and we plan to participate in this new experiment during the next few years.

In the following section we describe in more detail recent progress on three LAMPF experiments, E876, E1097, and E1234, one TRIUMF experiment, E372, and on the BNL experiments, E791 and E871.

II. PROGRESS ON RESEARCH PROJECTS

A. LAMPF E876, Spin Transfer Measurements in np Elastic Scattering

A major goal at LAMPF has been to determine the nucleon-nucleon isospin-zero ($NN\ I=0$) phase shifts and amplitudes near 800 MeV. During the summer of 1990 we measured four isospin-transfer observables which, when combined with previous spin dependent data near 800 MeV, lead to stable solutions. As recently as 1988 Arndt¹ stated that above 500 MeV the $NN\ I=0$ phase shifts were "essentially undefined". Bugg² pointed out that the spin transfer observables K_{LL} , K_{SS} , and K_{NN} were needed to establish stable, well determined solutions. Since our experimental method measures K_{LS} simultaneously with K_{LL} and K_{SL} simultaneously with K_{SS} , we measured these four observables. This over determination also allows some cross-checking of possible systematic errors.

Spinka³ has shown that by taking advantage of the symmetries of the amplitudes about 90° c.m. it is possible to solve for the amplitudes up to a discrete fourfold ambiguity using only the cross section, analyzing power, and the four spin correlation parameters. The addition of two of the spin transfer parameters reported here, K_{LL} and K_{LS} , completely determines the five complex scattering amplitudes. When K_{SS} and K_{SL} are included then the amplitudes are over-determined for the first time.

Nucleon-nucleon data bases and phase shift analyses are maintained by Arndt⁴, Bugg², Bystricky, Lehar and Leluc⁵, and by Hoshizaki^{6,7}. They report that with the inclusion of our new 800 MeV data, the phase shift analyses show "an immense improvement" and are well determined with well behaved error matrices for the first time. Correlations in the error matrix have almost disappeared, and previously reported problems near 800 MeV² have disappeared. Bugg reports a χ^2 per point of 1.1 for his fits to the new data.

During the summer of 1991 similar data were taken at 500 and 650 MeV. The experimental data are currently being compared with phase shift predictions.

The E876 apparatus, shown in figure 1, is essentially the same as had been used in previous LAMPF experiments⁸⁻¹⁰. Briefly, polarized protons are focussed onto a liquid deuterium target and neutrons, polarized by spin transfer, are collimated at zero degrees and directed onto a 15 liter liquid hydrogen target (the largest ever used at LAMPF). Scattered neutrons are detected in a large high-efficiency neutron detector. Recoil protons are detected in the Scylla spectrometer, which serves a dual purpose: 1) to measure the momentum and 2) to precess the recoil protons from L-spin to N-spin. Finally, the proton spin is analyzed in the Janus polarimeter.

Figure 1: E876 detector system

Extensive experience with the Scylla spectrometer and the Janus polarimeter in prior experiments enabled us to analyze some of the data on-line. The 800 MeV results are shown in figure 2. The lines solid lines are the new phase shift predictions of Bugg. The dotted lines indicates the older (1989) Arndt predictions. The 485 and 635 MeV data are shown respectively in Figure 3(a) and 3(b). Several conclusions can be drawn:

1. These new data are internally consistent. For example, the center of mass relation¹⁰ $K_{S1} = -K_{1S}$, where the spins have been transformed to the center of mass, checks out well.
2. The data are in excellent agreement with new phase shift solutions by Arndt, Bugg, Leluc and Lehar. They report that with the inclusion of these new data the solutions are well determined with a well behaved error matrix for the first time near 800 MeV.
3. The relationship $K_{LL} * K_{LL} + K_{LS} * K_{LS} < 1.0$ places an upper limit on the polarization of the neutron beam. This same neutron beam has been used in all previous np measurements at LAMPF. If we use the Chalmers¹¹ calibration of the neutron polarization, then our measurements would imply that $K_{LL} * K_{LL} + K_{LS} * K_{LS} = 1.15 \pm 0.03$. The implication is that the previous data will need to be normalized by 15%.

This renormalization is confirmed by our independent re-calibration of the neutron beam polarization. Using the same apparatus described above but with deuterium in both the primary and secondary targets (here the secondary target was a 3-liter target), and with

the spectrometer at zero degrees, we measured the square of the spin transfer coefficient from deuterium. From the polarization of the protons incident on the LD₂ neutron production target, we deduce K_{LL} without needing to know the (n,p) analyzing power. The preliminary value for $K_{LL}=0.68\pm0.03$, which compares with Chalmers⁸ value of 0.60 ± 0.05 and with Riley's¹² value of 0.64 ± 0.05 . We have used the value of $K_{LL}=0.68\pm0.03$ for our on-line calculations of polarization transfer values. The implication is that previous data which used the Chalmers's value of 0.60 should be normalized by a factor of 1.13. This renormalization is also consistent with the 13% renormalization predicted by Bugg².

In summary, the measurements of the four spin-transfer observables K_{LL} , K_{SS} , K_{SL} , and K_{LS} at 500, 650, and 800 MeV have been completed successfully. In 1992 we plan to complete E876, measuring the observables K_{NN} and P at 640, 725, and 800 MeV.

¹ R. A. Arndt, *et al.*, Phys. Rev. **D35**, 128, (1987).

² D. V. Bugg, Phys. Rev. **C41**, 2708, (1990).

³ H. Spinka, Phys. Rev. **D30**, 1461, (1984)

⁴ R. A. Arndt, Phys. Rev. **D37**, 2665, (1988).

⁵ J. Bystricky, C. Leluc, and F. Lehar, J. Phys. **48**, 199, (1987).

⁶ N. Hoshizaki, Prog. Theor. Phys. **60**, 1796 (1978)

⁷ N. Hoshizaki *et al.*, Proc. of Workshop on expts by KEK Pol. Prot. and Electron Beams (KEK, Ibaraki, Japan, Oct. 1988).

⁸ R. Ransome *et al.*, NIM **201**, 309, (1982).

⁹ M. W. McNaughton *et al.*, Phys. Rev. **C41**, 2809, (1990).

¹⁰ C. L. Hollas *et al.*, Phys. Rev. **C30**, 1251, (1984).

¹¹ J. S. Chalmers *et al.*, Phys. Letters **153B**, 235, (1985).

¹² P. J. Riley, *et al.*, Physics Letters **103B**, 313, (1981).

Figure 2: Spin transfer measurements at 788 MeV

Figure 3 (a and b): Spin transfer measurements at 485 and 635 MeV. Data are not yet completely analyzed.

B. LAMPF EXPERIMENT 1234, K_{LL} and P for np Elastic Scattering

Polarized neutrons for np elastic experiments at LAMPF are produced by directing the primary polarized-proton beam onto a liquid deuterium (LD_2) target and collimating the neutrons at a laboratory scattering angle of zero (180° c.m.) The neutron beam is polarized via the L-to-L spin-transfer observable K_{LL} for the $d(p,n)$ reaction. Thus measurements of K_{LL} affects the normalization of all polarized np experiments that have used this facility in the BR neutron channel at LAMPF. The disagreement that we discussed above at 800 MeV between our 1990 measurement and previous measurements opens the question of renormalizing previous data.

K_{LL} was measured by double-scattering from two liquid deuterium targets (LD_2). The first LD_2 target produced polarized neutrons near zero scattering angle via $d(p,n)$ with polarization $P_n = P_b K$. The second LD_2 target produced polarized protons near zero scattering angle via $d(n,p)$ with polarization $P_p = P_n K_{LL}$. By charge symmetry $K_{LL} = K_{LL}$ so that $P_p = P_b K_{LL}^2$. By measuring P_b and P_p we deduce K_{LL} . Measurements were carried out at nominal neutron energies (± 3 MeV) of 305, 485, 635, 722, and 788 MeV. The results are listed in table 1.

Table 1: K_{LL} for $d(p,n)$ at zero neutron angle (180° c.m.).
The total uncertainty includes statistics, 0.003 uncertainty from the shape of the angular distribution, and 1.4% normalization uncertainty.

ENERGY (MEV)	K_{LL}	$\pm$ STAT	$\pm$ TOTAL
305	-0.409	0.008	0.010
484	-0.577	0.007	0.011
634	-0.685	0.007	0.012
722	-0.716	0.008	0.013
788	-0.720	0.014	0.017

The results disagree with the previous measurements of Riley *et al.*¹, and Chalmers *et al.*². However, both these earlier measurements share a common systematic uncertainty of 7% resulting from the np-elastic analyzing power to which both of these results were normalized. The disagreement with these earlier data suggests that the np-elastic analyzing power data should be re-normalized.

¹ P. J. Riley, *et al.*, Physics Letters **103B**, 313, (1981).

² J. S. Chalmers *et al.*, Phys. Letters **153B**, 235, (1985).

C. TRIUMF Experiment 372, Single Pion Production in np Scattering

The purpose of TRIUMF experiment E372 is to measure the differential cross section and analyzing powers A_x , A_y , and A_z for the reaction $np \rightarrow pp\pi^-$ at 438 MeV. This reaction is important for two reasons: (i) the Δ^{++} resonance which dominates most of the $NN \rightarrow NN\pi$ reactions is not present, and (ii) both isospin $I = 0$ and $I = 1$ channels are open. The measurements should therefore help us to understand the role of nonresonant amplitudes in pion production. Almost all modern theoretical studies of the $NN \rightarrow NN\pi$ reactions are based on the formalism of Aaron, Amado and Young (AAY)¹. The AAY formalism can be made relativistically covariant; it preserves 2- and 3-body unitarity, and has the proper clustering properties. On the other hand, the theory does not properly respect the chirality of the πN interaction. It also excludes some diagrams that may be important, notably the crossed diagrams for pion absorption in the P_{11} and P_{33} channels. It has been assumed that sufficiently far above threshold these approximations would introduce little error. However, it is found that even in cases such as $pp \rightarrow np\pi^+$ where one isobar dominates the reaction that there is a large model dependence due to uncertainties in the $P_{11}N\pi$ interaction. The agreement between experiment and the standard formalisms, such as those of Dubach, Kloet and Silbar², of Matsuyama and Lee,³ of Blankleider *et al*,⁴ and of Afnan *et al*⁵ is not satisfactory. In addition, while fits may work at one energy, they may be seriously in error in the same observable at another energy. Dubach, Kloet, and Silbar have suggested that the isospin $I = 0$ amplitudes (which necessarily do not involve the Δ resonance at all) are as important in determining some spin observables as are the Δ -dominated $I=1$ amplitudes. Data are required both above and below the P_{33} resonance. Below the resonance (TRIUMF E372), the S-wave is relatively more important, while above the resonance, (LAMPF E1097) we expect to see the effects of interfering $I=0$ and $I=1$ contributions. The Saturne group under Y. Terrien has recently obtained data for $np \rightarrow pp\pi^-$ at 650 MeV. We hope that the data from the three experiments will have a major impact on our understanding of the $NN \rightarrow NN\pi$ system at medium energies.

TRIUMF E372 uses an intense polarized neutron beam which is directed by means of a collimator on to a liquid hydrogen target. The trajectories of the two protons are measured in a detector which sits directly downstream of the hydrogen target. Knowing the proton trajectories and the energy of the neutron beam, we can reconstruct the kinematics for each $pp\pi$ event. From this information, we bin our data to extract the observables and compare to theoretical models.

Figure 4 illustrates the main components of the E372 detector. The basic triggering elements are the start scintillator S1 and the stop scintillator bars S2. The kinematics of the $pp\pi$ reaction are such that no proton may leave the LH_2 target at an angle of greater than 45° . The scintillator array (S2) contains 18 scintillator bars, each $200 \times 3 \times 10.2 \text{ cm}^3$, with the axis of the cylinder horizontal and passing through the LH_2 target. These bars are mounted 120 cm from the LH_2 target and have almost full acceptance for all $pp\pi^-$ protons at an incident neutron energy of 438 MeV. Since at least two charged particles are detected in the $pp\pi$ events, and since no other neutron-proton reaction can produce two charged particles, we use the basic criterion that two S2 bars fire for our trigger. The S2 array also acts as a spectrometer since we calculate the momenta of the protons from their times of flight between the start scintillator and the bars. Between the scintillators and target are two large multiwire drift chambers, each containing six coordinate planes (x,y,u) to track the final state particles. We also use multiwire proportional wire chambers on the left and right sides of the target to detect pions which happen to scatter at large angles. In addition to these major components, we include a veto scintillator to veto charged particles in the neutron beam, a neutron profile monitor behind the assembly to monitor the beam position, calibration scintillators along the beam axis to calibrate the true center of our coordinate

system, "button" scintillators at precise positions along the backs of the scintillator bars for timing calibrations, and two neutron polarimeters before and after our precessing magnets.

Figure 4: Schematic diagram of E372 detector

Our first successful E372 data-taking period was from September 7 - September 21, 1990. The experiment was run with the neutron beam polarized successively in the N, L, and S directions. Data were also collected with the target empty. The incident neutron energy was 438 MeV, and polarized proton currents were on the order of 400-450 nA, limited mainly by deadtime considerations. The proton polarization was approximately 40%, which although less than hoped for, is adequate for the experiment. During this run, the new intense optically pumped ion source (I4) was used for the first time in an experiment at TRIUMF. The phase restricted cyclotron tune and fast timing used to monitor the proton beam time structure also worked well. We were able to collect a total of 36 million events during the run. The data are written to an Exabyte 8mm tape, and stored on VCR tapes. We also took data in the period February 20-March 6, 1991; during this period we obtained about 50 million events. After this last run we brought copies of the raw data on 8 mm tapes in case we might need to do the full analysis at Texas.

Data are under analysis at the University of Manitoba and at the University of Texas. The process can be broken up into two general stages. In the first stage, we decode the data from tape and extract the trajectories from the wire chambers ("tracking"). In the second stage we extract the kinematics from the trajectories ("event reconstruction"). Initially we had decided that tracking would be carried out at the University of Manitoba, and that event reconstruction would be done at the University of Texas using "skim tapes" passed from Manitoba to Texas. However, our first attempts, in December, 1990, at event reconstruction using skim tapes from the University of Manitoba revealed unexpected problems with vertex reconstruction and with the reconstructed kinematic variables, especially with 2-track events (events with only two charged particles in the detector). In February we carried out a careful study of expected background rates, the most important of which are two-track $n(n) \rightarrow np\pi^-$ events from the target flask walls. By April we began writing our own tracking codes here at Texas, and found that a prototype tracking code, although slow, produced much better tracking residuals than those deduced from the Manitoba skim tapes. We therefore continued development of our own tracking routine to

allow us to analyze E372 data independently from the University of Manitoba. This program was completed early in the summer of 1991.

Our tracking program uses large look-up tables (~1Mbyte) which are read in at the beginning of an analysis session. Using these tables, it is capable of doing a fast "brute force" fitting of data, checking every physically acceptable combination of wire cells from each event. The tracker seems to have an efficiency of up to 95%, but is relatively slow, taking about 1 second per event on a VAXstation 3100.

Using the tracker, we began careful recalibrations of the drift times. It became clear that the technique of integrating the drift time histograms to determine the drift distances was unsatisfactory, so we began an approach of successive iterations to the drift time functions. By "bootstrapping" from an initial guess drift function, and matching results with the tracking, we were able to converge on the proper drift functions for the 12 wire planes. This technique took about 4 iterations over the same data and resulted in 48 cubic polynomials (12 planes x 4 angle bins x 4 coefficients = 192 calibration constants) which determined the drift distance from the drift time for each wire in the drift chambers. By the end of June, using these drift time calibrations, we obtained tracking residuals of 0.6mm and very good vertex reconstruction, as is indicated in Figure 5. With good vertex reconstruction it became immediately clear why we had so many 2-track events which would not reconstruct: the S1 scintillator was an impressive source of background. In fact, vertex reconstruction (Figure 6) reveals that over 85% of our taped data came from background sources.

With a successful tracker and a way of rejecting much of our background (vertex cut), we returned to the task of kinematic event reconstruction. Three track events, which require only knowledge of angles, reconstructed well and produced believable kinematic plots. Two track events were harder because they require precise knowledge of the times-of-flight. Using np elastic calibration data, we calibrated the TOFs and used these calibrations to reconstruct $np \rightarrow pp\pi^-$ events. The reconstructed 2-track events had poorer χ^2 than we would have liked, and there was still much $n(n) \rightarrow np\pi^-$ background. This background is difficult to reject because there are corrections which must be made to the TOF to account for such things as energy loss in the LH₂ target, and timing offsets due to the fact that the S1 start scintillator detects two charged particles rather than one. We spent the latter half of summer studying these corrections, using Monte Carlo and transport routines to simulate the processes which affect our measurements.

By August, it became clear that we could not get the 2-track events satisfactorily unless we could more precisely determine the TOFs and use the ADC (dE/dx) information from the scintillator bars. We studied the TOF in more detail and began ADC calibrations using np elastic and Bethe-Bloch predictions for dE/dx in the NE102 bars. We found a systematic error of the order of 0.5nsec in the timing of the S1 scintillator. This error arose because the S1 scintillator is struck by two charged particles within 1 nanosecond of each other. The rise time for the scintillator and PMT is on the order of a nanosecond, so the resulting logic pulse coming from the constant fraction discriminator represents the average time of the two tracks, not the faster of the two as had been previously assumed. Making this adjustment to the calculations dramatically improved the TOFs. Using the improved TOFs we were then able to deduce the relationship between the pulse height from the bar photomultipliers (ADC) and the energy deposited in the bar (dE). This provided more information about the speed of a particle and its identity (Figure 7).

Figure 5: Bootstrapping technique to deduce drift time function. Tracking residuals converged at about $\sigma = 0.6\text{mm}$.

Figure 6: Top view of vertex reconstruction for E372 runs.

Figure 7: The TOF and pulse height (dE/dx) information from the bars aided in determining velocity and particle identification. The shape of this curve can be understood in terms of the Bethe-Bloch equation for energy loss in materials.

Using the improved TOFs and the ADC $\rightarrow$ dE calibrations, we were able to define a kinematic χ^2 as a function of some kinematic parameter, x , for 2-track events:

$$\chi^2(x) = \frac{(TOF_{meas} - TOF(x))^2}{\sigma_{TOF}^2} + \frac{(TOF_{meas} - TOF(x))^2}{\sigma_{TOF}^2} + \frac{(dE_{meas} - dE(x))^2}{\sigma_{dE}^2} + \frac{(dE_{meas} - dE(x))^2}{\sigma_{dE}^2}$$

We then reconstructed 2-track events by minimizing this χ^2 . The χ^2 for $np \rightarrow pp\pi^-$ were good, but remained poor for $n(n) \rightarrow np\pi^-$ events. This was expected, since background $n(n) \rightarrow np\pi^-$ events come from bound nucleons in the background material, and thus have Fermi motion associated with them. We observed a strong correlation between χ^2 and vertex reconstruction. Good χ^2 events, corresponding to $np \rightarrow pp\pi^-$ events, come mostly from the central target (LH₂) region. Poor χ^2 events, corresponding to $n(n) \rightarrow np\pi^-$ data, have vertices in the target walls and elsewhere (Figure 8). This correlation is direct evidence that we can identify and separate $np \rightarrow pp\pi^-$ events from background rather cleanly, even for 2-track events. Mark Bachman discussed this analysis in a paper he presented at the APS meeting at Michigan State on October 24, 1991.

Figure 8: Target vertex reconstruction is correlated to kinematic χ^2 . As expected, background events (e.g. target walls) give poor χ^2 .

We have taken a preliminary look at some kinematic variables to see the effects of our detector efficiency on the overall acceptance. Figure 9 (a) and (b) show plots of c.m. kinetic energies for the two protons, the relative probability of different invariant pp masses, and the relative probability of $\cos \theta^*_{\pi}$ for both two track and three track events. For three track events the pion must be emitted into the forward angle acceptance of the drift chambers. We expect to see very few such events with negative $\cos \theta^*_{\pi}$ values, and this is observed. For two track events most $\cos \theta^*_{\pi}$ values should be negative, since if the pion is emitted forward it should appear as a three track, rather than a two track event. We do observe an unexpectedly large contribution of two track events with positive $\cos \theta^*_{\pi}$ values. We are puzzled by this, but believe that it is primarily due to two track reconstruction and particle identification errors, and are working to correct them. The left side of Figure 9 (a) and (b) gives the our detector acceptances predicted by our Monte Carlo simulations, while the right side of the figure shows our observed acceptances. There is overall good agreement except for our unexpectedly large observed contribution from two track events with positive $\cos \theta^*_{\pi}$ values.

Three track events

- Clean trigger with almost no background ✓
- Kinematics well determined (based on six angles) ✓
- Limited phase space acceptance x

Figure 9a: Plots of selected kinematic variables for three track events. On the left are Monte Carlo predictions (uniform phase space); on the right are results of analysis. Detector efficiency is also shown.

Two track events

- Almost full phase space coverage
- Lots of background from $nn \rightarrow n\pi\pi^-$
- Kinematics less well determined (based on two TOFs)

Figure 9b: Plots of selected kinematic variables for two track events. On the left are Monte Carlo predictions (uniform phase space); on the right are results of analysis. Detector efficiency is also shown.

We now understand most of the nuances in our data and have been successful in fully analyzing a small subset of our data. We believe we should be able to begin mass analysis by January 1992. We plan to use an IBM RISC/6000 machine for the bulk of number crunching in the latter part of the analysis. The experimental raw data were written using VMS software, and most of the first stage analysis software is VAX specific. However, the codes needed for the second stage of analysis are more portable and depend less on the specifics of our data taking. Thus, we are encouraged to seek the benefits of the newer RISC architecture. This is especially true since we will want to rebin our data several times to find the most useful way to present our data, and since we will require much CPU time to compare with the theoretical models.

We are now responsible for the complete analysis of E372 from the raw data to the final observables. Although this was not how we originally planned to analyze the data, it does allow us complete control over the quality of the analysis, even though putting an undesirable strain on our resources.

-
- ¹ R. Aaron, R. D. Amado, and J. E. Young, Phys. Rev. **174**, 2022, (1968).
 - ² J. Dubach, W. M. Kloet, and R. R. Silbar, Nucl. Phys. **A466**, 573, (1987).
 - ³ A. Matsuyama and T.-S.H. Lee, Phys. Rev. **C34**, 1900, (1986).
 - ⁴ B. Blankleider and I. R. Afnan, Phys. Rev. **C31**, 1380, (1985).
 - ⁵ I. R. Afnan and R. J. McLeod, Phys. Rev. **C31**, 1821, (1985).
 - ⁶ A.B. Wicklund, *et al.*, Phys. Rev. **D34**, 19 (1986).

D. LAMPF E1097, Single Pion Production in np Scattering

1. E1097 Overview

In recent years, there has been a major effort in both the experimental and theoretical investigation of the coupled NN-NN π problem. This set of reactions is one of the simplest inelastic processes available for study. It sheds light on the NN and N π interactions and is key to understanding pion production in more complex systems. There are four independent channels available in the NN-NN π reaction. These channels can be expressed in terms of the total isospin of the initial (I) and final (I') state nucleons (I,I'): (1,0), (1,1), (0,1), (0,0). The dominant channel for pion production is through the (1,0) resonance, since the famous Δ^{++} (I=3/2, P=3/2) can proceed through this channel. The role of the non-resonant amplitudes, particularly the channel (0,1) remains elusive. The reaction np $\rightarrow$ pp π^- may proceed through the (1,1) and (0,1) channels, which avoid the Δ^{++} , making it an ideal reaction for studying the non-resonant contributions to pion production. The reaction is experimentally accessible, since all final state particles are charged, allowing efficient and precise determination of all outgoing trajectories.

LAMPF Experiment E1097 will measure the differential cross section, σ , and the spin observables A_{NO} , A_{LO} , A_{SO} , A_{OL} , A_{SL} , A_{NL} , and A_{LL} for the single pion production reaction np $\rightarrow$ pp π^- at neutron beam energies in the range 500-800 MeV. These data should allow a first order partial wave analysis of the I = 0 inelastic amplitudes. E1097 will run in two separate phases. Phase I, planned for 1993, will use a polarized neutron beam and a liquid hydrogen target; phase II, expected to run in 1994, will use a polarized hydrogen (frozen spin) target to enable the spin correlation parameters to be measured. 500 hours have been approved for Phase I of the experiment and it is our expectation that additional time will be approved for Phase II after the goals of the first measurement are met. The Phase I measurements are the same as those of TRIUMF E372 at a lower energy (438 MeV), and many of the E372 collaborators are also participating in E1097. In addition, the Saturne group under Y. Terrien are studying this reaction, and have measured asymmetries at several neutron beam energies between 572 and 1134 MeV. The Saturne group uses a polarized neutron beam but does not plan on using a polarized target; it will be of interest to compare their measurements, as well as those of TRIUMF E372, with those of E1097, Phase I. We hope that the data from the three experiments will have a major impact on our understanding of the NN-NN π system at medium energies.

2. E1097 Detector system.

The E1097 detector system consists of a large array of scintillator bars surrounding a cylindrical drift chamber, at the center of which is the target, as shown schematically in figure 10. The major part of the scintillator array will consist of the 18 bars, each 200 x 3 x 10.2 cm³, used in TRIUMF E372. These belong to the University of Manitoba group, and have been shipped to LAMPF for use in E1097. The scintillator will provide the first level trigger, and will measure the flight times (and therefore velocities) for the np $\rightarrow$ pp π^- protons. The vertical angular acceptance of the drift chamber is approximately from -60° to +60°; the horizontal acceptance (Phase II) is from -120° to 120° (for Phase I the horizontal acceptance can be larger). The cylindrical chamber has a total of 448 sense wires, and will be able to detect all three particles for more than 50% of phasespace. The chamber will measure positions perpendicular to the wires by measuring the drift time, and along the wires using charge division. This requires that the analog signal from both ends of each sense wire be read into ADCs and that some fraction of these signals be diverted into a summing circuit for discrimination and input to a TDC. We plan to use the LeCroy FERA system to provide these digitizations. Its extremely fast digitization and buffer transfer time

(20 μ s) makes it uniquely suited to the LAMPF beam structure (120 Hz at 10% duty). Since the cylindrical drift chamber is the major component of the E1097 detector system, most of our efforts for the past two years have involved design, fabrication, and testing of this detector.

Figure 10: E1097 Experimental detector

3. 1991 Progress

We have made steady progress on E1097 during 1991. During the first few three months our major project involved the stringing of the 1792 high voltage (HV) and 448 sense wires of the cylindrical drift detector. This was carried out at the Physics Department clean room at Rice University. In early May the detector was moved to LAMPF and installed in area BR downstream of the E876 setup for testing. For the summer E1097 test

runs we instrumented 7 of the 28 sense wire modules of the detector, each with 16 sense wires. The experimental setup used is indicated schematically in figures 11 and 12. A chamber support, an Ar/Freon/isobutane gas system, and a data acquisition system, including a microVAX II computer, MBD, tape drives, NIM and CAMAC crates, CAMAC crate controllers, branch highway cables, as well as FERA electronics, were provided by LAMPF. Scintillator paddles were installed on each side of the drift chamber to serve as charged particle triggers. High voltage and signal cables (shielded ribbon cables with 16 twisted pairs) were run between the MRS counting house and BR. The tests were carried out in a parasitic mode in the NPL laboratory (BR) at LAMPF, using (n,p) recoil protons from the large (15 liter) E876 LH₂ target. The main objective of the tests was to demonstrate the operation of the cylindrical drift chamber and to verify that the resolution is adequate for our needs.

Figure 11: E1097 phase 0 apparatus. Arrow indicates direction of protons scattered from E876 LH₂ target.

Figure 12: Trigger logic for E1097 phase 0.

Overall, our tests were successful, although they certainly demonstrated several problems. Noise pickup in the 250 foot long, twisted pair signal cables running between the preamp boards at the chamber end-plates and the discriminator boards (in the counting house) constituted, as expected, a major problem. Much time was spent in trying to reduce pickup and to eliminate ground loops. We were unsuccessful in bridging CAMAC crates with the FERA system, and we ended running with only one CAMAC crate of electronics, which restricted our testing to 3 modules at the same time. The last few days of the run were spent in testing modules 2, 7, and 11, in respectively layers A, B, and C of the drift chamber - with a total of 48 sense wires, 96 ADC's (excluding the additional 48 required for the TDC outputs) and 48 TDC's. We were able to obtain simultaneous TDC and ADC spectra for the wires, and carried out preliminary z-position calculations and efficiency checks. The data were recorded on tape for further off-line analyses. Most work was one with a 70/30 argon-isobutane gas mixture, and with high voltage ~2500 volts. Although breaking of HV wires proved very troublesome (about 15 HV wires broke during the

summer), during the final week of running the chamber proved to be both stable and reliable.

The passive ADC-TDC splitting network designed for the discriminator boards proved unsatisfactory, and only after modifying the circuit (of a few discriminator boards) as indicated in Figure 13 were we able to obtain satisfactory TDC signals (and from the bottom ends of the wires only). The test runs demonstrated, in addition, a need for better mounting of the preamplifier boards to allow better access to the detector end plates, the need to be able to "see" inside the drift chamber better than at present, and the need for a better chamber stand to provide for better stability, limited motion, and yet to allow easy access to both ends of the chamber.

Figure 13: Preamplifier boards used for E1097 detector.

An E1097 update was presented to the LAMPF PAC by Peter Riley on August 21. The response received from Jim Bradbury includes the following: "I am pleased to support the PAC recommendation for 500 hours of L-type beam at 800 MeV for Phase I with A-priority." The subcommittee report states that, "The Subcommittee remains convinced that the results of this experiment will be important to the understanding of hadronic reactions above the pion threshold. Although similar experiments at Saclay and TRIUMF have

already obtained some results, this is the only experiment proposing to obtain data on spin correlation parameters which will be crucial in the interpretation of the results.... Significant progress was reported in the construction and testing of the crucial component—the cylindrical drift chamber. However, the subcommittee is concerned that lack of a sufficient number of actively involved people is impeding progress on this and related issues. For example, it is not yet clear how to track lower energy pions and achieve kinematic reconstruction in the large magnetic field gradient of the frozen spin target needed for Phase II of the experiment. The subcommittee urges that the membership and organization of the collaboration be revised to offset the extensive other commitments of many of its members.”

It is clear that manpower for the experiment has been short. However, in September Kathleen Johnston accepted a LAMPF Post-doctoral position, and in addition accepted the responsibility of being an E1097 spokesperson. She has taken over a major responsibility for the experiment. Also in September, David Ambrose successfully passed his Ph. D. qualifying examination at the University of Texas, and is now able to spend a major part of his time working on the experiment. Effective June 1, he will be supported by an Associated Western Universities Fellowship. Patrick Coffey, who, with David Ambrose, spent the summer of 1991 working on E1097 tests, plans to spend the spring and summer of 1992 working at LAMPF on E1097. Finally, Alan Lan and Ed Hungerford of the University of Houston have both joined our E1097 collaboration and will provide additional help. With respect to the effect of the magnetic field on the drift chamber performance, we are proposing to carry out Monte Carlo simulations, and have obtained the CERN library code GARFIELD.

Since September we have worked to solve problems which arose during our summer test runs. Our problem with the bridging of CAMAC crates with the FERA system involved the dropping of data bits when we attempted to use one FERA driver to drive FERA's located in a different crate. Kok Heong McNaughton has been carrying out tests using a hi-power CAMAC crate on loan from LeCroy, and has been able to read 22 FERA's with one driver with no loss of data. It now appears that by using the hi-power CAMAC crates we can solve the problem.

Kathleen Johnston has been working on the E1097 chamber electronics. At the end of the summer we were faced with the need to modify our passive ADC-TDC splitting network. The solution consisted in adding an amplifier at the point on the receiver board where we split the signal, thus allowing us to send nearly all of the charge to the ADC, while still eliminating cross-talk between ends of the wires. We were thus faced with the need to redesign our discriminator boards, and to buy 448 amplifier chips in addition to discriminator boards for most of the chamber. (We had only enough for the summer's tests of 7 of the 28 modules). However, the MEGA collaboration has recently decided to switch from using charge division in the photon arm of their detector to the use of delay lines for z-position measurements. The University of Houston Medium Energy Physics group designed and built all of the MEGA charge division electronics. Dr. Ed Hungerford, the U.H. MEP group leader (and Kathleen Johnston's Ph. D. advisor) has offered us the MEGA charge division electronics for use on our chamber. It appears that with only slight modifications we can adapt the U.H. chamber electronics for our chamber. Kathleen has taken a complete set of the MEGA electronics to LAMPF and has begun tests to see if they will be suitable for our use. The major difference between the electronics appears to be that in the U.H. scheme the analog signal from the sense wire is split close to the chamber (rather than in the counting house). The TDC AMP-DISC board is then also located near the chamber, which then sends out an ECL pulse to the TDC located in the counting house. Thus, additional signal cables will be needed for this system.

4. Count Rate and Acceptance Studies

We have carried out rate and acceptance studies in order to optimize E1097 drift chamber and scintillator array geometries, and to determine the best event trigger for the experiment. To do this we have calculated the probability of detecting $np \rightarrow pp\pi^-$ events, as well as competing events, using the CERN library simulation program GEANT. In what we describe, the assumed configuration, as shown schematically in figure 14, consists of a LH_2 target placed in the middle of the drift chamber, followed immediately by a 1/16" thick S1 scintillator. The scintillator array consists of 24 back bars, with 6 "thin" bars (280 cm x 5.1 cm x 2.54 cm) sandwiched between the 18 bars (200 cm x 10.2 cm x 3 cm) used at TRIUMF, and two side arrays of 3 scintillator bars each (180 cm x 20 cm x 3 cm) as shown in the figure. Assumed materials and thicknesses for the LH_2 target, the S1 scintillator, and the drift chamber with its cylindrical carbon walls are indicated schematically in figure 15. Competing reactions, and their approximate 800 MeV cross sections, are given below:

Reaction	mbarn
$np \rightarrow pp\pi^-$	1.90
$np \rightarrow np\pi^+$	7.00
$np \rightarrow nn\pi^+$	1.90
$np \rightarrow d\pi^+$	0.70
$np \rightarrow np$	27.0
$nn \rightarrow nn\pi^+$	4.00
$nn \rightarrow np\pi^-$	18.0
$nn \rightarrow d\pi^-$	1.40

All events which compete with free $np \rightarrow pp\pi^-$ are considered as background events. We calculated acceptances as follows: for a given reaction, the event vertex was chosen randomly in the space defined by the intersection between beam and target. This procedure is not strictly correct since, for the LH_2 target, "bound" nucleons are constrained to the walls of the LH_2 flask and to the walls of the vacuum jacket. Momenta were selected randomly from the allowed phase-space distribution. GEANT then propagated each particle through the laboratory geometry, calculating all relevant physical processes including multiple scattering, energy straggling, pion decay, and hadronic interactions. 5000 events were thus propagated for each reaction. We have also included, based on our experience at TRIUMF, a 4% "cross talk" in the scintillator bars, where a charged particle will fire two bars, and a 1% neutron "conversion" (to a charged particle) in the scintillator bars. Acceptances are tabulated below for each reaction, where a drift chamber "track" is defined as at least 3 wire pairs hit. A track originating at the center and passing straight through the chamber would normally pass through, or "hit" the cells defined by 4 wire pairs. Track reconstruction should be possible provided that at least 3 wire pairs are hit. Thus, for the $np \rightarrow pp\pi^-$ reaction, 1677 events (out of 5000) fired three scintillator bars and gave three tracks in the cylindrical drift chamber. Two charged particles passing by the same wire will register as one hit; two charged particle passing through the same bar will likewise register as one bar hit. Mercator projections of proton and pion distributions over the E1097 detector are shown in Figures 16(a) and 16(b). Double and single hit probabilities for planes 1 and 7 (where the chamber is assumed to consist of 8 concentric signal wire planes) are shown in Figures 17(a) and 17(b), respectively.

Figure 14: Top view of laboratory used in GEANT simulation.

Figure 15: Details of materials used in GEANT simulation.

Figure 16 (a and b): Phasespace plots of $np \rightarrow pp\bar{\nu}$ events as seen by the detector. These Mercator projections show that all the protons and most of the pions are constrained to fall within the geometry of the detector.

Figure 17 (a and b): Single and double hit probabilities for E1097 wire chamber, plane 1 and plane 7.

Table 2: Monte Carlo acceptance calculations
E1097 detector acceptances, where a single "track" is defined as 3 (or more) wire pairs hit by a charged particle. N_t = no. of tracks, and N_b = no. of bar hits during a given event. See figures 10 and 14 for illustration.

$np \rightarrow pp\pi^-$					
	$N_b=0$	$N_b=1$	$N_b=2$	$N_b=3$	$N_b=4$
$N_t=0$	4	110	97	16	0
$N_t=1$	7	189	760	369	20
$N_t=2$	2	44	670	110	9
$N_t=3$	0	33	668	1677	208

$np \rightarrow np\pi^0$					
	$N_b=0$	$N_b=1$	$N_b=2$	$N_b=3$	$N_b=4$
$N_t=0$	380	373	20	0	0
$N_t=1$	151	3874	189	3	0
$N_t=2$	0	1	6	3	0
$N_t=3$	0	0	0	0	0

$np \rightarrow nn\pi^+$					
	$N_b=0$	$N_b=1$	$N_b=2$	$N_b=3$	$N_b=4$
$N_t=0$	1202	648	37	1	0
$N_t=1$	718	2260	118	1	0
$N_t=2$	0	3	11	1	0
$N_t=3$	0	0	0	0	0

$np \rightarrow d\pi^0$					
	$N_b=0$	$N_b=1$	$N_b=2$	$N_b=3$	$N_b=4$
$N_t=0$	453	81	8	0	0
$N_t=1$	183	4121	154	0	0
$N_t=2$	0	0	0	0	0
$N_t=3$	0	0	0	0	0

$np \rightarrow np$					
	$N_b=0$	$N_b=1$	$N_b=2$	$N_b=3$	$N_b=4$
$N_t=0$	707	323	16	0	0
$N_t=1$	503	3290	152	1	0
$N_t=2$	0	2	6	0	0
$N_t=3$	0	0	0	0	0

$nn \rightarrow nn\pi^0$					
	$N_b=0$	$N_b=1$	$N_b=2$	$N_b=3$	$N_b=4$
$N_t=0$	4884	98	1	0	0
$N_t=1$	0	16	1	0	0
$N_t=2$	0	0	0	0	0
$N_t=3$	0	0	0	0	0

$nn \rightarrow np\pi^-$					
	$N_b=0$	$N_b=1$	$N_b=2$	$N_b=3$	$N_b=4$
$N_t=0$	115	474	135	8	0
$N_t=1$	31	916	548	44	1
$N_t=2$	12	615	1929	160	5
$N_t=3$	0	0	4	3	0

$nn \rightarrow d\pi^-$					
	$N_b=0$	$N_b=1$	$N_b=2$	$N_b=3$	$N_b=4$
$N_t=0$	188	378	106	2	1
$N_t=1$	34	500	80	3	0
$N_t=2$	37	1090	2392	181	8
$N_t=3$	0	0	0	0	0

Having calculated acceptances, we calculated the expected event rates, r , for each reaction from

$$r = \Phi \times N \times \sigma \times \epsilon$$

where

Φ = neutron flux,

N = number of scatterers/cm²,

σ = reaction cross section,

ϵ = acceptance.

The neutron flux, based on an average proton beam current of 500 nA, a macro-pulse, or "spill" length of 600 μ sec, with spills at the rate of 100 Hz, and the E1097 LH₂ target a distance of 15m from the LD₂ production target, is 430 n/cm²/spill (at the LH₂ target). Assuming a neutron beam diameter of 4.24 cm at the LH₂ target, we obtain a neutron flux of 773,000 neutrons/sec passing through the LH₂ target. For the LH₂ target (a 3 inch diameter cylinder, with its axis vertical) we obtain 3.05×10^{23} free protons per cm², and 3.26×10^{22} per cm² for each of bound neutrons and protons from the mylar flask and vacuum jacket windows. The acceptance, ϵ , is defined as the percentage of events which satisfy a particular trigger requirement. Table 3 below gives the results obtained, first in

terms of rates in Hz for each event, and then in terms of acceptances, in percentages, for the specified trigger. The most restrictive trigger specified is $N_b > 1$, $N_t > 2$, where N_b refers to the number of scintillator bar hits, and N_t refers to the number of tracks (each with a minimum of three wire pairs) in the drift chamber. Thus, the overall acceptance for $np \rightarrow pp\pi^-$, with $N_b > 1$, $N_t > 2$, is 51%. It is clear that hardware triggers, such as $N_b > 1$, $N_t > 2$, will be needed both on the number of bar hits (N_b) and on the number of wire hits (N_t) in order to reduce background events. This will be particularly important for Phase II of the experiment, which uses a polarized proton target. It should be pointed out that we have not considered the scintillator S1, a 1/16" thick Bicron 404 scintillator in our rate calculations. Vertex reconstruction should eliminate these events on replay, but they will contribute to the counting rate of the experiment. We estimate a thickness of 0.16 gm/cm² from S1, about one third the total thickness of the LH₂ target. Thus, our overall count rate estimates, above, are too low.

Table 3: Rate Estimates for E1097

Estimates of E1097 rates for signal and background, given different trigger requirements.

Beam parameters

Beam width (cm)	4.24
Neut/spill/area	430.0
Neutrons/spill	7730.4
Spills/sec	100.0
Neutrons/sec	773036.8

Target parameters

Target material	Dens(g/cm ³)	Thickness (cm)	Area (cm ²)	Nucleons/cm ²
LH ₂	0.071	7.620	30.554	3.05×10^{23}
Mylar flask	1.390	0.026	0.114	2.24×10^{22}
Mylar window	1.390	0.050	0.215	4.22×10^{22}

Target summary

P free/cm ²	3.05×10^{23}
P bound/cm ²	3.24×10^{22}
N bound/cm ²	3.24×10^{22}

Approximate rates for each reaction

	Reaction	mbarns	Abs Prob	Rel Prob	Rate (Hz)
Free Protons	$np \rightarrow pp\pi^-$	1.90	5.80×10^{-4}	1.00	448.18
	$np \rightarrow np\pi^0$	7.00	2.14×10^{-3}	3.68	1651.19
	$np \rightarrow nn\pi^+$	1.90	5.80×10^{-4}	1.00	448.18
	$np \rightarrow d\pi^0$	0.70	2.14×10^{-4}	0.37	165.12
	$np \rightarrow np$	27.00	8.24×10^{-3}	14.21	6368.89
Bound Nucleons	$nn \rightarrow nn\pi^0$	4.00	1.29×10^{-4}	0.22	99.98
	$nn \rightarrow np\pi^-$	18.00	5.82×10^{-4}	1.00	449.92
	$nn \rightarrow d\pi^-$	1.40	4.53×10^{-5}	0.08	34.99
	$np \rightarrow pp\pi^-$	1.90	6.14×10^{-5}	0.11	47.49
	$np \rightarrow np\pi^0$	7.00	2.26×10^{-4}	0.39	174.97
	$np \rightarrow nn\pi^+$	1.90	6.14×10^{-5}	0.11	47.49
	$np \rightarrow d\pi^0$	0.70	2.26×10^{-5}	0.04	17.50
	$np \rightarrow np$	27.00	8.73×10^{-4}	1.51	674.88

 Acceptances for each reaction, given different triggers
 (N_b = Number of bars hit; N_t = Number of tracks reconstructed)

	Reaction	$N_b > 1$	$N_b > 2$	$N_b > 1, N_t > 1$	$N_b > 1, N_t > 2$
Free Protons	$np \rightarrow pp\pi^-$	92%	48%	67%	51%
	$np \rightarrow np\pi^0$	4%	0%	0%	0%
	$np \rightarrow nn\pi^+$	3%	0%	0%	0%
	$np \rightarrow d\pi^0$	3%	0%	0%	0%
	$np \rightarrow np$	4%	0%	0%	0%
Bound Nucleons	$nn \rightarrow nn\pi^0$	0%	0%	0%	0%
	$nn \rightarrow np\pi^-$	57%	4%	42%	0%
	$nn \rightarrow d\pi^-$	55%	4%	52%	0%
	$np \rightarrow pp\pi^-$	92%	48%	67%	51%
	$np \rightarrow np\pi^0$	4%	0%	0%	0%
	$np \rightarrow nn\pi^+$	3%	0%	0%	0%
	$np \rightarrow d\pi^0$	3%	0%	0%	0%
	$np \rightarrow np$	4%	0%	0%	0%

Event rate: Events/second

	Reaction	$N_b > 1$	$N_b > 2$	$N_b > 1, N_t > 1$	$N_b > 1, N_t > 2$
Free Protons	$np \rightarrow pp\pi^-$	4.12×10^2	2.15×10^2	3.00×10^2	2.29×10^2
	$np \rightarrow np\pi^0$	66.0	0.00	3.30	0.00
	$np \rightarrow nn\pi^+$	13.4	5.38×10^{-1}	1.25	0.00
	$np \rightarrow d\pi^0$	4.95	0.00	0.00	0.00
	$np \rightarrow np$	2.55×10^2	0.00	7.64	0.00
Bound Nucleons	$nn \rightarrow nn\pi^0$	0.00	0.00	0.00	0.00
	$nn \rightarrow np\pi^-$	2.56×10^2	18.0	1.89×10^2	6.30×10^{-1}
	$nn \rightarrow d\pi^-$	19.2	1.50	18.2	0.00
	$np \rightarrow pp\pi^-$	43.7	22.8	31.8	24.2
	$np \rightarrow np\pi^0$	7.00	0.00	2.10×10^{-1}	0.00
	$np \rightarrow nn\pi^+$	1.42	0.00	1.42×10^{-1}	0.00
	$np \rightarrow d\pi^0$	5.25×10^{-1}	0.00	4.20×10^{-2}	0.00
	$np \rightarrow np$	27.0	0.00	1.35	0.00

Estimated signal/background

Reaction	$N_b > 1$	$N_b > 2$	$N_b > 1, N_t > 1$	$N_b > 1, N_t > 2$
$np \rightarrow pp\pi^-$	1.00	1.00	1.00	1.00
Background	1.68	0.20	0.84	0.11

$np \rightarrow pp\pi^-$	37.25%	83.39%	54.22%	90.21%
Background	62.75%	16.61%	45.78%	9.79%

Recommended empty runs

Empty runs	$N_{bar} > 1$	$N_{bar} > 2$	$N_b > 1, N_t > 1$	$N_b > 1, N_t > 2$
% of beam	44.20%	28.95%	40.36%	23.83%

We next sought to determine where the 49% acceptance loss was occurring using the trigger $N_b > 1, N_t > 2$ for the $np \rightarrow pp\pi^-$ reaction with the E1097 setup. The factors contributing to the acceptance loss and their respective percent of events lost are shown below. The sum of all losses, 56.2%, is somewhat higher than our calculated acceptance of 49% since no account is taken in table 4 below of overlapping events. For example, tracks may be lost from double hits on a single wire, and in addition one of the protons may range out.

Table 4: Acceptance loss for E1097: trigger $N_b > 1, N_t > 2$.

Reason for loss	% of events lost
Pions lost out of the top of the chamber	0.6%
Tracks lost from double hits on a single wire	8.7%
Protons ranging out (initial KE < 60 MeV)	18.7%
Pions ranging out (initial KE < 20 MeV)	13.5%
Original proton track lost from hadronic processes	7.4%
Original pion track lost from hadronic processes	8.0%
Sum of all losses. Some losses may overlap	56.2%

GEANT simulations are underway to map out the efficiency of the E1097 detector throughout phasespace for several possible trigger configurations. The simulations will produce a complete history of a simulated run in a standard format. From these data we will be able to analyze the simulated run using the same procedure that we expect to use to analyze data from actual runs.

5. E1097 tracking and Reconstruction Software

A major part of the E1097 analysis will be the extraction of the five kinematic parameters which characterize a three-body final state. We will calculate 5 such parameters for each event using the directions of each of the 3 particles as determined by the drift chamber (6 values) and the times of flight for forward particles (normally two values) deduced from the scintillator array. Thus the data set will contain more information than is needed to reconstruct the kinematics of the events. The quality of fit, which assume the kinematics of $np \rightarrow pp\pi^-$, is used to identify background events. It is necessary that the data be over-constrained in order to cut against background in Phase II, where the frozen spin target is expected to introduce much noise due to quasi-free scattering of neutrons with the bound protons in the carbon (or nitrogen) nuclei in the target. The bound events in general have larger than the free events due to the Fermi motion associated with their protons.

A software package has been developed at the University of Texas by David Ambrose to process both real and simulated wire chamber data for tracking particles through the detector and reconstructing three-track events. The tracking programs consist of four main routines: data input, track pattern recognition, track fitting, and event reconstruction. The input stage will read in either detector data for real events, or simulate the data for a desired event type. Single-track events simulating Phase 0 operation (with elastic protons from the E876 LH₂ target traversing the chamber) or $np \rightarrow pp\pi^-$ events can be generated. Other, more detailed simulators, such as GEANT, which can incorporate physical processes such as energy loss and multiple scattering, can also be used. The track pattern recognition routine converts this input data, in the form of ADC and TDC values, into cylindrical coordinate hits. The hit distance along the sense wire (cylindrical z-position) is found through charge division of the ADC values from both ends of the wire, while the perpendicular drift distance of the hit from the wire must be calculated from the drift time (TDC) with a calibrated polynomial equation. Once the hit coordinates of an event have been established, certain hits are grouped together to form tracks by routines which recognize lines through the detector.

The third section of the tracker fits the track hits to a straight line by performing least squares analyses. From the slopes and intercepts of these lines, two angles describing the trajectory can be extracted. Uncertainties in these angles, dependent on the resolution and number of hits in the track, are also calculated. Finally, if all three $np \rightarrow pp\pi^-$ reaction products have been detected, the final program routine reconstructs the events by identifying the particles and calculating the momentum and energy of each.

In addition to these main program sections, other subroutines have been developed to calculate and histogram specific quantities of interest, compare tracking results with simulated data, and display graphically the events. At present the program is being applied to the Phase 0 test data from the summer of 1991. Analysis of this data has given us a measure of the efficiency and resolution of the chamber. These parameters can then be used by the program in our $np \rightarrow pp\pi^-$ reaction simulations to predict the performance of the chamber in Phases I and II of the experiment. Our Phase 0 parasitic data consists almost exclusively of events in which a single particle passes horizontally through the chamber. A typical such track (run no. 174, event 34) is shown in Figure 18, where the x's are used to indicate wire hits and the dashed lines are the reconstructed track projections. Hence, we expect the z-position along the wires should be nearly identical for all the hits in a given track. By calculating the difference in z-position between pairs of single-track hits with a sense wire layer, the charge division relation has been tested, and a z-position resolution of

about 1 cm has been found as shown in Figure 20. Additionally, drift distances have been calculated from the TDC values for the test data. Simulation of the experiment shows that these drift distances should be fairly uniform over the range of the sense wire cell, while the drift times measured during testing are non-linear over the TDC range. Thus, a polynomial fit has been made to convert the measured drift times to distances. This conversion from time to drift distance is shown in Figure 20 for 381 phase 0 tracks. The resolution of the drift distance, which is a function of the drift time and TDC resolution, has been estimated to have a maximum near $200\text{ }\mu\text{m}$.

Figure 18: E1097 phase 0 event with 5 hits. Track fit is shown as dotted line.

Figure 19: Drift time function and drift distance for E1097 wire chamber.

Figure 20: E1097 wire chamber vertical resolution.

5. E1097 Plans for 1992.

During the summer of 1992 we plan to carry out further parasitic tests of the drift chamber and its associated electronics in LAMPF area BR behind the E876 setup. For these tests we hope to have at least one-half of the chamber fully instrumented, including the requisite FERA electronics. If we can successfully test one-half of the chamber, we can be ready for Phase I of the E1097 experiment by 1993. During the January - June of 1992 we must finalize the chamber electronics, carry out extensive wiring of the chamber, design and build a detector stand, and begin work on testing and assembly of the scintillator array. The wiring chamber work is necessary since we must not only replace the broken HV wires, but we plan on modifying the connection of the sense wires to the inserts at the chamber end-plates to ensure stability and length uniformity of the sense wires.

6. Monte Carlo Comparison Between Theoretical Predictions and Experiment for $np \rightarrow p p \pi^-$

In our experiments we typically make measurements over a large range of kinematic points in phase space and then bin the data to selected variables. A problem with E372 and E1097, both of which measure spin observables over a large fraction of phase space available, lies in how best to bin data in order to allow meaningful comparisons between

experiment and theoretical predictions. The phase space for a three body final state contains five independent variables, which means that we must measure N^5 events, (where N is the number of bins per variable) if we wish to get a single count in each bin. Thus, if we wished to see only 10 bins per variable with about 100 counts in each bin, we would need to take about 10^7 events; if we wanted 100 bins, we would need 10^{12} events. A way to avoid the need for an unrealistic amount of data is to pick fewer independent variables to bin against, and to integrate over the remaining variables. However, this sometimes makes it difficult to compare with theory with experiment. The theoretical code written by Dubach, Kloet, and Silbar (DKS)¹ called PIPROD85 calculates spin observables for a given set of input kinematic variables. The kinematic parameters it uses to define an event for the reaction $np \rightarrow pp\pi^-$ are P_p (momentum of the first proton), θ_p , θ_π , and ϕ_π . The code implicitly assumes the fifth parameter $\phi_p = 0$ (again for the first proton). As it is written, the code is not suited to allow easy comparisons with our data. It would be useful, using predictions of the DKS (or of some other theoretical calculation), to be able to generate predictions that are directly comparable to our data. For example, we might want to show plots of our experimental yield versus $\cos\theta_\pi^*$ (the center of mass angle of the pion), as a function of different bins of M_{pp} , the invariant mass of the two protons. This represents integrations over the three other phase space variables, ϕ_π , $\cos\theta_p$, ϕ_p . The DKS code does not integrate over arbitrary variables, so we would be unable to make direct comparisons to the DKS predictions.

The direct solution is to integrate the theoretical predictions over the same variables that the experimentalist integrates his data. This would imply a major rewriting of PIPROD85, and probably of most other codes, to produce predictions that are convenient to our measurements. Further, we wish flexibility in choosing which variables to bin against in order to test different aspects of the physics involved. A direct change of the codes means we cannot be flexible about our variables, since we cannot rewrite the theoretical codes every time we want to try binning to new projections in phase space.

To resolve the problem, we propose to integrate the theoretical codes by a Monte Carlo technique. This procedure will have the advantage of being flexible (we will be able to integrate over any variables) and easy to implement allowing us to use it with a number of different theoretical codes. The basic strategy is as follows.

(1) We will run a phasespace Monte Carlo subroutine which returns the kinematics of a three body reaction ($np \rightarrow pp\pi^-$) chosen uniformly in phase space.

(2) We will then input each three-body event into the DKS code, and calculate the experimental observables for each event. For each event we will calculate its probability of occurrence, which in the simplest case will be its predicted differential cross section, $d^5\sigma/d\Omega^5$ (normalized so that $\int d^5\sigma = 1$). However, to include spin effects, we must supply additional weighting caused by asymmetries which can be calculated from the spin observables. We weight the event probability by $(I^{++})(d^5\sigma/d\Omega^5)$, where I^{++} is (as in the paper of Shypit *et al.*²)

$$I^{++} = 1 + A_b P_b^{++} + A_t P_t^{++} + A_{bt} P_b^{++} P_t^{++}.$$

In general, I refers to the event rate, the "+" signs to spin and target orientation, b to the beam, and t to the target. Thus, P_b refers to the beam polarization, P_t to that of the target, and A_b to the beam analyzing power. The calculation of the event probability will be done by a subroutine that incorporates PIPROD85 or any theoretical code which makes these predictions.

3) Each event selected *may* be written to disk. The chance of being written to disk will be based on the probability calculated in step 2. As the Monte Carlo loops through events, those with higher probability will be written to disk more often than events with lower probability. The resulting file will contain events in a density which reflects the physics of the theoretical model. At a later time, we can bin these events in the same way that we bin our experimental data so that the comparison will be direct. For example $d\sigma/d\Omega$ vs. $\cos\theta_{\pi^*}$ plotted as function of several bins of M_{pp} could be generated. We would calculate $\cos\theta_{\pi^*}$ and M_{pp} for all the stored events on disk, then bin those events which have M_{pp} in a desired range in bins of $\cos\theta_{\pi^*}$. The resulting histogram of counts will be proportional to the differential cross-section (to actually get the differential cross-section, we divide the bin counts by the bin width and the total number of events, then multiply by the total cross-section). In a similar way, we can calculate analyzing powers by tabulating left - right asymmetries for each bin. These calculations are the same as we do to our experimental data.

In selecting events from phase space we will employ the Metropolis algorithm³, which is essentially a random walk technique. We choose an event in phase space, $\mathbf{x}$, and then calculate its probability based on the observables for that point. Next, we choose another point in phase space, $\mathbf{x}'$, and calculate its probability. We move to the new point $\mathbf{x}'$ if a random number r chosen from 0 to 1 is less than $P(\mathbf{x}')/P(\mathbf{x})$. Thus, if the new position has a larger probability density, the algorithm will always move there. If not, it may move there. After each iteration, we write the current phase space point to a file. The resulting file contains points distributed with the probability $P(\mathbf{x})$.

An example of this algorithm is shown for the hydrogen atom. The probability for finding an electron at point $\mathbf{x}=(r,\theta,\phi)$ in a given quantum state (n,l,m) is given by:

$$P(\mathbf{x}) = |\Psi_{n,l,m}(r,\theta,\phi)|^2$$

where for $n=3, l=2, m=0$,

$$\begin{aligned}\Psi_{3,2,0}(r,\theta,\phi) &= Y_{2,0}(\theta,\phi) \cdot R_{3,2}(r) \\ &= \frac{1}{176} e^{-r/3} r^2 \cdot \left(\frac{3}{2} \cos^2\theta - \frac{1}{2}\right)\end{aligned}$$

Using the Metropolis algorithm, we can produce events in phase space (in this example, we consider only the position space of phase space). The resulting distribution of events is shown in the figure below. The experimentalist may actually only measure the angular distribution of electrons, but with the data set it is easy to integrate over radii and azimuthal angle to compare to the theoretical predictions.

Electron density plot of hydrogen 3D₀ state

Angular distribution of electrons

Figure 21: Results of Monte Carlo technique for the hydrogen atom

Although the procedure is simple in principle, we anticipate some problems in the details of writing the code. The DKS program PIPROD85, for example, implicitly assumes that ϕ_p for the first proton be 0, whereas ϕ_p can, in reality, range over all values. We will take this into account by rotating our system (the beam, target and polarizations) through the correct ϕ_p angle in calculating asymmetries. Thus, our Monte Carlo probabilities will be based on the projections of the polarizations to the plane defined by the first proton and beam.

We expect to input theoretical predictions other than those of DKS into our Monte Carlo "theoretical simulation." Silbar⁴ has suggested that it should be possible to run not only Tjon-vanFaassen model amplitudes, but also Earl Lomon's model amplitudes through PIPROD for 3-body final states. It would then be possible to have three model curves to compare directly to our experimental histograms.

¹ J. Dubach, W. M. Kloet, and R. R. Silbar, Nucl. Phys. **A466**, 573 (1987).

² R. L. Shypit *et al.*, Phys. Rev. **C40**, 2203, (1989).

³ N. Metropolis, A. Rosenbluth, M. Rosenbluth, A. Teller and E. Teller, J. Chem Phys. **21**, 1087, (1953).

⁴ R. R. Silbar, (private communication).

E. BNL E871: A New Search for Very Rare K_L^0 Decays

Overview

The present description of the fundamental particles and their electroweak and strong interactions is the Minimal Standard Model (MSM). Although this model has never been shown to be wrong, because of its many arbitrary parameters, it is suspected to be incomplete. Measurements performed in recent years make it clear that incompleteness must originate with physics at very large mass scales. Rare decay physics probes some of these higher mass scales.

In the MSM the decay $K_L^0 \rightarrow \mu e$ is forbidden by conservation of electron and muon additive quantum numbers. Its observation would be the first direct evidence of physics beyond the MSM. The decays $K_L^0 \rightarrow \mu\mu$ and $K_L^0 \rightarrow ee$ are permitted in the MSM, but are highly suppressed. $K_L^0 \rightarrow ee$ has not yet been seen, and observation of a branching ratio for this process that is significantly above MSM predictions would also be evidence for new physics.

BNL E791, a high sensitivity search for $K_L^0 \rightarrow \mu e$ and $K_L^0 \rightarrow ee$, completed data-taking at the Alternating Gradient Synchrotron facility (AGS) of the Brookhaven National Laboratory in 1990. The E791 spectrometer provided precise tracking with good (redundant) particle identification. Very high rate capability was achieved using custom built front-end electronics, a large parallel readout architecture, and a multi-level trigger system utilizing SLAC 3091/E emulators. The experiment had three production runs spanning 1988-1990. When data from the 1988, 1989, and 1990 runs are combined, the single event sensitivity to the decay $K_L^0 \rightarrow \mu e$ will be about 1.5×10^{-11} . The E791 collaboration concluded that more running with the same apparatus is not an attractive way to make further gains. Therefore, a new collaboration—with substantial overlap with E791—has formed to perform a new search for $K_L^0 \rightarrow \mu e$ and similar modes. A new proposal was written, E871, "A New Search for Very Rare K_L Decays," (Spokesmen; W. R. Molzon, University of California, Irvine, S. G. Wojcicki, Stanford, and J. L. Ritchie, University of Texas), and was presented to the BNL Program Advisory Committee on November 8, 1990. The new experiment will build on the experience of E791, the most sensitive kaon decay experiment performed to date, and will re-use some of the E791 equipment. Through increased acceptance, higher rate-handling capability, and improvements in several detector systems, the experiment should reach a single event sensitivity below 2×10^{-12} . At this sensitivity, a few decays of the type $K_L^0 \rightarrow ee$ should be observed if the decay occurs at the Standard Model level, along with about 10,000 $K_L^0 \rightarrow \mu\mu$ decays. The experiment is possible because of the increased beam flux made available by the Booster.

After the 1990 production run, a beam dump or "plug" was installed in the second dipole magnet to investigate whether such a concept could be utilized for a new, factor of 10 type improvement, experiment. The purpose of the plug is to stop the neutral beam near the upstream end of the spectrometer. Based on the results of the plug test, the E791 collaboration designed a new plug for additional tests which were made in the Spring of 1991. We helped to prepare stand-alone neutron and photon detectors which were used during the beam tests in the spring of 1991 to measure neutron and photon fluxes and energy distributions at different locations. We also operated several parts of the E791 spectrometer during the beam tests to make rate measurements in actual detector elements. During the summer, these tests were analyzed, and a new presentation was made to the BNL PAC by Jack Ritchie on August 28. Subsequently, E871 was approved for approximately 5000 hours of beam time over the next several years.

E791 Results and Detector

The E791 layout is shown in Figure 22. 24 GeV protons were incident on a one interaction length copper target. A neutral beam was defined by a series of collimators centered at a 2.75 degree angle from the incident proton beam direction. Two dipole sweeping magnets removed charged particles from the beam. The "decay volume" was a region extending from 10 meters from the target to the most upstream drift chamber at 18 meters from the target. Tracking was performed by 5 drift chamber modules (each module makes two x and two y measurements). Each of the two dipole magnets provided $\Delta p_T \approx 300$ MeV, but with opposite sign. Downstream of the final drift chamber, followed a finely segmented scintillator hodoscope, a gas threshold Cerenkov counter, another hodoscope and a large lead glass array. The scintillation hodoscopes provided the signals used in the lowest level (fast logic) trigger. The Cerenkov counter also provided a fast signal, indicating the presence of an electron, which was used in the low level trigger. The lead glass gave an electromagnetic energy measurement which was used for offline $\pi:e$ discrimination. A meter of steel followed the lead glass to stop all particles except muons. Downstream of the steel, a segmented scintillation hodoscope provided a fast muon signal for the low level trigger. Finally, muons were stopped in a segmented absorber stack with large proportional wire chambers spaced throughout the stack. This "rangefinder" provided a muon range measurement which corresponds to a 10% measurement of momentum and was important in the offline muon identification.

Trigger decisions were made in two stages. A low level fast logic trigger was based on the scintillation counter hodoscopes, the Cerenkov counter, the muon hodoscopes, and mean timer signals from the upstream drift chambers. A high level trigger was based on rudimentary event reconstruction using drift chamber hits. This was carried out by eight SLAC 3081/E parallel processors.

Results from the analysis of 1989 data are as follows:

$$\begin{aligned} \text{Br}(K_L \rightarrow \mu e) &< 8.4 \times 10^{-11} \text{ (90\% confidence level)} \\ \text{Br}(K_L \rightarrow ee) &< 1.1 \times 10^{-10} \text{ (90\% confidence level)} \\ \text{Br}(K_L \rightarrow \mu\mu) &= (7.6 \pm 0.5(\text{stat.}) \pm 0.4(\text{syst.})) \times 10^{-9} . \end{aligned}$$

Although results are not yet available, the sensitivity of the 1990 run was about 1.3 times better than that of the 1989 run.

The E871 Detector

E871 will, like E781, be mounted in the AGS B5 beamline, and will re-use a significant part of the existing E791 detector. The key features of the new experiment will be the following.

- The beamline will be rebuilt to provide a longer collimation channel.
- The decay volume will be lengthened.
- A high precision tracking device, probably a straw drift chamber, will be installed inside the vacuum decay region. A second tracker will also be used in the downstream part of the spectrometer and will perform both trigger and tracking functions.
- Detector apertures will be increased by using the existing 96D40 magnet as the upstream spectrometer magnet and building a new magnet to be located downstream of the 96D40.
- A beam stop, or plug, will be inserted in the 96D40 to stop the neutral beam.
- The two dipoles will be operated with opposite fields, but tuned to provide a net p_T kick of about 220 MeV, which will make daughters from 2 body K_L decays parallel to the beam direction. This parallelism will be used in forming the Level 1 trigger.

- Three existing drift chamber planes will be reused, but one new plane will be built. A faster drift chamber gas will be used than in E791.
- A new Cerenkov counter and an instrumented iron muon filter will be built.
- The lead glass array may be reconfigured and reused, but other alternatives will be considered.
- The muon rangefinder will be reconfigured and reused.

The layout of the new experiment is shown in Figure 23. E871 will rely on placing a beam dump, or plug, inside the spectrometer to stop the neutral beam. There will reduce the rates to to K_L decays in the detectors for downstream of the plug. The advantages of this new approach are summarized below.

- The acceptance of the experiment will be increased by about a factor of 2 over E791.
- The beam plug will reduce the rates in the detector elements downstream of the 96D40.
- the particle identification should be cleaner, owing to the much lower rates in the lead glass and muon detectors.
- The parallelism of tracks from 2-body decays will provide a large suppression in the Level 1 trigger rates and make it easier to group signals from trigger counters, the Cerenkov counter, and the muon counter.
- The improved trigger rejection at Level 1 will allow more time per event for the online processors. The parallel tracks at the back of the spectrometer will provide a powerful handle for fast pattern recognition.
- The parallelism of tracks will simplify the Cerenkov optics.
- The radiation dose in the lead glass will be much reduced.
- Making detectors continuous across the beam centerline will eliminate the degradation of performance the occurs near detector edges for some detectors (leakage, edge effects).

The Beam Plug

A critical feature of the E871 is the beam plug, which must stop both the neutral beam and the bulk of the secondary particles that are created in the beam plug. Work is continuing in order to optimize the design of the beam plug using a code HETC-MORSE that reproduces both hadronic showers and low energy neutron production, transport, and absorption. The space available for the plug is about 2 meters longitudinally, 1 meter vertically, and about 40 cm in width. The plug needs to be of high density, short interaction length material in the upstream part and in the core region, to attenuate hadrons as fast as possible to suppress pion decays to muons. Hydrogen rich material to attenuate slow neutrons is needed, on the other hand, on the periphery of the plug, and at the upstream and downstream ends. The plug consists of a tungsten core, backed up by copper, and surrounded by borated polyethylene. An outer layer of lead or tungsten attenuates the photons emitted in the capture of thermal neutrons. The quantity of tungsten used is about 4 tons. Figure 24 shows horizontal and vertical cross section views of the beam plug.

Schedules, Costs, and Responsibilities

The major milestones for the experiment are as follows:

November, 1990	Begin beam plug purchase/fabrication
March-May, 1991	Beam test with plug
Spring, 1992	Completion of beamline, beam tests
Spring, 1993	Detector in place, engineering run
Winter/spring, 1994	Physics run
Winter/spring, 1995	Physics run

The total hours requested for E871 are 6400. The total estimated cost is \$5,088K, of which \$2,095K are for the beamline, \$1,975K is for the detector, and \$1,018K is contingency. At present, five institutions: UC Irvine, Stanford, Temple, Texas, and William & Mary, are part of the collaboration making this proposal. Work has been underway at Texas to understand the problems associated with three E871 detector systems: straw tube counters, the electromagnetic calorimeter, and instrumented iron. The straw tube counters, which will replace E791 drift tubes counters at the upstream end of the detector system, have been proposed because of the high intensity of the E871 beam, the hostile plug environment, and the required overall robustness needed of the tracking system. The electromagnetic calorimeter mainly provides π :e discrimination. It may also be valuable in μ discrimination. The instrumented muon filter will (1) provide a signal to the level 1 logic which indicates the passage of a parallel muon with momentum greater than 1 GeV/c, and (2) allows determination of muon momentum in the 1 GeV/c to 1.5 GeV/c range to about 5% via range measurements in the iron. The detector will consist of about 2 meters of iron plates, three planes of x-y scintillators, and 19 MRG panels.

Figure 22: E791 Experimental detector

Figure 23: Proposed E871 detector

Figure 24: E871 beam "plug"

III. Status of Experiments

LAMPF E1072: pp Elastic Absolute Cross Section Measurements

Spokesperson: M. W. McNaughton

Participating Institutions: LANL, University of Texas, Texas A&M University, Rutgers University, UCLA

Status: Running period June-September, 1988. Data analysis has been completed.

Comments: The aim of this experiment, which was carried out during the summer of 1988, is to measure the differential cross section for pp elastic scattering to an absolute accuracy of 1%. The data were taken at 500-, 580-, 650-, 733-, and 800-MeV beam energies and over the angular range 15° to 90° c.m. The data were analyzed by a joint effort from the University of Texas (Kok Heong McNaughton) and Texas A&M University. The Ph. D. dissertation research of Tony Simon, of Texas A&M University, is based on E1072.

TRIUMF E372: Single Pion Production in np Scattering

Spokesperson: N. E. Davison

Participating Institutions: University of Manitoba, University of Alberta, California State University, TRIUMF, Rice University, University of Houston, University of Texas.

Status: Final data acquisition runs took place in September, 1990 and again February, 1991. Data are currently being analyzed at the University of Texas. The Ph. D. dissertation of Mark Bachman, of the University of Texas, will be based on this experiment.

LAMPF E876: Spin Transfer Measurements for np Elastic Scattering

Spokesperson: M. W. McNaughton

Participating Institutions: LANL, University of Texas, Texas A&M University, Rice University, Rutgers University, ANL, University of Montana, Washington State University

Status: Approved with A priority in the summer of 1990. Requires the high intensity optically pumped p⁻ ion source. Phase 1, which consists of measurements of the spin transfer parameters K_{LL}, K_{SL}, K_{LS}, and K_{SS}, has now been completed and the data analyzed. A paper describing the 788 MeV work will be published in the December, 1991 issue of Physical Review C. The 500 MeV and 650 MeV results are being written as a second paper. Phase 2, measurements of K_{NN} at 500, 650, and 800 MeV, will be carried out during the summer of 1992.

LAMPF E1234: K_{LL} and P for np Elastic Scattering

Spokesperson: M. W. McNaughton

Participating Institutions: LANL, University of Texas, Texas A&M University, Rice University, ANL, University of Montana, Washington State University, University of Central Arkansas

Status: The measurements were completed during the summer of 1991. The data have been analyzed, a manuscript has been written and will be submitted for publication by the end of 1991.

BNL E791: Study of Very Rare K_L⁰ Decays

Spokespeople: W. R. Molzon and R. D. Cousins

Participating Institutions: University of California, Irvine; University of California, Los Angeles; Los Alamos National Laboratory; Stanford University; Temple University; University of Texas; College of William and Mary

Status: The 1990 run time, the last one planned for E791, was an 18 week period from January-May. (Previous runs were made in 1988 and 1989 respectively, before our involvement in the experiment.)

Comments: The main goal of E791 is to search with high sensitivity for the separate lepton number non-conserving decay $K_L^0 \rightarrow \mu e$. The first stage of the offline analysis of the 1990 data is now complete. When all three data sets (runs from 1988, 1989, and 1990) are combined, it is expected that the single event sensitivity for $K_L^0 \rightarrow \mu e$ will be about 1.5×10^{-11} , which is expected to be the world's best limit for this decay.

BNL E871: A New Search for Very Rare K_L^0 Decays

Spokespeople: W. R. Molzon, J. L. Ritchie, and S. G. Wojcicki

Participating Institutions: University of California, Irvine; Stanford University; Temple University; University of Texas; College of William and Mary

Status: Approved. The tentative schedule calls for completion of the beam-line upgrades by the Spring of 1992, an engineering run with the detector in place by Spring, 1993, and Physics runs in 1994 and 1995.

Comments: The main goal of E871 is to search with even higher sensitivity than did E791 for the separate lepton number non-conserving decay $K_L^0 \rightarrow \mu e$. Through increased acceptance, higher rate-handling capability, and improvements in several detector system, the experiment should reach a single event sensitivity below 2×10^{-12} . At this sensitivity, a few decays of the type $K_L^0 \rightarrow ee$ should be observed if the decay occurs at the Standard Model level.

LAMPF E1097: Single Pion Production in np Scattering.

Spokespeople: D. L. Adams, N. E. Davison, K. Johnston, P. J. Riley. Project Manager, David Adams.

Participating Institutions: ANL, California State University, University of Houston, LANL, University of Manitoba, University of Alberta, Rice University, University of Texas, Texas A & M University.

Status: Approved with A⁻ priority by the LAMPF PAC, and by LAMPF management. Preliminary testing of the cylindrical drift chamber for the experiment was carried out during the summer of 1991, in a parasitic mode, at LAMPF. Final testing is scheduled for 1992. Phase I (unpolarized LH₂) target, is scheduled for 1993; Phase II (Polarized, frozen spin hydrogen target) is scheduled for 1994.

Comments: This experiment will measure the differential cross section, and the spin observables A_{NO} , A_{LO} , A_{SO} , A_{SL} , A_{NL} , and A_{LL} for the single pion production reaction $np \rightarrow pp\pi^-$ at neutron beam energies in the range 500-800 MeV. With the polarized target used in Phase II of E1097, a three charged-particle trigger will be required in order to enable us to discriminate against the quasifree $np \rightarrow pp\pi^-$ background events. A large acceptance cylindrical drift chamber has therefore been designed and built for E1097. Preliminary tests of the drift chamber, and of its associated electronics, were carried out at in area BR of LAMPF in parasitic mode during the summer of 1991. Final testing of our detector system is planned for 1992.

IV. Personnel Working on the Project

Peter J. Riley, Professor of Physics
Kok Heong McNaughton, Computer Programmer (3/4 time)
Kathleen Johnston, Postdoctorate, January-May, 1991

Graduate Students:

Mark Bachman (1/2 time)
David Ambrose (1/4 time, except for June, July, and August, when he was half time)
John Johnson (1/2 time, January through August, 1991. Terminated August 31)

Undergraduate Students:

Bernard Jobst (June, July, 1991)
Patrick Coffey (1/4 time, except for June, July, and August, when he was half time)

Peter Riley has participated in E372, E876, E1234, and E791 data runs, and has been much involved in E1097. Much of his time is being spent on E1097 work. Kok Heong McNaughton lives and works in Los Alamos, and is responsible for the software for all of our experiments there. In addition, she assists in data acquisition runs, and in data analysis at LAMPF. Kathleen Johnston, who joined our group for several months after completing her Ph. D. at the University of Houston in late 1990, has spent nearly all of the past year working on E1097. She worked on the fabrication of the E1097 cylindrical drift chamber both at the University of Houston and at Rice. In May she moved the chamber to Los Alamos and instrumented it for the summer tests. She spent the summer at LAMPF, working primarily on E1097. For the period June-August she was supported at LAMPF by Rice University. In September she accepted a LAMPF Post-doctoral position, and also accepted the responsibility of being an E1097 spokesperson. Mark Bachman, whose Ph. D. dissertation research is based on TRIUMF E372, has been either at TRIUMF working on E372 data runs, or at the University of Texas, where he is now working to analyze the E372 data. The Ph. D. thesis of David Ambrose will be based on E1097 research. David has been responsible for the development of E1097 tracking and event reconstruction software. He spent the past summer at LAMPF, helping both in E876 data acquisition and in E1097 tests. He has been awarded an Associated Western Universities (AWU) Fellowship, starting June 1, 1991, for the support of his LAMPF research on E1097. John Johnson, who is residing in Los Alamos, worked on E876 data at LAMPF, but left our group in August to continue Ph. D. research with Dr. C. Fred Moore's group. Bernard Jobst worked with us at Texas during the Spring of 1991; during the months of June and July he assisted us at LAMPF in E1097 tests. Pat Coffey has worked with GEANT development and preliminary benchmark tests of the IBM RISC machine (he has previous experience with UNIX). He spent the past summer at LAMPF assisting in E876 and especially in the E1097 test runs.

V. PUBLICATIONS and ABSTRACTS

PUBLICATIONS

"3-Spin Measurements in $p+d \rightarrow p+d$ at 794 MeV," G. Igo, E. Gulmez, D. L. Adams, S. Beedoe, M. Bleszynski, J. Bystricky, V. Ghazikhanian, T. Jaroszewicz, A. G. Ling, M. Nasser, M. W. McNaughton, S. Penttila, G. Glass, G. Kahrmanis, W. F. Kielhorn, K. H. McNaughton, P. J. Riley, S. Sen, and D. Wolf, in *Proceedings of the 4th Conference on the Intersections between Particle and Nuclear Physics*, Tucson, Arizona, May, 1991, Published by the American Institute of Physics.

"Analyzing Power Measurements in $pn \rightarrow \pi^{-}pp(^1S_0)$," Mark Bachman, Peter Riley, and Charles Hollas, *Physical Review C* **42**, 1751, (1990).

"Accurate Intensity Measurements for Proton Beams with a 201 MHz Structure," E. Gulmez, A. G. Ling, C. A. Whitten, Jr., J. F. Amann, M. W. McNaughton, T. Noro, D. L. Adams, V. R. Cupps, R. D. Ransome, G. Glass, A. J. Simon, K. H. McNaughton, and P. J. Riley, to be published in *Nuclear Instruments and Methods A* **297**, 7, (1990).

"Absolute Differential Cross Section Measurements for Proton-Deuteron Elastic Scattering at 641.3 and 792.7 MeV," E. Gulmez, S. Beedoe, A. G. Ling, C. A. Whitten, Jr., M. W. McNaughton, J. R. Santana, D. L. Adams, V. R. Cupps, A. J. Simon, M. L. Barlett, K. H. McNaughton, and P. J. Riley, *Physical Review C* **43**, 2067, (1991).

"NP Elastic Spin Transfer Measurements at 788 MeV," M. W. McNaughton, K. Koch, I. Supek, N. Tanaka, K. H. McNaughton, P. J. Riley, D. A. Ambrose, J. D. Johnson, A. Smith, G. Glass, J. C. Hiebert, L. C. Northcliffe, A. J. Simon, D. L. Adams, R. D. Ransome, D. B. Clayton, H. M. Spinka, R. H. Jeppeson, and G.E. Tripard, *Physical Review C*, December, 1991.

"Elastic scattering of N, L. and S-type polarized 794 MeV protons from an ND₃ target polarized in the S-L plane," E. Gulmez, D. L. Adams, S. Beedoe, M. Bleszynski, J. Bystricky, V. Ghazikhanian, G. Igo, T. Jaroszewicz, A. G. Ling, M. Nasser, M. W. McNaughton, S. Penttila, G. Glass, G. Kahrmanis, W. F. Kielhorn, K. H. McNaughton, P. J. Riley, S. Sen, and D. Wolf, accepted for publication in *Physical Review C*.

SUBMITTED FOR PUBLICATION

"Differential cross section for n-p elastic scattering in the angular region $50^\circ < \theta^* < 180^\circ$ at 459 MeV," L. C. Northcliffe, Mahavir Jain, M. L. Evans, G. Glass, J. C. Hiebert, R. A. Kenefick, B. E. Bonner, J. E. Simmons, C. W. Bjork and P. J. Riley, submitted for publication in *Physical Review C*.

"np Normalization via d(p,n) from 305 to 788 MeV," M. W. McNaughton, I. Supek, K. H. McNaughton, P. J. Riley, D. A. Ambrose, K. Johnston, P. Coffey, G. Glass, J. C. Hiebert, L. C. Northcliffe, A. J. Simon, D. Mercer, D. L. Adams, H. M. Spinka, R. H. Jeppeson, G.E. Tripard, and H. Woolverton, submitted for publication in *Physical Review C*.

ABSTRACTS

*Abstracts and papers removed and
cycled separately -*

DATE
FILMED
2 12 1 192

I